

1333

FOR OFFICIAL USE ONLY

718408

AD 03535

NDL-TR-79

WASTE DISPOSAL ASPECTS
OF A
NUCLEAR-WEAPON ACCIDENT

Richard F. Smale
Joseph C. Maloney

REPOSITORY Oak Ridge Operations
COLLECTION Records Holding Area
Doc. 1944-794
BOX No. A-46-5 Sec. Div. Bldg.
Disaster Plan - 2714-H
FOLDER Radiation Contamination
1967

NOVEMBER 1966

Each transmittal of this document outside the agencies of the United States Government must have prior approval of USA Nuclear Defense Laboratory.

US ARMY
NUCLEAR DEFENSE LABORATORY
EDGEWOOD ARSENAL, MARYLAND

FOR OFFICIAL USE ONLY

1127023

FOR OFFICIAL USE ONLY

Disposition

Destroy this report when no longer needed. Do not return it to the originator.

Disclaimer

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

FOR OFFICIAL USE ONLY

1127824

FOR OFFICIAL USE ONLY

NDL-TR-79

**WASTE DISPOSAL ASPECTS OF
A NUCLEAR-WEAPON ACCIDENT**

Richard F. Smale
Joseph C. Maloney

November 1966

Project 1N022601A089, Subtask 04-01

Each transmittal of this document outside the agencies
of the US Government must have prior approval of
US Army Nuclear Defense Laboratory

US ARMY
NUCLEAR DEFENSE LABORATORY
Edgewood Arsenal, Maryland

FOR OFFICIAL USE ONLY

1127625

FOR OFFICIAL USE ONLY

ABSTRACT

Procedures for decontamination, collection, packaging, transportation and ultimate disposal of the large quantities of radioactive waste generated as a result of a nuclear-weapon accident are presented. Plutonium hazard and dispersion, previous research on nuclear-weapon accident hazards, as well as acceptable levels of contamination are reviewed and discussed. From Test Group 57 and Roller Coaster data, the extent of the significantly contaminated area was estimated to be between 0.1 and 0.5 mi².

Types of waste generated and methods of collecting, packaging, and transporting are presented for rural, industrial, suburban, and airfield areas. Only first approximations of economic costs are made for reclamation of each type of area. Social and legal costs are not estimated. The equipment for cleanup available to the Army through organic units and through Government agencies is reviewed.

It is concluded that, while the Army theoretically has sufficient resources to conduct a cleanup of an accident site, further study is needed to determine preplanned procedures, optimum utilization of available equipment, and expedient packaging procedures.

FOREWORD

This work was authorized under Army Service Project LN022601A089, Subtask 04-01 "Radioactive Waste Disposal Techniques," and was conducted during calendar year 1965.

FOR OFFICIAL USE ONLY

CONTENTS

	Page
1. INTRODUCTION	7
1.1 Objectives.	7
1.2 Justification and Requirements.	7
1.3 Background.	7
1.3.1 Accident Hazard and Research	7
1.3.2 Plutonium Dispersion	8
1.3.3 Acceptable Levels of Contamination	11
1.3.4 Probable Areas Involved.	12
1.3.5 Radiological Reclamation	15
2. DECONTAMINATION AND DISPOSAL	21
2.1 General	21
2.2 Rural Areas	22
2.2.1 Characteristics.	22
2.2.2 Decontamination.	22
2.2.3 Collection and Packaging	22
2.2.4 Transportation.	24
2.2.5 Ultimate Disposal.	25
2.3 Industrial Areas.	25
2.3.1 Characteristics.	25
2.3.2 Decontamination.	26
2.3.3 Collection and Packaging	27
2.3.4 Transportation	27
2.3.5 Ultimate Disposal.	28
2.4 Suburban Areas and Airfields.	28
2.5 Radiological Safety Precautions	28
3. ECONOMICS.	29
3.1 General	29
3.2 Free Land-Open.	30
3.3 Free Land - Wooded.	34
3.4 Paved Areas	34
4. AVAILABLE RESOURCES.	35
4.1 Earthmoving	35
4.2 Disposal.	36
5. CONCLUSIONS.	36
6. RECOMMENDATIONS.	37
6.1 General	37
6.2 Packaging	37
6.3 Disposal.	37
LITERATURE CITED	39

FOR OFFICIAL USE ONLY

WASTE DISPOSAL ASPECTS OF A NUCLEAR-WEAPON ACCIDENT

1. INTRODUCTION

1.1 Objectives.

The objectives of this study are to estimate the quantity of bulk radioactive waste generated as a result of a nuclear-weapon accident, to survey the current Army capability to package and dispose of such waste, and to give general guidance and recommendations of procedures for collecting, packaging, transporting, and disposing of such waste. It is not the objective of this study to present a minutely detailed and absolutely precise economic and logistical study. Where economic costs and logistical factors are given, they are only a first approximation and are given purely as examples.

1.2 Justification and Requirements.

Present Army policy is unclear as to procedures that should be used for handling, packaging and disposing of the large quantity of waste generated as a result of a nuclear-weapon accident. Public and legal aspects of an accident of this nature may require disposal of quantities of waste greater than is medically necessary. Effective and economical decontamination and disposition can be facilitated by proper preplanning and guidance.

1.3 Background.

1.3.1 Accident Hazard and Research. The storage and movement of nuclear weapons have always been a special concern to safety experts. Even though the number of accidents involving nuclear weapons has been extraordinarily low, the continuing movement of such items through the normal logistical chain concedes the possibility, however remote, that a nuclear weapon either in storage or in transport, will be involved in a serious accident. In order to properly understand the scope of this study, it is necessary to summarize the hazards associated with nuclear-weapon accidents. More complete and detailed information may be obtained from the many excellent publications in this field (References 1 through 4).

The two most hazardous materials in a nuclear weapon are the high-explosive component and the nuclear material. As a result of a serious accident the high-explosive component may detonate high order (i.e. completely), detonate low order, burn, or be widely scattered. In any of these cases, and for the purposes of this study, it is assumed that prompt and effective action by Explosive Ordnance Disposal and other safety teams will quickly neutralize the high-explosive hazard. By the time land reclamation and waste disposal procedures are initiated, only the nuclear material will be considered a long-term hazard.

FOR OFFICIAL USE ONLY

Plutonium and uranium contaminations are the long-term radiological hazards of a nuclear-weapon accident. While uranium and plutonium contaminations are radiologically similar, uranium possesses a much lower specific activity. Consequently, measures and procedures sufficient to contain and dispose of plutonium will be more than adequate to deal with any uranium present.

Plutonium, a heavy metal similar in appearance to stainless steel, oxidizes easily and rapidly to take on a characteristic brownish-black appearance. Small filings are pyrophoric. If associated with a fire or an explosive, plutonium can easily be oxidized and pulverized into very minute particles that can cause serious contamination over a large area.

Plutonium is an alpha emitter. However, because of spontaneous fission and the fact the decay series includes isotopes that are beta and gamma emitters, beta-gamma radiation will always be present whenever plutonium is found in any quantity. When the plutonium is dispersed over a wide area, the beta-gamma radiation will be almost imperceptible (Reference 3).

As an alpha emitter, plutonium represents a radiological problem only when it gains entrance into the body. Radiological protection from plutonium consists simply in ensuring that it does not enter into the body. Body entry is through inhalation, ingestion, or breaks in the skin, with inhalation being the primary means. Since plutonium is highly insoluble in the gastro-intestinal tract (only 0.003 percent of that ingested will be absorbed in the bloodstream), and since deep wounds should not be a factor for the purposes of this study of long-term reclamation, hazards from ingestion and wound contamination are not considered. The primary hazard of plutonium is from inhalation of particles in the 1- to 10- μ range. Approximately 10 percent of the inhaled particles in this "optimum size" range are absorbed into the blood stream and will eventually be deposited in the bones. Plutonium deposited in the bones effectively remains for a lifetime and may cause long-term radiological damage.

With the increase in the number of plutonium-bearing weapons, present safety plans and hazards research are constantly being re-evaluated to minimize the possibilities of an accident and to better define the radiological hazards that would result if an accident were to occur. As early as 1955, Cowan and Kingsley (Reference 5) studied the hazard associated with an accident to a weapon containing plutonium and developed an idealized fallout pattern by use of parameters of specific meteorological conditions, particle size distribution, and cloud rise height.

The Los Alamos Scientific Laboratory performed the first field safety tests of pre-assembled plutonium-containing devices in the 56 Project at the Nevada Test Site (Reference 6). Although these were primarily safety tests, close-in alpha contamination studies were conducted and some contamination levels were documented; no fallout contours were delineated. Harris (Reference 7) made a comprehensive analysis, based partly on this data, of the acute and chronic radiological hazards and developed resuspension factors

FOR OFFICIAL USE ONLY

and acceptable permissible surface levels. The area of risk, the hazards within this area, and brief notes on decontamination techniques were also presented. Translation and extrapolation of the admittedly sparse data from Project 56 into shipping and storage safety criteria would have led to overly restrictive regulations, thus severely limiting the nation's response posture.

A more definitive evaluation of the plutonium contamination problem was required and was met by Test Group 57 of Operation Plumbbob in 1957 (Reference 8). This experiment involved a one-point detonation of a warhead for the sole purpose of evaluating all aspects of the plutonium hazard. This evaluation included (1) estimation of the extent of contamination, (2) biomedical evaluation, (3) decontamination effort, and (4) determination of resuspension factors. The decontamination effort (Reference 9) was large-scale and all practicable methods of decontamination were attempted and documented as to efficiency. This was the first documented large-area plutonium decontamination effort, and the results have since been used as standards for decontamination efficiencies in field and technical manuals (References 2, 3, 4, and 10).

The Test Group 57 Project remained the only large-scale field test of plutonium dispersal in a nuclear-weapon accident situation until the Roller Coaster Series in 1963. This later operation, conducted with joint US/UK participation, was a logical outgrowth of the 56 and 57 Projects and was designed (1) to investigate the biological hazard of plutonium scattered by non-nuclear explosions, (2) to evaluate the effectiveness of earth-covered storage structures in reducing the radiological hazard, and (3) to improve the forecast of the magnitude of the radiological exposure likely from a given accident situation. The series consisted of four separate events, each extensively documented for plutonium deposition, air concentration, and ground contamination (Reference 11). The bulk of data from the series has not been completely analyzed, but the plutonium deposition contours have been well documented for the various types of storage configurations.

Only two studies have extensively analyzed the expected costs and economics of a nuclear-weapon accident. For brevity, they will be denoted as the TORT Report (Reference 12) and the NAVWEPS Report (Reference 13). The TORT Report analyzed probabilities of incidents and accidents and developed expected overall recovery costs under various population density conditions. An acceptable level of ground contamination was arbitrarily assumed to be $100 \mu\text{g}/\text{m}^2$ of plutonium. A one-pass, one-week decontamination effort was analyzed. Recovery costs were based on such factors as (1) cost of weapon, (2) cost of equipment, (3) cost of decontamination and replacement of personal property, (4) cost of interruption of services, and (5) overhead costs. Costs were then calculated for a railroad accident and an accident involving an airplane at an airfield. Decontamination costs for a single weapon railroad accident ranged

FOR OFFICIAL USE ONLY

from \$20,000 per square mile for a sparsely populated rural area to \$4.5 million per square mile for an area of population density greater than 2,500 persons per square mile. Analysis of decontaminating a typical airfield was \$0.3 million per square mile. For these incidents, and for the one-pass decontamination effort, cost of land decontamination was based on cost of plowing under the topsoil.

The NAVWEPS Report estimated cleanup cost of a rural area at the value of the land plus the expense of plowing under the topsoil. The suburban, urban, and industrial decontamination cost is estimated from 10 to 50 percent of the total value of property improvements and personal property. With this criteria, costs range from \$0.1 million per square mile for rural areas to \$30 million per square mile for urban and industrial areas.

Study and comparison of these reports clearly indicate that estimates of costs for decontamination presupposes a minimum of radioactive waste. It was assumed that all open land would simply be plowed and that liquid runoff from washdowns would be allowed to leach into the ground or run into existing sewerage systems. No thought was given to the fact that, due to public apprehension and legal complications, a large amount of the land area may have to be physically removed, transported to another location, and disposed of as radioactive waste. The cost of a large scale removal operation of this type could be several orders of magnitude higher than that previously reported.

1.3.2 Plutonium Dispersion. In a nuclear-weapon accident, the plutonium may be spread either by detonation of the high explosive or by burning. If the high explosive in the weapon detonates high order (in one complete explosion) the plutonium will be pulverized, converted into an oxide fume of relatively fine particle size, become attached to larger particles, and taken up into a cloud to produce localized downwind fallout. If the high explosive in the weapon detonates low order (incomplete, or in a series of incomplete explosions), some of the plutonium will be pulverized and distributed as in a high order detonation and some will be scattered as debris. If the weapon is broken open and ignites, the plutonium will burn and the fine particulate oxide will be carried downwind in the smoke and dust. Plutonium that is not burned or vaporized will be locally scattered in sizable pieces.

The mechanics of plutonium dispersal during fires has been extensively reviewed by Mishima (Reference 14). He has shown that the particle-size distribution will vary widely with prior treatment, fire conditions, and physical shape. In general, it is assumed for conservative purposes that the oxide will be finely divided in the particulate-size range that will cause the greatest inhalation hazard.

FOR OFFICIAL USE ONLY

1127031

FOR OFFICIAL USE ONLY

In either case, the contaminated material is transported into a cloud, carried downwind, and deposited. The exact cloud distribution is dependent on particle size, cloud height, and specific meteorological parameters. The idealized cigar-shaped fallout pattern will not be followed in all cases because of the high percentage of particles that are too small to obey Stokes' Law, and their deposition is governed by local air turbulences, eddy currents, and terrain factors (Reference 7). These parameters will be unique to each situation so that it is impossible to construct a mathematical fallout pattern applicable to all accidents.

1.3.3 Acceptable Levels of Contamination. Once the cloud has passed and the plutonium is deposited on the ground, no external radiological hazard exists; if the plutonium-bearing particles are resuspended and subsequently inhaled, the chronic hazard would appear. An estimate of the chronic inhalation hazard can be made by defining a resuspension factor as

$$RF = \frac{AC}{GC}, \quad (1.1)$$

where RF = Resuspension Factor in units of m^{-1} ,
AC = Airborne Concentration,
and GC = Ground Concentration.

The airborne concentration is measured in units of micrograms per cubic meter ($\mu g/m^3$) or microcuries per cubic meter ($\mu c/m^3$). The ground concentration is measured in units of micrograms per square meter ($\mu g/m^2$) or microcuries per square meter ($\mu c/m^2$). The resuspension factor is then calculated in units of inverse meters (m^{-1}) and provides a linear relationship between the ground deposition and the chronic airborne hazard.

Mishima (Reference 14) tabulated values of variously reported resuspension factors ranging from $10^{-2} m^{-1}$ (resuspension of a finely divided material from a newly painted concrete floor due to air and mechanical motion) to $10^{-13} m^{-1}$ (resuspension of aged plutonium particulate matter from desert soil by natural turbulence). Realistic values range from $7 \times 10^{-5} m^{-1}$ (Nevada vehicular traffic) to $7 \times 10^{-7} m^{-1}$ (isolated area). Because the airborne hazard is directly proportional to the resuspension factor, any change or uncertainty in the resuspension has a direct bearing on the acceptable level of ground contamination.

In a typical field situation, the estimate of the resuspension factor will be uncertain by at least a factor of 10. This uncertainty is due to varying atmospheric conditions, different types of soil, different mechanics of deposition, and different kinds of movement within the area.

FOR OFFICIAL USE ONLY

For the purpose of this report, the minimum acceptable level of contamination for a weapon accident will be taken as $100 \mu\text{g}/\text{m}^3$ ($6.4 \mu\text{c}/\text{m}^3$). This value is in agreement with some authors (References 7 and 12) and in disagreement with others (Reference 13); it is convenient because most field tests have generally delineated the 1, 10, and $100 \mu\text{g}/\text{m}^3$ contours and, in the absence of detailed knowledge of resuspension factors, the use of $100 \mu\text{g}/\text{m}^3$ as an acceptable limit will probably be within the limits of error or uncertainty. As an added precaution, the area enclosed by the $10 \mu\text{g}/\text{m}^3$ contour should also be investigated to determine the feasibility of protective measures, such as fixation.

1.3.4 Probable Areas Involved. It has generally been accepted that for a given energy release and constant meteorological and terrain conditions, the area enclosed by any isocontamination line will be directly proportional to the amount of plutonium in the weapon and inversely proportional to the contamination intensity. This relationship may ideally be stated by

$$A = K \frac{P}{I}, \quad (1.2)$$

where

A is the affected area in square miles,

I is the contamination boundary in $\mu\text{g}/\text{m}^3$,

P is the mass of the plutonium in kilograms,

and K is a constant of proportionality.

Assume that both K and P (and therefore PK) are constant for any single accident situation; the relationships between areas bounded by isocontamination contours are ideally given by

$$A_1 I_1 = A_2 I_2, \quad (1.3)$$

where A_1, A_2 is the area bounded by any two isocontamination lines, I_1 and I_2 .

Notice that as long as consistency is maintained, this relationship is independent of the units involved. Because of localized conditions and variations in tests, correlation of formulas to determine K has been difficult. Use of a standard constant for any accident situation is impossible; Roller Coaster data have shown that various types of covering will drastically alter the scavenging characteristics of the local environment and directly affect the extent of the fallout area.

FOR OFFICIAL USE ONLY

On April 24, 1957, Operation Plumbbob Test Group 57 conducted a one-point detonation of a plutonium-bearing device for the purposes of studying the plutonium hazards from accidents involving weapons of this type. From D-day to D+2 days, approximately 1400 broom-finished concrete blocks measuring 10- by 10- by 1-inches, arrayed around the shot location, were surveyed by field alpha meters. The meter readings were converted to plutonium concentrations by a 1/3 roughness factor for self-absorption (Reference 15).

The alpha-survey results are shown in Figure 1.1. Areas within the isocontamination contours, the product of the area, and the maximum contamination are shown in Table 1.1.

TABLE 1.1 AREAS INCLOSED BY VARIOUS ISOCONTAMINATION CONTOURS, TEST GROUP 57, PROGRAM 74

Contour, I	Area, A	AI
$\mu\text{g}/\text{m}^2$	mi^2	
3500	0.003	10.5
1000	0.03	30
100	0.43	43
10	2.5	25

As can be seen from Figure 1.1, the areas are roughly elliptical in shape and were dependent on local wind conditions. Examination of Table 1.1 shows an AI product variation of a factor of 4.

In May 1963, the Roller Coaster series of one-point detonations was conducted at the Tonapah Test Range (1) to study the biological hazard of plutonium scattered by nonnuclear explosives, (2) to evaluate the effectiveness of earth-covered storage structures in reducing the radiological hazard produced by a detonation within the structure, and (3) to improve mathematical cloud models. Four shots, named Double Tracks and Clean Slate Nos. 1, 2, and 3, were fired according to the following conditions (Reference 11).

FOR OFFICIAL USE ONLY




Figure 1.1 Contours of TG-57 deposition, by alpha survey.

FOR OFFICIAL USE ONLY

Double Tracks. One device, normally containing plutonium and Orallo, was contained in an aluminum case and made suitable for one-point detonation. All Orallo was removed and replaced with Depletalloy of similar mass and configuration. The device was detonated 1 foot above a steel-faced concrete surface.

Clean Slate 1. Nine devices, one containing plutonium, and the others simply HE spheres containing Depletalloy, were detonated in sequence in an open storage configuration on a concrete pad.

Clean Slate 2. One plutonium-containing device was one-point detonated in a standard type igloo covered by 2 feet of earth. Eighteen other devices, with the plutonium replaced by Depletalloy, were stored in the same igloo and detonated in sequence.

Clean Slate 3. This shot was similar in all respects to Clean Slate 2 with the exception that the igloo was covered by 8 feet of earth.

After each shot, an alpha survey was conducted with survey meters and deposition contours were plotted. Representative displays are shown in Figures 1.2, 1.3, 1.4, and 1.5. The areas of selected isocontamination contours and the AI products are given in Table 1.2.

Comparisons of Figures 1.1 through 1.5 and Tables 1.1 and 1.2 show a great deal of variation, not only between the Test Group 57 and Roller Coaster data but also among the various Roller Coaster shots. The Test Group 57 data give areas different from the Roller Coaster data by factors of 3 to 10 greater at $10 \mu\text{g}/\text{m}^2$ and factors of 4 to 400 greater at $100 \mu\text{g}/\text{m}^2$. These differences can be attributed to local parameters, such as configuration of device, type of overburden or protective covering, scavenging by associated materials, and local weather conditions. It is obvious that theoretical cloud models, while useful, will not be capable of predicting the contaminated areas. The best that can be said is that the field studies show that the maximum hazard area requiring reclamation ($100 \mu\text{g}/\text{m}^2$) is 0.5 mi^2 ; it is also necessary to investigate areas up to 2.5 mi^2 ($10 \mu\text{g}/\text{m}^2$). The hazard area, however, could be only 0.001 to 0.1 mi^2 .

1.3.5 Radiological Reclamation. Large-scale decontamination and reclamation procedures have been extensively analyzed and evaluated in the area of radiological recovery, that is, recovery from a large-scale radiological warfare attack or a nuclear-fallout situation. The military and Civil Defense studies of this problem are generally directed at minimizing the beta-gamma hazards but the techniques and procedures are equally applicable to plutonium decontamination.

FOR OFFICIAL USE ONLY




Figure 1.2 Contours of DOUBLE TRACKS deposition in $\mu\text{g}/\text{m}^2$, by alpha survey.

FOR OFFICIAL USE ONLY

1127837

FOR OFFICIAL USE ONLY




Figure 1.3 Contours of CLEAN SLATE No. 1 deposition in $\mu\text{g}/\text{m}^2$, by alpha survey.

FOR OFFICIAL USE ONLY

1127638

FOR OFFICIAL USE ONLY




Figure 1.4 Contours of CLEAN SLATE No. 2 deposition in $\mu\text{g}/\text{m}^2$ alpha survey.

FOR OFFICIAL USE ONLY

1127839

FOR OFFICIAL USE ONLY




Figure 1.5 Contours of CLEAN SLATE No. 3 deposition in $\mu\text{g}/\text{m}^2$ by alpha survey.

FOR OFFICIAL USE ONLY

1127840

FOR OFFICIAL USE ONLY

TABLE 1.2 AREAS ENCLOSED BY VARIOUS ISOCONTAMINATION CONTOURS, ROLLER COASTER*

Shot	Contour, I	Area, A	AI
	$\mu\text{g}/\text{m}^2$	mi^2	
Double Tracks	1	15.1	15.1
	10	0.274	2.74
	100	0.001	0.1
Clean Slate 1	1	3.1	3.1
	10	0.284	2.84
	100	0.003	0.3
Clean Slate 2	1	3.6	3.6
	10	0.92	9.2
	100	0.10	10.0
Clean Slate 3	1	1.85	1.85
	10	0.77	7.7
	100	0.054	5.4

*Reference 11.

In 1954, a detailed survey on the recovery of a major industrial complex from a radiological warfare attack was conducted by the Chemical Corps Chemical and Radiological Laboratories (Reference 16), a predecessor organization of this Laboratory. In this report, an arbitrary density of radiation per square mile was assumed and the gross amount and type of radioactive waste generated during the reclamation procedure was analyzed. Specific amounts of waste for various types of land usage were calculated; liquid waste was to be carried off in the sewerage system while solid waste was to be hauled to a disposal site and buried by trench-fill procedures. A very detailed logistical analysis was made of each method of decontamination.

Reclamation of large land areas from radioactive fallout is well documented in TM 3-225, "Radiological Recovery of Fixed Military Installations" (Reference 17). This is the prime military guide and is complete in almost every detail. It includes stepwise mechanics of reclamation, rates of operation, effectiveness of the various methods of decontamination, and

FOR OFFICIAL USE ONLY

minor waste disposal aspects of the problem. Methods of reclamation that are documented include firehosing, motorized flushing, scrubbing, hot liquid cleaning, scraping soil with motorized scraper, motor grader or bulldozer, and filling. The manual also details the radiological safety procedures that must be followed, in particular the use of respirators and protective masks that must be worn to minimize the airborne hazard.

While both the CRL report and TM 3-225 are very detailed in the mechanics of reclamation of large areas, and the CRL Report outlines in minute detail waste disposal procedures, both are, to some extent, not applicable to the problem at hand. Reclamation after a nuclear or RW attack supposes an emergency wartime situation, domestic mobilization, and effective military or civil defense control of the area involved. These conditions will be absent where a peacetime weapon accident occurs on non-Government property. Although the military may have temporary control of the area, full mobilization of civilian resources will not be available. The emergency tolerances and relaxation of radiological safety precautions that might be attendant to extreme situations will not be present; reclamation work will have to proceed under the normal peacetime safety criteria and exposure limits. Such limits will appreciably reduce personnel and equipment work output and efficiency.

2. DECONTAMINATION AND DISPOSAL

2.1 General.

This section examines the various large-scale decontamination methods that may be used during reclamation of an accident site and estimates the magnitude of the waste generated during these operations. It should again be noted and emphasized that the volume of waste generated per unit area will be an order-of-magnitude estimate only; actual volumes will vary according to the type of terrain, type of equipment used, spillage, operator efficiencies, and numerous other variables.

For the purpose of this study, it is assumed that a maximum decontamination effort will be made; that is, all areas within the 100 $\mu\text{g}/\text{m}^2$ contour will be decontaminated to as low a level as possible. The area between the 100 $\mu\text{g}/\text{m}^2$ and 10 $\mu\text{g}/\text{m}^2$ contours may be fixed or decontaminated as the situation permits. Free land or open areas will be decontaminated by scraping off the first 3 inches of topsoil (98 to 100 percent efficient); hard-surface areas will be washed down with water or with water and detergent (96 to 100 percent efficient, Reference 3); trees and foliage will be collected and disposed of as solid waste. The volume of waste generated will be calculated per square mile of affected area; volumes for composite areas may be calculated by prorating the various areas involved.

FOR OFFICIAL USE ONLY

2.2 Rural Areas.

2.2.1 Characteristics. Rural areas include farmland, open areas, woods, and highways or railroad rights-of-way bordering these areas. Such areas constitute a major portion of nuclear-weapon shipment routes and can be considered as a prime area for an accident in shipment. Soil and climate may vary from hot dry desert soil to moist swamps. Over 98 percent of rural area is open or free land in the sense that it is not paved or improved. All of the radioactive waste generated will be solid, the majority being soil, the rest being trees, foliage, and small items of personal property. Open land represents the easiest area to reclaim because it is easy to survey and control. It is ideally suited for operation of earthmoving equipment thus minimizing the number of personnel and risk of contamination. Since there will be relatively few habitable dwellings, the need for an emergency or short recovery time will be less and a more detailed and comprehensive reclamation effort can be planned.

2.2.2 Decontamination. Open areas may be reclaimed in a variety of ways: (1) fencing off the area and allowing the plutonium to become fixed by weathering, (2) fixing the plutonium with an oil spray, (3) plowing the topsoil, (4) actually scraping the topsoil, or (5) combinations of these methods. Only scraping the topsoil can be precisely called decontamination in the sense that it physically removes the radioactive material; the others merely reduce the resuspension factor to a point where there is no airborne hazard. Only two methods of decontamination, stripping the soil and plowing under, will be studied in detail. Plowing the soil under is a minimum type effort requiring the least amount of time, manpower, and cost. The logistical problems in scraping, collecting, and moving the topsoil are sufficient to rank this as a maximum effort.

As an order-of-magnitude calculation, scraping off 3 inches of topsoil will yield 258,000 yd³ of soil per square mile of land worked. Addition of an estimated factor of 100 percent to compensate for soil loosening, uneven depths of cuts, spillage, foliage, underbrush, and debris will give an approximate total, exclusive of large trees or structures, of over 500,000 yd³ per square mile of open land. Using an approximate rule of thumb of a soil density of dry loam (2000 lb/yd³) gives an approximate weight of 500,000 tons of solid waste per square mile of open land area. An effort of this magnitude can be accomplished only by use of large earthmoving equipment such as tractors, dozers, scrapers, and graders. Such items are engineer equipment, and many manuals (References 18 through 22) are available to estimate the effectiveness and economic utilization of this equipment.

2.2.3 Collection and Packaging. Collection and packaging methods will vary in accordance with the total effort. If the decontamination effort is simply plowing under the open area, the total collection and packaging will be nearly zero. If the maximum effort of scraping the topsoil is attempted, it will be necessary to collect and package 500,000 yd³/mi² of contaminated soil, and the collection and packaging efforts will be maximized.

FOR OFFICIAL USE ONLY

At the accident site, the most efficient method of collection and packaging is by a motorized or towed scraper. After land clearing operations have been completed, the scraper removes the top 3 inches of soil by forcing the soil into the bucket body of the machine. When the body or pan is full, the scraper carries the soil to the railhead (or to the dump) and dumps the soil. With high-speed rubber tired scrapers, this method can be very rapid with the advantage of minimum handling and transfer. With an 18 cubic yard wheel-type scraper, rates can be as high as 100 yd³/h (References 18 and 19). The only disadvantage of this type of collection is that the unit must travel over the contaminated ground and must be monitored for contamination before leaving the accident area.

Another very efficient method is by grading the topsoil into windrows by either motorized graders or angledozers. The windrows are then cast into a hauler (dump truck, scraper, or dump wagon) by either a front-end loader or an elevating grader. Here again, the use of a grader puts part of the equipment on the contaminated soil but, since the grader does not have to leave the area, this problem is minimized. The hauling units can operate on the sections already scraped and thus minimize spreading the contamination. Major dust and resuspension problems are evident in either collection method and can be controlled by frequent and extensive water or oil spraying. The hauling equipment necessary to maintain efficient operations will again depend on the length of haul to the transfer point and the rate of speed of the hauling unit.

The packaging of the soil for shipment will be the most critical phase of the whole operation from an economic and radiological safety standpoint. Unless waivers or interpretations of ICC Regulations are favorable, the packaging restrictions will be so stringent that a large portion of the recovery cost will be needed to fabricate field expedients or construct shipping containers. If topsoil is hauled in open units such as dumps, wagons, and trucks, the load should be sprayed with a road oil spray or covered with canvas, metal, or plastic.

Standards for packaging of beta-gamma emitting material are well known but specific standards for low-activity, alpha-emitting waste are very vague. Packing and shielding regulations (49 CFR* 73.393) require an inside metal shipping container, ICC Spec 2R, for materials containing plutonium, and it is questionable as to whether railroad cars can meet the packaging exemptions listed in 49 CFR 73.392. If the entire rail car qualifies as a shipping container, the packaging can be done in a "Type LO" covered hopper car at an average of 70 yd³ per hopper. This would require a total of 7100 hopper car loads per square mile of land contamination. Although it would be theoretically feasible to utilize the large fleet of Army box cars to haul the soil, radiological contamination control problems probably would be greater than any cost reduction that might result.

*Code of Federal Regulations.

FOR OFFICIAL USE ONLY

Unless specific waivers are granted under 49 CFR 71.3 and 49 CFR 71.7, any type of shipment would have to conform to existing regulations or else be made under 49 CFR 73.7 (b), which states "Shipments of radioactive materials made by the Atomic Energy Commission or under its direction or supervision, which are escorted by personnel specially designated by the Atomic Energy Commission, are exempted from the regulations in parts 71 to 78."

Preclusion of bulk carload shipments would necessitate use of shipping containers. Fabrication of special shipping containers would be economically unfeasible; however, standard conex transporters* with a minimum of modification could be used adequately for bulk waste shipments. Properly loaded, sealed and braced, these containers can hold up to 10 yd³ and seven can be loaded into a 50-foot flat car, 70 yd³ per car, or 7100 carloads per square mile (50,000 total conex loads) of free land area processed. Loading of the soil into the conex can be accomplished at the accident site, the outside can be sealed and decontaminated prior to leaving the accident area, and the transportation to railhead and disposal site will be radiologically safer. Thus, the increased time and cost necessary to load the containers will be offset by a work-output increase resulting from reduced need for special clothing and protective equipment at all other points.

2.2.4 Transportation.

Motor

Unless the disposal site is within approximately 50 miles of the accident site, it is not feasible to transport the solid waste directly to the disposal site by overland transportation. An exception to this may occur when organic transportation units are used and direct costs are not levied against equipment usage and labor times. If transportation is by Government motor vehicle, an interpretation of ICC Regulations should be made to determine applicability of packaging requirements. If transportation is by open-top conveyances, the load should be fixed by oil spraying the top surface, or by attaching expedient covers of canvas, sheet metal, or plastic. The route should be carefully reviewed, patrolled, and continually surveyed for spillage. Because of the large number of units needed, the route should be used exclusively by the hauling units.

Rail

The fastest and most economical method of transportation is by rail. Using covered hoppers for bulk soil or flat cars for conex containers is an efficient method of transportation to the disposal site. Special routing of shipments at low traffic periods will have to be utilized for

*FSN 8115-271-7000 Box, Metal, Shipping, Reusable, Transporter, Steel Type 2, 295 cubic feet capacity, 8'-6" long, 6'-3" wide, 6'-10-1/2" high, cost \$2,000.

FOR OFFICIAL USE ONLY

FOR OFFICIAL USE ONLY

safety considerations. Bulk shipping rates from the railroad companies can be contracted on the strength of point-to-point routing and unit train makeup.

2.2.5 Ultimate Disposal. If the waste were to be physically removed from the accident site, it is apparent that the selection of the ultimate disposal site would be paramount. Disposal at commercial sites would be too expensive (\$20.00 per cubic yard plus \$0.06 to \$0.40 per ton-mile transportation). The most economical disposal site would be the accident site itself. The farther the disposal site is from the accident site, the more costly the transportation and radiological safety functions become. Precluding the accident site itself, the most desirable disposal area would be one under Government control, preferably a military installation. Such a disposal site should have the obvious advantages of good transportation facilities, large amounts of unused free land, and excellent control and security. Selection of such a site should be based upon the nearness of the installation to the accident, amount of free land, type of soil, and depth of the water table.

The only feasible method of disposing of waste soil is burial by the trench-fill method, which is commonly used in commercial refuse disposal. Side-by-side trenches 15 feet deep and 30 feet wide are excavated, by dragline or clamshell, as long as is necessary or convenient. The material to be disposed of is dumped into a trench and then covered by fresh soil from the adjacent trench excavation. A total trench length of 10,000 yards will be required to bury 500,000 yd³ of waste; this total can be broken down into many series of parallel trenches convenient to the shape of the disposal area. Transportation by hopper cars will necessitate construction of expedient unloading trestles or offloading into local hauling units for transportation to the trench. If the transportation is done by conex containers, rail spurs can be constructed parallel to each set of trenches and the containers lifted off by crane, dumped, and repositioned back onto the flat car for decontamination and subsequent rotation back to the accident site. In either case, proper preplanning can minimize outside contamination of the hauling units.

When all the waste has been deposited and covered with fresh soil, the area is revegetated for fixation purposes and fenced off as a controlled area.

2.3 Industrial Areas.

2.3.1 Characteristics. Industrial areas are typified by a low percentage of free land. The improved areas will be about equally divided between paved areas and built up industrial structures. Use of the very large construction equipment will not be practicable due to the variety of structures. Much of the work will have to be done with smaller equipment or by hand labor with a corresponding decrease in work output per unit area and a consequent increase in cost.

FOR OFFICIAL USE ONLY

Reclamation of an industrial area from a radiological warfare attack has been previously noted and extensively analyzed. Almost all procedures developed are applicable to a nuclear-weapon accident.

2.3.2 Decontamination. The paved areas should be decontaminated by vacuum cleaning the surface, by water hosing or motorized flushing. The structures are decontaminated by vacuum cleaning, hot-water lancing, or water hosing.

Vacuum sweeping presents the least problem. Reference 23 data indicate that available commercial sweepers can achieve high efficiencies and rates of operation with relatively little waste generation. The commercial sweeper can achieve realistic operating rates up to 67,000 ft²/h with high efficiency for containing dry particulates. With an operating factor of 60 percent, a total square mile of paved surface can be decontaminated in less than 700 equipment hours with surface dirt contained in the hopper being the only waste generated. The waste can then be bagged and sealed in relatively small shipping containers. This unit appears to be the fastest, safest, and most economical method of decontaminating paved areas.

For water hosing, large quantities of liquid waste will be generated. The criteria in TM 3-225 are used in Table 2.1 to summarize the amount of liquid waste that can be expected. All liquid methods, except the specialized hot-water cleaning, will generate over 20x10⁶ gal/mi² of liquid, or nearly 1 gal/ft². At a normal specific volume of 0.134 ft³/gal this will be equal to 2.8x10⁶ ft³ or 1x10⁵ yd³.

TABLE 2.1 ESTIMATED LIQUID WASTE GENERATION DUE TO CLEANING OPERATIONS
(REFERENCE 17)

Type of Operation	Water Rate 10 ³ gal/h	Rate of Operation 10 ³ ft ² /h	Waste Generated	
			gal/ft ²	10 ⁶ gal/mi ²
Firehosing Areas	6	7.5	0.8	22
Firehosing Structures	6	2	3	83
Motorized Flushing	48	35	1.37	38
Firehose & Hand Scrub, Areas	5	5	1	28
Firehose & Hand Scrub, Structures	5	2	2.5	70
Hot Liquid Cleaning, Roofs	12	2.5	0.48	13
Hot Liquid Cleaning, Walls	12	2	0.6	17

FOR OFFICIAL USE ONLY

Decontamination of any unpaved areas will be handled in the same manner as those discussed in Section 2.2 Rural Areas, with the exception that smaller equipment must be used due to the congested areas.

2.3.3 Collection and Packaging. If the liquid waste is to be collected, packaged, and transported to a disposal site rather than being diluted into a sewerage system, volumes on the order of 10^7 to 10^8 gal/mi² will have to be collected and packaged. Volumes of this type present unique problems in spillage, drainage, and collection. All available drainage outlets must be blocked off and collection and transfer areas must be established. The liquid, presents a very minor resuspension hazard, can be easily pumped to a storage system, and transferred with few contamination problems. For these reasons, liquid waste will not require as detailed radiological precautions as solid waste.

Volumes of liquids as large as 10 million to 100 million gallons require a multitude of high-capacity containers such as railroad tank cars, although transportation from the collection site to a railhead may be done by 5,000-gallon M131A2 semitrailers. The capacity of a standard USAX railroad tank car is 10,000 gallons; therefore, a volume of liquid waste between 10^7 and 10^8 gal/mi² would be from 1,000 to 10,000 tank-car loads.

The amount of liquid to be collected and packaged may be materially reduced by processing the liquid at the accident site, either by a chemical extraction method or by a simple distillation process. USANDL has investigated the feasibility of a semiportable wiped-film concentrator. With larger capacity units of this type, the liquid waste can be separated into a small volume of radioactive sludge and a large volume of noncontaminated water. The water can then be dumped or reused to washdown other contaminated structures, and the amount of liquid waste to be packaged can be materially reduced.

2.3.4 Transportation. As noted in the previous section, if the liquid has to be transported to a disposal site, the only feasible method of transportation is by 5,000-gallon semitrailers or 10,000-gallon tank cars. A determination would have to be made as to whether shipment of the liquid waste in tank car lots is allowable under existing ICC Regulations. The liquid would technically be a Poison, Class D, Group III, Radioactive Material (49 CFR 73.391), and as such would have to comply with the "inside container" package regulation (49 CFR 73.393). However, if it can be shown that the tank car is leakproof and that there is no external contamination or radiation shield, the shipment may be exempted from the packaging regulation (49 CFR 73.392).

In general, handling and shipping by rail of the liquid will be safer, more efficient, and more economical than handling and shipment of solid waste by any means. This is partly due to greater knowledge and more experience in handling dangerous liquids.

FOR OFFICIAL USE ONLY

2.3.5 Ultimate Disposal. As shown in Section 2.3.2, between 10^7 and 10^8 gal/mi² of liquid waste can be generated during the decontamination effort. The fastest and most economical means of disposal would be in accordance with 10 CFR 20.303, "Disposal by Release into Sanitary Sewerage Systems," which permits release of radioactive material into a sanitary sewerage system as long as the quantity, which if diluted by the average daily quantity of sewerage released, results in an average concentration equal to or less than specified limits. For insoluble plutonium, this is 8×10^{-4} $\mu\text{c/ml}$. By assuming no dilution factor, the maximum permissible release concentration is then 3 $\mu\text{c/gal}$ or 47 $\mu\text{g/gal}$. With an average washdown of 1 gal/ft² or 10.8 gal/m², the maximum surface concentration that may be treated with no dilution is 500 $\mu\text{g/m}^2$. For contamination levels greater than this, the waste liquid may be diluted with liquid from a less contaminated area.

If the liquid must be disposed of at a separate disposal site, all the factors outlined in Section 2.2.5 are again applicable. At the disposal site, the liquid may be discharged into settling ditches or ponds and allowed to leach into the soil.

2.4 Suburban Areas and Airfields.

Suburban type land is characterized by a higher percentage of paved or improved land than rural areas, but contains more than 50 percent free land area. The improved land is in the form of streets, roads, dwellings, stores, and light industry that restricts the mobility of large earthmoving equipment. Machine operations must be done with smaller units.

An airfield or airbase will be a composite of free land, large paved areas, and structures. Although an airfield may have the same proportion of free to improved land that a suburban area has, the extent on an airbase of each type of area is very large, that is, it is not sectionalized. For this reason, large earthmoving equipment and large-scale paved area decontamination techniques can easily be used. Previous analysis of the decontamination of a typical air base by water leaching or plowing has already been done (Reference 12).

In either case, suburban area or airfield, both solid or liquid waste will be generated in direct proportion to the amount and type of surface area involved. Decontamination, collection, packaging, and transportation procedures will be similar to those outlined in Sections 2.2 and 2.3.

2.5 Radiological Safety Precautions.

Radiological safety procedures during the collection and packaging procedures will be similar to those outlined in TM 3-225, with the exception that there will be no external radiation hazard. Resuspension factors during

FOR OFFICIAL USE ONLY

the collection phase will be extremely high and use of full face masks will be mandatory. Contamination zones must be established and anticontamination clothing must be worn by personnel inside the area to prevent the spread of contamination. If the waste is transported to a railhead and then loaded into some type of railroad car, the railhead will be designated as a contaminated area. The hauling unit may have to be decontaminated when it leaves the accident site for the railhead and decontaminated again when the unit leaves the railhead for return to the site. The railroad cars must also be decontaminated when they leave the disposal site.

In general, each place where the solid or liquid radioactive waste is openly handled will become a contaminated area and proper radiological precautions must be taken. Continuous air samples and routine swipe samples will be collected in each contaminated area to determine the actual hazard; frequent surveys of each area will be made to determine that no spread of contamination occurs. These requirements emphasize the concept of collecting and packaging the waste as early as possible in the disposal cycle. If the packaging can be accomplished early enough to eliminate one or more contaminated transfer points, the cleanup operation will be greatly improved.

If it is necessary to move the waste through noncontaminated areas (rail shipment, highway rights-of-way, etc.) precautions and surveys must be made to ensure that there is no spillage enroute. In addition, appropriate packaging regulations will be followed unless waivers to the provisions of 49 CFR are obtained.

3. ECONOMICS

3.1 General.

Because of the wide variety of parameters applicable to any given accident situation, it would be impractical to give a completely detailed economic analysis of a nuclear-weapon accident. The following study is based on very broad assumptions and generalizations that can easily cause order-of-magnitude errors in economic analysis.

In general, the costs are estimated according to standard practices of time and equipment utilization (Reference 24). Such cost factors vary with different areas and situations, equipment costs varying with current changes in purchase costs, and availability of such equipment. As a conservative factor, total costs have been raised an arbitrary 20 percent to compensate for increased costs and decreased utilization due to the radiological situation. This is independent of the cost of maintaining decontamination stations and conducting operational surveys.

FOR OFFICIAL USE ONLY

The total economic cost is calculated as follows:

- (1) The operation is broken down into component parts and each subunit is analyzed independently.
- (2) For each suboperation, the manpower and equipment time needed to perform each job is computed.
- (3) The total equipment and manpower time for each unit is multiplied by the unit time cost factor and summed for each unit to obtain total. The 20-percent compensation factor is then added.
- (4) The reclamation cost of the square mile or square yard of affected area involved is calculated. A linear cost per area relationship is assumed.

It should be noted that there are no replacement costs calculated, no land value usage costs and no litigation costs estimated. These factors are beyond the scope of this study and will not even be estimated.

3.2 Free Land, Open.

Free land, open, is defined as unimproved land, covered only with undergrowth and shrubbery, and large enough for use of full-scale earthmoving equipment. Economic costs will be estimated as to whether the waste disposal efforts are minimum, large, or maximum.

Minimum Effort - Minimum waste disposal effort of this type will be as follows: Heavy underbrush and very light trees are pushed to the side of the contaminated area where they are shallow-buried and covered with uncontaminated topsoil; the stripped area is then plowed under by deep plowing. Small objects such as fences are buried and any other structures are washed down. The cost of such an operation would be, as shown in Table 3.1, at least \$80,000 per square mile or \$0.03 per square yard of affected area. Notice that over 75 percent of this cost is the stripping operations. Absence of heavy brush will correspondingly decrease this cost figure, while presence of trees or woodlands will increase the cost figure.

Large Effort - A large-scale waste disposal effort is described as clearing the land and then removing 3 inches of topsoil and transporting it 30 miles to a site for burial. Collection will be made by 18 cubic yard wheel-type scrapers or by loading trucks or dump wagons with a power shovel. A decontamination station will be set up at the accident site and at disposal sites to decontaminate the vehicle as it leaves each area. Prior to leaving the accident site, the land will be fixed by spraying with road oil. For this estimate, the volume of brush, undergrowth, debris, etc.,

FOR OFFICIAL USE ONLY

TABLE 3.1 COST PER SQUARE MILE OF MINIMUM WASTE DISPOSAL EFFORT, FREE LAND - OPEN

Operation	Man Hours	Equipment Hours	Cost
1-Clearing Grubbing, & Stripping	8,850 (\$31,000)	8,850 (\$32,000)	\$63,000
2-Plowing	1,100 (\$4,000)	1,100 (\$5,000)	\$ 9,000
3-Radiological Safety	800 (\$8,000)		\$ 8,000
Total	10,750	9,950	\$80,000 (\$0.03 per square yard)

is added to the soil volume to obtain a working figure of $5 \times 10^5 \text{ yd}^3/\text{mi}^2$. Table 3.2 gives the economic costs for this effort. As shown, the cost varies from \$0.20 to about \$0.40 per square yard or approximately 10 times the cost of plowing under. The major cost is reflected in both the transportation and radiological safety costs. Shortening the haul distances and haul times will proportionately reduce the transportation costs while use of large bulk hauling equipment or Army equipment and personnel will reduce the labor and equipment costs.

Maximum Effort - In the maximum effort, the soil is picked up, carried 3 miles to the railhead, and shipped 100 miles by rail to a military installation for burial. The cost breakdown between bulk handling and conex shipment is shown in Table 3.3.

The transportation costs are the same for either conex containers or hopper cars since carload rates apply for both. These appear at first glance to be excessive; radioactive debris is considered by common carriers to be a dangerous material and the freight rates are almost double those for hauling ordinary soil or sand. However, for the movement of 7100 carloads per square mile (142 trains of 50 cars), it may be possible to negotiate a significant freight rate reduction if the true radiological hazard is established, and unit trains are used.

FOR OFFICIAL USE ONLY

TABLE 3.2 COST PER SQUARE MILE OF LARGE WASTE DISPOSAL EFFORT, FREE LAND-OPEN, FOR THREE TYPES OF HAULING EQUIPMENT

Operation	Man-Hours	Equipment Hours	Cost
1. Clearing, Grubbing	4,600 (\$16,000)	4,600 (\$17,000)	\$ 33,000
2. Stripping	1,700 (\$6,000)	1,700 (\$9,000)	\$ 15,000
3. Casting	3,000 (\$10,000)	3,000 (\$11,000)	\$ 21,000
4. Haul w/18 yd scraper	100,000 (\$350,000)	100,000 (\$500,000)	\$ 850,000
5. Haul w/trucks (5 ton)	240,000 (\$480,000)	240,000 (\$600,000)	\$1,080,000
6. Haul w/dump wagons (18 yd)	67,000 (\$170,000)	67,000 (\$240,000)	\$ 410,000
7. Burial Site Excavating and Filling	6,400 (\$22,000)	6,400 (\$23,000)	\$ 45,000
8. Radiological Safety	20,000 (\$100,000)		\$ 100,000
Total for Hauling w/Scrapers (Opera- tions 1,2,4,7,8)	132,700	112,700	\$1,043,000 (\$0.34 per square yard)
Total for Hauling w/Trucks (Operations 1,2,3,5,7,8)	275,700	255,700	\$1,294,000 (\$0.42 per square yard)
Total for Hauling w/Dump Wagons (Opera- tions 1,2,3,6,7,8)	102,700	82,700	\$624,000 (\$0.20 per square yard)

FOR OFFICIAL USE ONLY

3.3 Free Land - Wooded.

Wooded areas will greatly increase the magnitude and economics of the problem; an average wooded area will increase waste volume by 50 to 100 percent and more than triple the reclamation time because of the bulkiness and difficulties of handling the trees. Of course, the standard construction method of burning the wood will be inadmissible because of the radiological situation. Cost per unit area will be increased by an order-of-magnitude.

3.4 Paved Areas.

As noted in Section 2.3.5, paved areas present no waste disposal problems if enough water is used to satisfy the criteria of 10 CFR 20; the only waste disposal cost will be water, labor, and pumping or distributing equipment. Rates given in TM 3-225 are sufficient to give dilution and economic costs and are detailed in Table 3.4. Notice that the cost range is an order-of-magnitude less than costs of solid disposal. If the liquid waste has to be physically picked up and transported, the cost will rapidly approach that of a large land disposal effort.

TABLE 3.4 COST PER SQUARE MILE OF DECONTAMINATION OF HARD SURFACES

Operation	Man-Hours	Equipment Hours	Cost
1. Motorized	1,540	770	\$ 6,600
Flushing of	(\$4,600)	(\$2,000)	
Paved Areas			\$ 2,800
a- Water			\$ 3,800
b- Radiological	770		
Safety	(\$3,800)	Total	\$13,200
			(\$0.004 per square yard)
2. Firehose Paved	11,100	2,220	\$35,500
Areas	(\$35,500)	(Hoses only)	
a- Water			\$ 2,800
b- Radiological	2,220		\$11,100
Safety	(\$11,100)		
		Total	\$49,400
			(\$0.016 per square yard)
3. Firehose Struc-	13,900	2,780	\$44,500
tures	(\$44,500)	(Hoses only)	
a- Water			\$ 2,800
b- Radiological	2,780		\$13,900
Safety	(\$13,900)		
		Total	\$61,200
			(\$0.02 per square yard)

FOR OFFICIAL USE ONLY

TABLE 3.3 COST PER SQUARE MILE OF MAXIMUM WASTE DISPOSAL EFFORT, FREE LAND-OPEN, FOR TWO TYPES OF SHIPMENT

Operation	Man-Hours	Equipment Hours	Cost
1. Clearing, Grubbing	4,600 (\$16,000)	4,600 (\$17,000)	\$ 33,000
2. Stripping & Hauling	13,400 (\$47,000)	13,400 (\$67,000)	\$ 114,000
3. Transfer - Conex	100,000 (\$275,000)	50,000 (\$90,000)	\$ 365,000
4. Transfer - Hopper Car	9,900 (\$30,000)	3,300 (\$12,000)	\$ 42,000
5. Transfer Sites Construction	5,000 (\$18,000)	5,000 (\$18,000)	\$ 36,000
6. Transportation			\$7,000,000
7. Burial Site Excavation & Back-filling	6,400 (\$22,000)	6,400 (\$23,000)	\$ 45,000
8. Radiological Safety	27,000 (\$135,000)		\$ 135,000
Total for Conex Ship- ment (Operations 1,2, 3,5,6,7,8)	156,400	79,400	\$7,728,000 (\$2.50 per square yard)
Total for Hopper Car Shipment (Operations 1,2,4,5,6,7,8)	66,300	32,700	\$7,405,000 (\$2.40 per square yard)

FOR OFFICIAL USE ONLY

4. AVAILABLE RESOURCES

4.1 Earthmoving.

All of the vast earthmoving resources available to the Army are contained in the various engineering units and to list all of them at this time would be ponderous. Detailed characteristics and specifications are listed in the various Tables of Organization and field and technical manuals (References 18 through 22). In brief, the most appropriate type of unit to employ is the Engineering Construction Battalion (TOE 5-115) consisting of a Headquarters and Headquarters Company, one Engineer Equipment Maintenance Company, and three Construction Companies. This battalion is capable of producing 100,000 man hours of construction effort per month on a sustained two-shift basis at full strength and is capable of any large-scale earthmoving operation. Major pieces of earthmoving equipment are: crane shovels, ditching machines, scoop loaders, dump trucks, 18 cubic yard scrapers, full tracked and rubber tired tractors with dozer blades, graders, and water distributors.

For additional earth hauling, the Engineer Dump Truck Company (TOE 5-124), consisting of two platoons of twenty-four trucks each, is capable of moving 240 cubic yards of material per round trip. This capability may be augmented by use of additional dump trucks. Examination of requirements in Tables 3.1, 3.2, and 3.3 indicates that the Engineering Construction Battalion and the Engineer Dump Truck Company, augmented by extra dump trucks, are capable of reclaiming a square mile of contaminated land within 1 to 6 weeks. The Army also has the capability of moving material through Government-owned rail transportation, as shown in Table 4.1.

TABLE 4.1 DOD AND AEC RAILROAD ROLLING STOCK

Type	Number	Capability	Dimensions	Identification
Box	876	100,000 lb	50'x9'3"x10'	USNX - NAVY
Box	100	100,000 lb	40'x9'2"x10'6"	USAX - ARMY
Tank	3356	10,000 gal	N/A	USAX - ARMY
Flat	900	200,000 lb	54'x10'	USAX - ARMY
Hopper (Covered)	83	3120 ft ³	N/A	ATMX - AEC
Hopper (Covered)	14	4275 ft	N/A	ATMX - AEC

FOR OFFICIAL USE ONLY

The box cars could not be used for transporting radioactive waste because the extra effort necessary to seal the waste inside the car would make this method of shipment unfeasible.

In addition, the joint services possess nearly 100,000 conex transportainers scattered throughout the free world and it is reasonable to assume that the depot stockpile of 10 percent or 10,000 transportainers could be made available in the event that closed-container transportation is needed.

4.2 Disposal.

There are sufficient Army installations to ensure that disposal sites will be available; however, selection of the best disposal site will depend upon the amount of free land available, depth of the water table, soil characteristics, and economic features.

5. CONCLUSIONS

As a result of this study, the following conclusions, based on available experimental data, are made:

The land area contaminated to a significant extent ($100 \mu\text{g}/\text{m}^2$) due to a nuclear-weapon accident may be a maximum of 0.5 mi^2 . This area could extend to 2.5 mi^2 if decontamination were required to the $10 \mu\text{g}/\text{m}^2$ contour.

It is both economically and radiologically more practicable to plow under the contaminated soil and to wash down the contaminated paved areas with a minimum of waste disposal.

If it were necessary to decontaminate the area by removal of the contaminate to a disposal site:

1. The approximate magnitude of waste generated would be:

Soil: $5 \times 10^5 \text{ yd}^3/\text{mi}^2$

Liquid: 10^7 to $10^8 \text{ gal}/\text{mi}^2$

2. An Engineering Construction Battalion, augmented by an Engineering Dump Truck Company with extra equipment, could reclaim the affected area in 1 to 6 weeks.

3. The Army and DOD have sufficient transportation resources to transport the waste.

FOR OFFICIAL USE ONLY

4. The Army has sufficient land to provide a disposal site.

5. The cost of reclamation and waste disposal, based on equipment and labor costs, may vary from 0.08 to 7.8 million dollars, or more, per square mile of affected land.

6. RECOMMENDATIONS

6.1 General.

It should be recognized and re-emphasized that this study has been only a first approximation to a very complex and difficult problem and that a great deal of additional work must be done in order to completely evaluate it. Two of the more complex areas that need to be further analyzed are packaging and disposal.

6.2 Packaging.

Studies should be made in bulk packaging of soils with emphasis on radiological safety. The dusty conditions normally incident to bulk earthmoving operations must be suppressed. The ability of a road oil or water spray to inhibit resuspension during vehicular movement should be studied. Prototype protective covers should be designed for scrapers, dump trucks, and dump wagons. These covers should be either canvas or sheet metal, be easily installed, removed, and decontaminated, and should be extensively tested to determine the degree of radiological safety afforded under various conditions. The conex container should be extensively tested to verify that it can safely carry a 10-ton load of soil without failure. Expedient methods of reinforcement and sealing of the door areas to preclude content leakage should be determined.

6.3 Disposal.

A survey of Army installations should be made to determine and document those sites suitable for emergency disposal of bulk radioactive waste. All suitable installations should be so designated and appropriate contingency plans developed.

FOR OFFICIAL USE ONLY

LITERATURE CITED

1. DASA Technical Letter 20-6; "Atomic Weapon Accident Hazards, Precautions and Procedures;" Defense Atomic Support Agency; 1 January 1962; UNCLASSIFIED.
2. "Handbook for Nuclear Emergency Teams;" Atomic Weapons Training Group, Field Command DASA, Sandia Base, New Mexico; 10 August 1964; UNCLASSIFIED.
3. "The Hazards and Characteristics of Plutonium and Uranium Contamination;" Atomic Weapons Training Group, Field Command DASA, Sandia Base, New Mexico; 1 May 1962; UNCLASSIFIED.
4. "Nuclear Accident Contamination Control;" Department of the Army Field Manual FM 3-15; April 1964; UNCLASSIFIED.
5. Cowan, M. and Kingsley, W.; "Contamination from One Point Detonations;" (U) Tech Memo 272-55-50, Sandia Corporation; 1955; SECRET RESTRICTED DATA.
6. Clark, J. C.; "Report of the Test Director, 56 Project NTS" (U); Los Alamos Scientific Laboratory; LA-2018, March 1956; SECRET RESTRICTED DATA.
7. Harris, P. S., Anderson, E. C., and Langham, W. H.; "Contamination Hazard from Accidental Non-Critical Decontamination of Small Atomic Devices" (U); Los Alamos Scientific Laboratory; LA-2079, September 1956; SECRET RESTRICTED DATA.
8. Shreve, J. D., Jr.; "Summary Report, Test Group 57" (U); Sandia Corporation ITR-1515; October 1958; SECRET RESTRICTED DATA.
9. Pinson, E. A., et al; "Monitoring and Decontamination Techniques for Plutonium Fallout on Large Area Surfaces" (U); Sandia Corporation; ITR-1512, May 1957; SECRET RESTRICTED DATA.
10. Report No. 1959-2 on "Safety Criteria for the Storage, Transportation and Handling of Plutonium Bearing Weapons" (U); Joint Board on Future Storage of Atomic Weapons, Defense Atomic Support Agency; 16 November 1959; SECRET RESTRICTED DATA.
11. Dick, J. L., Shreve, J. D., and Iveson, J. S.; "Operation Roller Coaster, Interim Summary Report (U);" POIR-2500, September 1963; CONFIDENTIAL.
12. Transportation Operations Research Team (TORT); "A Report to the Nuclear Safety Working Group;" 17 September 1957; SECRET RESTRICTED DATA.

FOR OFFICIAL USE ONLY

1127859

FOR OFFICIAL USE ONLY

13. Rowe, M. H., et al; "Plutonium Contamination: Phenomenology, Consequence, Estimated Cost" (U); Naval Weapons Laboratory; NAVWEPS-R7306; September 1960; SECRET RESTRICTED DATA.

14. Mishima, J.; "A Review of Research on Plutonium Released During Overheating and Fires;" Hanford Atomic Products Operations HW 83668; August 1964; UNCLASSIFIED.

15. Butler, R. E., and Miller, H. M.; "Surface Alpha Monitoring as a Method of Measuring Plutonium Fallout;" Sandia Corporation, WT 1513, August 1961; UNCLASSIFIED.

16. Levanthal, L., et al; "A Study of the Waste Disposal Aspects of RW Decontamination" (U); A Tracerlab Inc. Report under Contract DA-18-108 Cml 3456, 30 Jun 1954; CRLR-437; Chemical Corps Chemical and Radiological Laboratories, Army Chemical Center, Maryland; SECRET RESTRICTED DATA.

17. "Radiological Recovery of Fixed Military Installations;" Departments of Army and Navy Technical Manual; TM 3-225 (NAVDOCKS TP-PL-13) April 1958; UNCLASSIFIED.

18. "Use of Road and Airfield Construction Equipment;" Department of the Army Technical Manual TM 5-252; January 1955; UNCLASSIFIED.

19. "Roads and Airfields;" Department of the Army Technical Manual, TM 5-250; August 1957; UNCLASSIFIED.

20. "Engineer Field Data;" Department of the Army Manual FM 5-34; 1958; UNCLASSIFIED.

21. "Handbook, Divisional and Non-Divisional Engineer Combat Units, ROAD;" US Army Engineer School, Fort Belvoir, Virginia; UNCLASSIFIED.

22. "Engineer Construction and Construction Support Units;" Department of the Army Field Manual FM 5-162.

23. Owen, W. L., et al; "Radiological Reclamation Performance Summary, Vol. I Performance Test Data Compilation;" USNRDL-TR-967; US Naval Radiological Defense Laboratory, San Francisco, California; October 1965; UNCLASSIFIED.

24. Peurofoy, R. L.; "Estimating Construction Costs;" McGraw Hill Book Co., Inc.; 1958; UNCLASSIFIED.

FOR OFFICIAL USE ONLY

1127860

FOR OFFICIAL USE ONLY

DISTRIBUTION LIST

Copies

Internal Distribution

1 Mail and Record Center, NDL (Record Copy)
5 NDL Library
1 Commander, USANDL
5 Division Chiefs, USANDL
25 Authors

Army

1 Commanding General, US Army Materiel Command, ATTN: AMCAD-SE,
Washington, D.C. 20315
1 Commanding General, US Army Materiel Command, ATTN:
AMCRD-DN-RE, Washington, D.C. 20315
1 Headquarters, Department of the Army, Office of the Assistant
Chief of Staff for Force Development, Directorate of CBR and
Nuclear Operations, ATTN: CM PP, Washington, D.C. 20310
1 Headquarters, Department of the Army, Office of the Chief of
Research and Development, ATTN: Atomic Office, Washington,
D.C. 20310
1 The Surgeon General, Department of the Army, ATTN: MEDPS-DM,
Washington, D.C. 20315
1 The Surgeon General, Department of the Army, ATTN: MEDPS-PC,
Washington, D.C. 20315
1 Chief of Engineers, Department of the Army, ATTN: ENGM-EM,
Washington, D.C. 20315
1 Director, Division of Nuclear Medicine, Walter Reed Army
Medical Center, Washington, D.C. 20012
2 Director, US Army Foreign Science and Technology Center,
Munitions Building, Washington, D.C. 20315
1 Chief of Transportation, Department of the Army, ATTN:
TCENG-TR, Washington, D.C. 20315
2 Director, US Army Chemical Research and Development Labora-
tories, ATTN: Technical Library, Edgewood Arsenal, Maryland
21010
1 Commanding Officer, Aberdeen Proving Ground, ATTN: Technical
Library, Building 313, Aberdeen Proving Ground, Maryland
21005
1 Commanding Officer, Ballistics Research Laboratory, Aberdeen
Proving Ground, Maryland 21005

FOR OFFICIAL USE ONLY

DISTRIBUTION LIST (Continued)

Copies

1 Commander, US Army Engineer Research and Development Laboratories, ATTN: Combat Research Branch, Fort Belvoir, Virginia 22060

1 Commanding General, CONARC, ATTN: ATTNG-CBR, Fort Monroe, Virginia

1 Commanding Officer, US Army Electronics Research and Development Laboratories, ATTN: SELRA/SAT, Fort Monmouth, New Jersey 07703

2 Commanding Officer, US Army Picatinny Arsenal, ATTN: SMUPA-VA6, Dover, New Jersey 07801

2 Commanding Officer, US Army Materials Research Agency, ATTN: AMXMR-TICL, Watertown, Massachusetts 02172

2 Commanding Officer, US Army Natick Laboratories, ATTN: Technical Library, Natick, Massachusetts 01762

1 Commanding Officer, US Army Research Office - Durham, ATTN: CRD-AA-IP, Box CM, Duke Station, Durham, North Carolina 27706

1 President, US Armor Board, Fort Knox, Kentucky 40121

2 Chief, Redstone Scientific Information Center, ATTN: Document Section, US Army Missile Command, Redstone Arsenal, Alabama 35809

1 Commanding Officer, US Army Combat Developments Command, CBRA, Fort McClellan, Alabama 36205

1 Commanding General, US Army Weapons Command, ATTN: SMSWE-RDR, Rock Island, Illinois 61202

1 Headquarters, US Army Tank-Automotive Center, 28251 Vandyke, ATTN: SMOTA-RCM.3, Warren, Michigan 48090

1 Headquarters, US Army Tank-Automotive Center, ATTN: SMOTA-RCS.1, Warren, Michigan 48090

1 Commanding Officer, US Army Medical Research Laboratory, Fort Knox, Kentucky 40121

1 Commanding Officer, US Army Rocky Mountain Arsenal, ATTN: SMURM-A-MD, Denver, Colorado 80240

1 Commanding General, US Army White Sands Missile Range, ATTN: Technical Library, White Sands Missile Range, New Mexico 88002

1 Commanding Officer, US Army Combat Developments Command, Institute of Nuclear Studies, Fort Bliss, Texas 79916

1 US Army Arctic Test Board, ATTN: Chief, Division 5, APO 98733, Seattle, Washington,

50 Office of Civil Defense, ATTN: Post Attack Division, Washington D.C. 20310

FOR OFFICIAL USE ONLY

1127862

FOR OFFICIAL USE ONLY

DISTRIBUTION LIST (Continued)

Copies

- 1 Commandant, US Army Air Defense School, Fort Bliss, Texas
79916
- 1 Director, Medical Field Service School, Brooke Army Medical
Center, ATTN: Stimson Library, Fort Sam Houston, Texas
78234
- 20 Chairman, Quadripartite, CBR Standardization Committee, Build-
ing 5101, Edgewood Arsenal, Maryland 21010

Navy

- 3 Director, US Naval Research Laboratory, ATTN: 4030, 7400,
7203, Washington, D.C. 20390
- 1 Director, US Naval Research Laboratory, ATTN: Dosimetry Branch,
Code 7280, Washington, D.C. 20390
- 1 Chief, Office of Naval Research, Biological Sciences Division,
Code 440, Washington, D.C. 20360
- 1 Chief, Bureau of Naval Weapons, RRNU, Department of the Navy,
Washington, D.C. 20360
- 1 Chief, Bureau of Ships, Code 320, Department of the Navy,
Washington, D.C. 20390
- 1 Director, Special Weapons Defense Division, Bureau of Medicine
and Surgery, Code 74, Navy Department, Potomac Annex,
Washington, D.C. 20390
- 2 Commanding Officer and Director (222A), US Naval Radiological
Defense Laboratory, San Francisco, California 94135
- 1 Commanding Officer and Director, US Naval Civil Engineering
Laboratory, ATTN: Code L31, Port Hueneme, California
93041

Air Force

- 1 Headquarters, US Air Force, AFRNEA, 5D-328, Pentagon,
Washington, D.C. 20330
- 1 Commanding General, US Air Force, DCS/Research and Develop-
ment, ATTN: Directorate of Science and Technology,
Science Division, Washington, D.C. 20330
- 1 Headquarters, US Air Force, AFRDQPO, Washington, D.C.
- 1 Commanding General, Wright Patterson AFB, ATTN: Systems
Engineering Group, (SEPRR), Wright-Patterson AFB, Ohio
45433

FOR OFFICIAL USE ONLY

1127863

FOR OFFICIAL USE ONLY

DISTRIBUTION LIST (Continued)

Copies

1 Headquarters, AFWL, ATTN: WLDN, Kirtland Air Force Base,
Albuquerque, New Mexico 87116

1 Director, Air Force Weapons Laboratory, Kirtland Air Force
Base, Albuquerque, New Mexico 87117

1 Director, Air University Library, ATTN: AUL3T-62-157,
Maxwell Air Force Base, Alabama 36112

1 Director, Air Proving Ground Center (PGBAP-1), Eglin Air
Force Base, Florida 32542

1 Commanding General, USAF School of Aerospace Medicine,
Aeromedical Library, Brooks Air Force Base, Texas 78235

2 Director, USAF Project RAND, Via: Air Force Liaison Office,
The RAND Corporation, 1700 Main Street, Santa Monica,
California 90406

Other DOD Activities

20 Defense Documentation Center, Cameron Station, Alexandria,
Virginia 22314

1 Director, Office of Atomic Programs, ODDR&E Room 3E-1071,
The Pentagon, Washington, D.C. 20301

1 Director, Weapons Systems Evaluation Group, Room 1D 847,
Pentagon, Washington, D.C. 20301

1 Director, Armed Forces Radiobiology Research Institute,
National Naval Medical Center, ATTN: Security Officer,
Bethesda, Maryland 20014

1 National Military Command Systems Support Center, ATTN:
Technical Library, Pentagon, Washington, D.C. 20301

2 Director, Defense Atomic Support Agency, Washington, D.C.
20301

2 Commander, Test Command, ATTN: TCSB-R and TCTB-R, Defense
Atomic Support Agency, Sandia Base, Albuquerque, New
Mexico 87115

AEC Activities and Others

1 US Atomic Energy Commission, ATTN: DRD(ARM), Washington,
D.C. 20545

2 US Atomic Energy Commission, ATTN: Reports Library, Room
G-017, Washington, D.C. 20545

3 US Atomic Energy Commission, Division of Technical Informa-
tion Extension, Post Office Box 63, Oak Ridge Tennessee
37831

FOR OFFICIAL USE ONLY

DISTRIBUTION LIST (Continued)

Copies

- 1 NASA Scientific and Technical Information Facility, P.O. Box 33, College Park, Maryland 20740
- 1 Los Alamos Scientific Laboratory, ATTN: Report Library, Post Office Box 1663, Los Alamos, New Mexico 87544
- 1 Sandia Corporation, Post Office Box 5800, ATTN: Technical Library, Sandia Base, Albuquerque, New Mexico 87115
- 2 University of California, Lawrence Radiation Laboratory, Technical Information Division, P.O. Box 808, Livermore, California 94551
- 1 Brookhaven National Laboratory, Technical Information Division, Upton, New York
- 1 Argonne National Laboratory, 9700 South Cass Avenue, Argonne, Illinois

Additional

- 1 Department of Sanitary Engineering, Walter Reed Army Institute of Research, Washington, D.C. 20012
- 1 Commanding General, Combat Developments Command, Materiel Requirements Division, Fort Belvoir, Virginia 22060
- 2 Defense Logistics Studies Information Exchange, US Army Logistics Management Center, Fort Lee, Virginia 23801
- 3 Army Library, TAGO, Civil Defense Unit, Room 1A518, The Pentagon, Washington, D.C. 20310
- 1 Dr. Harold Knapp, Weapons Systems Evaluation Division, Institute for Defense Analysis, 400 Army Navy Drive, Arlington, Virginia 22202
- 1 Advanced Research Projects Agency, Department of Defense, The Pentagon, Washington, D.C. 20301
- 1 US Atomic Energy Commission, Hq., Reports Library, G-017, Germantown, Maryland 20545
- 1 Mr. L. J. Deal, US Atomic Energy Commission, Germantown, Maryland 20545
- 1 Mr. Hal Hollister, US Atomic Energy Commission, Germantown, Maryland 20545
- 1 Institute for Defense Analysis, ATTN: Mr. S. E. Eastman, 400 Army Navy Drive, Arlington, Virginia 22202
- 1 Advisory Committee on Civil Defense, National Academy of Sciences, 2101 Constitution Avenue, N. W., ATTN: Mr. Richard Park, Washington, D.C. 20418

FOR OFFICIAL USE ONLY

FOR OFFICIAL USE ONLY

DISTRIBUTION LIST (Continued)

Copies

1 Dr. Eugene P. Wigner, Oak Ridge National Laboratory, Oak Ridge, Tennessee 37831

1 Dr. Joseph Coker, Office of Emergency Planning, Washington, D.C. 20504

2 Dr. Paul Parrino, Public Health Service, Department of Health, Education and Welfare, Washington, D.C. 20202

1 Dr. W. Fulton Abercrombie, US Public Health Service, Division of Health Mobilization, Washington, D.C. 20201

1 Dr. Frank Parker, Health Physics Division, Oak Ridge National Laboratory, Oak Ridge, Tennessee 37831

1 Dr. Morgan Seal, US Public Health Service, P.O. Box 684, Las Vegas, Nevada 89100

1 Mr. James G. Terrell, Jr., Radiological Health Division, US Public Health Service, DHEW, Washington, D.C.

1 Dr. Arnold H. Sparrow, Biology Department, Brookhaven National Laboratory, Upton, Long Island, New York 11973

1 Assistant to the Administrator, Agricultural Research, US Department of Agricultural Research, US Department of Agriculture, Washington, D.C. 20250

1 Dr. Stanley Auerbach, Radiation Ecology Section, Health Physics Division, Oak Ridge National Laboratory, Oak Ridge, Tennessee 37831

1 Idaho Operations Office AEC, ATTN: Mr. John C. McKinley, Box 2108, Idaho Falls, Idaho 83401

REPRINTING

50 Mr. F. Raymond Zintz, Division of Operational Safety, US Atomic Commission, Washington, D.C. 20545

5 Author

FOR OFFICIAL USE ONLY

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) US Army Nuclear Defense Laboratory Edgewood Arsenal, Maryland 21010		2a. REPORT SECURITY CLASSIFICATION FOR OFFICIAL USE ONLY	
		2b. GROUP	
3. REPORT TITLE WASTE DISPOSAL ASPECTS OF A NUCLEAR-WEAPON ACCIDENT			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
5. AUTHOR(S) (Last name, first name, initial) Smale, Richard F. Maloney, Joseph C.			
6. REPORT DATE November 1966		7a. TOTAL NO. OF PAGES 48	7b. NO. OF REFS 25
8a. CONTRACT OR GRANT NO. b. PROJECT NO. 1N022601A089 c. Subtask No. 04-01 d.		9a. ORIGINATOR'S REPORT NUMBER(S) NDL-TR-79 9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
10. AVAILABILITY/LIMITATION NOTICES Each transmittal of this document outside the agencies of the US Government must have prior approval of US Army Nuclear Defense Laboratory.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY Department of the Army	
13. ABSTRACT Procedures for decontamination, collection, packaging, transportation and ultimate disposal of the large quantities of radioactive waste generated as a result of a nuclear-weapon accident are presented. Plutonium hazard and dispersion, previous research on nuclear-weapon accident hazards, as well as acceptable levels of contamination are reviewed and discussed. From Test Group 57 and Roller Coaster data, the extent of the significantly contaminated area was estimated to be between 0.1 and 0.5 mi ² . Types of waste generated and methods of collecting, packaging and transporting are presented for rural, industrial, suburban, and airfield areas. Only first approximations of economic costs are made for reclamation of each type of area. Social and legal costs are not estimated. The equipment for cleanup available to the Army through organic units and through Government agencies is reviewed. It is concluded that, while the Army theoretically has sufficient resources to conduct a cleanup of an accident site, further study is needed to determine pre-planned procedures, optimum utilization of available equipment, and expedient packaging procedures.			

DD FORM 1473
1 JAN 64

FOR OFFICIAL USE ONLY
Security Classification

1127067

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Accident, nuclear weapon Nuclear weapon accident Contamination Plutonium Waste disposal Costs Equipment Packaging						
INSTRUCTIONS						
<p>1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (<i>corporate author</i>) issuing the report.</p> <p>2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.</p> <p>2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.</p> <p>3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.</p> <p>4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.</p> <p>5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.</p> <p>6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.</p> <p>7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.</p> <p>7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.</p> <p>8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.</p> <p>8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.</p> <p>9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.</p> <p>9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (<i>either by the originator or by the sponsor</i>), also enter this number(s).</p>			<p>10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:</p> <p>(1) "Qualified requesters may obtain copies of this report from DDC."</p> <p>(2) "Foreign announcement and dissemination of this report by DDC is not authorized."</p> <p>(3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."</p> <p>(4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."</p> <p>(5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."</p> <p>If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.</p> <p>11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.</p> <p>12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (<i>paying for</i>) the research and development. Include address.</p> <p>13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.</p> <p>It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).</p> <p>There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.</p> <p>14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.</p>			

1127058

FOR OFFICIAL USE ONLY

FOR OFFICIAL USE ONLY

1127869