

K--2073-Vol. 2
DE93 009486

**Oak Ridge K-25 Site
Technology Logic Diagram**

**Volume 2
Technology Logic Diagrams**

Prepared for the Office of Technology Development
U.S. Department of Energy

Published: February 26, 1993

Prepared by
Oak Ridge K-25 Site
Oak Ridge, Tennessee 37831
managed by
MARTIN MARIETTA ENERGY SYSTEMS, INC.
for the
U. S. DEPARTMENT OF ENERGY
under contract DE-AC05-84OR21400

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Foreword

The Oak Ridge K-25 Technology Logic Diagram (TLD), a decision support tool developed to provide a planning document that relates environmental restoration problems at the Oak Ridge K-25 Site to potential technologies that can remediate these problems. The TLD uses information from the Strategic Road Map for the Oak Ridge Reservation to develop the TLD.

The TLD technique identifies the research necessary to develop these technologies for technology transfer and application to waste management, remedial action, and decommissioning activities. It is essential that follow-on engineering studies are the output of this project. These studies will begin by selecting the most promising technology from the TLD and finding an optimum mix of technologies that will provide a socially acceptable balance of cost and risk.

The Oak Ridge K-25 Site TLD consists of four separate volumes—Vol. 1, Vol. 2, Vol. 3, and Vol. 4. Volume 1 provides introductory and overview information about the TLD. Volume 2 provides the Technology Logic Diagrams. Volume 3 has been divided into two separate volumes to facilitate handling and distribution.

This volume contains the Technology Logic Diagrams and an index. The information provided before the diagrams, contains technology names and technology descriptions. The diagrams locate specific technologies in Vol. 2.

The technology evaluations that are contained in these volumes are based on the information available during the TLD compilation. New or more accurate information is solicited from the user base. Please FAX comments (615-576-8558) to R. L. Fellows, Editor, Oak Ridge K-25 Site Technology Logic Diagram, Martin Marietta Energy Systems, P.O. Box 2003, Oak Ridge, TN 37831-6003.

word

am (TLD), a decision support tool for the K-25 Site, was
elates environmental restoration and waste management
echnologies that can remediate these problems. The TLD
the Oak Ridge Reservation and from a previous Hanford

ssary to develop these technologies to a state that allows
management, remedial action, and decontamination and
ow-on engineering studies are conducted to build on the
selecting the most promising technologies identified in the
that will provide a socially acceptable balance between

our separate volumes—Vol.1, Vol.2, Vol.3A, and Vol.3B.
mation about the TLD. Volume 2 contains logic diagrams.
nes to facilitate handling and use.
agrams and an index. The index for this volume, which is
ogy names and technology numbers to help TLD users

in these volumes are based on the best information avail-
ccurate information is solicited to improve the TLD data
R. L. Fellows, Editor, Oak Ridge K-25 Site Technology
P.O. Box 2003, Oak Ridge, TN 37831-7274.

Acknowledgmer

The authors acknowledge the significant contributions made by the DOE Overview Team for
Robert Benedetti, Holmer Dugger, Mitchell Erickson, Ned Hutchins, W

Project Manager

R.K. Kibbe D&D IDC

M.J. Stephenson
J.S. Watson

MMES Waste Mgt.
MMES Env. Restr.

Deputy Project Manager, General Editor

R.L. Fellows K-25 Tech.

Planning & Integration

R.L. Fellows
D.W. Phifer, Jr.

K-25 Tech.
Publications Manager (K-25 T

Team Leaders & Section Editors

R.D. Bundy Decontamination (K-25 Tech.)
L.C. Hensley Dismantlement (MMES Engr.)
H.M. Henson Characterization (K-25 Tech.)
C.G. Jones Regulatory Compliance (MMES Env. Compl.)
S.L. Schrock Robotics/Automation (ORNL Robotics)
S.P.N. Singh Waste Management (Chem. Tech.)
J.S. Watson Remedial Action (Env. Restr.)
J.R. Weir Materials Disposition (ORNL M&C)

Publications

J.M. Asher Technical Editor
S.N. Boone Technical Editor
B.Y. Brown Secretary (K-25 Tech.)
R.M. French Secretary (K-25 Tech.)
J.A. Getsi Technical Editor
G. Glandon Electronic Publisher
C.D. Gross Electronic Publisher
R.J. Harnett Technical Editor
D.Y. Johnson Electronic Publisher
M.G. Jones Electronic Publisher
G.W. Llanos Electronic Publisher
L. McCracken Graphic Designer (Analysis
L. Palmer Graphic Designer (Analysis
D.W. Phifer, Jr. Publications Manager (K-25 T
G.E. Powell Technical Editor
N.C. Smith Electronic Publisher
C.J. Stanfill Technical Editor
R.N. Thurmer Technical Editor
R.H. Van Dyke Technical Editor
Y.W. Walton Electronic Publisher
A.L. Wampler Electronic Publisher
P.S. Wood Electronic Publisher

Deputy Team Leaders & Section Editors

G.D. Del Cul Waste Management (K-25 Tech.)
D.C. Haley Robotics/Automation (ORNL Robotics)
D.P. Hoffmann Characterization (K-25 Tech.)
B. Prince Materials Disposition (K-25 D&D Program)
A.L. Rivera Waste Management (ORNL Chem. Tech.)
J.W. Smith Dismantlement (Cent. Engr.)
J.H. Wilson Decontamination (ORNL Chem. Tech.)

Senior Advisory Group

E.J. Barber Enrich. Tech.
J.T. Bradbury Co-chairman
R.K. Genung ORNL Chem. Tech.
J.M. Googin Y-12 Develop.
A.L. Lotts Consultant, Retired ORNL M&C
J.R. Merriman Chairman (V.P. ERWM)
J.O. Moore DOE-OR
J.H. Pashley Int. Tech.

Contributors

R.B. Alderfer Decontamination (K-25 Tech.)
K.A. Bane Dismantlement (K-25 Maint.)
T. Barnes Dismantlement (Mach. Kinetic
D.E. Beck Remedial Action, Decontamin
C.E. Benson Decontamination (ORNL Chem
J.L. Bock Characterization (K-25 Quality
W.D. Bostick Waste Management, Material
(K-25 Tech.)
D. H. Bunch Decontamination (K-25 Tech.)
M. Carroll Dismantlement (Mach. Kinetic
J.M. Chaing Waste Management (MMES
P.E. Denny Dismantlement (Penn. State)

Planning/Oversight/Coordination

L.D. Charles MMES Engr.
R.L. Fellows K-25 Tech.
J.M. Kennerly MMES D&D
R.K. Kibbe D&D IDC
R.L. Snipes HAZWRAP

edgments

Overview Team for the Technology Logic Diagram Review and Development:
-n, Ned Hutchins, William Schutte, and Randall Snipes.

Waste Mgt. nv. Restr.	J.G. Dorsey C. Dudney E.L. Etnier R.L. Fellows C.A. Foster C.W. Francis R.B. Gammage W.L. Gardner P.L. Goddard C.D. Goins M.R. Guerin R.C. Hagenauer J. Hannah H.H. Haselton W. Harwood H.W. Hayden W.H. Hermes L.C. Hensley J.N. Herndon J.P. Hitch L.M. Houlberg K.A. Ingle J.M. Kennerly W.K. Key C. Kimbrough H.E. Knee J.W. Koger S.Y. Lee D.K. Little G. Mackin M.E. Mitchell E.B. Munday L.L. Oakes P. Paulauskas J.J. Perona K.E. Plummer D.P. Schaefferkoetter S.L. Schrock B.H. Singletary D.B. Smith S.H. Stow S.L. Tayloe G. Taylor C.C. Tsai T.L. White J. Zolyniak	Characterization (Y-12 Analytical) Characterization (ORNL Health & Safety) Regulatory Compliance (ORNL H&SRD) Decontamination (K-25 Tech.) Decontamination (ORNL Fusion Energy) Remedial Action (ORNL Env. Sci.) Characterization (ORNL Health & Safety) Decontamination (ORNL Fusion Energy) Remedial Action (K-25 Env. Restr.) Regulatory Compliance (MMES Legal) Characterization (ORNL Analytical) Characterization (Int. Tech.) Dismantlement (DOE France) Decontamination (ORNL Fusion Energy) Remedial Action (ORISE) Materials Disposition (ORNL Env. Sci.) Waste Management (MMES Engr.) Characterization (MMES Engr.) Robotics/Automation (ORNL Robotics) Regulatory Compliance (ORNL H&SRD) Regulatory Compliance (ORNL H&SRD) Dismantlement (DSRD) Decontamination, Dismantlement (MMES Cent. D&D) Dismantlement (ORNL Appl. Tech.) Characterization (MMES Central) Robotics/Automation (ORNL Engr., Phy., Math) Dismantlement (Y-12 Develop.) Characterization (ORNL Env. Sciences) Waste Management (Y-12 W Minimization) Remedial Action (N.C. A&T) Regulatory Compliance (MMES Env. Compl.) Decontamination (K-25 Tech.) Dismantlement (HAZWRAP) Dismantlement (ORNL Appl. Tech.) Remedial Action (ORNL Chem. Tech.) Waste Management (ORNL Fuel Recycle) Waste Management (K-25 WM) Dismantlement (ORNL Robotics) Dismantlement, Robotics/Automation (MMES Engr.) Decontamination (ORNL Appl. Tech.) Materials Disposition (ORNL Env. Sci.) Regulatory Compliance (ORNL H&SRD) Dismantlement (Y-12 Develop.) Decontamination (ORNL Fusion Energy) Decontamination (ORNL Fusion Energy) Characterization (K-25 Quality)
ch. ions Manager (K-25 Tech.)		
al Editor al Editor y (K-25 Tech.) y (K-25 Tech.) al Editor ic Publisher ic Publisher al Editor ic Publisher ic Publisher ic Publisher ic Publisher Designer (Analysas Corp.) Designer (Analysas Corp.) ions Manager (K-25 Tech.) al Editor ic Publisher al Editor al Editor al Editor ic Publisher ic Publisher ic Publisher		
mination (K-25 Tech.) lement (K-25 Maint.) lement (Mach. Kinetics Corp.) al Action, Decontamination (K-25 Tech.) mination (ORNL Chem. Tech.) erization (K-25 Quality) Management, Materials Disposition ech.) mination (K-25 Tech.) lement (Mach. Kinetics Corp.) Management (MMES Engr.) lement (Penn. State)		

How to Use Volur

The Technology Wiring Diagram shows the logic linkage among the Oak Ridge K-25 Site environmental management (EM) goals, the specific environmental problems that must be solved to meet these goals, and the various technologies that have the potential to solve these problems. The Wiring Diagram relates, through the use of flow chart arrows, the environmental restoration and waste management (WM) problems at the K-25 Site to remedial technologies. The focus of the diagram is on remedial technologies, and the status of each is considered from the standpoint of maturity, improvements over existing approaches, and applicability to specific K-25 Site problems.

Volume 2 is divided into six major sections, or chapters. Each of these major sections contains information that addresses the logic flow in meeting the EM goal. The major sections are: **Characterization**—analysis of kinds and quantities of contaminants; **Decontamination**—process to remove contaminants and restore materials; **Dismantlement**—removal of contaminated equipment and deconstruction of facilities; **Robotics/Automation**—automated equipment and processes for all other sections; **Waste Management**—handling and disposal of hazardous/toxic materials; and **Remedial Action (RA)**—reconditioning and reclamation of contaminated natural resources.

The diagram flows from left to right, and is composed of columns of input data, or logic elements. Each logic element flows from *EM Goals*. These goals are shared to varying degrees by all sections of the U.S. Department of Energy (DOE) complex. *EM Problem* contains common problem areas agreed upon by EM and DOE, such as decontamination and decommissioning (D&D), soils and ground surface water (RA), and waste management. *K-25 Site Problem* describes the site-specific problems associated with the K-25 Site. *Problem Area/Constituents* contains specific K-25 Site constituents or tangible parts of the problem that must be addressed individually. These problem areas will be formulated differently for each major section of the Technology Wiring Diagram. The *Reference Requirements* element refers the reader to Vol. 1, Chapter 6, *Summary of Regulatory Needs*. Applicable regulations must be determined on a site specific set of factors including exact location and planned mobility of constituent and technology, location characteristics, exact type, quantity, and toxicity of constituents involved throughout the technology process, types and quantities of waste created, and planned manner of transportation, storage, or disposal. *Subelement* specifies one of the categories used to identify the universe of activities necessary to solve a problem. The Subelements are: Characterization, Decontamination, Dismantlement, Materials Disposition, Robotics/Automation, and Regulatory Compliance. *Alternatives* describes the general or generic technological approaches.

Technologies is the focal point of the diagram. This is a compilation of all technologies deemed applicable to solving the EM problem. *Status* is the information concerning the maturity of the technology listed in the prior column. The categories are: Accepted—in common use and directly applicable to the K-25 Site; Demonstration—available but not demonstrated for the K-25 Site problem; Predemonstration—under laboratory development; and Evolving Technology—technology that is at conceptual or preconceptual stage (some scientific or knowledge basis only). *Science/Technology Needs* indicates areas that are related to the fundamental understanding of the scientific phenomena underlying the basis for the technology. *Implementation Needs* relates to improvements that make current technology safer, more economical, effective, or efficient.

Each technology has been prioritized according to the probability of its making significant contributions to the D&D, RA, and WM efforts at the K-25 Site. Three categories are indicated on the diagrams by arrows as follows: high probability (———), medium probability (———), and low probability (———).

- To find all c
characterize
– Turn to th
– Scan eac
The techn
least pote
- To find all o
surfaces:
– Turn to th
– Under th
(transferr
All linked
contamin
- To find inform
– Refer to ti
– Turn to th
technical
the techn
- For example,
– Locate thi
– The pag
indicates
Vol.2.
- To find out wh
– Refer to ti
– Notice th
6.3-18 th
remediati
- To determine
– Find grou
– Notice th
section.
Science/
efforts rec

se Volume 2

Uses of the Technology Logic Diagram: Examples

- To find all of the possible technology tools that are considered to have the most potential for characterization work at the K-25 Site:
 - Turn to the Characterization section of this volume.
 - Scan each page under the column *Technology* for the listing of technologies. The technology names preceded by the boldest arrows have the most potential. (Those with the least potential have the least bold arrow.)
- To find all of the decontamination technologies that remove only transferrable contamination from surfaces:
 - Turn to the Decontamination section of this volume.
 - Under the Alternatives, or generic technology, column find the category *Surface Cleaning* (transferrable contamination). All linked technologies in the adjacent Technologies column will remove transferrable contamination.
- To find information about a specific technology:
 - Refer to the index (starting on the next page) to locate the page number from the technology name.
 - Turn to the indicated page(s) to acquire detailed information about that technology. Scientific and technical literature references and more detailed information can be obtained by cross referencing the technology number to Vol. 3.
- For example, to locate information on plasma arc saw cutting of equipment:
 - Locate this technology in the index by name or technology number.
 - The page numbers for this technology are located immediately under *plasma arc saw*, and indicates the pages (Section 3, pages 4 and 11) on which detailed information can be found in Vol.2.
- To find out what can be done with contaminated oil:
 - Refer to the index at the end of this section.
 - Notice that the index lists *contaminated oil* as being in the Waste Management section, pages 6.3-18 through 6.3-27. These pages contain the various technologies considered appropriate for remediating the contaminated oil problem.
- To determine how to implement a method to remove Tc from groundwater:
 - Find *groundwater* in the index of this volume.
 - Notice that the index lists Tc in groundwater, on pages 4-11 and 4-12 of the Remedial Action section. Adsorption and ion exchange are two technologies listed for Tc removal. The Status, Science/Technology Needs, and Implementation Needs columns give information on development efforts required for these technologies.

Index

- AA (Atomic Absorption):
1- 7
- Ablating, Ablation:
1- 2, 7-8
2- 4
3- 16
- Abrasion:
3- 11
- Abrasive Water Jet Cutting:
3- 3, 7, 10-11
- Absorbed:
4- 5
5- 2
- Absorbers:
1- 9
- Absorption:
1- 6-9
- Accepted Packages:
6.6- 1
- Accepted Quantities:
6.6- 1
- Acid-dissolving:
4- 1
- Acidic:
2- 13, 26, 28
- Acid Leaching:
4- 1
6.3- 26
- Acids:
1- 2
2- 11-12, 27-28, 37, 42, 48
- Acoustic:
1- 4, 10
3- 14
- Acoustic Emission:
1- 10
- Acoustical:
3- 14
- Acoustical Scanning of Drums:
3- 14
- Actinides:
2- 1-40
6.2- 13-15
- Activated:
2- 13, 19, 29, 41
4- 10, 12, 14
- Activation:
1- 7
- Adhering:
2- 22, 33, 44, 47
- Adsorbent:
4- 5, 10
- Adsorbents:
4- 3, 10
- Adsorption:
4- 6, 10-12, 14, 16
6.3- 1, 4-5, 8, 11, 14, 17, 19, 22, 24, 26, 28, 30-31, 33
6.4- 1, 4, 6-7
- Adsorption on Activated Carbon:
4- 12, 14
- Adsorption on Carbon:
4- 16
- Adsorption with Granular Activated Carbon:
4- 10
- Adsorption with Titanium Oxide:
4- 10
- Advance-Lasers for Cutting:
3- 5
- Advanced Automatic Fixture:
3- 9, 12
5- 1-5
- Advanced Lasers for Cutting:
3- 7
- Aerial:
1- 11
- Aerobic Digestion:
6.3- 10, 14, 25
- Aerosol:
3- 4
- AES:
1- 4
- Agitation:
2- 11, 27, 37, 42, 48
- Airborne:
1- 7, 11
3- 4-6, 9, 12
- Air Sparging:
6.3- 10
- Algorithms:
5- 2-3
- Alkali Metal Polyethylene Glycolate:
4- 7
- Alkaline Leaching:
4- 2
- Alloy:
3- 4, 9
5- 2
- Alpha Track Etch Detection:
1- 7
- Aluminum:
2- 1-19, 26-27, 37-38
3- 5
6.2- 1, 3, 8-10, 16
6.3- 29-30
6.5- 1-2
- Aluminum Pipe:
2- 1-13
- Anaerobic:
4- 16
6.3- 10, 27
- Anaerobic Digestion:
6.3- 10, 27
- Anions:
1- 6
- Annular Denuder Technology:
1- 3
- Anodes:
2- 10, 26, 37-38
- Anolytes:
1- 9
- Antenna:
1- 11
- APEG:
4- 7
- Apollo:
3- 9
- Appliances:
3- 11
- Approved commercial landfills for RCRA wastes:
6.7- 2
- Arc Saw Cutting:
3- 4
- Arc-waterjet:
3- 4
- Arm:
3- 5, 9
5- 1-2
- Aromatic(s):
4- 8
6.2- 2-3, 6, 9, 18, 20
6.3- 9, 12, 15
- As, Chromates, Ba, Dioxins:
2- 1-13, 39-40, 43-46
- As-Built Master Plan Data Base:
3- 13
- Asbestos:
1- 5
2- 39-40
3- 6-7, 9
4- 8
6.1- 1
6.2- 1-4
6.5- 1-2
6.6- 2
- 6.7- 1
6.8- 1
- Asbestos Fixation:
4- 8
- Asbestos In Soils:
4- 8
- Asbestos Pipe:
2- 39-40
6.2- 1-4
6.5- 1-2
- Asbestos Removal:
3- 6-7
4- 8
- Ash:
2- 40, 46, 49
- Asphalt:
4- 9
- Assay:
1- 10
- Atmosphere(s):
1- 8
2- 4, 16, 21, 32, 44
- Atomic:
1- 7
2- 29
6.7- 2-3
- Atomic Absorption Spectroscopy:
1- 7
- Atoms:
1- 5
- Audio:
5- 4
- Auger Electron Spectroscopy:
1- 4
- Auto-Correlation Optimized Multivariate Analysis:
1- 3
- Automated Brushing:
2- 7, 34
- Automated Separation Technologies for Material Recovery:
5- 2
- Automobiles:
3- 11
- Autonomy:
5- 1
- Axial:
3- 11
- Axis:
3- 4, 10
- Ba:
2- 1-13, 39-40, 43-46
- Backhoe:
3- 2
6.1- 1
- Bacteria:
2- 13, 29, 36, 41
- Bacterial:
2- 13, 29, 36
- Bagged:
3- 6
- Bagging:
3- 6
- Bags:
1- 10
3- 6
- Balance:
4- 16
- Balances:
4- 15-16
- Ball:
3- 1
6.2- 14
6.3- 20, 23, 29-30
6.4- 8
- Bandwidth:
5- 4
- Bank:
3- 4, 10
- Banks:
3- 10
- Barrier:
3- 12
- Basins:
6.1- 1
- Bath:
2- 9, 25
- Battelle:
3- 1
- Batteries:
5- 1
- Battery:
3- 3, 15
- Bay:
3- 9
- Beads:
2- 20, 30
- Beam:
3- 3, 5-7
4- 15
6.4- 2, 4
- Bearing:
2- 10, 13, 26, 29, 38
- Bed(s):
4- 5-6, 10, 12, 15-16
6.5- 1
- Beta:
1- 6, 10
2- 11, 27
- Biocompatibility Studies:
1- 11
- Biodegradation:
4- 6, 8, 15-16
6.2- 2-3, 6, 9, 18
6.3- 9, 15
- Biological:
2- 13, 29, 36, 41, 46
4- 10, 13, 15
6.3- 3, 10, 14, 25
- Biological Treatment:
6.3- 3, 10, 14, 25
- Bioreactor:
2- 41
- Bioremediation:
4- 7-9
- Biocludge:
4- 6
- Biosorbent:
4- 13
- Biosorption:
4- 10, 13
6.3- 3, 21, 24, 31
- Bioremediation:
6.3- 21, 24, 27, 31-32
- Bioventing:
4- 8
- Bitumen:
6.5- 1
- Blade:
3- 4, 10
- Blasters:
2- 1, 14, 20, 30, 44
- Blasting:
2- 1-3, 5-6, 8, 14-15, 18, 20-22, 30-33, 35, 40-41, 43-44, 47
3- 2, 6, 11
5- 1-5
6.1- 1
- Bleed:
4- 11
- Blow:
3- 7, 10

dex

Blow-through:
3- 1
Blower:
2- 39
Blown:
2- 34
Body:
5- 1
Bonding:
1- 8
2- 4-5, 17, 22
Borehole:
1- 11
6.6- 2
6.7- 2-3
Borehole Disposal:
6.6- 2
6.7- 2-3
Bridge:
3- 1
Bridge-Mounted Robotic Platform:
5- 1
Brushes:
2- 7, 18
Brushing:
2- 7, 18, 24, 34
Bubble:
2- 10, 26
Bucky Ball:
6.2- 14
6.3- 20, 23, 29-30
6.4- 8
Bucky Ball Chemistry:
6.2- 14
6.3- 20, 23, 29-30
6.4- 8
Buffer(ing):
3- 5, 8
Bug - O:
3- 9
Bulk Decontamination Methods:
2- 13, 29, 38-40, 42-43, 46, 49
Bulk packaging:
6.6- 2
Bundles:
3- 12
Burial:
3- 1-2, 6-7, 10
6.1- 1
By-products:
2- 19, 21, 32, 37, 44
6.2- 2-3, 6, 9
Cable:
3- 1, 3, 7, 11
5- 2
Cabs:
3- 16
Cages:
6.2- 14
6.3- 20, 23
6.4- 8
Cakes:
2- 39
Caking:
6.2- 15
Calcination:
6.2- 3, 5, 7-8, 14, 16, 18-19
Calibrate:
1- 4, 5-8
Calibration:
1- 5-7, 9
3- 15
5- 4
Camcorders:
3- 13
Camera:
1- 3
3- 13

Candidate:
6.7- 2-3
Capacities:
4- 11-12
Capture:
6.8- 1
Carbonyl:
2- 38
Carboxymethylcel:
2- 26
Carrier:
2- 26
4- 12
Cartesian:
5- 5
Cascades:
3- 8
Case:
3- 6, 16
Cases:
1- 2
4- 3
Casing:
3- 5
Cast:
2- 10, 26, 37
Catalog:
3- 14
Catalyst(s):
2- 38
4- 7, 15
Catalytic Destruction:
6.2- 4, 7-8, 16, 18
6.3- 10, 13, 16
6.4- 2-3
Catalytic Extraction Process:
2- 13, 29, 38-39, 43
Catepillar:
3- 8
Cathode:
2- 10, 12, 26-27, 36-37
Cations:
1- 6
Caustic Treatments:
2- 12, 28, 36, 42
Cauterization:
3- 6
Cavities:
1- 11
CD-ROM:
3- 14
Cement Grouting:
4- 2, 4, 8
Cementitious Materials:
6.5- 1
Centrifugal Cryogenic CO2 Blasting:
2- 15, 44
Centrifugation:
6.3- 18, 21, 25, 27-29
Centrifuge Cryogenic CO2 Blasting:
2- 20, 30
Centrifuge Cryogenic CO2 Pellet Blasting:
2- 2
Ceramic:
1- 6
6.5- 2
Cercia:
6.1- 1
Cerium:
2- 12, 28
CHAR-1-OG:
1- 4
CHAR-10-OG:
1- 5
CHAR-100-OG:
1- 8
CHAR-101-OG:
1- 9

CHAR-102-OG:
1- 6
CHAR-103-OG:
1- 6
CHAR-104-OG:
1- 6
CHAR-105-OG:
1- 10
CHAR-106-OG:
1- 6
CHAR-107-OG:
1- 7
CHAR-108-OG:
1- 6
CHAR-109-OG:
1- 7
CHAR-11-OG:
1- 5
CHAR-110-OG:
1- 4
CHAR-111-OG:
1- 7
CHAR-112-OG:
1- 6
CHAR-113-OG:
1- 5
CHAR-114-OG:
1- 11
CHAR-115-OG:
1- 10
CHAR-119-OG:
1- 3
CHAR-120-OG:
1- 1
CHAR-122-OG:
1- 3
CHAR-123-OG:
1- 11
CHAR-124-OG:
1- 11
CHAR-125-OG:
1- 11
CHAR-126-OG:
1- 11
CHAR-127-OG:
1- 11
CHAR-128-OG:
1- 11
CHAR-129-OG:
1- 7
CHAR-130-OG:
1- 8
CHAR-14-OG:
1- 9
CHAR-15-OG:
1- 4
CHAR-17-OG:
1- 8
CHAR-18-OG:
1- 9
CHAR-19-OG:
1- 2
CHAR-2-OG:
1- 4
CHAR-20-OG:
1- 2
CHAR-21-OG:
1- 3
CHAR-22-OG:
1- 1
CHAR-23-OG:
1- 9
CHAR-24-OG:
1- 8
CHAR-25-OG:
1- 4
CHAR-26-OG:
1- 3

3, 26, 29, 38

0, 12, 15-16

Studies:

15-16

5, 9, 18

9, 36, 41, 46

3, 15

14, 25

14, 25

3
24, 31

4, 27, 31-32

20, 30, 44

5-6, 8, 14-15, 18, 20-22, 30-31,

35, 40-41, 43-44, 47

11

CHAR-27-OG: 1- 9
 CHAR-28-OG: 1- 1
 CHAR-29-OG: 1- 3
 CHAR-3-OG: 1- 4
 CHAR-30-OG: 1- 8
 CHAR-31-OG: 1- 5
 CHAR-32-OG: 1- 4
 CHAR-33-OG: 1- 3
 CHAR-34-OG: 1- 3
 CHAR-35-OG: 1- 8
 CHAR-37-OG: 1- 5
 CHAR-38-OG: 1- 10
 CHAR-39-OG: 1- 10
 CHAR-4-OG: 1- 4
 CHAR-40-OG: 1- 10
 CHAR-41-OG: 1- 3
 CHAR-44-OG: 1- 10
 CHAR-45-OG: 1- 11
 CHAR-46-OG: 1- 3
 CHAR-47-OG: 1- 8
 CHAR-48-OG: 1- 5
 CHAR-49-OG: 1- 11
 CHAR-5-OG: 1- 8
 CHAR-50-OG: 1- 6
 CHAR-51-OG: 1- 6
 CHAR-55-OG: 1- 1
 CHAR-56-OG: 1- 9
 CHAR-58-OG: 1- 5
 CHAR-59-OG: 1- 1
 CHAR-6-OG: 1- 7
 CHAR-60-OG: 1- 3
 CHAR-61-OG: 1- 2
 CHAR-62-OG: 1- 2
 CHAR-64-OG: 1- 2-3
 CHAR-65-OG: 1- 6
 CHAR-66-OG: 1- 8-9
 CHAR-67-OG: 1- 2
 CHAR-68-OG: 1- 10
 CHAR-69-OG: 1- 10
 CHAR-7-OG: 1- 5
 CHAR-70-OG:

1- 10
 CHAR-71-OG: 1- 1
 CHAR-72-OG: 1- 1
 CHAR-73-OG: 1- 1
 CHAR-74-OG: 1- 3
 CHAR-75-OG: 1- 1
 CHAR-76-OG: 1- 7
 CHAR-77-OG: 1- 8
 CHAR-78-OG: 1- 8
 CHAR-8-OG: 1- 9
 CHAR-81-OG: 1- 2
 CHAR-82-OG: 1- 11
 CHAR-83-OG: 1- 11
 CHAR-86-OG: 1- 2
 CHAR-87-OG: 1- 2, 4
 CHAR-88-OG: 1- 9
 CHAR-89-OG: 1- 9
 CHAR-9-OG: 1- 7
 CHAR-90-OG: 1- 10
 CHAR-91-OG: 1- 8
 CHAR-92-OG: 1- 4
 CHAR-93-OG: 1- 4
 CHAR-95-OG: 1- 6
 CHAR-96-OG: 1- 7
 CHAR-97-OG: 1- 7
 CHAR-98-OG: 1- 7
 CHAR-99-OG: 1- 9
 Characterize: 1- 10
 3- 15
 4- 5
 6.8- 1
 Characterized: 4- 6
 Characterizing: 1- 6, 10
 3- 2
 Chelating: 2- 26
 Chem Char Process: 6.2- 5, 11, 13, 17-18, 20
 6.3- 13, 16, 20, 24-26, 29-30, 32-33
 Chemical Dechlorination: 4- 15-16
 6.3- 8, 25, 31
 Chemical Dechlorination with Iron: 4- 15-16
 Chemical Fixation: 6.3- 1, 5-6, 18, 27-28, 30
 6.5- 1-2
 Chemical Foams: 2- 10, 26
 Chemical Gels: 2- 26
 Chemical Leaching:

1- 5
 2- 39
 Chemical Leaching Tests: 1- 5
 Chemical Oxidation: 4- 9, 15-16
 Chemical Precipitation: 6.3- 2, 4, 7, 19, 22, 25, 28, 30, 32
 Chemical Reduction: 6.3- 2, 6
 Chemical Separation: 4- 1-3, 5, 8-16
 Chemical Surface Cleaning: 2- 10-13, 19, 26-29, 36-37, 41-42, 48
 Chemical Treatment: 4- 1
 6.2- 1-3, 6-15, 17-19
 6.3- 1-2, 4-9, 11-12, 15, 17-20, 22-33
 6.4- 1, 3, 5, 7-9
 Chemical Waste Management: 6.7- 2
 Chemistry: 2- 13, 19, 29, 41
 4- 2
 6.2- 14
 6.3- 20, 23, 27, 29-30
 6.4- 8
 6.5- 1
 Chemobyl: 2- 12, 27, 36
 Chemometrics: 1- 3
 Chlorides: 2- 11, 19, 37
 Chlorinated Volatile Organic Compounds: 4- 5
 Chromate: 2- 1-13, 30-36, 39-40
 Chromates: 2- 1-13, 29, 36, 39-40, 43-46
 Chromatography: 1- 6, 8-10
 Citric: 2- 11-12, 27-28
 Citrox: 2- 12, 28
 Classification: 1- 10
 4- 8
 Classified: 3- 12
 Clays: 6.3- 3, 6, 18, 22
 6.4- 5, 7
 Clean Debris: 6.7- 1
 CIF3: 2- 11, 19, 37
 6.2- 8, 10
 Cloth: 6.2- 1, 3, 11-13
 6.5- 1-2
 6.8- 1
 CO2 Blasting: 2- 2, 6, 15, 18, 20, 30-31, 33, 40, 44, 47
 3- 6, 11
 Co-precipitation: 4- 13
 6.2- 14
 6.3- 2, 4, 7, 19, 22
 Coagulation: 4- 9, 14
 Coal: 6.2- 5, 11, 13, 17-18, 20
 6.3- 13, 16, 20, 24
 Coating: 2- 48
 Collection Efficiency: 1- 2
 Collimators:

1- 1
 Compact, High Capacity / 5- 2
 Composite: 1- 10
 2- 43-46
 Composite Roofing: 2- 43-46
 Compressed: 2- 6, 18, 23, 33, 40
 Compressed Air Cryogeni: 2- 6, 18, 23, 33, 40
 Compression: 3- 13
 Compressor(s): 2- 4-5, 17
 3- 11, 15
 Computational: 5- 2
 Computer Based D&D Inf System: 3- 12, 14
 Computer Software: 6.8- 1
 Computer Tomography: 1- 3
 Computerized: 1- 1, 3
 3- 13
 Computerized Image Ana: 1- 3
 Computers: 3- 4, 14-15
 Computing: 1- 1, 3
 Concentrated: 2- 11, 27, 37, 42, 44
 4- 8, 11
 6.6- 1
 Concentrated Wastes: 6.6- 1
 Concentrates: 4- 11
 Concentrating: 4- 10
 Conduits: 1- 11
 Concrete: 1- 10-11
 2- 5, 30-36, 44, 46
 3- 1-2, 6-7, 9
 6.2- 1-2, 6
 6.3- 12
 6.5- 1-2
 Concrete Cutting: 3- 1
 Concrete Milling: 2- 31
 Configuration Definition: 3- 15-18
 Configuration Verification: 3- 12-14
 Contain: 2- 31, 43, 47
 3- 1
 4- 7
 Container(s): 1- 7
 3- 2, 14, 6-7
 6.6- 1-2
 Contaminated Clothing ar: 6.5- 1-2
 Contaminated Concrete F: 6.2- 1-2
 6.5- 1-2
 Contaminated Mercury: 6.3- 32
 Contaminated Oil: 6.3- 18-27
 Contaminated Solid Wast: 6.5- 1-2

Capacity Arms:

ing:

23, 33, 40
Cryogenic CO2 Blasting:
23, 33, 40

I D&D Information Retrieval
am:

are:

graphy:

nage Analysis:

5

, 37, 42, 48

astes:

36, 48
-7, 9

j:

t:

ation:

ritification:

, 47

8-7

othing and Rags:

oncrete Rubble:

lcury:

NI:

olid Wastes:

Contaminated Solvents:
6.3- 28-32
Contaminated Specialty Freons:
6.3- 32-33
Contaminated Wastewater:
6.3- 1-18
Continuous Air Monitoring:
1- 1
Control:
1- 1, 11
2- 2, 10, 22-23, 26, 29, 33, 44-48
3- 2, 5-6, 9, 12, 15
4- 14
5- 1-5
Controlled Blasting:
3- 2
6.1- 1
Conventional:
1- 10
3- 3, 6, 8-9, 11-12
4- 9
5- 1-5
Conventional Disassembly:
3- 3
5- 1-5
Conventional Leak Detection Methods:
1- 10
Copper:
2- 1-29, 40-42
3- 7, 10
6.2- 1, 3, 8-10
6.5- 1-2
Core:
1- 2, 11
3- 1, 5
Cored:
3- 1
Corona Discharge:
4- 6, 15
Corrosion:
2- 11, 27, 37, 42, 48
6.2- 15
Corrosive:
2- 11, 27, 37, 42, 48
Cr:
2- 1-13, 39, 47-49
4- 4-5, 12-13
Criticality Indices:
1- 10
Cutting:
3- 1-12, 15-16
5- 1-5
Cutting, Advanced:
3- 6-7, 10-11
Cyclone(s):
2- 2, 15, 20, 31, 43, 47
6.4- 5-6
Cyclone Separation:
6.4- 5-6
Cylinder:
5- 4
6.4- 8-9
Cylinders of uncertain integrity:
6.4- 8-9
Damage:
1- 10
2- 3, 15, 21, 31, 41, 43
Damaging:
2- 9, 24
Damping:
3- 14
Data Assessment:
1- 3, 10-11
Data Base:
1- 1, 3
2- 29, 36
3- 13-14
Data Collection:
1- 1, 11
5- 1-5
Data Fusion:

5- 3
Database Mgmt. for Large Data Collections:
1- 1
Decompose:
2- 21, 29, 32, 44
DCON-1-OG:
2- 39, 46
DCON-10-OG:
2- 11, 27
DCON-11-OG:
2- 12, 27, 36
DCON-12-OG:
2- 11, 27, 37, 42, 48
DCON-13-OG:
2- 12, 28, 36, 42
DCON-14-OG:
2- 12, 28
DCON-15-OG:
2- 13, 28
DCON-16-OG:
2- 11, 19, 37
6.2- 8, 10
DCON-17-OG:
2- 13, 29, 36, 41
DCON-18-OG:
2- 13, 19, 29, 41
DCON-19-OG:
2- 29
DCON-2-OG:
2- 40, 42, 46, 49
DCON-20-OG:
2- 36
6.2- 2, 6
DCON-31-OG:
2- 9, 25, 37
DCON-32-OG:
2- 10, 26, 37
DCON-33-OG:
2- 38
DCON-34-OG:
2- 10, 26, 38
DCON-35-OG:
2- 1, 20, 30, 43, 47
DCON-36-OG:
2- 1, 14, 20, 30, 44
DCON-37-OG:
2- 14, 30
DCON-38-OG:
2- 1, 14, 20, 30, 44
DCON-39-OG:
2- 2, 15, 20, 30, 44
5- 1-5
DCON-4-OG:
2- 39
DCON-40-OG:
2- 2, 20, 30, 43, 47
DCON-41-OG:
2- 2, 15, 20, 31, 40, 43, 47
DCON-42-OG:
2- 3, 15, 21, 31, 41, 43
DCON-43&44-OG:
2- 3, 21, 31
5- 1-5
DCON-43-OG:
2- 16
DCON-45-OG:
2- 3, 21
DCON-47-OG:
2- 31
DCON-48-OG:
2- 31
DCON-5-OG:
2- 39
DCON-51-OG:
2- 6, 18, 23, 33, 40
DCON-52-OG:
2- 5, 22, 33, 44, 47
DCON-53-OG:
2- 45
DCON-53-OG:
2- 6, 23, 33, 47

DCON-54-OG:
2- 6, 23, 33
DCON-55-OG:
2- 7, 23, 33, 45, 48
DCON-56&57-OG:
2- 24, 34
DCON-56-OG:
2- 7, 18
DCON-57-OG:
2- 7
DCON-58-OG:
2- 8, 18, 22, 35
DCON-59-OG:
2- 8, 24, 34
DCON-6-OG:
2- 13, 29, 38-39, 43
DCON-60-OG:
2- 8, 24, 34
6.2- 3, 7-8, 14, 16, 18-18
DCON-61&62-OG:
2- 24, 35, 42
DCON-61-OG:
2- 9
DCON-62&63-OG:
2- 45
DCON-62-OG:
2- 48
DCON-63-OG:
2- 9, 25, 25, 41, 45, 48
DCON-64-OG:
2- 19, 25, 35
DCON-66-OG:
2- 9, 25
DCON-71-OG:
2- 32
DCON-72-OG:
2- 4, 16, 21, 32, 44
5- 1-5
DCON-73-OG:
2- 4, 16, 21, 41
DCON-74-OG:
2- 4, 16
DCON-75-OG:
2- 5, 17, 22
DCON-76-OG:
2- 4, 17
DCON-77-OG:
2- 5, 17, 32
DCON-8-OG:
2- 10, 28
DCON-9-OG:
2- 28
DCON-SL-10-OG:
6.2- 5
Debris:
3- 2
6.2- 4-7
6.7- 1
Decantation:
6.3- 21, 26-27, 31
Decay:
2- 11, 19, 37
Decontaminated Bldgs.:
6.2- 1-2
Degreasing:
2- 9, 24
6.8- 1
Degrees of Freedom:
5- 1
Demolition:
3- 1-2, 5, 9
6.1- 1
Demolition Compounds:
3- 2
Depletion:
2- 2, 6, 15, 20, 31, 43, 47
Desorption:
1- 9
6.2- 1
6.3- 12, 27
Destroyed:

2- 39
 4- 7
 6.3- 12, 15
Destruction:
 2- 40, 42, 46, 49
 4- 6-9, 15-16
 6.2- 1-9, 11-14, 16-20
 6.3- 9-10, 12-16, 20, 23-25, 27, 32
 6.4- 2-4
Detergents:
 2- 10, 26
Diamond Wire Cutting:
 3- 1
 5- 1-5
Differential Optical Absorption Spectroscopy:
 1- 9
Differential Ultraviolet Absorption Spectroscopy:
 1- 8
Diffraction:
 1- 5
Diffused:
 2- 32
Digesting:
 1- 2
Digestion:
 1- 2
 6.3- 10, 14, 25, 27
Digital:
 1- 10
 3- 13
Digitized:
 3- 15
Digitizing:
 3- 15
Dilution:
 1- 5
Dioxide:
 5- 1-5
Dioxins:
 2- 1-13, 39-40, 43-46
Direct Sampling Ion Trap Mass Spectrometry:
 1- 10
Disassembly:
 2- 1-9, 15-16, 18-19, 24-25, 35, 40
 3- 3, 7, 10-12, 15-16
 5- 1-5
Disassembly of Major Components:
 3- 10-12
Discharge:
 1- 9
 4- 6, 15
 5- 1
Discharged:
 3- 2
Discharges:
 2- 4-5, 17, 22
 6.2- 14
 6.3- 2, 4, 7, 19, 22
DISM-11-OG:
 3- 1
DISM-12-OG:
 3- 1
 5- 1-5
DISM-21-OG:
 3- 1
DISM-22-OG:
 3- 2
DISM-23-OG:
 3- 2
DISM-31-OG:
 3- 2
 5- 1-5
DISM-32-OG:
 3- 3
DISM-33-OG:
 3- 3
 5- 1-5
DISM-34-OG:
 3- 3
DISM-35-OG:

3- 1
DISM-36-OG:
 3- 4, 9
 5- 1-5
DISM-37-OG:
 3- 4
DISM-38-OG:
 3- 4
DISM-40-OG:
 3- 4
DISM-41-OG:
 3- 4
DISM-42-OG:
 3- 5
DISM-44-OG:
 3- 5
DISM-45-OG:
 3- 5
DISM-46-OG:
 3- 6
DISM-47-OG:
 3- 6
DISM-48-OG:
 3- 6
DISM-49-OG:
 3- 6
DISM-50-OG:
 3- 7
DISM-52-OG:
 3- 7
DISM-53-OG:
 3- 7
DISM-54-OG:
 3- 8
 5- 1-5
DISM-55-OG:
 3- 8
DISM-56-OG:
 3- 5, 8, 11
DISM-57-OG:
 3- 9
 5- 1-5
DISM-58-OG:
 3- 9
DISM-59-OG:
 3- 10
DISM-60-OG:
 3- 10
DISM-61-OG:
 3- 10
DISM-62-OG:
 3- 10
DISM-64-OG:
 3- 11
DISM-65-OG:
 3- 11
DISM-67-OG:
 3- 12
DISM-68-OG:
 3- 12
DISM-69-OG:
 3- 12
DISM-70-OG:
 3- 12
DISM-71-OG:
 3- 13
DISM-72-OG:
 3- 13
DISM-73-OG:
 3- 14
DISM-74-OG:
 3- 14
DISM-75-OG:
 3- 15
DISM-76-OG:
 3- 15
DISM-77-OG:
 3- 15
DISM-78-OG:
 3- 16
DISM-80-OG:

3- 16
DISM-81-OG:
 3- 16
Dismantlement Support:
 3- 16
Disposal of final residues from D&D, ER, and WM operations:
 6.7- 1-3
Dispersement:
 3- 6
Dispersive:
 1- 8
Display:
 1- 1
 3- 13
Disposal:
 3- 7-12
Dispose:
 3- 8
 6.2- 9, 16
 6.3- 29-30
 6.7- 3
Disposing:
 2- 13, 29, 36
Dissociate:
 2- 29
Dissolve:
 2- 11, 27, 37, 42, 48
 4- 13
Dissolved:
 2- 10, 26, 38
 4- 11
Distillation:
 2- 43
 4- 8
 6.3- 3, 7, 10, 13, 25-26, 29, 32-33
Drill:
 1- 2
Drilled:
 4- 6
Drilling:
 1- 2, 11
 3- 1
Drums:
 1- 7
 3- 14
Dry:
 2- 7-8, 24, 34, 39
Drying:
 3- 2
Dry Heat:
 2- 8, 24, 34, 39
Dry Heat Roasting:
 2- 8, 24, 34
Eddy-Current:
 5- 5
Effluent:
 2- 15, 18-19
 3- 12
 6.2- 1, 4
Electrical Equipment:
 3- 7-12
Electrochemical Methods:
 1- 5
Electrodialysis:
 6.3- 4
Electrokinetic Removal:
 4- 2, 5
Electrolysis:
 6.3- 1, 5, 17, 21, 28, 30
Electrolyte:
 2- 10, 26, 36-37
Electrolytically:
 2- 12, 27, 36
Electromagnetic:
 1- 11
Electromigration:
 2- 36
Electron Beam:
 4- 15
 6.4- 2, 4

Electron Beam Destruction:
 6.4- 2, 4
Electron Diffraction:
 1- 5
Electron Microprobe:
 1- 8
Electron Spectroscopy For Chemical Analysis:
 1- 4
Electropolishing:
 2- 13, 28
Electrorefining:
 2- 10, 26, 37-38
Electrowinning:
 2- 10, 28, 38
Elements:
 1- 1-2, 4, 6, 8, 10
 2- 38
 6.4- 7-8
Elution:
 6.2- 15
Enabling Technologies:
 3- 12-16
Encapsulate:
 6.2- 14
 6.3- 20, 23
 6.4- 8
Enclosures:
 3- 2, 7, 16
End Effector Control:
 5- 2
Energy-Dispersive X-ray Spectroscopy:
 1- 8
Envirocare:
 6.7- 2-3
Equipment Interior:
 2- 1-19
Equipment Location:
 3- 8
Eroded:
 2- 1, 14
Erosion:
 2- 3, 15, 21, 31, 41, 43
ESCA:
 1- 4
Evaporation:
 2- 12, 28
 3- 11
 4- 14
 6.3- 3, 7, 13, 33
Exhaust:
 2- 14, 19
 3- 4-5, 9
Ex Situ Bioremediation:
 4- 8
Ex Situ Chemical:
 1- 4-10
Ex Situ Physical:
 1- 3
Ex Situ Radiological:
 1- 7
Expansive Grout:
 3- 2
Explosive:
 2- 31
 3- 2, 5
Exposed:
 3- 1, 8
Exposing:
 2- 9, 24, 35, 42, 45, 48
Exposure:
 1- 6
 2- 3, 21, 31
 3- 15
 4- 8
Extended X-Ray Absorption Fine Structure:
 1- 8
Exterior:
 2- 20-29
Extractant:
 4- 2-3, 9, 12
Extracted:

arm Destruction:

raction:

roprobe:

ectroscopy For Chemical Analysis:

hing:

3, 28

ing:

0, 26, 37-38

ing:

3, 26, 38

2, 4, 6, 8, 10

-8

5

chnologies:

-2-16

3:

4

0, 23

7, 16

r Control:

persive X-ray Spectroscopy:

-3

Interior:

-19

Location:

14

15, 21, 31, 41, 43

2, 28

1

4

1, 7, 13, 33

4, 19

-5, 9

remediation:

armical:

1-10

ysical:

biological:

Grout:

31

2, 5

8

24, 35, 42, 45, 48

21, 31

5

X-Ray Absorption Fine Structure:

20-29

3, 9, 12

4- 5

Extracting:

1- 2

Extrapolating:

2- 17

Extremely:

3- 11

3- 4-5, 10

Fabricate:

3- 8

Fabrication:

3- 8-9, 11

Facilitate:

1- 4

3- 15-16

6.2- 19

Failure Recovery:

5- 1

Fernald:

1- 5-7

4- 1-2

Ferrate:

6.2- 14

6.3- 2, 4, 7, 19, 22

Ferrous:

1- 11

6.2- 1, 3, 10-11

Fiber Optic Camera Systems:

1- 3

Fiber Optic Chemical Sensors:

1- 4

Filtration:

2- 4, 14-20, 43

4- 9

6.3- 1, 4-6, 8, 14, 17-18, 21-22, 25-29,

31-32

6.4- 3, 5-7

Fissile Wastes:

6.6- 1

Fixation:

4- 2-4, 8-9, 12

6.3- 1, 5-6, 18, 27-28, 30

6.5- 1-2

Fixed and transferable contamination:

2- 1-5, 9-13, 20-22, 25-29

Flameless Thermal Oxidizers:

6.4- 2, 4

Flashlamp Cleaning:

2- 5, 17, 32

Fluid Systems:

6.1- 1

Fluoboric Acid Treatment:

2- 12, 27, 36

Fluorescence:

1- 4, 7, 9

Foaming:

6.3- 8, 14, 18, 21, 28-29, 31

Force:

2- 21, 41

3- 14

5- 1-2, 4-5

Force Control:

5- 5

Force Limiter:

5- 2

Force Reflection:

5- 1

Fork Lift:

6.1- 1

Fourier Transform Infra-Red Spectroscopy:

1- 9

Freon:

2- 42-43

Freons:

6.3- 32-33

6.8- 1

Front-end Loader:

6.1- 1

FTIR:

1- 9

Fuzzy Control:

5- 4

Gamma-Radiolysis:

6.2- 2-3, 6, 9

6.3- 9, 15, 31

Gas Chromatography:

1- 8-10

Gas Chromatography Fourier Transform

Infrared Spectroscopy:

1- 9

Gas Chromatography Mass Spectroscopy:

1- 9

Gas Phase:

2- 11, 19, 37

6.2- 8, 10

Gas Phase Decon:

2- 11, 37

Gasket Material:

2- 43-46

GLF Images:

3- 13

Classification:

3- 6

Glow Discharge Ionization Mass

Spectroscopy:

1- 9

Grabber for Remotely Cutting Metals:

3- 5

5- 1-5

Gravity Separation:

6.3- 26-27, 32

Grinding, Honing, Scraping:

2- 3, 16, 21, 31

Grit Blasting:

2- 1, 14, 20, 30, 44

Ground Freezing:

4- 6

Groundwater:

1- 1-11

2- 1-49

3- 1-16

4- 1-16

5- 1-5

6.1- 1

6.2- 1-20

6.3- 1-33

6.4- 1-9

6.5- 1-2

6.6- 1-2

6.7- 1-3

6.8- 1

Ground-Penetrating Radar:

1- 11

Group I, II, III:

6.6- 2

Grouting:

4- 2-4, 8

Hadarnad Masking for Spatial Resolution:

1- 1

Halogenated:

6.2- 2-3, 6, 9, 18, 20

6.3- 9, 12, 15, 28-32

Hand and Automated Brushing:

2- 34

Hand Brushing:

2- 7, 18

Hand Grinding, Honing, Scraping:

2- 16

HDTV:

5- 4

Heavy Metals in Groundwater:

4- 12-13

Heavy Metals in Oil:

6.3- 21-24

Heavy Metals in Soils:

4- 4-5

Heavy Metals in Solvents:

6.3- 29-31

Heavy Metals in Water:

6.3- 5-7

HGMS:

6.3- 3, 6, 18, 22, 28, 30

6.4- 5, 7

High Gradient Magnetic Separation:

6.3- 3

High Gradient Magnetic Separation

(HGMS):*****

High Pressure Abrasive Water Jet:

3- 7, 10

High Pressure Abrasive Water Jet Cutting:

3- 7, 10

High Pressure Water:

2- 5, 22, 33, 44, 47

3- 1, 7, 10

5- 1-5

High Pressure Water Jet:

3- 10

5- 1-5

High-Pressure Water:

2- 1, 20, 30, 33, 44, 47

High-Temperature Crystalline Materials:

6.5- 2

High-Temperature Noncrystalline Materials:

6.5- 2

Holographic Imaging:

1- 3

3- 13

Hot Air:

2- 8, 24, 34

Hot Air Stripping:

2- 8, 34

Hot Water:

2- 6, 23, 33

Hydraulic Retrieval:

6.1- 1

Hydrocarbons in Soils:

4- 8-9

Ice Blasting:

2- 2, 20, 30, 43, 47

Imaging and Image Processing:

5- 4

Improved Protective Clothing and Equipment:

3- 16

In Situ:

1- 3-4, 6-11

2- 10-11, 19, 23, 26, 34, 37, 40

4- 2-8, 12, 14

In Situ Air Stripping:

4- 14

In situ Biodegradation:

4- 6, 8

In Situ Chemical:

1- 4, 7-9

In Situ Physical:

1- 3, 10-11

In Situ Radiological:

1- 6

In Situ Vitrification:

4- 2-4, 7

In-Situ Passive Monitors:

1- 6

Incineration:

2- 40, 42, 46, 49

4- 7-8

6.2- 3-4, 8, 11-12, 16-17, 19

6.3- 9, 12, 16, 20, 23, 25-26, 29-30, 32

6.4- 2-3

Incorporation with Asphalt:

4- 9

Inductively Coupled Plasma - Mass

Spectrometry:

1- 8

Inductively-Coupled Plasma Spectroscopy:

1- 8

Information Retrieval System:

3- 12, 14

Inorganic Acid Treatments:

2- 11, 27, 37, 42, 48

Inorganic Membrane Separation:

6.4- 1, 3-4, 6

Inorganic Microporous Filters:

6.3- 1, 4, 6, 8, 17-18, 22, 28, 30, 33

6.4- 1, 3-4, 6

spectroscopy:
 Drilling For Depth Profiling:
 Standardized Type A Packaging:
 Containers:
 40
 3:
 anner:
 Spectroscopy:
 Concrete:
 vation:
 Site:
 el:
 -19
 0-11, 26-27, 37-38, 42, 48
 , 3, 7-10
 -2
 -nyl:
 3
 -metal:
 -10
 onated:
 -5-32
 onated Organics In Oil:
 -5-27
 ctive Hazardous Waste:
 a Organics In Gases:
 2-4
 20-36, 39-40
 18-27
 U, Tc, Actinides:
 20-29
 24, 34, 39
 8
 2-8, 14, 16, 18-19
 32-33
 ckaging:
 2
 roscopy:
 4
 on of Sampling Designs:
 1
 cid Treatments:
 11, 27
 apor Monitoring:
 8
 1
 8-10
 13, 21, 32, 40, 44, 46, 49
 1
 1-20
 2, 5, 7, 9-16, 19-20, 23-27
 1-9
 as Cylinders:
 8-9
 ss I Low-Level Waste Landfill:
 2
 rap Bldg. Materials:
 1-2
 in Cement Kiln:

4- 9
 Oxygen Cutting:
 3- 4
 Ozonation-Photolysis:
 6.3- 12, 16
 Packaging equipment:
 6.8- 2
 Paper:
 2- 31
 6.2- 1, 3, 11-12
 6.5- 1-2
 6.8- 1
 Particle-Induced X-Ray Emission:
 1- 8
 Particulates In Gases:
 6.4- 4-6
 PAS:
 1- 4
 Passive Neutron:
 1- 6
 PCB:
 1- 9
 2- 30-36, 39, 41
 3- 3, 7-12
 4- 7-8, 16
 6.1- 1
 6.2- 2-4, 18, 20
 6.3- 9, 12, 15, 24-25, 31-32
 6.6- 1
 6.8- 1
 PCB Contaminated:
 3- 7-12
 6.6- 1
 PCB Contaminated Wastes:
 6.6- 1
 PCB in Oil:
 6.3- 24-25
 PCB in Solvents:
 6.3- 31-32
 PCBs:
 1- 8-10
 2- 13, 20-29, 34, 36, 39-46
 4- 7-8, 14, 16
 6.1- 1
 6.2- 1-2, 4-7
 6.3- 8-10
 PCBs in Groundwater:
 4- 16
 PCBs in Soils:
 4- 7-8
 PCBs in Water:
 6.3- 8-10
 Perception:
 5- 4-5
 Performance Oriented Packaging:
 6.6- 1-2
 Photocatalytic Oxidation:
 4- 7
 Photolysis:
 3- 16
 Photonic Removal of Contaminants:
 3- 16
 Physical In Situ:
 1- 10
 Physical Separation:
 4- 1, 5-6, 8-9, 14
 Physical Treatment:
 6.3- 1, 3-6, 8, 10-11, 14, 17-19, 21-22,
 24-33
 6.4- 1-8
 Plasma Arc cutting:
 3- 4, 9
 5- 1-5
 Plasma Arc Furnace:
 6.2- 1, 4
 Plasma Arc Saw:
 3- 4, 10
 Plasma Surface Cleaning:
 2- 4-5, 17, 22
 Plasma Torch:
 2- 4, 16, 21, 32, 44

3- 4, 10
 5- 1-5
 Plastic:
 2- 3, 15, 21, 31, 41, 43, 47-49
 3- 5
 6.5- 1-2
 Plastic Pellet Blasting:
 2- 3, 15, 21, 31, 41, 43
 Plastics:
 6.2- 1, 3, 11-12
 6.8- 1
 Plastics-Thermoplastics:
 6.5- 1
 Plastics-Thermosetting:
 6.5- 1
 Platform Control:
 5- 2
 Point and Direct:
 3- 16
 Polymer Grouting:
 4- 2, 4
 Polymer Impregnated Concrete:
 6.5- 1
 POP Container:
 6.6- 1-2
 Porous Aluminum:
 2- 37-38
 Porous Nickel:
 2- 37-38
 6.2- 1, 3, 7-8
 6.5- 1-2
 Position Sensors for Manipulator and End-
 Effectors:
 5- 5
 Positioning:
 3- 1, 8-9, 12
 5- 1-5
 Positioning Accuracy:
 5- 1
 Power Sources for Mobile Platform:
 5- 1
 Pre-Programmed Obstacle Avoidance:
 5- 3
 Precipitation:
 4- 12-13
 6.2- 14
 6.3- 2, 4, 7, 19, 22, 25, 28, 30, 32
 Profiling:
 1- 2, 4, 11
 Programmed Motions:
 5- 3
 Proportional Counting:
 1- 6
 Protective Clothing:
 3- 5, 7, 11, 16
 6.2- 1, 3, 12-13
 Proximity:
 5- 5
 Punch Cores:
 1- 11
 Pyrolysis:
 6.2- 5
 Qualitative IR Thermography:
 3- 3, 15
 RAD:
 1- 1, 7
 6.1- 1
 6.2- 1-13, 15-20
 6.3- 1-3, 18-21, 28-29, 32-33
 6.7- 1-2
 6.8- 1
 RAD and Technetium In Oil:
 6.3- 18-21
 RAD in Solvents:
 6.3- 28-29
 RAD in Water:
 6.3- 1-3
 Radioactive Elements In Gases:
 6.4- 7-8
 Radioactive Materials:
 2- 10, 26, 37

4- 4
 6.6- 1
 Radiographic Imaging:
 1- 10
 RCRA Waste:
 6.7- 2
 Recharacterize:
 6.4- 8
 REDOX Treatments:
 2- 12, 28
 Reduction Adsorption:
 4- 11
 Reduction and Fixation:
 4- 4, 12
 Redundant Drives:
 5- 1
 Reflection:
 1- 11
 5- 1
 Refraction:
 1- 11
 REMA-1:
 4- 2
 REMA-101:
 4- 16
 REMA-102:
 4- 16
 REMA-103:
 4- 16
 REMA-104:
 4- 16
 REMA-11:
 4- 1
 5- 1-5
 REMA-111:
 4- 12
 REMA-112:
 4- 12
 REMA-113:
 4- 13
 REMA-114:
 4- 13
 REMA-115:
 4- 13
 REMA-116:
 4- 13
 REMA-12:
 4- 1
 REMA-121:
 4- 11
 REMA-122:
 4- 11
 REMA-123:
 4- 11
 REMA-124:
 4- 12
 REMA-125:
 4- 12
 REMA-13:
 4- 1
 REMA-130:
 4- 15
 REMA-131:
 4- 15
 REMA-132:
 4- 15
 REMA-133:
 4- 9
 REMA-14:
 4- 1
 REMA-15:
 4- 2
 REMA-16:
 4- 2
 REMA-17:
 4- 2
 REMA-18:
 4- 2
 REMA-19:
 4- 3
 REMA-2:

4- 2
 REMA-21:
 4- 9
 REMA-22:
 4- 10
 REMA-23:
 4- 10
 REMA-24:
 4- 10
 REMA-25:
 4- 10
 REMA-26:
 4- 11
 REMA-31:
 4- 5
 REMA-32:
 4- 5
 REMA-33:
 4- 6
 REMA-34:
 4- 6
 REMA-35:
 4- 6
 REMA-37:
 4- 6
 REMA-38:
 4- 6
 REMA-39:
 4- 6
 REMA-41:
 4- 14
 REMA-42:
 4- 14
 REMA-43:
 4- 15
 REMA-44:
 4- 14
 REMA-46:
 4- 14
 REMA-47:
 4- 15
 REMA-48:
 4- 15
 REMA-49:
 4- 15
 REMA-51:
 4- 7
 REMA-52:
 4- 7
 REMA-53:
 4- 7
 REMA-55:
 4- 7
 REMA-56:
 4- 8
 REMA-57:
 4- 8
 REMA-58:
 4- 8
 REMA-59:
 4- 7
 REMA-61:
 4- 8
 REMA-63:
 4- 9
 REMA-64:
 4- 8
 REMA-65:
 4- 9
 REMA-67:
 4- 9
 REMA-68:
 4- 9
 REMA-69:
 4- 9
 REMA-70:
 4- 9
 REMA-71:
 4- 4
 REMA-72:
 4- 4

REMA-73:
 4- 5
 REMA-74:
 4- 5
 REMA-75:
 4- 4
 REMA-76:
 4- 4
 REMA-77:
 4- 4
 REMA-78:
 4- 4
 REMA-81:
 4- 3
 REMA-82:
 4- 3
 REMA-83:
 4- 3
 REMA-84:
 4- 3
 Repackage:
 6.4- 8
 Residue:
 2- 30
 4- 2, 8
 6.2- 5, 11, 13, 17-20
 6.3- 13, 16, 20, 24
 Reverse Osmosis:
 4- 11, 13-14
 6.3- 1, 3, 6, 14, 21
 ROBA-1-OG:
 5- 1
 ROBA-10-OG:
 5- 1
 ROBA-11-OG:
 5- 2
 ROBA-12-OG:
 5- 2
 ROBA-2-OG:
 5- 1
 ROBA-23-OG:
 5- 2
 ROBA-24-OG:
 5- 2
 ROBA-25-OG:
 5- 2
 ROBA-26-OG:
 5- 2
 ROBA-27-OG:
 5- 2-3
 ROBA-28-OG:
 5- 2
 ROBA-29-OG:
 5- 3
 ROBA-3-OG:
 5- 1
 ROBA-30-OG:
 5- 3
 ROBA-31-OG:
 5- 3
 ROBA-32-OG:
 5- 3
 ROBA-33-OG:
 5- 3
 ROBA-34-OG:
 5- 3
 ROBA-35-OG:
 5- 3
 ROBA-4-OG:
 5- 1
 ROBA-46-OG:
 5- 3
 ROBA-47-OG:
 5- 4
 ROBA-48-OG:
 5- 4
 ROBA-49-OG:
 5- 4
 ROBA-5-OG:
 5- 1
 ROBA-50-OG:

5- 4
 ROBA-51-OG:
 5- 4
 ROBA-52-OG:
 5- 4
 ROBA-53-OG:
 5- 4
 ROBA-54-OG:
 5- 4
 ROBA-6-OG:
 5- 1
 ROBA-65-OG:
 5- 4
 ROBA-66-OG:
 5- 4
 ROBA-67-OG:
 5- 4
 ROBA-68-OG:
 5- 5
 ROBA-69-OG:
 5- 5
 ROBA-7-OG:
 5- 1
 ROBA-70-OG:
 5- 5
 ROBA-71-OG:
 5- 5
 ROBA-72-OG:
 5- 5
 ROBA-73-OG:
 5- 5
 ROBA-74-OG:
 5- 5
 ROBA-75-OG:
 5- 5
 ROBA-8-OG:
 5- 1
 ROBA-9-OG:
 5- 1
 Rubble:
 2- 31-32
 3- 2
 6.2- 1-2
 6.3- 12
 6.5- 1-2
 S:
 1- 1, 4-6, 9-10
 2- 1-13, 16, 24, 39-41, 44, 47-49
 3- 1-5, 7, 9-12, 14-16
 4- 1, 3, 7, 13
 5- 1, 4-5
 6.1- 1
 6.2- 1, 3-4, 8-9, 11, 17
 6.3- 1, 3, 7-10, 12-14, 24-26, 28-29, 31-33
 6.4- 1, 3-8
 6.5- 1
 6.6- 1
 6.7- 2-3
 6.8- 1
 Sample Management:
 5- 3
 Sampling & Mixing Methods:
 1- 1-3, 8-11
 Sampling, Sample Prep:
 1- 1-2, 8
 SAW Sensors:
 1- 9
 Saws:
 3- 3, 12
 Scanning Electron Microscopy:
 1- 3
 Scrap Aluminum, Copper, and Other Non-Ferrous Metals:
 6.2- 1, 3, 9-10
 6.5- 1-2
 Scrap Asbestos:
 6.2- 1-4
 6.5- 1-2
 6.7- 1
 Scrap Asbestos Pipe & Insulation:

6.2- 1-4
 6.5- 1-2
 Scrap Metals:
 6.1- 1
 Scrap Plastic, Paper, and Cloth:
 6.5- 1-2
 Scrap Porous Nickel:
 6.2- 1, 3, 7-8
 6.5- 1-2
 Scrap Steel:
 6.5- 1-2
 Scrap Transite:
 6.2- 1-4
 6.5- 1-2
 Scrap Wood:
 6.1- 1
 Scrubbers:
 2- 11, 27, 37, 42, 48
 6.4- 1, 3, 5-7
 Secondary Ion Mass Spectrometry:
 1- 4
 Secondary Neutral Mass Spectrometry:
 1- 5
 Sedimentation:
 6.3- 8, 14, 17, 26
 Seismic Methods:
 1- 11
 Select Alpha Radionuclide Analysis By PER-ALS:
 1- 7
 SEM:
 1- 3
 Semi-Volatile Organics in Water:
 6.3- 14-16
 Sensor Delivery Systems:
 1- 1
 Sensors:
 1- 4, 9
 3- 15
 5- 1-5
 Sheet Metal:
 2- 21-29
 3- 11
 Shot Blasting:
 2- 1, 14, 20, 30, 44
 Shredding and Sorting:
 3- 11
 Signal Transmission:
 5- 4
 SIMS:
 1- 4
 Single Human-Multiple Vehicle Control Static:
 5- 3
 Sludges:
 2- 39
 4- 3
 6.2- 1, 3, 17-18
 Small Long-Range Alpha Detection:
 1- 6
 Smelt Purification:
 2- 9, 25, 37
 Smelting:
 2- 9, 25
 6.2- 5, 7-8, 10
 SNMS:
 1- 5
 Soil Venting:
 4- 5, 8-9
 Soil Washing:
 4- 1, 3, 5
 Soils:
 1- 1-11
 2- 1-49
 3- 1-16
 4- 1-16
 5- 1-5
 6.1- 1
 6.2- 1-20
 6.3- 1-33
 6.4- 1-9
 6.5- 1-2

	6.6- 1-2	6.6- 1	5- 2
	6.7- 1-3	Structural Steel:	Transferable contamination:
	6.8- 1	2- 1, 14, 20-29	2- 1-13, 20-29
Paper, and Cloth:	Solid Sorbent Sampling:	3- 3-5, 7, 9	Transmission Electron Microscopy:
	1- 8	Structure:	1- 3, 5
Nickel:	Solidification:	1- 3, 8, 10	Transmutation:
, 7-8	6.5- 1-2	3- 2, 14	6.2- 19
	Solids Separation:	4- 8	6.3- 28
	4- 1	Subsurface Complexation:	Transportable Control Stations:
	Solvent Extraction:	1- 11	5- 4
	1- 2	Sulfur Polymer Grouting:	Trench Disposal:
	2- 39, 46	4- 4	6.7- 1-2
	4- 1-2, 8-9	Supercritical CO ₂ :	Triangulation Mapping:
	6.2- 1, 3, 6, 9, 11-12, 14, 17, 19	2- 2, 15, 20, 31, 40, 43, 47	3- 15
	6.3- 2, 5, 7, 9, 11, 15, 19, 23-24, 26, 28,	Supercritical CO ₂ Blasting:	TRU Waste:
	31, 33	2- 2, 15, 31, 47	6.7- 3
	6.4- 1, 3, 5, 7-9	Supercritical Water Oxidation:	Type A Fissile Certified Packaging:
27, 37, 42, 48	Solvent Scrubbing:	6.2- 15	6.6- 1
4, 5-7	6.4- 1, 3, 5, 7-9	6.3- 25-26	Type A Package:
n Mass Spectrometry:	Solvent Washing:	Superheated Water:	6.6- 1
	2- 9, 24, 35, 42, 45, 48	2- 6, 23, 33, 45, 47	Type A Packaging:
Neutral Mass Spectrometry:	6.2- 1	Supported Liquid Membrane:	6.6- 1
	Solvents:	4- 12	Type B Fissile Certified Packaging:
	1- 2	Surface Cleaning:	6.6- 1
14, 17, 26	2- 9, 24, 35, 42, 45, 48	2- 4-13, 17-19, 22-29, 33-37, 40-42,	Type B Packaging:
ods:	6.3- 28-32	44-45, 47-48	6.6- 1
Radionuclide Analysis By PER-	6.8- 1	Surface Contamination:	U:
LS:	Sorting for Recycle:	1- 6, 9	1- 1, 5-10
	3- 11	2- 9, 27	2- 1-49
	Spent Ion Exchange Media:	Surface Removal:	3- 2-3, 6-8, 11-14
	2- 12, 28	2- 1-5, 14-17, 20-22, 30-32, 40-41, 43-	4- 2, 5-6, 8, 15
Organics in Water:	6.2- 1, 3, 15-17	44, 47	5- 1, 4-5
16	6.5- 1-2	3- 2, 16	6.1- 1
ary Systems:	Sponge Blasting:	5- 1-5	6.2- 1-2, 4, 6, 10, 12-13, 17
	2- 8, 18, 22, 35	Synchronous Fluorescence:	6.3- 1-3, 6, 8, 13-14, 17-18, 25, 28-29,
	Standardize Methodology:	1- 9	33
	1- 2	Tc:	6.4- 1-2, 6-7
9	Statistical Methods For Multivariate Data:	1- 5-8, 11	6.5- 2
	1- 3	2- 1-46	6.6- 2
5	Statistical Methods for Spatially Correlated	3- 3, 11-12	6.7- 2-3
	Data:	6.3- 32	U, Oil, Tc, PCBs, Actinides:
-29	1- 1	Tc Geochemical Behavioral Modeling:	2- 20-29, 39-40
	Statistics:	1- 11	U, S, Cr:
J:	1- 1, 11	Tc In Groundwater:	2- 1-13, 47-49
14, 20, 30, 44	Statistics, Data Collection:	4- 11-12	U, Tc:
nd Sorting:	1- 1, 11	Tc In Soils:	1- 5-7
mission:	Steam:	4- 3	2- 1-46
	2- 7, 23, 33, 45, 48	Technetium In Water:	U, Tc, Actinides:
	3- 7	6.3- 3-5	2- 1-38
	4- 5	Technical Resources Data Base:	U, Tc, Actinides, S, Cr:
	6.2- 13	3- 14	2- 1-13
un-Multiple Vehicle Control Station:	6.3- 13, 16	TEM:	U, Tc, PCBs:
	6.4- 2, 4	1- 3	2- 39-42
	Steam Extraction:	2- 18	UF ₆ , Tc, Actinides:
	4- 5	Tennessee:	2- 1-13
	Steam Stripping:	6.7- 1-3	Ultra High-Pressure Water:
3, 17-18	6.2- 13	Tethers:	2- 1, 20, 30
Range Alpha Detection:	6.3- 13	5- 1	Ultrafiltration:
	6.4- 2, 4	Thermal arc-waterjet:	6.3- 1, 3, 6, 14, 21, 28, 30
ation:	Steel:	3- 4	Ultrahigh Pressure Water:
25, 37	2- 1-29	Thermal Desorption:	2- 43
	3- 1-5, 7, 9-12	6.2- 1	Ultrahigh-Pressure Water:
25	6.2- 1, 3, 10-11	6.3- 12, 27	2- 1, 47
7-8, 10	6.5- 1-2	Thermal Substrate Surface Removal:	Ultrasonic:
	Steel Cylinders:	2- 4-5, 18-17, 21-22, 32	1- 2, 10-11
	2- 1-13	Thermal Treatment:	2- 9, 11, 25, 27, 37, 42, 48
	3- 11	4- 9	5- 5
8-9	Steel Metal:	6.2- 1, 3-5, 7-8, 10-12, 14-20	Ultrasonic Cleaning:
ig:	2- 20	6.3- 3, 9-10, 12-13, 16, 20, 23-27, 29-33	2- 9, 25
3, 5	Steel Pipe:	6.4- 2-4, 6	Ultrasonic Extraction:
	2- 1-13	Thermite Cutting:	1- 2
-11	Strippable Coatings:	3- 5	Ultrasonic Leak Detection:
-49	2- 9, 25, 35, 41, 45	Thickness:	1- 10
-16	Stripping:	3- 4-5, 7, 10	Ultrasonic Ranging and Data System:
-16	2- 8, 24, 34	5- 5	1- 11
-5	3- 6	Title:	Ultrasound:
	4- 14	2- 43-46	4- 15
-20	6.2- 2, 7, 10-11, 13, 15, 17, 19	6.2- 1, 3-7	Umbilical:
-33	6.3- 11, 13, 20, 29-31	1- 6	3- 9
-9	6.4- 2, 4	TLD Array for a Spatial Characterization:	5- 1, 4
-2	Strong Tight Containers:	Tool-Arm Interface:	Umbilical Cord:

5- 1
 Underground Disposal:
 6.7- 2-3
 Underground Waste Retrieval Facilities:
 6.7- 1
 UO₂F₂:
 6.2- 1, 3, 13-15
 6.5- 1-2
 Uranium in Groundwater:
 4- 9-11
 Uranium in Soils:
 4- 1-3
 Use of Existing Equipment for Disassembly:
 3- 12
 Use of Existing Fixtures and Tooling:
 3- 11
 Use of Existing Fixtures for Thermal Cutting:
 3- 8
 UT Landfill:
 6.7- 3
 UV Enhanced Chemical Oxidation:
 4- 15
 Vacuum Assisted, Reverse Flow Solvent
 Extraction Methods:
 1- 2
 Vacuum Cleaning:
 2- 35
 Vacuum Extraction:
 4- 5
 Vacuum System:
 2- 1, 7, 14, 18, 20-21, 31, 44
 3- 2, 6-7, 10
 Vacuuming:
 2- 19, 25
 Vapor Extraction:
 4- 6, 9
 Ventilation System:
 3- 7-12
 Venting:
 4- 5, 8-9
 Vibration:
 3- 14
 Video Mapping:
 3- 15
 Visual Display Of Statistical Information:
 1- 1
 Vitrification:
 4- 2-4, 7
 VOCs:
 1- 8-10
 4- 5-6, 14-15
 6.2- 1
 6.3- 12
 6.4- 1-2
 VOCs in Gases:
 6.4- 1-2
 Voice Control:
 5- 3
 Volatile Organic Compounds in Water:
 6.3- 10-14
 Waste Curie Monitoring:
 1- 7
 Waste Disposal:
 6.1- 1
 6.3- 1, 4, 6, 8, 17-18, 22, 28-31, 33
 6.4- 1, 3-4, 6
 6.5- 2
 6.7- 1-3
 6.8- 1
 Waste Gases of Unknown Characteristics from
 D&D and RA Operations:
 6.4- 8-9
 Waste Isolation Pilot Plant:
 6.7- 3
 Waste Minimization Evaluation System:
 6.8- 1
 Waste Off-Gases from D&D, RA, and WM
 Operations:
 6.4- 1-8
 Waste Packaging, Handling, and
 Transportation:

6.8- 2
 6.7- 1-3
 Waste Processing:
 6.2- 1-20
 6.3- 1-33
 6.4- 1-9
 6.5- 1-2
 Waste Processing Residuals:
 6.5- 1-2
 Waste Stabilization:
 6.2- 1-2, 4, 7-8, 10, 12-13, 15, 17, 19
 6.5- 1-2
 Waste UO₂F₂:
 6.2- 1, 3, 13-15
 6.5- 1-2
 Water Extractant:
 4- 2
 Wavelength Dispersive X-Ray Spectroscopy:
 1- 8
 WDIS-101-OG:
 6.7- 1
 WDIS-102-OG:
 6.7- 1
 WDIS-104-OG:
 6.7- 3
 WDIS-105-OG:
 6.7- 3
 WDIS-106-OG:
 6.7- 2
 Weak Beta Radionuclides:
 1- 6
 Wells & Punch Sources:
 1- 11
 Wet Air Oxidation:
 6.2- 18, 20
 6.3- 9, 12, 15
 WIPP:
 6.7- 3
 WMIN-100-OG:
 6.8- 1
 Wood:
 2- 43-46
 6.1- 1
 6.2- 1, 3-7
 6.8- 1
 WPH&T:
 6.8- 1-2
 6.7- 1-3
 WPHT- 100-OG:
 6.6- 1
 WPHT- 101-OG:
 6.8- 1
 WPHT- 105-OG:
 6.8- 2
 WPHT- 106-OG:
 6.8- 2
 WPHT-102-OG:
 6.8- 1
 WPHT-103-OG:
 6.8- 1
 WPHT-104-OG:
 6.8- 1
 WPHT-107-OG:
 6.8- 2
 WPR-303-OG:
 6.4- 8
 WPRO-100-OG:
 6.2- 2-3, 6, 9
 6.3- 9, 15, 24, 26, 31
 WPRO-101-OG:
 6.2- 14
 6.3- 20, 23, 29-30
 6.4- 8
 WPRO-104-OG:
 6.2- 15
 WPRO-105-OG:
 6.2- 9
 WPRO-106-OG:
 6.2- 1
 6.3- 12, 27
 WPRO-107-OG:

6.2- 1, 4
 WPRO-108-OG:
 6.2- 3-4, 8, 11-12, 16-17, 19
 6.3- 9, 12, 16, 20, 23, 25-26, 29-30, 32
 6.4- 2-3
 WPRO-109-OG:
 6.2- 4, 7-8, 16, 18
 6.3- 10, 13, 16
 6.4- 2-3
 WPRO-110-OG:
 6.2- 5
 WPRO-111-OG:
 6.2- 5-8, 10
 WPRO-112-OG:
 6.2- 7
 WPRO-113-OG:
 6.2- 12-13, 16, 20
 6.3- 13, 16, 20, 24-25, 27, 29, 31-32
 6.4- 2, 4, 6
 WPRO-114-OG:
 6.2- 5, 11, 13, 17-18, 20
 6.3- 13, 16, 20, 24-26, 29-30, 32-33
 WPRO-115-OG:
 6.2- 18, 20
 WPRO-116-OG:
 6.2- 15-16, 18, 20
 WPRO-200-OG:
 6.3- 10
 WPRO-201-OG:
 6.3- 8, 14, 17-18, 21, 25-29, 31-33
 6.4- 3, 5-7
 WPRO-204-OG:
 6.3- 3, 6, 18, 22, 28, 30
 6.4- 7
 WPRO-205-OG:
 6.3- 1, 5, 7, 17, 21, 28, 30
 WPRO-206-OG:
 6.3- 1, 3-4, 6, 14, 21, 28, 30
 WPRO-207-OG:
 6.3- 4, 6, 8, 17-18, 22, 28, 30
 WPRO-208:
 6.3- 1
 WPRO-209-OG:
 6.3- 2, 6, 8, 25, 31
 WPRO-210-OG:
 6.2- 14
 6.3- 2, 4, 19, 22, 25, 28, 30, 32
 WPRO-213-OG:
 6.2- 2, 7, 10-11, 13, 15, 17, 19
 6.3- 11, 20, 23-24, 26, 29-32
 WPRO-214-OG:
 6.3- 12, 15
 WPRO-215-OG:
 6.2- 18, 20
 6.3- 9, 12, 15
 WPRO-216-OG:
 6.2- 15
 6.3- 25-26
 WPRO-219-OG:
 6.2- 19
 WPRO-220-OG:
 6.3- 27
 6.4- 1-2
 WPRO-221-OG:
 6.2- 13
 6.3- 13
 6.4- 2, 4
 WPRO-222-OG:
 6.3- 3, 10, 13, 25-26, 29, 32-33
 WPRO-223-OG:
 6.3- 3, 7, 13, 33
 WPRO-224-OG:
 6.3- 10, 14, 25, 27
 WPRO-225-OG:
 6.3- 10
 WPRO-226-OG:
 6.3- 3, 21, 24, 31
 WPRO-227-OG:
 6.3- 10, 25, 32
 WPRO-300-OG:
 6.4- 1, 3-4, 6

WPRO-301-OG:
 6.4- 1, 3, 5-7
 WPRO-302-OG:
 6.4- 5-6
 WPRO-303-OG:
 6.4- 8
 WPRO-304-OG:
 6.4- 2, 4
 WPRO-305-OG:
 6.4- 2-4
 WSTA-100-OG:
 6.5- 1
 WSTA-101-OG:
 6.5- 1
 WSTA-104-OG:
 6.5- 1
 WSTA-105-OG:
 6.5- 2
 WSTA-106-OG:
 6.5- 2
 X-Ray Diffraction:
 1- 5
 X-Ray Fluorescence:
 1- 7
 Y-12 Plant Industrial Lan:
 6.7- 1
 Zoning for Containment:
 3- 8

-OG:
3, 5-7
-OG:
-8
-OG:
-OG:
4
-OG:
4
-OG:
i
-OG:
1
-OG:
1
-OG:
2
-OG:
2
action:
5
presence:
7
Industrial Landfill:
1
Containment:
8

Characterizat

The Characterization section is grouped into several subsections under the Alternatives, Collection, Sampling, In-Situ Characterization, Laboratory Characterization, and Data Analysis of General, RAD, Inorganic, and Organic Contamination.

K-25 Site problem areas were grouped to reflect common characteristics in terms of Characterization needs particular to environmental restoration activities are covered under headings. For this preliminary volume, the technologies are listed only once, so that the heading "General." Technologies with potential in-situ application are covered in the in-laboratories.


Characterization

Under the Alternatives column. These subsections are: Statistics and Data
ation, and Data Assessment. Each of these was discussed under the head-

istics in terms of size, complexity, accessibility, and expected contaminants.
are covered under Soils and Groundwater, Burial Waste, and Pond Waste
once, so that technologies with several applications are covered under the
covered in the in-situ section, even though they may be more widely used in


Technology Logic

Characterization




Logic Diagram

ization



Technology Log

Characterization




Logic Diagram


Characterization

Alternatives	Technologies	Status	Science/Technology Needs	Implementation Needs
→ Sampling, Sample Prep (cont.)	Multi-Angle Drilling For Depth Profiling CHAR-64-OG	→ Demonstrated Allows collection of samples for composition depth profiling in cases where core drilling is not possible.	→ Development - Need to conduct model studies based upon site specific needs.	→ Standard drilling equipment can be tailored for specific applications. Development cost \$100K.
	→ Metallographic Sample Preparation CHAR-67-OG	→ Accepted Widely used method to prepare representative cross-sections of materials. Valuable for contaminant spatial (particularly depth) distribution determinations.	→ Needs procedure and protocol development for specific matrices and applications.	→ Development Costs: 1K-30K, depending on application.
	→ Ultrasonic Extraction CHAR-20-OG	→ Pre-Demonstration Ultrasonic extraction is a widely used and EPA approved laboratory extraction technique. The technique could be adapted to more efficient sampling of porous media surfaces.	→ Development - Need to adapt flow through extraction cell for surface sampling, test solvents, acids and bases for extraction efficiency, and validate the method.	→ Adaptation for specific geometries. Equipment: \$4-4K Development Costs: \$250K
	→ Laser Ablation CHAR-86-OG	→ Demonstration Technique for sampling solid materials by ablating the surface followed by analysis of the removed material. Currently used in ICP-MS. This technology is becoming available for field and more general laboratory use (see CHAR-SYL-01).	→ Need to develop sampling equipment, procedures and protocols for specific field and laboratory applications.	→ Development Costs: \$100K Equipment: \$200K
	→ Correlation Of Matrix Porosity with Collection Efficiency: Standardize Methodology CHAR-61-OG	→ Conceptual. These studies would allow variations in collection efficiency as a function of the porosity of the host matrix to be understood, this would allow better correlation of data sets from various structural components.	→ Model studies and field tests to determine the effect of porosity. Protocols developed to ensure uniform interpretation of contaminant concentrations.	→ Sample collection and analysis program to identify suspect sampling scenarios. Development Costs: <\$50K
	→ Laser/Flashlamp Heating v CHAR-87-OG	→ Pre-demonstration Potentially rapid method for surface and subsurface sampling for contaminants, particularly useful for robotic and sensor applications.	→ Determination of sampled region and sampling effectiveness for specific contaminant/matrix systems.	→ To be determined for specific applications. Development Costs: >\$50K
	→ Vacuum Assisted, Reverse Flow Solvent Extraction Methods CHAR-62-OG	→ Conceptual. Solvent is introduced through a drill hole into a porous host matrix and a vacuum device is used to recover solvent plus contaminant through the host matrix.	→ Laboratory studies for assessment of collection efficiency; and development of portable sampling systems.	→ Development Costs: \$400K.
	→ Sampling & Mixing Methods CHAR-81-OG	→ Demonstration Standard procedures using portable field units are needed to "mix" particulate matter quickly and effectively. Protocols for assessment of non-homogeneous wasteforms have not yet been developed.	→ Development of protocols for the quantitative evaluation of homogeneity; assessment of commercially available and the probable development of portable mixing equipment. Procedures have been developed for individual applications; these could be expanded for more general use.	→ Development Costs: \$300K for mixing; \$300K for protocols. Equipment: 15K.
	→ Microwave Digestion CHAR-19-OG	→ Accepted Effective in digesting and extracting trace elements from soils and complex matrices prior to analysis. This is an emerging technology that shows much promise in reducing the amount of waste produced in sample analysis as well as increasing the quality of the data obtained.	→ Adaptation and optimization for specific applications.	→ Capital Equipment Costs: \$22 to 50K per instrument Operating Costs: <\$25 per test

Technology Logic


Characterization






Technology Log

Characterization




Logic Diagram

erization



- Cleanup Legacy
- Prevent Future Insult
- Develop Environmental Stewardship



- Enrichment Process Buildings
- Process Support Buildings
- Cooling Towers
- Electrical and Electrical Switch Gear
- Pumping Stations
- Laboratory Facilities
- Special Development Facilities
- Administrative Facilities

General Use:
(cont.)



Refer to Volume 1, Chapter 10, for potentially applicable proposed and promulgated environmental laws, signed and pending agreements for the ORR, radiation protection standards, DOE Orders, and non-regulatory guidance. As site- and waste-specific characteristics are provided for each technology, specific regulatory requirements will be specified.

Characterization
(cont.)

Ex Situ Chemical
(Laboratory)
(cont.)




Logic Diagram

terization

Alternatives	Technologies	Status	Science/Technology Needs	Implementation Needs
➤ Ex Situ Chemical (Laboratory) (cont.)	Secondary Neutral Mass Spectrometry (SNMS) CHAR-7-OG	➔ Accepted A wide variety of post ionization schemes are currently in use to increase the ion yield. This method of solid state mass spectroscopy has improved quantitative capabilities and would allow accurate U enrichment studies to be performed.	➔ System development and model studies for calibration of enrichment measurements for small particles of U.	➔ Capital Equipment Costs: \$500K Development Costs: \$200K
	Chemical Leaching Tests CHAR-113-OG	➔ Pre-Demonstration Tests of potential leachability conducted at Fernald.	➔ Science - Need development and validation of site-specific leaching tests.	➔ Development Costs: \$200K
	Nuclear Magnetic Resonance (NMR) CHAR-11-OG CHAR-58-OG	➔ Accepted This mature technology can be applied to both liquid and solid samples (MAS) and can provide imaging information. This technology is very useful for identifying materials as well as studying materials interactions.	➔ Model studies and protocols for adaptation and application of technology.	➔ Hardware: \$200K-\$2M Development Costs: \$200K-\$500K
	X-Ray Diffraction CHAR-31-OG	➔ Accepted Provides identification of crystalline phases in solid samples. Can supply quantitative, stress/strain, and particle size information. Mature technology widely used in industry	➔ Development - Need studies of model site-specific samples if quantitative analysis required.	➔ Technology available. Development Costs: \$100K Operating Costs: >\$100/sample.
	Electron Diffraction (ED, SAED, LEED) CHAR-37-OG	➔ Accepted Mature technology. When used in conjunction with transmission electron microscopy, can provide phase identification of sub-micron particulates and impurities in host matrix. Asbestos identification. Widely used and accepted by industry.	➔ Development of procedures, quantitative models and database for site-specific scenarios..	➔ <\$200/sample Development: \$50K
	Isotopic Dilution Mass Spectroscopy (IDMS) CHAR-48-OG	➔ Accepted Mature technology. High sensitivity, particularly suited for measurements of levels of fission products (eg, Tc, I) and neutron-capture product at levels as low as 10 ⁻⁷ atoms. Accepted by industry. Technique will give necessary precision for accountability analysis.	➔ Development - Set up to rapidly measure U/Tc ratios to determine extent of Tc at various stages of the cascade equipment.	➔ Instrumentation available. Development Costs: \$100K
	Electrochemical Methods CHAR-10-OG	➔ Accepted/Development There are a wide variety of electrochemical techniques (e.g. electrogravimetry, polarography, coulometry, voltammetry) that can provide chemical and materials interaction information. These techniques could be useful in waste treatment and interaction studies as well as identifying species present in waste streams.	➔ Adaptation and protocols for model studies to be performed on complex systems.	➔ Hardware: \$50K-\$250K Development Costs: \$250K


Technology Log

Characterization




Alternatives	Technologies	Status	Science/Technology Needs	Implementation Needs
→ Ex Situ Chemical (Laboratory) (cont.)	→ Ion Chromatography (IC) CHAR-50-OG	→ Accept Able to quickly and accurately determine anions or cations in solution to ppm or ppb concentration. Accepted by EPA and industry.	→ Development - Selection and set up of most appropriate system for site-specific needs.	→ Instruments available. Development Costs: @\$200K
→ In Situ Radiological	→ Measurement Of Natural Gamma Emitters CHAR-51-OG	→ Demonstration - The ability to obtain an accurate measure of gamma emitters for determination of background levels and to monitor small changes in concentration is very important.	→ Mature technology. Adapt existing equipment, calibrate, optimize procedures and write protocols to obtain in-situ measurements.	→ Development costs \$300K
	→ Passive Neutron CHAR-104-OG	→ Accepted - Useful for all matrices for U determination. F must be present. Should be calibrated with similar matrix material. Currently used to measure uranium holdup.	→ Calibration models for expected D&D scenarios.	→ <\$25 measurement
	→ TLD Array for a Spatial Characterization CHAR-103-OG	→ Demonstration Reusable detector sheet contains 1000 pixels; detection limit is 20 alpha rays/pixel; maps contamination fields.	→ Commercially available instrumentation needs adaptation for field use.	→ Ready for pilot testing. Laser reader \$60K, reusable detector sheet \$225; Development costs \$100K.
	→ NaI Gamma Spectroscopy / CHAR-106-OG CHAR-112-OG	→ Accepted Useful for U235 and U238 detection. Can measure subsurface activity. Technology and instrumentation available.	→ Correction factors methodology needs to be published.	→ High resolution Ge detector may be needed to determine correction factors for absorption. Combination NaI and Ge detectors \$40K; development cost \$250K. Measurement cost <\$25.
	→ Proportional Counting / CHAR-108-OG	→ Accepted - Sensitive to 100dpm/cm2. Probes can be made large for wide areas, or small to fit into process piping. May be able to distinguish between U and Tc.	→ Development work to distinguish between U and Tc. Modification for vertical, overhead or specific Site geometries.	→ Development cost \$50K.
	→ Small Long-Range Alpha Detection (LRAD) Δ CHAR-65-OG	→ Demonstration - Actively detects surfaces/objects contaminated at or below release limits; measures ionized air drawn from containment regardless of shape of article. Potential on-line measurement. Demonstrated at Fernald.	→ Adaptation for Site-specific applications, optimization of methods, and development of procedures and protocols.	→ Normal implementation costs. @\$2-3K for equipment, Operating Costs @ \$20/sample Development Costs: @\$100K
	→ "Electret" Passive Surface Alpha Detection Δ CHAR-95-OG	→ Demonstration - Sensitive (100minute exposure for quantification), inexpensive devices can be used in large numbers; particularly useful for cleanup verification. Commercialized for Radon monitoring; easily adapted for surface alpha contamination. Potential for niche applications.	→ Needs equipment adaptation, evaluation and validation for niche applications. Definition of limitations in mixed radiation fields.	→ Development cost \$200K.
	→ In-Situ Passive Monitors For surface Contamination By Weak Beta Radionuclides √ Δ CHAR-102-OG	→ Pre-demonstration - Re-useable TLD-like chip small size detectors for monitoring Tc in difficult-to-access locations. Detectors can be deployed in large numbers.	→ Thorough evaluation for use in mixed surface contamination areas. Testing and evaluation of ceramic exoelectron materials to select most suitable type for Site-specific applications.	→ Commercial exoelectron reader in hand; materials testing development work \$300K. <\$25 per detector.

Technology Logic Characterization




Logic Diagram

Characterization




Technology Log

Characterization




Logic Diagram

Characterization



Technology Logic Characterization




Logic Diagram


erization


Alternatives	Technologies	Status	Science/Technology Needs	Implementation Needs
In Situ Chemical (Laboratory)	Fourier Transform Infra-Red Spectroscopy (FTIR) CHAR-8-OG	Accepted A multitude of detector and sampling devices exist to allow gas, liquid, solid, and micro analysis to be performed. This is a very mature technique with a host of applications to any ERWM program.	Database for rapid materials identification and model studies of materials interaction.	Hardware Costs: \$25K to \$500K Development Costs: <\$200K
	Long-Path FTIR CHAR-18-OG	Pre-Demonstration - Capable of monitoring large areas, real-time measurements, remote sensing. Vendor units available.	Development - Need to develop software to enhance site-specific application.	Moderate capital and software development costs.
	SAW Sensors CHAR-14-OG	Development/demonstration - Fast response time direct measurement of organic vapors; when coupled with desorption (see sampling) applicable for surface contamination. Detection limits of ppm possible; can be tailored to a specific gas or family of gases. Particularly suitable for robotic applications. Development of PCB sensors under way on-site.	Coatings to allow detection of specific gases. Desorption devices need to be optimized for surface characterization. Extension to on-line process monitoring.	Development \$300K. Device cost \$10K.
	Immunoassay (PCB) CHAR-23-OG CHAR-99-OG	Demonstrated DOE/LMDField Methods Project has demonstrated 1ppm sensitivity in soils. Commercially available test kits.	Development - Need for slight adaptation of method for samples other than soils.	Normal development and implementation costs. Capital Costs: \$100-\$200 Development Costs: \$200K
Ex Situ Chemical (Laboratory)	Synchronous Fluorescence (PAH) ✓ CHAR-101-OG	Demonstrated Method currently being implemented at Y-12 for PAH in groundwater.	Development - Methods needs validation for various matrices in order to be accepted by EPA.	Normal implementation costs. Capital Costs: \$25K Development Costs: \$100K
	Gas Chromatography - Mass Spectroscopy (GC-MS) CHAR-88-OG	Accepted EPA approved technique for organic compound identification can provide rapid identification.	Improved sampling protocols for rapid turn around analysis. Protocols for automated instrumentation.	Capital Costs: \$300K Development Costs: \$100K
	Gas Chromatography - Fourier Transform Infrared Spectroscopy (GC-FTIR) CHAR-66-OG	Demonstration Technology demonstrated to supplement GC-MS for compound identification. GC-FTIR located at Y-12 and X-10. Not yet EPA approved.	Development - Need to develop protocols for targeted analysis and evaluate optimum commercial software for site-specific applications.	Capital Equipment: \$200K Development Costs: \$300K
	Liquid Chromatography - Mass Spectrometry (LC-MS) CHAR-89-OG	Demonstration Technology demonstrated to provide unambiguous identification and quantitative measurement of compounds not amenable to GC-MS. Not yet EPA-approved.	Development - Need to develop and validate protocols for targeted analytes.	Capital Equipment: \$200K Development Costs: \$300K
	Glow Discharge Ionization Mass Spectroscopy CHAR-56-OG	Accepted On site monitoring of organic compounds in a variety of host matrices with quantitation down to the ppb level. Rugged and portable.	Instrumental development. Model studies of host interactions and interferences for quantitative analysis.	Capital Equipment: \$500K Development Costs: \$200K
	Differential Optical Absorption Spectroscopy Δ CHAR-27-OG	Accepted Best suited for long UV absorbers; fast response time, stable spectral emission, ppm to ppb detection levels.	Model studios and quantitative calibration curves for specific monitoring scenarios.	Capital Equipment: \$200K

Technology Log

Characteriz








Logic Diagram

Characterization



Decontaminat


The Decontamination section addresses concepts and approaches for removing vi the large number of combinations of contaminants and substrates, some simplification accomplished by dividing problem areas into ten different groups that had common tre transite, asbestos pipe insulation, and Munter's Fill; porous nickel and aluminum; freon sheet metal, metal equipment (exterior), and copper; nickel-lined steel (interior), steel, cylinders (materials used on the interior of process equipment, pipes, etc. and such ite

amination

; for removing various contaminants from facilities and equipment. Because of the simplification was necessary to limit the size of the diagram. This was had common treatment technologies: insulated copper wires and instruments; aluminum; freon; plastic; tile, wood, gasket material, and composite roofing; (interior), steel, Monel, copper, aluminum, steel pipe, aluminum pipe, and steel etc. and such items that contained UF_6 gas); deposit recovery; and concrete.

Technology Logic

Decontamination



**Mechanical Substrate
Surface Removal**
(fixed and transferrable
contamination)

→ **Ultrahigh-Pressure Water**
(up to 50,000 psi)
DCON-35-OG

→ **Accepted**
Technology is used by industry to decontaminate metal parts. Should work for listed contaminants and substrates. Unless a recycle system is developed, waste would be 3-5 gal water per ft² cleaned containing contaminants removed plus, perhaps, some metal substrate.

→ **Development** - To minimize waste generation, a system is needed to treat the water so that it can be recycled.

Improvement - Vacuum systems with nozzles designed to match commonly decontaminated parts are needed to minimize the spread of contamination.

→ **Prior removal and disassembly** of contaminated equipment plus an enclosed glove box and/or room that is easily decontaminated on the inside is needed in which the ultra high-pressure water (UHPW) system will be used.

Development cost: \$1.3M (Recycle system); \$200-1000K (Vacuum system for each nozzle design)

Capital cost:
UHPW system: > \$500K (with vacuum system)
Glove box: <\$50K
Work room: About \$250K
Operating cost: >\$2/ft²

→ **Shot Blasting**
DCON-36-OG

→ **Accepted**
Commercial shot blasters are used to remove rust and marine growth from ship hulls and to clean structural steel. Decontamination factors of 10-100 can be expected. Waste is about 0.1 lb spent shot/ft² decontaminated plus contaminants removed and trace amounts of eroded substrate.

→ **Improvement** - Vacuum systems with nozzles designed to match commonly decontaminated parts are needed to minimize the spread of shot and contamination.

→ **Prior removal and disassembly** of contaminated equipment plus an enclosed glove box and/or room that is easily decontaminated on the inside is needed in which the shot blaster system will be used.

Development cost: \$200-1000K (Vacuum system for each nozzle design)

Capital cost:
Shot blaster: > \$50K (with vacuum system)
Glove box: <\$50K
Work room: About \$250K
Operating cost: About \$0.40/ft²

→ **Grit Blasting**
DCON-38-OG

→ **Accepted**
Has been used for many applications in the nuclear industry. Technology is generally effective (DF=10-100). Waste would be spent grit containing abraded substrate and removed contaminants plus filter. Waste production rates depend upon substrate being decontaminated (0.005-0.1 lb/ft²)

→ **Improvement** - 1) More durable blast media are needed to minimize wastes. 2) Better vacuum systems for collecting blast media are needed to minimize spread of blast media and contamination. 3) Demonstration of specific blast media for listed contaminants and substrates is needed. 4) Process automation is needed to improve efficiency. 5) A system to separate contaminants from blast media and package the wastes is needed.

→ **Prior removal and disassembly** of contaminated equipment plus a system to separate contaminants from blast media and package the wastes is needed.


Development costs: 1) More durable blast media, 2) Better vacuum systems, 3) demonstration on listed contaminants and media: \$1-6M, 4) Process automation: \$3-4M, 5) Waste treatment and packaging: About \$4M

Capital cost: About \$500K

Operating cost: >\$2/ft²


Technology Log

Decontamination




Logic Diagram

Decontamination




Technology Logic

Decontamination




Logic Diagram

amination




Technology Log


Decontamination




Logic Diagram

Contamination









Technology Log


Decontamin






Technology Log

Decontaminat




Logic Diagram

Contamination




Technology Log


Decontaminating



Logic Diagram


Contamination






Logic Diagram


tamination




Technology Log

Decontamin









Logic Diagram


Contamination




Technology Log

Decontamin









Logic Diagram

Contamination



Technology Log

Decontaminating



→ **Mechanical Substrate
Surface Removal**

→ **Shot Blasting
DCON-36-OG**

→ **Accepted**
Commercial shot blasters are used to remove rust and marine growth from ship hulls and to clean structural steel. Waste is about 0.1 lb spent shot/ft² decontaminated, removed deposits, trace amounts of eroded substrate, filters, and HEPA filters.

→ **Improvement - Vacuum/filter systems with nozzles designed to match decontaminated parts are needed to minimize the spread of shot and contamination.**

→ **Equipment must be removed and partially disassembled. An enclosed glovebox that has adequate filters and is easily decontaminated on the inside is needed in which the shot blaster system will be used.**
Development cost: \$200-1000K (Vacuum system for each nozzle design)
Capital cost:
Shot blaster: > \$50K (with vacuum system)
Glove box: <\$50K
Operating cost: About \$1.00/ft²

→ **Scabblers/Scarifiers
DCON-37-OG**

→ **Accepted**
Mechanical scabblers are widely used. They are generally effective, but leave some hot spots. Noise would be a problem. Waste would be removed deposit, trace amounts of eroded substrate, scabbler bits, filters, and HEPA filters.

→ **Improvement - Scabbler heads, vacuum systems with nozzles designed to match decontaminated parts, and filters are needed to minimize the spread of contamination.**


→ **Equipment must be removed and partially disassembled. An enclosed glovebox with adequate filters that is easily decontaminated on the inside is needed in which the mechanical scabbler system will be used.**
Development cost: \$300-1000K (Vacuum system and scabbler head for each design required)
Capital cost:
Scabbler: > \$50K (with vacuum system)
Glove box: <\$50K
Operating cost: About \$1.00/ft² (greater than for shot blaster)

→ **Grit Blasting
DCON-38-OG**

→ **Accepted**
Has been used for many applications in the nuclear industry. Technology is generally effective. Waste would be removed deposits, trace amounts of eroded substrate, spent grit, filters, and HEPA filters.


→ **Improvement - 1) Better vacuum/filter systems for collecting blast media are needed to minimize spread of blast media and contamination. 2) A system to separate contaminants from blast media and package the wastes is needed.**

→ **Equipment must be removed and partially disassembled. An enclosed glovebox that is easily decontaminated on the inside is needed in which the grit blaster system will be used. A system to separate contaminants from blast media and package the wastes is needed as well as a system to adequately filter the exhaust air.**
Development costs: 1) better vacuum/filtration systems: \$1-6M, 2) Waste treatment and packaging: About \$4M
Capital cost: About \$500K
Operating cost: >\$2/ft²




Logic Diagram

Decontamination



Technology Log

Decontamin



Mechanical Substrate Surface Removal

Hand Grinding, Honing, Scraping
DCON-43-OG

Accepted

Hand grinding and scraping have been used successfully for small-scale decontamination at K-25. Technology is successful. Waste would be removed substrate and deposits plus contaminated HEPA filters.

None

Prior removal and disassembly of contaminated equipment and a glove box that is easily decontaminated and has HEPA filters in which the decontamination will be accomplished plus a system for processing wastes to an acceptable form are needed to use this technology.
Capital cost:
Grinder: \$150
Glove box: <\$50K
Operating cost: About \$2/ft²

Thermal Substrate Surface Removal

Plasma Torch
DCON-72-OG

Evolving Technology

Conceptual - Plasma torches exist commercially to weld and cut materials that either have a very high melting temperature or require an inert atmosphere to prevent oxidation. Plasma torches have not been used to decontaminate metal but can be expected to do so effectively by melting or vaporizing the surface layer, including the contaminants. Waste would be vaporized or melted metal, removed deposits, and contaminated filters and HEPA filters.

Development - The efficacy of a plasma torch in removing deposits should be demonstrated on a bench scale. A method for collecting the removed substrate and contaminants is needed.

Prior removal and disassembly of contaminated equipment, a glove box in which the deposit removal is accomplished, and a collection system with an adequate filter system would be needed to use this technology.
Development cost: About \$3M
Capital cost:
Plasma torch and collection system: About \$200K
Glove box: <\$50K
Operating cost: \$0.20-\$5/ft²

Laser Heating
DCON-73-OG

Pre-demonstration

Decontamination of metals by surface removal has been demonstrated on a bench scale. Technology should be effective. The waste would be filters and HEPA filters containing the removed substrate and deposits.

Development - Existing laser based photothermal methods should be demonstrated on a larger scale. Lasers with different operating parameters should be tested on a bench scale to evaluate whether more efficient laser systems exist.

Prior removal and disassembly of contaminated equipment, a glove box in which the deposit removal is accomplished, and a collection system with an adequate filter system would be needed to use this technology.
Development cost: Over \$2M
Capital cost: \$500K-\$1000K
Operating cost: About \$1/ft²


Laser Etching and Ablating
DCON-74-OG

Pre-demonstration

(evolving technology) - The conceptual basis for this technology exists, and a similar technique is used to clean optical surfaces and microelectronics. Technique may be slow to remove large deposits. Wastes would be removed deposit, traces of removed substrate, and filters and HEPA filters from the filtration system.


Development: Existing lasers, optics, and vacuum and filtration systems need integration into a system; then, this system should be demonstrated.

Prior removal and disassembly of contaminated equipment, a glove box in which the deposit removal is accomplished, and a collection system with an adequate filter system would be needed to use this technology.
Development cost: Over \$2M
Capital cost: \$500K-\$1000K
Operating cost: About \$1/ft²




Logic Diagram


amination





Technology Log

Decontamination










Technology Log L

Decontamin



Mechanical Substrate Surface Removal
(fixed and transferable contamination)

Ultra High-Pressure Water
DCON-35-OG

Accepted
Technology has been used by industry.

Development- To minimize waste generation, a system is needed to treat the water so that it can be recycled.
Improvement: Automation

Normal implementation needs.
Development Cost: \$1300K
Capital cost: ~\$500K
Operating cost: ~\$1/ft²

Shot Blasting (using iron shot)
DCON-36-OG

Accepted
Commercial iron shot blasters are in use at the K-25 site. They are generally effective but leave some hot spots.

Improvement- Automation

A collection system with adequate filtration.
Development cost: None
Capital cost: ~\$50K
Operating cost: \$0.10-\$1/ft²

Grit Blasting (using sand, glass beads, metallic beads, etc.)
DCON-38-OG

Accepted
Has been used successfully for many applications in the nuclear industry. Technology is generally effective. Waste would be spent grit, abraded substrate, and removed contaminants in filters and HEPA filters.

Improvement- automation, more durable blast media. Better vacuum system demonstration.

A collection system with adequate filtration.
Development cost ~\$4-10M
Capital cost: ~\$500K
Operating cost: <\$2/ft²

Centrifuge Cryogenic CO₂ Blasting
DCON-39-OG

Predemonstration
Centrifuge pellet acceleration has been demonstrated in the DOE fusion energy program. Technology is likely successful with essentially infinite decontamination factors. Waste would be filters and HEPA filters filled with removed contaminants and some substrate.

Development - Demonstration of mobile system with high-velocity pellets delivered at a sufficient rate and adequate collection of removed contaminants.

A collection system with adequate filtration plus oxygen-depletion precautions.
Development cost: ~\$3.4M
Capital cost: ~\$200K
Operating cost: \$0.07 - \$0.75/ft² (200 - 2000 ft²/hr)

Ice Blasting
DCON-40-OG

Accepted by industry
Efficacy of commercial system for this application needs demonstration. Waste would be about 14-18 gallons/hour waste water containing removed contaminants.

Development- automation/robotics, especially for walls, corners, etc.

Normal implementation needs.
Capital cost: \$100K-\$1M
Evaporator for Waste water Treatment: ~\$60K
Operating cost: <\$1/hr

Supercritical CO₂
DCON-41-OG


Predemonstration
Likely to be effective with nearly infinite decontamination factors. Waste would be removed contaminants and some substrate contained in a cyclone and a HEPA filter.

Development - Investigate the effect of operating parameters on removal rates and removal and collection efficiencies for contaminants. Demonstrate efficacy for contaminants of interest

A collection system with adequate filtration plus oxygen depletion precautions.
Development cost: \$1-4M
Capital cost: \$800K - \$1300K
Operating cost: ~\$2/ft²


Technology Logic

Decontamination




Logic Diagram


tamination



Technology Log

Decontaminating





- Cleanup Legacy
- Prevent Future Insult
- Develop Environmental Stewardship

EM Problem

Decommissioning (D&D)

Soils, Groundwater and Surface Water (RA)

Waste Management (WM)

Enrichment Process Building →

Process Support Building

Electrical and Electrical Switch Gear

Pumping Stations

Laboratory Facilities

Special Development Facilities

Administrative Facilities

Cooling Towers

Sheet Metal
Metal Exterior Surfaces
Oil, PCBs, U, Tc, Actinides

Structural Steel
U, Oil, Tc, PCBs, Actinides

Metal Equipment Exterior
U, Oil, Tc, PCBs, Actinides

Copper
Oil

Refer to Volume 1, Chapter 10, for potentially applicable proposed and promulgated environmental laws, signed and pending agreements for the ORR, radiation protection standards, DOE Orders, and non-regulatory guidance. As site- and waste-specific characteristics are provided for each technology, specific regulatory requirements will be specified.

→ Decontamination

→ Surface Cleaning (transferrable contamination) (cont.)


Logic Diagram

Contamination

Alternatives	Technologies	Status	Science/ Technology Needs	Implementation Needs
Surface Cleaning (transferrable contamination) (cont.)	Compressed Air Cryogenic CO ₂ DCON-51-OG	Demonstration This technology is commercially available. It has been used at nuclear reactor sites to decontaminate hand tools and some equipment. The efficacy of this technology for removing the listed contaminants from the listed substrates has not been demonstrated. Wastes would be HEPA filters filled with the removed contaminants.	Development - Demonstration of the efficacy of this technology for the listed contaminants and substrates	Design and construction of a vacuum waste-handling system with HEPA filters to handle the vaporized CO ₂ containing the removed contaminants are needed to use this technology. A vacuum collection system with well designed nozzles might permit in situ decontamination of assembled equipment and structures. Development costs: \$750-\$3000K Capital cost: CO ₂ system: About \$200K Operating cost: \$0.50-\$10/ft ²
	Superheated Water DCON-53-OG	Accepted Technology is available and has been used by industry. Technology should be effective except for fixed insoluble contamination. Waste will be 0.4 to 2.0 gpm wastewater containing removed contaminants.	Development - To minimize waste generation, a water treatment system is needed for decontamination of the wastewater so that the water can be reused. Improvement - Remote operation will necessitate the adaptation of the superheated and vacuum collection systems to robotic system control.	Normal implementation needs. Development cost: Water treatment system: about \$1.2M Remote operation: \$3-4M Capital cost: About \$175K (about \$250K with remote operation) Operating cost: \$0.03-\$1.00/ft ²
	Hot Water DCON-54-OG	Accepted Flushing with hot water is often used following scrubbing. The technique is not effective on fixed insoluble contamination. The waste generated is the contaminated water from the flushing operation.	Improvement - To minimize waste generation, a water treatment system is needed for decontamination of the wastewater so that the water can be recycled and reused in the hot water cleaning operation.	A water treatment system is needed to minimize liquid wastes from this technology. Development cost: About \$1.2M Capital cost: <\$5K Operating cost: <\$1/ft ²
	Steam DCON-55-OG	Accepted The technique has proven useful, especially on complex shapes and large surfaces. Technology should be effective except for fixed insoluble contamination. Waste will be 0.4 to 2.0 gpm wastewater containing removed contaminants.	Development - To minimize waste generation, a water treatment system is needed for decontamination of the wastewater so that the water can be reused. Improvement - Remote operation will necessitate the adaptation of the steam and vacuum collection systems to robotic system control.	Normal implementation needs. Development cost: Water treatment system: about \$1.2M Remote operation: \$3-4M Capital cost: \$50K-\$75K (about \$250K with remote operation) Operating cost: \$0.03-\$1.00/ft ²

Technology Log

Decontamin



→ Surface Cleaning
(transferrable
contamination)
(cont'd)

→ Brushing
DCON-56&57-OG

→ **Accepted**
Manual brushing has been
used to remove loose conta-
mination for years.

Demonstration - Remote
power brushing was used to
clean the interior of plutoni-
um-contaminated pipe at
Rocky Flats to shiny metal.

Since most of the listed cont-
aminants are not expected to
be in loose form, brushing is
not expected to be effective.
Wastes consist of HEPA fil-
ters on the vacuum cleaner
used to pick up the removed
contaminants.

→ Development - A test to
demonstrate that this tech-
nique will work is needed
before a large capital invest-
ment is made for a power
brushing system at K-25.

→ Normal implementation
needs.
Manual brushing
Capital costs: <\$10K
Operating costs: >\$1/ft²
Power system
Development costs: \$200K-
\$1000K
Capital costs: About \$50K
(\$250K with remote opera-
tion)
Operating cost: >>\$10/ft²

→ Hot Air
DCON-59-OG

→ **Evolving Technology**
Conceptual - Air stripping
technology is well known for
removing volatiles from liq-
uids, but there is no known
use of this technology to
decontaminate metals. The
technology may be effective
in removing oil, PCBs, and
perhaps Tc, but probably
none of the other listed cont-
aminants from the listed sub-
strates. Wastes would be
spent chemicals from gas
treatment system containing
any removed contaminants.

→ Development - Effective
removal of the listed contam-
inants from metals should be
demonstrated; an effective
off-gas treatment system
needs to be designed and
tested.

→ An off-gas collection and
treatment system is needed
for this technology.
Development costs: \$1-5M
Capital cost: About \$200K
Operating cost: \$2-20/ft²

→ Dry Heat (Roasting)
DCON-60-OG

→ **Demonstration**
Although dry heat (roasting)
is an accepted industrial
process, its efficacy for
removing oil and PCBs from
the listed substrates needs
to be demonstrated.
Technology has a moderate
probability of success for oil
and PCBs, some probability
of success for Tc, and little
chance of success for the
other contaminants. Waste
would be removed oils and
PCBs (and, possibly Tc).
(Oils might be combusted.)

→ Development -
Demonstration of the effica-
cy of the process; develop-
ment and demonstration of
an off-gas treatment system.

→ An off-gas collection and
treatment system would be
needed to use this technol-
ogy.
Development cost: \$1-4M
Capital cost: About \$250K
with collection and treatment
system
Operating cost: \$2-20/ft²

→ Solvent washing
DCON-61&62-OG

→ **Evolving Technology**
Conceptual - Solvent
degreasing was used suc-
cessfully at K-25, but its use
was stopped to avoid expos-
ing workers and the environ-
ment to the hazardous sol-
vents. The effectiveness of
less hazardous solvents
would have to be demon-
strated. Wastes would be the
solvents containing any
removed contaminants.

→ Development - Solvents that
are less damaging to the
environment need to be
identified and their effective-
ness demonstrated.

→ Requires removal and dis-
assembly of contaminated
equipment and size reduc-
tion to roughly 2 tons/piece
for processing. Spent sol-
vents would have to be
"burned" at the TSCA inci-
nerator.

Development costs: \$1-4.5M
Capital cost: About \$400K
Operating cost: About
\$0.01/lb

- Cleanup Legacy
- Prevent Future Insult
- Develop Environmental Stewardship

EM Problem

Decommissioning (D&D)

Soils, Groundwater and Surface Water (RA)

Waste Management (WM)

Enrichment Process Building

Process Support Building

Electrical and Electrical Switch Gear

Pumping Stations

Laboratory Facilities

Special Development Facilities

Administrative Facilities

Cooling Towers

Sheet Metal
Metal Exterior Surfaces
Oil, PCBs, U, Tc, Actinides

Structural Steel
U, Oil, Tc, PCBs, Actinides

Metal Equipment Exterior
U, Oil, Tc, PCBs, Actinides

Copper
Oil

Refer to Volume 1, Chapter 10, for potentially applicable proposed and promulgated environmental laws, signed and pending agreements for the ORR, radiation protection standards, DOE Orders, and non-regulatory guidance. As site- and waste-specific characteristics are provided for each technology, specific regulatory requirements will be specified.


Decontamination

Surface Clean (transferrable contamination) (cont'd)

Metal Refining (fixed and trans contamination)


Logic Diagram

Decontamination




Technology Log

Decontamin




Logic Diagram

Decontamination




Technology Logi

Decontaminati




Logic Diagram

Decontamination




Technology Log

Decontamin




Logic Diagram

Decontamination




Technology Logic

Decontamination




Logic Diagram

Decontamination



Technology Log

Decontamin




Logic Diagram

tamination

Alternatives	Technologies	Status	Science/ Technology Needs	Implementation Needs
→ Mechanical Substrate Surface Removal	→ Ultra High-Pressure Water DCON-35-OG	→ Accepted Technology has been used by industry. Should work on concrete at GDPs. Unless a recycle system is developed, waste would be 3 - 5 gal water per ft ² concrete cleaned containing ~0.01 ft ³ concrete residue plus the contaminants removed.	→ Development- To minimize waste generation, a system is needed to treat the water so that it can be recycled. Improvement: Automation	→ Normal implementation needs. Development Cost: \$1300K Capital cost: ~\$500K Operating cost: ~\$1+/ft ²
	→ Shot Blasting (using iron shot) DCON-36-OG	→ Accepted Commercial iron shot blasters are in use at the K-25 site. They are generally effective but leave some hot spots. Waste is ~0.01 ft ³ removed concrete (1/16" cut) containing removed contaminants plus 0.05lb spent shot per ft ² of concrete decontaminated.	→ Improvement- Automation	→ Normal Implementation needs Development cost: None Capital cost: ~\$50K Operating cost: ~\$0.03/ft ²
	→ Mechanical Scabblers DCON-37-OG	→ Accepted Mechanical scabblers are used for concrete decontamination at ORGDP and elsewhere. They are generally effective, but leave some hot spots. Waste is ~0.01 ft ³ removed concrete (1/16" cut) containing removed contaminants per ft ² of concrete decontaminated	→ Improve ment - Automation	→ Normal implementation needs Development cost: None Capital cost: ~\$500K Operating cost: < \$1/ft ² (More than shot blasting)
	→ Grit Blasting (using sand, glass beads, metallic beads, etc.) DCON-38-OG	→ Accepted Has been used successfully for many applications in the nuclear industry. Technology is generally effective. Waste is ~0.01 ft ³ removed concrete (1/16" cut) containing removed contaminants per ft ² of concrete decontaminated plus spent grit.	→ Improvement- automation, especially for walls and ceilings.	→ Normal implementation needs Development cost: None Capital cost: ~\$500K Operating cost: \$1/ft ²
	→ Centrifuge Cryogenic CO ₂ Blasting DCON-39-OG	→ Predemonstration Centrifuge pellet acceleration has been demonstrated in the DOE fusion energy program. Technology is likely successful with essentially infinite decontamination factors. Waste would be filters and HEPA filters filled with removed concrete dust and contaminants.	→ Development-Demonstration of mobile system with high-velocity pellets delivered at a sufficient rate and adequate collection of removed contaminants.	→ Normal implementation needs plus oxygen-depletion precautions. Development cost: ~\$3.4M Capital cost: ~\$200K Operating cost: \$0.07 - \$0.75/ft ² (200 - 2000 ft ² /hr)
	→ Ice Blasting DCON-40-OG	→ Accepted by industry Efficacy of commercial system for this application needs demonstration at K-25. Waste would be about 14 to 18 gallons per hour waste water containing removed contaminants.	→ Development-automation/robotics, especially for walls, corners, etc.	→ Normal implementation needs. Capital cost: \$100K-\$1M Operating cost: <\$1/ft ²


Technology Log

Decontamination




Logic Diagram

Decontamination




Technology Log

Decontamin



Logic Diagram


Decontamination



EM Goals	K-25 Site Problem	Problem Area/Constituents	Reference Requirements	Subelements	Alternatives
<ul style="list-style-type: none"> Cleanup Legacy Prevent Future Insult Develop Environmental Stewardship 	Enrichment Process Building Process Support Building Pumping Stations Laboratory Facilities Special Development Facilities Administrative Facilities Cooling Towers	Concrete U Tc Actinides Chromate Oil PCB	Refer to Volume 1, Chapter 10, for potentially applicable proposed and promulgated environmental laws, signed and pending agreements for the ORR, radiation protection standards, DOE Orders, and non-regulatory guidance. As site- and waste-specific characteristics are provided for each technology, specific regulatory requirements will be specified.	Decontamination	Surface Cleanup
EM Problem Decommissioning (D&D) Soils, Groundwater and Surface Water (RA) Waste Management (WM)					


Logic Diagram

Contamination




Technology Log

Decontamin




Logic Diagram

amination




Technology Logic

Decontamination




Logic Diagram

Contamination




Technology Log

Decontamin




Logic Diagram

Decontamination




Technology Logic

Decontamination




Logic Diagram

Decontamination




Technology Log

Decontaminating




Logic Diagram

Contamination




Technology Log

Decontamin




Logic Diagram

mination




Technology Look-Forward Decontamination



Logic Diagram

Examination



- Cleanup Legacy
- Prevent Future Insult
- Develop Environmental Stewardship

EM Problem

Decommissioning (D&D)

Soils, Groundwater and Surface Water (RA)

Waste Management (WM)

Enrichment Process Building
Process Support Building
Electrical and Electrical Switch Gear
Pumping Stations
Laboratory Facilities
Special Development Facilities
Administrative Facilities

→ Insulated Copper Wiring
U
Tc

→ Instruments
U, Tc, PCBs

Refer to Volume 1, Chapter 10, for potentially applicable proposed and promulgated environmental laws, signed and pending agreements for the ORR, radiation protection standards, DOE Orders, and non-regulatory guidance. As site- and waste-specific characteristics are provided for each technology, specific regulatory requirements will be specified.

→ Decontamination

→ Mechanical Surface Removal (cont.)


→ Thermal Surface Removal

→ Surface Cleaning

→ Chemical Surface Cleaning


Logic Diagram

mination




Technology Log

Decontamin




Logic Diagram

Decontamination




Technology Logic

Decontamination




Logic Diagram

Decontamination




Technology Log

Decontamin




Logic Diagram

ntamination




Technology Logic

Decontamination




Logic Diagram


Contamination




Technology Log

Decontamin









Logic Diagram

Decontamination




Technology Log

Decontamin




Logic Diagram

mination



Technology Logic

Decontamination



Logic Diagram

Contamination

Alternatives	Technologies	Status	Science/ Technology Needs	Implementation Needs
<p>→ Bulk Decontamination Methods</p> <p>→ Incineration DCON-2-OG</p>		<p>→ Accepted</p> <p>Incineration is being used at K-25.</p> <p>A new incinerator would be needed because the existing incinerator cannot accept waste with more than 5 ppm total uranium and enrichments higher than one percent ²³⁵U.</p> <p>Efficacy - The K-1435 incinerator gives 99.99 to 99.999% destruction and removal efficiency when burning toxic organics.</p> <p>Waste generated - This will depend on the design of the incinerator and the ash content of the waste being burned. During a test, the K1435 incinerator generated 1.1 gallons of wastewater and 27 pounds of ash per 100 pounds of waste fed.</p>	<p>→ None</p>	<p>→ A new incinerator would be needed to burn wastes contaminated with enriched uranium.</p> <p>The present incinerator requires the services of about 30 maintenance workers (maintenance mechanics, electricians, pipe fitters, welders, and instrument mechanics), their supervisors, 34 chemical operators, their supervisors, and 7 engineers.</p> <p>About 8-10 years is required for writing an environmental impact statement, holding public hearings, and obtaining the necessary permits - TSCA permit, RCRA permit, NESHAP permit, and Clean Air Act permits.</p> <p>Cost: capital cost \$26 million (1987 dollars) Operation cost \$10/lb (1992 dollars)</p>

Dismantle

The Dismantlement section is written to address the K-25 Site problems specifically of equipment materials, major dismantlement (removal of equipment), disassembly of equipment. The approach is the assumption that dismantlement will not, in general, depend upon the type of protection are provided. Each section will explain the relationship of the subject to the overall effort to follow a sequence similar to the current ongoing D&D efforts elsewhere.

There are some basic assumptions for dismantlement including: (1) equipment materials remaining, or vestigial, contamination will have been located and characterized. The dismantlement will be sorted materials in forms suitable for disposal as recyclable scrap or other use. A list of materials will be desirable and/or required.


dismantlement

oms specific to dismantlement: massive concrete, structural steel, asbestos
i equipment, and the need for other "enabling technologies." Basic to this
end upon the type of contamination as long as containment and worker pro-
ject to the dismantlement problem list. Dismantlement has been assumed
re.

) equipment exteriors will have been decontaminated as much as practical,
characterized before dismantlement is initiated, (3) the products of dismantle-
scrap or waste or for disposition to complete decontamination, and (4) recy-


Technology Log

Dismantlem




Logic Diagram

ntlement




Technology Log

Dismantlement




Logic Diagram


Demolition



Technology Lo


Dismantle





Technology Loans

Dismantled and



Cutting
(cont.)

Plasma Arc cutting.
DISM-36-OG

Demonstration

Plasma ARC cutting is an accepted technology in industry and needs no further development.
1. Plasma ARC cutting are usually mobile and thus, can be transported to the job site.
2. Cutting can be performed on equipment in-place.
3. The system is relatively inexpensive.

Disadvantages of the system are:

1. Airborne contamination will be generated that will settle on equipment below the cutting site.
2. Uranium contamination may be alloyed with the structural members being removed thus making decontaminating significantly more difficult.

Need for making process continuous and computer assisted have been cited.

HEPA filtered exhaust system and a contained area for use when cutting contaminated material are needed.

Arc Saw Cutting
DISM-37-OG

Accepted

Current arc method for cutting conducting work pieces. Advantage of fast cutting. Disadvantages of not usable for all materials and thick cuts may require repeated passes.

None

Ventilation required if not operated under water. Blade requires water cooling.

Oxygen Cutting
DISM-38-OG

Accepted

Well understood usable approach but has some material limitations and can be labor intensive.

N/A

Exhaust ventilation required.

Plasma Arc Saw - this new technological development allows thermal cutting of steel with wall thickness up to 300 mm tubes, bank of tubes and geometric complicated components. Also, this technology can be used under water up to a depth of 20 meters. With a normal plasma torch it is not possible or at least extremely difficult.
DISM-40-OG

Demonstration

The Plasma Arc Saw technology enables thermal cutting of steel plates/walls independent of its thickness in a water depth up to 20 meters. This technology was demonstrated in cutting plates up to a thickness of 300 mm. The maximal permissible metallic wall thickness to be cut depends only on the diameter of the saw (plasma-arc) blade. The emission of dust and aerosol during the process, only depends on the melted material. This process is controlled by computers.

For large steel wall-thickness (>100 mm - requires the development of the large saw and re-runs in the process.

Requires transfer from development stages (prototype - 1990) to broad industrial application. Technology is available in commercial basis.

Thermal arc-waterjet - with this thermal arc waterjet cutting device it is possible to cut steels up to a wall thickness of 100 mm underwater up to 20 meters. The cutting process is based in an electric arc between the wire electrode and the metal sheet. Thus melting the metal in the work piece. The waterjet around the wire is used to "wash-a-way" the melted material from the cutting kerf. The wire is consumed because of the high current. The wire has to be fed so that the process can work continuously.
DISM-41-OG

Demonstrated


Demonstrated technology of cut metallic parts/walls up to 100 mm thick and up to 20 meters underwater. This thermal arc-waterjet cuts are in general, directed by computer numeric controller. With additional tooling support, cutting in several axis of operations, will be possible. Hole piercing up to a wall thickness of 30 mm could be done also. Cutting in vertical and horizontal motion. Pipes bank of pipes and geometrical complicated components, is possible.

No additional basic development necessary.

Required possible pre-runs to accommodate the arc waterjet cutter to possible room/space shortages in the working area. In general, no major changes on the cutter device is needed. Commercially available technology.


Technology Log

Dismantleme




Logic Diagram

Contamination



Dismantled ma



Stripping

Vacuum System - the vacuum system is self-contained and mounted on a towable trailer. The system includes a hopper, bagging port, HEPA filter. Self-powered vacuum system, and large diameter suction hose is routed to the asbestos removal area and transports the asbestos to the hopper to the removal point that can be up to 1000 ft away.
DISM-46-OG

Accepted

The technology is currently available and is in the use at the ENERGY SYSTEMS Y-12 Plant Site in Oak Ridge, TN. This system would save approximately 250% in the cost of materials and labor over the conventional removal and glovebag operation. An example of cost saving is an area requiring 11 laborers and 4000 bags using the conventional method would require 4 laborers and 1500 bags using the proposed automated method.

None required. However, this could be integrated with alternative highly automated systems in which case it would require additional engineering design support.

Operator training required on the system set-up and operation.

CO₂ Blasting - High Pressure CO₂ blasting is ultra high pressure CO₂ that is forced through a small diameter nozzle that creates a spray that cuts away the surface of material. The contaminated surface removed will be handled as waste. The remaining pipe can then be cut up by other methods and recycled, reused, or disposed of locally. The technology is currently available but has not been demonstrated at the ENERGY SYSTEMS Oak Ridge K-25 Plant.
DISM-47-OG

Demonstration

DOE Sponsored development; programmable robotic manipulators have been developed; high maintenance items: nozzles, hoses, and pumps. CO₂ blasting has been demonstrated but not at the K-25 plant site. By removing the contaminated surfaces which will be bagged and disposed of, the remainder of the decontaminated pipe can be recycled or reused. This will save \$17.00 cu-ft for disposal. Demonstrations for removing need to be completed before cost-payback can be evaluated. The recovery system would be well suited for contaminated piping.

Vacuum recovery system linked to robot controlled CO₂ blaster needs to be demonstrated. The development of this equipment; manipulators for tracking pipe during removal, remote operated robotic manipulators and an integrated vacuum system for demonstration would cost \$3.5M. The demonstration cost includes personnel protection, clothing and container storage but not transportation and burial charges.

Need to view videos available from other nuclear facilities and possible visit sites and evaluate recovery systems without on-site demonstration. Determine what robotics have been developed with in-house seminar from vendors on latest and future technology. Robotic manipulators with recovery system needs to be able to move around on floor, up and around concrete columns, and overhead (the underside of the floor above). Methods of addressing removal of asbestos from valves in piping. Piping elbows, and piping very close to walls will have to be made.

Glassification - Glassification is accomplished by taking a predetermined size of material and encasing it inside of glass. The size of the refuse can be linked to a machine that is capable of reducing larger pieces of asbestos refuse so that it can be run thru the glassification process. After glassification the fibers of the asbestos would be encased and could virtually eliminate air-borne particles of asbestos during shipping.
DISM-48-OG

Demonstration

Technology currently available however, it has not been tested at the K-25 plant site.

Need feasibility and design engineering to interface a confined environment machine equipped with a vacuum recovery system to process large pieces of asbestos into workable configurations. A study will need to be done to determine if this would create any new, unrecognized waste control or disposal problems. The development of this equipment; cutter, shredder or grinder, for demonstration would cost \$3.5M.

Need to view videos available from other nuclear facilities and possibly visit sites and evaluate recovery systems without on-site demonstration. Determine what robotics have been developed with in-house seminar from vendors on latest and future technology.

Cutting

Laser Cutting - Advanced laser for cutting of asbestos materials - laser cutting is accomplished with a laser beam which thermally sears thru the asbestos and cuts it into pieces easily handled for disposal. This method would be used to cut the transite panels from around the diffusion equipment. Laser manipulator could include either grippers or suction cups to safely remove and stack pieces during and after they have been cut.
DISM-49-OG

Pre-demonstration


DOE sponsored development; programmable robotic manipulators have been developed. Laser cutting of asbestos has had laboratory feasibility demonstration. Preliminary results indicate that cutting of material results in essentially no dispersal of fibers and leaves the asbestos cut interface cauterized. Thus helping seal the surface and prevent dispersal of fibers during handling. ND:YAG-Type lasers should have sufficient power and can be coupled with a fiber-optic delivery system for ease of adapting to automated systems and for improved safety.

Need confirmation of negligible asbestos dispersal and cut cauterization. Beam containment, laser safety, optics protection from flaming, etc., are issues to be addressed during development. The key issue is to substantiate that fusion of fibers occurs and does not create any new. Unrecognized waste control or disposal problems. The development of this equipment; manipulator track for laser; and grippers or holding devices for cut material for demonstration would cost \$3.5M.

Need to view videos available from other nuclear facilities and possibly visit sites and evaluate recovery systems without on-site demonstration. Determine what robotics have been developed with in-house seminars from vendors on latest and future technology. Robotic manipulators with recovery system needs to be able to move around on floor, up and around concrete columns, and overhead (the underside of the floor above).


Technology Log

Dismantlement




Logic Diagram

Demantlement




Technology Loans

Dismantled into




Logic Diagram

Dismantlement




L
an




Logic Diagram

Decontamination



Technology Lo Dismantle



→ Cutting, Advanced

High Pressure Abrasive Water Jet Cutting of Steel. Abrasive water/jet cutting, with or without abrasives is ultra high pressure water that is forced through a small diameter nozzle that creates a stream that cuts through metal. The contaminated parent material that's removed will be separated and handled as nuclear waste with the contaminated abrasives and water to be recycled. The blow through will have to be contained by shrouds attached to a high efficiency vacuum system with any other overspray contained in a pool. The shrouds will have to be designed for specific application with the containment pools being portable. DISM-59-OG

Demonstration
Abrasive waterjet cutting development was DOE sponsored. Programmable robotic manipulators have been developed. Water and abrasives can be recycled with 95% spoils recoverable. Any recyclable material accumulated will save \$20.00/cu-ft on disposal.

Abrasive waterjet cutting technology exists but high efficiency vacuum recovery and mobile containment system will need to be further developed with the shrouds, etc./designed for a specific application for a demo. A state of the art demo would cost \$3.5 M not including transportation or burial charges.

→ Develop state of the art system for demo on specific equipment. Develop market for massive amounts of recyclable steel, copper, etc.

High Pressure Water Jet: Previously used to disassemble converters in the late 1970's and early 1980's. Capabilities already exist. DISM-60-OG

Accepted
High pressure water jet fully developed. Some equipment may still be available at the site.

→ None

→ Modifications may exist for current regulatory concerns. Schematic layout and representation need to be addressed.

With Thermal Arc Water Jet Cutting it is possible to cut steels up to a wall thickness of 100 mm. The cutting process is based on an electric arc between the wire electrode and the metal sheet, thus melting the metal in the work piece. The waterjet around the wire is used to "wash-away" the melted material from the cutting kerf. The wire is consumed because of the high current. The wire has to be fed so that the process can work continuously. DISM-61-OG

Demonstration
Technology cuts metallic parts/walls up to 100 mm thick and up to 20 meters underwater. This thermal arc waterjet cuts are, in general, directed by computer numeric controller. With additional tooling support, cutting in several axes of operations will be possible. Hole piercing up to a wall thickness of 30 mm could be done also. With cutting in vertical and horizontal motion, pipes, banks of pipes, and geometrical complicated components cutting is possible.

→ No additional basic development necessary.

→ Required possible pre-runs to accommodate the arc waterjet cutter to possible room/space shortages in the working area. In general, no major changes on the cutter device are needed. Commercially available technology, at least in Germany.

Plasma Arc Saw. This new technological development allows thermal cutting of steel with wall thickness up to 300 mm, tubes, bank of tubes and geometric complicated components. Also, this technology can be used under water up to a depth of 20 meters. With a normal plasma torch it is not possible or at least extremely difficult. DISM-62-OG


The plasma arc saw technology enables thermal cutting of steel plates/walls independent of thickness in a water depth up to 20 meters. This technology was demonstrated in cutting plates up to a thickness of 300mm. The maximal permissible metallic wall thickness depends only on the diameter of the saw plasma-arc blade.

→ Large steel wall thickness (>100mm) requires the development of the large saw and re-runs in the process.

→ Requires transfer from development stages to broad industrial application. Technology is available in commercial basis.


Technology Logic

Dismantlement




Logic Diagram

Dismantlement




Technology Lo Dismantle




Logic Diagram

Contamination




Dismantler




Logic Diagram

Dismantlement




Technology Loss

Dismantler




Logic Diagram

Antlement




Technology Logi

Dismantlement




Logic Diagram

ntlement




Technology Lo

Dismantler



Logic Diagram

Dismantlement



Remedial


Remediation involves the removal of radioactive or toxic contaminants from polymer grouting methods to retain the contaminants and prevent the spread of were categorized as physical or chemical. A number of chemical methods were

ial Action

ts from soils, burial grounds, and groundwater, or of "fixation" by cement or
read of them. Methods for removal of contaminants from soils and solids
ds were identified for removing contaminants from groundwater.


Technology Logic

Remedial Action





Logic Diagram

ial Action




Technology La Remedial .






Technology Log

Remedial Action




Logic Diagram

Radial Action




Technology Log L

Remedial A




Logic Diagram

Radial Action




Technology Logic

Remedial Action




Logic Diagram

al Action




Technology Log

Remedial A



Logic Diagram


ial Action



[illegible]


Logic Diagram

dial Action




Technology Log

Remedial A




Logic Diagram

ial Action




Technology Log

Remedial Action




Logic Diagram

al Action




Technology Log

Remedial A




Logic Diagram

Medial Action




Technology Logic

Remedial Action




Logic Diagram

Radial Action




Technology Log

Remedial A




Logic Diagram

Final Action




Technology Logic

Remedial Action




Logic Diagram

ial Action




Technology Log

Remedial A




Logic Diagram

Medial Action




Technology Logic

Remedial Action




Logic Diagram

ial Action




Technology Log

Remedial A.



Logic Diagram

ial Action



Robotics/ Autor

The identification of the technologies required to use robotics/ automation in the d 25 was based upon the premise that the primary purpose of these technologies is to ization, decontamination, and dismantlement. Hence, in this section of the diagram t ing activities and no attempt to differentiate between activities was made. For exampl be equally applicable to deploy dismantlement tools.

The robotics/ automation technologies were grouped into three main categories: (groups identified under each of the categories. Technologies were selected for this s economy in the deployment of tools and sensors, adaptability of automated equipme, elimination of clothing exchange requirements, and reliability and efficiency in handlin


/ Automation

mation in the decommissioning, remedial action, and waste management at K-
nologies is to provide support for other necessary activities such as character-
f the diagram the problem areas are identified as these "other" decommission-
de. For example a robotic platform used to deploy a sensor was assumed to

n categories: (1) Mechanical, (2) Control, and (3) Sensors; with various sub-
ected for this section on the basis of the following considerations: speed and
iated equipment to repetitive tasks, ability to minimize waste by reduction or
ency in handling redundant tasks.


Technology Logic

Robotics/Automation




Logic Diagram

Automation




Technology Log

Robotics/Auto




Logic Diagram

Automation




Technology Logic I

Robotics/Automation Te




Logic Diagram


Automation Team



Technology Log


Robotics/Auto






Technology Logi

Robotics/Autom



Logic Diagram

s/Automation



Waste Mana

The Waste Management (WM) section of the TLD focuses on addressing the issues related to the waste management activities of the K-25 Site. The WM wiring diagrams are to enumerate and evaluate the likely WM activities from most effective to least effective in managing wastes. The WM wiring diagrams they relate to the K-25 Site D&D and RA activities: Waste Retrieval, Waste Processing, Waste Transportation, Waste Disposal, and Waste Minimization.

It should be noted that Waste Stabilization, as used in the K-25 Site Technology, is for residual solid wastes and does not include pretreatment of the wastes to stabilize them.


Management

essing the technologies for processing the waste streams likely to be generat-
medial action (RA), and current WM operations at the K-25 Site. The objec-
ely WM options and to rank these options in three broad categories ranging
ring diagrams were developed to address the following "EM Problem" areas as
aste Processing, Waste Stabilization, Waste Packaging, Handling, &

e Technology Logic Diagram, consists of processes for the final treatment of
to stabilize them before WM operations.


Technology Logic

Waste Management




Logic Diagram

Management




Technology Log

Waste Manag




Logic Diagram

Management




Technology Log

Waste Manag




Logic Diagram


Management



Technology Logic


Waste Management








Technology Log

Waste Manag









Logic Diagram

Management



Technology Log

Waste Manag



Chemical Treatment

Solvent Extraction
WPRO-111-OG

Demonstration.

Continuous solvent extraction in counter-current contactors (e.g., centrifugal contactors) is demonstrated technology for the separation of heavy metals or organics from aqueous or organic solutions. Centrifugal contactor based processes for the separation and recovery of radionuclides has been technology at DOE nuclear processing sites for over 25 years. The technology can be applied to treat and recover a wide range of contaminant concentrations. The advantages of the centrifugal contactor based extraction process are its relatively small size, small hold-up volume, and rapid start-up characteristics. This technology when used with other waste treatment processes would enhance the overall waste treatment strategy. However, the use of the technology for the treatment of solid wastes requires additional RD&D.

Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment.

The RD&D effort is estimated to require \$ 1-2.5 million. The payback could be significant.

Gamma-Radiolysis
WPRO-100-OG

Evolving Technology

The radiolytic destruction of halogenated and aromatic compounds at the laboratory scale is well documented. However, its application on an industrial scale needs additional RD&D. The process is capable of high (>90%) destruction efficiencies for organics.

Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment. Some of the issues to be resolved are the complete characterization of the radiolytic decomposition products under different conditions and for different waste materials and their relative toxicity. Another issue is the possibility of combining the radiolysis with enhanced biodegradation of the radiolytic byproducts.

The RD&D effort is estimated to require \$ 1.25-2.5 million.


Electro Osmosis/Migration
DCON-20-OG

Evolving Technology

Initial data indicate 90+% removal of uranium and technetium from concrete. The process could also be used to remove oils and organics however, this application needs additional RD&D.


Some development work is required to apply the method to treat the site wastes.

Normal implementation needs. Development costs are estimated to be \$ 400-1000K. Capital costs: Not available. Operating costs: Likely to be more expensive than other waste treatment methods.




Logic Diagram

Management



Technology Log


Waste Management






Technology Logi

Waste Managem




Logic Diagram


Management




Technology Log

Waste Manag





→ **Waste Stabilization** → See Waste Stabilization



- Cleanup Legacy
- Prevent Future Insult
- Develop Environmental Stewardship



EM Problem

Decommissioning (D&D)

Soils, Groundwater and Surface Water (RA)

Waste Management (WM)

Scrap Ferrous Metal (Iron and Steel)

- Steel
- RAD
- Organics
- Inorganics

Refer to Volume 1, Chapter 10, for potentially applicable proposed and promulgated environmental laws, signed and pending agreements for the ORR, radiation protection standards, DOE Orders, and non-regulatory guidance. As site- and waste-specific characteristics are provided for each technology, specific regulatory requirements will be specified.

Waste Processing

Chemical Treatme

Scrap Plastics, Paper, and Cloth (Except PPC and rags)

- Plastics, Paper, Cloth, RAD, Organics, Inorganics

Refer to Volume 1, Chapter 10, for potentially applicable proposed and promulgated environmental laws, signed and pending agreements for the ORR, radiation protection standards, DOE Orders, and non-regulatory guidance. As site- and waste-specific characteristics are provided for each technology, specific regulatory requirements will be specified.


Waste Processing

Thermal Treatme




Logic Diagram


Management





Technology Log

Waste Management






→ Waste Stabilization → See Waste Stabilization



Technology Logi

Waste Managem




Logic Diagram


Management





Technology Log

Waste Manag






- Cleanup Legacy
- Prevent Future Insult
- Develop Environmental Stewardship




Logic Diagram

Management




Technology Log


Waste Manag




Logic Diagram

Management








Technology Log

Waste Manag



► **Chemical Treatment (contd)** → Catalytic Destruction
WPRO-109-OG

→ **Pre-Demonstration**
This technology has been demonstrated to be effective (DRE>99+%) for the destruction of liquid and gaseous organic wastes. However, its use to remove and destroy the organics from solids needs additional RD&D.

→ Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment.

→ The RD&D effort is estimated to require \$ 0.75-1.5 million.

► **Thermal Treatment** → Calcination/Roasting
DCON-60-OG

→ **Demonstration**
This is accepted industrial technology for the treatment of ores. However, its use for the removal and destruction of oils and organics from the site wastes needs to be demonstrated.

→ The use of the technology to meet the site requirements needs to be demonstrated.

→ The RD&D effort is estimated to require \$ 2-5 million. The payback could be significant.

→ Chem Char Process
WPRO-114-OG

→ **Pre-Demonstration**
This is a developmental technology based on coal char gasification. The process is claimed to achieve near total destruction of the organics and produces an inert char residue that contains the non-volatile toxic metals and radionuclides. This char residue can either be vitrified to yield a glassy slag or immobilized in cement.

→ Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment.

→ The RD&D effort is estimated to require \$ 0.75-1.5 million.

→ Wet Air Oxidation
WPRO-215-OG

→ **Demonstration**
The process is commercially available. It is capable of greater than 99+% destruction of some organics however, it may not be able to completely destroy certain refractory organics such as halogenated aromatics (e.g., PCB). Processing costs are likely to be high.

→ Demonstrate the effectiveness of the technology to meet the site requirements.

→ The development effort is estimated to require approximately \$ 1 million.

→ Microwave Heating
WPRO-115-OG

→ **Demonstration**
This is a novel technology for the thermal treatment of radioactive wastes. The technology is at the laboratory scale of development.

→ Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment.

→ The RD&D effort is estimated to require \$ 2.5 million.

→ Molten Glass Combustor
WPRO-113-OG

→ **Accepted**
This is accepted industrial technology for mixed wastes treatment. The process can achieve DREs greater than 99%. EPA has accepted this process as best demonstrated available technology (BDAT) for the treatment of hazardous high-level nuclear wastes. Operating costs for the process are likely to be high.

→ Some development work is required to apply the method to treat the site wastes.

→ Knowledge of process application, funding, and regulatory approval.

► **Bioreatment** → Biodegradation
WPRO-117-OG

→ **Evolving Technology**
This is a promising technology for hazardous waste treatment. The process can achieve impressive treatment efficiencies for certain organics. However, the process is slow and may not be able to completely destroy certain refractory organics.

→ Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment.

→ The RD&D effort is estimated to require \$ 1-10 million. The payback could be significant.

- Cleanup Legacy
- Prevent Future Insult
- Develop Environmental Stewardship



EM Problem

Decommissioning
(D&D)

Soils, Groundwater
and Surface Water
(RA)

Waste Management
(WM)

Waste Processing Solid
Residuals

- Residue
- RAD
- Organics
- Inorganics


Refer to Volume1, Chapter 10,
for potentially applicable pro-
posed and promulgated envi-
ronmental laws, signed and
pending agreements for the
ORR, radiation protection stan-
dards, DOE Orders, and non-
regulatory guidance. As site-
and waste-specific characteris-
tics are provided for each tech-
nology, specific regulatory
requirements will be specified.

Waste Processing

Waste Stabiliza


Chemical Treatm

Thermal Treatm



Technology Log

Waste Manag



Thermal Treatment

Molten Salt Oxidation
WPRO-113-OG

Demonstration

This is not a new process however, its application for treating hazardous and radioactive contaminants has not been demonstrated. One advantage of the process is that the process and equipment is transportable (as opposed to a fixed treatment facility) and can be located near the waste site. The process should be capable of destroying organics with a >99% efficiency.

Additional RD&D is required to fully develop the process to treat mixed wastes.

Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment.

The RD&D effort is estimated to require \$ 1.4 million for a 3 year development effort.

Wet Air Oxidation
WPRO-215-OG

Demonstration

The process is commercially available. It is capable of greater than 99+% destruction of some organics however, it may not be able to completely destroy certain refractory organics such as halogenated aromatics (e.g., PCB). Processing costs are likely to be high.

Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment.

The development effort is estimated to require approximately \$ 1 million.

Chem Char Process
WPRO-114-OG

Pre-Demonstration

This is a developmental technology based on coal char gasification. The process is claimed to achieve near total destruction of the organics and produces an inert char residue that contains the non-volatile toxic metals and radionuclides. This char residue can either be vitrified to yield a glassy slag or immobilized in cement.

Further research, development, and demonstration (PD&D) on the process to develop the technology to deployment.

The RD&D effort is estimated to require \$ 0.75-1.5 million.

Microwave Heating
WPRO-115-OG

Demonstration

This is a novel technology for the thermal treatment of radioactive wastes. The technology is at the laboratory scale of development.

Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment.

The RD&D effort is estimated to require \$ 2.5 million.

Molten Glass Combustor
WPRO-116-OG

Accepted


This is accepted industrial technology for mixed wastes treatment. The process can achieve DREs greater than 99%. EPA has accepted this process as best demonstrated available technology (BDAT) for the treatment of hazardous high-level nuclear wastes. Operating costs for the process are likely to be high.

Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment.

The RD&D effort is estimated to require \$ 1-10 million. The payback could be significant.


Technology Logi

Waste Managem




Logic Diagram


anagement





Technology Log

Waste Manag













Technology Log

Waste Management












14000 500 1000 1500 2000






Technology Logistics Waste Management




Logic Diagram


Management



Technology Log


Waste Management





Technology Logic


Waste Management






Technology Log


Waste Manage






Technology Log

Waste Manage




Logic Diagram

Management




Technology Log

Waste Management




Logic Diagram

Management




Technology Logic

Waste Manageme




Logic Diagram

Management




Technology Lo

Waste Mana




Logic Diagram

Management




Technology Logic

Waste Management




Logic Diagram

Management




Technology Leads Waste Management




Logic Diagram

Management




Technology Logi

Waste Managem




Logic Diagram

Management




Technology Log

Waste Management




Logic Diagram

Management




Technology Logi

Waste Managem




Logic Diagram

Management




Technology Log

Waste Management




Logic Diagram

Management




Technology Logi

Waste Managem




Logic Diagram Management




Technology Lo

Waste Mana




Logic Diagram

Management




Technology Logic

Waste Management




Logic Diagram


Management



Technology Log


Waste Management






Technology Logic

Waste Management




Logic Diagram

Management




Technology Log

Waste Management




Logic Diagram

Management




Technology Logic

Waste Management




y Logic Diagram

ie Management




Technology Low Waste Management




Logic Diagram

Management




Technology Logic

Waste Management




Logic Diagram

Management




Technology Log

Waste Management




Logic Diagram


Management



Technology Logi


Waste Managen





Technology Look L


Waste Management M



Alternatives	Technologies	Status	Source/Technology Needs	Implementation Needs
Thermal Treatment	Incineration WPRO-108-OG	Accepted The RD&D effort is estimated to require \$ 1-2.5 million. The payback could be significant.	Though an accepted technology, the use of the technology to meet the site requirements needs to be demonstrated. Also, RD&D is required to develop better understanding of the process technology to improve its acceptability.	Knowledge of process application, funding, and regulatory approval. The RD&D effort is estimated to require \$ 1.25-2.5 million.
	Molten Salt Oxidation WPRO-113-OG	Demonstration Further RD&D on the process is needed to develop the optimum processing conditions.	Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment.	The RD&D effort is estimated to require \$ 1.4 million for a 3 year development effort.
	Distillation WPRO-222-OG	Demonstration Demonstration costs are estimated to be \$ 0.5-1 million.	The use of the technology to meet the site requirements needs to be demonstrated.	Knowledge of process application(s) and funding.
	Chem Char Process WPRO-114-OG	Pre-Demonstration The RD&D effort is estimated to require \$ 5 million for a 3-year R&D program.	Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment.	The RD&D effort is estimated to require \$ 0.75-1.5 million.
Biotreatment	Microbial Dechlorination WPRO-227-OG	Evolving Technology This process is at an early stage of development. Based on the available information, it appears the process should be able to achieve destruction efficiencies greater than 90%.	Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment.	The RD&D effort is estimated to require \$ 5-10 million. The payback could be significant.
Physical Treatment	Gravity Separation WPRO-201-OG	Demonstration Development and demonstration of the WMES is estimated to require \$ 3-5 million. The savings from implementing the system could be around \$ 1 billion or more.	The use of the technology to meet the site requirements needs to be demonstrated.	Demonstration costs are estimated to require up to \$ 1 million.
Chemical Treatment	Leaching WPRO-213-OG	Demonstration The use of the technology to meet the site requirements needs to be demonstrated.	Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment.	Demonstrate the effectiveness of the technology to meet the site requirements.
	Chemical Precipitation WPRO-21-OG	Demonstration The development effort is estimated to require approximately \$ 1 million.	Demonstrate the effectiveness of the technology to meet the site requirements.	The demonstration effort is estimated to require \$ 0.4 million.
Thermal Treatment	Distillation WPRO-222-OG	Demonstration Demonstration costs are estimated to be \$ 0.5-1 million.	The use of the technology to meet the site requirements needs to be demonstrated.	Knowledge of process application(s) and funding.
Physical Treatment	Gravity Separation WPRO-201-OG	Demonstration Development and demonstration of the WMES is estimated to require \$ 3-5 million. The savings from implementing the system could be around \$ 1 billion or more.	The use of the technology to meet the site requirements needs to be demonstrated.	Demonstration costs are estimated to require up to \$ 1 million.
	Filtration WPRO-201-OG	Demonstration This is an accepted process for separating solids from fluids. The process can achieve removal efficiencies greater than 99%. The use of the process to meet the site requirements will however, need to be demonstrated.	The use of the technology to meet the site requirements needs to be demonstrated.	Demonstration costs are estimated to require up to \$ 1 million.


Technology Logic

Waste Management




Logic Diagram

Management




Technology Log

Waste Manag




Logic Diagram

Management




Technology Log

Waste Management




Logic Diagram

Management




Technology Logic

Waste Management




Logic Diagram

Management




Technology Log

Waste Manag




Logic Diagram

Management




Technology Logic

Waste Managemen




Logic Diagram

Management



Technology Log L



Thermal Treatment

Molten Salt Oxidation
WPRO-113-OG

→ Demonstration

This is not a new process however, its application for treating hazardous and radioactive contaminants has not been demonstrated. One advantage of the process is that the process and equipment is transportable (as opposed to a fixed treatment facility) and can be located near the waste site. The process should be capable of destroying organics with a >99% efficiency. Additional RD&D is required to fully develop the process to treat mixed wastes.

→ Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment.

→ The RD&D effort is estimated to require \$ 1.4 million for a 3 year development effort.

Physical Treatment

Inorganic Membrane Separation
WPRO-300-OG

→ Pre-Demonstration

The RD&D effort to develop inorganic microporous filters is estimated to require \$ 0.75-1 million. The payback is estimated to be \$20-25 million based on significantly reduced waste disposal costs.

→ Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment.

→ The RD&D effort is estimated to require \$ 1.5-2 million to further develop the process to meet the site needs.

Adsorption
WPRO-202/203-OG

→ Pre-Demonstration

Laboratory studies indicate removal efficiencies greater than 90% for the removal of radioactive species using various adsorbing media. Further development is necessary to develop more effective adsorption media for the treatment of mixed waste contaminated liquids. Development would include for example, scale-up studies, development of high surface area and appropriate particle size media for continuous operations, and the development of appropriate media for the removal of various contaminants.

→ Further research, development, and demonstration (RD&D) on the process to develop the technology to deployment.

→ The RD&D effort is estimated to require \$ 1.25 million.

Filtration
WPRO-201-OG

→ Demonstration

This is an accepted process for separating solids from fluids. The process can achieve removal efficiencies greater than 99%. The use of the process to meet the site requirements will however, need to be demonstrated.

→ The use of the technology to meet the site requirements needs to be demonstrated.

→ Demonstration costs are estimated to require up to \$ 1 million.

Scrubbers
WPRO-301-OG

→ Demonstration

Scrubbers are commercially available though need to be demonstrated for particular applications at K-25.

→ Though an accepted technology, the use of the technology to meet the site requirements needs to be demonstrated.

→ Knowledge of process application(s) and funding.


Cyclone Separation
WPRO-302-OG

→ Demonstration

Application of commercially available cyclones to specific K-25 problems must be investigated before full-scale use


→ Though an accepted technology, the use of the technology to meet the site requirements needs to be demonstrated.

→ Demonstration costs are estimated to require up to \$ 1 million.




Logic Diagram

Management




Technology Log

Waste Management




Logic Diagram

Management




Technology Log

Waste Management




Logic Diagram

Management




Technology Logic Waste Management




Logic Diagram

Management




Technology Log

Waste Management




Logic Diagram

Management



Technology Log

Waste Manag



→ **Strong Tight Containers** → **Accepted Packages**
WPHT- 100-OG → **Accepted** → New package designs may be required. → **None**

→ **Multi-use Containers** → **Multi-use, standardized**
Type A Packaging
WPHT- 101-OG → **Evolving Technology** → New standardized Type A package designs need to be developed and qualified to meet regulations. Designs must be user friendly and available to a wide variety of users.
An operationally efficient multi-use Type A package, or packages, for radioactive materials needs to be developed. → **Funding requirements for R&D are estimated to be \$1 million.**


→ **Light Weight Containers** → **Type B Packaging**
WPHT-102-OG → **Accepted** → New package designs and certifications may be required.
Certified package design can be identified from RAMPAC database and Packaging management Transportation System (PMTS) database which will identify numbers and status of packagings available under development by EM-5621. → **None**

→ **Light Weight Containers** → **Type A Fissile Certified**
Packaging
Type B Fissile Certified
Packaging
WPHT-103-OG → **Accepted** → New package designs and certifications may be required.
Certified package design can be identified from RAMPAC database and Packaging management Transportation System (PMTS) database which will identify numbers and status of packagings available under development by EM-5621. → **None**

→ **POP Container** → **Performance Oriented**
Packaging (POP)
WPHT-104-OG → **Accepted** → New package designs may be required. → **None**


Technology Log

Waste Management




Logic Diagram

Management




Technology Logic

Waste Management




Logic Diagram

Management




Technology Log

Waste Manag




Logic Diagram

Management




Technology Log

Waste Management




Logic Diagram

Management




Technology Logic

Waste Management



Logic Diagram

Management



Internal

Abraham, T. J.
Altman, W. D.
Autrey, J. W.
Bailey, H. L.
Baker, M. L.
Bane, K. E.
Barber, E. J.
Beck, D. E.
Bell, D. T.
Bock, J. L.
Boes, K. S.
Bonezek, R. R.
Boston, H. L.
Bradbury, J. T.
Brady, K. L.
Bundy, R. D.
Burwinkle, T. W.
Cain, R. A.
Charles, L. D.
Chiang, J. M.
Childs, Y. C.
Clark, K.
Clausen, J.
Clayton, B.
Colburn, S. J.
Cook, K. W.
Cothron, T. K.
Craig, R. B.
Cross, S. L.
Cutshall, N. H.
Deacon, L. E.
Del Cul, G. D.
Delozier, F.

Devore, J. R.
Dierolf, R. K.
Douthat, D. M.
Dudney, C. S.
Eby, R. S.
Etnier, E. L.
Eversole, R. E.
Fellows, R. L.
Flynn, J. P.
Foster, C. E.
Francis, C. W.
Francis, M. W.
Frye, C. E.
Gagnier, T. R.
Gammage, R. B.
Gardner, W. L.
Garland, S. B.
Genung, R. K.
Gilbert, T.
Goddard, P. L.
Goins, C. D.
Googin, J. M.
Greene, J.
Griest, W. H.
Grubb, R. G.
Grumski, J. T.
Guerin, M. R.
Gunter, D. B.
Haas, J. W.
Hagenauer, R. C.
Haley, D.
Hall, L. E.
Haselton, H. H.

Hayden, H. W.
Heiskell, J.
Hensley, L. C.
Henson, H. M.
Hermes, W. H.
Herndon, J. N.
Higgins, R. L.
Hightower, J. R.
Hitch, J. P.
Hoffmann, D. P.
Horton, P.
Houlberg, L. M.
Howell, S. H.
Hutchins, D. A.
Ingle, K. A.
Jones, C. G.
Jordan, R.
Kahl, K. G.
Keeting, R.
Kendrick, C.
Kennerly, J. M.
Key, W. S.
Kibbe, R. K.
Kimmel, B. L.
Knee, H. E.
Koger, J. W.
Kornegay, F. C.
Kraemer, R. D.
Kubarewicz, J.
Kuhaida, A. J.
Lee, S. Y.
Leone, S. M.
Little, D. K.

tribution

ternal

on, H. W.	Long, L. W.	Sands, A.
ell, J.	Lotts, A. L.	Scanlan, T. F.
ey, L. C.	Lyons, J. R.	Schaefferkoetter, D. P.
on, H. M.	Malinauskas, A. P.	Schmidt, M. A.
os, W. H.	Mason, R. C.	Schrock, S. L.
on, J. N.	McGinnis, P.	Sharples, F. E.
is, R. L.	McNeese, L. E.	Siegrist, R. L.
ower, J. R.	Merriman, J. R.	Sigg, R. A.
J. P.	Mezga, L. J.	Singh, S. P.
ann, D. P.	Miller, R.	Singleton, B. H.
n, P.	Mitchell, M. E.	Smith, J. W.
erg, L. M.	Moore, J. O.	Smith, D. B.
ll, S. H.	Moore, J. M.	Smith, G. S.
ins, D. A.	Mueller, T. R.	Snipes, R. L.
K. A.	Munday, E. B.	Spalding, B. P.
, C. G.	Neiswander, D. W.	Stair, C. L.
n, R.	Oakes, L. L.	Stephenson, M. J.
K. G.	Pashley, J. H.	Stokely, J. R.
ig, R.	Paulauskas, P.	Stow, S. H.
ick, C.	Perona, J. J.	Subbaraman, G.
orly, J. M.	Perry, T. P.	Swanks, J. H.
W. S.	Person, G. A.	Tayloe, S. L.
, R. K.	Phifer, D. W.	Taylor, G.
el, B. L.	Piccolo, J. F.	Thompson, W. T.
, H. E.	Plummer, K. E.	Trabalka, J. R.
, J. W.	Powell, J. E.	Tsai, C. C.
gay, F. C.	Prince, B. E.	Waters, D. A.
ner, R. D.	Pugh, L. P.	Watson, J. S.
ewicz, J.	Richards, W. L.	Weir, J. R.
ida, A. J.	Rivera, A. L.	White, T. L.
S. Y.	Row, T. H.	Whitehead, H. D., Jr.
, S. M.	Roy, E. J.	Wilson, J. H.
. D. K.	Rymer, G. E.	Zolyniak, J. W.

Department

Adams, W. D.
DOE-OR
Assistant Mgr., ERWM

Bandy, Darrel H.
U. S. Department of Energy
P. O. Box 5400
Albuquerque, NM 87115

Bassi, Jo-Ann
DOE EM-351
c/o Ken Kuzio
Sandia Nat'l Lab
20201 Century Blvd.
2nd Floor, Rm. 211
Germantown, MD 20874

Cheng, Sam
US Department of Energy
Dayton Area Office
P. O. Box 66
Miamisburg, OH 45343

Clarke, Susanne
A6-55, US Department of Energy
P. O. Box 550
Richland, WA 99352

Duquella, Leon
ERWM, DOE-OR
Ellis, Nate
P. O. Box A
US Department of Energy
Solid Waste Division
Aiken, SC 29802

Frank, C. W.
Deputy Assistant Secretary, EM-50,
Rm. 6B132, Forestal Bldg.
U. S. Department of Energy
Washington, DC 20585

Gilbert, Bill
DOE-OR
WMD, K-25

Gist, Clayton
DOE-OR
ER

Goodenough, Jim
A5-19, US Department of Energy
825 Jadwin Ave.
Richland, WA 99352

Grace, Scott R.
US Department of Energy
Rocky Flats Office
DOE Bldg. 116
P. O. Box 928, Hwy 93
Golden, CO 80402-0928

Hain, K. E.
EM-55, Trevion II
U. S. Department of Energy
Washington, DC 20585

Heiskell, Marianne
DOE-OR
WMD, K-25

Hinschberger, Scott T.
785 DOE Place, MS-1219
Idaho Falls, ID 83401

Hultgren, R.O.
DOE-OR
X-10

Hyde, Jerry
EM-551, Trevion II
U. S. Department of Energy
Washington, DC 20585

Johnson, Sherri V.
US Department of Energy
P. O. Box A, 703 A-B211
Aiken, SC 29802

Jugan, Mike
DOE-OR
ER, ORNL

Korynta, Rick
DOE-OR
WM

Lankford, Mac
DOE-HQ, EM55

Lankford, Sherry
DOE-OR
ER, Y-12

Lien, Steve
EM-54, Trevion II
U. S. Department of Energy Washington,
DC 20585

Lester, Brady
DOE-OR, ER

Lingle, Nelson
DOE-OR

McWilliam, Katie
US Department of Energy
Nevada Field Office
P. O. Box 98518
Las Vegas, NV 89193-8518

Mikkola, A. W.
US Department of Energy
Idaho Field Office
785 DOE Place
Idaho Falls, ID 83415

Moore, Johnny
US Department of Energy
DOE-OR
P. O. Box E
200 Administration Rd.
(Zip: 37830)
Oak Ridge, TN 37831

ment of Energy

O'Rear, Michael
US Department of Energy,
Savannah River Field Office
RFD #1, Bldg. 703A
Rm. E-208-N
P. O. Box A
Aiken, SC 29802

Powell, Jane
DOE-OR
ER, ORNL

Price, Les
DOE-OR
ER Enrichment

Radcliffe, Larry
DOE-OR
WMD

Riddle, Suzy
DOE-OR, ER

Roddy, Mac
DOE-OR
WMD, ORNL

Sager, Joy
DOE-OR
WMD, Y-12

Saxman, Pamela A.
US Department of Energy
RDDT&E
P. O. Box 5400
Albuquerque, NM 87115

Schneider, George
US Department of Energy
Idaho Field Office
785 DOE Place
Idaho Falls, ID 83402

Schutte, W. C.
DOE-HQ, EM-551,
Trevion II
U. S. Department of Energy
Washington, DC 20585

Scott, Richard
US Department of Energy
San Francisco Field Office
1333 Broadway
Oakland, CA 94612

Shupe, Mel
DOE-HQ
EM-54

Sleeman, Bob
DOE-OR, ER Enrichment

Staats, Gary E.
US Department of Energy
Pittsburgh Energy Tech. Center
P. O. Box 10940
Receiving Dept. Bldg. 16
Cochran's Mill Road
Pittsburgh, PA 15236-0940

Stevenson, Karen
US Department of Energy
376 Hudson Street
New York, NY 10014-3621

Sweeney, John
DOE-OR
ER, ORNL

Tison, Tom
DOE-OR, K-25

Trader, Deborah E.
US Department of Energy
Richland Field Office
825 Jadwin Ave.
P. O. Box 550
Richland, WA 99352

Travaglini, Mike
DOE-OR
ER, Y-12

Tyler, Reginald
US Department of Energy
Rocky Flats Office
DOE Bldg. 116
P. O. Box 928, Hwy 93
Golden, CO 80402-0928

Underwood, Doug
DOE-OR
WMD

Velazquez, Luis
DOE-OR

Voelker, Gary
EM-50, Trevion II
Washington, DC 20585

Wallin, Bruce W.
US Department of Energy
Rocky Flats Office
P. O. Box 928
Golden, CO 80402-0928

Walker, Bryan
Deputy AM for ERWM
DOE-OR

Webster, Steve
US Department of Energy
Chicago Field Office
9800 South Cass Ave.
Argonne, IL 60439

Whitehead, Rebecca
DOE-OR

Wolf, Stan
EM-54, Trevion II
U. S. Department of Energy
Washington, DC 20585

External

Allen, D.
Radian Corp.
Oak Ridge, TN

Austin, Bill
WSRC
P. O. Box 616
Aiken, SC 29808

Bain, J.
SAIC
Route 2
Kevil, KY 42053

Barber, David
Sandia National Laboratories
Organization 7023
P. O. Box 5800
Albuquerque, NM 87185

Barnes, T.
Machine Kinetics Corp.

BDM International/SAIC
12850 Middlebrook Rd.
Suite 300
Germantown, MD 20874

Bliss, Wayne
ES&H Div.
Reynolds Elec. & Engineer Co.
P. O. Box 98521
Las Vegas, NV 89193-8521

Boing, Larry
Argonne National Laboratory
9700 S. Cass Ave.
Argonne, IL 60439-4831

Benedetti, R. L.
EG&G Rocky Flats, Inc.
P.O. Box 464
Golden, CO 80402-0464

Berger, James
Office of Tech. Integration
Westinghouse Hanford Co.
P. O. Box 1970, MS L-18
Richland, WA 99352

Berry, Dennis
Sandia Nat'l Laboratories
P. O. Box 5800, Dept. 6602
1515 Eubank S.E.
(Zip: 87123)
Albuquerque, NM 87185-5800

Brown, Craig
EPA, Region IV
Atlanta, GA

Buelt, Jim
Pacific Northwest Laboratory
P. O. Box 999, MSIN P7-41
Battelle Boulevard
Richland, WA 99352

Carlson, B.W.
Westinghouse Idaho Nuclear Co.
5108 P.O. Box 4000
Idaho Falls, ID 83415

Carroll, M. K.
Machine Kinetics Corp.
Knoxville, TN

Carter, Randy
Applied Radiological
Control, Inc
500 Chastain Center Blvd., Suite
545
Kennesaw, GA 30144-5559

Christian, Jerry
Westinghouse Idaho Nuclear Co.
P. O. Box 4000
Idaho Falls, ID 83403

Coleman, J. Todd
WSRC, Bldg. 773-41A
Aiken, SC 29808

Colombo, Peter
Brookhaven National Lab
Bldg. 703-50 Rutherford
Upton, NY 11973

Conway, Sheila
Colorado Center for Environmental
Mgmt
1536 Cole Blvd, Bldg 4
Suite 180
Golden, CO 80401

Corones, James
AMES Laboratory
329 Wilhelm Hall
Iowa State University
Ames, Iowa 50011

Crockett, John
Oak Ridge Institute for Science
and Energy
P. O. Box 117
Oak Ridge, TN 37831

Dantz, John
SAIC
Germantown

Demmer, Rick
Westinghouse Idaho
Nuclear Co.
P. O. Box 4000, MS-5218
Idaho Falls, ID 83403

Denny, Paul
Penn State Applied
Research Laboratory
State College, PA

Deonigi, Duane
PNL, P. O. Box 999
Richland, WA 99352

Ditch, Ralph
Argonne National Laboratory
9700 S. Cass Ave.
Argonne, IL 60439

Dugger, H. A.
Kaiser Engineering
214 Pinetree
Richland, WA 99352

Eagan, Neal S.
Prgrm Development Div.
MSE Inc.
P. O. Box 3767
Butte, Montana 59702

Eaton, A.
SAIC, Rt. 2
Kevil, KY 42053

Emilia, Dave
Strategic Planning Dept.
Chem-Nuclear Geotech
P. O. Box 14000
2597B-3/4 Rd. (81503)
Grand Junction, CO 81502

Erickson, M. D.
Argonne National Laboratory
9700 South Cass Ave. CM
Argonne, IL 60439-4837

Ferguson, James F.
Westinghouse Idaho
Nuclear Corporation
P. O. Box 1625, MS-3970
Idaho Falls, ID 83415

Flores, Pedro
Smith, R. H.
Savannah River Site
P.O. Box 616, Bldg. 707-H
Aiken, SC 29806

External

Ralph
National Laboratory
South Cass Ave.
Idaho Falls, IL 60439

H. A.
Engineering
Metree
Idaho, WA 99352

Neal S.
Development Div.
Inc.
Box 3767
Montana 59702

A.
Rt.
KY 42053

Dave
Planning Dept.
Nuclear Geotech
Box 14000
3/4 Rd. (81503)
Junction, CO 81502-2567

on, M. D.
National Laboratory
South Cass Ave. CMT/205
Idaho Falls, IL 60439-4837

on, James F.
Westinghouse Idaho
Nuclear Corporation
Box 1625, MS-3970
Idaho Falls, ID 83415

Pedro
R. H.
Snake River Site
Box 616, Bldg. 707-H
SC 29806

Frazee, Brad
Westinghouse Idaho
Nuclear Co.
P. O. Box 4000
Idaho Falls, ID 83403

Fredette, Debbie
SAIC
P. O. Box 99
West Paducah, KY 42086

Gilchrist, Roger
Technology Demonstration
Programs
Westinghouse Hanford Co.
P. O. Box 1970, MS L5-63
Richland, WA 99352

Gillies, Bruce
ETEC, D/030, T038
P. O. Box 1449
Canoga Park, CA 91304

Goodell, Mark D.
WSRC, Bldg. 773-41A
Aiken, SC 29808

Gupta, Bimleshwar (Bim)
Manager, WM Programs
Nat'l Renewable Energy
Laboratory
1617 Cole Boulevard
Golden, CO 80401

Haas, Bill
AMES Laboratory
7 Spedding Hall
Iowa State University
AMES, Iowa 50011

Helt, James E., PhD
Director
Office of Waste Mgmt Prgms
9700 South Cass Ave.
Argonne, IL 60439-4837

Heine, William F.
B3-63, Westinghouse
Hanford Co.
P. O. Box 1970
Richland, WA 99352

Herman, Donald
Westinghouse Env. Management
Co.
of Ohio, Inc.
P. O. Box 398704
Cincinnati, OH
45239-8704

Heywood, Ann Cochran
P. O. Box 808
7000 East Avenue
MS L-207
Livermore, CA 94612

Hinds, Ron
SRTC, Bldg. 773A, Room B121
Aiken, SC 29802

Hottel, Robert E.
WSRC, P. O. Box 616
Aiken, SC 29808

Ison, Mike
Westinghouse Idaho Nuclear Co.
P. O. Box 4000, MS-5119
Idaho Falls, ID 83415

Jacobson, Roger, PhD
Desert Research Institute
P. O. Box 19040
Las Vegas, NV 89132-0040

Jaeger, Ralph
EG&G-Mound
One Mound Rd.
Miamisburg, OH 45343

Jarrett, Jim
Pacific Northwest
Laboratories
P. O. Box 999, MS P7-43
Richland, WA 99352

Johnesee, Jim
Waste Policy Institute
12850 Middlebrook Rd.
Suite 108
Germantown, MD 20874

Jordan, David L.
Allied Signal Aerospace
Kansas City Plant
P. O. Box 419159,
D/272, FV43
2000 East 95th Street
Kansas City, MO 64141-6159

Kan, T.
AVLIS, LLNL
P. O. Box 94550
Livermore, CA

Karas, Theodore
EG&G, Bldg. T371 A
Rocky Flats Plant
P. O. Box 464
Golden, CO 80402-0464

Kelly, Vince
MSE, Inc.
P. O. Box 3767
Butte, Montana 59702

Koller, Ken
Waste Tech. Development
EG&G Idaho, Inc.
P. O. Box 1625
Idaho Falls, ID 83415-3940

Kostelnik, Lori
Westinghouse Idaho Nuclear Co.
Box 4000, MS-3205
Idaho Falls, ID 83415

Kuhl, Roger
AL/EQ
139 Barnes Dr., Bldg. 1117
Tyndall AFB, FL 32403-5319

Kuzio, Ken
Sandia Nat'l Lab
20201 Century Blvd.
2nd Floor, Rm. 211
Germantown, MD 20874

Larson, Scott
Princeton Plasma Physics Lab
P. O. Box 451
Princeton, NH 08543

Marske, Steve
Westinghouse Hanford Co.
P. O. Box 1970
Richland, WA 99352

McClure, Lloyd W.
Westinghouse Idaho Nuclear Co.
P. O. Box 4000
Idaho Falls, ID 83415-32111

McCoy, R. D.
Tennessee Department of
Environment &
Conservation
Emory Valley Road
Oak Ridge, TN 37830

McEvilly, Thomas
50E-111
Lawrence Berkeley Laboratory
1 Cyclotron Road
Berkeley, CA 94720

Mech, Steve
Westinghouse Hanford Co.
P. O. Box 1970,
MSIN L7-03
Richland, WA 99352

Merrill, Ken
EG&G Idaho, Inc.
P. O. Box 1625
Idaho Falls, ID 83415-3970

Meservey, Richard
D&D Program Manager, INEL
P. O. Box 1625, MS-1545
Idaho Falls, ID 83415

Meyer, Rod
Energy Technology
Engineering Center
P. O. Box 7930
Canoga Park, CA 93209-7930

Miller, R. L.
(H6-92), Westinghouse Hanford
Co.
P. O. Box 1970
Richland, WA 99352

Montoya, Gilbert
Los Alamos National Laboratory
P. O. Box 1663, MS #516
Los Alamos, NM 87545

Murphy, Hugh D.
ET-AET
Los Alamos Nat'l Lab
MS D446
Los Alamos, NM 87545

Neathery, A. P.
Kaiser Engineering -
Hanford
Richland, WA

Nelson, Jennifer
Sandia Nat'l Laboratories
P. O. Box 5800, Div. 6621
1515 Eubank S.E.,
(Zip 87123)
Albuquerque, NM 87185-5800

Newman, Christine
Westinghouse
Environmental
Management Co.
of Ohio, Inc.
P. O. Box 398704, MS 52
Cincinnati, OH
45239-8704

Nuhfer, Kimberly
Fernald Environmental
Management Co. of OH
P. O. Box 398704
Cincinnati, OH 45239-8704

O'Brien, Mike
EG&G
200 South Woodruff Ave.
Idaho Falls, ID 83415-3970

Olson, Herb
WSRC, P. O. Box 616
CCC Bldg. #4
Aiken, SC 29808

Peterson, Jerry L.
EG&G Rocky Flats, Inc.
Technology Department
P. O. Box 464
Golden, CO 80402-0464

Peterson, Mary
Pacific Northwest Laboratory
P. O. Box 999, MSIN P7-41
Battelle Boulevard
Richland, WA 99352

Petit, Paul J., PhD
FERMCO
6025 Dixie Hwy, Suite 250
Fairfield, OH 45014

Rankin, Nevyn
WSRC
P. O. Box 616
Aiken, SC 29808

Reynolds, Evan
Gilbert Commonwealth
1055 Commerce Park,
Suite 200
Oak Ridge, TN 37831

Robinson, Bill
Sandia Nat'l Laboratories
P. O. Box 969, Dept. 8240
7011 East Avenue (Zip: 94551)
Livermore, CA 94550

Rogers, Leo
EG&G Energy
Measurements, Inc.
P. O. Box 1912, M.
Las Vegas, NV 89
Rudin, M.
EM-54, Trevion II
U. S. Department of
1000 Independence
Ave. SW
Washington, DC
20585-0002

Sampinato, Phil
Princeton Plasma
Laboratory
Princeton, NJ

Sanford, Pete
KMI Services
4888 Pearl East Circle
Suite 103
Boulder, CO 80301

Sigg, R.
WSRC, P. O. Box
Bldg. 773A
Aiken, SC 29808

Slate, Steven C.
Pacific Northwest
MSIN KI-19
Office of Environmental
P. O. Box 999
Richland, WA 99352

Smet, David
Westinghouse Hanford
P. O. Box 1970
MSIN X5-52
Richland, WA 99352

Snook, Jeff
75 DOE Place
Idaho Falls, ID
83401-1562

Leo
Energy
Instruments, Inc.
Box 1912, MS RSL-11
Las Vegas, NV 89125

A.
Trevion II
Department of Energy
dependence
V
gton, DC
1002

ato, Phil
on Plasma Physics
cry
on, NJ

i, Pete
rvice
Earl East Circle
03
, CO 80301

P. O. Box 616
73A
C 29808

Steven C.
Northwest Laboratory
I-19
f Environmental Tech.
Box 999
d, WA 99352

David
House Hanford Company
Box 1970
5-52
d, WA 99352

Jeff
Place
alls, ID
1562

Spence, Scott
Kaiser Engineers - Hanford
P. O. Box 888, MISN #6-41
Richland, WA 99352

Steel, John L., P.E.
Waste Env. Remediation Prgms
Savannah River Tech. Center
Bldg. 773-41A
Aiken, SC 29802

Stein, Steve
Deputy General Manager
Environmental Mgmt Org.
Pacific Northwest Division
4000 N.E. 41st Street
Seattle, WA 98105

Stevens, Kenneth
WSRC
P. O. Box 616, Bldg.
992W-1
Aiken, SC 29808

Stewart, Irwin
Chem-Nuclear Geotech
P. O. Box 14000
Grand Junction,
CO 81506

Sturm, Harold F.
Savannah River Technology
Center
Savannah River Site
P. O. Box 616
Aiken, SC 29801

Swindle, Dave
Radian Corporation
Oak Ridge, TN

Walton, Russ
Princeton Plasma
Physic Lab.
P. O. Box 451
Princeton, NJ 08543

Waste Policy Institute
12850 Middlebrook Rd.
Suite 206
Germantown, MD 20874-5544

Waste Policy Institute
1872 Pratt Drive
Suite 1600
Blacksburg, VA 24060-6363

Wheelis, Ted
Sandia Nat'l Laboratories
Dept. 6623
1515 Eubank S.E.,
(Zip 87123)
Albuquerque, NM 87185

Wichlacz, Paul
INEL, EG&G
200 South Woodruff Ave.
Idaho Falls, ID 83415

Widrig, C.
Battelle—PNL
P. O. Box 999
Richland, WA 99352-K121

Wilks, D
SAIC, Rt. 2
Kevii, KY 42053

Woehr, C.
SAIC, Rt. 2
Kevii, KY 42053

Zeh, Charles
Morgantown Energy
Technology Center
3610 Collins Ferry Road
Morgantown, WV 26507-0880

END

**DATE
FILMED**

4 / 7 / 93

