



AIM


Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202


Centimeter



Inches



MANUFACTURED TO AIIM STANDARDS
BY APPLIED IMAGE, INC.



HW-78960

Cover Sheet for a Hanford Historical Document Released for Public Availability

Released 1994

**Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute**



~~DISTRIBUTION REQUESTED~~

DISTRIBUTION OF THIS DOCUMENT IS REQUESTED
BY THE FOLLOWING:

MAY 04 1994
OSTI

DISCLAIMER

This is a **historical document** that is being released for public availability. This was made from the best available copy. Neither the United States Government nor any agency thereof, nor Battelle Memorial Institute, nor any of their employees, makes any **warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights.** The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

54-3000-340 (3-57) AEC:GE RICHLAND, WASH.

DISTRIBUTION RESTRICTED (b)

(CLASSIFICATION)

DEPARTMENT OF THE NAVY (EX-1948) 100-1948

DECLASSIFIED

HW-78960

Page 1

This document classified by:

J.W. Van Wormer

This document consists of
11 pages.

GROUP 1

Excluded from automatic down-
grading and declassification.

PRODUCTION TEST-IP-616-A
IRRADIATION OF ENRICHED HOT-DIE-SIZE
DIFFUSION-BONDED FUEL ELEMENTS

Classification Declassify Change To

DECLASSIFIED

By

K. L. Hladek

By Authority of CC-PR-2
R M Oten 3-30-94

By John Malley 4-8-94 September 17, 1963
Verified By J E Saurly 4-15-94

HANFORD ATOMIC PRODUCTS OPERATION
RICHLAND, WASHINGTON

NOTICE

This report was prepared for use within General Electric Company in the course of work under Atomic Energy Commission Contract AT(45-1) - 1350, and any views or opinions expressed in the report are those of the author only. This report is subject to revision upon collection of additional data.

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

A. Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or

B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.

DECLASSIFIED

DECLASSIFIED

HW-78960

Page 2

DISTRIBUTION

1-2. AEC-RLOO: PM Midkiff	34. FW Knight
3. AEC-RLOO: RL Plum	35. LE Kusler
4. AEC-RLOO: CN Zangar	36. LW Lang
5. GS Allison	37. CG Lewis
6. TW Ambrose	38. AJ Low
7. ER Astley	39. GL Madsen
8. RS Bell	40. AR Maguire
9. CA Bennett	41. WW McIntosh
10. HE Berg	42. JE Minor
11. WA Blanton	43. WN Mobley
12. RR Bloomstrand	44. HC Money
13. CE Bowers	45. WI Neef
14. RW Bown	46. R Nilson
15. GN Brown	47. EV Padgett
16. CA Burgess	48. HG Powers
17. PA Carlson	49. CA Priode
18. MA Clinton	50. T Prudich
19. JA Cowan	51. RW Reid
20. RE Dunn	52. JD Schaffer
21. WJ Ferguson	53. OC Schroeder
22. GC Fullmer	54. HG Spencer
23. OH Greager	55. KB Stewart
24. AB Greninger	56. CA Strand
25. CN Gross	57. JT Stringer
26. PD Gross	58. FL Van Wyck
27. AK Hardin	59. FW Van Wormer
28. CM Heeb	60. AD Vaughn
29. KL Hladek	61. WD Widrig
30. RW Hooper	62. SA Wood
31. GA Huff	63. WK Woods
32. PC Jerman	64. 300 Area Files
33. SS Jones	65. Records Center

~~DECLASSIFIED~~

PRODUCTION TEST-IP-616-A
IRRADIATION OF ENRICHED HOT-DIE-SIZE
DIFFUSION-BONDED FUEL ELEMENTS

INTRODUCTION

Testing of hot-die-size diffusion-bonded fuel elements began under authority of Production Test-IP-546-A¹ in the C Reactor in July 1963. Eighteen columns of natural uranium fuel elements of that test are currently under irradiation. This test authorizes the initial irradiation of enriched, 0.947 w/o U-235, uranium hot-die-size diffusion-bonded fuel elements.

OBJECTIVES

The objectives of this production test are: (1) to authorize the irradiation of enriched uranium hot-die-size diffusion-bonded fuel elements; (2) to provide information for further evaluation of the hot-die-size process; (3) to evaluate the relative corrosion behavior of the enriched hot-die-sized fuel as compared to the corresponding Al-Si fuel model; and (4) to determine the gross dimensional stability of the fuel under irradiation.

TEST SUMMARY

This test authorizes irradiation of 19 monitor columns of enriched self-support fuel elements in the C Reactor. The columns will contain 28 fuel elements each; each of the columns will contain 14 fuel elements fabricated by the hot-die-size diffusion-bonded process and 14 elements of the standard Al-Si type. Ten of the columns will contain, in alternate positions in the downstream half of the charge, "paired" Al-Si and hot-die-size elements--elements containing cores from adjacent ingot rod positions. The remaining nine columns will contain hot-die-sized and Al-Si elements, paired by ingot only, in alternate positions in the downstream half of each column. The upstream portion of all charges will contain hot-die-sized and Al-Si elements in alternate column positions.

All of the columns of this test will be irradiated to an average column exposure of 1000 Mwd/t. The elements will be specially picked-up after discharge and subsequently examined in the 105-C Metal Examination Facility.

BASIS AND JUSTIFICATION

The incentives for the hot-die-sizing process now appear to be centered around the need for a "high performance" fuel element, probably of an enriched (w/o U-235) variety. The need for this element is derived from a proposed alternate product use of one or more of the Hanford reactors. If a product other than plutonium is to become a major portion of the plant production, a nonfissionable material

¹ Hladek, K. L., and C. A. Burgess. Production Test-IP-546-A, Irradiation of Hot-Die-Size Diffusion Bonded Fuel Elements, HW-75465. June 27, 1963. (SECRET)

~~DECLASSIFIED~~

HW-78960
Page 4

may be irradiated in fairly large quantities. To support the irradiation of the non-fissionable material a relatively high powered "driver" element may be required. This new element would ideally be capable of withstanding substantially more severe operating conditions than those imposed on the present fuel elements.

Although the demand for such elements is still speculative, should they be required, a relatively short period of time would probably be available for design and testing this element type. Any testing of proposed fuel concepts in advance of the actual schedule will enhance the probability of successfully meeting the demands of the proposal. At the present time, there is no irradiation experience at Hanford to indicate that hot-die-sizing will provide a "high performance" fuel element. Certainly much additional irradiation testing will be required before any statements can be made about the relative fuel performance of hot-die-sized elements.

This test is not designed to provide information for evaluation of the ultimate limitations of the hot-die-sized diffusion-bonded fuel elements. It will provide data for evaluation of certain basic parameters of the fuel element behavior.

TEST DETAILS

1. Reactor

Irradiation of the fuel elements of this test will take place in C Reactor.

2. Fuel Elements

a. Geometry

The geometry of fuel elements used in this test will be similar to the CDB2 E fuel element. All elements of this test will contain enriched uranium, 0.947 w/o U-235, fuel cores. All elements will be self-supported.

b. Dimensions

Nominal dimensions in inches for elements used in this test are:

	Bare Core			Finished Element		
	O. D.	I. D.	Length	O. D.	I. D.	Length
Hot-Die-Sized	1.432	0.437	6.600	1.494	0.375	7.034
Al-Si	1.406	0.488	6.053	1.494	0.375	6.593

c. Fabrication

The process specifications document² presents the detailed fabrication procedures for the hot-die-sized fuel elements. All Al-Si elements will

² Schweikhardt, G. M. Provisional Specifications for Hot-Die-Sizing Process, HW-77683. July 15, 1963. (SECRET)

~~REFURBISHED~~

HW-78960
Page 5

be fabricated according to the "F" process³ and shall meet all fabrication and quality specifications in effect at the time of fabrication. Aluminum components will be of 8001-F alloy; all fuel element cores will be of enriched uranium, 0.947 w/o U-235, fabricated by the ingot process.

d. Self-Supports

All supports used on elements of this test will be fabricated in accordance with Drawing H-3-7950 Revision 10 as specified for CIVES fuel elements. Placement of the supports on the fuel elements will be as specified on the same drawing. The supports are to be attached by ultrasonic welding techniques in accordance with the ultrasonic welding specifications.⁴

Minimum attached support heights for both element types will be 0.082 inches; the maximum circumscribed support circle will be 1.666 inches for all elements of this test.

e. Quantity

This test requires 266 hot-die-sized elements and 266 Al-Si elements. Approximately ten spare elements of each type will be supplied with the test columns.

f. Column Make-up

All fuel columns of this test will contain 14 hot-die-sized elements and 14 Al-Si elements. These element types are to be alternated in the fuel column positions. Ten fuel columns shall contain in the downstream half of the column, positions 1 through 14, seven "pairs" of elements, a pair consisting of an Al-Si element and a hot-die-sized element whose cores came from adjacent positions in the uranium ingot rod. The remainder of the column will contain hot-die-sized and Al-Si elements in alternate positions.

Nine fuel columns will contain Al-Si and hot-die-sized elements, in alternate positions, in the downstream half whose cores are from the same ingot rod, but not from adjacent rod positions. The upstream half of the columns will contain hot-die-sized and Al-Si elements in alternate positions.

All elements of this test will be identified as to position number within the fuel column, number one piece being downstream, and a series number will identify each fuel column. These identifying numbers will be stamped on the base end of the fuel element. All spare pieces will also be identified by numbers stamped on the base end.

³ Process Specifications, Fuel Element Manufacturing Processes, HW-47029.
(CONFIDENTIAL)

⁴ Stringer, J. T. Provisional Process Specifications for the Attachment of Projection Rails by Ultrasonic Spot Welding, HW-69886 REV2. December 3, 1962.
(CONFIDENTIAL)

DECLASSIFIED

HW-78960
Page 6

g. Pre-Irradiation Testing and Measurements

In addition to all the normal quality tests and measurements, all fuel elements of this test will have O.D. and I.D. at the three standard locations, warp-ellipticity, and length measurements recorded. The weight of all fuel elements in column positions 1 through 14 will be recorded; the weight of all fuel elements in column positions 27 and 28 will be recorded.

3. Process Tubes

Regular size, smooth-bore, Zircaloy-2 process tubes will be utilized in this test. Eighteen of the 69 tubes of this type in C Reactor are now in use with irradiation of natural uranium hot-die-sized elements and are unavailable for use with this test.

Since the elements of this test contain enriched uranium, they will be charged into tubes located on the far side of the reactor, to avoid problems associated with the overbore tube pattern on the near side of the reactor.

The test author, assigned Process Engineer, and assigned Pile Physicist, with the concurrence of the Manager, C Processing, will select the specific tubes for this test.

4. Irradiation

a. Charging

All test columns will be hand-charged in numerical sequence, number one piece being downstream. Each column series number will be recorded as to the tube into which it was charged. The location and number of any spare pieces used will be recorded. The charging will be monitored by a representative of Research and Engineering.

This test authorizes discharge of up to 19 subgoal fuel columns to permit charging of test fuel columns.

b. Downstream Dummy Pattern

The downstream dummy pattern for tubes of this test will be modified to position the center of the fuel charge about one element further upstream than the normal fuel columns. The downstream dummy pattern will contain, in addition to the normal thirteen 8-inch and one 5-inch perforated aluminum spacers, seven 8-inch spacers.

c. Operating Limits

The operating conditions and limits that apply to the CIVNS fuel element geometry will be applicable to this test material.* Existing process standards will be used as the basis for all operating conditions and limits.

*Personal communication with P. A. Carlson.

~~DECLASSIFIED~~

HW-78960
Page 7

d. Operating Conditions

Expected operating conditions for the fuel columns of this test, as calculated by MOFDA*, are listed below. The parameters, as calculated by the program for CIIN and CIIIIE fuel elements, are also listed.

<u>Fuel Type</u>	<u>Fuel Elements per Column</u>	<u>Tube Flow gpm</u>	<u>Tube At C</u>	<u>Tube Power kw</u>	<u>Average Specific Power kw/ft</u>
CIIN	32	50.2	90.9	1205	68.6
CIIIIE	32	56.5	85.1	1268	82.8
Hot-Die-Sized	28	52.1	95.2	1308	88.8

The hot-die-sized fuel columns will be operating at about 108 per cent of the calculated CIIN tube power and at about 103 per cent of the calculated CIIIIE tube power.

e. Water Shut-Off Time

Chart I gives the water shut-off times, time to reach boiling, for the fuel columns of this test.

f. Data

Daily flow and temperature data for the tubes of this test will be recorded on data sheets provided by the test authors.

g. Goal Exposure

All fuel columns of this test will be scheduled for discharge at average tube exposures of 1000 Mwd/t. Changes in this goal exposure plan may be made by the test author with the concurrence of the Manager, C Processing.

h. Discharge

All fuel columns of this test will require special pickup after discharge and subsequent shipment to the 105-C Metal Examination Facility. No more than four columns of metal may be combined in one bucket.

No fuel element failures are anticipated in this test, should a failure occur, the disposition of the remaining columns will require the concurrence of the Manager, C Processing.

* MOFDA - An integrated physics and engineering fuel design program, by R. O. Gumprecht.

5. General

a. Schedule

Elements for this test have been fabricated and are now ready for reactor use. The charging of the elements of this test will take place at the first outage of C Reactor following approval of this test.

b. Duration

The elements are expected to complete their irradiation period in approximately four months from the time of charging. This test authorization will expire on December 31, 1964.

c. Post-Irradiation Examination

All fuel elements of this test will receive the normal post-irradiation visual and dimensional measurements in the 105-C Metal Examination Facility. Weights of those elements that had been weighed before irradiation are required. Selected elements may require additional measurements as requested by the test author. Upon completion of the post-irradiation measurements, all fuel elements of this test are to be retained by the Metal Examination Facility until released by the test author. Elements of special interest may be sent to the Radiometallurgy Laboratory for destructive examination.

d. Costs

The outage time lost as a direct result of this test may be charged to cost code XXXX-5R23-XXX.71. Anticipated times required for charging and special pickup are:

Charging - 15 min/tube	5 hours total
Special Pickup - 10 min/tube	3 hours total

e. Hazards

The fuel elements of this test contain cores enriched to 0.947 w/o U-235. The normal precautions exercised in handling fuel elements enriched to this level must be exercised with the elements of this test. Although the elements of this test are somewhat larger in diameter and in length than any currently used enriched fuel elements, they (the elements of this test) are less reactive than the KIVE on which the nuclear safety specifications are based. The basis, therefore, for transporting and storing unirradiated enriched fuel elements will apply for the elements of this test. The critical mass per unit area of 420 lb. per square foot, or 63 fuel elements per square foot, should under no circumstances be exceeded.

The storage of irradiated elements of this test is governed by the requirements of this test--no more than four fuel columns, 112 elements, per storage bucket. Requirements for shipment of irradiated elements of this test will be provided by Process and Reactor Development and approved by Process Technology.*

*Personal communication with H. Toffer.

~~DECLASSIFIED~~

HW-78960

Page 9

RESPONSIBILITIES

1. Production Fuels Section will be responsible for canning, finishing, testing, quality control, and pre-irradiation measurements of fuel elements used in this test.
2. Research and Engineering
 - a. Process and Reactor Development Subsection will be responsible for over-all coordination of the test, reporting in-reactor performance of test material, and analysis of the reactor operating data.
 - b. Process Technology Subsection will be responsible for providing assistance to both Processing Operation and Process and Reactor Development Subsection in pre-shutdown scheduling, for forwarding operating data to the authors, and for specification of operating limits.
 - c. Operational Physics Subsection will be responsible for making reactivity adjustments as required by this test.
 - d. Testing Subsection will be responsible for post-irradiation fuel element examination and measurement.
3. Manufacturing Section
 - a. Production Scheduling will be responsible for maintaining accurate records of material charged under this program and for scheduling discharge of the test columns.
 - b. C Processing Operation will be responsible for operational safety and production continuity of the reactor, for charging and special pickup of the test material, and for recording data as requested.

K. L. Hladek

K. L. Hladek, Engineer
Reactor Engineering Unit
Process and Reactor Development
Research and Engineering Section

KLH:go




CHART 1
WATER SHUT OFF TIMES TO BOILING
TWENTY EIGHT CDB2E FUEL ELEMENTS

HW-78960
Page 10

DECLASSIFIED


~~DECLASSIFIED~~

HW-78960
Page 11


APPROVALS




T. W. Ambrose, Manager
Process and Reactor Development
Research and Engineering Section




R. W. Reid, Manager
Process Technology
Research and Engineering Section




G. C. Fullmer, Manager
Operational Physics
Research and Engineering Section




C. G. Lewis, Manager
Testing
Research and Engineering Section




O. H. Greager, Manager
RESEARCH AND ENGINEERING SECTION




R. E. Dunn, Manager
C Processing Operation
BC Reactor Subsection
Manufacturing Section



W. J. Ferguson, Manager
BC Reactor Subsection
Manufacturing Section




E. R. Astley, Manager
Applied Reactor Engineering
Manufacturing Section




C. A. Priode, Manager
Production Subsection
Manufacturing Section



O. C. Schroeder, Manager
MANUFACTURING SECTION



J. T. Stringer, Manager
Fuels Engineering Subsection
Production Fuels Section



for W. M. Mobley, Manager
PRODUCTION FUELS SECTION

9-27-63 pm

DATE
FILED

6/16/94

