

HW-68855

Cover Sheet for a Hanford Historical Document Released for Public Availability

Released 1994

**Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute**



REC'D

MAY 04 1994

100-71

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This is a **historical document** that is being released for public availability. This was made from the best available copy. Neither the United States Government nor any agency thereof, nor Battelle Memorial Institute, nor any of their employees, makes **any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights.** The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DECLASSIFIED

DOCUMENT NO.

HW-68855

C-65

SERIES AND COPY NO.

GENERAL ELECTRIC

INFORD ATOMIC PRODUCTS OPERATION - RICHLAND, WASHINGTON

RESTRICTED DATA
THIS DOCUMENT CONTAINS RESTRICTED DATA AS
DEFINED IN THE ATOMIC ENERGY ACT OF 1954.
IT IS A VIOLATION OF THE LAW TO TRANSMIT OR
DISCLOSE THIS INFORMATION IN ANY MANNER TO UNAUTHORIZED
PERSONS. IT IS PROHIBITED.

PRODUCTION TEST IP-401-A: IRRADIATION
OF ZIRCALOY-2 JACKETED UO₂ TUBULAR
ELEMENTS IN THE KER LOOPS

OTHER OFFICIAL CLASSIFIED INFORMATION

THIS MATERIAL CONTAINS INFORMATION AFFECTING
THE NATIONAL DEFENSE OF THE UNITED STATES
WITHIN THE MEANING OF THE ESPIONAGE LAWS,
TITLE 18, U. S. C., SECS. 793 AND 794, THE TRANS-
MISSION OR REVELATION OF WHICH IN ANY MANNER
TO AN UNAUTHORIZED PERSON IS PROHIBITED BY
LAW.

AUTHOR

W. K. Kratzer

CIRCULATING COPY
RECEIVED 100D AREA

APR 11 1961

RETURN TO

THIS DOCUMENT MUST NOT BE LEFT UNATTENDED OR WHEN AN UNAUTHORIZED PERSON MAY HAVE ACCESSED TO IT WHEN NOT IN USE, IT MUST BE STORED IN AN APPROVED LOCKER DEPOSITORY WITHIN A SECURED GUARDED AREA, WHILE IT IS IN YOUR POSSESSION AND UNTIL YOU HAVE OBTAINED A SIGNED RECEIPT FROM A CLASSIFIED PERSON, IT IS YOUR RESPONSIBILITY TO KEEP IT UNDER ITS CONTROL WITHIN THE LINES OF THIS PROJECT AND FROM UNAUTHORIZED PERSONS. ITS TRANSMISSION TO AND STORAGE AT YOUR PLACE OF RESIDENCE IS PROHIBITED. IT IS NOT TO BE DUPLICATED. IF ADDITIONAL COPIES ARE REQUIRED, OBTAIN THEM FROM A RELATED ISSUING FUNCTION. ALL PERSONS READING THIS DOCUMENT ARE REQUIRED TO SIGN IN THE SPACES PROVIDED BELOW.

ROUTE TO:	PAYROLL NO.	LOCATION	FILES ROUTE DATE	SIGNATURE AND DATE
Ed Evans	13097	325	APR 12 1961	Ed Evans
H. R. Klemm	20525	325	APR 20 1961	HRK
Don for	60008	703	MAY 2 1961	
R.W. Johnson	54182	103	MAY 3 1961	
R.F. Johnson	51539	105KW	7-5-61	

DECLASSIFIED

DECLASSIFIED

HW-68855
Page 1

DISTRIBUTION

1-2. AEC-HOO: RL Plum	29. LE Kusler
3. AEC-HOO: PM Midkiff	30. GA Last
4. FW Albaugh	31. CG Lewis
5. GS Allison	32. NR Miller
6. TW Ambrose	33. MK Millholen
7. ER Astley	34. JE Minor
8. GR Bailey	35. SL Nelson
9. LV Barker	36. R Nilson
10. RS Bell	37. WA Oldham
11. WA Blanton	38. RE Olson
12. RW Bown	39. GF Owsley
13. JH Brown	40. CA Priode
14. JJ Cadwell	41. T Prudich
Classification Cancelled and Changed To RL Call/GT Geering	42. RW Reid
DECLASSIFIED	43. OC Schroeder
15. WA Crossman	44. RD Shimer
16. DR Dickinson	45. WR Smit
17. EA Evans	46. HG Spencer
18. G Fiorelli	47. JT Stringer
WA Snyder, 2-20-64	48. RE Trumble
IM Fouts	49. FW VanWormer
By Gert Malen 3-15-64	50. EE Weyerts
Fullmer	51. FW Woodfield
SM Gill	52. HM Woods
3-16-64	53. 300 Files
23. SM Graves	54. Records Center
24. OH Greager	
25. RE Hall	
26. AK Hardin	
27. PC Jerman	
28. WK Kratzer	

This document contains restricted data as defined in the Atomic Energy Act of 1954. Its transmission, or the disclosure of its contents in any manner to any unauthorized person is prohibited.

This document classified by

FW Ambrose

This document consists of

March 16, 1961

IRRADIATION PROCESSING DEPARTMENT

DECLASSIFIED

HW-68855
Page 2

PRODUCTION TEST IP-401-A:
IRRADIATION OF ZIRCALOY-2 JACKETED UO₂ TUBULAR ELEMENTS
IN THE KER LOOPS

OBJECTIVE

The objective of this production test is to evaluate the behavior of large diameter tubular UO₂ fuel elements during high temperature irradiation.

SUMMARY

Eighteen inch long tubular UO₂ fuel elements 1.804 inch OD, 0.544 inch ID, in 0.060 inch Zircaloy-2 jackets will be irradiated in the KER loops either alone or in conjunction with other tests to exposures up to 3500 MWD/T of contained uranium.

BASIS AND JUSTIFICATION

Zircaloy-2 jacketed UO₂ fuel elements have potential application in N Reactor for phase III (power only) operation. Appreciable irradiation experience has been obtained from UO₂ elements in rod form and from tubular elements with thin fuel cross-sections irradiated in the vertical position. No experience, however, is available for tubular elements with 1/2 inch thick fuel cross-sections or for tubular elements irradiated in the horizontal position. Since a phase III tubular UO₂ fuel element would probably require thick fuel sections and would obviously be irradiated in the horizontal position, irradiation of the fuel elements authorized by this production test will provide information otherwise not available for evaluating UO₂ fuel element behavior.

TEST DETAILS

1. Fuel Elements

The fuel element dimensions are:

OD	- 1.804 inches
ID	- 0.544 inch
Length	- 18 inches
Zr-2 Jacket Thickness	- 0.060 inch
End Cap Thickness	- 3/16 inch

The fuel consists of sintered UO₂ prepared from natural uranium. After fusion welding one cap to the jacket in a helium atmosphere, powdered UO₂ was compacted in the jacket by vibration to 88% theoretical density for UO₂. The other cap was then fusion welded in place. The assembled elements have been helium leak tested, X-rayed for weld soundness, and autoclaved in steam for seventy-two hours at 400°C and 1500 psig.

Semi-flexible Zr-2 supports were spot welded to the jacket at each end. Fuel element details are shown in Figure 1.

MASTER

DECLASSIFIED

HW-68855
Page 3

2. Loading

The tube loading will be given in a document approved by Process Technology Operation and Process and Reactor Development Operation prior to charging. Coupon holders of a design approved by Coolant Testing Operation and Process and Reactor Development Operation may be included in the charge in positions not affecting the fuel element test.

3. Irradiation Facility

The fuel elements may be irradiated in any KER high temperature recirculating loop with a nominal 2.028 inch process tube ID.

4. Operating Conditions

The coolant will be pressurized water with the pH adjusted to 10.0 ± 0.5 by the addition of LiOH. The low pressure trip will be set at 1500 psig. For a charge in loops 2, 3, or 4, the desired operating flow is 60 gpm with a low flow trip of 48 gpm. For a charge in loop 1, the desired operating flow is 50 gpm with a low flow trip of 40 gpm. The high outlet temperature trip, maximum operating outlet temperature, desired operating outlet temperature (which can be varied at the discretion of the test author as long as it does not exceed the maximum operating outlet temperature), and boiling point suppression trip will be given for each loading in a document approved by Process Technology Operation and Process and Reactor Development Operation prior to charging.

If recirculation with system pressures less than 1500 psig is required, the outlet temperature will be reduced and maintained at a temperature such that fuel surface temperatures will be less than the coolant saturation temperature and local channeled coolant temperatures are sufficiently below the coolant saturation temperature to preclude subcooled burnout.

5. Power and Temperature Limits

The operating conditions will be chosen so that surface boiling will not occur on the fuel elements during normal operation, burnout will not occur at the limiting trip conditions, and the jacket-fuel interface temperature will not exceed 450°C . The maximum UO_2 temperature, although not precisely known, will probably not exceed 2500°C .

6. Exposure

The maximum exposure authorized by this production test is 3500 MWD/T of contained uranium.

7. Special Procedures

The fuel elements from this production test may be discharged into a special tray according to procedures developed by the KE Maintenance Operation, depending upon the discharge requirements for the fuel irradiated in conjunction with this test.

DECLASSIFIED

HW-68855
Page 4

8. Priority

Additional down-time is authorized if charging or discharging cannot be accomplished during a normal outage.

9. Costs

a. Cost Code: XXX-5R24-XXX.75
b. Time for each loading:

	<u>Elevator Time, Hours</u>		<u>Manhours</u>
	<u>Front</u>	<u>Rear</u>	
Charge	1	1	4
Discharge	2	4	10
	3	5	14

c. Reactivity Change: The test loading will have a reactivity intermediate between that of a dummy charge and a standard charge of normal fuel elements.

10. Data Desired

Routine operating data, including coolant flow, inlet and outlet temperature and pressure, system pressure, and operating time at temperature, will be taken during irradiation.

11. Hazards

The risk of process tube or reactor damage in the event of a fuel element failure is negligible with the UO₂ element since, with the sensitivity of the KER loop failure detection system and the rapidity of shutdown following detection, there should be no fuel element swelling or distortion as the result of failure.

RESPONSIBILITIES

Hanford Laboratories Operation

Reactor and Fuel Research and Development Operation

Fuels Development Operation

Ceramic Fuels Development Operation is responsible for fuel element fabrication, fuel evaluation, analysis of data, and issuance of technical reports.

Irradiation Processing Department

Research and Engineering Operation

Component Testing Operation is responsible for post-irradiation examination and testing of components in the test charge.

DECLASSIFIED

HW-68855
Page 5

Coolant Testing Operation is responsible for:

- a. Operation of the KER loops.
- b. Taking basic operating data.
- c. Scheduling the loop charge with the concurrence of KE Processing Operation.
- d. Reactor safety and production continuity as they are affected by loop Operation.

Process and Reactor Development Operation is responsible for:

- a. Technical aspects of the fuel element irradiation, including effect of the fuel elements on reactor safety.
- b. Termination of the production test and issuance of the final report.

KE-KW Reactor Operation

KE Processing Operation is responsible for:

- a. Operational safety.
- b. Production continuity, except where inconsistent with provisions of this test.
- c. Special discharges.



W. K. Kratzer
Process and Reactor Development Subsection
RESEARCH AND ENGINEERING SECTION

WKK:kmn

UNCLASSIFIED

DECLASSIFIED

HW -68855
Page 6




FIGURE I
Zircaloy-2 Jacketed Tubular UO₂ Element

DECLASSIFIED

HW-68855
Page 7

APPROVALS

J. H. Brown

J. H. Brown, Manager
Process and Reactor Development Subsection
RESEARCH AND ENGINEERING SECTION

R. W. Reid

R. W. Reid, Manager
Process Technology Subsection
RESEARCH AND ENGINEERING SECTION

C. G. Lewis

C. G. Lewis, Manager
Testing Subsection
RESEARCH AND ENGINEERING SECTION

O. H. Greager

O. H. Greager, Manager
RESEARCH AND ENGINEERING SECTION

S. L. Nelson for

S. L. Nelson, Manager
KE Processing Operation
MANUFACTURING SECTION

R. S. Bell

R. S. Bell, Manager
KE-KW Reactor Subsection
MANUFACTURING SECTION

E. R. Astley for

E. R. Astley, Manager
Applied Reactor Engineering Subsection
MANUFACTURING SECTION

O. C. Schreeder

O. C. Schreeder, Manager
MANUFACTURING SECTION

100-1394

100-1394
FILED
DATE