




**AIIM**


**Association for Information and Image Management**

1100 Wayne Avenue, Suite 1100  
Silver Spring, Maryland 20910  
301/587-8202

**Centimeter**



**Inches**



MANUFACTURED TO AIIM STANDARDS  
BY APPLIED IMAGE, INC.

1 of 1

**NOTICE**

**CERTAIN DATA  
CONTAINED IN THIS  
DOCUMENT MAY BE  
DIFFICULT TO READ  
IN MICROFICHE  
PRODUCTS.**

**DECLASSIFIED**

1-20 AEC-HOO Att: AT Gifford  
30 ABC-HOO: Att: PM Midkiff  
40 FW Albaugh  
50 WK Alexander  
60 GS Allison  
70 JA Ayres  
80 RS Bell  
90 WA Blanton  
100 RW Bown  
110 JH Brown  
120 SH Bush  
130 JJ Cadwell  
140 JL Call  
150 AC Callen  
160 TL Deobald  
170 RL Dickeman  
180 DR Dickinson  
190 RV Dulin  
200 JM Fouts  
210 FC Franklin  
220 GC Fullmer  
230 SM Gill  
240 OH Greager  
250 RE Hall  
260 TM Hall  
270 ME Jackson  
280 PC Jerman

290 CH Jones  
300 WK Kratzer  
310 GA Last  
320 HE Leitz  
330 CG Lewis  
340 NR Miller  
350 JE Minor  
360 JW Music  
370 WI Neef  
380 SL Nelson  
390 B Nilson  
400 GF Owsley  
410 CA Priode/WG Alber  
420 T Prudich/RE McGrath  
430 RW Reid  
440 RJ Shields  
450 HG Spencer  
460 JT Stringer  
470 WL Swanson  
480 JW Talbott  
490 B Thompson  
500 RE Trumble  
510 LD Turner  
520 JW Van Wormer  
530 FW Woodfield  
540 300 Files  
550 Record Copy

Classification: **DECLASSIFIED**  
Date: **4-21-94**  
By: **DR. S. Lewis**  
Reviewed: **DR. J. W. Malley**  
Approved: **DR. M. K. Hansen**

COPY 1 OF 1, SERIES MA

This document consists of  
6 pages.

This document classified by

October 16, 1959

PRODUCTION TEST IP-288-A, EVALUATION OF SEVEN-ROD  
CLUSTER ELEMENTS WITH MODIFIED END CLOSURES

OBJECTIVE

The objective of this production test is to obtain irradiation experience with the hot-headed closure for co-extruded Zircaloy-2 jacketed rods.

SUMMARY

Seven Zircaloy-2 jacketed natural uranium seven-rod cluster elements with hot-headed end closures and spark machined end supports will be irradiated in the KER Loops to an exposure of 2000 MWD/T in pH 8-11 coolant.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

**DECLASSIFIED**

**MASTER**

04/20/1994

# DECLASSIFIED

HW-62416  
Page 2

## BASIS AND JUSTIFICATION

The hot-headed end closure<sup>(1)</sup> on co-extruded Zircaloy-2 jacketed rods provides a closure in which the jacket is bonded over most of the end of the rod and two welds are employed between the uranium and the coolant. In contrast, the current end closure method uses an unbonded end cap and a single weld. This test will provide the initial irradiation of fuel element rods with the hot-headed closure. The method is being adapted to tubular elements, but has not been developed far enough for irradiation testing.

## TEST DETAILS

### 1. Fuel Elements

The fuel elements consist of seven 0.593 inch diameter rods with 0.020 inch thick Zircaloy-2 jackets arranged in the form of a cluster with 0.078 inch clearance between rods. Each rod contains 11.9 inches of uranium. The overall cluster length is 1200 inches. The rods are supported at the ends by spark machined Zircaloy-2 spiders. Details of the element are shown in SK-3-8912.

Steps in the fabrication of the elements from the co-extruded rod include:

- a. Cutting the rod to length (~12 inches).
- b. Extrusion heading the rods to form the jacket over both ends.
- c. Beta heat treatment in the vertical position.
- d. Chemical removal of copper and lubricant from the rods and vapor blast cleaning.
- e. Machining extrusions from rod ends.
- f. Ring projection welding the caps to rod ends.
- g. Ultrasonic bond testing.
- h. Pickling in citric - 1/4 HFO.
- i. Autoclaving in 400°C, 1500 psi steam for 12 hours.
- j. Electron beam fusion welding caps to jackets.
- k. Autoclaving in 400°C, 1500 psi steam for 48 hours.
- l. Welding to end spiders.
- m. Autoclaving 400°C, 1500 psi steam for 12 hours.

### 2. Loading

The loading shall consist of thirty downstream eight-inch spacer elements, seven seven-rod cluster elements, and up to sixteen eight-inch spacer elements upstream. Coupon holders of a design approved by Coolant Testing Operation and Process and Reactor Development Operation may be substituted for any of the eight-inch spacers except those adjacent to the cluster elements.

### 3. Irradiation Facility

The fuel elements may be irradiated in any of the high temperature recirculating KER Loops with a 2.020 inch ID process tube.

(1) Allison, G.S., P. A. Ard, and W. L. Wyman, "A Process for Nuclear Fuel Element End Closures," HW-61233, June 23, 1959. (Confidential-Undocumented).

**DECLASSIFIED**

HW-62416  
Page 3

**TEST DETAILS (cont'd)**

**4. Operating Conditions**

The coolant will be pressurized water with the pH adjusted to 8.0 to 11.0 by the addition of Li OH. The desired operating flow is 60 gpm with a low flow trip of 48 gpm. The low pressure trip will be set at 1500 psig. The desired operating outlet temperature, high outlet temperature trip, and boiling point suppression trip are given in Figure 1.

If recirculation with system pressures less than 1500 psig is required, the outlet temperature will be reduced and maintained at least 100°C below the system saturation temperature.

**5. Power and Temperature Limits**

The operating conditions have been chosen so that surface boiling will not occur on the fuel elements during normal operation, without will not occur at the lightning trip conditions, and the maximum outlet temperature will not exceed 660°C.

**6. Exposure**

The maximum exposure authorized by this production test is 2000 RWD/2 for the seven fuel cluster elements.

**7. Special Procedures**

The fuel elements from this production test will be discharged into a special tray to avoid damage resulting from their fall to the basin. A detailed discharge procedure approved by Processing, Irradiation and Coolant Testing operation will be issued prior to discharge.

**8. Priority**

Additional down-time is authorized if changing or discharging cannot be accomplished during a normal outage.

**9. Costs**

a. Cost Code - XXX.5320-XXX.09

b. Time

	<u>Elevator Time, Hours</u>		<u>Manhours</u>
	<u>Front</u>	<u>Rear</u>	
Charge	1	1	4
Discharge	2	4	10
	<u>3</u>	<u>5</u>	<u>14</u>

**10. Data Desired**

Routine operating data, including coolant flow, inlet and outlet temperature and pressure, system pressure, and operating time at temperature, will be taken during irradiation.

**11. Hazards**

The cluster elements authorized by this production test incorporate a new closure which has not been previously irradiation tested. Although the closure modification

# DECLASSIFIED

HW-62416

Page 4

is intended to produce a weld and end cap less susceptible to failure than those used in previous cluster element irradiations, there is always the possibility that the untried closure will fail. Detection and characterization of such operational difficulties is the basic purpose of this test.

The geometry, fabrication (other than end caps and welds), and testing procedures of the fuel elements in this test were sufficiently similar to those of previous cluster element tests to give no basis to assume that the probability of failure or severity of failure will be any different for these elements than for other seven-rod cluster elements that have been irradiated.

## 2. Deviation from Process Standards

This production test authorizes deviation from process standard K-050, Section 40001, which limits the maximum uranium temperature to 600°C. Uranium temperatures up to 660°C may occur at maximum tube power conditions, although the anticipated maximum uranium temperature will be less than 600°C.

## RESPONSIBILITIES

### 1. Laboratories Operation

#### Reactor and Fuels Research and Development Operation

##### Fuel Development Operation

Fuel Fabrication Development is responsible for the fabrication of the cluster elements, analysis of data, and issuance of technical reports.

### Irradiation Processing Department

#### Research and Engineering Operation

Component Testing Operation is responsible for post-irradiation examination and testing of components in the test charge.

#### Coolant Testing Operation is responsible for:

- a. Operation of the KER Loops.
- b. Taking basic operating data.
- c. Scheduling the loop charge with the concurrence of KE Processing Operation.
- d. Reactor safety and production continuity as they are affected by loop operation.

#### Process and Reactor Development Operation is responsible for:

- a. Technical aspects of the fuel element irradiation.
- b. Termination of the production test and issuance of the final report.

### KE-KW Reactor Operation

#### KE Processing Operation is responsible for:

- a. Operational safety.
- b. Production continuity, except where inconsistent with provisions of this test.
- c. Special discharges.

*W. J. Kratzer*  
Reactor Fuels Unit

Process and Reactor Development Sub-  
IRRADIATION PROCESSING DEPARTMENT


WJ Kratzer:gb

**DECLASSIFIED**

EW 624:6  
Page 5

Figure 1

Operating temperatures and trip settings  
as a function of the observed tube  $\Delta T$



**DECLASSIFIED**

HW-62416  
Page 6

**APPROVALS**

J. H. Brown J. H. Brown, Manager  
Process and Reactor Development  
IRRADIATION PROCESSING DEPARTMENT

J. F. Music J. F. Music, Manager  
Process Technology  
IRRADIATION PROCESSING DEPARTMENT

C. G. Lewis C. G. Lewis, Manager  
Testing Operation  
IRRADIATION PROCESSING DEPARTMENT

O. H. Greager O. H. Greager, Manager  
Research and Engineering  
IRRADIATION PROCESSING DEPARTMENT

S. L. Nelson S. L. Nelson, Manager  
KE Processing Operation  
IRRADIATION PROCESSING DEPARTMENT

R. S. Bell R. S. Bell, Manager  
KE-KW Reactor Operation  
IRRADIATION PROCESSING DEPARTMENT

R. L. Dickeman R. L. Dickeman, Manager  
Manufacturing Section  
IRRADIATION PROCESSING DEPARTMENT

**DISCLAIMER**

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

**DATE  
FILMED**

**8/11/94**

**END**

