

REFERENCE COPY

NOT FOR CIRCULATION

MAY 26 1983

RECEIVED-ROCKWELL

DOCUMENT CONTROL

RHO-RE-CR-8 P

-201

Long-Term Effects of Waste Solutions on Concrete and Reinforcing Steel

J.I. Daniel

D.C. Stark

P.H. Kaar

Construction Technology Laboratories

Portland Cement Association

Skokie, Illinois 60076

REFERENCE COPY

**Prepared for Rockwell Hanford Operations,
a Prime Contractor to the
United States Department of Energy
Under Contract DE-AC06-77RL01030**

Approved for Public Release;

Further Dissemination Unlimited

J. D. Aardal 06/16/2011



Rockwell International

**Rockwell Hanford Operations
Energy Systems Group
Richland, WA 99352**



Rockwell International

Rockwell Hanford Operations

Energy Systems Group

Richland, WA 99352

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DOCUMENT CLEARANCE REQUEST (Do Not Use For Speeches And Articles)				Date	Identification No.
327				Bldg.	Phone No.
Rockwell Hanford Operations Review Approvals - DOE-RL		AUTHOR COMPLETES PART 1 AND SUBMITS WITH (2) COPIES OF DOCUMENT TO TECHNICAL INFORMATION SERVICES.			
Title LONG-TERM EFFECTS OF WASTE SOLUTIONS ON CONCRETE AND REINFORCING STEEL		Author(s) J. I. Daniel, D.C. Stark, P.H. Kaar			
Description <input type="checkbox"/> Quarterly <input type="checkbox"/> Monthly <input type="checkbox"/> Manual of Document: <input type="checkbox"/> Progress <input checked="" type="checkbox"/> Topical <input type="checkbox"/> Other		Final <input type="checkbox"/> Originating Organization <input type="checkbox"/> Other Preparation: <input checked="" type="checkbox"/> Tech. Info Services			
Distribution: <input type="checkbox"/> TID - 4500 Category (Unclassified Reports)		<input checked="" type="checkbox"/> Other (Specify) Attached			
DOES THIS DOCUMENT CONTAIN OR DISCLOSE ANY OF THE FOLLOWING? (If yes, identify the information and location of document)					
1. (A) Copyrighted Material? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes - Identify		(B) Has permission to use been granted? <input type="checkbox"/> No <input type="checkbox"/> Yes			
2. (A) New or Novel (Patentable) subject matter? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes - Identify		(B) Has disclosure been submitted by Rockwell or other company? <input type="checkbox"/> No <input type="checkbox"/> Yes - Identify			
3. Information received from a foreign country under an exchange agreement? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes - Identify		4. Information received from others in confidence, such as proprietary data, trade secrets and/or inventions? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes - Identify			
5. Is any further Technical/Policy review required? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes - Identify					
CERTIFICATION					
I have reviewed the attached document and certify the information contained therein is appropriate for release and distribution as specified above.					
Author <i>C. DeFigh-Piace</i> <input type="checkbox"/> Approved <input checked="" type="checkbox"/> Disapproved		Supervisor <i>B.N. Anderson</i> <input type="checkbox"/> Approved <input checked="" type="checkbox"/> Disapproved	Manager <i>K.A. Gasper</i> <input type="checkbox"/> Approved <input checked="" type="checkbox"/> Disapproved	Date <i>Feb 10, 1983</i>	
Program Office <input checked="" type="checkbox"/> Approved <input type="checkbox"/> Disapproved		Classification <input checked="" type="checkbox"/> Unclassified <input type="checkbox"/> Classified	Date: <i>3/10/83</i>		
REVIEW APPROVALS ROCKWELL HANFORD OPERATIONS					
REVIEW APPROVALS DOE-RL					
Legal (Including Patent and Copyright)					
Patents					
Signed <i>Robert H. Johnson</i> <input type="checkbox"/> Approved <input checked="" type="checkbox"/> Disapproved		Signed <i>Robert H. Johnson</i> <input type="checkbox"/> Approved <input checked="" type="checkbox"/> Disapproved			
For Rockwell Hanford Operations Date <i>3-2-83</i>		For DOE Date <i>3/11/83</i>			
PUBLIC RELATIONS					
Signed <i>H.B. Linley</i> <input type="checkbox"/> Approved <input checked="" type="checkbox"/> Disapproved		Signed <i>John J. Decker</i> <input type="checkbox"/> Approved <input checked="" type="checkbox"/> Disapproved			
For Rockwell Hanford Operations Date <i>2-28-83</i>		For DOE Date <i>3/11/83</i>			
POLICY AND PROGRAM					
Signed <i>John J. Decker</i> <input type="checkbox"/> Approved <input checked="" type="checkbox"/> Disapproved		Signed <i>John J. Decker</i> <input type="checkbox"/> Approved <input checked="" type="checkbox"/> Disapproved			
For Rockwell Hanford Operations Date <i>2-28-83</i>		For DOE Date <i>3/11/83</i>			
OTHER (Specify)					
<input type="checkbox"/> Approved <input type="checkbox"/> Disapproved		<input type="checkbox"/> Approved <input type="checkbox"/> Disapproved			
Signed <i>John J. Decker</i> <input type="checkbox"/> Approved <input checked="" type="checkbox"/> Disapproved		For DOE Date <i>3/11/83</i>			
Signed <i>John J. Decker</i> <input type="checkbox"/> Approved <input checked="" type="checkbox"/> Disapproved					
REMARKS					
<i>127 - 3 more Cummings, Gerton, Harris from RL distribution and Craig</i>					
<i>What is significance of temp? Why 180°F? why after exposure to 80°F? why? Does it simulate environment? Accelerate attack? why not corrosion by chemical exposure? Did temp have any effect? What does 36 months prove? Approved of this a good technical paper or just a report on a poorly designed test? Would like to know the author & find what was done before DOE saw it!</i>					
3100 DOCUMENT CONTROL USE ONLY					
Date Approval Received <i>3/10/83</i>	Date Received From Printing	Date Distributed	<input type="checkbox"/> Onsite	<input type="checkbox"/> Offsite	Date Report And 426 Form To TIC
DISTRIBUTION ON COMPLETION: Original to Document Control Pink & Goldenrod - To DOE-RL			Yellow - To Author Green - To Rockwell Pat Rep.		
BC-6100-514 (R-4-79)					

U.S. DEPARTMENT OF ENERGY

DOE AND MAJOR CONTRACTOR RECOMMENDATIONS FOR
ANNOUNCEMENT AND DISTRIBUTION OF DOCUMENTS

See Instructions on Reverse Side

1. DOE Report No. <u>RHO-RE-CR-8 P</u>	2. Contract No. <u>DE-AC06-77RL01030</u>	3. Subject Category No.
4. Title <u>Long-Term Effects of waste solutions on Concrete and Reinforcing Steel.</u>		
5. Type of Document ("x" one) <input checked="" type="checkbox"/> a. Scientific and technical report <input type="checkbox"/> b. Conference paper: Title of conference _____		
6. Date of conference _____		
Exact location of conference _____ Sponsoring organization _____		
<input type="checkbox"/> c. Other (specify planning, educational, impact, market, social, economic, thesis, translations, journal article manuscript, etc.)		
7. Copies Transmitted ("x" one or more) <input type="checkbox"/> a. Copies being transmitted for standard distribution by DOE-TIC. <input type="checkbox"/> b. Copies being transmitted for special distribution per attached complete address list. <input checked="" type="checkbox"/> c. Two completely legible, reproducible copies being transmitted to DOE-TIC. (Classified documents, see instructions) <input type="checkbox"/> d. Twenty-seven copies being transmitted to DOE-TIC for TIC processing and NTIS sales.		
8. Recommended Distribution ("x" one) <input type="checkbox"/> a. Normal handling (after patent clearance): no restraints on distribution except as may be required by the security classification. Make available only <input type="checkbox"/> b. To U.S. Government agencies and their contractors. <input type="checkbox"/> c. within DOE and to DOE contractors. <input type="checkbox"/> d. within DOE. <input type="checkbox"/> e. to those listed in item 13 below. <input type="checkbox"/> f. Other (Specify) _____		
9. Recommended Announcement ("x" one) <input checked="" type="checkbox"/> a. Normal procedure may be followed. <input type="checkbox"/> b. Recommend the following announcement limitations:		
10. Reason for Restrictions Recommended in 7 or 8 above. <input type="checkbox"/> a. Preliminary information. <input type="checkbox"/> b. Prepared primarily for internal use. <input type="checkbox"/> c. Other (Explain) _____		
11. Patent, Copyright and Proprietary Information Does this information product disclose any new equipment, process or material? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes If so, identify page nos. _____ Has an invention disclosure been submitted to DOE covering any aspect of this information product? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes If so, identify the DOE (or other) disclosure number and to whom the disclosure was submitted. Are there any patent-related objections to the release of this information product? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes If so, state these objections. Does this information product contain copyrighted material? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes If so, identify the page number _____ and attach the license or other authority for the government to reproduce. Does this information product contain proprietary information? <input checked="" type="checkbox"/> No <input type="checkbox"/> Yes If so, identify the page numbers _____. ("x" one <input checked="" type="checkbox"/> a. DOE patent clearance has been granted by responsible DOE patent group. <input type="checkbox"/> b. Document has been sent to responsible DOE patent group for clearance.		
12. National Security Information (For classified document only; "x" one) Document <input type="checkbox"/> a. does <input type="checkbox"/> b. does not contain national security information		
13. Copy Reproduction and Distribution Total number of copies reproduced _____ Number of copies distributed outside originating organization _____		
14. Additional Information or Remarks (Continue on separate sheet, if necessary)		

14. Submitted by (Name and Position) (Please print or type)

IP KNAPP, MANAGER, DOCUMENT CONTROL
ROCKWELL WENFORD OPERATIONS, RICHLAND, WA 99352

Organization

IP KNAPP, MANAGER, DOCUMENT CONTROLSignature ROCKWELL WENFORD OPERATIONS, RICHLAND, WA 99352

Date

PMI 5-12-83

LONG-TERM EFFECTS OF WASTE SOLUTIONS ON
CONCRETE AND REINFORCING STEEL

J. I. Daniel
D. C. Stark
P. H. Kaar

Construction Technology Laboratories
of the Portland Cement Association
Skokie, Illinois 60076

April 1982

Prepared for Rockwell Hanford Operations
a prime contractor to the United States
Department of Energy
Under Contract DE-AC06-77RL01030

Rockwell International
Rockwell Hanford Operations
Energy Systems Group
Richland, Washington 99352

EXECUTIVE SUMMARY

This report has been prepared for the In Situ Waste Disposal Program Tank Assessment Task (WG-11) as part of an investigation to evaluate the long-term performance of waste storage tanks at the Hanford Site. This report, prepared by the Portland Cement Association, presents the results of four years of concrete degradation studies which exposed concrete and reinforcing steel, under load and at 180°F, to simulated double-shell slurry, simulated salt cake solution, and a control solution. Exposure length varied from 3 months to 36 months. In all cases, examination of the concrete and reinforcing steel at the end of the exposure indicated there was no attack, i.e., no evidence of rusting, cracking, disruption of mill scale or loss of strength.

TABLE OF CONTENTS

INTRODUCTION	1
FINDINGS	2
DESCRIPTION OF TEST SOLUTIONS	2
DESCRIPTION OF SPECIMENS	5
TEST RESULTS	11
CONCLUDING REMARKS	25

FIGURES:

1. Compressive Specimen Under Load	7
2. Flexural Specimen Under Load	8
3. Load Application to Flexural Specimen	9
4. Load Application to Compressive Specimen	9
5. Load Adjustments Being Conducted During Exposure Test	10
6. Load Versus Strain Relationships of Reinforce- ment Before and After Exposure for Three Months to Simulated Salt Cake Solution	18
7. Load Versus Strain Relationships of Reinforce- ment Before and After Exposure for Six Months to Simulated Salt Cake Solution	19
8. Load Versus Strain Relationships of Reinforce- ment Before and After Exposure for 19 Months to Simulated Salt Cake Solution	20
9. Load Versus Strain Relationships of Reinforcement Before and After Exposure for 19 Months to Control Solution	21
10. Load Versus Strain Relationships of Reinforce- ment Before and After Exposure for 13 Months to Simulated Salt Cake Solution and 12 Months to Double-Shell Slurry Solution	22
11. Load Versus Strain Relationships of Reinforce- ment Before and After Exposure for 36 Months to Simulated Salt Cake Solution	23
12. Load Versus Strain Relationships of Reinforcement Before and After Exposure for 36 Months to Control Solution	24

TABLES:

1. Project Team	3
2. Breakdown of Performance	4
3. Test Solutions Compositions	5
4. Concrete Mix Design	6
5. Reinforcement Tensile Tests After Three Months Exposure to Simulated Salt Cake Solution	11
6. Reinforcement Tensile Tests After Six Months Exposure to Simulated Salt Cake Solution	12
7. Reinforcement Tensile Tests After 19 Months Exposure to Simulated Salt Cake Solution.	13
8. Reinforcement Tensile Tests After 19 Months Exposure to Control Solution	14
9. Reinforcement Tensile Tests After 13 Months Exposure to Simulated Salt Cake Solution and 12 Months Exposure to Double-Shell Slurry Solution	15
10. Reinforcement Tensile Tests After 36 Months Exposure to Simulated Salt Cake Solution	16
11. Reinforcement Tensile Tests After 36 Months Exposure to Control Solution.	17

INTRODUCTION

Radioactive waste resulting from the chemical processing of reactor fuel for recovery of special nuclear materials (primarily plutonium), has been accumulating at the Hanford Site since 1944. The defense waste is currently being stored in underground waste tanks and in capsules stored in water basins.

Current U.S. Department of Energy (DOE) strategy is to emphasize development and implementation of technology for removal, solidification, and final disposition of defense waste at the Savannah River Site first, then at the Hanford Site. Final disposal of waste in tanks at Hanford is expected to consist of in-place stabilization of most tanks. Selected tank wastes may be retrieved. Disposal operations will be carried out during the next several decades. Consequently, defense waste will remain in the existing underground tanks at Hanford for at least several decades.

To ensure the safe storage of the waste, the waste storage tanks are being evaluated for continued service as part of the DOE Waste Tank Evaluation Program (AR-005-10-02-G). Technical studies and laboratory tests have been conducted to determine the effect of the stored waste's chemicals and temperature on the reinforced concrete.

Waste solutions, which can be chemically aggressive, could come in contact with the reinforced concrete waste tank wall and bottom through breaches in the steel liner. Tests have been conducted to estimate the relative durability of reinforced concrete specimens exposed to two different simulated Hanford waste solutions. Results of these tests will be used as input to a comprehensive evaluation of the integrity of the single-shell tanks for continued storage of radioactive waste. The information is also applicable to the newer double-shell tank designs.

This work was performed by the Construction Technology Laboratories, a division of the Portland Cement Association in Skokie, Illinois for Rockwell Hanford Operations (Rockwell).

Scope

Service Agreement SA-469 of the Prime Contract DE-AC06-77RL01030 between Rockwell International Corporation and the Portland Cement Association contained the following statement of work:

"The CONTRACTOR shall, as requested by ROCKWELL, provide necessary personnel, labor, material, facilities, and equipment to conduct a research program to provide an estimate of the relative durability of reinforced concrete specimens exposed to a simulated Hanford waste solution. The program shall consist of exposing, testing, and evaluating the specimens developed and prepared under Rockwell Contract SA-256. The testing shall be conducted as a three-year and four-month program as outlined hereunder."

This final report describes the effects of two simulated Hanford waste solutions and one control solution on the relative durability of reinforced concrete specimens when subjected to elevated temperature and load.

A total of 21 reinforced concrete specimens were fabricated under Rockwell Contract SA-256 dated October 26, 1977. Twelve of these specimens were tested under Rockwell Contract SA-256. The remaining nine specimens were tested under Rockwell Contract SA-469 dated September 25, 1980.

Table 1 presents the project team, and Table 2 lists the breakdown of performance for work conducted under both contracts. As outlined in Rockwell Contract SA-469, specimens were exposed to three specific test solutions. They were simulated salt cake waste, control, and double-shell slurry. Specimen loading conditions consisted of 400 psi in compression, 10,000 psi in flexure, and 20,000 psi in flexure. Exposure periods varied from 3 to 36 months.

Objective

The objective of this project was to determine the effects of simulated waste solutions and control solutions on laboratory constructed specimens. Specimens represented wall sections of a waste storage tank. Test specimens were cast using aggregates from the same source as used for Hanford waste storage tanks. Reinforced concrete specimens, while exposed to the solutions, were placed in an oven at $180^{\circ}\text{F} \pm 10^{\circ}\text{F}$. Performance was evaluated by determining stress-strain characteristics of reinforcing steel, petrographic examination of concrete, and visual inspection of the reinforcing steel. 180°F was selected to represent a top concrete temperature for most waste tanks.

FINDINGS

In general, physical testing of the reinforcing bars extracted from all of the specimens indicated no effects of the test solutions under conditions of the test exposure. Petrographic examination of the concrete showed no evidence of adverse reactions between the solutions and the concrete or the steel. Solutions penetrated to the reinforcement in the flexural specimens during exposure. However, examination of the reinforcing steel indicated no evidence of rusting, cracking, or disruption of the mill scale initially on the steel.

DESCRIPTION OF TEST SOLUTIONS

Specimens were exposed to three test solutions for different periods of time as indicated in Table 2. The test solutions were simulated salt cake waste, control, and double-shell slurry. Composition of each test solution is given in Table 3.

TABLE 1. Project Team.

Research Executed By:	Structural Experimental Section Structural Development Department Engineering Development Division
Responsible Executive:	Walter E. Kunze Group Vice President Research and Development Construction Technology Laboratories
Project Management:	Donald M. Schultz Manager Structural Experimental Section
	Dr. Henry G. Russell/ Director Structural Development Department
Principal Investigator:	James I. Daniel Structural Engineer Structural Experimental Section
Co-Investigators:	David C. Stark Principal Research Petrographer Concrete Materials Research Department
	Paul H. Kaar Former Senior Structural Engineer Structural Development Department
Lead Technicians:	William Hummerich (Testing of Reinforcement) Assistant Laboratory Foreman Structural Experimental Section
	William H. Graves (Construction and Extraction) Senior Technician Structural Experimental Section
	Bernard J. Doepp (Exposure Control) Senior Technician Structural Experimental Section

TABLE 2. Breakdown of Performance.

Specimen exposure period (month)	Solution	Specimen loading condition (load type/stress, psi x 1,000)	Prime contributors	Completion date
3	W ^a	Compressive/0.5	P. H. Kaar	
3	W	Flexural/10	D. C. Stark	
3	W	Flexural/20		August 1978
6	W	Compressive/0.5	P. H. Kaar	
6	W	Flexural/10	D. C. Stark	
6	W	Flexural/20		May 1979
19	W	Compressive/0.5	P. H. Kaar	
19	W	Flexural/10	D. C. Stark	
19	W	Flexural/20		September 1980
19	C ^b	Compressive/0.5		
19	C	Flexural/10		
19	C	Flexural/20		
13	W	Compressive/0.5		
12	DSS ^c			
13	W	Flexural/10	J. I. Daniel	
12	DSS		D. C. Stark	
13	W	Flexural/20	P. H. Kaar	
12	DSS			
36	W	Compressive/0.5		
36	W	Flexural/10	D. M. Schultz	
36	W	Flexural/20		October 8, 1982
36	C	Compressive/0.5		
36	C	Flexural/10		
36	C	Flexural/20		

^aWaste.^bControl.^cDouble-shell slurry.

TABLE 3. Test Solutions Compositions.

Chemical	Simulated waste solution	Control solution	Double-shell slurry solution
Calcium hydroxide	None	Saturated	None
Sodium hydroxide	7N*		7.3N
Sodium nitrate	3N		6.0N
Sodium nitrite	3N		4.5N
Sodium aluminate	2N		4.3N
Sodium chloride	0.1N	None	None
Sodium carbonate	0.2N		0.7N
Sodium sulphate	0.5N		0.2N
Sodium fluoride	0.1N		None
Sodium phosphate	None		0.3N

*Normality concentration (7.0 normal).

Solutions were stored separately in covered steel tanks. Bottoms of the tanks were slotted parallel to the specimen axis. The 1-1/2-in.-long by 1/8-in.-wide slots were large enough to keep the top of the specimen moist. Tanks were sealed around the bottom periphery.

DESCRIPTION OF SPECIMENS

Reinforced concrete specimens were 36-in. long, 9-in. deep, and 12-in. wide. Each specimen was reinforced with three No. 4 deformed bars. Top and side concrete cover of reinforcement was 3-in. Concrete mix proportions and materials were specified by Rockwell Hanford Operations in Service Agreement SA-256. Specimens were fabricated using ASTM Designation: C150 Type II cement containing 7% to 8% calcium aluminate (C_3A). The concrete mix design is shown in Table 4. Cement and aggregate were supplied by Rockwell and are identical to that used in the actual waste tanks. Reinforcing steel embedded in each specimen was manufactured by Bethlehem Steel Corporation.

Concrete for specimens was mixed, placed, and cured under conditions described in ASTM Designation: C192, "Method of Making and Curing Concrete Compression and Flexure Test Specimens in the Laboratory." Specimens were cured for 28 days in a moist room at 73°F and 100% relative humidity. Subsequent to moist curing, specimens were placed in the laboratory at 73°F and 50% relative humidity until loading. Specimens were at least 44 days old when loads were applied.

TABLE 4. Concrete Mix Design.

Constituent	Quantity (lb/yd ³)
Cement	494
Sand	1,154
Gravel (3/4 in. max. size)	2,000
Water	267
Characteristics	
Water to cement ratio	0.54
Percent fine aggregate of total aggregate	36.6%
Percent air	4% to 5%

For each combination of exposure period and test solution, three specimens were loaded as indicated in Table 2. One specimen was maintained under sustained flexural loads. The uncracked compressive specimen was maintained at 500 psi compressive stress. Flexural specimens were loaded to cracking. After cracking, load was applied so that reinforcement stress was 10,000 psi in one specimen and 20,000 psi in the other. Loading apparatus and photographs of load application to compressive and flexural specimens are shown in Figures 1 through 4.

Loads required to produce the desired reinforcement stress in flexural specimens were calculated using sectional analysis based on measured material properties, equilibrium of forces, and strain compatibility. Loads were checked using a dummy specimen identical to test specimens but instrumented with strain gages on the reinforcement. After confirming that calculated loads were those necessary to obtain the desired stress, the dummy specimen was discarded. Strain gages were not used on reinforcement in test specimens.

All specimens were exposed to test solutions in an oven held at 180°F ± 10°F. Load on each specimen was adjusted several times to compensate for creep of specimens and relaxation of load apparatus. Figure 5 shows technicians adjusting loads.

Specimen Exposed to Double-Shell Slurry Solution

Specimens exposed to double-shell slurry solution were originally manufactured under Rockwell Contract SA-256. Under this contract, specimens were exposed for 13 months to the simulated salt cake solution. Upon receipt of Rockwell Contract SA-469, these specimens subsequently were exposed for 12 months to the double-shell slurry solution as indicated in Table 2.





FIGURE 1. Compressive Specimen Under Load.



RCP8207-51

FIGURE 2. Flexural Specimen Under Load.




FIGURE 3. Load Application to Flexural Specimen.



FIGURE 4. Load Application to Compressive Specimen.




FIGURE 5. Load Adjustments Being Conducted During Exposure Test.

TEST RESULTS

Tensile Tests of Reinforcing Bars

At end of the exposure period, specimens were removed from the oven and the reinforcement was extracted. All three reinforcing bars from each specimen were tested. Tensile test results for all reinforcing bars are tabulated in Tables 5 through 11. Values of yield stress correspond with the yield plateau.

Load versus strain relationships of the reinforcement before and after exposure are shown in Figures 6 through 12. Some curves showed a rounding behavior prior to reaching the yield plateau. However, no significant differences were observed in the yield plateaus of reinforcement tested before and after exposure.

TABLE 5. Reinforcement Tensile Tests After Three Months Exposure to Simulated Salt Cake Solution.

Specimen	Yield stress (psi x 1,000)	Ultimate stress (psi x 1,000)	Percent elongation in 8 in.
Reinforcement as received	49.0	81.5	19.1
	49.0	82.0	20.6
	52.0	83.0	17.4
	Av. 50.0	Av. 82.2	Av. 19.0
Compression 500 psi	48.5	81.0	20.6
	48.0	81.0	20.3
	49.5	81.5	19.0
	Av. 48.7	Av. 81.2	Av. 20.0
Flexure 10,000 psi	48.5	82.0	17.7
	50.0	82.0	18.5
	48.5	82.0	18.6
	Av. 49.0	Av. 82.0	Av. 18.3
Flexure 20,000 psi	46.5	80.0	15.9
	48.0	81.5	18.6
	48.0	81.5	18.0
	Av. 47.5	Av. 81.0	Av. 17.5

TABLE 6. Reinforcement Tensile Tests After Six Months Exposure to Simulated Salt Cake Solution.

Specimen	Yield stress (psi x 1,000)	Ultimate stress (psi x 1,000)	Percent elongation in 8 in.
Reinforcement as received	49.0	81.5	19.1
	49.0	82.0	20.6
	52.0	83.0	17.4
	Av. 50.0	Av. 82.2	Av. 19.0
Compression 500 psi	49.0	82.0	19.2
	50.0	82.5	17.8
	49.5	83.0	22.3
	Av. 49.5	Av. 82.5	Av. 19.8
Flexure 10,000 psi	49.0	81.0	21.2
	51.0	82.5	19.3
	50.5	81.5	18.1
	Av. 50.2	Av. 81.7	Av. 19.5
Flexure 20,000 psi	49.5	81.0	17.6
	47.0	79.5	16.6
	47.5	80.5	18.2
	Av. 48.0	Av. 80.3	Av. 17.5

TABLE 7. Reinforcement Tensile Tests After 19 Months
Exposure to Simulated Salt Cake Solution.

Specimen	Yield stress (psi x 1,000)	Ultimate stress (psi x 1,000)	Percent elongation in 8 in.
Reinforcement as received	49.0	81.5	19.1
	49.0	82.0	20.6
	52.0	83.0	17.4
	Av. 50.0	Av. 82.2	Av. 19.0
Compression 500 psi	51.0	81.0	19.4
	51.0	81.5	13.7*
	50.5	80.0	19.9
	Av. 50.8	Av. 80.8	Av. 17.7
Flexure 10,000 psi	51.5	80.5	19.4
	51.0	81.5	20.4
	51.0	80.5	18.2
	Av. 51.2	Av. 80.8	Av. 19.3
Flexure 20,000 psi	50.5	80.5	19.6
	50.0	81.0	20.2
	51.0	80.0	19.6
	Av. 50.5	Av. 80.5	Av. 19.8

*Bar fractured outside gage points.

TABLE 8. Reinforcement Tensile Tests After 19 Months
Exposure to Control Solution.

Specimen	Yield stress (psi x 1,000)	Ultimate stress (psi x 1,000)	Percent elongation in 8 in.
Reinforcement as received	49.0	81.5	19.1
	49.0	82.0	20.6
	52.0	83.0	17.4
	Av. 50.0	Av. 82.2	Av. 19.0
Compression 500 psi	49.5	79.0	18.7
	50.5	81.5	17.2
	49.5	79.0	18.9
	Av. 49.8	Av. 79.8	Av. 18.3
Flexure 10,000 psi	50.5	80.2	16.2*
	51.0	80.0	19.9
	51.5	80.5	15.6*
	Av. 51.0	Av. 80.2	Av. 17.2
Flexure 20,000 psi	50.0	80.5	20.0
	50.0	79.0	17.2
	50.2	79.5	16.2*
	Av. 50.1	Av. 79.7	Av. 17.8

*Bar fractured outside gage points.

TABLE 9. Reinforcement Tensile Tests After 13 Months Exposure
to Simulated Salt Cake Solution and 12 Months Exposure to
Double-Shell Slurry Solution.

Specimen	Yield stress (psi x 1,000)	Ultimate stress (psi x 1,000)	Percent elongation in 8 in.
Reinforcement as received	49.0	81.5	19.1
	49.0	82.0	20.6
	52.0	83.0	17.4
	Av. 50.0	Av. 82.2	Av. 19.0
Compression 500 psi	49.5	80.0	16.6
	49.0	81.5	14.8
	51.0	82.0	19.5
	Av. 49.8	Av. 81.5	Av. 17.0
Flexure 10,000 psi	50.5	81.8	18.5
	50.0	81.8	18.9
	49.0	81.0	21.0
	Av. 49.8	Av. 81.5	Av. 19.5
Flexure 20,000 psi	50.0	81.0	17.5
	49.0	81.0	*
	50.0	81.5	17.5
	Av. 49.7	Av. 81.2	Av. 17.5





*Bar fractured outside gage points.

TABLE 10. Reinforcement Tensile Tests After 36 Months
Exposure to Simulated Salt Cake Solution.

Specimen	Yield stress (psi x 1,000)	Ultimate stress (psi x 1,000)	Percent elongation in 8 in.
Reinforcement as received	49.0	81.5	19.1
	49.0	82.0	20.6
	52.0	83.0	17.4
	Av. 50.0	Av. 82.2	Av. 19.0
Compression 500 psi	50.0	81.0	19.0
	49.5	81.0	18.3
	51.0	81.5	19.6
	Av. 50.2	Av. 81.2	Av. 19.0
Flexure 10,000 psi	50.0	81.0	17.8
	50.0	80.0	21.0
	50.0	81.0	18.3
	Av. 50.0	Av. 80.7	Av. 19.0
Flexure 20,000 psi	50.5	81.0	18.4
	49.0	80.5	18.1
	49.0	80.5	20.6
	Av. 49.5	Av. 80.7	Av. 19.0

TABLE 11. Reinforcement Tensile Tests After 36 Months
Exposure to Control Solution.

Specimen	Yield stress (psi x 1,000)	Ultimate stress (psi x 1,000)	Percent elongation in 8 in.
Reinforcement as received	49.0	81.5	19.1
	49.0	82.0	20.6
	52.0	83.0	17.4
	Av. 50.0	Av. 82.2	Av. 19.0
Compression 500 psi	50.5	81.0	17.9
	48.0	80.5	21.9
	51.0	81.0	18.3
	Av. 49.8	Av. 80.8	Av. 19.4
Flexure 10,000 psi	51.0	81.5	19.9
	52.0	82.0	18.8
	51.0	81.0	18.9
	Av. 51.3	Av. 81.5	Av. 19.2
Flexure 20,000 psi	51.0	81.5	18.4
	50.0	81.0	20.3
	50.0	81.5	18.0
	Av. 50.3	Av. 81.3	Av. 18.9



RCP8212-7

FIGURE 6. Load Versus Strain Relationships of Reinforcement Before and After Exposure for Three Months to Simulated Salt Cake Solution.




FIGURE 7. Load Versus Strain Relationships of Reinforcement Before and After Exposure for Six Months to Simulated Salt Cake Solution.

RCP8212-8




FIGURE 8. Load Versus Strain Relationships of Reinforcement Before and After Exposure for 19 Months to Simulated Salt Cake Solution.

RCP8212-9




FIGURE 9. Load Versus Strain Relationships of Reinforcement Before and After Exposure for 19 Months to Control Solution.

RCP8212-10





FIGURE 10. Load Versus Strain Relationships of Reinforcement Before and After Exposure for 13 Months to Simulated Salt Cake Solution and 12 Months to Double-Shell Slurry Solution.

RCP8212-11



RCP8212-12

FIGURE 11. Load Versus Strain Relationships of Reinforcement Before and After Exposure for 36 Months to Simulated Salt Cake Solution.




FIGURE 12. Load Versus Strain Relationships of Reinforcement Before and After Exposure for 36 Months to Control Solution.

RCP8212-13

Petrographic Examinations

Petrographic examinations of concrete and visual inspection of reinforcing bars extracted from all specimens revealed no evidence of steel corrosion, as indicated by the presence of corrosion reaction products. Electrical potentials measured on the steel while embedded in the concrete also indicated no active corrosion. Inspection of flexural crack surfaces revealed that the test solutions penetrated to the steel. Thus, it is concluded that the steel did not incur electrochemical corrosion in the presence of any one of the three test solutions under conditions of the test exposure.

CONCLUDING REMARKS

This final report describes specimens simulating a wall section of a Hanford reinforced concrete waste storage tank exposed for several time periods to simulated waste solutions. Similar specimens were subjected to a control solution of saturated calcium hydroxide. For the time periods of exposure to the test solutions, there was no significant change in concrete or reinforcement properties examined.

DISTRIBUTION

Number of copies

OFFSITE

6	<u>U.S. Department of Energy</u> Headquarters
	G. A. Daly J. E. Dieckhoner G. A. Heath D. J. McGoff G. K. Oertel R. D. Walton, Jr.
2	<u>Albuquerque Operations Office</u> R. Y. Lowery (2)
1	<u>E. I. du Pont de Nemours and Company</u> Savannah River Laboratory
	P. L. Gray
1	<u>Exxon Nuclear Idaho</u> P. W. Smith
1	<u>Idaho Falls Operations Office</u> J. P. Hamric
1	<u>Lawrence Livermore National Laboratory</u> J. D. Twebney
3	<u>Oak Ridge National Laboratory</u> L. R. Dole A. L. Lotts (2)
2	<u>Oak Ridge Operations Office</u> S. W. Ahrends (2)
1	<u>Office of Nuclear Waste Isolation</u> Battelle Memorial Institute-Columbus W. Carbeiner

5

Portland Cement Association

J. I. Daniel (3)
P. H. Kaar
M. S. Abrams

2

San Francisco Operations Office

S. G. Harbinson (2)

3

Savannah River Operations Office

E. S. Goldberg (2)
T. B. Hindman, Jr.

1

Savannah River Plant

R. Maher

ONSITE

4

Battelle Pacific Northwest Laboratory

W. J. Anderson
M. C. C. Bampton
R. D. Nelson
A. M. Platt

6

U.S. Department of Energy
Richland Operations Office

P. F. X. Dunigan
R. D. Izatt
J. J. Schreiber (3)
F. R. Standerfer

32

Rockwell Hanford Operations

J. F. Albaugh	R. Y. Lyon
M. R. Adams	R. E. Nevills
M. L. Bell	C. W. Manry
H. Babad	H. E. McGuire
D. J. Cockeram	L. H. Rodgers
C. DeFigh-Price (4)	J. H. Roecker

RHO-RE-CR-8 P

J. L. Deichman
K. A. Gasper
W. F. Heine
G. A. Huff
J. F. Kaser

S. A. Wiegman
D. G. Wilkins
D. D. Wodrich
D. E. Wood
R. A. Zinsli
Document Control (4)
RCP (3)