

# Probabilistic Analysis To Quantify Optical Performance And Error Budgets For Next Generation Heliostats

**Joshua Christian**

**Adam Moya**

**Clifford Ho**

**Charles Andraka**

**James Yuan**

SAND




Sandia National Laboratories is a multi-program laboratory managed and operated by Sandia Corporation, a wholly owned subsidiary of Lockheed Martin Corporation, for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-AC04-94AL85000.

*ASME 2013 7<sup>th</sup> International Conference*  
SAND2013-5769C  
on Energy Sustainability  
July 14-19, 2013

*Exceptional service  
in the national interest*




# Introduction



- What is the optical error budget for heliostats?
  - Plant levelized cost of energy (LCOE) is metric

# Introduction

Design Basis Document  
Error Budget Values



Tracking Error Sources	Azimuth Error (mrad)	Elevation Error (mrad)
Encoder resolution/drive back-lash	0.6	0.4
Sun position prediction	0.15	0.15
Light refraction	0.05	0.05
Error corrected tracking	0.4	0.4
Total error (RSS, mrad)	0.74	0.59
Total error req. (RMS, mrad)*	0.75	0.75

Beam Quality Error Sources	Azimuth Error (mrad)	Elevation Error (mrad)
Slope Error	1	1
Mirror specularity	0.25	0.25
Mirror alignment error	0.25	0.25
Structural deflections from gravity	0.8	0.8
Focal change with temperature	0.5	0.5
Total error (RSS, mrad)	1.33	1.33
Total error req. (RMS, mrad)*	1.8	1.8

• Zavoico, A. B., 2001, "Solar Power Tower: Design Basis Document," No. SAND2001-2100, Sandia National Laboratories, Albuquerque, NM and Livermore, California.

# **Presentation Overview**

---

- Objectives
- Approach
- Results
- Conclusion

# Objectives

---

- Determine a feasible optical error budget for next generation heliostats.



# **Presentation Overview**

---

- Objectives

- Approach

- Results

- Conclusion

# Probabilistic Modeling Approach

---

- I. Optical Error Impacts: Determine which optical errors are most impactful on LCOE
  - Use DELSOL to analyze error sources
2. Bundled Error Source: Determine the acceptable magnitude of a “bundled” error source on heliostats to achieve LCOE goal
3. Budget: Break down the “bundled” error value into design error sources

# Presentation Overview

---

- Objectives

- Approach

- Results

- Conclusion

# Optical Error Impacts

Heliostat Size Chosen (10-150 m<sup>2</sup>)



Slope Error Values Chosen  
(10,000 samples): Latin  
Hypercube Sampling (Beam  
Quality Errors 1-4 mrad,  
Tracking Errors 0.25-1.5  
mrad)

- The tower height was 170 m and remains fixed throughout the analysis.
- Two receiver geometries (external cylindrical) were evaluated: 1) 14.87 m diameter by 18.62 m height and 2) 12 m diameter by 10 m height.
- Heliostats were comprised of 25 facets: 5 facets across the width and 5 facets across the height, on-axis canting, flat facets.
- The required total electric power of the plant was fixed at 100 MWe.
- The solar multiple is set to 2.0 which allowed for at least 8 hours of thermal storage.
- The maximum flux limit on the receiver was set to 1100 kW/m<sup>2</sup>.
- The thermal to electric turbine efficiency was set to 55% matching the SunShot technical target.


DELSOL; 10,000 runs






Statistical Analysis

# Optical Error Impacts


D=14.87 m, H=18.62 m



D=12 m, H=10 m




# Bundled Error Source




# Optical Error Budget

Error	Initial Value (mrad)	Adjusted Error Value (mrad)
Slope error	1	1.26
Tracking	0.75	0.945
Canting (alignment)	0.25	0.315
Structural deflections	0.8	1.008
Temperature dependent slope error	0.5	0.63
RSS bundled error	1.59	2.00

# Optical Error Budget: 14.9 m by 18.6 m Receiver



# Optical Error Budget: 12 m by 10 m Receiver



# Presentation Overview

---

- Objectives
- Approach
- Results
- Conclusion

# Conclusions

---

- Beam quality errors have a significant impact on plant LCOE
- Size of receiver is a critical design feature
- A larger range of error magnitudes can be used depending on receiver design