

Diagnostic First Wall Conceptual Design Review

ITER Site
Cadarache, France
June 23, 2011

Dennis Youchison
Sandia National Laboratories

Sandia National Laboratories is a multi-program laboratory managed and operated by Sandia Corporation, a wholly owned subsidiary of Lockheed Martin Corporation, for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-AC04-94AL85000.





Mesh contains 5.6M cells
With 3 prism layers

Parameters




- 3.0 MPa, 70 C water
- 5.1 kg/s mass flow inlet
- $Q''=0.35 \text{ MW/m}^2$ on top surface.
- 1) $Q_n=e(1.55657-0.0621156x) \text{ W/cm}^3$ 16 cm e-folding distance
- 2) $Q_n=e(1.55657-0.1111096x) \text{ W/cm}^3$ 9 cm e-folding distance


4.1 M cells in fluid volume



Delta-P about 1.1 MPa


STAR-CCM+

Pressure distribution




Pressure distribution


• $\dot{m}=3.5 \text{ kg/s}$




Velocity distribution cutplane




Velocity distribution cutplane




Nuclear heating profile – $\lambda=16$ cm




Most surface temperatures are acceptable



Mounting tabs at 356 °C



Temperatures along top edges are high.




Coolant temperature distribution




$T_{sat}=233.9 \text{ }^{\circ}\text{C}$

local boiling



Nuclear heating profile – $\lambda=9$ cm




Temperatures are modest.



Although overall temperatures are low, possible thermal stress issues exist near plasma facing side.

 STAR-CCM+



- DFW Upper18 pressure drop ~ 0.5 MPa at 3.5 kg/s.
- DFW Upper18 mounting tabs at acceptable temperatures for both $\lambda=16$ (356 °C) and $\lambda=9$ cm (128 °C).
- DFW Upper18 plasma facing edges are hot
- Very localized boiling due to cavitation at inlet bend.
Delta-T in coolant=18.9 °C
- Thermal loads exported to Abaqus for thermal stress analysis