



# **Results from the Seven Percent Critical Experiment**

**American Nuclear Society  
2011 Annual Meeting**

**Hollywood, Florida**

**June 28, 2011**

**Gary A. Harms, John T. Ford, and Allison D. Miller  
Sandia National Laboratories  
[gaharms@sandia.gov](mailto:gaharms@sandia.gov)**



## Outline

---

- **Sandia Critical Experiments – Some History**
- **The Seven Percent Critical Experiment**
  - Design of the Experiment
  - Results from the Experiment
- **The Future of the Sandia Critical Experiments**




## We operated the SNTP CX in the late 80's

A critical experiment (CX) was run at Sandia as part of the Space Nuclear Thermal Propulsion (SNTP) program. The CX was designed to simulate the behavior of a nuclear rocket motor. It had:

- Stand-alone Authorization Basis
- New critical assembly hardware
- New critical assembly control system




## In 2002, we performed some critical experiments with rhodium





- The Burnup Credit Critical Experiment (BUCCX) was funded by the Nuclear Energy Research Initiative (NERI)
- We built a critical assembly in which we could insert fission product materials to measure reactivity effects
- The NERI funding was used to bring the experiment capability up and perform the first set of experiments
- We completed a set of experiments with rhodium
- The experiment is documented as LEU-COMP-THERM-079 in the International Handbook of Evaluated Criticality Safety Benchmark Experiments

# The BUCCX core was designed to be easy to model



- The assembly is a triangular-pitched array of Zircaloy-4 clad U(4.31%)O<sub>2</sub> fuel (driver) elements
- Test materials are placed between the fuel pellets in “experiment elements”
- The assembly has 3 control/safety elements
  - the B<sub>4</sub>C absorber is decoupled from the assembly by a polyethylene spacer
  - the absorber is followed by a fuel rod
- The source is in the central fuel element
- The grid plates are aluminum
- The pitch of the array is modified by replacing the grid plates







## The 7uPCX started as a NERI project

---

### *Reactor Physics and Criticality Benchmark Evaluations for Advanced Nuclear Fuel*


- The project was originally funded by the Nuclear Energy Research Initiative (NERI)
- The NERI project team:
  - AREVA Federal Services, LLC (Lynchburg, VA) – Conceptual Design, Analysis, Project Management
  - Sandia National Laboratories – Hardware Design, Transportation, Procurement, Experiments
  - Oak Ridge National Laboratory - Analysis
  - University of Florida - Analysis
- The NNSA NCSP is now funding the critical experiments

# The Seven Percent Critical Experiment (7uPCX) is a reactor physics experiment




**Project Objective: *Design, perform, and analyze critical benchmark experiments for validating reactor physics methods and models for fuel enrichments greater than 5-wt%  $^{235}\text{U}$***

- We built new 6.9% enriched experiment fuel
- We built critical assembly hardware to accommodate the new core
- The core is a 45x45 array of rods to simulate 9 commercial fuel elements in a 3x3 array
- The experiment is a reactor physics experiment as well as a critical experiment
- Additional measurements will be made
  - Fission density profiles
  - Soluble poison worth
  - Water hole worth



# The shut-down configuration of the assembly



**Fuel: 12 - CE/SE only**

**Safety Elements: Down**

**Control Element: Down**


**Core Tank: Empty**

**Personnel: Allowed**

In this condition, the assembly is “shut down.” Entry into the reactor room is allowed. The control system need not be manned. Fuel may be removed or added but a “new” configuration may not be built.



## Raise the safety elements



**Fuel: 12 - CE/SE only**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Empty**

**Personnel: Allowed**

In this condition, the assembly is “operating” and a qualified operator must be at the controls at all times. Entry into the reactor room is allowed. Fuel may be added to or removed from the array.



## Add fuel



**Fuel: 64**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Empty**

**Personnel: Allowed**

In this condition, the assembly is “operating” and a qualified operator must be at the controls at all times. Entry into the reactor room is allowed. Fuel may be added to or removed from the array.



## Add fuel



**Fuel: 116**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Empty**

**Personnel: Allowed**

In this condition, the assembly is “operating” and a qualified operator must be at the controls at all times. Entry into the reactor room is allowed. Fuel may be added to or removed from the array.



## Add fuel



**Fuel: 168**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Empty**

**Personnel: Allowed**

In this condition, the assembly is “operating” and a qualified operator must be at the controls at all times. Entry into the reactor room is allowed. Fuel may be added to or removed from the array.



## Add fuel



**Fuel: 318**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Empty**

**Personnel: Allowed**

In this condition, the assembly is “operating” and a qualified operator must be at the controls at all times. Entry into the reactor room is allowed. Fuel may be added to or removed from the array.



## Add fuel



**Fuel: 548**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Empty**

**Personnel: Allowed**

In this condition, the assembly is “operating” and a qualified operator must be at the controls at all times. Entry into the reactor room is allowed. Fuel may be added to or removed from the array.



## Add fuel



**Fuel: 740**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Empty**

**Personnel: Allowed**

In this condition, the assembly is “operating” and a qualified operator must be at the controls at all times. Entry into the reactor room is allowed. Fuel may be added to or removed from the array.



## Add fuel



**Fuel: 956**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Empty**

**Personnel: Allowed**

In this condition, the assembly is “operating” and a qualified operator must be at the controls at all times. Entry into the reactor room is allowed. Fuel may be added to or removed from the array.



## Add fuel



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Empty**

**Personnel: Allowed**

In this condition, the assembly is “operating” and a qualified operator must be at the controls at all times. Entry into the reactor room is allowed. Fuel may be added to or removed from the array.



## Fill the core tank



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Filling**

**Personnel: Excluded**

**Filling the core tank requires  
about 15 minutes.**



## Fill the core tank



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Filling**

**Personnel: Excluded**

**Filling the core tank requires  
about 15 minutes.**



## Fill the core tank



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Filling**

**Personnel: Excluded**

**Filling the core tank requires  
about 15 minutes.**



## Fill the core tank



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Filling**

**Personnel: Excluded**

**Filling the core tank requires  
about 15 minutes.**



## Fill the core tank



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Filling**

**Personnel: Excluded**

**Filling the core tank requires  
about 15 minutes.**



## Fill the core tank



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Filling**

**Personnel: Excluded**

**Filling the core tank requires  
about 15 minutes.**



## Fill the core tank



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Filling**

**Personnel: Excluded**

**Filling the core tank requires  
about 15 minutes.**



## Fill the core tank



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Filling**

**Personnel: Excluded**

**Filling the core tank requires  
about 15 minutes.**



## The core tank is full



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Full**

**Personnel: Excluded**

At this point, the “fast” fill pump is disabled by an interlock and the recirculation pump is turned on. Moderator enters under the water’s surface and drains to the dump tank through a stand pipe.



## Raise the control element



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Raising**


**Core Tank: Full**

**Personnel: Excluded**

**It takes about 90 seconds to raise the control element.**



## Raise the control element



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Raising**


**Core Tank: Full**

**Personnel: Excluded**

**It takes about 90 seconds to raise the control element.**



## Raise the control element



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Raising**


**Core Tank: Full**

**Personnel: Excluded**

**It takes about 90 seconds to raise the control element.**



## Raise the control element



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Raising**


**Core Tank: Full**

**Personnel: Excluded**

**It takes about 90 seconds to raise the control element.**



## Raise the control element



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Raising**


**Core Tank: Full**

**Personnel: Excluded**

**It takes about 90 seconds to raise the control element.**



## Raise the control element



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Raising**


**Core Tank: Full**

**Personnel: Excluded**

**It takes about 90 seconds to raise the control element.**



## The assembly reaches its most reactive state



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Up**


**Core Tank: Full**

**Personnel: Excluded**

With all control and safety elements up and full reflection (>6 in. of water on all sides), this is the highest reactivity state of the assembly. Multiplication measurements are made in this configuration.



## Lower the control element



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Lowering**


**Core Tank: Full**

**Personnel: Excluded**

**It takes about 90 seconds to lower the control element.**



## Lower the control element



**Fuel: 1136**

**Safety Elements: Up**


**Control Element: Down**

**Core Tank: Full**

**Personnel: Excluded**



## Drain the core tank



**Fuel: 1136**

**Safety Elements: Up**

**Control Element: Down**


**Core Tank: Draining**

**Personnel: Excluded**

**Draining the core tank requires  
only a few seconds.**



## Drain the core tank



**Fuel: 1136**

**Safety Elements: Up**


**Control Element: Down**

**Core Tank: Empty**

**Personnel: Allowed**

**Now we are back to a condition  
where fuel may be added to or  
removed from the array.**

# The shut-down configuration of the assembly



**Fuel: 1136**

**Safety Elements: Down**


**Control Element: Down**

**Core Tank: Empty**


**Personnel: Allowed**

In this condition, the assembly is “shut down.” Entry into the reactor room is allowed. The control system need not be manned. Fuel may be removed or added but a “new” configuration may not be built.

# Core configurations during the first approach-to-critical experiment (1)



740



956


$$\text{Multiplication: } M = \frac{1}{1 - k_{\text{eff}}}$$

$$\frac{1}{M} = 1 - k_{\text{eff}}$$


Project the two inverse multiplication measurements to zero and add half the increment to get the next array – in this case 1009 elements

The incremental fuel elements are shown in blue


The first two arrays have  $k_{\text{eff}} \sim 0.9$  and  $k_{\text{eff}} \sim 0.95$  (calculated)




## Core configurations during the first approach-to-critical experiment (2)



740




956



1009


The next array: 1059




The incremental fuel elements are shown in blue




# Core configurations during the first approach-to-critical experiment (3)




740



956




1009




1059

The next array: 1089




The incremental fuel elements are shown in blue

# Core configurations during the first approach-to-critical experiment (4)




1059




1089

The next array: 1115




The incremental fuel elements are shown in blue


# Core configurations during the first approach-to-critical experiment (4)



1059



1089




1115



We also made measurements with 1127, 1136, 1140, and 1144 elements (all subcritical). A core with 1148 elements was supercritical.

The next array: 1127

The incremental fuel elements are shown in blue



# Core configurations during the first approach-to-critical experiment (5)



$$N_{\text{crit}} = 1145.3$$


$$k_{\text{eff}} = 0.9984$$

$$M \sim 610$$


The incremental fuel elements are shown in blue



# The first 7uPCX core at the end of the approach




# Core “A” Configurations Starting 2/9/10







# The “A” core




# $k_{\text{eff}}$ from Approach Data














## We have performed critical experiments on several 7uPCX configurations



Sandia  
National  
Laboratories



## 7uPCX Critical Configurations





## The 7uPCX experiment matrix

---

- **We have two grid plate sets**
  - The sets were chosen to bound the fuel-to-water ratio of commercial PWRs
  - A full set of experiments will be done at each pitch
- **We will find the array that is critical with pure water moderator**
- **We will search for the boric acid concentration in the moderator that gives a critical array with all fuel element positions filled**
- **Fission density measurements will be made on the fully-loaded core**



## The Future for the Sandia Criticals

---

- We will maintain the critical experiment capability for the foreseeable future
  - The NCSP plans to support the operation of the critical experiments
- We are developing a critical experiments training course module as part of the DOE NCSP Nuclear Criticality Safety Engineer training program
- We will continue to work through the 7uPCX experiment matrix
  - Complete measurements on the cores with pure water moderator
  - Perform experimentation with dissolved boron in the moderator
- Other experiments are under development

# Critical Experiments at Sandia





## The Phase Space our Authorization Basis Allows is Large

---

- Our design space:
  - $\text{UO}_2$  fuel
  - Metal Cladding
  - Light Water Moderator
  - <20% Enrichment
  - <500 kg of  $\text{UO}_2$  in the reactor room
  - >50 kg of  $\text{UO}_2$  in a critical configuration