



BSL-3 Planning, Programming, and Operations Workshop

SAND2008-4268C



BSL3 Design Phase – Laboratory Design

Craig M. Free, P.E.

Diversified Laboratory Sciences, Inc.


July 15, 2008




SAND No. 2008-XXXXC

Sandia is a multiprogram laboratory operated by Sandia Corporation, a Lockheed Martin Company,
for the United States Department of Energy's National Nuclear Security Administration under contract DE-AC04-9AL85000.






Design Topics



- **Selecting design team with right expertise**
- **Selecting commissioning team with right expertise**
- **Facility type?**
 - Bricks and mortar or modular?
- **Building location**
- **Flows of personnel, materials, and waste**
- **Allocate mechanical space**
- **Address considerations for:**
 - Building control systems
 - Laboratory casework
 - Autoclaves
- **Plan for reviews**
 - Design
 - Peer
 - Value engineering
- **Complete commissioning plan**




Design Participants



- **Participants in the Laboratory Planning Process, plus**
- **Architectural and engineering (A&E) firm, and**
- **Commissioning consultant**

- **Also consider hiring a peer review team**


- **Remember, it's much cheaper to change paper designs than to fix during construction or renovate after occupation**



Design Process Overview




- **Schematic Design (Planning document to 20%)**
 - Completed list of laboratory equipment for each space
 - Further develop floor plans
 - Develop personnel, product, and waste flow diagrams
 - Finalize the Biosafety Risk Assessment
 - Finalize the Biosecurity Risk Assessment
 - Review budget (including design contingency, bid contingency, and construction contingency)
 - Coordinate between disciplines (structural, mechanical, electrical, plumbing, etc.)
 - Calculate preliminary heating and cooling loads



Design Process Overview continued




- **Design Development (20% to 50%)**
 - Finalize floor plans
 - Finalize heating and cooling loads
 - Duct & piping shown, but not sized
 - Develop general specifications
 - Review budget (design contingency should be reduced to half)
 - Coordinate between disciplines
- **Construction Documents (50% to 100%)**
 - Complete floor plans and specifications
 - Review budget (design contingency should be zero)
 - Coordinate between disciplines



Develop Flow Diagrams for Personnel, Materials, Waste


- **Personnel flow**
 - Determine the path of travel for the laboratory users.
- **Product/material flow**
 - Determine the path of travel for the products used within the laboratory, including live organisms, equipment, animals, supplies, cages, etc.
- **Waste flow**
 - Determine the path of travel for the waste to exit the lab.



LEGEND

Ante Room - PE Don/Doff


Laboratory Personnel Flow



Analysis of Laboratory Flows



- **Identify clean and dirty areas and corridors and grey zones**
 - Explicitly consider procedural controls versus engineering controls (primary and secondary barriers)
- **Make decisions about doors**
 - Where required for pressure differential between spaces
 - Where needed for programmatic reasons (e.g. security, to delineate research spaces, etc)
 - Determine where anterooms are needed
- **Determine space requirements for storage of PPE and supplies**
- **Identify areas for donning and doffing of PPE**
- **Identify BSL2 areas that support the BSL3 areas**




Laboratory Design – Primary Containment




Why does BSC selection matter?

BSC Type	Impact on:		
	ACH	Exhaust System	Exhaust Duct
A2, re-circulating	None	None	None
A2, indirect duct connection	Moderate	Low	Low
B2, total exhaust	High	High	High





Laboratory Design – Primary Containment

Indirect (thimble/canopy)
Connection



Direct (hard)
Connection






Laboratory Design – Air Changes Per Hour




- How do I calculate the ACH for my laboratory?
 - What you need to know:
 - Exhaust air flow rate
 - The interior volume of the laboratory: (length) * (width) * (ceiling height)
 - Formulas to use:
 - $n = 60 * Q / V$ (Imperial Units)
 - $n = 3600 * Q / V$ (SI Units)
 - Where $n = ACH$, $Q = \text{exhaust air flow rate}$, and $V = \text{interior volume}$
 - What are typical ACH for laboratories?
 - 10 – 12 ACH for conventional laboratories
 - 10 – 15 ACH for animal areas
 - In excess of 20 ACH can create ambient conditions not conducive to safe BSC operation




Laboratory Design – Physical Space Recommendations





- Builds upon recommendations for BSL-1 and BSL-2
- Biohazard warning sign posted at the entrance
- Separated from other areas with restricted access
- Double door entry through self closing and interlocked doors
- Ante room with clear delineation between clean and dirty
- Adequate storage space for street clothes
- Adequate space for PPE storage, electrical outlets for PAPRs, if required.
- Walls, floors, and ceilings smooth and easy to clean
- Envelope penetrations sealed to facilitate decontamination
- Windows closed, sealed, break resistant
- Hand washing station with hands-free operation
- Autoclave available in containment area
- Personnel Shower, if identified by RA
- Sustainability and maintainability are key




Double Door Entry Options




ROOM AS ACCESS ZONE



CORRIDOR AS ACCESS ZONE




SUITE CONCEPT



LAB AS ACCESS ZONE



CORRIDOR



ACCESS ZONE



BSL3



ENTRY DOOR 1



ENTRY DOOR 2



Laboratory Design – Engineering Recommendations




- Ducting systems designed to facilitate gaseous decontamination
- One-pass directional airflow with visual indicator
- Differential pressure vs. volumetric offset
- Controls to prevent sustained positive pressurization
- Monitored HVAC system
- HVAC control sequences for power interruption/failure and power restoration
- Interlock supply and exhaust
- Exhaust discharged away from occupied buildings and air intakes
- Exhaust HEPA filters, if identified by RA
- Interlock supply and exhaust equipment
- BSC's located away from lab traffic, doors, and room supply and exhaust



Laboratory Design – Engineering Recommendations




- **N+1 exhaust system, N+1 for supply system, if feasible**
- **Emergency power for HVAC systems and critical lab equipment**
- **Typical ventilation rate, 10 ACH**
- **Future flexibility**
- **Laminar (surgery room) diffusers**
- **Backflow prevention for water supply**
- **Vacuum breakers at each laboratory sink**
- **Vacuum lines protected with traps and HEPA filters**
- **Sprinkler heads, if required, pendant mounted**
- **Surface mounted light fixtures**
- **Emergency lighting**
- **Access to equipment provided outside containment envelope**
- **Liquid effluent decontamination system, if identified by the RA**
- **Lab gases stored outside the containment zone**




Directional Airflow


- **When Do You Need Directional Airflow?**
 - All BSL-3 laboratories
- **Airflow Offset Control**
 - Cascading airflow from lower levels of containment to higher levels
 - Relies on differential air pressure achieved by volumetric offset between supply and exhaust
 - Inflow of airflow through doors
 - Provides “Zone Control” of hazards and odors



Airflow
14



Summary



- **Laboratory personnel develop an accurate and complete laboratory equipment list for each space**
- **Coordination between disciplines**
- **Effort spent in design phase is well-spent**
 - Can help minimize likelihood of costly change orders or post-construction renovations
 - Hire a commissioning consultant early in the design process
 - Hire a peer review team
- **Monitor budget for the facility and construction market costs throughout the entire process**