


Exceptional service in the national interest



Source: Tokyo Electric Power Company



RCIC Operation in Fukushima Accidents as Modeled by MELCOR and Proposed Testing

R.O. Gauntt - Sandia National Laboratories
Presented at the BWR Owners Group General Meeting
Key West, Florida
October 7-8, 2014

Topics for discussion

 The image part with relationship ID r109 was not found in the file.

- Background
- Key observations from Forensics Analyses of Fukushima Accidents
- Modeling RCIC water ingestion and equipment functioning in real-world accidents
- Proposed path forward

SANDIA REPORT

SAND2012-6173

Unlimited Release

Printed August 2012

Fukushima Daiichi Accident Study (Status as of April 2012)

Randall Gauntt, Donald Kalinich, Jeff Cardoni, Jesse Phillips, Andrew Goldmann, Susan Pickering, Matthew Francis, Kevin Robb, Larry Ott, Dean Wang, Curtis Smith, Shawn St.Germain, David Schwieder, Cherie Phelan

Prepared by
Sandia National Laboratories
Albuquerque, New Mexico 87185 and Livermore, California 94550

Sandia National Laboratories is a multi-program laboratory managed and operated by Sandia Corporation, a wholly owned subsidiary of Lockheed Martin Corporation, for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-AC04-94AL85000.



Approved for public release; further dissemination unlimited.



Sandia National Laboratories

- Sandia commissioned by DOE to conduct forensics analyses of Fukushima accidents using MELCOR severe accident analysis code
- Comparison to pre-Fukushima analyses of SBO in Peach Bottom strikingly similar
- However, important differences observed in key areas
 - RCIC in particular

MELCOR Analysis of Fukushima Unit 1





- Prior to tsunami and loss of AC/DC
 - Isolation condensers cooling reactor
 - First two IC's then one
 - Exceeding cooldown rate of 100F/hr – too conservative?
- SBO at ~1 hour due to tsunami
 - Loss of control of functioning IC's
 - IC return valve closed
 - Loss of decay heat removal
- Core damage at ~4 hours
- MSL rupture at ~ 6.5 hours
 - Or SRV gasket failure
- Core slumping by ~8 hours
- Lower head failure ~12.5 hours

Fukushima Lessons Learned: Unit 1

- Isolation condenser was functioning and cooling reactor
 - Operators were cycling IC on and off to avoid cooldown rate exceeding 100 F/hr
 - IC “caught ” in off-position when tsunami flooding disabled DC power
 - Tech Spec cooldown of 100F/hr may be over-conservative – should be re-evaluated
- Unit 1 accident could *perhaps* have been avoided had IC been operating
 - Operators would have to refill IC secondary HX shell
- Potential Industry Response
 - Relax cooldown limits to preserve essential cooling capability (keep IC operating) – *needs evaluation*
 - Make IC easier to actuate with loss of power

MELCOR Analysis of Unit 3





- Unit 3 maintained DC power
 - Active control of RCIC
- RCIC starts level control – runs 21 hours
 - Beyond most current SBO coping times
- RCIC shuts down automatically on high turbine exhaust pressure
 - Automatic system protection
 - Otherwise functioning injection system cannot be restarted
- HPCI is started
 - System run continuously using test line to recirculate water and avoid cycling HPCI on/off
 - Deep depressurization of RPV results
 - After 28 hours HPCI injection is ineffective
 - HPCI stops after ~35 hours
- Core damage underway prior to system depressurization
- Unit 3 probably worst damaged of units

Fukushima Lessons Learned: Unit 3




- RCIC and HPCI were both operational due to DC availability
 - RCIC ran for 21 hours before shutting down on high turbine exhaust signal
 - RCIC and HPCI have numerous automated shutdown criteria to protect turbine and pump
 - HPCI started up but created such extreme RPV depressurization that HPCI pump was not injecting water
 - Core uncovering and early damage occurring as HPCI manually stopped
- Core damage could *perhaps* have been prevented had RCIC not automatically shut itself down
- Possible Industry Response
 - Disable some auto shutdown features in extended ELAP to keep critical equipment operating
 - Better understand operational capabilities of RCIC/HPCI under beyond design basis circumstances


MELCOR Analysis of Unit 2 RCIC



- First 45 minutes RCIC operates normally
- Arrival of tsunami results in loss of AC/DC power
 - RCIC runs uncontrolled (full open)
 - RPV pressure drops until water level reached main steam line (MSL)
 - Water carryover into RCIC turbine degrades performance and RPV heats up
- RCIC operates in self-regulating cyclic mode thereafter
 - RPV water level maintained near MSL with cyclic water ingestion and subsequent clearing
- MELCOR model was developed to account for water ingestion
- Long term pressure trends captured
- RCIC runs for nearly three days
- Eventual shutdown thought due to turbine over-speed
 - Pump cavitation?



Fukushima Lessons Learned: Unit 2




- RCIC operating at time of loss of power and continued to operate
 - Turbine governor opens fully
 - Electrical shutdown interlocks non-functional due to loss of DC: especially high RPV water level shutdown
 - Water level rose to top of steam lines by 1.5 hours producing liquid water ingestion by RCIC turbine
- RCIC ran for 72 hours running in uncontrolled mode
 - Water carryover did not shut down turbine
 - That's because the Terry Turbine design is *really robust*
- RCIC termination likely by cavitation-induced over-speed trip
 - Suppression pool saturation may have eventually led to pump cavitation and turbine over-speed trip (Mizokami 2013 TEPCO)
- System protection interlocks were defeated by loss of DC allowing RCIC to remain in service

Observations

- RCIC system ubiquitous at BWR installations world-wide
 - And widely used in PWR Aux Feed systems
- RCIC system more robust than previously credited
 - PRA and safety studies assume RCIC failure with loss of batteries after 4 to 8 hours – coping times short
- Post-Fukushima NRC Rulemaking will require extension of coping time considerably
- Existing RCIC system seems capable of extended operation even with loss of DC control
- Demonstrating extended RCIC operation under ELAP conditions can bridge gap between current coping times and FLEX implementation by 24 hours
- Propose full scale testing to demonstrate technical basis for extended RCIC operation

Power Requirements for Full Scale Testing


The image part with relationship ID r109 was not found in the file.



- Normal RCIC energy requirements in MW range
 - 500 hp typical pump power
- Energy draw with water ingestion is considerably larger
 - Larger specific enthalpy of water carryover
- Steam/water system required to demonstrate operation under water ingestion is roughly decay heat levels
 - 20 to 30 MW

Conceptual Design for General Test Facility – 30MW Boiler

The image part with relationship ID r629 was not found in the file.



- Considers wide range of testing capability
 - Turbine
 - Pump
 - WW
 - SRV
- Simpler design can be made for RCIC only
- MELCOR model to be developed
- 30 MW facility under consideration

Objectives of RCIC Testing

(and other critical systems and components)

The image part with relationship ID r109 was not found in the file.

- Confirm self-regulating operational mode of RCIC
 - Early testing of RCIC response to “water slug” suggests RCIC not damaged
 - Operational characteristics need to be demonstrated
 - Effect of liquid water fraction in steam flow
 - Long-term RCIC operation needs to be demonstrated
- Potential scope of investigations
 - Operating pressure and water carry-over fraction
 - Pump head versus water carryover
 - Turbine speed and pump effectiveness (flow and head)
 - Potential response of interlocks in self-regulating mode
 - Response to turbine exhaust pressure and other environmental conditions

Potential Participants

- Department of Energy
- Industry and Owners Groups
- EPRI
- International – Japan Institute of Applied Energy/TEPCO
- SNL performing scoping studies on RCIC model development, Costs and Requirements
 - Facilities – existing or new ?, will assess situation.
 - FY-15 initial DOE funds (\$250K) for model/design development and test protocol
 - FY-16 to 19 TBD

Summary

- Fukushima analyses have revealed deep insights into real-world operation of critical systems
 - Currently too conservative assumptions of operational capabilities
- Capable cooling systems disabled by:
 - loss of DC (IC control in Unit 1)
 - Shutdown interlocks (*availability of DC* caused shutdown of Unit 3 RCIC)
 - Long term operability of RCIC under water ingestion conditions suggested by Unit 2 *due to loss of DC*
- RCIC system can potentially bridge gap between current coping times and FLEX implementation
 - Full scale testing can confirm technical basis
 - Analogous benefit likely for turbine-driven Aux feed in PWR's