

CONF-9506162-39

DOE/MC/30127-96/C0556

**Development and Demonstration of a Solid Fuel-Fired Gas Turbine System**

**Authors:**

James G. Speight  
Vijay K. Sethi

**Contractor:**

Western Research Institute  
365 North 9th Street  
Laramie, Wyoming 82071-3395

**Contract Number:**

DE-FC21-93MC30127

**Conference Title:**

Advanced Coal-Fired Power Systems '95 Review Meeting

**Conference Location:**

Morgantown, West Virginia

**Conference Dates:**

June 27-29, 1995

**Conference Sponsor:**

U.S. Department of Energy, Morgantown Energy Technology Center  
(METC)

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED *FR*

**MASTER**

## **DISCLAIMER**

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, 175 Oak Ridge Turnpike, Oak Ridge, TN 37831; prices available at (615) 576-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161; phone orders accepted at (703) 487-4650.

## **DISCLAIMER**

**Portions of this document may be illegible  
electronic image products. Images are  
produced from the best available original  
document.**

## 5.4

## Development and Demonstration of a Solid Fuel-Fired Gas Turbine System

### CONTRACT INFORMATION

<b>Cooperative Agreement</b>	DE-FC21-93MC30127
<b>Contractor</b>	Western Research Institute 365 North 9th Street Laramie, Wyoming 82071-3395
<b>Contractor Project Manager</b>	James G. Speight
<b>Principal Investigator</b>	Vijay K. Sethi
<b>METC Project Manager</b>	Madhav Ghate
<b>Period of Performance</b>	March 94 to March 96

### ABSTRACT

Western Research Institute (WRI) and Power Generating Incorporated (PGI) are developing a solid fuel-fired gas turbine system for specialized cogeneration applications. The system is based on a patented pressurized combustor designed and tested by PGI in conjunction with McConnell Industries. The other components of the system are (a) fuel receiving, preparation, storage and feeding system, (b) gas clean-up equipment, and (c) a gas turbine generator.

A demonstration of the technical and economic viability of the integrated system is being funded by the U.S. DOE through METC and the National Renewable Energy Laboratory, and PGI. An approximately 400 kW prototype system is under construction at the WRI facilities in Laramie, Wyoming. As a part of this demonstration the integrated system, following a short shakedown period, will be operated on white wood. White wood was selected as the fuel for early tests because of its low ash (0.5 - 1.0 %), silica, and sulfur contents. The system will then be operated on coal. It is expected that the design of the coal-based system will evolve as the wood testing proceeds.

In previous similar wood-fired system development attempts, albeit at lower turbine inlet temperatures, a major technical hindrance to long-term operation of a gas turbine power system has been the degradation of the hot section of the gas turbine. Deposition, erosion, and corrosion are main issues that need to be addressed. In the wood-fired PGI system, erosion is not likely to be of concern because of the low silica and low overall ash content of the fuel and the fact that the wood ash particle size is expected to be in the range where little or no erosion would be

expected. However, because of the high alkali content of the fuel, deposition and corrosion can become major issues.

This paper will deal with the issues pertaining to the design of the prototype being constructed at the WRI premises. Preliminary thoughts on the design aspects of the plant modifications required for coal testing will also be presented.