


*Exceptional service in the national interest*



# Dry Cask Simulator for a Boiling Water Reactor Fuel Assembly


Sam Durbin, Eric Lindgren, and Ken Sorenson

# Overview




Aboveground Storage

Source: [www.nrc.gov/reading-rm/doc-collections/fact-sheets/storage-spent-fuel-fs.html](http://www.nrc.gov/reading-rm/doc-collections/fact-sheets/storage-spent-fuel-fs.html)



Underground Storage

Source: [www.holtecinternational.com/productsandservices/wasteandfuelmanagement/hi-storm/](http://www.holtecinternational.com/productsandservices/wasteandfuelmanagement/hi-storm/)



- Purpose: Validate assumptions in CFD calculations for spent fuel cask thermal design analyses
  - Used to determine steady-state cladding temperatures in dry casks
  - Needed to evaluate cladding integrity throughout storage cycle
- Measure temperature profiles for a wide range of decay power and helium cask pressures
  - Mimic conditions for above and belowground configurations of vertical, dry cask systems with canisters
  - Simplified geometry with well-controlled boundary conditions
  - Provide indirect measure of mass flow rates and convection heat transfer coefficients
- Use existing prototypic BWR Incoloy-clad test assembly

# Project Structure

- Boiling Water Reactor Cask Simulator (BCS)
- Partnership between USNRC and DOE
  - Equal cost sharing
  - Parallel reporting to PICS:NE and Monthly Letter Status Reports (MLSRs) to NRC
  - NRC staff has technical review lead
- Mutual benefits
  - Thermal-hydraulic data for validation exercises
  - Complimentary data for High-Burnup Cask Demonstration Project
    - Includes thermal lance comparisons to peak cladding temperature (PCT)
    - Possible to examine krypton settling issues

# Past Validation Efforts

## Unconsolidated Fuel

- Full scale, multi-assembly
  - Castor-V/21 [1986: EPRI NP-4887, PNL-5917]
  - REA 2023 [1986: PNL-5777 Vol. 1]
    - Both unventilated
    - Both unpressurized
- Small scale, single assembly
  - FTT (irradiated, vertical) [1986 PNL-5571]
  - SAHTT (electric, vertical & horizontal) [1986 PNL-5571]
  - Mitsubishi (electric, vertical & horizontal) [1986 IAEA-SM-286/139P]
  - For all three studies:
    - BC: Controlled outer wall temperature (unventilated)
    - Atmospheric (air & He) and vacuum
- None appropriate for elevated helium pressures or ventilated configurations






FIGURE 4-1. SAHTT Assembly




# Current Approach




- Focus on pressurized canister systems
  - BCS capable of 24 bar internal pressure @ 400 °C
    - Current commercial designs up to ~8 bar
- Ventilated designs
  - Aboveground configuration
  - Belowground configuration
    - With crosswind conditions
- Thermocouple (TC) attachment allows better peak cladding temperature measurement
  - 0.030" diameter sheath
    - Tip in direct contact with cladding
- Provide validation quality data for CFD
- Complimentary to Cask Demo Project

# Prototypic Hardware

Upper tie plate



Nose piece and debris catcher




BWR channel, water tubes and spacers




- Most common 9×9 BWR in US
- Prototypic 9×9 BWR hardware
  - Full length, prototypic 9×9 BWR components
  - Electric heater rods with Incoloy cladding
  - 74 fuel rods
    - 8 of these are partial length
    - Partial length rods end 2/3 the length up assembly
  - 2 water rods
  - 7 spacers

# Thermocouple Layout




- 97 total TC's internal to assembly
- 10 TC's mounted to channel box
  - 7 External wall
    - 24 in. spacing starting at 24 in. level
  - 3 Internal wall
    - 96, 120, and 144 in. levels

# CYBL Test Facility




- Large stainless steel containment
  - Repurposed from earlier CYLINDRICAL BOILING Testing sponsored by DOE
  - Excellent general-use engineered barrier for isolation of high-energy tests
    - 3/8 in. stainless steel
    - 17 ft diam. by 28 ft cylindrical workspace
- Part of the Nuclear Energy Work Complex (NEWC)

# Aboveground Configuration




- BWR Cask Simulator (BCS) system capabilities
  - Power: 0 – 2.5 kW (anticipated)
  - Pressure vessel
    - Vessel temperatures up to 400 °C
    - Pressures up to 24 bar
    - ~200 thermocouples throughout system
- Air velocity measurements at inlets
  - Calculate external mass flow rate
  - Estimate external convection coefficient

# Belowground Configuration



- Modification to aboveground ventilation configuration
  - Additional annular flow path
- Final design complete
  - Inlet and outlet based on prototypic configuration
  - Reviewed by NRC staff
- Scaling analysis completed
  - Favorable comparisons
    - Modified, channel Rayleigh number ( $Ra_s^*$ )
    - Reynolds (Re) number

# Crosswind Conditions



- Crosswind conditions imposed on belowground configuration
  - Speeds of 0 to 12 mph
- Air forced across inlet and outlet ducts
  - Push/Pull system currently considered for use in CYBL
    - Vessel size limitations / Minimization of vorticity
- CFD modeling indicates reduction in cooling air flow rate at sustained crosswinds of 5 mph
  - NUREG -2174


# Commercial Equipment





- Commercial off-the-shelf solutions when possible
  - Thermocouple feedthroughs
  - Electrode feedthroughs
  - Air velocity transducers
- Decreased cost and construction time

# BCS Pressure Vessel Hardware


- Fabricated and pressure tested
- Coated with ultra high temperature paint



# Custom TC Lance




- Complements the TC lance in the Cask Demo Project
  - Same fabricator (AREVA)
    - Same materials and fabrication process
- TC elevations match BWR assembly TCs
  - Provides direct comparison between lance TCs and clad TCs



# Gantt Chart

- 27 month total project duration
  - Aboveground configuration testing starts April 2016
  - Belowground configuration testing starts January 2017



# BCS Status


- Project is on schedule and budget
  - Initial safety analysis conducted May
- Pressure vessel hydrostatic test complete
  - Final pressure rating of 24 bar at 400 °C
- Overpack and inlet channel dimensions were optimized to match  $Ra_s^*$  and  $Re$
- Refinements of design ongoing with NRC staff
  - Current configurations are final
  - Remaining tasks include finalization of instrumentation layout
- Update report completed SAND 2015-7846

# BACKUP SLIDES

# Test Matrix

Aboveground		Belowground					
		Wind (m/s) =>	0.0		2.25		5.0
Helium pressure (bar)	Power (W)	Helium pressure (bar)	Power (W)	Helium pressure (bar)	Power (W)	Helium pressure (bar)	Power (W)
1	500	1	500				
	1500		1500				
	2500		2500				
4.5	500	4.5	500	4.5	500	4.5	500
	1500						
	2500		2500		2500		2500
8	250	8	500	8	500	8	500
	500						
	1000		2500		2500		2500
Step through powers	1500	Step through wind speeds					
	2500						


# Internal Dimensional Analyses



- Internal flow and convection prototypic
  - Near prototypic geometry for fuel and basket
- Downcomer and external cooling flows matched using elevated decay heat (5 kW)
  - Downcomer dimensionless groups

	BCS High Power	NAC TSC-87	Holtec 100U
$Re_{Down}$	290	220	220
$Ra_H^*$	4.7E+11	4.7E+11	5.6E+11
$Nu_H$	220	210	220

# External Dimensional Analyses




- External cooling flows matched using elevated decay heat (5 kW)
  - External dimensionless groups

	BCS High Power	NAC TSC-87	Holtec 100U
<b>External Cooling</b>			
$Re_{Ex}$	11200	7300	7700
$Ra_{DH}^*$	4.7E+09	3.0E+09	2.0E+09
$(D_{H, \text{Cooling}} / H_{PV}) \times Ra_{DH}^*$	1.9E+08	1.2E+08	6.9E+07
$Nu_{DH}$	29	26	23
<b>Aboveground Inlet Duct</b>			
$Re_{\text{Above, Inlet}}$	10700	11200	--
<b>Belowground Inlet Annulus</b>			
$Re_{\text{Below, Inlet}}$	8300	--	8600

# Past Validation Efforts

## Full Scale with Unconsolidated Fuel



- Full scale, multi-assembly
  - Castor-V/21 cast iron/graphite with polyethylene rod shielding
    - 1986: EPRI NP-4887, PNL-5917
    - 21 PWRs
    - 95 Thermocouples (TC's) total
      - 60 TC's on 10 lances deployed in 8 guide tubes and 2 basket void spaces
      - 35 TC's on outer surface of cask
  - Unventilated
  - Sub-atmospheric (air and He) and vacuum
- REA 2023 prototype steel-lead-steel cask with glycol water shield
  - 1986: PNL-5777 Vol. 1
  - 52 BWRs
  - 70 TC's total
    - 38 TC's at 8 axial levels in the basket and 7 assemblies
    - 32 TC's on outer cask surface
- Unventilated
- Sub-atmospheric (air & He) and vacuum

# Past Validation Efforts (cont.)

## Unconsolidated Fuel




FIGURE 4-1. SAHTT Assembly

- Small scale, single assembly
  - FTT (irradiated, vertical) and SAHTT (electric, vertical & horizontal)
    - 1986 PNL-5571
    - Single 15x15 PWR
    - Thermocouples (TC's)
      - FTT: 187 TC's total
      - SAHTT: 98 TC's total
    - BC: Controlled cask outer wall temperature
    - Atmospheric (air & He) and vacuum
  - Mitsubishi test assembly (electric, vertical & horizontal)
    - 1986 IAEA-SM-286/139P
    - Single 15x15 PWR
    - 92 TC's total, all distributed over 4 levels inside tube bundle
    - BC: Controlled outer wall temperature of fuel tube
    - Atmospheric (air & He) and vacuum
- Not appropriate for elevated helium pressures or belowground configurations