

LA-UR-16-28810

Approved for public release; distribution is unlimited.

Title: Organic Synthetic Advanced Materials for Optoelectronic and Energy Applications (at Center for Condensed Matter Sciences)

Author(s): Yen, Hung-Ju

Intended for: Job Interview at Center for Condensed Matter Sciences, Taiwan

Issued: 2016-11-14

Disclaimer:

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the Los Alamos National Security, LLC for the National Nuclear Security Administration of the U.S. Department of Energy under contract DE-AC52-06NA25396. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

***Organic Synthetic Advanced Materials for
Optoelectronic and Energy Applications
(at Center for Condensed Matter Sciences)***

顏宏儒 (Hung-Ju Yen)

**Chemistry Division, Los Alamos National Laboratory (LANL),
New Mexico, USA**



Dec. 23, 2016

國立臺灣大學 凝態科學研究中心

Professional Experience And Education


- Jan. 2014-present,
J. Robert Oppenheimer Distinguished Postdoctoral Fellow, LANL
- May 2013-Jan. 2014,
Director's Postdoc Fellow, LANL
- Feb.-Aug. 2011 & July 2012-May 2013,
Postdoctoral Researcher, National Taiwan University (NTU)
- July-Sep. 2009,
Visiting Doctoral Researcher, Tokyo Institute of Technology

- Jan. 2011, *Ph.D. with 1st prize, (4.0/4)*
Institute of Polymer Science and Engineering, NTU
- June 2007, *M.S. with Honors, (3.8/4)*
Department of Applied Chemistry, National Chi Nan University
- June 2006, *B.S., (3.2/4)*
Department of Applied Chemistry, National Chi Nan University



Current Challenges for LIBs

Lithium-Ion Battery



Challenges:

- ◆ Insufficient capacity – Li adsorption sites
- ◆ Slow charging rate – Li diffusivity
- ◆ Cycling stability – Structural instability
- ◆ Energy density (Wh/Kg) – Light weight required


Solution: Advanced Nanomaterials




Development of advanced nanomaterials is required to overcome these challenges

Graphene, Graphene Oxide and Nanographene

Graphene Oxide





Graphene




Exfoliation of Graphite
Chemical Vapor Deposition

Precise Bottom-Up Synthesis




Li et al., *J. Am. Chem. Soc.*, 2010, 132, 5944.


Nanographenes with Various Functional Groups



HBC-H




HBC-OMe




HBC-tBuOMe



HBC-OH












HBC-Br




HBC-F



Fine Tune d -Spacing through Organic Synthesis: Varying Functional Group



Schematic View of LIBs





Nanographenes as LIB Anode



- These NG anode LIBs exhibiting stable cycle stability.
- Capacity: OMe > tBuOMe > H > OH > Br > F

Rate Performance (Charging-Discharging)



Excellent rate performance achieved on the NG **HBC-OMe** anode, evidenced by the high capacity at high charging-discharging current.

Comparative study between **HBC-OMe**, **HBC-*t*BuOMe** and **HBC-H** reveals electron donating group enhance the rate performance.

Electrochromism



Electrochromic theory
J. R. Platt

J. Chem. Phys. **1961**, 34, 862




Electrochromic devices
S. K. Deb

Appl. Optics, supp. **1969**, 3, 192

Electrochromic Technology

■ Electrochromic Display (NTera®)



U. Bach et al. *Adv. Mater.* 2002, 14, 845

Anti-Glare Back Mirror



Smart Window




Smart Sunglasses




Electrochromic Materials

- Metal oxides (WO_3 , IrO_2 , MoO_3 , etc.)
- Mixed-valence metal oxides complex (*Prussian Blue*; $Fe^{III}[Fe^{II}(CN)_6] \cdot K^+$)
- Small organic molecules (Viologens and phthalocyanines)
- Electroactive polymers (PPy, PT, PEDOT, etc.)



Advantages of Triphenylamine

- Hole Transporting Material
- High Electron Mobility
- Low Ionization Potential
- Electrochemical Stability
 - Reversible Redox Couple
- Processability
 - Good Solubility
- Thermal Stability
 - High Glass Transition Temperature (T_g)
 - High Thermal Stability (T_d)







Requirement of Electrochromic Materials for Practical Applications

- (1) Low driving voltage (< 1.5 or 3.5 V)
- (2) Rapid response time [second (mirror)~ minute (window)]
- (3) High color contrast (transmittance attenuation= $\Delta T > 30\%$)
- (4) Long cycle life (>10 yr for window, >3 yr for mirror)
- (5) Environmental stability (electrochemical, thermal, & UV)
- (6) Low cost, easy processing
- (7) Multiple colors with the same material

Requirement of Electrochromic Materials for Practical Applications

- (1) Low driving voltage (< 1.5 or 3.5 V)
- (2) Rapid response time [second (mirror)~ minute (window)]
- (3) High color contrast (transmittance attenuation= $\Delta T > 30\%$)
- (4) Long cycle life (>10 yr for window, >3 yr for mirror)
- (5) Environmental stability (electrochemical, thermal, & UV)
- (6) Low cost, easy processing
- (7) Multiple colors with the same material

Low driving voltage & Long cycle life











Polym. Chem. **2012**, *3*, 255-264
J. Mater. Chem. **2008**, *17*, 1007-1015
Macromolecules **2008**, *41*, 2800-2808

Requirement of Electrochromic Materials for Practical Applications


- (1) Low driving voltage (< 1.5 or 3.5 V)
- (2) Rapid response time [second (mirror)~ minute (window)]
- (3) High color contrast (transmittance attenuation= $\Delta T > 30\%$)
- (4) Long cycle life (>10 yr for window, >3 yr for mirror)
- (5) Environmental stability (electrochemical, thermal, & UV)
- (6) Low cost, easy processing
- (7) **Multiple colors with the same material**

Increasing the electroactive sites by multi-step synthetic procedures.






Polym. Chem. **2012**, *3*, 255-264 ¹⁹

Synthetic route to Starburst Triarylamine-based Polyamide





Electrochromism ranging from visible to NIR region




Chem. Mater. 2009, 21, 4062-4070
J. Mater. Chem. 2011, 21, 6230-6237

Electrochromism ranging from visible to NIR region







$-1 e^-$ (Ox. 1)



JPS-A. **2011**, *49*, 3805-3816



J. Mater. Chem. **2011**, *21*, 6230-6237

Transmissive to Black Electrochromism



Chem. Mater. 2009, 21, 4062-4070
J. Mater. Chem. 2011, 21, 6230-6237


RGB & CMY Electrochromism



Summary

- This talk covered my recent work in the synthesis and structural design of functional materials, which were further used for optoelectronic and energy applications, such as **lithium ion battery**, **solar cell**, **LED**, **electrochromic**, and **fuel cells**.

未來規劃1



未來規劃2

