

IDC RE-ENGINEERING REPORT

SAND2017-XXXXXX

Unlimited Release

January 2017

IDC Re-Engineering Phase 2 System Specification Document

Version 1.5

Allena Satpathi, John Burns, J. Mark Harris

Prepared by
Sandia National Laboratories
Albuquerque, New Mexico 87185 and Livermore, California 94550

Sandia National Laboratories is a multi-mission laboratory managed and operated by Sandia Corporation, a wholly owned subsidiary of Lockheed Martin Corporation, for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-AC04-94AL85000.

Approved for public release; further dissemination unlimited.



Sandia National Laboratories

Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

NOTICE: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, make any warranty, express or implied, or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represent that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof, or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof, or any of their contractors.

Printed in the United States of America. This report has been reproduced directly from the best available copy.



SAND2017-XXXXXX

Unlimited Release

January 2017

IDC Re-Engineering Phase 2

System Specification Document

Version 1.5

Allena Satpathi, John Burns, J. Mark Harris
Next Generation Monitoring Systems
Sandia National Laboratories
P.O. Box 5800
Albuquerque, New Mexico 87185-MS0401

Abstract

This document contains the system specifications derived to satisfy the system requirements found in the IDC System Requirements Document for the IDC Re-Engineering Phase 2 project.

Revisions

Version	Date	Author/Team	Revision Description	Authorized by
1.0	12/2014	IDC Re-Engineering Project Team	Initial delivery	M. Harris
1.1	02/2015	IDC Re-Engineering Project Team	Iteration I2 Review Comments	M. Harris
1.2	02/2015	IDC Re-Engineering Project Team	Iteration I2 Review Comments	D. Brown
1.2.1	05/2015	IDC Re-Engineering Project Team	Associations of SRD-618, -619, -621, -622, -623	D. Brown
1.3	12/2015	IDC Re-Engineering Project Team	Release for E1	M. Harris
1.4	06/2016	IDC Re-Engineering Project Team	Release for E2	M. Harris
1.5	01/2017	IDC Re-Engineering Project Team	Release for E3	M. Harris

Contents

IDC Re-Engineering Phase 2.....	3
System Specification Document.....	3
1 Introduction.....	6
1.1 Scope.....	6
1.2 Relationship to the US NDC Modernization Project.....	6
2 About The Requirements.....	6
2.1 Background Documents	6
2.2 Verification	6
2.2.1 Verification Methodologies	6
2.2.1.2 Analysis (A).....	7
2.2.1.3 Demonstration (D).....	7
2.2.1.4 Test (T).....	7
3 System Requirements.....	7
3.1 Format.....	7
3.2 Specifications.....	7
3.2.1 Data Acquisition	7
3.2.2 Waveform Quality Control.....	21
3.2.3 Signal Enhancement.....	29
3.2.4 Signal Detection	40
3.2.5 Feature Extraction.....	44
3.2.6 Association.....	56
3.2.7 Location	74
3.2.8 Source Properties.....	81
3.2.9 Earth Propagation Models.....	93
3.2.10 Processing Stage Workflow	106
3.2.11 Interactive Analysis	109
3.2.12 User Interface	118
3.2.13 Geographic Information Systems.....	120
3.2.14 Event Bulletins and Reports.....	125
3.2.15 Data Management	130
3.2.16 Performance Monitoring	134
3.2.17 Timeliness and System Loading	144
3.2.18 Security.....	147
3.2.19 Testing	150
3.2.20 External Interfaces	151
3.2.21 System Startup and Shutdown.....	157
3.2.22 Design Constraints	159
3.2.23 Subsystems	160
3.2.24 Hardware	166
4 Specification Traceability.....	168

1 INTRODUCTION

1.1 Scope

This System Specification Document (SSD) defines waveform data processing requirements for the International Data Centre (IDC) of the Comprehensive Nuclear Test Ban Treaty Organization (CTBTO). The IDC applies, on a routine basis, automatic processing methods and interactive analysis to raw International Monitoring System (IMS) data in order to produce, archive, and distribute standard IDC products on behalf of all States Parties. The routine processing includes characterization of events with the objective of screening out events considered to be consistent with natural phenomena or non-nuclear, man-made phenomena. This document does not address requirements concerning acquisition, processing and analysis of radionuclide data but includes requirements for the dissemination of radionuclide data and products.

1.2 Relationship to the US NDC Modernization Project

Like the IDC, the US NDC has begun a project to modernize its waveform processing system. The US NDC and IDC systems are similar in mission functionality and structure, each having evolved from a common early system. These projects are now collaborating to develop a common core architecture. Many IDC specifications benefit from leveraging the specifications developed for US NDC Modernization. The IDC specifications provided here are identified as being common both systems or unique to the IDC.

2 ABOUT THE REQUIREMENTS

2.1 Background Documents

- IDC Reengineering Phase 2 System Requirements Document, Version 1.1, CTBTO, 19 November 2014
- UN General Assembly A/RES/50/245, Comprehensive Nuclear Test-Ban Treaty, 17 September 1996 –
- Operational Manual for Hydroacoustic Monitoring and the International Exchange of Hydroacoustic Data, CTBT/WGB/TL-11, 17/16, Latest Revision –
- Operational Manual for Infrasound Monitoring and the International Exchange of Infrasound Data, CTBT/WGB/TL-11, 17/17, Latest Revision –
- Operational Manual for Seismological Monitoring and the International Exchange of Seismological Data, CTBT/WGB/TL-11, 17/15, Latest Revision –
- International Data Centre Draft Operational Manual, CTBT/WGB/TL-11, 17/23, Latest Revision –
- International Data Centre Analyst Instructions for Seismic, Hydroacoustic, and Infrasound Data, IDC-OPS-SOP-001, Latest Revision

2.2 Verification

SRD requirements are derived into lower level System Specification requirements in the System Specification Document (SSD). The SSD requirements are tested per the following methodologies: Inspection, Analysis, Demonstration, and Test. For some requirements, multiple verification methods may be employed. The following section describes each verification method.

2.2.1 Verification Methodologies.

2.2.1.1 Inspection (I).

Inspection is accomplished by physically examining hardware, source code, parameter files, and/or other physical manifestations of hardware and software, such as software-generated printouts and diagrams. Inspection implies observation/examination to verify requirements, usually without the need for analysis, demonstration, or test. Inspection does not involve software execution.

2.2.1.2 Analysis (A).

Analysis is accomplished by examining and analyzing the internal structure of hardware and software. This will most likely be required when a requirement cannot be directly tested and observed. Analysis may require a review or study of data, mathematical expressions, or software models.

2.2.1.3 Demonstration (D).

Demonstration is accomplished by observing the performance of software or hardware, where specific inputs have an expected result, and when the software is executed on the hardware according to the test procedure.

2.2.1.4 Test (T).

Test is accomplished by exercising software or hardware with pre-determined inputs and then recording and analyzing the measurable response. Test involves measurements or quantitative observations of the performance of a function or equipment. The requirement is verified by comparing test results with quantitative criteria such as predicted values, a range of values, accuracies, or tolerances.

3 SYSTEM REQUIREMENTS

3.1 Format

The specifications presented in this System Specifications Document (SSD) satisfy the system requirements described in the IDC System Requirements Document (SRD). SSD requirements are intended to be unitary, complete, consistent, verifiable, and traceable to SRD requirements. SSD requirements generally contain a higher level of detail than SRD requirements. These specifications are traced to requirements in the IDC Reengineering Phase 2 System Requirements Document (SRD). This relationship is shown for each specification in the "Requirements Trace" field and are identified by their SRD-<number>.

Specifications that define a function or attribute of the system are written in the form "The System shall ...". These functions may be automatically performed or available for use as needed. Specifications that define a user interaction with the System are written in the form "The System shall provide the user the capability to . . .". The term "capability" in this context indicates that the System is required to provide a user interface to perform the defined function. These requirements are written in the same format to identify the requirement as a user interface requirement.

Specifications regarding configuration of processing operations by geographic region facilitate tuning of system performance to adapt to varying earth structure, sensor network coverage, and sources of events.

Specifications numbers are shown in the parenthetical statement after the text of each specification along with the applicability of the specification. The applicability of each specification can be:

- Common – The specification applies to both the IDC Reengineering Phase 2 project and the US NDC Modernization project.
- IDC only – The specification applies to the IDC Reengineering Phase 2 project only.

3.2 Specifications

3.2.1 Data Acquisition

The System hardware and software acquires, organizes, and distributes near-real-time waveform and alphanumeric data from a global sensor network and external monitoring agencies.

3.2.1.1 Data Sources

When a station is added or updated, several configuration parameters are provided which characterize the station and sensors. Station configuration parameters are: station identification, station location, station type, channel configuration, instrument response functions (including the spatial filter for infrasound stations, which makes the overall response a function of azimuth and vertical slowness), time shift, and calibration information.

The System also configures data sources for bulletin data and meteorological data.

3.2.1.1.1 Data Sources Processing

3.2.1.1.2 Data Sources Support Interfaces

3.2.1.1.2.1 The System shall provide the System Maintainer the capability to configure new stations. (S-1133; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-278, SRD-279, SRD-280

3.2.1.1.2.2 The System shall provide the System Maintainer the capability to configure the station instrumentation parameter and sensor deployment. (S-1134; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-278, SRD-384

3.2.1.1.2.3 The System shall provide the System Maintainer the capability to configure processing of data from a new station in processing stages without disrupting ongoing processing operations. (S-1135; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-278, SRD-280

3.2.1.1.2.4 The System shall provide the System Maintainer the capability to configure whether acquisition and storage is enabled or disabled for new station data. (S-1136; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-278, SRD-280

3.2.1.1.2.5 The System shall provide the System Maintainer the capability to configure whether selection for interactive processing is enabled or disabled for new station data. (S-1137; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-278, SRD-280

3.2.1.1.2.6 The System shall provide the System Maintainer the capability to configure whether station processing is enabled or disabled for new station data. (S-1138; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-278, SRD-280

3.2.1.1.2.7 The System shall provide the System Maintainer the capability to configure whether network processing is enabled or disabled for new station data. (S-1139; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-278, SRD-280

3.2.1.1.2.8 The System shall provide the System Maintainer the capability to configure which stations are no longer processed. (S-1140; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-279, SRD-280

3.2.1.1.2.9 The System shall provide the System Maintainer the capability to configure whether ongoing processing or acquisition operations of data from a station or instrument is enabled or disabled in processing stages without disrupting ongoing processing operations. (S-1141; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-279, SRD-280

3.2.1.1.2.10 The System shall provide the System Maintainer the capability to configure seismic stations as either primary or auxiliary. (S-5606; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-432, SRD-433, SRD-434

3.2.1.1.2.11 The System shall provide the System Maintainer the capability to configure event bulletin acquisition sources. (S-5972; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-15

3.2.1.1.2.12 The System shall provide the System Maintainer the capability to configure event bulletin acquisition formats. (S-5973; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-15

3.2.1.1.2.13 The System shall provide the System Maintainer the capability to configure meteorological data acquisition sources. (S-5976; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-411

3.2.1.1.2.14 The System shall provide the System Maintainer the capability to configure meteorological data acquisition formats. (S-5977; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-411

3.2.1.1.3 Data Sources User Interfaces

3.2.1.1.3.1 The System shall provide the System User the capability to view the station instrumentation, station deployment, and station configuration parameter values. (S-1143; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-384, SRD-398

3.2.1.1.3.2 The System shall provide the Authorized External User the capability to view the station instrumentation, station deployment, and station configuration parameter values. (S-5965; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-384, SRD-398

3.2.1.1.4 Data Sources Storage

3.2.1.1.4.1 The System shall store station configuration parameters. (S-1146; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-172, SRD-189, SRD-512

3.2.1.1.4.2 The System shall store the processing time periods when station configuration parameters are active. (S-1147; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-172, SRD-189, SRD-512

3.2.1.1.4.3 The System shall store event bulletin acquisition parameters. (S-5980; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-15

3.2.1.1.4.4 The System shall store meteorological data acquisition parameters. (S-5981; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-411

3.2.1.2 Data Acquisition Status

The System tracks channel data completeness and real-time data acquisition status of each channel. Data completeness states are:

1. Missing data is available but has not been received from the station.
2. Incomplete data is not available, i.e. the station was down.
3. Complete data has been received from the station. Real-time data acquisition status is:
 1. Receiving
 2. Not receiving

3.2.1.2.1 Data Acquisition Status Processing

3.2.1.2.1.1 The System shall notify the Analyst within 1 minute of acquisition when new waveform data arrives during a waveform analysis session that is relevant to that session. (S-1158; Common)

Priority: Objective / Priority 2
Verification Methodology: Test
Requirements Trace: SRD-131

3.2.1.2.1.2 The System shall notify the Analyst within 1 minute of acquisition when new alphanumeric data becomes available during a waveform analysis session that is relevant to that session. (S-1159; Common)

Priority: Objective / Priority 2
Verification Methodology: Test
Requirements Trace: SRD-131

3.2.1.2.1.3 The System shall notify the Analyst within 1 minute of data creation when new alphanumeric data (e.g. events, signal detections) is created during a waveform analysis session that is relevant to that session. (S-6485; Common)

Priority: Objective / Priority 2

Verification Methodology: Test

Requirements Trace: SRD-131

3.2.1.2.2 Data Acquisition Status Support Interfaces

3.2.1.2.3 Data Acquisition Status User Interfaces

3.2.1.2.3.1 The System shall provide the Analyst the capability to view newly acquired waveform data within 1 minute of acquisition. (S-1157; Common)

Priority: Objective / Priority 2

Verification Methodology: Test

Requirements Trace: SRD-130, SRD-131

3.2.1.2.3.2 The System shall provide the System User the capability to view the data completeness states of raw channels on the OPS Subsystem Data Acquisition Partition. (S-1150; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-11

3.2.1.2.3.3 The System shall provide the System User the capability to view the data completeness states of raw channels on the OPS Subsystem Data Processing Partition. (S-1151; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-11

3.2.1.2.3.4 The System shall provide the System User the capability to view the data completeness states of raw channels on the ALT Subsystem Data Acquisition Partition. (S-1152; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-11

3.2.1.2.3.5 The System shall provide the System User the capability to view the data completeness states of raw channels on the ALT Subsystem Data Processing Partition. (S-1153; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-11

3.2.1.2.3.6 The System shall provide the System User the capability to view the real-time data acquisition status of raw channels. (S-1154; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-12

3.2.1.2.3.7 The System shall provide the System User the capability to view the real-time mission capability state of each station. (S-1155; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-12

3.2.1.2.4 Data Acquisition Status Storage

3.2.1.3 Data Acquisition Control

The System acquires station data through multiple paths. All station data must be available on both the OPS and ALT Subsystems. The System Controller controls station data routing to either the OPS Subsystem or the ALT Subsystem. The OPS and ALT Subsystems then exchange data so both Subsystems have the complete set of station data.

The System acquires bulletin data from External Data Centers. The System acquires meteorological data from weather information sources. The System Controller selects to enable or disable data from bulletin or meteorological data sources.

3.2.1.3.1 Data Acquisition Control Processing

3.2.1.3.1.1 The System shall identify data lost during transfer between partitions. (S-2064; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-177

3.2.1.3.1.2 The System shall automatically forward acquired waveform data between partitions. (S-6542; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-441

3.2.1.3.1.3 The System shall provide data buffering allowing acceptance of waveform data arriving a minimum of 10 days after its recording at a station. (S-5580; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-436

3.2.1.3.1.4 The System shall complete transfer of waveform data from the Data Acquisition Partition to the Data Processing Partition within 5 minutes of receipt of the data. (S-5785; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-441

3.2.1.3.1.5 The System shall acquire continuous waveform data from hydroacoustic, infrasound, and primary seismic stations of the IMS Network. (S-5577; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-430

3.2.1.3.1.6 The System shall request waveform data segments from auxiliary seismic stations of the IMS network. (S-5578; IDC only)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-432, SRD-434

3.2.1.3.1.7 The System shall acquire waveform data from auxiliary seismic stations of the IMS Network. (S-5607; IDC only)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-432

3.2.1.3.1.8 The System shall acquire continuous waveform data from hydroacoustic, infrasound, and primary seismic stations of the IMS Network. (S-5609; IDC only)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-433

3.2.1.3.1.9 The System shall acquire all ISC bulletin products. (S-5584; IDC only)

Priority: Objective / Priority 1
Verification Methodology: Demonstration
Requirements Trace: SRD-15

3.2.1.3.1.10 The System shall accept event bulletin data from External Data Centers. (S-5585; Common)

Priority: Objective / Priority 1
Verification Methodology: Demonstration
Requirements Trace: SRD-15

3.2.1.3.1.11 The System shall accept event bulletin data in new formats. (S-1241; Common)

Priority: Objective / Priority 1
Verification Methodology: Demonstration
Requirements Trace: SRD-15

3.2.1.3.1.12 The Data Processing Partition shall access and process all waveform data stored on the system. (S-5610; Common)

Priority: Threshold
Verification Methodology: Analysis
Requirements Trace: SRD-171, SRD-438

3.2.1.3.1.13 The System shall request global meteorological data from specified sources within 10 minutes of its availability. (S-5759; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-600

3.2.1.3.1.14 The system shall request global meteorological data (3D wind, temperature and uncertainties) from specified sources spanning the altitude range of 0 km (sea level) to 140 km above sea level. (S-5623; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-411

3.2.1.3.1.15 The system shall convert global meteorological data received in pressure coordinate format into altitude coordinate format. (S-5624; Common)

Priority: Threshold
Verification Methodology: Demonstration

Requirements Trace: SRD-411, SRD-600, SRD-652

3.2.1.3.1.16 The system shall compute data availability metrics for data acquisition as specified in the IDC Operational Manual. (S-5622; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-442

3.2.1.3.2 Data Acquisition Control Support Interfaces

3.2.1.3.2.1 The System shall provide the System Controller the capability to select the stations providing data to ALT Subsystem. (S-1179; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-432, SRD-433, SRD-434

3.2.1.3.2.2 The System shall provide the System Controller the capability to start acquiring data from one or more stations. (S-1180; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-13

3.2.1.3.2.3 The System shall provide the System Controller the capability to stop acquiring data from one or more stations. (S-1181; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-13

3.2.1.3.2.4 The System shall provide the System Controller the capability to select the stations providing data to OPS Subsystem. (S-1182; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-432

3.2.1.3.2.5 The System shall provide the System Controller the capability to request that waveform data be re-transmitted between partitions (S-1184; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-18

3.2.1.3.2.6 The System shall provide the System Controller the capability to select per event bulletin data source whether event bulletin data acquisition is enabled or disabled for new event bulletin data. (S-5974; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-15

3.2.1.3.2.7 The System shall provide the System Controller the capability to select per meteorological data source whether meteorological data acquisition is enabled or disabled for new meteorological data. (S-5978; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-411

3.2.1.3.2.8 The System shall provide the System Maintainer the capability to configure how the System creates seed events from event bulletins. (S-6524; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-76, SRD-77

3.2.1.3.3 Data Acquisition Control User Interfaces

3.2.1.3.3.1 The System shall provide the System User the capability to view acquired station State-of-Health data. (S-1189; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.1.3.3.2 The System shall provide the Analyst the capability to access and view all waveform data stored on the System. (S-1878; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-124, SRD-136, SRD-171, SRD-218, SRD-438

3.2.1.3.3.3 The System shall provide the Analyst the capability to request auxiliary seismic waveform data from the Data Acquisition Partition. (S-5612; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-438

3.2.1.3.4 Data Acquisition Control Storage

3.2.1.3.4.1 The System shall store all raw waveform data. (S-1191; Common)

Priority: Objective / Priority 1

Verification Methodology: Analysis

Requirements Trace: SRD-171, SRD-611

3.2.1.3.4.2 The System shall store signed waveform data in a format supporting retrospective authentication. (S-1192; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-10, SRD-611

3.2.1.3.4.3 The System shall store all data that are available for external release on the Data Acquisition Partition. (S-5625; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-431

3.2.1.3.4.4 The System shall store station calibration results. (S-5670; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-493

3.2.1.4 Data Authentication

Data authentication is used to ensure that data processed by the System is the data that was created and transmitted by a Station or External Data Center. A digital signature is generated for each data packet at the source of the data and transmitted with the data. The system uses the digital signature and the signer's public key to verify

that the data is authentic. A public key infrastructure (PKI) system is used to certify, store, and distribute public keys.

3.2.1.4.1 Data Authentication Processing

3.2.1.4.1.1 The System shall authenticate the digital signature using PKI credentials upon receipt of signed station waveform data. (S-1199; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-9

3.2.1.4.1.2 The System shall use PKI to digitally authenticate data requests received from an External Data Center. (S-5613; IDC only)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-21

3.2.1.4.1.3 The System shall use PKI to digitally authenticate data requests received from the Authorized External User. (S-5614; IDC only)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-21

3.2.1.4.1.4 The System shall perform retrospective authentication on signed waveform data. (S-1203; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-10

3.2.1.4.1.5 The System shall allow for PKI credential changes without interrupting operations if made prior to key expiration. (S-1204; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-9

3.2.1.4.1.6 The System shall mark acquired waveform data as unauthenticated when the data cannot be authenticated. (S-1205; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-9

3.2.1.4.2 Data Authentication Support Interfaces

3.2.1.4.2.1 The System shall provide the System Controller the capability to generate and install PKI credentials. (S-1207; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-9

3.2.1.4.2.2 The System shall notify the System Controller of expiring PKI credentials a minimum of five (5) days prior to key expiration. (S-1208; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-9

3.2.1.4.2.3 The System shall provide the System Maintainer the capability to retrospectively authenticate signed waveform data. (S-5946; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-10

3.2.1.4.3 Data Authentication User Interfaces

3.2.1.4.4 Data Authentication Storage

3.2.1.4.4.1 The System shall store all PKI credentials used to digitally sign station waveform data. (S-1210; Common)

Priority: Objective / Priority 1
Verification Methodology: Analysis
Requirements Trace: SRD-10, SRD-179

3.2.1.5 Data Forwarding

The system receives and continuously sends waveform data and bulletins to a defined set of external customers. This process is called data forwarding.

3.2.1.5.1 Data Forwarding Processing

3.2.1.5.1.1 The System shall automatically forward data in near-real time in the CD1.1 format. (S-1220; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-22

3.2.1.5.1.2 The System shall convert station configuration data to Station/FDSNXML format. (S-5706; IDC only)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-505

3.2.1.5.1.3 The System shall convert station configuration data to SeisComP3XML format. (S-5707; IDC only)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-505

3.2.1.5.1.4 The System shall provide an extensible architecture for the distribution of new data and reports. (S-5710; Common)

Priority: Threshold
Verification Methodology: Analysis
Requirements Trace: SRD-409, SRD-505

3.2.1.5.2 Data Forwarding Support Interfaces

3.2.1.5.3 Data Forwarding User Interfaces

3.2.1.5.3.1 The System shall provide the System Controller the capability to select the station data forwarded to each internal destination. (S-1227; Common)

Priority: Threshold
Verification Methodology: Demonstration

Requirements Trace: SRD-22

3.2.1.5.3.2 The System shall provide the System Controller the capability to select the station data forwarded to each external destination. (S-1228; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-22

3.2.1.5.3.3 The System shall provide the System User the capability to view the authentication status of waveform data. (S-5582; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-25

3.2.1.5.3.4 The System shall provide the System User the capability to view information about forwarded waveform data. (S-5583; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-22, SRD-25

3.2.1.5.3.5 The System shall provide the System Controller the capability to select the destinations of forwarded waveform data. (S-5781; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-22

3.2.1.5.3.6 The System shall provide the System Controller the capability to select the bulletins forwarded to each internal destination. (S-5782; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-22

3.2.1.5.3.7 The System shall provide the System Controller the capability to select the bulletins forwarded to each external destination. (S-5783; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-22

3.2.1.5.3.8 The System shall provide the System Controller the capability to select the destinations of forwarded bulletins. (S-5784; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-22

3.2.1.5.4 Data Forwarding Storage

3.2.1.6 Waveform Formats

3.2.1.6.1 Waveform Formats Processing

3.2.1.6.1.1 The System shall accept station information in the StationXML format. (S-6500; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-300

3.2.1.6.1.2 The System shall accept station information in the SC3XML format. (S-6501; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-300

3.2.1.6.1.3 The System shall accept waveform data in the CD1.1 format. (S-1234; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-430

3.2.1.6.1.4 The System shall accept waveform data in the CD1.0 format. (S-1235; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-430

3.2.1.6.1.5 The System shall accept station information, waveform data, and processing results in the CSS3.0 format. (S-1236; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-430

3.2.1.6.1.6 The System shall accept station information and waveform data in the SEED format. (S-1237; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-611

3.2.1.6.1.7 The System shall accept waveform data in the mini-SEED format. (S-1238; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-611

3.2.1.6.1.8 The System shall accept waveform data in the Antelope format. (S-1239; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-611

3.2.1.6.1.9 The System shall accept station information, waveform data, and processing results in the Geolib format. (S-6538; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-300

3.2.1.6.1.10 The System shall accept station information, waveform data, and processing results in the IMS2.0 format. (S-5970; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-430

3.2.1.6.1.11 The System shall accept waveform data in the SAC format. (S-5971; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-245

3.2.1.6.1.12 The System shall accept waveform data in new formats. (S-1240; Common)

Priority: Extensibility

Verification Methodology: Test

Requirements Trace: SRD-611

3.2.1.6.1.13 The System shall export station information, waveform data, and processing results in the CSS3.0 format. (S-6502; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-300

3.2.1.6.1.14 The System shall export station information, waveform data, and processing results in the Geolib format. (S-6539; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-300

3.2.1.6.1.15 The System shall export station information, waveform data, and processing results in the IMS2.0 format. (S-6503; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-300

3.2.1.6.1.16 The System shall export waveform data in the SEED format. (S-6504; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-300

3.2.1.6.1.17 The System shall export waveform data in the mini-SEED format. (S-6505; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-300

3.2.1.6.1.18 The System shall export waveform data in the SAC format. (S-6506; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-300

3.2.1.6.1.19 The System shall export station information in the SEED format. (S-6507; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-300

3.2.1.6.1.20 The System shall export station information in the StationXML format. (S-6508; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-300

3.2.1.6.1.21 The System shall export station information in the SC3XML format. (S-6509; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-300

3.2.1.6.1.22 The System shall export waveform data in new formats. (S-6510; Common)

Priority: Extensibility

Verification Methodology: Analysis

Requirements Trace: SRD-300

3.2.1.6.1.23 The System shall export event bulletin data in new formats. (S-6511; Common)

Priority: Extensibility

Verification Methodology: Analysis

Requirements Trace: SRD-300

3.2.1.6.2 Waveform Formats Support Interfaces

3.2.1.6.3 Waveform Formats User Interfaces

3.2.1.6.3.1 The System shall provide the Authorized External User the capability to request waveform data in the SEED format. (S-1247; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-616

3.2.1.6.3.2 The System shall provide the Authorized External User the capability to request waveform data in the CSS 3.0 format. (S-1248; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-616

3.2.1.6.3.3 The System shall provide the Authorized External User the capability to request waveform data in the IMS2.0 format. (S-1250; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace:

3.2.1.6.4 Waveform Formats Storage

3.2.2 Waveform Quality Control

The System's waveform data may contain errors caused by recording or transmission problems. Waveform Quality Control processing identifies waveform sections containing errors and marks those sections with Waveform Quality Control Masks (Waveform QC Masks). Each Waveform QC Mask has a defined start time and end time delimiting the waveform section marked and potentially removed from processing. If configured, the System does not use waveform sections marked with Waveform QC Masks during waveform processing.

3.2.2.1 Waveform Quality Control Processing

3.2.2.1.1 The System shall automatically identify waveforms containing repairable data gaps. (S-1253; Common)

Priority: Threshold

Verification Methodology: Test
Requirements Trace: SRD-29, SRD-406

3.2.2.1.2 The System shall automatically identify waveforms containing long data gaps. (S-5592; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-29, SRD-406

3.2.2.1.3 The System shall automatically create a Waveform QC Mask for a waveform containing a long data gap. (S-1254; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-29, SRD-406

3.2.2.1.4 The System shall automatically identify waveforms containing amplitude spikes. (S-1255; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-29, SRD-406

3.2.2.1.5 The System shall automatically create a Waveform QC Mask for a waveform containing an amplitude spike. (S-1256; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-29, SRD-406

3.2.2.1.6 The System shall automatically identify waveforms containing repeated adjacent amplitude values. (S-1257; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-29, SRD-406

3.2.2.1.7 The System shall automatically create a Waveform QC Mask for a waveform containing a repeated amplitude value data error. (S-1258; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-29, SRD-406

3.2.2.1.8 The System shall automatically identify waveforms containing linear trends in amplitude. (S-1259; Common)

Priority: Extensibility
Verification Methodology: Test
Requirements Trace: SRD-29, SRD-406

3.2.2.1.9 The System shall automatically fit linear trends to waveform data. (S-1260; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-29, SRD-406

3.2.2.1.10 The System shall automatically create a Waveform QC Mask for a waveform containing a waveform linear trend data error. (S-1261; Common)

Priority: Extensibility
Verification Methodology: Test

Requirements Trace: SRD-29, SRD-406

3.2.2.1.11 The System shall automatically create a Waveform QC Mask for a waveform containing a calibration signal. (S-1262; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-29, SRD-406

3.2.2.1.12 The System shall automatically create a Waveform QC Mask for a waveform containing invalid gain. (S-1264; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-29, SRD-406

3.2.2.1.13 The System shall automatically identify the percent of data samples in a waveform section containing data errors. (S-1265; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-29, SRD-406

3.2.2.1.14 The System shall automatically create a Waveform QC Mask for a waveform section containing errors in more than the allowed percentage of data samples. (S-1266; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-29, SRD-406

3.2.2.1.15 The System shall automatically identify waveform data that fails data authentication. (S-6219; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-29, SRD-406

3.2.2.1.16 The System shall automatically create a Waveform QC Mask for waveform data that fails data authentication. (S-6220; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-29, SRD-406

3.2.2.1.17 The System shall maximize the length of a Waveform QC Mask created for a waveform section containing errors in more than the allowed percentage of data samples. (S-1267; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-29, SRD-406

3.2.2.1.18 The System shall begin a Waveform QC Mask created for a waveform section containing errors in more than the allowed percentage of data samples on a sample containing a data error. (S-1268; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-29, SRD-406

3.2.2.1.19 The System shall terminate an automatically created Waveform QC Mask when the condition leading to the creation of that Waveform QC Mask is no longer satisfied. (S-1269; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-29, SRD-406

3.2.2.1.20 The System shall use State-of-Health information acquired from stations to identify waveform sections known to contain data errors and create Waveform QC Masks for those sections. (S-1270; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-29, SRD-406

3.2.2.1.21 The System shall create a Waveform QC Mask for a channel from a multichannel station containing noisy data relative to the other channels from that station. (S-1271; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-29, SRD-54, SRD-406

3.2.2.1.22 The System shall create a Waveform QC Mask for a channel containing noisy data relative to a global noise model. (S-5593; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-29, SRD-54, SRD-406

3.2.2.1.23 The System shall create a Waveform QC Mask for a channel containing noisy data relative to a station noise model. (S-5594; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-29, SRD-54, SRD-406

3.2.2.1.24 The System shall create Waveform QC Masks with times in the future. (S-1272; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-31

3.2.2.1.25 The System shall select to process waveform data containing a QC Mask based on configured parameters. (S-1273; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-33

3.2.2.1.26 The System shall automatically identify waveform data containing timing errors. (S-6495; Common)

Priority: Objective / Priority 2

Verification Methodology: Test

Requirements Trace: SRD-29, SRD-406

3.2.2.1.27 The System shall automatically create a Waveform QC Mask for waveform data containing timing errors. (S-6496; Common)

Priority: Objective / Priority 2
Verification Methodology: Test
Requirements Trace: SRD-29, SRD-406

3.2.2.2 Waveform Quality Control Support Interfaces

3.2.2.2.1 The System shall provide the System Maintainer the capability to configure the minimum change in amplitude with respect to time that is automatically recognized as an amplitude spike. (S-1275; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-29, SRD-406

3.2.2.2.2 The System shall provide the System Maintainer the capability to configure the minimum number of equal, consecutive amplitude values required for automatic recognition of a repeated amplitude value data error. (S-1276; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-29, SRD-406

3.2.2.2.3 The System shall provide the System Maintainer the capability to configure the maximum percent of data samples in a waveform section allowed to contain data errors. (S-1278; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-29, SRD-406

3.2.2.2.4 The System shall provide the System Maintainer the capability to configure Waveform QC Mask processing parameters on a per station basis. (S-5595; IDC only)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-29, SRD-406

3.2.2.2.5 The System shall provide the System Maintainer the capability to configure the execution order of Waveform QC Mask application on a per sensor basis. (S-1280; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-29, SRD-406

3.2.2.2.6 The System shall provide the System Maintainer the capability to configure the maximum time length in the future for user created Waveform QC Masks. (S-1281; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-31

3.2.2.2.7 The System shall provide the System Maintainer the capability to authorize a System User to create Waveform QC masks extending into the future. (S-1282; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-31

3.2.2.2.8 The System shall provide the System Maintainer the capability to configure on a channel basis whether waveform data with a specific type of QC mask is processed. (S-5936; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-29

3.2.2.3 Waveform Quality Control User Interfaces

3.2.2.3.1 The System shall provide the Analyst the capability to view Waveform QC Masks. (S-1284; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-33, SRD-34, SRD-124, SRD-136, SRD-444

3.2.2.3.2 The System shall provide the Analyst the capability to view the Waveform QC Masks that were active at a user specified date and time. (S-1285; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-30, SRD-34, SRD-124, SRD-136, SRD-407, SRD-444

3.2.2.3.3 The System shall provide the Analyst the capability to create a Waveform QC Mask for a selected channel and time interval. (S-1286; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-30, SRD-124, SRD-136, SRD-407, SRD-623

3.2.2.3.4 The System shall provide the Analyst the capability to modify Waveform QC Masks. (S-1287; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-30, SRD-124, SRD-136, SRD-407

3.2.2.3.5 The System shall provide the Analyst the capability to reject Waveform QC Masks. (S-1288; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-30, SRD-124, SRD-136, SRD-407

3.2.2.3.6 The System shall provide the Analyst the capability to enter rationale for creating a Waveform QC Mask. (S-1289; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-30, SRD-124, SRD-136, SRD-407

3.2.2.3.7 The System shall provide the Analyst the capability to enter rationale for modifying a Waveform QC Mask. (S-1290; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-30, SRD-124, SRD-136, SRD-407

3.2.2.3.8 The System shall provide the Analyst the capability to enter rationale for removing a Waveform QC Mask. (S-1291; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-30, SRD-124, SRD-136, SRD-407

3.2.2.3.9 The System shall provide the System User the capability to compare Waveform QC Masks generated by each processing stage for selected points in the processing history. (S-1292; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-237

3.2.2.3.10 The System shall provide the System User the capability to compare Waveform QC Masks generated by each Subsystem for selected points in the processing history. (S-1293; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-237

3.2.2.3.11 The System shall provide an authorized System User the capability to create a Waveform QC Mask extending into the future. (S-1294; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-31, SRD-136

3.2.2.4 Waveform Quality Control Storage

3.2.2.4.1 The System shall store the processing time period(s) during which each Waveform QC Mask was applied to the underlying waveform data. (S-1296; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-33, SRD-172, SRD-189

3.2.2.4.2 The System shall store the Waveform QC Masks applied to the waveform data used for each waveform processing operation. (S-1297; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-33, SRD-172, SRD-189, SRD-444

3.2.2.4.3 The System shall store the channel masked by each Waveform QC Mask. (S-1298; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-30, SRD-172, SRD-189

3.2.2.4.4 The System shall store the identity of the user or processing stage creating each Waveform QC Mask. (S-1299; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-30, SRD-189

3.2.2.4.5 The System shall store the identity of the user or processing stage modifying each Waveform QC Mask. (S-1300; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-30, SRD-189

3.2.2.4.6 The System shall store the identity of the user or processing stage removing each Waveform QC Mask. (S-1301; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-30, SRD-189

3.2.2.4.7 The System shall store the time of each Waveform QC Mask creation. (S-1302; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-32, SRD-189

3.2.2.4.8 The System shall store the time of each Waveform QC Mask removal. (S-1303; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-32, SRD-189

3.2.2.4.9 The System shall store the time of each Waveform QC Mask modification. (S-1304; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-32, SRD-189

3.2.2.4.10 The System shall store the type of error being masked for each automatically created Waveform QC Mask. (S-1305; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-32, SRD-172, SRD-189, SRD-492

3.2.2.4.11 The System shall store the Analyst's rationale for creating a Waveform QC Mask. (S-1306; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-30, SRD-189

3.2.2.4.12 The System shall store the Analyst's rationale for modifying a Waveform QC Mask. (S-1307; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-30, SRD-189

3.2.2.4.13 The System shall store the Analyst's rationale for removing a Waveform QC Mask. (S-1308; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-30, SRD-189

3.2.3 Signal Enhancement

Waveform processing is performed to enhance event signals while suppressing background noise. The System creates derived channels from raw channel inputs by filtering, rotating, or beaming input channels.

3.2.3.1 Waveform Filtering

3.2.3.1.1 Waveform Filtering Processing

3.2.3.1.1.1 The System shall provide a waveform filter library containing commonly used filters. (S-1312; Common)

Priority: Threshold

Verification Methodology: Inspection

Requirements Trace: SRD-38

3.2.3.1.1.2 The System shall filter waveforms using the coefficients from the numerator and denominator of the filter's transfer function. (S-1313; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-38

3.2.3.1.1.3 The System shall downsample waveforms (filter and decimate). (S-1314; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-38

3.2.3.1.1.4 The System shall apply a constant phase offset while downsampling waveforms. (S-1315; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-38

3.2.3.1.1.5 The System shall upsample waveforms. (S-1316; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-38

3.2.3.1.1.6 The System shall apply a constant phase offset while upsampling waveforms. (S-1317; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-38

3.2.3.1.1.7 The System shall cascade up to 10 filters. (S-1318; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-38, SRD-62, SRD-653

3.2.3.1.1.8 The System shall convert analog filter transfer functions to digital filter transfer functions. (S-1319; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-38

3.2.3.1.1.9 The System shall compute the time shift of a filter's group delay from the coefficients of that filter's transfer function. (S-1320; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-39

3.2.3.1.1.10 The System shall shift filter output waveforms to remove filter group delay. (S-1321; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-39

3.2.3.1.1.11 The System shall automatically shift waveforms to remove recording instrument response delay. (S-1322; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-39

3.2.3.1.1.12 The System shall remove recording instrument response from waveforms. (S-1323; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-38

3.2.3.1.1.13 The System shall remove a waveform's DC offset. (S-1324; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-38

3.2.3.1.1.14 The System shall convert amplitude measurements from measured counts to earth displacement. (S-1326; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-62

3.2.3.1.1.15 The System shall convert amplitude measurements from measured counts to velocity. (S-5631; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-62

3.2.3.1.1.16 The System shall convert amplitude measurements from measured counts to acceleration. (S-5632; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-62

3.2.3.1.1.17 The System shall not apply a filter to any waveform for which the difference between the filter's sample rate and the waveform's sample rate is greater than the filter's sample rate tolerance. (S-1327; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-38

3.2.3.1.1.18 The System shall filter waveforms using phase match filters. (S-6199; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-38

3.2.3.1.1.19 The System shall filter waveforms using autoregressive filters. (S-6200; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-38

3.2.3.1.1.20 The System shall filter waveforms using pseudo-correlation filters. (S-6201; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-38

3.2.3.1.2 Waveform Filtering Support Interfaces

3.2.3.1.2.1 The System shall provide the System Maintainer the capability to configure waveform filters by channel. (S-2418; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38

3.2.3.1.2.2 The System shall provide the System Maintainer the capability to configure the dispersion models to be used for phase match filtering. (S-6195; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38

3.2.3.1.2.3 The system shall provide the System Maintainer the capability to configure a set of pre-defined filters for Analyst application to waveforms. (S-6202; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38

3.2.3.1.3 Waveform Filtering User Interfaces

3.2.3.1.3.1 The System shall provide the Analyst the capability to design a Butterworth filter. (S-1334; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38, SRD-124, SRD-136

3.2.3.1.3.2 The System shall provide the Analyst the capability to design a Pseudo Correlation filter. (S-1335; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38, SRD-62, SRD-124, SRD-136, SRD-653

3.2.3.1.3.3 The System shall provide the Analyst the capability to design a Phase Match filter. (S-1336; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38, SRD-62, SRD-124, SRD-136, SRD-653

3.2.3.1.3.4 The System shall provide the Analyst the capability to design an autoregressive filter. (S-1337; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38, SRD-62, SRD-124, SRD-136, SRD-653

3.2.3.1.3.5 The System shall provide the Analyst the capability to design a filter by directly specifying the coefficients of the numerator and denominator of the filter's transfer function. (S-1338; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38, SRD-124, SRD-136

3.2.3.1.3.6 The System shall provide the Analyst the capability to enter textual descriptions for user designed waveform filters. (S-1339; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38, SRD-124, SRD-136

3.2.3.1.3.7 The System shall provide the Analyst the capability to save user designed filters. (S-5956; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-136

3.2.3.1.3.8 The System shall provide the Analyst the capability to view filtered waveforms. (S-1340; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38, SRD-124, SRD-136

3.2.3.1.3.9 The System shall provide the Analyst the capability to view predefined filters. (S-5955; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-136

3.2.3.1.3.10 The System shall provide the Analyst the capability to view predefined waveform filter parameters. (S-1341; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38, SRD-124, SRD-136

3.2.3.1.3.11 The System shall provide the Analyst the capability to apply predefined filters to selected waveforms. (S-1342; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38, SRD-124, SRD-136

3.2.3.1.3.12 The System shall provide the Analyst the capability to design filter cascades. (S-1343; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38, SRD-124, SRD-136

3.2.3.1.3.13 The System shall notify the Analyst when a filter is not applied to a waveform because the difference between the filter's sample rate and the waveform's sample rate is greater than the filter's sample rate tolerance. (S-1344; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-38, SRD-124, SRD-136

3.2.3.1.3.14 The System shall provide the Researcher the capability to decimate waveforms. (S-1331; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38, SRD-124, SRD-136

3.2.3.1.3.15 The System shall provide the Researcher the capability to interpolate waveforms. (S-1332; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38, SRD-124, SRD-136

3.2.3.1.3.16 The System shall provide the Researcher the capability to resample waveforms. (S-1333; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38, SRD-124, SRD-136

3.2.3.1.3.17 The System shall provide the Analyst the capability to select the dispersion model to be used for phase match filtering. (S-6196; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-38, SRD-124, SRD-136

3.2.3.1.4 Waveform Filtering Storage

3.2.3.1.4.1 The System shall store a textual description with each waveform filter. (S-1346; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-38, SRD-189

3.2.3.1.4.2 The System shall store filters using the coefficients of the numerator and denominator of the filter's transfer function. (S-1347; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-38

3.2.3.2 Waveform Rotation

Data from a three component seismometer is rotated to the signal's angle of arrival to form traces that correspond to radial and transverse ground motion.

3.2.3.2.1 Waveform Rotation Processing

3.2.3.2.1.1 The System shall rotate the components of 3-component seismic waveform data from one 3-dimensional coordinate system to another 3-dimensional coordinate system. (S-1350; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-382

3.2.3.2.2 Waveform Rotation Support Interfaces

3.2.3.2.2.1 The System shall provide the System Maintainer the capability to configure 3-component seismic waveform rotations by station. (S-2422; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-382

3.2.3.2.3 Waveform Rotation User Interfaces

3.2.3.2.3.1 The System shall provide the Analyst the capability to rotate the components of 3-component seismic waveform data to any Analyst specified 3-dimensional coordinate system. (S-1352; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-382

3.2.3.2.3.2 The System shall provide the Analyst the capability to rotate the components of 2-component horizontal seismic waveform data to any Analyst specified azimuth. (S-1353; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-382

3.2.3.2.4 Waveform Rotation Storage

3.2.3.3 Beamforming

Beamforming is a multichannel signal processing technique that focuses the elements of an array in a specific direction. This provides a signal to noise ratio gain via constructive interference of coherent directional signals and destructive interference of incoherent background noise. Beam definition parameters are: channels forming the beam, time interval, waveform filter, beam type (fk, origin, or detection), azimuth targeted by the beam, slowness targeted by the beam, phase targeted by the beam, whether or not the beam is coherent, travel time model and travel time uncertainty model used to predict signal arrival times.

3.2.3.3.1 Beamforming Processing

3.2.3.3.1.1 The System shall create beams using a specified set of channels. (S-1356; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-384

3.2.3.3.1.2 The System shall form coherent beams. (S-1357; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-384

3.2.3.3.1.3 The System shall form incoherent beams. (S-1358; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-384

3.2.3.3.1.4 The System shall form beams for specified time windows. (S-1359; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-384

3.2.3.3.1.5 The System shall form beams for specified azimuth and slowness pairs. (S-1360; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-384

3.2.3.3.1.6 The System shall compute continuous beams for virtual event hypotheses for predefined geographic regions. (S-1361; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-144

3.2.3.3.1.7 The System shall account for differences in array element sensor vertical position when forming beams. (S-1362; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-384

3.2.3.3.1.8 The System shall filter waveform data from individual channels before beam forming to make channel frequency content consistent across all channels in the beam. (S-1363; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-384

3.2.3.3.1.9 The System shall convert individual channels from measured counts to earth displacement before using the channels to form beams. (S-1364; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-384

3.2.3.3.1.10 The System shall first rotate 3-component data from each seismic array element before beaming to form radial origin beams for 3-component seismic arrays. (S-1365; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-382, SRD-384

3.2.3.3.1.11 The System shall first rotate 3-component data from each seismic array element before beaming to form transverse origin beams for 3-component seismic arrays. (S-1366; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-382, SRD-384

3.2.3.3.1.12 The System shall first rotate 3-component data from each seismic array element before beaming to form radial fk-beams for 3-component seismic arrays. (S-1367; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-382, SRD-384

3.2.3.3.1.13 The System shall first rotate 3-component data from each seismic array element before beaming to form transverse fk-beams for 3-component seismic arrays. (S-1368; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-382, SRD-384

3.2.3.3.1.14 The System shall create an origin beam steered to an event hypothesis' hypocenter and a seismic array station's predicted first P arrival time whenever a seismic array station lacks a first P signal detection association. (S-1405; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-447

3.2.3.3.1.15 The System shall automatically generate fk spectra from array station waveform data when a signal detection occurs at an array element. (S-1403; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-384, SRD-446

3.2.3.3.1.16 The System shall automatically generate a beam for the vector corresponding to the fk spectrum peak for a detection. (S-1404; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-384, SRD-446

3.2.3.3.1.17 The System shall create beams steered to the measured azimuth and slowness for all signal detections created for array stations. (S-5787; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-446

3.2.3.3.1.18 The System shall create a time-series of maximum F-statistic values for specified time windows. (S-6197; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-384

3.2.3.3.1.19 The System shall create detection feature maps with the time and frequency dependent spatial coherence of waveforms. (S-6467; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-653

3.2.3.3.2 Beamforming Support Interfaces

3.2.3.3.2.1 The System shall provide the System Maintainer the capability to configure array station beams by station. (S-2424; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-384

3.2.3.3.2.2 The System shall provide the System Maintainer the capability to configure for which phases and stations to automatically create origin beams. (S-5789; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-384, SRD-447

3.2.3.3.2.3 The System shall provide the System Maintainer the capability to configure detection feature map calculations per station. (S-6470; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-653

3.2.3.3.3 Beamforming User Interfaces

3.2.3.3.3.1 The System shall notify the Analyst when the channels selected for a beam measure inconsistent types of ground motion. (S-1370; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-124, SRD-136, SRD-384

3.2.3.3.3.2 The System shall notify the Analyst when any two channels selected for a beam have sample rates that differ by more than the beam's sample rate tolerance. (S-1371; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-124, SRD-136, SRD-384

3.2.3.3.3.3 The System shall provide the Analyst the capability to view continuous beams. (S-1372; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.3.3.3.4 The System shall provide the Analyst the capability to view continuous beams for virtual event hypotheses for predefined geographic regions. (S-1373; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-144

3.2.3.3.3.5 The System shall provide the Analyst the capability to view beam parameters. (S-1374; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-171

3.2.3.3.3.6 The System shall provide the Analyst the capability to select channels included in a beam from a subset of configured channels. (S-1375; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-384

3.2.3.3.3.7 The System shall provide the Analyst the capability to create beams for a user specified time interval. (S-1376; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-384

3.2.3.3.3.8 The System shall provide the Analyst the capability to create beams for a user specified azimuth and slowness selected from an fk spectra. (S-1377; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-145, SRD-384

3.2.3.3.3.9 The System shall provide the Analyst the capability to create beams for a user specified event hypothesis and phase. (S-1378; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-145, SRD-384

3.2.3.3.3.10 The System shall provide the Analyst the capability to create beams for a user specified hypocenter (latitude, longitude, depth) and phase. (S-1379; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-145, SRD-384

3.2.3.3.3.11 The System shall provide the Analyst the capability to form coherent beams. (S-1380; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-384

3.2.3.3.3.12 The System shall provide the Analyst the capability to form incoherent beams. (S-1381; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-384

3.2.3.3.3.13 The System shall provide the Analyst the capability to create beams for a user specified/selected point in slowness space. (S-1382; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-145

3.2.3.3.3.14 The System shall provide the Analyst the capability to view array coherence. (S-1383; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-245

3.2.3.3.3.15 The System shall provide the Analyst the capability to create detection feature maps. (S-6468; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-653

3.2.3.3.3.16 The system shall provide the Analyst the capability to view a time-series of maximum F-statistic values for specified time windows. (S-6198; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.3.3.4 Beamforming Storage

3.2.3.3.4.1 The System shall store the beam definition parameters for all beams. (S-1386; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-171, SRD-189, SRD-384

3.2.3.3.4.2 The System shall store continuous beams for virtual event hypotheses for predefined locations. (S-1387; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189

3.2.3.3.4.3 The System shall store detection feature maps. (S-6469; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-653

3.2.3.4 Derived Waveform Data

The System indefinitely stores raw waveforms and derived waveforms with associated signal detections. Once stored, derived waveforms with no associated signal detections will be deleted after the Operational Processing Time Period unless saved by the Analyst.

3.2.3.4.1 Derived Waveform Data Processing

3.2.3.4.2 Derived Waveform Data Support Interfaces

3.2.3.4.2.1 The System shall provide the System Maintainer the capability to configure which derived waveforms with no related signal detections are stored during automated processing. (S-1391; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-180

3.2.3.4.3 Derived Waveform Data User Interfaces

3.2.3.4.3.1 The System shall provide the Analyst the capability to store selected derived waveforms. (S-2420; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-171, SRD-189

3.2.3.4.4 Derived Waveform Data Storage

3.2.3.4.4.1 The System shall store all derived channels related to one or more signal detections. (S-1393; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-171

3.2.3.4.4.2 The System shall store derived waveform data with no related signal detections for the Operational Processing Time Period. (S-1394; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-171, SRD-180

3.2.4 Signal Detection

The System is designed to automatically and continuously detect signals of interest.

A signal detection marks a signal of interest's onset time on a particular channel.

Power detectors are used to find signal onset by recognizing sudden increases in a waveform's energy content over the typical (background noise) energy content of the waveform. Power detectors work by forming a detection when the ratio of the waveform's short term average energy (STA) to the waveform's long term average energy (LTA) exceeds a threshold value. The phrases "short term" and "long term" are used to indicate relative lengths of time, and the LTA is assumed to represent the background noise level.

Z detectors are extensions of power detectors used to find signal onset by recognizing when STA differs from LTA by more than the amount expected for a time period containing only background noise. To do this, the standard error, Z, of (STA-LTA) is computed and detections are formed when the ratio of (STA-LTA) to Z exceeds a threshold.

Log-Z detectors operate the same as Z-detectors but use $\log(\text{STA})$ and $\log(\text{LTA})$ in place of STA and LTA.

Power detectors, Z detectors, and log-Z detectors are parameterized by: short term time length, long term time length, the offset between the beginning of the short term and long term time periods, and threshold.

F detectors are used by array stations to find signal onset time. The signal is assumed to be coherent across array elements and the noise is assumed to be incoherent, so the background noise power is estimated using the residuals between each array element's power and the beam power. Because of this, the time period used to find signal power is the same as the time period used to find the noise power. F detectors form a detection when the ratio of beam power to noise power exceeds a threshold.

F detectors are parameterized by: the time period used to calculate power and threshold.

Waveform correlation detectors find waveform sections containing high cross correlation with waveforms from known events. Waveform correlation detection includes subspace detection.

In addition to the parameters that control when detections are declared, detectors must also have parameters controlling the time intervals detectors must wait before declaring new signal detections. Too short an interval can

lead to bursts of spurious detections following a legitimate detection while too long an interval can lead to missing legitimate detections. Waiting time intervals only prevent signal detectors from declaring new signal detections for signals arriving with the same azimuth and slowness as the original signal detection initiating the time interval.

3.2.4.1 Signal Detection Processing

3.2.4.1.1 The System shall use power detectors to form signal detections on waveforms. (S-1397; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-653

3.2.4.1.2 The System shall use Z detectors to form signal detections on waveforms. (S-1398; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-653

3.2.4.1.3 The System shall use log-Z detectors to form signal detections on waveforms. (S-1399; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-653

3.2.4.1.4 The System shall use the Progressive Multi-Channel Correlation (PMCC) detector to form signal detections on waveforms. (S-5573; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-653

3.2.4.1.5 The System shall use F detectors to form signal detections on beams. (S-1400; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-653

3.2.4.1.6 The System shall detect signals of interest in waveform data by correlating the waveform with waveforms from historic event hypotheses. (S-1401; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-653

3.2.4.1.7 The System shall use array sensor waveforms to detect signals based on time periods containing spatially coherent data. (S-1402; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-653

3.2.4.1.8 The System shall use a statistical approach to address the loss of coherence between sensors when performing array signal detection. (S-5574; IDC only)

Priority: Extensibility

Verification Methodology: Analysis

Requirements Trace: SRD-653

3.2.4.1.9 The System shall make separate signal detections for signals arriving at a station for simultaneous arrivals from different directions. (S-1406; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-55

3.2.4.1.10 The System shall deconflict detections of the same signal made by multiple detection algorithms. (S-5969; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-653

3.2.4.1.11 The System shall identify microbarom signals. (S-5641; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-620

3.2.4.1.12 The System shall prevent association of microbarom signals to events. (S-5642; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-620

3.2.4.1.13 The System shall compute the probability of a station detecting a signal from an event. (S-6541; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-99

3.2.4.2 Signal Detection Support Interfaces

3.2.4.2.1 The System shall provide the System Maintainer the capability to configure signal detection parameters per channel. (S-1408; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-56, SRD-653

3.2.4.2.2 The System shall provide the System Maintainer the capability to configure channel detection criteria by time of year. (S-1409; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-54

3.2.4.2.3 The System shall provide the System Maintainer the capability to configure channel detection criteria by time of day. (S-1410; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-54

3.2.4.2.4 The System shall provide the System Maintainer the capability to configure signal processing operations to apply prior to signal detection. (S-1411; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-52

3.2.4.2.5 The System shall provide the System Maintainer the capability to configure signal processing operations to apply prior to signal detection by geographic region. (S-1412; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-52

3.2.4.2.6 The System shall provide the System Maintainer the capability to configure signal processing operations to apply prior to signal detection by station. (S-1413; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-52

3.2.4.2.7 The System shall provide the System Maintainer the capability to configure the microbarom identification parameters. (S-5643; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-620

3.2.4.3 Signal Detection User Interfaces

3.2.4.3.1 The System shall provide the Analyst the capability to add signal detections. (S-1416; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-103, SRD-124, SRD-136

3.2.4.3.2 The System shall provide the Analyst the capability to view signal detections. (S-5953; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-136

3.2.4.3.3 The System shall provide the Analyst the capability to view Progressive Multi-Channel Correlation (PMCC) results. (S-5851; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.4.3.4 The System shall provide the Analyst the capability to reject signal detections. (S-1417; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.4.3.5 The System shall provide the Analyst the capability to view signal detection phase designation on the waveform display. (S-5954; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-136

3.2.4.3.6 The System shall provide the Analyst the capability to modify the time of signal detections on the waveform display. (S-1418; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.4.3.7 The System shall provide the Analyst the capability to create signal detections when waveform data is not available. (S-1419; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.4.3.8 The System shall provide the Analyst the capability to select signal detection parameters. (S-6305; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-56

3.2.4.4 Signal Detection Storage

3.2.4.4.1 The System shall store all signal detections. (S-1421; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-653

3.2.5 Feature Extraction

Feature extraction is a range of time domain and frequency domain waveform processing to measure parameters from waveforms. Feature extraction includes time domain waveform measurements, polarization feature measurements, frequency domain waveform measurements, and frequency-wavenumber measurements.

3.2.5.1 Time Domain Waveform Measurements

Time domain measurements are: period, peak-to-peak amplitude, zero-to-peak amplitude, signal to noise ratio, and RMS amplitude. Additional hydroacoustic time domain measurements are: signal termination time, signal summation time, signal time spread, signal skewness, signal kurtosis, peak energy in a defined time period, intensity average time in a defined time period, peak energy in a defined time period, and crossing counts (the number of times a waveform crosses a threshold in a defined time period).

3.2.5.1.1 Time Domain Waveform Measurements Processing

3.2.5.1.1.1 The System shall compute time domain measurements for signal detections. (S-1425; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-62

3.2.5.1.1.2 The System software shall provide an extensible architecture for integrating new amplitude algorithms and measurements. (S-1426; Common)

Priority: Extensibility

Verification Methodology: Analysis

Requirements Trace: SRD-66

3.2.5.1.1.3 The System shall compute infrasound closure and consistency measurements. (S-5630; Common)

Priority: Threshold

Verification Methodology: Test
Requirements Trace: SRD-62

3.2.5.1.1.4 The System shall compute uncertainties for observed signal detection measurements. (S-1427; Common)

Priority: Threshold

Verification Methodology: Test
Requirements Trace: SRD-102

3.2.5.1.2 Time Domain Waveform Measurements Support Interfaces

3.2.5.1.2.1 The System shall provide the System Maintainer the capability to configure time domain measurement configuration parameters per channel. (S-1429; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-56, SRD-62

3.2.5.1.2.2 The System shall provide the System Maintainer the capability to configure time domain measurement configuration parameters by geographic region. (S-1430; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-62

3.2.5.1.3 Time Domain Waveform Measurements User Interfaces

3.2.5.1.3.1 The System shall provide the Analyst the capability to view time domain measurements. (S-1432; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-62, SRD-124, SRD-136

3.2.5.1.3.2 The System shall provide the Analyst the capability to perform time domain waveform measurements. (S-1433; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-62, SRD-124, SRD-136

3.2.5.1.3.3 The System shall provide the Analyst the capability to select time domain waveform measurement parameters. (S-1434; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-136

3.2.5.1.3.4 The System shall provide the Analyst the capability to modify time domain waveform measurements. (S-1435; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-103, SRD-124, SRD-136

3.2.5.1.4 Time Domain Waveform Measurements Storage

3.2.5.1.4.1 The System shall store time domain measurements. (S-1438; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-62, SRD-189

3.2.5.2 Polarization Feature Measurements

The System measures polarization features for 3-component seismic stations. Polarization feature measurements are: azimuth, azimuth uncertainty, rectilinearity, planarity, long axis incidence angle, short axis incidence angle, slowness, slowness uncertainty, the horizontal-to-vertical power ratio, and pseudo fk.

3.2.5.2.1 Polarization Feature Measurements Processing

3.2.5.2.1.1 The System shall compute polarization feature measurements. (S-1441; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-44, SRD-62

3.2.5.2.2 Polarization Feature Measurements Support Interfaces

3.2.5.2.2.1 The System shall provide the System Maintainer the capability to configure polarization feature measurement parameters per channel. (S-1443; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-44, SRD-56, SRD-62

3.2.5.2.3 Polarization Feature Measurements User Interfaces

3.2.5.2.3.1 The System shall provide the Analyst the capability to view polarization feature measurements. (S-1445; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-44, SRD-62, SRD-124, SRD-136, SRD-382

3.2.5.2.3.2 The System shall provide the Analyst the capability to make polarization feature measurements. (S-1446; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-44, SRD-62, SRD-124, SRD-136

3.2.5.2.3.3 The System shall provide the Analyst the capability to select polarization feature measurement parameters per channel. (S-1447; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-44, SRD-124, SRD-136

3.2.5.2.4 Polarization Feature Measurements Storage

3.2.5.2.4.1 The System shall store polarization feature measurements. (S-1450; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-44, SRD-62, SRD-189, SRD-382

3.2.5.3 Frequency Domain Waveform Measurements

Frequency domain waveform measurements are: total energy, total power, average power, power spectral density, and signal spectrum.

3.2.5.3.1 Frequency Domain Waveform Measurements Processing

3.2.5.3.1.1 The System shall compute frequency domain waveform measurements. (S-1453; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-41

3.2.5.3.1.2 The System shall compute the Fourier transform of a waveform. (S-1454; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-41

3.2.5.3.1.3 The System shall compute the inverse Fourier transform of a waveform. (S-1455; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-41

3.2.5.3.1.4 The System shall calculate spectrograms for any channel. (S-2101; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-124, SRD-136, SRD-264

3.2.5.3.1.5 The System shall calculate power spectral density. (S-2104; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-238, SRD-264

3.2.5.3.2 Frequency Domain Waveform Measurements Support Interfaces

3.2.5.3.2.1 The System shall provide the System Maintainer the capability to configure frequency domain waveform measurement parameters per channel. (S-1457; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-41, SRD-56

3.2.5.3.2.2 The System shall provide the System Maintainer the capability to configure frequency domain waveform measurement parameters by geographic region. (S-1458; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-41

3.2.5.3.2.3 The System shall provide the System Maintainer the capability to configure the parameters used to calculate spectrograms per channel. (S-5719; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-238, SRD-264

3.2.5.3.2.4 The System shall provide the System Maintainer the capability to configure the parameters used to calculate power spectral density for any channel. (S-5721; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-238

3.2.5.3.3 Frequency Domain Waveform Measurements User Interfaces

3.2.5.3.3.1 The System shall provide the Analyst the capability to make frequency domain waveform measurements. (S-1460; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-41, SRD-124, SRD-136

3.2.5.3.3.2 The System shall provide the Analyst the capability to view frequency domain waveform measurements. (S-1461; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-41, SRD-124, SRD-136

3.2.5.3.3.3 The System shall provide the Analyst the capability to select frequency domain waveform measurement parameters. (S-1462; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-41, SRD-124, SRD-136

3.2.5.3.3.4 The System shall provide the System User the capability to view spectrograms for any channel. (S-2099; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-238, SRD-264

3.2.5.3.3.5 The System shall provide the System User the capability to select the parameters used to calculate spectrograms per channel. (S-2100; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-238, SRD-264

3.2.5.3.3.6 The System shall provide the System User the capability to view power spectral density for any channel. (S-2102; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-238

3.2.5.3.3.7 The System shall provide the System User the capability to select the parameters used to calculate power spectral density for any channel. (S-2103; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-238

3.2.5.3.4 Frequency Domain Waveform Measurements Storage

3.2.5.3.4.1 The System shall store frequency domain waveform measurements. (S-1465; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-41, SRD-189

3.2.5.3.4.2 The System shall store spectrograms. (S-5720; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-238

3.2.5.3.4.3 The System shall store power spectral density. (S-5722; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-238

3.2.5.4 Frequency-Wavenumber (fk) Power Spectra Measurements

The System computes fk spectra from waveforms recorded by array station elements. The term "fk spectra" refers to fk power spectra and F-statistic, and is the term used in specifications that apply to both. If a specification applies to only the fk power spectra or the F-statistic, then either the term "fk power spectra" or "F-statistic" is used as needed. The System takes feature measurements from the fk spectra. The fk spectra measurements are: slowness, slowness uncertainty, azimuth, azimuth uncertainty, and array coherence.

3.2.5.4.1 Frequency-Wavenumber (fk) Power Spectra Measurements Processing

3.2.5.4.1.1 The System shall calculate fk spectra for a set of waveforms. (S-1468; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-42

3.2.5.4.1.2 The System shall make fk spectra measurements on fk spectra. (S-1469; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-42, SRD-446

3.2.5.4.1.3 The System shall normalize array station channels for fk spectra calculations. (S-1470; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-42

3.2.5.4.1.4 The System shall apply fk space-based filters to fk spectra. (S-1471; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-67

3.2.5.4.1.5 The System shall account for differences in array element sensor vertical position when calculating fk spectra. (S-2359; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-42

3.2.5.4.2 Frequency-Wavenumber (fk) Spectra Measurements Support Interfaces

3.2.5.4.2.1 The System shall provide the System Maintainer the capability to configure fk spectra measurement parameters per channel. (S-1473; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-42, SRD-56, SRD-67

3.2.5.4.2.2 The System shall provide the System Maintainer the capability to configure fk spectra measurement parameters by phase type. (S-1474; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-42, SRD-67

3.2.5.4.2.3 The System shall provide the System Maintainer the capability to configure if array station waveform data is automatically normalized prior to fk spectra calculations. (S-1475; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-42

3.2.5.4.2.4 The System shall provide the System Maintainer the capability to configure fk space-based filters. (S-1476; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-67

3.2.5.4.3 Frequency-Wavenumber (fk) Spectra Measurements User Interfaces

3.2.5.4.3.1 The System shall provide the Analyst the capability to view normalized fk spectra plots for a selected set of waveforms. (S-1478; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-42, SRD-124, SRD-136

3.2.5.4.3.2 The System shall provide the Analyst the capability to view absolute fk spectra plots for a selected set of waveforms. (S-1479; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-42, SRD-124, SRD-136

3.2.5.4.3.3 The System shall provide the Analyst the capability to apply fk space based filters. (S-1480; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-67, SRD-124, SRD-136

3.2.5.4.3.4 The System shall provide the Analyst the capability to make fk spectra measurements on fk spectra. (S-1481; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-42, SRD-124, SRD-136

3.2.5.4.3.5 The System shall provide the Analyst the capability to select fk spectra measurement parameters. (S-1482; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-42, SRD-124, SRD-136

3.2.5.4.3.6 The System shall provide the Analyst the capability to normalize waveform data for an array prior to fk spectra calculations. (S-1483; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-42, SRD-136

3.2.5.4.4 Frequency-Wavenumber (fk) Spectra Measurements Storage

3.2.5.4.4.1 The System shall store fk spectra measurements. (S-1486; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-42, SRD-189

3.2.5.5 Seismic Station Signal Detection Phase Assignment

Initial seismic phase identifications are made for seismic signal detections prior to using the signal detections in network event hypothesis processing. The signal detections from a single seismic station are collected into signal detection groups believed to represent signal detections of the same event. Phase assignments are then made for each group of signal detections using measurements based on the actual signal detections and expected observations of the event hypothesis based on geophysical properties, empirical knowledge, and model based parameters.

Seismic signal detection phase assignment takes as input a collection of signal detections (and measurements based on those detections) from a single station and outputs the provided collection of signal detections with updated phase assignments.

Seismic signal detection phase assignment parameters are: channel waveform data, arrival time, amplitude, slowness, azimuth, horizontal-to-vertical power ratio, frequency, phases of other seismic signal detections in the group, data availability, and Signal QC measurements.

After grouping seismic signal detections into event hypotheses, residuals for the above parameters, empirical phase identification matching using the above parameters, empirical values for the above parameters, the event hypothesis itself (e.g., magnitude, depth for depth phases), can also be used.

Seismic signal detection grouping criteria are combinations of: number of seismic signal detections, types of seismic signal detection phase assignments, number of seismic signal detection phase assignments of particular types, values of the seismic signal detection phase assignment parameters, thresholds for Signal Detection QC Metrics, and the method used to form groups and/or make phase identifications (e.g., waveform correlation might be weighted more heavily than classic techniques).

3.2.5.5.1 Seismic Station Signal Detection Phase Assignment Processing

3.2.5.5.1.1 The System shall group seismic signal detections from a single station that belong to the same event. (S-1489; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-75

3.2.5.5.1.2 The System shall use seismic signal detection phase assignment parameters and presumed event hypotheses formed using the seismic signal detection grouping criteria to assign phases to seismic signal detections. (S-1490; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-64, SRD-75, SRD-78

3.2.5.5.1.3 The System shall support concurrent seismic signal detection grouping criteria. (S-1491; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-75

3.2.5.5.1.4 The System shall use event location to assign phase identifications to signal detections based on predicted phase ID matching. (S-5600; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-74

3.2.5.5.1.5 The System shall use event location to assign phase identifications to signal detections based on available empirical phase ID matching. (S-5601; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-74

3.2.5.5.2 Seismic Station Signal Detection Phase Assignment Support Interfaces

3.2.5.5.2.1 The System shall provide the System Maintainer the capability to configure the seismic signal detection grouping criteria. (S-1493; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-75

3.2.5.5.2.2 The System shall provide the System Maintainer the capability to configure the seismic signal detection phase assignment parameters. (S-1494; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-64, SRD-76

3.2.5.5.2.3 The System shall provide the System Maintainer the capability to configure seismic signal detection grouping criteria by geographic region. (S-1495; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-75

3.2.5.5.2.4 The System shall provide the System Maintainer the capability to configure seismic signal detection grouping criteria by station. (S-1496; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-75

3.2.5.5.2.5 The System shall provide the System Maintainer the capability to configure seismic signal detection phase assignment parameters by station. (S-1497; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-64, SRD-76

3.2.5.5.2.6 The System shall provide the System Maintainer the capability to configure seismic signal detection phase assignment parameters by geographic region. (S-1498; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-64, SRD-76

3.2.5.5.3 Seismic Station Signal Detection Phase Assignment User Interfaces

3.2.5.5.4 Seismic Station Signal Detection Phase Assignment Storage

3.2.5.6 Infrasonic Station Signal Detection Phase Assignment

3.2.5.6.1 Infrasonic Station Signal Detection Phase Assignment Processing

3.2.5.6.1.1 The System shall use infrasonic signal detection phase assignment parameters and presumed event hypotheses formed using the infrasonic signal detection grouping criteria to assign phases to infrasonic signal detections. (S-5647; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-64

3.2.5.6.1.2 The System shall group infrasonic signal detections from a single station that belong to the same event. (S-5633; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-75

3.2.5.6.1.3 The System shall support concurrent infrasound signal detection grouping criteria (S-5634; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-75

3.2.5.6.2 Infrasonic Station Signal Detection Phase Assignment Support Interfaces

3.2.5.6.2.1 The System shall provide the System Maintainer the capability to configure infrasonic phase grouping criteria. (S-5635; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-75

3.2.5.6.2.2 The System shall provide the System Maintainer the capability to configure infrasonic phase grouping criteria by station (S-5636; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-75

3.2.5.6.2.3 The System shall provide the System Maintainer the capability to configure the infrasound signal detection phase assignment parameters. (S-5639; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-76

3.2.5.6.2.4 The System shall provide the System Maintainer the capability to configure infrasound signal detection phase assignment parameters by station. (S-5640; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-76

3.2.5.6.3 Infrasonic Station Signal Detection Phase Assignment User Interfaces

3.2.5.6.3.1 The System shall provide the Analyst the capability to create infrasonic signal detection groups. (S-5637; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-75

3.2.5.6.3.2 The System shall provide the Analyst the capability to modify infrasonic signal detection groups. (S-5638; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-75

3.2.5.6.4 Infrasonic Station Signal Detection Phase Assignment Storage

3.2.5.7 Hydroacoustic Signal Detection Groups (Hydroacoustic Arrival Groups)

A hydroacoustic signal detection group (also referred to as a hydroacoustic arrival group, or HAG) is a group of signal detections on different hydrophones from a single hydroacoustic station that have been determined to come from the same event and that can be used to determine azimuth back to the event. HAGs can only be formed for multiple element (array) stations, and hence apply to H stations but not T stations.

Hydroacoustic phase grouping criteria are: hydroacoustic signal detection feature measurements, group delay, types of signal detection phase assignments, number of signal detection phase assignments of particular types, thresholds for Signal Detection QC Metrics, and the method used to form signal detections and/or make phase identifications (e.g., waveform correlation might be weighted more heavily than other signal detection or event detection techniques).

3.2.5.7.1 Hydroacoustic Signal Detection Groups Processing

3.2.5.7.1.1 The System shall group hydroacoustic signal detections from a single station that belong to the same event (i.e. create hydroacoustic arrival groups). (S-2411; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-75

3.2.5.7.1.2 The System shall support concurrent hydroacoustic signal detections grouping criteria. (S-5626; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-75

3.2.5.7.1.3 The System shall use hydroacoustic signal detection phase assignment parameters and presumed event hypotheses formed using the hydroacoustic signal detection grouping criteria to assign phases to hydroacoustic signal detections. (S-5644; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-64

3.2.5.7.2 Hydroacoustic Signal Detection Groups Support Interfaces

3.2.5.7.2.1 The System shall provide the System Maintainer the capability to configure hydroacoustic signal detection grouping criteria by geographic region. (S-2412; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-75

3.2.5.7.2.2 The System shall provide the System Maintainer the capability to configure hydroacoustic signal detection grouping criteria by station. (S-2413; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-75

3.2.5.7.2.3 The System shall provide the System Maintainer the capability to configure the hydroacoustic signal detection phase assignment parameters. (S-5627; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-76

3.2.5.7.2.4 The System shall provide the System Maintainer the capability to configure hydroacoustic signal detection phase assignment parameters by station. (S-5628; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-76

3.2.5.7.2.5 The System shall provide the System Maintainer the capability to configure hydroacoustic signal detection phase assignment parameters by geographic region. (S-5629; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-76

3.2.5.7.3 Hydroacoustic Signal Detection Groups User Interfaces

3.2.5.7.3.1 The System shall provide the Analyst the capability to select values for the hydroacoustic signal detection grouping criteria. (S-2414; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-76

3.2.5.7.3.2 The System shall provide the Analyst the capability to create hydroacoustic signal detection groups. (S-2415; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-76

3.2.5.7.3.3 The System shall provide the Analyst the capability to modify hydroacoustic signal detection groups. (S-2416; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-75, SRD-76

3.2.5.7.4 Hydroacoustic Signal Detection Groups Storage

3.2.5.7.4.1 The System shall store hydroacoustic signal detection groups (S-2417; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189

3.2.6 Association

After signals are detected, they are associated to common event hypotheses.

3.2.6.1 Network Signal Association

Seismic, hydroacoustic, and infrasound signal detections are used to form event hypotheses and refine signal detection phase assignments in a process called network signal association. Event hypothesis formation criteria can be specified for creating single station event hypotheses, single phenomenology event hypotheses, or multiple phenomenology event hypotheses. Network signal association takes as input a collection of signal detections (and measurements based on those detections) from a network of sensors. Network signal association outputs a collection of event hypotheses meeting the event hypothesis formation criteria and the input collection of signal detections with updated phase assignments.

Event hypotheses are defined by: location, time, magnitude, and associated signal detections.

Seismic network signal association parameters are: channel waveform data, arrival time, amplitude, slowness, azimuth, frequency, horizontal-to-vertical power ratio, rectilinearity, planarity, long axis incidence angle, short axis incidence angle, initial phase from seismic station signal detection phase assignment processing, data availability, Waveform QC measurements, Signal QC measurements, empirical phase identification matching using the above parameters, empirical values for the above parameters, and historic probability of signal detection for event hypotheses with similar locations and magnitudes.

After preliminary event hypothesis formation, residuals for the above parameters, the event hypothesis location itself (e.g., depth for depth phases), and the event hypothesis magnitude are also used.

Hydroacoustic network signal association parameters are: channel waveform data, arrival time, amplitude, azimuth, signal duration overlap, data availability, Waveform QC measurements, Signal QC measurements, empirical phase identification matching using the above parameters, empirical values for the above parameters, and historic probability of signal detection for event hypotheses with similar locations and magnitudes.

After preliminary event hypothesis formation, residuals for the above parameters, the event hypothesis location, path blockage, and event hypothesis magnitude are also used.

Infrasound network signal association parameters are: channel waveform data, arrival time, slowness, azimuth, data availability, Waveform QC measurements, Signal QC measurements, empirical phase identification matching using the above parameters, empirical values for the above parameters, and historic probability of signal detection for event hypotheses with similar locations and magnitudes.

After preliminary event hypothesis formation, residuals for the above parameters, the event hypothesis location, atmospheric wind conditions, and event hypothesis magnitude are also used.

Signal association event hypothesis formation criteria are: number of distinct stations with signal detections, types of stations with signal detections, number of signal detections, types of signal detection phase assignments, number of signal detection phase assignments of particular types, values of the network signal association parameters, thresholds for Signal Detection QC Metrics, the methods used to form event hypotheses and/or make phase identifications (e.g., waveform correlation might be weighted more heavily than classic techniques), and station quality metrics.

3.2.6.1.1 Network Signal Association Processing

3.2.6.1.1.1 The System shall use the seismic, hydroacoustic, and infrasound network signal association parameters to form event hypotheses from any combination of seismic, hydroacoustic, and infrasound signal detections meeting the signal association event hypothesis formation criteria. (S-1504; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-73, SRD-76, SRD-77, SRD-78, SRD-79, SRD-89

3.2.6.1.1.2 The System shall use empirical values of the network signal association parameters during event hypothesis formation. (S-1505; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-79, SRD-99

3.2.6.1.1.3 The System shall use historic probability of signal detection during event hypothesis formation. (S-1506; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-79, SRD-99

3.2.6.1.1.4 The System shall use seismic network signal association parameters to assign phases to seismic signal detections. (S-1507; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-78

3.2.6.1.1.5 The System shall use hydroacoustic network signal association parameters to assign H phases to hydroacoustic signal detections at hydrophone stations. (S-1508; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-65, SRD-78

3.2.6.1.1.6 The System shall use hydroacoustic network signal association parameters to assign T phases to hydroacoustic signal detections from T-phase stations. (S-1509; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-65, SRD-78

3.2.6.1.1.7 The System shall use infrasound network signal association parameters to assign phases to infrasound signal detections. (S-1510; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-78, SRD-418

3.2.6.1.1.8 The System shall support concurrent signal association event hypothesis formation criteria. (S-1511; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-76, SRD-77

3.2.6.1.1.9 The System shall merge event hypotheses created using different event formation algorithms. (S-1512; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-77

3.2.6.1.1.10 The System shall associate unassociated signal detections created by any signal detection algorithm to event hypotheses formed by any event formation algorithm. (S-1513; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-77

3.2.6.1.1.11 The System shall compute the station probability of detecting an event hypothesis during event formation. (S-1514; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-72

3.2.6.1.1.12 The System shall use station-to-event distance when associating signal detections to events. (S-5596; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-72

3.2.6.1.1.13 The System shall use event magnitude when associating signal detections to events. (S-5597; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-72

3.2.6.1.1.14 The System shall use waveform data quality when associating signal detections to events. (S-5598; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-72

3.2.6.1.1.15 The System shall use station noise level when associating signal detections to events. (S-5599; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-72

3.2.6.1.1.16 The System shall use variable resolution representations of the Earth for signal association parameter predictions during signal association to account for the varying ability to resolve signals originating in different areas. (S-1515; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-84

3.2.6.1.1.17 The System shall create new event hypotheses which modify existing user-reviewed event hypotheses only when the event quality metric for the automatic event hypothesis improves more than a configured threshold. (S-1516; Common)

Priority: Objective / Priority 2

Verification Methodology: Test

Requirements Trace: SRD-124, SRD-136, SRD-138

3.2.6.1.1.18 The System shall recreate previously rejected event hypotheses as a result of the Analyst invoking automated processing algorithms only when the event quality metric for the automatic event hypothesis improves more than a configured threshold. (S-1517; Common)

Priority: Objective / Priority 2

Verification Methodology: Test

Requirements Trace: SRD-124, SRD-136, SRD-138

3.2.6.1.1.19 The System shall provide the Analyst the capability to recreate previously rejected event hypotheses as a result of invoking automated processing algorithms only when the event quality metric for the automatic event hypothesis improves more than a configured threshold. (S-2607; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-124, SRD-136, SRD-138

3.2.6.1.1.20 The System shall use the configured earth model(s) during signal detection association. (S-1518; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-71

3.2.6.1.1.21 The System shall build new events using signal detection templates. (S-3026; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-77

3.2.6.1.1.22 The System shall associate signal detections to existing events using signal detection templates. (S-5968; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-77

3.2.6.1.1.23 The System shall find similar events using signal detection templates. (S-6241; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-77

3.2.6.1.1.24 The System shall find similar events by matching event parameters. (S-6242; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-77

3.2.6.1.1.25 The System shall set to non-defining newly associated signal detections when the Analyst invokes automated processing algorithms to associate signal detections to existing event hypotheses. (S-1554; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-124, SRD-136, SRD-138

3.2.6.1.1.26 The System shall build new events using seed events from third-party event bulletins. (S-6513; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-76, SRD-77

3.2.6.1.1.27 The System shall compute seed event quality for each seed event based on the source providing the seed event. (S-6519; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-76, SRD-77

3.2.6.1.2 Network Signal Association Support Interfaces

3.2.6.1.2.1 The System shall provide the System Maintainer the capability to configure the signal association event hypothesis formation criteria. (S-1520; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-76, SRD-77, SRD-80

3.2.6.1.2.2 The System shall provide the System Maintainer the capability to configure the network signal association parameters by station. (S-1521; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-76, SRD-77, SRD-80

3.2.6.1.2.3 The System shall provide the System Maintainer the capability to configure the network signal association parameters by geographic region. (S-1522; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-76, SRD-77, SRD-80

3.2.6.1.2.4 The System shall provide the System Maintainer the capability to configure the signal association event hypothesis formation criteria by geographic region. (S-1524; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-76, SRD-77

3.2.6.1.2.5 The System shall provide the System Maintainer the capability to configure the signal association event hypothesis formation criteria for single station event hypotheses by station. (S-1525; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-75

3.2.6.1.2.6 The System shall provide the System Maintainer the capability to configure the event hypothesis merge criteria by geographic region. (S-1526; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-77

3.2.6.1.2.7 The System shall provide the System Maintainer the capability to configure the event quality metric improvement threshold for modifying user-reviewed event hypotheses. (S-1527; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-138

3.2.6.1.2.8 The System shall provide the System Maintainer the capability to configure how the System uses seed events to build new events. (S-6520; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-76, SRD-77

3.2.6.1.3 Network Signal Association User Interfaces

3.2.6.1.3.1 The System shall provide the Analyst the capability to associate signal detections to existing event hypotheses. (S-1529; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.6.1.3.2 The System shall provide the Analyst the capability to unassociate signal detections from existing event hypotheses. (S-1530; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.6.1.3.3 The System shall provide the Analyst the capability to assign phase labels to signal detections. (S-1531; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.6.1.3.4 The System shall provide the Analyst the capability to reject an event hypothesis. (S-1532; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-96, SRD-124, SRD-136

3.2.6.1.3.5 The System shall provide the Analyst the capability to invoke algorithms and parameters used during automated processing for the generation of new event hypotheses for evaluation. (S-1533; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-138, SRD-142

3.2.6.1.3.6 The System shall provide the Analyst the capability to select the signal association event hypothesis formation criteria. (S-1534; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-138, SRD-142

3.2.6.1.3.7 The System shall provide the Analyst the capability to invoke algorithms used during automated processing to find unassociated signal detections and associate them with existing event hypotheses. (S-1535; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-138, SRD-142

3.2.6.1.3.8 The System shall provide the Analyst the capability to form new event hypotheses from unassociated signal detections. (S-1536; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-138

3.2.6.1.3.9 The System shall provide the Analyst the capability to create a virtual event hypothesis (an event hypothesis with no associated signal detections). (S-1537; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.6.1.3.10 The System shall provide the Analyst the capability to define signal detection templates for automatic event hypothesis formation. (S-3023; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-142

3.2.6.1.3.11 The System shall provide the Analyst the capability to build events using a selected signal detection template. (S-3024; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-138

3.2.6.1.3.12 The System shall provide the Analyst the capability to create a signal detection template from an existing event. (S-3025; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-142

3.2.6.1.3.13 The System shall provide the Analyst the capability to associate signal detections to existing events using signal detection templates. (S-6010; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-77, SRD-124, SRD-136, SRD-138

3.2.6.1.4 Network Signal Association Storage

3.2.6.1.4.1 The System shall store all event hypotheses formed by the System. (S-1556; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-79, SRD-82, SRD-138, SRD-189

3.2.6.1.4.2 The System shall store all signal detection associations for each event hypothesis stored by the System. (S-1557; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-189

3.2.6.1.4.3 The System shall store seed events. (S-6521; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189

3.2.6.1.4.4 The System shall store seed event quality. (S-6522; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189

3.2.6.2 Late Network Signal Association

Late network signal association refers to network signal association for a time interval that is run after the initial network signal association for that time interval. It is triggered by the availability of signal detections for that time interval that were not available during the initial network signal association. Late network signal association uses the network signal association parameters and signal association event hypothesis formation criteria used in network signal association. Late network signal association uses unassociated arrivals to form new event hypotheses and also associates arrivals to previously formed event hypotheses. As part of event hypothesis formation, late network signal association compares potential event hypotheses to event hypotheses previously rejected during interactive review. If late network signal association finds a potential event hypothesis matching a previously rejected event hypothesis, the event hypothesis is not reformed unless the event quality metric improves beyond a configured threshold. Parameters used to prevent reforming rejected event hypotheses are: event location and tolerances on each event location parameter. Late network signal association occurs as needed.

3.2.6.2.1 Late Network Signal Association Processing

3.2.6.2.1.1 The System shall perform late network signal association using the seismic, hydroacoustic, and infrasound network signal association parameters to form event hypotheses from any combination of seismic, hydroacoustic, and infrasound signal detections meeting the signal association event hypothesis formation criteria. (S-1540; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-73, SRD-76, SRD-77, SRD-79, SRD-81, SRD-280, SRD-421

3.2.6.2.1.2 The System shall perform late network signal association for a time interval when one or more signal detections for that time interval become available that were not available during prior network signal association or late network signal associations for that time interval. (S-1541; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-79, SRD-81, SRD-217, SRD-280

3.2.6.2.1.3 The System shall not automatically perform network signal association affecting signal detections that the Analyst is actively reviewing. (S-1542; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-79, SRD-81

3.2.6.2.1.4 The System shall recreate an event hypothesis during late association that was rejected in user review only when the event quality metric for the automatic event hypothesis improves more than a configured threshold or when the new event hypothesis definition differs from the original event hypothesis more than a configurable threshold. (S-1547; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-82

3.2.6.2.1.5 The System shall not automatically reassociate a signal detection to an event hypothesis if an Analyst has previously unassociated that signal detection from the event hypothesis. (S-1548; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-81, SRD-82, SRD-83

3.2.6.2.1.6 The System shall perform late network signal association during the operational processing time period. (S-1549; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-79, SRD-81, SRD-280

3.2.6.2.1.7 The System shall mark as requiring Analyst review any event previously reviewed by an Analyst that has its signal detection associations subsequently modified by the System. (S-2342; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-79, SRD-81

3.2.6.2.2 Late Network Signal Association Support Interfaces

3.2.6.2.2.1 The System shall provide the System Maintainer the capability to configure by geographic region the parameters used by late network signal association to prevent the formation of event hypotheses previously rejected during Analyst review. (S-1551; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-82

3.2.6.2.3 Late Network Signal Association User Interfaces

3.2.6.2.4 Late Network Signal Association Storage

3.2.6.3 Waveform Correlation

Waveform correlation event processors find event hypotheses in waveforms by comparing databases of waveforms corresponding to historical event hypotheses. When a match is found there is high probability a new event hypothesis has occurred at nearly the same location as the original event hypothesis, allowing signal detections at stations across the network to be associated to the new event hypothesis by mapping them to compatible signal

detections associated to the historical event hypothesis. Signal association and phase assignments based on waveform correlation event processing can occur for signal detections on any channel in the network, not just the channel correlated to the historical event hypothesis.

Compatible signal detections are found using the network signal association parameters.

3.2.6.3.1 Waveform Correlation Processing

3.2.6.3.1.1 The System shall detect events in a waveform by correlating the waveform with waveforms from historic event hypotheses. (S-5949; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-77

3.2.6.3.1.2 The System shall associate signal detections to event hypotheses found with waveform correlation event processing by mapping signal detections on all network sensors to compatible signal detections on the historic waveforms. (S-1560; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-76, SRD-77, SRD-79

3.2.6.3.1.3 The System shall assign phase identifications to signal detections associated to event hypotheses found via waveform correlation to the same phases as the matching historic event hypotheses. (S-1561; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-64, SRD-78

3.2.6.3.1.4 The System shall locate event hypotheses found using waveform correlation processing using the same location algorithms as events found using other types of event processing. (S-1563; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-92

3.2.6.3.1.5 The System shall calculate signal detection feature measurement uncertainties for signal detections found using waveform correlation using the cross correlation coefficient. (S-1564; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-92

3.2.6.3.1.6 The System shall use waveform correlation to find historical event hypotheses occurring within a specified distance from an event hypothesis being analyzed. (S-2344; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-653

3.2.6.3.1.7 The System shall find similar events using waveform correlation. (S-6243; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-77

3.2.6.3.2 Waveform Correlation Support Interfaces

3.2.6.3.2.1 The System shall provide the System Maintainer the capability to configure subspace waveform correlators. (S-2348; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-653

3.2.6.3.2.2 The System shall provide the System Maintainer the capability to configure single channel waveform correlators. (S-2349; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-653

3.2.6.3.2.3 The System shall provide the System Maintainer the capability to configure multi-component waveform correlators. (S-2350; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-653

3.2.6.3.2.4 The System shall provide the System Maintainer the capability to configure array station waveform correlators. (S-2351; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-653

3.2.6.3.2.5 The System shall provide the System Maintainer the capability to configure the dynamic waveform correlation search parameters the System uses to find previously analyzed event hypotheses occurring at locations near an event hypothesis. (S-2352; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-653

3.2.6.3.2.6 The System shall provide the System Maintainer the capability to configure the dynamic waveform correlation search parameters by geographic region. (S-2353; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-653

3.2.6.3.3 Waveform Correlation User Interfaces

3.2.6.3.3.1 The System shall provide the Researcher the capability to create subspace waveform correlators. (S-1414; Common)

Priority: Extensibility

Verification Methodology: Demonstration

Requirements Trace: SRD-653

3.2.6.3.3.2 The System shall provide the Researcher the capability to create single channel waveform correlators. (S-2345; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-653

3.2.6.3.3.3 The System shall provide the Researcher the capability to create multi-component waveform correlators. (S-2346; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-653

3.2.6.3.3.4 The System shall provide the Researcher the capability to create array station waveform correlators. (S-2347; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-653

3.2.6.3.3.5 The System shall provide the Analyst the capability to select the dynamic waveform correlation search parameters the System uses to find previously analyzed event hypotheses occurring at locations near an event hypothesis. (S-2358; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-653

3.2.6.3.4 Waveform Correlation Storage

3.2.6.4 Conflict Resolution

Conflict resolution mediates automatically formed event hypotheses created by distinct network signal association processes. This might occur if separate network signal association processes are run for specific collections of stations or for event hypotheses occurring in specific areas. Conflict resolution:

1. Forces each signal detection to be associated to at most one event hypothesis.
2. Merges duplicate event hypotheses created by more than one association process into a single event hypothesis.
3. Corrects erroneously associated signal detections by moving signal detections between event hypotheses.

All event hypotheses formed or modified during conflict resolution meet the signal association event hypothesis formation criteria. If an event hypothesis modified during conflict resolution no longer meets the signal association event hypothesis formation criteria, the event hypothesis is dissolved by unassociating all of its signal detections.

Parameters used in conflict resolution are: the network signal association parameters and the signal association event hypothesis formation criteria.

3.2.6.4.1 Conflict Resolution Processing

3.2.6.4.1.1 The System shall use the seismic, hydroacoustic, and infrasound network signal association parameters and the signal association event hypothesis formation criteria to resolve situations where the same signal detection is associated to more than one event hypothesis by reassociating the signal detection to at most one event hypothesis. (S-1567; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-89, SRD-421

3.2.6.4.1.2 The System shall use the seismic, hydroacoustic, and infrasound network signal association parameters and the signal association event hypothesis formation criteria to merge redundant event hypotheses. (S-1568; Common)

Priority: Threshold

Verification Methodology: Test
Requirements Trace: SRD-89, SRD-421

3.2.6.4.1.3 The System shall use the seismic, hydroacoustic, and infrasound network signal association parameters and the signal association event hypothesis formation criteria to correct erroneously associated signal detections. (S-1569; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-89, SRD-421

3.2.6.4.2 Conflict Resolution Support Interfaces

3.2.6.4.3 Conflict Resolution User Interfaces

3.2.6.4.4 Conflict Resolution Storage

3.2.6.5 Station Quality Metric

The station quality metric is computed using a combination of the station network signal association parameters as well as: station type (array vs. non-array), and whether or not the station was operational during the time period it would observe the event (used to evaluate the significance of non-detecting stations).

3.2.6.5.1 Station Quality Metric Processing

3.2.6.5.1.1 The System shall compute the station quality metric for all events. (S-1572; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-85, SRD-89, SRD-408

3.2.6.5.2 Station Quality Metric Operational Support Interfaces

3.2.6.5.3 Station Quality Metric User Interfaces

3.2.6.5.3.1 The System shall provide the System User the capability to view station quality metrics. (S-1574; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-89

3.2.6.5.4 Station Quality Metric Storage

3.2.6.5.4.1 The System shall store the station quality metrics for all stations for each event hypothesis. (S-1576; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-89, SRD-189, SRD-408

3.2.6.6 Event Hypothesis Quality Metric

An event hypothesis quality metric indicating the quality of the event hypothesis is computed for every event hypothesis formed on the System. The System forms event hypothesis quality metrics using event hypothesis quality statistics. The System recomputes event hypothesis quality metrics whenever any event hypothesis statistic is updated and stored. Event hypothesis quality metrics are calculated for automatic and Analyst created event hypotheses. Any automatic decisions based on the event hypothesis quality metric are ignored for Analyst created or updated event hypotheses.

Event hypothesis quality statistics are: event hypothesis location uncertainty, number of station detections associated to the event hypothesis, signal detection quality statistics for signal detections associated to the event hypothesis, STA/LTA noise levels, SNR, location, travel-time residuals, azimuth residuals, slowness residuals, amplitude residuals, observed and non-observed maximum likely signal detection associations to the event hypothesis, similar historic event hypotheses and their associated signal detections.

3.2.6.6.1 Event Hypothesis Quality Metric Processing

3.2.6.6.1.1 The System shall compute an event hypothesis quality metric using the event hypothesis quality statistics for each event hypothesis formed on the System. (S-1579; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-85, SRD-88

3.2.6.6.1.2 The System shall recompute the event hypothesis quality metric for an event hypothesis when any of the event hypothesis quality statistics used to calculate the event hypothesis quality metric are updated. (S-1580; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-85, SRD-87, SRD-88

3.2.6.6.1.3 The System shall not automatically form event hypotheses with event hypothesis quality metrics below the event hypothesis quality metric threshold. (S-1581; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-86

3.2.6.6.1.4 The System shall not screen any Analyst created event hypotheses by their event hypothesis quality metrics. (S-1582; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-86

3.2.6.6.2 Event Hypothesis Quality Metric Support Interfaces

3.2.6.6.2.1 The System shall provide the System Maintainer the capability to configure the event hypothesis quality metric threshold by geographic region. (S-1584; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-86

3.2.6.6.2.2 The System shall provide the System Maintainer the capability to configure the event hypothesis quality metric threshold. (S-5620; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-86

3.2.6.6.3 Event Hypothesis Quality Metric User Interfaces

3.2.6.6.3.1 The System shall provide the Analyst the capability to view event hypothesis quality metrics. (S-1586; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-85, SRD-88, SRD-124, SRD-136

3.2.6.6.4 Event Hypothesis Quality Metric Storage

3.2.6.6.4.1 The System shall store the event quality metric for each event hypothesis. (S-1588; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-85, SRD-189

3.2.6.7 Event Consistency

3.2.6.7.1 Event Consistency Processing

3.2.6.7.1.1 The System shall correct event parameters based on the Event Consistency checks as permitted by the configured settings. (S-5735; IDC only)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-427

3.2.6.7.1.2 The System shall compute Event Consistency checks when an event hypothesis is saved. (S-5795; IDC only)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-490, SRD-625

3.2.6.7.1.3 The System shall generate an Event Consistency check in less than 3 seconds per event hypothesis. (S-5796; IDC only)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-425

3.2.6.7.1.4 The System shall include a check of minimum number of primary stations as part of the event consistency calculation. (S-5815; IDC only)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-424, SRD-624

3.2.6.7.1.5 The System shall perform a check of time, azimuth, and slowness residuals and weights as part of the event consistency calculation. (S-5816; IDC only)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-424, SRD-624

3.2.6.7.1.6 The System shall perform an event consistency check that deep events have more than a specified threshold number of location defining signal detections. (S-5841; IDC only)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-624

3.2.6.7.1.7 The System shall perform an event consistency check that the ordered list of phases at each station is consistent with the configured list of phases for the event location and magnitude. (S-5819; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-424, SRD-626

3.2.6.7.1.8 The System shall perform an event consistency check that there are no duplicate phases among the associated signal detections at each station. (S-5843; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-626

3.2.6.7.1.9 The System shall perform an event consistency check that the difference between ML and mb magnitudes is not larger than a specified threshold. (S-5820; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-424, SRD-626

3.2.6.7.1.10 The System shall include a check of observing stations related to event geographic location and magnitude as part of the event consistency calculation. (S-5823; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-424, SRD-626

3.2.6.7.1.11 The System shall include a check for station magnitude outliers as part of the event consistency calculation. (S-5824; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-424, SRD-626

3.2.6.7.1.12 The System shall include a check for consistency of time, azimuth, slowness defining settings per associated arrival as part of the event consistency calculation. (S-5825; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-424, SRD-627

3.2.6.7.1.13 The System shall perform an event consistency check that the time, azimuth, and slowness residuals for location defining associated signal detections do not exceed the configured thresholds. (S-5826; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-424, SRD-627

3.2.6.7.1.14 The System shall perform an event consistency check that a deep event is located in an area where deep events are known to occur. (S-5846; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-626

3.2.6.7.1.15 The System shall perform an event consistency check that if any signal detections belonging to a group of hydroacoustic signal detections is associated to an event, then all signal detections in the group must be associated. (S-5847; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-626

3.2.6.7.1.16 The System shall perform an event consistency check that the time, azimuth, and slowness residuals for location non-defining associated signal detections do not exceed the configured thresholds. (S-5849; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-627

3.2.6.7.1.17 The System shall perform an event consistency check that the event definition criteria, if currently defined, are satisfied for each event hypothesis. (S-6291; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-424

3.2.6.7.1.18 The System shall perform an event consistency check that all event-related information is internally consistent and populated with valid types for each event hypothesis. (S-6292; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-424, SRD-490, SRD-491

3.2.6.7.1.19 The System shall perform an event consistency check that event information is consistent for an event located at the hypothesized source location with the estimated magnitude. (S-6293; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-424, SRD-490, SRD-491

3.2.6.7.2 Event Consistency Support Interfaces

3.2.6.7.2.1 The System shall provide the System Maintainer the capability to configure the event parameters that can be automatically corrected by the System. (S-5734; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-427

3.2.6.7.2.2 The System shall provide the System Maintainer the capability to configure the threshold number of location defining signal detections for deep events as part of the event consistency calculation. (S-5842; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-624

3.2.6.7.2.3 The System shall provide the System Maintainer the capability to configure the minimum number of event location defining primary stations as part of the event consistency calculation. (S-5833; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-624

3.2.6.7.2.4 The System shall provide the System Maintainer the capability to configure a threshold value of the sum of weights for location defining signal detections as part of the event consistency calculation. (S-5834; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-624

3.2.6.7.2.5 The System shall provide the System Maintainer the capability to configure an expected list of phases at each station as a function of event location and magnitude as part of the event consistency calculation. (S-5835; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-625

3.2.6.7.2.6 The System shall provide the System Maintainer the capability to configure a threshold values of the difference between ML and mb magnitudes as part of the event consistency calculation. (S-5845; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-626

3.2.6.7.2.7 The System shall provide the System Maintainer the capability to configure an expected set of observing stations as a function of event location and magnitude as part of the event consistency calculation. (S-5836; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-626

3.2.6.7.2.8 The System shall provide the System Maintainer the capability to configure the station magnitude consistency with network magnitude range. (S-5837; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-626

3.2.6.7.2.9 The System shall provide the System Maintainer the capability to configure allowed values for time, azimuth, slowness defining settings per associated signal detection as part of the event consistency calculation. (S-5838; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-627

3.2.6.7.2.10 The System shall provide the System Maintainer the capability to configure the threshold value for time, azimuth, and slowness residuals for location defining associated signal detections as part of the event consistency calculation. (S-5839; IDC only)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-627

3.2.6.7.2.11 The System shall provide the System Maintainer the capability to configure what geographic regions are known to have deep seismicity as part of the event consistency calculation. (S-5848; IDC only)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-626

3.2.6.7.2.12 The System shall provide the System Maintainer the capability to configure the threshold value for time, azimuth, and slowness residuals for location non-defining associated signal detections as part of the event consistency calculation. (S-5850; IDC only)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-627

3.2.6.7.3 Event Consistency User Interfaces

3.2.6.7.3.1 The System shall provide the Analyst the capability to interactively compute a subset of the Event Consistency checks. (S-5794; IDC only)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-424, SRD-491

3.2.6.7.4 Event Consistency Storage

3.2.7 Location

Due to the heterogeneity of the Earth, location of events in three dimensions is a scientifically challenging problem. The System must integrate the constantly evolving state-of-the-art earth models and location algorithms.

3.2.7.1 Event Hypothesis Relocation

Event hypothesis relocation refers to a process used to determine an event's hypocenter and origin time using event hypothesis observations (and measurements from those observations) as recorded at one or more stations and either an Earth model or empirical observations of well-located event hypotheses. Location algorithms have the goal of spatially and temporally locating an event hypothesis such that the actual event hypothesis observations align as closely as possible with expected observations of the event hypothesis made using either the Earth model or empirical data. Computed event hypothesis locations are estimates represented by spatial location, temporal location, and associated uncertainties.

Values used during event hypothesis location are:

- Signal detection measurements including uncertainties: arrival time, backazimuth, and horizontal slowness for signal detections associated to the event hypothesis.
- Signal Predictions including uncertainties: arrival time, backazimuth, horizontal slowness. Note: Predictions come from either empirical data or an Earth model.
- Preliminary event hypothesis location.

Inputs to event hypothesis relocation calculations include: signal detection measurements and uncertainties, signal detection phase assignments, model predictions of the measurements, uncertainties of the model predictions, and a preliminary event hypothesis location.

Event hypothesis relocation calculation outputs include: the hypocenter (latitude, longitude, and depth) and origin time of the event hypothesis, and the event hypothesis location uncertainty (the covariance matrix and the location uncertainty bound scaling factors).

N-location solutions: multiple different location solutions can be computed using the observations of any given event hypothesis by limiting the location solution's input parameters. Individual signal detection measurements are either defining or non-defining for each event hypothesis relocation calculation. Each calculation only uses the defining signal detection measurements for that calculation.

The System uses two approaches to toggle signal detection measurements between defining and non-defining for event hypothesis location processing during event hypothesis relocation processing. First, signal detection measurements are made non-defining if their residuals from signal predictions (or residuals weighted by the signal detection measurement uncertainty) exceed a configurable threshold. Second, signal detection measurements are made non-defining if the System determines they are inconsistent with geophysical properties (e.g., a signal detection has a phase assignment that is impossible for the event hypothesis, such as a Pn signal detection at a teleseismic distance). The System toggles signal detections measurements it previously made non-defining for event location processing during event hypothesis relocation processing back to defining if the processing updates the event hypothesis location such that the signal detection measurement no longer meets the criteria used to make it non-defining.

The System uses these parameters to set criteria for toggling the signal detection defining/non-defining state: signal detection measurements, signal detection measurement uncertainties, signal predictions, signal prediction uncertainties, and signal detection phase assignments.

Event hypothesis location uncertainty is a general term referring to the values constraining an event hypothesis' estimated location at a given probability level. The most general uncertainty representation is the covariance matrix. This matrix can be used to build a 4-dimensional hyper-ellipse bounding an event hypothesis location's hypocenter and origin time. Projecting this hyper-ellipse onto other spaces yields other uncertainty bounds. Definitions for these other uncertainty bounds as used in the System are:

- Depth uncertainty: 1-dimensional uncertainty of the event hypothesis' depth. This value comes directly from the corresponding diagonal element of the covariance matrix.
- Time uncertainty: 1-dimensional uncertainty of the event hypothesis' temporal location. This value comes directly from the corresponding diagonal element of the covariance matrix.
- Uncertainty ellipse: 2-dimensional ellipse defining the joint uncertainty of the latitude and longitude of the event hypothesis. An ellipse is created by projecting the 4-dimensional hyper-ellipse onto the latitude-longitude plane.
- Uncertainty ellipsoid: 3-dimensional ellipsoid defining the joint uncertainty of the 3 components of the event hypothesis' hypocenter. An ellipsoid is created by projecting the 4-dimensional hyper-ellipse onto the three spatial dimensions.

Different types of event hypothesis location uncertainty bounds can be constructed through scaling. In each case, the basic shape and magnitudes of the uncertainty bounds are controlled by the uncertainties of the observations and model predictions propagated through the event hypothesis relocation calculation. Each of the different types of event hypothesis location uncertainty bounds involves a scale factor that adjusts the size of the uncertainty bounds to account for potential inaccuracy of the observation and model prediction uncertainties used in the relocation. The available types of location uncertainty bound scaling factors are:

- Coverage bound scaling factor: location uncertainty bounds are scaled using an a priori estimate of the scale factor. The factor is set to 1 if the observation and model prediction uncertainties are believed to be correct but may be specified to be larger or smaller depending on if historical, empirical, information indicates that the uncertainties are too large or small, respectively..
- Confidence bound scaling factor: location uncertainty bounds are scaled using a posteriori information obtained by assuming that the weighted residuals after relocating the event hypothesis provide a reliable estimate of how accurate the original estimates of the observation and prediction uncertainties were. The scale factor is set equal to the mean sum squared weighted residual of all observations contributing to the location. For event hypothesis locations computed with a large number of observations, this value should be ~1 if the original estimates of the observation and prediction uncertainties were accurate..
- K-weighted bound scaling factor: location uncertainty bounds scaled using a weighted combination of the a priori and a posteriori scale factors.

3.2.7.1.1 Event Hypothesis Relocation Processing

3.2.7.1.1.1 The System shall compute event hypothesis relocations using seismic, hydroacoustic, and infrasound signal detection feature measurements. (S-1592; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-92, SRD-102, SRD-418, SRD-419

3.2.7.1.1.2 The System shall compute event hypothesis relocations using the signal detection feature measurements from a single station. (S-1593; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-101

3.2.7.1.1.3 The System shall compute event hypothesis relocations using the signal detection feature measurements from multiple stations. (S-1594; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-101

3.2.7.1.1.4 The System shall compute event hypothesis relocation uncertainty bounds. (S-1595; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-92

3.2.7.1.1.5 The System shall compute the uncertainty coverage ellipse for each event hypothesis relocation. (S-1596; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-92

3.2.7.1.1.6 The System shall compute new event hypothesis relocations when an automatic process associates a new location defining signal detection to that event hypothesis. (S-1597; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-100

3.2.7.1.1.7 The System shall compute new event hypothesis relocations when an automatic process unassociates a location defining signal detection from that event hypothesis. (S-1598; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-100

3.2.7.1.1.8 The System shall compute a new event hypothesis relocation when an automatic process modifies any event hypothesis relocation parameter contributing to that event hypothesis' location. (S-1599; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-100

3.2.7.1.1.9 The System shall set the defining/non-defining state for signal detection measurements during event hypothesis relocation processing. (S-1600; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-92

3.2.7.1.1.10 The System shall compute event hypothesis relocations using teleseismic and regional seismic signal detections. (S-1631; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-93

3.2.7.1.1.11 The System shall compute modeling uncertainties for model based predictions of signal detection measurements. (S-1601; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-102

3.2.7.1.1.12 The System shall set signal detections to non-defining for event hypothesis location calculations when the System automatically associates them to Analyst reviewed event hypotheses. (S-1543; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-83

3.2.7.1.2 Event Hypothesis Relocation Support Interfaces

3.2.7.1.2.1 The System shall provide the System Maintainer the capability to configure the criteria used during event hypothesis relocation processing to set the defining/non-defining state for signal detection measurements for event hypothesis relocation by geographic region. (S-1603; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-92, SRD-103

3.2.7.1.2.2 The System shall provide the System Maintainer the capability to configure the criteria used during event hypothesis relocation processing to set the defining/non-defining state for signal detection measurements for event hypothesis relocation by channel. (S-1604; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-92, SRD-103

3.2.7.1.3 Event Hypothesis Relocation User Interfaces

3.2.7.1.3.1 The System shall provide the Analyst the capability to set uncertainties for observed signal detection measurements. (S-1606; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-102, SRD-124, SRD-136

3.2.7.1.3.2 The System shall provide the Analyst the capability to select the confidence level used to compute an event hypothesis location uncertainty bound. (S-1607; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-92, SRD-124, SRD-136

3.2.7.1.3.3 The System shall provide the Analyst the capability to select the type of each event hypothesis location uncertainty bound to compute. (S-1608; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-92, SRD-124, SRD-136

3.2.7.1.3.4 The System shall provide the Analyst the capability to select the defining/non-defining state for a signal detection time measurement for event hypothesis relocation unless prohibited by the default defining/non-defining state. (S-1610; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-103, SRD-124, SRD-136

3.2.7.1.3.5 The System shall provide the Analyst the capability to select the defining/non-defining state for a signal detection azimuth measurement for event hypothesis relocation unless prohibited by the default defining/non-defining state. (S-1611; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-103, SRD-124, SRD-136

3.2.7.1.3.6 The System shall provide the Analyst the capability to select the defining/non-defining state for a signal detection slowness measurement for event hypothesis relocation unless prohibited by the default defining/non-defining state. (S-1612; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-103, SRD-124, SRD-136

3.2.7.1.3.7 The System shall provide the Analyst the capability to select the defining/non-defining state for signal detection measurements for event hypothesis relocation based on channel unless prohibited by the default defining/non-defining state. (S-1613; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-103, SRD-124, SRD-136

3.2.7.1.3.8 The System shall provide the Analyst the capability to select the defining/non-defining state for signal detection measurements for event hypothesis relocation based on signal detection phase assignment unless prohibited by the default defining/non-defining state. (S-1614; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-103, SRD-124, SRD-136

3.2.7.1.3.9 The System shall provide the Analyst the capability to relocate event hypotheses. (S-1615; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.7.1.4 Event Hypothesis Relocation Storage

3.2.7.1.4.1 The System shall store up to 300 unique event hypotheses for each event. (S-1618; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-94

3.2.7.1.4.2 The System shall store the confidence level of each computed event hypothesis location uncertainty bound. (S-1619; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-92, SRD-189

3.2.7.1.4.3 The System shall store the type (i.e., confidence, coverage, or k-weighted with the associated weights) of each location uncertainty bound. (S-1620; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-92, SRD-189

3.2.7.1.4.4 The System shall store modeling uncertainties for model based predictions of signal detection measurements. (S-1621; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-102, SRD-189

3.2.7.1.4.5 The System shall store uncertainties for observed signal detection measurements. (S-1622; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-102, SRD-189

3.2.7.1.4.6 The System shall store the sum squared weighted residual for each event hypothesis location. (S-1623; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-94, SRD-189

3.2.7.1.4.7 The System shall store the defining/non-defining state for each signal detection measurement associated to a stored event hypothesis. (S-1624; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-170, SRD-189

3.2.7.2 Restrained Event Hypothesis Relocation

Restrained event hypothesis locations limit one or more of the computed event hypothesis location components, the stations used to locate the event hypothesis, or the phases used to locate the event hypothesis. Unrestrained event hypothesis locations do not limit these parameters. Restraining event hypothesis location parameters are: latitude, longitude, depth, time, stations, and phases.

3.2.7.2.1 Restrained Event Hypothesis Relocation Processing

3.2.7.2.2 Restrained Event Hypothesis Relocation Support Interfaces

3.2.7.2.2.1 The System shall provide the System Maintainer the capability to configure which types of event hypothesis locations (e.g. restrained event hypothesis locations, unrestrained event hypothesis locations, types of n-locations) to automatically compute for each event hypothesis. (S-1633; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-94

3.2.7.2.2.2 The System shall provide the System Maintainer the capability to configure which types of event hypothesis locations to automatically compute by geographic region. (S-1634; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-94

3.2.7.2.3 Restrained Event Hypothesis Relocation User Interfaces

3.2.7.2.3.1 The System shall provide the Analyst the capability to compute restrained event hypothesis locations. (S-1636; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-94, SRD-124, SRD-136

3.2.7.2.3.2 The System shall provide the Analyst the capability to compute unrestrained event hypothesis locations. (S-1637; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-94, SRD-124, SRD-136

3.2.7.2.4 Restrained Event Hypothesis Relocation Storage

3.2.7.3 Relative Event Hypothesis Relocation

Relative event hypothesis relocation is an event hypothesis relocation process that simultaneously relocates a group of event hypotheses rather than relocating each event hypothesis individually. This allows the locator to take advantage of additional information based on the relative differences in measurements between event hypotheses. Travel time differences between groups of event hypotheses can be calculated using: waveform cross correlation time offsets or signal detection onset times.

3.2.7.3.1 Relative Event Hypothesis Relocation Processing

3.2.7.3.1.1 The System shall perform master event relocation using travel time differences. (S-1640; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-92, SRD-129

3.2.7.3.1.2 The System shall perform multiple event relocation using differences in signal detection feature measurements. (S-6290; Common)

Priority: Threshold

Verification Methodology: Test
Requirements Trace: SRD-92, SRD-129

3.2.7.3.2 Relative Event Hypothesis Relocation Support Interfaces

3.2.7.3.3 Relative Event Hypothesis Relocation User Interfaces

3.2.7.3.3.1 The System shall provide the Researcher the capability to compute the relative relocations of a selected set of event hypotheses using a selected set of stations. (S-1642; Common)

Priority: Objective / Priority 1
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-129, SRD-136

3.2.7.3.3.2 The System shall provide the Analyst the capability to map signal detections and their phase assignments from one channel to another channel. (S-1643; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-129, SRD-136

3.2.7.3.3.3 The System shall provide the Analyst the capability to manually align waveforms. (S-1644; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-129, SRD-136

3.2.7.3.3.4 The System shall provide the Analyst the capability to align waveforms based on travel time differences. (S-1645; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-129, SRD-136

3.2.7.3.3.5 The System shall provide the Analyst the capability to align waveforms based on optimal lag calculated by waveform cross correlation. (S-1646; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-129, SRD-136

3.2.7.3.4 Relative Event Hypothesis Relocation Storage

3.2.8 Source Properties

Source property calculations estimate the source sizes of event hypotheses using event hypothesis magnitude estimates. The System also computes moment tensor solutions for event hypotheses meeting certain criteria.

3.2.8.1 Magnitude Estimation

An event magnitude is a measure of the size of an event. An event magnitude measured from an event hypothesis is an estimate of the actual event's magnitude and is referred to as an event hypothesis magnitude estimate. Event hypothesis magnitude estimates are made using signal detection measurements, event hypothesis locations, and knowledge of Earth structure. Different types of magnitude estimates are made using different input parameters. For example, different types of magnitude estimates are made using the amplitudes of body waves and surface waves.

Event hypothesis magnitude estimate calculations are typically defined using linear relationships of their input parameters. Changing the constant coefficients used in a relationship produces a different type of event hypothesis

magnitude estimate that is related to the original event hypothesis magnitude estimate. The general form of an event hypothesis magnitude estimate relationship can therefore be thought of as defining a family of related event hypothesis magnitude estimates, with different coefficient assignments used for different event hypothesis source types, locations, or source conditions.

Event hypothesis magnitude estimate calculation parameters are: magnitude type, signal amplitude, frequency band, event hypothesis location, signal decay (path, phase and frequency dependent), waveform data (for coda measurements), and a parameterization of the magnitude estimate function's coefficients. Relative event hypothesis magnitude estimate calculations use the magnitude estimate calculation parameters from multiple event hypotheses located in the same region to simultaneously estimate the magnitudes of each of the event hypotheses.

Maximum Likelihood Estimation (MLE) magnitudes for an event hypothesis use as input: the magnitude estimate calculation inputs for stations detecting the event hypothesis, magnitude estimate calculation inputs for stations not detecting the event hypothesis (measurements at non-detecting stations are for noise data at the expected signal arrival time rather than for signal detections), and empirical station detection thresholds.

Magnitude estimate calculations are: ML, mb, mbMLE, mbrel, MS, MSMLE, MSVMAX, Mwcoda, and infrasound magnitude. Single station magnitude estimates are computed using the magnitude estimate calculation parameters from a single station. Network magnitude estimates are computed using two or more of the single station magnitude estimates for an event hypothesis and a parameterization of the combining function used to calculate the network magnitude estimate from the single station magnitude estimates. The values in the combining function's parameterization are dependent on the network magnitude estimate type.

3.2.8.1.1 Magnitude Estimation Processing

3.2.8.1.1.1 The System shall compute single station magnitude estimates using the station's event hypothesis magnitude estimate calculation parameters. (S-1650; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-106, SRD-107

3.2.8.1.1.2 The System shall compute network magnitude estimates using single station magnitude estimates and the network magnitude estimate combining function's parameter values. (S-1651; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-106

3.2.8.1.1.3 The System shall compute uncertainties for all event hypothesis magnitude estimates. (S-1652; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-108

3.2.8.1.1.4 The System shall compute new event hypothesis magnitude estimates when a new event hypothesis location is computed. (S-1653; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-106

3.2.8.1.1.5 The System shall compute the mb body wave magnitude estimate. (S-6486; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-106

3.2.8.1.1.6 The System shall compute the mbMLE maximum likelihood body wave magnitude estimate. (S-6487; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-106

3.2.8.1.1.7 The System shall compute the mbrel relative body wave magnitude estimate. (S-6488; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-106

3.2.8.1.1.8 The System shall compute the ms surface wave magnitude estimate. (S-6489; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-106

3.2.8.1.1.9 The System shall compute the msVMAX surface wave magnitude estimate. (S-6490; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-106

3.2.8.1.1.10 The System shall compute the msMLE maximum likelihood surface wave magnitude estimate. (S-6491; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-106

3.2.8.1.1.11 The System shall compute the ml local magnitude estimate. (S-6492; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-106

3.2.8.1.1.12 The System shall compute the mwcoda coda magnitude estimate. (S-6493; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-106

3.2.8.1.1.13 The System shall compute infrasound magnitude. (S-6494; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-106

3.2.8.1.1.14 The System shall set station magnitudes to non-defining for event hypothesis magnitude calculations when the System automatically associates them to Analyst reviewed event hypotheses. (S-1544; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-83

3.2.8.1.2 Magnitude Estimation Support Interfaces

3.2.8.1.2.1 The System shall provide the System Maintainer the capability to configure the types of event hypothesis magnitude estimates to compute for newly computed event hypothesis locations by geographic region. (S-1655; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-106

3.2.8.1.2.2 The System shall provide the System Maintainer the capability to configure event hypothesis magnitude estimate calculation parameters by channel. (S-1656; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-106

3.2.8.1.2.3 The System shall provide the System Maintainer the capability to configure event hypothesis magnitude estimate calculation parameters by geographic region. (S-1657; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-106

3.2.8.1.3 Magnitude Estimation User Interfaces

3.2.8.1.3.1 The System shall provide the Analyst the capability to run event hypothesis magnitude estimate calculations with user selected input parameters. (S-1659; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-106, SRD-124, SRD-136

3.2.8.1.3.2 The System shall provide the Analyst the capability to select the type of magnitude to compute. (S-1660; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-110, SRD-124, SRD-136

3.2.8.1.3.3 The System shall provide the Analyst the capability to select the defining/non-defining state for a station magnitude estimate used for network magnitude estimation unless prohibited by the default defining/non-defining state. (S-1661; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-103, SRD-110, SRD-124, SRD-136

3.2.8.1.4 Magnitude Estimation Storage

3.2.8.1.4.1 The System shall store uncertainties for all event hypothesis magnitude estimates. (S-1663; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-108, SRD-189

3.2.8.1.4.2 The System shall store each single station magnitude estimate for each event hypothesis. (S-1664; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-106, SRD-189

3.2.8.1.4.3 The System shall store each network magnitude estimate for each event hypothesis. (S-1665; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-106, SRD-189

3.2.8.1.4.4 The System shall store the defining/non-defining state for each station magnitude associated to a stored event hypothesis. (S-1666; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-170, SRD-189

3.2.8.2 Moment Tensor Solutions

The System automatically computes moment tensor solutions for event hypotheses meeting specific criteria.

Synthetic and observed seismograms used in moment tensor calculations measure ground motion in either displacement or velocity. These criteria are specified using: event hypothesis location, event hypothesis magnitude, event hypothesis to station distance, and signal detection SNR for the phases used in computing the moment tensor.

3.2.8.2.1 Moment Tensor Solutions Processing

3.2.8.2.1.1 The System shall calculate Green functions using region specific 1D Earth models. (S-1684; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-394, SRD-395

3.2.8.2.1.2 The System shall calculate synthetic displacement waveforms. (S-1685; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-394, SRD-395

3.2.8.2.1.3 The System shall calculate synthetic velocity waveforms. (S-1686; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-394, SRD-395

3.2.8.2.1.4 The System shall calculate synthetic seismograms using Green functions computed using frequency-wavenumber integration. (S-1687; Common)

Priority: Objective / Priority 1

Verification Methodology: Test
Requirements Trace: SRD-394, SRD-395

3.2.8.2.1.5 The System shall compute Green functions in real time while computing moment tensor solutions. (S-1688; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-394, SRD-395

3.2.8.2.1.6 The System shall apply the same filter to observed and synthetic waveforms during moment tensor calculations. (S-1689; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-394, SRD-395

3.2.8.2.1.7 The System shall compute moment tensor solutions using waveform data from one or more seismic stations. (S-1690; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-394, SRD-395

3.2.8.2.1.8 The System shall decompose moment tensor solutions into isotropic and deviatoric components. (S-1691; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-394

3.2.8.2.1.9 The System shall decompose deviatoric moment tensor solutions into double couple and compensated linear vector dipole (CLVD) components. (S-1692; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-394

3.2.8.2.1.10 The System shall compute the percentage of deviatoric moment tensor solutions belonging to the double couple components. (S-1693; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-394

3.2.8.2.1.11 The System shall compute shear phase radiation patterns for moment tensor solutions. (S-1694; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-394, SRD-395

3.2.8.2.1.12 The System shall compute compressional phase radiation patterns for moment tensor solutions. (S-1695; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-394, SRD-395

3.2.8.2.1.13 The System shall compute double couple fault planes from moment tensor solutions. (S-1696; Common)

Priority: Objective / Priority 1

Verification Methodology: Test
Requirements Trace: SRD-394

3.2.8.2.1.14 The System shall compute the scalar seismic moment from moment tensor solutions. (S-1697; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-394, SRD-395

3.2.8.2.1.15 The System shall calculate station specific goodness of fit between theoretical and observed waveforms for moment tensor solutions. (S-1698; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-394, SRD-395

3.2.8.2.2 Moment Tensor Solutions Support Interfaces

3.2.8.2.2.1 The System shall provide the System Maintainer the capability to configure the criteria used to determine if a moment tensor solution is automatically computed for an event hypothesis by geographic region. (S-1701; Common)

Priority: Objective / Priority 1
Verification Methodology: Demonstration
Requirements Trace: SRD-394, SRD-395

3.2.8.2.2.2 The System shall provide the System Maintainer the capability to configure the type of ground motion (displacement or velocity) to use for moment tensor calculations by station. (S-1702; Common)

Priority: Objective / Priority 1
Verification Methodology: Demonstration
Requirements Trace: SRD-394, SRD-395

3.2.8.2.2.3 The System shall provide the System Maintainer the capability to configure which stations that have detected an event hypothesis are used in automatically initiated moment tensor calculations by geographic region. (S-1703; Common)

Priority: Objective / Priority 1
Verification Methodology: Demonstration
Requirements Trace: SRD-394, SRD-395

3.2.8.2.2.4 The System shall provide the System Maintainer the capability to configure the filter applied to observed and synthetic waveforms when computing moment tensor solutions. (S-1704; Common)

Priority: Objective / Priority 1
Verification Methodology: Demonstration
Requirements Trace: SRD-394, SRD-395

3.2.8.2.3 Moment Tensor Solutions User Interfaces

3.2.8.2.3.1 The System shall provide the Analyst the capability to compute a moment tensor solution for a selected event hypothesis and collection of seismic stations. (S-1706; Common)

Priority: Objective / Priority 1
Verification Methodology: Demonstration
Requirements Trace: SRD-136, SRD-394, SRD-395

3.2.8.2.3.2 The System shall provide the Analyst the capability to view the theoretical waveform overlaid on the observed waveform for a moment tensor solution. (S-1707; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-394, SRD-395

3.2.8.2.3.3 The System shall provide the Analyst the capability to view the station specific goodness of fit between theoretical and observed waveforms for moment tensor solutions. (S-1708; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-394, SRD-395

3.2.8.2.3.4 The System shall provide the Analyst the capability to view double couple focal mechanisms. (S-1709; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-394

3.2.8.2.4 Moment Tensor Solutions Storage

3.2.8.2.4.1 The System shall store the type of ground motion used by moment tensor calculations. (S-1711; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-394, SRD-395

3.2.8.2.4.2 The System shall store the filter applied to observed and synthetic waveforms when computing moment tensor solutions. (S-1712; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-394, SRD-395

3.2.8.2.4.3 The System shall store the Green functions used to compute a moment tensor solution. (S-1713; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-394, SRD-395

3.2.8.2.4.4 The System shall store the Earth models used to compute a moment tensor solution. (S-1714; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-394, SRD-395

3.2.8.2.4.5 The System shall store the elements of moment tensor solutions. (S-1715; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-394, SRD-395

3.2.8.2.4.6 The System shall store the percentage of deviatoric moment tensor solutions belonging to the double couple components. (S-1716; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-394, SRD-395

3.2.8.2.4.7 The System shall store the double couple fault plane solution computed from a moment tensor solution. (S-1717; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-394, SRD-395

3.2.8.2.4.8 The System shall store the scalar seismic moment computed from a moment tensor solution. (S-1718; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-394, SRD-395

3.2.8.2.4.9 The System shall store the station specific goodness of fit between theoretical and observed waveforms for moment tensor solutions. (S-1719; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-394, SRD-395

3.2.8.3 Moment Tensor Source Type Plotting

Moment tensor source type plots display moment tensors in terms of two source type parameters, ϵ and k . ϵ is a measure of how much a deviatoric moment tensor deviates from a double couple source and k is a measure of volume change showing deviation from a purely explosive source. Hudson's source type plots involve a transformation on this 2D space and are described in the referenced paper.

Uncertainty bounds on ϵ and k are found using bootstrap resampling. New moment tensor solutions are created through bootstrapping. Using sampling with replacement, collections of stations contributing to the moment tensor solution are sampled from the stations used in the initial moment tensor solution. New moment tensor solutions are calculated for each sample, and ϵ and k are computed for each new moment tensor. This gives a representative distribution of ϵ and k from which uncertainty bounds are computed.

3.2.8.3.1 Moment Tensor Source Type Plotting Processing

3.2.8.3.1.1 The System shall compute Hudson's ϵ value for moment tensor solutions. (S-1722; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-395

3.2.8.3.1.2 The System shall compute Hudson's k value for moment tensor solutions. (S-1723; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-395

3.2.8.3.1.3 The System shall use bootstrap resampling on the stations used in moment tensor solutions to estimate the distributions of ϵ for the moment tensor solutions. (S-1724; Common)

Priority: Objective / Priority 1

Verification Methodology: Test
Requirements Trace: SRD-395

3.2.8.3.1.4 The System shall use bootstrap resampling on the stations used in moment tensor solutions to estimate the distributions of κ for the moment tensor solutions. (S-1725; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-395

3.2.8.3.1.5 The System shall use the distributions of ϵ and κ from bootstrap resampling on moment tensor solutions to compute the uncertainty bound on ϵ and κ at a fixed confidence level for the moment tensor solutions. (S-1726; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-395

3.2.8.3.2 Moment Tensor Source Type Plotting Support Interfaces

3.2.8.3.3 Moment Tensor Source Type Plotting User Interfaces

3.2.8.3.3.1 The System shall provide the Analyst the capability to select the number of samples to use during bootstrap resampling on moment tensor solutions to estimate the distributions of ϵ and κ . (S-1728; Common)

Priority: Objective / Priority 1
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-136, SRD-395

3.2.8.3.3.2 The System shall provide the Analyst the capability to select the confidence level used to compute uncertainty bounds on ϵ and κ for a moment tensor solution. (S-1729; Common)

Priority: Objective / Priority 1
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-136, SRD-395

3.2.8.3.3.3 The System shall provide the Analyst the capability to view transformed source type plots for moment tensor solutions as described in Hudson, Pearce, and Rogers (1989). (S-1730; Common)

Priority: Objective / Priority 1
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-136, SRD-395

3.2.8.3.3.4 The System shall provide the Analyst the capability to view the uncertainty bound on ϵ and κ in transformed source type plots. (S-1731; Common)

Priority: Objective / Priority 1
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-136, SRD-395

3.2.8.3.3.5 The System shall provide the Analyst the capability to view multiple moment tensor solutions and their associated uncertainty bounds on ϵ and κ on the same transformed source type plot. (S-1732; Common)

Priority: Objective / Priority 1
Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-395

3.2.8.3.3.6 The System shall provide the Analyst the capability to select a group of event hypotheses for which moment tensor solutions and their associated uncertainty bounds on ϵ and k are plotted on a transformed source type plot. (S-1733; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-395

3.2.8.3.4 Moment Tensor Source Type Plotting Storage

3.2.8.3.4.1 The System shall store the ϵ value computed for moment tensor solutions. (S-1735; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-395

3.2.8.3.4.2 The System shall store the k value computed for moment tensor solutions. (S-1736; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-395

3.2.8.3.4.3 The System shall store the uncertainty bounds on ϵ and k computed for moment tensor solutions. (S-1737; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-395

3.2.8.3.4.4 The System shall store the confidence level of uncertainty bounds on ϵ and k computed for moment tensor solutions. (S-1738; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-395

3.2.8.4 Event Screening

The System attempts to screen events that are non-nuclear based on configurable criteria applied to characteristics of Analyst reviewed events.

3.2.8.4.1 Event Screening Processing

3.2.8.4.1.1 The System shall calculate a numerical metric for each configured screening criterion for each event. (S-5744; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-613

3.2.8.4.1.2 The System shall assign an overall screening category based on a combination of the individual screening criteria numerical metric scores. (S-5745; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-449

3.2.8.4.1.3 The System shall calculate event definition criteria for each event based on a weighted count of defining signal detection feature measurements. (S-6548; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-613

3.2.8.4.1.4 The System shall calculate event definition criteria for each event based on the number of configured observation types at specific station types. (S-6549; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-613

3.2.8.4.1.5 The System shall publish events in the Reviewed Event Bulletin (REB) based on the event definition criteria. (S-6550; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-613

3.2.8.4.2 Event Screening Support Interfaces

3.2.8.4.2.1 The System shall provide the System Maintainer the capability to configure which screening criterion to calculate for each event. (S-5743; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-613

3.2.8.4.2.2 The System shall provide the System Maintainer the capability to configure which individual screening criteria numerical metric scores are combined to calculate an overall screening category. (S-5746; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-449

3.2.8.4.2.3 The System shall provide the System Maintainer the capability to configure the event definition criteria. (S-6551; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-613

3.2.8.4.3 Event Screening User Interfaces

3.2.8.4.3.1 The System shall provide the Analyst the capability to mark signal detections associated to an event so as to exclude them from event screening calculations. (S-5827; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-623

3.2.8.4.4 Event Screening Storage

3.2.9 Earth Propagation Models

3.2.9.1 Earth Model Predictions

For an event that occurs anywhere in the Earth, predictions of the following observables are needed. –

- Seismic body waves: -
 - Phase-specific source-receiver travel time
 - Phase-specific horizontal slowness observed at a station
 - Phase-specific back-azimuth observed at a station
 - Frequency and phase-specific signal amplitude at a station
- Seismic surface waves: -
 - Frequency and phase specific source-receiver travel time
 - Frequency and phase specific horizontal slowness observed at a station
 - Frequency and phase specific back-azimuth observed at a station
 - Frequency and phase specific signal amplitude at a station
 - Blockage at a station
- Infrasound waves: -
 - Frequency and phase specific source-receiver travel time
 - Frequency and phase specific horizontal slowness observed at a station
 - Frequency and phase specific back-azimuth observed at a station
 - Frequency and phase specific signal amplitude at a station
 - Blockage at a station
- Hydroacoustic waves: -
 - Phase-specific source-receiver travel time –
 - Phase-specific horizontal slowness observed at a station –
 - Phase-specific back-azimuth observed at a station –
 - Frequency and phase-specific signal amplitude at a station –
 - Blockage at a station

Note: the only hydroacoustic phases are H and T

For travel time, horizontal slowness and back azimuth predictions, the following components are necessary: the predicted value, the uncertainty of the predicted value, and derivatives of the predicted value with respect to spatial position and time. For amplitude, only the predicted value and the associated uncertainty are needed. In the remainder of this preamble, the term prediction includes the associated uncertainty and derivatives (except for amplitude where the derivatives are not needed).

Predicted back azimuth is often assumed to be the azimuth of the great circle path from the receiver to the source. Because this prediction is based only on geometry and requires no geophysical knowledge at all, there are no requirements in this SSD related to computing back azimuth predictions in this manner. There are exceptions however. Ray tracing through Earth models where the velocity varies as a function of position can generate back azimuth predictions that do not coincide with the receiver-source great circle path and requirements related to phase-specific back azimuth prediction are included to cover that possibility.

The System may choose to implement acquisition of predictions in one of three basic ways. The choice of method is based on the state of knowledge of Earth properties, the computational cost of implementation, and the ability to verify the robustness and fidelity of the computed values.

1. On-the-fly integration of Earth properties

Fundamental properties of the Earth, which are generally stored in geophysical Earth models, are integrated along phase-specific ray paths from source to receiver. The System will compute predictions on-the-fly at the time that they are required. The Earth properties to be integrated for each prediction are:

- Seismic body wave predictions: seismic velocity

- Seismic surface wave predictions: group or phase velocity; or seismic velocity
- Infrasound predictions: sound speed in air
- Hydroacoustic predictions: sound speed in water (SOFAR channel)
- Amplitude predictions: quality factor, Q This approach is most appropriate when the integral is computationally inexpensive and the robustness of the computed predictions is easily verified.

This approach is often adopted for predicting seismic surface wave travel-time and MDAC seismic body-wave amplitude, largely due to the fact the ray paths are well represented by simple great circle paths from source to receivers, rendering the path integral very simple to calculate.

2. Precomputed Prediction Lookup Tables

Similar to the first option, but predictions are pre-computed off-line for a grid of hypothetical source locations and stored in lookup tables. Actors external to the System may perform this step. Later, when predictions are required, their values are interpolated from the appropriate lookup table based on an assumed source location. The current system uses this approach for travel time prediction of teleseismic phases. This approach is also typically used for seismic body wave travel-time predictions computed using 3D velocity models because complex ray-tracing is required which can be computationally demanding and the robustness of the results can be challenging to verify.

3. Models derived directly from empirical observations

Empirical observations of the relevant parameter are statistically distilled into spatially varying estimates of the predicted values. No path integral through a model of Earth properties is performed, either on-the-fly or offline. Predicted values for a particular station-phase are obtained from a station-phase specific model by interpolation from the model at the assumed source location. This approach is often used for body wave amplitude predictions because the state of knowledge about the distribution of Q in the Earth does not warrant the complexity of ray tracing, even along great circle paths.

4. Empirical corrections to basemodel predictions

So far, the discussion has focused on models that are capable of producing predictions for events anywhere on the Earth, even regions where events have never been recorded before. To improve these predictions for events in regions with a substantial history of recorded events, empirically derived corrections for earth model predictions are developed. These corrections describe how observed values of a phase at a station for events in a particular region differ from basemodel predictions. Corrections are applied to values predicted from basemodels to improve the match between the predicted values and historical observations.

Signal predictions may be computed either by on-the-fly integration of Earth properties or by interpolation of values from precomputed lookup tables.

Earth model predictions are used during: predicting arrivals, event hypothesis magnitude estimation, event hypothesis location, and signal association.

3.2.9.1.1 Earth Model Predictions Processing

3.2.9.1.1.1 The System shall use correction surfaces to compute corrections to earth model predictions. (S-1776; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-203, SRD-204, SRD-212

3.2.9.1.1.2 The System shall apply earth model prediction corrections to earth model predictions computed from basemodels. (S-1777; Common)

Priority: Threshold

Verification Methodology: Test
Requirements Trace: SRD-203, SRD-204, SRD-212

3.2.9.1.1.3 The System shall apply empirical Master Event Corrections by station and phase to earth model predictions and prediction uncertainties. (S-1778; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-203

3.2.9.1.1.4 The System shall compute predicted slowness using a one-dimensional phase-specific basemodel. (S-1779; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-197

3.2.9.1.1.5 The System shall compute phase-specific slowness predictions using a velocity model where the velocity of the Earth varies as a function of depth/elevation but not latitude or longitude. (S-1780; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-197

3.2.9.1.1.6 The System shall compute the uncertainties of predicted slowness computed using a one-dimensional phase-specific basemodel. (S-1781; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-197

3.2.9.1.1.7 The System shall compute the uncertainty of phase-specific slowness predictions using a velocity model where the velocity of the Earth varies as a function of depth/elevation but not latitude or longitude. (S-1782; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-197

3.2.9.1.1.8 The System shall compute predicted slowness using a three-dimensional phase-specific basemodel. (S-1783; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-198

3.2.9.1.1.9 The System shall compute phase-specific slowness predictions using a velocity model where the velocity of the Earth varies as a function of latitude, longitude, and depth/elevation. (S-1784; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-198

3.2.9.1.1.10 The System shall compute the uncertainties of predicted slowness computed using a three-dimensional phase-specific basemodel. (S-1785; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-198

3.2.9.1.1.11 The System shall compute the uncertainty of phase-specific slowness predictions using a velocity model where the velocity of the Earth varies as a function of latitude, longitude, and depth/elevation. (S-1786; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-198

3.2.9.1.1.12 The System shall compute predicted azimuths using a three-dimensional phase-specific basemodel. (S-1787; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-199

3.2.9.1.1.13 The System shall compute phase-specific azimuth predictions using a velocity model where the velocity of the Earth varies as a function of latitude, longitude, and depth/elevation. (S-1788; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-199

3.2.9.1.1.14 The System shall compute the uncertainties of predicted azimuths computed using a three-dimensional phase-specific basemodel. (S-1789; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-199

3.2.9.1.1.15 The System shall compute uncertainty of phase-specific azimuth predictions using a velocity model where the velocity of the Earth varies as a function of latitude, longitude, and depth/elevation. (S-1790; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-199

3.2.9.1.1.16 The System shall use a meteorological model for computing azimuths in infrasound data. (S-5830; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-199

3.2.9.1.1.17 The System shall compute predicted travel-times using a one-dimensional phase-specific basemodel. (S-1791; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-200

3.2.9.1.1.18 The System shall compute phase-specific travel-time predictions using a velocity model where the velocity of the Earth varies as a function of depth/elevation but not latitude or longitude. (S-1792; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-200

3.2.9.1.1.19 The System shall compute the uncertainties of predicted travel-times computed using a one-dimensional phase-specific basemodel. (S-1793; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-200

3.2.9.1.1.20 The System shall compute the uncertainty of phase-specific travel-time predictions using a velocity model where the velocity of the Earth varies as a function of depth but not latitude or longitude. (S-1794; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-200

3.2.9.1.1.21 The System shall compute predicted travel-times using a two-dimensional phase-specific basemodel. (S-1795; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-201, SRD-206

3.2.9.1.1.22 The System shall compute phase-specific travel-time predictions using a velocity model where the velocity of the Earth varies as a function of latitude and longitude but not depth/elevation. (S-1796; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-201, SRD-206

3.2.9.1.1.23 The System shall compute predicted travel time of Rayleigh waves and Love waves using frequency-specific group and phase velocity models where the group/phase velocity varies as a function of latitude and longitude but not depth. (S-1797; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-201, SRD-206

3.2.9.1.1.24 The System shall compute the uncertainties of predicted travel-times computed using a two-dimensional phase-specific basemodel. (S-1798; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-201

3.2.9.1.1.25 The System shall compute phase-specific uncertainty of predicted travel-time using a velocity model where the velocity of the Earth varies as a function of latitude and longitude but not depth/elevation. (S-1799; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-201

3.2.9.1.1.26 The System shall compute uncertainty of predicted travel time of Rayleigh waves and Love waves using frequency-specific group and phase velocity models where the group/phase velocity varies as a function of latitude and longitude but not depth. (S-1800; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-201

3.2.9.1.1.27 The System shall compute predicted travel-times using a three-dimensional phase-specific basemodel. (S-1801; Common)

Priority: Extensibility

Verification Methodology: Test

Requirements Trace: SRD-202, SRD-206

3.2.9.1.1.28 The System shall compute phase-specific travel-time predictions using a velocity model where the velocity of the Earth varies as a function of latitude, longitude, and depth/elevation. (S-1802; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-202, SRD-206

3.2.9.1.1.29 The System shall compute the uncertainties of predicted travel-times computed using a three-dimensional phase-specific basemodel. (S-1803; Common)

Priority: Extensibility

Verification Methodology: Test

Requirements Trace: SRD-202

3.2.9.1.1.30 The System shall compute phase-specific uncertainty of predicted travel-time using a velocity model where the velocity of the Earth varies as a function of latitude, longitude, and depth/elevation. (S-1804; Common)

Priority: Extensibility

Verification Methodology: Test

Requirements Trace: SRD-202

3.2.9.1.2 Earth Model Predictions Support Interfaces

3.2.9.1.2.1 The System shall provide the System Maintainer the capability to configure the default earth models used for earth model predictions per observation type. (S-1806; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-71

3.2.9.1.2.2 The System shall provide the System Maintainer the capability to configure the default earth models used for earth model predictions per station, phase, frequency and channel. (S-1807; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-71

3.2.9.1.2.3 The System shall provide the System Maintainer the capability to configure station, phase, and frequency dependent correction surfaces for earth model prediction corrections. (S-1808; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-203, SRD-204, SRD-212

3.2.9.1.2.4 The System shall provide the System Maintainer the capability to configure earth model parameters. (S-1809; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-137

3.2.9.1.3 Earth Model Predictions User Interfaces

3.2.9.1.3.1 The System shall provide the Analyst the capability to select the earth model used for an earth model prediction. (S-1811; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-137, SRD-197, SRD-198, SRD-199, SRD-200, SRD-201, SRD-202, SRD-209, SRD-211

3.2.9.1.3.2 The System shall provide the Analyst the capability to select the correction surface used for correcting an earth model prediction. (S-1812; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-203, SRD-204, SRD-212

3.2.9.1.3.3 The System shall provide the Analyst the capability to apply Master Event Corrections. (S-1813; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-136, SRD-203

3.2.9.1.3.4 The System shall provide the Analyst the capability to view theoretical arrival times for an Analyst selected set of seismic phases. (S-1814; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.9.1.3.5 The System shall provide the Analyst the capability to view the model parameters used to predict signal propagation. (S-5852; Common)

Priority: Extensibility

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.9.1.3.6 The System shall provide the Analyst the capability to view the earth models on a map. (S-5853; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.9.1.4 Earth Model Predictions Storage

3.2.9.1.4.1 The System shall store the earth model and version used to compute an earth model prediction. (S-1816; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-197, SRD-198, SRD-199, SRD-200, SRD-201, SRD-202, SRD-209, SRD-211

3.2.9.1.4.2 The System shall store the corrections applied to earth model predictions. (S-1817; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-203, SRD-204, SRD-212

3.2.9.1.4.3 The System shall store the correction surface used to correct an earth model prediction. (S-1818; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-203, SRD-204, SRD-212

3.2.9.1.4.4 The System shall store the predicted slowness computed from a basemodel. (S-1819; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-197, SRD-198

3.2.9.1.4.5 The System shall store the uncertainties of a predicted slowness computed using a basemodel. (S-1820; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-197, SRD-198

3.2.9.1.4.6 The System shall store the predicted azimuths computed using a phase-specific basemodel. (S-1821; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-199

3.2.9.1.4.7 The System shall store the uncertainties of predicted azimuths computed using a basemodel. (S-1822; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-199

3.2.9.1.4.8 The System shall store the predicted travel-times computed from a basemodel. (S-1823; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-200, SRD-201, SRD-202

3.2.9.1.4.9 The System shall store the uncertainties of predicted travel-times computed using a basemodel. (S-1824; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-200, SRD-201, SRD-202

3.2.9.1.4.10 The System shall store global meteorological data. (S-5714; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-610

3.2.9.1.4.11 The System shall store wind velocity (including uncertainty) computed from meteorological models. (S-5715; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-610

3.2.9.1.4.12 The System shall store temperature (including uncertainty) computed from meteorological models. (S-5716; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-610

3.2.9.1.4.13 The System shall store gravity wave corrections to temperature predictions. (S-5717; Common)

Priority: Extensibility

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-610

3.2.9.2 Amplitude Attenuation Basemodels

Amplitude attenuation basemodels describe how signal amplitudes decay as a result of propagating through physical media from sources to receivers. Three classes of amplitude attenuation basemodels are available:

- One-dimensional basemodels: account for distance between source and receiver.
- Two-dimensional basemodels: account for the great circle signal propagation path between source and receiver.
- Three-dimensional basemodels: account for the 3D signal propagation path between source and receiver.

Each type of amplitude attenuation basemodel is dependent on signal phase and frequency.

3.2.9.2.1 Amplitude Attenuation Basemodels Processing

3.2.9.2.1.1 The System shall compute predicted amplitude attenuation from phase and frequency dependent one-dimensional basemodels. (S-1827; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-209

3.2.9.2.1.2 The System shall compute amplitude correction factors using Q models where Q in the Earth varies as a function of phase, frequency and depth, but not latitude or longitude. (S-1828; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-209

3.2.9.2.1.3 The System shall compute predicted amplitude attenuation uncertainties from phase and frequency dependent one-dimensional basemodels. (S-1829; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-209

3.2.9.2.1.4 The System shall compute the uncertainty of amplitude correction factors computed using Q models where Q in the Earth varies as a function of phase, frequency and depth, but not latitude or longitude. (S-1830; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-209

3.2.9.2.1.5 The System shall compute predicted amplitude attenuation from frequency dependent three-dimensional basemodels. (S-1837; Common)

Priority: Extensibility

Verification Methodology: Test

Requirements Trace: SRD-211

3.2.9.2.1.6 The System shall compute amplitude correction factors using Q models where Q in the Earth varies as a function of phase, frequency, latitude, longitude and depth. (S-1838; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-211

3.2.9.2.1.7 The System shall compute predicted amplitude attenuation uncertainties from frequency dependent three-dimensional basemodels. (S-1839; Common)

Priority: Extensibility

Verification Methodology: Test

Requirements Trace: SRD-211

3.2.9.2.1.8 The System shall compute the uncertainty of amplitude correction factors computed using Q models where Q in the Earth varies as a function of phase, frequency, latitude, longitude and depth. (S-1840; Common)

Priority: Extensibility

Verification Methodology: Test

Requirements Trace: SRD-211

3.2.9.2.1.9 The System shall compute predicted signal amplitude decay from geometric spreading as a function of phase and distance from the source. (S-3041; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-209

3.2.9.2.1.10 The System shall compute uncertainty of predicted signal amplitude decay from geometric spreading as a function of phase and distance from the source. (S-3042; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-209

3.2.9.2.1.11 The System shall compute predicted signal amplitude decay from geometric spreading as a function of phase, frequency, and propagation path from the source. (S-3043; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-211

3.2.9.2.1.12 The System shall compute uncertainty of predicted signal amplitude decay from geometric spreading as a function of phase, frequency, and propagation path from the source. (S-3044; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-211

3.2.9.2.1.13 The System shall correct signal amplitudes for decay from geometric spreading when applying amplitude attenuation corrections. (S-3045; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-209, SRD-211

3.2.9.2.2 Amplitude Attenuation Basemodels Support Interfaces

3.2.9.2.3 Amplitude Attenuation Basemodels User Interfaces

3.2.9.2.4 Amplitude Attenuation Basemodels Storage

3.2.9.2.4.1 The System shall store predicted amplitude attenuation. (S-1842; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-209, SRD-211

3.2.9.2.4.2 The System shall store predicted amplitude attenuation uncertainties. (S-1843; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-209, SRD-211

3.2.9.3 Basemodel Temporal Variation

Variations in atmospheric and oceanic conditions lead to a time dependence in the amplitude attenuation of infrasonic and hydroacoustic signals. Infrasonic signals attenuate according to atmospheric wind conditions.

Hydroacoustic signals can travel global distances in the SOFAR channel, but attenuate more outside of this channel. Depth of the SOFAR channel is related to ocean temperature.

Atmospheric model resolution for use in the System should be hourly or finer to support diurnal variations and daily, weekly, or monthly to support seasonal variations. Two types of climate models capturing temporal variations are available.

- Climatological models average diurnal or seasonal conditions over a period of time.
- Meteorological models cover conditions for specific time periods

Propagation path specific temporal variations can be computed by using signal propagation velocity to sample the climate model along points on the propagation path at the time the signal crosses those points.

Time dependent travel time and/or amplitude attenuation models are used to compute: predicted signal detections, distance corrected signal detection feature measurements (such as amplitude), and event hypothesis locations.

Temporal dependence is not needed for seismic signals since changes in geological structures occur much slower than changes in water and air.

3.2.9.3.1 Basemodel Temporal Variation Processing

3.2.9.3.1.1 The System shall compute time dependent predicted amplitude attenuation for infrasonic signals. (S-1846; Common)

Priority: Extensibility

Verification Methodology: Test

Requirements Trace: SRD-213

3.2.9.3.1.2 The System shall compute time dependent predicted amplitude attenuation uncertainties for infrasonic signals. (S-1847; Common)

Priority: Extensibility

Verification Methodology: Test

Requirements Trace: SRD-213

3.2.9.3.1.3 The System shall compute time dependent predicted amplitude attenuation for hydroacoustic signals. (S-1848; Common)

Priority: Extensibility

Verification Methodology: Test

Requirements Trace: SRD-213

3.2.9.3.1.4 The System shall compute time dependent predicted amplitude attenuation uncertainties for hydroacoustic signals. (S-1849; Common)

Priority: Extensibility

Verification Methodology: Test

Requirements Trace: SRD-213

3.2.9.3.1.5 The System shall compute wind velocity predictions using meteorological models that vary as a function of latitude, longitude, altitude, and time. (S-5615; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-418, SRD-652

3.2.9.3.1.6 The System shall compute corrections to wind velocity predictions based on a model for atmospheric gravity waves. (S-5652; Common)

Priority: Extensibility

Verification Methodology: Test

Requirements Trace: SRD-418, SRD-601

3.2.9.3.1.7 The System shall compute corrections to atmospheric temperature predictions based on a model for atmospheric gravity waves. (S-5653; Common)

Priority: Extensibility

Verification Methodology: Test

Requirements Trace: SRD-418, SRD-601

3.2.9.3.1.8 The system shall compute an infrasound propagation model using gravity wave corrected wind velocity and atmospheric temperature predictions. (S-5654; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-418

3.2.9.3.1.9 The system shall compute an infrasound propagation model that incorporates high resolution meteorological data. (S-5656; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-419

3.2.9.3.1.10 The System shall incorporate monthly variations in hydroacoustic blockage. (S-1851; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-205

3.2.9.3.1.11 The System shall incorporate monthly variations in travel time for hydroacoustic data. (S-1852; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-206

3.2.9.3.1.12 The System shall use a meteorological model for computing travel times in infrasound data. (S-1853; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-206

3.2.9.3.1.13 The system shall compute infrasound travel-time, trace velocity, and attenuation using an infrasound propagation model and thermospheric, tropospheric, stratospheric, and direct phases. (S-5655; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-206, SRD-419

3.2.9.3.1.14 The system shall compute uncertainties of infrasound travel-time, trace velocity, and attenuation using an infrasound propagation model and thermospheric, tropospheric, stratospheric, and direct phases. (S-5657; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-419

3.2.9.3.1.15 The System shall use a daily and hourly varying meteorological model for computing travel times in infrasound data. (S-5828; Common)

Priority: Objective / Priority 1
Verification Methodology: Test
Requirements Trace: SRD-206

3.2.9.3.1.16 The System shall model Lamb waves when computing travel times in infrasound data. (S-1856; Common)

Priority: Objective / Priority 2
Verification Methodology: Test
Requirements Trace: SRD-206

3.2.9.3.2 Basemodel Temporal Variation Support Interfaces

3.2.9.3.3 Basemodel Temporal Variation User Interfaces

3.2.9.3.3.1 The System shall provide the System User the capability to view temporal amplitude attenuation for infrasonic and hydroacoustic signals. (S-1850; Common)

Priority: Extensibility
Verification Methodology: Demonstration
Requirements Trace: SRD-213

3.2.9.3.4 Basemodel Temporal Variation Storage

3.2.10 Processing Stage Workflow

The System runs groups of operations to prepare for future system processing stages whenever particular triggering events occur. Operations available for grouping include: time domain measurements, frequency domain measurements, beamforming, magnitude calculations, phase identification, and signal detection association.

Triggering events include: completion of a particular processing stage, initiating magnitude estimation calculation, upon Analyst initiation for data, upon Analyst initiation for one or more Analyst modified arrivals, upon Analyst initiation for one or more Analyst created arrivals, upon Analyst initiation for one or more Analyst modified events, and upon Analyst initiation for one or more Analyst created events.

3.2.10.1 Processing Stage Workflow Processing

3.2.10.1.1 The System shall set the processing stage workflow status of a processing time interval to reflect analysis activity. (S-1859; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-403

3.2.10.1.2 The System shall set the processing stage workflow status of events to reflect analysis activity. (S-2588; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-403

3.2.10.1.3 The System shall process waveform data within a configurable processing time interval when a configurable percentage of data is available. (S-1860; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-276

3.2.10.1.4 The System shall process all available alphanumeric data within a configurable processing time interval. (S-1861; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-276

3.2.10.1.5 The System shall run a previously configured group of operations whenever the triggering event for that group of operations occurs. (S-1862; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-63, SRD-81, SRD-263, SRD-276, SRD-402

3.2.10.1.6 The System shall automatically execute processing of waveform data (i.e., data acquisition, data processing, and data storage). (S-2173; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-356

3.2.10.1.7 The System shall by default invoke the same algorithms during interactive processing as those used in automated processing. (S-5621; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-135

3.2.10.2 Processing Stage Workflow Support Interfaces

3.2.10.2.1 The System shall provide the System Maintainer the capability to configure the processing time interval and percentage of data available for waveform data processing. (S-1865; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-277

3.2.10.2.2 The System shall provide the System Maintainer the capability to configure the processing time interval for event hypothesis data processing. (S-1866; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-277

3.2.10.2.3 The System shall provide the System Maintainer the capability to configure the initiation of automatic processing based on time intervals. (S-1867; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-217, SRD-402

3.2.10.2.4 The System shall provide the System Maintainer the capability to configure the initiation of automatic processing based on data availability. (S-1868; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-217, SRD-280, SRD-402

3.2.10.2.5 The System shall provide the System Maintainer the capability to configure the initiation of automatic processing based on processing stage completion. (S-1869; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-217, SRD-402

3.2.10.2.6 The System shall provide the System Maintainer the capability to configure groups of operations to run whenever a triggering event specified by the System Maintainer occurs. (S-1870; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-63, SRD-81, SRD-263, SRD-276, SRD-402

3.2.10.2.7 The System shall provide the System Maintainer the capability to configure whether the Analyst can interrupt automated event hypothesis processing. (S-5557; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-276

3.2.10.3 Processing Stage Workflow User Interfaces

3.2.10.3.1 The System shall provide the Analyst the capability to set the processing stage workflow status of a processing time interval. (S-2589; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-403

3.2.10.3.2 The System shall provide the Analyst the capability to set the processing stage workflow status of an event. (S-2590; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-403

3.2.10.3.3 The System shall provide the Analyst the capability to interrupt automated event hypothesis processing to analyze data if configured. (S-1872; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-136, SRD-140

3.2.10.3.4 The System shall provide the System User the capability to view the processing stage workflow status of processing time intervals. (S-1874; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-403

3.2.10.3.5 The System shall provide the Analyst the capability to allocate analysis time intervals for a processing stage. (S-1875; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-404

3.2.10.3.6 The System shall notify Analysts working in a common processing stage if they are concurrently modifying event hypotheses for an event. (S-1876; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-402

3.2.10.3.7 The System shall notify Analysts working in a common processing stage if they are concurrently modifying signal detections in the same analysis time interval. (S-1877; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-402

3.2.10.3.8 The System shall provide the Analyst the capability to analyze any data stored on the System where station configuration data exists. (S-1879; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-136, SRD-218

3.2.10.3.9 The System shall provide the System User the capability to retrieve stored processing results from computations. (S-2040; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-136, SRD-169

3.2.10.4 Processing Stage Storage

3.2.10.4.1 The System shall store all data and derived processing results to persistent storage as soon as the data and/or derived processing results are available. (S-2223; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-271

3.2.10.4.2 The System shall store automatic and interactive processing results. (S-2043; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-63, SRD-79, SRD-83, SRD-169, SRD-189, SRD-263

3.2.11 Interactive Analysis

Interactive Analysis provides System Users the capability to review, refine, correct, and display the processing results generated by pipeline processing or interactive analysis.

3.2.11.1 Waveform Interaction

3.2.11.1.1 Waveform Interaction Processing

3.2.11.1.1.1 The System shall display 24 hours of continuous waveform data before the waveform displays flatline. (S-1885; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124

3.2.11.1.2 Waveform Interaction Support Interfaces

3.2.11.1.2.1 The System shall provide the System Maintainer the capability to configure the visibility of waveforms for interactive analysis by station as default, available on demand, and limited analysis. (S-2595; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-278

3.2.11.1.3 Waveform Interaction User Interfaces

3.2.11.1.3.1 The System shall provide the Analyst the capability to select for analysis a time block of continuous waveform data. (S-1887; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-127, SRD-136

3.2.11.1.3.2 The System shall provide the Analyst the capability to analyze continuous waveform data from within a selected time block. (S-1888; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-127, SRD-136

3.2.11.1.3.3 The System shall provide the Analyst the capability to access late-arriving waveform data within one (1) minute of receipt by the Data Processing Partition. (S-2604; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-136, SRD-265

3.2.11.1.3.4 The System shall provide the System User the capability to access requested waveform data. (S-2603; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-136

3.2.11.1.3.5 The System shall provide the Analyst the capability to overlay waveforms with other waveforms. (S-1889; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-133, SRD-136

3.2.11.1.3.6 The System shall provide the Analyst the capability to select the amount of waveform data to view before waveform displays flatline. (S-1890; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.7 The System shall provide the Analyst the capability to select if waveform displays show flatlined waveforms. (S-1891; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.8 The System shall provide the Analyst the capability to sort channels based on distance from event. (S-1893; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.9 The System shall provide the Analyst the capability to sort channels based on station name. (S-1894; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.10 The System shall provide the Analyst the capability to sort channels based on station probability of detection for an event. (S-1895; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.11 The System shall provide the Analyst the capability to show all channels for a beam. (S-1896; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.12 The System shall provide the Analyst the capability to show all channels for an array. (S-1897; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.13 The System shall provide the Analyst the capability to show all channels for a 3-component station. (S-1898; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.14 The System shall provide the Analyst the capability to zoom the time axis of the waveform display. (S-1899; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.15 The System shall provide the Analyst the capability to scale the amplitude of individual displayed waveforms. (S-1900; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.16 The System shall provide the Analyst the capability to view a group of waveforms with their amplitudes scaled relative to the amplitudes of the other waveforms in the group. (S-1901; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.17 The System shall provide the Analyst the capability to adjust the height of an individual waveform display. (S-1902; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.18 The System shall provide the Analyst the capability to scroll waveform data along the time axis. (S-1903; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.19 The System shall provide the Analyst the capability to scroll the channels shown on the waveform display. (S-1904; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.20 The System shall provide the Analyst the capability to select the number of channels that are simultaneously visible on the waveform display. (S-1905; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.21 The System shall provide the Analyst the capability to time align waveforms based on observed signal detections for a user selected phase. (S-1906; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.22 The System shall provide the Analyst the capability to time align waveforms based on real time. (S-1907; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.23 The System shall provide the Analyst the capability to align waveforms based on theoretical signal detections for a user selected phase. (S-1908; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.24 The System shall provide the Analyst the capability to select signal detections as processing input based on a time interval for an entire network during an analysis session. (S-1927; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-138, SRD-142

3.2.11.1.3.25 The System shall provide the Analyst the capability to select signal detections as processing input based on a time interval for a selected subset of stations during an analysis session. (S-1928; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-138, SRD-142

3.2.11.1.3.26 The System shall provide the Analyst the capability to individually select signal detections as processing input during an analysis session. (S-1929; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-138, SRD-142

3.2.11.1.3.27 The System shall display the detection feature map for an infrasound signal detection. (S-6295; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124

3.2.11.1.3.28 The System shall provide the Analyst the capability to time align detection feature maps based on signal detections. (S-6437; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.29 The System shall provide the Analyst the capability to time align detection feature maps with waveforms. (S-6438; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-136

3.2.11.1.3.30 The System shall provide the Analyst the capability to select signal detections on a detection feature map. (S-6439; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-136

3.2.11.1.4 Waveform Interaction Storage

3.2.11.2 Event Interaction

3.2.11.2.1 Event Interaction Processing

3.2.11.2.2 Event Interaction Support Interfaces

3.2.11.2.2.1 The System shall provide the System Maintainer the capability to configure when multiple Analysts are allowed to concurrently process data based on processing stage. (S-1913; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-274

3.2.11.2.3 Event Interaction User Interfaces

3.2.11.2.3.1 The System shall provide the Analyst the capability to process data without altering another Analyst's existing solution. (S-1915; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-136, SRD-274

3.2.11.2.3.2 The System shall provide the Analyst the capability to select and retrieve an event and associated waveform data from an event catalog. (S-1916; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-136, SRD-139, SRD-141

3.2.11.2.3.3 The System shall provide the Analyst the capability to add or remove an event from an event catalog. (S-1917; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-136, SRD-141

3.2.11.2.3.4 The System shall provide the Analyst the capability to view a list of events from an event catalog. (S-1918; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-141

3.2.11.2.3.5 The System shall provide the Analyst the capability to view the preferred event hypothesis for each event. (S-5957; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-136

3.2.11.2.3.6 The System shall provide the Analyst the capability to designate the preferred event hypothesis for each event. (S-1616; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-95, SRD-124, SRD-136, SRD-402

3.2.11.2.3.7 The System shall provide the Analyst the capability to analyze events in any order. (S-1919; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-128, SRD-136

3.2.11.2.3.8 The System shall provide the Analyst the capability to view any saved event hypothesis. (S-1920; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-133, SRD-136, SRD-139, SRD-140

3.2.11.2.3.9 The System shall provide the Analyst the capability to enter comments for an event hypothesis. (S-1921; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-400

3.2.11.2.3.10 The System shall provide the Analyst the capability to view comments for an event hypothesis. (S-1922; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-400

3.2.11.2.3.11 The System shall provide the Analyst the capability to provide feedback on other Analysts' work. (S-1923; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-133, SRD-136

3.2.11.2.3.12 The System shall provide the Analyst the capability to view feedback provided by an Analyst. (S-5556; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-133

3.2.11.2.3.13 The System shall notify the Analyst of feedback provided by another Analyst. (S-1924; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-133

3.2.11.2.3.14 The System shall provide the Analyst the capability to view event counts (total, regional, hydro, etc.) for a specified set of analysts over a specified period of time. (S-5958; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-133

3.2.11.2.3.15 The System shall provide the Analyst the capability to view one Analyst's location, depth, and overall accuracy statistics compared to another Analyst's results for the same event. (S-5959; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-133

3.2.11.2.3.16 The System shall provide the Analyst the capability to export performance metrics for a set of Analysts over a specified period of time. (S-5960; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-133

3.2.11.2.3.17 The System shall provide the System User the capability to view the complete history of an event. (S-1926; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-139

3.2.11.2.3.18 The System shall provide the Analyst the capability to remotely view waveform processing results from any location. (S-5669; IDC only)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-328

3.2.11.2.3.19 The System shall provide the Analyst the capability to iteratively undo/redo back to the last saved state of an event. (S-1892; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-287

3.2.11.2.3.20 The System shall provide the Analyst the capability to view effective sound speed ratios at a selected altitude for a given meteorological model. (S-6296; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124

3.2.11.2.3.21 The System shall provide the Analyst the capability to view infrasonic ray paths between a receiver and hypothesized source location when reviewing events with an infrasound phase. (S-6297; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124

3.2.11.2.3.22 The System shall provide the Analyst the capability to store new event hypotheses created during interactive processing. (S-1930; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-138

3.2.11.2.4 Event Interaction Storage

3.2.11.2.4.1 The System shall store a preferred event hypothesis for each event for each processing stage. (S-1625; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-95, SRD-189

3.2.11.2.4.2 The System shall store the processing stage during which each event hypothesis location was created. (S-1626; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-96, SRD-189, SRD-448

3.2.11.2.4.3 The System shall store the processing stage during which an event hypothesis is modified. (S-1627; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-96, SRD-189, SRD-448

3.2.11.2.4.4 The System shall store the processing stage that rejected an event. (S-1628; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-96, SRD-189, SRD-448

3.2.11.3 Hierarchical Clustering

The System uses agglomerative hierarchical clustering to compare similarity of multiple waveforms recorded by the same channel.

Agglomerative hierarchical clustering distance algorithms are: nearest neighbor, furthest neighbor, median distance, group mean distance, central distance, minimum variance, and general weighted distance.

Agglomerative hierarchical clustering threshold selection algorithms are: Mojena, intraclass variance, and cophenetic.

3.2.11.3.1 Hierarchical Clustering Processing

3.2.11.3.1.1 The System shall create agglomerative hierarchical clusters of sets of waveforms based on the maximum cross correlation coefficient of each pair of waveforms in the set. (S-1934; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-125

3.2.11.3.1.2 The System shall use the agglomerative hierarchical clustering distance algorithms while agglomerative hierarchical clustering. (S-1935; Common)

Priority: Threshold

Verification Methodology: Analysis
Requirements Trace: SRD-125

3.2.11.3.1.3 The System shall automatically choose a correlation threshold value to determine clusters when forming a dendrogram. (S-1936; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-125

3.2.11.3.2 Hierarchical Clustering Support Interfaces

3.2.11.3.3 Hierarchical Clustering User Interfaces

3.2.11.3.3.1 The System shall provide the Analyst the capability to view the results of correlation analysis in a dendrogram. (S-1938; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-125, SRD-136

3.2.11.3.3.2 The System shall provide the Analyst the capability to select the weights used by the general weighted distance clustering algorithm. (S-1939; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-125, SRD-136

3.2.11.3.3.3 The System shall provide the Analyst the capability to select the agglomerative hierarchical clustering distance algorithm to use in agglomerative hierarchical clustering. (S-1940; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-125, SRD-136

3.2.11.3.3.4 The System shall provide the Analyst the capability to select the set of waveforms to use in agglomerative hierarchical clustering. (S-1941; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-125, SRD-136

3.2.11.3.3.5 The System shall provide the Analyst the capability to select the threshold value used in hierarchical clustering. (S-1942; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-125, SRD-136

3.2.11.3.3.6 The System shall provide the Analyst the capability to select the agglomerative hierarchical clustering threshold selection algorithm to use in agglomerative hierarchical clustering. (S-1943; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-124, SRD-125, SRD-136

3.2.11.3.4 Hierarchical Clustering Storage

3.2.12 User Interface

3.2.12.1 User Interface Processing

3.2.12.1.1 The System shall synchronize the System User's displays based on user actions. (S-1946; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-126, SRD-136

3.2.12.1.2 The System shall implement user interfaces according to the User Interface Guidelines. (S-1947; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-124, SRD-136, SRD-285

3.2.12.1.3 The System shall provide a command line interface to initiate each application using specific configuration parameters. (S-1952; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-286

3.2.12.2 User Interface Support Interfaces

3.2.12.2.1 The System shall provide the System Maintainer the capability to configure the triggering event activities recorded in the Operations Log. (S-1949; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-122

3.2.12.2.2 The System shall provide the System Maintainer the capability to configure which System Users are authorized to view the Operations Log. (S-1954; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-122, SRD-160

3.2.12.2.3 The System shall provide the System Maintainer the capability to configure the criteria for failures, warnings and notifications. (S-1955; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-80, SRD-289

3.2.12.3 User Interface User Interfaces

3.2.12.3.1 The System shall provide the Analyst the capability to enable and disable automatic display synchronization for each display. (S-1957; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-126

3.2.12.3.2 The System shall provide an authorized System User the capability to view the Operations Log. (S-1958; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-122

3.2.12.3.3 The System shall provide the System User the capability to view on-line help. (S-1959; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-285

3.2.12.3.4 The System shall provide the authorized System User the capability to enter Operations Log data. (S-1960; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-122

3.2.12.3.5 The System shall provide the System User audible and visual cues denoting failures, warnings, and notifications. (S-1961; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-80, SRD-228, SRD-289

3.2.12.3.6 The System shall provide the System User the capability to review logged failures, warnings and notifications. (S-1962; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-80, SRD-229, SRD-290

3.2.12.3.7 The System shall provide the System User the capability to select which logged failures, warnings and notifications are displayed. (S-1963; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-80, SRD-229, SRD-290

3.2.12.3.8 The System shall provide the System User the capability to select the audible notification associated with failures, warning and notifications. (S-1964; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-80, SRD-290

3.2.12.3.9 The System shall provide the System User the capability to view the common error log file. (S-1965; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-228, SRD-288

3.2.12.3.10 The System shall provide the Researcher the capability to initiate system software applications without dependency on an automated processing pipeline. (S-1950; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-270

3.2.12.3.11 The System shall provide the Researcher the capability to use the command line interface. (S-1951; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-286

3.2.12.4 User Interface Storage

3.2.12.4.1 The System shall store results from all stages of data processing. (S-1967; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-189, SRD-378

3.2.12.4.2 The System shall record selected triggering event activities in the Operations Log. (S-1968; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-122

3.2.12.4.3 The System shall store the Operations Log. (S-1969; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-122

3.2.12.4.4 The System shall store failures, warnings and notifications. (S-1970; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-228

3.2.12.4.5 The System shall store errors in a common log file. (S-1971; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-228

3.2.12.4.6 The System shall provide the System User the capability to export the current view to a standard graphic format (e.g. TIFF, JPG or PNG) (S-5703; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-452

3.2.13 Geographic Information Systems

The System's data analysis includes evaluating geospatial relationships on a global scale. An interactive, graphical Geographic Information System (GIS) supports analysis by displaying information and performing spatial operations, such as measuring distance from events to geographic features, on maps of the Earth.

Data available in the GIS are:

- Event Hypothesis Data: event hypothesis location set, event hypotheses location uncertainty ellipse, and associated signal detections with great circle path indicating azimuth and slowness.
- Geographic Data: test sites, station locations, volcanoes, geology, mineral resources, mine locations, Flinn-Engdahl regions, seismicity, seismic faults, geophysical attenuation maps, blockage maps, satellite imagery, topography, political boundaries, population centers, cities, railroads, tunnels, rivers, and roads.
- Station Data: station location, associated signal detections, unassociated signal detections.

The System's geographic data can also change over time, e.g. stations are added, political boundaries change. The System tracks change history for the geographic data that the System uses.

3.2.13.1 GIS Processing

3.2.13.1.1 The System shall generate graphical images of the results of spatial processing of geospatial data. (S-1974; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-154

3.2.13.1.2 The System shall generate tabular listings of the results of spatial processing of geospatial data, e.g. event hypothesis data selected by spatial processing with geographic information. (S-1975; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-154, SRD-156

3.2.13.1.3 The System shall determine whether an event hypothesis location is within an active geographic region. (S-1976; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-98, SRD-144, SRD-152, SRD-156

3.2.13.1.4 The System shall determine whether an event hypothesis uncertainty bound intersects an active geographic region. (S-1977; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-98, SRD-152, SRD-156

3.2.13.1.5 The System shall determine whether an event hypothesis location is within an active geographic region for a particular time. (S-1978; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-98, SRD-152, SRD-156

3.2.13.1.6 The System shall determine whether an event hypothesis location uncertainty bound intersects an active geographic region for a particular time. (S-1979; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-98, SRD-152, SRD-156

3.2.13.2 GIS Support Interfaces

3.2.13.2.1 The System shall provide the System Maintainer the capability to configure a geographic region. (S-1981; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-144, SRD-151

3.2.13.2.2 The System shall provide the System Maintainer the capability to configure an active time range of a geographic region. (S-1983; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-144, SRD-151

3.2.13.3 GIS User Interfaces

3.2.13.3.1 The System shall provide the System User the capability to view event hypothesis data on an interactive map. (S-1985; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-149, SRD-150

3.2.13.3.2 The System shall provide the Authorized External User the capability to view event hypothesis data on an interactive map. (S-5986; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-149, SRD-150

3.2.13.3.3 The System shall provide the System User the capability to view associated and unassociated signal detections on an interactive map. (S-1986; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-149, SRD-150

3.2.13.3.4 The System shall provide the System User the capability to view station data on an interactive map. (S-1987; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-149, SRD-150, SRD-398

3.2.13.3.5 The System shall provide the Authorized External User to view station data on an interactive map. (S-5988; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-149, SRD-150, SRD-398

3.2.13.3.6 The System shall provide the System User the capability to view geographic data on an interactive map. (S-1988; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-153

3.2.13.3.7 The System shall provide the Authorized External User the capability to view geographic data on an interactive map. (S-5989; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-153

3.2.13.3.8 The System shall provide the System User the capability to view active geographic region boundaries on an interactive map. (S-1989; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-151

3.2.13.3.9 The System shall provide the Authorized External User the capability to view active geographic region boundaries on an interactive map. (S-5990; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-151

3.2.13.3.10 The System shall provide the System User the capability to view inactive geographic region boundaries on an interactive map. (S-5603; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-151

3.2.13.3.11 The System shall provide the System User the capability to simultaneously view event hypothesis locations and active geographic region boundaries on an interactive map. (S-1990; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-151

3.2.13.3.12 The System shall provide the Authorized External User the capability to simultaneously view event hypothesis locations and active geographic region boundaries on an interactive map. (S-5993; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-151

3.2.13.3.13 The System shall provide the System User the capability to simultaneously view event hypothesis locations and inactive geographic region boundaries on an interactive map. (S-5604; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-151

3.2.13.3.14 The System shall provide the Authorized External User the capability to simultaneously view event hypothesis locations and inactive geographic region boundaries on an interactive map. (S-5994; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-151

3.2.13.3.15 The System shall provide the System User the capability to view on an interactive map whether an event hypothesis location is within active geographic regions. (S-1991; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-98, SRD-124, SRD-136, SRD-152

3.2.13.3.16 The System shall provide the Authorized External User the capability to view on an interactive map whether an event hypothesis location is within active geographic regions. (S-5992; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-98, SRD-124, SRD-136, SRD-152

3.2.13.3.17 The System shall provide the System User the capability to view on an interactive map whether an event hypothesis location is within an active geographic region for a user specified time. (S-5997; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-98, SRD-124, SRD-136, SRD-152

3.2.13.3.18 The System shall provide the System User the capability to view on an interactive map whether an event hypothesis location uncertainty bound intersects an active geographic region for a user specified time. (S-1993; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-98, SRD-124, SRD-136, SRD-152

3.2.13.3.19 The System shall provide the System User the capability to specify the time associated with whether an event hypothesis location or event hypothesis location uncertainty is within an active geographic region. (S-2597; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-98, SRD-124, SRD-136, SRD-152

3.2.13.3.20 The System shall provide the System User the capability to search via GIS for the percentage of an event hypothesis uncertainty ellipse that is within an active geographic region. (S-1995; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-156

3.2.13.3.21 The System shall provide the System User the capability to access geospatial data. (S-1996; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.13.3.22 The System shall provide the Authorized External User the capability to access geospatial data. (S-6000; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136

3.2.13.3.23 The System shall provide the System User the capability to determine the spatial relationships of geospatial data. (S-1998; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-156

3.2.13.3.24 The System shall provide the System User the capability to view geographic data on a two-dimensional projection and on a three-dimensional virtual globe. (S-5666; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-451

3.2.13.3.25 The System shall provide the Authorized External User the capability to view geographic data on a two-dimensional projection and on a three-dimensional virtual globe. (S-6002; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-451

3.2.13.3.26 The System shall provide the System User the capability to view tabular listings of the results of spatial processing of geospatial data. (S-1999; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-136, SRD-154, SRD-156

3.2.13.3.27 The System shall provide the System User the capability to view graphical images of the results of spatial processing of geospatial data. (S-2000; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-136, SRD-154, SRD-156

3.2.13.3.28 The System shall provide the Authorized External User the capability to select geographical data on any interactive map (such as events and stations) and export them to a standardized format (e.g. KML/KMZ). (S-6430; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-453

3.2.13.3.29 The System shall provide the System User the capability to select geographical data on any interactive map (such as events and stations) and export them to a standard geographic format (e.g. KML/KMZ). (S-5702; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-453

3.2.13.4 GIS Storage

3.2.13.4.1 The System shall provide the Analyst the capability to save geospatial data. (S-1997; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-136, SRD-154

3.2.13.4.2 The System shall export geographic data in KML/KMZ format. (S-6431; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-453

3.2.14 Event Bulletins and Reports

Event bulletins are one of the primary system reports. Event bulletins contain information on locations of event hypotheses (latitude, longitude, depth, time and magnitude) and their associated signal detections (station, phase label, onset time, and signal amplitude). Event bulletins can be created by any combination of the following criteria: time, location, magnitude, or source type. Data and reports applies to seismic, infrasound, hydroacoustic and radionuclide stations.

3.2.14.1 Event Bulletins and Reports Processing

3.2.14.1.1 The System shall apply user-specified processing to existing data and products to create custom reports. (S-5763; IDC only)

Priority: Extensibility

Verification Methodology: Test

Requirements Trace: SRD-508

3.2.14.1.2 The System shall publish events in the Standard Event Lists (SEL1, SEL2, SEL3) based on configuration. (S-6552; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-613

3.2.14.2 Event Bulletins and Reports Support Interfaces

3.2.14.2.1 The System shall provide the System Maintainer the capability to configure a maximum data size request limit threshold per type of report. (S-5771; IDC only)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-511

3.2.14.2.2 The System shall provide the System Maintainer the capability to configure the criteria used to publish bulletins. (S-6553; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-613

3.2.14.3 Event Bulletins and Reports User Interfaces

3.2.14.3.1 The System shall provide the System User the capability to access the System as an Authorized External User. (S-6428; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-163, SRD-482, SRD-484, SRD-505, SRD-621

3.2.14.3.2 The System shall provide the System User the capability to access third-party event bulletins in the same way they access event bulletins produced by the System. (S-2019; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-163

3.2.14.3.3 The System shall provide the Authorized External User the capability to access third-party event bulletins in the same way they access event bulletins produced by the System. (S-6456; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-163

3.2.14.3.4 The System shall provide the Authorized External User the capability to view a list of events created in any processing stage (automated or interactive). (S-2020; Common)

Priority: Threshold

Verification Methodology: Demonstration
Requirements Trace: SRD-165

3.2.14.3.5 The System shall provide the System User the capability to view a list of events containing the events created in any processing stage (automatic or interactive) that forms events. (S-6432; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-165

3.2.14.3.6 The System shall provide the Authorized External User the capability to select user-specified processing of data and products to create custom reports. (S-5764; IDC only)

Priority: Extensibility
Verification Methodology: Demonstration
Requirements Trace: SRD-508
Note: the Authorized External User can provide a new type of processing to be used when creating the report (e.g. a new screening algorithm).

3.2.14.3.7 The System shall provide the Authorized External User the capability to access reports based on their roles and privileges. (S-2006; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-160, SRD-163, SRD-482

3.2.14.3.8 The System shall provide the Authorized External User the capability to access reports via a web server. (S-2007; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-163, SRD-621

3.2.14.3.9 The System shall provide the Authorized External User the capability to view reports. (S-5892; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-621

3.2.14.3.10 The System shall provide the Authorized External User the capability to view station SOH via a web server. (S-2008; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-621

3.2.14.3.11 The System shall provide the System User the capability to view reports. (S-5893; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-621

3.2.14.3.12 The System shall provide the Authorized External User the capability to access third-party reports. (S-2012; Common)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-163

3.2.14.3.13 The System shall provide the Authorized External User the capability to view third-party event bulletins. (S-6429; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-163

3.2.14.3.14 The System shall provide the Authorized External User the capability to access reports via a GIS. (S-5894; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-484

3.2.14.3.15 The System shall provide the Authorized External User the capability to access reports via tabular format. (S-5962; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-621

3.2.14.3.16 The System shall provide the Authorized External User the capability to create an event bulletin from the set of released events. (S-2016; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-160

3.2.14.3.17 The System shall provide the Authorized External User the capability to view an event from any processing stage that has been approved for release. (S-6433; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-160

3.2.14.3.18 The System shall provide the Authorized External User the capability to create event bulletins based on any combination of geographic region, time interval, depth, magnitude interval, source type, stations, latitude, and longitude. (S-2017; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-165

3.2.14.3.19 The System shall provide the Authorized External User the capability to request event bulletins in SeisComP3XML format. (S-6301; IDC only)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-611

3.2.14.3.20 The System shall provide the Authorized External User the capability to subscribe to reports and waveform data. (S-5930; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-507

3.2.14.3.21 The System shall provide the Authorized External User the capability to subscribe to radionuclide data. (S-6384; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-485

3.2.14.3.22 The System shall provide the Authorized External User the capability to request alphanumeric data in the CSS 3.0 format. (S-1249; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-505, SRD-616

3.2.14.3.23 The System shall provide the Authorized External User the capability to view station data acquisition statistics via a web site. (S-1229; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-25

3.2.14.3.24 The System shall provide the System User the capability to compare two event bulletins for signal detection characteristics of two event hypotheses. (S-2111; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-247

3.2.14.3.25 The System shall provide the System User the capability to compare two event bulletins for the characteristics of two event hypotheses. (S-2112; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-247

3.2.14.3.26 The System shall provide the System User the capability to perform statistical comparisons between two event bulletins. (S-2113; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-247

3.2.14.3.27 The System shall provide the Fusion and Review Officer the capability to create an event report. (S-6457; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-165

3.2.14.3.28 The System shall provide the Fusion and Review Officer the capability to create a State Requested Methods Report. (S-6458; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-165

3.2.14.3.29 The System shall provide the Fusion and Review Officer the capability to save an event to the Updated Event Bulletin. (S-6459; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-165

3.2.14.3.30 The System shall provide the Fusion and Review Officer the capability to distribute a State Requested Methods Report. (S-6460; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-165

3.2.14.3.31 The System shall provide the Authorized External User the capability to view station calibration results. (S-6434; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-493

3.2.14.3.32 The System shall provide the Authorized External User the capability to view the authentication status of waveform data. (S-5964; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-25

3.2.14.4 Event Bulletins and Reports Storage

3.2.14.4.1 The System shall store third-party bulletin data in the System data format. (S-2024; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-163, SRD-174

3.2.15 Data Management

The System stores waveforms, configuration parameters, and processing results.

3.2.15.1 System Configuration

3.2.15.1.1 System Configuration Processing

3.2.15.1.1.1 The System shall maintain a history of the system configurations. (S-5736; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-651

3.2.15.1.2 System Configuration Support Interfaces

3.2.15.1.2.1 The System shall provide the System Maintainer the capability to install software updates. (S-2275; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-168, SRD-216, SRD-370

3.2.15.1.2.2 The System shall provide the System Maintainer the capability to install software updates on the Backup without affecting the Primary. (S-6463; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-168

3.2.15.1.2.3 The System shall provide the System Maintainer the capability to restore the configuration that was valid at a specific time in the past. (S-5737; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-651

3.2.15.1.3 System Configuration User Interfaces

3.2.15.1.4 System Configuration Storage

3.2.15.2 Common Object Interface

3.2.15.2.1 Common Object Interface Processing

3.2.15.2.1.1 The System shall use a common object interface (data model and methods) for data. (S-2028; Common)

Priority: Objective / Priority 1
Verification Methodology: Analysis
Requirements Trace: SRD-268

3.2.15.2.2 Common Object Interface Support Interfaces

3.2.15.2.3 Common Object Interface User Interfaces

3.2.15.2.3.1 The System shall provide the Researcher the capability to access data through a common object interface. (S-2030; Common)

Priority: Objective / Priority 1
Verification Methodology: Demonstration
Requirements Trace: SRD-268

3.2.15.2.3.2 The System shall provide the Researcher the capability to access the database through a read-only ANSI/ISO standard SQL interface. (S-2031; IDC only)

Priority: Threshold
Verification Methodology: Demonstration
Requirements Trace: SRD-301

3.2.15.2.4 Common Object Interface Storage

3.2.15.3 Processing Parameters

The System provides an infrastructure linking processing parameter and recipe information with each event hypothesis, event hypothesis location, and signal detection created and stored by the System. Automatic and interactive processing applications use this infrastructure to set default values for processing parameters and recipes, and to track changes in processing parameters and recipes.

This infrastructure insures processing results can be recreated from one processing stage to the next (e.g., for both interactive and automatic fk analysis, use the same stations (spatial sampling), frequency-band (frequency sampling), lead and lag (temporal sampling), and Waveform QC Masks). Processing parameters are dynamic values preserved at each processing stage rather than static values used by all processing stages. When default values can be overridden when computing a processing result, the overridden values are linked to that processing result.

Defining/non-defining state behavior refers to how measurements are used in an event processing function. A measurement that is associated to a particular calculation is considered "defining" if it is enabled as input to that calculation; otherwise it is considered "non-defining" for that calculation. System configuration and precedence rules determine the default defining state by geographic region, time of year, time of day, network, station, channel, phase, observable type, and processing function. System processing may adjust the defining state based on data quality and measurement residual. Analysts may adjust the defining state as desired during interactive processing.

3.2.15.3.1 Processing Parameters Processing

3.2.15.3.1.1 The System shall use configured default defining/non-defining state settings and precedence rules to determine the initial defining/non-defining state for each parameter. (S-2036; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-110, SRD-291

3.2.15.3.2 Processing Parameters Support Interfaces

3.2.15.3.2.1 The System shall provide the System Maintainer the capability to configure the default defining/non-defining state by geographic region, time of year, network, station, channel, phase, parameter type, and processing function. (S-2038; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-110, SRD-291

3.2.15.3.3 Processing Parameters User Interfaces

3.2.15.3.4 Processing Parameters Storage

3.2.15.3.4.1 The System shall store automatic and interactive processing parameters in the database. (S-2042; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189

3.2.15.3.4.2 The System shall store the relation of processing results to processing parameters in the database. (S-2044; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189

3.2.15.4 Database Backup

3.2.15.4.1 Database Backup Processing

3.2.15.4.1.1 The System shall backup all information necessary to reconstruct the entire system including software and data. (S-2048; Common)

Priority: Threshold

Verification Methodology: Inspection

Requirements Trace: SRD-168

3.2.15.4.2 Database Backup Support Interfaces

3.2.15.4.2.1 The System shall provide the System Maintainer the capability to recover the entire system including software and data. (S-2049; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-168

3.2.15.4.3 Database Backup User Interfaces

3.2.15.4.4 Database Backup Storage

3.2.15.4.4.1 The System shall store backups off-line. (S-2056; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-168

3.2.15.4.4.2 The System shall store backups off-site. (S-2057; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-168

3.2.15.5 Database Synchronization

3.2.15.5.1 Database Synchronization Processing

3.2.15.5.1.1 The System shall synchronize bulletin data from the data acquisition system of the Primary to the Data Acquisition Partition of the Backup in near real-time. (S-2060; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-472

3.2.15.5.1.2 The System shall synchronize databases from the Data Processing Partition of the Primary to the Data Processing Partition of the Backup in near real-time. (S-2061; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-472

3.2.15.5.1.3 The System shall synchronize waveform data from the Data Acquisition Partition of the Primary to the Data Acquisition Partition of the Backup in near real-time. (S-2062; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-472

3.2.15.5.1.4 The System shall synchronize waveform data from the Data Processing Partition of the Primary to the Data Processing Partition of the Backup in near real-time. (S-2063; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-472

3.2.15.5.1.5 The System shall synchronize meteorological data from the Data Acquisition Partition of the Primary to the Data Acquisition Partition of the Backup in near real-time. (S-6472; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-472

3.2.15.5.1.6 The System shall confirm 100% of data transfer integrity prior to deleting data from source storage. (S-2067; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-187

3.2.15.5.1.7 The System Data Acquisition Partition shall import data from high-density media. (S-2068; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-184, SRD-300

3.2.15.5.1.8 The System Data Processing Partition shall import data from high-density media. (S-2069; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-184, SRD-300

3.2.15.5.2 Database Synchronization Support Interfaces

3.2.15.5.2.1 The System shall provide the System Maintainer the capability for importing data. (S-2072; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-300

3.2.15.5.3 Database Synchronization User Interfaces

3.2.15.5.3.1 The System shall provide the System User the capability to export selected data. (S-2071; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-300

3.2.15.5.4 Database Synchronization Storage

3.2.16 Performance Monitoring

Performance Monitoring involves the calculation, display and archiving of key indicators for each component of the System data processing system. The key indicators are statistically derived values providing empirical validation for theoretical forecast models and are the inputs to system capability reporting. Key indicator archiving has a threefold mission of maintaining appropriate resolution, providing a baseline to gauge the impact of changes to the System, and establishing compatibility with forecast models. Users view Performance Monitoring key indicators, perform trend analysis, and receive automated notifications when key indicators reach critical status.

3.2.16.1 Mission Performance Monitoring

3.2.16.1.1 Mission Performance Monitoring Processing

3.2.16.1.1.1 The System shall compute station ambient noise probability density functions. (S-2076; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-238

3.2.16.1.1.2 The System shall compute maximum likelihood empirical station magnitude detection thresholds by geographic region based on the historic event bulletin. (S-2077; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-242

3.2.16.1.1.3 The System shall compute station processing statistics. (S-2078; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-240

3.2.16.1.1.4 The System shall compute uncertainties associated with empirical station magnitude detection thresholds for a geographic region. (S-2079; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-242

3.2.16.1.1.5 The System shall estimate a station's empirical magnitude detection threshold for aseismic regions using historic event hypotheses within a configurable distance range from that station. (S-2080; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-242

3.2.16.1.1.6 The System shall calculate event hypothesis statistics for a geographic region and time period. (S-2081; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-243

3.2.16.1.2 Mission Performance Monitoring Support Interfaces

3.2.16.1.3 Mission Performance Monitoring User Interfaces

3.2.16.1.3.1 The System shall provide the System User the capability to view real-time estimates of event detection probability at a specified magnitude based on empirical and model based parameters. (S-2091; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-244

3.2.16.1.3.2 The System shall provide the System User the capability to view real-time estimates of event location uncertainty based on empirical and model based parameters. (S-2092; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-244

3.2.16.1.3.3 The System shall provide the Performance Monitor the capability to select thresholds for station processing statistics. (S-2084; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-240

3.2.16.1.3.4 The System shall provide the Performance Monitor the capability to select the time interval used for computing station processing statistics. (S-2085; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-240

3.2.16.1.3.5 The System shall provide the Performance Monitor the capability to select the computation of station processing statistics based on geographic region. (S-2086; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-240

3.2.16.1.3.6 The System shall provide the Performance Monitor the capability to select the geographic regions the System uses to compute empirical station magnitude detection thresholds. (S-2087; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-242

3.2.16.1.3.7 The System shall provide the Performance Monitor the capability to select by geographic region the distance range the System uses to compute the station magnitude detection thresholds for aseismic regions. (S-2088; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-242

3.2.16.1.3.8 The System shall provide the Performance Monitor the capability to select the temporal range used to compute the station magnitude detection threshold for a specific geographic region (S-2089; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-242

3.2.16.1.3.9 The System shall provide the Performance Monitor the capability to select the models to be used for network capability simulation. (S-2094; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-244

3.2.16.1.3.10 The System shall provide the Performance Monitor the capability to select the parameters to be used for network capability simulation. (S-2095; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-244

3.2.16.1.3.11 The System shall provide the Performance Monitor the capability to select the network configuration to be used for network capability simulation. (S-2096; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-244

3.2.16.1.3.12 The System shall provide the Performance Monitor the capability to view tables of station processing statistics. (S-2105; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-240

3.2.16.1.3.13 The System shall provide the System User the capability to graphically view station processing statistics. (S-2106; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-240

3.2.16.1.3.14 The System shall provide the Performance Monitor the capability to simultaneously view station processing statistics, the processing parameters used to compute those statistics, and the dates and times of changes to those processing parameters. (S-2107; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-240

3.2.16.1.3.15 The System shall provide the Performance Monitor the capability to compare a current station statistic with other (up to 5) selectable time periods concurrently. (S-2109; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-241

3.2.16.1.3.16 The System shall provide the System User the capability to view station magnitude detection thresholds computed for a geographic region. (S-2110; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-242

3.2.16.1.3.17 The System shall provide the Authorized External User the capability to view station magnitude detection thresholds computed for a geographic region. (S-6455; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-242

3.2.16.1.3.18 The System shall provide the System User the capability to view event hypothesis statistics for a user specified geographic region for a specified time period. (S-2114; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-243

3.2.16.1.3.19 The System shall notify the Performance Monitor when a station processing statistic varies outside of a configurable range. (S-2115; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-240

3.2.16.1.4 Mission Performance Monitoring Storage

3.2.16.1.4.1 The System shall store ambient noise probability density functions. (S-2117; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189

3.2.16.1.4.2 The System shall store station processing statistics. (S-2118; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-240

3.2.16.1.4.3 The System shall store station magnitude detection thresholds for a geographic region. (S-2119; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-242

3.2.16.1.4.4 The System shall store uncertainties associated with station magnitude detection thresholds for a geographic region. (S-2120; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-242

3.2.16.2 Station State-of-Health

Station health is a combination of key indicators that include the ability to identify which components of a station are functioning, the reason for malfunctioning components, and the timing of routine/emergency maintenance.

3.2.16.2.1 Station State-of-Health Processing

3.2.16.2.1.1 The System shall update system State-of-Health displays with newly acquired data within 1 minute of acquisition. (S-2123; Common)

Priority: Objective / Priority 2

Verification Methodology: Test

Requirements Trace: SRD-130

3.2.16.2.1.2 The System shall compute latency measurements of waveform data intervals between station waveform data recording and waveform data arrival at the System. (S-2124; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-232

3.2.16.2.1.3 The System shall continuously compute station quality metrics to monitor station performance. (S-6481; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-408

3.2.16.2.2 Station State-of-Health Support Interfaces

3.2.16.2.2.1 The System shall provide the System Maintainer the capability to configure the parameters the System uses to calculate station ambient noise probability density functions. (S-2083; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-238

3.2.16.2.2.2 The System shall provide the System Maintainer the capability to configure how often the System computes station quality metrics. (S-6482; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-89, SRD-408

3.2.16.2.2.3 The System shall provide the System Maintainer the capability to configure for which raw channels and derived channels the System computes the station quality metric. (S-6483; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-89, SRD-408

3.2.16.2.3 Station State-of-Health User Interfaces

3.2.16.2.3.1 The System shall provide the System User the capability to view all station State-of Health status values. (S-2127; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-120, SRD-136

3.2.16.2.3.2 The System shall provide the System User the capability to view all network State-of Health status values. (S-2128; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-120, SRD-136

3.2.16.2.3.3 The System shall provide the Analyst the capability to view waveform data availability at a user specified time. (S-2129; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-233, SRD-617

3.2.16.2.3.4 The System shall provide the System User the capability to view latency measurements for waveform data intervals. (S-2130; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-124, SRD-136, SRD-232

3.2.16.2.3.5 The System shall provide the System User the capability to view station ambient noise probability density functions. (S-2097; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-136, SRD-238

3.2.16.2.3.6 The System shall provide the Authorized External User the capability to view station ambient noise probability density functions. (S-5963; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-238

3.2.16.2.3.7 The System shall provide the System User the capability to compare current station ambient noise probability density functions with the station's ambient noise probability density functions from other (up to 5) selectable time periods concurrently. (S-2098; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-136, SRD-239

3.2.16.2.3.8 The System shall provide the System User the capability to compare current station spectrograms with the station's spectrograms from other (up to 5) selectable time periods concurrently. (S-5723; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-239

3.2.16.2.3.9 The System shall provide the System User the capability to compare current station power spectral density with the station's power spectral density from other (up to 5) selectable time periods concurrently. (S-5724; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-239

3.2.16.2.3.10 The System shall provide the System User the capability to select the parameters the System uses to calculate station ambient noise probability density functions. (S-5718; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-238

3.2.16.2.3.11 The System shall provide the System User the capability to view station calibration results. (S-5674; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-493

3.2.16.2.4 Station State-of-Health Storage

3.2.16.2.4.1 The System shall store raw waveform data availabilities for specific points in the processing history. (S-2134; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-172, SRD-189, SRD-233, SRD-617

3.2.16.2.4.2 The System shall store latency measurements for waveform data intervals. (S-2135; Common)

Priority: Threshold

Verification Methodology: Test

3.2.16.3 System Performance Monitoring

General system State-of-Health captures many system characteristics impacting performance and reliability. These values are sampled, captured, and reported using operating system tools. System State-of-Health status values are:

- Memory usage
- Uptime
- Network interface average receiving rate
- Network interface peak receiving rate
- Network interface average transmitting rate
- Network interface peak transmitting rate
- Available disk space
- Used disk space
- Compute node response state
- Application program run status
 - Application program load times
 - Orphaned application processes
 - Current level of backlogged waveform data waiting for pipeline processing

Storage health provides key indicators for determining stored data integrity and disk consumption rate. Key indicators are:

- Critical storage limit
- Load usage failure level, and usage rates
- Daily number of new core files per application per day
- Summary of files in /data/opspipe/log/error and messages in /var/adm/

Critical failures include:

1. hardware failures
2. database crashes, and
3. network failures that prevent event detection.

Non-critical failures include:

1. processes that crash but are auto-restarted successfully without loss of data or significant impact to processes, and
2. crashes of components such as GUIs or monitor applications.

Analyst Application Usage

Analyst Applications are software tools available to Analysts and specific subsets of activities, such as the primary operations, provided by those tools. Analyst Applications contain instrumentation to measure usage and statistical displays summarize Analyst Application usage. Analyst Application usage measurements include:

- elapsed time to invoke an application,
- elapsed time spent processing within an application,
- application invocation counts per Analyst, and
- application time of use per Analyst.

Analyst Application usage statistics include average, minimum, maximum, and variance of Analyst Application usage measurements over configurable time intervals.

3.2.16.3.1 System Performance Monitoring Processing

3.2.16.3.1.1 The System shall monitor, detect, log, and characterize software and hardware failures of all systems and networks. (S-2138; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-227

3.2.16.3.1.2 The System shall report failures, warnings and notifications using a common messaging infrastructure. (S-2139; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-228, SRD-289

3.2.16.3.1.3 The System shall measure Analyst Application usage. (S-2140; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-249

3.2.16.3.2 System Performance Monitoring Support Interfaces

3.2.16.3.2.1 The System shall provide the System User the capability to view Analyst Application usage statistics. (S-2146; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-249

3.2.16.3.3 System Performance Monitoring User Interfaces

3.2.16.3.3.1 The System shall provide the System User the capability to view the state of all system processes in near real time. (S-2143; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-226, SRD-288

3.2.16.3.3.2 The System shall provide the System User the capability to view all system State-of-Health status values. (S-2144; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-120, SRD-225, SRD-226

3.2.16.3.3.3 The System shall provide the System User the capability to monitor the State-of-Health of critical hardware components of the Primary from the Backup. (S-2147; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-225, SRD-360

3.2.16.3.3.4 The System shall provide the System User the capability to monitor the State-of-Health of critical hardware components of the Primary from the Primary. (S-2148; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-225

3.2.16.3.3.5 The System shall provide the System User the capability to monitor the State-of-Health of critical software components of the Primary from the Backup. (S-2149; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-226, SRD-360

3.2.16.3.3.6 The System shall provide the System User the capability to monitor the State-of-Health of critical software components of the Primary from the Primary. (S-2150; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-226

3.2.16.3.3.7 The System shall provide the System User the capability to monitor the State-of-

Health of critical hardware components of the Backup from the Primary. (S-2151; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-225, SRD-360

3.2.16.3.3.8 The System shall provide the System User the capability to monitor the State-of-Health of critical hardware components of the Backup from the Backup. (S-2152; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-225

3.2.16.3.3.9 The System shall provide the System User the capability to monitor the State-of-Health of critical software components of the Backup from the Primary. (S-2153; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-226, SRD-360

3.2.16.3.3.10 The System shall provide the System User the capability to monitor the State-of-Health of critical software components of the Backup from the Backup. (S-2154; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-226

3.2.16.3.4 System Performance Monitoring Storage

3.2.16.3.4.1 The System shall store all available system State-of-Health status values. (S-2156; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-120, SRD-225

3.2.16.3.4.2 The System shall store Analyst Application usage measurements. (S-2157; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-189, SRD-249

3.2.16.4 Geophysical Performance Tuning

The System will provide a set of software tools to support tuning and evaluation of geophysical performance. These tools will allow a user to rerun decision algorithms (including detection and association) with a range of values for a single input parameter. All other parameters will be fixed to view the influence of the single parameter on the decision. In addition, system will allow the user to export time-series signals generated during signal processing. Signal processing may contain several transformations (including filtering, beaming, STA/LTA, etc...). The System should allow the user to export after each transformation.

3.2.16.4.1 Geophysical Performance Tuning Processing

3.2.16.4.2 Geophysical Performance Tuning Support Interfaces

3.2.16.4.3 Geophysical Performance Tuning User Interfaces

3.2.16.4.3.1 The System shall provide the Researcher the capability to store time-series signals generated by each transformation applied during system signal processing for evaluation by third-party tools. (S-2159; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-245

3.2.16.4.3.2 The System shall provide the Researcher the capability to view a detection algorithm's change in performance over a range of values for parameters of the respective detection algorithm. (S-2160; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-245

3.2.16.4.3.3 The System shall provide the Researcher the capability to view change in performance for event hypothesis formation over a range of values for parameters of the respective event hypothesis formation algorithm. (S-2161; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-245

3.2.16.4.4 Geophysical Performance Tuning Storage

3.2.17 Timeliness and System Loading

System performance refers to data processing timeliness and system loading requirements. Projecting future growth, the interactive data processing software needs to be designed with a possible 2,000 events per day.

The design of interactive applications should take into account the current loads on the users as well as changes in the future to ensure the tools are capable of supporting the users in both normal and swarm conditions. These requirements impact not only the memory and CPU loads of the tools but also the presentation of the data to the users. This may include getting data to the user quickly, providing the "next step" to the user automatically, or ensuring communication between multiple windows/applications in both the current user's session as well as other users.

3.2.17.1 Timeliness and System Loading Processing

3.2.17.1.1 The System shall access requested waveform data within one (1) minute of receipt by the Data Processing Partition. (S-2164; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-261

3.2.17.1.2 The System shall generate virtual origin beams for a specified location for a time interval up to 2 hours and an array station up to 20 channels in less than 1 second. (S-2165; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-262

3.2.17.1.3 The System shall automatically process late-arriving waveform data within one (1) minute of receipt by the Data Processing Partition. (S-2166; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-265

3.2.17.1.4 The System shall read a 6 hour or less time block of 40Hz waveform data within the Operational Processing Time Period with a maximum 5 second latency. (Goal: 1 second.) (S-2169; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-185

3.2.17.1.5 The System shall read a 6 hour or less time block of processing results within the Operational Processing Time Period with a maximum 5 second latency. (Goal: 1 second.) (S-5708; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-185

3.2.17.1.6 The System shall write a 6 hour or less time block of 40Hz waveform data within the Operational Processing Time Period with a maximum 5 second latency. (Goal: 1 second.) (S-2167; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-185

3.2.17.1.7 The System shall read a 6 hour or less time block of processing results outside the Operational Processing Time Period with a maximum 10 second latency. (Goal: 2 seconds.) (S-5712; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-186

3.2.17.1.8 The System shall write a 6 hour or less time block of processing results within the Operational Processing Time Period with a maximum 5 second latency. (Goal: 1 second.) (S-5709; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-185

3.2.17.1.9 The System shall write a 6 hour or less time block of processing results from outside the Operational Processing Time Period with a maximum 10 second latency. (Goal: 2 seconds.) (S-5713; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-186

3.2.17.1.10 The System shall read a 6 hour or less time block of 40Hz waveform data outside the Operational Processing Time Period with a maximum 10 second latency. (Goal: 2 seconds.) (S-2168; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-186

3.2.17.1.11 The System shall write a 6 hour or less time block of 40Hz waveform data outside the Operational Processing Time Period with a maximum 10 second latency. (Goal: 2 seconds.) (S-2170; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-186

3.2.17.1.12 The System shall prioritize the processing of real time data over the processing of late arriving data. (S-2171; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-277

3.2.17.1.13 The System shall automatically initiate data processing within 5 minutes of data acquisition on the Data Processing Partition. (S-2172; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-255

3.2.17.1.14 The System shall generate automated measurements in less than three (3) seconds for an event hypothesis with up to 100 associated signal detections. (S-2174; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-263

3.2.17.1.15 The System shall process up to 2000 seismic event hypotheses per day without disruption of the Data Processing Partition. (S-2175; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-253, SRD-280

3.2.17.1.16 The System shall provide a team of 10 concurrent analysts the capability to process up to 2000 seismic event hypotheses per 24 hour day. (S-2176; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-136, SRD-253

3.2.17.1.17 The System shall produce an automated event bulletin in near real-time during normal conditions without disrupting operations. (S-2177; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-255

3.2.17.1.18 The System shall produce an automated event bulletin in near real-time during swarm conditions without disrupting operations. (S-2178; Common)

Priority: Threshold

Verification Methodology: Test
Requirements Trace: SRD-255

3.2.17.2 Timeliness and System Loading Support Interfaces

3.2.17.3 Timeliness and System Loading User Interfaces

3.2.17.4 Timeliness and System Loading Storage

3.2.18 Security

3.2.18.1 Security Processing

3.2.18.1.1 The System shall provide user identification and authentication for access control. (S-2183; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-319

3.2.18.1.2 The System shall provide separate access control for users accessing the system internally and externally. (S-5697; Common)

Priority: Threshold
Verification Methodology: Analysis
Requirements Trace: SRD-160

3.2.18.1.3 The System shall uniquely record the users logged on to the System. (S-2184; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-324

3.2.18.1.4 The System shall log all user login attempts and logouts. (S-2186; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-316

3.2.18.1.5 The System shall encrypt user passwords when stored on the System. (S-2187; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-316

3.2.18.1.6 The System shall lock the user account upon a configurable number of successive authentication failures involving an incorrect password. (S-2188; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-316

3.2.18.1.7 The System shall reject authentication requests involving passwords over a configurable number of days old. (S-2189; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-316

3.2.18.1.8 The System shall log all requests to initiate and terminate system processing. (S-2190; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-318

3.2.18.1.9 The System shall reject all processing requests from unauthorized Users. (S-2191; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-317, SRD-318

3.2.18.1.10 The System shall prevent unauthorized access. (S-2192; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-320

3.2.18.1.11 The System shall record the date and time of each auditable security event. (S-2196; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-325

3.2.18.1.12 The System shall record the type of each auditable security event. (S-2197; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-325

3.2.18.1.13 The System shall record the success or failure of each auditable security event. (S-2198; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-325

3.2.18.1.14 The System shall record the name of the object that was introduced, accessed, modified or deleted as part of each auditable security event. (S-2199; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-325

3.2.18.1.15 The System shall monitor security logs and notify the System Maintainer of security events. (S-2208; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-324

3.2.18.1.16 The System shall provide user identification and authentication through the CTBTO “single sign on”. (S-5687; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-483

3.2.18.2 Security Support Interfaces

3.2.18.2.1 The System shall provide the System Maintainer the capability to review security logs. (S-2204; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-324

3.2.18.2.2 The System shall provide the System Maintainer the capability to view the authorized users and when each last accessed the System. (S-2205; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-316

3.2.18.2.3 The System shall provide the System Maintainer the capability to configure which user accounts are locked or unlocked. (S-2206; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-316

3.2.18.2.4 The System shall provide the System Maintainer the capability to configure temporary user passwords. (S-2207; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-316

3.2.18.2.5 The System shall provide the System Maintainer the capability to configure which user accounts are available (i.e. add and delete user accounts). (S-2185; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-316

3.2.18.2.6 The System shall provide the System Maintainer the capability to configure access control for System Users by roles and privileges. (S-5695; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-160, SRD-483

3.2.18.2.7 The System shall provide the System Maintainer the capability to configure the access control for Authorized External Users by roles and privileges. (S-5696; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-160

3.2.18.3 Security User Interfaces

3.2.18.3.1 The System shall provide the System User the capability to access the System using their CTBTO “single sign on” credentials. (S-5686; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-483

3.2.18.4 Security Storage

3.2.19 Testing

3.2.19.1 Testing Processing

3.2.19.1.1 The Development Subsystem shall replay waveform data using the data's original acquisition sequencing and latencies. (S-2214; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-299, SRD-414

3.2.19.1.2 The Development Subsystem shall replay waveform data faster than real time. (S-5729; Common)

Priority: Extensibility

Verification Methodology: Test

Requirements Trace: SRD-414

3.2.19.1.3 The Development Subsystem shall replay Analyst actions using the same waveform and event data as when the System recorded the Analyst actions. (S-6203; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-299, SRD-414

3.2.19.1.4 The Development Subsystem shall replay Analyst actions faster than real time. (S-6204; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-299, SRD-414

3.2.19.1.5 The Development Subsystem shall replay Analyst actions using the same configuration as when the System recorded the Analyst actions. (S-6218; Common)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-299, SRD-414

3.2.19.2 Testing Support Interfaces

3.2.19.3 Testing User Interfaces

3.2.19.3.1 The System shall provide the Developer the capability to synchronize injection of waveform replay data stemming from multiple data sources. (S-2215; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-299

3.2.19.3.2 The System shall provide the Developer the capability to capture waveform raw data and acquisition times for the purpose of replay. (S-2213; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-299, SRD-414

3.2.19.3.3 The System shall provide the Developer the capability to record Analyst actions for the purpose of replay. (S-6205; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-299, SRD-414

3.2.19.3.4 The Development Subsystem shall provide the Developer the capability to select the waveform data for replay. (S-5728; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-299, SRD-414

3.2.19.3.5 The Development Subsystem shall provide the Developer the capability to select the Analyst actions for replay. (S-6206; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-299, SRD-414

3.2.19.3.6 The Development Subsystem shall provide the Developer the capability to select the waveform data replay data rate. (S-5730; Common)

Priority: Extensibility

Verification Methodology: Demonstration

Requirements Trace: SRD-299, SRD-414

3.2.19.3.7 The Development Subsystem shall provide the Developer the capability to select the Analyst action replay rate. (S-6207; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-299, SRD-414

3.2.19.4 Testing Storage

3.2.20 External Interfaces

3.2.20.1 External Interfaces Processing

3.2.20.1.1 The System shall provide authorized systems read-only access to database contents. (S-2238; Common)

Priority: Objective / Priority 1

Verification Methodology: Analysis

Requirements Trace: SRD-297, SRD-622

3.2.20.1.2 The System shall provide a secure web services interface for System and processing SOH data. (S-5791; IDC only)

Priority: Objective / Priority 1

Verification Methodology: Analysis

Requirements Trace: SRD-622

3.2.20.1.3 The System shall securely issue commands to seismic, hydroacoustic, infrasound, and radionuclide stations of the IMS network following IDC Formats and Protocols. (S-5586; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-493

3.2.20.1.4 The System shall provide a language for requesting station information. (S-5748; Common)

Priority: Objective / Priority 1
Verification Methodology: Analysis
Requirements Trace: SRD-410

3.2.20.1.5 The System shall provide a language for formulating requests for waveform data that provides the specification of attribute values (e.g. time, station, associated with event) of the data to be transferred. (S-5780; Common)

Priority: Threshold
Verification Methodology: Analysis
Requirements Trace: SRD-410, SRD-616

3.2.20.1.6 The System shall provide a language for requesting event bulletin data. (S-5750; Common)

Priority: Objective / Priority 1
Verification Methodology: Analysis
Requirements Trace: SRD-410

3.2.20.1.7 The System shall send data and reports to the Authorized External Users based on roles and privileges. (S-5753; Common)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-160, SRD-163, SRD-616

3.2.20.1.8 The System shall distribute all waveform data for an event that satisfies a user-specified set of rules. (S-5779; IDC only)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-616

3.2.20.1.9 The System shall apply a digital signature to the reports and waveform data to be distributed. (S-5765; IDC only)

Priority: Threshold
Verification Methodology: Test
Requirements Trace: SRD-619

3.2.20.1.10 The System shall support at least 1000 Authorized External Users. (S-5766; IDC only)

Priority: Threshold
Verification Methodology: Analysis
Requirements Trace: SRD-509

3.2.20.1.11 The System shall support each Authorized External User requesting up to 4GB of data per day. (S-5767; IDC only)

Priority: Threshold
Verification Methodology: Analysis
Requirements Trace: SRD-509

3.2.20.1.12 The System shall support at least 30000 requests for data and products per day. (S-5768; IDC only)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-510

3.2.20.1.13 The System shall provide a prioritization scheme of queued requests such that reports provided interactively are served faster than via email. (S-5769; Common)

Priority: Objective / Priority 1

Verification Methodology: Analysis

Requirements Trace: SRD-511

3.2.20.1.14 The System shall respond to Authorized External User requests for waveform data and reports within the timeframes specified in the IDC Operations manual. (S-5770; IDC only)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-511

3.2.20.1.15 The System shall convert event bulletin data to the CSS 3.0 format. (S-1244; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-505

3.2.20.1.16 The System shall convert event bulletins to SeisComP3XML format. (S-6300; IDC only)

Priority: Objective / Priority 1

Verification Methodology: Test

Requirements Trace: SRD-505

3.2.20.1.17 The System shall provide requested data and reports via email. (S-5699; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-505, SRD-654

3.2.20.1.18 The System shall provide requested data and reports via a secure website. (S-5701; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-505

3.2.20.1.19 The System shall provide a secure web services interface to reports and waveform data. (S-5891; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-506

3.2.20.1.20 The System shall distribute reports and waveform data in the IMS 2.0 format. (S-5931; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-485, SRD-507

3.2.20.1.21 The System shall distribute radionuclide data as specified in the IDC Formats and Protocols document. (S-6385; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-485

3.2.20.1.22 The System shall convert waveform data to the SEED format. (S-1242; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-505

3.2.20.1.23 The System shall convert waveform data to the CSS 3.0 format. (S-1243; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-505

3.2.20.1.24 The System shall convert waveform data to the IMS2.0 format. (S-1245; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-505

3.2.20.2 External Interfaces Support Interfaces

3.2.20.2.1 The System shall provide the System Maintainer the capability to configure which Authorized External Users are authorized to access reports. (S-6237; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-160

3.2.20.2.2 The System shall provide the System Maintainer the capability to configure which Authorized External Users are authorized to access released events. (S-6238; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-160

3.2.20.2.3 The System shall provide the System Maintainer the capability to configure which Authorized External Users are authorized to access waveform data. (S-6239; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-160

3.2.20.2.4 The System shall provide the System Maintainer the capability to configure by station which Authorized External Users can be sent waveform data. (S-5758; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-160, SRD-616

3.2.20.3 External Interfaces User Interfaces

3.2.20.3.1 The System shall provide the Authorized External User the capability to view station calibration results. (S-6434; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-493

3.2.20.3.2 The System shall provide the Authorized External User the capability to request reports via email. (S-5698; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-505, SRD-654

3.2.20.3.3 The System shall provide the Authorized External User the capability to request reports via a secure website. (S-5700; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-505

3.2.20.3.4 The System shall provide the Authorized External User the capability to request waveform data for an event. (S-5751; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-616

3.2.20.3.5 The System shall provide the Authorized External User the capability to export reports. (S-2011; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-621

3.2.20.3.6 The System shall provide the Authorized External User the capability to request event bulletins in SeisComP3XML format. (S-6301; IDC only)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-611

3.2.20.3.7 The System shall provide the Authorized External User the capability to subscribe to reports and waveform data. (S-5930; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-507

3.2.20.3.8 The System shall provide the Authorized External User the capability to subscribe to radionuclide data. (S-6384; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-485

3.2.20.3.9 The System shall provide the Authorized External User the capability to request alphanumeric data in the CSS 3.0 format. (S-1249; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-505, SRD-616

3.2.20.3.10 The System shall provide the Authorized External User the capability to request the System to send station configuration data at user defined time intervals. (S-2576; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-507

3.2.20.3.11 The System shall provide the Authorized External User the capability to request the System to send station SOH data at user defined time intervals. (S-2578; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-507

3.2.20.3.12 The System shall provide the Authorized External User the capability to request the System to send reports at user defined time intervals. (S-2579; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-507

3.2.20.3.13 The System shall provide the Authorized External User the capability to request the System to send event bulletins at user defined time intervals. (S-2580; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-507

3.2.20.3.14 The System shall provide the Authorized External User the capability to request the System to send station configuration data when there is a change in that data. (S-2581; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-507

3.2.20.3.15 The System shall provide the Authorized External User the capability to request the System to send station data acquisition statistics when there is a change in those statistics. (S-2582; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-507

3.2.20.3.16 The System shall provide the Authorized External User the capability to request the System to send station SOH data when there is a change in that data. (S-2583; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-507

3.2.20.3.17 The System shall provide the Authorized External User the capability to request the System to send reports when there is a change in those reports. (S-2584; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-507

3.2.20.3.18 The System shall provide the Authorized External User the capability to request the System to send event bulletins when there is a change in those event bulletins. (S-2585; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-507

3.2.20.3.19 The System shall provide the Authorized External User the capability to request station configuration data in the Station/FDSNXML format. (S-5704; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-505

3.2.20.3.20 The System shall provide the Authorized External User the capability to request station configuration data in the SeisComP3XML format. (S-5705; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-505

3.2.20.3.21 The System shall provide the Authorized External User the capability to request the System to send waveform data at user defined time intervals. (S-1225; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-505

3.2.20.3.22 The System shall provide the Authorized External User the capability to select the screening criteria parameters the System uses to calculate a National Standard Screened Event Bulletin. (S-6543; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-508

3.2.20.3.23 The System shall provide the Authorized External User the capability to select parameters controlling which screening criteria numerical metric scores the System combines when calculating overall screening categories for a National Standard Screened Event Bulletin. (S-6544; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-508

3.2.20.4 External Interfaces Storage

3.2.21 System Startup and Shutdown

The System has both a planned and an urgent unplanned shutdown. Both planned and urgent unplanned shutdowns are initiated by the user. Planned shutdowns must complete within 30 minutes and gracefully shutdown all software (including transfer of the pipeline) and hardware with no loss of data and no damage to the hardware. An urgent unplanned shutdown must complete within 15 minutes and must shutdown all hardware with no damage. For example, the System should undergo an urgent unplanned shutdown if the System is running on UPS power with only 15 minutes of battery life. During an urgent unplanned shutdown, there is no requirement to gracefully shutdown software.

3.2.21.1 System Startup and Shutdown Processing

3.2.21.1.1 The System shall complete a planned shutdown within 30 minutes of its initiation. (S-2290; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-357

3.2.21.1.2 The System shall complete an urgent shutdown within 15 minutes of its initiation. (S-2294; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-358

3.2.21.1.3 The System shall be operational within one hour of a hardware restart. (S-2567; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-415

3.2.21.1.4 The System shall be operational within 30 minutes of a software restart. (S-2568; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-416

3.2.21.2 System Startup and Shutdown Support Interfaces

3.2.21.3 System Startup and Shutdown User Interfaces

3.2.21.3.1 The System shall provide the System Controller the capability to perform a planned shutdown of the System. (S-2288; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-357

3.2.21.3.2 The System shall provide the System Controller the capability to perform a startup of the System. (S-2289; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-415, SRD-416

3.2.21.3.3 The System shall provide the System User the capability to shutdown individual analyst workstations without affecting the operation of other analyst workstations. (S-2291; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-357, SRD-358

3.2.21.3.4 The System shall provide the System User the capability to startup individual analyst workstations without affecting the operation of other analyst workstations. (S-2292; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-415, SRD-416

3.2.21.3.5 The System shall provide the System Controller the capability to perform an urgent shutdown of the System. (S-2293; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-358

3.2.21.3.6 The System shall provide the System Controller the capability to start processes. (S-2295; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-288

3.2.21.3.7 The System shall provide the System Controller the capability to stop processes. (S-2296; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-288

3.2.21.3.8 The System shall provide the System Controller the capability to initiate and terminate system processing. (S-2297; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-317

3.2.21.4 System Startup and Shutdown Storage

3.2.22 Design Constraints

3.2.22.1 The System shall make use of commercial off-the-shelf (COTS) and open source software where possible. (S-2218; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-273

3.2.22.2 The System shall use commercial off-the-shelf (COTS) and open source software with a defined upgrade path. (S-2219; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-273

3.2.22.3 The System shall reuse suitable existing software where practical. (S-5738; IDC only)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-273

3.2.22.4 The System shall use relational database management systems that support ACID transactions, referential integrity and fine grained locking. (S-5831; IDC only)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-461

3.2.22.5 The System shall use a distributable open source database for Standalone Subsystems. (S-5832; IDC only)

Priority: Threshold

Verification Methodology: Inspection

Requirements Trace: SRD-461

3.2.22.6 The System shall use open-source software whenever possible. (S-5739; IDC only)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-460

3.2.22.7 The System shall use open-source software when both open-source and commercial software are available. (S-5740; IDC only)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-460

3.2.22.8 The System software shall be written using a minimum number of programming languages. (S-2220; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-272

3.2.22.9 The System shall implement dates and times that include leap years and seconds. (S-2224; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-281

3.2.22.10 The System shall use date formats with four digit years. (S-5725; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-282

3.2.22.11 The System shall use year 2038 epoch rollover compliant date formats. (S-2226; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-282

3.2.22.12 The System software shall be maintained and controlled via configuration management software. (S-2233; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-298, SRD-355

3.2.23 Subsystems

3.2.23.1 Subsystem Definition

3.2.23.1.1 The System shall be comprised of discrete subsystems each configured to support its mission, including: 1) Operational (OPS) Subsystem; 2) Alternate (ALT) Operational Subsystem; 3) Testbed (SUS/TST) Subsystem; 4) Development (DEV) Subsystem; 5) Continuous Automated Testing (CATS) Subsystem; 6) Training Subsystem; and 7) Standalone Subsystems. (S-5690; IDC only)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-500

3.2.23.2 OPS/ALT Subsystems

3.2.23.2.1 The System shall provide access to all Analyst capabilities from a remote location over a secure connection. (S-5689; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-450

3.2.23.2.2 The System shall provide the System User the capability to remotely access required user interface functions on the OPS Subsystem from a remote connection over a secure connection. (S-5688; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-450

3.2.23.2.3 The System shall provide the System User the capability to remotely access required user interface functions on the Primary from the Backup. (S-2248; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-360

3.2.23.2.4 The System shall provide the System User the capability to remotely access required user interface functions on the Backup from the Primary. (S-2249; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-360

3.2.23.2.5 The System shall provide the System Controller the capability to remotely operate the Primary from the Backup. (S-2250; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-360

3.2.23.2.6 The System shall provide the System Controller the capability to remotely operate the Backup from the Primary. (S-2251; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-360

3.2.23.2.7 The System shall provide station data to external users in no more than one (1) hour following an unplanned switch between the Primary and Backup. (S-5886; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-473

3.2.23.2.8 The System shall provide the System Controller the capability to initiate a switch between the Primary and Backup. (S-5887; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-474

3.2.23.2.9 The System shall initiate the automatic processing of waveform data in no more than six (6) hours from the start of an unplanned switch between the Primary and Backup. (S-5888; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-475

3.2.23.2.10 The System shall provide the Analyst the capability to perform interactive reviews of processing results in no more than six (6) hours from the start of an unplanned switch between the Primary and Backup. (S-5889; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-475

3.2.23.2.11 The System shall provide the System Controller the capability to disseminate data and products in no more than six (6) hours from the start of an unplanned switch between the Primary and Backup. (S-5890; IDC only)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-475

3.2.23.2.12 The ALT Subsystem shall be a copy of the OPS Subsystem in software and hardware not physically collocated with OPS. (S-5731; IDC only)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-361

3.2.23.2.13 The System shall complete a planned switch between the Primary and Backup with no loss of data or data consistency. (S-5885; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-472

3.2.23.3 SUS/SALT/DEV Subsystem

3.2.23.3.1 The System shall forward selected waveform data and processing results data to the SUS/TST Subsystem. (S-2260; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-366, SRD-367, SRD-432

3.2.23.3.2 The System shall provide the System Maintainer the capability to configure the waveform and processing results data to send to the SUS/TST Subsystem. (S-2261; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-366, SRD-432

3.2.23.3.3 The SUS/TST Subsystem shall be a functionally redundant copy of the OPS Subsystem. (S-2262; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-367

3.2.23.3.4 The Development Subsystem shall provide the Developer the capability to access, modify, create, compile, run, and test source code and configuration files. (S-2264; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-298

3.2.23.3.5 The SUS/TST Subsystem shall provide the Developer the capability to access, modify, create, compile, run, and test source code and configuration files. (S-2265; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-298

3.2.23.3.6 The Development Subsystem shall provide the Developer the capability to access, modify, run, and test existing and new processes in an operational-like mode. (S-2266; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-299

3.2.23.3.7 The SUS/TST Subsystem shall provide the Developer the capability to access, modify, run, and test existing and new processes in an operational-like mode without affecting the OPS Subsystem. (S-2267; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-299, SRD-366

3.2.23.4 CATS Subsystem

3.2.23.4.1 The CATS subsystem shall provide the Developer the capability to access, modify, create, compile, run, and test software (source code and configuration files). (S-5807; IDC only)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-615

3.2.23.4.2 The CATS subsystem shall test software without affecting the OPS Subsystem. (S-5808; IDC only)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-615

3.2.23.4.3 The CATS subsystem shall test software on a regular basis at user defined time intervals. (S-5809; IDC only)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-615

3.2.23.4.4 The CATS subsystem shall provide the Developer the capability to request the CATS subsystem to test software at user defined time intervals. (S-5810; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-615

3.2.23.4.5 The CATS subsystem shall provide the Developer the capability to perform semi-automatic testing of stations prior to release for operational use. (S-5814; IDC only)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-496

3.2.23.5 Standalone Subsystem

3.2.23.5.1 The Standalone Subsystem shall be scalable to operate on a field laptop. (S-2269; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-216

3.2.23.5.2 The Standalone Subsystem shall be scalable to operate on a reduced data center hardware installation. (S-2270; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-216

3.2.23.5.3 The Standalone Subsystem shall operate on low-cost computing infrastructure including the database management system. (S-2271; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-216

3.2.23.5.4 The System shall provide components that can be distributed and run on the Standalone Subsystems. (S-2272; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-216

3.2.23.5.5 The Standalone Subsystem software distribution shall be available for use by any authorized party without export restrictions. (S-6442; IDC only)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-216

3.2.23.6 Training Subsystem

The Training Subsystem is a fully standalone subsystem with no external network connection. The Training Subsystem is totally geared towards new analysts. This subsystem does not acquire data, although it does have a basic pipeline and a workflow acquisition simulator. Instead, this subsystem uses a fixed set of (interesting) data. This data is primarily raw data and is exported from the OPS Subsystem to physical media which is physically taken to the training site and imported; this happens infrequently (on the order of yearly).

There is a training network set up, and the instructor can see the student workstations with their work in progress and even remotely command a student's work station. Ten instructor/student workstations are a part of the Training Subsystem.

The students work in separate areas. This allows them to process the same input data but store multiple output solutions. No permanent history is retained.

The Training Subsystem is run and managed by an entirely different group than the group that manages OPS/ALT.

Periodic software upgrades happen once or twice per year.

3.2.23.6.1 The Training Subsystem shall provide the Analyst with an environment that is functionally equivalent to the OPS/ALT Subsystems. (S-2274; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-369

3.2.23.6.2 The Training Subsystem shall provide 10 student workstations. (S-2276; Common)

Priority: Threshold

Verification Methodology: Inspection

Requirements Trace: SRD-371

3.2.23.6.3 The Training Subsystem shall include a central instructor workstation that allows interaction (including remote operation and viewing) with individual student workstations. (S-2277; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-371, SRD-372, SRD-376, SRD-377

3.2.23.6.4 The Training Subsystem shall include a central instructor workstation that allows simultaneous interaction (including remote operation and viewing) with all student workstations. (S-2278; Common)

Priority: Threshold

Verification Methodology: Demonstration

Requirements Trace: SRD-371, SRD-376, SRD-377

3.2.23.6.5 The Training Subsystem shall provide the Analyst Instructor the capability to delete processing results and waveforms selected based on time interval, instructor, student, and/or dataset. (S-2279; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-194, SRD-378

3.2.23.6.6 The System shall provide the System User the capability to create training data sets that include selected configuration, waveforms, and processing results from selected processing stages. (S-2280; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-192, SRD-618

3.2.23.6.7 The Training Subsystem shall provide the Analyst Instructor the capability to view a report highlighting the differences between the processing results of the instructor and the processing results of a selected student. (S-2281; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-193

3.2.23.6.8 The Training Subsystem shall provide the Analyst the capability to view a report highlighting the differences between their processing results and the processing results of the instructor. (S-2282; Common)

Priority: Objective / Priority 1

Verification Methodology: Demonstration

Requirements Trace: SRD-133, SRD-193

3.2.23.6.9 The Training Subsystem shall provide the Analyst Instructor the capability to install waveform and processing results data using start time, end time, phenomenology and stations to select which data is to be loaded. (S-2283; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-373

3.2.23.6.10 The Training Subsystem shall provide the Analyst Instructor the capability to delete waveform and processing results data using start time, end time, phenomenology and stations to select which data is to be deleted. (S-2284; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-373

3.2.23.6.11 The Training Subsystem shall store data processing results and associated data for each Analyst in an independent solution set that is separate from that of other Analysts using the Subsystem. (S-2285; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-374, SRD-375, SRD-378

3.2.23.6.12 The Training Subsystem shall have individual accounts for each student. (S-2286; Common)

Priority: Threshold

Verification Methodology: Inspection

Requirements Trace: SRD-374

3.2.23.6.13 The System shall provide the Analyst Instructor the capability to select access restrictions on training data sets. (S-6499; Common)

Priority: Objective / Priority 2

Verification Methodology: Demonstration

Requirements Trace: SRD-379

3.2.24 Hardware

3.2.24.1 Reliability, Maintainability, Availability

3.2.24.1.1 The System shall automatically backup all data. (S-2314; Common)

Priority: Threshold

Verification Methodology: Test

Requirements Trace: SRD-334

3.2.24.1.2 The System shall maintain a mission profile operating 52 weeks a year, 7 days per week, and 24 hours a day. (S-2317; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-336

3.2.24.2 Data Storage

The System provides data storage for processing incoming seismic, hydroacoustic, and infrasound data originating from stations located around the world. This processing includes: 1) processing of incoming raw data; 2) all routine

automatic processing; and 3) all interactive analysis of data. Although the majority of incoming raw data are processed on a continuous basis, some data are processed as per request.

3.2.24.2.1 The System shall store on the System all existing data and five (5) additional years of data. (S-2331; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-349

3.2.24.2.2 The Training Subsystem shall provide storage with sufficient capacity to accommodate thirty (30) days of multi-phenomenology waveform data for stations available on the OPS Subsystem. (S-2332; Common)

Priority: Threshold

Verification Methodology: Analysis

Requirements Trace: SRD-351

4 SPECIFICATION TRACEABILITY

System Requirements (SRD)	System Specifications (SSD)
SRD-9	S-1199, S-1204, S-1205, S-1207, S-1208
SRD-10	S-1192, S-1203, S-1210, S-5946
SRD-11	S-1150, S-1151, S-1152, S-1153
SRD-12	S-1154, S-1155
SRD-13	S-1180, S-1181
SRD-15	S-1241, S-5584, S-5585, S-5972, S-5973, S-5974, S-5980
SRD-18	S-1184
SRD-21	S-5613, S-5614
SRD-22	S-1220, S-1227, S-1228, S-5583, S-5781, S-5782, S-5783, S-5784
SRD-25	S-1229, S-5582, S-5583, S-5964
SRD-29	S-1253, S-1254, S-1255, S-1256, S-1257, S-1258, S-1259, S-1260, S-1261, S-1262, S-1263, S-1264, S-1265, S-1266, S-1267, S-1268, S-1269, S-1270, S-1271, S-1275, S-1276, S-1278, S-1280, S-5592, S-5593, S-5594, S-5595, S-5936, S-6219, S-6220, S-6495, S-6496
SRD-30	S-1285, S-1286, S-1287, S-1288, S-1289, S-1290, S-1291, S-1298, S-1299, S-1300, S-1301, S-1306, S-1307, S-1308
SRD-31	S-1272, S-1281, S-1282, S-1294
SRD-32	S-1302, S-1303, S-1304, S-1305
SRD-33	S-1273, S-1284, S-1296, S-1297
SRD-34	S-1284, S-1285
SRD-38	S-1312, S-1313, S-1314, S-1315, S-1316, S-1317, S-1318, S-1319, S-1323, S-1324, S-1327, S-1331, S-1332, S-1333, S-1334, S-1335, S-1336, S-1337, S-1338, S-1339, S-1340, S-1341, S-1342, S-1343, S-1344, S-1346, S-1347, S-2418, S-6195, S-6196, S-6199, S-6200, S-6201, S-6202
SRD-39	S-1320, S-1321, S-1322
SRD-41	S-1453, S-1454, S-1455, S-1457, S-1458, S-1460, S-1461, S-1462, S-1465
SRD-42	S-1468, S-1469, S-1470, S-1473, S-1474, S-1475, S-1478, S-1479, S-1481, S-1482, S-1483, S-1486, S-2359
SRD-44	S-1441, S-1443, S-1445, S-1446, S-1447, S-1450
SRD-52	S-1411, S-1412, S-1413
SRD-54	S-1271, S-1409, S-1410, S-5593, S-5594
SRD-55	S-1406
SRD-56	S-1408, S-1429, S-1443, S-1457, S-1473, S-6305
SRD-62	S-1318, S-1326, S-1335, S-1336, S-1337, S-1425, S-1429, S-1430, S-1432, S-1433, S-1438, S-1441, S-1443, S-1445, S-1446, S-1450, S-5630, S-5631, S-5632
SRD-63	S-1862, S-1870, S-2043
SRD-64	S-1490, S-1494, S-1497, S-1498, S-1561, S-5644, S-5647
SRD-65	S-1508, S-1509
SRD-66	S-1426
SRD-67	S-1471, S-1473, S-1474, S-1476, S-1480
SRD-71	S-1518, S-1806, S-1807
SRD-72	S-1514, S-5596, S-5597, S-5598, S-5599
SRD-73	S-1504, S-1540
SRD-74	S-5600, S-5601
SRD-75	S-1489, S-1490, S-1491, S-1493, S-1495, S-1496, S-1525, S-2411, S-2412, S-2413, S-2416,

System Requirements (SRD)	System Specifications (SSD)
	S-5626, S-5633, S-5634, S-5635, S-5636, S-5637, S-5638
SRD-76	S-1494, S-1497, S-1498, S-1504, S-1511, S-1520, S-1521, S-1522, S-1524, S-1540, S-1560, S-2414, S-2415, S-2416, S-5627, S-5628, S-5629, S-5639, S-5640, S-6513, S-6519, S-6520, S-6524
SRD-77	S-1504, S-1511, S-1512, S-1513, S-1520, S-1521, S-1522, S-1524, S-1526, S-1540, S-1560, S-3026, S-5949, S-5968, S-6010, S-6241, S-6242, S-6243, S-6513, S-6519, S-6520, S-6524
SRD-78	S-1490, S-1504, S-1507, S-1508, S-1509, S-1510, S-1561
SRD-79	S-1504, S-1505, S-1506, S-1540, S-1541, S-1542, S-1549, S-1556, S-1560, S-2043, S-2342
SRD-80	S-1520, S-1521, S-1522, S-1955, S-1961, S-1962, S-1963, S-1964
SRD-81	S-1540, S-1541, S-1542, S-1548, S-1549, S-1862, S-1870, S-2342
SRD-82	S-1547, S-1548, S-1551, S-1556
SRD-83	S-1543, S-1544, S-1548, S-2043
SRD-84	S-1515
SRD-85	S-1572, S-1579, S-1580, S-1586, S-1588
SRD-86	S-1581, S-1582, S-1584, S-5620
SRD-87	S-1580
SRD-88	S-1579, S-1580, S-1586
SRD-89	S-1504, S-1567, S-1568, S-1569, S-1572, S-1574, S-1576, S-6482, S-6483
SRD-92	S-1563, S-1564, S-1592, S-1595, S-1596, S-1600, S-1603, S-1604, S-1607, S-1608, S-1619, S-1620, S-1640, S-6290
SRD-93	S-1631
SRD-94	S-1618, S-1623, S-1633, S-1634, S-1636, S-1637
SRD-95	S-1616, S-1625
SRD-96	S-1532, S-1626, S-1627, S-1628
SRD-98	S-1976, S-1977, S-1978, S-1979, S-1991, S-1993, S-2597, S-5992, S-5996, S-5997
SRD-99	S-1505, S-1506, S-6541
SRD-100	S-1597, S-1598, S-1599
SRD-101	S-1593, S-1594
SRD-102	S-1427, S-1592, S-1601, S-1606, S-1621, S-1622
SRD-103	S-1416, S-1435, S-1603, S-1604, S-1610, S-1611, S-1612, S-1613, S-1614, S-1661
SRD-106	S-1650, S-1651, S-1653, S-1655, S-1656, S-1657, S-1659, S-1664, S-1665, S-6486, S-6487, S-6488, S-6489, S-6490, S-6491, S-6492, S-6493, S-6494
SRD-107	S-1650
SRD-108	S-1652, S-1663
SRD-110	S-1660, S-1661, S-2036, S-2038
SRD-120	S-2127, S-2128, S-2144, S-2156
SRD-122	S-1949, S-1954, S-1958, S-1960, S-1968, S-1969
SRD-124	S-1189, S-1284, S-1285, S-1286, S-1287, S-1288, S-1289, S-1290, S-1291, S-1292, S-1293, S-1331, S-1332, S-1333, S-1334, S-1335, S-1336, S-1337, S-1338, S-1339, S-1340, S-1341, S-1342, S-1343, S-1344, S-1352, S-1353, S-1370, S-1371, S-1372, S-1373, S-1374, S-1375, S-1376, S-1377, S-1378, S-1379, S-1380, S-1381, S-1382, S-1383, S-1416, S-1417, S-1418, S-1419, S-1432, S-1433, S-1434, S-1435, S-1445, S-1446, S-1447, S-1460, S-1461, S-1462, S-1478, S-1479, S-1480, S-1481, S-1482, S-1516, S-1517, S-1529, S-1530, S-1531, S-1532, S-1533, S-1534, S-1535, S-1536, S-1537, S-1554, S-1586, S-1606, S-1607, S-1608, S-1610, S-1611, S-1612, S-1613, S-1614, S-1615, S-1616, S-1636, S-1637, S-1642, S-1643, S-1644, S-1645, S-1646, S-1659, S-1660, S-1661, S-1707, S-1708, S-1709, S-1728, S-1729, S-1730, S-1731, S-1732, S-1733, S-1811, S-1812, S-1814, S-1872, S-1878, S-1879, S-1885, S-1887, S-1888, S-1889, S-1890, S-1891, S-1892, S-1893, S-1894, S-1895, S-1896, S-1897, S-1898,

System Requirements (SRD)	System Specifications (SSD)
	S-1899, S-1900, S-1901, S-1902, S-1903, S-1904, S-1905, S-1906, S-1907, S-1908, S-1915, S-1916, S-1917, S-1918, S-1919, S-1920, S-1921, S-1922, S-1923, S-1926, S-1927, S-1928, S-1929, S-1930, S-1938, S-1939, S-1940, S-1941, S-1942, S-1943, S-1946, S-1947, S-1985, S-1986, S-1987, S-1988, S-1989, S-1990, S-1991, S-1993, S-1995, S-1996, S-1998, S-2019, S-2040, S-2099, S-2100, S-2101, S-2102, S-2103, S-2110, S-2129, S-2130, S-2595, S-2597, S-2607, S-3023, S-3024, S-3025, S-5603, S-5604, S-5851, S-5852, S-5853, S-5986, S-5988, S-5989, S-5990, S-5992, S-5993, S-5994, S-5996, S-5997, S-6000, S-6010, S-6196, S-6198, S-6295, S-6296, S-6297, S-6437, S-6438, S-6439, S-6456
SRD-125	S-1934, S-1935, S-1936, S-1938, S-1939, S-1940, S-1941, S-1942, S-1943
SRD-126	S-1946, S-1957
SRD-127	S-1887, S-1888
SRD-128	S-1919
SRD-129	S-1640, S-1642, S-1643, S-1644, S-1645, S-1646, S-6290
SRD-130	S-1157, S-2123
SRD-131	S-1157, S-1158, S-1159, S-6485
SRD-133	S-1889, S-1920, S-1923, S-1924, S-2282, S-5556, S-5958, S-5959, S-5960
SRD-135	S-5621
SRD-136	S-1189, S-1284, S-1285, S-1286, S-1287, S-1288, S-1289, S-1290, S-1291, S-1292, S-1293, S-1294, S-1331, S-1332, S-1333, S-1334, S-1335, S-1336, S-1337, S-1338, S-1339, S-1340, S-1341, S-1342, S-1343, S-1344, S-1352, S-1353, S-1370, S-1371, S-1372, S-1373, S-1374, S-1375, S-1376, S-1377, S-1378, S-1379, S-1380, S-1381, S-1382, S-1383, S-1416, S-1417, S-1418, S-1419, S-1432, S-1433, S-1434, S-1435, S-1445, S-1446, S-1447, S-1460, S-1461, S-1462, S-1478, S-1479, S-1480, S-1481, S-1482, S-1483, S-1516, S-1517, S-1529, S-1530, S-1531, S-1532, S-1533, S-1534, S-1535, S-1536, S-1537, S-1554, S-1586, S-1606, S-1607, S-1608, S-1610, S-1611, S-1612, S-1613, S-1614, S-1615, S-1616, S-1636, S-1637, S-1642, S-1643, S-1644, S-1645, S-1646, S-1659, S-1660, S-1661, S-1706, S-1707, S-1708, S-1709, S-1728, S-1729, S-1730, S-1731, S-1732, S-1733, S-1811, S-1812, S-1813, S-1814, S-1872, S-1878, S-1879, S-1887, S-1888, S-1889, S-1890, S-1891, S-1892, S-1893, S-1894, S-1895, S-1896, S-1897, S-1898, S-1899, S-1900, S-1901, S-1902, S-1903, S-1904, S-1905, S-1906, S-1907, S-1908, S-1915, S-1916, S-1917, S-1918, S-1919, S-1920, S-1921, S-1922, S-1923, S-1926, S-1927, S-1928, S-1930, S-1938, S-1939, S-1940, S-1941, S-1942, S-1943, S-1946, S-1947, S-1985, S-1986, S-1987, S-1988, S-1989, S-1990, S-1991, S-1993, S-1995, S-1996, S-1997, S-1998, S-1999, S-2000, S-2019, S-2040, S-2097, S-2098, S-2099, S-2100, S-2101, S-2102, S-2103, S-2110, S-2127, S-2128, S-2129, S-2130, S-2176, S-2597, S-2603, S-2604, S-2607, S-3023, S-3024, S-3025, S-5603, S-5604, S-5851, S-5852, S-5853, S-5953, S-5954, S-5955, S-5956, S-5957, S-5986, S-5988, S-5989, S-5990, S-5992, S-5993, S-5994, S-5996, S-5997, S-6000, S-6010, S-6196, S-6198, S-6437, S-6438, S-6439, S-6456
SRD-137	S-1809, S-1811
SRD-138	S-1516, S-1517, S-1527, S-1533, S-1534, S-1535, S-1536, S-1554, S-1556, S-1927, S-1928, S-1929, S-1930, S-2607, S-3024, S-6010
SRD-139	S-1916, S-1920, S-1926
SRD-140	S-1872, S-1920
SRD-141	S-1916, S-1917, S-1918
SRD-142	S-1533, S-1534, S-1535, S-1927, S-1928, S-1929, S-3023, S-3025
SRD-144	S-1361, S-1373, S-1976, S-1981, S-1983
SRD-145	S-1377, S-1378, S-1379, S-1382
SRD-149	S-1985, S-1986, S-1987, S-5986, S-5988
SRD-150	S-1985, S-1986, S-1987, S-5986, S-5988
SRD-151	S-1981, S-1983, S-1989, S-1990, S-5603, S-5604, S-5990, S-5993, S-5994
SRD-152	S-1976, S-1977, S-1978, S-1979, S-1991, S-1993, S-2597, S-5992, S-5996, S-5997

System Requirements (SRD)	System Specifications (SSD)
SRD-153	S-1988, S-5989
SRD-154	S-1974, S-1975, S-1997, S-1999, S-2000
SRD-156	S-1975, S-1976, S-1977, S-1978, S-1979, S-1995, S-1998, S-1999, S-2000
SRD-160	S-1954, S-2006, S-2016, S-5695, S-5696, S-5697, S-5753, S-5758, S-6237, S-6238, S-6239, S-6433
SRD-163	S-2006, S-2007, S-2012, S-2019, S-2024, S-5753, S-6428, S-6429, S-6456
SRD-165	S-2017, S-2020, S-6432, S-6457, S-6458, S-6459, S-6460
SRD-168	S-2048, S-2049, S-2056, S-2057, S-2275, S-6463
SRD-169	S-2040, S-2043
SRD-170	S-1624, S-1666
SRD-171	S-1191, S-1374, S-1386, S-1393, S-1394, S-1878, S-2420, S-5610
SRD-172	S-1146, S-1147, S-1296, S-1297, S-1298, S-1305, S-1306, S-1307, S-1308, S-1346, S-1386, S-1387, S-1421, S-1438, S-1450, S-1465, S-1486, S-1556, S-1557, S-1576, S-1588, S-1619, S-1620, S-1621, S-1622, S-1623, S-1624, S-1625, S-1626, S-1627, S-1628, S-1663, S-1664, S-1665, S-1666, S-1711, S-1712, S-1713, S-1714, S-1715, S-1716, S-1717, S-1718, S-1719, S-1735, S-1736, S-1737, S-1738, S-1816, S-1817, S-1818, S-1819, S-1820, S-1821, S-1822, S-1823, S-1824, S-1842, S-1843, S-1967, S-2042, S-2043, S-2044, S-2117, S-2119, S-2134, S-2157, S-2417, S-2420, S-5714, S-5715, S-5716, S-5717, S-5720, S-5722, S-6521, S-6522
SRD-189	S-2280
SRD-193	S-2281, S-2282
SRD-194	S-2279
SRD-197	S-1779, S-1780, S-1781, S-1782, S-1811, S-1816, S-1819, S-1820
SRD-198	S-1783, S-1784, S-1785, S-1786, S-1811, S-1816, S-1819, S-1820
SRD-199	S-1787, S-1788, S-1789, S-1790, S-1811, S-1816, S-1821, S-1822, S-5830
SRD-200	S-1791, S-1792, S-1793, S-1794, S-1811, S-1816, S-1823, S-1824
SRD-201	S-1795, S-1796, S-1797, S-1798, S-1799, S-1800, S-1811, S-1816, S-1823, S-1824
SRD-202	S-1801, S-1802, S-1803, S-1804, S-1811, S-1816, S-1823, S-1824
SRD-203	S-1776, S-1777, S-1778, S-1808, S-1812, S-1813, S-1817, S-1818
SRD-204	S-1776, S-1777, S-1808, S-1812, S-1817, S-1818
SRD-205	S-1851
SRD-206	S-1795, S-1796, S-1797, S-1801, S-1802, S-1852, S-1853, S-1856, S-5655, S-5828
SRD-209	S-1811, S-1816, S-1827, S-1828, S-1829, S-1830, S-1842, S-1843, S-3041, S-3042, S-3045
SRD-211	S-1811, S-1816, S-1837, S-1838, S-1839, S-1840, S-1842, S-1843, S-3043, S-3044, S-3045
SRD-212	S-1776, S-1777, S-1808, S-1812, S-1817, S-1818
SRD-213	S-1846, S-1847, S-1848, S-1849, S-1850
SRD-216	S-2269, S-2270, S-2271, S-2272, S-2275, S-6442
SRD-217	S-1541, S-1867, S-1868, S-1869

System Requirements (SRD)	System Specifications (SSD)
SRD-218	S-1878, S-1879
SRD-220	S-1880
SRD-225	S-2144, S-2147, S-2148, S-2151, S-2152, S-2156
SRD-226	S-2143, S-2144, S-2149, S-2150, S-2153, S-2154
SRD-227	S-2138
SRD-228	S-1961, S-1965, S-1970, S-1971, S-2139
SRD-229	S-1962, S-1963
SRD-232	S-2124, S-2130, S-2135
SRD-233	S-2129, S-2134, S-2135
SRD-237	S-1292, S-1293
SRD-238	S-2076, S-2083, S-2097, S-2099, S-2100, S-2102, S-2103, S-2104, S-5718, S-5719, S-5720, S-5721, S-5722, S-5963
SRD-239	S-2098, S-5723, S-5724
SRD-240	S-2078, S-2084, S-2085, S-2086, S-2105, S-2106, S-2107, S-2115, S-2118
SRD-241	S-2109
SRD-242	S-2077, S-2079, S-2080, S-2087, S-2088, S-2089, S-2110, S-2119, S-2120, S-6455
SRD-243	S-2081, S-2114
SRD-244	S-2091, S-2092, S-2094, S-2095, S-2096
SRD-245	S-1329, S-1383, S-2159, S-2160, S-2161, S-5971
SRD-247	S-2111, S-2112, S-2113
SRD-249	S-2140, S-2146, S-2157
SRD-253	S-2175, S-2176
SRD-255	S-2172, S-2177, S-2178
SRD-261	S-2164
SRD-262	S-2165
SRD-263	S-1862, S-1870, S-2043, S-2174
SRD-264	S-2099, S-2100, S-2101, S-2104, S-5719
SRD-265	S-2166, S-2604
SRD-268	S-2028, S-2030
SRD-270	S-1950
SRD-271	S-2223
SRD-272	S-2220
SRD-273	S-2218, S-2219, S-5738
SRD-274	S-1913, S-1915
SRD-276	S-1860, S-1861, S-1862, S-1870, S-5557
SRD-277	S-1865, S-1866, S-2171
SRD-278	S-1133, S-1134, S-1135, S-1136, S-1137, S-1138, S-1139, S-2595
SRD-279	S-1133, S-1140, S-1141
SRD-280	S-1133, S-1135, S-1136, S-1137, S-1138, S-1139, S-1140, S-1141, S-1540, S-1541, S-1549, S-1868, S-2175
SRD-281	S-2224
SRD-282	S-2226, S-5725
SRD-285	S-1947, S-1959
SRD-286	S-1951, S-1952
SRD-287	S-1892
SRD-288	S-1965, S-2143, S-2295, S-2296

System Requirements (SRD)	System Specifications (SSD)
SRD-289	S-1955, S-1961, S-2139
SRD-290	S-1962, S-1963, S-1964
SRD-291	S-2036, S-2038
SRD-297	S-2238
SRD-298	S-2233, S-2264, S-2265
SRD-299	S-2213, S-2214, S-2215, S-2266, S-2267, S-5728, S-5730, S-6203, S-6204, S-6205, S-6206, S-6207, S-6218
SRD-300	S-2068, S-2069, S-2071, S-2072, S-6500, S-6501, S-6502, S-6503, S-6504, S-6505, S-6506, S-6507, S-6508, S-6509, S-6510, S-6511, S-6538, S-6539
SRD-301	S-2031
SRD-316	S-2185, S-2186, S-2187, S-2188, S-2189, S-2205, S-2206, S-2207
SRD-317	S-2191, S-2297
SRD-318	S-2190, S-2191
SRD-319	S-2183
SRD-320	S-2192
SRD-324	S-2184, S-2204, S-2208
SRD-325	S-2196, S-2197, S-2198, S-2199
SRD-328	S-5669
SRD-334	S-2314
SRD-336	S-2317
SRD-349	S-2331
SRD-351	S-2332
SRD-355	S-2233
SRD-356	S-2173
SRD-357	S-2288, S-2290, S-2291
SRD-358	S-2291, S-2293, S-2294
SRD-360	S-2147, S-2149, S-2151, S-2153, S-2248, S-2249, S-2250, S-2251
SRD-361	S-5731
SRD-366	S-2260, S-2261, S-2267
SRD-367	S-2260, S-2262
SRD-369	S-2274
SRD-370	S-2275
SRD-371	S-2276, S-2277, S-2278
SRD-372	S-2277
SRD-373	S-2283, S-2284
SRD-374	S-2285, S-2286
SRD-375	S-2285
SRD-376	S-2277, S-2278
SRD-377	S-2277, S-2278
SRD-378	S-1967, S-2279, S-2285
SRD-379	S-6499
SRD-382	S-1350, S-1352, S-1353, S-1365, S-1366, S-1367, S-1368, S-1445, S-1450, S-2422
SRD-384	S-1134, S-1143, S-1356, S-1357, S-1358, S-1359, S-1360, S-1362, S-1363, S-1364, S-1365, S-1366, S-1367, S-1368, S-1370, S-1371, S-1375, S-1376, S-1377, S-1378, S-1379, S-1380, S-1381, S-1386, S-1403, S-1404, S-2424, S-5789, S-5965, S-6197
SRD-394	S-1684, S-1685, S-1686, S-1687, S-1688, S-1689, S-1690, S-1691, S-1692, S-1693, S-1694,

System Requirements (SRD)	System Specifications (SSD)
	S-1695, S-1696, S-1697, S-1698, S-1701, S-1702, S-1703, S-1704, S-1706, S-1707, S-1708, S-1709, S-1711, S-1712, S-1713, S-1714, S-1715, S-1716, S-1717, S-1718, S-1719
SRD-395	S-1684, S-1685, S-1686, S-1687, S-1688, S-1689, S-1690, S-1694, S-1695, S-1697, S-1698, S-1701, S-1702, S-1703, S-1704, S-1706, S-1707, S-1708, S-1711, S-1712, S-1713, S-1714, S-1715, S-1716, S-1717, S-1718, S-1719, S-1720, S-1721, S-1722, S-1723, S-1724, S-1725, S-1726, S-1728, S-1729, S-1730, S-1731, S-1732, S-1733, S-1735, S-1736, S-1737, S-1738
SRD-398	S-1143, S-1987, S-5965, S-5988
SRD-400	S-1921, S-1922
SRD-402	S-1616, S-1862, S-1867, S-1868, S-1869, S-1870, S-1876, S-1877
SRD-403	S-1859, S-1874, S-2588, S-2589, S-2590
SRD-404	S-1875
SRD-406	S-1253, S-1254, S-1255, S-1256, S-1257, S-1258, S-1259, S-1260, S-1261, S-1262, S-1263, S-1264, S-1265, S-1266, S-1267, S-1268, S-1269, S-1270, S-1271, S-1275, S-1276, S-1278, S-1280, S-5592, S-5593, S-5594, S-5595, S-6219, S-6220, S-6495, S-6496
SRD-407	S-1285, S-1286, S-1287, S-1288, S-1289, S-1290, S-1291
SRD-408	S-1572, S-1576, S-6481, S-6482, S-6483
SRD-409	S-5710
SRD-410	S-5748, S-5750, S-5780
SRD-411	S-5623, S-5624, S-5976, S-5977, S-5978, S-5981
SRD-414	S-2213, S-2214, S-5728, S-5729, S-5730, S-6203, S-6204, S-6205, S-6206, S-6207, S-6218
SRD-415	S-2289, S-2292, S-2567
SRD-416	S-2289, S-2292, S-2568
SRD-418	S-1510, S-1592, S-5615, S-5652, S-5653, S-5654
SRD-419	S-1592, S-5655, S-5656, S-5657
SRD-421	S-1540, S-1567, S-1568, S-1569
SRD-424	S-5794, S-5815, S-5816, S-5819, S-5820, S-5823, S-5824, S-5825, S-5826, S-6291, S-6292, S-6293
SRD-425	S-5796
SRD-427	S-5734, S-5735
SRD-430	S-1234, S-1235, S-1236, S-5577, S-5970
SRD-431	S-5625
SRD-432	S-1179, S-1182, S-2260, S-2261, S-5578, S-5606, S-5607
SRD-433	S-1179, S-5606, S-5609
SRD-434	S-1179, S-5578, S-5606
SRD-436	S-5580
SRD-438	S-1878, S-5610, S-5612
SRD-441	S-5785, S-6542
SRD-442	S-5622
SRD-444	S-1284, S-1285, S-1297
SRD-446	S-1403, S-1404, S-1469, S-5787
SRD-447	S-1405, S-5789
SRD-448	S-1626, S-1627, S-1628
SRD-449	S-5745, S-5746
SRD-450	S-5688, S-5689
SRD-451	S-5666, S-6002
SRD-452	S-5703
SRD-453	S-5702, S-6430, S-6431

System Requirements (SRD)	System Specifications (SSD)
SRD-460	S-5739, S-5740
SRD-461	S-5831, S-5832
SRD-472	S-2060, S-2061, S-2062, S-2063, S-5885, S-6472
SRD-473	S-5886
SRD-474	S-5887
SRD-475	S-5888, S-5889, S-5890
SRD-482	S-2006, S-6428
SRD-483	S-5686, S-5687, S-5695
SRD-484	S-5894, S-6428
SRD-485	S-5931, S-6384, S-6385
SRD-490	S-5795, S-6292, S-6293
SRD-491	S-5794, S-6292, S-6293
SRD-492	S-1305
SRD-493	S-5586, S-5670, S-5674, S-6434
SRD-496	S-5814
SRD-500	S-5690
SRD-505	S-1225, S-1242, S-1243, S-1244, S-1245, S-1249, S-5698, S-5699, S-5700, S-5701, S-5704, S-5705, S-5706, S-5707, S-5710, S-6300, S-6428
SRD-506	S-5891
SRD-507	S-2576, S-2578, S-2579, S-2580, S-2581, S-2582, S-2583, S-2584, S-2585, S-5930, S-5931
SRD-508	S-5763, S-5764, S-6543, S-6544
SRD-509	S-5766, S-5767
SRD-510	S-5768
SRD-511	S-5769, S-5770, S-5771
SRD-512	S-1146, S-1147
SRD-600	S-5624, S-5759
SRD-601	S-5652, S-5653
SRD-610	S-5714, S-5715, S-5716, S-5717
SRD-611	S-1191, S-1192, S-1237, S-1238, S-1239, S-1240, S-6301
SRD-613	S-5743, S-5744, S-6548, S-6549, S-6550, S-6551, S-6552, S-6553
SRD-615	S-5807, S-5808, S-5809, S-5810
SRD-616	S-1247, S-1248, S-1249, S-5751, S-5753, S-5758, S-5779, S-5780
SRD-617	S-2129, S-2134, S-2135
SRD-618	S-2280
SRD-619	S-5765
SRD-620	S-5641, S-5642, S-5643
SRD-621	S-2007, S-2008, S-2011, S-5892, S-5893, S-5962, S-6428
SRD-622	S-2238, S-5791
SRD-623	S-1286, S-5827
SRD-624	S-5815, S-5816, S-5833, S-5834, S-5841, S-5842
SRD-625	S-5795
SRD-626	S-5819, S-5820, S-5823, S-5824, S-5835, S-5836, S-5837, S-5843, S-5845, S-5846, S-5847, S-5848
SRD-627	S-5825, S-5826, S-5838, S-5839, S-5849, S-5850
SRD-651	S-5736, S-5737
SRD-652	S-5615, S-5624

System Requirements (SRD)	System Specifications (SSD)
SRD-653	S-1318, S-1335, S-1336, S-1337, S-1397, S-1398, S-1399, S-1400, S-1401, S-1402, S-1408, S-1414, S-1421, S-2344, S-2345, S-2346, S-2347, S-2348, S-2349, S-2350, S-2351, S-2352, S-2353, S-2358, S-5573, S-5574, S-5969, S-6467, S-6468, S-6469, S-6470
SRD-654	S-5698, S-5699