

Metal Hydride Compression

PI: Terry Johnson

Sandia National Laboratories

Team: Robert Bowman, Barton Smith, Lawrence Anovitz

Oak Ridge National Laboratory

Craig Jensen

Hawaii Hydrogen Carriers, LLC

June 6, 2017

Project ID PD138

This presentation does not contain any proprietary, confidential, or otherwise restricted information

Overview

Timeline

- Project Start Date: 10/01/16
- Project End Date: 09/30/19

Budget

- Total Project Budget: \$1.8M
 - Total Recipient Share: \$180K
 - Total Federal Share: \$1.62M
 - Total DOE Funds Spent*: \$154K

* As of 3/31/17

Barriers – Hydrogen Delivery


- B. Reliability and Costs of Gaseous Hydrogen Compression

Partners

- Lead: Sandia National Laboratories
- Hawaii Hydrogen Carriers, LLC
- Oak Ridge National Laboratory


Relevance: H₂ compressors dominate station costs and downtime

70 Mpa station cost distribution



Compressors represent 31% of total station cost

Compressors are largest contributors to maintenance hours





Relevance: Metal hydride compression can improve reliability of 700 bar refueling

Main Objective – *Demonstrate a two-stage metal hydride compressor with a feed pressure of ~50 bar delivering high purity H₂ gas at 1 kg H₂/hr at an outlet pressure of 875 bar.*

- Demonstrate an increase in the TRL of this technology from 2 to 5
- Enable the development of a comprehensive cost analysis for a production system scaled to 100 kg H₂/hr
- FY17 Objectives:
 - Demonstrate through laboratory characterization two metal hydrides for each stage that meet system level requirements
 - Demonstrate compressor feasibility through analysis using a system-level compressor model
 - Down select compressor bed designs for both stages based on trade studies

Approach: Two-stage Metal Hydride Compressor

- Two-stage metal hydride compressor
 - Feed pressure 50-100 bar
 - Outlet pressure ≥ 875 bar
 - High purity H₂ gas
- Optimized material for each stage
 - 2-3 candidates per stage will be characterized (thermodynamics, kinetics, and hydrogen capacities) to determine optimum design
- Each stage consists of multiple (2-3) hydride beds
 - synchronized hydrogenation & dehydrogenation cycles
 - size and number of beds will be optimized for continuous pumping at desired pressure with minimal heat input




Approach: Trade study to determine bed designs including heat transfer enhancement


External heating/cooling ENG additive for heat transfer



Internal heating/cooling Al foam for heat transfer



Approach: Dynamic system-level model developed for feasibility and design trade studies




Approach: Status of Milestones

Type	Milestone Number	Milestone Description	Scheduled Date	Status
Milestone	2.1	At least two candidate alloys identified for both LP and HP	12/16	100%
Milestone	2.2	At least two LP and HP materials fully characterized	4/17	10% (Delayed)
Milestone	3.2.1	Desired effective thermal conductivity determined along with additive type and amount.	7/17	0%
Go/No-Go Decision Point	Go/No-Go #1	Laboratory characterization demonstrates the ability of two metal hydride alloys to compress hydrogen from 100 bar to 875 bar, and engineering simulations using the system-level compressor model reasonably predict that the compressor can achieve an energy consumption of < 2.0 kWh/kg-H ₂ under 100-875 bar operation relying on process waste heat from co-located equipment.	10/17	0%
Milestone	6.1	Detailed design complete	1/18	0%
Milestone	7.1	Receipt of complete lots of both the LP and HP alloys by 17th month to allow time for processing into powders and confirmation of hydrogen absorption/desorption parameters while the bed assemblies are being fabricated.	3/18	0%
Milestone	7.2	Completed assembly of 2-stage compressor with at least two each LP and HP compressor beds	7/18	0%
Go/No-Go Decision Point	Go/No-Go #2	One LP and one HP hydride must show degradation less than 20% of initial capacity over ~1000 cycles or regeneration potential.	8/18	0%

Accomplishments: Dynamic system model used to predict performance for baseline two-stage design

Baseline Configuration:

- 25 kg of LP hydride ($\text{TiMn}_{1.66}\text{Vf}_{0.34}$)
- 21.7 kg of HP hydride ($\text{TiCrMn}_{0.7}\text{Fe}_{0.2}\text{V}_{0.1}$)
- 12 minute half cycles
- Heating/cooling of beds with heat transfer fluid
 - Cold loop temperature set to **10 °C**
 - Hot loop temperature set to **177 °C**



Results:

- Utilization = 49.5% for all beds
 - $$\text{Utilization} = \frac{\text{Hydrogen delivered}}{\text{Storage capacity}}$$
- **1.07 kg/hr average flow rate** 
- Energy usage for heating **12.5 kWh/kg H₂**
- Model used to characterize design space
 - Alloys, cycle times, bed geometry, feed pressure



Accomplishments: Several approaches identified to achieve energy efficiency/cost targets

- Heat recuperator design could reduce the sensible heat requirement of the system by ~40% bringing required heat down to ~10 kWh/kg
- Waste heat utilization:
 - Coupling to an SMR system is possible (heat available at appropriate temperature), but not likely in forecourt
 - Waste-to-energy systems identified with available, high quality heat
 - BESI system at HCATT has 190 kW of steam at ~180 °C and cooling water
- Low cost heat:
 - Natural gas burner can provide 10 kWh/kg of heat for about \$.25/kg
- Heat pump options:
 - VCC operating between 25 °C and 125 °C
 - Using R21 gives COP = 2.7 resulting in 3.7 kWh/kg
 - Using methanol gives a COP of 3.2 resulting in 3.1 kWh/kg
 - A natural gas-fired AHP system might produce a COP of ~1.4 with these temperatures requiring 7.1 kWh/kg of heat or \$.18/kg

Accomplishments: Five candidate alloys identified for each compressor stage; paired down to two each


- Alloy selection based on thermodynamics reported in literature
 - Minimal hysteresis and flat plateaus
 - Promising pressure at reasonable temperature
- Two high-pressure and low-pressure AB_2 alloys selected for PCT characterization

High Pressure Candidates


- $TiCr_{1.6}Mn_{0.2}$
- $TiCr_{1.8}$
- $Ti_{0.95}Zr_{0.05}Cr_{1.20}Mn_{0.75}V_{0.05}$
- $(Ti_{0.97}Zr_{0.03})_{1.1}Cr_{1.6}Mn_{0.4}$
- $TiCrMn_{0.7}Fe_{0.2}V_{0.1}$

Low Pressure Candidates

- $MmNi_{4.7}Al_{0.3}$
- $TiMn_{1.66}Vf_{0.34}$
- $Zr_{0.8}Ti_{0.2}FeNi_{0.8}V_{0.2}$
- $TiCr_{1.6}Mn_{0.2}$
- $Ti_{0.955}Zr_{0.045}Mn_{1.52}V_{0.43}Fe_{0.12}Al_{0.03}$
(Hydralloy C5)



M.T. Hagstrom et al. JALCOM 293–295 (1999) 67



Accomplishments: Vendors engaged to supply alloys for low and high pressure beds

- Vendors contacted: Eutectix, Ergenics, GfE, Ames Laboratory, Sigma Aldrich, Japan Metals and Chemicals (JMC), Japan Steel Works (JSW)
- Sandia owns ~100kg of Hydralloy C5 ($Ti_{0.955}Zr_{0.045}Mn_{1.52}V_{0.43}Fe_{0.12}Al_{0.03}$)
 - Will be characterized for possible LP alloy
- Small samples of LP alloys obtained from GfE and Sigma Aldrich
 - But, similar alloys to Hydralloy C5
- Ames able to produce LP and HP alloys: small batches, expensive
- JMC able to produce LP and HP alloys in large quantities for less cost
 - Procure test quantities (i.e., ~ 50 grams) of three AB_2 alloys
 1. $Zr_{0.8}Ti_{0.2}Fe_{1.0}Ni_{0.8}V_{0.2}$ (Low-Pressure)
 2. $Ti_{0.95}Zr_{0.05}Cr_{1.20}Mn_{0.75}V_{0.05}$ (High-Pressure)
 3. $Ti_{1.0}Cr_{1.0}Mn_{0.7}Fe_{0.2}V_{0.1}$ (High-Pressure)



Accomplishments: High pressure cycling apparatus designed; assembly and calibration in progress

- High-pressure Sievert's system design completed in December
 - Incorporated ideas/practices from JPL hydride temperature cycling station and SNL high-pressure station
 - Used existing infrastructure at ORNL as much as possible
 - Focus on minimizing internal volume to enable measurements of small quantities of hydride alloys
- Safety review completed and design approved in January
- Assembly and system testing began in February
- PCT experiments will determine if
 1. Desorption pressure > 875 bar at T < 150 ° C
 2. Alloys properties are stable over ~1000 cycles
- First measurements of high-pressure hydride to be completed in June
- Characterization of high-pressure hydrides to be completed in August

Accomplishments: High pressure cycling apparatus design minimizes internal volume

ORNL High-Pressure Sieverts System

Pressure: 0-1000 bar, Temperature: 0-150°C
 Internal volume minimized to enable accurate isotherms measurements of hydride alloy at pressures >300 bar



Accomplishments: PCT system set to characterize low pressure alloys



Suzuki Shokan 2 channel thermo-volumetric analyzer (Sievert's type apparatus aka PCT) with medium (≥ 150 atm) pressure capability.



Isotherms of a minimum of 2 candidate AB₂ hydrides will be obtained at 25, 70, 100 and 150 °C by June 1, 2017.

Responses to Previous Year Reviewer's Comments

- This project was not reviewed last year

Collaborations: Experienced team well-suited for executing this project plan

- Sandia National Laboratories
 - Project lead/project management
 - Lead compressor bed and system design (system model, pressure vessel design, heat transfer enhancement)
 - Low pressure hydride degradation assessment
 - Experimental evaluation of the prototype compressor
- Oak Ridge National Laboratory
 - Hydride identification
 - High pressure hydride characterization and degradation assessment
 - Support SNL in developing compressor bed and system designs
- Hawaii Hydrogen Carriers, LLC
 - Low pressure hydride characterization
 - Hydride sourcing and procurement
 - Fabrication of the prototype 2-stage compressor
 - Cost analysis of the commercial system concept.

Remaining Challenges and Barriers

- Challenge: Achieve an energy consumption of < 2.0 kWh/kgH₂ or cost less than \$0.22/kgH₂
 - Metal hydride thermodynamics require 6-7 kWh/kgH₂ minimum for a two-stage compressor; sensible heating requirements and losses push this to ~12 kWh/kgH₂
 - 12 kWh/kgH₂ of heat provided by a natural gas combustion unit (assuming natural gas costs \$0.065/mm-btu, and burners are about 85% efficient) is about \$.30/kg
 - Must show potential for waste heat utilization and/or lower cost heat
- Challenge: Identifying two metal hydride alloys to compress hydrogen from 100 bar to 875 bar within reasonable operating temperatures with degradation less than 20% of initial capacity over ~1000 cycles or regeneration potential
- Challenge: Bed design (especially to >875 bar) that maximizes energy efficiency by minimizing sensible heating, thermal losses, and void volume while also maximizing H₂ flow rate

Proposed Future Work

Remainder of FY17

- Characterize at least two alloys for each stage
 - Produce absorption and desorption isotherms
 - Demonstrate system requirements can be met by at least one alloy for each stage
- Perform trade studies on design configurations for the prototype LP & HP compressor beds and down select
- Complete feasibility assessment using system-level compressor model
 - Demonstrate performance with measured properties and final bed designs
 - Demonstrate path to energy and/or cost targets

FY18

- Perform accelerated cycling tests (~1000 cycles) on hydrides
 - determine degradation rate
 - assess regeneration potential.
- Complete fabrication and assembly drawings of compressor beds
- Procure hydride alloys and fabricate bed components
- Process hydrides, load compressor bed, perform leak and pressure tests then integrate into prototype compressor.
- Configure test facility to enable performance testing.

Any proposed future work is subject to change based on funding levels

Technology Transfer Activities

Potential Follow-on Prototype Demonstration

- Discussions with HCATT/BESI on integration of the prototype system into BESI waste-to-energy system in Peal Harbor, HI or University Park, IL

Tech-to-Market Plan

- Two-year developmental phase
 - HHC will team with an electrolyzer, fueling station supplier, or reformer company to produce a scaled-up, commercial version of the compressor
 - Units will be marketed as upgrades for current hydrogen generation systems, or for localized H₂ production via renewable sources such as solar or wind for residential, businesses or small utility fleets.
- Final two-year phase
 - Further scale-up effort for the development and marketing of larger hydride compressors with output of 10 kg H₂/hr to 100 kg H₂/hr for hydrogen fueling stations









Summary

- A metal hydride compressor has potentially significant advantages over current technology
 - Greatly reduced operating costs
 - Requires little or no maintenance
 - Can be powered by waste heat rather than electricity
 - More Reliable: Simple design and operation with no moving parts
 - High purity H_2 delivery: Oil free operation
- Candidate alloys for low and high pressure stages are readily available in quantities required for a prototype system
- System-level analysis of a baseline design demonstrates feasibility of 50 - 875 bar H_2 compression and delivery at reasonably achievable temperatures
- Metal hydride compressors can be energy efficient by taking advantage of waste heat sources or using heat pumps; inexpensive to operate if low cost heat is available


TECHNICAL BACK-UP SLIDES

Interstitial metal hydrides for H₂ compression

AB₅ and AB₂ most commonly used

Group (representative)	Structure of parent alloy	Structure of hydride	$\Delta V/V_0 [\%]$
A (BCC-V)			35.5 (V \rightarrow VH ₂) 30.9 (V ₂ H \rightarrow VH ₂)
B (LaNi ₅)			20.4 (LaNi ₅ \rightarrow LaNi ₅ H ₆)
C (TiMn ₂)			19.6 (TiMn ₂ \rightarrow TiMn ₂ H _{2.5})
D (TiFe)			18.3 (TiFe \rightarrow TiFeH ₂)


Pressure-Composition-Temperature (PCT) Isotherms for a “Prototype” Metal Hydride




- where α - & β -phases co-exist, a plateau occurs
- plateau pressure is temperature dependent

Estimates of compression ratio must account for real metal hydride properties

Pressure – composition isotherms at $T_L=20\text{ }^\circ\text{C}$ (1) and $T_H=150\text{ }^\circ\text{C}$ (2) for H – $\text{La}_{0.85}\text{Ce}_{0.15}\text{Ni}_5$ system



(a) –idealized (flat plateaus, desorption isotherms)



b) – real (sloping plateaus, absorption isotherm at T_L , desorption isotherm at T_H).

Metal hydride compressors have advantages over mechanical compression, but other challenges

Advantages

- Simple design and operation
- Absence of moving parts
- Oil-free
- Compact
- Safe and reliable
- Able to utilize waste industrial heat
 - Dramatic decreases in operational costs
 - Advantage with on-site generation

Challenges

- Achieving required pressure range within reasonable operating temperatures
- Capacity degradation over the compressor lifetime
- Hysteresis effects
- Resistance to impurities
- Efficiency
- Minimizing effect of vessel heat capacity

2-Stage 700 bar Compressor Demonstrated Used AB₂ Hydrides

[X. Wang, et al., Int. J. Hydrogen Energy 36 (2011) 9079-9085.]




Fig. 6 – Schematic diagram of hydrogen compression system.

- 1st stage Alloy: Ti_{0.95}Zr_{0.05}Cr_{0.8}Mn_{0.8}V_{0.2}Ni_{0.2}
- 2nd stage Alloy: Ti_{0.8}Zr_{0.2}Cr_{0.95}Fe_{0.95}V_{0.1}
- Circulated cold (~300 K) and hot (~423 K) oil in beds
- Periodic Pressurization steps and not continuous supply of 700 bar H₂ gas




Fig. 7 – Compression performance of the two-stage compression system.

REVIEWER-ONLY SLIDES

Critical Assumptions and Issues

Issue: Given the fundamental limitation of metal hydride heats of formation, a two-stage MH compressor cannot inherently meet energy efficiency or H₂ delivery cost requirements

Solution: Demonstrate practical application(s) where waste heat from co-located equipment can be used to meet energy requirements and/or low cost heat can be used to meet cost requirements

Assumption: At least one LP and one HP alloy can be obtained that compress hydrogen from 100 bar to 875 bar within reasonable operating temperatures with degradation less than 20% of initial capacity over ~1000 cycles or can be regenerated

Solution: FY17 characterization studies and FY18 degradation studies will prove or disprove this assumption

Issue: Challenging to design compressor beds (especially to >875 bar) that maximize energy efficiency by minimizing sensible heating, thermal losses, and void volume while also maximizing H₂ flow rate

Solution: FY17 design studies along with supporting analyses using the system-level dynamic model should address this issue.

Publications and Presentations

- Johnson, T. A., Oral Presentation at Joint CSTT-HDTT Meeting, “Metal Hydride Compressor for High-Pressure (≥ 875 bar) Hydrogen Delivery,” Golden, CO, Nov. 2, 2016
- Bowman, R., Oral Presentation at Joint HSTT-HDTT Meeting, “Metal Hydride Compressor for High-Pressure (≥ 875 bar) Hydrogen Delivery,” Southfield, MI, Feb. 16, 2017
- Bowman, R., Oral Presentation at 11th International Symposium on Hydrogen & Energy, “Status of High-Pressure Metal Hydride Compressors for Applications Exceeding 700 Bar,” Waikoloa, HI, Feb. 28, 2017