


Pulsed power performance of the Z machine: *ten years after the upgrade*

SAND2017-7687C



**M.E. Savage, K.N. Austin, B.T. Hutsel, R.J. Kamm, G.R.
McKee, W.A. Stygar, P.E. Wakeland, W.M. White**




Sandia National Laboratories is a multimission laboratory managed and operated by National Technology and Engineering Solutions of Sandia, LLC, a wholly owned subsidiary of Honeywell International, Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.

Summary

- The Z machine is a low-impedance fast driver that delivers megajoules of magnetic energy to cm^3 volumes
- The 110 ns time to peak current requires megavolts from the pulse-forming section:
 - 6 MV Marx generators
 - 6 MV gas switches
 - 6 MV vacuum insulator
- Z can deliver megabar pressures, and hundreds of terawatts of X-rays
- Late-time energy is the scourge of a large machine, and component design and energy diversion are critical


The Z machine has multiple uses

- **Megabar pressure source for dynamic compression of solid materials**
- **Radiation source for effects testing**
- **Drive source for inertial confinement fusion studies**



Z is expected to perform a high-quality, fully diagnosed physics experiment every working day


Z is all about power



Introduction



- As an operating user facility, Z allows unique access to performance data on pulsed power mainstay components at extreme levels:
 - More than two thousand energy-storage capacitors (85 kV, 160 kA)
 - Thirty-six laser triggered SF6-insulated switches (6 MV, 600 kA)
 - Thirty-six water insulated transmission lines (6 MV, 700 kA)
 - Thirty-six self-closing water switches (3 MV, 700 kA)
 - Four water/plastic/vacuum interfaces (150 kV/cm, 7 MA, 21 m²)
 - Post-hole current addition and inductive load (2 MV, 27 MA)

Z is a system of 36 largely independent modules driving a common load




Marx generators

The Z Marx generators deliver 100s of kJ at 6MV



Capacitor reliability is important



Total capacitor failures

1000

100

10



1

1





Laser triggered gas switches

The 6 MV laser triggered gas switch determines load current timing and pulse shape





The LTGS withstands 6 MV and 600 kA



Ratio of charge time to 1- σ jitter: ~300


A new LTGS triggers more reliably



Gas switch spread does not appreciably contribute to load current rise time


10%-90% rise times:

- Total current: 68.7 ns
- Gas switch closure: 10.4 ns
- **Quadrature difference: 67.9 ns**



Accurate data analysis guides maintenance work on Z

- Visual review of every signal is tedious, error-prone and unnecessary
- Generally, we compare each signal to a reference (known good signal, circuit model, or analytic calculation) and use the entire waveform
- In every case, we use multiple waveform points and fit calculations to assess the result



Laser triggered gas switch run time calculation

Water pulse-forming section


Late-time breakdown can damage metal structure

- Breakdown that affects the shot is rare, but damaged parts must be replaced



To enhance reliability, Z uses nonlinear energy diverters

- Late-time energy is not beneficial and can cause damage that must be repaired before the next shot



Water-vacuum interface


The water-vacuum interface operates with large mechanical stress

- 3.5 m diameter
- 1 MN axial vacuum load
- 60 kN compression
- 2 MN radial force on plastic
- 5G, 40 Hz acceleration of the entire assembly




The Z water-vacuum interface operates at 150 kV/cm peak field

- Before Z data, it was not known what insulator stress could be tolerated on damaged insulators



The delivered current is reproducible

- Five nominally identical experiments
 - Timing 900 ps 1- σ
 - Amplitude 0.24% 1- σ



Conclusions

- Operating Z is a learning experience because it is unique
- Z provides a useful combination of high magnetic pressure, fast rise time, variable pulse shapes and a shot every day
- Z shots can be reproducible to the nanosecond and 1% level
- Six-MV triggered gas switches have been developed to be reliable and low jitter
- The water-vacuum interface operates routinely at 150 kV/cm

Keeping Z working

