

Thermal-Hydraulic Measurements in Support of Model Validation for Dry Cask Storage

Sam Durbin, Eric Lindgren, and Ramon Pulido
Principal Member of the Technical Staff
Sandia National Laboratories


Nuclear Waste Technical Review Board
Albuquerque, NM
October 24, 2018

Overview




Aboveground Storage

Source: www.nrc.gov/reading-rm/doc-collections/fact-sheets/storage-spent-fuel-fs.html



Belowground Storage

Source: www.holtecinternational.com/productsandservices/wasteandfuelmanagement/hi-storm/



- Purpose: Validate assumptions in CFD calculations for spent fuel cask thermal design analyses
 - Used to determine steady-state cladding temperatures in dry casks
 - Needed to evaluate cladding integrity throughout storage cycle
- Measure temperature profiles for a wide range of decay power and helium cask pressures
 - Mimic conditions for above and belowground configurations of vertical, dry cask systems with canisters
 - Simplified geometry with well-controlled boundary conditions
 - Provide measure of mass flow rates and temperatures throughout system
- Use existing prototypic BWR Incoloy-clad test assembly

Past Validation Efforts







FIGURE 4-1. SAHTT Assembly

- Full scale, multi-assembly
 - Castor-V/21 [1986: EPRI NP-4887, PNL-5917]
 - Unconsolidated, unpressurized, unventilated
 - REA 2023 [1986: PNL-5777 Vol. 1]
 - Unconsolidated, unpressurized, unventilated
 - VSC-17 [1992: EPRI TR-100305, PNL-7839]
 - Consolidated, unpressurized, early ventilated design
- Small scale, single assembly
 - FTT (irradiated, vertical) [1986 PNL-5571]
 - SAHTT (electric, vertical & horizontal) [1986 PNL-5571]
 - Mitsubishi (electric, vertical & horizontal) [1986 IAEA-SM-286/139P]
 - For all three studies:
 - Unconsolidated
 - BC: Controlled outer wall temperature (unventilated)
 - Unpressurized
- None appropriate for elevated helium pressures or modern ventilated configurations





Current Approach



- Focus on pressurized canister systems
 - DCS capable of 2,400 kPa internal pressure @ 400 °C
 - Current commercial designs up to ~800 kPa
- Ventilated designs
 - Aboveground configuration
 - Belowground configuration
 - With crosswind conditions
- Thermocouple (TC) attachment allows better peak cladding temperature measurement
 - 0.030" diameter sheath
 - Tip in direct contact with cladding
- Provide validation quality data for CFD
 - Complimentary to High-Burnup Cask Demo. Project



DCS Pressure Vessel Hardware

- Scaled components with instrumentation well
- Coated with ultra high temperature paint



Prototypic Assembly Hardware

Upper tie plate




Nose piece and
debris catcher




BWR channel, water tubes
and spacers

- Most common 9×9 BWR in US
- Prototypic 9×9 BWR hardware
 - Full length, prototypic 9×9 BWR components
 - Electric heater rods with Incoloy cladding
 - 74 fuel rods
 - 8 of these are partial length
 - Partial length rods 2/3 the length of assembly
 - 2 water rods
 - 7 spacers



Thermocouple Layout



Internal Thermocouples

Radial Array

24" spacing

11 TC's each level

66 TC's total (details below)

• Axial array A1

6" spacing

20 TC's




■ Axial array A2

12" spacing – 7 TC's


Water rods inlet and exit – 4 TC's

Total of 97 TC's

- 97 total TC's internal to assembly
- 10 TC's mounted to channel box
 - 7 External wall
 - 24 in. spacing starting at 24 in. level
 - 3 Internal wall
 - 96, 119, and 144 in. levels




Internal Dimensional Analyses



- Internal flow and convection near prototypic
 - Prototypic geometry for fuel and basket
- Downcomer scaling insensitive to wide range of decay heats
 - External cooling flows matched using elevated decay heat
 - Downcomer dimensionless groups

Parameter	Aboveground		
	DCS Low Power	DCS High Power	Cask
Power (kW)	0.5	5.0	36.9
Re_{Down}	170	190	250
Ra_H^*	3.1E+11	5.9E+11	4.6E+11
Nu_H	200	230	200


External Dimensional Analyses



- External cooling flows evaluated against prototypic
 - External dimensionless groups

Parameter	Aboveground		
	DCS Low Power	DCS High Power	Cask
Power (kW)	0.5	5.0	36.9
Re_{Ex}	3,700	7,100	5,700
Ra_{DH}^*	2.7E+08	2.7E+09	2.3E+08
$(D_{H, Cooling} / H_{PV}) \times Ra_{DH}^*$	1.1E+07	1.1E+08	4.8E+06
Nu_{DH}	16	26	14


Aboveground Configuration




- BWR Dry Cask Simulator (DCS) system capabilities
 - Power: 0.1 – 20 kW
 - Pressure vessel
 - Vessel temperatures up to 400 °C
 - Pressures up to 2,400 kPa
 - ~200 thermocouples throughout system (internal and external)
 - Air velocity measurements at inlets
 - Calculate external mass flow rate
- *Testing Completed August 2016*
 - 14 data sets collected
 - Transient and steady state
 - Ongoing validation exercises

Steady State Values vs. Decay Heat

Aboveground Configuration





- PCT and air flow $\uparrow$ as simulated decay heat $\uparrow$
 - Significant increase in PCT for $P = 0.3$ kPa
 - Due to air in “canister” instead of helium






Graphical Steady State Comparisons

Aboveground Configuration



- PCT average difference of 2 K across all conditions
 - 95% exp. uncertainty
 - +/- 1% reading in Kelvin
 - ($U_{PCT, max} = 7$ K)
 - Max. observed difference = 9 K
 - (5 kW and 4.5 bar)
- Air flow rate average difference of 6.2E-4 kg/s for all conditions
 - 95% exp. uncertainty of $U_{\dot{m}} = 1.5E-3$ kg/s
 - Max. observed difference = -1.6E-3 kg/s
 - (5 kW and 800 kPa)


Belowground Configuration






- Modification to aboveground ventilation configuration
 - Additional annular flow path
- *Testing Completed April 2017*
 - 14 data sets recorded
 - Transient and steady state

Steady State Values vs. Decay Heat

Belowground Configuration





- Similar performance to aboveground configuration
 - Within 2% for PCT
 - Within 5% for $\dot{m}$




Graphical Steady State Comparisons

Belowground Configuration





- PCT average difference of 6 K across all conditions
 - 95% exp. uncertainty of $U_{PCT, max} = 7$ K
 - Max. observed difference = 16 K
 - (5 kW and 100 kPa)
- Air flow rate lower for experiment
 - 95% exp. uncertainty of $U_{\dot{m}} = 7E-4$ kg/s
 - Max. observed difference = $5E-3$ kg/s
 - (5 kW and 450 bar)



Non-uniformities
at flow
straightener
seams



Cross Wind Testing




- Wind machine installed inside test enclosure
 - Three air-driven blowers
 - Specially fabricated duct with flow straightening
 - Cross winds of up to 5.4 m/s (12 mph)





**CFD simulations
by A. Zigh (USNRC)**

Reduction of External Air Flow Rate



- Moderate, sustained cross winds have significant impact on external air mass flow rate
 - Reductions of up to 50%
 - Thermal impact limited for DCS
 - Potentially more significant effect for prototypic systems



Summary

- Dry cask simulator (DCS) testing complete for all configurations
 - Over 40 unique data sets collected
 - 14 each for two primary configurations
 - Aboveground and belowground
 - 13 additional data sets for cross-wind testing
- Comparisons with CFD simulations show favorable agreement
 - Within experimental uncertainty for nearly all cases
 - Additional steady state comparisons for basket, “canister”, and “overpack” also show good agreement

Future Testing

Thermal-Hydraulic Testing and Modeling Activities

- Phase I: BWR Dry Cask Simulator at SNL
 - Mockup of 1 BWR assembly in convective heat transfer
 - Thermocouples attached directly to cladding
 - NRC has modeled the results
 - PNNL and Spain to model using the input deck provided by SNL

Previous SNL slides


Ongoing Work
- Phase II: HBU Demonstration Cask
 - Multiple activities as outlined previously

Previous PNNL Presentation
- Phase III: Ongoing and Future Thermal-Hydraulic Studies
 - Horizontal Dry Cask Simulator
 - Advanced simulators
 - Potential collaboration with South Korea under the High Level Bilateral Commission studies


These slides

Modification of the Dry Cask Simulator

- Horizontal Simulation
 - Place single assembly dry cask simulator in a horizontal position
 - Enclose pressure vessel to simulate vault
 - Monitor air flow through inlet ducts
 - Hot wire anemometers
 - Measure temperatures for various powers
 - Fill to prototypic internal helium pressures




Assembly Modifications



- DCS presently deconstructed
- Convert to horizontal
 - Outer shell and inner shells removed
 - Pressure vessel opened
 - Basket removed
- Maintain concentricity and enhance heat conduction
 - Add stabilizers
 - Between channel box and basket
 - Between basket and canister wall
 - Full length to limit convective cells
 - Keep from damaging existing TC's
- Reassemble and move

Facility Transition



- After performing in-vessel modifications
- Move DCS from inside vessel to the 3rd floor
- GENTLY rotate assembly to horizontal configuration
- Construct “vault” enclosure
 - Inlet and outlets
- Install additional instrumentation
- Reconnect to DAQ
 - Power control
 - Instrumentation
- Conduct testing

Advanced Simulators

- Explore various concepts
 - Limited number of full-length assemblies
 - Inter-assembly heat transfer
 - Scaled assemblies
 - Simplified but representative mock fuel assemblies
 - Better simulation of prototypic cask loadings
- Investigate known sources of modeling uncertainties
 - Basket-to-canister contacts
 - Boral construction
- Refine best practice guidelines
 - Offer insights for selection of modeling assumptions
 - Further understanding of uncertainties