

SANDIA REPORT

SAND2020-4000 - Unlimited Release

Printed April 9, 2020



Sandia
National
Laboratories

SIERRA Multimechanics Module: Aria User Manual – Version 4.56

SIERRA Thermal/Fluid Development Team

Prepared by
Sandia National Laboratories
Albuquerque, New Mexico 87185
Livermore, California 94550

Issued by Sandia National Laboratories, operated for the United States Department of Energy by National Technology & Engineering Solutions of Sandia, LLC.

NOTICE: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, make any warranty, express or implied, or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represent that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof, or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof, or any of their contractors.

Printed in the United States of America. This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from

U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831

Telephone: (865) 576-8401
Facsimile: (865) 576-5728
E-Mail: reports@osti.gov
Online ordering: <http://www.osti.gov/scitech>

Available to the public from

U.S. Department of Commerce
National Technical Information Service
5301 Shawnee Road
Alexandria, VA 22312

Telephone: (800) 553-6847
Facsimile: (703) 605-6900
E-Mail: orders@ntis.gov
Online order: <https://classic.ntis.gov/help/order-methods>



ABSTRACT

Aria is a Galerkin finite element based program for solving coupled-physics problems described by systems of PDEs and is capable of solving nonlinear, implicit, transient and direct-to-steady state problems in two and three dimensions on parallel architectures. The suite of physics currently supported by Aria includes thermal energy transport, species transport, and electrostatics as well as generalized scalar, vector and tensor transport equations. Additionally, Aria includes support for manufacturing process flows via the incompressible Navier-Stokes equations specialized to a low Reynolds number ($Re < 1$) regime. Enhanced modeling support of manufacturing processing is made possible through use of either arbitrary Lagrangian-Eulerian (ALE) and level set based free and moving boundary tracking in conjunction with quasi-static nonlinear elastic solid mechanics for mesh control. Coupled physics problems are solved in several ways including fully-coupled Newton's method with analytic or numerical sensitivities, fully-coupled Newton-Krylov methods and a loosely-coupled nonlinear iteration about subsets of the system that are solved using combinations of the aforementioned methods. Error estimation, uniform and dynamic h -adaptivity and dynamic load balancing are some of Aria's more advanced capabilities.

ACKNOWLEDGMENTS

Aria represents a new generation code implementation of heat transfer algorithms. The mathematical models described herein would never have been implemented without the efforts of the Calore development team: Bob Cochran, Mike Glass, Randy Lober, Chris Newman, Steve Bova and Tolu Okusanya. Bruce Bainbridge, Ben Blackwell, Merlin Decker, Kevin Dowding and Vicente Romero made significant contributions to the development and testing of Calore. Many of the algorithms implemented in Calore were first implemented in COYOTE, and therefore we are indebted to David Gartling, Roy Hogan, and others who contributed to its development. In particular, the algorithms associated with chemistry were developed by Mel Baer.

The basic capabilities of Calore were implemented in Aria by Patrick Notz and Samuel Subia. Further implementation of new capabilities by the Sierra T/F code team is a continuing effort. The following Sandia staff have been involved with the Aria project, either in code development, math model definitions, or requirements definition: Adrian Kopacz, Alec Kucala, Alex Toth, Brian Carnes, Chris Luchini, Dan Turner, Daniel Moser, David Baur, David Glaze, David Noble, Elizabeth Armstrong, Flint Pierce, Greg Wagner, Harry Moffat, Jason Sanchez, John Tencer, Jonathan Clausen, Ken Franko, Lindsay Erickson, Malachi Phillips, Mark Hoemmen, Matt Kury, Matthew Hopkins, Mike Hansen, Pat Notz, Philip Sakievich, Richard Drake, Samuel Subia, Scott Roberts, Stefan Domino, Steve Bova, Tolu Okusanya, Tyler Voskuilen, and Victor Brunini.

CONTENTS

Contents	5
List of Figures	20
List of Tables	22
1. Introduction	23
1.1. Overview	23
1.2. A Brief History of Aria	23
1.3. Nonlinear Coupling Strategies in Aria	24
1.4. Constraints Equations within Aria	25
1.5. Level Set Algorithm	25
1.6. “Production” vs. “Experimental” Code and Known Issues	26
1.7. Outline of the Manual	26
2. Getting Started	28
2.1. Setting The Environment-Users External to Sandia Labs	28
2.2. Setting Up Your Environment-Users at Sandia Labs	28
2.3. Running Aria	28
2.4. Platform-Specific Guidelines	29
2.5. Aria Environment Overview	29
2.6. Overview of the Input File Structure	31
2.7. Fields	36
2.8. Equations	39
2.9. Equation String-Naming Convention	39
2.10. Internal Field Definition	39

2.II.	User Fields	40
3.	Model Definition	41
3.I.	Model Overview	41
3.2.	Finite Element Model	46
3.3.	Parameters For Block	51
3.4.	Uniform Mesh Refinement	54
3.5.	Timing Overview	55
3.6.	Global Constants	55
3.7.	Function Overview	58
3.8.	Definition For Function	58
3.9.	Values	67
3.I0.	Restarting	68
4.	Material Properties	69
4.I.	Aria Material Overview	69
4.2.	BAR AREA	577
4.3.	BETA	577
4.4.	BULK VISCOSITY	579
4.5.	CTE	581
4.6.	CURRENT DENSITY	583
4.7.	DENSITY	584
4.8.	ELECTRICAL CONDUCTIVITY	591
4.9.	ELECTRIC DISPLACEMENT	595
4.I0.	ELECTRICAL PERMITTIVITY	595
4.II.	ELECTRICAL RESISTANCE	596
4.I2.	EMISSIVITY	599
4.I3.	ENTHALPY	602
4.I4.	EQUATION OF STATE	603
4.I5.	HEAT CONDUCTION	604
4.I6.	HEAT OF VAPORIZATION	606

4.17.	HEAT TRANSFER COEFFICIENT	607
4.18.	INTRINSIC PERMEABILITY	610
4.19.	INTERNAL ENERGY	610
4.20.	LEVEL SET HEAVISIDE.....	612
4.21.	LEVEL SET WIDTH	612
4.22.	LUBRICATION HEIGHT LOWER.....	613
4.23.	LUBRICATION HEIGHT UPPER	613
4.24.	LUBRICATION K	614
4.25.	LUBRICATION VELOCITY LOWER.....	615
4.26.	LUBRICATION VELOCITY UPPER	616
4.27.	MASS FLUX	616
4.28.	MESH LAMBDA	617
4.29.	MESH TWO MU	619
4.30.	MESH STRESS	620
4.31.	MOLECULAR WEIGHT	624
4.32.	MOMENTUM STRESS	625
4.33.	POISSONS RATIO	629
4.34.	POROSITY	630
4.35.	RADIATION FORM FACTOR	632
4.36.	RADIATIVE CONDUCTIVITY.....	635
4.37.	RELATIVE PERMEABILITY	638
4.38.	SEEBECK COEFFICIENT	640
4.39.	SHELL THICKNESS.....	643
4.40.	SKELETON DENSITY	643
4.41.	SKELETON INTERNAL ENERGY	644
4.42.	SKELETON SPECIFIC HEAT	646
4.43.	SOLID LAMBDA.....	648
4.44.	SOLID TWO MU	650
4.45.	SOLID STRESS	652
4.46.	SPECIES DIFFUSION	655

4.47.	SPECIES DIFFUSIVITY	656
4.48.	SPECIFIC HEAT	658
4.49.	PHASE CHANGE SPECIFIC HEAT	663
4.50.	SURFACE TENSION	664
4.51.	SUSPENSION FLUX	666
4.52.	THERMAL CONDUCTIVITY	666
4.53.	THERMAL DIFFUSIVITY	674
4.54.	TOTAL INTERNAL ENERGY	676
4.55.	VALENCE	677
4.56.	VISCOSITY	679
4.57.	FLOWING LIQUID VISCOSITY	688
4.58.	VOLUME FRACTION GAS	689
4.59.	YOUNGS MODULUS	692

5. Equations Aria Solves 694

5.1.	Generalized Conservation Equation	694
5.2.	Conservation of Mass	695
5.3.	Conservation of Energy	695
5.4.	Conservation of Chemical Species	697
5.5.	Conservation of Fluid Momentum	698
5.6.	Conservation of Solid Momentum	699
5.7.	Voltage Equation	700
5.8.	Current Equation	701
5.9.	Charge Density Equation	701
5.10.	Ampere Equation	702
5.11.	Suspension Equation	703
5.12.	Porous Flow Equations	703
5.13.	Brinkman Momentum	714
5.14.	Lubrication Equation	715
5.15.	Stress Tensor Projection Equation	715

5.16.	Potential Projection Equation	716
5.17.	Notes on Solid Mechanics	717
5.18.	Units and Unit Conversions	719

6. Equation Specification 724

6.1.	EQ CONTINUITY	725
6.2.	EQ CURRENT	726
6.3.	EQ CHARGE_DENSITY	726
6.4.	EQ ENERGY	727
6.5.	EQ LEVEL_SET	727
6.6.	EQ EXTENSION_SPEED	728
6.7.	EQ MASS_BALANCE	728
6.8.	EQ MESH	729
6.9.	EQ MOMENTUM	729
6.10.	EQ POROUS_SPECIES	730
6.11.	EQ POROUS_ENTHALPY	731
6.12.	EQ POTENTIAL	731
6.13.	EQ PROJECTION	732
6.14.	EQ SOLID	733
6.15.	EQ SPECIES	733
6.16.	EQ SP	734
6.17.	EQ SUSPENSION	735
6.18.	EQ VOLTAGE	735
6.19.	EQ BRINKMAN_MOMENTUM	736
6.20.	EQ LUBRICATION	736
6.21.	EQ STRESS_TENSOR_PROJECTION	737
6.22.	ELASTICITY FORMULATION	737
6.23.	PRESSURE STABILIZATION	738
6.24.	SAVE RESIDUALS	739
6.25.	INTEGRATION RULE	739

6.26.	MESH GROUP	740
6.27.	ADVECTION VELOCITY	740
7.	Data for Material, BC, IC, SRC	742
7.1.	Data Block	742
8.	Initial Conditions	744
8.1.	IC CIRC_X	745
8.2.	IC CIRC_Y	745
8.3.	IC CONSTANT	745
8.4.	IC COUETTE_X	746
8.5.	IC COUETTE_Y	746
8.6.	IC COUETTE_SH	747
8.7.	IC READ_FILE	747
8.8.	IC LINEAR	748
8.9.	IC PARAB	749
8.10.	ANNEAL MESH ON STARTUP	749
9.	Boundary Conditions	750
9.1.	BC Dirichlet	750
9.2.	BC FLUX	764
9.3.	Periodic BC Overview	1034
9.4.	Periodic	1035
9.5.	Coupling BCs for Organic Material Decomposition	1038
9.6.	BC EDGE	1040
10.	Distinguishing Conditions	1041
10.1.	An Introduction to Distinguishing Conditions	1041
10.2.	BC DISTING	1041
11.	Volumetric Sources	1046
11.1.	POINT SOURCE FOR	1046

11.2.	VECTOR POINT SOURCE FOR...	1047
11.3.	SOURCE FOR ENERGY	1048
11.4.	SOURCE FOR MOMENTUM	1057
11.5.	SOURCE FOR CURRENT	1060
11.6.	SOURCE FOR SPECIES	1062
11.7.	SOURCE FOR POROUS_SPECIES	1064
11.8.	SOURCE FOR VOLTAGE	1064
11.9.	SOURCE FOR POTENTIAL	1065
11.10.	SOURCE FOR MESH	1066
11.11.	SOURCE FOR SOLID	1067
12.	Constraint Conditions	1068
12.1.	CONSTRAIN	1068
12.2.	Submodel	1069
13.	Element Death	1072
13.1.	Standard Element Death	1072
13.2.	CDFEM Element Death	1073
13.3.	General Death Syntax	1073
13.4.	Element Death	1074
14.	Solution Control Reference	1076
14.1.	Overview	1076
14.2.	Solution Control Description	1084
14.3.	System	1085
14.4.	Transient	1089
14.5.	Nonlinear	1094
14.6.	Subcycle	1098
14.7.	Sequential	1102
14.8.	Initialize	1106

14.9.	Parameters For	1107
15.	Transfer Reference	1116
15.1.	Overview	1116
15.2.	Transfer	1122
16.	Time Integration Commands	1132
16.1.	Setting Up a Transient Problem	1132
16.2.	Initial Time Step Estimation for Thermal Problems	1133
16.3.	Fixed Time Step Selection	1135
16.4.	Adaptive Time Step Selection	1136
16.5.	Parameters For Aria Region	1142
16.6.	Other Timestep Related Commands	1156
16.7.	Predictor Related Commands	1157
17.	Nonlinear Solution Strategy	1159
17.1.	Equation System Overview	1159
17.2.	Global Solution For Equation Systems	1160
17.3.	Nonlinear Solution Specifications	1163
18.	Writing User Plugins	1171
18.1.	About Plugins	1171
18.2.	Compiling and Using Plugins with Dynamically Loaded Libraries	1171
18.3.	An Important Note About Model Names	1173
18.4.	The Input File	1173
18.5.	Example Plugin Code: My_Density.C	1174
18.6.	Testing Your Plugin	1178
19.	Dynamic Load Balancing	1180
19.1.	ENABLE REBALANCE	1180
19.2.	REBALANCE LOAD MEASURE	1181
19.3.	MAXIMUM NUMBER OF REBALANCES	1181

19.4.	REBALANCE TIME STEP FREQUENCY	1182
20.	Linear Solver Reference	1183
20.1.	Overview	1183
20.2.	Tpetra Equation Solver	1186
20.3.	Trilinos Equation Solver	1200
20.4.	Aztec Equation Solver	1211
20.5.	Gdsw Equation Solver	1220
21.	Postprocessing Operations	1225
21.1.	Overview	1225
21.2.	Solution Options	1228
21.3.	Residual Based Integrated Surface Flux Calculations	1232
21.4.	Postprocessing flux global variables and fields on specified sidesets	1234
22.	Enclosure Radiation Reference	1237
22.1.	Enclosure Radiation	1237
22.2.	Enclosure Radiation Surface Flux	1239
22.3.	Solution Strategy	1240
22.4.	Banded Wavelength Enclosure Radiation	1241
22.5.	Enclosure Radiation Modeling	1242
22.6.	Viewfactor Calculation	1248
22.7.	Viewfactor Smoothing	1254
22.8.	Radiosity Solver	1257
22.9.	Enclosure Definition	1259
22.10.	Banded Wavelength Model	1278

22.II.	Band	1279
23.	SPn Radiation Reference	1283
23.I.	Radiative Transport	1283
24.	Contact Reference	1285
24.I.	Contact Overview	1285
24.2.	Contact Definition	1287
24.3.	Enforcement	1291
24.4.	Enforcement Models	1297
24.5.	Interaction	1307
24.6.	Search Options	1308
25.	Output Reference	1310
25.I.	Output Overview	1310
25.2.	Results Output	1311
25.3.	Heartbeat	1325
25.4.	History Output	1334
25.5.	Data Probe	1342
25.6.	Restart Overview	1346
25.7.	Restart Data	1346
26.	Input Output Region Reference	1357
26.I.	Input_Output Region Overview	1357
26.2.	Input_Output Region	1358
27.	Log File Output	1363
27.I.	Introduction	1363
27.2.	Preamble	1363
27.3.	Run-time Reporting	1367
27.4.	Run Summary	1376

27.5.	Summary	1380
28.	Diagnostic Output	1381
28.1.	About Diagnostic Streams	1381
28.2.	Diagnostic Output Command Reference	1382
28.3.	Diagnostic Control	1382
29.	Level Set Reference	1386
29.1.	Level Set Overview	1386
29.2.	Level Set Interface	1386
29.3.	Level Set Initial Conditions	1390
29.4.	Analytic Initial Condition	1391
30.	Local Coordinate System Reference	1396
30.1.	Local Coordinate Systems	1396
30.2.	Local Coordinate System	1398
31.	Bulk Volume Reference	1401
31.1.	Bulk Volume Element	1401
31.2.	Bulk Fluid Element	1403
31.3.	Closed Surface Volume	1408
31.4.	Restarting With Bulk Volume Element	1409
31.5.	Bulk Node Coupling	1410
32.	Toggle Reference	1412
32.1.	Feature Toggling	1412
32.2.	Toggle Block	1415
33.	Thermal Analysis Reference	1418
33.1.	General Thermal Analysis	1418
33.2.	Checking Conservation	1419
33.3.	Non-physical Temperature Solutions	1419
33.4.	Initial Condition	1420

33.5.	Temperature Boundary Condition	1423
33.6.	Heat Flux Boundary Condition	1428
33.7.	Laser Heat Flux Boundary Condition	1437
33.8.	Convection Heat Transfer	1447
33.9.	Convective Flux Boundary Condition	1447
33.10.	Aerodynamic Convection Heat Transfer	1460
33.11.	Aero Heat Flux Boundary Condition	1461
33.12.	Advective Bar	1475
33.13.	Advective Bar Network	1477
33.14.	Radiative Flux Boundary Condition	1484
33.15.	User Variable	1496
33.16.	Volume Heating	1499
33.17.	Laser Heating	1507
33.18.	Closed Surface Volume	1517
33.19.	Real and Integer Data Access - Data Block	1518
33.20.	User Subroutines and Variables	1524
33.21.	C Calore-Style User Subroutines and Variables	1525
33.22.	FORTRAN-like C Interfaces	1528
33.23.	FORTRAN-like C Interface Functions	1545
33.24.	Debug Output From User Subroutines	1552
33.25.	FORTRAN User Subroutines	1555
33.26.	FORTRAN Interfaces	1556
33.27.	FORTRAN Subroutine Interface Functions	1563
33.28.	Solution Mapping Methodology	1566

34. Correlation Heat Transfer Coefficient Reference

1572

34.1.	Heat Transfer Coefficient Correlation Library	1572

34.2.	Heat Transfer Correlation Coefficient	1584
35.	Chemistry Overview	1593
35.1.	Feature Comparison	1593
36.	CHEMEQ Reference	1595
36.1.	Common Input Style	1595
36.2.	Chemical Heating	1595
36.3.	Alternate Reaction Models	1597
36.4.	Concentration Units	1597
36.5.	Numerical Solution	1598
36.6.	Parameters For Chemeq Model	1599
36.7.	Chemeq Solver For	1607
37.	General Chemistry Reference	1616
37.1.	Introduction	1616
37.2.	Required Prerequisites	1617
37.3.	General Chemistry	1618
37.4.	Molar Formulation of Chemical Mechanism	1624
37.5.	Mass Formulation of Chemical Mechanism	1627
37.6.	Specifying Standard States for Species Enthalpy	1630
37.7.	Heterogeneous Reaction Energy Term	1630
37.8.	Reaction Block Overview	1631
37.9.	Reaction Units	1632
37.10.	Reaction Inputs	1632
38.	Chemistry Solver Reference	1643
38.1.	Introduction	1643
38.2.	Solution Approaches	1643
38.3.	ODE Solver Parameters	1644

38.4.	Chemistry Solver Parameters For	1646
39.	Pressurization Model Reference	1649
39.1.	Pressurization Zones	1649
39.2.	Pressurization Model	1654
40.	Burn Front Model Reference	1660
40.1.	Burn Front Model	1660
41.	Solution Options	1662
41.1.	Solution Options	1662
41.2.	Cvfem Algorithm Specification	1667
41.3.	Porous Flow Options	1678
41.4.	Turbulence Model Specification	1679
41.5.	Edc Model Specification	1684
41.6.	Oxidizer Mixture Specification	1688
42.	String Functions	1690
42.1.	Expression Evaluation	1690
42.2.	Scalar String Functions	1697
42.3.	Vector String Functions	1698
42.4.	Tensor String Functions	1698
42.5.	Using Conditional Operators	1698
43.	Frequently Asked Questions	1699
43.1.	General	1700
43.2.	Capability	1702
43.3.	Errors	1704
43.4.	Solver	1705
43.5.	Thermal	1706
43.6.	Radiation	1710
43.7.	Time Stepping	1711

43.8.	Contact	1712
43.9.	Species	1713
43.10.	Porous Media	1714
43.11.	Electrostatics	1716
43.12.	Grid Refinement	1717
43.13.	Post Processing	1718
44.	Developer Documentation	1722
44.1.	Setting The Environment-Developers at Sandia Labs	1722
44.2.	An Introduction to Aria's Expression System	1723
44.3.	Nonlinear Coupling Strategies in Aria	1725
44.4.	Developer Recipes	1726
44.5.	Expression Reference and API	1727
44.6.	Newton Sensitivity Checking for Expressions	1728
44.7.	Profiling	1728
44.8.	Purify: Memory Analysis and Debugging	1729
44.9.	Building Against Other Projects	1729
44.10.	Interfacing with MATLAB	1730
44.11.	Error Handling	1731
44.12.	Outputting User Information (Logging)	1734
44.13.	Catalogue of Assembly Kernel Expressions	1736
44.14.	Defining and Solving ODEs in Aria Plugins	1739
44.15.	Defining and Using Global Variables	1740
44.16.	Errors and Warnings How-To	1740
44.17.	Diagnostic Writer How-To	1746
44.18.	Timers and Timing How-To	1751
Glossary		1756
Bibliography		1757
Index		1761

LIST OF FIGURES

2.5-1. Schematic UML class diagram for the Expression subsystem.....	30
2.7-1. General format of Aria’s string-based naming convention for expressions. Fields in square brackets are optional.	37
2.9-1. General format of Aria’s string-based naming convention for equations. Fields in square brackets are optional.	39
3.1-1. Enumerated Block and Named Block Models.....	42
3.1-2. Enumerated Block and Named Block Syntax.	44
9.3-1. Standard and Cyclic Periodicity	1035
15.1-1. Valid Transfer Operations	1117
15.1-2. Invalid Transfer Operation	1118
16.2-1. Geometry and mesh of finned radiator problem. Dimensions are in inches.....	1134
16.2-2. Temperature ratio versus Fourier number for various Biot numbers.	1135
16.2-3. Temperature ratio versus Fourier number for various Biot numbers.	1136
16.4-1. Time Step Selection Schematic.	1141
22.1-1. Surface to surface interaction in enclosure radiation	1238
22.4-1. Emissivity Bands For Two-Surface Problem	1242
22.5-1. Discretization and Associated Closed Enclosure Surface.	1243
22.5-2. Discretization and Associated Partial Enclosure Surface.....	1243
22.5-3. Superposed Radiation Enclosures.	1245
22.5-4. Two-Body Radiative Transfer Model	1246
22.5-5. Two Surface Network Model	1246
22.5-6. View Factor Configuration	1246

22.5-7.Partial Enclosure Radiative Transfer Model	1247
22.5-8.Three Surface Network Model	1247
22.5-9.Three Surface Network Model ($\varepsilon_3 = 0$ and $\varepsilon_3 = 1$)	1248
24.1-1.Calculation of contact distance per integration point.	1286
30.1-1. A depiction of the available local coordinate system options and how they are constructed given ORIGIN, VECTOR, and POINT.	1397
33.12-1Interior Body Flow	1475
33.12-2Flow Entrance Effect Coordinate	1476
33.22-1Anisotropic conductivity Orientation within Cartesian frame.	1541
36.5-1.Chemistry Time Step Selection	1599
44.2-1.Schematic UML class diagram for the Expression subsystem.	1724

LIST OF TABLES

2.7-1. Valid values of the <Operator> prefix.	37
2.7-2. Valid values of the <Phase> suffix. Phase labels are used in level set calculations only. ...	38
2.7-3. Valid values of the <Component> suffix. In non-Cartesian coordinate systems these may refer to, for example, radial or angular components.	38
2.7-4. Examples of well formed string names for Aria Expressions.	38
5.18-1. Fundamental SI units.	720
5.18-2. SI magnitude prefixes.	720
5.18-3. SI derived units and their definitions.	721
5.18-4. CGS derived units and their definitions.	722
5.18-5. Units and conversion factors for force.	722
5.18-6. Units and conversion factors for pressure and stress.	722
5.18-7. Units and conversion factors for viscosity.	723
5.18-8. Units and conversion factors for density.	723
5.18-9. Units and conversion factors for thermal conductivity.	723
5.18-10. Units and conversion factors for heat-transfer coefficients.	723
28.1-1. Aria diagnostic output print masks.	1382
35.1-1. Feature table for CHEMEQ and General Chemistry.	1594
44.17-1. Diagnostic writer options for Framework (fmwkout).	1748
44.17-2. Diagnostic writer options for Aria (arialog).	1749

1. INTRODUCTION

1.1. OVERVIEW

The SIERRA Multimechanics Module: Aria, henceforth referred to as Aria for brevity, is an application implementing the finite element method (FEM) for solving systems of partial differential equations (PDEs). Foremost, Aria's development targets applications which involve incompressible flow (Navier-Stokes for $Re < 1$). However, the general design of Aria lends itself to the solution of systems of PDEs describing physical processes including energy transport, species transport with reactions, electrostatics and general transport of scalar, vector and tensor quantities in two and three dimensions both transient and direct to steady state. Moreover, different regions of the physical domain (i.e., the input mesh) may have either different materials and/or different collections of physics (viz., PDEs) defined on them. These systems of equations may be solved alone, in a segregated but coupled algorithm ("loosely coupled") or as a single, fully-coupled system. Additionally, Aria can be loosely coupled to the quasi-statics solid mechanics code Adagio using the coupling application Arpeggio.

Aria is able to accommodate meshes that utilize linear and quadratic elements in two and three dimensions. In two dimensions, Aria supports quadrilateral (4 and 9 node) and triangular (3 and 6 node) elements. In three dimensions, Aria supports hexahedral (8 and 27 node) and tetrahedral (4 and 10 node) elements. Moreover, meshes may be comprised of combinations of these elements (i.e., both quadrilateral and triangular elements in two dimensions).

The physical coordinates and mesh displacements are always interpolated in accordance with the input mesh, but other solution degrees of freedom may be interpolated using a lower order basis function. For example, if the input mesh is composed of 9 node (quadratic) quadrilateral elements, then the physical coordinates and mesh displacements (if active) will be interpolated using quadratic basis functions, whereas other degrees of freedom, e.g., temperature or voltage, could use linear shape functions.

Additional information concerning the project may be found at the Aria's home page, [Aria Users Homepage](#) [1], and at Aria's Trac wiki web site, [Aria Trac Wiki](#) [2]. Both of those web sites currently require access to Sandia's internal restricted network.

1.2. A BRIEF HISTORY OF ARIA

In many respects, the predecessor code to Aria is the highly successful Goma code. Although none of the Goma code is included in Aria, Goma has inspired many of the algorithm, design and implementation decisions in Aria. Several of the staff members who contributed to Goma have also contributed to Aria, either as developers or users and testers.

Like Goma, Aria's primary nonlinear algorithm is a full Newton-Raphson method with analytical sensitivities. However, Aria takes aspects of the implementation further by adding versatility in how the sensitivities are constructed and providing options for both finite-difference, and automatic differentiation sensitivities. Furthermore, Aria has a richer suite of nonlinear solver capabilities including matrix-free Newton-Krylov, methods and even loose coupling. Like its muse Goma, Aria includes a large suite of physics and capabilities which can be included in an analysis.

On December 5, 2000 Phil Sackinger initiated the Opera code which was to serve as a test bed for what would become Aria. The Opera code was patterned after the Calore code which is a thermal analysis GFEM code, but differed in many respects. At that time, no applications had been written on top of the Sierra Framework that used multiple degrees of freedom (e.g., velocity AND pressure) or that used multiple element type (e.g., linear and quadratic interpolations). Opera was created as an exploratory code, to determine what changes would need to be made to the Framework and to experiment with the Framework in constructing such an application. During this period, the principle developers of Opera were Phil Sackinger, Sam Subia and Matt Hopkins.

On November 20, 2001 Matt Hopkins made the first commit to the Aria code base, using Opera as the starting point. And thus Aria was born.

1.3. NONLINEAR COUPLING STRATEGIES IN ARIA

One of the difficulties with writing broadly applicable computational mechanics software is that developers can't take advantage of specific knowledge of the application domain in order to optimize the algorithm. Thus, in providing generality one sometimes sacrifices efficiency. One place this is evident in multiphysics modeling is in the choice of coupling strategies. While it is well understood that a fully coupled system solved with Newton's method utilizing analytic sensitivities is formally the most robust and correct approach to solving multiphysics applications it is also computationally expensive and complex to implement. Furthermore, while Newton's method has the fastest rate of asymptotic convergence its domain of convergence is often empirically observed to be smaller than other methods. Lastly, in some applications, certain subsets of the physics may be only weakly coupled so that a loosely coupled approach may be more computationally efficient. To address these concerns while remaining general and flexible Aria offers a number of options for nonlinear solution strategies and physics coupling.

In defining a problem in Aria, users configure one or more **Regions**. Each **Region** consists of one or more PDEs to be solved on some or all of the input mesh. All of the PDEs in each **Region** are solved in a tightly coupled (i.e., single matrix) manner using one of several nonlinear solution strategies available. Users may then define loose couplings between two or more **Regions**. For example, some or all of a solution from one **Region** may be transferred to another **Region** where it is treated as a constant, external field. The aggregate nonlinear problem including the contributions from all of the **Regions** may be iterated to convergence. The particulars of which physics are solved in each **Region** and the nonlinear solution strategy used within and between **Regions** is completely specified through the input file. Furthermore, an Aria user may pick a simple, minimal algorithm without needing to fit it into an overly-generalized worst-case scenario that represents the union of all possible algorithms.

Dynamically-specified loose coupling has many potential advantages that users may leverage. First, the resulting linear system is considerably smaller and contains far fewer off-diagonal contributions which can significantly increase the performance of linear solvers. Also, a resulting linear system may have a more attractive form, such as symmetric positive-definite, that permits the use of tailored iterative solutions techniques. Other extensions to loose coupling include subcycling of transient simulations where each **Region** may advance in time with its own time step size and in-core coupling to other Sierra applications.

1.4. CONSTRAINTS EQUATIONS WITHIN ARIA

Aria has a unique capability associated with the specification of global constraint equations. These may be used to specify conserved quantities that are not specifically specified as part of the equations set. For example, in some electrochemistry problems where current is specified as a boundary condition, the global conservation of charge neutrality must be imposed as an additional global condition.

Constraint equations have unique issues associated with their solution.

1.5. LEVEL SET ALGORITHM

Level set algorithms utilize a signed distance function F such that one material, or *phase*, is associated with regions of space where $F > 0$ and a different phase is associated with regions of space where $F < 0$. The curve or surface where $F = 0$ defines the interface between the two phases. In Goma and most other level set codes F is used to partition material property models such that the property has the appropriate values in each phase and, typically, transitions smoothly from one phase to the other. In Aria, however, F is used to partition contributions of the residual equations between the two phases.

In both cases the partitioning is done using a Heaviside function to partition the physical space into two phases which we'll label A and B . The Heaviside function $H_A(F)$ is defined such that $H_A(F) = 1$ in phase A and $H_A(F) = 0$ in phase B ; in the vicinity of $F = 0$ the Heaviside function may be defined to be a smooth function that transitions from 0 to 1. Likewise, $H_B(F) = 1$ in phase B and $H_B(F) = 0$ in phase A . In fact $H_B(F)$ is defined as $H_B(F) \equiv 1 - H_A(F)$.

In Goma, this Heaviside function is used to partition the material properties such that a material property σ is defined as

$$\sigma(F, \dots) = \sigma_A(\dots)H_A(F) + \sigma_B(\dots)H_B(F). \quad (1.1)$$

In Aria, however, the integrand of each residual equation is multiplied by the sum of Heaviside function so as to decompose the equation into contributions from each phase,

$$\int_V (\dots) dV \rightarrow \int_V H_A(F) (\dots) dV + \int_V H_B(F) (\dots) dV. \quad (1.2)$$

This formulation has a number of advantages. Material models are not functions of F so no special models need to be written and the input syntax is the same as well. Secondly, this approach is conservative for conservative governing equations. For example, the MASS and ADVECTION terms of the energy equation (see section 5.3) are proportional to ρC_p and hence, in Goma’s formulation, proportional to $H^2(F)$ where as the DIFFUSION term is proportional κ and hence proportional to $H(F)$. Thus, in the vicinity of the interface $F = 0$ energy is not transported correctly between these transport modes.

In Aria, each assembly kernel has an arbitrary list of coefficients that multiply the integrand of the kernel (see section 44.13). Thus, the formulation depicted in equation 1.2 is accomplished by simply adding the appropriate Heaviside function to the list of coefficients for each kernel associated with the equation.

1.6. “PRODUCTION” VS. “EXPERIMENTAL” CODE AND KNOWN ISSUES

Aria is a unique application code in that it contains both production and experimental code capabilities in the same codebase. Generally speaking, well-tested capabilities are more comprehensively documented and can be considered production-ready.

Documentation of code features which possess some level of maturity but are still under development will be marked as follows with possible caveats of usage.



Beta Capability: This feature is not sufficiently tested to be classified as a full production capability.

Documentation of code features which are strictly research or “experimental” capabilities may appear in the user manual will be designated as such with a warning.



Warning: This capability is currently being researched. Use at your own risk.

Although many code features in Aria are well-tested, there may be cases where combinations of “production” features may not function correctly together. When in doubt, one may always refer to sierra-help for guidance.

A compilation of known issues are contained in release notes for each major code release which occurs roughly every six months.

1.7. OUTLINE OF THE MANUAL

In chapter 2 we will discuss the overall environment for running Aria applications, including the layout for the Aria input deck. In chapter 5 we will present the general equations that are solved by Aria. These should be read by every user.

In later chapters, we will delve down to discuss individual line commands of the input deck. Chapter 6 discusses equation line cards (i.e., EQ), which serve to add individual equations with coupled independent unknowns to a coupled PDE representation of a region. Chapter 8 discusses how to apply initial conditions to the field variables associated with the equation sets. Chapter 9 presents the line commands associated with specifying boundary conditions. Chapter 10 introduces the concepts associated with distinguishing conditions. Chapter 11 introduces line commands associated with source terms.

2. GETTING STARTED

2.1. SETTING THE ENVIRONMENT-USERS EXTERNAL TO SANDIA LABS

To access Sierra/Aria one will likely need to setup the user environment. This setup will differ upon location and the local system administrator can provide information on setting up your local environment.

2.2. SETTING UP YOUR ENVIRONMENT-USERS AT SANDIA LABS

The environment for using Aria is the same as for individual Sierra applications and can be configured by module files. The modules ensure that the look and feel of running Sierra applications is the same across a multitude of compute platforms. To obtain the proper environment for code execution one simply runs:

```
$ module load sierra
```

2.3. RUNNING ARIA

This section includes some very simple examples of how to run Aria. For more information on running on some of Sandia's clusters, etc. see [\[3\]](#).

In its simplest form, Aria can be run like this:

```
$ sierra -np 1 aria -i ariarun.i
```

In this example, `ariarun.i` is the Aria input file. The output – nonlinear iterations, time step information, etc. – will be written to a file called `ariarun.log`. So, you can monitor the progress of the simulation by watching the log file. Alternatively, you can have all of the output sent to the screen by using the `-l logfile` command line option. If you set the log file to be `-` (a single “minus” character) all of the output will be sent to the standard output (usually your screen):

```
$ sierra -np 1 aria -i ariarun.i -l -
```

If you would like to use `aprepro` in your input file, add the `-a` command line option to have your input file automatically processed:

```
$ sierra -np 1 aria -i ariarun.i -l - -a
```

Oftentimes we want to run Aria remotely or locally in a batch mode, save any standard output and perhaps even log out from a session. Unfortunately, termination of the session through either voluntary (interactive) or involuntary (timeout) log-out may in effect terminate the Aria job. In this case one can prevent the job from terminating by using the Unix `nohup` command in conjunction with the standard execution command line.

```
$ nohup sierra -np 1 aria -i ariarun.i -l YourLogFile -a
```

If one wishes to run the job in a background mode the `nohup` command should be terminated with `&` at the end of the command line.

2.4. PLATFORM-SPECIFIC GUIDELINES

2.4.1. ATS-1/Trinity

The ATS-1 Trinity machine has two partitions, `haswell` and `knl`, each having different Intel CPU architectures on the compute nodes. Each compute node in the `haswell` partition has two i6-core Intel Haswell CPUs, and each compute node in the `knl` partition has one 68-core Intel Knights Landing CPU. The `haswell` partition is supported starting with the 4.46.1 release of Sierra, the `knl` partition starting with the 4.46.2 release.

For both partitions we recommend a target of approximately 500,000 elements per node as a good balance between parallel efficiency and simulation turnaround time for standard thermal analysis problems. Additionally, the `haswell` partition is expected to be 50-75% faster than the `knl` partition for the 4.46 release. On the `haswell` partition we recommend using $32 * num\_nodes$ processors, on the `KNL` partition we recommend $64 * num\_nodes$. The `sierra` script will handle supplying the appropriate core binding flags for each partition, and the desired partition can be selected by using the `"-queue-name haswell"` or `"-queue-name knl"` option.

2.5. ARIA ENVIRONMENT OVERVIEW

Aria is a Sierra application implementing the finite element method (FEM) for solving systems of partial differential equations (PDEs). Foremost, Aria's development targets applications which involve incompressible flow (Navier-Stokes). However, the general design of Aria lends itself to the solution of systems of PDEs describing physical processes including energy transport, species transport with reactions, electrostatics and general transport of scalar, vector and tensor quantities in two and three dimensions both transient and direct to steady state. Moreover, different regions of the physical domain (i.e., the input mesh) may have either different materials and/or different collections of physics (viz., PDEs) defined on them. These systems of equations may be solved alone, in a segregated but coupled




Figure 2.5-1.. Schematic UML class diagram for the Expression subsystem.

algorithm (“loosely coupled”) or as a single, fully-coupled system. Currently, Aria’s loose coupling capabilities are handled by the Arpeggio application which also allows Aria to couple (loosely) to the quasistatic structural mechanics code, Adagio.

Aria’s models and algorithms are integrated into the Sierra framework through the architecture illustrated in Figure 2.5-1. A Sierra-based application has four layers of code: Domain, Procedure, Region, and Model/Algorithm.

The outermost layer of an application is the Domain, or “main” program of the application. This domain layer is implemented by the Sierra Framework to manage the startup/shutdown of an application, and to orchestrate the execution of an application-provided set of procedures.

Code at the Procedure level is responsible for evolving one or more loosely coupled sets of physics through a sequence of steps. This sequence may be a set of time steps, nonlinear solver iterations, or some combinations of these or other types of steps.

An application may define multiple procedures to implement hand-off coupling between physics within the same main program. In hand-off coupling the first (or preceding) procedure completes execution, mesh and field data is transferred to a succeeding procedure, and the succeeding procedure continues the simulation with a different set of physics. For example, the first thermal procedure could calculate a temperature distribution inside a differentially heated fluid, and the second procedure could simulate natural convection of the fluid due to the density gradients set up by the resulting temperature field.

Code at the region level is responsible for evolving a tightly coupled set of physics through a single step. Loose coupling of Regions is supported by the advanced transfer services provided by Sierra Framework and Sierra Toolkit.

Each region owns (1) a set of models or algorithms that implement its tightly coupled set of physics and solvers and (2) an in-memory parallel distributed mesh and field database. This mesh and field data is fully distributed among parallel processors via domain decomposition.

2.6. OVERVIEW OF THE INPUT FILE STRUCTURE

An Aria model is described by commands contained in an ASCII input file. The structure of the input file follows a nested hierarchy. The topmost level of this hierarchy is named the domain. Underneath the domain is a level called the procedure, followed by the region level. Figure 1.1 shows this nesting.

The domain level contains one or more procedures. At the domain level, you also find commands associated with describing the finite element mesh, the linear solver set-up, material properties associated with a defined material, and user functions associated with source terms and boundary conditions that are added into Aria's intrinsic set of functions.

The procedure level contains one or more regions. The procedure level is also used to specify the time stepping parameters, and interactions between regions, such as data transfers. Essentially at the procedure level, loose coupling algorithms are specified. Loose coupling here is defined within the context of Aria's implicitly full-coupled paradigm. Whenever an independent variable's interaction with other variables in the solution procedure is not fully represented in the global matrix, the algorithm for loose coupling of that variable and its associated equation will be described at the procedure level. This loose coupling algorithm is given a fancy name called a "solution control description". The procedure level contains a block specifying the solution control procedure. An analogy to this block in simpler codes would be top level loop. For example in time dependent applications, the solution control description block would involve a block to solve the time dependent problem repeated for each time step until the desired solution time is reached.

The region level is used to specify details about the tightly coupled equation system to be solved. The details include boundary conditions and initial conditions, where materials models are applied, and where surface and volumetric source terms are applied. Essentially, meshes and material properties described at the domain level are tied into the problem statement here via their names.

Global constraints equations are also specified at the region level. At the region level, specification of what gets sent to the output file and at what frequency also is made. Additional post-processing associated with the output is specified. For example, additional volumetric fields which are functions of the independent variables may be specified to be added to the output file.

There are two types of commands in the input file. The first type is referred to as a block command. A block command is a grouping mechanism. A block command contains a set of commands made up of other block commands and line commands. A line command is the second type of command. The domain, procedure, and region levels are all parsed as block commands. A block command is defined in the input file by a matching pair of Begin and End lines. For example,

```
Begin SIERRA myJob
    ... block commands
End SIERRA myJob
```

A set of key words for the block command follows the "Begin" and "End" keywords. In most cases a user-specified name is added to the block commands. In the example above the keywords, SIERRA myJob, are added. Optionally, the keyword may be left off of the end of the block.

The second type of command is the line command. A line command is used to specify parameters within a given block command. In the remaining chapters and sections of this manual, the scope of each block and line command is identified, along with summaries of the meanings. Note that the ordering of any commands within a command block is arbitrary. Thus,

```
Begin Finite Element model fluid
  Database name is pipeflow2d.g
  Use Material water for block1
End Finite Element model fluid
```

will have the same effect as

```
Begin Finite Element model fluid
  Use Material water for block1
  Database name is pipeflow2d.g
End Finite Element model fluid
```

And the ordering of command blocks within the domain/procedure/region blocks are arbitrary—allowing you considerable freedom to collect and arrange commands. Note that the terms “command block” and “block command” are interchangeable.

The sierra command block must contain a block for a procedure containing an aria region:

```
Begin procedure  myProcedureName
.
  Begin Aria region myRegionName
.
  End   Aria region myRegionName
End procedure myProcedure
```

The procedure command block is used to contain all of the Aria commands that are associated with a solution procedure defined for a set of Aria Regions. The myProcedureName and name keywords of the procedure and region blocks are left up to you. Note that the Aria procedure command block must be present in the input file and must contain at least one Aria region command block. The procedure command block also contains other important command blocks such as the SOLUTION CONTROL block.

2.6.1. Syntax Conventions for Commands

In this section we describe the conventions used in presenting all the command descriptions in the remainder of this manual. There are four basic kinds of tokens, or words, that Aria expects to find as it parses an input file. These are keywords, names, parameters and delimiters.

2.6.1.1. Keywords

The words which distinguish one block command, or line command, from another we term keywords. Keywords are denoted in this manual in the monospaced font, for example, `BOUNDARY CONDITION`.

2.6.1.2. Names

The word, or words, that you supply on the same line of the `begin` line of a block command, is the name. Many times you may need to supply this name as a character parameter in a separate line command. Names are denoted in italics, name, as are parameters.

It is worth noting that the interpreter used to process standard input command lines is also used to process lines defining algebraic operations. This means that a "-" appearing within a name would be interpreted as a subtraction operation and as a consequence, the use of "-" within a name is not allowed. Thus instead of

```
Begin Aria region name-1
```

one could perhaps use

```
Begin Aria region name_1.
```

2.6.1.3. Parameters

There are three types of input parameters one will need to supply to line commands: character strings, integers, and real numbers. These are denoted in the documentation as (C), (R), and (I), respectively.

In most cases character strings may be specified in a free format. One exception to this paradigm is when a string begins a number. In this case the character string must be specified within quotation marks in order to be properly interpreted.

Real numbers may be entered in decimal form or exponential form. For example 0.0001, .1E-3, 10.0d-5 are all equivalent. Furthermore, if a real(R) is expected, an integer can be used.

Integer values (I) need not include a decimal point in their specification.

2.6.1.4. Multiple Parameters

For the case when a list of one or more parameters is allowed, or required, for a command, (C,...) denotes a list of character strings, (I,...) a list of integers, and (R, ...) a list of real numbers. For a list of character strings, the separator between the strings must be one or more spaces or tab characters. Therefore, phrases with multiple spaces and words in them are tokenized into multiple character parameters before being processed by the application. For a list of real or integer numbers the comma can also be used as a separator.

2.6.1.5. *Enumerated Parameters*

Certain commands have predefined parameters, called enumerations, which are listed within {}. Each parameter in the list is separated using |. The default parameter for the list of parameters is enclosed by <>.

2.6.1.6. *Delimiters*

The keywords of a line command are often required to be separated from the parameters by a delimiter. You have a choice of delimiters to use: the equal sign, =, or a word. In this manual, we denote the choices surrounded by {}, and separated by |. You may use any one of the delimiters from those listed. For example, the line command to specify the density within the Aria Material Block command is

Density {= |IS} (R)

Examples of valid forms you could write in the input file are

```
Begin Aria Material water
...
Density = constant rho = 1.0E-3 # kg/m^3 at 20C
...
End
```

and

Examples of valid forms you could write in the input file are

```
Begin Aria Material water
...
Density is constant rho = 1.0E-3 # kg/m^3 at 20C
...
End
```

2.6.1.7. *White Space*

Command keywords, names, and parameters and delimiters must have spaces around them.

2.6.1.8. *Indentation*

All leading spaces and/or tab characters are ignored in the input file. Of course, we recommend that you use indentation to improve the readability for yourself and others that may need to see your files.

2.6.1.9. Including Files

External text files containing input commands can be included at any point in the Aria input file using the INCLUDEFILE command. This command can be used in any context in the input file. To use this command, simply use the command INCLUDEFILE followed by the name of the file to be included. For example, the command:

```
INCLUDEFILE extrafile.i
```

would include the contents of `extrafile.i` at the locations where it is included in the input file. The included file is contained in the standard echo of the input that is provided at the beginning of the log file.

NOTE: Though this line command works well in many simple circumstances, it is known to cause issues when file names are involved. The most robust method to include files is to use Aprepro's include function and pre-process the input file with aprepro before running. An example is below:

```
#{include(extrafile.i)}
```

2.6.1.10. Case Sensitivity

None of the command keywords, parameters, or delimiters read from the input file are case sensitive. For example, the following two lines are equivalent:

```
Use Material water for block_1
.
```

and

```
USE material wATer for bLOCK_1
.
```

The exception to this rule are file names used for input and output, because the current operating systems on which SIERRA applications are run are based on UNIX, where file names are case sensitive.

2.6.1.11. Comments and Line Continuation

You may place comments in the input file starting with either the \$ or # character. All further characters on a line following a comment character are ignored.

You can continue a command in the input file to the next line by using the line continuation character, \\$, or you may optionally follow it with a comment, \#. All further characters on the same line following a line continuation character \\$ are ignored, and the characters on the following line are joined and parsing continues. An example is the line command used to specify the title of a thermal model:

```
Begin SIERRA Job_Identifier
# This thermal model for Aria simulates a convective heat transfer

Title    The title command is used to set the analysis title \$
         Convective heat transfer to a part. The analysis \$
         makes use of conjugate heat transfer to account for \$
         cooling of a part due to flowing water.
...
End SIERRA Job_Identifier
```

2.6.1.12. Checking the Syntax

Errors in the input deck can be checked by adding the command, -check-syntax to the aria command line. For example,

```
$ sierra -np 1 aria -check-syntax -i input.i
```

This command will print the code echo of the input deck and any syntax errors within it to the screen.

2.7. FIELDS

Fields are defined as variables which are distributed on mesh objects. For example, if the temperature is defined via Q_I interpolation on a 2D mesh consisting of quadrilaterals, then the vector of nodal temperature coefficients that make up the interpolation would be defined as the Temperature field on that mesh. Fields may be defined on any mesh object type (e.g., elements, faces, edges, nodes, node sets, and side sets), not just at nodes.

The mesh object and field data may be distributed among parallel processors via a domain decomposition algorithm. Both fields and meshes are owned at the region level. A particular field may or may not be part of Aria's solution vector for the particular region. However, all fields in Aria's solution vector are fields defined on the mesh for that region.

[<Operator>_] <Name> [_<Subindex>] [_<Phase>] [_<Component>]

Figure 2.7-1.. General format of Aria’s string-based naming convention for expressions. Fields in square brackets are optional.

Operator	Description
(none)	“No-Op”, no-operator
DT	Time derivative
GRAD	Gradient
DIV	Divergence
DET	Determinant of a 2-tensor
DETJ	Determinate of the Jacobian of transformation
SURFACE_DETJ	Determinate of the Jacobian of transformation
REF_FRAME	“No-Op” in the undeformed reference frame
GRAD_REF_FRAME	Gradient in the undeformed reference frame
DIV_REF_FRAME	Divergence in the undeformed reference frame
DETJ_REF_FRAME	Determinate of the Jacobian of transformation in the undeformed reference frame
SURFACE_DETJ_REF_FRAME	Determinate of the Jacobian of transformation in the undeformed reference frame
OLD	“No-Op” at the previous time step
GRAD_OLD	Gradient at the previous time step
DIV_OLD	Divergence at the previous time step

Table 2.7-1.. Valid values of the <Operator> prefix.

2.7.1. Field String-Naming Convention

Due to the dynamic nature of fields and variables in Aria a consistent naming convention must be used for sanity sake. This section describes the format of string-names of Aria Expressions. These string forms are used for input and output only; Aria has more efficient internal structures for referencing Expressions.

Briefly, the overall format is described in Figure 2.7-1.

Valid values of the <Operator> field are listed in Table 2.7-1. Valid values of the <Name> field are too numerous to list here; they include things like degrees of freedom (VELOCITY, SPECIES) and material properties (VISCOSITY, ELECTRICAL_CONDUCTIVITY). The <Subindex> field can be used to designate multiple instances of a field. This is typically used for species equations. All integer values are valid subindex values but it’s best to use values ≥ 1 . The <Phase> field is used in level set problems. Some fields are present in “all phases” while others, such as material properties, depend on which phase is being referred to. The <Component> field allows the user to specify a particular component of vector and tensor fields; valid values are described in Table 2.7-3.

Phase	Description
(none)	A field present in all phases within a material
A	Phase A
B	Phase B
C	Phase C

Table 2.7-2.. Valid values of the <Phase> suffix. Phase labels are used in level set calculations only.

Component	Description
(none)	No specified component
X	First vector component
Y	Second vector component
Z	Third vector component
XX	(1,1) 2-tensor component (default: 0)
XY	(1,2) 2-tensor component (default: 0)
XZ	(1,3) 2-tensor component (default: 0)
YX	(2,1) 2-tensor component (default: 0)
YY	(2,2) 2-tensor component (default: 0)
YZ	(2,3) 2-tensor component (default: 0)
ZX	(3,1) 2-tensor component (default: 0)
ZY	(3,2) 2-tensor component (default: 0)
ZZ	(3,3) 2-tensor component (default: 0)

Table 2.7-3.. Valid values of the <Component> suffix. In non-Cartesian coordinate systems these may refer to, for example, radial or angular components.

String-Name	Description
TEMPERATURE	Just the temperature.
SPECIES_2	Species number two
VELOCITY_X	The first component of the velocity vector
DIV_VELOCITY	The divergence of the velocity field
DENSITY	The density
DENSITY_A	The density in level set phase A
GRAD_SPECIES_2_Y_B	The second component of the gradient of species number 2 in level set phase B

Table 2.7-4.. Examples of well formed string names for Aria Expressions.

<code><Equation_Name>[_<Subindex>][_<Phase>][_<Component>]</code>

Figure 2.9-1.. General format of Aria’s string-based naming convention for equations. Fields in square brackets are optional.

2.8. EQUATIONS

Equations are defined within an Aria region to represent an particular continuity equation to be solved. Within the Aria input deck, solution variables are assigned as the independent unknowns to equations. In general, there is a one-to-one correspondence between solution unknowns and equation degrees of freedom.

2.9. EQUATION STRING-NAMING CONVENTION

Similar to the field string-naming convention, equation names pose a similar requirement. This section describes the format of string-names of Aria equations. These string forms are used for input and output only; Aria has more efficient internal structures for referencing equations.

Briefly, the overall format is described in Figure 2.9-1.

Valid values of the `<Equation_Name>` field are numerous and changing in time. Typical values include `MOMENTUM`, `ENERGY`, `SPECIES`, `LEVEL_SET`, `MESH`, `CURRENT` and `VOLTAGE`; see chapter 6 for a complete description of existing equations. All integer values are valid subindex values but it’s best to use values ≥ 1 – currently -1 has a special meaning of “no subindex”. The `<Phase>` field is used in level set problems. Some fields are present in “all phases” while others, such as material properties, depend on which phase is being referred to. The `<Component>` field allows the user to specify a particular component of vector and tensor equation; valid values are described in Table 2.7-3.

2.10. INTERNAL FIELD DEFINITION

Internal to the Aria code Fields mentioned in the previous section 2.7-4 have alternative internal names that facilitate their algorithmic usage. In most cases this naming convention will be “usage”->field_name where “usage” categorizes its internal usage. From a user perspective the “usage” category will be “solution” and as an example the voltage solution is internally known as solution->voltage. Application output is managed independent of the application thus output requests must correspond to the internal code Field names rather than the Field name stated in the previous section.

2.11. USER FIELDS

Situations often arise where one wishes to provide Field data storage so that data can be transferred into or out of Aria. The mechanism used for this capability is provided by the USER FIELD command line.

2.11.1. User Field

Scope:

```
User Field REAL_or_INTEGER NODE_or_FACE_or_ELEMENT
SCALAR_or_VECTOR_or_TENSOR Variable_name On Mesh_extent [ Value {=|are|
is} Magnitude... ]
```

Parameter	Value	Default
<i>REAL_or_INTEGER</i>	string	undefined
<i>NODE_or_FACE_or_ELEMENT</i>	string	undefined
<i>SCALAR_or_VECTOR_or_TENSOR</i>	string	undefined
<i>Variable_name</i>	string	undefined
<i>Mesh_extent</i>	string	undefined

Summary Defines a user field of standard type *data_type* (REAL or INTEGER) on the FEM entity (NODE, FACE, or ELEMENT) with the specified name and Sierra field type (SCALAR, VECTOR, or TENSOR). The field will be defined on the specified mesh part or mesh group alias. Normally this field would be supplied to Aria through a transfer.

3. MODEL DEFINITION

3.1. MODEL OVERVIEW

The basic structure of an input file can be described as having three levels of commands, domain, procedure and region. The domain level is defined as the outside level commands, the procedure level is nested within the domain level and the region level is nested within the procedure. The basic structure of the input file is illustrated below.

```
Begin Sierra myJob
.
Begin Finite Element Model my_fem_model
.
End

Begin Global Constants
.
End

.
Model definition commands
.
Begin Procedure My_Aria_Procedure
.
Begin Aria Region My_Region
.
use Finite Element Model my_fem_model
.
End
.
End
.
End Sierra myJob
```

The model discretization (mesh database) and the mesh components to be used in the model are defined at the Domain level and are later referenced by the application at the Region level. Specification of a mesh database and association of material properties with portions of the mesh are defined within the *Finite Element Model* command block. In coupled analyses the need often arises for different

discretizations of the same physical domain. In this case one must supply a different *Finite Element Model* command block for each discretization since only a single mesh can be referenced within this command block.

3.1.1. Mesh Database Part Names

The input ExodusII mesh database can be created by a variety of mesh generators. While analysts prefer to designate portions of the mesh with user-defined names, traditionally these portions of the mesh have been designated by an internal naming convention using the meshed entity/part with a numbered index, (e.g. surface_1, block_8). Fortunately, provisions are also made within Sierra to allow referencing of meshed entities with user-specified names and in the use of user-specified names two distinct use cases will arise:

- Mesh was created with enumerated parts convention(surface_#, block_#).
- Mesh was created with named part convention.

Within the *Finite Element Model* command block these two cases are treated syntactically different in the association of material properties with portions of the mesh. This difference in syntax imposes restrictions on part name usage within the *Finite Element Model* and is discussed with regard to block_1 and block_4 of the model shown in Figure 3.1.1 using the two part naming conventions.




Figure 3.1-1.. Enumerated Block and Named Block Models.

Note that even when a mesh was created with the numbered-index naming convention one is still able to employ user-defined names. This is accomplished by defining an association between a selected name and the block/surface/nodeset numbered-index part name on the database using the Alias command line within the *Finite Element Model* command block. As an example aliasing a subset of the simple model

```
alias orange as block_1
```

would allow one to use "orange" instead of block_1 within the Region scope.

Unfortunately, despite the fact that the named alias is defined within the *Finite Element Model* command block, it is still not possible to then use that name in the command block during assignment of the associated material. Assignment of the associated material can be accomplished in two different ways and an acceptable syntax would be:

```
alias orange as block_1
use material 304L for block_1
alias Blue as block_4
use material 304L for block_4
```

or alternatively

```
alias orange as block_1
Begin Parameters for Block block_1
  material 304L
End
alias Blue as block_4
Begin Parameters for Block Blue
  material 304L
End
```

If the mesh was created with user-defined part names then those names are automatically respected within the Region scope. However, there are still restrictions as to how the internally defined names are currently used in the *Finite Element Model* in the material assignment. Here an unacceptable syntax is

```
use material 304L for orange
use material 304L for blue
```

where the user-specified name cannot be used and the user must know the corresponding numbered-index part name instead to perform the assignment. If the numbered-index part name is not known, one can employ the *io_info* Seacas tool to obtain the equivalent numbered-index part name to user-specified name mapping. Note that one could still include the Alias command lines here but they would be redundant.

The preferred usage of user-defined part names in association of material

```
Begin Parameters for Block orange
  material 304L
End
Begin Parameters for Block Blue
  material 304L
End
```

is explicit but also can be overly verbose in large models. However, for models in which many blocks are of the same material this syntax provides some flexibility with user-defined block names. For example if both element blocks were of the same material, say 304L, then one could use

```
Begin Parameters for Block orange Blue
  material 304L
End
```

which is clearly more succinct. The analogous command using numbered-index part names is even more compact

```
use material 304L for block_1 block_4
```

but again it cannot be used with user-defined block names.

With respect to [3.1.1](#) an illustration of differences in the two methods of defining part-to-material associations is illustrated in Figure [3.1-2](#) below

Enumerated Block Syntax	Named Block Syntax
Begin Finite Element Model Thermal alias block_1 as orange alias block_2 as red alias block_3 as green alias block_4 as blue omit block block_3 use Material 304L for block_1 use Material Cu for block_2 use Material Inconel for block_3 use Material 304L for block_4 End	Begin Finite Element Model Thermal Begin Parameters for Block Orange Material 304L End Begin Parameters for Block Red Material Cu End Omit Block Green Begin Parameters for Block Green Material Inconel End Begin Parameters for Block Blue Material 304L End End

Figure 3.1-2.. Enumerated Block and Named Block Syntax.

From within the Region scope, block, surface and nodeset entities/parts can be referenced by the user-defined when setting up the model but those parts will be internally referenced by the numbered-index naming convention during code execution. Hence code diagnostic and error messages may sometimes reflect the numbered-index naming convention of parts rather than the user-defined name.

For debugging purposes the user-defined part to numbered-part mapping is written to a portion of the log file in the general form shown below.

Based on IO aliases, will use name orange for part block_1

Based on IO aliases, will use name blue for part block_4

Alternatively, one can employ the *io_info* Seacas tool to determine the part name mapping for all parts in the database for debugging.

3.2. FINITE ELEMENT MODEL

Scope: Sierra

```
Begin Finite Element Model Label

    Alias DatabaseName As InternalName

    Component Separator Character Option Separator

    Create GroupType NewSurfaceName Add SurfaceName...

    Database Name {=|are|is} StreamName

    Database Type {=|are|is} DatabaseTypes

    Global Id Mapping Backward Compatibility Option1 Option2

    Omit Block BlockList...

    Omit Volume VolumeList...

    Time Scale Factor Option Scale

    Use Generic Names

    Use Material MaterialName For VolumeList...

    Begin Parameters For Block Blockname

    End

    Begin Parameters For Phase Phase Name

    End

    Begin Parameters For Surface Surface_Name

    End

End
```

Summary Describes the location and type of the input stream used for defining a geometry model for the enclosing region.

3.2.1. Alias

Scope: Finite Element Model

Alias *DatabaseName* As *InternalName*

Parameter	Value	Default
<i>DatabaseName</i>	string	undefined
<i>InternalName</i>	string	undefined

Summary Name the database entity "DatabaseName" as "InternalName"

Description This "InternalName" may then be referenced in the data file in addition to the original name.

3.2.2. Component Separator Character

Scope: Finite Element Model

Component Separator Character *Option Separator*

Parameter	Value	Default
<i>Option</i>	{= is}	undefined
<i>Separator</i>	string	undefined

Summary The separator is the single character used to separate the output variable basename (e.g. "stress") from the suffices (e.g. "xx", "yy") when displaying the names of the individual variable components. For example, the default separator is "_", which results in names similar to "stress_xx", "stress_yy", ... "stress_zx". To eliminate the separator, specify an empty string ("") or NONE.

3.2.3. Create

Scope: Finite Element Model

Create *GroupType NewSurfaceName* Add *SurfaceName...*

Parameter	Value	Default
<i>GroupType</i>	{edgeset elemset faceset nodeset sideset surface}	undefined
<i>NewSurfaceName</i>	string	undefined
<i>SurfaceName</i>	string...	undefined

Summary Create a new set (node, edge, face, element, side/surface) as the union of two or more existing sets. The sets must exist in the mesh database or have been created by a previous CREATE command.

3.2.4. Database Name

Scope: Finite Element Model

Database Name `{=|are|is} StreamName`

Parameter	Value	Default
<i>StreamName</i>	string	undefined

Summary The base name of the database containing the output results. If the filename begins with the '/' character, it is an absolute path; otherwise, the path to the current directory will be prepended to the name. If this line is omitted, then a filename will be created from the basename of the input file with a ".g" suffix appended.

3.2.5. Database Type

Scope: Finite Element Model

Database Type `{=|are|is} DatabaseTypes`

Parameter	Value	Default
<i>DatabaseTypes</i>	{catalyst dof dof_exodus exodus exodusii generated genesis parallel_exodus}	undefined

Summary The database type/format used for the mesh.

3.2.6. Global Id Mapping Backward Compatibility

Scope: Finite Element Model

Global Id Mapping Backward Compatibility *Option1 Option2*

Parameter	Value	Default
<i>Option1</i>	{= is}	undefined
<i>Option2</i>	{false no off on true yes}	undefined

Summary (Unsupported, do not use)

3.2.7. Omit Block

Scope: Finite Element Model

Omit Block *BlockList...*

Parameter	Value	Default
<i>BlockList</i>	string...	undefined

Summary Specifies that the element blocks named in the blockList be omitted from the analysis.

Description If an element block is omitted, then it is illegal to refer to it later in the input file e.g an initial condition may not be specified on an omitted element block. The elements, faces, etc are never created and it is as if the omitted element blocks did not exist in the mesh file. If a surface is completely determined by the omitted element block, then it is illegal to specify boundary conditions on that surface. However, if the surface spans multiple element blocks, boundary conditions may be applied on the portion of the surface supported by the element blocks that are not omitted.

3.2.8. Omit Volume

Scope: Finite Element Model

Omit Volume *VolumeList...*

Parameter	Value	Default
<i>VolumeList</i>	string...	undefined

Summary Specifies that the volumes named in the volumeList be omitted from the analysis.

Description If a volume is omitted, then it is illegal to refer to it later in the input file e.g an initial condition may not be specified on an omitted volume. The elements, faces, etc are never created and it is as if the omitted volumes did not exist in the mesh file. If a surface is completely determined by the omitted volume, then it is illegal to specify boundary conditions on that surface. However, if the surface spans multiple volumes, boundary conditions may be applied on the portion of the surface supported by the volumes that are not omitted.

3.2.9. Time Scale Factor

Scope: Finite Element Model

Time Scale Factor *Option Scale*

Parameter	Value	Default
<i>Option</i>	{= is}	undefined
<i>Scale</i>	real	undefined

Summary The scale factor to be applied to the times on the mesh database. If the scale factor is 20 and the times on the mesh database are 0.1, 0.2, 0.3, then the application will see the mesh times as 2, 4, 6.

3.2.10. Use Generic Names

Scope: Finite Element Model

Summary If this command is present then the name of all blocks and sets in the mesh will be of the form "type_"+id. For example, an element block with id=42 will be named "block_42"; a sideset with id 314 will be named "surface_314". If there are any names in the mesh file, those names will be aliases for the blocks and sets. If this command is not present, then if a name is in the mesh file, it will be used as the name and the generic generated name will be an alias. This is used as a workaround in codes that do not correctly handle named blocks and sets or as a workaround in meshes which contain non-user-specified names.

3.2.11. Use Material

Scope: Finite Element Model

Use Material *MaterialName* For *VolumeList*...

Parameter	Value	Default
<i>MaterialName</i>	string	undefined
<i>VolumeList</i>	string...	undefined

Summary Associate the given volumes with the indicated material name.

3.2.12. Decomposition Method

Scope:

Decomposition Method {=|are|is} *Method*

Parameter	Value	Default
<i>Method</i>	{block cyclic external geom_kway hsfc kway kway_geom linear metis_sfc random rcb rib}	undefined

Summary The decomposition algorithm to be used to partition elements to each processor in a parallel run.

3.2.13. Coordinate System

Scope:

Coordinate System {=|are|is} *CoordinateSystem*

Parameter	Value	Default
<i>CoordinateSystem</i>	{axisymmetric barycentric cartesian cyclidic cylindrical polar quadriplanar skew spherical toroidal trilinear}	undefined

Summary The interpretation of the geometry data stored in this database. Optional. Defaults to Cartesian.



Beta Capability: Aria fully supports only the global Cartesian and Axisymmetric coordinate systems. Additionally cylindrical coordinates are partially supported.

3.3. PARAMETERS FOR BLOCK

Scope: Finite Element Model

Begin Parameters For Block *Blockname*

Density Scale Factor {=|are|is} *densityScaleFactor*

Include All Blocks

Inversion Aversion Exponent {=|are|is} *ia_exponent*

Inversion Aversion Stiffness {=|are|is} *ia_stiffness*

Inversion Aversion Transition Jacobian {=|are|is}
transition_jacobian

Local Coordinate System {=|are|is} *Mesh Entities*

Material *MatName*

Material = *MatName*

Phase *PhaseLabel* {=|are|is} *MaterialName*

Remove Block {=|are|is} *ExcludeBlockList...*

End

Summary Specifies analysis parameters associated with each element block.

3.3.1. Density Scale Factor

Scope: Parameters For Block

Density Scale Factor {=|are|is} *densityScaleFactor*

Parameter	Value	Default
<i>densityScaleFactor</i>	real	undefined

Summary Specifies a scale factor to apply to the density defined in the material. This value must be greater than zero. The default is 1.0 (no scaling).

3.3.2. Include All Blocks

Scope: Parameters For Block

Summary Use this parameters definition for all blocks.

When using this option within the FINITE ELEMENT MODEL command block the PARAMETERS FOR BLOCK will not use a Blockname.

3.3.3. Inversion Aversion Exponent

Scope: Parameters For Block

Inversion Aversion Exponent {=|are|is} *ia_exponent*

Parameter	Value	Default
<i>ia_exponent</i>	integer	5

Summary Sets the exponent used to compute the smooth approximate nodal jacobian ratio. A higher exponent results in a more-accurate approximation to the ratio. This is only active for uniform gradient elements. Default = 5.

3.3.4. Inversion Aversion Stiffness

Scope: Parameters For Block

Inversion Aversion Stiffness {=|are|is} *ia_stiffness*

Parameter	Value	Default
<i>ia_stiffness</i>	real	1.e5

Summary Sets a stiffness parameter for the inversion aversion penalty. This is only active for uniform gradient elements. Default = 1.0e5.

3.3.5. Inversion Aversion Transition Jacobian

Scope: Parameters For Block

Inversion Aversion Transition Jacobian {=|are|is} *transition_jacobian*

Parameter	Value	Default
<i>transition_jacobian</i>	real	0

Summary Sets the critical relative nodal Jacobian ratio for inversion aversion. If this value is nonzero, an additional recoverable energy term is added which penalizes further element distortion. This energy is only active for uniform gradient elements.

3.3.6. Local Coordinate System

Scope: Parameters For Block

Local Coordinate System {=|are|is} *Mesh Entities*

Parameter	Value	Default
<i>Mesh Entities</i>	string	undefined

Summary Associate coordinate system with mesh entity.

Description Specify the local coordinate system to be used in conjunction with given element blocks.

3.3.7. Material

Scope: Parameters For Block

Material *MatName*

Parameter	Value	Default
<i>MatName</i>	string	undefined

Summary Associates this element block with its material properties.

3.3.8. Material =

Scope: Parameters For Block

Material = *MatName*

Parameter	Value	Default
<i>MatName</i>	string	undefined

Summary Associates this element block with its material properties.

3.3.9. Phase

Scope: Parameters For Block

Phase *PhaseLabel* {=|are|is} *MaterialName*

Parameter	Value	Default
<i>PhaseLabel</i>	string	undefined
<i>MaterialName</i>	string	undefined

Summary Associate phase *PhaseLabel* with material *Material_Name* on this block.

3.3.10. Remove Block

Scope: Parameters For Block

Remove Block {=|are|is} *ExcludeBlockList...*

Parameter	Value	Default
<i>ExcludeBlockList</i>	string...	undefined

Summary List of blocks to exclude.

3.3.11. Axisymmetry Axis

Scope:

Axisymmetry Axis {=|are|is} *AxisType*

Parameter	Value	Default
<i>AxisType</i>	{x y}	Y

Summary When the COORDINATE SYSTEM = AXISYMMETRIC command appears within the Finite Element Model command block one can select at the Region level the coordinate axis about which the 2D axisymmetric sweep will occur. Note that there can be no overlap between the model and the axis of rotation.

3.4. UNIFORM MESH REFINEMENT

Produces initial uniform refinement for num iterations. This also precedes initialization of the Region, including setting initial conditions. This line command should be put inside the Aria Region.

Syntax:

INITIAL UNIFORM REFINEMENT FOR num ITERATIONS

3.5. TIMING OVERVIEW

Overall timing information for code execution is provided by default. Alternatively, the user can increase the granularity of timing information by requesting the output explicitly using the *PRINT TIMER* command line. Here the timing information is itemized by code functionality and identify what portion of time is spent performing specific operations. Note that this command line must be applied at the Domain Scope (i.e. outside of the Procedure).

3.5.1. Print Timer Information Every

Scope:

Print Timer Information Every *Procedure-step-interval* Steps *Checkpointed*

Parameter	Value	Default
<i>Procedure-step-interval</i>	integer	undefined
<i>Checkpointed</i>	{accumulated checkpointed}	undefined

Summary Specifies the procedure step count interval to print timer information

3.6. GLOBAL CONSTANTS

Scope: Sierra

Begin Global Constants *empty*

Gravity Vector {=|are|is} *Gravity₁ Gravity₂ Gravity₃*

Ideal Gas Constant {=|are|is} *Sigma*

K-E Turbulence Model Parameter *Param* {=|are|is} *Value*

K-W Turbulence Model Parameter *Param* {=|are|is} *Value*

Les Turbulence Model Parameter *Param* {=|are|is} *Value*

Light Speed {=|are|is} *LightSpeed*

Planck Constant {=|are|is} *PlanckConstant*

Stefan Boltzmann Constant {=|are|is} *Sigma*

Turbulence Model *Param* Number {=|are|is} *Value*

End

Summary Set of universal constants for a simulation.

3.6.1. Gravity Vector

Scope: Global Constants

Gravity Vector {=`|are|is`} *Gravity*₁ *Gravity*₂ *Gravity*₃

Parameter	Value	Default
<i>Gravity</i>	real_1 real_2 real_3	undefined

Summary Gravity constant in vector form, acceleration components.

3.6.2. Ideal Gas Constant

Scope: Global Constants

Ideal Gas Constant {=`|are|is`} *Sigma*

Parameter	Value	Default
<i>Sigma</i>	real	undefined

Summary Ideal gas constant. **NOTE:** Another ideal gas constant value can be specified while using certain code capabilities. This global constants value will be discarded for any other specified ideal gas constant values.

3.6.3. K-E Turbulence Model Parameter

Scope: Global Constants

K-E Turbulence Model Parameter *Param* {=`|are|is`} *Value*

Parameter	Value	Default
<i>Param</i>	string	undefined
<i>Value</i>	real	undefined

Summary $k - \epsilon$ RANS turbulence model parameters.

3.6.4. K-W Turbulence Model Parameter

Scope: Global Constants

K-W Turbulence Model Parameter *Param* {=`|are|is`} *Value*

Parameter	Value	Default
<i>Param</i>	string	undefined
<i>Value</i>	real	undefined

Summary $k - \omega$ RANS turbulence model parameters.

3.6.5. Les Turbulence Model Parameter

Scope: Global Constants

Les Turbulence Model Parameter *Param* {=|are|is} *Value*

Parameter	Value	Default
<i>Param</i>	string	undefined
<i>Value</i>	real	undefined

Summary LES turbulence model parameters.

3.6.6. Light Speed

Scope: Global Constants

Light Speed {=|are|is} *LightSpeed*

Parameter	Value	Default
<i>LightSpeed</i>	real	undefined

Summary Speed of Light. Depending on the units involved in the specific problem by the user, this value will differ.

3.6.7. Planck Constant

Scope: Global Constants

Planck Constant {=|are|is} *PlanckConstant*

Parameter	Value	Default
<i>PlanckConstant</i>	real	undefined

Summary Planck Constant. Depending on the units involved in the specific problem by the user, this value will differ.

3.6.8. Stefan Boltzmann Constant

Scope: Global Constants

Stefan Boltzmann Constant {=|are|is} *Sigma*

Parameter	Value	Default
<i>Sigma</i>	real	undefined

Summary Stefan-Boltzmann constant. Depending on the units involved in the specific problem by the user, this value will differ.

3.6.9. Turbulence Model

Scope: Global Constants

Turbulence Model *Param* Number {=|are|is} *Value*

Parameter	Value	Default
<i>Param</i>	string	undefined
<i>Value</i>	real	undefined

Summary Turbulence model Schmidt and Prandtl numbers

3.7. FUNCTION OVERVIEW

User supplied functions are supported by Aria. The functions can be either tabular or analytical, where the most prevalent use of this capability is tabular data functions. These functions can in turn be tied to different features and models in the applications. Examples of this usage would be to define material data or load profiles, either spatially or in time.

3.8. DEFINITION FOR FUNCTION

Scope: Sierra

Begin Definition For Function *FunctionName*

Abscissa {=|are|is} *Name...*

Abscissa Offset {=|are|is} *Abscissa_offset*

Abscissa Scale {=|are|is} *Abscissa_scale*

At Discontinuity Evaluate To *Option*

Column Titles *Titles₁ Titles₂...*

Data File = *filename* [X From Column *xcol* Y From Column *ycol*]

Debug {=|are|is} *Option*

Differentiate Expression {=|are|is} *Expr*

Evaluate Expression {=|are|is} *Expr*

Evaluate From *x0* To *x1* By *Dx*

Expression Variable: *Expr* = *VarType value_var_name...*

Expression Variable: *Expr*

Ordinate {=|are|is} *Name...*

Ordinate Offset {=|are|is} *Ordinate_offset*

Ordinate Scale {=|are|is} *Ordinate_scale*

Scale By *x*

Type {=|are|is} *Type*

X Offset {=|are|is} *X_offset*

X Scale {=|are|is} *X_scale*

Y Offset {=|are|is} *Y_offset*

Y Scale {=|are|is} *Y_scale*

Begin Expressions *empty*

End

Begin Values *empty*

End

End

Summary Defines a function in terms of its type and values.

3.8.1. Abscissa

Scope: Definition For Function

Abscissa {=|are|is} *Name...*

Parameter	Value	Default
<i>Name</i>	string...	undefined

Summary Specifies a string identifier for the independent variable. Optionally specify a scale and/or offset value which transforms the abscissa values into `scaled_abscissa = scale * ( abscissa + abscissa_offset)`.

3.8.2. Abscissa Offset

Scope: Definition For Function

Abcissa Offset {=|are|is} *Abcissa_offset*

Parameter	Value	Default
<i>Abcissa_offset</i>	real	undefined

Summary Alias for X OFFSET

3.8.3. Abscissa Scale

Scope: Definition For Function

Abcissa Scale {=|are|is} *Abcissa_scale*

Parameter	Value	Default
<i>Abcissa_scale</i>	real	undefined

Summary Alias for X SCALE

3.8.4. At Discontinuity Evaluate To

Scope: Definition For Function

At Discontinuity Evaluate To *Option*

Parameter	Value	Default
<i>Option</i>	{left right}	undefined

Summary Control the behavior of a piecewise constant function when evaluated at a discontinuity (plus or minus a small tolerance). The default behavior is to take the value to the right of the discontinuity. If "Left" is specified, the value to the left of the discontinuity is taken instead.

3.8.5. Column Titles

Scope: Definition For Function

Column Titles *Titles₁ Titles₂...*

Parameter	Value	Default
<i>Titles</i>	string_1 string_2...	undefined

Summary Name the columns (and also defined the expected number of columns) for Multicolumn Piecewise Linear tabular data.

3.8.6. Data File

Scope: Definition For Function

Data File = *filename* [X From Column *xcol* Y From Column *ycol*]

Parameter	Value	Default
<i>filename</i>	string	undefined

Summary Function will read tabular data from an input file. Compatible with the piecewise linear function type. File must be of form like:

```
----- # EXAMPLE FILE 1.099 1191 1.101 221 5.9011 133.1
-----
```

Lines headed by a # are considered comments and will be ignored. Data itself must be in tabular columns separated by whitespace or commas.

3.8.7. Debug

Scope: Definition For Function

Debug {=|are|is} *Option*

Parameter	Value	Default
<i>Option</i>	{off on}	undefined

Summary Prints functions to the log file.

3.8.8. Differentiate Expression

Scope: Definition For Function

Differentiate Expression {=|are|is} *Expr*

Parameter	Value	Default
<i>Expr</i>	(expression)	undefined

Summary Specifies the expression of derivative of evaluation expression.

3.8.9. Evaluate Expression

Scope: Definition For Function

Evaluate Expression {=|are|is} *Expr*

Parameter	Value	Default
<i>Expr</i>	(expression)	undefined

Summary Specifies the expression to evaluate.

Description This will greatly help with manufactured solutions, and be useful for other purposes as well.

This first implementation goes like this:

```

begin definition for function pressure
type is analytic
evaluate expression is "x <= 0.0 ? 0.0 : (x < 0.5 ?
x*200.0 : (x < 1.0 ? (x - 0.5) *50.0 + 100.00 :
150.0));"
# type is piecewise linear
# begin values
# 0.0 0.0
# 0.5 100.0
# 1.0 150.0
# end values
end definition for function pressure

```

Also, notice that semicolon at the end. Be sure to put it there for now. You can actually provide multiple expressions to be evaluated, each terminated with a semicolon. This will be handy when multi-dependent variable come into the fold.

The following functions are currently implemented.

Operators All C-language operators are supported, e.g. + - */ || ? : etc

Parens ()

Math Functions

abs(x) absolute value of x

mod(x, y) modulus of x|y

ipart(x) integer part of x

fpart(x) fractional part of x

min(x0, x1, ...) minimum value of xn

max(x0, x1, ...) maximum value of xn

Power functions

pow(x, y) x to the y power

sqrt(x) square root of x

Trig functions

sin(x) sine of x

sinh(x) hyperbolic sine of x

asin(x) arcsine of x

cos(x) cosine of x

cosh(x) hyperbolic cosine of x

acos(x) arccosine of x

tan(x) tangent of x

tanh(x) hyperbolic tangent of x

atan(x) arctangent of x

atan2(y, x) arctangent of y/x, signs of x and y determine quadrant (see atan2 man page)

Logarithm functions

log(x) natural logarithm of x

ln(x) natural logarithm of x

exp(x) e to the x power

logn(x, y) the y base logarithm of x

Rounding functions

ceil(x) smallest integral value not less than x

floor(x) largest integral value not greater than x

Random functions

rand(x) random number between 0.0 and 1.0, not including 1.0

srand(x) seeds the random number generator

Conversion routines

deg(x) converts radians to degrees

rad(x) converts degrees to radians

recttopolr(x, y) magnitude of vector x, y

recttopola(x, y) angle of vector x, y

poltorectx(r, theta) x coordinate of angle theta at distance r

poltorecty(r, theta) y coordinate of angle theta at distance r

3.8.10. Evaluate From

Scope: Definition For Function

Evaluate From x_0 To x_1 By Dx

Parameter	Value	Default
x_0	real	undefined
x_1	real	undefined
Dx	real	undefined

Summary Specifies the range and evaluation interval.

3.8.11. Expression Variable:

Scope: Definition For Function

Expression Variable: *Expr* = *VarType* *value_var_name...*

Parameter	Value	Default
<i>Expr</i>	string	undefined
<i>VarType</i>	{element element_sym_tensor element_tensor element_vector face global nodal nodal_sym_tensor nodal_tensor nodal_vector}	undefined
<i>value_var_name</i>	string...	undefined

Summary Specifies what the arguments of an expression correspond to. For example:

```
BEGIN DEFINITION FOR FUNCTION dx_shear TYPE = ANALYTIC
EXPRESSION variable: mx = NODAL model_coordinates(x) EXPRESSION variable:
my = NODAL model_coordinates(y) EXPRESSION variable: time = GLOBAL time
EVALUATE EXPRESSION = "(time/termTime)*(stretchx*(mx - 0.0) +
((my-0.25)/0.5)*stretchxy)" END
```

Assuming the above expression is being evaluated on nodes the current values for x and y model coordinates would be placed into mx and my and current analysis time placed into time

3.8.12. Expression Variable:

Scope: Definition For Function

Expression Variable: *Expr*

Parameter	Value	Default
<i>Expr</i>	string	undefined

Summary Specifies what the arguments of an expression exists, but does not define it correspond to. For example:

```
BEGIN DEFINITION FOR FUNCTION dx_shear TYPE = ANALYTIC
EXPRESSION variable: mx EXPRESSION variable: my EXPRESSION variable: time
EVALUATE EXPRESSION = "(time/termTime)*(stretchx*(mx - 0.0) +
((my-0.25)/0.5)*stretchxy)" END
```

Call function must determine what each variable actually is based off of the string name

3.8.13. Ordinate

Scope: Definition For Function

Ordinate {=|are|is} *Name...*

Parameter	Value	Default
<i>Name</i>	string...	undefined

Summary Specifies a string identifier for the dependent variable. Optionally specify a scale and/or offset value which transforms the ordinate values into $\text{scaled\_ordinate} = \text{scale} * (\text{ordinate} + \text{ordinate\_offset})$.

3.8.14. Ordinate Offset

Scope: Definition For Function

Ordinate Offset {=|are|is} *Ordinate_offset*

Parameter	Value	Default
<i>Ordinate_offset</i>	real	undefined

Summary Alias for Y OFFSET

3.8.15. Ordinate Scale

Scope: Definition For Function

Ordinate Scale {=|are|is} *Ordinate_scale*

Parameter	Value	Default
<i>Ordinate_scale</i>	real	undefined

Summary Alias for Y SCALE

3.8.16. Scale By

Scope: Definition For Function

Scale By x

Parameter	Value	Default
x	real	undefined

Summary Specifies a scale factor to be applied.

3.8.17. Type

Scope: Definition For Function

Type `{=|are|is} Type`

Parameter	Value	Default
<i>Type</i>	<code>{analytic constant multicolumn piecewise linear piecewise analytic piecewise constant piecewise linear piecewise multivariate xtable}</code>	undefined

Summary Specifies the type of function.

3.8.18. X Offset

Scope: Definition For Function

X Offset `{=|are|is} X_offset`

Parameter	Value	Default
<i>X_offset</i>	real	undefined

Summary Sets an offset for the x-axis

3.8.19. X Scale

Scope: Definition For Function

X Scale `{=|are|is} X_scale`

Parameter	Value	Default
<i>X_scale</i>	real	undefined

Summary Sets a scale factor for the x-axis

3.8.20. Y Offset

Scope: Definition For Function

Y Offset {=|are|is} *Y_offset*

Parameter	Value	Default
<i>Y_offset</i>	real	undefined

Summary Sets an offset for the y-axis

3.8.21. Y Scale

Scope: Definition For Function

Y Scale {=|are|is} *Y_scale*

Parameter	Value	Default
<i>Y_scale</i>	real	undefined

Summary Sets a scale factor for the y-axis

3.9. VALUES

Scope: Definition For Function

Begin Values *empty*

Xyvalues...

End

Summary Lists the values of the function. The values should be listed one pair per line, independent variable first, with whitespace or comma as a separator.

3.9.1.

Scope: Values

Xyvalues...

Parameter	Value	Default
<i>Xyvalues</i>	real...	undefined

Summary For a piecewise linear function, lists an x-y pair for the nth interpolation point.

3.10. RESTARTING

Convenient utilities are provided for restarting an analysis from previous results. The most general capability supplements the results of a previous analysis with internal state variables to continue an analysis. In this case the input mesh is supplied from the Input Database Name from the Finite Element Model command block [3.1](#) and the restart information is obtained from the the Input Database Name from the Restart Data command block [25.6](#). Continuation of a job using restart data output is invoked using the command line which follows.

Often one wishes to restart an analysis by initializing with results from another analysis. For this case Aria provides another means, IC READ_FILE [8.7](#), by which to begin the job with variables from existing results.

4. MATERIAL PROPERTIES

4.1. ARIA MATERIAL OVERVIEW

Material property values are prescribed for unique material names using input line commands within an "Aria Material" command block. The association of these material properties with mesh entities is specified within the Finite Element Model command block [3.1](#).

The general format of the material property line commands as follows

```
Property Type = Model_Name Value_Name = Value Model_Parameter1 ....  
Model_ParameterN.
```

For some material properties, clarification of how the property is to be used must be also be supplied. This clarification usually impacts the computational efficiency of how the property values are being used. As an example, in the case of diffusion coefficients one needs to specify whether it will be used in a scalar or tensor based formulation of flux.

Chemical material models solved using the CHEMEQ library require an entire set of parameters. In this case those parameters are defined within a `Parameters for CHEMEQ` command block embedded within the Aria Material command block. A description of the CHEMEQ related parameters is contained in a subsequent chapter [36.2](#).

The material models `Encore Function`, `Global`, `User Function`, `Polynomial`, `User Field` and `Exponential` are termed `Generic` and are available for any material property evaluation. The `Constant` material model is also available for all properties but differs syntactically for each material property.



Known Issue: The feature toggling capability is not currently supported for setting material property values, although the line command to do so is listed when the material is specified as a `User_Function`.

Aria material command blocks appear in the Domain scope of the input file as illustrated below.

```
Begin Sierra myJob  
.  
  Begin Aria Material my_mat  
  .  
    material property commands
```

```

.
End   Aria Material my_mat
.
Begin Procedure My_Aria_Procedure
.
    Begin Aria Region My_Region
    .
    .
    End   Aria Region My_Region
.
End   Procedure My_Aria_Procedure
.
End   Sierra myJob

```

4.1.1. Absorption Coefficient

Scope: Aria Material

Absorption Coefficient [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |K = *k*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>k</i>	real	undefined

Summary Constant value

4.1.2. Absorption Coefficient: Copied

Scope: Aria Material

Absorption Coefficient: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.3. Absorption Coefficient: User Plugin

Scope: Aria Material

Absorption Coefficient: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.4. Absorption Coefficient: Scalar String Function

Scope: Aria Material

Absorption Coefficient: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.5. Absorption Coefficient: Porous Phase Average

Scope: Aria Material

Absorption Coefficient: Porous Phase Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous_Phase_Average [Liquid_Phase_Name = *Liquid_Phase_Name* | Gas_Phase_Name = *Gas_Phase_Name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Liquid_Phase_Name</i>	"string"	undefined
<i>Gas_Phase_Name</i>	"string"	undefined

Summary Absorption coefficient for a multiphase material of two or three phases

4.1.6. Absorption Cross Section

Scope: Aria Material

Absorption Cross Section [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Abs = *abs*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>abs</i>	real	undefined

Summary Constant value

4.1.7. Absorption Cross Section: Copied

Scope: Aria Material

Absorption Cross Section: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.8. Absorption Cross Section: User Plugin

Scope: Aria Material

Absorption Cross Section: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |*magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.9. Absorption Cross Section: Scalar String Function

Scope: Aria Material

Absorption Cross Section: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.10. Absorption Cross Section: Linearized

Scope: Aria Material

Absorption Cross Section: Linearized [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Linearized [Sigma_0 = *sigma_0* | D_Sigma_D_Rho = *d_sigma_d_rho* | D_Sigma_D_T = *d_sigma_d_t* | T_Sigma_0 = *t_sigma_0* | Rho_Sigma_0 = *rho_sigma_0*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>sigma_0</i>	real	undefined
<i>d_sigma_d_rho</i>	real	undefined
<i>d_sigma_d_t</i>	real	undefined
<i>t_sigma_0</i>	real	undefined
<i>rho_sigma_0</i>	real	undefined

Summary Linearized absorption cross section

4.1.11. Absorption Cross Section: Calore User Sub

Scope: Aria Material

Absorption Cross Section: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Calore user subroutine absorption cross section

4.1.12. Advected Bubble

Scope: Aria Material

Advected Bubble [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.13. Advected Bubble: Copied

Scope: Aria Material

Advected Bubble: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.14. Advected Bubble: User Plugin

Scope: Aria Material

Advected Bubble: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.15. Advected Bubble: Scalar String Function

Scope: Aria Material

Advected Bubble: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.16. Advection Velocity

Scope: Aria Material

Advection Velocity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Valuex = *valuex* |Valuey = *valuey* |Valuez = *valuez*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>valuex</i>	real	undefined
<i>valuey</i>	real	undefined
<i>valuez</i>	real	undefined

Summary Constant value

4.1.17. Advection Velocity: User Plugin

Scope: Aria Material

Advection Velocity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.18. Advection Velocity: Vector String Function

Scope: Aria Material

Advection Velocity: Vector String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Vector_String_Function [F_X = *f_x* | F_Y = *f_y* | F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

4.1.19. Air Water Mass Flux: Fickian

Scope: Aria Material

Air Water Mass Flux: Fickian [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Fickian []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Fickian diffusion for the air-water mass flux

4.1.20. Altitude

Scope: Aria Material

Altitude [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* | A = *a*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>a</i>	real	undefined

Summary Constant value

4.1.21. Altitude: Copied

Scope: Aria Material

Altitude: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.22. Altitude: User Plugin

Scope: Aria Material

Altitude: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.23. Altitude: Scalar String Function

Scope: Aria Material

Altitude: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.24. Ambient Pressure

Scope: Aria Material

Ambient Pressure [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.25. Ambient Pressure: Copied

Scope: Aria Material

Ambient Pressure: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.26. Ambient Pressure: User Plugin

Scope: Aria Material

Ambient Pressure: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.27. Ambient Pressure: Scalar String Function

Scope: Aria Material

Ambient Pressure: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.28. Angular Intensity

Scope: Aria Material

Angular Intensity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.29. Angular Intensity: Copied

Scope: Aria Material

Angular Intensity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.30. Angular Intensity: User Plugin

Scope: Aria Material

Angular Intensity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.31. Angular Intensity: Scalar String Function

Scope: Aria Material

Angular Intensity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.32. Annulus Diameter Ratio

Scope: Aria Material

Annulus Diameter Ratio [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |R = *r*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>r</i>	real	undefined

Summary Constant value

4.1.33. Annulus Diameter Ratio: Copied

Scope: Aria Material

Annulus Diameter Ratio: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.34. Annulus Diameter Ratio: User Plugin

Scope: Aria Material

Annulus Diameter Ratio: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.35. Annulus Diameter Ratio: Scalar String Function

Scope: Aria Material

Annulus Diameter Ratio: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.36. Annulus Diameter Ratio: Spatial User Function

Scope: Aria Material

Annulus Diameter Ratio: Spatial User Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Spatial_User_Function [Threshold = *threshold* |Multiplier = *multiplier* |Name = *name* |Bar = *bar* |X = *x*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>threshold</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>name</i>	"string"	undefined
<i>bar</i>	"string"	undefined
<i>x</i>	"string"	undefined

Summary Spatially varying annulus diameter ratio based on a coordinate dependent user function

4.1.37. Annulus Diameter Ratio: Correlation

Scope: Aria Material

Annulus Diameter Ratio: Correlation [{of|species|subindex} *Species*]= Correlation [R = *r* |Threshold = *threshold* |Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>r</i>	real	undefined
<i>threshold</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation annulus diameter ratio based on hydraulic diameter and wetted perimeter

4.1.38. Annulus Diameter Ratio: Correlation Spatial User Function

Scope: Aria Material

Annulus Diameter Ratio: Correlation Spatial User Function [{of|species|subindex} *Species*]= Correlation_Spatial_User_Function [Threshold = *threshold* |Multiplier = *multiplier* |Name = *name* |Bar = *bar* |X = *x* |Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>threshold</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>name</i>	"string"	undefined
<i>bar</i>	"string"	undefined
<i>x</i>	"string"	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation spatially varying annulus diameter ratio based on a coordinate dependent user function

4.1.39. Auxiliary Mesh Field: Scalar

Scope: Aria Material

Auxiliary Mesh Field: Scalar [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar [Field_Name = *field_name* |Expression_Name = *expression_name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>field_name</i>	"string"	undefined
<i>expression_name</i>	"string"	undefined

Summary Scalar auxiliary mesh field

4.1.40. Bar Area

Scope: Aria Material

Bar Area [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* | A = *a*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>a</i>	real	undefined

Summary Constant value

4.1.41. Bar Area: Copied

Scope: Aria Material

Bar Area: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.42. Bar Area: User Plugin

Scope: Aria Material

Bar Area: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.43. Bar Area: Scalar String Function

Scope: Aria Material

Bar Area: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.44. Bar Area: Element Attribute

Scope: Aria Material

Bar Area: Element Attribute [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Element_Attribute [Multiplier = *multiplier* |Attribute_Name = *attribute_name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>attribute_name</i>	"string"	undefined

Summary Distribution Factor for the bar area

4.1.45. Bar Perimeter

Scope: Aria Material

Bar Perimeter [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |P = *p*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>p</i>	real	undefined

Summary Constant value

4.1.46. Bar Perimeter: Copied

Scope: Aria Material

Bar Perimeter: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.47. Bar Perimeter: User Plugin

Scope: Aria Material

Bar Perimeter: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.48. Bar Perimeter: Scalar String Function

Scope: Aria Material

Bar Perimeter: Scalar String Function [{of|species|subindex} *Species* |
{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.49. Bar Perimeter: Element Attribute

Scope: Aria Material

Bar Perimeter: Element Attribute [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Element_Attribute [Multiplier = *multiplier* |Attribute_Name = *attribute_name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>attribute_name</i>	"string"	undefined

Summary Distribution Factor for the bar perimeter

4.1.50. Bc Heat Flux

Scope: Aria Material

Bc Heat Flux [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Qx = *qX* |Qy = *qY* |Qz = *qZ*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>qX</i>	real	undefined
<i>qY</i>	real	undefined
<i>qZ</i>	real	undefined

Summary Constant value

4.1.51. Bc Heat Flux: User Plugin

Scope: Aria Material

Bc Heat Flux: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |*magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.52. Bc Heat Flux: Vector String Function

Scope: Aria Material

Bc Heat Flux: Vector String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Vector_String_Function [F_X = *f_x* |F_Y = *f_y* |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

4.1.53. Bc Heat Flux: User Field Times Inward Normal

Scope: Aria Material

Bc Heat Flux: User Field Times Inward Normal [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
User_Field_Times_Inward_Normal [Name = *name* |Scaling = *scaling* |
Global_Var = *global_var* |Time_Function = *time_function*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>scaling</i>	real	undefined
<i>global_var</i>	"string"	undefined
<i>time_function</i>	"string"	undefined

Summary Transform a scalar flux term into a vector quantity by multiplying by the inward surface normal.

4.1.54. Bc Rad Reference Temperature

Scope: Aria Material

Bc Rad Reference Temperature [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |T_Ref = *t_ref*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>t_ref</i>	real	undefined

Summary Constant value

4.1.55. Bc Rad Reference Temperature: Copied

Scope: Aria Material

Bc Rad Reference Temperature: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.56. Bc Rad Reference Temperature: User Plugin

Scope: Aria Material

Bc Rad Reference Temperature: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.57. Bc Rad Reference Temperature: Scalar String Function

Scope: Aria Material

Bc Rad Reference Temperature: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.58. Bc Rad Reference Temperature: Bulk Node

Scope: Aria Material

Bc Rad Reference Temperature: Bulk Node [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Bulk_Node [Name = *name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined

Summary Use a bulk node temperature as the reference temperature for radiation boundary conditions

4.1.59. Bc Rad Reference Temperature: Calore User Sub

Scope: Aria Material

Bc Rad Reference Temperature: Calore User Sub [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

4.1.60. Bc Rad Reference Temperature: Fortran

Scope: Aria Material

Bc Rad Reference Temperature: Fortran [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Fortran [Multiplier = *multiplier* | Sub_Name = *sub_name* | Real_Data = *real_data* | Int_Data = *int_data* | Resource_Name = *resource_name* | Data = *data*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>sub_name</i>	"string"	undefined
<i>real_data</i>	"string"	undefined
<i>int_data</i>	"string"	undefined
<i>resource_name</i>	"string"	undefined
<i>data</i>	"string"	undefined

Summary Fortran subroutine reference temperature.

4.1.61. Bc Reference Temperature

Scope: Aria Material

Bc Reference Temperature [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value* | T_Ref = *t_ref*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>t_ref</i>	real	undefined

Summary Constant value

4.1.62. Bc Reference Temperature: Copied

Scope: Aria Material

Bc Reference Temperature: Copied [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.63. Bc Reference Temperature: User Plugin

Scope: Aria Material

Bc Reference Temperature: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.64. Bc Reference Temperature: Scalar String Function

Scope: Aria Material

Bc Reference Temperature: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.65. Bc Reference Temperature: Bulk Node

Scope: Aria Material

Bc Reference Temperature: Bulk Node [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Bulk_Node [Name = *name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined

Summary Use a bulk node temperature as the reference temperature for convection boundary conditions

4.1.66. Bc Reference Temperature: Calore User Sub

Scope: Aria Material

Bc Reference Temperature: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

4.1.67. Bc Reference Temperature: Computed Adiabatic Wall

Scope: Aria Material

Bc Reference Temperature: Computed Adiabatic Wall [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Computed_Adiabatic_Wall [T_On = *t_on* |T_Off = *t_off* |Specific_Heat_Function = *specific_heat_function* |Conductivity_Function = *conductivity_function* |Viscosity_Function = *viscosity_function* |Offset_Direction = *offset_direction* |Coord_Offset = *coord_offset* |Gas_Constant = *gas_constant*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>t_on</i>	real	undefined
<i>t_off</i>	real	undefined
<i>specific_heat_function</i>	"string"	undefined
<i>conductivity_function</i>	"string"	undefined
<i>viscosity_function</i>	"string"	undefined
<i>offset_direction</i>	"string"	undefined
<i>coord_offset</i>	"string"	undefined
<i>gas_constant</i>	real	undefined

Summary Adiabatic wall temperature computed based upon freestream and recovery factor.

4.1.68. Bc Reference Temperature: Fortran

Scope: Aria Material

Bc Reference Temperature: Fortran [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Fortran [Multiplier = *multiplier* | Sub_Name = *sub_name* | Real_Data = *real_data* | Int_Data = *int_data* | Resource_Name = *resource_name* | Data = *data*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>sub_name</i>	"string"	undefined
<i>real_data</i>	"string"	undefined
<i>int_data</i>	"string"	undefined
<i>resource_name</i>	"string"	undefined
<i>data</i>	"string"	undefined

Summary Fortran subroutine reference temperature.

4.1.69. Beta

Scope: Aria Material

Beta [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* | Beta = *beta*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>beta</i>	real	undefined

Summary Constant value

4.1.70. Beta: Copied

Scope: Aria Material

Beta: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.71. Beta: User Plugin

Scope: Aria Material

Beta: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.72. Beta: Scalar String Function

Scope: Aria Material

Beta: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.73. Beta: Converted

Scope: Aria Material

Beta: Converted [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Converted []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Coefficient of thermal stress computed from Poisson's ratio, thermal expansion coefficient and elastic modulus

4.1.74. Beta: Linear

Scope: Aria Material

Beta: Linear [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Linear [A = *a* | B = *b*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>a</i>	real	undefined
<i>b</i>	real	undefined

Summary This model has been deprecated and removed from the code.

4.1.75. Body Acceleration

Scope: Aria Material

Body Acceleration [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Valuex = *valuex* | Valuey = *valuey* | Valuez =
valuez]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>valuex</i>	real	undefined
<i>valuey</i>	real	undefined
<i>valuez</i>	real	undefined

Summary Constant value

4.1.76. Body Acceleration: User Plugin

Scope: Aria Material

Body Acceleration: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.77. Body Acceleration: Vector String Function

Scope: Aria Material

Body Acceleration: Vector String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Vector_String_Function [F_X = f_x | F_Y = f_y | F_Z = f_z]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f_x	"string"	undefined
f_y	"string"	undefined
f_z	"string"	undefined

Summary Value from a string function

4.1.78. Boundary Entrained Enthalpy

Scope: Aria Material

Boundary Entrained Enthalpy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* | H = *h*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>h</i>	real	undefined

Summary Constant value

4.1.79. Boundary Entrained Enthalpy: Copied

Scope: Aria Material

Boundary Entrained Enthalpy: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.80. Boundary Entrained Enthalpy: User Plugin

Scope: Aria Material

Boundary Entrained Enthalpy: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.81. Boundary Entrained Enthalpy: Scalar String Function

Scope: Aria Material

Boundary Entrained Enthalpy: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.82. Boundary Entrained Mass Fraction

Scope: Aria Material

Boundary Entrained Mass Fraction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Y = *y*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>y</i>	real	undefined

Summary Constant value

4.1.83. Boundary Entrained Mass Fraction: Copied

Scope: Aria Material

Boundary Entrained Mass Fraction: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.84. Boundary Entrained Mass Fraction: User Plugin

Scope: Aria Material

Boundary Entrained Mass Fraction: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.85. Boundary Entrained Mass Fraction: Scalar String Function

Scope: Aria Material

Boundary Entrained Mass Fraction: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.86. Boundary Pressure

Scope: Aria Material

Boundary Pressure [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* | P = *p*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>p</i>	real	undefined

Summary Constant value

4.1.87. Boundary Pressure: Copied

Scope: Aria Material

Boundary Pressure: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.88. Boundary Pressure: User Plugin

Scope: Aria Material

Boundary Pressure: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.89. Boundary Pressure: Scalar String Function

Scope: Aria Material

Boundary Pressure: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.90. Bulk Conductivity

Scope: Aria Material

Bulk Conductivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Kbulk = *Kbulk*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>Kbulk</i>	real	undefined

Summary Constant value

4.1.91. Bulk Conductivity: Copied

Scope: Aria Material

Bulk Conductivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.92. Bulk Conductivity: User Plugin

Scope: Aria Material

Bulk Conductivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.93. Bulk Conductivity: Scalar String Function

Scope: Aria Material

Bulk Conductivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.94. Bulk Conductivity: T Exponent

Scope: Aria Material

Bulk Conductivity: T Exponent [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= T_Exponent [Kbulk_Ref = *kbulk_ref* |T_Ref = *t_ref* |N = *n*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>kbulk_ref</i>	real	undefined
<i>t_ref</i>	real	undefined
<i>n</i>	real	undefined

Summary Thermal conductivity for bulk material. $\kappa_{\text{bulk}} = \kappa_{\text{ref}} \frac{\rho_{\text{solid}}}{\rho_{\text{bulk}}} \left(\frac{T}{T_{\text{ref}}} \right)^n$.

4.1.95. Bulk Conductivity: Volume Average

Scope: Aria Material

Bulk Conductivity: Volume Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Volume_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Bulk conductivity computed from volume average of species bulk conductivities

4.1.96. Bulk Conductivity: Linear Temperature And Density

Scope: Aria Material

Bulk Conductivity: Linear Temperature And Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Linear_Temperature_And_Density [C_0 = *c_0* |C_Rho = *C_rho* |C_T = *c_t*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>c_0</i>	real	undefined
<i>C_rho</i>	real	undefined
<i>c_t</i>	real	undefined

Summary Bulk conductivity that is a linear function of both temperature and density.

$$\kappa_{bulk} = C_0 + C_\rho \rho + C_T T$$

4.1.97. Bulk Conductivity: Porous Phase Average

Scope: Aria Material

Bulk Conductivity: Porous Phase Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous_Phase_Average [Liquid_Phase_Name = *Liquid_Phase_Name* |Gas_Phase_Name = *Gas_Phase_Name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Liquid_Phase_Name</i>	"string"	undefined
<i>Gas_Phase_Name</i>	"string"	undefined

Summary Bulk conductivity for a multiphase material of two or three phases

4.1.98. Bulk Density

Scope: Aria Material

Bulk Density [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |Rho_B = *rho_b*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>rho_b</i>	real	undefined

Summary Constant value

4.1.99. Bulk Density: Copied

Scope: Aria Material

Bulk Density: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.100. Bulk Density: User Plugin

Scope: Aria Material

Bulk Density: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.101. Bulk Density: Scalar String Function

Scope: Aria Material

Bulk Density: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.102. Bulk Density: T Exponent

Scope: Aria Material

Bulk Density: T Exponent [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= T_Exponent [Rho_Ref = *rho_ref* |T_Ref = *t_ref* |N = *n*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>rho_ref</i>	real	undefined
<i>t_ref</i>	real	undefined
<i>n</i>	real	undefined

Summary Bulk density as a power of normalized temperature $\rho_{\text{bulk}} = \rho_{\text{ref}} \left(\frac{T}{T_{\text{ref}}} \right)^n$.

4.1.103. Bulk Density: Single Component Ideal Gas

Scope: Aria Material

Bulk Density: Single Component Ideal Gas [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Single_Component_Ideal_Gas [P_Ref = *p_ref* |T_Ref = *t_ref* |M = *m* |R = *r*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>p_ref</i>	real	undefined
<i>t_ref</i>	real	undefined
<i>m</i>	real	undefined
<i>r</i>	real	undefined

4.1.104. Bulk Element Pressure

Scope: Aria Material

Bulk Element Pressure [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [$V = v$ |Bulk_Node = *bulk_node*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>v</i>	real	undefined
<i>bulk_node</i>	"string"	undefined

Summary Constant value for the bulk element pressure

4.1.105. Bulk Element Pressure: Integrated

Scope: Aria Material

Bulk Element Pressure: Integrated [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Integrated [Name = *name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined

Summary Bulk element pressure computed from equation of state

4.1.106. Bulk Element Pressure: Calore User Sub

Scope: Aria Material

Bulk Element Pressure: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Bulk_Node = *bulk_node*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>bulk_node</i>	"string"	undefined

Summary Bulk element pressure from Calore User Subroutine

4.1.107. Bulk Element Volume

Scope: Aria Material

Bulk Element Volume [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [$V = v$ |Bulk_Node = *bulk_node*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>v</i>	real	undefined
<i>bulk_node</i>	"string"	undefined

Summary Constant value for the bulk element volume

4.1.108. Bulk Element Volume: Integrated

Scope: Aria Material

Bulk Element Volume: Integrated [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Integrated [Name = *name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined

Summary Bulk element volume computed from bounding surfaces

4.1.109. Bulk Element Volume: Calore User Sub

Scope: Aria Material

Bulk Element Volume: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Bulk_Node = *bulk_node*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>bulk_node</i>	"string"	undefined

Summary Bulk element volume from Calore User Subroutine

4.1.110. Bulk Mass Density: Porous Density

Scope: Aria Material

Bulk Mass Density: Porous Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous_Density []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Bulk mass density computed from density and porosity.

4.1.111. Bulk Mass Density: Density

Scope: Aria Material

Bulk Mass Density: Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Density []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Bulk mass density copied from density.

4.1.112. Bulk Mass Density: Mass Fraction Density

Scope: Aria Material

Bulk Mass Density: Mass Fraction Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mass_Fraction_Density []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Bulk mass density computed from mass fraction and density.

4.1.113. Bulk Mass Density: Mass Fraction Porous Density

Scope: Aria Material

Bulk Mass Density: Mass Fraction Porous Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mass_Fraction_Porous_Density []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Bulk mass density computed from mass fraction, porosity and density.

4.1.114. Bulk Mass Density: Multiphase Porous Density

Scope: Aria Material

Bulk Mass Density: Multiphase Porous Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Multiphase_Porous_Density []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Bulk mass density computed from density, saturation and porosity for a multiphase material.

4.1.115. Bulk Mass Density

Scope: Aria Material

Bulk Mass Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.116. Bulk Mass Density: Copied

Scope: Aria Material

Bulk Mass Density: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.117. Bulk Mass Density: User Plugin

Scope: Aria Material

Bulk Mass Density: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.118. Bulk Mass Density: Scalar String Function

Scope: Aria Material

Bulk Mass Density: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.119. Bulk Viscosity

Scope: Aria Material

Bulk Viscosity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Kappa = *kappa*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>kappa</i>	real	undefined

Summary Constant value

4.1.120. Bulk Viscosity: Copied

Scope: Aria Material

Bulk Viscosity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.121. Bulk Viscosity: User Plugin

Scope: Aria Material

Bulk Viscosity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.122. Bulk Viscosity: Scalar String Function

Scope: Aria Material

Bulk Viscosity: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.123. Bulk Viscosity: Curing Foam

Scope: Aria Material

Bulk Viscosity: Curing Foam [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Curing_Foam [Extent_Subindex = *extent_subindex* | Extent_Species_Name = *extent_species_name* | Extent_Species_Phase = *extent_species_phase* | Mu_A = *mu_a* | T_Mu = *T_mu* | N_Mu = *n_mu* | Ksi_C = *ksi_c* | M_Ksi_C = *m_ksi_c* | E_Mu = *E_mu* | R = *r*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>extent_subindex</i>	integer	undefined
<i>extent_species_name</i>	"string"	undefined
<i>extent_species_phase</i>	"string"	undefined
<i>mu_a</i>	real	undefined
<i>T_mu</i>	real	undefined
<i>n_mu</i>	real	undefined
<i>ksi_c</i>	real	undefined
<i>m_ksi_c</i>	real	undefined
<i>E_mu</i>	real	undefined
<i>r</i>	real	undefined

4.1.124. Bulk Viscosity: Phase Average

Scope: Aria Material

Bulk Viscosity: Phase Average [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Phase_Average [Subindex_A = *subindex_a* | Subindex_B = *subindex_b*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>subindex_a</i>	integer	undefined
<i>subindex_b</i>	integer	undefined

Summary Phase-averaged values

4.1.125. Bulk Viscosity: Interpolated Phase Average

Scope: Aria Material

Bulk Viscosity: Interpolated Phase Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Interpolated_Phase_Average [Subindex_A = *subindex_a* | Subindex_B = *subindex_b*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>subindex_a</i>	integer	undefined
<i>subindex_b</i>	integer	undefined

Summary Phase-averaged values

4.1.126. Bulk Viscosity: Mass Average

Scope: Aria Material

Bulk Viscosity: Mass Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mass_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Bulk Viscosity computed from mass average of species viscosities

4.1.127. Bulk Viscosity: Volume Average

Scope: Aria Material

Bulk Viscosity: Volume Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Volume_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Bulk Viscosity computed from volume average of species viscosities, over a material phase

4.1.128. Burn Front Width

Scope: Aria Material

Burn Front Width [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Width = *width* |Use_Crossing_Time = *use_crossing_time*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>width</i>	real	undefined
<i>use_crossing_time</i>	integer	undefined

Summary Specification of a constant width burn front

4.1.129. Burn Heat Release

Scope: Aria Material

Burn Heat Release [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.130. Burn Heat Release: Copied

Scope: Aria Material

Burn Heat Release: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.131. Burn Heat Release: User Plugin

Scope: Aria Material

Burn Heat Release: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.132. Burn Heat Release: Scalar String Function

Scope: Aria Material

Burn Heat Release: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.133. Burn Initiation: Temperature

Scope: Aria Material

Burn Initiation: Temperature [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Temperature [Tign = *Tign* |
Min_Ignition_Spacing = *min_ignition_spacing* |Hard_Start_Ignition =
hard_start_ignition]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Tign</i>	real	undefined
<i>min_ignition_spacing</i>	real	undefined
<i>hard_start_ignition</i>	integer	undefined

Summary Thermally activated burn front. If `min_ignition_spacing` is provided then multiple burn initiations are supported, otherwise only one initiation per block is supported. Pick a minimum ignition spacing (d) that is several times larger than your interface width ($d > 3w$), and that provides $Da \gg 10$, where $Da = \frac{v_b d}{\alpha}$ (α = thermal diffusivity and v_b = burn speed) By default, the level set is shifted back by $w/2$ on ignition so the burn starts smoothly. To disable this and use a hard start (no shifting of burn front) set `hard_start_ignition=1`

4.1.134. Burn Speed

Scope: Aria Material

Burn Speed [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.135. Capillary Pressure

Scope: Aria Material

Capillary Pressure [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.136. Capillary Pressure: Copied

Scope: Aria Material

Capillary Pressure: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.137. Capillary Pressure: User Plugin

Scope: Aria Material

Capillary Pressure: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.138. Capillary Pressure: Scalar String Function

Scope: Aria Material

Capillary Pressure: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.139. Capillary Pressure: Van Genuchten

Scope: Aria Material

Capillary Pressure: Van Genuchten [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Van_Genuchten [Residual_Wetting_Phase_Saturation = *residual_wetting_phase_saturation* | Residual_Nonwetting_Phase_Saturation = *residual_nonwetting_phase_saturation* |Beta_Field = *beta_field* |Pcref_Field = *pcref_field* |Sgr_Field = *sgr_field* |Slr_Field = *slr_field* |Reference_Capillary_Pressure = *reference_capillary_pressure* |Beta = *beta* |Wetting_Phase = *wetting_phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>residual_wetting_phase_saturation</i>	real	undefined
<i>residual_nonwetting_phase_saturation</i>	real	undefined
<i>beta_field</i>	"string"	undefined
<i>pcref_field</i>	"string"	undefined
<i>sgr_field</i>	"string"	undefined
<i>slr_field</i>	"string"	undefined
<i>reference_capillary_pressure</i>	real	undefined
<i>beta</i>	real	undefined
<i>wetting_phase</i>	"string"	undefined

Summary A Van Genuchten model for air/water capillary pressure

4.1.140. Capillary Pressure: Encore Saturation

Scope: Aria Material

Capillary Pressure: Encore Saturation [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Encore_Saturation [Name = *name* | Result_Name = *result_name* | Eval_Type = *eval_type*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>result_name</i>	"string"	undefined
<i>eval_type</i>	"string"	undefined

Summary A Van Genuchten model for air/water capillary pressure based on an encore function for saturation

4.1.141. Capillary Pressure: Udell Cubic

Scope: Aria Material

Capillary Pressure: Udell Cubic [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Udell_Cubic [Residual_Wetting_Phase_Saturation = *residual_wetting_phase_saturation* | Residual_Nonwetting_Phase_Saturation = *residual_nonwetting_phase_saturation* | Sigma = *sigma* | C1 = *c1* | C2 = *c2* | C3 = *c3* | Wetting_Phase = *wetting_phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>residual_wetting_phase_saturation</i>	real	undefined
<i>residual_nonwetting_phase_saturation</i>	real	undefined
<i>sigma</i>	real	undefined
<i>c1</i>	real	undefined
<i>c2</i>	real	undefined
<i>c3</i>	real	undefined
<i>wetting_phase</i>	"string"	undefined

Summary A Udel cubic model for air/water capillary pressure

4.1.142. Capillary Pressure: Computed

Scope: Aria Material

Capillary Pressure: Computed [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Computed [Wetting_Phase = *wetting_phase* | Nonwetting_Phase = *nonwetting_phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>wetting_phase</i>	"string"	undefined
<i>nonwetting_phase</i>	"string"	undefined

Summary Capillary pressure computed based on the pressure difference between the non-wetting and wetting phases, each of which may be specified as parameters.

4.1.143. Capillary Pressure: Brooks Corey

Scope: Aria Material

Capillary Pressure: Brooks Corey [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Brooks_Corey [Wetting_Phase = *wetting_phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>wetting_phase</i>	"string"	undefined

Summary Capillary pressure computed based on the Brooks-Corey model

4.1.144. Characteristic Length: Correlation

Scope: Aria Material

Characteristic Length: Correlation [{of|species|subindex} *Species*]=
Correlation [Dh = *Dh* | Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>Dh</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation characteristic length with constant value

4.1.145. Characteristic Length: Correlation Bar Perimeter

Scope: Aria Material

Characteristic Length: Correlation Bar Perimeter [{of|species|subindex} *Species*]= Correlation_Bar_Perimeter [Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation characteristic length with bar perimeter model

4.1.146. Characteristic Length: Correlation Hydraulic Diameter

Scope: Aria Material

Characteristic Length: Correlation Hydraulic Diameter [{of|species|subindex} *Species*]= Correlation_Hydraulic_Diameter [Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation characteristic length with hydraulic diameter model

4.1.147. Characteristic Length: Correlation Wetted Perimeter

Scope: Aria Material

Characteristic Length: Correlation Wetted Perimeter [{of|species|subindex} *Species*]= Correlation_Wetted_Perimeter [Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation characteristic length with wetted perimeter model

4.1.148. Charge Density

Scope: Aria Material

Charge Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.149. Charge Density: Copied

Scope: Aria Material

Charge Density: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.150. Charge Density: User Plugin

Scope: Aria Material

Charge Density: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.151. Charge Density: Scalar String Function

Scope: Aria Material

Charge Density: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.152. Chemical Potential: Ideal Solution

Scope: Aria Material

Chemical Potential: Ideal Solution [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Ideal_Solution [R = *r* |
Temperature_Material_Phase = *temperature_material_phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>r</i>	real	undefined
<i>temperature_material_phase</i>	"string"	undefined

Summary Ideal solution chemical potential, $\mu = RT \log(C)$.

4.1.153. Chemical Potential: From Equilibrium Potential

Scope: Aria Material

Chemical Potential: From Equilibrium Potential [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Equilibrium_Potential [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	real	undefined

Summary Chemical potential from the equilibrium voltage of an electrochemical reaction. This model assumes that it is a single electron intercalation reaction and that only differences in the chemical potential are relevant, not the absolute magnitude. Therefore $\mu = -F\phi_{eq}$.

4.1.154. Chemical Potential: Isotropic Mesh Stress

Scope: Aria Material

Chemical Potential: Isotropic Mesh Stress [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Isotropic_Mesh_Stress [Strain_Coeff = *strain_coeff*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>strain_coeff</i>	real	undefined

Summary Contribution to the chemical potential from species strain. Assumes that the strain is isotropic so $\mu = \Omega\sigma_{kk}/3$ where Ω is the volumetric expansion coefficient and σ is the stress tensor. This model uses the mesh stress provided by a projection equation in order to recover stress gradients.

4.1.155. Contact Electrical Conductance Coefficient

Scope: Aria Material

Contact Electrical Conductance Coefficient [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |H = *h*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>h</i>	real	undefined

Summary Constant value

4.1.156. Contact Electrical Conductance Coefficient: Copied

Scope: Aria Material

Contact Electrical Conductance Coefficient: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.157. Contact Electrical Conductance Coefficient: User Plugin

Scope: Aria Material

Contact Electrical Conductance Coefficient: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |*magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.158. Contact Electrical Conductance Coefficient: Scalar String Function

Scope: Aria Material

Contact Electrical Conductance Coefficient: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.159. Contact Electrical Conductance Coefficient: Calore User Sub

Scope: Aria Material

Contact Electrical Conductance Coefficient: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

4.1.160. Contact Heat Transfer Coefficient

Scope: Aria Material

Contact Heat Transfer Coefficient [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |H = *h*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>h</i>	real	undefined

Summary Constant value

4.1.161. Contact Heat Transfer Coefficient: Copied

Scope: Aria Material

Contact Heat Transfer Coefficient: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.162. Contact Heat Transfer Coefficient: User Plugin

Scope: Aria Material

Contact Heat Transfer Coefficient: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.163. Contact Heat Transfer Coefficient: Scalar String Function

Scope: Aria Material

Contact Heat Transfer Coefficient: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.164. Contact Heat Transfer Coefficient: Calore User Sub

Scope: Aria Material

Contact Heat Transfer Coefficient: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

4.1.165. Continuity Diffusion Coefficient

Scope: Aria Material

Continuity Diffusion Coefficient [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.166. Continuity Diffusion Coefficient: Copied

Scope: Aria Material

Continuity Diffusion Coefficient: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.167. Continuity Diffusion Coefficient: User Plugin

Scope: Aria Material

Continuity Diffusion Coefficient: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.168. Continuity Diffusion Coefficient: Scalar String Function

Scope: Aria Material

Continuity Diffusion Coefficient: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [*F = f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.169. Continuity Diffusion Coefficient: Shakib

Scope: Aria Material

Continuity Diffusion Coefficient: Shakib [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Shakib []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Pressure POISSON with diffusion coefficient given by Shakib tau.

4.1.170. Continuity Diffusive Flux: Basic

Scope: Aria Material

Continuity Diffusive Flux: Basic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Basic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Basic model of continuity diffusive flux

4.1.171. Continuity Diffusive Flux: Pressure Poisson

Scope: Aria Material

Continuity Diffusive Flux: Pressure Poisson [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Pressure_Poisson []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary This model has been deprecated and removed from the code.

4.1.172. Continuity Face Stabilization Scaling: Default

Scope: Aria Material

Continuity Face Stabilization Scaling: Default [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Default []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Default face stabilization scaling for continuity equation

4.1.173. Cte

Scope: Aria Material

Cte [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Constant [Value = *value* |Cte = *cte*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>cte</i>	real	undefined

Summary Constant value

4.1.174. Cte: Copied

Scope: Aria Material

Cte: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.175. Cte: User Plugin

Scope: Aria Material

Cte: User Plugin [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.176. Cte: Scalar String Function

Scope: Aria Material

Cte: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.177. Current Density

Scope: Aria Material

Current Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Valuex = *valuex* | Valuey = *valuey* | Valuez = *valuez*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>valuex</i>	real	undefined
<i>valuey</i>	real	undefined
<i>valuez</i>	real	undefined

Summary Constant value

4.1.178. Current Density: User Plugin

Scope: Aria Material

Current Density: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.179. Current Density: Vector String Function

Scope: Aria Material

Current Density: Vector String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Vector_String_Function [F_X = f_x | F_Y = f_y | F_Z = f_z]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f_x	"string"	undefined
f_y	"string"	undefined
f_z	"string"	undefined

Summary Value from a string function

4.1.180. Current Density: Ohms Law

Scope: Aria Material

Current Density: Ohms Law [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Ohms_Law []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Ohms law current density

4.1.181. Current Density: Basic

Scope: Aria Material

Current Density: Basic [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Basic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Basic current density

4.1.182. Current Density: Electrolyte

Scope: Aria Material

Current Density: Electrolyte [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Electrolyte [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	real	undefined

Summary Electrolyte current density

4.1.183. Current Density: Dielectric Displacement

Scope: Aria Material

Current Density: Dielectric Displacement [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Dielectric_Displacement []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Dielectric displacement current density

4.1.184. Current Density: Thermoelectric

Scope: Aria Material

Current Density: Thermoelectric [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Thermoelectric []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Thermoelectric current density

4.1.185. Current Density: Mhd

Scope: Aria Material

Current Density: Mhd [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mhd [Magnetic_Field = *magnetic_field* |No_Adv = *no_adv*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>magnetic_field</i>	"string"	undefined
<i>no_adv</i>	"string"	undefined

Summary Magnetohydrodynamic current density

4.1.186. Current Density: Curl B

Scope: Aria Material

Current Density: Curl B [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Curl_B []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Calculate current density from magnetic field

4.1.187. Current Exchange Density

Scope: Aria Material

Current Exchange Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |I_0 = *i_0*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>i_0</i>	real	undefined

Summary Constant value

4.1.188. Current Exchange Density: Copied

Scope: Aria Material

Current Exchange Density: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.189. Current Exchange Density: User Plugin

Scope: Aria Material

Current Exchange Density: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.190. Current Exchange Density: Scalar String Function

Scope: Aria Material

Current Exchange Density: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.191. Cantera Xml File

Scope: Aria Material

Cantera Xml File {=*|are|is|*} *XML Path*

Parameter	Value	Default
<i>XML Path</i>	string	undefined

Description This specifies the name of the XML file used by Cantera to import the properties of the chemical species mixture. The order of the species in the simulation will be set by the order in this file.

4.1.192. Decay Constant: Hdiff

Scope: Aria Material

Decay Constant: Hdiff [{*of|species|subindex|*} *Species* |{*in|material_phase|*} *MaterialPhase*]= Hdiff [Decay = *decay*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>decay</i>	real	undefined

Summary Decay constant used for hydrogen transport

4.1.193. Density

Scope: Aria Material

Density [{*of|species|subindex|*} *Species* |{*in|material_phase|*} *MaterialPhase*]= Constant [Value = *value* |Rho = *rho*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>rho</i>	real	undefined

Summary Constant value

4.1.194. Density: Copied

Scope: Aria Material

Density: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.195. Density: User Plugin

Scope: Aria Material

Density: User Plugin [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.196. Density: Scalar String Function

Scope: Aria Material

Density: Scalar String Function [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.197. Density: Calore User Sub

Scope: Aria Material

Density: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

4.1.198. Density: Cantera

Scope: Aria Material

Density: Cantera [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Cantera [Poffset = *poffset*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>poffset</i>	real	undefined

Summary Cantera density summary

4.1.199. Density: Cantera Molten Salt

Scope: Aria Material

Density: Cantera Molten Salt [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Cantera_Molten_Salt [Densityconversion = *densityConversion* |Canteraxmlfile = *canteraXMLFile*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>densityConversion</i>	real	undefined
<i>canteraXMLFile</i>	"string"	undefined

Summary This model has been deprecated and removed from the code.

4.1.200. Density: Clsm

Scope: Aria Material

Density: Clsm [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Clsm [Primaryproperty = *primaryProperty* | Secondaryproperty = *secondaryProperty*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>primaryProperty</i>	real	undefined
<i>secondaryProperty</i>	real	undefined

Summary CLSM density

4.1.201. Density: Compressible Boussinesq

Scope: Aria Material

Density: Compressible Boussinesq [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Compressible_Boussinesq [Ref_Density = *ref_density* |Alpha = *alpha* |Ref_Pressure = *ref_pressure* |Ref_Temperature = *ref_temperature*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>ref_density</i>	real	undefined
<i>alpha</i>	real	undefined
<i>ref_pressure</i>	real	undefined
<i>ref_temperature</i>	real	undefined

Summary A compressible Boussinesq model for the density

4.1.202. Density: Curing Foam

Scope: Aria Material

Density: Curing Foam [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Curing_Foam [Vfrac_Subindex = *vfrac_subindex* |Rho_E = *rho_e* |Rho_F = *rho_f* |R = *r* |Phi_Zero = *phi_zero*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>vfrac_subindex</i>	integer	undefined
<i>rho_e</i>	real	undefined
<i>rho_f</i>	real	undefined
<i>r</i>	real	undefined
<i>phi_zero</i>	real	undefined

4.1.203. Density: Exp Decay

Scope: Aria Material

Density: Exp Decay [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Exp_Decay [Rho_Initial = *rho_initial* |Rho_Final = *rho_final* |K = *k*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>rho_initial</i>	real	undefined
<i>rho_final</i>	real	undefined
<i>k</i>	real	undefined

Summary Density as an exponential decay function in time

4.1.204. Density: Foam Time Temp

Scope: Aria Material

Density: Foam Time Temp [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Foam_Time_Temp [Rho_Initial = *rho_initial* |Rho_Final = *rho_final* |C_Param = *c_param* |D_Param = *d_param* |T_Max = *t_max* |Time_Naught = *time_naught*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>rho_initial</i>	real	undefined
<i>rho_final</i>	real	undefined
<i>c_param</i>	real	undefined
<i>d_param</i>	real	undefined
<i>t_max</i>	real	undefined
<i>time_naught</i>	real	undefined

Summary Foam time temp density

4.1.205. Density: From Volume Fraction Gas

Scope: Aria Material

Density: From Volume Fraction Gas [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Volume_Fraction_Gas []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Foam density calculated from a weighting with the volume fraction of gas.

4.1.206. Density: From Bubble State

Scope: Aria Material

Density: From Bubble State [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Bubble_State [Gas_Species_Name = *gas_species_name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>gas_species_name</i>	"string"	undefined

Summary Density from foam bubble model

4.1.207. Density: General Ideal Gas

Scope: Aria Material

Density: General Ideal Gas [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= General_Ideal_Gas [R = *r* |Pref = *pref* |Poffset = *poffset*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>r</i>	real	undefined
<i>pref</i>	real	undefined
<i>poffset</i>	real	undefined

Summary General ideal gas density

4.1.208. Density: General Ideal Gas Extract Average Pressure

Scope: Aria Material

Density: General Ideal Gas Extract Average Pressure [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= General_Ideal_Gas_Extract_Average_Pressure [R = *r* |Pref = *pref* |Poffset = *poffset*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>r</i>	real	undefined
<i>pref</i>	real	undefined
<i>poffset</i>	real	undefined

Summary General ideal gas density that subtracts off the average pressure value as a constant every time step so that the pressure dof stays O(1) throughout the simulation.

4.1.209. Density: General Ideal Gas Thermodynamic Pressure

Scope: Aria Material

Density: General Ideal Gas Thermodynamic Pressure [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= General_Ideal_Gas_Thermodynamic_Pressure [R = *r* |Initial_Thermodynamic_Pressure = *initial_thermodynamic_pressure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>r</i>	real	undefined
<i>initial_thermodynamic_pressure</i>	real	undefined

Summary General ideal gas density that uses the thermodynamic pressure in the pressure-density relation, as in the low Mach equations.

4.1.210. Density: Ideal Gas

Scope: Aria Material

Density: Ideal Gas [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Ideal_Gas []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Ideal gas density

4.1.211. Density: Incompressible Ideal Gas

Scope: Aria Material

Density: Incompressible Ideal Gas [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Incompressible_Ideal_Gas [P_Ref = *p_ref* | T_Ref = *t_ref* | R = *r*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>p_ref</i>	real	undefined
<i>t_ref</i>	real	undefined
<i>r</i>	real	undefined

Summary Incompressible ideal gas density

4.1.212. Density: Mixture Fraction

Scope: Aria Material

Density: Mixture Fraction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mixture_Fraction [Primaryproperty = *primaryProperty* |Secondaryproperty = *secondaryProperty*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>primaryProperty</i>	real	undefined
<i>secondaryProperty</i>	real	undefined

4.1.213. Density: Phase Average

Scope: Aria Material

Density: Phase Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Phase_Average [Subindex_A = *subindex_a* | Subindex_B = *subindex_b*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>subindex_a</i>	integer	undefined
<i>subindex_b</i>	integer	undefined

Summary Phase-averaged values

4.1.214. Density: Interpolated Phase Average

Scope: Aria Material

Density: Interpolated Phase Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Interpolated_Phase_Average [Subindex_A = *subindex_a* | Subindex_B = *subindex_b*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>subindex_a</i>	integer	undefined
<i>subindex_b</i>	integer	undefined

Summary Interpolated Phase-averaged values

4.1.215. Density: Single Component Ideal Gas

Scope: Aria Material

Density: Single Component Ideal Gas [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Single_Component_Ideal_Gas [P_Ref = p_{ref} |T_Ref = t_{ref} |M = m |R = r]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
p_{ref}	real	undefined
t_{ref}	real	undefined
m	real	undefined
r	real	undefined

4.1.216. Density: Single Component Adiabatic Ideal Gas

Scope: Aria Material

Density: Single Component Adiabatic Ideal Gas [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Single_Component_Adiabatic_Ideal_Gas [P_Ref = p_{ref} |P_0 = p_0 |Density_0 = $density_0$ |Gamma = $gamma$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
p_{ref}	real	undefined
p_0	real	undefined
$density_0$	real	undefined
$gamma$	real	undefined

4.1.217. Density: Stanford

Scope: Aria Material

Density: Stanford [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Stanford [N = n]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
n	real	undefined

4.1.218. Density: Thermal

Scope: Aria Material

Density: Thermal [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Thermal [A = *a* |B = *b* |C = *c* |D = *d*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>a</i>	real	undefined
<i>b</i>	real	undefined
<i>c</i>	real	undefined
<i>d</i>	real	undefined

Summary Density as a cubic polynomial in temperature

4.1.219. Density: Mass Average

Scope: Aria Material

Density: Mass Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mass_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Density as a mass average of the species bulk densities ($\rho = \sum_i \left(\frac{Y_i}{\rho_{b,i}} \right)^{-1}$).

4.1.220. Density: Mass Preserving

Scope: Aria Material

Density: Mass Preserving [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mass_Preserving [Rho = *rho*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>rho</i>	real	undefined

Summary Density applied as a ratio of original to current element volume.

4.1.221. Density: Concentration Average

Scope: Aria Material

Density: Concentration Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Concentration_Average [Fluid_Density = *fluid_density* |Lambda = *lambda*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>fluid_density</i>	real	undefined
<i>lambda</i>	real	undefined

Summary This model is now deprecated

4.1.222. Density: From Mass Fraction

Scope: Aria Material

Density: From Mass Fraction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Mass_Fraction []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Species density computed from mass fraction

4.1.223. Density: Adaptive Table Lookup

Scope: Aria Material

Density: Adaptive Table Lookup [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Adaptive_Table_Lookup [File_Name = *file_name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>file_name</i>	"string"	undefined

Summary An adaptive table lookup of density

4.1.224. Density: Porous Phase Average

Scope: Aria Material

Density: Porous Phase Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous_Phase_Average [Liquid_Phase_Name = *Liquid_Phase_Name* | Gas_Phase_Name = *Gas_Phase_Name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Liquid_Phase_Name</i>	"string"	undefined
<i>Gas_Phase_Name</i>	"string"	undefined

Summary Density for a multiphase material of two or three phases

4.1.225. Density: From Chemeq

Scope: Aria Material

Density: From Chemeq [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Chemeq []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Density of one species extracted from ChemEq

4.1.226. Density: From Chemeq Solids

Scope: Aria Material

Density: From Chemeq Solids [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Chemeq_Solids [Rhob0 = *rhob0*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>rhobo</i>	real	undefined

Summary Condensed phase density from ChemEq species concentrations for solid species

4.1.227. Density: Sum All Species

Scope: Aria Material

Density: Sum All Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Sum_All_Species []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.228. Density: Fortran

Scope: Aria Material

Density: Fortran [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Fortran [Multiplier = *multiplier* |Sub_Name = *sub_name* |Real_Data = *real_data* |Int_Data = *int_data* |Resource_Name = *resource_name* |Data = *data*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>sub_name</i>	"string"	undefined
<i>real_data</i>	"string"	undefined
<i>int_data</i>	"string"	undefined
<i>resource_name</i>	"string"	undefined
<i>data</i>	"string"	undefined

Summary Fortran subroutine density.

4.1.229. Dispersed Phase Density

Scope: Aria Material

Dispersed Phase Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.230. Dispersed Phase Density: Copied

Scope: Aria Material

Dispersed Phase Density: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.231. Dispersed Phase Density: User Plugin

Scope: Aria Material

Dispersed Phase Density: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.232. Dispersed Phase Density: Scalar String Function

Scope: Aria Material

Dispersed Phase Density: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F =
f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.233. Dispersed Phase Momentum Stress: Newtonian

Scope: Aria Material

Dispersed Phase Momentum Stress: Newtonian [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Newtonian [Value = *value* |Cts = *cts*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>cts</i>	real	undefined

4.1.234. Dispersed Phase Velocity

Scope: Aria Material

Dispersed Phase Velocity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Velocity_X = *Velocity_X* | Velocity_Y = *Velocity_Y* |Velocity_Z = *Velocity_Z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Velocity_X</i>	real	undefined
<i>Velocity_Y</i>	real	undefined
<i>Velocity_Z</i>	real	undefined

Summary Constant value

4.1.235. Dispersed Phase Velocity: User Plugin

Scope: Aria Material

Dispersed Phase Velocity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.236. Dispersed Phase Velocity: Vector String Function

Scope: Aria Material

Dispersed Phase Velocity: Vector String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Vector_String_Function [$F_X = f_x$ | $F_Y = f_y$ | $F_Z = f_z$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f_x	"string"	undefined
f_y	"string"	undefined
f_z	"string"	undefined

Summary Value from a string function

4.1.237. Dispersed Phase Volume Fraction

Scope: Aria Material

Dispersed Phase Volume Fraction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.238. Dispersed Phase Volume Fraction: Copied

Scope: Aria Material

Dispersed Phase Volume Fraction: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.239. Dispersed Phase Volume Fraction: User Plugin

Scope: Aria Material

Dispersed Phase Volume Fraction: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.240. Dispersed Phase Volume Fraction: Scalar String Function

Scope: Aria Material

Dispersed Phase Volume Fraction: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.241. Distribution Coefficient

Scope: Aria Material

Distribution Coefficient [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Kd = *kd*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>kd</i>	real	undefined

Summary Constant value

4.1.242. Distribution Coefficient: Copied

Scope: Aria Material

Distribution Coefficient: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.243. Distribution Coefficient: User Plugin

Scope: Aria Material

Distribution Coefficient: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.244. Distribution Coefficient: Scalar String Function

Scope: Aria Material

Distribution Coefficient: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.245. Distribution Coefficient: Langmuir

Scope: Aria Material

Distribution Coefficient: Langmuir [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Langmuir [K = k |K_I = k_I]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
k	real	undefined
k_I	real	undefined

Summary This model has been deprecated and removed from the code.

4.1.246. Distribution Coefficient: Competitive Langmuir

Scope: Aria Material

Distribution Coefficient: Competitive Langmuir [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Competitive_Langmuir [K_I = k_i |K_J = k_j |K_Ie = k_{ie} |Species_J = *species_j*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
k_i	real	undefined
k_j	real	undefined
k_{ie}	real	undefined
<i>species_j</i>	integer	undefined

Summary This model has been deprecated and removed from the code.

4.1.247. Effective Diffusivity: Hdiff

Scope: Aria Material

Effective Diffusivity: Hdiff [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Hdiff [K_T = k_t |N_L = n_l]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
k_t	real	undefined
n_l	real	undefined

Summary Effective Hydrogen Diffusivity $D = 1 + \frac{N_T N_L}{(c_L \theta_T)^2}$

4.1.248. Electric Displacement: Linear

Scope: Aria Material

Electric Displacement: Linear [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Linear []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Linear electric displacement

4.1.249. Electric Displacement: Basic

Scope: Aria Material

Electric Displacement: Basic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Basic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Basic electric displacement

4.1.250. Electric Displacement: Generalized

Scope: Aria Material

Electric Displacement: Generalized [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Generalized []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Generalized electric displacement

4.1.251. Electrical Conductivity

Scope: Aria Material

Electrical Conductivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Sigma = *sigma*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>sigma</i>	real	undefined

Summary Constant value

4.1.252. Electrical Conductivity: Copied

Scope: Aria Material

Electrical Conductivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.253. Electrical Conductivity: User Plugin

Scope: Aria Material

Electrical Conductivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |*magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.254. Electrical Conductivity: Scalar String Function

Scope: Aria Material

Electrical Conductivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.255. Electrical Conductivity: From Resistivity

Scope: Aria Material

Electrical Conductivity: From Resistivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Resistivity []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Electrical conductivity calculated from the electrical resistance

4.1.256. Electrical Conductivity: Tbc

Scope: Aria Material

Electrical Conductivity: Tbc [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Tbc [Ki = *ki* |Ti = *ti* |E = *e* |R = *r*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>ki</i>	real	undefined
<i>ti</i>	real	undefined
<i>e</i>	real	undefined
<i>r</i>	real	undefined

Summary This model has been deprecated and removed from the code.

4.1.257. Electrical Conductivity: Thermal

Scope: Aria Material

Electrical Conductivity: Thermal [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Thermal [A = *a* |B = *b* |C = *c* |D = *d*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>a</i>	real	undefined
<i>b</i>	real	undefined
<i>c</i>	real	undefined
<i>d</i>	real	undefined

Summary This model has been deprecated and removed from the code. Use the generic polynomial model.

4.1.258. Electrical Conductivity: Bruggeman Volume Averaged

Scope: Aria Material

Electrical Conductivity: Bruggeman Volume Averaged [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Bruggeman_Volume_Averaged [Exponent = *exponent*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>exponent</i>	real	undefined

Summary This model averages the properties of each species in the same material phase based on their volume fraction assuming a Bruggeman tortuosity model.

4.1.259. Electrical Conductivity: Arrhenius

Scope: Aria Material

Electrical Conductivity: Arrhenius [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Arrhenius [R = *r* |Sigma0 = *sigma0* |A = *a* |Ea = *Ea*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>r</i>	real	undefined
<i>sigmao</i>	real	undefined
<i>a</i>	real	undefined
<i>Ea</i>	real	undefined

Summary Arrhenius electrical conductivity, $\sigma = \sigma_0 + A * \exp\left(-\frac{E_a}{RT}\right)$

4.1.260. Electrical Conductivity: Electrode

Scope: Aria Material

Electrical Conductivity: Electrode [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Electrode []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Deprecated model. Replace with string function or polynomial generic model.

4.1.261. Electrical Permittivity

Scope: Aria Material

Electrical Permittivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Kappa = *kappa*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>kappa</i>	real	undefined

Summary Constant value

4.1.262. Electrical Permittivity: Copied

Scope: Aria Material

Electrical Permittivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.263. Electrical Permittivity: User Plugin

Scope: Aria Material

Electrical Permittivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.264. Electrical Permittivity: Scalar String Function

Scope: Aria Material

Electrical Permittivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F =
f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.265. Electrical Resistance

Scope: Aria Material

Electrical Resistance [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.266. Electrical Resistance: Copied

Scope: Aria Material

Electrical Resistance: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.267. Electrical Resistance: User Plugin

Scope: Aria Material

Electrical Resistance: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.268. Electrical Resistance: Scalar String Function

Scope: Aria Material

Electrical Resistance: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.269. Electrical Resistivity

Scope: Aria Material

Electrical Resistivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Rho = *rho*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>rho</i>	real	undefined

Summary Constant value

4.1.270. Electrical Resistivity: Copied

Scope: Aria Material

Electrical Resistivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.271. Electrical Resistivity: User Plugin

Scope: Aria Material

Electrical Resistivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.272. Electrical Resistivity: Scalar String Function

Scope: Aria Material

Electrical Resistivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [*F* = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.273. Electrical Resistivity: From Conductivity

Scope: Aria Material

Electrical Resistivity: From Conductivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Conductivity []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Electrical resistivity calculated from the electrical conductivity

4.1.274. Electromigration Coefficient

Scope: Aria Material

Electromigration Coefficient [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |M = *m*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>m</i>	real	undefined

Summary Constant value

4.1.275. Electromigration Coefficient: Copied

Scope: Aria Material

Electromigration Coefficient: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.276. Electromigration Coefficient: User Plugin

Scope: Aria Material

Electromigration Coefficient: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.277. Electromigration Coefficient: Scalar String Function

Scope: Aria Material

Electromigration Coefficient: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.278. Emissivity

Scope: Aria Material

Emissivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* | $E = e$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>e</i>	real	undefined

Summary Constant value

4.1.279. Emissivity: Copied

Scope: Aria Material

Emissivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.280. Emissivity: User Plugin

Scope: Aria Material

Emissivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.281. Emissivity: Scalar String Function

Scope: Aria Material

Emissivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.282. Emissivity: Calore User Sub

Scope: Aria Material

Emissivity: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

4.1.283. Emissivity: Fortran

Scope: Aria Material

Emissivity: Fortran [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Fortran [Multiplier = *multiplier* |Sub_Name = *sub_name* | Real_Data = *real_data* |Int_Data = *int_data* |Resource_Name = *resource_name* |Data = *data*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>sub_name</i>	"string"	undefined
<i>real_data</i>	"string"	undefined
<i>int_data</i>	"string"	undefined
<i>resource_name</i>	"string"	undefined
<i>data</i>	"string"	undefined

Summary Fortran subroutine emissivity.

4.1.284. Emissivity: Banded Wavelength

Scope: Aria Material

Emissivity: Banded Wavelength [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Banded_Wavelength [E0 = *e0* |E1 = *e1* |E2 = *e2* |E3 = *e3* |E4 = *e4* |E5 = *e5* |E6 = *e6* |E7 = *e7* | Wavelength_Band_Model = *wavelength_band_model*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>e0</i>	real	undefined
<i>e1</i>	real	undefined
<i>e2</i>	real	undefined
<i>e3</i>	real	undefined
<i>e4</i>	real	undefined
<i>e5</i>	real	undefined
<i>e6</i>	real	undefined
<i>e7</i>	real	undefined
<i>wavelength_band_model</i>	"string"	undefined

Summary Banded wavelength emissivity.

4.1.285. Enclosure MbK

Scope: Aria Material

```
Enclosure MbK [ {of|species|subindex} Species |{in|material_phase}
MaterialPhase ]= Constant [ Value = value |K = k ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>k</i>	real	undefined

Summary Constant value

4.1.286. Enclosure MbK: Copied

Scope: Aria Material

```
Enclosure MbK: Copied [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]= Copied [ Source = source ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.287. Enclosure Mbk: User Plugin

Scope: Aria Material

Enclosure Mbk: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.288. Enclosure Mbk: Scalar String Function

Scope: Aria Material

Enclosure Mbk: Scalar String Function [{of|species|subindex} *Species* |
{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.289. Enclosure Mbk: Calore User Sub

Scope: Aria Material

Enclosure Mbk: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type*
|Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data
= *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

4.1.290. Enclosure Mbl

Scope: Aria Material

Enclosure Mbl [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |L = *l*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>l</i>	real	undefined

Summary Constant value

4.1.291. Enclosure Mbl: Copied

Scope: Aria Material

Enclosure Mbl: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.292. Enclosure Mbl: User Plugin

Scope: Aria Material

Enclosure Mbl: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.293. Enclosure Mbl: Scalar String Function

Scope: Aria Material

Enclosure Mbl: Scalar String Function [{of|species|subindex} *Species* |
{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.294. Enclosure Mbl: Calore User Sub

Scope: Aria Material

Enclosure Mbl: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type*
|Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data
= *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

4.1.295. Enclosure Mbl: From Geometry

Scope: Aria Material

Enclosure Mbl: From Geometry [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Geometry [Prefactor = *prefactor* | Enclosure = *enclosure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>prefactor</i>	real	undefined
<i>enclosure</i>	"string"	undefined

Summary Values from geometry with a user selectable pre-factor

4.1.296. Energy Diffusive Flux: Basic

Scope: Aria Material

Energy Diffusive Flux: Basic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Basic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Basic model of energy diffusive flux

4.1.297. Energy Diffusive Flux: From Mixture Mass Diffusivity

Scope: Aria Material

Energy Diffusive Flux: From Mixture Mass Diffusivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
From_Mixture_Mass_Diffusivity []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Energy diffusive flux = -density * mixture_mass_diffusivity * grad(enthalpy)

4.1.298. Energy Diffusive Flux: Energy Mass

Scope: Aria Material

Energy Diffusive Flux: Energy Mass [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Energy_Mass []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Energy mass model of energy diffusive flux

4.1.299. Energy Face Stabilization Scaling: Default

Scope: Aria Material

Energy Face Stabilization Scaling: Default [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Default []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Default face stabilization scaling for energy equation

4.1.300. Enthalpy

Scope: Aria Material

Enthalpy [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |H = *h*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>h</i>	real	undefined

Summary Constant value

4.1.301. Enthalpy: Copied

Scope: Aria Material

Enthalpy: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.302. Enthalpy: User Plugin

Scope: Aria Material

Enthalpy: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.303. Enthalpy: Scalar String Function

Scope: Aria Material

Enthalpy: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.304. Enthalpy: Cantera

Scope: Aria Material

Enthalpy: Cantera [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Cantera [Poffset = *poffset*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>poffset</i>	real	undefined

Summary Cantera enthalpy

4.1.305. Enthalpy: From Temperature

Scope: Aria Material

Enthalpy: From Temperature [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Temperature [Value = *value* |T = *t* | Poffset = *poffset*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>t</i>	real	undefined
<i>poffset</i>	real	undefined

Summary Cantera enthalpy computed from temperature

4.1.306. Enthalpy: Mass Average

Scope: Aria Material

Enthalpy: Mass Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mass_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Enthalpy computed from mass average of species enthalpies

4.1.307. Enthalpy Advection: Porous

Scope: Aria Material

Enthalpy Advection: Porous [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Advected quantity for porous enthalpy equation

4.1.308. Enthalpy Advection: Porous Upwind

Scope: Aria Material

Enthalpy Advection: Porous Upwind [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous_Upwind []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Upwinded advected quantity for porous enthalpy equation. Only valid for CVFEM.

4.1.309. Enthalpy Advection: Material Phase Sum

Scope: Aria Material

Enthalpy Advection: Material Phase Sum [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Material_Phase_Sum []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Sum the enthalpy advection terms from multiple material phases for use in a one temperature model.

4.1.310. Entrance Distance: Correlation Bar

Scope: Aria Material

Entrance Distance: Correlation Bar [{of|species|subindex} *Species*]=
Correlation_Bar [Phase = *phase* | Gas_Exponent = *gas_exponent* |
Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>phase</i>	"string"	undefined
<i>gas_exponent</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correction factor for difference between near-wall and bulk fluid state for Gnielinski pipe and annulus correlations.

4.1.311. Entrance Length: Correlation

Scope: Aria Material

Entrance Length: Correlation [{of|species|subindex} *Species*]=
Correlation [De = *De* | Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>De</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation Entrance Length

4.1.312. Entry Pressure

Scope: Aria Material

Entry Pressure [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |Pe = *pe*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>pe</i>	real	undefined

Summary Constant value

4.1.313. Entry Pressure: Copied

Scope: Aria Material

Entry Pressure: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.314. Entry Pressure: User Plugin

Scope: Aria Material

Entry Pressure: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.315. Entry Pressure: Scalar String Function

Scope: Aria Material

Entry Pressure: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.316. Equilibrium Constant: Arrhenius

Scope: Aria Material

Equilibrium Constant: Arrhenius [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Arrhenius [$C = c$ | $M = m$ | $W_B = w_b$ | $R = r$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>c</i>	real	undefined
<i>m</i>	real	undefined
<i>w_b</i>	real	undefined
<i>r</i>	real	undefined

Summary Arrhenius Equilibrium Constant, $E = C + M * \exp\left(-\frac{W_B}{RT}\right)$

4.1.317. Equilibrium Potential

Scope: Aria Material

Equilibrium Potential [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value* | $U = u$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>u</i>	real	undefined

Summary Constant value

4.1.318. Equilibrium Potential: Copied

Scope: Aria Material

Equilibrium Potential: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.319. Equilibrium Potential: User Plugin

Scope: Aria Material

Equilibrium Potential: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.320. Equilibrium Potential: Scalar String Function

Scope: Aria Material

Equilibrium Potential: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.321. Equilibrium Potential: Nernst

Scope: Aria Material

Equilibrium Potential: Nernst [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Nernst [Species_A = *species_a* |Species_B = *species_b* |R = *r* |F = *f* |U = *u*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>species_a</i>	"string"	undefined
<i>species_b</i>	"string"	undefined
<i>r</i>	real	undefined
<i>f</i>	real	undefined
<i>u</i>	real	undefined

Summary Nernst-Einstein form of the equilibrium potential

4.1.322. Equilibrium Potential: From Chemical Potential

Scope: Aria Material

Equilibrium Potential: From Chemical Potential [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Chemical_Potential [F = *f* |Species_Name = *species_name* |Species_Phase = *species_phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	real	undefined
<i>species_name</i>	"string"	undefined
<i>species_phase</i>	"string"	undefined

Summary Determine the equilibrium voltage based on the chemical potential of a selected species where $\phi_{equil} = -\mu/F$.

4.1.323. Equilibrium Potential: Two Phase

Scope: Aria Material

Equilibrium Potential: Two Phase [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Two_Phase [Cmin = *Cmin* |Cmax = *Cmax* |R = *r* |Species_Name = *species_name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Cmin</i>	real	undefined
<i>Cmax</i>	real	undefined
<i>r</i>	real	undefined
<i>species_name</i>	"string"	undefined

Summary Equilibrium potential that is constant between Cmin and Cmax corresponding to a two-phase region. Outside of that range it behaves as an ideal solution.

4.1.324. Equilibrium Potential: Lcoo2

Scope: Aria Material

Equilibrium Potential: Lcoo2 [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Lcoo2 []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Equilibrium potential

4.1.325. Equilibrium Pressure

Scope: Aria Material

Equilibrium Pressure [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |P = *p*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>p</i>	real	undefined

Summary Constant value

4.1.326. Equilibrium Pressure: Copied

Scope: Aria Material

Equilibrium Pressure: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.327. Equilibrium Pressure: User Plugin

Scope: Aria Material

Equilibrium Pressure: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.328. Equilibrium Pressure: Scalar String Function

Scope: Aria Material

Equilibrium Pressure: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.329. Exchange Current Density

Scope: Aria Material

Exchange Current Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.330. Exchange Current Density: Copied

Scope: Aria Material

Exchange Current Density: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.331. Exchange Current Density: User Plugin

Scope: Aria Material

Exchange Current Density: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.332. Exchange Current Density: Scalar String Function

Scope: Aria Material

Exchange Current Density: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.333. Exchange Current Density: Rate Constant Species

Scope: Aria Material

Exchange Current Density: Rate Constant Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Rate_Constant_Species [F = *f* |K = *k* |Liquid_Exponent = *liquid_exponent* |Solid_Exponent = *solid_exponent* |Cs_Max = *Cs_max* |Liquid_Species = *liquid_species* |Solid_Species = *solid_species*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	real	undefined
<i>k</i>	real	undefined
<i>liquid_exponent</i>	real	undefined
<i>solid_exponent</i>	real	undefined
<i>Cs_max</i>	real	undefined
<i>liquid_species</i>	"string"	undefined
<i>solid_species</i>	"string"	undefined

Summary Computes an exchange current density of the form
$$i_0 = kF \prod \text{liquid\_species}^{\text{liquid\_exponent}} \times \prod \text{solid\_species}^{\text{solid\_exponent}}$$
where the species whose concentrations are included are user-specified parameters.

4.1.334. Extension Speed

Scope: Aria Material

Extension Speed [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.335. Extension Speed: Copied

Scope: Aria Material

Extension Speed: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.336. Extension Speed: User Plugin

Scope: Aria Material

Extension Speed: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.337. Extension Speed: Scalar String Function

Scope: Aria Material

Extension Speed: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.338. Extension Speed Diffusive Flux: Definition

Scope: Aria Material

Extension Speed Diffusive Flux: Definition [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Definition []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary The definition of the extension speed diffusive flux

4.1.339. Extension Speed Multiplier

Scope: Aria Material

Extension Speed Multiplier [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.340. Extension Speed Multiplier: Copied

Scope: Aria Material

Extension Speed Multiplier: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.341. Extension Speed Multiplier: User Plugin

Scope: Aria Material

Extension Speed Multiplier: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.342. Extension Speed Multiplier: Scalar String Function

Scope: Aria Material

Extension Speed Multiplier: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.343. Fission Cross Section

Scope: Aria Material

Fission Cross Section [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value* | Fiss = *fiss*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>fiss</i>	real	undefined

Summary Constant value

4.1.344. Fission Cross Section: Copied

Scope: Aria Material

Fission Cross Section: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.345. Fission Cross Section: User Plugin

Scope: Aria Material

Fission Cross Section: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.346. Fission Cross Section: Scalar String Function

Scope: Aria Material

Fission Cross Section: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F =
f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.347. Fission Cross Section: Linearized

Scope: Aria Material

Fission Cross Section: Linearized [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Linearized [Sigma_0 = *sigma_0* |
D_Sigma_D_Rho = *d_sigma_d_rho* |D_Sigma_D_T = *d_sigma_d_t* |T_Sigma_0 =
t_sigma_0 |Rho_Sigma_0 = *rho_sigma_0*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>sigma_0</i>	real	undefined
<i>d_sigma_d_rho</i>	real	undefined
<i>d_sigma_d_t</i>	real	undefined
<i>t_sigma_0</i>	real	undefined
<i>rho_sigma_0</i>	real	undefined

Summary Linearized fission cross section

4.1.348. Flow Area

Scope: Aria Material

Flow Area [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |A = *a*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>a</i>	real	undefined

Summary Constant value

4.1.349. Flow Area: Copied

Scope: Aria Material

Flow Area: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.350. Flow Area: User Plugin

Scope: Aria Material

Flow Area: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.351. Flow Area: Scalar String Function

Scope: Aria Material

Flow Area: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.352. Flow Area: Spatial User Function

Scope: Aria Material

Flow Area: Spatial User Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Spatial_User_Function [Threshold =
threshold |Multiplier = *multiplier* |Name = *name* |Bar = *bar* |X = *x*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>threshold</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>name</i>	"string"	undefined
<i>bar</i>	"string"	undefined
<i>x</i>	"string"	undefined

Summary Spatially varying flow area based on a coordinate dependent user function

4.1.353. Flow Area: Correlation Spatial User Function

Scope: Aria Material

```
Flow Area: Correlation Spatial User Function [ {of|species|subindex}
Species ]= Correlation_Spatial_User_Function [ Threshold = threshold |
Multiplier = multiplier | Name = name | Bar = bar | X = x |
Bulk_Node_Interface = bulk_node_interface ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>threshold</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>name</i>	"string"	undefined
<i>bar</i>	"string"	undefined
<i>x</i>	"string"	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation spatially varying flow area based on a coordinate dependent user function

4.1.354. Flowing Liquid Viscosity

Scope: Aria Material

```
Flowing Liquid Viscosity [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]= Constant [ Value = value | Mu = mu ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>mu</i>	real	undefined

Summary Constant value

4.1.355. Flowing Liquid Viscosity: Copied

Scope: Aria Material

```
Flowing Liquid Viscosity: Copied [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]= Copied [ Source = source ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.356. Flowing Liquid Viscosity: User Plugin

Scope: Aria Material

Flowing Liquid Viscosity: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.357. Flowing Liquid Viscosity: Scalar String Function

Scope: Aria Material

Flowing Liquid Viscosity: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.358. Fluid Beta: Correlation

Scope: Aria Material

Fluid Beta: Correlation [{of|species|subindex} *Species*]= Correlation [Beta = *beta* | Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>beta</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation Expansion Coefficient

4.1.359. Fluid Density: Correlation

Scope: Aria Material

Fluid Density: Correlation [{of|species|subindex} *Species*]= Correlation
[Rho = *rho* | Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>rho</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation fluid temperature

4.1.360. Fluid Temperature

Scope: Aria Material

Fluid Temperature [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* | T = *t*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>t</i>	real	undefined

Summary Constant valueConstant value

4.1.361. Fluid Temperature: Copied

Scope: Aria Material

Fluid Temperature: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expressionCopied value from another expression

4.1.362. Fluid Temperature: User Plugin

Scope: Aria Material

Fluid Temperature: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user pluginValue from a user plugin

4.1.363. Fluid Temperature: Scalar String Function

Scope: Aria Material

Fluid Temperature: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string functionValue from a string function

4.1.364. Fluid Velocity Magnitude: Correlation

Scope: Aria Material

Fluid Velocity Magnitude: Correlation [{of|species|subindex} *Species*]= Correlation [V = *v* |Prereq_Model = *prereq_model* |Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>v</i>	real	undefined
<i>prereq_model</i>	"string"	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation fluid velocity

4.1.365. Flux Vector: Summed

Scope: Aria Material

Flux Vector: Summed [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Summed [Contributions = *contributions*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>contributions</i>	"string"	undefined

Summary Flux vector as a sum of user-specified flux vectors

4.1.366. Forchheimer Drag Coeff

Scope: Aria Material

Forchheimer Drag Coeff [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |C_F = *c_f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>c_f</i>	real	undefined

Summary Constant value

4.1.367. Forchheimer Drag Coeff: Copied

Scope: Aria Material

Forchheimer Drag Coeff: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.368. Forchheimer Drag Coeff: User Plugin

Scope: Aria Material

Forchheimer Drag Coeff: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.369. Forchheimer Drag Coeff: Scalar String Function

Scope: Aria Material

Forchheimer Drag Coeff: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.370. Freestream Density

Scope: Aria Material

Freestream Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Fsdens = *fsdens*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>fsdens</i>	real	undefined

Summary Constant value

4.1.371. Freestream Density: Copied

Scope: Aria Material

Freestream Density: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.372. Freestream Density: User Plugin

Scope: Aria Material

Freestream Density: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.373. Freestream Density: Scalar String Function

Scope: Aria Material

Freestream Density: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.374. Freestream Gamma

Scope: Aria Material

Freestream Gamma [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |G = *g*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>g</i>	real	undefined

4.1.375. Freestream Pressure

Scope: Aria Material

Freestream Pressure [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |Fspres = *fspres*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>fspres</i>	real	undefined

Summary Constant value

4.1.376. Freestream Pressure: Copied

Scope: Aria Material

Freestream Pressure: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.377. Freestream Pressure: User Plugin

Scope: Aria Material

Freestream Pressure: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.378. Freestream Pressure: Scalar String Function

Scope: Aria Material

Freestream Pressure: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.379. Freestream Temperature

Scope: Aria Material

Freestream Temperature [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Fstemp = *fstemp*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>fstemp</i>	real	undefined

Summary Constant value

4.1.380. Freestream Temperature: Copied

Scope: Aria Material

Freestream Temperature: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.381. Freestream Temperature: User Plugin

Scope: Aria Material

Freestream Temperature: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.382. Freestream Temperature: Scalar String Function

Scope: Aria Material

Freestream Temperature: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.383. Friction Factor

Scope: Aria Material

Friction Factor [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* | $F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>f</i>	real	undefined

Summary Constant value

4.1.384. Friction Factor: Copied

Scope: Aria Material

Friction Factor: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.385. Friction Factor: User Plugin

Scope: Aria Material

Friction Factor: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.386. Friction Factor: Scalar String Function

Scope: Aria Material

Friction Factor: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.387. Friction Factor: Smooth Tube

Scope: Aria Material

Friction Factor: Smooth Tube [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Smooth_Tube []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Friction factor computed from smooth tube model

4.1.388. Friction Factor: Smooth Annulus

Scope: Aria Material

Friction Factor: Smooth Annulus [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Smooth_Annulus [$R = r$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>r</i>	"string"	undefined

Summary Friction factor computed from smooth annulus model

4.1.389. Friction Factor: Correlation

Scope: Aria Material

Friction Factor: Correlation [{of|species|subindex} *Species*]=
Correlation [$F = f$ | Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>f</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation friction factor with constant value

4.1.390. Friction Factor: Correlation Smooth Tube

Scope: Aria Material

Friction Factor: Correlation Smooth Tube [{of|species|subindex} *Species*]=
Correlation_Smooth_Tube [Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation friction factor with smooth tube model

4.1.391. Friction Factor: Correlation Smooth Annulus

Scope: Aria Material

Friction Factor: Correlation Smooth Annulus [{of|species|subindex} *Species*]=
Correlation_Smooth_Annulus [Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation friction factor with smooth annulus model

4.1.392. Gamma

Scope: Aria Material

Gamma [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |G = *g*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>g</i>	real	undefined

4.1.393. Gamma Dot

Scope: Aria Material

Gamma Dot [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.394. Gamma Dot: Copied

Scope: Aria Material

Gamma Dot: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.395. Gamma Dot: User Plugin

Scope: Aria Material

Gamma Dot: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.396. Gamma Dot: Scalar String Function

Scope: Aria Material

Gamma Dot: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.397. Gap Conductance Coefficient

Scope: Aria Material

Gap Conductance Coefficient [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |H = *h*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>h</i>	real	undefined

Summary Constant value

4.1.398. Gap Conductance Coefficient: Copied

Scope: Aria Material

Gap Conductance Coefficient: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.399. Gap Conductance Coefficient: User Plugin

Scope: Aria Material

Gap Conductance Coefficient: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.400. Gap Conductance Coefficient: Scalar String Function

Scope: Aria Material

Gap Conductance Coefficient: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.401. Gap Conductance Coefficient: Calore User Sub

Scope: Aria Material

Gap Conductance Coefficient: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Calore user subroutine contact gap conductance

4.1.402. Gap Conductance Coefficient: Fortran

Scope: Aria Material

Gap Conductance Coefficient: Fortran [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Fortran [Multiplier = *multiplier* | Sub_Name = *sub_name* |Real_Data = *real_data* |Int_Data = *int_data* | Resource_Name = *resource_name* |Data = *data*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>sub_name</i>	"string"	undefined
<i>real_data</i>	"string"	undefined
<i>int_data</i>	"string"	undefined
<i>resource_name</i>	"string"	undefined
<i>data</i>	"string"	undefined

Summary Fortran contact gap conductance subroutine.

4.1.403. Gap Height

Scope: Aria Material

Gap Height [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |H = *h*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>h</i>	real	undefined

Summary Constant value

4.1.404. Gap Height: Copied

Scope: Aria Material

Gap Height: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.405. Gap Height: User Plugin

Scope: Aria Material

Gap Height: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.406. Gap Height: Scalar String Function

Scope: Aria Material

Gap Height: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.407. Gas Phase Retardation

Scope: Aria Material

Gas Phase Retardation [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |R = *r*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>r</i>	real	undefined

Summary Constant value

4.1.408. Gas Phase Retardation: Copied

Scope: Aria Material

Gas Phase Retardation: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.409. Gas Phase Retardation: User Plugin

Scope: Aria Material

Gas Phase Retardation: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.410. Gas Phase Retardation: Scalar String Function

Scope: Aria Material

Gas Phase Retardation: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.411. Glass Transition Temperature

Scope: Aria Material

Glass Transition Temperature [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.412. Glass Transition Temperature: Copied

Scope: Aria Material

Glass Transition Temperature: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.413. Glass Transition Temperature: User Plugin

Scope: Aria Material

Glass Transition Temperature: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.414. Glass Transition Temperature: Scalar String Function

Scope: Aria Material

Glass Transition Temperature: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.415. Glass Transition Temperature: Debenedeto

Scope: Aria Material

Glass Transition Temperature: Debenedeto [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] = Debenedeto [Extent_Species_Name = *extent_species_name* | A = *a* | Tg0 = *Tg0* | Tginfinity = *TgInfinity*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>extent_species_name</i>	"string"	undefined
<i>a</i>	real	undefined
<i>Tg0</i>	real	undefined
<i>TgInfinity</i>	real	undefined

Summary deBenedeto model for the glass transition temperature based on the extent of polymerization, x , and material parameters $A, T_{g0}, T_{g\infty}$ $T_g = \frac{T_{g0}(1-x) + AxT_{g\infty}}{1-x+Ax}$.

4.1.416. Gnielinski Film Gradient Correction: Correlation

Scope: Aria Material

Gnielinski Film Gradient Correction: Correlation [{of|species|subindex} *Species*] = Correlation [Phase = *phase* | Gas_Exponent = *gas_exponent* | Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>phase</i>	"string"	undefined
<i>gas_exponent</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correction factor for difference between near-wall and bulk fluid state for Gnielinski pipe and annulus correlations.

4.1.417. Gravitational Constant: Correlation

Scope: Aria Material

Gravitational Constant: Correlation [{of|species|subindex} *Species*] = Correlation [G = *g* | Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>g</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation Gravitational Constant

4.1.418. Hausen Entrance Effect Correction: Correlation

Scope: Aria Material

Hausen Entrance Effect Correction: Correlation [{of|species|subindex} *Species*]= Correlation [Max_Correction = *max_correction* | Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>max_correction</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correction factor for entrance effects for Gnielinski pipe and annulus correlations.

4.1.419. Hdiff Flux: Constant C1

Scope: Aria Material

Hdiff Flux: Constant C1 [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant_C1 [Jx = *jx* |Jy = *jy* |Jz = *jz*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>jx</i>	real	undefined
<i>jy</i>	real	undefined
<i>jz</i>	real	undefined

Summary This model has been deprecated and removed from the code.

4.1.420. Heat Conduction: Generalized

Scope: Aria Material

Heat Conduction: Generalized [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Generalized []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Generalized model for heat conduction - can use either a scalar or tensor thermal conductivity.

4.1.421. Heat Conduction: Convected Enthalpy

Scope: Aria Material

Heat Conduction: Convected Enthalpy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Convected_Enthalpy []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Convected enthalpy model for heat conduction

4.1.422. Heat Conduction: Phase Average

Scope: Aria Material

Heat Conduction: Phase Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Phase_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Phase average model for heat conduction

4.1.423. Heat Conduction: Thermoelectric

Scope: Aria Material

Heat Conduction: Thermoelectric [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Thermoelectric []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Thermoelectric model for heat conduction

4.1.424. Heat Conduction: Fouriers Law

Scope: Aria Material

Heat Conduction: Fouriers Law [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Fouriers_Law []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Equivalent to GENERALIZED, present for backwards compatibility.

4.1.425. Heat Conduction: Radiative Flux

Scope: Aria Material

Heat Conduction: Radiative Flux [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Radiative_Flux [Ndof = *ndof* |Multiplier = *multiplier* |Enclosure = *enclosure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>ndof</i>	integer	undefined
<i>multiplier</i>	real	undefined
<i>enclosure</i>	"string"	undefined

Summary Transforms the radiative heat flux calculated by Chaparral into a nodal surface heat conduction flux quantity.

4.1.426. Heat Conduction: Basic

Scope: Aria Material

Heat Conduction: Basic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Basic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Equivalent to GENERALIZED, present for backwards compatibility.

4.1.427. Heat Conduction: Mass Diffusion Energy Transport

Scope: Aria Material

Heat Conduction: Mass Diffusion Energy Transport [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]=
Mass_Diffusion_Energy_Transport []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Mass diffusion model for energy transport

4.1.428. Heat Conduction: Porous Diffusive Enthalpy Flux

Scope: Aria Material

Heat Conduction: Porous Diffusive Enthalpy Flux [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]=
Porous_Diffusive_Enthalpy_Flux []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Porous diffusive enthalpy flux model

4.1.429. Heat Conduction: Porous Simplified Diffusive Enthalpy Flux

Scope: Aria Material

Heat Conduction: Porous Simplified Diffusive Enthalpy Flux [{of|species|
subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Porous_Simplified_Diffusive_Enthalpy_Flux []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Porous simplified diffusive enthalpy flux model

4.1.430. Heat Of Vaporization

Scope: Aria Material

Heat Of Vaporization [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Hv = *hv*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>hv</i>	real	undefined

Summary Constant value

4.1.431. Heat Of Vaporization: Copied

Scope: Aria Material

Heat Of Vaporization: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.432. Heat Of Vaporization: User Plugin

Scope: Aria Material

Heat Of Vaporization: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.433. Heat Of Vaporization: Scalar String Function

Scope: Aria Material

Heat Of Vaporization: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.434. Heat Transfer Coefficient

Scope: Aria Material

Heat Transfer Coefficient [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |H = *h*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>h</i>	real	undefined

Summary Constant value

4.1.435. Heat Transfer Coefficient: Copied

Scope: Aria Material

Heat Transfer Coefficient: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.436. Heat Transfer Coefficient: User Plugin

Scope: Aria Material

Heat Transfer Coefficient: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.437. Heat Transfer Coefficient: Scalar String Function

Scope: Aria Material

Heat Transfer Coefficient: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.438. Heat Transfer Coefficient: Calore User Sub

Scope: Aria Material

Heat Transfer Coefficient: Calore User Sub [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

4.1.439. Heat Transfer Coefficient: Aero

Scope: Aria Material

```
Heat Transfer Coefficient: Aero [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]= Aero [ T_On = t_on |T_Off = t_off |
Specific_Heat_Function = specific_heat_function |Conductivity_Function =
conductivity_function |Viscosity_Function = viscosity_function |
Offset_Direction = offset_direction |Coord_Offset = coord_offset |
Cone_Length = cone_length |Gas_Constant = gas_constant ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>t_on</i>	real	undefined
<i>t_off</i>	real	undefined
<i>specific_heat_function</i>	"string"	undefined
<i>conductivity_function</i>	"string"	undefined
<i>viscosity_function</i>	"string"	undefined
<i>offset_direction</i>	"string"	undefined
<i>coord_offset</i>	"string"	undefined
<i>cone_length</i>	real	undefined
<i>gas_constant</i>	real	undefined

Summary Heat transfer coefficient for external flow about conical tipped body accounting for flow conditions including Mach number, altitude, fluid properties and local flow regime.

4.1.440. Heat Transfer Coefficient: Fortran

Scope: Aria Material

```
Heat Transfer Coefficient: Fortran [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]= Fortran [ Multiplier = multiplier |
```

```
Sub_Name = sub_name | Real_Data = real_data | Int_Data = int_data |
Resource_Name = resource_name | Data = data ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>sub_name</i>	"string"	undefined
<i>real_data</i>	"string"	undefined
<i>int_data</i>	"string"	undefined
<i>resource_name</i>	"string"	undefined
<i>data</i>	"string"	undefined

Summary Fortran subroutine heat transfer coefficient.

4.1.441. Heat Transfer Coefficient: Correlation

Scope: Aria Material

```
Heat Transfer Coefficient: Correlation [ {of|species|subindex} Species ]=
Correlation [ Rex = Rex | Bulk_Node_Interface = bulk_node_interface ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>Rex</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation based heat transfer coefficient

4.1.442. Hydraulic Diameter

Scope: Aria Material

```
Hydraulic Diameter [ {of|species|subindex} Species | {in|material_phase}
MaterialPhase ]= Constant [ Value = value | D = d ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>d</i>	real	undefined

Summary Constant value

4.1.443. Hydraulic Diameter: Copied

Scope: Aria Material

Hydraulic Diameter: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.444. Hydraulic Diameter: User Plugin

Scope: Aria Material

Hydraulic Diameter: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.445. Hydraulic Diameter: Scalar String Function

Scope: Aria Material

Hydraulic Diameter: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.446. Hydraulic Diameter: Spatial User Function

Scope: Aria Material

Hydraulic Diameter: Spatial User Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Spatial_User_Function [Threshold = *threshold* |Multiplier = *multiplier* |Name = *name* |Bar = *bar* |X = *x*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>threshold</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>name</i>	"string"	undefined
<i>bar</i>	"string"	undefined
<i>x</i>	"string"	undefined

Summary Spatially varying hydraulic diameter based on a coordinate dependent user function

4.1.447. Hydraulic Diameter: Correlation

Scope: Aria Material

Hydraulic Diameter: Correlation [{of|species|subindex} *Species*]= Correlation [D = *d* |Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>d</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation hydraulic diameter based on sectional area and wetted perimeter

4.1.448. Hydraulic Diameter: Correlation Spatial User Function

Scope: Aria Material

Hydraulic Diameter: Correlation Spatial User Function [{of|species|subindex} *Species*]= Correlation_Spatial_User_Function [Threshold = *threshold* |Multiplier = *multiplier* |Name = *name* |Bar = *bar* |X = *x* |Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>threshold</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>name</i>	"string"	undefined
<i>bar</i>	"string"	undefined
<i>x</i>	"string"	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation spatially varying hydraulic diameter based on a coordinate dependent user function

4.1.449. Hydrogen Advection Velocity: Hdiff

Scope: Aria Material

Hydrogen Advection Velocity: Hdiff [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Hdiff [R = r | V_H = v_h]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>r</i>	real	undefined
<i>v_h</i>	real	undefined

Summary Advection velocity term for hydrogen transport

4.1.450. Hydrogen Diffusion Supg Tau: Shakib

Scope: Aria Material

Hydrogen Diffusion Supg Tau: Shakib [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Shakib [H = h |Use_Advection = *use_advection* |Use_Diffusion = *use_diffusion* |Use_Time = *use_time* |Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>h</i>	real	undefined
<i>use_advection</i>	integer	undefined
<i>use_diffusion</i>	integer	undefined
<i>use_time</i>	integer	undefined
<i>multiplier</i>	real	undefined

Summary ?

4.1.451. Hydrostatic Pressure

Scope: Aria Material

Hydrostatic Pressure [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.452. Hydrostatic Pressure: Copied

Scope: Aria Material

Hydrostatic Pressure: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.453. Hydrostatic Pressure: User Plugin

Scope: Aria Material

Hydrostatic Pressure: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.454. Hydrostatic Pressure: Scalar String Function

Scope: Aria Material

Hydrostatic Pressure: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [*F* = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.455. Induction Time Constant

Scope: Aria Material

Induction Time Constant [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Tau = *tau*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>tau</i>	real	undefined

Summary Constant value

4.1.456. Induction Time Constant: Copied

Scope: Aria Material

Induction Time Constant: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.457. Induction Time Constant: User Plugin

Scope: Aria Material

Induction Time Constant: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.458. Induction Time Constant: Scalar String Function

Scope: Aria Material

Induction Time Constant: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.459. Initial Porosity

Scope: Aria Material

Initial Porosity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Phi = *phi*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>phi</i>	real	undefined

Summary Constant value

4.1.460. Initial Porosity: Copied

Scope: Aria Material

Initial Porosity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.461. Initial Porosity: User Plugin

Scope: Aria Material

Initial Porosity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.462. Initial Porosity: Scalar String Function

Scope: Aria Material

Initial Porosity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.463. Intensity Diffusion: Spherical Harmonic

Scope: Aria Material

Intensity Diffusion: Spherical Harmonic [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Spherical_Harmonic [Spn_Order = *SPn_order* | Scaled = *scaled*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>SPn_order</i>	integer	undefined
<i>scaled</i>	"string"	undefined

Summary Spherical harmonic intensity diffusion

4.1.464. Internal Energy

Scope: Aria Material

Internal Energy [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.465. Internal Energy: Copied

Scope: Aria Material

Internal Energy: Copied [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.466. Internal Energy: User Plugin

Scope: Aria Material

Internal Energy: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.467. Internal Energy: Scalar String Function

Scope: Aria Material

Internal Energy: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.468. Internal Energy: Gas Phase

Scope: Aria Material

Internal Energy: Gas Phase [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Gas_Phase []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Gas phase model for internal energy

4.1.469. Interphase Area

Scope: Aria Material

Interphase Area [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |Sa = *sa*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>sa</i>	real	undefined

Summary Constant value

4.1.470. Interphase Area: Copied

Scope: Aria Material

Interphase Area: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.471. Interphase Area: User Plugin

Scope: Aria Material

Interphase Area: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.472. Interphase Area: Scalar String Function

Scope: Aria Material

Interphase Area: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.473. Interphase Friction Coefficient: Wen Yu

Scope: Aria Material

Interphase Friction Coefficient: Wen Yu [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Wen_Yu [Value = *value* | Diameter = *diameter*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>diameter</i>	real	undefined

4.1.474. Intrinsic Permeability

Scope: Aria Material

Intrinsic Permeability [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [$X_x = xx$ | $T_{11} = t_{11}$ | $X_y = xy$ | $T_{12} = t_{12}$ | $X_z = xz$ | $T_{13} = t_{13}$ | $Y_x = yx$ | $T_{21} = t_{21}$ | $Y_y = yy$ | $T_{22} = t_{22}$ | $Y_z = yz$ | $T_{23} = t_{23}$ | $Z_x = zx$ | $T_{31} = t_{31}$ | $Z_y = zy$ | $T_{32} = t_{32}$ | $Z_z = zz$ | $T_{33} = t_{33}$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>xx</i>	real	undefined
<i>t11</i>	real	undefined
<i>xy</i>	real	undefined
<i>t12</i>	real	undefined
<i>xz</i>	real	undefined
<i>t13</i>	real	undefined
<i>yx</i>	real	undefined
<i>t21</i>	real	undefined
<i>yy</i>	real	undefined
<i>t22</i>	real	undefined
<i>yz</i>	real	undefined
<i>t23</i>	real	undefined
<i>zx</i>	real	undefined
<i>t31</i>	real	undefined
<i>zy</i>	real	undefined
<i>t32</i>	real	undefined
<i>zz</i>	real	undefined
<i>t33</i>	real	undefined

Summary Constant tensor value for the intrinsic permeability

4.1.475. Intrinsic Permeability: Diagonal

Scope: Aria Material

Intrinsic Permeability: Diagonal [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Diagonal [Variable = *variable*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>variable</i>	"string"	undefined

4.1.476. Intrinsic Permeability: Reordered Adagio

Scope: Aria Material

Intrinsic Permeability: Reordered Adagio [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Reordered_Adagio [Variable = *variable* |Restriction = *restriction*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>variable</i>	"string"	undefined
<i>restriction</i>	"string"	undefined

4.1.477. Intrinsic Permeability: Log Reordered Adagio

Scope: Aria Material

Intrinsic Permeability: Log Reordered Adagio [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Log_Reordered_Adagio [Variable = *variable*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>variable</i>	"string"	undefined

4.1.478. Intrinsic Permeability: Volume Average

Scope: Aria Material

Intrinsic Permeability: Volume Average [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Volume_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Average intrinsic permeability: $\text{sum}(\text{volume\_fractions} * \text{permeabilities}) / \text{sum}(\text{volume\_fractions})$

4.1.479. Intrinsic Permeability: Young And Todd

Scope: Aria Material

Intrinsic Permeability: Young And Todd [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Young_And_Todd [Pore_Diameter = *pore_diameter* | Liquid_Phase_Name = *Liquid_Phase_Name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>pore_diameter</i>	real	undefined
<i>Liquid_Phase_Name</i>	"string"	undefined

Summary The Young and Todd permeability model described in SAND2010-0254. $\kappa = \frac{d^2}{32} \frac{\phi}{\tau^2}$

4.1.480. Intrinsic Permeability: Carmen Kozeny

Scope: Aria Material

Intrinsic Permeability: Carmen Kozeny [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Carmen_Kozeny [Sv = *Sv* |Min_Porosity = *min_porosity* |Liquid_Phase_Name = *Liquid_Phase_Name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Sv</i>	real	undefined
<i>min_porosity</i>	real	undefined
<i>Liquid_Phase_Name</i>	"string"	undefined

Summary The Carmen-Kozeny model for permeability. $\kappa = \frac{1}{2\tau^2 S_v^2} \frac{\phi^3}{(1-\phi)^2}$, where S_v is the surface-to-volume ratio. This form is from B.R. Corrochano et al. Journal of Food Engineering 150 (2015) 106-116 and reduces to the traditional form if $S_v = 6/d$ and $\tau = \sqrt{(2.5)}$.

4.1.481. Intrinsic Permeability: Tensor String Function

Scope: Aria Material

Intrinsic Permeability: Tensor String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Tensor_String_Function [F_Xx = *f_xx* | F_Yy = *f_yy* | F_Xy = *f_xy* | F_Zz = *f_zz* | F_Xz = *f_xz* | F_Yz = *f_yz* | F_Yx = *f_yx* | F_Zx = *f_zx* | F_Zy = *f_zy*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_xx</i>	"string"	undefined
<i>f_yy</i>	"string"	undefined
<i>f_xy</i>	"string"	undefined
<i>f_zz</i>	"string"	undefined
<i>f_xz</i>	"string"	undefined
<i>f_yz</i>	"string"	undefined
<i>f_yx</i>	"string"	undefined
<i>f_zx</i>	"string"	undefined
<i>f_zy</i>	"string"	undefined

Summary Value from a string function

4.1.482. Intrinsic Permeability: Tensor String Function Symmetric

Scope: Aria Material

Intrinsic Permeability: Tensor String Function Symmetric [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Tensor_String_Function_Symmetric [F_Xx = f_{xx} |F_Yy = f_{yy} |F_Xy = f_{xy} |
F_Zz = f_{zz} |F_Xz = f_{xz} |F_Yz = f_{yz} |F_Yx = f_{yx} |F_Zx = f_{zx} |F_Zy = f_{zy}]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f_{xx}	"string"	undefined
f_{yy}	"string"	undefined
f_{xy}	"string"	undefined
f_{zz}	"string"	undefined
f_{xz}	"string"	undefined
f_{yz}	"string"	undefined
f_{yx}	"string"	undefined
f_{zx}	"string"	undefined
f_{zy}	"string"	undefined

Summary Value from a string function

4.1.483. Intrinsic Permeability Scaling

Scope: Aria Material

Intrinsic Permeability Scaling [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |S = *s*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>s</i>	real	undefined

Summary Constant value

4.1.484. Intrinsic Permeability Scaling: Copied

Scope: Aria Material

Intrinsic Permeability Scaling: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.485. Intrinsic Permeability Scaling: User Plugin

Scope: Aria Material

Intrinsic Permeability Scaling: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.486. Intrinsic Permeability Scaling: Scalar String Function

Scope: Aria Material

Intrinsic Permeability Scaling: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.487. Intrinsic Permeability Scaling: Kozeny

Scope: Aria Material

Intrinsic Permeability Scaling: Kozeny [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Kozeny [Multiplier = *multiplier* | Phi_Ref = *phi_ref*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>phi_ref</i>	real	undefined

Summary Intrinsic Permeability scaling function using Kozeny's model.

4.1.488. Intrinsic Permeability Scaling: T Exponent

Scope: Aria Material

Intrinsic Permeability Scaling: T Exponent [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= T_Exponent [K_Ref = *k_ref* |T_Ref = *t_ref* |N = *n*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>k_ref</i>	real	undefined
<i>t_ref</i>	real	undefined
<i>n</i>	real	undefined

Summary Intrinsic permeability scaling factor as a power of normalized temperature

4.1.489. Intrinsic Permeability Scaling: Forchheimer

Scope: Aria Material

Intrinsic Permeability Scaling: Forchheimer [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Forchheimer [Inertia_Coeff = *inertia_coeff* |Gx = *gx* |Gy = *gy* |Gz = *gz* |Xx = *xx* |Yy = *yy* |Zz = *zz* |Xy = *xy* |Xz = *xz* |Yz = *yz* |Yx = *yx* |Zx = *zx* |Zy = *zy* |Fluid_Phase = *fluid_phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>inertia_coeff</i>	real	undefined
<i>gx</i>	real	undefined
<i>gy</i>	real	undefined
<i>gz</i>	real	undefined
<i>xx</i>	real	undefined
<i>yy</i>	real	undefined
<i>zz</i>	real	undefined
<i>xy</i>	real	undefined
<i>xz</i>	real	undefined
<i>yz</i>	real	undefined
<i>yx</i>	real	undefined
<i>zx</i>	real	undefined
<i>zy</i>	real	undefined
<i>fluid_phase</i>	"string"	undefined

Summary Intrinsic Permeability scaling for Forchheimer flow.

4.1.490. Inv Neutron Velocity

Scope: Aria Material

Inv Neutron Velocity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Invnu = *InvNu*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>InvNu</i>	real	undefined

Summary Constant value

4.1.491. Inv Neutron Velocity: Copied

Scope: Aria Material

Inv Neutron Velocity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.492. Inv Neutron Velocity: User Plugin

Scope: Aria Material

Inv Neutron Velocity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.493. Inv Neutron Velocity: Scalar String Function

Scope: Aria Material

Inv Neutron Velocity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.494. Irradiation

Scope: Aria Material

Irradiation [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* | I = *i*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>i</i>	real	undefined

Summary Constant value

4.1.495. Irradiation: Copied

Scope: Aria Material

Irradiation: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.496. Irradiation: User Plugin

Scope: Aria Material

Irradiation: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.497. Irradiation: Scalar String Function

Scope: Aria Material

Irradiation: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.498. Irradiation: Calore User Sub

Scope: Aria Material

```
Irradiation: Calore User Sub [ {of|species|subindex} Species |{in|  
material_phase} MaterialPhase ]= Calore_User_Sub [ Name = name |Type = type  
|Multiplier = multiplier |Material_Data_Block = material_data_block |Data  
= data |Scaling_Field = scaling_field ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

4.1.499. Isobaric Compressibility

Scope: Aria Material

```
Isobaric Compressibility [ {of|species|subindex} Species |{in|  
material_phase} MaterialPhase ]= Constant [ Value = value |Beta = beta ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>beta</i>	real	undefined

Summary Constant value

4.1.500. Isobaric Compressibility: Copied

Scope: Aria Material

```
Isobaric Compressibility: Copied [ {of|species|subindex} Species |{in|  
material_phase} MaterialPhase ]= Copied [ Source = source ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.501. Isobaric Compressibility: User Plugin

Scope: Aria Material

Isobaric Compressibility: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.502. Isobaric Compressibility: Scalar String Function

Scope: Aria Material

Isobaric Compressibility: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.503. K Factor

Scope: Aria Material

K Factor [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.504. K Factor: Copied

Scope: Aria Material

K Factor: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.505. K Factor: User Plugin

Scope: Aria Material

K Factor: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.506. K Factor: Scalar String Function

Scope: Aria Material

K Factor: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.507. Kinematic Viscosity: Correlation

Scope: Aria Material

Kinematic Viscosity: Correlation [{of|species|subindex} *Species*]=
Correlation [Nu = *nu* |Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>nu</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation kinematic viscosity

4.1.508. Lambda Brooks Corey

Scope: Aria Material

Lambda Brooks Corey [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |Lambda = *lambda*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>lambda</i>	real	undefined

Summary Constant value

4.1.509. Lambda Brooks Corey: Copied

Scope: Aria Material

Lambda Brooks Corey: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.510. Lambda Brooks Corey: User Plugin

Scope: Aria Material

Lambda Brooks Corey: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.511. Lambda Brooks Corey: Scalar String Function

Scope: Aria Material

Lambda Brooks Corey: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.512. Laminar Correlation Heat Transfer Coefficient: Correlation

Scope: Aria Material

Laminar Correlation Heat Transfer Coefficient: Correlation [{of|species|subindex} *Species*]= Correlation [Number = *number* | Rex = *Rex* | Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>number</i>	integer	undefined
<i>Rex</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation based heat transfer coefficient

4.1.513. Laser Power

Scope: Aria Material

Laser Power [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |P = *p*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>p</i>	real	undefined

Summary Constant value

4.1.514. Laser Power: Copied

Scope: Aria Material

Laser Power: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.515. Laser Power: User Plugin

Scope: Aria Material

Laser Power: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.516. Laser Power: Scalar String Function

Scope: Aria Material

Laser Power: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.517. Latent Heat

Scope: Aria Material

Latent Heat [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.518. Latent Heat: Copied

Scope: Aria Material

Latent Heat: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.519. Latent Heat: User Plugin

Scope: Aria Material

Latent Heat: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.520. Latent Heat: Scalar String Function

Scope: Aria Material

Latent Heat: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.521. Latent Heat: Porous Phase Specific Average

Scope: Aria Material

Latent Heat: Porous Phase Specific Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous_Phase_Specific_Average [Liquid_Phase_Name = *Liquid_Phase_Name* | Gas_Phase_Name = *Gas_Phase_Name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Liquid_Phase_Name</i>	"string"	undefined
<i>Gas_Phase_Name</i>	"string"	undefined

Summary Latent heat for a multiphase material of two or three phases

4.1.522. Level Set

Scope: Aria Material

Level Set [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.523. Level Set: Copied

Scope: Aria Material

Level Set: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.524. Level Set: User Plugin

Scope: Aria Material

Level Set: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.525. Level Set: Scalar String Function

Scope: Aria Material

Level Set: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.526. Level Set Curvature

Scope: Aria Material

Level Set Curvature [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Kappa = *kappa*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>kappa</i>	real	undefined

Summary Constant value

4.1.527. Level Set Curvature: Copied

Scope: Aria Material

Level Set Curvature: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.528. Level Set Curvature: User Plugin

Scope: Aria Material

Level Set Curvature: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.529. Level Set Curvature: Scalar String Function

Scope: Aria Material

Level Set Curvature: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.530. Level Set Diffusive Flux: Shock Capturing

Scope: Aria Material

Level Set Diffusive Flux: Shock Capturing [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Shock_Capturing [Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined

Summary This model is now deprecated

4.1.531. Level Set Diffusive Flux: Unit Gradient

Scope: Aria Material

Level Set Diffusive Flux: Unit Gradient [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Unit_Gradient []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary This model has been deprecated and removed from the code.

4.1.532. Level Set Diffusive Flux

Scope: Aria Material

Level Set Diffusive Flux [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Coeff = *coeff*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>coeff</i>	real	undefined

Summary This model has been deprecated and removed from the code.

4.1.533. Level Set Heaviside

Scope: Aria Material

Level Set Heaviside [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.534. Level Set Heaviside: Copied

Scope: Aria Material

Level Set Heaviside: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.535. Level Set Heaviside: User Plugin

Scope: Aria Material

Level Set Heaviside: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.536. Level Set Heaviside: Scalar String Function

Scope: Aria Material

Level Set Heaviside: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.537. Level Set Heaviside: Smooth

Scope: Aria Material

Level Set Heaviside: Smooth [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Smooth [Use_Crossing_Time = *use_crossing_time*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>use_crossing_time</i>	integer	undefined

Summary Smooth level set Heaviside

4.1.538. Level Set Heaviside: Interpolated

Scope: Aria Material

Level Set Heaviside: Interpolated [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Interpolated [Epsilon = *epsilon*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>epsilon</i>	real	undefined

Summary Interpolated level set Heaviside

4.1.539. Level Set Heaviside: Bf Interpolated

Scope: Aria Material

Level Set Heaviside: Bf Interpolated [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Bf_Interpolated [Use_Crossing_Time = *use_crossing_time*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>use_crossing_time</i>	integer	undefined

Summary BF interpolated level set Heaviside

4.1.540. Level Set Heaviside: Sharp Analytic

Scope: Aria Material

Level Set Heaviside: Sharp Analytic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Sharp_Analytic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Sharp analytic level set Heaviside

4.1.541. Level Set Normal Bulk Conductivity

Scope: Aria Material

Level Set Normal Bulk Conductivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |K = *k*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>k</i>	real	undefined

Summary Constant value

4.1.542. Level Set Normal Bulk Conductivity: Copied

Scope: Aria Material

Level Set Normal Bulk Conductivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.543. Level Set Normal Bulk Conductivity: User Plugin

Scope: Aria Material

Level Set Normal Bulk Conductivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.544. Level Set Normal Bulk Conductivity: Scalar String Function

Scope: Aria Material

Level Set Normal Bulk Conductivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.545. Level Set Normal Bulk Conductivity: Inverse Volume Average

Scope: Aria Material

Level Set Normal Bulk Conductivity: Inverse Volume Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Inverse_Volume_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Bulk Thermal conductivity normal to a level set field as a volume average of the species bulk densities $(\rho = \sum_i \left(\frac{v_i}{K_{b,i}} \right)^{-1})$.

4.1.546. Level Set Normal Bulk Conductivity: Volume Average

Scope: Aria Material

Level Set Normal Bulk Conductivity: Volume Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Volume_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Bulk Thermal conductivity normal to a level set field computed from volume average of species conductivities

4.1.547. Level Set Normal Conductivity

Scope: Aria Material

Level Set Normal Conductivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |K = *k*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>k</i>	real	undefined

Summary Constant value

4.1.548. Level Set Normal Conductivity: Copied

Scope: Aria Material

Level Set Normal Conductivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.549. Level Set Normal Conductivity: User Plugin

Scope: Aria Material

Level Set Normal Conductivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.550. Level Set Normal Conductivity: Scalar String Function

Scope: Aria Material

Level Set Normal Conductivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.551. Level Set Tangential Bulk Conductivity: Inverse Volume Average

Scope: Aria Material

Level Set Tangential Bulk Conductivity: Inverse Volume Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Inverse_Volume_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Bulk Thermal conductivity tangential to a level set field as a volume average of the species bulk densities $(\rho = \sum_i \left(\frac{v_i}{K_{b,i}} \right)^{-1})$.

4.1.552. Level Set Tangential Bulk Conductivity: Volume Average

Scope: Aria Material

Level Set Tangential Bulk Conductivity: Volume Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Volume_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Bulk Thermal conductivity tangential to a level set field computed from volume average of species conductivities

4.1.553. Level Set Tangential Bulk Conductivity

Scope: Aria Material

Level Set Tangential Bulk Conductivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |K = *k*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>k</i>	real	undefined

Summary Constant value

4.1.554. Level Set Tangential Bulk Conductivity: Copied

Scope: Aria Material

Level Set Tangential Bulk Conductivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.555. Level Set Tangential Bulk Conductivity: User Plugin

Scope: Aria Material

Level Set Tangential Bulk Conductivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |*magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.556. Level Set Tangential Bulk Conductivity: Scalar String Function

Scope: Aria Material

Level Set Tangential Bulk Conductivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f	"string"	undefined

Summary Value from a string function

4.1.557. Level Set Tangential Conductivity

Scope: Aria Material

Level Set Tangential Conductivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* | $K = k$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
k	real	undefined

Summary Constant value

4.1.558. Level Set Tangential Conductivity: Copied

Scope: Aria Material

Level Set Tangential Conductivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.559. Level Set Tangential Conductivity: User Plugin

Scope: Aria Material

Level Set Tangential Conductivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.560. Level Set Tangential Conductivity: Scalar String Function

Scope: Aria Material

Level Set Tangential Conductivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.561. Level Set Width

Scope: Aria Material

Level Set Width [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Width = *width*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>width</i>	real	undefined

Summary Specification of a constant width diffuse level set

4.1.562. Liquid Phase Retardation

Scope: Aria Material

Liquid Phase Retardation [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Constant [Value = *value* |R = *r*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>r</i>	real	undefined

Summary Constant value

4.1.563. Liquid Phase Retardation: Copied

Scope: Aria Material

Liquid Phase Retardation: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.564. Liquid Phase Retardation: User Plugin

Scope: Aria Material

Liquid Phase Retardation: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.565. Liquid Phase Retardation: Scalar String Function

Scope: Aria Material

Liquid Phase Retardation: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.566. Lubrication Height

Scope: Aria Material

Lubrication Height [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value* | H = *h*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>h</i>	real	undefined

Summary Constant value

4.1.567. Lubrication Height: Copied

Scope: Aria Material

Lubrication Height: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.568. Lubrication Height: User Plugin

Scope: Aria Material

Lubrication Height: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.569. Lubrication Height: Scalar String Function

Scope: Aria Material

Lubrication Height: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.570. Lubrication Height: Combined

Scope: Aria Material

Lubrication Height: Combined [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Combined []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Calculate the lubrication height by combining the upper and lower heights

4.1.571. Lubrication Height Lower

Scope: Aria Material

Lubrication Height Lower [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |H_Lower = *h_lower*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>h_lower</i>	real	undefined

Summary Constant value

4.1.572. Lubrication Height Lower: Copied

Scope: Aria Material

Lubrication Height Lower: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.573. Lubrication Height Lower: User Plugin

Scope: Aria Material

Lubrication Height Lower: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.574. Lubrication Height Lower: Scalar String Function

Scope: Aria Material

Lubrication Height Lower: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.575. Lubrication Height Upper

Scope: Aria Material

Lubrication Height Upper [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value* | H_Upper = *h_upper*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>h_upper</i>	real	undefined

Summary Constant value

4.1.576. Lubrication Height Upper: Copied

Scope: Aria Material

Lubrication Height Upper: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.577. Lubrication Height Upper: User Plugin

Scope: Aria Material

Lubrication Height Upper: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.578. Lubrication Height Upper: Scalar String Function

Scope: Aria Material

Lubrication Height Upper: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.579. Lubrication K

Scope: Aria Material

Lubrication K [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |K = *k*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>k</i>	real	undefined

Summary Constant value

4.1.580. Lubrication K: Copied

Scope: Aria Material

Lubrication K: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.581. Lubrication K: User Plugin

Scope: Aria Material

Lubrication K: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.582. Lubrication K: Scalar String Function

Scope: Aria Material

Lubrication K: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.583. Lubrication Pressure

Scope: Aria Material

Lubrication Pressure [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.584. Lubrication Pressure: Copied

Scope: Aria Material

Lubrication Pressure: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.585. Lubrication Pressure: User Plugin

Scope: Aria Material

Lubrication Pressure: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.586. Lubrication Pressure: Scalar String Function

Scope: Aria Material

Lubrication Pressure: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F =
f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.587. Lubrication Velocity Lower

Scope: Aria Material

Lubrication Velocity Lower [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [V_Lowerx = *v_lowerx* |V_Lowery =
v_lowery |V_Lowerz = *v_lowerz*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>v_lowerx</i>	real	undefined
<i>v_lowery</i>	real	undefined
<i>v_lowerz</i>	real	undefined

Summary Constant value

4.1.588. Lubrication Velocity Lower: User Plugin

Scope: Aria Material

Lubrication Velocity Lower: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.589. Lubrication Velocity Lower: Vector String Function

Scope: Aria Material

Lubrication Velocity Lower: Vector String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Vector_String_Function [$F_X = f_x$ | $F_Y = f_y$ | $F_Z = f_z$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f_x	"string"	undefined
f_y	"string"	undefined
f_z	"string"	undefined

Summary Value from a string function

4.1.590. Lubrication Velocity Upper

Scope: Aria Material

Lubrication Velocity Upper [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [$V_{Upperx} = v_{upperx}$ | $V_{Uppery} = v_{uppery}$ | $V_{Upperz} = v_{upperz}$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
v_{upperx}	real	undefined
v_{uppery}	real	undefined
v_{upperz}	real	undefined

Summary Constant value

4.1.591. Lubrication Velocity Upper: User Plugin

Scope: Aria Material

Lubrication Velocity Upper: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.592. Lubrication Velocity Upper: Vector String Function

Scope: Aria Material

Lubrication Velocity Upper: Vector String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Vector_String_Function [*F_X* = *f_x* | *F_Y* = *f_y* | *F_Z* = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

4.1.593. Mach Number

Scope: Aria Material

Mach Number [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value* | *Ma* = *Ma*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>Ma</i>	real	undefined

Summary Constant value

4.1.594. Mach Number: Copied

Scope: Aria Material

Mach Number: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.595. Mach Number: User Plugin

Scope: Aria Material

Mach Number: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.596. Mach Number: Scalar String Function

Scope: Aria Material

Mach Number: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.597. Magnetic Field Flux: Remanent

Scope: Aria Material

Magnetic Field Flux: Remanent [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Remanent []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Remanent Field Flux

4.1.598. Magnetic Flux Intensity

Scope: Aria Material

Magnetic Flux Intensity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.599. Magnetic Flux Intensity: Copied

Scope: Aria Material

Magnetic Flux Intensity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.600. Magnetic Flux Intensity: User Plugin

Scope: Aria Material

Magnetic Flux Intensity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.601. Magnetic Flux Intensity: Scalar String Function

Scope: Aria Material

Magnetic Flux Intensity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [*F* = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.602. Magnetic Flux Stress: Grad B

Scope: Aria Material

Magnetic Flux Stress: Grad B [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Grad_B []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.603. Magnetic Flux Stress: Magnetic Pressure

Scope: Aria Material

Magnetic Flux Stress: Magnetic Pressure [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Magnetic_Pressure []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.604. Magnetic Flux Stress: Grad Div B

Scope: Aria Material

Magnetic Flux Stress: Grad Div B [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Grad_Div_B []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.605. Magnetic Permeability

Scope: Aria Material

Magnetic Permeability [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value* | Mu = *mu*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>mu</i>	real	undefined

Summary Constant value

4.1.606. Magnetic Permeability: Copied

Scope: Aria Material

Magnetic Permeability: Copied [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.607. Magnetic Permeability: User Plugin

Scope: Aria Material

Magnetic Permeability: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.608. Magnetic Permeability: Scalar String Function

Scope: Aria Material

Magnetic Permeability: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.609. Magnetic Potential Stress: Grad A

Scope: Aria Material

Magnetic Potential Stress: Grad A [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Grad_A []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.610. Magnetic Potential Stress: Voltage

Scope: Aria Material

Magnetic Potential Stress: Voltage [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Voltage []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.611. Magnetic Pressure

Scope: Aria Material

Magnetic Pressure [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.612. Magnetic Pressure: Copied

Scope: Aria Material

Magnetic Pressure: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.613. Magnetic Pressure: User Plugin

Scope: Aria Material

Magnetic Pressure: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.614. Magnetic Pressure: Scalar String Function

Scope: Aria Material

Magnetic Pressure: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.615. Magnetic Relative Permeability

Scope: Aria Material

Magnetic Relative Permeability [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.616. Magnetic Relative Permeability: Copied

Scope: Aria Material

Magnetic Relative Permeability: Copied [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.617. Magnetic Relative Permeability: User Plugin

Scope: Aria Material

Magnetic Relative Permeability: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.618. Magnetic Relative Permeability: Scalar String Function

Scope: Aria Material

Magnetic Relative Permeability: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.619. Magnetization

Scope: Aria Material

Magnetization [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Mx = *mx* |My = *my* |Mz = *mz*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>mx</i>	real	undefined
<i>my</i>	real	undefined
<i>mz</i>	real	undefined

Summary Constant value

4.1.620. Magnetization: User Plugin

Scope: Aria Material

Magnetization: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.621. Magnetization: Vector String Function

Scope: Aria Material

Magnetization: Vector String Function [{of|species|subindex} *Species* |
{in|material_phase} *MaterialPhase*]= Vector_String_Function [F_X = *f_x* |
F_Y = *f_y* |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

4.1.622. Masking

Scope: Aria Material

Masking [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.623. Masking: Copied

Scope: Aria Material

Masking: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.624. Masking: User Plugin

Scope: Aria Material

Masking: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.625. Masking: Scalar String Function

Scope: Aria Material

Masking: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.626. Mass Balance Advective Flux: Porous

Scope: Aria Material

Mass Balance Advective Flux: Porous [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Mass balance advection term from mass fraction and mass flux.

4.1.627. Mass Balance Advective Flux: Porous Upwind

Scope: Aria Material

Mass Balance Advective Flux: Porous Upwind [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous_Upwind []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Mass balance advection term from mass fraction and mass flux.

4.1.628. Mass Balance Advective Flux: Single Phase

Scope: Aria Material

Mass Balance Advective Flux: Single Phase [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Single_Phase []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Mass balance advection term from density and velocity

4.1.629. Mass Balance Diffusive Flux: Porous

Scope: Aria Material

Mass Balance Diffusive Flux: Porous [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Mass balance diffusive term from porosity, mass diffusivity, mass fraction and density.

4.1.630. Mass Balance Diffusive Flux: Nernst Planck

Scope: Aria Material

Mass Balance Diffusive Flux: Nernst Planck [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Nernst_Planck [$F = f$ | $R = r$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f	real	undefined
r	real	undefined

4.1.631. Mass Balance Diffusive Flux: Density

Scope: Aria Material

Mass Balance Diffusive Flux: Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Density []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Mass balance diffusive term from porosity, mass diffusivity, mass fraction and density.

4.1.632. Mass Balance Diffusive Flux: Basic

Scope: Aria Material

Mass Balance Diffusive Flux: Basic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Basic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Mass balance diffusive term from mass diffusivity, mass fraction and density.

4.1.633. Mass Diffusivity

Scope: Aria Material

Mass Diffusivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |D = *d*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>d</i>	real	undefined

Summary Constant value

4.1.634. Mass Diffusivity: Copied

Scope: Aria Material

Mass Diffusivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.635. Mass Diffusivity: User Plugin

Scope: Aria Material

Mass Diffusivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.636. Mass Diffusivity: Scalar String Function

Scope: Aria Material

Mass Diffusivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.637. Mass Diffusivity: Cantera

Scope: Aria Material

Mass Diffusivity: Cantera [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Cantera [Poffset = *poffset*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>poffset</i>	real	undefined

Summary Cantera mass diffusivity

4.1.638. Mass Diffusivity: From Schmidt

Scope: Aria Material

Mass Diffusivity: From Schmidt [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Schmidt []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Mass diffusivity from a Schmidt number and viscosity

4.1.639. Mass Diffusivity: Air Water

Scope: Aria Material

Mass Diffusivity: Air Water [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Air_Water [Tortuosity = *tortuosity* |P_Ref = *p_ref* |D_Ref = *d_ref* |Exponent = *exponent*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>tortuosity</i>	real	undefined
<i>p_ref</i>	real	undefined
<i>d_ref</i>	real	undefined
<i>exponent</i>	real	undefined

Summary Air/Water mass diffusivity

4.1.640. Mass Diffusivity: Arrhenius

Scope: Aria Material

Mass Diffusivity: Arrhenius [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Arrhenius [R = *r* |C = *c* |D = *d* |Q = *q*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>r</i>	real	undefined
<i>c</i>	real	undefined
<i>d</i>	real	undefined
<i>q</i>	real	undefined

Summary Arrhenius mass diffusivity, $D_m = C + D * \exp\left(-\frac{Q}{RT}\right)$

4.1.641. Mass Diffusivity: Chapman Enskog

Scope: Aria Material

Mass Diffusivity: Chapman Enskog [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Chapman_Enskog [D0 = *d0* |P0 = *p0* |T0 = *t0*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>d0</i>	real	undefined
<i>p0</i>	real	undefined
<i>t0</i>	real	undefined

Summary Mass diffusivity model for gases that scales with $T^{3/2}/P$ based on Chapman-Enskog theory.

4.1.642. Mass Flux: Darcy

Scope: Aria Material

Mass Flux: Darcy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Darcy []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.643. Mass Fraction

Scope: Aria Material

Mass Fraction [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.644. Mass Fraction: Copied

Scope: Aria Material

Mass Fraction: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.645. Mass Fraction: User Plugin

Scope: Aria Material

Mass Fraction: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.646. Mass Fraction: Scalar String Function

Scope: Aria Material

Mass Fraction: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] = Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.647. Mass Fraction: Fracbal

Scope: Aria Material

Mass Fraction: Fracbal [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] = Fracbal []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Mass fraction of one species to yield a unity sum over all species

4.1.648. Mass Fraction: From Chemeq

Scope: Aria Material

Mass Fraction: From Chemeq [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] = From_Chemeq []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Mass fraction of one species extracted from ChemEq

4.1.649. Mass Fraction: From Density

Scope: Aria Material

Mass Fraction: From Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Density []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Species density / overall density.

4.1.650. Mass Fraction Diffusive Flux: Basic

Scope: Aria Material

Mass Fraction Diffusive Flux: Basic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Basic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Basic model of mass fraction diffusive flux

4.1.651. Mass Fraction Diffusive Flux: Energy Mass

Scope: Aria Material

Mass Fraction Diffusive Flux: Energy Mass [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Energy_Mass []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Energy_Mass model of mass fraction diffusive flux

4.1.652. Material Data Block: Resource

Scope: Aria Material

Material Data Block: Resource [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Resource [Data_Block_Name = *data_block_name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>data_block_name</i>	"string"	undefined

Summary Resource material data block

4.1.653. Melt Temperature

Scope: Aria Material

Melt Temperature [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.654. Melt Temperature: Copied

Scope: Aria Material

Melt Temperature: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.655. Melt Temperature: User Plugin

Scope: Aria Material

Melt Temperature: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.656. Melt Temperature: Scalar String Function

Scope: Aria Material

Melt Temperature: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.657. Mesh Body Acceleration

Scope: Aria Material

Mesh Body Acceleration [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Valuex = *valuex* |Valuey = *valuey* |Valuez = *valuez*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>valuex</i>	real	undefined
<i>valuey</i>	real	undefined
<i>valuez</i>	real	undefined

Summary Constant value

4.1.658. Mesh Body Acceleration: User Plugin

Scope: Aria Material

Mesh Body Acceleration: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.659. Mesh Body Acceleration: Vector String Function

Scope: Aria Material

Mesh Body Acceleration: Vector String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Vector_String_Function [F_X = *f_x* |F_Y = *f_y* |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

4.1.660. Mesh Lambda

Scope: Aria Material

Mesh Lambda [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Lambda = *lambda*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>lambda</i>	real	undefined

Summary Constant value

4.1.661. Mesh Lambda: Copied

Scope: Aria Material

Mesh Lambda: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.662. Mesh Lambda: User Plugin

Scope: Aria Material

Mesh Lambda: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.663. Mesh Lambda: Scalar String Function

Scope: Aria Material

Mesh Lambda: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.664. Mesh Lambda: Converted

Scope: Aria Material

Mesh Lambda: Converted [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Converted []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Lame coefficient computed from Poisson's ratio and elastic modulus

4.1.665. Mesh Lambda: Converted Plane Stress

Scope: Aria Material

Mesh Lambda: Converted Plane Stress [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Converted_Plane_Stress []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary This model has been deprecated and removed from the code.

4.1.666. Mesh Lambda: Elemental Volume

Scope: Aria Material

Mesh Lambda: Elemental Volume [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Elemental_Volume []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Lambda computed from elemental volume

4.1.667. Mesh Lambda: Inverse Element Volume

Scope: Aria Material

Mesh Lambda: Inverse Element Volume [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Inverse_Element_Volume [Lagged = *lagged*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>lagged</i>	integer	undefined

Summary This model has been deprecated and removed from the code.

4.1.668. Mesh Poissons Ratio

Scope: Aria Material

Mesh Poissons Ratio [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Nu = *nu*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>nu</i>	real	undefined

Summary Constant value

4.1.669. Mesh Poissons Ratio: Copied

Scope: Aria Material

Mesh Poissons Ratio: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.670. Mesh Poissons Ratio: User Plugin

Scope: Aria Material

Mesh Poissons Ratio: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.671. Mesh Poissons Ratio: Scalar String Function

Scope: Aria Material

Mesh Poissons Ratio: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.672. Mesh Stress

Scope: Aria Material

Mesh Stress [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Xx = *xx* |T11 = *t11* |Xy = *xy* |T12 = *t12* |Xz = *xz* |T13 = *t13* |Yx = *yx* |T21 = *t21* |Yy = *yy* |T22 = *t22* |Yz = *yz* |T23 = *t23* |Zx = *zx* |T31 = *t31* |Zy = *zy* |T32 = *t32* |Zz = *zz* |T33 = *t33*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>xx</i>	real	undefined
<i>t11</i>	real	undefined
<i>xy</i>	real	undefined
<i>t12</i>	real	undefined
<i>xz</i>	real	undefined
<i>t13</i>	real	undefined
<i>yx</i>	real	undefined
<i>t21</i>	real	undefined
<i>yy</i>	real	undefined
<i>t22</i>	real	undefined
<i>yz</i>	real	undefined
<i>t23</i>	real	undefined
<i>zx</i>	real	undefined
<i>t31</i>	real	undefined
<i>zy</i>	real	undefined
<i>t32</i>	real	undefined
<i>zz</i>	real	undefined
<i>t33</i>	real	undefined

Summary Constant value

4.1.673. Mesh Stress: User Plugin

Scope: Aria Material

```
Mesh Stress:  User Plugin [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]= User_Plugin [ Name = Name |
magic_trailing_string_vector_param ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.674. Mesh Stress: Tensor String Function

Scope: Aria Material

```
Mesh Stress:  Tensor String Function [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]= Tensor_String_Function [ F_Xx = f_xx |F_Yy
```

= f_{yy} | $F_{Xy} = f_{xy}$ | $F_{Zz} = f_{zz}$ | $F_{Xz} = f_{xz}$ | $F_{Yz} = f_{yz}$ | $F_{Yx} = f_{yx}$
| $F_{Zx} = f_{zx}$ | $F_{Zy} = f_{zy}$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f_{xx}	"string"	undefined
f_{yy}	"string"	undefined
f_{xy}	"string"	undefined
f_{zz}	"string"	undefined
f_{xz}	"string"	undefined
f_{yz}	"string"	undefined
f_{yx}	"string"	undefined
f_{zx}	"string"	undefined
f_{zy}	"string"	undefined

Summary Value from a string function

4.1.675. Mesh Stress: Tensor String Function Symmetric

Scope: Aria Material

Mesh Stress: Tensor String Function Symmetric [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Tensor_String_Function_Symmetric [$F_{Xx} = f_{xx}$ | $F_{Yy} = f_{yy}$ | $F_{Xy} = f_{xy}$ |
 $F_{Zz} = f_{zz}$ | $F_{Xz} = f_{xz}$ | $F_{Yz} = f_{yz}$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f_{xx}	"string"	undefined
f_{yy}	"string"	undefined
f_{xy}	"string"	undefined
f_{zz}	"string"	undefined
f_{xz}	"string"	undefined
f_{yz}	"string"	undefined

Summary Value from a string function

4.1.676. Mesh Stress: Isothermal

Scope: Aria Material

Mesh Stress: Isothermal [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Isothermal [$T = t$ | $T_{Ref} = t_{ref}$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>t</i>	real	undefined
<i>t_ref</i>	real	undefined

4.1.677. Mesh Stress: Linear Elastic

Scope: Aria Material

Mesh Stress: Linear Elastic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Linear_Elastic [Reference_Frame = *reference_frame*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>reference_frame</i>	"string"	undefined

4.1.678. Mesh Stress: Porous Effective

Scope: Aria Material

Mesh Stress: Porous Effective [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous_Effective [Pressure = *pressure* | Phase = *phase* | Biot = *biot*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>pressure</i>	"string"	undefined
<i>phase</i>	"string"	undefined
<i>biot</i>	real	undefined

Summary Apply the pressure as an isotropic mesh stress. Primarily used as an effective stress in porous flow problems.

4.1.679. Mesh Stress: Saturation Weighted Porous Effective

Scope: Aria Material

Mesh Stress: Saturation Weighted Porous Effective [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Saturation_Weighted_Porous_Effective [Pressure = *pressure* | Phase = *phase* | Biot = *biot*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>pressure</i>	"string"	undefined
<i>phase</i>	"string"	undefined
<i>biot</i>	real	undefined

Summary Apply the saturation-weighted pressure as an isotropic mesh stress. Primarily used as an effective stress in porous flow problems.

4.1.680. Mesh Stress: Mooney Rivlin

Scope: Aria Material

```
Mesh Stress: Mooney Rivlin [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]= Mooney_Rivlin [ ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.681. Mesh Stress: Neohookean Elastic

Scope: Aria Material

```
Mesh Stress: Neohookean Elastic [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]= Neohookean_Elastic [ ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.682. Mesh Stress: Nonlinear Elastic

Scope: Aria Material

```
Mesh Stress: Nonlinear Elastic [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]= Nonlinear_Elastic [ ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.683. Mesh Stress: Residual

Scope: Aria Material

```
Mesh Stress: Residual [ {of|species|subindex} Species |{in|material_phase} MaterialPhase ]= Residual [ Sz = sz |Szz = szz |Sxz = szx |Syz = syx |Sy = sy |Syy = syy |Sxy = sxy |Sx = sx |Sxx = sxx ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>sz</i>	real	undefined
<i>szz</i>	real	undefined
<i>szx</i>	real	undefined
<i>syx</i>	real	undefined
<i>sy</i>	real	undefined
<i>syy</i>	real	undefined
<i>sxy</i>	real	undefined
<i>sx</i>	real	undefined
<i>sxx</i>	real	undefined

4.1.684. Mesh Stress: Thermal

Scope: Aria Material

```
Mesh Stress: Thermal [ {of|species|subindex} Species |{in|material_phase} MaterialPhase ]= Thermal [ ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.685. Mesh Stress: Electrode Old

Scope: Aria Material

```
Mesh Stress: Electrode Old [ {of|species|subindex} Species |{in|material_phase} MaterialPhase ]= Electrode_Old [ F = f |Electrodefile = electrodeFile |Kmolconversion = kmolConversion |Jconversion = JConversion |Meterconversion = meterConversion |Max_Sub_Timesteps = max_sub_timesteps |Base_Delta = base_delta ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	real	undefined
<i>electrodeFile</i>	"string"	undefined
<i>kmolConversion</i>	real	undefined
<i>JConversion</i>	real	undefined
<i>meterConversion</i>	real	undefined
<i>max_sub_timesteps</i>	integer	undefined
<i>base_delta</i>	real	undefined

4.1.686. Mesh Stress: Species

Scope: Aria Material

Mesh Stress: Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Species [Sref = *sref* |Phase = *phase* |Species = *strain_species_name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>sref</i>	real	undefined
<i>phase</i>	"string"	undefined
<i>strain_species_name</i>	"string"	undefined

Summary A linear mechanical strain due to a species concentration

4.1.687. Mesh Stress: Species Transversely Isotropic

Scope: Aria Material

Mesh Stress: Species Transversely Isotropic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Species_Transversely_Isotropic [Refval = *refval* |Beta_N = *beta_n* |Beta_T = *beta_t* |N_X = *n_x* |N_Y = *n_y* |N_Z = *n_z* |Phase = *phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>refval</i>	real	undefined
<i>beta_n</i>	real	undefined
<i>beta_t</i>	real	undefined
<i>n_x</i>	real	undefined
<i>n_y</i>	real	undefined
<i>n_z</i>	real	undefined
<i>phase</i>	"string"	undefined

Summary A linear mechanical strain that is transversely isotropic due to a species concentration

4.1.688. Mesh Stress: Species Anisotropic

Scope: Aria Material

Mesh Stress: Species Anisotropic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Species_Anisotropic [Sref = *sref* |Phase = *phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>sref</i>	real	undefined
<i>phase</i>	"string"	undefined

Summary Anisotropic linear mechanical strain due to a species concentration

4.1.689. Mesh Stress: Lame

Scope: Aria Material

Mesh Stress: Lame [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Lame [Model = *model*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>model</i>	"string"	undefined

4.1.690. Mesh Two Mu

Scope: Aria Material

```
Mesh Two Mu [ {of|species|subindex} Species |{in|material_phase}  
MaterialPhase ]= Constant [ Value = value |Two_Mu = two_mu ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>two_mu</i>	real	undefined

Summary Constant value

4.1.691. Mesh Two Mu: Copied

Scope: Aria Material

```
Mesh Two Mu: Copied [ {of|species|subindex} Species |{in|material_phase}  
MaterialPhase ]= Copied [ Source = source ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.692. Mesh Two Mu: User Plugin

Scope: Aria Material

```
Mesh Two Mu: User Plugin [ {of|species|subindex} Species |{in|  
material_phase} MaterialPhase ]= User_Plugin [ Name = Name |  
magic_trailing_string_vector_param ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.693. Mesh Two Mu: Scalar String Function

Scope: Aria Material

Mesh Two Mu: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.694. Mesh Two Mu: Converted

Scope: Aria Material

Mesh Two Mu: Converted [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Converted []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Lamé coefficient computed from Poisson's ratio and elastic modulus

4.1.695. Mesh Two Mu: Elemental Volume

Scope: Aria Material

Mesh Two Mu: Elemental Volume [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Elemental_Volume []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary 2 mu computed from elemental volume

4.1.696. Mesh Two Mu: Inverse Element Volume

Scope: Aria Material

```
Mesh Two Mu: Inverse Element Volume [ {of|species|subindex} Species |{in|material_phase} MaterialPhase ]= Inverse_Element_Volume [ Lagged = lagged ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>lagged</i>	integer	undefined

Summary This model has been deprecated and removed from the code.

4.1.697. Mesh Two Mu: Faux Plasticity

Scope: Aria Material

```
Mesh Two Mu: Faux Plasticity [ {of|species|subindex} Species |{in|material_phase} MaterialPhase ]= Faux_Plasticity [ E = e |Yield_Stress = yield_stress |Hard = hard |Min_Stress_Multiplier = min_stress_multiplier ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>e</i>	real	undefined
<i>yield_stress</i>	real	undefined
<i>hard</i>	"string"	undefined
<i>min_stress_multiplier</i>	real	undefined

4.1.698. Mesh Velocity

Scope: Aria Material

```
Mesh Velocity [ {of|species|subindex} Species |{in|material_phase} MaterialPhase ]= Constant [ X = x |Y = y |Z = z ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>x</i>	real	undefined
<i>y</i>	real	undefined
<i>z</i>	real	undefined

Summary Constant value

4.1.699. Mesh Velocity: User Plugin

Scope: Aria Material

Mesh Velocity: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.700. Mesh Velocity: Vector String Function

Scope: Aria Material

Mesh Velocity: Vector String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Vector_String_Function [F_X = *f_x* | F_Y = *f_y* | F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

4.1.701. Mesh Youngs Modulus

Scope: Aria Material

Mesh Youngs Modulus [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value* | E = *e*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>e</i>	real	undefined

Summary Constant value

4.1.702. Mesh Youngs Modulus: Copied

Scope: Aria Material

Mesh Youngs Modulus: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.703. Mesh Youngs Modulus: User Plugin

Scope: Aria Material

Mesh Youngs Modulus: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.704. Mesh Youngs Modulus: Scalar String Function

Scope: Aria Material

Mesh Youngs Modulus: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.705. Mesh Youngs Modulus: Melting Jamming Porous

Scope: Aria Material

```
Mesh Youngs Modulus: Melting Jamming Porous [ {of|species|subindex}
Species |{in|material_phase} MaterialPhase ]= Melting_Jamming_Porous [
Jam_Porosity = jam_porosity |Jam_Width = jam_width |Solid_Modulus =
solid_modulus |Melted_Modulus = melted_modulus |Jammed_Modulus =
jammed_modulus |Melt_Dt = melt_DT ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>jam_porosity</i>	real	undefined
<i>jam_width</i>	real	undefined
<i>solid_modulus</i>	real	undefined
<i>melted_modulus</i>	real	undefined
<i>jammed_modulus</i>	real	undefined
<i>melt_DT</i>	real	undefined

4.1.706. Mesh Youngs Modulus: Faux Plasticity

Scope: Aria Material

```
Mesh Youngs Modulus: Faux Plasticity [ {of|species|subindex} Species |{in
|material_phase} MaterialPhase ]= Faux_Plasticity [ E = e |Yield_Stress =
yield_stress |Hard = hard |Min_Stress_Multiplier = min_stress_multiplier
]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>e</i>	real	undefined
<i>yield_stress</i>	real	undefined
<i>hard</i>	"string"	undefined
<i>min_stress_multiplier</i>	real	undefined

4.1.707. Mixture Density

Scope: Aria Material

```
Mixture Density [ {of|species|subindex} Species |{in|material_phase}
MaterialPhase ]= Constant [ Value = value ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.708. Mixture Density: Copied

Scope: Aria Material

Mixture Density: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.709. Mixture Density: User Plugin

Scope: Aria Material

Mixture Density: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.710. Mixture Density: Scalar String Function

Scope: Aria Material

Mixture Density: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.711. Mixture Fraction

Scope: Aria Material

Mixture Fraction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.712. Mixture Fraction: Copied

Scope: Aria Material

Mixture Fraction: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.713. Mixture Fraction: User Plugin

Scope: Aria Material

Mixture Fraction: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_parameter</i>	string	undefined

Summary Value from a user plugin

4.1.714. Mixture Fraction: Scalar String Function

Scope: Aria Material

Mixture Fraction: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.715. Mixture Fraction Diffusive Flux: Basic

Scope: Aria Material

Mixture Fraction Diffusive Flux: Basic [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Basic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Basic model of mixture fraction diffusive flux

4.1.716. Mixture Fraction Diffusivity

Scope: Aria Material

Mixture Fraction Diffusivity [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = value | Dz = Dz]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>Dz</i>	real	undefined

Summary Constant value

4.1.717. Mixture Fraction Diffusivity: Copied

Scope: Aria Material

Mixture Fraction Diffusivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.718. Mixture Fraction Diffusivity: User Plugin

Scope: Aria Material

Mixture Fraction Diffusivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.719. Mixture Fraction Diffusivity: Scalar String Function

Scope: Aria Material

Mixture Fraction Diffusivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.720. Mixture Fraction Diffusivity: From Schmidt

Scope: Aria Material

Mixture Fraction Diffusivity: From Schmidt [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Schmidt []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Mixture fraction diffusivity from Schmidt number and viscosity

4.1.721. Mixture Mass Diffusivity

Scope: Aria Material

Mixture Mass Diffusivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Dmix = *Dmix*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>Dmix</i>	real	undefined

Summary Constant value

4.1.722. Mixture Mass Diffusivity: Copied

Scope: Aria Material

Mixture Mass Diffusivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.723. Mixture Mass Diffusivity: User Plugin

Scope: Aria Material

Mixture Mass Diffusivity: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.724. Mixture Mass Diffusivity: Scalar String Function

Scope: Aria Material

Mixture Mass Diffusivity: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [*F* = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.725. Mixture Mass Diffusivity: Mixture Average

Scope: Aria Material

Mixture Mass Diffusivity: Mixture Average [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Mixture_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Linear mixture-averaged mass diffusivity

4.1.726. Mixture Molecular Weight

Scope: Aria Material

Mixture Molecular Weight [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Mmix = *Mmix*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>Mmix</i>	real	undefined

Summary Constant value

4.1.727. Mixture Molecular Weight: Copied

Scope: Aria Material

Mixture Molecular Weight: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.728. Mixture Molecular Weight: User Plugin

Scope: Aria Material

Mixture Molecular Weight: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |*magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.729. Mixture Molecular Weight: Scalar String Function

Scope: Aria Material

Mixture Molecular Weight: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [*F* = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.730. Mixture Molecular Weight: Cantera

Scope: Aria Material

Mixture Molecular Weight: Cantera [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Cantera [*Poffset* = *poffset*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>poffset</i>	real	undefined

Summary Cantera mixture molecular weight

4.1.731. Mixture Molecular Weight: Mass Average

Scope: Aria Material

Mixture Molecular Weight: Mass Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mass_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Mass averaged mixture molecular weight

4.1.732. Mixture Molecular Weight: Mole Average

Scope: Aria Material

Mixture Molecular Weight: Mole Average [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Mole_Average [Species_Variable = *species_variable*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>species_variable</i>	"string"	undefined

Summary Mole averaged mixture molecular weight

4.1.733. Molecular Weight

Scope: Aria Material

Molecular Weight [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value* | M = *m*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>m</i>	real	undefined

Summary Constant value

4.1.734. Molecular Weight: Copied

Scope: Aria Material

Molecular Weight: Copied [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.735. Molecular Weight: User Plugin

Scope: Aria Material

Molecular Weight: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.736. Molecular Weight: Scalar String Function

Scope: Aria Material

Molecular Weight: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.737. Molecular Weight: Cantera

Scope: Aria Material

Molecular Weight: Cantera [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Cantera [Poffset = *poffset*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>poffset</i>	real	undefined

Summary Cantera molecular weight

4.1.738. Molecular Weight: Dynamic Species

Scope: Aria Material

Molecular Weight: Dynamic Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Dynamic_Species []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Calculate the molecular weight dynamically from density/molar concentration.

4.1.739. Momentum Face Stabilization Scaling: Default

Scope: Aria Material

Momentum Face Stabilization Scaling: Default [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Default []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Default face stabilization scaling for momentum equation

4.1.740. Momentum Stress: Bad Sensitivity

Scope: Aria Material

Momentum Stress: Bad Sensitivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Bad_Sensitivity []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.741. Momentum Stress: Balanced Force

Scope: Aria Material

Momentum Stress: Balanced Force [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Balanced_Force []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.742. Momentum Stress: Grad Div

Scope: Aria Material

Momentum Stress: Grad Div [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Grad_Div [Pressure = *pressure* |Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>pressure</i>	"string"	undefined
<i>multiplier</i>	real	undefined

4.1.743. Momentum Stress: Formal Newtonian

Scope: Aria Material

Momentum Stress: Formal Newtonian [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Formal_Newtonian [Pressure = *pressure* |Phase = *phase* |Biot = *biot* |Reference_Frame = *reference_frame*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>pressure</i>	"string"	undefined
<i>phase</i>	"string"	undefined
<i>biot</i>	real	undefined
<i>reference_frame</i>	"string"	undefined

4.1.744. Momentum Stress: Incompressible Newtonian

Scope: Aria Material

Momentum Stress: Incompressible Newtonian [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Incompressible_Newtonian [Pressure = *pressure* |Phase = *phase* |Biot = *biot* |Reference_Frame = *reference_frame*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>pressure</i>	"string"	undefined
<i>phase</i>	"string"	undefined
<i>biot</i>	real	undefined
<i>reference_frame</i>	"string"	undefined

4.1.745. Momentum Stress: Suspension

Scope: Aria Material

Momentum Stress: Suspension [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Suspension [Pressure = *pressure* |Phase = *phase* |Biot = *biot* |Reference_Frame = *reference_frame*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>pressure</i>	"string"	undefined
<i>phase</i>	"string"	undefined
<i>biot</i>	real	undefined
<i>reference_frame</i>	"string"	undefined

4.1.746. Momentum Stress: Ls Capillary

Scope: Aria Material

Momentum Stress: Ls Capillary [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Ls_Capillary []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.747. Momentum Stress: Ls Implicit Capillary

Scope: Aria Material

Momentum Stress: Ls Implicit Capillary [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Ls_Implicit_Capillary []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.748. Momentum Stress: Ls Implicit Normal Capillary

Scope: Aria Material

Momentum Stress: Ls Implicit Normal Capillary [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Ls_Implicit_Normal_Capillary [Mu0 = *mu0*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>muo</i>	real	undefined

4.1.749. Momentum Stress: Newtonian Dilational

Scope: Aria Material

Momentum Stress: Newtonian Dilational [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Newtonian_Dilational [Reference_Frame = *reference_frame*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>reference_frame</i>	"string"	undefined

4.1.750. Momentum Stress: Newtonian Viscous

Scope: Aria Material

Momentum Stress: Newtonian Viscous [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Newtonian_Viscous [Reference_Frame = *reference_frame*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>reference_frame</i>	"string"	undefined

4.1.751. Momentum Stress: Newtonian Pressure

Scope: Aria Material

Momentum Stress: Newtonian Pressure [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Newtonian_Pressure [Pressure = *pressure* | Phase = *phase* | Biot = *biot*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>pressure</i>	"string"	undefined
<i>phase</i>	"string"	undefined
<i>biot</i>	real	undefined

4.1.752. Momentum Stress: Maxwell

Scope: Aria Material

Momentum Stress: Maxwell [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Maxwell []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary The gradient of the Maxwell stress tensor is the force on a fluid due to an electrical field and is non-zero when there is either a net charge density or a non-uniform electric permittivity. $\nabla \cdot \mathbf{M} = \rho_{charge} \mathbf{E} - \frac{1}{2}(\mathbf{E} \cdot \mathbf{E}) \nabla \epsilon$

4.1.753. Momentum Stress: Mckenzie

Scope: Aria Material

Momentum Stress: Mckenzie [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mckenzie [Pressure = *pressure* |Phase = *phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>pressure</i>	"string"	undefined
<i>phase</i>	"string"	undefined

Summary Provides a stress tensor based on a spherical and deviatoric decomposition. The pressure is derived from the pressure of the gas phase and the divergence of the flow field. The deviatoric stress is linear in the deviatoric velocity gradient. $\sigma = (1. - \phi)((P_g - \beta \nabla \cdot v)I + \frac{\mu}{2}(\nabla v + \nabla v^T - \frac{2}{3} \nabla \cdot v))$

4.1.754. Momentum Stress: Lorentz

Scope: Aria Material

Momentum Stress: Lorentz [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Lorentz []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.755. Neutron

Scope: Aria Material

Neutron [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.756. Neutron: Copied

Scope: Aria Material

Neutron: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.757. Neutron: User Plugin

Scope: Aria Material

Neutron: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.758. Neutron: Scalar String Function

Scope: Aria Material

Neutron: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.759. Neutron Diffusion: Ficks Law

Scope: Aria Material

Neutron Diffusion: Ficks Law [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Ficks_Law []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Fick's Law neutron diffusion

4.1.760. Neutron Diffusion: Basic

Scope: Aria Material

Neutron Diffusion: Basic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Basic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Basic neutron diffusion

4.1.761. Neutron Diffusivity

Scope: Aria Material

Neutron Diffusivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |D = *d*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>d</i>	real	undefined

Summary Constant value

4.1.762. Neutron Diffusivity: Copied

Scope: Aria Material

Neutron Diffusivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.763. Neutron Diffusivity: User Plugin

Scope: Aria Material

Neutron Diffusivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.764. Neutron Diffusivity: Scalar String Function

Scope: Aria Material

Neutron Diffusivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.765. Neutron Diffusivity: Five Ten

Scope: Aria Material

Neutron Diffusivity: Five Ten [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Five_Ten []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Five ten neutron diffusivity

4.1.766. Nonwetting Phase Retardation

Scope: Aria Material

Nonwetting Phase Retardation [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |R = *r*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>r</i>	real	undefined

Summary Constant value

4.1.767. Nonwetting Phase Retardation: Copied

Scope: Aria Material

Nonwetting Phase Retardation: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.768. Nonwetting Phase Retardation: User Plugin

Scope: Aria Material

Nonwetting Phase Retardation: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.769. Nonwetting Phase Retardation: Scalar String Function

Scope: Aria Material

Nonwetting Phase Retardation: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.770. Open Circuit Voltage

Scope: Aria Material

Open Circuit Voltage [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [$V_x = vx$ | $V_y = vy$ | $V_z = vz$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>vx</i>	real	undefined
<i>vy</i>	real	undefined
<i>vz</i>	real	undefined

Summary Constant value

4.1.771. Open Circuit Voltage: User Plugin

Scope: Aria Material

Open Circuit Voltage: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.772. Open Circuit Voltage: Vector String Function

Scope: Aria Material

Open Circuit Voltage: Vector String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Vector_String_Function [$F_X = f_x$ | $F_Y = f_y$ | $F_Z = f_z$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

4.1.773. Open Circuit Voltage: Electrode Object

Scope: Aria Material

Open Circuit Voltage: Electrode Object [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Electrode_Object [Electrodefile = *electrodeFile* | Initialactivevolumefrac = *initialActiveVolumeFrac* | F = *f* | Kmolconversion = *kmolConversion* | Jconversion = *JConversion* | Meterconversion = *meterConversion* | Deactivationvoltage = *deactivationVoltage* | Voltagevariablename = *voltageVariableName* | Abortaction = *abortAction* | Pref = *Pref* | Sens_Eps = *Sens_eps* | Sens_Order = *Sens_order*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>electrodeFile</i>	"string"	undefined
<i>initialActiveVolumeFrac</i>	real	undefined
<i>f</i>	real	undefined
<i>kmolConversion</i>	real	undefined
<i>JConversion</i>	real	undefined
<i>meterConversion</i>	real	undefined
<i>deactivationVoltage</i>	real	undefined
<i>voltageVariableName</i>	"string"	undefined
<i>abortAction</i>	"string"	undefined
<i>Pref</i>	real	undefined
<i>Sens_eps</i>	real	undefined
<i>Sens_order</i>	"string"	undefined

Summary Open circuit voltage from the electrode

4.1.774. Partial Enclosure Area

Scope: Aria Material

Partial Enclosure Area [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value* | A = *a*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>a</i>	real	undefined

Summary Constant value

4.1.775. Partial Enclosure Area: Copied

Scope: Aria Material

Partial Enclosure Area: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.776. Partial Enclosure Area: User Plugin

Scope: Aria Material

Partial Enclosure Area: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.777. Partial Enclosure Area: Scalar String Function

Scope: Aria Material

Partial Enclosure Area: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F =
f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.778. Partial Enclosure Area: Calore User Sub

Scope: Aria Material

Partial Enclosure Area: Calore User Sub [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

4.1.779. Partial Enclosure Emissivity

Scope: Aria Material

Partial Enclosure Emissivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |E = *e*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>e</i>	real	undefined

Summary Constant value

4.1.780. Partial Enclosure Emissivity: Copied

Scope: Aria Material

Partial Enclosure Emissivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.781. Partial Enclosure Emissivity: User Plugin

Scope: Aria Material

Partial Enclosure Emissivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.782. Partial Enclosure Emissivity: Scalar String Function

Scope: Aria Material

Partial Enclosure Emissivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.783. Partial Enclosure Emissivity: Calore User Sub

Scope: Aria Material

Partial Enclosure Emissivity: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

4.1.784. Partial Enclosure Temperature

Scope: Aria Material

Partial Enclosure Temperature [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |T = *t*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>t</i>	real	undefined

Summary Constant value

4.1.785. Partial Enclosure Temperature: Copied

Scope: Aria Material

Partial Enclosure Temperature: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.786. Partial Enclosure Temperature: User Plugin

Scope: Aria Material

Partial Enclosure Temperature: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.787. Partial Enclosure Temperature: Scalar String Function

Scope: Aria Material

Partial Enclosure Temperature: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.788. Partial Enclosure Temperature: Calore User Sub

Scope: Aria Material

Partial Enclosure Temperature: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

4.1.789. Partial Molar Volume

Scope: Aria Material

Partial Molar Volume [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.790. Partial Molar Volume: Copied

Scope: Aria Material

Partial Molar Volume: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.791. Partial Molar Volume: User Plugin

Scope: Aria Material

Partial Molar Volume: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.792. Partial Molar Volume: Scalar String Function

Scope: Aria Material

Partial Molar Volume: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.793. Peltier Coefficient

Scope: Aria Material

Peltier Coefficient [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.794. Peltier Coefficient: Copied

Scope: Aria Material

Peltier Coefficient: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.795. Peltier Coefficient: User Plugin

Scope: Aria Material

Peltier Coefficient: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.796. Peltier Coefficient: Scalar String Function

Scope: Aria Material

Peltier Coefficient: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.797. Phase Change Specific Heat

Scope: Aria Material

Phase Change Specific Heat [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Cp = *Cp*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>Cp</i>	real	undefined

Summary Constant value

4.1.798. Phase Change Specific Heat: Scalar String Function

Scope: Aria Material

Phase Change Specific Heat: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.799. Phase Change Specific Heat: Calore User Sub

Scope: Aria Material

Phase Change Specific Heat: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutineValues from a Calore user subroutine

4.1.800. Phase Change Specific Heat: Curing Foam

Scope: Aria Material

Phase Change Specific Heat: Curing Foam [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Curing_Foam []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Phase change specific heat for a curing foamPhase change specific heat for a curing foam

4.1.801. Phi

Scope: Aria Material

Phi [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.802. Phi: Copied

Scope: Aria Material

Phi: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.803. Phi: User Plugin

Scope: Aria Material

Phi: User Plugin [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.804. Phi: Scalar String Function

Scope: Aria Material

Phi: Scalar String Function [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.805. Plastic Strain

Scope: Aria Material

Plastic Strain [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.806. Plastic Strain: Copied

Scope: Aria Material

Plastic Strain: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.807. Plastic Strain: User Plugin

Scope: Aria Material

Plastic Strain: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.808. Plastic Strain: Scalar String Function

Scope: Aria Material

Plastic Strain: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.809. Polymerization Shift Factor

Scope: Aria Material

Polymerization Shift Factor [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.810. Polymerization Shift Factor: Copied

Scope: Aria Material

Polymerization Shift Factor: Copied [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.811. Polymerization Shift Factor: User Plugin

Scope: Aria Material

Polymerization Shift Factor: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.812. Polymerization Shift Factor: Scalar String Function

Scope: Aria Material

Polymerization Shift Factor: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.813. Polymerization Shift Factor: Wlf

Scope: Aria Material

Polymerization Shift Factor: Wlf [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Wlf [C1 = *c1* |C2 = *c2*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>c1</i>	real	undefined
<i>c2</i>	real	undefined

4.1.814. Porosity

Scope: Aria Material

Porosity [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |Phi = *phi*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>phi</i>	real	undefined

Summary Constant value

4.1.815. Porosity: Deforming

Scope: Aria Material

Porosity: Deforming [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Deforming [Phi_Init = *phi_init*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>phi_init</i>	real	undefined

Summary This model has been deprecated

4.1.816. Porosity: Mesh Deforming

Scope: Aria Material

Porosity: Mesh Deforming [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Mesh_Deforming [Biot = *biot*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>biot</i>	real	undefined

Summary Rock compressibility linearized model of porosity for deforming media

4.1.817. Porosity: Solid Deforming

Scope: Aria Material

Porosity: Solid Deforming [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Solid_Deforming [Biot = *biot*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>biot</i>	real	undefined

Summary Rock compressibility linearized model of porosity for deforming media

4.1.818. Porosity: Rock Compressible

Scope: Aria Material

Porosity: Rock Compressible [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Rock_Compressible [Cr = *cr* |Ref_Porosity = *ref_porosity* |Ref_Pressure = *ref_pressure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>cr</i>	real	undefined
<i>ref_porosity</i>	real	undefined
<i>ref_pressure</i>	real	undefined

Summary Rock compressibility linearized model of porosity

4.1.819. Porosity: Deformable Rock Compressible

Scope: Aria Material

Porosity: Deformable Rock Compressible [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Deformable_Rock_Compressible [Cr = *cr* |Ref_Porosity = *ref_porosity* |Ref_Pressure = *ref_pressure* |Biot = *biot*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>cr</i>	real	undefined
<i>ref_porosity</i>	real	undefined
<i>ref_pressure</i>	real	undefined
<i>biot</i>	real	undefined

Summary Rock compressibility linearized model of porosity for deforming media

4.1.820. Porosity: Coussy

Scope: Aria Material

Porosity: Coussy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Coussy [M_Inv = *m_inv* |Biot = *biot* |Ref_Porosity = *ref_porosity* |Ref_Pressure = *ref_pressure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>m_inv</i>	real	undefined
<i>biot</i>	real	undefined
<i>ref_porosity</i>	real	undefined
<i>ref_pressure</i>	real	undefined

Summary Coussy's model of porosity for deforming media (based on pore pressure and $\text{div}(\mathbf{u})$)

4.1.821. Porosity: From Density Ratio

Scope: Aria Material

Porosity: From Density Ratio [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Density_Ratio [Solid_Density = *solid_density*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>solid_density</i>	real	undefined

Summary Porosity computed as one minus the density ratio between solved for solid-phase density and solid density of non-porous material.

4.1.822. Porosity: One Minus Volume Fractions

Scope: Aria Material

Porosity: One Minus Volume Fractions [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= One_Minus_Volume_Fractions [Phi_Min = *phi_min*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>phi_min</i>	real	undefined

Summary Porosity computed directly from volume fractions of species.

4.1.823. Porosity: Constant From Electrode Object Old

Scope: Aria Material

Porosity: Constant From Electrode Object Old [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Constant_From_Electrode_Object_Old [Electrodefile = *electrodeFile*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>electrodeFile</i>	"string"	undefined

Summary This model has been deprecated and removed from the code.

4.1.824. Porosity: From Volume Fraction Gas

Scope: Aria Material

Porosity: From Volume Fraction Gas [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Volume_Fraction_Gas []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Porosity from the defined volume fraction of gas

4.1.825. Porosity: Modified Kozeny

Scope: Aria Material

Porosity: Modified Kozeny [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Modified_Kozeny [C = *c* |B1 = *b1* |B2 = *b2* |L_Bed = *L_bed* |R_Bed = *R_bed* |Nx = *nx*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>c</i>	real	undefined
<i>b1</i>	real	undefined
<i>b2</i>	real	undefined
<i>L_bed</i>	real	undefined
<i>R_bed</i>	real	undefined
<i>nx</i>	real	undefined

Summary Porosity of a cylindrical particle bed of domain of length L and radius R using experimental model parameters $c, b1, b2$ and nx . For 2D $r = x$ and 3D $r = \sqrt{x^2 + z^2}$ with $\bar{r} = r/R$, $\bar{F}1 = 1 - (1 - b1)/2$, $\bar{F}2 = b2 + (1 - b2)/2$, $F1 = 1 - (1 - b1)y/L$, $F2 = b2 + (1 - b2)(1 - \bar{r}^{nx})$, then the porosity $\phi = cF1F2/\bar{F}1\bar{F}2$.

4.1.826. Porosity: Scalar String Function

Scope: Aria Material

Porosity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Variable porosity defined by a scalar string function.

4.1.827. Porosity Def

Scope: Aria Material

Porosity Def [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Phi = *phi*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>phi</i>	real	undefined

Summary Constant value

4.1.828. Porosity Def: Copied

Scope: Aria Material

Porosity Def: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.829. Porosity Def: User Plugin

Scope: Aria Material

Porosity Def: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.830. Porosity Def: Scalar String Function

Scope: Aria Material

Porosity Def: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.831. Porosity Def: Deforming

Scope: Aria Material

Porosity Def: Deforming [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Deforming []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Deforming model for porosity def

4.1.832. Porous Flow System: Single Phase

Scope: Aria Material

Porous Flow System: Single Phase [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Single_Phase [Gx = *gx* |Gy = *gy* |Gz = *gz*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>gx</i>	real	undefined
<i>gy</i>	real	undefined
<i>gz</i>	real	undefined

4.1.833. Porous Flow System: Mixed Single Phase

Scope: Aria Material

Porous Flow System: Mixed Single Phase [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mixed_Single_Phase [Gx = *gx* |Gy = *gy* |Gz = *gz*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>gx</i>	real	undefined
<i>gy</i>	real	undefined
<i>gz</i>	real	undefined

4.1.834. Porous Flow System: Two Phase Immiscible

Scope: Aria Material

Porous Flow System: Two Phase Immiscible [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Two_Phase_Immiscible [Gx = *gx* |Gy = *gy* |Gz = *gz* |Relative_To = *relative_to*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>gx</i>	real	undefined
<i>gy</i>	real	undefined
<i>gz</i>	real	undefined
<i>relative_to</i>	"string"	undefined

4.1.835. Porous Flow System: Air Water

Scope: Aria Material

Porous Flow System: Air Water [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Air_Water [Gx = *gx* |Gy = *gy* |Gz = *gz* |Relative_To = *relative_to*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>gx</i>	real	undefined
<i>gy</i>	real	undefined
<i>gz</i>	real	undefined
<i>relative_to</i>	"string"	undefined

4.1.836. Porous Flow System: Co2 Brine Salt

Scope: Aria Material

Porous Flow System: Co2 Brine Salt [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Co2_Brine_Salt [X_Sat_Co2_File_Name = *x_sat_co2_file_name* |Rho_G_File_Name = *rho_g_file_name* |Rho_Co2_File_Name = *rho_co2_file_name* |Gx = *gx* |Gy = *gy* |Gz = *gz* |Relative_To = *relative_to*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>x_sat_co2_file_name</i>	"string"	undefined
<i>rho_g_file_name</i>	"string"	undefined
<i>rho_co2_file_name</i>	"string"	undefined
<i>gx</i>	real	undefined
<i>gy</i>	real	undefined
<i>gz</i>	real	undefined
<i>relative_to</i>	"string"	undefined

4.1.837. Potential

Scope: Aria Material

Potential [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.838. Potential: Copied

Scope: Aria Material

Potential: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.839. Potential: User Plugin

Scope: Aria Material

Potential: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.840. Potential: Scalar String Function

Scope: Aria Material

Potential: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.841. Pp: Mesh Von Mises

Scope: Aria Material

Pp: Mesh Von Mises [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Mesh_Von_Mises []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Mesh Von Mises model

4.1.842. Pp: Solid Von Mises

Scope: Aria Material

Pp: Solid Von Mises [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Solid_Von_Mises []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Solid Von Mises model

4.1.843. Pp: Fluid Traction

Scope: Aria Material

Pp: Fluid Traction [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Fluid_Traction []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Fluid Traction model

4.1.844. Pp: Viscous Traction

Scope: Aria Material

Pp: Viscous Traction [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Viscous_Traction []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Viscous Traction model - like Surface_Traction but omits the pressure contribution

4.1.845. Pp: Mesh Traction

Scope: Aria Material

Pp: Mesh Traction [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Mesh_Traction []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Mesh Traction model

4.1.846. Pp: Solid Traction

Scope: Aria Material

Pp: Solid Traction [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Solid_Traction []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Solid Traction model

4.1.847. Pp: Cvfem Yplus

Scope: Aria Material

Pp: Cvfem Yplus [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Cvfem_Yplus []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Cvfem YPLUS model

4.1.848. Pp: Yplus

Scope: Aria Material

Pp: Yplus [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Yplus [Scale_Factor = *scale_factor*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>scale_factor</i>	real	undefined

Summary YPLUS model

4.1.849. Pp: Turbulent Kinetic Energy Source

Scope: Aria Material

Pp: Turbulent Kinetic Energy Source [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Turbulent_Kinetic_Energy_Source []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.850. Pp: Surface Normal Shell

Scope: Aria Material

Pp: Surface Normal Shell [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Surface_Normal_Shell []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.851. Pp: Vector Mean Curvature

Scope: Aria Material

Pp: Vector Mean Curvature [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Vector_Mean_Curvature []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.852. Prandtl Number

Scope: Aria Material

Prandtl Number [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Pr = *Pr*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>Pr</i>	real	undefined

Summary Constant value

4.1.853. Prandtl Number: Copied

Scope: Aria Material

Prandtl Number: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.854. Prandtl Number: User Plugin

Scope: Aria Material

Prandtl Number: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.855. Prandtl Number: Scalar String Function

Scope: Aria Material

Prandtl Number: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.856. Prandtl Number: General

Scope: Aria Material

Prandtl Number: General [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= General []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary General Prandtl number computed from material properties

4.1.857. Prandtl Number: Correlation

Scope: Aria Material

Prandtl Number: Correlation [{of|species|subindex} *Species*]=
Correlation [Pr = *Pr* |Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>Pr</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation Prandtl number computed from material properties

4.1.858. Precursor Concentration

Scope: Aria Material

Precursor Concentration [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.859. Precursor Concentration: Copied

Scope: Aria Material

Precursor Concentration: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.860. Precursor Concentration: User Plugin

Scope: Aria Material

Precursor Concentration: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.861. Precursor Concentration: Scalar String Function

Scope: Aria Material

Precursor Concentration: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.862. Precursor Conservation

Scope: Aria Material

Precursor Conservation [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.863. Precursor Conservation: Copied

Scope: Aria Material

Precursor Conservation: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.864. Precursor Conservation: User Plugin

Scope: Aria Material

Precursor Conservation: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.865. Precursor Conservation: Scalar String Function

Scope: Aria Material

Precursor Conservation: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.866. Pressure

Scope: Aria Material

Pressure [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.867. Pressure: Copied

Scope: Aria Material

Pressure: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.868. Pressure: User Plugin

Scope: Aria Material

Pressure: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.869. Pressure: Scalar String Function

Scope: Aria Material

Pressure: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.870. Pressure: Copy Phase All

Scope: Aria Material

Pressure: Copy Phase All [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copy_Phase_All []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Copy the overall multi-phase pressure to the individual phase.

4.1.871. Pressure: From No Material Phase

Scope: Aria Material

Pressure: From No Material Phase [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_No_Material_Phase []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Copy the overall pressure to the material phase (i.e. gas phase or solid phase).

4.1.872. Pressure: From Other Material Phase

Scope: Aria Material

Pressure: From Other Material Phase [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Other_Material_Phase [Other_Phase = *other_phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>other_phase</i>	"string"	undefined

Summary Copy the overall pressure from a different phase (i.e. gas phase or solid phase).

4.1.873. Pressure: Pressurization Model

Scope: Aria Material

Pressure: Pressurization Model [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Pressurization_Model []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Pressure from a pressurization model

4.1.874. Pressure: Ideal Gas

Scope: Aria Material

Pressure: Ideal Gas [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Ideal_Gas [$R = r$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>r</i>	real	undefined

Summary Calculate the pressure based on the ideal gas law

4.1.875. Pressure: Equation Of State

Scope: Aria Material

Pressure: Equation Of State [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Equation_Of_State [Model_Name = *model_name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>model_name</i>	"string"	undefined

Summary Pressure calculated based on species, temperature, and equation of state for the specified pressurization model.

4.1.876. Pressure: From Ideal Gas Density

Scope: Aria Material

Pressure: From Ideal Gas Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Ideal_Gas_Density [Mw = *mw* | R = *r*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>mw</i>	real	undefined
<i>r</i>	real	undefined

Summary Calculate pressure using the density and ideal gas law.

4.1.877. Pressure: From Capillary Pressure

Scope: Aria Material

Pressure: From Capillary Pressure [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Capillary_Pressure []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Compute the liquid phase pressure = Pgas - Pcapillary

4.1.878. Projected Level Set Curvature

Scope: Aria Material

Projected Level Set Curvature [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.879. Projected Level Set Curvature: Copied

Scope: Aria Material

Projected Level Set Curvature: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.880. Projected Level Set Curvature: User Plugin

Scope: Aria Material

Projected Level Set Curvature: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.881. Projected Level Set Curvature: Scalar String Function

Scope: Aria Material

Projected Level Set Curvature: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.882. Projected Pressure Gradient

Scope: Aria Material

Projected Pressure Gradient [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [$\text{Value}_x = \text{value}_X$ | $\text{Value}_y = \text{value}_Y$ | $\text{Value}_z = \text{value}_Z$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>valueX</i>	real	undefined
<i>valueY</i>	real	undefined
<i>valueZ</i>	real	undefined

Summary Constant value

4.1.883. Projected Pressure Gradient: User Plugin

Scope: Aria Material

Projected Pressure Gradient: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.884. Projected Pressure Gradient: Vector String Function

Scope: Aria Material

Projected Pressure Gradient: Vector String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Vector_String_Function [F_X = f_x |F_Y = f_y |F_Z = f_z]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f_x	"string"	undefined
f_y	"string"	undefined
f_z	"string"	undefined

Summary Value from a string function

4.1.885. Projected Pressure Stab Tau

Scope: Aria Material

Projected Pressure Stab Tau [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.886. Projected Pressure Stab Tau: Copied

Scope: Aria Material

Projected Pressure Stab Tau: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.887. Projected Pressure Stab Tau: User Plugin

Scope: Aria Material

Projected Pressure Stab Tau: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.888. Projected Pressure Stab Tau: Scalar String Function

Scope: Aria Material

Projected Pressure Stab Tau: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.889. Radiation Form Factor

Scope: Aria Material

Radiation Form Factor [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* | F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>f</i>	real	undefined

Summary Constant value

4.1.890. Radiation Form Factor: Copied

Scope: Aria Material

Radiation Form Factor: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.891. Radiation Form Factor: User Plugin

Scope: Aria Material

Radiation Form Factor: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.892. Radiation Form Factor: Scalar String Function

Scope: Aria Material

Radiation Form Factor: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.893. Radiation Form Factor: Calore User Sub

Scope: Aria Material

Radiation Form Factor: Calore User Sub [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* | Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

4.1.894. Radiation Form Factor: Fortran

Scope: Aria Material

Radiation Form Factor: Fortran [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Fortran [Multiplier = *multiplier* | Sub_Name = *sub_name* |Real_Data = *real_data* |Int_Data = *int_data* | Resource_Name = *resource_name* |Data = *data*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>sub_name</i>	"string"	undefined
<i>real_data</i>	"string"	undefined
<i>int_data</i>	"string"	undefined
<i>resource_name</i>	"string"	undefined
<i>data</i>	"string"	undefined

Summary Fortran subroutine emissivity.

4.1.895. Radiative Conductivity

Scope: Aria Material

Radiative Conductivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Krad = *Krad*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>Krad</i>	real	undefined

Summary Constant value

4.1.896. Radiative Conductivity: Copied

Scope: Aria Material

Radiative Conductivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.897. Radiative Conductivity: User Plugin

Scope: Aria Material

Radiative Conductivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.898. Radiative Conductivity: Scalar String Function

Scope: Aria Material

Radiative Conductivity: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f	"string"	undefined

Summary Value from a string function

4.1.899. Radiative Conductivity: Optically Thick

Scope: Aria Material

Radiative Conductivity: Optically Thick [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Optically_Thick [Beta_R = β_r | $N = n$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
β_r	real	undefined
n	real	undefined

Summary Radiation conductivity for optically thick materials

4.1.900. Radiative Conductivity: Volume Average

Scope: Aria Material

Radiative Conductivity: Volume Average [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Volume_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Radiation conductivity computed from normalized volume average of species radiation conductivities

4.1.901. Radiative Conductivity: Chemeq Foam

Scope: Aria Material

Radiative Conductivity: Chemeq Foam [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Chemeq_Foam [Kc0 = *Kc0* |Kc1 = *Kc1*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Kc0</i>	real	undefined
<i>Kc1</i>	real	undefined

Summary Radiation conductivity for ChemEq foams, adjusting for the mass fraction of solids in the foam

4.1.902. Reaction Rate Multiplier

Scope: Aria Material

Reaction Rate Multiplier [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.903. Reaction Rate Multiplier: Copied

Scope: Aria Material

Reaction Rate Multiplier: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.904. Reaction Rate Multiplier: User Plugin

Scope: Aria Material

Reaction Rate Multiplier: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.905. Reaction Rate Multiplier: Scalar String Function

Scope: Aria Material

Reaction Rate Multiplier: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.906. Reaction Rate Multiplier: One Minus Gas Volume Fraction

Scope: Aria Material

Reaction Rate Multiplier: One Minus Gas Volume Fraction [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= One_Minus_Gas_Volume_Fraction []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Compute a multiplier that is one minus the gas volume fractions

4.1.907. Reaction Rate Multiplier: Vitrification

Scope: Aria Material

Reaction Rate Multiplier: Vitrification [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Vitrification [W = *w* |Beta = *beta*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>w</i>	real	undefined
<i>beta</i>	real	undefined

Summary Compute vitrification rate multiplier from polymerization shift factor

4.1.908. Reaction Rate Multiplier: Electrode Object

Scope: Aria Material

Reaction Rate Multiplier: Electrode Object [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Electrode_Object [Electrodefile = *electrodeFile* |Initialactivevolumefrac = *initialActiveVolumeFrac* |F = *f* |Kmolconversion = *kmolConversion* |Jconversion = *JConversion* |Meterconversion = *meterConversion* |Deactivationvoltage = *deactivationVoltage* |Voltagevariablename = *voltageVariableName* |Abortaction = *abortAction* |Pref = *Pref* |Sens_Eps = *Sens_eps* |Sens_Order = *Sens_order*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>electrodeFile</i>	"string"	undefined
<i>initialActiveVolumeFrac</i>	real	undefined
<i>f</i>	real	undefined
<i>kmolConversion</i>	real	undefined
<i>JConversion</i>	real	undefined
<i>meterConversion</i>	real	undefined
<i>deactivationVoltage</i>	real	undefined
<i>voltageVariableName</i>	"string"	undefined
<i>abortAction</i>	"string"	undefined
<i>Pref</i>	real	undefined
<i>Sens_eps</i>	real	undefined
<i>Sens_order</i>	"string"	undefined

Summary Rate multiplier based on melting of the electrolyte and global deactivation of the electrodes

4.1.909. Relative Permeability

Scope: Aria Material

Relative Permeability [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |K = *k*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>k</i>	real	undefined

Summary Constant value

4.1.910. Relative Permeability: Copied

Scope: Aria Material

Relative Permeability: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.911. Relative Permeability: User Plugin

Scope: Aria Material

Relative Permeability: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.912. Relative Permeability: Scalar String Function

Scope: Aria Material

Relative Permeability: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f	"string"	undefined

Summary Value from a string function

4.1.913. Relative Permeability: T Exponent

Scope: Aria Material

Relative Permeability: T Exponent [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= T_Exponent [$K_{Ref} = k_{ref}$ | $T_{Ref} = t_{ref}$ | $N = n$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
k_{ref}	real	undefined
t_{ref}	real	undefined
n	real	undefined

Summary Relative permeability as a power of normalized temperature

4.1.914. Relative Permeability: Volume Average

Scope: Aria Material

Relative Permeability: Volume Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Volume_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Relative permeability computed from volume average of species relative permeabilities

4.1.915. Relative Permeability: Mass Average

Scope: Aria Material

Relative Permeability: Mass Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mass_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Linear mixture-averaged mass diffusivity

4.1.916. Relative Permeability: Van Genuchten Gas

Scope: Aria Material

Relative Permeability: Van Genuchten Gas [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Van_Genuchten_Gas [Liquid_Phase_Name = *liquid_phase_name* |Beta_Field = *beta_field* |Sgr_Field = *sgr_field* |Slr_Field = *slr_field* |Beta = *beta* |Residual_Liquid_Phase_Saturation = *residual_liquid_phase_saturation* |Residual_Gas_Phase_Saturation = *residual_gas_phase_saturation*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>liquid_phase_name</i>	"string"	undefined
<i>beta_field</i>	"string"	undefined
<i>sgr_field</i>	"string"	undefined
<i>slr_field</i>	"string"	undefined
<i>beta</i>	real	undefined
<i>residual_liquid_phase_saturation</i>	real	undefined
<i>residual_gas_phase_saturation</i>	real	undefined

Summary A Van Genuchten gas model for relative permeability

4.1.917. Relative Permeability: Udell Cubic Gas

Scope: Aria Material

Relative Permeability: Udell Cubic Gas [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Udell_Cubic_Gas [Liquid_Phase_Name = *liquid_phase_name* |Residual_Liquid_Phase_Saturation = *residual_liquid_phase_saturation* |Residual_Gas_Phase_Saturation = *residual_gas_phase_saturation*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>liquid_phase_name</i>	"string"	undefined
<i>residual_liquid_phase_saturation</i>	real	undefined
<i>residual_gas_phase_saturation</i>	real	undefined

Summary A UdeLL cubic gas model for relative permeability

4.1.918. Relative Permeability: Van Genuchten Liquid

Scope: Aria Material

```
Relative Permeability: Van Genuchten Liquid [ {of|species|subindex}
Species |{in|material_phase} MaterialPhase ]= Van_Genuchten_Liquid [
Liquid_Phase_Name = liquid_phase_name |Beta_Field = beta_field |Sgr_Field
= sgr_field |Slr_Field = slr_field |Beta = beta |
Residual_Liquid_Phase_Saturation = residual_liquid_phase_saturation |
Residual_Gas_Phase_Saturation = residual_gas_phase_saturation ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>liquid_phase_name</i>	"string"	undefined
<i>beta_field</i>	"string"	undefined
<i>sgr_field</i>	"string"	undefined
<i>slr_field</i>	"string"	undefined
<i>beta</i>	real	undefined
<i>residual_liquid_phase_saturation</i>	real	undefined
<i>residual_gas_phase_saturation</i>	real	undefined

Summary A Van Genuchten liquid model for relative permeability

4.1.919. Relative Permeability: UdeLL Cubic Liquid

Scope: Aria Material

```
Relative Permeability: UdeLL Cubic Liquid [ {of|species|subindex} Species
|{in|material_phase} MaterialPhase ]= UdeLL_Cubic_Liquid [
Liquid_Phase_Name = liquid_phase_name |Residual_Liquid_Phase_Saturation =
residual_liquid_phase_saturation |Residual_Gas_Phase_Saturation =
residual_gas_phase_saturation ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>liquid_phase_name</i>	"string"	undefined
<i>residual_liquid_phase_saturation</i>	real	undefined
<i>residual_gas_phase_saturation</i>	real	undefined

Summary A Udel cubic liquid model for relative permeability

4.1.920. Relative Permeability: Brooks Corey

Scope: Aria Material

Relative Permeability: Brooks Corey [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Brooks_Corey [Liquid_Phase_Name = *liquid_phase_name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>liquid_phase_name</i>	"string"	undefined

Summary A Brooks-Corey liquid/gas model for relative permeability

4.1.921. Reservoir Depth

Scope: Aria Material

Reservoir Depth [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |H = *h*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>h</i>	real	undefined

Summary Constant value

4.1.922. Reservoir Depth: Copied

Scope: Aria Material

Reservoir Depth: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.923. Reservoir Depth: User Plugin

Scope: Aria Material

Reservoir Depth: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.924. Reservoir Depth: Scalar String Function

Scope: Aria Material

Reservoir Depth: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.925. Residual Saturation

Scope: Aria Material

Residual Saturation [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.926. Residual Saturation: Copied

Scope: Aria Material

Residual Saturation: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.927. Residual Saturation: User Plugin

Scope: Aria Material

Residual Saturation: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.928. Residual Saturation: Scalar String Function

Scope: Aria Material

Residual Saturation: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.929. Retardation: Saturated Distributed

Scope: Aria Material

Retardation: Saturated Distributed [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Saturated_Distributed []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary This model has been deprecated and removed from the code.

4.1.930. Retardation: Gas Phase Distributed

Scope: Aria Material

Retardation: Gas Phase Distributed [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Gas_Phase_Distributed []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Distributed retardation factor for gas phase in porous flow. The corresponding distribution coefficient should be defined with a DISTRIBUTION COEFFICIENT model.

4.1.931. Retardation: Liquid Phase Distributed

Scope: Aria Material

Retardation: Liquid Phase Distributed [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Liquid_Phase_Distributed []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Distributed retardation factor for liquid phase porous flow. The corresponding distribution coefficient should be defined with a DISTRIBUTION COEFFICIENT model.

4.1.932. Retardation: Wetting Phase Distributed

Scope: Aria Material

Retardation: Wetting Phase Distributed [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Wetting_Phase_Distributed []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Distributed retardation factor for wetting phase porous flow. The corresponding distribution coefficient should be defined with a DISTRIBUTION COEFFICIENT model.

4.1.933. Retardation: Nonwetting Phase Distributed

Scope: Aria Material

Retardation: Nonwetting Phase Distributed [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Nonwetting_Phase_Distributed []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Distributed retardation factor for non-wetting phase in porous flow. The corresponding distribution coefficient should be defined with a DISTRIBUTION COEFFICIENT model.

4.1.934. Retardation

Scope: Aria Material

Retardation [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |R = *r*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>r</i>	real	undefined

Summary Constant value

4.1.935. Retardation: Copied

Scope: Aria Material

Retardation: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.936. Retardation: User Plugin

Scope: Aria Material

Retardation: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.937. Retardation: Scalar String Function

Scope: Aria Material

Retardation: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.938. Reynolds Number

Scope: Aria Material

Reynolds Number [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Re = *Re*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>Re</i>	real	undefined

Summary Constant value

4.1.939. Reynolds Number: Copied

Scope: Aria Material

Reynolds Number: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.940. Reynolds Number: User Plugin

Scope: Aria Material

Reynolds Number: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.941. Reynolds Number: Scalar String Function

Scope: Aria Material

Reynolds Number: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.942. Reynolds Number: General

Scope: Aria Material

Reynolds Number: General [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= General [L = *l*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>l</i>	real	undefined

Summary Reynold number computed from a specified length scale

4.1.943. Reynolds Number: Correlation

Scope: Aria Material

Reynolds Number: Correlation [{of|species|subindex} *Species*]=
Correlation [*Re* = *Re* |Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>Re</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation Reynolds number computed from material properties

4.1.944. Saturated Retardation

Scope: Aria Material

Saturated Retardation [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |R = *r*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>r</i>	real	undefined

Summary Constant value

4.1.945. Saturated Retardation: Copied

Scope: Aria Material

Saturated Retardation: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.946. Saturated Retardation: User Plugin

Scope: Aria Material

Saturated Retardation: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.947. Saturated Retardation: Scalar String Function

Scope: Aria Material

Saturated Retardation: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.948. Saturation

Scope: Aria Material

Saturation [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |S = *s*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>s</i>	real	undefined

Summary Constant value

4.1.949. Saturation: Copied

Scope: Aria Material

Saturation: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.950. Saturation: User Plugin

Scope: Aria Material

Saturation: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.951. Saturation: Scalar String Function

Scope: Aria Material

Saturation: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.952. Saturation: Van Genuchten

Scope: Aria Material

```
Saturation: Van Genuchten [ {of|species|subindex} Species |{in|  
material_phase} MaterialPhase ]= Van_Genuchten [ Is_Wetting_Phase =  
is_wetting_phase |Nonwetting_Phase = nonwetting_phase |  
Reference_Capillary_Pressure = reference_capillary_pressure |Beta = beta |  
Residual_Wetting_Phase_Saturation = residual_wetting_phase_saturation |  
Residual_Nonwetting_Phase_Saturation = residual_nonwetting_phase_saturation  
|Pcstar = PcStar |Pcmax = PcMax |Wetting_Phase = wetting_phase ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>is_wetting_phase</i>	integer	undefined
<i>nonwetting_phase</i>	"string"	undefined
<i>reference_capillary_pressure</i>	real	undefined
<i>beta</i>	real	undefined
<i>residual_wetting_phase_saturation</i>	real	undefined
<i>residual_nonwetting_phase_saturation</i>	real	undefined
<i>PcStar</i>	real	undefined
<i>PcMax</i>	real	undefined
<i>wetting_phase</i>	"string"	undefined

Summary A Van Genuchten model for saturation using capillary pressure

4.1.953. Saturation: From Other Phase

Scope: Aria Material

```
Saturation: From Other Phase [ {of|species|subindex} Species |{in|  
material_phase} MaterialPhase ]= From_Other_Phase [ ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Get the saturation from one minus the other phase saturation

4.1.954. Scaling

Scope: Aria Material

```
Scaling [ {of|species|subindex} Species |{in|material_phase} MaterialPhase  
]= Constant [ Value = value ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.955. Scaling: Copied

Scope: Aria Material

Scaling: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.956. Scaling: User Plugin

Scope: Aria Material

Scaling: User Plugin [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.957. Scaling: Scalar String Function

Scope: Aria Material

Scaling: Scalar String Function [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.958. Scattering Coefficient

Scope: Aria Material

Scattering Coefficient [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.959. Scattering Coefficient: Copied

Scope: Aria Material

Scattering Coefficient: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.960. Scattering Coefficient: User Plugin

Scope: Aria Material

Scattering Coefficient: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_parameter</i>	string	undefined

Summary Value from a user plugin

4.1.961. Scattering Coefficient: Scalar String Function

Scope: Aria Material

Scattering Coefficient: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.962. Scattering Cross Section

Scope: Aria Material

Scattering Cross Section [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = value |Scat = scat]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>scat</i>	real	undefined

Summary Constant value

4.1.963. Scattering Cross Section: Copied

Scope: Aria Material

Scattering Cross Section: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = source]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.964. Scattering Cross Section: User Plugin

Scope: Aria Material

Scattering Cross Section: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.965. Scattering Cross Section: Scalar String Function

Scope: Aria Material

Scattering Cross Section: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.966. Scattering Cross Section: Calore User Sub

Scope: Aria Material

Scattering Cross Section: Calore User Sub [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Calore user subroutine scattering cross section

4.1.967. Schmidt Number

Scope: Aria Material

Schmidt Number [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |Sc = *Sc*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>Sc</i>	real	undefined

Summary Constant value

4.1.968. Schmidt Number: Copied

Scope: Aria Material

Schmidt Number: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.969. Schmidt Number: User Plugin

Scope: Aria Material

Schmidt Number: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.970. Schmidt Number: Scalar String Function

Scope: Aria Material

Schmidt Number: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.971. Seebeck Coefficient

Scope: Aria Material

Seebeck Coefficient [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* | A = *a*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>a</i>	real	undefined

Summary Constant value

4.1.972. Seebeck Coefficient: Copied

Scope: Aria Material

Seebeck Coefficient: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.973. Seebeck Coefficient: User Plugin

Scope: Aria Material

Seebeck Coefficient: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.974. Seebeck Coefficient: Scalar String Function

Scope: Aria Material

Seebeck Coefficient: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F =
f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.975. Shell Lofting Factor

Scope: Aria Material

Shell Lofting Factor [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* | F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>f</i>	real	undefined

Summary Constant value

4.1.976. Shell Lofting Factor: Copied

Scope: Aria Material

Shell Lofting Factor: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.977. Shell Lofting Factor: User Plugin

Scope: Aria Material

Shell Lofting Factor: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.978. Shell Lofting Factor: Scalar String Function

Scope: Aria Material

Shell Lofting Factor: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.979. Shell Lofting Factor: Element Attribute

Scope: Aria Material

Shell Lofting Factor: Element Attribute [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Element_Attribute [Multiplier = *multiplier* | Attribute_Name = *attribute_name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>attribute_name</i>	"string"	undefined

Summary Element Distribution Factor for the lofting of shell surface

4.1.980. Shell Thickness

Scope: Aria Material

Shell Thickness [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value* | T = *t*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>t</i>	real	undefined

Summary Constant value

4.1.981. Shell Thickness: Copied

Scope: Aria Material

Shell Thickness: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.982. Shell Thickness: User Plugin

Scope: Aria Material

Shell Thickness: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.983. Shell Thickness: Scalar String Function

Scope: Aria Material

Shell Thickness: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.984. Shell Thickness: Element Attribute

Scope: Aria Material

Shell Thickness: Element Attribute [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Element_Attribute [Multiplier = *multiplier* |Attribute_Name = *attribute_name* |Contact = *contact*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>attribute_name</i>	"string"	undefined
<i>contact</i>	"string"	undefined

Summary Distribution Factor for the shell thickness

4.1.985. Skeleton Density

Scope: Aria Material

Skeleton Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Rho = *rho*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>rho</i>	real	undefined

Summary Constant value

4.1.986. Skeleton Density: Copied

Scope: Aria Material

Skeleton Density: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.987. Skeleton Density: User Plugin

Scope: Aria Material

Skeleton Density: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.988. Skeleton Density: Scalar String Function

Scope: Aria Material

Skeleton Density: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.989. Skeleton Enthalpy: Cpt

Scope: Aria Material

Skeleton Enthalpy: Cpt [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Cpt []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary CPT model for the the solid skeleton enthalpy

4.1.990. Skeleton Internal Energy

Scope: Aria Material

Skeleton Internal Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |E = *e*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>e</i>	real	undefined

Summary Constant value

4.1.991. Skeleton Internal Energy: Copied

Scope: Aria Material

Skeleton Internal Energy: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.992. Skeleton Internal Energy: User Plugin

Scope: Aria Material

Skeleton Internal Energy: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |*magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.993. Skeleton Internal Energy: Scalar String Function

Scope: Aria Material

Skeleton Internal Energy: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.994. Skeleton Internal Energy: Cpt

Scope: Aria Material

Skeleton Internal Energy: Cpt [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Cpt []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary CPT model for the the solid skeleton internal energy

4.1.995. Skeleton Internal Energy: Linear

Scope: Aria Material

Skeleton Internal Energy: Linear [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Linear [Cp = *cp* |T_Ref = *T_ref*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>cp</i>	real	undefined
<i>T_ref</i>	real	undefined

Summary CPT model for the the solid skeleton internal energy

4.1.996. Skeleton Specific Heat

Scope: Aria Material

Skeleton Specific Heat [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Cp = *cp*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>cp</i>	real	undefined

Summary Constant value

4.1.997. Skeleton Specific Heat: Copied

Scope: Aria Material

Skeleton Specific Heat: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.998. Skeleton Specific Heat: User Plugin

Scope: Aria Material

Skeleton Specific Heat: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.999. Skeleton Specific Heat: Scalar String Function

Scope: Aria Material

Skeleton Specific Heat: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1000Solid Body Acceleration

Scope: Aria Material

Solid Body Acceleration [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Valuex = *valuex* |Valuey = *valuey* |Valuez = *valuez*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>valuex</i>	real	undefined
<i>valuey</i>	real	undefined
<i>valuez</i>	real	undefined

Summary Constant value

4.1.1001Solid Body Acceleration: User Plugin

Scope: Aria Material

Solid Body Acceleration: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |*magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1002Solid Body Acceleration: Vector String Function

Scope: Aria Material

Solid Body Acceleration: Vector String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Vector_String_Function [$F_X = f_x$ | $F_Y = f_y$ | $F_Z = f_z$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f_x	"string"	undefined
f_y	"string"	undefined
f_z	"string"	undefined

Summary Value from a string function

4.1.1003Solid Density

Scope: Aria Material

Solid Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Rho_Solid = *rho_solid*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>rho_solid</i>	real	undefined

Summary Constant value

4.1.1004Solid Density: Copied

Scope: Aria Material

Solid Density: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1005 Solid Density: User Plugin

Scope: Aria Material

Solid Density: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1006 Solid Density: Scalar String Function

Scope: Aria Material

Solid Density: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1007 Solid Lambda

Scope: Aria Material

Solid Lambda [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Lambda = *lambda*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>lambda</i>	real	undefined

Summary Constant value

4.1.1008Solid Lambda: Copied

Scope: Aria Material

Solid Lambda: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1009Solid Lambda: User Plugin

Scope: Aria Material

Solid Lambda: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1010Solid Lambda: Scalar String Function

Scope: Aria Material

Solid Lambda: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1011 Solid Lambda: Converted

Scope: Aria Material

Solid Lambda: `Converted [ {of|species|subindex} Species |{in|material_phase} MaterialPhase ]= Converted [ ]`

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Lame coefficient computed from Poisson's ratio and elastic modulus

4.1.1012 Solid Lambda: Converted Plane Stress

Scope: Aria Material

Solid Lambda: `Converted Plane Stress [ {of|species|subindex} Species |{in|material_phase} MaterialPhase ]= Converted_Plane_Stress [ ]`

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary This model has been deprecated and removed from the code.

4.1.1013 Solid Poissons Ratio

Scope: Aria Material

Solid Poissons Ratio `[ {of|species|subindex} Species |{in|material_phase} MaterialPhase ]= Constant [ Value = value |Nu = nu ]`

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>nu</i>	real	undefined

Summary Constant value

4.1.1014 Solid Poissons Ratio: Copied

Scope: Aria Material

Solid Poissons Ratio: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1015 Solid Poissons Ratio: User Plugin

Scope: Aria Material

Solid Poissons Ratio: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1016 Solid Poissons Ratio: Scalar String Function

Scope: Aria Material

Solid Poissons Ratio: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F =
f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1017 Solid Pressure Gradient: Gidaspow

Scope: Aria Material

Solid Pressure Gradient: Gidaspow [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Gidaspow [$G0 = g0$ | $C = c$ | $Fmax = fmax$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>g0</i>	real	undefined
<i>c</i>	real	undefined
<i>fmax</i>	real	undefined

Summary This model has been deprecated and removed from the code.

4.1.1018 Solid Stress

Scope: Aria Material

Solid Stress [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [$Xx = xx$ | $T11 = t11$ | $Xy = xy$ | $T12 = t12$ | $Xz = xz$ | $T13 = t13$ | $Yx = yx$ | $T21 = t21$ | $Yy = yy$ | $T22 = t22$ | $Yz = yz$ | $T23 = t23$ | $Zx = zx$ | $T31 = t31$ | $Zy = zy$ | $T32 = t32$ | $Zz = zz$ | $T33 = t33$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>xx</i>	real	undefined
<i>t11</i>	real	undefined
<i>xy</i>	real	undefined
<i>t12</i>	real	undefined
<i>xz</i>	real	undefined
<i>t13</i>	real	undefined
<i>yx</i>	real	undefined
<i>t21</i>	real	undefined
<i>yy</i>	real	undefined
<i>t22</i>	real	undefined
<i>yz</i>	real	undefined
<i>t23</i>	real	undefined
<i>zx</i>	real	undefined
<i>t31</i>	real	undefined
<i>zy</i>	real	undefined
<i>t32</i>	real	undefined
<i>zz</i>	real	undefined
<i>t33</i>	real	undefined

Summary Constant value

4.1.1019 Solid Stress: User Plugin

Scope: Aria Material

Solid Stress: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1020 Solid Stress: Tensor String Function

Scope: Aria Material

Solid Stress: Tensor String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Tensor_String_Function [F_Xx = *f_xx* |
F_Yy = *f_yy* |F_Xy = *f_xy* |F_Zz = *f_zz* |F_Xz = *f_xz* |F_Yz = *f_yz* |F_Yx =
f_yx |F_Zx = *f_zx* |F_Zy = *f_zy*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_xx</i>	"string"	undefined
<i>f_yy</i>	"string"	undefined
<i>f_xy</i>	"string"	undefined
<i>f_zz</i>	"string"	undefined
<i>f_xz</i>	"string"	undefined
<i>f_yz</i>	"string"	undefined
<i>f_yx</i>	"string"	undefined
<i>f_zx</i>	"string"	undefined
<i>f_zy</i>	"string"	undefined

Summary Value from a string function

4.1.1021 Solid Stress: Tensor String Function Symmetric

Scope: Aria Material

Solid Stress: Tensor String Function Symmetric [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Tensor_String_Function_Symmetric [F_Xx = *f_xx* |F_Yy = *f_yy* |F_Xy = *f_xy* |
F_Zz = *f_zz* |F_Xz = *f_xz* |F_Yz = *f_yz*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_xx</i>	"string"	undefined
<i>f_yy</i>	"string"	undefined
<i>f_xy</i>	"string"	undefined
<i>f_zz</i>	"string"	undefined
<i>f_xz</i>	"string"	undefined
<i>f_yz</i>	"string"	undefined

Summary Value from a string function

4.1.1022 Solid Stress: Isothermal

Scope: Aria Material

Solid Stress: Isothermal [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Isothermal [T = *t* |T_Ref = *t_ref*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>t</i>	real	undefined
<i>t_ref</i>	real	undefined

4.1.1023 Solid Stress: Linear Elastic

Scope: Aria Material

Solid Stress: Linear Elastic [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Linear_Elastic [Reference_Frame =
reference_frame]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>reference_frame</i>	"string"	undefined

4.1.1024 Solid Stress: Porous Effective

Scope: Aria Material

Solid Stress: Porous Effective [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous_Effective [Pressure = *pressure* | Phase = *phase* | Biot = *biot*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>pressure</i>	"string"	undefined
<i>phase</i>	"string"	undefined
<i>biot</i>	real	undefined

Summary Apply the pressure as an isotropic mesh stress. Primarily used as an effective stress in porous flow problems.

4.1.1025 Solid Stress: Saturation Weighted Porous Effective

Scope: Aria Material

Solid Stress: Saturation Weighted Porous Effective [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Saturation_Weighted_Porous_Effective [Pressure = *pressure* | Phase = *phase* | Biot = *biot*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>pressure</i>	"string"	undefined
<i>phase</i>	"string"	undefined
<i>biot</i>	real	undefined

Summary Apply the pressure as an isotropic mesh stress. Primarily used as an effective stress in porous flow problems.

4.1.1026 Solid Stress: Mooney Rivlin

Scope: Aria Material

Solid Stress: Mooney Rivlin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mooney_Rivlin []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1027 Solid Stress: Neohookean Elastic

Scope: Aria Material

Solid Stress: Neohookean Elastic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Neohookean_Elastic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1028 Solid Stress: Incompressible Newtonian

Scope: Aria Material

Solid Stress: Incompressible Newtonian [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Incompressible_Newtonian [Pressure = *pressure* |Phase = *phase* |Biot = *biot* |Reference_Frame = *reference_frame*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>pressure</i>	"string"	undefined
<i>phase</i>	"string"	undefined
<i>biot</i>	real	undefined
<i>reference_frame</i>	"string"	undefined

4.1.1029 Solid Stress: Nonlinear Elastic

Scope: Aria Material

Solid Stress: Nonlinear Elastic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Nonlinear_Elastic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1030 Solid Stress: Residual

Scope: Aria Material

Solid Stress: Residual [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Residual [Sz = *sz* |Szz = *szz* |Sxz = *szx* |Syx = *syz* |Sy = *sy* |Syy = *syy* |Sxy = *sxy* |Sx = *sx* |Sxx = *sxx*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>sz</i>	real	undefined
<i>szz</i>	real	undefined
<i>sxz</i>	real	undefined
<i>syz</i>	real	undefined
<i>sy</i>	real	undefined
<i>syγ</i>	real	undefined
<i>sxy</i>	real	undefined
<i>sx</i>	real	undefined
<i>sxx</i>	real	undefined

4.1.1031 Solid Stress: Thermal

Scope: Aria Material

Solid Stress: Thermal [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Thermal []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1032 Solid Stress: Species

Scope: Aria Material

Solid Stress: Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Species [Sref = *sref* |Phase = *phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>sref</i>	real	undefined
<i>phase</i>	"string"	undefined

Summary A linear mechanical strain due to a species concentration

4.1.1033 Solid Stress: Species Transversely Isotropic

Scope: Aria Material

Solid Stress: Species Transversely Isotropic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=

Species_Transversely_Isotropic [Refval = *refval* | Beta_N = *beta_n* | Beta_T = *beta_t* | N_X = *n_x* | N_Y = *n_y* | N_Z = *n_z* | Phase = *phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>refval</i>	real	undefined
<i>beta_n</i>	real	undefined
<i>beta_t</i>	real	undefined
<i>n_x</i>	real	undefined
<i>n_y</i>	real	undefined
<i>n_z</i>	real	undefined
<i>phase</i>	"string"	undefined

Summary A linear mechanical strain that is transversely isotropic due to a species concentration

4.1.1034 Solid Stress: Species Anisotropic

Scope: Aria Material

Solid Stress: Species Anisotropic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Species_Anisotropic [Sref = *sref* | Phase = *phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>sref</i>	real	undefined
<i>phase</i>	"string"	undefined

Summary Anisotropic linear mechanical strain due to a species concentration

4.1.1035 Solid Stress: Lame

Scope: Aria Material

Solid Stress: Lame [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Lame [Model = *model*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>model</i>	"string"	undefined

4.1.1036Solid Two Mu

Scope: Aria Material

Solid Two Mu [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |Two_Mu = *two_mu*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>two_mu</i>	real	undefined

Summary Constant value

4.1.1037Solid Two Mu: Copied

Scope: Aria Material

Solid Two Mu: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1038Solid Two Mu: User Plugin

Scope: Aria Material

Solid Two Mu: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1039Solid Two Mu: Scalar String Function

Scope: Aria Material

Solid Two Mu: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1040Solid Two Mu: Converted

Scope: Aria Material

Solid Two Mu: Converted [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Converted []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Lamé coefficient computed from Poisson's ratio and elastic modulus

4.1.1041Solid Youngs Modulus

Scope: Aria Material

Solid Youngs Modulus [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |E = *e*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>e</i>	real	undefined

Summary Constant value

4.1.1042Solid Youngs Modulus: Copied

Scope: Aria Material

Solid Youngs Modulus: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1043Solid Youngs Modulus: User Plugin

Scope: Aria Material

Solid Youngs Modulus: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1044Solid Youngs Modulus: Scalar String Function

Scope: Aria Material

Solid Youngs Modulus: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F =
f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1045 Soret Coefficient

Scope: Aria Material

Soret Coefficient [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |S = *s*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>s</i>	real	undefined

Summary Constant value

4.1.1046 Soret Coefficient: Copied

Scope: Aria Material

Soret Coefficient: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1047 Soret Coefficient: User Plugin

Scope: Aria Material

Soret Coefficient: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1048 Soret Coefficient: Scalar String Function

Scope: Aria Material

Soret Coefficient: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1049 Sound Speed

Scope: Aria Material

Sound Speed [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* | $C = c$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>c</i>	real	undefined

4.1.1050 Species

Scope: Aria Material

Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1051Species: Copied

Scope: Aria Material

Species: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1052Species: User Plugin

Scope: Aria Material

Species: User Plugin [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1053Species: Scalar String Function

Scope: Aria Material

Species: Scalar String Function [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1054Species: Partial Molar Volume

Scope: Aria Material

Species: Partial Molar Volume [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Partial_Molar_Volume []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1055Species: Sum All Species

Scope: Aria Material

Species: Sum All Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Sum_All_Species []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1056Species: Solvent Concentration From Solute Concentrations And Partial Molar Volumes

Scope: Aria Material

Species: Solvent Concentration From Solute Concentrations And Partial Molar Volumes [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Solvent_Concentration_From_Solute_Concentrations_And_Partial_Molar_Volumes []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1057Species: Chemeq Gas

Scope: Aria Material

Species: Chemeq Gas [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Chemeq_Gas []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1058Species: From Chemeq

Scope: Aria Material

Species: From Chemeq [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= From_Chemeq []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Species concentration of one species extracted from ChemEq

4.1.1059Species: From Mass Fraction

Scope: Aria Material

Species: From Mass Fraction [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= From_Mass_Fraction []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Molar concentration of a single species calculated from its mass fraction, molecular weight, and overall density

4.1.1060Species: Phase Average

Scope: Aria Material

Species: Phase Average [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Phase_Average [Subindex_A = *subindex_a* |
Subindex_B = *subindex_b*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>subindex_a</i>	integer	undefined
<i>subindex_b</i>	integer	undefined

Summary Phase-averaged values

4.1.1061 Species: From Phase All

Scope: Aria Material

```
Species: From Phase All [ {of|species|subindex} Species |{in|  
material_phase} MaterialPhase ]= From_Phase_All [ ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Copy the species from PHASE_ALL to the desired phase.

4.1.1062 Species: From Material Phase

Scope: Aria Material

```
Species: From Material Phase [ {of|species|subindex} Species |{in|  
material_phase} MaterialPhase ]= From_Material_Phase [ Phase_Name =  
phase_name ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>phase_name</i>	"string"	undefined

Summary Copy the species from another material phase to the desired material phase.

4.1.1063 Species: From Density

Scope: Aria Material

```
Species: From Density [ {of|species|subindex} Species |{in|  
material_phase} MaterialPhase ]= From_Density [ ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1064 Species Diffusion: Ficks Law

Scope: Aria Material

Species Diffusion: Ficks Law [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Ficks_Law []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1065 Species Diffusion: Nernst Planck

Scope: Aria Material

Species Diffusion: Nernst Planck [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Nernst_Planck [F = *f* |R = *r*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	real	undefined
<i>r</i>	real	undefined

4.1.1066 Species Diffusion: All Subindices Use Stefan Maxwell

Scope: Aria Material

Species Diffusion: All Subindices Use Stefan Maxwell [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= All_Subindices_Use_Stefan_Maxwell [Velocityconversion = *velocityConversion* |Canteraxmlfile = *canteraXMLFile* |Solidscaling = *solidScaling* | Velocitybasis = *velocityBasis*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>velocityConversion</i>	real	undefined
<i>canteraXMLFile</i>	"string"	undefined
<i>solidScaling</i>	real	undefined
<i>velocityBasis</i>	"string"	undefined

4.1.1067 Species Diffusion: Basic

Scope: Aria Material

Species Diffusion: Basic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Basic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1068 Species Diffusion: Constant Tensorial

Scope: Aria Material

Species Diffusion: Constant Tensorial [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant_Tensorial [D_Xx = d_{xx} | D_Xy = d_{xy} | D_Xz = d_{xz} | D_Yx = d_{yx} | D_Yy = d_{yy} | D_Yz = d_{yz} | D_Zx = d_{zx} | D_Zy = d_{zy} | D_Zz = d_{zz}]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
d_{xx}	real	undefined
d_{xy}	real	undefined
d_{xz}	real	undefined
d_{yx}	real	undefined
d_{yy}	real	undefined
d_{yz}	real	undefined
d_{zx}	real	undefined
d_{zy}	real	undefined
d_{zz}	real	undefined

4.1.1069 Species Diffusion: Tensorial

Scope: Aria Material

Species Diffusion: Tensorial [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Tensorial []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1070 Species Diffusion: Tensorial Dispersive

Scope: Aria Material

Species Diffusion: Tensorial Dispersive [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Tensorial_Dispersive [Alpha_T = *alpha_t* |Alpha_L = *alpha_l* |Tau = *tau*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>alpha_t</i>	real	undefined
<i>alpha_l</i>	real	undefined
<i>tau</i>	real	undefined

4.1.1071 Species Diffusion: Thermophoresis

Scope: Aria Material

Species Diffusion: Thermophoresis [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Thermophoresis []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1072 Species Diffusion: Tensor Thermophoresis

Scope: Aria Material

Species Diffusion: Tensor Thermophoresis [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Tensor_Thermophoresis []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary This model has been deprecated and removed from the code.

4.1.1073Species Diffusion: Electromigration

Scope: Aria Material

Species Diffusion: Electromigration [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Electromigration []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1074Species Diffusion: Tensor Electromigration

Scope: Aria Material

Species Diffusion: Tensor Electromigration [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Tensor_Electromigration []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary This model has been deprecated and removed from the code.

4.1.1075Species Diffusion: Darcy

Scope: Aria Material

Species Diffusion: Darcy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Darcy []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1076Species Diffusion: Chemical Potential

Scope: Aria Material

Species Diffusion: Chemical Potential [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Chemical_Potential []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Model species diffusion using a flux determined from the gradient of the chemical potential. $\vec{J} = -Mc\nabla\mu$ where M is the mobility, c the species concentration, and mu the chemical potential.

4.1.1077Species Diffusion: Tensor Chemical Potential

Scope: Aria Material

Species Diffusion: Tensor Chemical Potential [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Tensor_Chemical_Potential []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Model species diffusion using a flux determined from the gradient of the chemical potential. $\vec{J} = -Mc\nabla\mu$ where M is the tensor mobility, c the species concentration, and mu the chemical potential.

4.1.1078Species Diffusion: Mass Balance Fracbal

Scope: Aria Material

Species Diffusion: Mass Balance Fracbal [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mass_Balance_Fracbal []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Species diffusion for the fracbal species in a mass balance equation system.

$$\vec{J}_i = -1 \sum_{j \neq i} (m \dot{ot}_j) / MW_i.$$

4.1.1079Species Diffusivity

Scope: Aria Material

Species Diffusivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |D = *d*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>d</i>	real	undefined

Summary Constant valueConstant value

4.1.1080Species Diffusivity: Copied

Scope: Aria Material

Species Diffusivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expressionCopied value from another expression

4.1.1081Species Diffusivity: User Plugin

Scope: Aria Material

Species Diffusivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user pluginValue from a user plugin

4.1.1082Species Diffusivity: Scalar String Function

Scope: Aria Material

Species Diffusivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string functionValue from a string function

4.1.1083 Species Diffusivity: Arrhenius

Scope: Aria Material

Species Diffusivity: Arrhenius [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Arrhenius [R = *r* | C = *c* | D = *d* | Q = *q*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>r</i>	real	undefined
<i>c</i>	real	undefined
<i>d</i>	real	undefined
<i>q</i>	real	undefined

Summary Arrhenius species diffusivity, $D_i = C + D * \exp\left(-\frac{Q}{RT}\right)$ Arrhenius species diffusivity, $D_i = C + D * \exp\left(-\frac{Q}{RT}\right)$

4.1.1084 Species Diffusivity: Dissolution

Scope: Aria Material

Species Diffusivity: Dissolution [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Dissolution [D = *d*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>d</i>	"string"	undefined

Summary Dissolution species diffusivity for a species dissolving in a liquid from a gas. Dissolution species diffusivity for a species dissolving in a liquid from a gas.

4.1.1085 Species Expansion Coeff

Scope: Aria Material

Species Expansion Coeff [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* | Species_Expansion_Coeff = *species_expansion_coeff*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>species_expansion_coeff</i>	real	undefined

Summary Constant value

4.1.1086 Species Expansion Coeff: Copied

Scope: Aria Material

Species Expansion Coeff: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1087 Species Expansion Coeff: User Plugin

Scope: Aria Material

Species Expansion Coeff: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1088 Species Expansion Coeff: Scalar String Function

Scope: Aria Material

Species Expansion Coeff: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1089Species Face Stabilization Scaling: Default

Scope: Aria Material

Species Face Stabilization Scaling: Default [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]= Default []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Default face stabilization scaling for energy equation

4.1.1090Species Fraction

Scope: Aria Material

Species Fraction [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1091Species Fraction: Copied

Scope: Aria Material

Species Fraction: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1092 Species Fraction: User Plugin

Scope: Aria Material

Species Fraction: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1093 Species Fraction: Scalar String Function

Scope: Aria Material

Species Fraction: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1094 Species Fraction: From Chemeq

Scope: Aria Material

Species Fraction: From Chemeq [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Chemeq []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Species fraction of one species extracted from ChemEq

4.1.1095 Species Fraction: From Species

Scope: Aria Material

Species Fraction: From Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Species []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Species fraction of one species from it's concentration and the overall concentration

4.1.1096 Species Mobility

Scope: Aria Material

Species Mobility [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1097 Species Mobility: Copied

Scope: Aria Material

Species Mobility: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1098 Species Mobility: User Plugin

Scope: Aria Material

Species Mobility: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.1099 Species Mobility: Scalar String Function

Scope: Aria Material

Species Mobility: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [*F* = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1100 Species Mobility: Nernst Einstein

Scope: Aria Material

Species Mobility: Nernst Einstein [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Nernst_Einstein [*R* = *r* | Temperature_Material_Phase = *temperature_material_phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>r</i>	real	undefined
<i>temperature_material_phase</i>	"string"	undefined

Summary Mobility from diffusivity, $M = D/(RT)$.

4.1.1101 Species Production: From Time Rate Of Change

Scope: Aria Material

Species Production: From Time Rate Of Change [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Time_Rate_Of_Change [Max_Order = *max_order*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>max_order</i>	integer	undefined

Summary Species production rate from the time derivative of species concentration. This is done by default using a first-order time integration scheme (new - old)/dt To use the same order as the overall solve, set max_order > 1

4.1.1102 Species Surface

Scope: Aria Material

Species Surface [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1103 Species Surface: Copied

Scope: Aria Material

Species Surface: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1104Species Surface: User Plugin

Scope: Aria Material

Species Surface: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1105Species Surface: Scalar String Function

Scope: Aria Material

Species Surface: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1106Species Surface: Equivalent To Bulk

Scope: Aria Material

Species Surface: Equivalent To Bulk [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Equivalent_To_Bulk []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Approximate a surface species concentration as identical to the bulk concentration

4.1.1107Species Surface: Diffusion To Surf Correction

Scope: Aria Material

Species Surface: Diffusion To Surf Correction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Diffusion_To_Surf_Correction [Species_A = *species_a* |Species_B = *species_b* |D = *d* |R = *r* |F = *f* |K = *k* |Eqpot = *eqPot* |Dir = *dir*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>species_a</i>	"string"	undefined
<i>species_b</i>	"string"	undefined
<i>d</i>	real	undefined
<i>r</i>	real	undefined
<i>f</i>	real	undefined
<i>k</i>	real	undefined
<i>eqPot</i>	real	undefined
<i>dir</i>	real	undefined

Summary Correction for surface concentration based on balancing reaction rate and diffusion from pore center to wall.

4.1.1108Species Valence

Scope: Aria Material

Species Valence [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Z = *z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>z</i>	real	undefined

Summary Constant value

4.1.1109Species Valence: Copied

Scope: Aria Material

Species Valence: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1110Species Valence: User Plugin

Scope: Aria Material

Species Valence: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1111Species Valence: Scalar String Function

Scope: Aria Material

Species Valence: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1112Specific Dissipation Rate

Scope: Aria Material

Specific Dissipation Rate [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1113 Specific Dissipation Rate: Copied

Scope: Aria Material

Specific Dissipation Rate: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1114 Specific Dissipation Rate: User Plugin

Scope: Aria Material

Specific Dissipation Rate: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1115 Specific Dissipation Rate: Scalar String Function

Scope: Aria Material

Specific Dissipation Rate: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1116 Specific Dissipation Rate Density

Scope: Aria Material

Specific Dissipation Rate Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1117 Specific Dissipation Rate Density: Copied

Scope: Aria Material

Specific Dissipation Rate Density: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1118 Specific Dissipation Rate Density: User Plugin

Scope: Aria Material

Specific Dissipation Rate Density: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_parameter</i>	string	undefined

Summary Value from a user plugin

4.1.1119 Specific Dissipation Rate Density: Scalar String Function

Scope: Aria Material

Specific Dissipation Rate Density: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1120 Specific Dissipation Rate Diffusive Flux: Basic

Scope: Aria Material

Specific Dissipation Rate Diffusive Flux: Basic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Basic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Basic model of specific dissipation rate diffusive flux

4.1.1121 Specific Heat: Scalar String Function

Scope: Aria Material

Specific Heat: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1122 Specific Heat: Calore User Sub

Scope: Aria Material

Specific Heat: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

4.1.1123 Specific Heat: Curing Foam

Scope: Aria Material

Specific Heat: Curing Foam [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Curing_Foam []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Specific heat for a curing foam

4.1.1124 Specific Heat: Phase Average

Scope: Aria Material

Specific Heat: Phase Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Phase_Average [Subindex_A = *subindex_a* | Subindex_B = *subindex_b*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>subindex_a</i>	integer	undefined
<i>subindex_b</i>	integer	undefined

Summary Phase-averaged values

4.1.1125 Specific Heat: Use Phase Change

Scope: Aria Material

Specific Heat: Use Phase Change [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Use_Phase_Change [Flh = *flh* |Ts = *ts* |Tl = *tl*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>flh</i>	real	undefined
<i>ts</i>	real	undefined
<i>tl</i>	real	undefined

Summary For versions > 4.53 this material model automatically creates a "MELTING" source term for the energy equation and uses the accompanying PHASE CHANGE SPECIFIC HEAT model to define the specific heat.

4.1.1126 Specific Heat: Interpolated Phase Average

Scope: Aria Material

Specific Heat: Interpolated Phase Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Interpolated_Phase_Average [Subindex_A = *subindex_a* |Subindex_B = *subindex_b*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>subindex_a</i>	integer	undefined
<i>subindex_b</i>	integer	undefined

Summary Phase-averaged values

4.1.1127 Specific Heat: Porous Phase Specific Average

Scope: Aria Material

Specific Heat: Porous Phase Specific Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Porous_Phase_Specific_Average [Liquid_Phase_Name = *Liquid_Phase_Name* |
Gas_Phase_Name = *Gas_Phase_Name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Liquid_Phase_Name</i>	"string"	undefined
<i>Gas_Phase_Name</i>	"string"	undefined

Summary Specific heat for a multiphase material of two or three phases

4.1.1128 Specific Heat: Mass Average

Scope: Aria Material

Specific Heat: Mass Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mass_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Specific heat computed from mass average of species specific heats

4.1.1129 Specific Heat: Cantera

Scope: Aria Material

Specific Heat: Cantera [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Cantera [Poffset = *poffset*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>poffset</i>	real	undefined

Summary Cantera specific heat for low Mach number applications

4.1.1130 Specific Heat

Scope: Aria Material

Specific Heat [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [$H_0 = h_0$ | $S_0 = s_0$ | $T_{\text{Standard}} = T_{\text{standard}}$ | $C_p = C_p$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>h₀</i>	real	undefined
<i>s₀</i>	real	undefined
<i>T_{standard}</i>	real	undefined
<i>C_p</i>	real	undefined

Summary Constant specific heat from an evaluator

4.1.1131 Specific Heat: T Exponent

Scope: Aria Material

Specific Heat: T Exponent [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= T_Exponent [$H_0 = h_0$ | $S_0 = s_0$ | $T_{\text{Standard}} = T_{\text{standard}}$ | $C_{p\_Ref} = C_{p\_ref}$ | $T_{\text{Ref}} = T_{\text{ref}}$ | $N = n$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>h₀</i>	real	undefined
<i>s₀</i>	real	undefined
<i>T_{standard}</i>	real	undefined
<i>C_{p_ref}</i>	real	undefined
<i>T_{ref}</i>	real	undefined
<i>n</i>	real	undefined

Summary Temperature exponent specific heat from an evaluator

4.1.1132 Specific Heat: Nasa14

Scope: Aria Material

Specific Heat: Nasa14 [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Nasa14 [$H_0 = h_0$ | $S_0 = s_0$ | $T_{\text{Standard}} = T_{\text{standard}}$ | $T_{\text{mid}} = T_{\text{mid}}$ | $T_{\text{max}} = T_{\text{max}}$ | $R = r$ | $L_0 = l_0$ | $L_1 = l_1$ | $L_2 = l_2$ | $L_3 = l_3$ | $L_4 = l_4$ | $L_5 = l_5$ | $L_6 = l_6$ | $H_1 = h_1$ | $H_2 = h_2$ | $H_3 = h_3$ | $H_4 = h_4$ | $H_5 = h_5$ | $H_6 = h_6$ | $T_{\text{Offset}} = t_{\text{offset}}$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>h₀</i>	real	undefined
<i>s₀</i>	real	undefined
<i>T_{standard}</i>	real	undefined
<i>T_{mid}</i>	real	undefined
<i>T_{max}</i>	real	undefined
<i>r</i>	real	undefined
<i>l₀</i>	real	undefined
<i>l₁</i>	real	undefined
<i>l₂</i>	real	undefined
<i>l₃</i>	real	undefined
<i>l₄</i>	real	undefined
<i>l₅</i>	real	undefined
<i>l₆</i>	real	undefined
<i>h₁</i>	real	undefined
<i>h₂</i>	real	undefined
<i>h₃</i>	real	undefined
<i>h₄</i>	real	undefined
<i>h₅</i>	real	undefined
<i>h₆</i>	real	undefined
<i>t_{offset}</i>	real	undefined

Summary Value from a NASA14 polynomial function

4.1.1133 Specific Heat: Fortran

Scope: Aria Material

Specific Heat: Fortran [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*] = Fortran [Multiplier = *multiplier* | Sub_Name = *sub_name* | Real_Data = *real_data* | Int_Data = *int_data* | Resource_Name = *resource_name* | Data = *data*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>sub_name</i>	"string"	undefined
<i>real_data</i>	"string"	undefined
<i>int_data</i>	"string"	undefined
<i>resource_name</i>	"string"	undefined
<i>data</i>	"string"	undefined

Summary Fortran subroutine specific heat.

4.1.1134 Specific Heat Cp

Scope: Aria Material

Specific Heat Cp [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1135 Specific Heat Cp: Copied

Scope: Aria Material

Specific Heat Cp: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1136 Specific Heat Cp: User Plugin

Scope: Aria Material

Specific Heat Cp: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1137 Specific Heat Cp: Scalar String Function

Scope: Aria Material

Specific Heat Cp: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1138 Specific Heat Cp: Cantera

Scope: Aria Material

Specific Heat Cp: Cantera [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Cantera [Poffset = *poffset*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>poffset</i>	real	undefined

Summary Cantera specific heat for low Mach number applications

4.1.1139 Specific Surface Area

Scope: Aria Material

Specific Surface Area [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1140 Specific Surface Area: Copied

Scope: Aria Material

Specific Surface Area: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1141 Specific Surface Area: User Plugin

Scope: Aria Material

Specific Surface Area: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1142 Specific Surface Area: Scalar String Function

Scope: Aria Material

Specific Surface Area: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1143 Supg Tau: Shakib Energy

Scope: Aria Material

```
Supg Tau: Shakib Energy [ {of|species|subindex} Species |{in|  
material_phase} MaterialPhase ]= Shakib_Energy [ H = h |Use_Advection =  
use_advection |Use_Diffusion = use_diffusion |Use_Time = use_time |  
Multiplier = multiplier ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>h</i>	real	undefined
<i>use_advection</i>	integer	undefined
<i>use_diffusion</i>	integer	undefined
<i>use_time</i>	integer	undefined
<i>multiplier</i>	real	undefined

Summary A Shakib SUPG Tau model

4.1.1144 Supg Tau: Shakib Enthalpy

Scope: Aria Material

```
Supg Tau: Shakib Enthalpy [ {of|species|subindex} Species |{in|  
material_phase} MaterialPhase ]= Shakib_Enthalpy [ Multiplier = multiplier  
|Use_Diffusion = use_diffusion |Use_Time = use_time ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>use_diffusion</i>	integer	undefined
<i>use_time</i>	integer	undefined

Summary A Shakib SUPG Tau model

4.1.1145 Supg Tau: Shakib Momentum

Scope: Aria Material

```
Supg Tau: Shakib Momentum [ {of|species|subindex} Species |{in|  
material_phase} MaterialPhase ]= Shakib_Momentum [ H = h |Use_Advection =  
use_advection |Use_Diffusion = use_diffusion |Use_Time = use_time |  
Multiplier = multiplier ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>h</i>	real	undefined
<i>use_advection</i>	integer	undefined
<i>use_diffusion</i>	integer	undefined
<i>use_time</i>	integer	undefined
<i>multiplier</i>	real	undefined

Summary A Shakib SUPG Tau model

4.1.1146Supg Tau: Shakib Level Set

Scope: Aria Material

Supg Tau: Shakib Level Set [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Shakib_Level_Set [H = *h* |Use_Advection = *use_advection* |Use_Diffusion = *use_diffusion* |Use_Time = *use_time* |Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>h</i>	real	undefined
<i>use_advection</i>	integer	undefined
<i>use_diffusion</i>	integer	undefined
<i>use_time</i>	integer	undefined
<i>multiplier</i>	real	undefined

Summary A Shakib SUPG Tau model

4.1.1147Supg Tau: Shakib Suspension

Scope: Aria Material

Supg Tau: Shakib Suspension [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Shakib_Suspension [H = *h* |Use_Advection = *use_advection* |Use_Diffusion = *use_diffusion* |Use_Time = *use_time* |Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>h</i>	real	undefined
<i>use_advection</i>	integer	undefined
<i>use_diffusion</i>	integer	undefined
<i>use_time</i>	integer	undefined
<i>multiplier</i>	real	undefined

Summary A Shakib SUPG Tau model for the suspension equation

4.1.1148Supg Tau: Classic Energy

Scope: Aria Material

Supg Tau: Classic Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Classic_Energy [Epsilon = *epsilon* | Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>epsilon</i>	real	undefined
<i>multiplier</i>	real	undefined

Summary A Shakib SUPG Tau model

4.1.1149Supg Tau: Classic Momentum

Scope: Aria Material

Supg Tau: Classic Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Classic_Momentum [Epsilon = *epsilon* | Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>epsilon</i>	real	undefined
<i>multiplier</i>	real	undefined

Summary A Shakib SUPG Tau model

4.1.1150 Supg Tau: Shakib Cvfem Momentum

Scope: Aria Material

Supg Tau: Shakib Cvfem Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Shakib_Cvfem_Momentum [Multiplier = *multiplier* |Use_Diffusion = *use_diffusion* |Use_Time = *use_time*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>use_diffusion</i>	integer	undefined
<i>use_time</i>	integer	undefined

Summary A Shakib SUPG Tau model

4.1.1151 Supg Tau: Shakib Cvfem Mixture Fraction

Scope: Aria Material

Supg Tau: Shakib Cvfem Mixture Fraction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Shakib_Cvfem_Mixture_Fraction [Multiplier = *multiplier* |Use_Diffusion = *use_diffusion* |Use_Time = *use_time*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>use_diffusion</i>	integer	undefined
<i>use_time</i>	integer	undefined

Summary A Shakib SUPG Tau model

4.1.1152 Supg Tau: Shakib Cvfem Level Set

Scope: Aria Material

Supg Tau: Shakib Cvfem Level Set [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Shakib_Cvfem_Level_Set [Multiplier = *multiplier* |Use_Diffusion = *use_diffusion* |Use_Time = *use_time*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>use_diffusion</i>	integer	undefined
<i>use_time</i>	integer	undefined

Summary A Shakib SUPG Tau model

4.1.1153Supg Tau: Shakib Cvfem Dispersed Phase Momentum

Scope: Aria Material

Supg Tau: Shakib Cvfem Dispersed Phase Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Shakib_Cvfem_Dispersed_Phase_Momentum [Multiplier = *multiplier* |
Use_Diffusion = *use_diffusion* |Use_Time = *use_time*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>use_diffusion</i>	integer	undefined
<i>use_time</i>	integer	undefined

Summary A Shakib SUPG Tau model

4.1.1154Supg Tau: Classic Mixture Fraction

Scope: Aria Material

Supg Tau: Classic Mixture Fraction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Classic_Mixture_Fraction [Epsilon = *epsilon* |Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>epsilon</i>	real	undefined
<i>multiplier</i>	real	undefined

Summary A Shakib SUPG Tau model

4.1.1155Supg Tau: Shakib Mixture Fraction

Scope: Aria Material

Supg Tau: Shakib Mixture Fraction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Shakib_Mixture_Fraction [Multiplier = *multiplier* |Use_Diffusion = *use_diffusion* |Use_Time = *use_time*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>use_diffusion</i>	integer	undefined
<i>use_time</i>	integer	undefined

Summary A Shakib SUPG Tau model

4.1.1156Supg Tau: Classic Species

Scope: Aria Material

Supg Tau: Classic Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Classic_Species [Epsilon = *epsilon* | Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>epsilon</i>	real	undefined
<i>multiplier</i>	real	undefined

Summary A Shakib SUPG Tau model

4.1.1157Supg Tau: Shakib Species

Scope: Aria Material

Supg Tau: Shakib Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Shakib_Species [Multiplier = *multiplier* | Use_Diffusion = *use_diffusion* |Use_Time = *use_time*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>use_diffusion</i>	integer	undefined
<i>use_time</i>	integer	undefined

Summary A Shakib SUPG Tau model

4.1.1158Supg Tau: Shakib Mass Balance

Scope: Aria Material

Supg Tau: Shakib Mass Balance [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Shakib_Mass_Balance [Multiplier = *multiplier* |Use_Diffusion = *use_diffusion* |Use_Time = *use_time*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>use_diffusion</i>	integer	undefined
<i>use_time</i>	integer	undefined

Summary A Shakib SUPG Tau model

4.1.1159Supg Tau: Shakib Charge Density

Scope: Aria Material

Supg Tau: Shakib Charge Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Shakib_Charge_Density [H = *h* |Use_Advection = *use_advection* |Use_Diffusion = *use_diffusion* |Use_Time = *use_time* |Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>h</i>	real	undefined
<i>use_advection</i>	integer	undefined
<i>use_diffusion</i>	integer	undefined
<i>use_time</i>	integer	undefined
<i>multiplier</i>	real	undefined

Summary A Shakib SUPG Tau model

4.1.1160 Surface Tension

Scope: Aria Material

Surface Tension [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Sigma = *sigma*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>sigma</i>	real	undefined

Summary Constant value

4.1.1161 Surface Tension: Copied

Scope: Aria Material

Surface Tension: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1162 Surface Tension: User Plugin

Scope: Aria Material

Surface Tension: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1163 Surface Tension: Scalar String Function

Scope: Aria Material

Surface Tension: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] = Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1164 Surface Tension: Linear T

Scope: Aria Material

Surface Tension: Linear T [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] = Linear_T [Sigma0 = *sigma0* | Dsigmadt = *dsigmadt* | T_Ref = *T_ref*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>sigma0</i>	real	undefined
<i>dsigmadt</i>	real	undefined
<i>T_ref</i>	real	undefined

Summary Linear T surface tension

4.1.1165 Suspension Flux: Phillips

Scope: Aria Material

Suspension Flux: Phillips [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] = Phillips [K_Mu = *k_mu* | K_C = *k_c* | Phi_Max = *phi_max* | Beta = *beta* | Particle_Radius = *particle_radius* | K_0 = *k_0* | Phi_Tol = *phi_tol* | Use_Fd = *use_fd*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>k_mu</i>	real	undefined
<i>k_c</i>	real	undefined
<i>phi_max</i>	real	undefined
<i>beta</i>	real	undefined
<i>particle_radius</i>	real	undefined
<i>k_o</i>	real	undefined
<i>phi_tol</i>	real	undefined
<i>use_fd</i>	integer	undefined

4.1.1166Suspension Flux: Fad Phillips

Scope: Aria Material

Suspension Flux: Fad Phillips [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Fad_Phillips [K_Mu = *k_mu* |K_C = *k_c* |Phi_Max = *phi_max* |Beta = *beta* |Particle_Radius = *particle_radius* |K_0 = *k_o* |Phi_Tol = *phi_tol*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>k_mu</i>	real	undefined
<i>k_c</i>	real	undefined
<i>phi_max</i>	real	undefined
<i>beta</i>	real	undefined
<i>particle_radius</i>	real	undefined
<i>k_o</i>	real	undefined
<i>phi_tol</i>	real	undefined

4.1.1167Suspension Flux: Balance

Scope: Aria Material

Suspension Flux: Balance [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Balance [A = *a* |Mu_S = *mu_s* |Lambda_1 = *lambda_1* |Lambda_2 = *lambda_2* |Lambda_3 = *lambda_3*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>a</i>	real	undefined
<i>mu_s</i>	real	undefined
<i>lambda_1</i>	real	undefined
<i>lambda_2</i>	real	undefined
<i>lambda_3</i>	real	undefined

4.1.1168Suspension Flux: Hydrostatic

Scope: Aria Material

Suspension Flux: Hydrostatic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Hydrostatic [Gx = *gx* |Gy = *gy* |Gz = *gz* |Lambda = *lambda* |Fluid_Density = *fluid_density* |B = *b* |Phi_Max = *phi_max*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>gx</i>	real	undefined
<i>gy</i>	real	undefined
<i>gz</i>	real	undefined
<i>lambda</i>	real	undefined
<i>fluid_density</i>	real	undefined
<i>b</i>	real	undefined
<i>phi_max</i>	real	undefined

Summary This model has been deprecated

4.1.1169Suspension Hindrance Function: Morris

Scope: Aria Material

Suspension Hindrance Function: Morris [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Morris [Alpha = *alpha* |Phi_Max = *phi_max* |Phi_Tol = *phi_tol*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>alpha</i>	real	undefined
<i>phi_max</i>	real	undefined
<i>phi_tol</i>	real	undefined

4.1.1170 Suspension Normal Viscosity: Morris

Scope: Aria Material

Suspension Normal Viscosity: Morris [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Morris [$K_N = K_n$ | $\Phi_{Max} = \phi_{max}$ | $\Phi_{Tol} = \phi_{tol}$ | $\mu_S = \mu_s$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
K_n	real	undefined
ϕ_{max}	real	undefined
ϕ_{tol}	real	undefined
μ_s	real	undefined

4.1.1171 Suspension Q Tensor: Isotropic

Scope: Aria Material

Suspension Q Tensor: Isotropic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Isotropic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1172 Suspension Q Tensor: Ct Aligned

Scope: Aria Material

Suspension Q Tensor: Ct Aligned [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Ct_Aligned [$\Lambda_1 = \lambda_{1_1}$ | $\Lambda_2 = \lambda_{2_2}$ | $\Lambda_3 = \lambda_{3_3}$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
λ_{1_1}	real	undefined
λ_{2_2}	real	undefined
λ_{3_3}	real	undefined

4.1.1173Suspension Q Tensor: Flow Aligned

Scope: Aria Material

Suspension Q Tensor: Flow Aligned [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Flow_Aligned_ [Lambda_A = *lambda_a* | Lambda_B = *lambda_b*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>lambda_a</i>	real	undefined
<i>lambda_b</i>	real	undefined

4.1.1174Species Names

Scope: Aria Material

Species Names {=|are|is} *Names...*

Parameter	Value	Default
<i>Names</i>	string...	undefined

Description This defines the available chemical species, if they are not already specified by an external property TPL.

4.1.1175Temperature

Scope: Aria Material

Temperature [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant valueConstant value

4.1.1176.Temperature: Copied

Scope: Aria Material

Temperature: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expressionCopied value from another expression

4.1.1177.Temperature: User Plugin

Scope: Aria Material

Temperature: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user pluginValue from a user plugin

4.1.1178.Temperature: Scalar String Function

Scope: Aria Material

Temperature: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string functionValue from a string function

4.1.1179.Temperature: Calore User Sub

Scope: Aria Material

Temperature: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Multiplier = *multiplier* |Name = *name* |Type = *type* |Material_Data_Block = *material_data_block* |Data = *data*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined

Summary Values from a Calore user subroutineValues from a Calore user subroutine

4.1.1180.Temperature: From No Material Phase

Scope: Aria Material

Temperature: From No Material Phase [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_No_Material_Phase []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Copy the temperature from NO_MATERIAL_PHASE to the desired material phase.Copy the temperature from NO_MATERIAL_PHASE to the desired material phase.

4.1.1181.Temperature: Cantera

Scope: Aria Material

Temperature: Cantera [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Cantera [Omit_Fd_Sens = *omit_fd_sens*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>omit_fd_sens</i>	integer	undefined

Summary Cantera enthalpy computed from temperatureCantera enthalpy computed from temperature

4.1.1182.Temperature: Fortran User Sub

Scope: Aria Material

Temperature: Fortran User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Fortran_User_Sub [Multiplier = *multiplier* |Name = *name* |Type = *type* |Real_Data = *real_data* |Int_Data = *int_data* |Resource_Name = *resource_name* |Data = *data* |Material_Data_Block = *material_data_block*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>real_data</i>	"string"	undefined
<i>int_data</i>	"string"	undefined
<i>resource_name</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>material_data_block</i>	"string"	undefined

Summary Dirichlet value from a Fortran user subroutineDirichlet value from a Fortran user subroutine

4.1.1183.Temperature: Cht Robin

Scope: Aria Material

Temperature: Cht Robin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Cht_Robin [Temperature_Field = *temperature_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>temperature_field</i>	"string"	undefined

Summary Dirichlet boundary condition for interface coupled with Robin style BC CHT_ROBIN. This BC computes the heat flux for the other side.Dirichlet boundary condition for interface coupled with Robin style BC CHT_ROBIN. This BC computes the heat flux for the other side.

4.1.1184.Temperature: Correlation Wall

Scope: Aria Material

Temperature: Correlation Wall [{of|species|subindex} *Species*]=
Correlation_Wall [$T_w = T_w$ |Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>T_w</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation wall temperature

4.1.1185.Temperature: Correlation Fluid

Scope: Aria Material

Temperature: Correlation Fluid [{of|species|subindex} *Species*]=
Correlation_Fluid [$T = t$ |Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>t</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation fluid temperature

4.1.1186.Tensor Bulk Conductivity

Scope: Aria Material

Tensor Bulk Conductivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [$X_x = x_x$ | $T_{11} = t_{11}$ | $X_y = x_y$ |
 $T_{12} = t_{12}$ | $X_z = x_z$ | $T_{13} = t_{13}$ | $Y_x = y_x$ | $T_{21} = t_{21}$ | $Y_y = y_y$ | $T_{22} = t_{22}$ |
 $Y_z = y_z$ | $T_{23} = t_{23}$ | $Z_x = z_x$ | $T_{31} = t_{31}$ | $Z_y = z_y$ | $T_{32} = t_{32}$ | $Z_z = z_z$ |
 $T_{33} = t_{33}$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>xx</i>	real	undefined
<i>t11</i>	real	undefined
<i>xy</i>	real	undefined
<i>t12</i>	real	undefined
<i>xz</i>	real	undefined
<i>t13</i>	real	undefined
<i>yx</i>	real	undefined
<i>t21</i>	real	undefined
<i>yy</i>	real	undefined
<i>t22</i>	real	undefined
<i>yz</i>	real	undefined
<i>t23</i>	real	undefined
<i>zx</i>	real	undefined
<i>t31</i>	real	undefined
<i>zy</i>	real	undefined
<i>t32</i>	real	undefined
<i>zz</i>	real	undefined
<i>t33</i>	real	undefined

Summary Constant tensor value for the bulk conductivity.

4.1.1187.Tensor Bulk Conductivity: Diagonal

Scope: Aria Material

Tensor Bulk Conductivity: Diagonal [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Diagonal [Variable = *variable*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>variable</i>	"string"	undefined

4.1.1188.Tensor Bulk Conductivity: Volume Average

Scope: Aria Material

Tensor Bulk Conductivity: Volume Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Volume_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Bulk conductivity tensor computed from volume average of species bulk conductivities

4.1.1189.Tensor Bulk Conductivity: Tensor String Function

Scope: Aria Material

Tensor Bulk Conductivity: Tensor String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Tensor_String_Function [F_Xx = f_{xx} |F_Yy = f_{yy} |F_Xy = f_{xy} |F_Zz = f_{zz} |F_Xz = f_{xz} |F_Yz = f_{yz} |F_Yx = f_{yx} |F_Zx = f_{zx} |F_Zy = f_{zy}]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f_{xx}	"string"	undefined
f_{yy}	"string"	undefined
f_{xy}	"string"	undefined
f_{zz}	"string"	undefined
f_{xz}	"string"	undefined
f_{yz}	"string"	undefined
f_{yx}	"string"	undefined
f_{zx}	"string"	undefined
f_{zy}	"string"	undefined

Summary Value from a string function

4.1.1190.Tensor Bulk Conductivity: Tensor String Function Symmetric

Scope: Aria Material

Tensor Bulk Conductivity: Tensor String Function Symmetric [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Tensor_String_Function_Symmetric [F_Xx = f_{xx} |F_Yy = f_{yy} |F_Xy = f_{xy} |F_Zz = f_{zz} |F_Xz = f_{xz} |F_Yz = f_{yz} |F_Yx = f_{yx} |F_Zx = f_{zx} |F_Zy = f_{zy}]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_{xx}</i>	"string"	undefined
<i>f_{yy}</i>	"string"	undefined
<i>f_{xy}</i>	"string"	undefined
<i>f_{zz}</i>	"string"	undefined
<i>f_{xz}</i>	"string"	undefined
<i>f_{yz}</i>	"string"	undefined
<i>f_{yx}</i>	"string"	undefined
<i>f_{zx}</i>	"string"	undefined
<i>f_{zy}</i>	"string"	undefined

Summary Value from a string function

4.1.1191.Tensor Bulk Conductivity: Level Set Aligned

Scope: Aria Material

Tensor Bulk Conductivity: Level Set Aligned [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Level_Set_Aligned [K_Normal = *k_{normal}* |K_Tangent = *k_{tangent}* |Level_Set_Subindex = *level_set_subindex*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>k_{normal}</i>	real	undefined
<i>k_{tangent}</i>	real	undefined
<i>level_set_subindex</i>	integer	undefined

Summary Tensor values for the bulk thermal conductivity aligned to a level set field

4.1.1192.Tensor Bulk Conductivity Scaling

Scope: Aria Material

Tensor Bulk Conductivity Scaling [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |S = *s*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>s</i>	real	undefined

Summary Constant value

4.1.1193.Tensor Bulk Conductivity Scaling: Copied

Scope: Aria Material

Tensor Bulk Conductivity Scaling: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1194.Tensor Bulk Conductivity Scaling: User Plugin

Scope: Aria Material

Tensor Bulk Conductivity Scaling: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.1195.Tensor Bulk Conductivity Scaling: Scalar String Function

Scope: Aria Material

Tensor Bulk Conductivity Scaling: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1196.Tensor Bulk Conductivity Scaling: T Exponent

Scope: Aria Material

Tensor Bulk Conductivity Scaling: T Exponent [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]= T_Exponent [Kbulk_Ref =
kbulk_ref |T_Ref = *t_ref* |N = *n*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>kbulk_ref</i>	real	undefined
<i>t_ref</i>	real	undefined
<i>n</i>	real	undefined

Summary Tensor thermal conductivity scaling for bulk material. Nominally this returns $k = k_{ref} \left(\frac{T}{T_{ref}} \right)^n$. If you provide expressions for BULK_DENSITY and SOLID_DENSITY this is also scaled by the ratio of SOLID_DENSITY/BULK_DENSITY

4.1.1197.Tensor Electrical Conductivity: Calore User Sub

Scope: Aria Material

Tensor Electrical Conductivity: Calore User Sub [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name =
name |Type = *type* |Multiplier = *multiplier* |Material_Data_Block =
material_data_block |Data = *data*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined

Summary Tensor values for temperature dependent electrical conductivity from a calore user subroutine

4.1.1198.Tensor Electrical Conductivity

Scope: Aria Material

Tensor Electrical Conductivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Xx = *xx* |T11 = *t11* |Xy = *xy* |T12 = *t12* |Xz = *xz* |T13 = *t13* |Yx = *yx* |T21 = *t21* |Yy = *yy* |T22 = *t22* |Yz = *yz* |T23 = *t23* |Zx = *zx* |T31 = *t31* |Zy = *zy* |T32 = *t32* |Zz = *zz* |T33 = *t33*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>xx</i>	real	undefined
<i>t11</i>	real	undefined
<i>xy</i>	real	undefined
<i>t12</i>	real	undefined
<i>xz</i>	real	undefined
<i>t13</i>	real	undefined
<i>yx</i>	real	undefined
<i>t21</i>	real	undefined
<i>yy</i>	real	undefined
<i>t22</i>	real	undefined
<i>yz</i>	real	undefined
<i>t23</i>	real	undefined
<i>zx</i>	real	undefined
<i>t31</i>	real	undefined
<i>zy</i>	real	undefined
<i>t32</i>	real	undefined
<i>zz</i>	real	undefined
<i>t33</i>	real	undefined

Summary Constant tensor value for the electrical conductivity

4.1.1199.Tensor Electrical Conductivity: Tensor String Function

Scope: Aria Material

Tensor Electrical Conductivity: Tensor String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Tensor_String_Function [F_Xx = *f_xx* |F_Yy = *f_yy* |F_Xy = *f_xy* |F_Zz = *f_zz* |F_Xz = *f_xz* |F_Yz = *f_yz* |F_Yx = *f_yx* |F_Zx = *f_zx* |F_Zy = *f_zy*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_{xx}</i>	"string"	undefined
<i>f_{yy}</i>	"string"	undefined
<i>f_{xy}</i>	"string"	undefined
<i>f_{zz}</i>	"string"	undefined
<i>f_{xz}</i>	"string"	undefined
<i>f_{yz}</i>	"string"	undefined
<i>f_{yx}</i>	"string"	undefined
<i>f_{zx}</i>	"string"	undefined
<i>f_{zy}</i>	"string"	undefined

Summary Value from a string function

4.1.1200.Tensor Electrical Conductivity: Tensor String Function Symmetric

Scope: Aria Material

Tensor Electrical Conductivity: Tensor String Function Symmetric [{of | species | subindex} *Species* | {in | material_phase} *MaterialPhase*] =
Tensor_String_Function_Symmetric [F_{Xx} = *f_{xx}* | F_{Yy} = *f_{yy}* | F_{Xy} = *f_{xy}* | F_{Zz} = *f_{zz}* | F_{Xz} = *f_{xz}* | F_{Yz} = *f_{yz}* | F_{Yx} = *f_{yx}* | F_{Zx} = *f_{zx}* | F_{Zy} = *f_{zy}*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_{xx}</i>	"string"	undefined
<i>f_{yy}</i>	"string"	undefined
<i>f_{xy}</i>	"string"	undefined
<i>f_{zz}</i>	"string"	undefined
<i>f_{xz}</i>	"string"	undefined
<i>f_{yz}</i>	"string"	undefined
<i>f_{yx}</i>	"string"	undefined
<i>f_{zx}</i>	"string"	undefined
<i>f_{zy}</i>	"string"	undefined

Summary Value from a string function

4.1.1201.Tensor Electromigration Coefficient

Scope: Aria Material

Tensor Electromigration Coefficient [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Xx = *xx* |T11 = *t11* |Xy = *xy* |T12 = *t12* |Xz = *xz* |T13 = *t13* |Yx = *yx* |T21 = *t21* |Yy = *yy* |T22 = *t22* |Yz = *yz* |T23 = *t23* |Zx = *zx* |T31 = *t31* |Zy = *zy* |T32 = *t32* |Zz = *zz* |T33 = *t33*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>xx</i>	real	undefined
<i>t11</i>	real	undefined
<i>xy</i>	real	undefined
<i>t12</i>	real	undefined
<i>xz</i>	real	undefined
<i>t13</i>	real	undefined
<i>yx</i>	real	undefined
<i>t21</i>	real	undefined
<i>yy</i>	real	undefined
<i>t22</i>	real	undefined
<i>yz</i>	real	undefined
<i>t23</i>	real	undefined
<i>zx</i>	real	undefined
<i>t31</i>	real	undefined
<i>zy</i>	real	undefined
<i>t32</i>	real	undefined
<i>zz</i>	real	undefined
<i>t33</i>	real	undefined

Summary Constant tensor value for the Soret coefficient

4.1.1202.Tensor Mass Diffusivity

Scope: Aria Material

Tensor Mass Diffusivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Xx = *xx* |T11 = *t11* |Xy = *xy* |T12 = *t12* |Xz = *xz* |T13 = *t13* |Yx = *yx* |T21 = *t21* |Yy = *yy* |T22 = *t22* |Yz = *yz* |T23 = *t23* |Zx = *zx* |T31 = *t31* |Zy = *zy* |T32 = *t32* |Zz = *zz* |T33 = *t33*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>xx</i>	real	undefined
<i>t11</i>	real	undefined
<i>xy</i>	real	undefined
<i>t12</i>	real	undefined
<i>xz</i>	real	undefined
<i>t13</i>	real	undefined
<i>yx</i>	real	undefined
<i>t21</i>	real	undefined
<i>yy</i>	real	undefined
<i>t22</i>	real	undefined
<i>yz</i>	real	undefined
<i>t23</i>	real	undefined
<i>zx</i>	real	undefined
<i>t31</i>	real	undefined
<i>zy</i>	real	undefined
<i>t32</i>	real	undefined
<i>zz</i>	real	undefined
<i>t33</i>	real	undefined

Summary Constant value

4.1.1203.Tensor Mass Diffusivity: User Plugin

Scope: Aria Material

Tensor Mass Diffusivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1204.Tensor Mass Diffusivity: Tensor String Function

Scope: Aria Material

Tensor Mass Diffusivity: Tensor String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Tensor_String_Function [

$F_{Xx} = f_{xx} \mid F_{Yy} = f_{yy} \mid F_{Xy} = f_{xy} \mid F_{Zz} = f_{zz} \mid F_{Xz} = f_{xz} \mid F_{Yz} = f_{yz} \mid F_{Yx} = f_{yx} \mid F_{Zx} = f_{zx} \mid F_{Zy} = f_{zy}]$

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_{xx}</i>	"string"	undefined
<i>f_{yy}</i>	"string"	undefined
<i>f_{xy}</i>	"string"	undefined
<i>f_{zz}</i>	"string"	undefined
<i>f_{xz}</i>	"string"	undefined
<i>f_{yz}</i>	"string"	undefined
<i>f_{yx}</i>	"string"	undefined
<i>f_{zx}</i>	"string"	undefined
<i>f_{zy}</i>	"string"	undefined

Summary Value from a string function

4.1.1205.Tensor Mass Diffusivity: Tensor String Function Symmetric

Scope: Aria Material

Tensor Mass Diffusivity: Tensor String Function Symmetric [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Tensor_String_Function_Symmetric [$F_{Xx} = f_{xx} \mid F_{Yy} = f_{yy} \mid F_{Xy} = f_{xy} \mid F_{Zz} = f_{zz} \mid F_{Xz} = f_{xz} \mid F_{Yz} = f_{yz}]$

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_{xx}</i>	"string"	undefined
<i>f_{yy}</i>	"string"	undefined
<i>f_{xy}</i>	"string"	undefined
<i>f_{zz}</i>	"string"	undefined
<i>f_{xz}</i>	"string"	undefined
<i>f_{yz}</i>	"string"	undefined

Summary Value from a string function

4.1.1206.Tensor Soret Coefficient

Scope: Aria Material

Tensor Soret Coefficient [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [$Xx = xx \mid T11 = t11 \mid Xy = xy \mid T12 = t12 \mid Xz = xz \mid T13 = t13 \mid Yx = yx \mid T21 = t21 \mid Yy = yy \mid T22 = t22 \mid$

Yz = yz | T23 = t_{23} | Zx = zx | T31 = t_{31} | Zy = zy | T32 = t_{32} | Zz = zz |
T33 = t_{33}]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
xx	real	undefined
t_{11}	real	undefined
xy	real	undefined
t_{12}	real	undefined
xz	real	undefined
t_{13}	real	undefined
yx	real	undefined
t_{21}	real	undefined
yy	real	undefined
t_{22}	real	undefined
yz	real	undefined
t_{23}	real	undefined
zx	real	undefined
t_{31}	real	undefined
zy	real	undefined
t_{32}	real	undefined
zz	real	undefined
t_{33}	real	undefined

Summary Constant tensor value for the Soret coefficient

4.1.1207.Tensor Species Diffusivity

Scope: Aria Material

Tensor Species Diffusivity [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Constant [Xx = xx | T11 = t_{11} | Xy = xy |
T12 = t_{12} | Xz = xz | T13 = t_{13} | Yx = yx | T21 = t_{21} | Yy = yy | T22 = t_{22} |
Yz = yz | T23 = t_{23} | Zx = zx | T31 = t_{31} | Zy = zy | T32 = t_{32} | Zz = zz |
T33 = t_{33}]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>xx</i>	real	undefined
<i>t11</i>	real	undefined
<i>xy</i>	real	undefined
<i>t12</i>	real	undefined
<i>xz</i>	real	undefined
<i>t13</i>	real	undefined
<i>yx</i>	real	undefined
<i>t21</i>	real	undefined
<i>yy</i>	real	undefined
<i>t22</i>	real	undefined
<i>yz</i>	real	undefined
<i>t23</i>	real	undefined
<i>zx</i>	real	undefined
<i>t31</i>	real	undefined
<i>zy</i>	real	undefined
<i>t32</i>	real	undefined
<i>zz</i>	real	undefined
<i>t33</i>	real	undefined

Summary Constant value

4.1.1208.Tensor Species Diffusivity: User Plugin

Scope: Aria Material

Tensor Species Diffusivity: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1209.Tensor Species Diffusivity: Tensor String Function

Scope: Aria Material

Tensor Species Diffusivity: Tensor String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Tensor_String_Function [

$F_{Xx} = f_{xx} \mid F_{Yy} = f_{yy} \mid F_{Xy} = f_{xy} \mid F_{Zz} = f_{zz} \mid F_{Xz} = f_{xz} \mid F_{Yz} = f_{yz} \mid F_{Yx} = f_{yx} \mid F_{Zx} = f_{zx} \mid F_{Zy} = f_{zy}]$

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_{xx}</i>	"string"	undefined
<i>f_{yy}</i>	"string"	undefined
<i>f_{xy}</i>	"string"	undefined
<i>f_{zz}</i>	"string"	undefined
<i>f_{xz}</i>	"string"	undefined
<i>f_{yz}</i>	"string"	undefined
<i>f_{yx}</i>	"string"	undefined
<i>f_{zx}</i>	"string"	undefined
<i>f_{zy}</i>	"string"	undefined

Summary Value from a string function

4.1.1210.Tensor Species Diffusivity: Tensor String Function Symmetric

Scope: Aria Material

Tensor Species Diffusivity: Tensor String Function Symmetric [{of|species |subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Tensor_String_Function_Symmetric [$F_{Xx} = f_{xx} \mid F_{Yy} = f_{yy} \mid F_{Xy} = f_{xy} \mid F_{Zz} = f_{zz} \mid F_{Xz} = f_{xz} \mid F_{Yz} = f_{yz}]$

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_{xx}</i>	"string"	undefined
<i>f_{yy}</i>	"string"	undefined
<i>f_{xy}</i>	"string"	undefined
<i>f_{zz}</i>	"string"	undefined
<i>f_{xz}</i>	"string"	undefined
<i>f_{yz}</i>	"string"	undefined

Summary Value from a string function

4.1.1211.Tensor Species Expansion Coeff

Scope: Aria Material

Tensor Species Expansion Coeff [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [$Xx = xx \mid T_{11} = t_{11} \mid Xy = xy \mid$

$T_{12} = t_{12} \mid X_z = xz \mid T_{13} = t_{13} \mid Y_x = yx \mid T_{21} = t_{21} \mid Y_y = yy \mid T_{22} = t_{22} \mid$
 $Y_z = yz \mid T_{23} = t_{23} \mid Z_x = zx \mid T_{31} = t_{31} \mid Z_y = zy \mid T_{32} = t_{32} \mid Z_z = zz \mid$
 $T_{33} = t_{33} \mid$

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>xx</i>	real	undefined
<i>t11</i>	real	undefined
<i>xy</i>	real	undefined
<i>t12</i>	real	undefined
<i>xz</i>	real	undefined
<i>t13</i>	real	undefined
<i>yx</i>	real	undefined
<i>t21</i>	real	undefined
<i>yy</i>	real	undefined
<i>t22</i>	real	undefined
<i>yz</i>	real	undefined
<i>t23</i>	real	undefined
<i>zx</i>	real	undefined
<i>t31</i>	real	undefined
<i>zy</i>	real	undefined
<i>t32</i>	real	undefined
<i>zz</i>	real	undefined
<i>t33</i>	real	undefined

Summary Constant tensor value for the stress coefficient due to species concentration.

4.1.1212.Tensor Species Mobility: Nernst Einstein

Scope: Aria Material

Tensor Species Mobility: Nernst Einstein [{of|species|subindex} *Species*
 |{in|material_phase} *MaterialPhase*]= Nernst_Einstein [R = *r* |
 Temperature_Material_Phase = *temperature_material_phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>r</i>	real	undefined
<i>temperature_material_phase</i>	"string"	undefined

Summary Tensor mobility from diffusivity, $M = D/(RT)$.

4.1.1213.Tensor Species Mobility

Scope: Aria Material

Tensor Species Mobility [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Xx = *xx* |T11 = *t11* |Xy = *xy* |T12 = *t12* |Xz = *xz* |T13 = *t13* |Yx = *yx* |T21 = *t21* |Yy = *yy* |T22 = *t22* |Yz = *yz* |T23 = *t23* |Zx = *zx* |T31 = *t31* |Zy = *zy* |T32 = *t32* |Zz = *zz* |T33 = *t33*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>xx</i>	real	undefined
<i>t11</i>	real	undefined
<i>xy</i>	real	undefined
<i>t12</i>	real	undefined
<i>xz</i>	real	undefined
<i>t13</i>	real	undefined
<i>yx</i>	real	undefined
<i>t21</i>	real	undefined
<i>yy</i>	real	undefined
<i>t22</i>	real	undefined
<i>yz</i>	real	undefined
<i>t23</i>	real	undefined
<i>zx</i>	real	undefined
<i>t31</i>	real	undefined
<i>zy</i>	real	undefined
<i>t32</i>	real	undefined
<i>zz</i>	real	undefined
<i>t33</i>	real	undefined

Summary Constant tensor value for the electrical conductivity

4.1.1214.Tensor Thermal Conductivity: Calore User Sub

Scope: Aria Material

Tensor Thermal Conductivity: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined

Summary Tensor values for the thermal conductivity from a calore user subroutine

4.1.1215.Tensor Thermal Conductivity

Scope: Aria Material

```
Tensor Thermal Conductivity [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]= Constant [ Xx = xx |T11 = t11 |Xy = xy |
T12 = t12 |Xz = xz |T13 = t13 |Yx = yx |T21 = t21 |Yy = yy |T22 = t22 |
Yz = yz |T23 = t23 |Zx = zx |T31 = t31 |Zy = zy |T32 = t32 |Zz = zz |
T33 = t33 ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>xx</i>	real	undefined
<i>t11</i>	real	undefined
<i>xy</i>	real	undefined
<i>t12</i>	real	undefined
<i>xz</i>	real	undefined
<i>t13</i>	real	undefined
<i>yx</i>	real	undefined
<i>t21</i>	real	undefined
<i>yy</i>	real	undefined
<i>t22</i>	real	undefined
<i>yz</i>	real	undefined
<i>t23</i>	real	undefined
<i>zx</i>	real	undefined
<i>t31</i>	real	undefined
<i>zy</i>	real	undefined
<i>t32</i>	real	undefined
<i>zz</i>	real	undefined
<i>t33</i>	real	undefined

Summary Constant tensor value for the thermal conductivity

4.1.1216.Tensor Thermal Conductivity: Mesh Input

Scope: Aria Material

Tensor Thermal Conductivity: Mesh Input [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Mesh_Input [Multiplier = *multiplier* |Name = *name* |Type = *type* |Axis1 = *axis1* |Axis2 = *axis2* |Tolerance = *tolerance*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>axis1</i>	"string"	undefined
<i>axis2</i>	"string"	undefined
<i>tolerance</i>	real	undefined

Summary Tensor thermal conductivity from the input mesh database

4.1.1217.Tensor Thermal Conductivity: Mass Average

Scope: Aria Material

Tensor Thermal Conductivity: Mass Average [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Mass_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Thermal conductivity computed from mass average of species conductivities

4.1.1218.Tensor Thermal Conductivity: Summed

Scope: Aria Material

Tensor Thermal Conductivity: Summed [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Summed [Contributions = *contributions*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>contributions</i>	"string"	undefined

Summary Tensor thermal conductivity as a sum of user-specified conductivities

4.1.1219.Tensor Thermal Conductivity: Level Set Aligned

Scope: Aria Material

Tensor Thermal Conductivity: Level Set Aligned [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]= Level_Set_Aligned [K_Normal
= *k_normal* |K_Tangent = *k_tangent* |Level_Set_Subindex = *level_set_subindex*
]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>k_normal</i>	real	undefined
<i>k_tangent</i>	real	undefined
<i>level_set_subindex</i>	integer	undefined

Summary Tensor values for the thermal conductivity aligned to a level set field

4.1.1220.Tensor Thermal Conductivity: Tensor String Function

Scope: Aria Material

Tensor Thermal Conductivity: Tensor String Function [{of|species|
subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Tensor_String_Function [F_Xx = *f_xx* |F_Yy = *f_yy* |F_Xy = *f_xy* |F_Zz =
f_zz |F_Xz = *f_xz* |F_Yz = *f_yz* |F_Yx = *f_yx* |F_Zx = *f_zx* |F_Zy = *f_zy*
]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_xx</i>	"string"	undefined
<i>f_yy</i>	"string"	undefined
<i>f_xy</i>	"string"	undefined
<i>f_zz</i>	"string"	undefined
<i>f_xz</i>	"string"	undefined
<i>f_yz</i>	"string"	undefined
<i>f_yx</i>	"string"	undefined
<i>f_zx</i>	"string"	undefined
<i>f_zy</i>	"string"	undefined

Summary Value from a string function

4.1.1221.Tensor Thermal Conductivity: Tensor String Function Symmetric

Scope: Aria Material

Tensor Thermal Conductivity: Tensor String Function Symmetric [{of | species | subindex} *Species* | {in | material_phase} *MaterialPhase*] = Tensor_String_Function_Symmetric [F_Xx = *f_xx* | F_Yy = *f_yy* | F_Xy = *f_xy* | F_Zz = *f_zz* | F_Xz = *f_xz* | F_Yz = *f_yz* | F_Yx = *f_yx* | F_Zx = *f_zx* | F_Zy = *f_zy*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_xx</i>	"string"	undefined
<i>f_yy</i>	"string"	undefined
<i>f_xy</i>	"string"	undefined
<i>f_zz</i>	"string"	undefined
<i>f_xz</i>	"string"	undefined
<i>f_yz</i>	"string"	undefined
<i>f_yx</i>	"string"	undefined
<i>f_zx</i>	"string"	undefined
<i>f_zy</i>	"string"	undefined

Summary Value from a string function

4.1.1222.Thermal Conductivity

Scope: Aria Material

Thermal Conductivity [{of | species | subindex} *Species* | {in | material_phase} *MaterialPhase*] = Constant [Value = *value* | K = *k*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>k</i>	real	undefined

Summary Constant value

4.1.1223.Thermal Conductivity: Copied

Scope: Aria Material

Thermal Conductivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1224.Thermal Conductivity: User Plugin

Scope: Aria Material

Thermal Conductivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.1225.Thermal Conductivity: Scalar String Function

Scope: Aria Material

Thermal Conductivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1226.Thermal Conductivity: Calore User Sub

Scope: Aria Material

Thermal Conductivity: Calore User Sub [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* | Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

4.1.1227.Thermal Conductivity: Cantera

Scope: Aria Material

Thermal Conductivity: Cantera [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Cantera [Poffset = *poffset*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>poffset</i>	real	undefined

Summary Cantera thermal conductivity

4.1.1228.Thermal Conductivity: Curing Foam

Scope: Aria Material

Thermal Conductivity: Curing Foam [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Curing_Foam []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1229.Thermal Conductivity: From Prandtl

Scope: Aria Material

Thermal Conductivity: From Prandtl [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Prandtl []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary ?

4.1.1230.Thermal Conductivity: Optically Thick

Scope: Aria Material

Thermal Conductivity: Optically Thick [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Optically_Thick [K = *k* |Beta_R = *beta_r* |N = *n*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>k</i>	real	undefined
<i>beta_r</i>	real	undefined
<i>n</i>	real	undefined

Summary Thermal conductivity model for optically thick materials

4.1.1231.Thermal Conductivity: Phase Average

Scope: Aria Material

Thermal Conductivity: Phase Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Phase_Average [Subindex_A = *subindex_a* |Subindex_B = *subindex_b*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>subindex_a</i>	integer	undefined
<i>subindex_b</i>	integer	undefined

Summary Phase-averaged values

4.1.1232.Thermal Conductivity: Interpolated Phase Average

Scope: Aria Material

Thermal Conductivity: Interpolated Phase Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Interpolated_Phase_Average [Subindex_A = *subindex_a* |Subindex_B = *subindex_b*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>subindex_a</i>	integer	undefined
<i>subindex_b</i>	integer	undefined

Summary Phase-averaged values

4.1.1233.Thermal Conductivity: Power Law

Scope: Aria Material

Thermal Conductivity: Power Law [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Power_Law [A = *a* |Gamma = *gamma*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>a</i>	real	undefined
<i>gamma</i>	real	undefined

Summary Thermal conductivity as a power law in temperature, $k = aT^\gamma$

4.1.1234.Thermal Conductivity: Saturation Power Law

Scope: Aria Material

Thermal Conductivity: Saturation Power Law [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Saturation_Power_Law [K_Dry = *k_dry* |K_Wet = *k_wet* |Power = *power*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>k_dry</i>	real	undefined
<i>k_wet</i>	real	undefined
<i>power</i>	real	undefined

Summary Thermal conductivity as a power law in liquid saturation for two phase porous flows

4.1.1235. Thermal Conductivity: Thermal

Scope: Aria Material

Thermal Conductivity: Thermal [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Thermal [A = *a* | B = *b* | C = *c* | D = *d*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>a</i>	real	undefined
<i>b</i>	real	undefined
<i>c</i>	real	undefined
<i>d</i>	real	undefined

Summary Thermal conductivity as a cubic polynomial in temperature

4.1.1236. Thermal Conductivity: T Exponent

Scope: Aria Material

Thermal Conductivity: T Exponent [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= T_Exponent [K_Ref = *k_ref* | T_Ref = *t_ref* | N = *n*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>k_ref</i>	real	undefined
<i>t_ref</i>	real	undefined
<i>n</i>	real	undefined

Summary Thermal conductivity as a power of normalized temperature

4.1.1237. Thermal Conductivity: Volume Average

Scope: Aria Material

Thermal Conductivity: Volume Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Volume_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Thermal conductivity computed from volume average of species thermal conductivities

4.1.1238.Thermal Conductivity: Summed

Scope: Aria Material

Thermal Conductivity: Summed [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Summed [Contributions = *contributions*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>contributions</i>	"string"	undefined

Summary Thermal conductivity as a sum of user-specified conductivities

4.1.1239.Thermal Conductivity: Activation User Function

Scope: Aria Material

Thermal Conductivity: Activation User Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Activation_User_Function [Background = *background* |Name = *name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>background</i>	real	undefined
<i>name</i>	"string"	undefined

Summary Temperature user function thermal conductivity model activated by an activation Field.

4.1.1240.Thermal Conductivity: Linear Temperature And Density

Scope: Aria Material

Thermal Conductivity: Linear Temperature And Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Linear_Temperature_And_Density [C_0 = *c_0* |C_Rho = *C_rho* |C_T = *c_t*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>c_0</i>	real	undefined
<i>C_rho</i>	real	undefined
<i>c_t</i>	real	undefined

Summary Thermal conductivity that is a linear function of both temperature and density.
$$\kappa = C_0 + C_\rho \rho + C_T T$$

4.1.1241. Thermal Conductivity: Mass Average

Scope: Aria Material

Thermal Conductivity: Mass Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mass_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Thermal conductivity computed from mass average of species conductivities

4.1.1242. Thermal Conductivity: Porous Arithmetic Mixture

Scope: Aria Material

Thermal Conductivity: Porous Arithmetic Mixture [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous_Arithmetic_Mixture [Liquid_Phase_Name = *Liquid_Phase_Name* | Gas_Phase_Name = *Gas_Phase_Name* | Initial_Saturation = *Initial_Saturation* | Melt_Dt = *melt_DT*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Liquid_Phase_Name</i>	"string"	undefined
<i>Gas_Phase_Name</i>	"string"	undefined
<i>Initial_Saturation</i>	real	undefined
<i>melt_DT</i>	real	undefined

Summary Thermal conductivity computed arithmetic mean of phase properties

4.1.1243. Thermal Conductivity: Porous Harmonic Mixture

Scope: Aria Material

Thermal Conductivity: Porous Harmonic Mixture [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous_Harmonic_Mixture [Liquid_Phase_Name = *Liquid_Phase_Name* | Gas_Phase_Name = *Gas_Phase_Name* | Initial_Saturation = *Initial_Saturation* | Melt_Dt = *melt_DT*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Liquid_Phase_Name</i>	"string"	undefined
<i>Gas_Phase_Name</i>	"string"	undefined
<i>Initial_Saturation</i>	real	undefined
<i>melt_DT</i>	real	undefined

Summary Thermal conductivity computed harmonic mean of phase properties

4.1.1244. Thermal Conductivity: Porous Geometric Mixture

Scope: Aria Material

Thermal Conductivity: Porous Geometric Mixture [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous_Geometric_Mixture [Liquid_Phase_Name = *Liquid_Phase_Name* | Gas_Phase_Name = *Gas_Phase_Name* | Initial_Saturation = *Initial_Saturation* | Melt_Dt = *melt_DT*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Liquid_Phase_Name</i>	"string"	undefined
<i>Gas_Phase_Name</i>	"string"	undefined
<i>Initial_Saturation</i>	real	undefined
<i>melt_DT</i>	real	undefined

Summary Thermal conductivity computed geometric mean of phase properties

4.1.1245. Thermal Conductivity: Porous Emt Mixture

Scope: Aria Material

Thermal Conductivity: Porous Emt Mixture [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous_Emt_Mixture [Liquid_Phase_Name = *Liquid_Phase_Name* | Gas_Phase_Name = *Gas_Phase_Name* | Initial_Saturation = *Initial_Saturation* | Melt_Dt = *melt_DT*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Liquid_Phase_Name</i>	"string"	undefined
<i>Gas_Phase_Name</i>	"string"	undefined
<i>Initial_Saturation</i>	real	undefined
<i>melt_DT</i>	real	undefined

Summary Thermal conductivity computed effective medium theory model

4.1.1246.Thermal Conductivity: Fortran

Scope: Aria Material

Thermal Conductivity: Fortran [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Fortran [Multiplier = *multiplier* | Sub_Name = *sub_name* | Real_Data = *real_data* | Int_Data = *int_data* | Resource_Name = *resource_name* | Data = *data*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>sub_name</i>	"string"	undefined
<i>real_data</i>	"string"	undefined
<i>int_data</i>	"string"	undefined
<i>resource_name</i>	"string"	undefined
<i>data</i>	"string"	undefined

Summary Fortran subroutine thermal conductivity.

4.1.1247.Thermal Diffusivity

Scope: Aria Material

Thermal Diffusivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* | D = *d*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>d</i>	real	undefined

Summary Constant value

4.1.1248.Thermal Diffusivity: Copied

Scope: Aria Material

Thermal Diffusivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1249.Thermal Diffusivity: User Plugin

Scope: Aria Material

Thermal Diffusivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1250.Thermal Diffusivity: Scalar String Function

Scope: Aria Material

Thermal Diffusivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F =
f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1251.Thermal Diffusivity: Calore User Sub

Scope: Aria Material

Thermal Diffusivity: Calore User Sub [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Calore_User_Sub [Name = *name* |Type =
type |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |
Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Calore user subroutine for the thermal diffusivity

4.1.1252.Thermodynamic Pressure

Scope: Aria Material

Thermodynamic Pressure [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1253.Thermodynamic Pressure: Copied

Scope: Aria Material

Thermodynamic Pressure: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1254.Thermodynamic Pressure: User Plugin

Scope: Aria Material

Thermodynamic Pressure: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.1255.Thermodynamic Pressure: Scalar String Function

Scope: Aria Material

Thermodynamic Pressure: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1256.Tic Drag: Basic

Scope: Aria Material

Tic Drag: Basic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Basic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Model for drag created in the Theory of Interacting Continua

4.1.1257.Tic Drag Coeff

Scope: Aria Material

Tic Drag Coeff [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Alpha_Tic = *alpha_TIC*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>alpha_TIC</i>	real	undefined

Summary Constant value

4.1.1258.Tic Drag Coeff: Copied

Scope: Aria Material

Tic Drag Coeff: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1259.Tic Drag Coeff: User Plugin

Scope: Aria Material

Tic Drag Coeff: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1260.Tic Drag Coeff: Scalar String Function

Scope: Aria Material

Tic Drag Coeff: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1261.Time Derivative: Calculated

Scope: Aria Material

Time Derivative: Calculated [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Calculated [Variable = *variable* | Max_Order = *max_order*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>variable</i>	"string"	undefined
<i>max_order</i>	integer	undefined

Summary Calculated time derivative of any expression. This is done by default using a first-order time integration scheme (new - old)/dt To use the same order as the overall solve, set max_order > 1

4.1.1262.Tortuosity Factor

Scope: Aria Material

Tortuosity Factor [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1263.Tortuosity Factor: Copied

Scope: Aria Material

Tortuosity Factor: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1264.Tortuosity Factor: User Plugin

Scope: Aria Material

Tortuosity Factor: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1265.Tortuosity Factor: Scalar String Function

Scope: Aria Material

Tortuosity Factor: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1266.Tortuosity Factor: Bruggeman

Scope: Aria Material

Tortuosity Factor: Bruggeman [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Bruggeman [Exponent = *exponent* | Multiplier = *multiplier* | Omit_Saturation = *omit_saturation*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>exponent</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>omit_saturation</i>	integer	undefined

Summary Bruggeman model for tortuosity factor. $\tau = \frac{1}{a\phi^n}$ with a default value of $n = 0.5$ and $a = 1$. Set alternate values for them with the 'exponent' and 'multiplier' arguments, respectively.

4.1.1267.Tortuosity Factor: Lanfrey

Scope: Aria Material

Tortuosity Factor: Lanfrey [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Lanfrey [Sphericity = *sphericity* | Min_Porosity = *min_porosity*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>sphericity</i>	real	undefined
<i>min_porosity</i>	real	undefined

Summary This model has been deprecated and removed from the code.

4.1.1268.Tortuosity Factor: Comiti

Scope: Aria Material

Tortuosity Factor: Comiti [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Comiti [Min_Porosity = *min_porosity*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>min_porosity</i>	real	undefined

Summary This model has been deprecated and removed from the code.

4.1.1269.Total Internal Energy

Scope: Aria Material

Total Internal Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1270.Total Internal Energy: Copied

Scope: Aria Material

Total Internal Energy: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1271.Total Internal Energy: User Plugin

Scope: Aria Material

Total Internal Energy: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1272.Total Internal Energy: Scalar String Function

Scope: Aria Material

Total Internal Energy: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1273.Total Internal Energy: Porous Flow

Scope: Aria Material

Total Internal Energy: Porous Flow [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous_Flow []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Total internal energy for porous flow

4.1.1274.Transition Reynolds Number: Correlation

Scope: Aria Material

Transition Reynolds Number: Correlation [{of|species|subindex} *Species*]= Correlation [Rex = *Rex* |Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>Rex</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation Reynolds number computed from material properties

4.1.1275.Transport Cross Section

Scope: Aria Material

Transport Cross Section [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Trans = *trans*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>trans</i>	real	undefined

Summary Constant value

4.1.1276.Transport Cross Section: Copied

Scope: Aria Material

Transport Cross Section: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1277.Transport Cross Section: User Plugin

Scope: Aria Material

Transport Cross Section: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1278.Transport Cross Section: Scalar String Function

Scope: Aria Material

Transport Cross Section: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1279.Transport Cross Section: Linearized

Scope: Aria Material

Transport Cross Section: Linearized [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Linearized [Sigma_0 = *sigma_0* | D_Sigma_D_Rho = *d_sigma_d_rho* |D_Sigma_D_T = *d_sigma_d_t* |T_Sigma_0 = *t_sigma_0* |Rho_Sigma_0 = *rho_sigma_0*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>sigma_0</i>	real	undefined
<i>d_sigma_d_rho</i>	real	undefined
<i>d_sigma_d_t</i>	real	undefined
<i>t_sigma_0</i>	real	undefined
<i>rho_sigma_0</i>	real	undefined

Summary Linearized transport cross section

4.1.1280.Transported Enthalpy: Standard

Scope: Aria Material

Transported Enthalpy: Standard [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Standard []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Transported quantity for porous enthalpy equation

4.1.1281.Transported Enthalpy: Porous

Scope: Aria Material

Transported Enthalpy: Porous [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Porous []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Transported quantity for porous enthalpy equation

4.1.1282.Turbulence Dissipation Rate

Scope: Aria Material

Turbulence Dissipation Rate [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1283.Turbulence Dissipation Rate: Copied

Scope: Aria Material

Turbulence Dissipation Rate: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1284.Turbulence Dissipation Rate: User Plugin

Scope: Aria Material

Turbulence Dissipation Rate: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.1285.Turbulence Dissipation Rate: Scalar String Function

Scope: Aria Material

Turbulence Dissipation Rate: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1286.Turbulence Dissipation Rate Diffusive Flux: Basic

Scope: Aria Material

Turbulence Dissipation Rate Diffusive Flux: Basic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Basic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Basic model of turbulence dissipation rate diffusive flux

4.1.1287.Turbulent Bulk Viscosity

Scope: Aria Material

Turbulent Bulk Viscosity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Kappa = *kappa*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>kappa</i>	real	undefined

Summary Constant value

4.1.1288.Turbulent Bulk Viscosity: Copied

Scope: Aria Material

Turbulent Bulk Viscosity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1289.Turbulent Bulk Viscosity: User Plugin

Scope: Aria Material

Turbulent Bulk Viscosity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |*magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1290.Turbulent Bulk Viscosity: Scalar String Function

Scope: Aria Material

Turbulent Bulk Viscosity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1291.Turbulent Correlation Heat Transfer Coefficient: Correlation

Scope: Aria Material

Turbulent Correlation Heat Transfer Coefficient: Correlation [{of|species|subindex} *Species*]= Correlation [Number = *number* |Rex = *Rex* | Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>number</i>	integer	undefined
<i>Rex</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation based heat transfer coefficient

4.1.1292.Turbulent Energy Diffusive Flux: Gradient Transport

Scope: Aria Material

Turbulent Energy Diffusive Flux: Gradient Transport [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Gradient_Transport []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Gradient transport model of turbulent energy diffusive flux

4.1.1293.Turbulent Kinetic Energy

Scope: Aria Material

Turbulent Kinetic Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1294.Turbulent Kinetic Energy: Copied

Scope: Aria Material

Turbulent Kinetic Energy: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1295.Turbulent Kinetic Energy: User Plugin

Scope: Aria Material

Turbulent Kinetic Energy: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1296.Turbulent Kinetic Energy: Scalar String Function

Scope: Aria Material

Turbulent Kinetic Energy: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1297.Turbulent Kinetic Energy Density

Scope: Aria Material

Turbulent Kinetic Energy Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1298.Turbulent Kinetic Energy Density: Copied

Scope: Aria Material

Turbulent Kinetic Energy Density: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1299.Turbulent Kinetic Energy Density: User Plugin

Scope: Aria Material

Turbulent Kinetic Energy Density: User Plugin [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.1300.Turbulent Kinetic Energy Density: Scalar String Function

Scope: Aria Material

Turbulent Kinetic Energy Density: Scalar String Function [{of|species|
subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1301.Turbulent Kinetic Energy Diffusive Flux: Basic

Scope: Aria Material

Turbulent Kinetic Energy Diffusive Flux: Basic [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]= Basic []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Basic model of turbulent kinetic energy diffusive flux

4.1.1302.Turbulent Mass Diffusivity

Scope: Aria Material

Turbulent Mass Diffusivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Dt = *Dt*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>Dt</i>	real	undefined

Summary Constant value

4.1.1303.Turbulent Mass Diffusivity: Copied

Scope: Aria Material

Turbulent Mass Diffusivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1304.Turbulent Mass Diffusivity: User Plugin

Scope: Aria Material

Turbulent Mass Diffusivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1305.Turbulent Mass Diffusivity: Scalar String Function

Scope: Aria Material

Turbulent Mass Diffusivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1306.Turbulent Mass Diffusivity: From Schmidt

Scope: Aria Material

Turbulent Mass Diffusivity: From Schmidt [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Schmidt []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Turbulent mass diffusivity from Schmidt number and viscosity

4.1.1307.Turbulent Mass Fraction Diffusive Flux: Gradient Transport

Scope: Aria Material

Turbulent Mass Fraction Diffusive Flux: Gradient Transport [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Gradient_Transport []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Gradient transport model of turbulent mass fraction diffusive flux

4.1.1308.Turbulent Mixture Fraction Diffusive Flux: Gradient Transport

Scope: Aria Material

Turbulent Mixture Fraction Diffusive Flux: Gradient Transport [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Gradient_Transport []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Gradient transport model of turbulent mixture fraction diffusive flux

4.1.1309.Turbulent Mixture Fraction Diffusivity

Scope: Aria Material

Turbulent Mixture Fraction Diffusivity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Dt = *Dt*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>Dt</i>	real	undefined

Summary Constant value

4.1.1310.Turbulent Mixture Fraction Diffusivity: Copied

Scope: Aria Material

Turbulent Mixture Fraction Diffusivity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1311.Turbulent Mixture Fraction Diffusivity: User Plugin

Scope: Aria Material

Turbulent Mixture Fraction Diffusivity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = Name |magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.1312.Turbulent Mixture Fraction Diffusivity: Scalar String Function

Scope: Aria Material

Turbulent Mixture Fraction Diffusivity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1313.Turbulent Mixture Fraction Diffusivity: From Schmidt

Scope: Aria Material

Turbulent Mixture Fraction Diffusivity: From Schmidt [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Schmidt []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Turbulent mixture fraction diffusivity from trb Schmidt number and trb viscosity

4.1.1314.Turbulent Momentum Stress

Scope: Aria Material

Turbulent Momentum Stress [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Xx = *xx* |T11 = *t11* |Xy = *xy* |T12 = *t12* |Xz = *xz* |T13 = *t13* |Yx = *yx* |T21 = *t21* |Yy = *yy* |T22 = *t22* |Yz = *yz* |T23 = *t23* |Zx = *zx* |T31 = *t31* |Zy = *zy* |T32 = *t32* |Zz = *zz* |T33 = *t33*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>xx</i>	real	undefined
<i>t11</i>	real	undefined
<i>xy</i>	real	undefined
<i>t12</i>	real	undefined
<i>xz</i>	real	undefined
<i>t13</i>	real	undefined
<i>yx</i>	real	undefined
<i>t21</i>	real	undefined
<i>yy</i>	real	undefined
<i>t22</i>	real	undefined
<i>yz</i>	real	undefined
<i>t23</i>	real	undefined
<i>zx</i>	real	undefined
<i>t31</i>	real	undefined
<i>zy</i>	real	undefined
<i>t32</i>	real	undefined
<i>zz</i>	real	undefined
<i>t33</i>	real	undefined

Summary Constant value

4.1.1315.Turbulent Momentum Stress: User Plugin

Scope: Aria Material

Turbulent Momentum Stress: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |*magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1316.Turbulent Momentum Stress: Tensor String Function

Scope: Aria Material

Turbulent Momentum Stress: Tensor String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Tensor_String_Function [F_Xx = f_{xx} |F_Yy = f_{yy} |F_Xy = f_{xy} |F_Zz = f_{zz} |F_Xz = f_{xz} |F_Yz = f_{yz} |F_Yx = f_{yx} |F_Zx = f_{zx} |F_Zy = f_{zy}]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f_{xx}	"string"	undefined
f_{yy}	"string"	undefined
f_{xy}	"string"	undefined
f_{zz}	"string"	undefined
f_{xz}	"string"	undefined
f_{yz}	"string"	undefined
f_{yx}	"string"	undefined
f_{zx}	"string"	undefined
f_{zy}	"string"	undefined

Summary Value from a string function

4.1.1317.Turbulent Momentum Stress: Tensor String Function Symmetric

Scope: Aria Material

Turbulent Momentum Stress: Tensor String Function Symmetric [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Tensor_String_Function_Symmetric [F_Xx = f_{xx} |F_Yy = f_{yy} |F_Xy = f_{xy} |F_Zz = f_{zz} |F_Xz = f_{xz} |F_Yz = f_{yz}]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f_{xx}	"string"	undefined
f_{yy}	"string"	undefined
f_{xy}	"string"	undefined
f_{zz}	"string"	undefined
f_{xz}	"string"	undefined
f_{yz}	"string"	undefined

Summary Value from a string function

4.1.1318.Turbulent Momentum Stress: Formal Newtonian Isotropic

Scope: Aria Material

Turbulent Momentum Stress: Formal Newtonian Isotropic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Formal_Newtonian_Isotropic [Reference_Frame = *reference_frame*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>reference_frame</i>	"string"	undefined

4.1.1319.Turbulent Momentum Stress: Incompressible Newtonian Isotropic

Scope: Aria Material

Turbulent Momentum Stress: Incompressible Newtonian Isotropic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Incompressible_Newtonian_Isotropic [Reference_Frame = *reference_frame*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>reference_frame</i>	"string"	undefined

4.1.1320.Turbulent Momentum Stress: Newtonian Dilational Isotropic

Scope: Aria Material

Turbulent Momentum Stress: Newtonian Dilational Isotropic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Newtonian_Dilational_Isotropic [Reference_Frame = *reference_frame*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>reference_frame</i>	"string"	undefined

4.1.1321.Turbulent Momentum Stress: Newtonian Isotropic

Scope: Aria Material

Turbulent Momentum Stress: Newtonian Isotropic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Newtonian_Isotropic [Reference_Frame = *reference_frame*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>reference_frame</i>	"string"	undefined

4.1.1322.Turbulent Prandtl Number

Scope: Aria Material

Turbulent Prandtl Number [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Pr_T = *Pr_t*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>Pr_t</i>	real	undefined

Summary Constant value

4.1.1323.Turbulent Prandtl Number: Copied

Scope: Aria Material

Turbulent Prandtl Number: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1324.Turbulent Prandtl Number: User Plugin

Scope: Aria Material

Turbulent Prandtl Number: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1325.Turbulent Prandtl Number: Scalar String Function

Scope: Aria Material

Turbulent Prandtl Number: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1326.Turbulent Schmidt Number

Scope: Aria Material

Turbulent Schmidt Number [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value* | Sc_T = *Sc_t*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>Sc_t</i>	real	undefined

Summary Constant value

4.1.1327.Turbulent Schmidt Number: Copied

Scope: Aria Material

Turbulent Schmidt Number: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1328.Turbulent Schmidt Number: User Plugin

Scope: Aria Material

Turbulent Schmidt Number: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1329.Turbulent Schmidt Number: Scalar String Function

Scope: Aria Material

Turbulent Schmidt Number: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1330.Turbulent Thermal Conductivity: From Prandtl

Scope: Aria Material

Turbulent Thermal Conductivity: From Prandtl [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]= From_Prandtl []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Turbulent thermal conductivity when closing energy term by grad T

4.1.1331.Turbulent Thermal Diffusivity: From Prandtl

Scope: Aria Material

Turbulent Thermal Diffusivity: From Prandtl [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]= From_Prandtl []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary ?

4.1.1332.Use Data Block

Scope: Aria Material

Use Data Block *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Reference to predefined data to be used by the user subroutine. These values may be changed by the user subroutine.

4.1.1333User Expression

Scope: Aria Material

User Expression [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [User_Tag = *user_tag* |Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>user_tag</i>	"string"	undefined
<i>value</i>	real	undefined

Summary Constant user expression

4.1.1334User Expression: Scalar String Function

Scope: Aria Material

User Expression: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [User_Tag = *user_tag* |F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>user_tag</i>	"string"	undefined
<i>f</i>	"string"	undefined

Summary String function user expression

4.1.1335Valence

Scope: Aria Material

Valence [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Z = *z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>z</i>	real	undefined

Summary Constant value

4.1.1336.Valence: Copied

Scope: Aria Material

Valence: Copied [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1337.Valence: User Plugin

Scope: Aria Material

Valence: User Plugin [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1338.Valence: Scalar String Function

Scope: Aria Material

Valence: Scalar String Function [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1339.Velocity: Melting Capillary Darcy

Scope: Aria Material

Velocity: Melting Capillary Darcy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Melting_Capillary_Darcy [Melt_Dt = *melt_DT* |Melt_Time = *melt_time* |Gx = *gx* |Gy = *gy* |Gz = *gz*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>melt_DT</i>	real	undefined
<i>melt_time</i>	real	undefined
<i>gx</i>	real	undefined
<i>gy</i>	real	undefined
<i>gz</i>	real	undefined

4.1.1340.Velocity: Darcy

Scope: Aria Material

Velocity: Darcy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Darcy [Gx = *gx* |Gy = *gy* |Gz = *gz* |Relative_To = *relative_to*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>gx</i>	real	undefined
<i>gy</i>	real	undefined
<i>gz</i>	real	undefined
<i>relative_to</i>	"string"	undefined

Summary This model is designed to provide the normalized fluid velocity within a matrix that itself may be moving. If the matrix phase has a velocity the fluid velocity returned will be in the lab frame. If not relative phase is provided, the matrix phase is assumed to have a velocity of zero. $u_g = v_r \phi - \frac{k_r}{\mu} \mathbf{K}_i (\nabla P_g - \rho_g \vec{g})$

4.1.1341.Velocity: Darcy Solvent

Scope: Aria Material

Velocity: Darcy Solvent [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Darcy_Solvent [Gx = *gx* |Gy = *gy* |Gz = *gz* |Relative_To = *relative_to*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>gx</i>	real	undefined
<i>gy</i>	real	undefined
<i>gz</i>	real	undefined
<i>relative_to</i>	"string"	undefined

Summary This model is intended for problems where the porous species equation is being solved for pressure with a solvent species concentration as the mass term in order to solve for the velocity of that solvent species.

4.1.1342.Velocity: Schloegl

Scope: Aria Material

Velocity: Schloegl [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Schloegl [K_Phi = *k_phi* |F = *f* |Gx = *gx* |Gy = *gy* |Gz = *gz* |Proton_Name = *proton_name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>k_phi</i>	real	undefined
<i>f</i>	real	undefined
<i>gx</i>	real	undefined
<i>gy</i>	real	undefined
<i>gz</i>	real	undefined
<i>proton_name</i>	"string"	undefined

4.1.1343.Velocity: From Mesh Displacement

Scope: Aria Material

Velocity: From Mesh Displacement [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Mesh_Displacement []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

4.1.1344.Velocity

Scope: Aria Material

Velocity [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [X = *x* |Y = *y* |Z = *z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>x</i>	real	undefined
<i>y</i>	real	undefined
<i>z</i>	real	undefined

Summary Constant value

4.1.1345.Velocity: User Plugin

Scope: Aria Material

Velocity: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1346.Velocity: Vector String Function

Scope: Aria Material

Velocity: Vector String Function [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Vector_String_Function [F_X = *f_x* |F_Y =
f_y |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

4.1.1347.Velocity Flux

Scope: Aria Material

Velocity Flux [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1348.Velocity Flux: Copied

Scope: Aria Material

Velocity Flux: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1349.Velocity Flux: User Plugin

Scope: Aria Material

Velocity Flux: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1350.Velocity Flux: Scalar String Function

Scope: Aria Material

Velocity Flux: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1351.Venting Volumetric Flow Rate

Scope: Aria Material

Venting Volumetric Flow Rate [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1352.Venting Volumetric Flow Rate: Copied

Scope: Aria Material

Venting Volumetric Flow Rate: Copied [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1353.Venting Volumetric Flow Rate: User Plugin

Scope: Aria Material

Venting Volumetric Flow Rate: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.1354.Venting Volumetric Flow Rate: Scalar String Function

Scope: Aria Material

Venting Volumetric Flow Rate: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1355.Venting Volumetric Flow Rate: K Factor

Scope: Aria Material

Venting Volumetric Flow Rate: K Factor [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= K_Factor [Flow_Rate_Limiter = *flow_rate_limiter*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>flow_rate_limiter</i>	real	undefined

Summary Volumetric flow rate, Q , calculated as $Q = K \sqrt{\frac{P - P_{ambient}}{\rho}}$. Absent any other sources, the maximum flow rate is defined based on the mass loss to achieve pressure equilibrium and the fluid time step. If the optional flow rate limiter is specified, the flow rate is limited by the product of the limiter factor and the maximum flow rate without any other sources.

4.1.1356 Venting Volumetric Flow Rate: K Factor With Choking

Scope: Aria Material

Venting Volumetric Flow Rate: K Factor With Choking [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] =
 K_Factor_With_Choking [Critical_Pressure_Ratio = *critical_pressure_ratio* |
 Flow_Rate_Limiter = *flow_rate_limiter*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>critical_pressure_ratio</i>	real	undefined
<i>flow_rate_limiter</i>	real	undefined

Summary Volumetric flow rate, Q , calculated as $Q = K \sqrt{\frac{P - P_{ambient}}{\rho}}$ for $\frac{P}{P_{ambient}} < R_p$, where R_p is the critical_pressure_ratio. Above R_p the flow rate is calculated as $Q = K \sqrt{\frac{P_{high}(1 - 1/R_p)}{\rho}}$. Absent any other sources, the maximum flow rate is defined based on the mass loss to achieve pressure equilibrium and the fluid time step. If the optional flow rate limiter is specified, the flow rate is limited by the product of the limiter factor and the maximum flow rate without any other sources.

4.1.1357 Viscosity

Scope: Aria Material

Viscosity [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] = Constant [Value = *value* | Mu = *mu*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>mu</i>	real	undefined

Summary Constant value

4.1.1358.Viscosity: Copied

Scope: Aria Material

Viscosity: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1359.Viscosity: User Plugin

Scope: Aria Material

Viscosity: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1360.Viscosity: Scalar String Function

Scope: Aria Material

Viscosity: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1361Viscosity: Arrhenius

Scope: Aria Material

Viscosity: Arrhenius [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Arrhenius [Mu0 = *mu0* |E = *e* |Mu_Max = *mu_max*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>mu0</i>	real	undefined
<i>e</i>	real	undefined
<i>mu_max</i>	real	undefined

Summary A viscosity model dependent on the temperature T

$$\mu(T) = \mu_0 e^{-E/T}, \quad (4.1)$$

where μ_0 and E are model parameters.

4.1.1362Viscosity: Arrhenius Carreau

Scope: Aria Material

Viscosity: Arrhenius Carreau [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Arrhenius_Carreau [Mu_Zero = *mu_zero* | Mu_Inf = *mu_inf* |N = *n* |A = *a* |Lambda = *lambda* |K = *k* |T_Ref = *t_ref* | Skip_Sensitivities = *skip_sensitivities* |Sensitivity_Scaling = *sensitivity_scaling* |Ramp_Sensitivities_Over_Time = *ramp_sensitivities_over_time*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>mu_zero</i>	real	undefined
<i>mu_inf</i>	real	undefined
<i>n</i>	real	undefined
<i>a</i>	real	undefined
<i>lambda</i>	real	undefined
<i>k</i>	real	undefined
<i>t_ref</i>	real	undefined
<i>skip_sensitivities</i>	integer	undefined
<i>sensitivity_scaling</i>	real	undefined
<i>ramp_sensitivities_over_time</i>	real	undefined

Summary This viscosity model is a function of the shear rate (Carreau model) and temperature (Arrhenius model). The two contributions are combined multiplicatively.

$$\mu(\dot{\gamma}, T) = \left[\mu_{\infty} + (\mu_0 - \mu_{\infty}) (1 + (\lambda \dot{\gamma})^a)^{\frac{n-1}{a}} \right] e^{\frac{K}{T} - \frac{K}{T_{ref}}}, \quad (4.2)$$

where μ_{∞} is the infinite shear viscosity (defaults to zero), μ_0 is the zero shear viscosity, n and a (defaults to 2) are model parameters, $\dot{\gamma}$ is the shear rate, λ is a time constant (defaults to 1), T_{ref} is a reference temperature and K is an Arrhenius constant.

4.1.1363.Viscosity: Bingham Wlf

Scope: Aria Material

Viscosity: Bingham Wlf [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*] = Bingham_Wlf [Mu_Zero = *mu_zero* | Mu_Inf = *mu_inf* | F = *f* | N = *n* | A = *a* | Lambda = *lambda* | Tau_Y = *tau_y* | Skip_Sensitivities = *skip_sensitivities*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>mu_zero</i>	real	undefined
<i>mu_inf</i>	real	undefined
<i>f</i>	real	undefined
<i>n</i>	real	undefined
<i>a</i>	real	undefined
<i>lambda</i>	real	undefined
<i>tau_y</i>	real	undefined
<i>skip_sensitivities</i>	integer	undefined

Summary A viscosity model dependent on the shear rate $\dot{\gamma}$

$$\mu(\dot{\gamma}) = \mu_{\infty} + \left(\mu_0 - \mu_{\infty} + \tau_y \frac{1 - e^{-\dot{\gamma} F}}{\dot{\gamma}} \right) (1 + (\lambda \dot{\gamma})^a)^{\frac{n-1}{a}}, \quad (4.3)$$

where μ_{∞} is the infinite shear viscosity, μ_0 is the zero shear viscosity, λ is a time constant, τ_y is the yield stress, and F , a and n are additional model parameters.

4.1.1364.Viscosity: Bingham Wlft

Scope: Aria Material

Viscosity: Bingham Wlft [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*] = Bingham_Wlft [Mu_Zero = *mu_zero* | Mu_Inf = *mu_inf* | F = *f* | N = *n* | A = *a* | Lambda = *lambda* | Tau_Y = *tau_y* | T_Ref = *t_ref* | C1 = *c1* | C2 = *c2* | Skip_Sensitivities = *skip_sensitivities*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>mu_zero</i>	real	undefined
<i>mu_inf</i>	real	undefined
<i>f</i>	real	undefined
<i>n</i>	real	undefined
<i>a</i>	real	undefined
<i>lambda</i>	real	undefined
<i>tau_y</i>	real	undefined
<i>t_ref</i>	real	undefined
<i>c1</i>	real	undefined
<i>c2</i>	real	undefined
<i>skip_sensitivities</i>	integer	undefined

Summary A viscosity model dependent on the shear rate $\dot{\gamma}$ and temperature T

$$\mu(\dot{\gamma}, T) = a_T \left(\mu_{\infty} + \left(\mu_0 - \mu_{\infty} + \tau_y \frac{1 - e^{-a_T \dot{\gamma}^F}}{a_T \dot{\gamma}} \right) (1 + (a_T \lambda \dot{\gamma})^a)^{\frac{n-1}{a}} \right), \quad (4.4)$$

where μ_{∞} is the infinite shear viscosity, μ_0 is the zero shear viscosity, τ_y is the yield stress, λ is the time constant, and where

$$a_T = e^{\frac{c_1(T_0 - T)}{c_2 + T - T_0}}, \quad (4.5)$$

with T_0 the reference temperature. Additional model parameters are a , n , c_1 , and c_2 .

4.1.1365.Viscosity: Carreau

Scope: Aria Material

Viscosity: Carreau [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*] = Carreau [Mu_Zero = *mu_zero* |Mu_Inf = *mu_inf* |N = *n* |A = *a* |Lambda = *lambda* |Skip_Sensitivities = *skip_sensitivities*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>mu_zero</i>	real	undefined
<i>mu_inf</i>	real	undefined
<i>n</i>	real	undefined
<i>a</i>	real	undefined
<i>lambda</i>	real	undefined
<i>skip_sensitivities</i>	integer	undefined

Summary A viscosity model dependent on the shear rate $\dot{\gamma}$

$$\frac{\mu(\dot{\gamma}) - \mu_{\infty}}{\mu_o - \mu_{\infty}} = (1 + (\lambda\dot{\gamma})^a)^{\frac{n-1}{a}}, \quad (4.6)$$

where μ_{∞} is the infinite shear viscosity (defaults to zero), μ_o is the zero shear viscosity, n and a (defaults to 2) are model parameters, and λ is a time constant.

4.1.1366.Viscosity: Carreau T

Scope: Aria Material

Viscosity: Carreau T [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Carreau_T [Mu_Zero = *mu_zero* |Mu_Inf = *mu_inf* |N = *n* |A = *a* |K = *k* |Skip_Sensitivities = *skip_sensitivities*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>mu_zero</i>	real	undefined
<i>mu_inf</i>	real	undefined
<i>n</i>	real	undefined
<i>a</i>	real	undefined
<i>k</i>	real	undefined
<i>skip_sensitivities</i>	integer	undefined

Summary A viscosity model dependent on the shear rate $\dot{\gamma}$ and temperature T

$$\frac{\mu(\dot{\gamma}, T) - \mu_{\infty}}{\mu_o - \mu_{\infty}} = \left(1 + (e^{k/T}\dot{\gamma})^a\right)^{\frac{n-1}{a}}, \quad (4.7)$$

where μ_{∞} is the infinite shear viscosity (defaults to zero), μ_o is the zero shear viscosity, and n , a (defaults to 2), and k are model parameters. The quantity $e^{k/T}$ is a temperature dependent time scale replacing the time scale λ in the Carreau model.

4.1.1367.Viscosity: Casson

Scope: Aria Material

Viscosity: Casson [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Casson [Mu_Zero = *mu_zero* |M = *m* |Shear_Reference = *shear_reference* |Yield_Stress = *yield_stress*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>mu_zero</i>	real	undefined
<i>m</i>	real	undefined
<i>shear_reference</i>	real	undefined
<i>yield_stress</i>	real	undefined

Summary A viscosity model dependent on the shear rate $\dot{\gamma}$

$$\mu(\dot{\gamma}) = \left[\sqrt{\mu_{\infty}} + \sqrt{\tau_y / \dot{\gamma}} \left(1 - e^{-\sqrt{m \dot{\gamma} / \dot{\gamma}_{ref}}} \right) \right]^2, \quad (4.8)$$

where μ_{∞} is the infinite shear viscosity, μ_{∞} is the zero shear viscosity, τ_y is the yield stress, $\dot{\gamma}_{ref}$ is a reference shear rate, and m is a model parameter.

4.1.1368.Viscosity: Cantera

Scope: Aria Material

Viscosity: Cantera [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Cantera [Poffset = *poffset*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>poffset</i>	real	undefined

4.1.1369.Viscosity: Clsm

Scope: Aria Material

Viscosity: Clsm [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Clsm [Primaryproperty = *primaryProperty* | Secondaryproperty = *secondaryProperty*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>primaryProperty</i>	real	undefined
<i>secondaryProperty</i>	real	undefined

Summary CLSM viscosity

4.1.1370.Viscosity: Curing Epoxy

Scope: Aria Material

Viscosity: Curing Epoxy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Curing_Epoxy [Mu_A = *mu_a* |T_Mu = *t_mu* | N_Mu = *n_mu* |Ksi_C = *ksi_c* |M_Ksi_C = *m_ksi_c* |E_Mu = *e_mu* |R = *r* | Epoxy_Subindex = *epoxy_subindex* |Epoxy_Species_Name = *epoxy_species_name* | Epoxy_Species_Phase = *epoxy_species_phase*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>mu_a</i>	real	undefined
<i>t_mu</i>	real	undefined
<i>n_mu</i>	real	undefined
<i>ksi_c</i>	real	undefined
<i>m_ksi_c</i>	real	undefined
<i>e_mu</i>	real	undefined
<i>r</i>	real	undefined
<i>epoxy_subindex</i>	integer	undefined
<i>epoxy_species_name</i>	"string"	undefined
<i>epoxy_species_phase</i>	"string"	undefined

Summary For a curing epoxy with extent of reaction ξ the viscosity is given by

$$\mu(\xi, T) = \mu_a \left(1 - \frac{T}{T_\mu}\right) \left(1 - \left(\frac{\xi}{\xi_c}\right)^m\right)^{n_\mu} e^{E_\mu/RT} \quad (4.9)$$

where T is the temperature and the default model parameters are $\mu_a = 800.93$, $T_\mu = 364.059$, $n_\mu = -4/3$, $E_\mu = 0.0$, $R = 1.987$, and $\xi_c = 0.45$. NOTE: The extent of reaction field is assumed to be a SPECIES field with the subindex provided by the EXTENT_SUBINDEX parameter.

4.1.1371.Viscosity: Curing Foam

Scope: Aria Material

Viscosity: Curing Foam [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Curing_Foam [Extent_Subindex = *extent_subindex* |Mu_A = *mu_a* |T_Mu = *T_mu* |N_Mu = *n_mu* |Ksi_C = *ksi_c* | M_Ksi_C = *m_ksi_c* |E_Mu = *E_mu* |R = *r*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>extent_subindex</i>	integer	undefined
<i>mu_a</i>	real	undefined
<i>T_mu</i>	real	undefined
<i>n_mu</i>	real	undefined
<i>ksi_c</i>	real	undefined
<i>m_ksi_c</i>	real	undefined
<i>E_mu</i>	real	undefined
<i>r</i>	real	undefined

Summary For a curing foam with gas volume fraction ϕ_g and extent of reaction ξ the viscosity is given by

$$\mu(\xi, \phi_g, T) = \mu_a \left(1 - \frac{T}{T_\mu}\right) \left(1 - \left(\frac{\xi}{\xi_c}\right)^m\right)^{n_\mu} e^{E_\mu/RT} e^{\phi_g/(1-\phi_g)} \quad (4.10)$$

where T is the temperature and the default model parameters are $\mu_a = 800.93$, $T_\mu = 364.059$, $n_\mu = -4/3$, $E_\mu = 0.0$, $R = 1.987$, and $\xi_c = 0.45$. NOTE: The gas volume fraction is assumed to be a SPECIES field with the subindex provided by the VFRAC_SUBINDEX parameter. Likewise, the extent of reaction field is assumed to be a SPECIES field with the subindex provided by the EXTENT_SUBINDEX parameter.

4.1.1372Viscosity: Keyes

Scope: Aria Material

Viscosity: Keyes [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] = Keyes [A0 = *a0* | A = *a* | A1 = *a1*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>a0</i>	real	undefined
<i>a</i>	real	undefined
<i>a1</i>	real	undefined

Summary A viscosity model dependent on the temperature T

$$\mu(T) = k a_0 \frac{T^{3/2}}{T + a 10^{-a_1/T}}, \quad (4.11)$$

where $k = 1 \times 10^{-6}$ and where a_0, a, a_1 are model parameters.

4.1.1373Viscosity: Krieger

Scope: Aria Material

Viscosity: Krieger [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Krieger [Beta = *beta* |Phi_Max = *phi_max* |Mu_S = *mu_s* | Use_Fd = *use_fd*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>beta</i>	real	undefined
<i>phi_max</i>	real	undefined
<i>mu_s</i>	real	undefined
<i>use_fd</i>	integer	undefined

Summary A viscosity model [4] dependent on the suspension concentration ϕ

$$\mu(\phi) = \mu_s \left(1 - \frac{\phi}{\phi_{max}}\right)^{\beta}, \quad (4.12)$$

where β is the Krieger exponent, ϕ_{max} is the maximum suspension concentration and μ_s is the solvent viscosity.

4.1.1374Viscosity: Mixture Fraction

Scope: Aria Material

Viscosity: Mixture Fraction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mixture_Fraction [Primaryproperty = *primaryProperty* |Secondaryproperty = *secondaryProperty*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>primaryProperty</i>	real	undefined
<i>secondaryProperty</i>	real	undefined

Summary Viscosity model dependent on the mixture fraction f

$$\mu(f) = f\mu_1 + (1 - f)\mu_2, \quad (4.13)$$

where μ_1 and μ_2 are viscosities corresponding to $f = 1$ and $f = 0$ respectively.

4.1.1375.Viscosity: Mixture Fraction Turbulent

Scope: Aria Material

Viscosity: Mixture Fraction Turbulent [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Mixture_Fraction_Turbulent [Primaryproperty = *primaryProperty* |Secondaryproperty = *secondaryProperty*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>primaryProperty</i>	real	undefined
<i>secondaryProperty</i>	real	undefined

Summary Turbulent viscosity model dependent on the mixture fraction f

$$\mu(f) = f\mu_1 + (1 - f)\mu_2, \quad (4.14)$$

where μ_1 and μ_2 are viscosities corresponding to $f = 1$ and $f = 0$ respectively.

4.1.1376.Viscosity: Morris Boulay

Scope: Aria Material

Viscosity: Morris Boulay [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Morris_Boulay [$K_S = K_s$ | $\Phi_{Max} = \phi_{i\_max}$ | $\Phi_{Tol} = \phi_{i\_tol}$ | $\mu_S = \mu_s$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
K_s	real	undefined
ϕ_{i_max}	real	undefined
ϕ_{i_tol}	real	undefined
μ_s	real	undefined

Summary A viscosity model for noncolloidal suspensions

$$\mu(\phi) = \mu_s \left(1 + 2.5\phi_{max} (1 - \bar{\phi})^{-1} + K_s \bar{\phi}^2 (1 - \bar{\phi})^{-2} \right), \quad (4.15)$$

where ϕ is the volume fraction, $\bar{\phi} = \phi/\phi_{max}$ is the volume fraction normalized by the max volume fraction, μ_s is the suspending fluid viscosity, and K_s is a model parameter.
NOTE: $\bar{\phi}$ is bounded such that

$$0 \leq \bar{\phi} \leq \frac{\phi_{tol}}{\phi_{max}}, \quad (4.16)$$

where ϕ_{tol} is the max attainable volume fraction.

4.1.1377Viscosity: Phase Average

Scope: Aria Material

Viscosity: Phase Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Phase_Average [Subindex_A = *subindex_a* | Subindex_B = *subindex_b*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>subindex_a</i>	integer	undefined
<i>subindex_b</i>	integer	undefined

Summary Phase-averaged values

4.1.1378Viscosity: Interpolated Phase Average

Scope: Aria Material

Viscosity: Interpolated Phase Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Interpolated_Phase_Average [Subindex_A = *subindex_a* | Subindex_B = *subindex_b*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>subindex_a</i>	integer	undefined
<i>subindex_b</i>	integer	undefined

Summary Phase-averaged values

4.1.1379Viscosity: Power Law

Scope: Aria Material

Viscosity: Power Law [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Power_Law [K = *k* | N = *n*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>k</i>	real	undefined
<i>n</i>	real	undefined

Summary A viscosity model dependent on the shear rate $\dot{\gamma}$

$$\mu(\dot{\gamma}) = K\dot{\gamma}^{N-1}, \quad (4.17)$$

where K is a model parameter, and N is the power law exponent.

4.1.1380.Viscosity: Sutherland

Scope: Aria Material

Viscosity: Sutherland [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Sutherland [Tref = *tref* |C = *c*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>tref</i>	real	undefined
<i>c</i>	real	undefined

Summary A viscosity model dependent on temperature T

$$\mu(T) = \frac{cT^{1.5}}{T + T_{ref}}, \quad (4.18)$$

where T_{ref} and c are model parameters.

4.1.1381.Viscosity: Weld

Scope: Aria Material

Viscosity: Weld [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Weld [Interpolated = *interpolated* |Beta = *beta* |C0 = *c0* |C1 = *c1* |C2 = *c2* |C3 = *c3* |T_Liq = *T_liq* |T_90 = *t_90* |T_Max = *T_max*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>interpolated</i>	integer	undefined
<i>beta</i>	real	undefined
<i>c0</i>	real	undefined
<i>c1</i>	real	undefined
<i>c2</i>	real	undefined
<i>c3</i>	real	undefined
<i>T_liq</i>	real	undefined
<i>t_90</i>	real	undefined
<i>T_max</i>	real	undefined

Summary This is an empirical model that emulates the melting of a solid metal during the laser welding process.

$$\mu(T) = \begin{cases} \mu_{90} + (\mu_{liq} - \mu_{90}) \left(\frac{T - T_{90}}{T_{liq} - T_{90}} \right) & T < T_{liq} \\ c_0 + c_1 \hat{T} + c_2 \hat{T}^2 + c_3 \hat{T}^3 & T \geq T_{liq}, \end{cases}$$

where μ_{liq} is given by

$$\mu_{liq} = c_0 + c_1 T_{liq} + c_2 T_{liq}^2 + c_3 T_{liq}^3, \quad (4.19)$$

and where $\mu_{90} = \beta \mu_{liq}$ and $\hat{T} = \min(T, T_{max})$. The default value of β is 10^{11} .

4.1.1382 Viscosity: Ramaccioti

Scope: Aria Material

Viscosity: Ramaccioti [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*] = Ramaccioti [Interpolated = *interpolated* | T_Liq = *T_liq* | T_Sol = *T_sol* | C = *c* | Mu_Liq = *mu_liq*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>interpolated</i>	integer	undefined
<i>T_liq</i>	real	undefined
<i>T_sol</i>	real	undefined
<i>c</i>	real	undefined
<i>mu_liq</i>	real	undefined

Summary A viscosity model used for corium melts

$$\mu(T) = \mu_{liq} e^{2.5Cf_s}, \quad (4.20)$$

where $f_s = \min(\bar{f}_s, 1)$ with $\bar{f}_s$ defined as

$$\bar{f}_s = \begin{cases} \frac{T_{liq} - T}{T_{liq} - T_{sol}} & T < T_{liq} \\ 0 & T \geq T_{liq}, \end{cases}$$

where T is the temperature, μ_{liq} is the viscosity of the liquid, T_{liq} is the liquidus temperature, T_{sol} is the solidus temperature and $4 \leq C \leq 8$ is a model parameter.

4.1.1383 Viscosity: Thermal

Scope: Aria Material

Viscosity: Thermal [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*] = Thermal [A = *a* | B = *b* | C = *c* | D = *d*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>a</i>	real	undefined
<i>b</i>	real	undefined
<i>c</i>	real	undefined
<i>d</i>	real	undefined

Summary A viscosity model dependent on the temperature T

$$\mu(T) = A + BT + CT^2 + DT^3, \quad (4.21)$$

where A, B, C, D are coefficients of a fitted cubic polynomial.

4.1.1384.Viscosity: Mass Average

Scope: Aria Material

Viscosity: Mass Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Mass_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Viscosity computed from mass average of species viscosities

4.1.1385.Viscosity: Volume Average

Scope: Aria Material

Viscosity: Volume Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Volume_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Viscosity computed from volume average of species viscosities, over a material phase

4.1.1386.Viscosity: Species Average

Scope: Aria Material

Viscosity: Species Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Species_Average []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Viscosity computed from mass average of species viscosities

4.1.1387.Voltage

Scope: Aria Material

Voltage [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1388.Voltage: Copied

Scope: Aria Material

Voltage: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1389.Voltage: User Plugin

Scope: Aria Material

Voltage: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.1390.Voltage: Scalar String Function

Scope: Aria Material

Voltage: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1391.Volume Fraction

Scope: Aria Material

Volume Fraction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1392 Volume Fraction: Copied

Scope: Aria Material

Volume Fraction: Copied [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] = Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1393 Volume Fraction: User Plugin

Scope: Aria Material

Volume Fraction: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] = User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1394 Volume Fraction: Scalar String Function

Scope: Aria Material

Volume Fraction: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] = Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1395 Volume Fraction: From Mass Fraction

Scope: Aria Material

Volume Fraction: From Mass Fraction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Mass_Fraction []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Compute the volume fraction from the ratio of species porous density ($\rho_{\text{bulk}} * Y_i$) to species solid density. The overall density material phase to use can be specified with the optional 'Density_Phase_Name' argument, which can be necessary for porous systems depending on how the mass fractions are defined.

4.1.1396 Volume Fraction: From Porosity

Scope: Aria Material

Volume Fraction: From Porosity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Porosity []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Compute the volume fraction from a species porosity.

4.1.1397 Volume Fraction: From Molar Volume

Scope: Aria Material

Volume Fraction: From Molar Volume [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Molar_Volume []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Compute the volume fraction of a species as the product of its concentration and partial molar volume.

4.1.1398.Volume Fraction: From Electrode Object Old

Scope: Aria Material

Volume Fraction: From Electrode Object Old [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Electrode_Object_Old [F = *f* | Electrodefile = *electrodeFile* |Kmolconversion = *kmolConversion* | Jconversion = *JConversion* |Meterconversion = *meterConversion* | Max_Sub_Timesteps = *max_sub_timesteps* |Base_Delta = *base_delta*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	real	undefined
<i>electrodeFile</i>	"string"	undefined
<i>kmolConversion</i>	real	undefined
<i>JConversion</i>	real	undefined
<i>meterConversion</i>	real	undefined
<i>max_sub_timesteps</i>	integer	undefined
<i>base_delta</i>	real	undefined

Summary Get the solid volume fraction for all species tracked by the Electrode object being used to calculate electrochemical reaction source terms.

4.1.1399.Volume Fraction Gas

Scope: Aria Material

Volume Fraction Gas [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

4.1.1400.Volume Fraction Gas: Copied

Scope: Aria Material

Volume Fraction Gas: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1401 Volume Fraction Gas: User Plugin

Scope: Aria Material

Volume Fraction Gas: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1402 Volume Fraction Gas: Scalar String Function

Scope: Aria Material

Volume Fraction Gas: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F =
f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1403 Volume Fraction Gas: From Density

Scope: Aria Material

Volume Fraction Gas: From Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Density [Rho_Liquid = *rho_liquid* |
Rho_Gas = *rho_gas* |Rho_Initial = *rho_initial*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>rho_liquid</i>	real	undefined
<i>rho_gas</i>	real	undefined
<i>rho_initial</i>	real	undefined

Summary Compute the gas volume fraction from the gas density

4.1.1404. Volume Fraction Gas: Fromfoamtimetemp

Scope: Aria Material

Volume Fraction Gas: Fromfoamtimetemp [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Fromfoamtimetemp [Rho_Liquidfluorinert = *rho_liquidfluorinert* | Rho_Vaporfluorinert = *rho_vaporfluorinert* | Rho_Air = *rho_air* | Massfraction_Air = *massfraction_air* | Rho_Initial = *rho_initial*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>rho_liquidfluorinert</i>	real	undefined
<i>rho_vaporfluorinert</i>	real	undefined
<i>rho_air</i>	real	undefined
<i>massfraction_air</i>	real	undefined
<i>rho_initial</i>	real	undefined

Summary Compute the gas volume fraction from the foam time/temperature profile

4.1.1405. Volume Fraction Gas: Phase Average

Scope: Aria Material

Volume Fraction Gas: Phase Average [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Phase_Average [Subindex_A = *subindex_a* | Subindex_B = *subindex_b*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>subindex_a</i>	integer	undefined
<i>subindex_b</i>	integer	undefined

Summary Phase-averaged values

4.1.1406.Volume Fraction Gas: Interpolated Phase Average

Scope: Aria Material

Volume Fraction Gas: Interpolated Phase Average [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Interpolated_Phase_Average [Subindex_A = *subindex_a* |Subindex_B = *subindex_b*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>subindex_a</i>	integer	undefined
<i>subindex_b</i>	integer	undefined

Summary Phase-averaged values

4.1.1407.Volume Fraction Gas: From Reaction Extent

Scope: Aria Material

Volume Fraction Gas: From Reaction Extent [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Reaction_Extent [Al_1 = *al_1* | Al_2 = *al_2* |V_Liq = *v_liq* |N_I = *n_i* |N_Max = *n_max* |Mw = *mw* |T_Ref = *t_ref*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>al_1</i>	real	undefined
<i>al_2</i>	real	undefined
<i>v_liq</i>	real	undefined
<i>n_i</i>	real	undefined
<i>n_max</i>	real	undefined
<i>mw</i>	real	undefined
<i>t_ref</i>	real	undefined

Summary Gas volume fraction from reaction extent for foaming applications

4.1.1408.Volume Fraction Gas: Species

Scope: Aria Material

Volume Fraction Gas: Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Species [Gas_Species_Subindex = *gas_species_subindex* |Gas_Species_Name = *gas_species_name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>gas_species_subindex</i>	integer	undefined
<i>gas_species_name</i>	"string"	undefined

Summary Compute the gas volume fraction as $C_g * MW_g / \rho_g$ where C_g is the molar concentration of the gas, MW_g is the molecular weight, and ρ_g is the density of the pure gas at the current T, P. The species to use for C_g and MW_g can be specified either by name or by subindex.

4.1.1409 Volume Fraction Gas: From Thermal Expansion

Scope: Aria Material

Volume Fraction Gas: From Thermal Expansion [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] = From_Thermal_Expansion [$\Phi_0 = \phi_0$ | $\rho_{ho} = \rho_{ho}$ | $\rho_{ho} = \rho_{ho}$ | $\beta_0 = \beta_0$ | $\beta_1 = \beta_1$ | $T_0 = t_0$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>phi0</i>	real	undefined
<i>rhob0</i>	real	undefined
<i>rhoc0</i>	real	undefined
<i>beta0</i>	real	undefined
<i>beta1</i>	real	undefined
<i>t0</i>	real	undefined

Summary Gas volume fraction from thermal expansion of the condensed phase

4.1.1410 Volume Fraction Gas: From Mass Fractions

Scope: Aria Material

Volume Fraction Gas: From Mass Fractions [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] = From_Mass_Fractions []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Compute the gas volume fraction from the mass fractions and bulk densities

4.1.1411 Volume Fraction Gas: From Species

Scope: Aria Material

Volume Fraction Gas: From Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Species []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Compute the gas volume fraction from the species concentrations pulled from ChemEq

4.1.1412 Volume Fraction Gas: From Porosity

Scope: Aria Material

Volume Fraction Gas: From Porosity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= From_Porosity []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined

Summary Gas volume fraction from the porosity

4.1.1413 Volumetric Heat Transfer Coefficient

Scope: Aria Material

Volumetric Heat Transfer Coefficient [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |H = *h*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>h</i>	real	undefined

Summary Constant value

4.1.1414 Volumetric Heat Transfer Coefficient: Copied

Scope: Aria Material

Volumetric Heat Transfer Coefficient: Copied [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1415 Volumetric Heat Transfer Coefficient: User Plugin

Scope: Aria Material

Volumetric Heat Transfer Coefficient: User Plugin [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1416 Volumetric Heat Transfer Coefficient: Scalar String Function

Scope: Aria Material

Volumetric Heat Transfer Coefficient: Scalar String Function [{of|species
|subindex} *Species* |{in|material_phase} *MaterialPhase*]=
Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1417Wall Angle: Correlation

Scope: Aria Material

Wall Angle: Correlation [{of|species|subindex} *Species*]= Correlation [Theta = *theta* |Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>theta</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation Wall Angle

4.1.1418Wall Length: Correlation

Scope: Aria Material

Wall Length: Correlation [{of|species|subindex} *Species*]= Correlation [L = *l* |Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>l</i>	real	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation Wall length

4.1.1419Wall Temperature

Scope: Aria Material

Wall Temperature [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |Tw = *Tw*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>Tw</i>	real	undefined

Summary Constant valueConstant value

4.1.1420Wall Temperature: Copied

Scope: Aria Material

Wall Temperature: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expressionCopied value from another expression

4.1.1421Wall Temperature: User Plugin

Scope: Aria Material

Wall Temperature: User Plugin [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user pluginValue from a user plugin

4.1.1422Wall Temperature: Scalar String Function

Scope: Aria Material

Wall Temperature: Scalar String Function [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Scalar_String_Function [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string functionValue from a string function

4.1.1423Wetted Perimeter

Scope: Aria Material

Wetted Perimeter [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]= Constant [Value = *value* |P = *p*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>p</i>	real	undefined

Summary Constant value

4.1.1424Wetted Perimeter: Copied

Scope: Aria Material

Wetted Perimeter: Copied [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1425Wetted Perimeter: User Plugin

Scope: Aria Material

Wetted Perimeter: User Plugin [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

4.1.1426Wetted Perimeter: Scalar String Function

Scope: Aria Material

Wetted Perimeter: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
f	"string"	undefined

Summary Value from a string function

4.1.1427Wetted Perimeter: Spatial User Function

Scope: Aria Material

Wetted Perimeter: Spatial User Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Spatial_User_Function [Threshold = *threshold* |Multiplier = *multiplier* |Name = *name* |Bar = *bar* |X = *x*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>threshold</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>name</i>	"string"	undefined
<i>bar</i>	"string"	undefined
<i>x</i>	"string"	undefined

Summary Spatially varying wetted perimeter based on a coordinate dependent user function

4.1.1428Wetted Perimeter: Correlation Spatial User Function

Scope: Aria Material

Wetted Perimeter: Correlation Spatial User Function [{of|species|subindex} *Species*]= Correlation_Spatial_User_Function [Threshold = *threshold* |Multiplier = *multiplier* |Name = *name* |Bar = *bar* |X = *x* | Bulk_Node_Interface = *bulk_node_interface*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>threshold</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>name</i>	"string"	undefined
<i>bar</i>	"string"	undefined
<i>x</i>	"string"	undefined
<i>bulk_node_interface</i>	"string"	undefined

Summary Correlation spatially varying wetted perimeter based on a coordinate dependent user function

4.1.1429.Wetting Phase Retardation

Scope: Aria Material

Wetting Phase Retardation [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Constant [Value = *value* |R = *r*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>value</i>	real	undefined
<i>r</i>	real	undefined

Summary Constant value

4.1.1430.Wetting Phase Retardation: Copied

Scope: Aria Material

Wetting Phase Retardation: Copied [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]= Copied [Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

4.1.1431Wetting Phase Retardation: User Plugin

Scope: Aria Material

Wetting Phase Retardation: User Plugin [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= User_Plugin [Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

4.1.1432Wetting Phase Retardation: Scalar String Function

Scope: Aria Material

Wetting Phase Retardation: Scalar String Function [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Scalar_String_Function [*F* = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

4.1.1433Wisdom: Magic Eight Ball

Scope: Aria Material

Wisdom: Magic Eight Ball [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]= Magic_Eight_Ball [Question = *question*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>question</i>	"string"	undefined

Summary The Eight ball knows all

4.2. BAR AREA

BAR AREA = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the bar cross-sectional area.

Summary Specifies the material model and parameters for the bar cross-sectional area.

Parent
Block(s)
ARIA MATERIAL

4.2.1. BAR AREA = CONSTANT

Parameters

A = *REAL*

Example

Bar Area = Constant A = 0.8

Description A is the value of the bar cross-sectional area.

4.2.2. BAR AREA = ELEMENT_ATTRIBUTE

Parameters

MULTIPLIER = *REAL*

Example

Bar Area = Element_Attribute multiplier = 1.0

Description For bar elements the ExodusII mesh file can contain area attribute values for each element within an element block. This value can then be retrieved and used by the application. This model is used to scale the value of area attribute by Multiplier to obtain the bar cross-sectional area for a particular element.

4.3. BETA

BETA = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the coefficient for thermal stress.

Summary The solid stress $\mathbf{T}$ is given by

$$\mathbf{T} = \lambda E_{kk} \mathbf{I} + 2\mu \mathbf{E} - \beta (T - T_{ref}) \mathbf{I} \quad (4.22)$$

where λ and μ are the Lamé coefficients, $\mathbf{E} = \frac{1}{2} (\nabla \mathbf{d} + \nabla \mathbf{d}^T)$ is the deformation tensor, β is the coefficient of thermal stress, T is temperature and T_{ref} is the thermal strain reference temperature.

These Lamé coefficients are related to the more standard Young's modulus, Poisson's ratio and CTE (α) as follows:

$$2\mu = \frac{E}{(1 + \nu)} \quad (4.23)$$

$$\lambda = \frac{\nu E}{(1 + \nu)(1 - 2\nu)} = 2\mu \frac{\nu}{(1 - 2\nu)} \quad (4.24)$$

$$\beta = \frac{\alpha E}{(1 - 2\nu)} = \alpha (3\lambda + 2\mu) \quad (4.25)$$

When a user supplies the Young's modulus, Poisson's ratio and CTE properties Aria internally converts them into the Lamé coefficients.

Parent
Block(s)
ARIA MATERIAL

4.3.1. BETA = CONSTANT

Parameters

BETA = *REAL*

Example

BETA = CONSTANT BETA = 1.0

Description BETA is the value of β .

4.3.2. BETA = CONVERTED

Parameters

(None)

Example

BETA = Converted

Description Aria will use Young's modulus, Poisson ratio and CTE to compute the Lamé β coefficient. Supplying the Lamé coefficients is more computationally efficient but perhaps less convenient, especially if the material properties are varying (e.g., temperature dependent in a non-isothermal problem).

4.3.3. BETA = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

Beta = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.3.4. BETA = LINEAR

Parameters

A = *REAL*

B = *REAL*

Example

BETA = LINEAR A = 1.0 B = -.005

Description β is a linear function of temperature T ,

$$\beta = A + BT \quad (4.26)$$

4.4. BULK VISCOSITY

BULK VISCOSITY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the fluid bulk viscosity.

Summary Specifies the material model for the fluid bulk viscosity.

Parent
Block(s)
ARIA MATERIAL

4.4.1. BULK VISCOSITY = CONSTANT

Parameters

KAPPA = *REAL*

Example

BULK VISCOSITY = CONSTANT KAPPA = 1.0e-5

Description KAPPA is the value of the constant fluid bulk viscosity.

4.4.2. BULK VISCOSITY = CURING_FOAM

Parameters

VFRAC_SUBINDEX = *INT*

EXTENT_SUBINDEX = *INT*

PHI_ZERO = *REAL*

[A = *REAL*]

[B = *REAL*]

[C = *REAL*]

[KSI_C = *REAL*]

Example

Bulk Viscosity = Curing_Foam Vfrac_Subindex=1 Extent_Subindex=2

Phi_Zero=0.45

Description For a curing epoxy with volume fraction ϕ and extent of reaction ξ the viscosity is given by

$$\kappa = \frac{4}{3}\mu_o \frac{\phi_o - \phi - 1}{\phi_o - \phi} \quad (4.27)$$

where μ_o is given by

$$\mu_o = (a - bT) \left(\frac{\xi_c^2 - \xi^2}{\xi_c^2} \right)^c \quad (4.28)$$

where T is the temperature. The remaining parameters a , b , c and ξ_c have default values of $a = 20$, $b = 0.22$, $c = -4/3$ and $\xi_c = 0.45$ though they can be overridden with the optional model parameters.

NOTE: The volume fraction is assumed to be a SPECIES field with the subindex provided by the VFRAC_SUBINDEX parameter. Likewise, the extent of reaction field is assumed to be a SPECIES field with the subindex provided by the EXTENT_SUBINDEX parameter.

4.4.3. BULK VISCOSITY = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

Bulk Viscosity = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.5. CTE

CTE = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the coefficient of thermal expansion.

Summary The solid stress $\mathbf{T}$ is given by

$$\mathbf{T} = \lambda E_{kk} \mathbf{I} + 2\mu \mathbf{E} - \beta (T - T_{ref}) \mathbf{I} \quad (4.29)$$

where λ and μ are the Lamé coefficients, $\mathbf{E} = \frac{1}{2} (\nabla \mathbf{d} + \nabla \mathbf{d}^T)$ is the deformation tensor, β is the coefficient of thermal stress, T is temperature and T_{ref} is the thermal strain reference temperature.

These Lamé coefficients are related to the more standard Young's modulus, Poisson's ratio and CTE (α) as follows:

$$2\mu = \frac{E}{(1 + \nu)} \quad (4.30)$$

$$\lambda = \frac{\nu E}{(1 + \nu)(1 - 2\nu)} = 2\mu \frac{\nu}{(1 - 2\nu)} \quad (4.31)$$

$$\beta = \frac{\alpha E}{(1 - 2\nu)} = \alpha (3\lambda + 2\mu) \quad (4.32)$$

When a user supplies the Young's modulus, Poisson's ratio and CTE properties Aria internally converts them into the Lamé coefficients.

Supplying the Lamé coefficients is more computationally efficient but perhaps less convenient, especially if the material properties are varying (e.g., temperature dependent in a non-isothermal problem).

Parent
Block(s)
ARIA MATERIAL

4.5.1. CTE = CONSTANT

Parameters

CTE = *REAL*

Example

CTE = CONSTANT cte = 1.0

Description CTE is the value of the coefficient of thermal expansion.

4.5.2. CTE = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

CTE = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.6. CURRENT DENSITY

CURRENT DENSITY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material (constitutive) model for the current density in the bulk.

Summary Specifies the material (constitutive) model for the current density in the bulk.

Parent

Block(s)

ARIA MATERIAL

4.6.1. CURRENT DENSITY = BASIC

This is an alias for OHMS_LAW.

Example

Current Density = Basic

4.6.2. CURRENT DENSITY = DIELECTRIC_DISPLACEMENT

Parameters

(none)

Example

Current Density = Dielectric_Displacement

Description The current density $\mathbf{J}$ is taken to be

$$\mathbf{J} = -\epsilon \nabla \frac{\partial V}{\partial t} - \frac{\partial \epsilon}{\partial t} \nabla V \quad (4.33)$$

where ϵ is the electrical permittivity and V is the voltage (electric potential). This model can be used to simulate dielectric materials adjoined to conducting materials in transient problems.

This arises from time-differentiating Gauss' Law

$$-\nabla \cdot (\epsilon \nabla V) = \rho_f \quad (4.34)$$

which gives

$$-\nabla \cdot \left(\epsilon \nabla \frac{\partial V}{\partial t} + \frac{\partial \epsilon}{\partial t} \nabla V \right) = \frac{\partial \rho_f}{\partial t}. \quad (4.35)$$

The left hand side of this equation can be used to eliminate the $\partial \rho_f / \partial t$ from the current density equation.

4.6.3. CURRENT DENSITY = OHMS_LAW

Parameters

(none)

Example

Current Density = Ohms_Law

Description The current density $\mathbf{J}$ is given by Ohm's Law,

$$\mathbf{J} = -\sigma_e \nabla V \quad (4.36)$$

where σ_e is the electrical conductivity and V is the voltage (electric potential).

4.6.4. CURRENT DENSITY = THERMOELECTRIC

Parameters

(none)

Example

Current Density = Thermoelectric

Description The current density $\mathbf{J}$ is given by a combination of Ohm's Law and a contribution related to the temperature gradient,

$$\mathbf{J} = -\sigma_e (\nabla V + \alpha \nabla T) \quad (4.37)$$

where σ_e is the electrical conductivity, V is the voltage (electric potential), α is the Seebeck coefficient and T is the temperature. This current density is used in conjunction with a THERMOELECTRIC heat conduction [4.15.5](#).

4.7. DENSITY

DENSITY = MODEL [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the density.

Summary Specifies the material model for the density.

Parent

Block(s)

ARIA MATERIAL

4.7.1. DENSITY = CALORE_USER_SUB

Parameters

NAME = *STRING*
TYPE = *STRING*
[MULTIPLIER = *REAL*]
[NR = *INT*]
[R0 = *INT*]
[R1 = *INT*(etc.)]
[NI = *INT*]
[IO = *INT*]
[I1 = *INT*(etc.)]

Example

Density = Calore_User_Sub name=w80afftuser type=element NR=2
R0=1000 R1=0.7

Description NAME is the name of the user subroutine was registered with. NR and NI are the numbers of real and integer parameters, respectively. Each real (int) parameter is supplied by the Rn (In) parameter. Note: the parameters use zero based counting. The TYPE parameter denotes the API the user subroutine uses; currently Aria only supports types ELEMENT and NODE.

The optional MULTIPLIER parameter (defaults to 1.0) can be supplied to scale the output of the user subroutine, i.e., the flux f will be $f = m f_{user}$ where m is the multiplier and f_{user} is the output of the user subroutine.

See section [9.2.2](#) for a more complete example of a Calore user subroutine.

4.7.2. DENSITY = COMPRESSIBLE_BOUSSINESQ

Parameters

REF_DENSITY
ALPHA = *REAL*
REF_PRESSURE
[BETA = *REAL*]
[REF_TEMPERATURE]

Example

Density = Compressible_Boussinesq Ref_Density=1.0 alpha=1e-8
Ref_Pressure=101235 beta=1e-3 Ref_Temperature=298

Description

$$\rho = \rho_{ref} (1 + \alpha (P - P_{ref}) + \beta (T - T_{ref})) \quad (4.38)$$

Here ρ_{ref} is specified by the REF_DENSITY parameter and is the density at pressure $P = P_{ref}$ (given by the REF_PRESSURE parameter) and temperature $T = T_{ref}$ (given

by the REF_TEMPERATURE parameter). The parameter ALPHA specifies the isothermal compressibility α . The parameter BETA specifies the isobaric compressibility β .

However, if the temperature is not available, then the temperature effects are not included and the BETA and REF_TEMPERATURE parameters do not need to be supplied.

4.7.3. DENSITY = CONSTANT

Parameters

RHO = *REAL*

Example

DENSITY = CONSTANT RHO = 1.0

Description RHO is the value of the constant density.

4.7.4. DENSITY = CURING_FOAM

Parameters

R = *REAL*

RHO_E = *REAL*

RHO_F = *REAL*

PHI_ZERO = *REAL*

VFRAC_SUBINDEX = *INT*

Example

Molecular Weight = Constant Subindex=1 M = 17.0

Density = Curing_Foam R=8.314472E3 RHO_E=1 RHO_F=1.5

PHI_ZERO=0.2 VFRAC_SUBINDEX=1

Description The density curing epoxy foam with volume fraction ϕ , molecular weight M , temperature T , and pressure p is given by

$$\rho = (\phi_o - \phi) \frac{pM}{RT} + (1 - \phi_o) \rho_e + \phi \rho_f \quad (4.39)$$

where R is the gas constant, ϕ_o is the reference volume fraction in the flourinert ρ_e is the pure epoxy density and ρ_f is the pure flourinert density.

NOTE: The volume fraction is assumed to be a SPECIES field with the subindex provided by the VFRAC_SUBINDEX parameter.

4.7.5. DENSITY = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

Density = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.7.6. DENSITY = EXP_DECAY

Parameters

RHO_INITIAL = *REAL*

RHO_FINAL = *REAL*

K = *REAL*

Example

Density = Exp_Decay K=1.2 RHO_INITIAL=1.0 RHO_FINAL=0.2

Description This model supplies a density that is an exponential decay,

$$\rho = \rho_f + (\rho_i - \rho_f) e^{-kt} \quad (4.40)$$

where ρ_i is the initial density (RHO_INITIAL), ρ_f is the final density (RHO_FINAL) and k (K) is the decay constant.

4.7.7. DENSITY = IDEAL_GAS

Parameters

R = *REAL*

[P_REF = *REAL*]

[T_REF = *REAL*]

Example

Molecular Weight = Constant Subindex=1 M = 17.0

Molecular Weight = Constant Subindex=2 M = 23.0

Density = Ideal_Gas R=8.314472E3 T_ref=273.15 P_ref=101325.0

Description The density of a multicomponent ideal gas in kg m^{-3} may be written as

$$\rho = \frac{P_{ref} + P}{R(T_{ref} + T)} \sum_i^N M_i y_i \quad (4.41)$$

where N is the number of species, P is the pressure in Pascals, P_{ref} is a reference pressure, R is the gas constant, T is the temperature, T_{ref} is a reference temperature, M_i is the molecular weight of species i in kg kmol^{-1} and y_i is the mole fraction of species i . Note, the units given here and on the density card are SI units; any units may be used as long as internal consistency is maintained.

The optional reference values for the temperature and pressure allow you to solve for the temperature and pressure using relative units (e.g., Celsius temperature and gauge pressure) and but still use absolute values as required by this material model.

4.7.8. DENSITY = INCOMPRESSIBLE_IDEAL_GAS

Parameters

R = *REAL*

P_REF = *REAL*

[T_REF = *REAL*]

Example

Molecular Weight = Constant Subindex=1 M = 17.0

Molecular Weight = Constant Subindex=2 M = 23.0

Density = Incompressible_Ideal_Gas R=8.314472E3 T_ref=273.15

P_ref=101325.0

Description The density of a multicomponent ideal gas in kg m^{-3} may be written as

$$\rho = \frac{P_{ref}}{R(T_{ref} + T)} \sum_i^N M_i y_i \quad (4.42)$$

where N is the number of species, P_{ref} is a reference pressure in pascal, R is the gas constant in $\text{J kmol}^{-1} \text{K}^{-1}$, T is the temperature, T_{ref} is a reference temperature, M_i is

the molecular weight of species i in kg kmol^{-1} , and y_i is the mole fraction of species i . Note, the units given here and on the density card are SI units; any units may be used as long as internal consistency is maintained.

The optional reference value for the temperature allow you to solve for the temperature using relative units (e.g., Celsius temperature) and but still use absolute values as required by this material model.

4.7.9. DENSITY = POLYNOMIAL

Parameters

VARIABLE = *STRING* ORDER = *INT* [VARIABLE_OFFSET = *REAL*] [C0 = *REAL*] [C1 = *REAL*] ... [CN = *REAL*]

Example

Density= Polynomial Variable=Temperature Order=1 C0=401.0
C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$\rho = \sum_{i=0}^N C_i (X + X_o)^i \quad (4.43)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter, X_o is an optional offset (VARIABLE_OFFSET, default is zero) and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section [2.7.1](#).

4.7.10. DENSITY = SINGLE_COMPONENT_IDEAL_GAS

Parameters

R = *REAL*
[M = *REAL*]
[P_REF = *REAL*]
[T_REF = *REAL*]

Example

Density = Single_Component_Ideal_Gas R=8.314 T_ref=273.15
P_ref=101325.0

Description This supplies the density for a single component ideal gas,

$$\rho = \frac{(P_{ref} + P) M}{R (T_{ref} + T)} \quad (4.44)$$

P is the pressure, P_{ref} is a reference pressure (defaults to zero), R is the gas constant, T is the temperature, T_{ref} is a reference temperature (defaults to zero), and M is the molecular weight (defaults to one).

The optional reference values for the temperature and pressure allow you to solve for the temperature and pressure using relative units (e.g., Celsius temperature and gauge pressure) and but still use absolute values as required by this material model.

4.7.11. DENSITY = THERMAL

Parameters

[A = *REAL*]

[B = *REAL*]

[C = *REAL*]

[D = *REAL*]

Example

DENSITY = THERMAL A = 1.0 B = -.005

Description Cubic polynomial function of temperature for the density.

$$\rho = A + BT + CT^2 + DT^3 \quad (4.45)$$

4.7.12. DENSITY = USER_FUNCTION

Parameters

NAME = *STRING*

X = *STRING*

Example

```

Begin Definition for Function Water_Density
  # Source Appendix 2 from "Transport Processes and
  # Unit Operations" by C. J. Geankoplis
  Type is Piecewise Linear
  Begin Values
    # K      kg * m^-3
    273.15   999.87
    277.15   1000.00
    283.15   999.73
    293.15   998.23
    298.15   997.08
    303.15   995.68
    313.15   992.25
    323.15   988.07
    333.15   983.24
    343.15   977.81
    353.15   971.83
    363.15   965.34
    373.15   958.38
  End
End
...

Begin Aria Material Foo
  ...
  Density = User_Function Name=Water_Density X=Temperature
  ...
End Aria Material Foo

```

Description A look-up function is used to compute the values of the density as a function of some other variable, i.e. $f(x)$. The function type (“piecewise linear” in the example above) must support the `differentiate()` method for Newton’s method.

Here NAME is the name of the user-defined function (Water_Density in the example) and X is the Aria name of the abscissa variable (TEMPERATURE in the example). Note that X is not necessarily the same name as the abscissa variable identified in the user-defined function (T in the example).

4.8. ELECTRICAL CONDUCTIVITY

ELECTRICAL CONDUCTIVITY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the electrical conductivity.

Summary Specifies the material model for the electrical conductivity.

Parent
Block(s)
ARIA MATERIAL

4.8.1. ELECTRICAL CONDUCTIVITY = CONSTANT

Parameters
SIGMA = *REAL*

Example
ELECTRICAL CONDUCTIVITY = CONSTANT SIGMA = 1.0

Description SIGMA is the value of the constant electrical conductivity.

4.8.2. ELECTRICAL CONDUCTIVITY = ENCORE_FUNCTION

Parameters
NAME = *STRING*
[EVAL_TYPE = *STRING*]

Example
ELECTRICAL CONDUCTIVITY = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.8.3. ELECTRICAL CONDUCTIVITY = EXPONENTIAL

Parameters

VARIABLE = *STRING*
[CONSTANT = *REAL*]
[MULTIPLIER = *REAL*]
EXPONENT = *REAL*

Example

Electrical Conductivity = Exponential Variable=Temperature
Multiplier=1.0 Exponent=-0.3

Description Exponential function of in specified scalar variable. The electrical conductivity is computed as

$$\sigma_e = C + Me^{EX} \quad (4.46)$$

Here, C is the constant term supplied by the CONSTANT parameter which defaults to zero, M is the value supplied by the MULTIPLIER parameter which defaults to unity, X is the variable supplied by the VARIABLE parameter and E is the exponential multiplier provided by the EXPONENT parameter.

4.8.4. ELECTRICAL CONDUCTIVITY = FROM_RESISTANCE

Parameters

None.

Example

ELECTRICAL CONDUCTIVITY = FROM_RESISTANCE

Description The conductivity is computed as the inverse of the electrical resistance which must be provided separately.

4.8.5. ELECTRICAL CONDUCTIVITY = POLYNOMIAL

Parameters

VARIABLE = *STRING* ORDER = *INT* [VARIABLE_OFFSET = *REAL*] [CO = *REAL*] [C1 = *REAL*] ... [CN = *REAL*]

Example

Electrical Conductivity= Polynomial Variable=Temperature Order=1
C0=401.0 C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$\sigma_e = \sum_{i=0}^N C_i (X + X_o)^i \quad (4.47)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter, X_o is an optional offset (VARIABLE_OFFSET, default is zero) and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section 2.7.1.

4.8.6. ELECTRICAL CONDUCTIVITY = TBC

Parameters

Ki = *REAL*

Ti = *REAL*

E = *REAL*

R = *REAL*

Example

ELECTRICAL CONDUCTIVITY = TBC Ki=1.0 Ti=273 R=8.314 E=1e-3

Description Thermal battery electrical conductivity model (see Ken Chen).

$$\kappa(T) = \kappa_i \frac{T_i}{T} e^{-\frac{E}{R} \left(\frac{1}{T} - \frac{1}{T_i} \right)} \quad (4.48)$$

Here, T is temperature, T_i is the initial temperature provided by Ti, κ_i is the electrical conductivity at T_i provided by Ki, R is the universal gas constant provided by R and E is the energy provided by E.

4.8.7. ELECTRICAL CONDUCTIVITY = THERMAL

Parameters

[A = *REAL*]

[B = *REAL*]

[C = *REAL*]

[D = *REAL*]

Example

ELECTRICAL CONDUCTIVITY = THERMAL A = 1.0 B = -0.01

Description Cubic polynomial function of temperature for the conductivity.

$$\sigma_e = A + BT + CT^2 + DT^3 \quad (4.49)$$

4.9. ELECTRIC DISPLACEMENT

ELECTRIC DISPLACEMENT = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material (constitutive) model for the electric displacement

Summary Specifies the material (constitutive) model for the electric displacement

Parent

Block(s)

ARIA MATERIAL

4.9.1. ELECTRIC DISPLACEMENT = BASIC

This is an alias for LINEAR.

Example

Electric Displacement = Basic

4.9.2. ELECTRIC DISPLACEMENT = LINEAR

Parameters

(none)

Example

Electric Displacement = Linear

Description The electric displacement $\mathbf{D}$ is linearly proportional to the electric field ($\mathbf{E} = -\nabla V$)

$$\mathbf{D} = -\epsilon \nabla V \quad (4.50)$$

where ϵ is the electrical permittivity and V is the voltage (electric potential).

4.10. ELECTRICAL PERMITTIVITY

ELECTRICAL PERMITTIVITY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the electrical permittivity.

Summary Specifies the material model for the electrical permittivity.

Parent

Block(s)

ARIA MATERIAL

4.10.1. ELECTRICAL PERMITTIVITY = CONSTANT

Parameters

$E = REAL$

Example

ELECTRICAL PERMITTIVITY = CONSTANT $E = 1.0$

Description E is the value of the constant electrical permittivity.

4.10.2. ELECTRICAL PERMITTIVITY = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

ELECTRICAL PERMITTIVITY = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.11. ELECTRICAL RESISTANCE

ELECTRICAL RESISTANCE = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the electrical resistance.

Summary Specifies the material model for the electrical resistance.

Parent

Block(s)

ARIA MATERIAL

4.11.1. ELECTRICAL RESISTANCE = CONSTANT

Parameters

None.

Example

ELECTRICAL RESISTANCE = CONSTANT R = 1.0

Description R is the value of the constant electrical resistance.

4.11.2. ELECTRICAL RESISTANCE = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

ELECTRICAL RESISTANCE = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.11.3. ELECTRICAL RESISTANCE = EXPONENTIAL

Parameters

VARIABLE = *STRING*

[CONSTANT = *REAL*]

[MULTIPLIER = *REAL*]

EXPONENT = *REAL*

Example

Electrical Resistance = Exponential Variable=Temperature

Multiplier=1.0 Exponent=-0.3

Description Exponential function of in specified scalar variable. The electrical resistance is computed as

$$R = C + Me^{EX} \quad (4.51)$$

Here, C is the constant term supplied by the `CONSTANT` parameter which defaults to zero, M is the value supplied by the `MULTIPLIER` parameter which defaults to unity, X is the variable supplied by the `VARIABLE` parameter and E is the exponential multiplier provided by the `EXPONENT` parameter.

4.11.4. ELECTRICAL RESISTANCE = FROM_CONDUCTIVITY

Parameters

`R = REAL`

Example

`ELECTRICAL RESISTANCE = FROM_CONDUCTIVITY`

Description The resistance is computed as the inverse of the electrical conductivity which must be provided separately.

4.11.5. ELECTRICAL RESISTANCE = POLYNOMIAL

Parameters

`VARIABLE = STRING ORDER = INT [VARIABLE_OFFSET = REAL] [C0 = REAL] [C1 = REAL] ... [CN = REAL]`

Example

`Electrical Resistance= Polynomial Variable=Temperature Order=1
C0=401.0 C1=88.5`

Description Arbitrary order polynomial function of a specified scalar variable.

$$R = \sum_{i=0}^N C_i (X + X_o)^i \quad (4.52)$$

Here, N is the order of the polynomial provided by the `ORDER` parameter and X is the variable supplied by the `VARIABLE` parameter, X_o is an optional offset (`VARIABLE_OFFSET`, default is zero) and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The `VARIABLE` argument can be `TIME` or any internal Expression that evaluates to a scalar. For the latter case, the format of the `VARIABLE` argument is described in section [2.7.1](#).

4.11.6. ELECTRICAL RESISTANCE = USER_FUNCTION

Parameters

NAME = *STRING*

X = *STRING*

Example

Begin definition for function RESISTANCE_DATA

 Type is piecewise linear

 Abscissa is T

 Ordinate is Electrical_Resistance

 Begin Values

 # [K] [Ohm-um]

 273 1.00E-9

 323 7.99E-10

 ...

 873 1.09E-11

 End Values

End definition for function RESISTANCE_DATA

...

Begin Aria Material Foo

 ...

 Electrical Resistance = User_Function Name=RESISTANCE_DATA X=Temperature

 ...

End Aria Material Foo

Description A look-up function is used to compute the values of the resistance as a function of some other variable, i.e. $f(x)$. The function type (“piecewise linear” in the example above) must support the `differentiate()` method for Newton’s method.

Here NAME is the name of the user-defined function (RESISTANCE_DATA in the example) and X is the Aria name of the abscissa variable (TEMPERATURE in the example). Note that X is not necessarily the same name as the abscissa variable identified in the user-defined function (T in the example).

4.12. EMISSIVITY

EMISSIVITY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the emissivity.

Summary Specifies the material model for the emissivity.

Parent
Block(s)
ARIA MATERIAL

4.12.1. EMISSIVITY = CALORE_USER_SUB

Parameters

NAME = *STRING*
TYPE = *STRING*
[MULTIPLIER = *REAL*]
[NR = *INT*]
[R0 = *INT*]
[R1 = *INT*(etc.)]
[NI = *INT*]
[IO = *INT*]
[I1 = *INT*(etc.)]

Example

```
Emissivity = Calore_User_Sub name=w80afftuser type=element NR=2  
R0=1000 R1=0.7
```

Description NAME is the name of the user subroutine was registered with. NR and NI are the numbers of real and integer parameters, respectively. Each real (int) parameter is supplied by the R_n (I_n) parameter. Note: the parameters use zero based counting. The TYPE parameter denotes the API the user subroutine uses; currently Aria only supports types ELEMENT and NODE.

The optional MULTIPLIER parameter (defaults to 1.0) can be supplied to scale the output of the user subroutine, i.e., the flux f will be $f = m f_{user}$ where m is the multiplier and f_{user} is the output of the user subroutine.

See section [9.2.2](#) for a more complete example of a Calore user subroutine.

4.12.2. EMISSIVITY = CONSTANT

Parameters

E = *REAL*

Example

```
Emissivity = Constant E = 0.8
```

Description E is the value of the constant emissivity.

4.12.3. EMISSIVITY = POLYNOMIAL

Parameters

VARIABLE = *STRING* ORDER = *INT* [VARIABLE_OFFSET = *REAL*] [C0 = *REAL*] [C1 = *REAL*] ... [CN = *REAL*]

Example

Emissivity= Polynomial Variable=Temperature Order=1 C0=401.0
C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$\epsilon = \sum_{i=0}^N C_i (X + X_o)^i \quad (4.53)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter, X_o is an optional offset (VARIABLE_OFFSET, default is zero) and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section [2.7.1](#).

4.12.4. EMISSIVITY = ENCORE_FUNCTION

Parameters

NAME = *STRING*
[EVAL_TYPE = *STRING*]

Example

Emissivity = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.12.5. EMISSIVITY = USER_FUNCTION

Parameters

NAME = *STRING*

X = *STRING*

Example

Begin Definition for Function My_Emissivity

 Type is Piecewise Linear

 Begin Values

 100 0.7

 200 0.6

 300 0.5

 End

End

...

Begin Aria Material Foo

 ...

 Emissivity = User_Function Name=My_Emissivity X=Temperature

 ...

End Aria Material Foo

Description A look-up function is used to compute the values of the emissivity as a function of some other variable, i.e. $f(x)$. The function type (“piecewise linear” in the example above) must support the `differentiate()` method for Newton’s method.

Here NAME is the name of the user-defined function (My_Emissivity in the example) and X is the Aria name of the abscissa variable (TEMPERATURE in the example). Note that X is not necessarily the same name as the abscissa variable identified in the user-defined function (T in the example).

4.13. ENTHALPY

ENTHALPY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies a model for the enthalpy of a material.

Summary Specifies a model for the enthalpy of a material.

Parent

Block(s)

ARIA MATERIAL

4.13.1. ENTHALPY = CONSTANT

Parameters

H = *REAL*

Example

Enthalpy = Constant H=1e-4

Description The value is constant in space and time.

4.13.2. ENTHALPY = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

Enthalpy = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.14. EQUATION OF STATE

EQUATION OF STATE = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the equation of state for gas dynamics problems.

Summary Specifies the equation of state for gas dynamics problems.

Parent

Block(s)

ARIA MATERIAL

4.14.1. EQUATION OF STATE = IDEAL_GAS

Parameters

R = *REAL*

GAMMA = *REAL*

Example

Equation of State = Ideal_Gas R=8.314 Gamma=1.4

Description R is the gas constant and GAMMA is the ratio of heat capacities.

This model is used for gas dynamics problems where the density is an unknown. In this case, the pressure is given by the ideal gas law,

$$p = RT\rho \quad (4.54)$$

where T is the temperature and ρ is the density. Activating this model supplies several quantities that are related to this equation of state such as the pressure, temperature, and other gas dynamics related quantities.

4.15. HEAT CONDUCTION

HEAT CONDUCTION = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material (constitutive) model for the heat conduction (diffusive flux) in the bulk.

Summary Specifies the material (constitutive) model for the heat conduction (diffusive flux) in the bulk.

Parent

Block(s)

ARIA MATERIAL

4.15.1. HEAT CONDUCTION = BASIC

This is an alias for FOURIERS_LAW.

Example

Heat Conduction = Basic

4.15.2. HEAT CONDUCTION = CONVECTED_ENTHALPY

Parameters

(none)

Example

Heat Conduction = Convected_Enthalpy

Description The heat conduction (flux) $\mathbf{q}$ is given by,

$$\mathbf{q} = -h\rho\mathbf{v} \quad (4.55)$$

where h is the enthalpy, ρ is the density and $\mathbf{v}$ is the velocity.

4.15.3. HEAT CONDUCTION = FOURIERS_LAW

Parameters

(none)

Example

Heat Conduction = Fouriers_Law

Description The heat conduction (flux) $\mathbf{q}$ is given by Fourier's Law,

$$\mathbf{q} = -\kappa\nabla T \quad (4.56)$$

where κ is the thermal conductivity and T is the temperature.

4.15.4. HEAT CONDUCTION = GENERALIZED

Parameters

(none)

Example

Heat Conduction = Generalized

Description The heat conduction (flux) $\mathbf{q}$ is given by Fourier's Law,

$$\mathbf{q} = -\kappa\nabla T \quad (4.57)$$

where κ is the thermal conductivity tensor and T is the temperature.

4.15.5. HEAT CONDUCTION = THERMOELECTRIC

Parameters

(none)

Example

Heat Conduction = Thermoelectric

Description The heat conduction (flux) $\mathbf{q}$ is given by Fourier's Law combined with an electric energy flux,

$$\mathbf{q} = -\kappa \nabla T + \alpha T \mathbf{J} \quad (4.58)$$

where κ is the thermal conductivity, α is the Seebeck coefficient, T is the temperature and $\mathbf{J}$ is the thermoelectric current density [4.6.4](#).

4.16. HEAT OF VAPORIZATION

HEAT OF VAPORIZATION = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the heat of vaporization for a material or for a particular species.

Summary Quantifies the amount of energy consumed during evaporation per unit mass.

Parent

Block(s)

ARIA MATERIAL

4.16.1. HEAT OF VAPORIZATION = CONSTANT

Parameters

H_v = *REAL*

[SUBINDEX = *INT*]

Example

HEAT OF VAPORIZATION = CONSTANT SUBINDEX=0 H_v = 1.0

HEAT OF VAPORIZATION = CONSTANT SUBINDEX=1 H_v = 2.0

HEAT OF VAPORIZATION = CONSTANT SUBINDEX=3 H_v = 3.14

Description H_v is the value of the constant heat of vaporization and SUBINDEX is the optional species index (used in multicomponent systems).

4.17. HEAT TRANSFER COEFFICIENT

HEAT TRANSFER COEFFICIENT = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the heat transfer coefficient.

Summary Specifies the material model for the heat transfer coefficient.

Parent

Block(s)

ARIA MATERIAL

4.17.1. HEAT TRANSFER COEFFICIENT = CALORE_USER_SUB

Parameters

NAME = *STRING*

TYPE = *STRING*

[MULTIPLIER = *REAL*]

[NR = *INT*]

[R0 = *INT*]

[R1 = *INT*(etc.)]

[NI = *INT*]

[I0 = *INT*]

[I1 = *INT*(etc.)]

Example

```
Heat Transfer Coefficient = Calore_User_Sub name=w80afftuser  
type=element NR=2 R0=1000 R1=0.7
```

Description NAME is the name of the user subroutine was registered with. NR and NI are the numbers of real and integer parameters, respectively. Each real (int) parameter is supplied by the R_n (I_n) parameter. Note: the parameters use zero based counting. The TYPE parameter denotes the API the user subroutine uses; currently Aria only supports types ELEMENT and NODE.

The optional MULTIPLIER parameter (defaults to 1.0) can be supplied to scale the output of the user subroutine, i.e., the flux f will be $f = m f_{user}$ where m is the multiplier and f_{user} is the output of the user subroutine.

See section [9.2.2](#) for a more complete example of a Calore user subroutine.

4.17.2. HEAT TRANSFER COEFFICIENT = CONSTANT

Parameters

`H = REAL`

Example

Heat Transfer Coefficient = Constant `h = 0.8`

Description `H` is the value of the constant heat transfer coefficient.

4.17.3. HEAT TRANSFER COEFFICIENT = ENCORE_FUNCTION

Parameters

`NAME = STRING`

`[EVAL_TYPE = STRING]`

Example

Heat Transfer Coefficient = Encore_Function `Name=My_Function`

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument `EVAL_TYPE` can be used to select the particular function on the Encore function object. Valid options include `VALUE`, `DOT`, `GRADIENT`, `FLUX` and `STRESS`. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – `VALUE` for `NO_OP` expressions, `DOT` for `DT_OP` expressions and `GRADIENT` for `GRAD_OP` expressions.

4.17.4. HEAT TRANSFER COEFFICIENT = POLYNOMIAL

Parameters

`VARIABLE = STRING` `ORDER = INT` `[VARIABLE_OFFSET = REAL]` `[C0 = REAL]` `[C1 = REAL]` ... `[CN = REAL]`

Example

Heat Transfer Coefficient= Polynomial Variable=Temperature
Order=1 C0=401.0 C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$h = \sum_{i=0}^N C_i (X + X_o)^i \quad (4.59)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter, X_o is an optional offset (VARIABLE_OFFSET, default is zero) and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section [2.7.1](#).

4.17.5. HEAT TRANSFER COEFFICIENT = USER_FUNCTION

Parameters

NAME = *STRING*

X = *STRING*

Example

```
Begin Definition for Function My_Heat_Transfer_Coefficient
```

```
    Type is Piecewise Linear
```

```
    Begin Values
```

```
        100 0.7
```

```
        200 0.6
```

```
        300 0.5
```

```
    End
```

```
End
```

```
...
```

```
Begin Aria Material Foo
```

```
    ...
```

```
    Heat Transfer Coefficient = User_Function Name=My_Heat_Transfer_Coefficient
```

```
    X=Temperature
```

```
    ...
```

```
End Aria Material Foo
```

Description A look-up function is used to compute the values of the heat transfer coefficient as a function of some other variable, i.e. $f(x)$. The function type (“piecewise linear” in the example above) must support the `differentiate()` method for Newton’s method.

Here NAME is the name of the user-defined function (My_Heat_Transfer_Coefficient in the example) and X is the Aria name of the abscissa variable (TEMPERATURE in the example). Note that X is not necessarily the same name as the abscissa variable identified in the user-defined function (T in the example).

4.18. INTRINSIC PERMEABILITY

INTRINSIC PERMEABILITY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the intrinsic permeability tensor for porous flow in Darcy's Law.

Summary Specifies the material model for the intrinsic permeability tensor for porous flow in Darcy's Law. In general, the permeability may be nonisotropic in porous media. In that case, Darcy's law may be written as,

$$\rho \mathbf{v}_d = \mathbf{f} = -\frac{\rho k_r}{\mu} \mathbf{K} \cdot (\nabla P - \rho \mathbf{g}) \quad (4.60)$$

where $\mathbf{K}$ is the intrinsic permeability tensor, ρ is the density, $\mathbf{v}_d$ is the Darcy velocity, $\mathbf{f}$ is the mas flux, k_r is the relative permeability, P is pressure and $\mathbf{g}$ is gravity.

Parent
Block(s)
ARIA MATERIAL

4.18.1. INTRINSIC PERMEABILITY = CONSTANT

Parameters

[XX = *REAL*]
[XY = *REAL*]
[XZ = *REAL*]
[YX = *REAL*]
[YY = *REAL*]
[YZ = *REAL*]
[ZX = *REAL*]
[ZY = *REAL*]
[ZZ = *REAL*]

Example

Intrinsic Permeability = Constant XX=1 YY=2 ZZ=1

Description All components default to zero and all values are constant in space and time.

4.19. INTERNAL ENERGY

INTERNAL ENERGY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies a model for the internal energy of a material.

Summary Specifies a model for the internal of a material.

Parent
Block(s)
ARIA MATERIAL

4.19.1. INTERNAL ENERGY = ENCORE_FUNCTION

Parameters

NAME = *STRING*
[EVAL_TYPE = *STRING*]

Example

Internal Energy = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.19.2. INTERNAL ENERGY = GAS_PHASE

Parameters

(none)

Example

Internal Energy = Gas_Phase

Description The internal energy e is computed using thermodynamic relation

$$e = h - P/\rho \quad (4.61)$$

where h is the enthalpy, P is the (partial) pressure and ρ is the density.

4.20. LEVEL SET HEAVISIDE

LEVEL SET HEAVISIDE = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the functional form of the Heaviside function used with level set algorithms. This also implies the Dirac delta function used for level set algorithms.

Summary Specifies the functional form of the Heaviside function used with level set algorithms. This also implies the Dirac delta function used for level set algorithms.

Parent
Block(s)
ARIA MATERIAL

4.20.1. LEVEL SET HEAVISIDE = SMOOTH

Parameters
(none)

Example
LEVEL SET HEAVISIDE = SMOOTH

Description The Heaviside function in this case is given as

$$H(f) = \frac{1}{2} [1 + f/w + \sin(\pi f/w) / \pi] \quad (4.62)$$

Here f is the level set distance function and w is half of the level set width (see [4.21](#)).

4.21. LEVEL SET WIDTH

LEVEL SET WIDTH = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the total width of the level set interface. Half of this width falls on the positive side of the zero level set and half falls on the negative side.

Summary Specifies the total width of the level set interface. Half of this width falls on the positive side of the zero level set and half falls on the negative side.

Parent
Block(s)
ARIA MATERIAL

4.21.1. LEVEL SET WIDTH = CONSTANT

Parameters

WIDTH = *REAL*

Example

LEVEL SET WIDTH = CONSTANT WIDTH=0.1

Description This is what you'd expect it to be – a uniform constant everywhere for all time.

4.22. LUBRICATION HEIGHT LOWER

LUBRICATION HEIGHT LOWER = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the lower height function for the lubrication equation.

Summary Specifies the material model for the lower height function for the lubrication equation.

Parent

Block(s)

ARIA MATERIAL

4.22.1. LUBRICATION HEIGHT LOWER = CONSTANT

Parameters

H_LOWER = *REAL*

Example

LUBRICATION HEIGHT LOWER = CONSTANT H_LOWER = 1.0

Description H_LOWER is the constant value.

4.23. LUBRICATION HEIGHT UPPER

LUBRICATION HEIGHT UPPER = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the upper height function for the lubrication equation.

Summary Specifies the material model for the upper height function for the lubrication equation.

Parent

Block(s)

ARIA MATERIAL

4.23.1. LUBRICATION HEIGHT UPPER = CONSTANT

Parameters

H_UPPER = *REAL*

Example

LUBRICATION HEIGHT UPPER = CONSTANT H_UPPER = 1.0

Description H_UPPER is the constant value.

4.24. LUBRICATION K

LUBRICATION K = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the “k” model for the lubrication equation.

Summary In the standard derivation of Reynolds’ lubrication theory, the flow is assumed to be laminar and the constant “12” appears in the equation. However, there are extensions to the standard lubrication theory that allow studying turbulent flow by replacing the “12” with a model for turbulent mixing, a scalar that we call K .

If this line is omitted, the value of $K = 12$ is assumed. However, other forms for this constant K may be used.

Parent

Block(s)

ARIA MATERIAL

4.24.1. LUBRICATION K = CONSTANT

Parameters

K = *REAL*

Example

LUBRICATION K = CONSTANT K = 12.0

Description K is the constant value. Defaults to $K = 12$ if this line is omitted.

4.24.2. LUBRICATION K = PRANDTL_MIXING

Parameters

(none)

Example

LUBRICATION K = PRANDTL_MIXING

Description This model calculates the turbulent mixing viscosity based on the standard Prandtl mixing theory. First, the Reynolds' number is calculated using

$$Re = \frac{h\rho\sqrt{V_{UPPER} - V_{LOWER}}}{\mu}. \quad (4.63)$$

Then, the value of K is calculated with

$$K = \begin{cases} 12 & Re < 2000 \\ 0.03(2Re)^{0.75} & Re > 2000 \end{cases}. \quad (4.64)$$

4.25. LUBRICATION VELOCITY LOWER

LUBRICATION VELOCITY LOWER = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the velocity of the lower boundary for the lubrication equation.

Summary Specifies the material model for the velocity of the lower boundary for the lubrication equation.

Parent

Block(s)

ARIA MATERIAL

4.25.1. LUBRICATION VELOCITY LOWER = CONSTANT

Parameters

V_LOWER = *REAL*

Example

LUBRICATION VELOCITY LOWER = CONSTANT V_LOWER = 0.0

Description V_LOWER is the constant value.

4.26. LUBRICATION VELOCITY UPPER

LUBRICATION VELOCITY UPPER = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the velocity of the upper boundary for the lubrication equation.

Summary Specifies the material model for the velocity of the upper boundary for the lubrication equation.

Parent
Block(s)
ARIA MATERIAL

4.26.1. LUBRICATION VELOCITY UPPER = CONSTANT

Parameters
V_UPPER = *REAL*

Example
LUBRICATION VELOCITY UPPER = CONSTANT V_UPPER = 0.0

Description V_UPPER is the constant value.

4.27. MASS FLUX

MASS FLUX = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies a constitutive model for the mass flux for porous flow applications.

Summary Specifies a constitutive model for the mass flux for porous flow applications.

Parent
Block(s)
ARIA MATERIAL

4.27.1. MASS FLUX = DARCY

Parameters

[GX = *REAL*]

[GY = *REAL*]

[GZ = *REAL*]

Example

Mass Flux = Darcy GY=-9.8

Description The macroscopic, convective mass flux in phase β , $\rho \mathbf{v}$ is obtained from the extended Darcy's Law,

$$\mathbf{F} = \rho \mathbf{f} = -\frac{\rho k_r}{\mu} \mathbf{K} \cdot (\nabla P - \rho \mathbf{g}) \quad (4.65)$$

4.28. MESH LAMBDA

MESH LAMBDA = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the λ Lamé coefficient for the mesh (psuedo-solid) stress tensor.

Summary The solid stress $\mathbf{T}$ is given by

$$\mathbf{T} = \lambda E_{kk} \mathbf{I} + 2\mu \mathbf{E} - \beta (T - T_{ref}) \mathbf{I} \quad (4.66)$$

where λ and μ are the Lamé coefficients, $\mathbf{E} = \frac{1}{2} (\nabla \mathbf{d} + \nabla \mathbf{d}^T)$ is the deformation tensor, β is the coefficient of thermal stress, T is temperature and T_{ref} is the thermal strain reference temperature.

These Lamé coefficients are related to the more standard Young's modulus, Poisson's ratio and CTE (α) as follows:

$$2\mu = \frac{E}{(1 + \nu)} \quad (4.67)$$

$$\lambda = \frac{\nu E}{(1 + \nu)(1 - 2\nu)} = 2\mu \frac{\nu}{(1 - 2\nu)} \quad (4.68)$$

$$\beta = \frac{\alpha E}{(1 - 2\nu)} = \alpha (3\lambda + 2\mu) \quad (4.69)$$

When a user supplies the Young's modulus, Poisson's ratio and CTE properties Aria internally converts them into the Lamé coefficients.

Parent

Block(s)

ARIA MATERIAL

4.28.1. MESH LAMBDA = CONSTANT

Parameters

$L = \textit{REAL}$

Example

MESH LAMBDA = CONSTANT L = 1.0

Description L is the value of the constant λ .

4.28.2. MESH LAMBDA = CONVERTED

Parameters

(None)

Example

MESH LAMBDA = Converted

Description Aria will use Young's modulus and Poisson ratio to compute the Lamé λ coefficient. Supplying the Lamé coefficients is more computationally efficient but perhaps less convenient, especially if the material properties are varying (e.g., temperature dependent in a non-isothermal problem).

4.28.3. MESH LAMBDA = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

MESH LAMBDA = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.29. MESH TWO MU

MESH TWO MU = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for twice the μ Lamé coefficient for the mesh (psuedo-solid) stress tensor.

Summary The solid stress $\mathbf{T}$ is given by

$$\mathbf{T} = \lambda E_{kk} \mathbf{I} + 2\mu \mathbf{E} - \beta (T - T_{ref}) \mathbf{I} \quad (4.70)$$

where λ and μ are the Lamé coefficients, $\mathbf{E} = \frac{1}{2} (\nabla \mathbf{d} + \nabla \mathbf{d}^T)$ is the deformation tensor, β is the coefficient of thermal stress, T is temperature and T_{ref} is the thermal strain reference temperature.

These Lamé coefficients are related to the more standard Young's modulus, Poisson's ratio and CTE (α) as follows:

$$2\mu = \frac{E}{(1 + \nu)} \quad (4.71)$$

$$\lambda = \frac{\nu E}{(1 + \nu)(1 - 2\nu)} = 2\mu \frac{\nu}{(1 - 2\nu)} \quad (4.72)$$

$$\beta = \frac{\alpha E}{(1 - 2\nu)} = \alpha (3\lambda + 2\mu) \quad (4.73)$$

When a user supplies the Young's modulus, Poisson's ratio and CTE properties Aria internally converts them into the Lamé coefficients.

Parent
Block(s)
ARIA MATERIAL

4.29.1. MESH TWO MU = CONSTANT

Parameters
TWO_MU = *REAL*

Example
MESH TWO MU = CONSTANT TWO_MU = 1.0

Description TWO_MU is the value of 2μ .

4.29.2. MESH TWO MU = CONVERTED

Parameters

(None)

Example

```
MESH TWO MU = Converted
```

Description Aria will use Young's modulus and Poisson ratio to compute the Lamé μ coefficient. Supplying the Lamé coefficients is more computationally efficient but perhaps less convenient, especially if the material properties are varying (e.g., temperature dependent in a non-isothermal problem).

4.29.3. MESH TWO MU = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

```
TWO_MU = Encore_Function Name=My_Function
```

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.30. MESH STRESS

```
MESH STRESS = MODEL [param1 = val1, param2 = val2 ...]
```

Description Specifies a contribution to the mesh (pseudo-solid) stress tensor. Multiple stresses are combined additively and may be specified by using this line command multiple times.

Summary Specifies a contribution to the mesh (pseudo-solid) stress tensor. The total stress $\mathbf{T}$ is given by

$$\mathbf{T} = \sum_j \mathbf{T}_j \quad (4.74)$$

Parent
Block(s)
 ARIA MATERIAL

4.30.1. MESH STRESS = ISOTHERMAL

Parameters

$T = \text{REAL}$

$T\_REF = \text{REAL}$

Example

MESH STRESS = Isothermal T=500 T_ref=325

Description This stress accounts for the mechanical stresses due to thermally induced strains.

$$\mathbf{T} = -\beta (T - T_{ref}) \mathbf{I} \quad (4.75)$$

where β is the Lamé coefficient of thermal stress (related to the coefficient of thermal expansion, α), T is the temperature and T_{ref} is the temperature of the undeformed reference state of the mesh (pseudo-solid). This is a specialization of the THERMAL model that uses uniform, fixed temperature and thermal strain reference temperature.

4.30.2. MESH STRESS = LINEAR_ELASTIC

Parameters

REFERENCE_FRAME = ‘MOVING’ | ‘UNDEFORMED’

Example

MESH STRESS = Linear_Elastic Reference_Frame = undeformed

Description Supplies the linear elasticity stress tensor,

$$\mathbf{T} = \lambda \text{trace } \mathbf{E} \mathbf{I} + 2\mu \mathbf{E} \quad (4.76)$$

where λ and μ are the Lamé coefficients and $\mathbf{E}$ is the strain tensor. When the choice of reference frame is “UNDEFORMED” then the strain is computed in the undeformed reference state; this is commonly referred to as small strain theory. When the reference frame is “MOVING” then the strain is computed with respect to the deformed coordinates.

Specifically, the strain tensor is given by

$$\mathbf{E} = \frac{1}{2} (\nabla \mathbf{d} + \nabla \mathbf{d}^t) \quad (4.77)$$

where $\mathbf{d}$ is the mesh displacement field. The choice of reference frame determines whether the ∇ operator is computed in the undeformed or moving reference frames.

4.30.3. MESH STRESS = NEOHOOKEAN_ELASTIC

Parameters
(none)

Example
MESH STRESS = Neohookean_Elastic

Description Supplies a nonlinear hyperelastic stress of the form,

$$\mathbf{T} = \frac{\mu}{J} (\mathbf{b} - \mathbf{I}) + \frac{\lambda}{J} \ln J \mathbf{I} \quad (4.78)$$

where λ and μ and the Lamé coefficients, $\mathbf{b} \equiv \mathbf{F} \cdot \mathbf{F}^t$ is the left Cauchy-Green tensor, $\mathbf{F}$ is the deformation gradient and $J \equiv \det \mathbf{F}$. See, e.g., [5] or [6].

4.30.4. MESH STRESS = NONLINEAR_ELASTIC

Parameters
(none)

Example
MESH STRESS = Nonlinear_Elastic

Description Supplies a nonlinear elastic stress,

$$\mathbf{T} = \lambda \text{trace } \mathbf{E} \mathbf{I} + 2\mu \mathbf{E} \quad (4.79)$$

where λ and μ and the Lamé coefficients and $\mathbf{E}$ is the strain tensor. The particular choice of strain tensor chosen depends on where the configuration (reference frame) which is set via the MESH MOTION command line. See section 5.17 for more information. When the MESH MOTION is set to REFERENCE_FRAME then the Green strain is used. Otherwise, the Almansi strain is used.

4.30.5. MESH STRESS = RESIDUAL

Parameters

[SXX | SX = *REAL*]

[SYY | SY = *REAL*]

[SZZ | SZ = *REAL*]

[SXY = *REAL*]

[SXZ = *REAL*]

[SYZ = *REAL*]

Example

SOLID STRESS = Residual Sxx=0.02 Syy=0.02

Description This stress accounts for the initial residual stress in a solid that is constant and uniform everywhere. The components of the residual stress tensor are supplied by the (up-to) six components SXX, SYY, SZZ, SXY, SXZ, and SYZ.

This is directly analogous to the ISTRESS condition in ANSYS. To that end, the diagonal components can be specified as either SXX or SX etc.

4.30.6. MESH STRESS = THERMAL

Parameters

(none)

Example

MESH STRESS = Thermal

Description This stress accounts for the mechanical stresses due to thermally induced strains.

$$\mathbf{T} = -\beta (T - T_{ref}) \mathbf{I} \quad (4.80)$$

where β is the Lamé coefficient of thermal stress (related to the coefficient of thermal expansion, α), T is the temperature and T_{ref} is the temperature of the undeformed reference state of the mesh (pseudo-solid).

4.30.7. MESH STRESS = LAME

Parameters

MODEL = *STRING*

Example

MESH STRESS = Lame Model = Neo_Hookean

Description This stress interfaces with the Lamé constitutive model library used by Sierra/SolidMechanics. As such, it allows the use of many of Lamé's constitutive models. Sierra/Multimechanics prepares the kinematic quantities, and Lamé returns the Cauchy stress, which is integrated in the MESH equation.

Material parameters for the constitutive models are handled by an input block consistent with the Sierra/SolidMechanics formatting. For documentation of the available constitutive models and the required parameter input, please see the Sierra/SolidMechanics documentation.

Currently this interface is instrumented to support hyperelastic constitutive models, and is restricted to the following models:

- NEO_HOOKEAN
- THERMALBATTERYSEPARATOR
- SOILFOAMPHASETRANSITION

4.31. MOLECULAR WEIGHT

MOLECULAR WEIGHT = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the molecular weight for a species.

Summary Specifies the molecular weight for a species.

Parent
Block(s)
ARIA MATERIAL

4.31.1. MOLECULAR WEIGHT = CONSTANT

Parameters

M = *REAL*
[SUBINDEX = *INT*]

Example

Molecular Weight = Constant Subindex=1 M = 17.0
Molecular Weight = Constant Subindex=2 M = 23.0
Molecular Weight = Constant Subindex=5 M = 34.0

Description M is the value of the molecular weight.

SUBINDEX is the species subindex.

4.31.2. MOLECULAR WEIGHT = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

Molecular Weight = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.32. MOMENTUM STRESS

MOMENTUM STRESS = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies a contribution to the fluid stress tensor. Multiple stresses are combined additively and may be specified by using this line command multiple times.

Summary Specifies a contribution to the fluid momentum stress tensor. The total stress $\mathbf{T}$ is given by

$$\mathbf{T} = \sum_j \mathbf{T}_j \quad (4.81)$$

Parent

Block(s)

ARIA MATERIAL

4.32.1. MOMENTUM STRESS = LS_CAPILLARY

Parameters

(none)

Example

MOMENTUM STRESS = Newtonian

MOMENTUM STRESS = LS_Capillary

Description This adds the capillary boundary condition contributions in the vicinity of the level set interface.

$$\mathbf{T} = \sigma \delta(F) (\mathbf{I} - \mathbf{N}\mathbf{N}) \quad (4.82)$$

where σ is the surface tension, $\delta(F)$ is the level set delta function, F is the level set distance function and $\mathbf{N}$ is the level set normal field.

4.32.2. MOMENTUM STRESS = INCOMPRESSIBLE_NEWTONIAN

Parameters

[PRESSURE = *STRING*]

Example

MOMENTUM STRESS = Incompressible_Newtonian

Description Supplies the incompressible Newtonian stress tensor,

$$\mathbf{T} = -p\mathbf{I} + \mu (\nabla \mathbf{v} + \nabla \mathbf{v}^t) \quad (4.83)$$

where μ is the fluid viscosity, p is the pressure and $\mathbf{v}$ is the fluid velocity. The viscosity μ is provided with the viscosity line command as described in section [4.56](#).

Note that this model does not include stress contributions that are proportional to the divergence of the velocity. To incorporate those contributions, use the NEWTONIAN_DILATIONAL stress model in addition to this model, or use the FORMAL_NEWTONIAN stress model instead of this model.

By default, the pressure field used by this model is PRESSURE with the same subindex as the model. The optional parameter PRESSURE can be used to specify an alternate pressure field. This is useful for running problems with a continuous velocity field but a discontinuous pressure field.

4.32.3. MOMENTUM STRESS = FORMAL_NEWTONIAN

Parameters

(none)

Example

MOMENTUM STRESS = Formal_Newtonian

Description Supplies the complete Newtonian stress tensor,

$$\mathbf{T} = -p\mathbf{I} + \mu (\nabla \mathbf{v} + \nabla \mathbf{v}^t) + \left(\kappa - \frac{2}{3}\mu \right) \nabla \cdot \mathbf{v} \mathbf{I} \quad (4.84)$$

where μ is the fluid viscosity, p is the pressure and $\mathbf{v}$ is the fluid velocity. The viscosity μ is provided with the viscosity line command as described in section 4.56. The bulk viscosity κ is provided with the bulk viscosity line command as described in section 4.4.

4.32.4. MOMENTUM STRESS = NEWTONIAN_DILATIONAL

Parameters

(none)

Example

MOMENTUM STRESS = Newtonian_Dilational

Description Adds the dilational stress contribution for Newtonian fluids,

$$\mathbf{T} = \left(\kappa - \frac{2}{3}\mu \right) \nabla \cdot \mathbf{v} \mathbf{I} \quad (4.85)$$

where κ is the bulk viscosity of the fluid, μ is the fluid (dynamic) viscosity and $\mathbf{v}$ is the fluid velocity. The viscosity μ is provided with the viscosity line command as described in section 4.56. The bulk viscosity κ is provided with the bulk viscosity line command as described in section 4.4.

See, also, the NEWTONIAN momentum stress model.

4.32.5. MOMENTUM STRESS = NEWTONIAN_VISCOUS

Parameters

(none)

Example

MOMENTUM STRESS = Newtonian_Viscous

Description Supplies only the viscous contribution of the Newtonian stress tensor,

$$\mathbf{T} = \mu (\nabla \mathbf{v} + \nabla \mathbf{v}^t) \quad (4.86)$$

where μ is the fluid viscosity and $\mathbf{v}$ is the fluid velocity. The viscosity μ is provided with the viscosity line command as described in section 4.56.

4.32.6. MOMENTUM STRESS = NEWTONIAN_PRESSURE

Parameters

(none)

Example

MOMENTUM STRESS = Newtonian_Pressure

Description Supplies only the pressure contribution of the Newtonian stress tensor,

$$\mathbf{T} = -p\mathbf{I} \quad (4.87)$$

where p is the pressure.

4.32.7. MOMENTUM STRESS = MAXWELL

Parameters

(none)

Example

MOMENTUM STRESS = Maxwell

Description Includes the force due to an electric field (neglecting magnetic effects) due to the Maxwell stress tensor,

$$\mathbf{T}_M = \varepsilon \left(\mathbf{E}\mathbf{E}^T - \frac{1}{2}(\mathbf{E} \cdot \mathbf{E})\mathbf{I} \right) \quad (4.88)$$

where ε is the electrical permittivity and $\mathbf{E}$ is the electric field. The divergence of the Maxwell stress tensor is a force applied to the momentum equation,

$$\nabla \cdot \mathbf{T}_M = \rho_e \mathbf{E} - \frac{1}{2}(\mathbf{E} \cdot \mathbf{E})\nabla \varepsilon, \quad (4.89)$$

where ρ_e is the volumetric charge density.

4.33. POISSONS RATIO

POISSONS RATIO = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the Poisson's ratio.

Summary The solid stress $\mathbf{T}$ is given by

$$\mathbf{T} = \lambda E_{kk} \mathbf{I} + 2\mu \mathbf{E} - \beta (T - T_{ref}) \mathbf{I} \quad (4.90)$$

where λ and μ are the Lamé coefficients, $\mathbf{E} = \frac{1}{2} (\nabla \mathbf{d} + \nabla \mathbf{d}^T)$ is the deformation tensor, β is the coefficient of thermal stress, T is temperature and T_{ref} is the thermal strain reference temperature.

These Lamé coefficients are related to the more standard Young's modulus, Poisson's ratio and CTE (α) as follows:

$$2\mu = \frac{E}{(1 + \nu)} \quad (4.91)$$

$$\lambda = \frac{\nu E}{(1 + \nu)(1 - 2\nu)} = 2\mu \frac{\nu}{(1 - 2\nu)} \quad (4.92)$$

$$\beta = \frac{\alpha E}{(1 - 2\nu)} = \alpha (3\lambda + 2\mu) \quad (4.93)$$

When a user supplies the Young's modulus, Poisson's ratio and CTE properties Aria internally converts them into the Lamé coefficients.

Supplying the Lamé coefficients is more computationally efficient but perhaps less convenient, especially if the material properties are varying (e.g., temperature dependent in a non-isothermal problem).

Parent
Block(s)
ARIA MATERIAL

4.33.1. POISSONS RATIO = CONSTANT

Parameters

PR = *REAL*

Example

POISSONS RATIO = CONSTANT PR = 1.0

Description PR is the value of the constant Poisson's ratio.

4.33.2. POISSONS RATIO = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

POISSONS RATIO = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.34. POROSITY

POROSITY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the porosity for porous flow applications.

Summary Specifies the material model for the porosity for porous flow applications.

Parent

Block(s)

ARIA MATERIAL

4.34.1. POROSITY = CONSTANT

Parameters

PHI = *REAL*

Example

Porosity = Constant PHI=0.1

Description The value is constant in space and time.

4.34.2. POROSITY = DEFORMING

Parameters

PHI_INIT = *REAL*

Example

Porosity = Deforming

Description The porosity evolves from an initial value in accordance with a deforming media.

$$\phi = 1 - (1 - \phi_o) e^{\epsilon_v} \quad (4.94)$$

where ϵ_v is the volume strain,

$$\epsilon_v = \nabla \cdot \mathbf{d} \quad (4.95)$$

where $\mathbf{d}$ is the total mesh displacement field. Here ϕ_o is the initial porosity value given by the PHI_INIT parameter.

4.34.3. POROSITY = POLYNOMIAL

Parameters

VARIABLE = *STRING* ORDER = *INT* [VARIABLE_OFFSET = *REAL*] [C0 = *REAL*] [C1 = *REAL*] ... [CN = *REAL*]

Example

Porosity= Polynomial Variable=Temperature Order=1 C0=401.0
C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$\phi = \sum_{i=0}^N C_i (X + X_o)^i \quad (4.96)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter, X_o is an optional offset (VARIABLE_OFFSET, default is zero) and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section [2.7.1](#).

4.34.4. POROSITY = ROCK_COMPRESSIBLE

Parameters

REF_POROSITY = *REAL*

REF_PRESSURE = *REAL*

CR = *REAL*

Example

Porosity = Rock_Compressible Ref_Porosity=0.1
Ref_Pressure=101325 Cr=-1e-7

Description The compressibility of a porous material is defined as

$$C_r = \frac{1}{\phi} \frac{\partial \phi}{\partial P} \quad (4.97)$$

where ϕ is the porosity and P is pressure. Using this definition, we define an approximate model for the porosity as a function of pressure,

$$\phi = \phi_{ref} (1 + C_r (P - P_{ref})) \quad (4.98)$$

where ϕ_{ref} is given by the REF_POROSITY parameter and is the porosity at the reference pressure P_{ref} which is given by the REF_PRESSURE parameter. The compressibility C_r is given by the CR parameter.

4.35. RADIATION FORM FACTOR

RADIATION FORM FACTOR = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the radiative heat transfer form factor used in the GENERALIZED_RAD boundary condition.

Summary The form factor represents the fraction of the radiation leaving a surface which interacts with a body at another temperature. Thus the form factor should be less than or equal to unity.

Parent

Block(s)

ARIA MATERIAL

4.35.1. RADIATION FORM FACTOR = CALORE_USER_SUB

Parameters

NAME = *STRING*

TYPE = *STRING*

[MULTIPLIER = *REAL*]

[NR = *INT*]

[R0 = *INT*]

[R1 = *INT*(etc.)]

[NI = *INT*]

[I0 = *INT*]

[I1 = *INT*(etc.)]

Example

Radiation Form Factor = Calore_User_Sub name=w80afftuser
type=element NR=2 R0=1000 R1=0.7

Description NAME is the name of the user subroutine was registered with. NR and NI are the numbers of real and integer parameters, respectively. Each real (int) parameter is supplied by the Rn (In) parameter. Note: the parameters use zero based counting. The TYPE parameter denotes the API the user subroutine uses; currently Aria only supports types ELEMENT and NODE.

The optional MULTIPLIER parameter (defaults to 1.0) can be supplied to scale the output of the user subroutine, i.e., the flux f will be $f = m f_{user}$ where m is the multiplier and f_{user} is the output of the user subroutine.

See section [9.2.2](#) for a more complete example of a Calore user subroutine.

4.35.2. RADIATION FORM FACTOR = CONSTANT

Parameters

$F = REAL$

Example

Radiation Form Factor = Constant $F = 0.8$

Description F is the value of the constant radiation form factor.

4.35.3. RADIATION FORM FACTOR = POLYNOMIAL

Parameters

VARIABLE = *STRING* ORDER = *INT* [VARIABLE_OFFSET = *REAL*] [CO = *REAL*] [C1 = *REAL*] ... [CN = *REAL*]

Example

Radiation Form Factor= Polynomial Variable=Temperature Order=1
C0=401.0 C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$F = \sum_{i=0}^N C_i (X + X_o)^i \quad (4.99)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter, X_o is an optional offset (VARIABLE_OFFSET, default is zero) and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section [2.7.1](#).

4.35.4. RADIATION FORM FACTOR = ENCORE_FUNCTION

Parameters

NAME = *STRING*
[EVAL_TYPE = *STRING*]

Example

Radiation Form Factor = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.35.5. RADIATION FORM FACTOR = USER_FUNCTION

Parameters

NAME = *STRING*
X = *STRING*

Example

```

Begin Definition for Function My_Radiation_Form_Factor
  Type is Piecewise Linear
  Begin Values
    100 0.7
    200 0.6
    300 0.5
  End
End
...

Begin Aria Material Foo
  ...
  Radiation Form Factor = User_Function Name=My_Radiation_Form_Factor X=Temperature
  ...
End Aria Material Foo

```

Description A look-up function is used to compute the values of the form factor as a function of some other variable, i.e. $f(x)$. The function type (“piecewise linear” in the example above) must support the `differentiate()` method for Newton’s method.

Here NAME is the name of the user-defined function (My_Radiation_Form_Factor in the example) and X is the Aria name of the abscissa variable (TEMPERATURE in the example). Note that X is not necessarily the same name as the abscissa variable identified in the user-defined function (T in the example).

4.36. RADIATIVE CONDUCTIVITY

RADIATIVE CONDUCTIVITY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the radiative effective thermal conductivity.

Summary Specifies the material model for the radiative portion of thermal conductivity that appears in the diffusion term of the energy equation for temperature.

Parent
Block(s)
 ARIA MATERIAL

4.36.1. RADIATIVE CONDUCTIVITY = CONSTANT

Parameters
 Krad = *REAL*

Example
 RADIATIVE CONDUCTIVITY = CONSTANT Krad = 1.0

Description Krad is the value of the constant radiative thermal conductivity.

4.36.2. RADIATIVE CONDUCTIVITY = CHEMEQ_FOAM

Parameters

Kc0 = *REAL*

Kc1 = *REAL*

Example

Radiative Conductivity = ChemEq_Foam Kc0 = 0.00268 Kc1 = 0.0

Description For a reacting foam defined in ChemEq, this model uses

$$k_{rad} = \frac{Kc_0}{Kc_1 + \sum_s Y_i} \sigma T^3 \quad (4.100)$$

where the denominator includes the sum of the mass fractions of the solid species of the foam. This uses the species phase definition from the ChemEq block to determine which species are solid. This model can only be used in a material block which also contains a ChemEq definition.

This uses expressions for the mass fractions, so its material block must also include “Mass_Fraction of X = From_ChemEq” for each solid species.

The GLOBAL CONSTANTS block must include include the STEFAN-BOLTZMANN CONSTANT entry to provide a value of σ .

4.36.3. RADIATIVE CONDUCTIVITY = OPTICALLY_THICK

Parameters

K = *REAL*

N = *REAL*

BETA_R = *REAL*

Example

RADIATIVE CONDUCTIVITY = OPTICALLY_THICK N = 2.1 BETA_R = 1.0e-5

Description Thermal conductivity used to model effective radiative conductivity diffusion in the optically-thick limit. Constant values for index of refraction n , and Rosseland-mean extinction coefficient β_R must be provided on the input line.

$$k_{rad} = \frac{16\sigma n^2}{3\beta_R} T^3 \quad (4.101)$$

The GLOBAL CONSTANTS block must include include the STEFAN-BOLTZMANN CONSTANT entry to provide a value of σ .

4.36.4. RADIATIVE CONDUCTIVITY = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

Radiative Conductivity = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.36.5. RADIATIVE CONDUCTIVITY = POLYNOMIAL

Parameters

VARIABLE = *STRING* ORDER = *INT* [VARIABLE_OFFSET = *REAL*] [C0 = *REAL*] [C1 = *REAL*] ... [CN = *REAL*]

Example

Radiative Conductivity= Polynomial Variable=Temperature Order=1
C0=401.0 C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$\kappa = \sum_{i=0}^N C_i (X + X_o)^i \quad (4.102)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter, X_o is an optional offset (VARIABLE_OFFSET, default is zero) and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section [2.7.1](#).

4.36.6. RADIATIVE CONDUCTIVITY = USER_FUNCTION

Parameters

NAME = *STRING*

X = *STRING*

Example

```
begin definition for function SI_Kr
```

```
  type is piecewise linear
```

```
  begin values
```

```
    20.0      5.50e7
```

```
    100.0     4.60e7
```

```
    ...
```

```
    800.0     1.30e7
```

```
    2000.0    1.30e7
```

```
  end values
```

```
end definition for function SI_Kr
```

```
...
```

```
Begin Aria Material Foo
```

```
  ...
```

```
    Radiative Conductivity = User_Function Name=SI_Kr X=Temperature
```

```
  ...
```

```
End Aria Material Foo
```

Description A look-up function is used to compute the values of the thermal conductivity as a function of some other variable, i.e. $f(x)$. The function type (“piecewise linear” in the example above) must support the `differentiate()` method for Newton’s method.

Here NAME is the name of the user-defined function for (CONDUCTIVITY_DATA, SI_K, in the example) and X is the Aria name of the abscissa variable (TEMPERATURE in the example). Note that X is not necessarily the same name as the optional abscissa variable identified in the user-defined function.

4.37. RELATIVE PERMEABILITY

RELATIVE PERMEABILITY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the relative permeability (scalar) for porous flow in Darcy’s Law.

Summary Specifies the material model for the relative permeability (scalar) for porous flow in Darcy’s Law. In general, the permeability may be nonisotropic in porous media. In that

case, Darcy's law may be written as,

$$\rho \mathbf{v}_d = \mathbf{f} = \frac{\rho k_r}{\mu} \mathbf{K} \cdot (\nabla P + \rho \mathbf{g}) \quad (4.103)$$

where $\mathbf{K}$ is the intrinsic permeability tensor, ρ is the density, $\mathbf{v}_d$ is the Darcy velocity, $\mathbf{f}$ is the mass flux, k_r is the relative permeability, μ is the dynamic viscosity, P is pressure and $\mathbf{g}$ is gravity.

Parent
Block(s)
ARIA MATERIAL

4.37.1. RELATIVE PERMEABILITY = CONSTANT

Parameters

$K = REAL$

Example

Relative Permeability = Constant K=1e-3

Description The value is constant in space and time.

4.37.2. RELATIVE PERMEABILITY = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

Relative Permeability = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.37.3. RELATIVE PERMEABILITY = POLYNOMIAL

Parameters

VARIABLE = *STRING* ORDER = *INT* [VARIABLE_OFFSET = *REAL*] [C0 = *REAL*] [C1 = *REAL*] ... [CN = *REAL*]

Example

Relative Permeability= Polynomial Variable=Temperature Order=1
C0=401.0 C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$k_r = \sum_{i=0}^N C_i (X + X_o)^i \quad (4.104)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter, X_o is an optional offset (VARIABLE_OFFSET, default is zero) and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section [2.7.1](#).

4.38. SEEBECK COEFFICIENT

SEEBECK COEFFICIENT = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for Seebeck coefficient.

Summary Specifies the material model for the Seebeck coefficient that appears in a thermoelectric contribution to the the diffusion term of the energy equation for temperature. This command line must be accompanied the HEAT_CONDUCTION = THERMOELECTRIC [4.15.5](#) and CURRENT_DENSITY = THERMOELECTRIC [4.6.4](#) options which utilize isotropic thermal and electrical conductivity tensors. Additionally the Energy equation for temperature should have the SRC term active for JOULE HEATING [11.3.13](#).

Parent

Block(s)

ARIA MATERIAL

4.38.1. SEEBECK COEFFICIENT = CONSTANT

Parameters

A = *REAL*

Example

SEEBECK COEFFICIENT = CONSTANT A = 1.0

Description A is the value of the constant Seebeck coefficient. Must be accompanied by the HEAT_CONDUCTION = THERMOELECTRIC option.

4.38.2. SEEBECK COEFFICIENT = ENCORE_FUNCTION

Parameters

NAME = *STRING*
[EVAL_TYPE = *STRING*]

Example

Seebeck Coefficient = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.38.3. SEEBECK COEFFICIENT = POLYNOMIAL

Parameters

VARIABLE = *STRING* ORDER = *INT* [VARIABLE_OFFSET = *REAL*] [C0 = *REAL*] [C1 = *REAL*] ... [CN = *REAL*]

Example

Seebeck Coefficient= Polynomial Variable=Temperature Order=1
C0=401.0 C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$\kappa = \sum_{i=0}^N C_i (X + X_o)^i \quad (4.105)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter, X_o is an optional offset

(VARIABLE_OFFSET, default is zero) and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section [2.7.1](#).

4.38.4. SEEBECK COEFFICIENT = USER_FUNCTION

Parameters

NAME = *STRING*

X = *STRING*

Example

```
begin definition for function SI_K
  type is piecewise linear
  begin values
    20.0      5.50e7
    100.0     4.60e7
    ...
    800.0     1.30e7
    2000.0    1.30e7
  end values
end definition for function SI_K
```

...

Begin Aria Material Foo

...

Seebeck Coefficient = User_Function Name=SI_K X=Temperature

...

End Aria Material Foo

Description A look-up function is used to compute the values of the thermal conductivity as a function of some other variable, i.e. $f(x)$. The function type (“piecewise linear” in the example above) must support the `differentiate()` method for Newton’s method.

Here NAME is the name of the user-defined function for (COEFFICIENT_DATA, SI_K, in the example) and X is the Aria name of the abscissa variable (TEMPERATURE in the example). Note that X is not necessarily the same name as the optional abscissa variable identified in the user-defined function. Must be accompanied by the HEAT_CONDUCTION = THERMOELECTRIC option. Full effect of this contribution can only be realized if Energy equation for temperature has the SRC term active for JOULE HEATING ([11.3.13](#)).

4.39. SHELL THICKNESS

SHELL THICKNESS = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the shell thickness.

Summary Specifies the material model and parameters for the shell thickness.

Parent

Block(s)

ARIA MATERIAL

4.39.1. SHELL THICKNESS = CONSTANT

Parameters

T = *REAL*

Example

Shell Thickness = Constant T = 0.8

Description T is the value of the constant shell thickness.

4.39.2. SHELL THICKNESS = ELEMENT_ATTRIBUTE

Parameters

MULTIPLIER = *REAL*

Example

Shell Thickness = Element_Attribute multiplier = 1.0

Description For shell elements the ExodusII mesh file can contain area attribute values for each element within an element block. This value can then be retrieved and used by the application. This model is used to scale the value of area attribute by Multiplier to obtain the shell thickness for a particular element.

4.40. SKELETON DENSITY

SKELETON DENSITY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies a model for the porous skeleton density of a material.

Summary Specifies a model for the porous skeleton density of a material.

Parent

Block(s)

ARIA MATERIAL

4.40.1. SKELETON DENSITY = CONSTANT

Parameters

RHO = *REAL*

Example

Skeleton Density = Constant Rho=1e3

Description The value is constant in space and time.

4.40.2. SKELETON DENSITY = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

Skeleton Density = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.41. SKELETON INTERNAL ENERGY

SKELETON INTERNAL ENERGY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies a model for the porous skeleton internal energy of a material.

Summary Specifies a model for the porous skeleton internal energy of a material.

Parent

Block(s)

ARIA MATERIAL

4.41.1. SKELETON INTERNAL ENERGY = CONSTANT

Parameters

$E = \textit{REAL}$

Example

Skeleton Internal Energy = Constant $E=2.3e-4$

Description The value is constant in space and time.

4.41.2. SKELETON INTERNAL ENERGY = ENCORE_FUNCTION

Parameters

$\text{NAME} = \textit{STRING}$

$[\text{EVAL\_TYPE} = \textit{STRING}]$

Example

Skeleton Internal Energy = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.41.3. SKELETON INTERNAL ENERGY = LINEAR

Parameters

$\text{CP} = \textit{REAL}$

$\text{T\_REF} = \textit{REAL}$

Example

Skeleton Internal Energy = Linear $\text{Cp}=13.7$ $\text{T\_ref}=298.15$

Description The internal energy of the porous skeleton, e_s , is given by the simple relation,

$$e_s = C_p (T - T_{ref}) \quad (4.106)$$

where C_p is the specific heat supplied by the CP parameter and T_{ref} is a reference temperature supplied by the T_REF parameter. This model also supplies the time derivative of e_s ,

$$\frac{\partial e_s}{\partial t} = C_p \frac{\partial T}{\partial t} \quad (4.107)$$

4.42. SKELETON SPECIFIC HEAT

SKELETON SPECIFIC HEAT = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies a model for the porous skeleton specific heat of a material.

Summary Specifies a model for the porous skeleton specific heat of a material.

Parent

Block(s)

ARIA MATERIAL

4.42.1. SKELETON SPECIFIC HEAT = CONSTANT

Parameters

CP = *REAL*

Example

Skeleton Specific Heat = Constant Cp=400

Description The value is constant in space and time.

4.42.2. SKELETON SPECIFIC HEAT = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

Skeleton Specific Heat = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```

Begin String Function My_Function
  Value is "200 + 1.0*t"
End

```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.42.3. SKELETON SPECIFIC HEAT = POLYNOMIAL

Parameters

```

VARIABLE = STRING ORDER = INT [VARIABLE_OFFSET = REAL] [CO =
REAL] [C1 = REAL] ... [CN = REAL]

```

Example

```

Skeleton Specific Heat= Polynomial Variable=Temperature Order=1
C0=401.0 C1=88.5

```

Description Arbitrary order polynomial function of a specified scalar variable.

$$C_p = \sum_{i=0}^N C_i (X + X_o)^i \quad (4.108)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter, X_o is an optional offset (VARIABLE_OFFSET, default is zero) and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section [2.7.1](#).

4.42.4. SKELETON SPECIFIC HEAT = USER_FUNCTION

Parameters

```

NAME = STRING
X = STRING

```

Example

Begin Definition for Function Table_Fcn

 Type is Piecewise Linear

 Begin Values

 273.15 100

 277.15 200

 283.15 300

 End

End

...

Begin Aria Material Foo

 ...

 Skeleton Specific Heat = User_Function Name=Table_Fcn X=Temperature

 ...

End Aria Material Foo

Description A look-up function is used to compute the values of the skeleton specific heat as a function of some other variable, i.e. $f(x)$. The function type (“piecewise linear” in the example above) must support the `differentiate()` method for Newton’s method.

Here NAME is the name of the user-defined function (Table_Fcn in the example) and X is the Aria name of the abscissa variable (TEMPERATURE in the example). Note that X is not necessarily the same name as the abscissa variable identified in the user-defined function (T in the example).

4.43. SOLID LAMBDA

SOLID LAMBDA = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the λ Lamé coefficient for the solid stress tensor.

Summary The solid stress $\mathbf{T}$ is given by

$$\mathbf{T} = \lambda E_{kk} \mathbf{I} + 2\mu \mathbf{E} - \beta (T - T_{ref}) \mathbf{I} \quad (4.109)$$

where λ and μ are the Lamé coefficients, $\mathbf{E} = \frac{1}{2} (\nabla \mathbf{d} + \nabla \mathbf{d}^T)$ is the deformation tensor, β is the coefficient of thermal stress, T is temperature and T_{ref} is the thermal strain reference temperature.

These Lamé coefficients are related to the more standard Young’s modulus, Poisson’s

ratio and CTE (α) as follows:

$$2\mu = \frac{E}{(1 + \nu)} \quad (4.110)$$

$$\lambda = \frac{\nu E}{(1 + \nu)(1 - 2\nu)} = 2\mu \frac{\nu}{(1 - 2\nu)} \quad (4.111)$$

$$\beta = \frac{\alpha E}{(1 - 2\nu)} = \alpha (3\lambda + 2\mu) \quad (4.112)$$

When a user supplies the Young's modulus, Poisson's ratio and CTE properties Aria internally converts them into the Lamé coefficients.

Parent
Block(s)
ARIA MATERIAL

4.43.1. SOLID LAMBDA = CONSTANT

Parameters
LAMBDA = *REAL*

Example
SOLID LAMBDA = CONSTANT LAMBDA = 1.0

Description LAMBDA is the value of the constant λ .

4.43.2. SOLID LAMBDA = CONVERTED

Parameters
(None)

Example
SOLID LAMBDA = Converted

Description Aria will use Young's modulus and Poisson ratio to compute the Lamé λ coefficient. Supplying the Lamé coefficients is more computationally efficient but perhaps less convenient, especially if the material properties are varying (e.g., temperature dependent in a non-isothermal problem).

4.43.3. SOLID LAMBDA = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

SOLID LAMBDA = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.44. SOLID TWO MU

SOLID TWO MU = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for twice the μ Lamé coefficient for the solid stress tensor.

Summary The solid stress $\mathbf{T}$ is given by

$$\mathbf{T} = \lambda E_{kk} \mathbf{I} + 2\mu \mathbf{E} - \beta (T - T_{ref}) \mathbf{I} \quad (4.113)$$

where λ and μ are the Lamé coefficients, $\mathbf{E} = \frac{1}{2} (\nabla \mathbf{d} + \nabla \mathbf{d}^T)$ is the deformation tensor, β is the coefficient of thermal stress, T is temperature and T_{ref} is the thermal strain reference temperature.

These Lamé coefficients are related to the more standard Young's modulus, Poisson's ratio and CTE (α) as follows:

$$2\mu = \frac{E}{(1 + \nu)} \quad (4.114)$$

$$\lambda = \frac{\nu E}{(1 + \nu)(1 - 2\nu)} = 2\mu \frac{\nu}{(1 - 2\nu)} \quad (4.115)$$

$$\beta = \frac{\alpha E}{(1 - 2\nu)} = \alpha (3\lambda + 2\mu) \quad (4.116)$$

When a user supplies the Young's modulus, Poisson's ratio and CTE properties Aria internally converts them into the Lamé coefficients.

Parent
Block(s)
ARIA MATERIAL

4.44.1. SOLID TWO MU = CONSTANT

Parameters
`TWO_MU = REAL`

Example
`SOLID TWO MU = CONSTANT TWO_MU = 1.0`

Description `TWO_MU` is the value of 2μ .

4.44.2. SOLID TWO MU = CONVERTED

Parameters
(None)

Example
`SOLID TWO MU = Converted`

Description Aria will use Young's modulus and Poisson ratio to compute the Lamé μ coefficient. Supplying the Lamé coefficients is more computationally efficient but perhaps less convenient, especially if the material properties are varying (e.g., temperature dependent in a non-isothermal problem).

4.44.3. SOLID TWO MU = ENCORE_FUNCTION

Parameters
`NAME = STRING`
`[EVAL_TYPE = STRING]`

Example
`TWO_MU = Encore_Function Name=My_Function`

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```

Begin String Function My_Function
  Value is "200 + 1.0*t"
End

```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.45. SOLID STRESS

SOLID STRESS = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies a contribution to the solid stress tensor. Multiple stresses are combined additively and may be specified by using this line command multiple times.

Summary Specifies a contribution to the solid stress tensor. The total stress $\mathbf{T}$ is given by

$$\mathbf{T} = \sum_j \mathbf{T}_j \quad (4.117)$$

Parent
Block(s)
ARIA MATERIAL

4.45.1. SOLID STRESS = ISOTHERMAL

Parameters

T = *REAL*

T_REF = *REAL*

Example

SOLID STRESS = Isothermal T=500 T_ref=325

Description This stress accounts for the mechanical stresses due to thermally induced strains.

$$\mathbf{T} = -\beta (T - T_{ref}) \mathbf{I} \quad (4.118)$$

where β is the Lamé coefficient of thermal stress (related to the coefficient of thermal expansion, α), T is the temperature and T_{ref} is the temperature of the undeformed reference state of the mesh (pseudo-solid). This is a specialization of the THERMAL model that uses uniform, fixed temperature and thermal strain reference temperature.

4.45.2. SOLID STRESS = LINEAR_ELASTIC

Parameters

REFERENCE_FRAME = ‘MOVING’ | ‘UNDEFORMED’

Example

SOLID STRESS = Linear_Elastic Reference_Frame=Moving

Description Supplies the linear elasticity stress tensor,

$$\mathbf{T} = \lambda \text{trace } \mathbf{E} \mathbf{I} + 2\mu \mathbf{E} \quad (4.119)$$

where λ and μ are the Lamé coefficients and $\mathbf{E}$ is the strain tensor. When the choice of reference frame is “UNDEFORMED” then the strain is computed in the undeformed reference state; this is commonly referred to as small strain theory. When the reference frame is “MOVING” then the strain is computed with respect to the deformed coordinates.

Specifically, the strain tensor is given by

$$\mathbf{E} = \frac{1}{2} (\nabla \mathbf{d} + \nabla \mathbf{d}^t) \quad (4.120)$$

where $\mathbf{d}$ is the solid displacement field. The choice of reference frame determines whether the ∇ operator is computed in the undeformed or moving reference frames.

4.45.3. SOLID STRESS = NEOHOOKEAN_ELASTIC

Parameters

(none)

Example

SOLID STRESS = Neohookean_Elastic

Description Supplies a nonlinear hyperelastic stress of the form,

$$\mathbf{T} = \frac{\mu}{J} (\mathbf{b} - \mathbf{I}) + \frac{\lambda}{J} \ln J \mathbf{I} \quad (4.121)$$

where λ and μ are the Lamé coefficients, $\mathbf{b} \equiv \mathbf{F} \cdot \mathbf{F}^t$ is the left Cauchy-Green tensor, $\mathbf{F}$ is the deformation gradient and $J \equiv \det \mathbf{F}$. See, e.g., [5] or [6].

4.45.4. SOLID STRESS = NONLINEAR_ELASTIC

Parameters

(none)

Example

SOLID STRESS = Nonlinear_Elastic

Description Supplies a nonlinear elastic stress,

$$\mathbf{T} = \lambda \text{trace } \mathbf{E} \mathbf{I} + 2\mu \mathbf{E} \quad (4.122)$$

where λ and μ and the Lamé coefficients and $\mathbf{E}$ is the strain tensor. The particular choice of strain tensor chosen depends on where the configuration (reference frame) which is set via the MESH MOTION command line. See section 5.17 for more information.

When the MESH MOTION is set to REFERENCE_FRAME then the Green strain is used. Otherwise, the Almansi strain is used.

4.45.5. SOLID STRESS = RESIDUAL

Parameters

[SXX | SX = REAL]

[SYY | SY = REAL]

[SZZ | SZ = REAL]

[SXY = REAL]

[SXZ = REAL]

[SYZ = REAL]

Example

SOLID STRESS = Residual Sxx=0.02 Syy=0.02

Description This stress accounts for the initial residual stress in a solid that is constant and uniform everywhere. The components of the residual stress tensor are supplied by the (up-to) six components SXX, SYY, SZZ, SXY, SXZ, and SYZ.

This is directly analogous to the ISTRESS condition in ANSYS. To that end, the diagonal components can be specified as either SXX or SX etc.

4.45.6. SOLID STRESS = THERMAL

Parameters

(none)

Example

SOLID STRESS = Thermal

Description This stress accounts for the mechanical stresses due to thermally induced strains.

$$\mathbf{T} = -\beta (T - T_{ref}) \mathbf{I} \quad (4.123)$$

where β is the Lamé coefficient of thermal stress (related to the coefficient of thermal expansion, α), T is the temperature and T_{ref} is the temperature of the undeformed reference state of the solid.

4.45.7. SOLID STRESS = LAME

Parameters

MODEL = *STRING*

Example

SOLID STRESS = Lamé Model = Neo_Hookean

Description This stress interfaces with the Lamé constitutive model library used by Sierra/SolidMechanics. As such, it allows the use of many of Lamé's constitutive models. Sierra/Multimechanics prepares the kinematic quantities, and Lamé returns the Cauchy stress, which is integrated in the SOLID equation.

Material parameters for the constitutive models are handled by an input block consistent with the Sierra/SolidMechanics formatting. For documentation of the available constitutive models and the required parameter input, please see the Sierra/SolidMechanics documentation.

Currently this interface is instrumented to support hyperelastic constitutive models, and is restricted to the following models:

- NEO_HOOKEAN
- THERMALBATTERYSEPARATOR
- SOILFOAMPHASETRANSITION

4.46. SPECIES DIFFUSION

SPECIES DIFFUSION = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material (constitutive) model for the species diffusion (diffusive flux) in the bulk.

Summary Specifies the material (constitutive) model for the species diffusion (diffusive flux) in the bulk.

Parent

Block(s)

ARIA MATERIAL

4.46.1. SPECIES DIFFUSION = BASIC

This is an alias for FICKS_LAW.

Example

Species Diffusion = Basic

4.46.2. SPECIES DIFFUSION = FICKS_LAW

Parameters

(none)

Example

Species Diffusion = Ficks_Law

Description The diffusive species flux q is given by Fick's Law,

$$q = -D\nabla C \quad (4.124)$$

where D is the species diffusivity and C is the species concentration.

4.47. SPECIES DIFFUSIVITY

SPECIES DIFFUSIVITY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the species diffusivity.

Summary Specifies the material model for the species diffusivity.

Parent

Block(s)

ARIA MATERIAL

4.47.1. SPECIES DIFFUSIVITY = ARRHENIUS

Parameters

[C = *REAL*]

D = *REAL*

Q = *REAL*

R = *REAL*

Example

SPECIES DIFFUSIVITY = Arrhenius D=2e-6 Q=6900 R=8.314

Description The species diffusivity is given by the Arrhenius function

$$D = C + D_0 e^{-Q/RT} \quad (4.125)$$

where C is given by the C parameter, D_0 is given by the D parameter, Q is given by the Q parameter and R is given by the R parameter.

4.47.2. SPECIES DIFFUSIVITY = CONSTANT

Parameters

$D = REAL$

Example

```
SPECIES DIFFUSIVITY = CONSTANT D = 1.0
```

Description D is the value of the constant species diffusivity.

4.47.3. SPECIES DIFFUSIVITY = ENCORE_FUNCTION

Parameters

$NAME = STRING$

$[EVAL\_TYPE = STRING]$

Example

```
SPECIES DIFFUSIVITY = Encore_Function Name=My_Function
```

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument `EVAL_TYPE` can be used to select the particular function on the Encore function object. Valid options include `VALUE`, `DOT`, `GRADIENT`, `FLUX` and `STRESS`. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – `VALUE` for `NO_OP` expressions, `DOT` for `DT_OP` expressions and `GRADIENT` for `GRAD_OP` expressions.

4.48. SPECIFIC HEAT

SPECIFIC HEAT = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the specific heat.

Summary Specifies the material model for the specific heat.

Parent

Block(s)

ARIA MATERIAL

4.48.1. SPECIFIC HEAT = CONSTANT_EVALUATOR

Parameters

CP = *REAL* h0 = *REAL*

Example

SPECIFIC HEAT = CONSTANT_EVALUATOR CP = 1.0 h0 = 500

Description CP is the value of the constant specific heat, and h0 (optional) is the value of the reference enthalpy. This also creates an expression for enthalpy, as $h(T) = h_0 + C_p T$.

4.48.2. SPECIFIC HEAT = POLYNOMIAL_EVALUATOR

Parameters

a0 = *REAL* a1 = *REAL* a2 = *REAL* a3 = *REAL* a4 = *REAL* a5 = *REAL* a6 =
REAL a7 = *REAL* a8 = *REAL* R = *REAL*

Example

SPECIFIC HEAT = POLYNOMIAL_EVALUATOR a0 = 50 a1 = 1000 a2 = 1 R
= 8.314

Description The coefficients a0 to a8 are the polynomial coefficients and R is the gas constant they are based on (defaults to 8.314). Only a0 and a1 are required.

Specific heat is evaluated using $C_p(T)/R = \sum_{i=1}^n a_i T^{i-1}$ and enthalpy by $h(T)/R = a_0 + \sum_{i=1}^n \frac{1}{i} a_i T^i$. The polynomial order is determined by how many non-zero entries are provided.

4.48.3. SPECIFIC HEAT = TABULAR_EVALUATOR

Parameters

Cp_function = *STRING* h0 = *REAL*

Example

SPECIFIC HEAT = TABULAR_EVALUATOR Cp_function = f_Cp

Description The function specified here is the same syntax as for USER_FUNCTION, but the function must be with respect to temperature. The reference enthalpy, h0 is optional. This also provides an expression for enthalpy that is based on an integration of the tabular values of specific heat.

4.48.4. SPECIFIC HEAT = T_EXPONENT

Parameters

Cp_ref = *REAL* T_ref = *REAL* n = *REAL* h0 = *REAL*

Example

SPECIFIC HEAT = T_EVALUATOR Cp_ref = 1000 T_ref = 300 n = 2

Description This provides specific heat as $C_p(T) = C_{p,ref} \left(\frac{T}{T_{ref}} \right)^n$ and enthalpy as $h(T) = h_0 + \frac{C_{p,ref}}{T_{ref}^n} \frac{T^{n+1}}{n+1}$.

4.48.5. SPECIFIC HEAT = CONSTANT

Parameters

CP = *REAL*

Example

SPECIFIC HEAT = CONSTANT CP = 1.0

Description CP is the value of the constant specific heat.

4.48.6. SPECIFIC HEAT = CURING_FOAM

Parameters

VFRAC_SUBINDEX = *INT*

[CP_FL = *REAL*]

[CP_FG = *REAL*]

[CP_E = *REAL*]

[PHI_ZERO = *REAL*]

Example

Specific Heat = Curing_Foam Vfrac_Subindex=1 Cp_fL=1 Cp_fG=1
Cp_e=1 phi_zero=0.2

Description For a curing epoxy with volume fraction ϕ the specific heat is given by

$$C_p = C_{p,fL}\phi + C_{p,fG}(\phi_o - \phi) + C_{p,e}(1 - \phi_o) \quad (4.126)$$

$$= a + b\phi \quad (4.127)$$

where $C_{p,fL}$ is the specific heat of the liquid phase flourinert, $C_{p,fG}$ is the specific heat of the gas phase flourinert, $C_{p,e}$ is the specific heat of the epoxy and ϕ_o is the reference volume fraction in the flourinert. In the latter form of this relationship

$$a = C_{p,fL} - C_{p,fG} \quad (4.128)$$

$$b = C_{p,fG}\phi_o + C_{p,e}(1 - \phi_o). \quad (4.129)$$

NOTE: The volume fraction is assumed to be a SPECIES field with the subindex provided by the VFRAC_SUBINDEX parameter.

4.48.7. SPECIFIC HEAT = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

SPECIFIC HEAT = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.48.8. SPECIFIC HEAT = EXPONENTIAL

Parameters

VARIABLE = *STRING*
[CONSTANT = *REAL*]
[MULTIPLIER = *REAL*]
EXPONENT = *REAL*

Example

Specific Heat = Exponential Variable=Temperature Multiplier=1.0
Exponent=-0.3

Description Exponential function of in specified scalar variable. The specific heat is computed as

$$C_p = C + Me^{EX} \quad (4.130)$$

Here, C is the constant term supplied by the CONSTANT parameter which defaults to zero, M is the value supplied by the MULTIPLIER parameter which defaults to unity, X is the variable supplied by the VARIABLE parameter and E is the exponential multiplier provided by the EXPONENT parameter.

4.48.9. SPECIFIC HEAT = POLYNOMIAL

Parameters

VARIABLE = *STRING* ORDER = *INT* [VARIABLE_OFFSET = *REAL*] [C0 =
REAL] [C1 = *REAL*] ... [CN = *REAL*]

Example

Specific Heat= Polynomial Variable=Temperature Order=1 C0=401.0
C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$C_p = \sum_{i=0}^N C_i (X + X_o)^i \quad (4.131)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter, X_o is an optional offset (VARIABLE_OFFSET, default is zero) and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section [2.7.1](#).

4.48.10. SPECIFIC HEAT = USER_FUNCTION

Parameters

NAME = *STRING*

X = *STRING*

Example

```
begin definition for function Water_Heat_Capacity
  # Source Appendix 2 from "Transport Processes and
  # Unit Operations" by C. J. Geankoplis
  type is piecewise linear
  begin values
    # K      J / kg K
    273.15  4220
    283.15  4195
    293.15  4185
    298.15  4182
    303.15  4181
    313.15  4181
    323.15  4183
    333.15  4187
    343.15  4192
    353.15  4199
    363.15  4208
    373.15  4219
  end
end
...
```

Begin Aria Material Foo

```
...
Specific Heat = User_Function X=Temperature Name=Water_Heat_Capacity
...
```

End Aria Material Foo

Description A look-up function is used to compute the values of the specific heat as a function of some other variable, i.e. $f(x)$. The function type (“piecewise linear” in the example above) must support the `differentiate()` method for Newton’s method.

Here NAME is the name of the user-defined function (Water_Heat_Capacity in the example) and X is the Aria name of the abscissa variable (TEMPERATURE in the example). Note that X is not necessarily the same name as the abscissa variable identified in the user-defined function (T in the example).

4.48.11. SPECIFIC HEAT = USE_PHASE_CHANGE

SPECIFIC HEAT = USE_PHASE_CHANGE FLH=LH_VAL TS=T_SOLIDUS
TL=T_LIQUIDUS

Description Defines a specialized material model to account for change of phase during melting or solidification. Must be accompanied by the PHASE CHANGE SPECIFIC HEAT command line.

Summary Phase change is being modeled by treating the phase transition temperature region as a mushy-zone about the melt temperature. Here the energy associated with phase change in the mushy-zone is accounted for by modifying the specific heat to include the latent heat of fusion as an additional contribution to the energy equation.

$$\text{Specific Heat} = \begin{cases} C_p(T) & T_s < T \\ C_p(T) + \frac{FLH}{T_l - T_s} & T_s < T < T_l \\ C_p(T) & T > T_l \end{cases}$$

where T is the current temperature, $C_p(T)$ is the specific heat of the material, FLH is the latent heat of fusion, T_s is a solidus temperature, T_l is a liquidus temperature and $T_l - T_s$ is the temperature range of the mushy zone.

Material outside of the mushy-zone, $T < T_s$ or $T > T_l$, will employ a standard specific heat model, $C_p(T)$.

While a material is undergoing phase change, the time stepping will be restricted so that the modeled phase change behavior will be captured. Use of this model will often require additional restrictions be placed upon the adaptive time stepping [16.4](#), [16.4.1](#).

Parent
Block(s)
ARIA MATERIAL

Parameters
 $FLH = REAL$
 $T_s = REAL$
 $T_l = REAL$

Example
Specific Heat = USE_PHASE_CHANGE FLH = 2.3E+04 TS = 599 TL =
600.5

4.49. PHASE CHANGE SPECIFIC HEAT

PHASE CHANGE SPECIFIC HEAT = SPECIFIC_HEAT_MODEL [param₁ = val₁, param₂ = val₂
...]

Description Defines the specific heat material model used in conjunction with phase change. This command can request any valid SPECIFIC HEAT model aside from USE_PHASE_CHANGE and must be accompanied by a SPECIFIC HEAT = USE_PHASE_CHANGE command line.

Summary Includes the parameters for the specific heat material model.

Parent
Block(s)
ARIA MATERIAL

Parameters
The optional parameters are those appropriate to the SPECIFIC_HEAT_MODEL.

Example
Phase Change Specific Heat = Constant cp = 1.0

4.50. SURFACE TENSION

SURFACE TENSION = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the model to use for the surface (interfacial) tension.

Summary Specifies the model to use for the surface (interfacial) tension.

Parent
Block(s)
ARIA MATERIAL

4.50.1. SURFACE TENSION = CONSTANT

Parameters
SIGMA = *REAL*

Example
Surface Tension = Constant Sigma = 72.0

Description SIGMA is the value of the surface tension.

4.50.2. SURFACE TENSION = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

Surface Tension = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.50.3. SURFACE TENSION = LINEAR_T

Parameters

SIGMA0 = *REAL*

DSIGMADT = *REAL*

T_REF = *REAL*

Example

Surface Tension = Linear_T sigma0=72. dsigmadT = -.15 T_ref = 298.

Description SIGMA0 is the value of the surface tension at the reference temperature T_REF and DSIGMADT is the derivative of the surface temperature with respect to temperature, i.e.,

$$\sigma = \sigma_0 + m(T - T_{ref}) \quad (4.132)$$

where m is DSIGMADT.

4.51. SUSPENSION FLUX

SUSPENSION FLUX = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the parameters for the suspension flux model.

Summary Specifies the suspension flux model and its parameters for this material.

Parent

Block(s)

ARIA MATERIAL

4.51.1. SUSPENSION FLUX = PHILLIPS

Parameters

K_mu = *REAL*

K_c = *REAL*

phi_max = *REAL*

beta = *REAL*

particle_radius = *REAL*

Example

SUSPENSION FLUX = Phillips K_mu=0.62 K_c=0.41 phi_max=0.68
beta=-1.82 particle_radius=0.01

Description The Phillips diffusive flux model is intended to be used in conjunction with the Krieger viscosity model ([4.56.10](#)). Here, the flux is given by

$$\mathbf{q} = \left(K_c a^2 - K_\mu a^2 \beta \frac{\phi}{\phi_m - \phi} \right) \dot{\gamma} \phi \nabla \phi + K_c a^2 \phi^2 \nabla \dot{\gamma} \quad (4.133)$$

where $\dot{\gamma}$ is the shear rate, ϕ is the suspension concentration, ϕ_m is the maximum suspension concentration and a is the particle radius.

4.52. THERMAL CONDUCTIVITY

THERMAL CONDUCTIVITY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the thermal conductivity.

Summary Specifies the material model for the thermal conductivity that appears in the diffusion term of the energy equation for temperature. The command line must be accompanied by either the HEAT_CONDUCTION = BASIC option for an isotropic conductivity tensor or the HEAT_CONDUCTION = GENERALIZED option for the anisotropic case.

Parent

Block(s)

ARIA MATERIAL

4.52.1. THERMAL CONDUCTIVITY = CALORE_USER_SUB

Parameters

NAME = *STRING*
TYPE = *STRING*
[MULTIPLIER = *REAL*]
[NR = *INT*]
[R0 = *INT*]
[R1 = *INT*(etc.)]
[NI = *INT*]
[IO = *INT*]
[I1 = *INT*(etc.)]

Example

Thermal Conductivity = Calore_User_Sub name=w80afftuser
type=element NR=2 R0=1000 R1=0.7

Description The Calore_User_Sub model allows the user to explicitly evaluate thermal conductivity as a function of temperature and position within an element. Additionally, a user_query feature allows evaluation of thermal conductivity based upon other problem criteria. NAME is the name of the user subroutine was registered with. NR and NI are the numbers of real and integer parameters, respectively. Each real (int) parameter is supplied by the Rn (Ini) parameter. Note: the parameters use zero based counting. The TYPE parameter denotes the API the user subroutine uses; currently Aria supports type ELEMENT for scalar valued thermal conductivity.

The optional MULTIPLIER parameter (defaults to 1.0) can be supplied to scale the output of the user subroutine, i.e., the flux f will be $f = m f_{user}$ where m is the multiplier and f_{user} is the output of the user subroutine.

See section [9.2.2](#) for a more complete example of a Calore user subroutine.

Must be accompanied by the HEAT_CONDUCTION = BASIC option.

4.52.2. THERMAL CONDUCTIVITY = CONSTANT

Parameters

K = *REAL*

Example

THERMAL CONDUCTIVITY = CONSTANT K = 1.0

Description K is the value of the constant thermal conductivity. Must be accompanied by the HEAT_CONDUCTION = BASIC option.

4.52.3. THERMAL CONDUCTIVITY = CURING_FOAM

Parameters

RHO_E = *REAL*

K_F = *REAL*

K_E = *REAL*

Example

Thermal Conductivity = Curing_Foam rho_e=1.3 k_e=14 k_f=2.7

Description For a curing epoxy with mixture density ρ

$$\kappa = \frac{2}{3} \left(\frac{\rho}{\rho_e} \right) \kappa_e + \left(1 - \frac{\rho}{\rho_e} \right) \kappa_f \quad (4.134)$$

$$= a + b\rho \quad (4.135)$$

where ρ_e is the density of the epoxy, κ_e is the thermal conductivity of the epoxy and κ_f is the thermal conductivity of the flourinert. In the latter form of this relationship

$$a = \kappa_f \quad (4.136)$$

$$b = \frac{1}{\rho_e} \left(\frac{2}{3} \kappa_e - \kappa_f \right) \quad (4.137)$$

Must be accompanied by the HEAT_CONDUCTION = BASIC option.

4.52.4. THERMAL CONDUCTIVITY = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

Thermal Conductivity = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument `EVAL_TYPE` can be used to select the particular function on the Encore function object. Valid options include `VALUE`, `DOT`, `GRADIENT`, `FLUX` and `STRESS`. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – `VALUE` for `NO_OP` expressions, `DOT` for `DT_OP` expressions and `GRADIENT` for `GRAD_OP` expressions.

4.52.5. THERMAL CONDUCTIVITY = MESH_INPUT

Parameters

`NAME = STRING`
`AXIS1 = STRING`
`AXIS2 = STRING`
`[TYPE = STRING]`
`[MULTIPLIER = REAL]`
`[TOLERANCE = REAL]`

Example

```
THERMAL CONDUCTIVITY = MESH_INPUT NAME = COND AXIS1 = A1 AXIS2 =  
A2 TOLERANCE = 1.0E-4 TYPE = SYMMETRIC MULTIPLIER = 2.0
```

Description Thermal conductivity is being provided from the input mesh file.

The `TYPE` parameter defines what tensor components are supplied in the input file. The default `TYPE = PRINCIPAL` will cause the code to expect principal components only. Supplying `TYPE = SYMMETRIC` will require that the file contain corresponding the symmetric tensor components.

The `NAME` parameter specifies the base name of the tensor component values present in the mesh file. Component names are internally generated using the base name and the component subscripts. For example for `TYPE = SYMMETRIC` in the two-dimensional a base name of `COND` would generate `COND11`, `COND22` and `COND12`, and for `TYPE = PRINCIPAL` would generate `COND11` and `COND22`.

The tensor components provided are assumed to be defined in an orientation compactly described with unit vectors. For two-dimensional problems one unit vector must be provided and for three-dimensional problems one must provide two unit vectors. In 3D the `AXIS1` and `AXIS2` parameters define the variable names which specify orientation vectors associated with the components. Default value of `AXIS1 = FIBER` and default value of `AXIS2 = NORMAL`. Orientation vectors are given relative to the fixed Cartesian (*xyz*) frame. Internal to the code `AXIS1` and `AXIS2` will be used to generate the remaining orthogonal axis needed to define a complete ortho-normal transformation into the computational reference frame. Internal checks are done to guarantee that orientation vectors are of nonzero length. For 2D only the `AXIS1` variable need be provided and `AXIS2`, if provided, will be ignored.

The TOLERANCE parameter defines a desired tolerance for the dot product of vectors defined by AXIS1 and AXIS2. An error message will be generated when the dot product is greater than the specified tolerance. Default value for TOLERANCE = 1.0E9

Use of the MULTIPLIER parameter results in scaling all components of the conductivity tensor.

4.52.6. THERMAL CONDUCTIVITY = OPTICALLY_THICK

Parameters

K = *REAL*

N = *REAL*

BETA_R = *REAL*

Example

THERMAL CONDUCTIVITY = OPTICALLY_THICK K = 3.0 N = 2.1 BETA_R = 1.0e-5

Description Thermal conductivity used to model combined pure diffusion and radiative diffusion in the optically-thick limit. Constant values for the pure diffusion thermal conductivity K , index of refraction n , and Rosseland-mean extinction coefficient β_R must be provided on the input line.

$$\kappa = K + \frac{16\sigma n^2}{3\beta_R} T^3 \quad (4.138)$$

Must be accompanied by the HEAT_CONDUCTION = BASIC option. Additionally the GLOBAL CONSTANTS block must include the STEFAN-BOLTZMANN CONSTANT entry to provide a value of σ .

4.52.7. THERMAL CONDUCTIVITY = POWER_LAW

Parameters

A = *REAL*

GAMMA = *REAL*

Example

THERMAL CONDUCTIVITY = POWER_LAW A = 3.8 GAMMA = -1.2

Description Thermal conductivity is a power law function of temperature

$$\kappa = AT^\gamma \quad (4.139)$$

where A is a scale factor and γ is the power law exponent. For values of $\gamma = 1$ the THERMAL model 4.52.9 should be used instead. Must be accompanied by the HEAT_CONDUCTION = BASIC option.

4.52.8. THERMAL CONDUCTIVITY = POLYNOMIAL

Parameters

VARIABLE = *STRING* ORDER = *INT* [VARIABLE_OFFSET = *REAL*] [C0 = *REAL*] [C1 = *REAL*] ... [CN = *REAL*]

Example

Thermal Conductivity= Polynomial Variable=Temperature Order=1
C0=401.0 C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$\kappa = \sum_{i=0}^N C_i (X + X_o)^i \quad (4.140)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter, X_o is an optional offset (VARIABLE_OFFSET, default is zero) and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section [2.7.1](#).

4.52.9. THERMAL CONDUCTIVITY = THERMAL

Parameters

[A = *REAL*]
[B = *REAL*]
[C = *REAL*]
[D = *REAL*]

Example

THERMAL CONDUCTIVITY = THERMAL A = 401.0 B = 88.5

Description Cubic polynomial function of temperature for the conductivity.

$$\kappa = A + BT + CT^2 + DT^3 \quad (4.141)$$

Must be accompanied by the HEAT_CONDUCTION = BASIC option.

4.52.10. THERMAL CONDUCTIVITY = USER_FUNCTION

Parameters

NAME = *STRING*
X = *STRING*

Example

```
begin definition for function SI_K
  type is piecewise linear
  begin values
    20.0      5.50e7
    100.0     4.60e7
    ...
    800.0     1.30e7
    2000.0    1.30e7
  end values
end definition for function SI_K
```

...

Begin Aria Material Foo

```
...
  Thermal Conductivity = User_Function Name=SI_K X=Temperature
...
```

End Aria Material Foo

Description A look-up function is used to compute the values of the thermal conductivity as a function of some other variable, i.e. $f(x)$. The function type (“piecewise linear” in the example above) must support the `differentiate()` method for Newton’s method.

Here NAME is the name of the user-defined function for (CONDUCTIVITY_DATA, SI_K, in the example) and X is the Aria name of the abscissa variable (TEMPERATURE in the example). Note that X is not necessarily the same name as the optional abscissa variable identified in the user-defined function. Must be accompanied by the HEAT_CONDUCTION = BASIC option.

4.52.11. THERMAL CONDUCTIVITY = CONSTANT (TENSOR)

Parameters

```
XX = REAL = REAL
[XY = REAL]
[XZ = REAL]
[YX = REAL]
YY = REAL = REAL
[YZ = REAL]
[ZX = REAL]
[ZY = REAL]
[ZZ = REAL]
```

Example

```
TENSOR THERMAL CONDUCTIVITY = Constant XX=1.0 YY=2.0 ZZ=1.0
TENSOR THERMAL CONDUCTIVITY = Constant 11=1.0 22=2.0 33=1.0
```


Description All components default to zero and all values are constant in space and time. Must be accompanied by the HEAT_CONDUCTION = GENERALIZED option.

4.52.12. THERMAL CONDUCTIVITY = USER_FUNCTION (TENSOR)

Parameters

NAME_XX = *STRING*

NAME_YY = *STRING*

[NAME_ZZ = *STRING*]

X = *STRING*

Example

```
begin definition for function SI_K11
```

```
  type is piecewise linear
```

```
  begin values
```

```
    20.0      5.50e7
```

```
   100.0      4.60e7
```

```
    ...
```

```
   800.0      1.30e7
```

```
  2000.0      1.30e7
```

```
  end values
```

```
end definition for function SI_K11
```

```
begin definition for function SI_K22
```

```
  type is piecewise linear
```

```
  begin values
```

```
    20.0      8.50e7
```

```
   100.0      7.60e7
```

```
    ...
```

```
   800.0      0.30e7
```

```
  2000.0      0.30e7
```

```
  end values
```

```
end definition for function SI_K22
```

```
...
```

```
Begin Aria Material Foo
```

```
  ...
```

```
    Tensor Thermal Conductivity = User_Function Name_xx=SI_K11 Name_xx=SI_K22 X=Temperature
```

```
  ...
```

```
End Aria Material Foo
```

Description A look-up function is used to compute the values of the thermal conductivity as a function of some other variable, i.e. $f(x)$. The function type (“piecewise linear” in the example above) must support the `differentiate()` method for Newton’s method.

Here NAME_XX, NAME_YY, NAME_ZZ, are the names of user-defined functions for (CONDUCTIVITY_DATA, SI_K11, SI_K22 in the example) and X is the Aria name of the abscissa variable (TEMPERATURE in the example). NAME_ZZ is required only for three-dimensional analysis. Note that X is not necessarily the same name as the optional abscissa variable identified in the user-defined function. Must be accompanied by the HEAT_CONDUCTION = GENERALIZED option.

4.52.13. THERMAL CONDUCTIVITY = CALORE_USER_SUB (TENSOR)

Parameters

NAME = *STRING*
 TYPE = *STRING*
 [MULTIPLIER = *REAL*]
 [NR = *INT*]
 [R0 = *INT*]
 [R1 = *INT* (etc.)]
 [NI = *INT*]
 [I0 = *INT*]
 [I1 = *INT* (etc.)]

Example

```
Tensor Thermal Conductivity = Calore_User_Sub name=w80afftuser
type=element_tensor NR=2 R0=1000 R1=0.7
```

Description The Calore_User_Sub Tensor model allows the user to explicitly evaluate thermal conductivity as a function of temperature and position within an element. Additionally, a user_query feature allows evaluation of thermal conductivity based upon other problem criteria. NAME is the name of the user subroutine was registered with. NR and NI are the numbers of real and integer parameters, respectively. Each real (int) parameter is supplied by the R_n (I_n) parameter. Note: the parameters use zero based counting. The TYPE parameter denotes the API the user subroutine uses; currently Aria supports type ELEMENT_TENSOR for tensor valued thermal conductivity.

The optional MULTIPLIER parameter (defaults to 1.0) can be supplied to scale the output of the user subroutine, i.e., the flux f will be $f = m f_{user}$ where m is the multiplier and f_{user} is the output of the user subroutine.

See section [9.2.2](#) for a more complete example of a Calore user subroutine.

Must be accompanied by the HEAT_CONDUCTION = GENERALIZED option.

4.53. THERMAL DIFFUSIVITY

THERMAL DIFFUSIVITY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the thermal diffusivity.

Summary Specifies the material model for the thermal diffusivity.

Parent

Block(s)

ARIA MATERIAL

4.53.1. THERMAL DIFFUSIVITY = CALORE_USER_SUB

Parameters

NAME = *STRING*

TYPE = *STRING*

[MULTIPLIER = *REAL*]

[NR = *INT*]

[R0 = *INT*]

[R1 = *INT*(etc.)]

[NI = *INT*]

[I0 = *INT*]

[I1 = *INT*(etc.)]

Example

Thermal Diffusivity = Calore_User_Sub name=w80afftuser
type=element NR=2 R0=1000 R1=0.7

Description NAME is the name of the user subroutine was registered with. NR and NI are the numbers of real and integer parameters, respectively. Each real (int) parameter is supplied by the R_n (I_n) parameter. Note: the parameters use zero based counting. The TYPE parameter denotes the API the user subroutine uses; currently Aria only supports types ELEMENT and NODE.

The optional MULTIPLIER parameter (defaults to 1.0) can be supplied to scale the output of the user subroutine, i.e., the flux f will be $f = m f_{user}$ where m is the multiplier and f_{user} is the output of the user subroutine.

See section [9.2.2](#) for a more complete example of a Calore user subroutine.

4.53.2. THERMAL DIFFUSIVITY = CONSTANT

Parameters

D = *REAL*

Example

THERMAL DIFFUSIVITY = CONSTANT D = 1.0

Description D is the value of the constant thermal diffusivity.

4.53.3. THERMAL DIFFUSIVITY = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

THERMAL DIFFUSIVITY = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.54. TOTAL INTERNAL ENERGY

TOTAL INTERNAL ENERGY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies a model for the total internal energy of a material.

Summary Specifies a model for the total internal of a material.

Parent

Block(s)

ARIA MATERIAL

4.54.1. TOTAL INTERNAL ENERGY = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

Total Internal Energy = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.54.2. TOTAL INTERNAL ENERGY = POROUS

Parameters

(none)

Example

Total Internal Energy = Porous

Description The total internal energy e is computed as

$$e = (1 - \phi)\rho_s e_s + \phi * \rho_f e_f \quad (4.142)$$

where ϕ is the porosity, ρ_s is the density of the solid porous skeleton, e_s is the internal energy of the solid porous skeleton, ρ_f is the density of the fluid phase and e_f is the internal energy of the fluid phase.

4.55. VALENCE

VALENCE = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the valence (net charge) for a species.

Summary Specifies the valence (net charge) for a species.

Parent

Block(s)

ARIA MATERIAL

4.55.1. VALENCE = CONSTANT

Parameters

`Z = REAL`
`[SUBINDEX = INT]`

Example

`Valence = Constant Subindex=1 Z = 1`
`Valence = Constant Subindex=2 Z = -1`
`Valence = Constant Subindex=5 Z = -2`

Description Z is the value of the species valence.

SUBINDEX is the species subindex.

4.55.2. VALENCE = ENCORE_FUNCTION

Parameters

`NAME = STRING`
`[EVAL_TYPE = STRING]`

Example

`Valence = Encore_Function Name=My_Function`

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.56. VISCOSITY

VISCOSITY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the fluid viscosity.

Summary Specifies the material model for the fluid viscosity.

Parent
Block(s)
ARIA MATERIAL

4.56.1. VISCOSITY = ARRHENIUS

Parameters

mu0 = *REAL*

E = *REAL*

Example

VISCOSITY = Arrhenius mu0=16.4 E=5000.

Description This model provides a viscosity with an Arrhenius temperature dependence:

$$\mu = \mu_0 e^{-E/T} \quad (4.143)$$

where T is the temperature.

4.56.2. VISCOSITY = ARRHENIUS_CARREAU

Parameters

MU_ZERO = *REAL*

[MU_INF = *REAL*]

[A = *REAL*]

N = *REAL*

[LAMBDA = *REAL*]

K = *REAL*

T_REF = *REAL*

[SKIP_SENSITIVITIES = *INT*]

Example

Viscosity = Arrhenius_Carreau ...

Description This viscosity model is a function of the shear rate (Carreau model) and temperature (Arrhenius model). The two contributions are combined multiplicatively.

$$\mu = \left[\mu_{\infty} + (\mu_o - \mu_{\infty}) (1 + (\lambda \dot{\gamma})^a)^{\frac{n-1}{a}} \right] e^{\frac{K}{T} - \frac{K}{T_{ref}}} \quad (4.144)$$

where μ_{∞} is the infinite shear viscosity (MU_INF, defaults to zero), μ_o is the zero shear viscosity (MU_ZERO), n (N) and a (A, defaults to 2) are model parameters, $\dot{\gamma}$ is the shear rate, λ (LAMBDA) is a time constant (defaults to 1), T_{ref} is a reference temperature and K is an Arrhenius constant.

If the optional flag SKIP_SENSITIVITIES is nonzero then no Newton sensitivities will be included.

4.56.3. VISCOSITY = BINGHAM_WLF

Parameters

MU_ZERO = *REAL*

MU_INF = *REAL*

F = *REAL*

N = *REAL*

A = *REAL*

LAMBDA = *REAL*

TAU_Y = *REAL*

[SKIP_SENSITIVITIES = *INT*]

Example

VISCOSITY = Bingham_WLF ...

Description

$$\mu = \mu_{\infty} + \left(\mu_o - \mu_{\infty} + \tau_y \frac{1 - e^{-\dot{\gamma} F}}{\dot{\gamma}} \right) (1 + (\lambda \dot{\gamma})^a)^{\frac{n-1}{a}} \quad (4.145)$$

where $\dot{\gamma}$ is the shear rate.

If the optional flag SKIP_SENSITIVITIES is nonzero then no Newton sensitivities will be included.

4.56.4. VISCOSITY = BINGHAM_WLFT

Parameters

MU_ZERO = *REAL*
 MU_INF = *REAL*
 F = *REAL*
 N = *REAL*
 A = *REAL*
 LAMBDA = *REAL*
 TAU_Y = *REAL*
 C_1 = *REAL*
 C_2 = *REAL*
 T_REF = *REAL*
 [SKIP_SENSITIVITIES = *INT*]

Example

VISCOSITY = Bingham_WLFT ...

Description

$$\mu = a_T \left(\mu_\infty + \left(\mu_o - \mu_\infty + \tau_y \frac{1 - e^{-a_T \dot{\gamma} F}}{a_T \dot{\gamma}} \right) (1 + (a_T \lambda \dot{\gamma})^a)^{\frac{n-1}{a}} \right) \quad (4.146)$$

where

$$a_T = e^{\frac{c_1(T_o - T)}{c_2 + T - T_o}} \quad (4.147)$$

and T is the temperature and $\dot{\gamma}$ is the shear rate.

If the optional flag SKIP_SENSITIVITIES is nonzero then no Newton sensitivities will be included.

4.56.5. VISCOSITY = CARREAU

Parameters

MU_ZERO = *REAL*
 [MU_INF = *REAL*]
 [A = *REAL*]
 N = *REAL*
 LAMBDA = *REAL*
 [SKIP_SENSITIVITIES = *INT*]

Example

Viscosity = Carreau ...

Description

$$\frac{\mu - \mu_\infty}{\mu_o - \mu_\infty} = (1 + (\lambda \dot{\gamma})^a)^{\frac{n-1}{a}} \quad (4.148)$$

or

$$\mu = \mu_\infty + (\mu_o - \mu_\infty) (1 + (\lambda \dot{\gamma})^a)^{\frac{n-1}{a}} \quad (4.149)$$

where μ_∞ is the infinite shear viscosity (MU_INF, defaults to zero), μ_o is the zero shear viscosity (MU_ZERO), n (N) and a (A, defaults to 2) are model parameters, $\dot{\gamma}$ is the shear rate and λ (LAMBDA) is a time constant.

If the optional flag SKIP_SENSITIVITIES is nonzero then no Newton sensitivities will be included.

4.56.6. VISCOSITY = CARREAU_T

Parameters

MU_ZERO = *REAL*

[MU_INF = *REAL*]

[A = *REAL*]

N = *REAL*

K = *REAL*

[SKIP_SENSITIVITIES = *INT*]

Example

Viscosity = Carreau_T ...

Description

$$\frac{\mu - \mu_{\infty}}{\mu_o - \mu_{\infty}} = \left(1 + (e^{k/T} \dot{\gamma})^a\right)^{\frac{n-1}{a}} \quad (4.150)$$

or

$$\mu = \mu_{\infty} + (\mu_o - \mu_{\infty}) \left(1 + (e^{k/T} \dot{\gamma})^a\right)^{\frac{n-1}{a}} \quad (4.151)$$

where μ_{∞} is the infinite shear viscosity (MU_INF, defaults to zero), μ_o is the zero shear viscosity (MU_ZERO), n (N) and a (A, defaults to 2) are model parameters and $\dot{\gamma}$ is the shear rate. The quantity $e^{k/T}$, where T is temperature and k (K) is a reference temperature, is a temperature dependent time scale; it takes the place of the constant λ time scale in the CARREAU model.

If the optional flag SKIP_SENSITIVITIES is nonzero then no Newton sensitivities will be included.

4.56.7. VISCOSITY = CONSTANT

Parameters

MU = *REAL*

Example

VISCOSITY = CONSTANT MU = 1.0

Description MU is the value of the constant fluid viscosity.

4.56.8. VISCOSITY = CURING_FOAM

Parameters

VFRAC_SUBINDEX = *INT*
EXTENT_SUBINDEX = *INT*
PHI_ZERO = *REAL*
[A = *REAL*]
[B = *REAL*]
[C = *REAL*]
[KSI_C = *REAL*]

Example

Viscosity = Curing_Foam Vfrac_Subindex=1 Extent_Subindex=2
Phi_Zero=0.45

Description For a curing epoxy with volume fraction ϕ and extent of reaction ξ the viscosity is given by

$$\mu = \mu_o \exp \frac{\phi_o - \phi}{1 - \phi_o + \phi} \quad (4.152)$$

where μ_o is given by

$$\mu_o = (a - bT) \left(\frac{\xi_c^2 - \xi^2}{\xi_c^2} \right)^c \quad (4.153)$$

where T is the temperature. The remaining parameters a , b , c and ξ_c have default values of $a = 20$, $b = 0.22$, $c = -4/3$ and $\xi_c = 0.45$ though they can be overridden with the optional model parameters.

NOTE: The volume fraction is assumed to be a SPECIES field with the subindex provided by the VFRAC_SUBINDEX parameter. Likewise, the extent of reaction field is assumed to be a SPECIES field with the subindex provided by the EXTENT_SUBINDEX parameter.

4.56.9. VISCOSITY = ENCORE_FUNCTION

Parameters

NAME = *STRING*
[EVAL_TYPE = *STRING*]

Example

VISCOSITY = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```

Begin String Function My_Function
  Value is "200 + 1.0*t"
End

```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.56.10. VISCOSITY = KRIEGER

Parameters

BETA = *REAL*

PHI_MAX = *REAL*

MU_S = *REAL*

Example

VISCOSITY = KRIEGER BETA = -1.65, PHI_MAX = 1.0, MU_S = 1.0

Description In the viscosity model of [\[4\]](#)

$$\mu = \mu_s \left(1 - \frac{\phi}{\phi_m}\right)^\beta \quad (4.154)$$

BETA is the Krieger exponent, PHI_MAX is the maximum suspension concentration and MU_S is the solvent viscosity.

4.56.11. VISCOSITY = POLYNOMIAL

Parameters

VARIABLE = *STRING* ORDER = *INT* [VARIABLE_OFFSET = *REAL*] [C0 = *REAL*] [C1 = *REAL*] ... [CN = *REAL*]

Example

Viscosity= Polynomial Variable=Temperature Order=1 C0=401.0
C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$\mu = \sum_{i=0}^N C_i (X + X_o)^i \quad (4.155)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter, X_o is an optional offset

(VARIABLE_OFFSET, default is zero) and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section [2.7.1](#).

4.56.12. VISCOSITY = POWER_LAW

Parameters

K = *REAL*

N = *REAL*

Example

Viscosity = Power_Law K=0.8 N=0.5

Description The viscosity is proportional to the shear rate, $\dot{\gamma}$ raised to some power, e.g.,

$$\mu = k\dot{\gamma}^n \quad (4.156)$$

where k (K) and n (N) are model parameters.

4.56.13. VISCOSITY = THERMAL

Parameters

[A = *REAL*]

[B = *REAL*]

[C = *REAL*]

[D = *REAL*]

Example

VISCOSITY = THERMAL A=1750 C=0.12 D=0

Description This model is simply a cubic polynomial in temperature where the viscosity is given by

$$\mu = A + BT + CT^2 + DT^3 \quad (4.157)$$

where T is the temperature.

4.56.14. VISCOSITY = USER_FUNCTION

Parameters

NAME = *STRING*

X = *STRING*

Example

```

begin definition for function Water_Viscosity
  # Source Appendix 2 from "Transport Processes and
  # Unit Operations" by C. J. Geankoplis
  type is piecewise linear
  begin values
    # K      Pa*s (or cP)
    273.15  1.7921
    275.15  1.6728
    277.15  1.5674
    279.15  1.4728
    281.15  1.3860
    283.15  1.3077
    285.15  1.2363
    287.15  1.1709
    289.15  1.1111
    291.15  1.0559
    293.15  1.0050
    293.35  1.0000
    295.15  0.9579
    297.15  0.9142
    299.15  0.8737
    301.15  0.8360
    303.15  0.8007
    305.15  0.7679
    307.15  0.7371
    309.15  0.7085
    311.15  0.6814
    313.15  0.6560
    315.15  0.6321
    317.15  0.6097
    319.15  0.5883
    321.15  0.5683
    323.15  0.5494
    325.15  0.5315
    327.15  0.5146
    329.15  0.4985
    331.15  0.4832
    333.15  0.4688
    335.15  0.4550
    337.15  0.4418
    339.15  0.4293
    341.15  0.4174
    343.15  0.4061
    345.15  0.3952
    347.15  0.3849
    349.15  0.3750
    351.15  0.3655
    353.15  0.3565
    355.15  0.3478
    357.15  0.3395

```

Description A look-up function is used to compute the values of the viscosity as a function of some other variable, i.e. $f(x)$. The function type (“piecewise linear” in the example above) must support the `differentiate()` method for Newton’s method.

Here NAME is the name of the user-defined function (Water_Viscosity in the example) and X is the Aria name of the abscissa variable (TEMPERATURE in the example). Note that X is not necessarily the same name as the abscissa variable identified in the user-defined function (T in the example).

4.56.15. VISCOSITY = WELD

Parameters

[BETA = *REAL*]
C0 = *REAL*
C1 = *REAL*
C2 = *REAL*
C3 = *REAL*
T_LIQ = *REAL* T_90 = *REAL* T_MAX = *REAL*

Example

Viscosity = Weld C0=1 C1=-1e-2 C2=0 C3=0 T_LIQ=920 T_MAX=1400
T_90=1000

Description This is an empirical model that emulates the melting of a solid metal during the laser welding process.

$$\mu = \begin{cases} \mu_{90} + (\mu_{liq} - \mu_{90}) \frac{T - T_{90}}{T_{liq} - T_{90}} & : T < T_{liq} \\ c_0 + c_1 \hat{T} + c_2 \hat{T}^2 + c_3 \hat{T}^3 & : T \geq T_{liq} \end{cases} \quad (4.158)$$

where μ_{liq} is given by

$$\mu_{liq} = c_0 + c_1 T_{liq} + c_2 T_{liq}^2 + c_3 T_{liq}^3, \quad (4.159)$$

$\mu_{90} = \beta \mu_{liq}$ and $\hat{T} = \min(T, T_{max})$. The default value of BETA is 10^{11} .

4.57. FLOWING LIQUID VISCOSITY

FLOWING LIQUID VISCOSITY = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the fluid viscosity.

Summary Specifies the material model for the fluid viscosity in the Brinkman momentum equation.

Parent

Block(s)

ARIA MATERIAL

4.57.1. FLOWING LIQUID VISCOSITY = CONSTANT

Parameters

MU = *REAL*

Example

FLOWING LIQUID VISCOSITY = CONSTANT MU = 1.0

Description MU is the value of the constant fluid viscosity.

4.58. VOLUME FRACTION GAS

VOLUME FRACTION GAS = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the volume fraction of gas.

Summary Specifies the material model for the volume fraction of gas.

Parent

Block(s)

ARIA MATERIAL

4.58.1. VOLUME FRACTION GAS = CONSTANT

Parameters

value = *REAL*

Example

Volume Fraction Gas = Constant value = 1.0

Description value is the volume fraction of gas.

4.58.2. VOLUME FRACTION GAS = FROM_MASS_FRACTIONS

Parameters

None

Example

Volume Fraction Gas = From_Mass_Fractions

Description For a multiphase ChemEq model, this model uses

$$\phi = 1 - \rho \sum_s \frac{Y_i}{\rho_{b,i}} \quad (4.160)$$

where ϕ is the gas volume fraction, ρ is the overall density, $\rho_{b,i}$ is the bulk density of the i^{th} solid species, and Y_i is the mass fraction of the i^{th} solid species. This model uses the species phase definitions from the ChemEq definition to determine which species are solid. As such, the model can only be used in a material block which also contains a ChemEq definition.

This uses expressions for the mass fractions, so its material block must also include “Mass_Fraction of X = From_ChemEq” for each solid species, or some comparable definition for mass fraction.

You must also provide an expression for the bulk density of each solid species.

4.58.3. VOLUME FRACTION GAS = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

Volume Fraction Gas = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

4.58.4. VOLUME FRACTION GAS = POLYNOMIAL

Parameters

VARIABLE = *STRING* ORDER = *INT* [VARIABLE_OFFSET = *REAL*] [CO = *REAL*] [C1 = *REAL*] ... [CN = *REAL*]

Example

Volume Fraction Gas= Polynomial Variable=Temperature Order=1
CO=401.0 C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$\kappa = \sum_{i=0}^N C_i (X + X_o)^i \quad (4.161)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter, X_o is an optional offset (VARIABLE_OFFSET, default is zero) and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section [2.7.1](#).

4.58.5. VOLUME FRACTION GAS = USER_FUNCTION

Parameters

NAME = *STRING*
X = *STRING*

Example

```
begin definition for function SI_phi
  type is piecewise linear
  begin values
    20.0      5.50e7
    100.0     4.60e7
    ...
    800.0     1.30e7
    2000.0    1.30e7
  end values
end definition for function SI_phi

...

Begin Aria Material Foo
  ...
  Volume Fraction Gas = User_Function Name=SI_phi X=Temperature
  ...
End Aria Material Foo
```

Description A look-up function is used to compute the values of the thermal conductivity as a function of some other variable, i.e. $f(x)$. The function type (“piecewise linear” in the example above) must support the `differentiate()` method for Newton’s method.

Here NAME is the name of the user-defined function (SI_phi, in the example) and X is the Aria name of the abscissa variable (TEMPERATURE in the example). Note that X is not necessarily the same name as the optional abscissa variable identified in the user-defined function.

4.59. YOUNGS MODULUS

YOUNGS MODULUS = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Specifies the material model for the Young’s modulus.

Summary The solid stress $\mathbf{T}$ is given by

$$\mathbf{T} = \lambda E_{kk} \mathbf{I} + 2\mu \mathbf{E} - \beta (T - T_{ref}) \mathbf{I} \quad (4.162)$$

where λ and μ are the Lamé coefficients, $\mathbf{E} = \frac{1}{2} (\nabla \mathbf{d} + \nabla \mathbf{d}^T)$ is the deformation tensor, β is the coefficient of thermal stress, T is temperature and T_{ref} is the thermal strain reference temperature.

These Lamé coefficients are related to the more standard Young’s modulus, Poisson’s ratio and CTE (α) as follows:

$$2\mu = \frac{E}{(1 + \nu)} \quad (4.163)$$

$$\lambda = \frac{\nu E}{(1 + \nu)(1 - 2\nu)} = 2\mu \frac{\nu}{(1 - 2\nu)} \quad (4.164)$$

$$\beta = \frac{\alpha E}{(1 - 2\nu)} = \alpha (3\lambda + 2\mu) \quad (4.165)$$

When a user supplies the Young’s modulus, Poisson’s ratio and CTE properties Aria internally converts them into the Lamé coefficients.

Supplying the Lamé coefficients is more computationally efficient but perhaps less convenient, especially if the material properties are varying (e.g., temperature dependent in a non-isothermal problem).

Parent
Block(s)
ARIA MATERIAL

4.59.1. YOUNGS MODULUS = CONSTANT

Parameters

YM = *REAL*

Example

YOUNGS MODULUS = CONSTANT YM = 1.0

Description YM is the value of the constant Young's modulus.

4.59.2. YOUNGS MODULUS = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

YOUNGS MODULUS = Encore_Function Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

5. EQUATIONS ARIA SOLVES

5.1. GENERALIZED CONSERVATION EQUATION

We first introduce a general conservation equation, as a model for the specific equations that Aria solves, demonstrating how the Galerkin finite element method is applied to it, and how the integration by parts is carried out on its individual terms. Following [7], the conservation of a general scalar quantity $b(\mathbf{x}, t)$, with units of amount-per-unit-volume, at a point $\mathbf{x}$ and time t can be expressed as

$$\frac{\partial b}{\partial t} + \nabla \cdot (b\mathbf{v}) = -\nabla \cdot \mathbf{f} + B_V \quad (5.1)$$

where $\mathbf{v}$ is the mass average velocity, $\mathbf{f}$ is the diffusive flux of b , and B_V is the volumetric source of b .

The Galerkin FEM (G/FEM) residual form of 5.1 is formed by bringing the right hand side terms to the left, multiplying by the FEM weight function ϕ^i and integrating over the volume V ,

$$R_b^i = \int_V \left(\frac{\partial b}{\partial t} + \mathbf{v} \cdot \nabla b + b \nabla \cdot \mathbf{v} + \nabla \cdot \mathbf{f} - B_V \right) \phi^i dV = 0. \quad (5.2)$$

In many applications $\nabla \cdot \mathbf{v} = 0$ so we ignore that term from here on. However, it is straight forward to account for this term via the source term B_V . Using the vector identity $(\nabla \cdot \mathbf{f})\phi^i = \nabla \cdot (\mathbf{f}\phi^i) - \nabla \phi^i \cdot \mathbf{f}$ and using the divergence theorem, 5.2 becomes

$$R_b^i = \int_V \left[\left(\frac{\partial b}{\partial t} + \mathbf{v} \cdot \nabla b - B_V \right) \phi^i - \nabla \phi^i \cdot \mathbf{f} \right] dV + \int_S \mathbf{n} \cdot \mathbf{f} \phi^i dS = 0. \quad (5.3)$$

Here $\mathbf{n}$ is a unit normal along the boundary S , pointing out of the volume V .

Equation 5.3 embodies the sign convention for sources, fluxes and equation terms used within Aria. For example, scalar flux expressions in Aria provide values for $f_n \equiv \mathbf{n} \cdot \mathbf{f}$ and should be positive for a flux of b leaving the volume V .

Note also that we have not assigned a units convention to the equation. Any unit system may be employed in the specification of the individual terms in 5.1. However, each term in 5.1 must have overall units of $[b] / [\text{time}]$, and the overall residual expression has units of $[b] * [L]^3 / [\text{time}]$, where $[b]$ are units of the conserved quantity, b , $[L]$ is the unit of the length scale, and $[\text{time}]$ is the unit for time.

5.2. CONSERVATION OF MASS

For a material with density ρ , letting $b = \rho$ results in the conservation of mass. Since there is no net flow relative to the mass average velocity $\mathbf{f} = \mathbf{0}$. Although there are no sources of mass, having such a source can be convenient in modeling and simulation; so, we let the mass source be $B_V = q_m$. Thus, (5.1) becomes

$$\frac{\partial \rho}{\partial t} + \rho \nabla \cdot \mathbf{v} + \mathbf{v} \cdot \nabla \rho = q_m. \quad (5.4)$$

For the special but common case of constant density, this reduces to

$$\nabla \cdot \mathbf{v} = 0. \quad (5.5)$$

Using equation 5.3, the G/FEM residual form is

$$R_P^i = \int_V \left(-\frac{\partial \rho}{\partial t} - \rho \nabla \cdot \mathbf{v} - \mathbf{v} \cdot \nabla \rho + q_m \right) \phi^i dV = 0. \quad (5.6)$$

Important Note: Equation 5.6 has been multiplied by -1 because this form results in a better linear system for the special case of incompressible flow. This is important to remember when defining mass source terms.

In Aria, each term in 5.6 is specified separately as identified in equation 5.7.

$$R_P^i = \underbrace{\int_V -\frac{\partial \rho}{\partial t} \phi^i dV}_{\text{MASS}} + \underbrace{\int_V -(\mathbf{v} \cdot \nabla \rho + \rho \nabla \cdot \mathbf{v}) \phi^i dV}_{\text{ADV}} + \underbrace{\int_V q_m \phi^i dV}_{\text{SRC}} = 0 \quad (5.7)$$

For a purely incompressible form, Aria offers the alternative form given in 5.8;

$$R_P^i + \underbrace{\int_V -\nabla \cdot \mathbf{v} \phi^i dV}_{\text{DIV}} + \underbrace{\int_V q_m \phi^i dV}_{\text{SRC}} = 0 \quad (5.8)$$

5.3. CONSERVATION OF ENERGY

For a material with constant density and specific heat C_p , temperature T , heat flux $\mathbf{q}$ and volumetric energy source H_V , letting $b = \rho C_p T$, $\mathbf{f} = \mathbf{q}$ and $B_V = H_V$ results in the conservation of energy.

$$\rho C_p \frac{\partial T}{\partial t} + \rho C_p \mathbf{v} \cdot \nabla T = -\nabla \cdot \mathbf{q} + H_V. \quad (5.9)$$

A common constitutive relationship for $\mathbf{q}$ is Fourier's law, $\mathbf{q} = -\kappa \nabla T$ where κ is the thermal conductivity. However, we leave the heat flux as an option to be specified as part of the material properties (see section 4.15). Using equation 5.3, the G/FEM residual form is

$$R_T^i = \int_V \left[\left(\rho C_p \frac{\partial T}{\partial t} + \rho C_p \mathbf{v} \cdot \nabla T - H_V \right) \phi^i - \nabla \phi^i \cdot \mathbf{q} \right] dV + \int_S q_n \phi^i dS = 0 \quad (5.10)$$

where q_n is the heat flux at the boundary. For example, the natural convection boundary condition gives $q_n = h(T - T_\infty)$ where h is the heat transfer coefficient and T_∞ is the bulk temperature away from the surface.

In Aria, each term in 5.10 is specified separately as identified in equation 5.11.

$$R_T^i = \underbrace{\int_V \rho C_p \frac{\partial T}{\partial t} \phi^i dV}_{\text{MASS}} + \underbrace{\int_V \rho C_p \mathbf{v} \cdot \nabla T \phi^i dV}_{\text{ADV}} - \underbrace{\int_V H_V \phi^i dV}_{\text{SRC}} - \underbrace{\int_V \nabla \phi^i \cdot \mathbf{q} dV}_{\text{DIFF}} + \int_S q_n \phi^i dS = 0 \quad (5.11)$$

More and more often we need to account for variable density problems and so we need to bring back some of the terms we threw away because we were going to assume $\nabla \cdot \mathbf{v} \equiv 0$. Here's a do-over of equation 5.11 that accommodates a variable density through the DIV term:

$$R_T^i = \underbrace{\int_V \rho C_p \frac{\partial T}{\partial t} \phi^i dV}_{\text{MASS}} + \underbrace{\int_V \rho C_p \mathbf{v} \cdot \nabla T \phi^i dV}_{\text{ADV}} + \underbrace{\int_V \rho C_p T \nabla \cdot \mathbf{v} \phi^i dV}_{\text{DIV}} - \underbrace{\int_V H_V \phi^i dV}_{\text{SRC}} - \underbrace{\int_V \nabla \phi^i \cdot \mathbf{q} dV}_{\text{DIFF}} + \int_S q_n \phi^i dS = 0 \quad (5.12)$$

Note, however, that equation 5.12 still assumes a constant specific heat C_p .

5.3.1. SUPG

SUPG stabilization can be activated by adding the SUPG term on the input file line. This capability is still under development.

5.4. CONSERVATION OF CHEMICAL SPECIES

For a material with species k with molar concentration C_k , molar flux $\mathbf{J}_k$ relative to the mass average velocity and volumetric reaction rate $R_{V,k}$, letting $b = y_k$, $\mathbf{f} = \mathbf{J}_k$ and $B_V = R_{V,k}$ in (5.1) results in the conservation equation for species k ,

$$\frac{\partial C_k}{\partial t} + \mathbf{v} \cdot \nabla C_k = -\nabla \cdot \mathbf{J}_k + R_{V,k}. \quad (5.13)$$

For liquid mixtures which are dilute in all species except one, Fick's law is often used to approximate $\mathbf{J}_k$. In this approximation, D_k represents the diffusion coefficient of species k with respect to the concentrated species and it is assumed that the interactions between dilute species is assumed negligible. Again, however, we choose to leave the governing equation in the more general form and require the particular diffusive flux model as user input (see section 4.46). Using equation 5.3, the G/FEM residual form is

$$R_{C_k}^i = \int_V \left[\left(\frac{\partial C_k}{\partial t} + \mathbf{v} \cdot \nabla C_k - R_{V,k} \right) \phi^i - \nabla \phi^i \cdot \mathbf{J}_k \right] dV + \int_S q_{n,k} \phi^i dS = 0 \quad (5.14)$$

where $q_{n,k}$ is the mass flux at the boundary. For example, the natural convection boundary condition gives $q_n = k(C_k - C_{\infty,k})$ where k is the mass transfer coefficient and $C_{\infty,k}$ is the bulk concentration away from the surface.

In Aria, each term in 5.14 is specified separately as identified in equation 5.15.

$$R_{C_k}^i = \underbrace{\int_V \frac{\partial C_k}{\partial t} \phi^i dV}_{\text{MASS}} + \underbrace{\int_V \mathbf{v} \cdot \nabla C_k \phi^i dV}_{\text{ADV}} - \underbrace{\int_V R_{V,k} \phi^i dV}_{\text{SRC}} - \underbrace{\int_V \nabla \phi^i \cdot \mathbf{J}_k dV}_{\text{DIFF}} + \int_S q_{n,k} \phi^i dS = 0 \quad (5.15)$$

More and more often we need to account for variable density problems and so we need to bring back some of the terms we threw away because we were going to assume $\nabla \cdot \mathbf{v} \equiv 0$. Here's a do-over of equation 5.15 that accommodates a variable density through the DIV term:

$$R_{C_k}^i = \underbrace{\int_V \frac{\partial C_k}{\partial t} \phi^i dV}_{\text{MASS}} + \underbrace{\int_V \mathbf{v} \cdot \nabla C_k \phi^i dV}_{\text{ADV}} + \underbrace{\int_V C \nabla \cdot \mathbf{v} \phi^i dV}_{\text{DIV}} - \underbrace{\int_V R_{V,k} \phi^i dV}_{\text{SRC}} - \underbrace{\int_V \nabla \phi^i \cdot \mathbf{J}_k dV}_{\text{DIFF}} + \int_S q_{n,k} \phi^i dS = 0 \quad (5.16)$$

Often times it is useful to solve for mass, weight or volume fractions of each species rather than for the concentration directly. In that case, an additional condition exists,

$$\sum_k C_k = 1 \quad (5.17)$$

Using this condition, it is only necessary to solve for $N - 1$ species fractions where N is the total number of species present in the problem. The final species, then, is simply given as

$$C_j = 1 - \sum_{k \neq j} C_k \quad (5.18)$$

This method can be triggered in Aria by specifying the equation term FRACBAL. In this case, the equation for C_j is not included in the system of unknowns but is instead post-processed on the fly. Aria will automatically detect all other species equations and include them in the fraction balance.

5.5. CONSERVATION OF FLUID MOMENTUM

The Cauchy momentum equation is given by

$$\rho \frac{\partial \mathbf{v}}{\partial t} + \rho \mathbf{v} \cdot \nabla \mathbf{v} - \mathbf{g} - \nabla \cdot \mathbf{T} = \mathbf{0} \quad (5.19)$$

where $\mathbf{T}$ is the fluid stress tensor and $\mathbf{g}$ is a body force. We construct the G/FEM residual form of 5.19 by contracting with the unit coordinate vector in the k -direction, $\mathbf{e}_k$, multiplying by the weight function ϕ^i and integrating over the volume. Using the vector identity $(\nabla \cdot \mathbf{T}) \cdot \mathbf{e}_k \phi^i = \nabla \cdot (\mathbf{T} \cdot \mathbf{e}_k \phi^i) - \mathbf{T}^t : \nabla (\mathbf{e}_k \phi^i)$ and integrating by parts gives

$$R_{m,k}^i = \int_V \left[\left(\rho \frac{\partial \mathbf{v}}{\partial t} + \rho \mathbf{v} \cdot \nabla \mathbf{v} - \mathbf{g} \right) \cdot \mathbf{e}_k \phi^i + \mathbf{T}^t : \nabla (\mathbf{e}_k \phi^i) \right] dV - \int_S \mathbf{n} \cdot \mathbf{T} \cdot \mathbf{e}_k \phi^i dS = 0 \quad (5.20)$$

In Aria, each term in 5.20 is specified separately as identified in equation 5.15.

$$\begin{aligned} R_{m,k}^i = & \underbrace{\int_V \rho \frac{\partial \mathbf{v}}{\partial t} \cdot \mathbf{e}_k \phi^i dV}_{\text{MASS}} + \underbrace{\int_V \rho \mathbf{v} \cdot \nabla \mathbf{v} \cdot \mathbf{e}_k \phi^i dV}_{\text{ADV}} - \underbrace{\int_V \mathbf{g} \cdot \mathbf{e}_k \phi^i dV}_{\text{SRC}} \\ & + \underbrace{\int_V \mathbf{T}^t : \nabla (\mathbf{e}_k \phi^i) dV}_{\text{DIFF}} - \int_S \mathbf{n} \cdot \mathbf{T} \cdot \mathbf{e}_k \phi^i dS = 0 \quad (5.21) \end{aligned}$$

5.6. CONSERVATION OF SOLID MOMENTUM

Aria currently solves the quasistatic form of the solid momentum equations. Furthermore, the solid stress is treated as a linear elastic material. In this limit, the Cauchy momentum equation is given by

$$\nabla \cdot \mathbf{T} = 0 \quad (5.22)$$

where $\mathbf{T}$ is the solid stress tensor. We construct the G/FEM residual form of 5.19 by contracting with the unit coordinate vector in the k -direction, $\mathbf{e}_k$, multiplying by the weight function ϕ^i and integrating over the volume. Using the vector identity $(\nabla \cdot \mathbf{T}) \cdot \mathbf{e}_k \phi^i = \nabla \cdot (\mathbf{T} \cdot \mathbf{e}_k \phi^i) - \mathbf{T}^t : \nabla (\mathbf{e}_k \phi^i)$ and integrating by parts gives

$$R_{m,k}^i = \int_V \mathbf{T}^t : \nabla (\mathbf{e}_k \phi^i) \, dV = 0 \quad (5.23)$$

Here, the surface contribution, $\int_S \mathbf{n} \cdot \mathbf{T} \cdot \mathbf{e}_k \phi^i \, dS$, has been dropped because Aria currently only supports Dirichlet and natural (homogeneous) boundary conditions for the solid equation.

In Aria, each term in 5.23 is specified separately as identified in equation 5.24.

$$R_{m,k}^i = \underbrace{\int_V \mathbf{T}^t : \nabla (\mathbf{e}_k \phi^i) \, dV}_{\text{DIFF}} = 0 \quad (5.24)$$

Currently, Aria does not support direct specification of the more popular stress-strain parameterization that utilizes Young's modulus E , Poisson's ratio ν and coefficient of thermal expansion α (note, the shear modulus $G = \mu$). The relationship between these two parameterizations is summarized here for convenience.

$$2\mu = \frac{E}{(1 + \nu)} \quad (5.25)$$

$$\lambda = \frac{\nu E}{(1 + \nu)(1 - 2\nu)} = 2\mu \frac{\nu}{(1 - 2\nu)} \quad (5.26)$$

$$\beta = \frac{\alpha E}{(1 - 2\nu)} = \alpha (3\lambda + 2\mu) \quad (5.27)$$

When the solid momentum equation is solved, the physical coordinates of the region, used to calculate integration quantities, is deformed by the displacement vector. The current configuration, $\mathbf{x}$, is calculated from the reference configuration, $\mathbf{X}$, by

$$\mathbf{x} = \mathbf{X} + \mathbf{d}, \quad (5.28)$$

where $\mathbf{d}$ is the displacement field. The displacement field is chosen automatically by the code, but may be overridden by setting a solution option. These displaced, physical coordinates are used for integration of all of the equations.

Additionally, the code supports the integration of the solid momentum equations in the reference configuration, rather than in the current configuration. This is activated through the use of the REF_DIFF equation term rather than the DIFF term. When this is used, the Cauchy stress tensor is rotated into the Second Piola-Kirchhoff stress tensor. Integration quantities are also calculated in the reference configuration. Care should be taken to ensure that the constitutive model used also changes its strain measure to one which is work conjugate with the Second Piola-Kirchhoff stress tensor.

If both the MESH and SOLID equations are defined in the same region, then the TALE mesh motion algorithm is activated automatically. Here, the reference frame for the SOLID equation is changed to the TALE reference frame, which is defined as

$$\underline{\mathbf{x}}_r = \underline{\mathbf{X}} + \underline{\mathbf{d}}_m - \underline{\mathbf{d}}_s \quad (5.29)$$

where $\underline{\mathbf{x}}_r$ is the new TALE reference frame, $\underline{\mathbf{d}}_m$ is MESH_DISPLACEMENTS, and $\underline{\mathbf{d}}_s$ is SOLID_DISPLACEMENTS. This affects the calculation of strain measures, such as $\underline{\mathbf{F}}$, and integration quantities, such as $\det(J)$, among others. More details of the TALE method will be available soon in a pending report.

5.7. VOLTAGE EQUATION

The electric potential or voltage V is frequently used in determining the electric field, $\mathbf{E} = -\nabla V$. While (5.1) cannot be applied to the voltage, the equation governing the voltage – Gauss’ law from Maxwell’s equations – has a similar form. Writing the electric displacement $\mathbf{D}$ as $\mathbf{D} = \epsilon \mathbf{E}$, where ϵ is the electric permittivity, Gauss’ law is

$$-\nabla \cdot \epsilon \nabla V = \rho_e \quad (5.30)$$

where the permittivity is taken to be a constant and ρ_e is the volumetric free charge density.

Using equation 5.3, the G/FEM residual form is

$$R_V^i = \int_V (-\rho_e \phi^i + \nabla \phi^i \cdot \epsilon \nabla V) dV + \int_S q_n \phi^i dS = 0 \quad (5.31)$$

In Aria, each term in 5.31 is specified separately as identified in equation 5.32.

$$R_V^i = \underbrace{- \int_V \rho_e \phi^i dV}_{\text{SRC}} + \underbrace{\int_V \nabla \phi^i \cdot \epsilon \nabla V dV}_{\text{DIFF}} + \int_S q_n \phi^i dS = 0 \quad (5.32)$$

5.8. CURRENT EQUATION

An alternate formulation in solving for the electrical potential (see section 5.7) is to solve the “current” equation which is a conservation equation for electrical charge. The electrical current $\mathbf{J}$ is frequently related to the electric field $\mathbf{E}$ using Ohm’s law as $\mathbf{J} = \sigma_e \mathbf{E}$ where σ_e is the electrical conductivity. The electric potential or voltage V is used in determining the electric field, $\mathbf{E} = -\nabla V$. However, we choose to leave the electrical current as a more general constitutive model to be provided as a material model input (see section 4.6). More complex version for charged ion fluxes (Nerst Planck, etc. can be utilized with the species equation).

$$-\nabla \cdot \mathbf{J} = S \quad (5.33)$$

Here S is a current source term, for example from electrochemical reactions in a battery simulation.

Using equation 5.3, the G/FEM residual form is

$$R_V^i = \int_V (-S\phi^i - \nabla\phi^i \cdot \mathbf{J}) dV + \int_S q_n\phi^i dS = 0 \quad (5.34)$$

In Aria, each term in 5.34 is specified separately as identified in equation 5.35.

$$R_V^i = - \underbrace{\int_V S\phi^i dV}_{\text{SRC}} - \underbrace{\int_V \nabla\phi^i \cdot \mathbf{J} dV}_{\text{DIFF}} + \int_S q_n\phi^i dS = 0 \quad (5.35)$$

5.9. CHARGE DENSITY EQUATION

This equation solves for the volumetric free charge density, ρ_e , and is meant to be coupled with the voltage equation in section 5.7). This equation can also be used in place of the current equation 5.33, since this equation has the correct form (the current equation has the correct form with ρ_e when electric displacement is activated) and the charge density is treated as a variable. The charge density evolves as

$$\frac{\partial \rho_e}{\partial t} + \mathbf{v} \cdot \nabla \rho_e = -\nabla \cdot \mathbf{J} = \nabla \cdot (\sigma \nabla V) \quad (5.36)$$

where $\mathbf{J} = -\sigma \nabla V$ is assumed to obey Ohm’s law and σ represents the conductivity.

The G/FEM residual form of this equation is

$$R_V^i = \int_V \left(\frac{\partial \rho_e}{\partial t} \phi^i + \nabla\phi^i \cdot \mathbf{v} + \nabla\phi^i \cdot \sigma \nabla V \right) dV + \int_S q_n\phi^i dS = 0 \quad (5.37)$$

In Aria, each term in 5.37 is specified separately as identified in equation 5.38.

$$R_V^i = \underbrace{\int_V \frac{\partial \rho_e}{\partial t} \phi^i dV}_{\text{MASS}} + \underbrace{\int_V \nabla\phi^i \cdot \mathbf{v} dV}_{\text{ADV}} + \underbrace{\int_V \nabla\phi^i \cdot \sigma \nabla V dV}_{\text{DIFF}} + \int_S q_n\phi^i dS = 0. \quad (5.38)$$

5.10. AMPERE EQUATION

Ampere's equation in a conductive material is given by

$$\nabla \times \mathbf{H} = \mathbf{J} + \frac{\partial \mathbf{D}}{\partial t} \quad (5.39)$$

where $\mathbf{H}$ is the magnetic field intensity, $\mathbf{J}$ is the current density and $\mathbf{D}$ is the electric displacement. Ignoring time dependent change in electric displacement a common approach of solving Ampere's equation for a magnetic flux intensity $\mathbf{H}$ in a conductive material is to recast the formulation in terms of magnetic field flux $\mathbf{B}$ by employing the constitutive equation relating magnetic field intensity to magnetic field flux, permeability of free space μ_o and magnetization vector $\mathbf{M}$, $\mathbf{H} = \frac{1}{\mu_o} \mathbf{B} - \mathbf{M}$ subject to the constraint $\nabla \cdot \mathbf{B} = 0$. An alternative formulation of this problem is obtained by introducing a magnetic vector potential $\mathbf{A}$ where $\nabla \times \mathbf{A} = \mathbf{B}$. This approach circumvents the need to explicitly impose the divergence free constraint $\nabla \cdot \mathbf{B}$ required in the formulation of the magnetic flux density. For static configurations the current density is a function of the electric field $\mathbf{E}$ and the electrical conductivity σ , $\mathbf{J} = \sigma \cdot \mathbf{E}$ whereas for conductors moving with velocity $\mathbf{v}$ $\mathbf{J} = \sigma \cdot \mathbf{E} + \sigma \cdot (\mathbf{v} \times \mathbf{B})$. Hence the formulation for moving conductors will include contributions obtained from the solution of Ohm's law for voltage V 5.7.

$$\frac{\partial \mathbf{A}}{\partial t} - \mathbf{v} \times (\nabla \times \mathbf{A}) + \frac{1}{\mu\sigma} \nabla \times (\nabla \times \mathbf{A}) - \nabla \left(\frac{1}{\mu\sigma} \nabla \cdot \mathbf{A} \right) + \nabla V - \nabla \times \mathbf{M} = \mathbf{0} \quad (5.40)$$

and using the curl-curl identity and recalling that $\nabla \cdot \mathbf{A} = 0$ then

$$\frac{\partial \mathbf{A}}{\partial t} - \mathbf{v} \times (\nabla \times \mathbf{A}) + \nabla^2 \frac{1}{\mu\sigma} \mathbf{A} + \nabla V - \nabla \times \mathbf{M} = \mathbf{0} . \quad (5.41)$$

Using equation 5.3, the G/FEM residual form is

$$R_{m,k}^i = \int_V \left[\left(\rho \frac{\partial \mathbf{A}}{\partial t} - \mathbf{v} \times (\nabla \times \mathbf{A}) + \nabla V - \nabla \times \mathbf{M} \right) \cdot \mathbf{e}_k \phi^i + \frac{1}{\mu\sigma} \nabla \mathbf{A} \cdot \nabla (\mathbf{e}_k \phi^i) \right] dV - \int_S \frac{1}{\mu\sigma} (\mathbf{n} \cdot \nabla \mathbf{A}) \cdot \mathbf{e}_k \phi^i dS = 0 . \quad (5.42)$$

In Aria, each term in 5.42 is specified separately as identified in equation 5.43.

$$R_{m,k}^i = \underbrace{\int_V \frac{\partial \mathbf{A}}{\partial t} \cdot \mathbf{e}_k \phi^i dV}_{\text{MASS}} - \underbrace{\int_V (\mathbf{v} \times \nabla \times \mathbf{A}) \cdot \mathbf{e}_k \phi^i dV}_{\text{ADV}} + \underbrace{\int_V (\nabla V - \nabla \times \mathbf{M}) \cdot \mathbf{e}_k \phi^i dV}_{\text{SRC}} + \underbrace{\int_V \frac{1}{\mu\sigma} \nabla \mathbf{A} \cdot \nabla (\mathbf{e}_k \phi^i) dV}_{\text{DIFF}} - \int_S \frac{1}{\mu\sigma} (\mathbf{n} \cdot \nabla \mathbf{A}) \cdot \mathbf{e}_k \phi^i dS = 0 . \quad (5.43)$$

5.11. SUSPENSION EQUATION

In treating the suspension as a continuum, we introduce an evolution equation for particle volume fraction, ϕ , as

$$\frac{\partial \phi}{\partial t} + \mathbf{v} \cdot \nabla \phi + \nabla \cdot \mathbf{N} = 0. \quad (5.44)$$

The particle volume fraction is defined as the total summed volume of particles per volume of the particle medium. 5.44 represents a balance between the stored particles, the convected particle flux, and the diffusive particle flux, $\mathbf{N}$. Several mechanisms which include Brownian motion, sedimentation, hydrodynamic particle interactions, and gradients in suspension viscosity may contribute to the diffusive particle flux. Specification of the appropriate flux model must then be carried out to close the definition of the conservation equation.

5.12. POROUS FLOW EQUATIONS

In what follows we use a subscript α to denote a component index and N_α is the total number of components. We use a subscript β to denote a phase and the total number of phases is N_β . The subscript s is used to refer to the solid phase of the porous skeleton; this phase is not included in N_β . Summations over α and β are assumed to range from one to N_α and N_β , respectively, unless otherwise specified.

5.12.1. Generalized Equations

This write up follows, directly, the reports of [8], [9] and [10].

5.12.1.1. Porosity and Void Ratio

In modeling of porous materials, one often needs to know the relative volume of pore space (V_p) and the solid porous skeleton (V_s). The most common measure of this is the *porosity*, ϕ , which is defined as the ratio of the volume of pore space (V_p) per unit total volume ($V_t = V_p + V_s$), viz.,

$$\phi = \frac{V_p}{V_t} = \frac{V_p}{V_p + V_s}. \quad (5.45)$$

The *void ratio* (r) is sometimes used as well and is defined as the ratio of the pore volume to the solid volume, viz.,

$$r = \frac{V_p}{V_s} \quad (5.46)$$

Clearly the porosity and void ratio are related,

$$r = \frac{\phi}{1 - \phi} \quad (5.47)$$

$$\phi = \frac{r}{1 + r} \quad (5.48)$$

5.12.1.2. Component Mass Balances

The mass balance for each component across all phases can be written

$$\frac{\partial d_\alpha}{\partial t} + \nabla \cdot \mathbf{F}_\alpha = Q_\alpha \quad \alpha = 1, \dots, N_\alpha \quad (5.49)$$

where d_α is mass concentration of component α across all phases, t is time, $\mathbf{F}_\alpha$ is the total mass flux of component α relative to a fixed frame of reference and Q_α is the volumetric source of component α .

The mass concentration of component α can be written as

$$d_\alpha = \phi \sum_{\beta} Y_{\alpha\beta} \rho_{\beta} S_{\beta} \quad (5.50)$$

where ϕ is the interstitial volume fraction, a.k.a. the porosity, that ranges from zero to one, Y denotes mass fraction so that $Y_{\alpha\beta}$ is the mass fraction of component α in phase β , ρ_{β} is mixture density of phase β and S_{β} is saturation which is defined as the fraction of the interstitial pore space occupied by phase β .

For completeness it is noted here that the mass fractions sum to one in each phase and that the saturations of all phases sum to unity,

$$\sum_{\alpha} Y_{\alpha\beta} = 1 \quad (5.51)$$

$$\sum_{\beta} S_{\beta} = 1. \quad (5.52)$$

The macroscopic mass flux in phase β , $\rho_{\beta} \mathbf{v}_{\beta}$ is obtained from the extended Darcy's Law,

$$\rho_{\beta} \mathbf{v}_{\beta} = \mathbf{f}_{\beta} = -\frac{\rho_{\beta} \kappa_{r\beta}}{\mu_{\beta}} \mathbf{K} \cdot (\nabla P_{\beta} + \rho_{\beta} \mathbf{g}) \quad (5.53)$$

where $\kappa_{r\beta}$ is the relative permeability of phase β and $\mathbf{K}$ is the permeability tensor which are both intrinsic properties of the porous material and so may vary spatially. The mixture viscosity of phase β is μ_{β} , P_{β} is the pressure in phase β and $\mathbf{g}$ is the gravitational acceleration.

The component mass flux, $\mathbf{F}_{\alpha}$ can be written as the sum of the component mass fluxes across each phase,

$$\mathbf{F}_{\alpha} = \sum_{\beta} \mathbf{F}_{\alpha\beta}. \quad (5.54)$$

Within each phase, the component mass flux can be decomposed in its convective and diffusive components,

$$\mathbf{F}_{\alpha\beta} = Y_{\alpha\beta} \mathbf{f}_{\beta} + \mathbf{J}_{\alpha\beta} \quad (5.55)$$

where $\mathbf{J}_{\alpha\beta}$ is the diffusive flux of component α in phase β . For example, for a gaseous, dilute binary mixture the diffusive flux may be modeled using Fick's Law,

$$\mathbf{J}_{\alpha\beta} = -\rho_{\beta} \mathcal{D}_{\alpha\beta} \nabla Y_{\alpha\beta} \quad (\text{dilute binary gas mixture}) \quad (5.56)$$

where $\mathcal{D}_{\alpha\beta}$ is the diffusion coefficient of component α in phase β .

5.12.1.3. Porous Species

The porous species equation is identical to the mass balance equation, with all quantities being molar concentrations. The porous species equation is written as

$$\frac{\partial c_\alpha}{\partial t} + \nabla \cdot \Pi_\alpha = R_\alpha \quad \alpha = 1, \dots, N_\alpha, \quad (5.57)$$

where c_α is the molar concentration, defined analogously to (5.50), Π_α is the molar flux, and R_α is the volumetric molar source of component α . The porous species equation exists to facilitate using expressions derived for use with the non porous-flow species equation. An analogous set of terms to those found in the mass balance equation can be derived on a molar concentration basis.

5.12.1.4. Energy Balance

In order to accomodate multicomponent transport problems we employ a enthalpy based energy conservation law,

$$\frac{\partial e}{\partial t} + \nabla \cdot \mathbf{q} = Q_e \quad (5.58)$$

where e is the total internal energy, $\mathbf{q}$ is the total heat flux relative to a stationary frame of reference and Q_e is the volumetric source of energy. The total internal energy is written as a sum of the energies of all components across all phases as well as the internal energy of the solid porous structure,

$$e = (1 - \phi) \rho_s e_s + \phi \sum_{\beta} S_{\beta} \rho_{\beta} e_{\beta} \quad (5.59)$$

where ρ_{β} and e_{β} are the mixture density and internal energy of phase β . Generally, thermodynamic relations are required to relate these quantities to the component specific quantities.

The total heat flux can be decomposed into different modes of transport. Typically,

$$\mathbf{q} = -\lambda_T \nabla T + \sum_{\beta} \sum_{\alpha} h_{\alpha\beta} \mathbf{F}_{\alpha\beta} \quad (5.60)$$

where λ_T is the effective thermal conductivity, T is the temperature and $h_{\alpha\beta}$ is the partial enthalpy of component α in phase β which is interpreted as the enthalpy of pure component α at the temperature and pressure of phase β . Using (5.55), we can expand (5.60) such that

$$\begin{aligned} \sum_{\alpha} h_{\alpha\beta} \mathbf{F}_{\alpha\beta} &= \sum_{\alpha} h_{\alpha\beta} (Y_{\alpha\beta} \mathbf{f}_{\beta} + \mathbf{J}_{\alpha\beta}) \\ &= h_{\beta} \mathbf{f}_{\beta} + \sum_{\alpha} h_{\alpha\beta} \mathbf{J}_{\alpha\beta} \end{aligned} \quad (5.61)$$

where $h_{\beta} = \sum_{\alpha} h_{\alpha\beta} Y_{\alpha\beta}$ is the mixture enthalpy of phase β . Thus, the total heat flux can be expressed as the sum of conductive, convective and diffusive contributions,

$$\mathbf{q} = -\lambda_T \nabla T + \sum_{\beta} \rho_{\beta} \mathbf{v}_{\beta} h_{\beta} + \sum_{\beta} \sum_{\alpha} h_{\alpha\beta} \mathbf{J}_{\alpha\beta} \quad (5.62)$$

5.12.2. Porous Flow Systems

To facilitate various flavors of single phase and multiphase flow in Aria, the porous flow system model was created to manage expression creation. In addition to the single phase model (sections 5.12.2.1 and 5.12.2.2), there are several others available including: mixed single phase, CO₂-salt-brine (section 5.12.2.6), two-phase-immiscible (sections 5.12.2.3 and 5.12.2.4), air-water (section 5.12.2.5), and organic-material-decomposition (section 5.12.2.7). The basic purpose of the porous flow system model is to create the necessary expressions for each system. There are examples of each flow system in the regression tests, which are the best place to start when developing an input for a similar system. The input syntax for a porous flow system is given in section 4.1 in addition to the required parameters for each porous flow system..

5.12.2.1. Single Phase, Single Component, Isothermal Flow

The simplest possible case is for a single phase flow ($N_\beta = 1, S = 1$) with a single component ($N_\alpha = 1, Y = 1$) at a fixed temperature. This is the single phase porous flow system. For a single component flow, there is no diffusive mass flux so $\mathbf{J} = \mathbf{0}$ and $\mathbf{F} = \mathbf{f}$ where

$$\mathbf{F} = \mathbf{f} = \rho \mathbf{v} = -\frac{\rho \kappa_r}{\mu} \mathbf{K} \cdot (\nabla P + \rho \mathbf{g}) \quad (5.63)$$

In this case, the mass balance equation is all that is needed to solve for the unknown pressure field P .

$$\frac{\partial d}{\partial t} + \nabla \cdot \mathbf{f} = Q \quad (5.64)$$

Since the density is most likely a function of temperature, the constant uniform temperature will have to be specified. Finally, in this special case, (5.50) reduces to $d = \phi \rho$.

5.12.2.2. Single Phase, Single Component, Non-isothermal Flow

Building on the simple case developed in section 5.12.2.1, the next step is to accommodate a non-isothermal flow. Here, we still have a single phase flow ($N_\beta = 1, S = 1$) with a single component ($N_\alpha = 1, Y = 1$). For a single component flow, there is no diffusive mass flux so $\mathbf{J} = \mathbf{0}$ and $\mathbf{F} = \mathbf{f}$ where

$$\mathbf{F} = \mathbf{f} = \rho \mathbf{v} = -\frac{\rho \kappa_r}{\mu} \mathbf{K} \cdot (\nabla P + \rho \mathbf{g}) \quad (5.65)$$

Again, the mass balance equation is all that is needed to solve for the unknown pressure field P .

$$\frac{\partial d}{\partial t} + \nabla \cdot \mathbf{f} = Q \quad (5.66)$$

Again, in this special case, (5.50) reduces to $d = \phi \rho$.

In order to solve for the unknown temperature, T , we solve an energy transport equation in the enthalpy form as described in section 5.12.1.4. Here, the energy flux in equation (5.60) reduces to

$$\mathbf{q} = -\lambda_T \nabla T + \rho \mathbf{v} h \quad (5.67)$$

where h is the pure component enthalpy which may be a function of P and T .

5.12.2.3. Two-Phase Immiscible

In this section, we define a formulation for two-phase flow of immiscible fluids, that is, without mass transfer between the phases. Common examples include oil/water, under pressure and temperature conditions where phase transitions are negligible, and systems involving non-aqueous phase liquids (NAPL) occurring in subsurface contamination by organic liquids, e.g., solvents, fuels, oils. If we disallow partitioning of components across phases, then we get the following system of mass balance equations for a wetting and non-wetting phase,

$$\frac{\partial}{\partial t}(\rho_w \phi(1 - S_n)) = \nabla \cdot \left(\rho_w \frac{k_{rw}}{\mu_w} \mathbf{K} \cdot (\nabla p - \rho_w \mathbf{g}) \right) + Q_w \quad (5.68)$$

$$\frac{\partial}{\partial t}(\rho_n \phi S_n) = \nabla \cdot \left(\rho_n \frac{k_{rn}}{\mu_n} \mathbf{K} \cdot (\nabla p + \nabla p_c - \rho_n \mathbf{g}) \right) + Q_n \quad (5.69)$$

In these equations, the subscript w represents wetting phase properties and the subscript n nonwetting phase properties. We have also incorporated the Darcy flux terms, including pressure and gravitational forces, as well as capillary pressure:

$$p_c = p_n - p_w \quad (5.70)$$

The symbol p in the equations is used in place of wetting phase pressure, p_w . Also, the pore space is assumed saturated with fluids,

$$S_w + S_n = 1 \quad (5.71)$$

This constraint has been incorporated in the wetting phase mass balance. In addition to the density models described in the previous section, models for density and viscosity can be specified as constant, polynomial with respect to other primary or secondary variables, or by tabular functions, or a user-defined plug-in.

Both the capillary pressure and relative permeability are functions of phase saturations. Either of these can be specified by the user in a tabular form, as a function of either phase saturation. A plug-in can also be written by the user for either of these functions. Several commonly used functions are built-in to the code.

5.12.2.4. Pressure-pressure Formulation for Two-phase Immiscible

The $P_w - S_n$ formulation is generally known to have superior numerical behavior for $S_w \rightarrow 0$, however, the capillary pressure in heterogeneous media creates a problem for a vertex-centered (e.g. FEM) numerical scheme. In FEM, because a node straddles a material interface, which separates two materials with different texture and therefore different wetting properties, the capillary pressure is continuous across the interface, but the saturation is not. So, a (P_w, S_n) formulation in FEM would require dealing with discontinuous DOF for S_n . One alternative is to instead solve for two pressures. Two pairs of pressure-based DOFs available in Aria include (P_w, P_c) and (P_w, P_n) . (Note that in single phase regions, where $S_w = 0$ or 1, then P_w or P_n are undefined. The formulation should work for the thermal battery problem so long as $S_w > 0$.)

The following system of mass balance equations for a wetting and non-wetting phase describes an immiscible flow,

$$\frac{\partial}{\partial t}(\rho_w \phi S_w) = \nabla \cdot \left(\rho_w \frac{k_{rw}}{\mu_w} \mathbf{K} \cdot (\nabla P_w - \rho_w \mathbf{g}) \right) + Q_w \quad (5.72)$$

$$\frac{\partial}{\partial t}(\rho_n \phi S_n) = \nabla \cdot \left(\rho_n \frac{k_{rn}}{\mu_n} \mathbf{K} \cdot (\nabla P_w + \nabla P_c - \rho_n \mathbf{g}) \right) + Q_n \quad (5.73)$$

In these equations, the subscript w represents wetting phase properties and the subscript n non-wetting phase properties. We have also incorporated the Darcy flux terms, including pressure and gravitational forces, as well as capillary pressure:

$$p_c = p_n - p_w \quad (5.74)$$

Also, the pore space is assumed saturated with fluids,

$$S_w + S_n = 1 \quad (5.75)$$

The current implementation in Aria uses a van Genuchten function to model the relationship between the capillary pressure and the saturation. This relationship is inverted for saturation given the capillary pressure in the pressure-pressure formulation.

5.12.2.5. Two-phase Air-Water

This model describes the nonisothermal two-component, two-phase transport of water and air in a porous medium. The air is treated as a non-condensable gas, but it can dissolve in the liquid phase. The water can exist as water vapor or liquid. The model allows the fluids to partition between the two phases, depending on pressure and temperature conditions. Two single phase states (all liquid or all gas) and one two-phase state are allowed.

The component mass balance equations describing two-phase transport of water, air and energy are:

$$\frac{\partial}{\partial t}(\phi(S_l Y_{wl} \rho_l + S_g Y_{wg} \rho_g)) + \nabla \cdot (Y_{wl} \rho_l \mathbf{v}_l + Y_{wg} \rho_g \mathbf{v}_g + \mathbf{J}_{wg}) + Q_w = 0 \quad (5.76)$$

$$\frac{\partial}{\partial t}(\phi(S_l Y_{al} \rho_l + S_g Y_{ag} \rho_g)) + \nabla \cdot (Y_{al} \rho_l \mathbf{v}_l + Y_{ag} \rho_g \mathbf{v}_g + \mathbf{J}_{ag}) + Q_a = 0 \quad (5.77)$$

$$\frac{\partial}{\partial t} [(1 - \phi) \rho_s e_s + \phi(\rho_l S_l e_l + \rho_g S_g e_g)] + \nabla \cdot (-\lambda_T \nabla T + \rho_l \mathbf{v}_l h_l + \rho_g \mathbf{v}_g h_g + h_{wg} \mathbf{J}_{wg} + h_{ag} \mathbf{J}_{ag}) + Q_e = 0 \quad (5.78)$$

where

$$\mathbf{J}_{ag} = -\rho_g D_{wa} \nabla Y_{ag} \quad (5.79)$$

is the gas-phase binary diffusion flux for water vapor through air. In these equations, subscript l refers to the liquid phase and g to the gas phase. In addition to previously defined variables: $Y_{\alpha\beta}$ is the mass fraction of component α (w for water, a for air) in phase β , S_β is the saturation of phase β , ρ_β is the phase density, e_β is the internal energy of phase β , λ_T is the effective thermal heat conduction, h_β is the enthalpy of phase β and $h_{\alpha\beta}$ is the component enthalpy in the gas phase.

The liquid and gas phase Darcy velocities are

$$\mathbf{v}_l = -\frac{k_{rl}}{\mu_l} \mathbf{K} \cdot (\nabla P_l + \rho_l \mathbf{g}) \quad (5.80)$$

$$\mathbf{v}_g = -\frac{k_{rg}}{\mu_g} \mathbf{K} \cdot (\nabla P_g + \rho_g \mathbf{g}) \quad (5.81)$$

In addition, the following constraints hold:

$$S_l + S_g = 1 ; \quad Y_{w\beta} + Y_{a\beta} = 1 , \text{ for } \beta = l \text{ or } g \quad (5.82)$$

5.12.2.6. CO₂-salt-brine

The CO₂-salt-brine system is intended to model the interaction of CO₂ gas, solid salt, and liquid brine. In this system there are three mass balance equations that must be solved for the saturations of each. This formulation describes a 3-component 2-phase flow for the water-CO₂-NaCl system. The two phases are brine, denoted by subscript w, a liquid phase of water with salt and CO₂ dissolved in it, and “gas” denoted by subscript g, a CO₂-rich phase, with some water dissolved in it, but no salt. The formulation also deals with precipitation of salt from the liquid phase.

To deal with the precipitation of NaCl from the liquid to form solid salt, the fluid system is treated as a three-phase system, with two flowing phases composed of the brine and CO₂ phases, and one non-flowing solid phase, which is the solid salt precipitate. Obviously, the formulation holds for other chloride salts, e.g. CaCl, KCl.

$$\frac{\partial}{\partial t} \phi(S_w \rho_w x_w + S_g \rho_g y_w) + \nabla \cdot (\rho_w x_w \mathbf{v}_w + \rho_g y_w \mathbf{v}_g + \mathbf{J}_w^{H_2O} + \mathbf{J}_g^{H_2O}) = Q^{H_2O} \quad (5.83)$$

$$\frac{\partial}{\partial t} \phi(S_w \rho_w x_{CO_2} + S_g \rho_g y_{CO_2}) + \nabla \cdot (\rho_w x_{CO_2} \mathbf{v}_w + \rho_g y_{CO_2} \mathbf{v}_g + \mathbf{J}_w^{CO_2} + \mathbf{J}_g^{CO_2}) = Q^{CO_2} \quad (5.84)$$

$$\frac{\partial}{\partial t} \phi(S_w \rho_w x_{NaCl} + S_g \rho_s) + \nabla \cdot (\rho_w x_{NaCl} \mathbf{v}_w + \mathbf{J}_w^{NaCl}) = Q^{NaCl} \quad (5.85)$$

In the equations above, we have used the following nomenclature, S_s is the saturation of solid salt precipitate, S_w is the brine phase saturation, S_g is the CO₂-rich phase saturation, x_w is the mass fraction of water in the brine phase, x_{CO_2} is the mass fraction of CO₂ in the brine phase, x_{NaCl} is the mass fraction of salt dissolved in the brine phase, y_{CO_2} is the mass fraction of CO₂ in the CO₂-rich (“gas”) phase, y_w is the mass fraction of water in the gas phase, $\rho_s(T, p)$ is the density of solid precipitate, and $\mathbf{J}_\beta^\alpha$ is the diffusion flux of component α in phase β which can also include dispersion. The subscript ‘w’ refers to the brine phase, ‘g’ refers to the CO₂ phase and ‘s’ refers to the solid salt phase.

This model treats all the separate-phase CO₂ as a single CO₂-rich phase. The phase diagram for the CO₂-H₂O system displays a saturation line where liquid water, liquid CO₂ and a vapor phase can co-exist. The saturated water vapor pressure on this line is small, so the vapor phase is mostly CO₂.

$$S_w + S_g + S_s = 1 ; \quad x_w + x_{CO_2} + x_{NaCl} = 1 ; \quad y_w + y_{CO_2} + y_{NaCl} = 1 \quad (5.86)$$

We also have the constraint on the over-all composition, which can replace either of the last two constraints above,

$$z_w + z_{CO2} + z_{NaCl} = 1 \quad (5.87)$$

To solve for the pressure, in all compositional situations, we can solve a pressure equation, obtained by summing all component balances. Since the resulting equation is not independent, it replaces one of the three mass balance equations presented earlier.

$$\frac{\partial}{\partial t} \phi (S_w \rho_w + S_g \rho_g + S_s \rho_s) + \nabla \cdot (\rho_w \mathbf{v}_w + \rho_g \mathbf{v}_g) + Q^{H2O} + Q^{CO2} + Q^{NaCl} = 0 \quad (5.88)$$

In the numerical implementation, this equation could be obtained after all BCs have been applied to the discrete equations, by summing the three residual equations together.

Recall, the primary variables for this system are defined as a set of variables that allow one to compute all the remaining (secondary) variables appearing in the mass and energy balance equations. For this problem, the primary solution vector (assuming we will also solve an energy balance for T) is $[P, z_{CO2}, \rho_{NaCl}, T]$, where

$$z_{CO2} = \frac{S_w \rho_w x_{CO2} + S_g \rho_g y_{CO2}}{S_w \rho_w + S_g \rho_g} = (1 - \nu) x_{CO2} + \nu y_{CO2} \quad (5.89)$$

is the over-all mass fraction of CO₂ in the flowing phases. We have introduced the fraction of gas, defined as,

$$\nu = \frac{\rho_g S_g}{\rho_w S_w + \rho_g S_g} \quad (5.90)$$

Similarly, the overall density of salt is defined by,

$$\rho_{NaCl} = \rho_w S_w x_{NaCl} + \rho_s S_s = (1 - \nu) x_{NaCl} F + \rho_s S_s \quad (5.91)$$

where we have introduced, for later convenience, the following mass density,

$$F = \rho_w S_w + \rho_g S_g \quad (5.92)$$

Note that the accumulation term in the CO₂ balance can be written as $\phi F z_{CO2}$.

In this formulation, P is solved for from the pressure equation, z_{CO2} from the CO₂ mass balance equation, ρ_{NaCl} from the NaCl mass balance and T from the energy balance equation. We assume the phase equilibrium for this system is done ahead of time.

The thermodynamics algorithm for this system is still in development and has not yet been completed.

5.12.2.7. Organic Material Decomposition (OMD)

Organic material decomposition (OMD) models currently define two-phase (solid and gas) problems in which the solid (or porous) species react to produce additional gas species that pressurize a system and volumetric heat transfer between phases. The notation used above does not include the porous solid as a phase, but since for OMD we are solving equations for the solid phase including reactions, we set $N_\beta = 2$, with it being understood that one of these phases is the solid phase. OMD problems will extend to include a liquid phase in the future. The OMD equations described here are based on the combustion model [11]. Further details about coupling boundary conditions between fluid-only and porous regions are provided in section 9.5. There are separate mass balance equations for the solid phase and gas phase. The solid phase mass balance equation is used to solve for solid phase density:

$$\underbrace{\frac{\partial \bar{\rho}}{\partial t}}_{MASS} = \underbrace{-\dot{\omega}_{f,g}'''}_{SRC} \quad (5.93)$$

where $\bar{\rho}$ is the solid phase density and $\dot{\omega}_{f,g}'''$ is the rate of formation of gases due to heterogenous reaction kinetics. The mass balance equation for the gas phase solves for the pressure (from the gas phase density via the ideal gas law),

$$\underbrace{\frac{\partial(\psi \rho_g)}{\partial t}}_{MASS} + \underbrace{\frac{\partial(\rho_g u_{j,g})}{\partial x_j}}_{ADV} = \underbrace{\dot{\omega}_{f,g}'''}_{SRC} \quad (5.94)$$

where ρ_g is the gas-phase density and ψ is the mixture-averaged solid-phase porosity. The porosity is the void space not taken up by the volume fractions of each solid phase species, typically defined as a function of the volume fractions of each solid species,

$$\psi = 1 - \sum_{\alpha} X_{\alpha} \quad (5.95)$$

The volume fraction of each solid species is calculated as

$$X_{\alpha} = \frac{\bar{\rho} Y_{\alpha}}{\rho_{s0,\alpha}}, \quad (5.96)$$

where $\rho_{s0,\alpha}$ is the solid (non-porous) density for each species. In equation 5.94, $u_{j,g}$ is the gas-phase velocity and gets computed from Darcy's approximation as

$$\psi v_{j,g} = u_{j,g} = -\frac{\bar{K}_{ij}}{\mu_g} \left(\frac{\partial p_g}{\partial x_i} + \rho_g g_i \right), \quad (5.97)$$

where $\bar{K}_{ij}$ is the mixture-averaged solid-phase permeability tensor defined as the normalized volume average of the solid phase species' permeabilities,

$$\bar{K}_{ij} = \frac{\sum_{\alpha} X_{\alpha} K_{\alpha j}}{\sum_{\alpha} X_{\alpha}} \quad (5.98)$$

where

$$K_{\alpha j} = K_{ref} \left(\frac{T}{T_{ref}} \right)^n \delta_{\alpha j} \quad (5.99)$$

The intrinsic permeability is the product of the intrinsic permeability scaling and the intrinsic permeability. The reason it is separated in this way is that scalar models have access to many generic functions, whereas tensor entries can only be constants. A more complex function for the intrinsic permeability tensor would have to be written as a user subroutine.

In equation 5.97 the parameter μ_g is the gas-phase viscosity and g_j is the gravity vector. The ideal gas law gets used for the gas density in the pressure form of equation 5.94

$$\rho_g = \frac{P\bar{M}}{RT_g}. \quad (5.100)$$

Therefore the actual equation for pressure being solved here is

$$\frac{\partial}{\partial t} \left(\frac{p_g \bar{M} \psi}{RT_g} \right) + \frac{\partial}{\partial x_j} \left[\frac{p_g \bar{M}}{RT_g} \frac{K_{\alpha j}}{\mu_g} \left(\frac{\partial p_g}{\partial x_j} + \frac{p_g \bar{M}}{RT_g} g_j \right) \right] = 0. \quad (5.101)$$

where $\bar{M}$ is the mass averaged molecular weight,

$$\bar{M} = \sum_{\alpha} Y_{\alpha} M_{\alpha}, \quad (5.102)$$

where Y_{α} are the gas phase mass fractions and M_{α} are the molecular weights of the gaseous species.

The solid phase species equations solve for the solid phase mass fractions, $Y_{\alpha,s}$, of species α

$$\underbrace{\frac{\partial(\bar{\rho}Y_{\alpha})}{\partial t}}_{MASS} = \underbrace{(\dot{\omega}_{f,\alpha}''' - \dot{\omega}_{d,\alpha}''')}_{SRC}. \quad (5.103)$$

where $\dot{\omega}_{f,\alpha}'''$ is the formation rate of species α and $\dot{\omega}_{d,\alpha}'''$ is its destruction rate. The gas-phase species equations solve for the gas-phase mass fraction $Y_{\alpha,g}$ of species α

$$\underbrace{\frac{\partial(\psi \rho_g Y_{\alpha,g})}{\partial t}}_{MASS} + \underbrace{\frac{\partial(\rho_g u_{j,g} Y_{\alpha,g})}{\partial x_j}}_{ADV} + \underbrace{\frac{\partial q_{\alpha j}^{Y,g}}{\partial x_j}}_{DIFF} = \underbrace{\dot{\omega}_{\alpha,g}}_{SRC} \quad (5.104)$$

No source terms are included in this model. The gas-phase species diffusion flux vector $q_{\alpha j}^{Y,g}$ is modeled as

$$q_{\alpha j}^{Y,g} = -\psi \rho_g D_{\alpha,g} \frac{\partial Y_{\alpha,g}}{\partial x_j}, \quad (5.105)$$

where $D_{\alpha,g}$ is the gas-phase mass diffusivity for species α .

Enthalpy equations are used to solve for temperature, and OMD type problems allow for different temperature fields in the gas and solid phases, so these are described separately here.

The solid phase enthalpy equation for the solid phase temperature $\bar{T}$ is given by

$$\underbrace{\frac{\partial(\bar{\rho}c_p \bar{T})}{\partial t}}_{MASS} = \underbrace{-\frac{\partial q_j^h}{\partial x_j}}_{DIFF} + \underbrace{h_{cv}(T_g - \bar{T})}_{SRC} \quad (5.106)$$

There is no advection term here since the solid phase is stationary. The solid phase energy diffusive flux vector $q_j^{h,g}$ is given by Fourier's law,

$$q_j^{h,g} = -\kappa \frac{\partial \bar{T}}{\partial x_j}, \quad (5.107)$$

where κ is the thermal conductivity.

The gas-phase enthalpy equation within a porous region, to be solved for the gas-phase enthalpy (and corresponding temperature) $h_g = c_p T_g$, is

$$\underbrace{\frac{\partial(\psi \rho_g h_g)}{\partial t}}_{MASS} + \underbrace{\frac{\partial(\rho_g u_{j,g} h_g)}{\partial x_j}}_{ADV} = -\underbrace{\frac{\partial q_j^{h,g}}{\partial x_j}}_{DIFF} + \underbrace{\left(\frac{\partial \psi p_g}{\partial t} \right)}_{SRC} + \underbrace{h_{cv} (\bar{T} - T_g)}_{SRC} \quad (5.108)$$

where h_g is the mixture-averaged gas-phase enthalpy, h_{cv} is the volumetric heat transfer coefficient which gets set outside of the solid/gas phases of the material definition, $\bar{T}$ is the porous solid-phase temperature and T_g is the gas phase temperature. The gas-phase energy diffusive flux vector $q_j^{h,g}$ is modeled as

$$q_j^{h,g} = -\psi \rho_g D_g \frac{\partial h_g}{\partial x_j}, \quad (5.109)$$

where D_g is the mixture-averaged gas-phase mass diffusivity. The compressible pressure source term for the enthalpy equation has been derived in the context of Darcy flow. The volumetric transfer source accounts for the heat transfer between the solid and gas phases.

5.12.3. Porosity Models

There are several models for porosity in the porous flow capabilities in Aria. The following list provides a brief description for each.

5.12.3.1. Mesh Deforming

In the mesh (or solid) deforming porosity model, the expression for the porosity is given as

$$\phi = 1.0 - \frac{b(1.0 - \phi_0)}{\det(\mathbf{F})} \quad (5.110)$$

where ϕ_0 is the initial porosity, b is the Biot coefficient, and $\mathbf{F}$ is the mesh deformation gradient.

5.12.3.2. Rock Compressible

For the Rock Compressible porosity model, the porosity is given as

$$\phi = \phi_0 (1.0 + Cr(p - p_{ref})) \quad (5.111)$$

where again, ϕ_0 is the initial porosity, Cr is a rock compressibility coefficient, p is the pore pressure, and p_{ref} is a reference pore pressure defined in the input parameters.

5.12.3.3. Coussy

For the Coussy porosity model, the expression for porosity is

$$\phi = \phi_0 + \frac{1}{M}(p - p_{ref}) + b\epsilon_u \quad (5.112)$$

where M represents the formation compressibility, $\epsilon_u = \text{div}(\mathbf{u})$ is the divergence of the solid deformation vector, b is the Biot coefficient, p is the pore pressure, and p_{ref} is a reference pore pressure.

5.13. BRINKMAN MOMENTUM

The Brinkman (Brinkman-Forchheimer) momentum equation is a porous media specialization of the fluid momentum equation 5.19 given by

$$\frac{\partial}{\partial t} \left(\frac{\rho}{\varphi} \mathbf{v} \right) + \frac{\rho}{\varphi^2} \mathbf{v} \cdot \nabla \mathbf{v} - \nabla \cdot \mathbf{T} + \left[\frac{\rho \hat{c}}{\sqrt{k}} \|\mathbf{v}\| + \frac{\mu}{k} \right] \mathbf{v} - \mathbf{g} = \mathbf{0} \quad (5.113)$$

where φ is the matrix porosity, $\mathbf{T}$ is the fluid stress tensor $\mathbf{g}$ is a body force and μ is termed the flowing liquid viscosity. The bracketed terms are often referred to as the Forchheimer or inertial flow contribution and the Darcy term respectively. In the limit of low velocities the equation reduces to a balance of pressure and a scaled velocity and Darcy's law for a single component fluid is recovered [12]. This equation is most useful in cases where a clear fluid domain is bounded by a porous media. In most applications of this equation the hydrostatic contribution will be negligible but is retained here for completeness. We construct the G/FEM residual form of 5.113 by contracting with the unit coordinate vector in the k -direction, $\mathbf{e}_k$, multiplying by the weight function ϕ^i and integrating over the volume. Using the vector identity $(\nabla \cdot \mathbf{T}) \cdot \mathbf{e}_k \phi^i = \nabla \cdot (\mathbf{T} \cdot \mathbf{e}_k \phi^i) - \mathbf{T}^t : \nabla (\mathbf{e}_k \phi^i)$ and integrating by parts gives

$$R_{m,k}^i = \int_V \left[\frac{\partial}{\partial t} \left(\frac{\rho}{\varphi} \mathbf{v} \right) + \frac{\rho}{\varphi^2} \mathbf{v} \cdot \nabla \mathbf{v} + \left[\frac{\rho \hat{c}}{\sqrt{k}} \|\mathbf{v}\| + \frac{\mu}{k} \right] \mathbf{v} - \mathbf{g} \right] \cdot \mathbf{e}_k \phi^i + \mathbf{T}^t : \nabla (\mathbf{e}_k \phi^i) dV - \int_S \mathbf{n} \cdot \mathbf{T} \cdot \mathbf{e}_k \phi^i dS = 0 \quad (5.114)$$

Here we note that the viscosity associated with the stress tensor $\mathbf{T}$ is not the viscosity of the fluid but instead a so-called Brinkman viscosity μ_B . In Aria, each term in 5.114 is specified separately as identified in equation 5.15.

$$R_{m,k}^i = \underbrace{\int_V \frac{\partial}{\partial t} \left(\frac{\rho}{\varphi} \mathbf{v} \right) \cdot \mathbf{e}_k \phi^i dV}_{\text{MASS}} + \underbrace{\int_V \frac{\rho}{\varphi^2} \mathbf{v} \cdot \nabla \mathbf{v} \cdot \mathbf{e}_k \phi^i dV}_{\text{ADV}} - \underbrace{\int_V \mathbf{g} - \left[\frac{\rho \hat{c}}{\sqrt{k}} \|\mathbf{v}\| + \frac{\mu}{k} \right] \mathbf{v} \cdot \mathbf{e}_k \phi^i dV}_{\text{SRC}} + \underbrace{\int_V \mathbf{T}^t : \nabla (\mathbf{e}_k \phi^i) dV}_{\text{DIFF}} - \int_S \mathbf{n} \cdot \mathbf{T} \cdot \mathbf{e}_k \phi^i dS = 0 \quad (5.115)$$

5.14. LUBRICATION EQUATION

Reynolds' lubrication equation is a reduced-order model for fluid flow in thin, confined regions. This equation is commonly used for manufacturing applications, such as bearings, coating processes, and nanomanufacturing processes. Lubricating flows also occur in high-speed machinery, such as pumps. It is only defined for reduced-order elements, such as shells.

The lubrication equation implemented here is given by

$$-\frac{\partial h}{\partial t} + \nabla \cdot \mathbf{q} + \mathbf{B}_u \cdot \nabla h_u - \mathbf{B}_l \cdot \nabla h_l = 0 \quad (5.116)$$

where $\mathbf{q}$ is the lubrication flow rate, given by

$$\mathbf{q} = -\frac{h^3}{k\mu} \nabla p_{\text{lub}} + \frac{h}{2} (\mathbf{B}_u + \mathbf{B}_l). \quad (5.117)$$

In these equations, the independent variable is the lubrication pressure, p_{lub} . Other variables are the lubrication region height (thickness) h , velocity of the upper confining surface $\mathbf{B}_u$, velocity of the lower confining surface $\mathbf{B}_l$, the upper wall height h_u , the lower wall height h_l , turbulent parameter k , and viscosity μ . The lubrication height is defined as $h = h_u - h_l + \mathbf{n} \cdot \mathbf{d}$, where $\mathbf{n}$ is the shell normal vector and $\mathbf{d}$ is the mesh displacement. This equation is detailed in [13].

Using equation 5.116, the G/FEM residual form is

$$R_V^i = - \underbrace{\int_V \frac{\partial h}{\partial t} \phi^i dV}_{\text{MASS}} + \underbrace{\int_V \mathbf{q} \cdot \nabla \phi^i dV}_{\text{DIFF}} + \underbrace{\int_V (\mathbf{B}_u \cdot \nabla h_u - \mathbf{B}_l \cdot \nabla h_l) \phi^i dV}_{\text{BOUND}} + \int_S \mathbf{n} \cdot \mathbf{q} \phi^i dS = 0 \quad (5.118)$$

5.15. STRESS TENSOR PROJECTION EQUATION

A projection equation is defined as an equation where a derived quantity at the interior Gauss points is evaluated and projected to be a solution unknown at the nodal points. The stress tensor projection equation projects the momentum stresses, tau, without the pressure term, to the nodal points. Projecting the momentum stress smooths out the momentum stress tensor and allows for a dot product to be carried out on the projected field, which is needed for least squares stabilization schemes. The solution variable, τ_{ab} , is calculated from 5.119.

$$R_V^i = - \underbrace{\int_V (\tau_{ab} - \text{src\_}\tau_{ab}) \phi^i dV}_{\text{DEF}} = 0 \quad (5.119)$$

τ_{ab} is a tensor variable. For 2D problems, ab stands for XX, XY, YX, and YY. For 3D problems ab stands for XX, XY, XZ, YX, YY, YZ, ZX, ZY, and ZZ. The source term in the equation $src_{\tau_{ab}}$ refers to the momentum stress without the pressure diagonal term.

$$src_{\tau_{xx}} = 2\mu \frac{du}{dx} - \frac{2}{3}(\mu - \lambda)(\nabla \cdot \mathbf{v})$$

$$src_{\tau_{yy}} = 2\mu \frac{dv}{dy} - \frac{2}{3}(\mu - \lambda)(\nabla \cdot \mathbf{v})$$

$$src_{\tau_{zz}} = 2\mu \frac{dw}{dz} - \frac{2}{3}(\mu - \lambda)(\nabla \cdot \mathbf{v})$$

$$src_{\tau_{xy}} = src_{\tau_{yx}} = \mu \left(\frac{du}{dy} + \frac{dv}{dx} \right)$$

$$src_{\tau_{xz}} = src_{\tau_{zx}} = \mu \left(\frac{du}{dz} + \frac{dw}{dx} \right)$$

$$src_{\tau_{yz}} = src_{\tau_{zy}} = \mu \left(\frac{dv}{dz} + \frac{dw}{dy} \right)$$

5.16. POTENTIAL PROJECTION EQUATION

This equation is used to create a potential field which minimizes difference between the potential, ψ , and the potential source, $\mathbf{S}$, in the least-squares sense

$$(\nabla \psi - \mathbf{S})^2 = 0. \quad (5.120)$$

This equation was derived to create a hydrostatic potential field, so the most common usage is where $\mathbf{S} = \rho_s \mathbf{g}$.

Equation 5.120 is integrated by parts, resulting in the residual

$$R^i = \underbrace{\int_V \nabla \psi \cdot \nabla (\mathbf{e}_k \phi^i) dV}_{\text{DEF}} - \underbrace{\int_V \mathbf{S} \cdot \nabla (\mathbf{e}_k \phi^i) dV}_{\text{SRC}} \quad (5.121)$$

5.17. NOTES ON SOLID MECHANICS

Some of the standard references on solid mechanics include [14], [15], [5] and [6]. As is often the case, the mathematical notion used through-out these texts is different in many cases and this is often a source of confusion. Here, we'll lay out some basic definitions in our notation and, when possible, give the notation used in these other texts.

In what follows, $\mathbf{x}$ is the position vector of a material particle in the *deformed* or *current* spatial configuration and $\mathbf{X}$ is the position vector of a material particle in the *undeformed* or *initial* or *reference* configuration. The displacement vector $\mathbf{d}$ is the difference between these two states¹ viz. $\mathbf{x} = \mathbf{X} + \mathbf{d}$.

We will make extensive use of the gradients of these fields and so it is important to distinguish between gradients in the reference configuration and the current configuration. Gradients in the current configuration are denoted ∇ in Gibbs notation or $\partial / \partial x_i$ in index notation. Gradients in the reference configuration are denoted ∇_X in Gibbs notation or $\partial / \partial X_i$ in index notation².

Next, we define the deformation gradient $\mathbf{F}$

$$\mathbf{F} \equiv \nabla_X \mathbf{x}^t \quad (5.122)$$

$$= \nabla_X \mathbf{X}^t + \nabla_X \mathbf{d}^t \quad (5.123)$$

$$= \mathbf{I} + \nabla_X \mathbf{d}^t \quad (5.124)$$

where the superscript t denotes the transpose operator³. The inverse deformation gradient⁴, $\mathbf{F}^{-1}$, is also useful and can be computed as

$$\mathbf{F}^{-1} \equiv \nabla \mathbf{X}^t \quad (5.125)$$

$$= \nabla \mathbf{x}^t - \nabla \mathbf{d}^t \quad (5.126)$$

$$= \mathbf{I} - \nabla \mathbf{d}^t. \quad (5.127)$$

The determinants of $\mathbf{F}$ and $\mathbf{F}^{-1}$ are denoted J and J^{-1} respectively and are often used in transformations between different stress definitions⁵.

It's worth noting at this point that in Aria both gradient operators, ∇ and ∇_X , are available as Expression objects as are $\mathbf{F}$, $\mathbf{F}^{-1}$, J and J^{-1} .

The Green or Green-Lagrange strain tensor $\mathbf{E}$ is defined⁶ as

$$\mathbf{E} \equiv \frac{1}{2} (\mathbf{F}^t \cdot \mathbf{F} - \mathbf{I}) \quad (5.128)$$

$$= \frac{1}{2} (\nabla_X \mathbf{d} + \nabla_X \mathbf{d}^t + \nabla_X \mathbf{d} \cdot \nabla_X \mathbf{d}^t). \quad (5.129)$$

¹ $\mathbf{d}$ is denoted $\mathbf{u}$ in [14], [15], [5], and [6].

²In [6] ∇_X is denoted ∇_0 .

³In [15] this is called the *conjugate dyadic* and is denoted with a subscript c . In [14] the quantity $\nabla_X \mathbf{x}^t$ is denoted $\mathbf{x} \overleftarrow{\nabla}_X$ where the arrow over the gradient operator denotes the direction of the operation.

⁴In [15] $\mathbf{F}^{-1}$ is denoted $\mathbf{H}$.

⁵Sometimes J is expressed as a ratio of the densities between the reference and current configurations, ρ_0 / ρ .

⁶In [15] $\mathbf{E}$ is denoted $\mathbf{L}_G$ and is called the *Lagrangian strain*.

The Green strain is a strain measure in the reference configuration and is suitable for large deformations and large rotations. The analogous Eulerian (or Almansi's) strain tensor $\mathbf{E}^*$ is defined⁷ as

$$\mathbf{E}^* \equiv \frac{1}{2} (\mathbf{I} - \mathbf{F}^{-t} \cdot \mathbf{F}^{-1}) \quad (5.130)$$

$$= \frac{1}{2} (\nabla \mathbf{d} + \nabla \mathbf{d}^t - \nabla \mathbf{d} \cdot \nabla \mathbf{d}^t) . \quad (5.131)$$

The Eulerian strain is also a suitable strain measure for large deformations and rotations but is defined in the current configuration.

The Cauchy stress, $\boldsymbol{\sigma}$, is a stress measure defined in the current configuration as

$$\boldsymbol{\sigma} = \lambda E_{kk} \mathbf{I} + 2\mu \mathbf{E} \quad (5.132)$$

where E_{kk} denotes the trace of $\mathbf{E}$ and λ and μ are the Lamé coefficients. This constitutive equation may also be augmented with some initial residual stress or a thermal stress,

$$\boldsymbol{\sigma} = \lambda E_{kk} \mathbf{I} + 2\mu \mathbf{E} - \beta (T - T_o) \mathbf{I} + \boldsymbol{\sigma}_r. \quad (5.133)$$

Here β is related to the coefficient of thermal expansion, T is the temperature, T_o is the reference temperature of the solid and $\boldsymbol{\sigma}_r$ is the residual stress.

For large deformations and large rotations Aria uses the second Piola-Kirchhoff stress which is defined in the reference configuration and is related to the Cauchy stress as

$$\mathbf{S} = J \mathbf{F}^{-1} \cdot \boldsymbol{\sigma} \cdot \mathbf{F}^{-t}. \quad (5.134)$$

The reverse transformation is readily given by

$$\boldsymbol{\sigma} = J^{-1} \mathbf{F} \cdot \mathbf{S} \cdot \mathbf{F}^t. \quad (5.135)$$

Mathematically, the Cauchy stress $\boldsymbol{\sigma}$ is most conveniently expressed in terms of the Lamé coefficients λ , μ and β . In practice, however, it is more common to measure and report a different but related set of parameters: the Young's modulus E , the Poisson's ratio ν and the coefficient of thermal expansion α . (Note, the shear modulus $G = \mu$.) The relationship between these two sets of parameters is

$$2\mu = \frac{E}{(1 + \nu)} \quad (5.136)$$

$$\lambda = \frac{\nu E}{(1 + \nu)(1 - 2\nu)} = 2\mu \frac{\nu}{(1 - 2\nu)} \quad (5.137)$$

$$\beta = \frac{\alpha E}{(1 - 2\nu)} = \alpha (3\lambda + 2\mu) \quad (5.138)$$

In Aria, there are separate `Expression_Names` for the Cauchy stress and the second Piola-Kirchhoff stress expressions. In the input files, users provide their choice of constitutive relations in the material model specification, e.g.,

⁷In [15] $\mathbf{E}^*$ is denoted $\mathbf{E}_A$.

```

Begin Aria Material The_Material
  Density      = Constant rho = 2.33e-15
  Mesh Lambda = Constant lambda = 52810.30445
  Mesh Two Mu  = Constant two_mu = 134426.2295
  Mesh Stress  = Nonlinear_Elastic Reference_Frame=Moving
  Mesh Stress  = Residual Sx=-11 Sy=-11
  Mesh Stress  = Isothermal T=800 T_ref=450
End

```

In this Example, there will be three contributions to the stress in the mesh stress: nonlinear elasticity, a planar residual stress and an isotropic linear thermal stress. Internally, Aria contains a separate expression for transforming these Cauchy stresses into Piola-Kirchhoff stresses, viz.

$$\mathbf{S} = J\mathbf{F}^{-1} \cdot \left(\sum_i \boldsymbol{\sigma}_i \right) \cdot \mathbf{F}^{-t}. \quad (5.139)$$

Note that second Piola-Kirchhoff stresses are not specified in the input file – only Cauchy stresses are. Aria automatically creates an Expression to compute the transform in (5.139).

5.18. UNITS AND UNIT CONVERSIONS

Aria make no a priori specification concerning the units of each term. However, as with all engineering codes, errors associated with unit conversions are quite easy to do. In some situations, with just one or two driving forces playing a role in a calculation, nondimensionalization of the equations can lead to a simplification of the problem statement (and to increased solution robustness due to proper scaling of the terms in the equations). However, in complicated cases with multiple competing forces and rate constants, sticking to unit systems to specify all quantities frequently leads to less errors in engineering calculations, and also leads to the ability to incorporate third party library packages for specification of source terms and transport properties which necessarily presume to employ units systems in their application programming interfaces (API). The next section discusses the SI units system, and its application for reacting flow and electromagnetic applications.

5.18.1. SI Units

Quantity	Name	Abbreviation
length	meter (metre)	m
mass	kilogram	kg
time	second	s
electric current	ampere	A
thermodynamic temperature	kelvin	K
amount of substance	kmole	kmol
luminous intensity	candela	cd

Table 5.18-1.. Fundamental SI units.

discuss electromagnetic unit specification, e.g., Gauss's law.

Factor	Prefix	Abbreviation
10^{24}	yotta	Y
10^{21}	zetta	Z
10^{18}	exa	E
10^{15}	peta	P
10^{12}	tera	T
10^9	giga	G
10^6	mega	M
10^3	kilo	k
10^2	hecto	h
10^1	deca	da
10^{-1}	deci	d
10^{-2}	centi	c
10^{-3}	milli	m
10^{-6}	micro	μ
10^{-9}	nano	n
10^{-12}	pico	p
10^{-15}	femto	f
10^{-18}	atto	a
10^{-21}	zepto	z
10^{-24}	yocto	y

Table 5.18-2.. SI magnitude prefixes.

Quantity	Unit	Definition
Frequency	hertz	$\text{Hz} = 1/\text{s}$
Force	newton	$\text{N} = \text{m} \cdot \text{kg}/\text{s}^2$
Pressure, stress	pascal	$\text{Pa} = \text{N}/\text{m}^2 = \text{kg}/\text{m} \cdot \text{s}^2$
Energy, work, quantity of heat	joule	$\text{J} = \text{N} \cdot \text{m} = \text{m}^2 \cdot \text{kg}/\text{s}^2$
Power, radiant flux	watt	$\text{W} = \text{J}/\text{s} = \text{m}^2 \cdot \text{kg}/\text{s}^3$
Quantity of electricity, electric charge	coulomb	$\text{C} = \text{s} \cdot \text{A}$
Electric potential	volt	$\text{V} = \text{W}/\text{A} = \text{m}^2 \cdot \text{kg}/\text{s}^3 \cdot \text{A}$
Capacitance	farad	$\text{F} = \text{C}/\text{V} = \text{s}^4 \cdot \text{A}^2/\text{m}^2 \cdot \text{kg}$
Electric resistance	ohm	$\text{Omega} = \text{V}/\text{A} = \text{m}^2 \cdot \text{kg}/\text{s}^3 \cdot \text{A}^2$
Conductance	siemens	$\text{S} = \text{A}/\text{V} = \text{s}^3 \cdot \text{A}^2/\text{m}^2 \cdot \text{kg}$
Magnetic flux	weber	$\text{Wb} = \text{V} \cdot \text{s} = \text{m}^2 \cdot \text{kg}/\text{s}^2 \cdot \text{A}$
Magnetic flux density, magnetic induction	tesla	$\text{T} = \text{Wb}/\text{m}^2 = \text{kg}/\text{s}^2 \cdot \text{A}$
Inductance	henry	$\text{H} = \text{Wb}/\text{A} = \text{m}^2 \cdot \text{kg}/\text{s}^2 \cdot \text{A}^2$
Luminous flux	lumen	$\text{lm} = \text{cd} \cdot \text{sr}$
Illuminance	lux	$\text{lx} = \text{lm}/\text{m}^2 = \text{cd} \cdot \text{sr}/\text{m}^2$
Activity (ionizing radiations)	becquerel	$\text{Bq} = 1/\text{s}$
Absorbed dose	gray	$\text{Gy} = \text{J}/\text{kg} = \text{m}^2/\text{s}^2$
Dynamic viscosity	pascal second	$\text{Pa} \cdot \text{s} = \text{kg}/\text{m} \cdot \text{s}$
Moment of force	meter newton	$\text{N} \cdot \text{m} = \text{m}^2 \cdot \text{kg}/\text{s}^2$
Surface tension	newton per meter	$\text{N}/\text{m} = \text{kg}/\text{s}^2$
Heat flux density, irradiance	watt per square meter	$\text{W}/\text{m}^2 = \text{kg}/\text{s}^3$
Heat capacity, entropy	joule per kelvin	$\text{J}/\text{K} = \text{m}^2 \cdot \text{kg}/\text{s}^2 \cdot \text{K}$
Specific heat capacity, specific entropy	joule per kilogram kelvin	$\text{J}/\text{kg K} = \text{m}^2/\text{s}^2 \cdot \text{K}$
Specific energy	joule per kilogram	$\text{J}/\text{kg} = \text{m}^2/\text{s}^2$
Thermal conductivity	watt per meter kelvin	$\text{W}/\text{m} \cdot \text{K} = \text{m} \cdot \text{kg}/\text{s}^3 \cdot \text{K}$
Energy density	joule per cubic meter	$\text{J}/\text{m}^3 = \text{kg}/\text{m} \cdot \text{s}^2$
Electric field strength	volt per meter	$\text{V}/\text{m} = \text{m} \cdot \text{kg}/\text{s}^3 \cdot \text{A}$
Electric charge density	coulomb per cubic meter	$\text{C}/\text{m}^3 = \text{s} \cdot \text{A}/\text{m}^3$
Electric displacement, electric flux density	coulomb per square meter	$\text{C}/\text{m}^2 = \text{s} \cdot \text{A}/\text{m}^2$
Permittivity	farad per meter	$\text{F}/\text{m} = \text{s}^4 \cdot \text{A}^2/\text{m}^3 \cdot \text{kg}$
Permeability	henry per meter	$\text{H}/\text{m} = \text{m} \cdot \text{kg}/\text{s}^2 \cdot \text{A}^2$
Molar energy	joule per kmol	$\text{J}/\text{kmol} = \text{m}^2 \cdot \text{kg}/\text{s}^2 \cdot \text{kmol}$
Molar entropy, molar heat capacity	joule per kmol kelvin	$\text{J}/\text{kmol K} = \text{m}^2 \cdot \text{kg}/\text{s}^2 \cdot \text{K} \cdot \text{kmol}$
Exposure (ionizing radiations)	coulomb per kilogram	$\text{C}/\text{kg} = \text{s} \cdot \text{A}/\text{kg}$
Absorbed dose rate	gray per second	$\text{Gy}/\text{s} = \text{m}^2/\text{s}^3$

Table 5.18-3.. SI derived units and their definitions.

Quantity	Unit
erg	1 erg = 10^{-7} J
dyne	1 dyn = 10^{-5} N
poise	1 P = 1 dyn·s/cm ² = 0.1 Pa·s
stokes	1 St = 1 cm ² /s = 10^{-4} m ² /s
gauss	1 G = 10^{-4} T
oersted	1 Oe = (1000/(4 pi)) A/m
maxwell	1 Mx = 10^{-8} Wb
stilb	1 sb = 1 cd/cm ² = 10^4 cd/m ²
phot	1 ph = 10^4 lx

Table 5.18-4.. CGS derived units and their definitions.

5.18.2. Common Units and Conversion Factors

$$\begin{aligned}
 1 \text{ g} \cdot / \text{s}^2 &= 1 \text{ dyn} = 10^{-5} \text{ kg} \cdot \text{m} / \text{s}^2 = 10^{-5} \text{ N} \\
 1 \text{ g} \cdot / \text{s}^2 &= 7.2330 \times 10^{-5} \text{ lb}_m \cdot \text{ft} / \text{s}^2 \text{ (poundal)} \\
 1 \text{ lb}_f &= 4.4482 \text{ N} \\
 1 \text{ g} \cdot / \text{s}^2 &= 2.2481 \times 10^{-6} \text{ lb}_f
 \end{aligned}$$

Table 5.18-5.. Units and conversion factors for force.

$$\begin{aligned}
 1 \text{ bar} &= 10^5 \text{ Pa} = 10^5 \text{ N/m}^2 \\
 1 \text{ psia} &= 1 \text{ lb}_f / \text{in}^2 \\
 1 \text{ psia} &= 2.0360 \text{ in Hg at } 0^\circ \text{C} \\
 1 \text{ psia} &= 2.311 \text{ ft H}_2\text{O at } 70^\circ \text{F} \\
 1 \text{ psia} &= 51.715 \text{ mm Hg at } 0^\circ \text{C} (\rho_{\text{Hg}} = 13.5955 \text{ g/cm}^3) \\
 1 \text{ atm} &= 14.696 \text{ psia} = 1.01325 \times 10^5 \text{ N/m}^2 = 1.01325 \text{ bar} \\
 1 \text{ atm} &= 760 \text{ mm Hg at } 0^\circ \text{C} = 1.01325 \times 10^5 \text{ Pa} \\
 1 \text{ atm} &= 29.921 \text{ in Hg at } 0^\circ \text{C} \\
 1 \text{ atm} &= 33.90 \text{ ft H}_2\text{O at } 4^\circ \text{C}
 \end{aligned}$$

Table 5.18-6.. Units and conversion factors for pressure and stress.

$$\begin{aligned}
1 \text{ cp} &= 10^{-2} \text{ g/cm} \cdot \text{s} = 10^{-2} \text{ Poise} \\
1 \text{ cp} &= 2.4191 \text{ lb}_m/\text{ft} \cdot \text{h} \\
1 \text{ cp} &= 6.7197 \times 10^{-4} \text{ lb}_m/\text{ft} \cdot \text{s} \\
1 \text{ cp} &= 10^{-3} \text{ Pa} \cdot \text{s} = 10^{-3} \text{ kg/m} \cdot \text{s} = 10^{-3} \text{ N} \cdot \text{s}/\text{m}^2 \\
1 \text{ cp} &= 2.0886 \times 10^{-5} \text{ lb}_f \cdot \text{s}/\text{ft}^2 \\
1 \text{ Pa} \cdot \text{s} &= 1 \text{ N} \cdot \text{s}/\text{m}^2 = 1 \text{ kg/m} \cdot \text{s} = 1000 \text{ cp} = 0.67197 \text{ lb}_m/\text{ft} \cdot \text{s}
\end{aligned}$$

Table 5.18-7.. Units and conversion factors for viscosity.

$$\begin{aligned}
1 \text{ g/cm}^3 &= 1000 \text{ kg/m}^3 = 62.43 \text{ lb}_m/\text{ft}^3 \\
1 \text{ g/cm}^3 &= 8.345 \text{ lb}_m/\text{U.S. gal} \\
1 \text{ lb}_m/\text{ft}^3 &= 16.0185 \text{ kg/m}^3
\end{aligned}$$

Table 5.18-8.. Units and conversion factors for density.

$$\begin{aligned}
1 \text{ btu/h} \cdot \text{ft} \cdot ^\circ\text{F} &= 4.1365 \times 10^{-3} \text{ cal/s} \cdot \text{cm} \cdot ^\circ\text{C} \\
1 \text{ btu/h} \cdot \text{ft} \cdot ^\circ\text{F} &= 1.73073 \text{ W/m} \cdot \text{K}
\end{aligned}$$

Table 5.18-9.. Units and conversion factors for thermal conductivity.

$$\begin{aligned}
1 \text{ btu/h} \cdot \text{ft}^2 \cdot ^\circ\text{F} &= 1.3571 \times 10^{-4} \text{ cal/s} \cdot \text{cm}^2 \cdot ^\circ\text{C} \\
1 \text{ btu/h} \cdot \text{ft}^2 \cdot ^\circ\text{F} &= 5.6783 \times 10^{-4} \text{ W/cm}^2 \cdot ^\circ\text{C} \\
1 \text{ btu/h} \cdot \text{ft}^2 \cdot ^\circ\text{F} &= 5.6783 \text{ W/m}^2 \cdot ^\circ\text{C} \\
1 \text{ kcal/h} \cdot \text{m}^2 \cdot ^\circ\text{F} &= 0.2048 \text{ btu/h} \cdot \text{ft}^2 \cdot ^\circ\text{F}
\end{aligned}$$

Table 5.18-10.. Units and conversion factors for heat-transfer coefficients.

6. EQUATION SPECIFICATION

This chapter documents the EQ line commands within the current version of Aria. EQ line commands add equations and independent variables to Aria's specification of the equation set to be solved for within each region. The equation is also associated with a field variable here that becomes part of the solution vector for Aria. EQ commands occur in Aria's input file within Region blocks.

The EQ command line adds an equation to be solved for on a particular *MESH_PART*. The format is as follows

EQ equation FOR *DOF* on *MESH_PART* using *INTERP* with $TERM_0 \dots TERM_n$

Equation is the string identifier for the individual equations listed in the previous chapter. The format for the equation string identifiers is listed in a subsection of Chapter 2. The *DOF* keyword specifies the independent unknown that is solved for in order to satisfy the equation. Normally, it is a strict function of the equation keyword. In other words, the temperature is the only valid *DOF* entry if the energy equation is being solved. *MESH_PART* is usually the name of an active element block in the finite element model. Unfortunately, if an equation is to be solved on the entire finite element model, this means that there must be multiple EQ keywords for each element block defined in the mesh.

INTERP defines the finite element interpolation to be used. Currently the valid entries for this keyword are Po, P1, Q1, Q2 and Q2S with standard volumes, e.g. hexahedron, tetrahedron, quadrilateral and triangle. These keywords imply the interpolation and polynomial order for the solution field where P denotes (polynomial) element interpolation and Q denotes the nodal interpolation (Q1 - linear, Q2 - quadratic and Q2S for near-quadratic, serendipity). We note that no syntactical distinction is made between element topology (i.e. triangle and quadrilateral or tetrahedron and hexahedron), that is, the syntax indicates only the level of interpolation. The association of element topology with the equation is handled internal to the code and allowing the specification of interpolation independent of the topology enables the use of superparametric elements (i.e. quadratic geometry with linear interpolation).

Parametric coordinates of shell and bar elements differ from those of conventional bulk volume elements (e.g. hexahedron and tetrahedron) since their meshed geometric description lacks a thickness or area dimension. This missing dimension (SHELL THICKNESS and BAR AREA) can be provided for each material independent of the meshed discretization. Hence when defining equations on shell elements the *INTERP* keywords previously mentioned are paired (e.g. Q1Po) according to interpolation in the shell plane and interpolation through the shell thickness. For example Q1Po represents linear nodal interpolation in the plane of the shell and constant interpolation through the shell thickness. Similarly for bar elements an *INTERP* specification of Q1Po represents linear nodal interpolation along the length of the bar and constant interpolation in the bar section. In sets of coupled equations,

arbitrary combinations of interpolations are sometimes not permitted for solution variables appearing in coupling terms of an equation as interpolation must be consistent in any given equation.

$TERM_n$ refer to the broad categories for the terms in a general advection-diffusion continuity equation. Each term in the equation must be explicitly turned on for it to appear in the conservation equation. Admissible values of $TERM$ are $MASS$, $LUMPED\_MASS$, ADV , $DIFF$, SRC , and $XFER$. While $MASS$, $LUMPED\_MASS$, ADV , $DIFF$, SRC terms imply the activation of mathematical operators appearing in an equation, $XFER$ implies that a solution field values for this equation are being provided externally so the equation can still be thought of as belonging to the overall equation set.

Provisions are made for supplying multiple equation contributions for $DIFF$. These contributions are usually activated via settings in the Aria Materials command block 4.1. Multiple contributions can also be defined for SRC by adding additional source command lines II. In order to accommodate different definitions of velocity for ADV the user can request the velocity to be provided from another equation, from transfer or from other available velocity models 6.27.

All equations are assumed to be formulated in Cartesian coordinates. For two-dimensional problems, axisymmetric formulations are available as well as the Cartesian forms. Invocation of the axisymmetric option is described in the Model Definition chapter of this manual 3.1 in the FINITE ELEMENT MODEL section.

6.1. EQ CONTINUITY

`EQ CONTINUITY[_<Subindex>][_<Phase>]` for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$

Description Activates the continuity equation 5.4.

Summary The only admissible value for *DOF* is $PRESSURE$.

Admissible values of *INTERP* are $Q_1, Q_2, Q_{2S}, P_1, P_0$, for standard volume elements and $Q_1P_0, Q_2P_0, Q_{2S}P_0, Q_1Q_1$ and Q_1Q_2 for shell elements.

Admissible values of $TERM_n$ are $MASS, LUMPED\_MASS, DIV, ADV, SRC$, and $XFER$.

With the exception of $XFER$ these terms are described in the Equations Aria Solves section 5 of the manual.

The *MESH_PART* must be an active element block.

Parent
Block(s)
`ARIA_REGION`

6.2. EQ CURRENT

EQ CURRENT[_<Subindex>][_<Phase>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$

Description Activates the electrical current equation 5.33.

Summary The only admissible value for *DOF* is VOLTAGE.

Admissible values of *INTERP* are Q_1, Q_2, Q_{2S} .

Admissible values of $TERM_n$ are DIFF, SRC, and XFER.

With the exception of XFER these terms are described in the Equations Aria Solves section 5 of the manual.

The *MESH_PART* must be an active element block.

Parent
Block(s)
ARIA_REGION

6.3. EQ CHARGE_DENSITY

EQ CHARGE_DENSITY[_<Subindex>][_<Phase>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$



Beta Capability: The charge density capability is not well tested and should be used with caution.

Description Activates the charge density equation 5.36.

Summary The only admissible value for *DOF* is CHARGE_DENSITY.

Admissible values of *INTERP* are Q_1, Q_2, Q_{2S} .

Admissible values of $TERM_n$ are MASS, LUMPED_MASS, ADV, DIFF, and XFER.

With the exception of XFER these terms are described in the Equations Aria Solves section 5 of the manual.

The *MESH_PART* must be an active element block.

Parent
Block(s)
ARIA_REGION

6.4. EQ ENERGY

EQ ENERGY[_<Subindex>][_<Phase>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$

Description Activates the energy conservation transport equation [5.9](#).

Summary Admissible values for *DOF* are TEMPERATURE and ENTHALPY.

Admissible values of *INTERP* are Q_1 , Q_2 , Q_{2S} , for standard volume elements and $Q_1 P_0$, $Q_2 P_0$, $Q_1 Q_1$ and $Q_1 Q_2$ for shell elements.

Admissible values of $TERM_n$ are MASS, LUMPED_MASS, ADV, DIFF, SRC, and XFER.

With the exception of XFER these terms are described in the Equations Aria Solves section [\[5.3\]](#) of the manual.

The *MESH_PART* must be an active element block.

Parent
Block(s)
ARIA_REGION

6.5. EQ LEVEL_SET

EQ LEVEL_SET[_<Subindex>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$

Description Activates the level set (distance function) equation. This equation is often accompanied by additional commands described in [29](#).

Summary The only admissible value for *DOF* is LEVEL_SET.

Admissible values of *INTERP* are Q_1 , Q_2 , Q_{2S} .

Admissible values of $TERM_n$ are MASS, LUMPED_MASS, ADV, DIFF, SRC, and XFER.

With the exception of XFER these terms are described in the Equations Aria Solves section [5](#) of the manual.

The *MESH_PART* must be an active element block.

Parent
Block(s)
ARIA_REGION

6.6. EQ EXTENSION_SPEED

EQ EXTENSION_SPEED[_<Subindex>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$

Description Activates an equation for extension speed, which is used by the level set equation (29) to define the interface speed.

Summary The only admissible value for *DOF* is EXTENSION_SPEED.

Admissible values of *INTERP* are Q_1, Q_2, Q_{2S} .

Admissible values of $TERM_n$ are DEF, SRC, and XFER.

With the exception of XFER these terms are described in the Equations Aria Solves section 5 of the manual.

The *MESH_PART* must be an active element block.

Parent
Block(s)
ARIA_REGION

6.7. EQ MASS_BALANCE

EQ MASS_BALANCE[_<Subindex>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$

Description The mass balance equation for porous media. See general porous flow information in section 5.12

Summary Admissible value for *DOF* are PRESSURE, DENSITY, and MASS_FRACTION.

Admissible values of *INTERP* are Q_1, Q_2, Q_{2S} .

Admissible values of $TERM_n$ are MASS, LUMPED_MASS, ADV, UPWIND_ADV, DIFF, SRC, and XFER.

With the exception of XFER these terms are described in the Equations Aria Solves section 5 of the manual.

The *MESH_PART* must be an active element block.

Parent
Block(s)
ARIA_REGION

6.8. EQ MESH

EQ MESH[_<Subindex>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$

Description Activates the pseudo-solid mesh equation 5.22.



Beta Capability: Material models for this capability are under active development hence this equation should be used with caution.

Summary The only admissible value for *DOF* is MESH_DISPLACEMENTS.

Admissible values of *INTERP* are Q_1, Q_2, Q_{2S} .

Admissible values of $TERM_n$ are DIFF, REF_DIFF, TSTRAIN, SRC, and XFER.

With the exception of XFER these terms are described in the Equations Aria Solves section 5 of the manual.

If both the MESH and SOLID equations are defined in the same region, then the TALE mesh motion algorithm is activated automatically. In this case, the MESH equation must be defined on all blocks in the region. More details of the TALE method can be found in section 5.6.

The *MESH_PART* must be an active element block.

Parent
Block(s)
ARIA_REGION

6.9. EQ MOMENTUM

EQ MOMENTUM[_<Subindex>] [_<Phase>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$



Beta Capability: The momentum equation is tested for low Reynolds numbers, $Re < 10$ but should be used with caution beyond that range.

Description Activates the fluid momentum equation 5.19.

Summary The only admissible value for *DOF* is VELOCITY.

Admissible values of *INTERP* are Q_1 , Q_2 , Q_{2S} .

Admissible values of $TERM_n$ are MASS, LUMPED_MASS, ADV, DIFF, SRC, and XFER.

With the exception of XFER these terms are described in the Equations Aria Solves section 5 of the manual.

The *MESH_PART* must be an active element block.

Parent
Block(s)
ARIA_REGION

6.10. EQ POROUS_SPECIES

EQ POROUS_SPECIES[_<Subindex>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$

Description The species transport equation porous media. See general porous flow information in section 5.12

Summary Admissible value for *DOF* are PRESSURE, SPECIES, and SPECIES_FRACTION.

Admissible values of *INTERP* are Q_1 , Q_2 , Q_{2S} .

Admissible values of $TERM_n$ are MASS, LUMPED_MASS, ADV, UPWIND_ADV, DIFF, SRC, and XFER.

With the exception of XFER these terms are described in the Equations Aria Solves section 5 of the manual.

The *MESH_PART* must be an active element block.

Additionally, one can choose whether to integrate the advection term by parts by setting the flag INTEGRATE_ADVECTION_BY_PARTS = false in the POROUS_FLOW_OPTIONS block of SOLUTION_OPTIONS. The default is true.

Parent
Block(s)
ARIA_REGION

6.11. EQ POROUS_ENTHALPY

EQ POROUS_ENTHALPY[_<Subindex>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$

Description The enthalpy transport equation porous media. See general porous flow information in section [5.12](#)

Summary The only admissible value for *DOF* is TEMPERATURE.

Admissible values of *INTERP* are Q_1, Q_2, Q_{2S} .

Admissible values of $TERM_n$ are MASS, LUMPED_MASS, ADV, UPWIND_ADV, DIFF, SRC, and XFER.

With the exception of XFER these terms are described in the Equations Aria Solves section [5](#) of the manual.

The *MESH_PART* must be an active element block.

Additionally, one can choose whether to integrate the advection term by parts by setting the flag INTEGRATE ADVECTION BY PARTS = false in the POROUS_FLOW_OPTIONS block of SOLUTION_OPTIONS. The default is true.

Parent
Block(s)
ARIA_REGION

6.12. EQ POTENTIAL

EQ POTENTIAL[_<Subindex>][_<Phase>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$

Description Activates the potential projection equation for the potential, which is defined in equation [5.120](#).

Summary The only admissible value for *DOF* is POTENTIAL.

Admissible values of *INTERP* are Q_1, Q_2, Q_{2S} .

Admissible values of $TERM_n$ are DEF and SRC, and both terms must be active for this equation to behave properly. The value used in SRC must be a separately defined source equation.

The *MESH_PART* must be an active element block.

Parent
Block(s)
ARIA_REGION

6.13. EQ PROJECTION

EQ [LUMPED_|LAGGED_|QUASI_IMPLICIT_]PROJECTION[_<Subindex>][_<Phase>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$

Description Perform a projection of an expression from integration points to nodal values.

Summary The string *DOF* refers to a new degree of freedom to be created and solved for via the projection equation. *DOF* can be chosen to be any expression valid at the integration points, in which case the string used for *DOF* should be the decorated version of the original expression name. A prefix of "PROJECTED_", "PROJECTED_VECTOR_", and "PROJECTED_TENSOR_" should be used for scalar, vector, and tensor expressions, respectively.

By default, projection equations use a consistent source term resulting in a formal L2 projection; however, projection equations can also use a lumped source term by specifying "LUMPED_" before "PROJECTION_". Projection equations are normally solved by the linear solver; however, they can be lagged and solved at the start of a time step by specifying "LAGGED_" or once per nonlinear iteration by specifying "QUASI_IMPLICIT_". Using either the "LAGGED_" or "QUASI_IMPLICIT_" prefixes will not burden the linear solver, but explicit solution necessarily requires that both options use a lumped projection.

Admissible values of *INTERP* are Q_1, Q_2, Q_{2S} .

The only admissible value of $TERM_n$ is DEF.

The *MESH_PART* must be an active element block.

Examples: To project the heat conduction on every block using linear elements, one would use the command

EQ PROJECTION for VECTOR_HEAT_CONDUCTION on ALL_BLOCKS using Q_I with DEF

Likewise, to project a mesh stress, one could specify

EQ PROJECTION for PROJECTED_TENSOR_MESH_STRESS on ALL_BLOCKS using Q_I with DEF

Parent
Block(s)
ARIA_REGION

6.14. EQ SOLID

EQ SOLID[_<Subindex>][_<Phase>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$



Beta Capability: Material models for this capability are under active development hence this equation should be used with caution.

Description Activates the solid momentum equation [5.22](#).

Summary The only admissible value for *DOF* is SOLID_DISPLACEMENTS.

Admissible values of *INTERP* are Q_1, Q_2, Q_{2S} .

Admissible values of $TERM_n$ are DIFF, TSTRAIN, SRC, and XFER.

With the exception of XFER these terms are described in the Equations Aria Solves section [5](#) of the manual.

If both the MESH and SOLID equations are defined in the same region, then the TALE mesh motion algorithm is activated automatically. In this case, the reference configuration for the SOLID equation is converted to the TALE reference frame. More details of the TALE method can be found in section [5.6](#).

The *MESH_PART* must be an active element block.

Parent
Block(s)
ARIA_REGION

6.15. EQ SPECIES

EQ SPECIES[_<Subindex>][_<Phase>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$



Beta Capability: The species equation is tested for low Reynolds numbers, $Re < 10$ but should be used with caution beyond that range.

Description Activates the species transport equation [5.13](#).

Summary The only admissible value for *DOF* is SPECIES.

Admissible values of *INTERP* are Q_1, Q_2, Q_{2S} .

Admissible values of $TERM_n$ are MASS, LUMPED_MASS, ADV, DIFF, SRC, FRACBAL and XFER. With the exception of XFER these terms are described in the Equations Aria Solves section 5 of the manual. The FRACBAL term may not be included with other terms.

Some other things to note about species equations in Aria.

- The FRACBAL term may be assigned to any species number.
- Species numbers in Aria are arbitrary; they may start at any value and need not be continuous.
- For the species fraction balances, Aria will automatically detect all species that are present in the problem and include them in the balance.

The *MESH_PART* must be an active element block.

Parent
Block(s)
ARIA_REGION

6.16. EQ SP

EQ SP *ORDER* for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$



Beta Capability: The spherical harmonics capability is not well tested and should be used with caution.

Description Specifies the Spherical Harmonics equation set to solve for Participating Media Radiation (PMR). User provides the order, degree of freedom associated with the equation, the element type and the mesh part (element block) on which to apply the equation 23.2.

Summary Admissible values for *ORDER* are odd values (1, 3, 5, ...).

The only admissible value for *DOF* is angular_intensity.

The *MESH_PART* must be an active element block.

Admissible values of *INTERP* are Q_1, Q_2, Q_{2S}

Admissible value of $TERM_n$ is SRC.

Parent
Block(s)
ARIA_REGION

6.17. EQ SUSPENSION

EQ SUSPENSION[_<Subindex>][_<Phase>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$



Beta Capability: The suspension modeling capability is not well tested and should be used with caution.

Description Activates the suspension transport equation [5.44](#).

Summary The only admissible value for *DOF* is PHI.

Admissible values of *INTERP* are Q_1, Q_2, Q_{2S} .

Admissible values of $TERM_n$ are ADV, DIFF, SRC, and XFER.

With the exception of XFER these terms are described in the Equations Aria Solves section [5](#) of the manual.

The *MESH_PART* must be an active element block.

Parent
Block(s)
ARIA_REGION

6.18. EQ VOLTAGE

EQ VOLTAGE[_<Subindex>][_<Phase>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$

Description Activates the voltage equation (electric-displacement formulation) [5.30](#). See also the CURRENT equation.

Summary The only admissible value for *DOF* is VOLTAGE.

Admissible values of *INTERP* are Q_1, Q_2, Q_{2S} .

Admissible values of $TERM_n$ are DIFF, SRC, and XFER.

With the exception of XFER these terms are described in the Equations Aria Solves section [5](#) of the manual.

The *MESH_PART* must be an active element block.

Parent
Block(s)
ARIA_REGION

6.19. EQ BRINKMAN_MOMENTUM

EQ BRINKMAN_MOMENTUM[_<Subindex>] [_<Phase>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$



Beta Capability: The porous media capability is under active development hence the Brinkman momentum equation should be used with caution.

Description Activates the Brinkman momentum equation [5.113](#).

Summary The only admissible value for *DOF* is VELOCITY.

Admissible values of *INTERP* are Q_1, Q_2, Q_{2S} .

Admissible values of $TERM_n$ are MASS, LUMPED_MASS, ADV, DIFF, SRC, and XFER.

With the exception of XFER these terms are described in the Equations Aria Solves section [5](#) of the manual.

The *MESH_PART* must be an active element block.

Parent
Block(s)
ARIA_REGION

6.20. EQ LUBRICATION

EQ LUBRICATION[_<Subindex>] [_<Phase>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$



Beta Capability: The lubrication modeling capability is under active development hence this equation should be used with caution.

Description Activates the Reynolds' lubrication equation [5.116](#).

Summary The only admissible value for *DOF* is LUBRICATION_PRESSURE.

Admissible values of *INTERP* is $Q_1 P_0$.

Admissible values of $TERM_n$ are MASS, DIFF, and BOUND.

For problems with fluid-structural interactions, the lubrication equation needs to be defined on all blocks, including 3-D blocks adjoining the shell lubrication region. In order to accommodate this, there is an additional term, DEF, which applies the equation

$p = 0$ on adjoining 3-D blocks where this is used. The other terms should not be used on 3-D blocks. It is weighted so that it does not affect the residual on the shell blocks.

The *MESH_PART* must be an active shell element block.

Parent
Block(s)
ARIA_REGION

6.21. EQ STRESS_TENSOR_PROJECTION

EQ Stress_Tensor_Projection[_<Subindex>] [_<Phase>] for *DOF* ON *MESH_PART* USING *INTERP* with $TERM_0 \dots TERM_n$

Description Activates the Stress Tensor Projection equation.

Summary The only admissible value for *DOF* is Stress_Tensor.

Admissible values of *INTERP* are Q_1, Q_2, Q_{2S} .

The only admissible values of $TERM_n$ are DEF.

With the exception of XFER these terms are described in the Equations Aria Solves section 5 of the manual.

The *MESH_PART* must be an active element block.

Parent
Block(s)
ARIA_REGION

6.22. ELASTICITY FORMULATION

ELASTICITY FORMULATION = PLANE *TYPE*

Description Assigns the elasticity formulation *TYPE* for two-dimensional problems involving the MESH and SOLID equation 5.22.

Summary Allowable formulation PLANE *TYPE* is PLANE STRESS or PLANE STRAIN.

Parent
Block(s)
ARIA_REGION

6.23. PRESSURE STABILIZATION

PRESSURE STABILIZATION IS *TYPE* WITH SCALING = *C*

Description Prescribe a stabilization technique for solving the MOMENTUM 5.19 and CONTINUITY 5.4 equations with equal order interpolation.

Summary Aria supports both PSPG (Pressure Stabilized Petrov-Galerkin) and PSPP (Pressure Stabilized Pressure Projection) stabilization techniques for solving the MOMENTUM and CONTINUITY equations with equal order interpolation.

Valid options for the *TYPE* specification are NO_STABILIZATION, PSPG_CONSTANT, PSPG_LOCAL, PSPG_GLOBAL and PSPP_CONSTANT.

NO_STABILIZATION disables any stabilization.

PSPP_CONSTANT results in the recently developed stabilization technique of [16] and [17].

In the PSPG forms of stabilization, introduced by [18], terms from the momentum equation are added to the continuity equation scaled by a multiplier, α . The exact form of the multiplier depend on a global Reynolds number that is defined as

$$Re \equiv \frac{\rho|\mathbf{v}|\langle h \rangle}{2\mu} \quad (6.1)$$

Here, ρ is the density, μ is the viscosity, $|\mathbf{v}|$ is a velocity scale and $\langle h \rangle$ is an element length scale. Armed with Re , the stabilization multiplier α is defined in one of two ways.

$$Re \leq 3 \quad : \quad \alpha \equiv \frac{\tau \langle h \rangle^2}{12\mu} \quad (6.2)$$

$$Re > 3 \quad : \quad \alpha \equiv \frac{\tau \langle h \rangle}{2\rho|\mathbf{v}|} \quad (6.3)$$

NB: Currently, Aria always uses the low-Reynolds number for of α , as defined in (6.2). The PSPG_LOCAL method computes $|\mathbf{v}|$ and $\langle h \rangle$ within each element. The PSPG_GLOBAL method computes $|\mathbf{v}|$ and $\langle h \rangle$ as averages over all of the elements with the MOMENTUM equation defined. The PSPG_CONSTANT gives $|\mathbf{v}|$ and $\langle h \rangle$ a value of 1 (one) and just uses the scale factor.

Parent
Block(s)
ARIA_REGION

6.24. SAVE RESIDUALS

SAVE RESIDUALS = *MODE*

Description Causes Aria to save the residuals to a field with the prefix `residual->`, e.g., `residual->Temperature`. This will be done for all fields (though we could make it a per-field option). Valid choices are OFF (default), BEFORE_BCS and AFTER_BCS.

Summary Causes Aria to save the residuals to a field with the prefix `residual->`, e.g., `residual->Temperature`. This will be done for all fields (though we could make it a per-field option). Valid choices are OFF (default), BEFORE_BCS and AFTER_BCS.

For the choice BEFORE_BCS the residuals will be saved at the point in the assembly process where the primary equations have been assembled but prior to the assembly of any boundary conditions or distinguishing conditions. For the choice of AFTER_BCS the residuals will be saved after all BCs and distinguishing conditions have been applied. The default, OFF, is to not save the residuals.

This feature is only applicable when using the NEWTON nonlinear solution strategy.

Parent
Block(s)
ARIA_REGION

6.25. INTEGRATION RULE



Beta Capability: Non-default integration rules are not heavily tested and should be used with caution.

INTEGRATION RULE for *block_name* = *INT*

Description Overrides the default integration rule for the equations defined on *block_name*.

Summary Overrides the default integration rule for the equations defined on *block_name*.

Parent
Block(s)
ARIA_REGION

6.26. MESH GROUP

```
MESH GROUP alias_name = mesh_entity1 . . . mesh_entityN
MESH GROUP alias_name = group1 + mesh_entity
MESH GROUP alias_name = group1 - group2
MESH GROUP alias_name = block_1 to block_N
```

Description Assigns aliased grouping of selected mesh entities (block, surface or nodelist). These aliases can then be used in defining equations, source terms, initial conditions, Dirichlet boundary conditions, surface flux conditions, postprocessing operations and the INTEGRATION RULE command.

In order to simplify the specification of mesh groups for large models, sum, difference and range operators are provided.

Summary Only mesh entities can be aliased within a group and a mesh entity can appear in several groups. Mesh entities aliased within the FINITE ELEMENT MODEL command block can appear within MESH GROUP and are treated in the same way as the mesh entity itself. Additionally mesh entities with names supplied from the input file can also be referenced

By default the aliases *all_blocks* and *all_volumes* reference all active element blocks in the mesh and the *all_surfaces* alias references all active surfaces in the mesh. Default aliases are also defined for element blocks by topology and number of nodes, e.g. Hexahedron_8_blocks.

The first mesh_entity can be an alias to an existing MESH GROUP provided subsequent entries define addition or subtraction to the group using (+, plus, and, -, minus, less) to define the operation used to compose an alias. For example:

```
MESH GROUP alias_name = all_blocks - block_8
```

An additional form of the command defines a range of element blocks. In this case the group range is defined using (to, thru or through) to specify the first and last element blocks in the range based upon block number. Note that Mesh Group commands are parsed sequentially, thus command line ordering must be honored when using one Mesh Group to define another Mesh Group.

Parent
Block(s)
ARIA_REGION

6.27. ADVECTION VELOCITY

```
ADVECTION VELOCITY for block_name = STRING
```

Description Defines the velocity model to be used for the equations defined on *block_name*.

Summary Velocity model can be XFER or any other vector velocity model defined in the Region.

Parent
Block(s)
ARIA_REGION

7. DATA FOR MATERIAL, BC, IC, SRC

In many numerical simulations the need often arises to define quantities that involve the same numerical values and are accessible in user defined functions (i.e. user plugins and user subroutines). To facilitate this usage Aria provides a means by which one can collectively define problem dependent real and integer data as named members of a "Data Block", where named data members can be defined either as independent values or as arrays. The utility of Data Block information in setting up problem descriptions is that rather than referencing individual data values, the data collection can be referenced as a whole using the name of the parent data block. This provides a convenient means of reusing data when defining material behavior, boundary conditions and initial conditions with user defined functions for a particular class of problem.

For material parameters the scope of Data Block information is at Domain scope (i.e. outside of the Procedure) hence the corresponding Data Block is specified at the domain scope. For boundary conditions, source terms and initial conditions the scope of Data Block information lies within an Aria Region. Each Data Block must have a unique name and will be referenced by that name within the problem setup. Reference to individual Data Block members will occur only within user defined functions.

Because Data Block values are named then within user defined functions code individual members of the Data Block can be easily referenced by name. This feature is particularly useful in both Calore style user subroutines and in user plugin utilities. The usage of Data Blocks with Calore-style user subroutines is detailed in the Chapter on Thermal Analysis [33.19](#). The Data Block can be used in two distinct ways, at the code feature level or at the Region level. An association between the Data Block and a code feature or the Region is established with a Use Data Block `DataBlockName` command.

Note that an analogous capability `aprepro` exists for substituting fixed or computed data values directly in the input file. Using `aprepro` one can perform these substitutions anywhere within the input file.

7.1. DATA BLOCK

Scope: Aria Region

```
Begin Data DataBlockName

  Real {= |parameter_name |=} value...

  Integer {= |parameter_name |=} value...

End
```

Summary Parameters for Data Blocks within Aria. The DataBlockName must be referenced within the definition of an initial condition, volumetric source, boundary condition or material property Calore_User_Sub in order to be available for use within a user subroutine.

The DataBlockName may also be used to define parameters for all equation line commands by specifying USE DATA BLOCK DataBlockName as the first parameter argument on the equation. When used in this manner, the typed name-value pairs of the Data Block are assigned as the parameters for the equation.

7.1.1. Real

Scope: Data Block

Real {=|parameter_name|=} *value...*

Parameter	Value	Default
<i>values</i>	<i>real...</i>	

Summary Specifies the Real data values for this data block.

7.1.2. Integer

Scope: Data Block

Integer {=|parameter_name|=} *value...*

Parameter	Value	Default
<i>values</i>	<i>integer...</i>	

Summary Specifies the Integer data values for this data block.

8. INITIAL CONDITIONS

This chapter documents the initial condition, IC, line commands within the current version of Aria. The IC simply represents an initialization the Field variable. Technically speaking initial conditions have meaning only in time-dependent partial differential equations. However, within the Aria code the IC command line results in an initialization of Field values used in the assembly of a Jacobian matrix. Thus the IC is equally applicable for assigning starting values in a steady solution. Note that in the case of steady solutions the Aria output will contain two "time" steps, an initialization output plane, and the steady solution output. A distinction between the meaning of these two steps is particularly important when using a steady solution result to provide the initial condition from file for a transient problem.

Within the input file initial conditions command lines will appear at the Region scope as illustrated below. Note that input specification of initial conditions on portions of the FEM mesh can be simplified by aggregation of element blocks into Mesh Groups [6.26](#).

```
.  
.   
.   
Begin Procedure My_Aria_Procedure  
  .  
  .  
  Begin Aria Region My_Region  
    .  
    .  
    IC related commands  
    .  
    .  
  End  
End  
  
.  
.
```



Beta Capability: These initial conductions are defined in a paradigm that will eventually be deprecated.

8.1. IC CIRC_X

IC CIRC_X AT *MESH_PART* *DOF* AMP = Ω

Description Initial boundary condition for the x component of a vector variable with constant tangential magnitude along circles of radius $r(x, y)$ defined on the mesh entity.

Summary Sets *DOF* to the provided value on nodeset associated with the name *MESH_PART* according to the relation

$$DOF = -\Omega r(x, y) \sin \theta. \quad (8.1)$$

The rotation Ω is assumed to be about the vector $(0, 0, 1)$ passing through point $(0, 0, 0)$.

Parent
Block(s)
ARIA_REGION

8.2. IC CIRC_Y

IC CIRC_Y AT *MESH_PART* *DOF* AMP = Ω

Description Initial boundary condition for the y component of a vector variable with constant tangential magnitude along circles of radius $r(x, y)$ defined on the mesh entity.

Summary Sets *DOF* to the provided value on nodeset associated with the name *MESH_PART* according to the relation

$$DOF = \Omega r(x, y) \cos \theta. \quad (8.2)$$

The rotation Ω is assumed to be about the vector $(0, 0, 1)$ passing through point $(0, 0, 0)$.

Parent
Block(s)
ARIA_REGION

8.3. IC CONSTANT

IC CONST AT *MESH_PART* *DOF* = *REAL*

Description Constant initial condition.

Summary Sets *DOF* to the provided constant value on mesh entity associated with the name *MESH_PART*.

Parent
Block(s)
ARIA_REGION

8.4. IC COUETTE_X

IC COUETTE_X AT *MESH_PART* *DOF* PARAMS = r_i r_o Ω

Description Initial condition for x component of a vector variable in a Couette device with inner radius r_i , outer radius r_o and driven at angular velocity Ω , that varies spatially over a mesh entity.

Summary Sets *DOF* to vary spatially over the nodeset associated with the name *MESH_PART* according to the relation

$$DOF = -\Omega r(x, y) \frac{r_i r_o}{r_o^2 - r_i^2} \left(\frac{r_o^2}{r} - r \right) \sin \theta \quad (8.3)$$

The rotation Ω is assumed to be about the vector $(0, 0, 1)$ passing through point $(0, 0, 0)$.

Parent
Block(s)
ARIA_REGION

8.5. IC COUETTE_Y

IC COUETTE_Y AT *MESH_PART* *DOF* PARAMS = r_i r_o Ω

Description Initial condition for y component of a vector variable in a Couette device with inner radius r_i , outer radius r_o and driven at angular velocity Ω , that varies spatially over a mesh entity.

Summary Sets *DOF* to vary spatially over the nodeset associated with the name *MESH_PART* according to the relation

$$DOF = \Omega r(x, y) \frac{r_i r_o}{r_o^2 - r_i^2} \left(\frac{r_o^2}{r} - r \right) \cos \theta \quad (8.4)$$

The rotation Ω is assumed to be about the vector $(0, 0, 1)$ passing through point $(0, 0, 0)$.

Parent
Block(s)
ARIA_REGION

8.6. IC COUETTE_SH

IC COUETTE_SH AT *MESH_PART* *DOF* PARAMS = r_i r_o Ω

Description Initial condition for generalized shear rate in a Couette device with inner radius r_i , outer radius r_o and driven at angular velocity Ω , that varies spatially over a mesh entity.

Summary Sets *DOF* to the provided value on nodeset associated with the name *MESH_PART* according to the relation

$$DOF = \frac{\Omega}{r^2(x, y)} \frac{r_i r_o}{r_o^2 - r_i^2} \left(\frac{1}{r(x, y)} - \frac{r(x, y)}{r_o^2} \right) \quad (8.5)$$

The rotation Ω is assumed to be about the vector $(0, 0, 1)$ passing through point $(0, 0, 0)$.

Parent
Block(s)
ARIA_REGION

8.7. IC READ_FILE

IC READ_FILE *DOF* = *STRING* AT TIME *REAL*

Description This IC command will initialize the field *DOF* with values from the field with the name given by the *STRING* argument in the input mesh database.

Summary This IC command will initialize the field *DOF* in the current analysis with values from the input mesh database containing variable *STRING*. For example, if the mesh database as specified in the FINITE ELEMENT MODEL command block (3.1) contains a vector field named U then one could use the file to initialize a velocity field by setting *DOF* to VELOCITY and the *STRING* argument to U.

Note that Sierra Mechanics uses a *DOF* naming convention which distinguishes vector fields from scalar fields using an underscore plus component notation (e.g. fieldBaseName_I, fieldBaseName_X). Hence use of external scalar field variable names that include an indexed notation will require that the file variable be renamed in order to be processed correctly as a scalar field in the IC READ_FILE setup.

In cases where the field *DOF* has a several components (i.e. *DOF* is a vector field) and the input mesh database contains the vector components defined as scalar fields, the command must be called once for each component. Here the *DOF* is specified as *DOF_component*.

A typical usage example would be initialize a transient calculation from a previously performed steady-state calculation in the following way. The steady-state calculation would be performed and its output variables saved to some output file. In most cases one

might employ a copy of the output file to be used as a mesh file for the transient calculation. Finally, one would use the file IC command line to tie the variable named "FileVariableName" in the mesh file to the variable named *DOF* in the current simulation.

When the mesh database file contains multiple timesteps and the TIME option is not supplied, the default behavior will be to extract the requested field from the last timeplane in the file. The TIME option must be used if the initial condition is to be extracted from any specific database timeplane other than the last timeplane. In using the TIME option the database time step nearest to the specified time value will be used for the assignment. For an initial condition taken from a steady-state results file, the optional TIME parameter should be omitted.

Steady solution results are sometimes written to file in two steps. When this command is used to initialize values from a steady solution one must select the solution file step according to the content of the steady solution file results. If the file contains two solution steps then one should employ the time option and select the time corresponding to the second step.

CAVEAT: Current implementations do not allow restricting this initialization by mesh subsets. e. g. If one wishes to initialize the temperature, then all nodes in the mesh will be initialized.

NOTE: Those wishing to perform initializations as part of a formal restart are referred to RESTART DATA services (25.1).

Parent
Block(s)
ARIA_REGION

8.8. IC LINEAR

IC LINEAR AT *MESH_PART* *DOF* COEF = C_0 C_1 C_2 C_3

Description Initial condition that varies spatially over a mesh entity in a linear fashion.

Summary Sets *DOF* to the provided value on nodeset associated with the name *MESH_PART* in the following manner

$$DOF = C_0 + C_1x + C_2y + C_3z. \quad (8.6)$$

Parent
Block(s)
ARIA_REGION

8.9. IC PARAB

IC PARAB AT *MESH_PART* *DOF* COEF = C_0 C_1 C_2 C_3 C_4 C_5 C_6 C_7 C_8 C_9

Description Initial condition that varies spatially over a mesh entity in a parabolic fashion.

Summary Sets *DOF* to the provided value on nodeset associated with the name *MESH_PART* in the following manner

$$DOF = C_0 + C_1x + C_2y + C_3z + C_4xy + C_5xz + C_6yz + C_7x^2 + C_8y^2 + C_9z^2. \quad (8.7)$$

Parent

Block(s)

ARIA_REGION

8.10. ANNEAL MESH ON STARTUP

ANNEAL MESH ON STARTUP

Description With the command in the Region block Aria will search for a displacements field and, if found, will apply the displacements to the model and physical coordinates.

Summary With the command in the Region block Aria will search for a displacements field and, if found, will apply the displacements to the model and physical coordinates.

Parent

Block(s)

ARIA_REGION

9. BOUNDARY CONDITIONS

Boundary conditions are needed in order to define a well-posed boundary value problem as described by the FEM equations. These boundary conditions are often denoted as Dirichlet, Neumann or Robin conditions. Dirichlet or essential boundary conditions for a solution field stem directly from the governing equations for a particular physics. In Aria, Neumann and Robin conditions are generally categorized as flux boundary conditions.

This section documents primarily the native Aria boundary condition, BC, line commands within the current version of the code. Recall from a previous chapter outlining the general FEM that the method gives rise to boundary terms [5.3](#), i.e. various flux boundary conditions. In what follows, Dirichlet boundary conditions are first described [9.1](#) followed by flux boundary condition descriptions [9.2](#).

Boundary conditions are defined at the Region scope of the input file as illustrated below.

```
Begin Sierra myJob
.
.
Begin Procedure My_Aria_Procedure
.
.
Begin Aria Region My_Region
.
.
BC related commands
.
.
End

End

End Sierra myJob
```

9.1. BC DIRICHLET

Dirichlet or essential boundary conditions for a solution field stem directly from the governing equations for a particular physics. Here the boundary conditions are strongly enforced by substituting the user prescribed evaluation of solution unknown into the system residual and the corresponding

solution increment equal to zero. In Aria default enforcement of the Dirichlet boundary condition involves a matrix row modification. Optional methods of Dirichlet BC enforcement can be specified through the linear solver interface
tt BC Enforcement command line.

The boundary condition specification corresponds to the solution variable or degree-of-freedom (DOF) for a given equation as it appears in the EQ command line. As an example in the EQ command line:

EQ Energy for Temperature on block_2 using Q1 with Diff mass

Temperature is the DOF that used in specification of the Dirichlet boundary condition whereas Energy is the equation to which the condition is applied.

For thermal analysis another interface for Dirichlet BC specification is described in the Thermal Analysis chapter [33.1](#). The advantage of this approach is that the syntax is fully supported within the Sandia Analysis Workbench (SAW).

Dirichlet boundary conditions are applied at a surface of the physical problem domain. Within the context of Sierra Mechanics that surface corresponds to a surface (e.g. surface_3) or a nodelist (e.g. nodelist_2). In what follows the Constant, Encore Function, Global, User Function, Polynomial, User Field and Exponential conditions must be applied to a surface. The remainder of the Dirichlet BCs listed can be applied to either a surface or a nodelist.

Note that stylistically the syntax for Constant, Encore Function, Global, User Function, Polynomial, User Field and Exponential conditions differ from the remaining Dirichlet BC command lines. As an example:

BC Dirichlet BC for Energy on surface_3 = constant value = 273.0

implicitly refers to a Temperature boundary condition. This is in contrast to the remaining Dirichlet BC command lines:

BC Const Dirichlet at surface_3 temperature = 273.0

where the DOF is explicitly stated.

9.1.1. Generic: Constant

Scope: Equation System

Generic: Constant

For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* = Constant [Using Data Specification *Data Spec Name*][Value = *value*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>value</i>	real	undefined

Summary Constant value

9.1.2. Generic: Encore Function

Scope: Equation System

Generic: Encore Function

```
For Dof Name [ {of|species|subindex} Species |{in|material_phase}  
MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name = Encore_Function [  
Using Data Specification Data Spec Name ][ Name = name |Result_Name =  
result_name |Eval_Type = eval_type ]
```

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>name</i>	"string"	undefined
<i>result_name</i>	"string"	undefined
<i>eval_type</i>	"string"	undefined

Summary Value from an Encore function

9.1.3. Generic: Global

Scope: Equation System

Generic: Global

```
For Dof Name [ {of|species|subindex} Species |{in|material_phase}  
MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name = Global [ Using  
Data Specification Data Spec Name ][ Global_Name = global_name ]
```

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>global_name</i>	"string"	undefined

Summary Value from a global variable

9.1.4. Generic: User Function

Scope: Equation System

Generic: User Function

```
For Dof Name [ {of|species|subindex} Species |{in|material_phase}  
MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name = User_Function [  
Using Data Specification Data Spec Name ][ Name = name |X = x |  
X_Multiplier = x_multiplier |Multiplier = multiplier |Toggle = toggle ]
```

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>name</i>	"string"	undefined
<i>x</i>	"string"	undefined
<i>x_multiplier</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>toggle</i>	"string"	undefined

Summary Value from a user function

9.1.5. Generic: Polynomial

Scope: Equation System

Generic: Polynomial

```
For Dof Name [ {of|species|subindex} Species |{in|material_phase}  
MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name = Polynomial [  
Using Data Specification Data Spec Name ][ Variable = variable |Order =  
order |Variable_Offset = variable_offset |C0 = c0 |C1 = c1 |C2 = c2 |C3  
= c3 |C4 = c4 |C5 = c5 |C6 = c6 |C7 = c7 |C8 = c8 ]
```

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>variable</i>	"string"	undefined
<i>order</i>	integer	undefined
<i>variable_offset</i>	real	undefined
<i>c0</i>	"string"	undefined
<i>c1</i>	real	undefined
<i>c2</i>	real	undefined
<i>c3</i>	real	undefined
<i>c4</i>	real	undefined
<i>c5</i>	real	undefined
<i>c6</i>	real	undefined
<i>c7</i>	real	undefined
<i>c8</i>	real	undefined

Summary Value from a polynomial function

9.1.6. **Generic: User Field**

Scope: Equation System

Generic: User Field

For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]{@|at|for|in|on|over} *Mesh Extent Name* = User_Field [
Using Data Specification *Data Spec Name*][Name = *name* |Scaling = *scaling*
|Global_Var = *global_var*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>name</i>	"string"	undefined
<i>scaling</i>	real	undefined
<i>global_var</i>	"string"	undefined

Summary Value from a user field

9.1.7. Generic: Exponential

Scope: Equation System

Generic: Exponential

For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]{@|at|for|in|on|over} *Mesh Extent Name* = Exponential [
Using Data Specification *Data Spec Name*][Variable = *variable* |Constant =
constant |Multiplier = *multiplier* |Exponent = *exponent*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>variable</i>	"string"	undefined
<i>constant</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>exponent</i>	real	undefined

Summary Value from an exponential function

9.1.8. BC Dirichlet = BC CIRC_X

BC CIRC_X DIRICHLET AT *MESH_PART* *DOF* AMP = Ω

Description Dirichlet boundary condition for the x component of a vector variable with constant tangential magnitude along circles of radius $r(x, y)$ defined on the mesh entity.

Summary Sets *DOF* to the provided value on nodeset associated with the name *MESH_PART* according to the relation

$$DOF = -\Omega r(x, y) \sin \theta. \quad (9.1)$$

The rotation Ω is assumed to be about the vector $(0, 0, 1)$ passing through point $(0, 0, 0)$.

Parent
Block(s)
ARIA_REGION

9.1.9. BC Dirichlet = BC CIRC_Y

BC CIRC_Y DIRICHLET AT *MESH_PART* *DOF* AMP = Ω

Description Dirichlet boundary condition for the y component of a vector variable with constant tangential magnitude along circles of radius $r(x, y)$ defined on the mesh entity.

Summary Sets *DOF* to the provided value on nodeset associated with the name *MESH_PART* according to the relation

$$DOF = \Omega r(x, y) \cos \theta. \quad (9.2)$$

The rotation Ω is assumed to be about the vector $(0, 0, 1)$ passing through point $(0, 0, 0)$.

Parent
Block(s)
ARIA_REGION

9.1.10. BC Dirichlet = BC CONST

BC CONST DIRICHLET AT *MESH_PART* *DOF* = *REAL*

Description Constant Dirichlet condition.

Summary Sets *DOF* to the provided constant value on mesh entity associated with the name *MESH_PART*.

Parent
Block(s)
ARIA_REGION

9.1.11. BC Dirichlet = BC DISTRIBUTION FACTOR

BC DISTRIBUTION FACTOR DIRICHLET AT *MESH_PART* *DOF* SCALING = *REAL*

Description Dirichlet condition from node distribution factors.

Summary Sets *DOF* to the a scaled value of the distribution factors present on mesh entity associated with nodeset of name *MESH_PART*.

Parent
Block(s)
ARIA_REGION

9.1.12. BC Dirichlet = BC LINEAR

BC LINEAR DIRICHLET AT *MESH_PART* *DOF* COEF = C_0 C_1 C_2 C_3

Description Dirichlet boundary condition that varies spatially over a mesh entity in a linear fashion.

Summary Sets *DOF* to the provided value on nodeset associated with the name *MESH_PART* in the following manner

$$DOF = C_0 + C_1x + C_2y + C_3z. \quad (9.3)$$

Parent
Block(s)
ARIA_REGION

9.1.13. BC Dirichlet = BC LINEAR_IN_TIME

BC LINEAR_IN_TIME DIRICHLET AT *MESH_PART* *DOF* COEF = C_0 C_1

Description Dirichlet boundary condition whose value is a linear function in time.

Summary Sets *DOF* to the provided value on nodeset associated with the name *MESH_PART* according to the relation

$$DOF = C_0 + C_1t \quad (9.4)$$

Parent
Block(s)
ARIA_REGION

9.1.14. BC Dirichlet = BC PARAB

BC PARAB DIRICHLET AT *MESH_PART* *DOF* COEF = C_0 C_1 C_2 C_3 C_4 C_5 C_6 C_7 C_8 C_9

Description Dirichlet boundary condition for *DOF* that varies spatially over a mesh entity in a parabolic fashion.

Summary Sets *DOF* to the provided value on nodeset associated with the name *MESH_PART* in the following manner

$$DOF = C_0 + C_1x + C_2y + C_3z + C_4xy + C_5xz + C_6yz + C_7x^2 + C_8y^2 + C_9z^2. \quad (9.5)$$

Parent
Block(s)
ARIA_REGION

9.1.15. BC Dirichlet = BC PERIODIC_LINEAR_IN_TIME


BC PERIODIC_LINEAR_IN_TIME DIRICHLET AT *MESH_PART* *DOF* COEF = C_0 C_1 C_2 C_3

Description Dirichlet boundary condition that provides a periodic linear (ramp) function in time over a portion of the local time period $\tau = C_3$.

Summary The value of *DOF* is given by a periodic linear (ramp) function in time, within a local time interval τ as illustrated in figure below.

$$DOF = \begin{cases} C_0 + C_1 t_p & t_p \leq t_d \\ C_0 & otherwise \end{cases} \quad (9.6)$$

where $t_p = t - \tau \text{Int}(t/\tau)$ is a local time period and $t_d = C_2$ is the dwell time within this time period. Note that $t_d < \tau$ in order for the boundary condition to be uniquely defined.



Parent
Block(s)
ARIA_REGION

9.1.16. BC Dirichlet = BC PERIODIC_STEP_IN_TIME


BC PERIODIC_STEP_IN_TIME DIRICHLET AT *MESH_PART* *DOF* COEF = C_0 C_1 C_2 C_3

Description Dirichlet boundary condition that provides a periodic step function in time over a portion of the local time period $\tau = C_3$.

Summary The value of *DOF* is given by a periodic step function in time, as illustrated in figure below.

$$DOF = \begin{cases} C_0 & t_p \leq t_d \\ C_1 & otherwise \end{cases} \quad (9.7)$$

where $t_p = t - \tau \text{Int}(t/\tau)$ is a local period time and $t_d = C_2$ is the dwell time within this time period. Note that $t_d < \tau$ in order for the boundary condition to be uniquely defined.



Parent
Block(s)
ARIA_REGION

9.1.17. BC Dirichlet = BC RAMP_LINEAR_IN_TIME


BC RAMP_LINEAR_IN_TIME DIRICHLET AT *MESH_PART DOF* COEF = C_0 C_1 C_2

Description Dirichlet boundary condition that provides a linear function in time over a range $t = 0$ to $t = C_2$ and constant value thereafter.

Summary The value of *DOF* is given by a linear function of time, as illustrated in figure below.

$$DOF = C_0 + (C_1 - C_0) \text{MIN}(t/C_2, 1.0) \quad (9.8)$$

where C_0 is the initial value, C_1 is the final value and C_2 is the time at which the final value C_1 is achieved.



Parent
Block(s)
ARIA_REGION

9.1.18. BC Dirichlet = BC ROTATING_X

BC ROTATING_X DIRICHLET AT *MESH_PART DOF* $\Omega = \Omega$ C_0 C_1 C_2

Description Dirichlet boundary condition that applies the x -component of a rotation in time about the z -axis.

Summary Sets *DOF* to the provided value on nodeset associated with the name *MESH_PART* according to the relation

$$DOF\_X = X_0 (\cos \omega t - 1) - Y_0 \sin \omega t \quad (9.9)$$

The rotation Ω is assumed to be about the vector $(0, 0, 1)$ passing through point $(0, 0, 0)$.

Parent
Block(s)
ARIA_REGION

9.1.19. BC Dirichlet = BC ROTATING_Y

BC ROTATING_X DIRICHLET AT *MESH_PART* *DOF* Omega = Ω C_0 C_1 C_2

Description Dirichlet boundary condition that applies the *y*-component of a rotation in time about the *z*-axis.

Summary Sets *DOF* to the provided value on nodeset associated with the name *MESH_PART* according to the relation

$$DOF\_Y = X_0 \sin \omega t + Y_0 (\cos \omega t - 1) \quad (9.10)$$

The rotation Ω is assumed to be about the vector $(0, 0, 1)$ passing through point $(0, 0, 0)$.

Parent
Block(s)
ARIA_REGION

9.1.20. BC Dirichlet = BC TRANSLATE

BC TRANSLATE DIRICHLET AT *MESH_PART* *DOF* SCALE = C_0

Description Dirichlet boundary condition for translating a value in time.

Summary Sets *DOF* to the provided value on nodeset associated with the name *MESH_PART* according to the relation

$$DOF = C_0 t \quad (9.11)$$

Parent
Block(s)
ARIA_REGION

9.1.21. BC Dirichlet = BC UNIDIRECTIONAL_FLOW_X


BC UNIDIRECTIONAL_FLOW_X DIRICHLET AT *MESH_PART* *DOF* coef = c_0 c_1 c_2

Description A specialized boundary condition for conveniently specifying inflow boundary conditions on simple geometries.

Summary This boundary condition is really meant for specifying inflow velocity profiles in a convenient way. The three coefficients provide the magnitudes of plug, shear and parabolic flow as a function of the y -coordinate. Specifically,

$$DOF = c_0 + c_1 \frac{y - y_o}{H} + c_2 \left[1 - \left(\frac{y - y_o}{H} \right)^2 \right] \quad (9.12)$$

Here y_o is the y -coordinate of the middle of the surface (sideset) or nodelist (nodeset) and H is the half-width of the surface or nodelist. Both y_o and H are automatically calculated by Aria. This combination of flows is represented graphically as



Parent
Block(s)
ARIA_REGION

9.1.22. BC Dirichlet = BC UNIDIRECTIONAL_FLOW_Y


BC UNIDIRECTIONAL_FLOW_Y DIRICHLET AT *MESH_PART* *DOF* coef = c_0 c_1 c_2

Description A specialized boundary condition for conveniently specifying inflow boundary conditions on simple geometries.

Summary This boundary condition is really meant for specifying inflow velocity profiles in a convenient way. The three coefficients provide the magnitudes of plug, shear and parabolic flow as a function of the x -coordinate. Specifically,

$$DOF = c_0 + c_1 \frac{x - x_o}{H} + c_2 \left[1 - \left(\frac{x - x_o}{H} \right)^2 \right] \quad (9.13)$$

Here x_o is the x -coordinate of the middle of the surface (sideset) or nodelist (nodeset) and H is the half-width of the surface or nodelist. Both x_o and H are automatically calculated by Aria. This combination of flows is represented graphically as



Parent
Block(s)
ARIA_REGION

9.1.23. BC Dirichlet = BC XFER

BC XFER DIRICHLET AT *MESH_PART DOF*

Description Constant Dirichlet condition where the value is set via a transfer.

Summary Allows *DOF* to set to a value that comes from a transfer operation on mesh entity associated with the name *MESH_PART*. Within the transfer operation the target (destination) Field should be defined as solution->*DOF* state NEW.

Example

Assuming that a scalar Field for temperature is being provided from Transfer then use of the XFER BC could be defined as follows:

```
BEGIN PROCEDURE myProcedure
.
  BEGIN ARIA REGION myRegion
    .
    BC Xfer Dirichlet at surface_2 Temperature
    .
  END ARIA REGION myRegion

  BEGIN transfer my_transfer
    .
    send field afield state none to solution->temperature state new
    .
  END transfer my_transfer
.
END PROCEDURE myProcedure
```

Parent
Block(s)
ARIA_REGION

9.1.24. BC Dirichlet = BC USER FIELD

BC USER FIELD DIRICHLET AT *MESH_PART DOF* = UserFieldName

Description Dirichlet boundary condition to provide values as a function of time via a user defined Field.

Summary This Dirichlet boundary condition provides *DOF* values as a function of time from a user defined Field. Typically these values would be supplied by an Encore utility or from an external source via the Transfer utility.

Example

Assuming that a scalar Field `tf_BC` is being provided from Transfer then use of the BC could be defined as follows:

```
BEGIN PROCEDURE myProcedure
.
  BEGIN ARIA REGION myRegion
    .
    USER FIELD REAL NODAL SCALAR tf_BC on surface_2
    .
    BC User Field Dirichlet at surface_2 Temperature = tf_BC
    .
  END ARIA REGION myRegion

  BEGIN transfer my_transfer
    .
    send field afield state none to tf_BC state none
    .
  END transfer my_transfer
.
END PROCEDURE myProcedure
```

Parent
Block(s)
ARIA_REGION

9.1.25. BC Dirichlet = BC USER_FUNCTION_IN_TIME

BC USER_FUNCTION_IN_TIME DIRICHLET AT *MESH_PART DOF* = UserFunctionName

Description Dirichlet boundary condition that provides values as a function of time via a user input function.

Summary Dirichlet boundary condition that provides values as a function of time via a user input function.

Example

```
Begin Sierra myJob
.
Begin Definition for Function T_BC_func
  Type is Piecewise Linear
  Column Titles Time Temperature
  Begin Values
    0 0
    10 50
  End
End
BEGIN PROCEDURE myProcedure
.
  BEGIN ARIA REGION myRegion
  .
    BC User_Function_In_Time Dirichlet at surface_3 Temperature = T_BC_func
  .
  END ARIA REGION myRegion
.
END PROCEDURE myProcedure
End Sierra myJob

Parent
Block(s)
ARIA_REGION
```

9.2. BC FLUX

In Aria, Neumann and Robin conditions are categorized as flux boundary conditions applied to a surface of the problem domain. Here the flux boundary conditions are applied by performing a surface integration of the user prescribed evaluation to generate the appropriate system residual contributions.

The flux boundary condition specification corresponds to a given equation as it appears in the EQ command line. As an example in the EQ command line:

```
EQ Energy for Temperature on block_2 using Q1 with Diff mass
```

Energy is the equation to which the residual contributions will be applied.

For thermal analysis another form of Flux BC specification (Calore-style syntax) is described in the Thermal Analysis chapter [33.1](#). The advantage of this approach is that the syntax is fully supported within the Sandia Analysis Workbench (SAW).

Native Aria boundary conditions differ from those in the Calore-style in that they are succinctly contained within a single line rather than in a command block. In what follows the `Constant`, `Distribution_Factor`, `Encore_Function` and `User_Field` Flux conditions can be applied to any equation. The remainder of the Flux conditions listed apply to specific equations.

One additional difference between the native Aria and Calore-style flux boundary condition syntax is that the native Aria constant flux condition is defined based upon a mathematical convention rather than an engineering convention. By contrast, a constant flux condition in the Calore-style flux condition respects the engineering sign convention, i.e. energy input is positive while energy output is negative. Thus the native Aria constant flux sign convention is opposite that of the Calore-style convention. For other flux boundary conditions these differences are resolved internal code so that problems are always solved in a consistent manner. Nevertheless, users must be aware of the difference in these sign conventions when setting up thermal problems.

For both the native Aria and Calore-style syntax, specification of boundary conditions on portions of the FEM mesh can be simplified by aggregation of surface parts into Mesh Groups [6.26](#). Flux boundary conditions available in Aria are listed following a definition of the general syntax and the associated operation.

BC FLUX FOR *EQNAME* ON *MESH_PART* = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

or

BC LUMPED_FLUX FOR *EQNAME* ON *MESH_PART* = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Neumann boundary condition that sets the surface normal flux of the degree of freedom associated with equation *EQNAME* to that provided by the specified *MODEL*.

Summary *MODEL* supplies a diffusive flux $f_n \equiv \mathbf{n} \cdot \mathbf{f}$ in accordance with equation [5.3](#). I.e., it adds the surface integral

$$\int_{MESH\_PART} \mathbf{n} \cdot \mathbf{f} \phi^i dS \quad (9.14)$$

to the residual for equation *EQNAME*. See, e.g., q_n in equation [5.10](#).

When LUMPED_FLUX is used in place of FLUX, the integral will be evaluated at node locations, instead of the gauss points. This can be beneficial when $\mathbf{f}$ varies strongly along the surface dS , by preventing oscillations in the solution at the expense of integration accuracy for higher-order element types.

Parent

Block(s)

ARIA_REGION

9.2.1. BC FLUX = CONSTANT

Parameters

FLUX = *REAL*

Example

BC Flux for Energy on surface_10 = Constant Flux=3.14159

Description FLUX is the value of the constant flux where positive values indicate a loss, i.e., positive flux leaves the volume.

9.2.2. BC FLUX = CALORE_USER_SUB

Parameters

NAME = *STRING*
TYPE = *STRING*
[MULTIPLIER = *REAL*]
[SCALING_FIELD= *STRING*]
[DATA = *STRING*]
[EXPR_NAME = *STRING*]

Example

```
Begin data block Rdata  
Real Rdata = 1000.0 0.7  
End
```

```
BC FLUX for Energy on surface_10 = Calore_User_Sub  
name=w80afftuser type=element DATA=Rdata
```

Description NAME is the name of the user subroutine was registered with. The TYPE parameter denotes the API the user subroutine requires; TYPE = ELEMENT for heat flux contributions.

The optional MULTIPLIER parameter (defaults to 1.0) can be supplied to scale the output of the user subroutine, i.e., the flux f will be $f = m.f_{user}$ where m is the multiplier and f_{user} is the output of the user subroutine. SCALING_FIELD is similar to MULTIPLIER but here the scaling is applied by specifying the name of a user defined field.

DATA is the name of a Data Block containing Real and integer subroutine parameters, see Chapter 7.

EXPR_NAME is the name of a model entry in a material block where the subroutine is requested. The model value can then be retrieved in the user subroutine. Note: This can only be used in the context of a material block.

See Section 33.21 for a comprehensive description of the Calore_User_Sub setup.

The following is an example user subroutine that provides a free-space radiation energy flux. Note that the flux sign convention is that positive values indicate a heat loss, i.e., positive flux leaves the volume.

Example

```

#include "math.h"
#include "Aria_Calore_User_Sub_Support.h"

Int
w80afftuser(UserQuery &                user_query,
             ElementIds                 element_id,
             Int                        num_elements,
             Int                        num_points,
             Int                        spatial_dimension,
             CoordinateElementIntegrationPoints coordinate_array,
             TemperatureElementIntegrationPoints temperature_array,
             ScalarElementIntegrationPoints flux_array)
{

    RealArray1d rdat(2);
    sierra::String Rdata_label("Rdata");

    user_query.getUserRealInstanceData(rdat, Rdata_label);

    const double Tref          = rdat(0);
    const double emissivity    = rdat(1);

    const double sb_emissivity = 5.67E-8 * emissivity;
    const double Tref4         = Tref * Tref * Tref * Tref;

    for(Int element=0; element < num_elements; ++element)
    {
        for(Int point=0; point < num_points; ++point)
        {
            const double & T          = temperature_array(element,point);
            const double T2           = T*T;
            flux_array(element,point) = sb_emissivity * (T2*T2 - Tref4);
        }
    }
    return 0;
}

RegisterFunction(ElemUserSubC, w80afftuser, "w80afftuser");

```

Description To use this subroutine, you must add a line command at the domain level of your Aria input file that gives the name of a shared object corresponding to the user subroutine source file,

Load User Plugin File `./w80afftuser.so`

Then one must compile the user subroutine,

```
sierra --make aria -i w80afftuser_aria.i
```

to create the shared object w80afftuser.so file. Finally, the problem can be run using the following command line,

```
sierra aria -i w80afftuser_aria.i
```

9.2.3. BC FLUX = DISTRIBUTION_FACTOR

Parameters

MULTIPLIER = *REAL*

Example

BC Flux for Energy on *MESH_PART*= distribution_factor
multiplier=3.2

Description Sets the surface flux to the value of the distribution factor scaled by the MULTIPLIER parameter. Here the distribution factor is present on a mesh entity associated with a sideset (surface) of named *MESH_PART*.

9.2.4. BC FLUX = ENCLOSURE_RADIATION

Parameters

[MULTIPLIER = *REAL*]

Example

BC Flux for Energy on surface_10 = Enclosure_Radiation

Description This boundary condition incorporates the heat flux that's computed using Chaparral for enclosure radiation.

See [chapter 22](#) for more information on enclosure radiation.

9.2.5. BC FLUX = ENCORE_FUNCTION

Parameters

NAME = *STRING*

[EVAL_TYPE = *STRING*]

Example

BC Flux for Energy on surface_10 = Encore_Function
Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

9.2.6. BC FLUX = PID_CONTROLLED

Parameters

```
Max_Output = REAL
Setpoint_Function_Name = STRING
Control_Variable = STRING
[P = REAL]
[I = REAL]
[D = REAL]
[Band = REAL]
[Filter_Tau = REAL]
```

Example

```
BC Flux for Energy on surface_1 = PID_Controlled P=0.1
I=1e-4 Max_Output=20000 Setpoint_Function_Name=pid_setpoints1
Control_Variable=ctrlT1
```

Description This boundary condition imposes an energy flux using a PID controller. The controller setpoint vs. time is defined in a user function, and the controller feedback point uses a global variable (a data probe or Encore function).

The derivative term uses a filtered error value, using a low pass filter whose time constant is specified by the user.

Like a heater, this is only capable of providing a positive influx. Even if the controller output is negative, the applied heat flux will be truncated at 0. Likewise, the applied heat flux cannot exceed the specified max flux.

The nominal scaled PID controller output (from 0 to 1) is

$$u(t) = K_p e(t) + K_i \int_0^t e(\tau) d\tau + K_d \frac{\partial e_f}{\partial t} \quad (9.15)$$

where it is important to note that the K_p coefficient does not scale the others. In some PID implementations, the K_i and K_d coefficients are internally multiplied by K_p so care must be taken to provide the correct coefficients. This output from 0 to 1 is scaled by the specified Max_Output value to produce the applied energy flux. This means you should not include the output magnitude scaling in your P, I, or D parameters.

The P, I, and D coefficients can be specified in a number of ways:

- Just give a 'Band' argument. This calculates $P = 1/\text{Band}$ and uses the defaults of $I = 0.01 \cdot P$ and $D = 0$.
- Give a 'Band' argument and non-defaults for I and/or D. This still multiplies whatever you give for I and D by P.
- Give a 'P' argument instead of 'Band'. NOTE: in this mode the I and D values are not scaled by P.

If you provide both P and Band, P is used, the Band argument is ignored, and I and D are not scaled.

The default values for I and D are 0.01 and 0 if not provided.

The setpoint, controller output, error, filtered error, and filtered error time derivative are all output to automatically created global variables for diagnostics and postprocessing.

9.2.7. BC FLUX = PID_CONTROLLED_COOLER

Parameters

```
Max_Cooling_Power = REAL
Setpoint_Function_Name = STRING
Control_Variable = STRING
[P = REAL]
[I = REAL]
[D = REAL]
[Band = REAL]
[Filter_Tau = REAL]
```

Example

```
BC Flux for Energy on surface_1 = PID_Controlled_Cooler P=0.1
I=1e-4 Max_Cooling_Power=20000 Setpoint_Function_Name=pid_setpoints1
Control_Variable=ctrlT1
```

Description This is similar to PID_Controlled, however, the flux is applied to cool the surface instead of heat it. Max_Cooling_Power should be a positive value.

9.2.8. BC FLUX = PID_CONTROLLED_BIDIRECTIONAL

Parameters

Max_Cooling_Power = *REAL*
Max_Heating_Power = *REAL*
Setpoint_Function_Name = *STRING*
Control_Variable = *STRING*
[P = *REAL*]
[I = *REAL*]
[D = *REAL*]
[Band = *REAL*]
[Filter_Tau = *REAL*]

Example

BC Flux for Energy on surface_1 = PID_Controlled_Bidirectional
P=0.1 I=1e-4 Max_Cooling_Power=20000 Max_Heating_Power=20000
Setpoint_Function_Name=pid_setpoints1 Control_Variable=ctrlT1

Description This is similar to PID_Controlled, however, the flux is applied to cool and heat the surface instead of just heating it. Max_Cooling_Power and Max_Heating_Power should both be positive values.

9.2.9. BC FLUX = LASER

Parameters

T_ON = *REAL*
T_OFF = *REAL*
X_0 = *REAL*
Y_0 = *REAL*
R0 = *REAL* W = *REAL*
FLUX = *REAL*
R = *REAL*

Example

BC Flux for Energy on surface_10 = Laser t_on=0 t_off=10 X_0=0
Y_0=0 w=1.0 r=0.025 flux=3.14159 r0=0.01

Description This boundary condition imposes an energy flux due to an incident laser. The laser is directed in the z direction and travels in a circular path of radius r_0 .

T_ON is the time when the laser is turned on.

T_OFF is the time when the laser is turned off.

X_0 is the x coordinate of the center of the laser path.

Y_0 is the y coordinate of the center of the laser path.

R0 is the radius of the circular laser path.

W is the angular velocity of the laser.

FLUX is the value of the energy flux *into* the surface. (The usual convention is that positive fluxes indicate loss.)

R is the radius of the laser beam.

9.2.10. BC FLUX = LASER_WELD

Parameters

PATH_FUNCTION = *STRING*

FLUX = *REAL*

R = *REAL*

[NORMAL_TOLERANCE = *REAL*]

Example

This function lives at the top level, inside the 'Begin Sierra' block

Begin Definition for Function PATH

Type is Multicolumn Piecewise Linear

Column Titles Time X Y Z

Begin Values

0.0000000E+00	0.0000000E+00	0.0000000E+00	0.0000000E+00
0.2250000E+00	0.1500000E+00	0.0000000E+00	0.0000000E+00
0.2328540E+00	0.1552336E+00	-0.1370490E-03	0.0000000E+00

...

End

End

This goes in the Aria Region with all of the other BCs

BC Flux for Energy on surface_10 = Laser Path_Function=PATH

R=0.025 Flux=3.14159

Description This boundary condition imposes an energy flux due to an incident laser. The position of the laser is dictated by a user supplied function which contains x , y and z coordinates as a function of time; Aria uses linear piecewise interpolation to obtain the location of the laser at a given time.

PATH is the name of the user supplied function which has time as the first column and contains columns titled X, Y and Z containing the x , y and z coordinates.

FLUX is the value of the energy flux *into* the surface. (The usual convention is that positive fluxes indicate loss.)

R is the radius of the laser beam.

The determination of whether a point in space has an incident laser flux is done as follows. At time t the laser is at a point $\mathbf{P}$ and the Laser_Weld boundary condition is being evaluated at a point $\mathbf{x}$ (typically an integration point). The distance of $\mathbf{x}$ from $\mathbf{P}$ is defined as $\mathbf{r} \equiv \mathbf{P} - \mathbf{x}$. If a tolerance NORMAL_TOLERANCE is supplied and the out-of-surface portion of $\mathbf{r}$ is greater than the tolerance then the flux is taken to be zero. Otherwise, the out-of-surface portion of $\mathbf{r}$ is subtracted to neglect minor differences between the PATH_FUNCTION and the discretized mesh, $\mathbf{r}_s \equiv \mathbf{r} - (\mathbf{n} \cdot \mathbf{r})\mathbf{n}$ where $\mathbf{n}$ is the outward unit normal at $\mathbf{x}$. If $|\mathbf{r}_s| < R$ then the point $\mathbf{x}$ is considered to be in the beam and the flux is applied; otherwise, no flux is applied.

9.2.11. BC FLUX = GAUSSIAN_LINE_WELD

Parameters

```
SRC_X = REAL
SRC_Y = REAL
[ SRC_Z = REAL ]
DIR_X = REAL
DIR_Y = REAL
[ DIR_Z = REAL ]
VEL_X = REAL
VEL_Y = REAL
[ VEL_Z = REAL ]
FLUX = REAL
R = REAL
R_EFF = REAL
[ T_ON = REAL ]
[ T_OFF = REAL ]
[ ALPHA = REAL ]
[ COMPUTE_VISIBILITY_FIELD = STRING ]
[ DEPTH_ENHANCED_LASER_ABSORPTION_COEFFICIENT = STRING ]
```


Example

```
BC Flux for Energy on surface_10 = Gaussian_Line_Weld Src_X=0
Src_Y=3 Dir_X=0 Dir_Y=-1 Flux=1000 R=0.01 VEL_X=0.1 VEL_Y=0
```

Description This boundary condition imposes an energy flux due to an incident laser. The laser source is at the coordinates

$$\mathbf{s} = \mathbf{x}_s + \mathbf{v}_s(t - t_{on}) \quad (9.16)$$

where $\mathbf{x}_s$ is provided by the SRC vector coordinates and $\mathbf{v}_s$ is provided by the VEL vector coordinates. The laser is directed from $\mathbf{s}$ by the DIR vector ($\mathbf{d}$ in the figure below).



The point-wise energy flux, f_{eff} , is computed using a Gaussian distribution based on the effective radius R_{eff} (R_EFF),

$$f_{eff} = 2R_{eff} f e^{-\frac{R_{eff} r_p^2}{R^2}} \quad (9.17)$$

where r_p is the radial coordinate from the center of the incident laser.

The radius of the laser is provided by R (R in the figure). A positive FLUX is defined as energy input to the surface. That is, the net normal flux is

$$q_n = \frac{(-\mathbf{n}) \cdot \mathbf{d}}{|\mathbf{d}|} (-f_{eff}) = \frac{\mathbf{n} \cdot \mathbf{d}}{|\mathbf{d}|} f_{eff} \quad (9.18)$$

Here, the term $-\mathbf{n} \cdot \mathbf{d}$ accounts for the fact that the surface may not be orthogonal to the laser.

The optional parameter ALPHA is the absorption coefficient for the incident laser flux (defaults to 1.0).

The optional parameter COMPUTE_VISIBILITY_FIELD is used to enable the calculation of the visibility of the laser to the given surface. When this parameter is given, the provided field will be populated with 1 for each node of the surface that is visible to the laser, and 0 for each node that is obstructed by other portions of the surface. This field is then used to multiply the incident flux so that the obstructed portions of the surface do not get heated by the laser.

The optional parameter DEPTH_ENHANCED_LASER_ABSORPTION_COEFFICIENT is used to specify a filename containing tabular data that will be used to compute an absorption coefficient that depends on the relative depth of the point and the aspect ratio of the given surface, defined as the surface depth/ R . The text file is formatted as follows. The first line contains a list of the relative depth values and the second line contains of list of aspect ratio values. It is assumed that the number of relative depth values and aspect ratios are the same. The remaining rows define a table of absorption coefficient for increasing depth values and fixed increasing aspect ratios. Bilinear interpolation is used to

evaluated the enhanced absorption coefficient for each point on the surface. For any point that lies outside of the specified range of relative depth or aspect ratio values, the value will be extrapolated using the nearest bilinear cell.

The net absorption coefficient is the product of ALPHA (defaults to 1.0), the results of the optional COMPUTE_VISIBILITY_FIELD calculation, and the optional DEPTH_ENHANCED_LASER_ABSORPTION_COEFFICIENT calculation.

9.2.12. BC FLUX = GAUSSIAN_SPOT_WELD


Parameters

SRC_X = *REAL*
SRC_Y = *REAL*
[SRC_Z = *REAL*]
DIR_X = *REAL*
DIR_Y = *REAL*
[DIR_Z = *REAL*]
FLUX = *REAL*
R = *REAL*
R_EFF = *REAL*
[T_ON = *REAL*]
[T_OFF = *REAL*]
[ALPHA = *REAL*]
[COMPUTE_VISIBILITY_FIELD = *STRING*]
[DEPTH_ENHANCED_LASER_ABSORPTION_COEFFICIENT = *STRING*]

Example

BC Flux for Energy on surface_10 = Gaussian_Spot_Weld Src_X=0
Src_Y=3 Dir_X=0 Dir_Y=-1 Flux=1000 R=0.01

Description This boundary condition imposes an energy flux due to an incident laser. The laser source is at the coordinates provided by the SRC vector coordinates (*s* in the figure below) and it is directed from there as specified by the DIR vector (*d* in the figure below).



The point-wise energy flux, f_{eff} , is computed using a Gaussian distribution based on the effective radius R_{eff} (R_EFF),

$$f_{eff} = 2R_{eff} f e^{-\frac{R_{eff} r_p^2}{R^2}} \quad (9.19)$$

where r_p is the radial coordinate from the center of the incident laser.

The radius of the laser is provided by R (R in the figure). A positive FLUX is defined as energy input to the surface. That is, the net normal flux is

$$q_n = \frac{(-\mathbf{n}) \cdot \mathbf{d}}{|\mathbf{d}|} (-f_{eff}) = \frac{\mathbf{n} \cdot \mathbf{d}}{|\mathbf{d}|} f_{eff} \quad (9.20)$$

Here, the term $-\mathbf{n} \cdot \mathbf{d}$ accounts for the fact that the surface may not be orthogonal to the laser.

The optional parameter ALPHA is the absorption coefficient for the incident laser flux (defaults to 1.0).

The optional parameter COMPUTE_VISIBILITY_FIELD is used to enable the calculation of the visibility of the laser to the given surface. When this parameter is given, the provided field will be populated with 1 for each node of the surface that is visible to the laser, and 0 for each node that is obstructed by other portions of the surface. This field is then used to multiply the incident flux so that the obstructed portions of the surface do not get heated by the laser.

The optional parameter DEPTH_ENHANCED_LASER_ABSORPTION_COEFFICIENT is used to specify a filename containing tabular data that will be used to compute an absorption coefficient that depends on the relative depth of the point and the aspect ratio of the given surface, defined as the surface depth/ R . The text file is formatted as follows. The first line contains a list of the relative depth values and the second line contains of list of aspect ratio values. It is assumed that the number of relative depth values and aspect ratios are the same. The remaining rows define a table of absorption coefficient for increasing depth values and fixed increasing aspect ratios. Bilinear interpolation is used to

evaluated the enhanced absorption coefficient for each point on the surface. For any point that lies outside of the specified range of relative depth or aspect ratio values, the value will be extrapolated using the nearest bilinear cell.

The net absorption coefficient is the product of ALPHA (defaults to 1.0), the results of the optional COMPUTE_VISIBILITY_FIELD calculation, and the optional DEPTH_ENHANCED_LASER_ABSORPTION_COEFFICIENT calculation.

9.2.13. BC FLUX = GENERALIZED_NAT_CONV

Parameters

[MULTIPLIER = REAL]

Example

BC Flux for Energy on surface_10 = Generalized_Nat_Conv

Description This boundary condition adds a heat flux due to Newton's law of cooling. This is similar to the NAT_CONV boundary condition except that it utilizes the HEAT_TRANSFER_COEFFICIENT and BC_REFERENCE_TEMPERATURE models.

$$q = mh(T - T_{ref}) \quad (9.21)$$

where m is the optional MULTIPLIER parameter (defaults to 1.0), h is the heat transfer coefficient, T is the temperature at the surface and T_{ref} is a reference temperature.

9.2.14. BC FLUX = GENERALIZED_RAD

Parameters

[MULTIPLIER = REAL]

Example

BC Flux for Energy on surface_10 = Generalized_Rad

Description This boundary condition accounts for the heat flux due to radiation in free space, similar to the RAD boundary condition but the model is more general in that it uses specific models for EMISSIVITY, RADIATION FORM FACTOR and BC RAD REFERENCE TEMPERATURE. The functional form of this boundary condition is

$$q = mF\sigma\epsilon(T^4 - T_{ref}^4) \quad (9.22)$$

where m is the optional MULTIPLIER parameter (defaults to 1.0), F is the RADIATION FORM FACTOR, σ is the Stefan-Boltzmann constant, ϵ is the emissivity of the surface, T is the temperature at the surface and T_{ref} is a reference temperature which must be supplied from a BC RAD REFERENCE TEMPERATURE material model.

The Stefan-Boltzmann constant must be defined in the input file using a Global Constants block, e.g.,

```

Begin Global Constants
  Stefan Boltzmann Constant = 5.67e-14
End

```

9.2.15. BC FLUX = SHARP_LINE_WELD

Parameters

```

SRC_X = REAL
SRC_Y = REAL
[ SRC_Z = REAL ]
DIR_X = REAL
DIR_Y = REAL
[ DIR_Z = REAL ]
VEL_X = REAL
VEL_Y = REAL
[ VEL_Z = REAL ]
FLUX = REAL
R = REAL
[ T_ON = REAL ]
[ T_OFF = REAL ]
[ ALPHA = REAL ]
[ COMPUTE_VISIBILITY_FIELD = STRING ]
[ DEPTH_ENHANCED_LASER_ABSORPTION_COEFFICIENT = STRING ]

```

Example

```


BC Flux for Energy on surface_10 = Sharp_Line_Weld Src_X=0
Src_Y=3 Dir_X=0 Dir_Y=-1 Flux=1000 R=0.01 VEL_X=0.1 VEL_Y=0

```

Description This boundary condition imposes an energy flux due to an incident laser. The laser source is at the coordinates

$$\mathbf{s} = \mathbf{x}_s + \mathbf{v}_s(t - t_{on}) \quad (9.23)$$

where $\mathbf{x}_s$ is provided by the SRC vector coordinates and $\mathbf{v}_s$ is provided by the VEL vector coordinates. The laser is directed from $\mathbf{s}$ by the DIR vector ($\mathbf{d}$ in the figure below).



The radius of the laser is provided by R (R in the figure) and the energy flux is provided by the FLUX argument (written as f below). A positive FLUX is defined as energy input to the surface. That is, the net normal flux is

$$q_n = \frac{(-\mathbf{n}) \cdot \mathbf{d}}{|\mathbf{d}|}(-f) = \frac{\mathbf{n} \cdot \mathbf{d}}{|\mathbf{d}|}f \quad (9.24)$$

Here, the term $-\mathbf{n} \cdot \mathbf{d}$ accounts for the fact that the surface may not be orthogonal to the laser.

The optional parameter ALPHA is the absorption coefficient for the incident laser flux (defaults to 1.0).

The optional parameter COMPUTE_VISIBILITY_FIELD is used to enable the calculation of the visibility of the laser to the given surface. When this parameter is given, the provided field will be populated with 1 for each node of the surface that is visible to the laser, and 0 for each node that is obstructed by other portions of the surface. This field is then used to multiply the incident flux so that the obstructed portions of the surface do not get heated by the laser.

The optional parameter DEPTH_ENHANCED_LASER_ABSORPTION_COEFFICIENT is used to specify a filename containing tabular data that will be used to compute an absorption coefficient that depends on the relative depth of the point and the aspect ratio of the given surface, defined as the surface depth/ R . The text file is formatted as follows. The first line contains a list of the relative depth values and the second line contains of list of aspect ratio values. It is assumed that the number of relative depth values and aspect ratios are the same. The remaining rows define a table of absorption coefficient for increasing depth values and fixed increasing aspect ratios. Bilinear interpolation is used to evaluated the enhanced absorption coefficient for each point on the surface. For any point that lies outside of the specified range of relative depth or aspect ratio values, the value will be extrapolated using the nearest bilinear cell.

The net absorption coefficient is the product of ALPHA (defaults to 1.0), the results of the optional COMPUTE_VISIBILITY_FIELD calculation, and the optional DEPTH_ENHANCED_LASER_ABSORPTION_COEFFICIENT calculation.

9.2.16. BC FLUX = SHARP_SPOT_WELD


Parameters

SRC_X = *REAL*
 SRC_Y = *REAL*
 [SRC_Z = *REAL*]
 DIR_X = *REAL*
 DIR_Y = *REAL*
 [DIR_Z = *REAL*]
 FLUX = *REAL*
 R = *REAL*
 [T_ON = *REAL*]
 [T_OFF = *REAL*]

Example

BC Flux for Energy on surface_10 = Sharp_Spot_Weld Src_X=0
 Src_Y=3 Dir_X=0 Dir_Y=-1 Flux=1000 R=0.01

Description This boundary condition imposes an energy flux due to an incident laser. The laser source is at the coordinates provided by the SRC vector coordinates (s in the figure below) and it is directed from there as specified by the DIR vector (d in the figure below).



The radius of the laser is provided by R (R in the figure) and the energy flux is provided by the FLUX argument (written as f below). A positive FLUX is defined as energy input to the surface. That is, the net normal flux is

$$q_n = \frac{(-n) \cdot d}{|d|}(-f) = \frac{n \cdot d}{|d|}f \quad (9.25)$$

Here, the term $-n \cdot d$ accounts for the fact that the surface may not be orthogonal to the laser.

9.2.17. BC FLUX = LATENT_HEAT

Parameters

Y0 = *REAL*
[SPECIES = *INT*]

Example

BC Flux for Energy on surface_10 = Latent_Heat Y0=0.2 SPECIES=0
BC Flux for Energy on surface_10 = Latent_Heat Y0=0.4 SPECIES=1
BC Flux for Energy on surface_10 = Latent_Heat Y0=0.0
SPECIES=2

Description This boundary condition accounts for the heat flux due to the latent heat of vaporization (evaporation).

$$q = H_v \rho (Y_i - Y_{\infty,i}) \quad (9.26)$$

where $H_{v,i}$ is the heat of vaporization of species i , ρ is the density of the material, Y_i is the mass fraction of species i and $Y_{\infty,i}$ is the mass fraction of species i far from the surface.

SPECIES is the index of the species to use (in multicomponent systems), = i in equation 9.26.

Yinf is the mass fraction of species i far from the surface, = $Y_{\infty,i}$ in equation 9.26.

9.2.18. BC FLUX = NAT_CONV

Parameters

T_REF = *REAL*
H = *REAL*

Example

BC Flux for Energy on surface_10 = Nat_Conv T_REF=273.15 H=300

Description This boundary condition accounts for the heat flux due to natural heat convection:

$$q = h(T - T_{ref}) \quad (9.27)$$

T_REF is the reference temperature of free space.

H is the heat transfer coefficient.

9.2.19. BC FLUX = RAD

Parameters

T_REF = *REAL*

CRAD = *REAL*

Example

BC Flux for Energy on surface_10 = Rad T_REF=273.15

CRAD=1.3e-8

Description This boundary condition accounts for the heat flux due to radiation in free space:

$$q = c_{rad}(T^4 - T_{ref}^4) \quad (9.28)$$

T_REF is the temperature of free space.

CRAD is the coefficient that multiplies the radiation term, viz., the product of the emissivity and the Stefan-Boltzmann constant, which is $5.67 \times 10^{-08} \text{ W m}^{-2} \text{ K}^{-4}$ (SI Units).

9.2.20. BC FLUX = VAPOR_COOLING

Parameters

TBOIL = *REAL*

Example

BC Flux for Energy on surface_10 = Vapor_Cooling Tboil=3000

Description This boundary condition accounts for the cooling of a material due to vaporization.

TBOIL is the boiling point of the material.

9.2.21. BC FLUX = NAT_CONV

Parameters

Yinf = *REAL*

k = *REAL*

Example

BC Flux for Species_2 on surface_10 = Nat_Conv k=0.15 Yinf=0.8

Description This boundary condition accounts for the mass flux due to natural convection:

$$q = k(Y - Y_{\infty}) \quad (9.29)$$

Yinf is the bulk species concentration, Y_{∞} .

k is the mass transfer coefficient.

9.2.22. BC FLUX = CAPILLARY

Parameters

(none)

Example

BC FluxBP for Momentum on surface_10 = Capillary

Description This boundary condition implements the capillary (surface tension) contributions to the traction boundary condition [19]. Specifically, this boundary condition adds to the k^{th} component of the i^{th} momentum residual

$$\int_S \sigma (\mathbf{I} - \mathbf{n}\mathbf{n}) : \nabla (\phi^i \mathbf{e}^k) \, dS. \quad (9.30)$$

where σ is the surface tension and $\mathbf{n}$ is the unit outward normal to the interface. This condition accounts for both the curvature and surface tension gradient contributions to the traction condition.

9.2.23. BC FLUX = CONSTANT_TRACTION

Parameters

[X = *REAL*]

[Y = *REAL*]

[Z = *REAL*]

Example

BC Flux for Momentum on surface_10 = Constant_Traction Y=0.5

or

BC Flux for Mesh on surface_10 = Constant_Traction X=0.1 Y=0.5

or

BC Flux for Solid on surface_10 = Constant_Traction Z=0.5

Description This boundary condition integrates a constant and uniform traction over a surface for either fluid momentum, mesh elasticity or solid elasticity. Specifically, this boundary condition adds to the k^{th} component of the i^{th} momentum/mesh/solid residual

$$\int_S \mathbf{f}_t \phi^i \, dS. \quad (9.31)$$

where $\mathbf{f}_t$ is the constant traction vector whose components are given by the parameters X, Y and Z.

9.2.24. BC FLUX = ELECTRIC_TRACTION

Parameters

[SIGN = *REAL*]

Example

BC Flux for Momentum on surface_10 = Electric_Traction

BC Flux for Mesh on surface_10 = Electric_Traction

BC Flux for Solid on surface_10 = Electric_Traction

Description This boundary condition adds the stress contribution for due to the presence of an electric field. Here, the electric stress tensor is taken to be

$$\mathbf{T}_e = \epsilon \mathbf{E} \mathbf{E} - \frac{1}{2} \epsilon \mathbf{E} \cdot \mathbf{E} \mathbf{I} \quad (9.32)$$

where $\mathbf{E} = -\nabla V$ is the electric field and V is voltage and ϵ is the electric permittivity. The electric traction is then defined as

$$\mathbf{t} = \epsilon \mathbf{n} \cdot \mathbf{E} \mathbf{E} - \frac{1}{2} \epsilon \mathbf{E} \cdot \mathbf{E} \mathbf{n} \quad (9.33)$$

where $\mathbf{n}$ is the outward normal to the boundary.

9.2.25. BC FLUX = NAT_E

Example

BC Flux for Charge_Density on surface_1 = Nat_E

Description This boundary condition creates a no-flux boundary condition for the charge density equation when DIFF is activated in the equation. The diffusion operator for this equation is not of the standard no-flux type, and so this term needs to be added to get the correct surface term contribution.

9.2.26. BC FLUX = FLOW_HYDROSTATIC

Parameters

[GX = *REAL*]

[GY = *REAL*]

[GZ = *REAL*]

[P_REF = *REAL*]

Example

BC Flux for Momentum on surface_10 = Flow_Hydrostatic Gy=-9.8

Description This boundary condition provides a hydrostatic pressure head along a boundary. The acceleration vector g is specified with the parameters GX, GY and GZ (all default to zero). The reference pressure P_{ref} (P_REF, defaults to zero) is taken to be the pressure datum at the origin (0, 0, 0). Specifically, this BC adds

$$\mathbf{n} \cdot \mathbf{T} = - \left(P_{ref} + \sum_i^{N_d} \rho g_i x_i \right) \mathbf{n} \quad (9.34)$$

to the momentum equation. Here N_d is the spatial dimension of the problem, g_i are the components of the acceleration, x_i are the coordinate components and ρ is the density. NOTE: This BC evaluates the density material model for ρ thus the parameters for $\mathbf{g}$ should *not* include the density.

9.2.27. BC FLUX = FREE_OPEN_FLOW

Parameters

PRESSURE = *REAL*

Example

BC Flux for Momentum on surface_10 = Free_Open_Flow

Pressure=1000

Description This boundary condition adds back the stress contribution for inlet/outlet flows where the pressure is prescribed. This command line is used in open-flow applications to set the pressure datum but imposes no other constraints on the flow profile.

$$\mathbf{q} = -p_o \mathbf{n} + \mu \mathbf{n} \cdot (\nabla \mathbf{v} + \nabla \mathbf{v}^t) \quad (9.35)$$

Here, p_o is the pressure provided by the user, μ is the viscosity, $\nabla \mathbf{v}$ is the velocity gradient, and $\mathbf{n}$ is the outward normal to the boundary.

9.2.28. BC FLUX = OPEN_FLOW

Parameters

PRESSURE = *REAL*

Example

BC Flux for Momentum on surface_10 = Open_Flow Pressure=1000

Description This boundary condition adds back the stress contribution for inlet/outlet flows where the pressure is prescribed, and the flow is unidirectional and fully developed. Specifically, it removes the normal component of the viscous stresses (and any other non-pressure stresses).

$$\mathbf{q} = -p_o \mathbf{n} + \mathbf{n} \cdot \boldsymbol{\tau} \cdot (\mathbf{I} - \mathbf{n}\mathbf{n}) \quad (9.36)$$

Here, p_o is the pressure provided by the user $\mathbf{n}$ is the outward normal to the boundary and $\boldsymbol{\tau}$ is the sum of all other stresses except the the isotropic pressure (e.g., NEWTONIAN_PRESSURE_MOMENTUM_STRESS)

9.2.29. BC FLUX = PRESSURE

Parameters

P = *REAL*

[C_T = *REAL*]

Example

BC Flux for Momentum on surface_10 = Pressure P=101325

or

BC Flux for Mesh on surface_10 = Pressure P=101325

or

BC Flux for Solid on surface_10 = Pressure P=101325

Description This boundary condition integrates a uniform pressure over a surface for either fluid momentum, mesh elasticity or solid elasticity. The optional parameter C_T allows the pressure to vary linearly in time. Specifically, this boundary condition adds to the k^{th} component of the i^{th} momentum/mesh/solid residual

$$\int_S - (p + c_t t) \mathbf{n} \phi^i dS. \quad (9.37)$$

where p is the pressure provided by the parameter P, t is time and c_t is a constant provided by the C_T parameter.

9.2.30. BC FLUX = LUBRICATION_PRESSURE

Parameters

(none)

Example

BC Flux for Mesh on surface_10 = Lubrication_Pressure

or

BC Flux for Solid on surface_10 = Lubrication_Pressure

Description This boundary condition integrates the lubrication pressure (the DOF from the lubrication equation) over a surface. This is intended to apply the fluid pressure to a solid region, and can be used for either the MESH or SOLID equations.

9.2.31. BC FLUX = ORIENTED_SLIP

Parameters

BETA_NORMAL = *REAL*

BETA_TANGENT = *REAL*

[VS_X = *REAL*]

[VS_Y = *REAL*]

[VS_Z = *REAL*]

Example

BC Flux for Momentum on surface_7 = Oriented_Slip
Beta_Tangent=1e-1 Beta_Normal=1e-5

Description This is similar to the classic SLIP condition except that it permits separate slip coefficients for the normal and tangent directions.

$$\mathbf{q} = \mathbf{n} \cdot \mathbf{T} = \frac{1}{\beta_t} (\mathbf{v}_s - \mathbf{v}) + \left(\frac{1}{\beta_n} - \frac{1}{\beta_t} \right) (\mathbf{v}_s - \mathbf{v}) \cdot \mathbf{n} \mathbf{n} \quad (9.38)$$

where β_t is the Navier slip coefficient for the tangent direction (BETA_TANGENT), β_n is that for the normal direction (BETA_NORMAL, $\mathbf{v}$ is the fluid velocity and $\mathbf{v}_s$ is the velocity of the surface. The surface velocity is zero by default but a nonzero velocity can be supplied in component form using one or more of the optional VS_X, VS_Y and VS_Z parameters.

9.2.32. BC FLUX = SLIP

Parameters

BETA = *REAL*
[VS_X = *REAL*]
[VS_Y = *REAL*]
[VS_Z = *REAL*]

Example

BC Flux for Momentum on surface_10 = Slip Beta = 0.01

Description This boundary condition implements the Navier slip boundary condition along a surface wherein the tangential velocity along the surface is proportional to the fluid stress,

$$\mathbf{q} = \mathbf{n} \cdot \mathbf{T} = \frac{1}{\beta} (\mathbf{v}_s - \mathbf{v}) \quad (9.39)$$

where β is the Navier slip coefficient, $\mathbf{v}$ is the fluid velocity and $\mathbf{v}_s$ is the velocity of the surface. The surface velocity is zero by default but a nonzero velocity can be supplied in component form using one or more of the optional VS_X, VS_Y and VS_Z parameters.

9.2.33. BC FLUX = TRANSIENT_TRACTION

Parameters

[A_X = *REAL*]
[A_Y = *REAL*]
[A_Z = *REAL*]
[B_X = *REAL*]
[B_Y = *REAL*]
[B_Z = *REAL*]

Example

BC Flux for Momentum on surface_10 = Transient_Traction B_Y=0.5

or

BC Flux for Mesh on surface_10 = Transient_Traction A_X=0.1

A_Y=0.5

or

BC Flux for Solid on surface_10 = Transient_Traction B_Z=0.5

Description This boundary condition integrates a uniform but time dependent traction over a surface for either fluid momentum, mesh elasticity or solid elasticity. Specifically, this boundary condition adds to the k^{th} component of the i^{th} momentum/mesh/solid residual

$$\int_S (\mathbf{f}_a + t\mathbf{f}_b) \phi^i dS. \quad (9.40)$$

where t is time and $\mathbf{f}_a$ and $\mathbf{f}_b$ are constant traction vectors whose components are given by the parameters A_X, A_Y and A_Z and B_X, B_Y and B_Z respectively.

9.2.34. BC FLUX = WETTING_SPEED_BLAKE_LS

Parameters

V_W = *REAL*

G = *REAL*

THETA = *REAL*

WIDTH = *REAL*

Example

BC Disting for Momentum_A on surface_3 = Wetting_Speed_Blake_LS

V_w=1e-1 g=1 Width=1 Theta=60

BC Disting for Momentum_B on surface_3 = Wetting_Speed_Blake_LS

V_w=1e-1 g=1 Width=1 Theta=60

Description This boundary condition is a distinguishing condition that enforces a slip velocity in accordance with the model provided by [20].

$$\mathbf{v} - f(\phi)v_w \sinh(g(\cos\theta_s - \cos\theta_a)) \frac{\mathbf{n}_{ls} - \cos\theta_a \mathbf{n}_w}{1 - \cos^2\theta_a} = \mathbf{0} \quad (9.41)$$

Here θ_s is the static or equilibrium contact angle and is provided by the THETA input parameter, θ_a is the actual (or “observed” or “current”) contact angle, g is a constant parameter given by the G input parameter and v_w is the characteristic slip velocity and is given by the input parameter V_W. In their paper, Blake and De Coninck develop g and v_w theoretically.

The function $f(\phi)$ where ϕ is the level set distance function is simply a triangle shape function which causes the velocity to vary from v_w to zero over the distance given by the

input parameter WIDTH. Taking h_w to half of the input WIDTH parameter, $f(\phi)$ is given as

$$f(\phi) = \begin{cases} 0 & : & \phi < -h_w \\ 1 + \phi/h_w & : & -h_w \leq \phi < 0 \\ 1 - \phi/h_w & : & 0 \leq \phi < h_w \\ 0 & : & h_w \leq \phi \end{cases}$$

This boundary condition is a distinguishing condition which means the momentum equations are discarded at the nodes where this is applied. Also, the velocity provided by this boundary condition is purely tangential. Thus, this boundary condition automatically enforces no-penetration in addition to slip/no-slip.

Note: The interface normal points out of the *negative* phase (negatively signed level set distance ϕ) into the *positive* phase. Thus, the contact angle is measured from the wall, through the *negative* phase and to the level set interface $\phi = 0$.

9.2.35. BC FLUX = USER_FUNCTION

Parameters

NAME = *STRING*

X = *STRING*

Example

```
BC Flux for Energy on surface_6 = USER_FUNCTION NAME=testflux
X=TIME
```

Description The flux boundary condition value is defined by a tabular function of the given name which is evaluated as a function of argument X.

9.2.36. Darcy Leak

Scope: Equation System

```
Darcy Leak Disting For Momentum [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Darcy_Leak [
Using Data Specification Data Spec Name ][ P_Ref = p_ref |L = l |K = k |
Pressure = pressure ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>p_ref</i>	real	undefined
<i>l</i>	real	undefined
<i>k</i>	real	undefined
<i>pressure</i>	"string"	undefined

Summary Darcy leak model for momentum distinguishing condition

9.2.37. Vector User Function Disting

Scope: Equation System

Vector User Function Disting Disting For Momentum [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh
Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Vector_User_Function_Disting [Using Data Specification *Data Spec Name*] [
Name_X = *name_x* |Name_Y = *name_y* |Name_Z = *name_z* |X = *x* |Multiplier =
multiplier |Mult = *Mult*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>name_x</i>	"string"	undefined
<i>name_y</i>	"string"	undefined
<i>name_z</i>	"string"	undefined
<i>x</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>Mult</i>	real	undefined

Summary Vector user function model for momentum distinguishing condition

9.2.38. Wetting Outflow

Scope: Equation System

Wetting Outflow Edge For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]Where *SidePart0Name* Intersects *SidePart1Name*
= Wetting_Outflow [Theta_S = *theta_s*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>SidePart0Name</i>	string	undefined
<i>SidePart1Name</i>	string	undefined
<i>theta_s</i>	real	undefined

Summary Sharp wetting edge source term for outflow

9.2.39. Wetting

Scope: Equation System

Wetting Edge For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]Where *SidePart0Name* Intersects *SidePart1Name*
= Wetting [Theta_S = *theta_s*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>SidePart0Name</i>	string	undefined
<i>SidePart1Name</i>	string	undefined
<i>theta_s</i>	real	undefined

Summary Sharp wetting edge source term

9.2.40. Capillary

Scope: Equation System

Capillary Fluxbp For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Capillary [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Momentum capillary flux BP BC

9.2.41. Vector String Function

Scope: Equation System

Vector String Function Fluxbp For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Vector_String_Function [Using Data Specification *Data Spec Name*][F_X = *f_x* |F_Y = *f_y* |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.42. Ls Capillary

Scope: Equation System

Ls Capillary Fluxbp For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Ls_Capillary [Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Momentum capillary flux BP BC using level set normal

9.2.43. Smoothed Capillary

Scope: Equation System

Smoothed Capillary Fluxbp For Momentum [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Smoothed_Capillary [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Momentum capillary flux BP BC

9.2.44. Normal Capillary Stabilization

Scope: Equation System

Normal Capillary Stabilization Fluxbp For Cvfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Normal_Capillary_Stabilization [Using Data Specification *Data Spec Name*] [$\mu_0 = \mu_0$ |Multiplier = *multiplier* | Use_Velocity_Correction = *use_velocity_correction*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>mu0</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>use_velocity_correction</i>	integer	undefined

Summary Momentum capillary stabilization flux BP BC

9.2.45. Ls Capillary Stabilization

Scope: Equation System

```
Ls Capillary Stabilization Fluxbp For Cvfem_Momentum [ {of|species|
subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|
over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing
OpposingMeshExtent ]= Ls_Capillary_Stabilization [ Using Data Specification
Data Spec Name ][  $\mu_0 = \mu_0$  |Multiplier = multiplier |
Use_Velocity_Correction = use_velocity_correction ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>mu0</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>use_velocity_correction</i>	integer	undefined

Summary Momentum capillary stabilization flux BP BC using level set normal

9.2.46. Free Open Flow

Scope: Equation System

```
Free Open Flow Flux For Cvfem_Momentum [ {of|species|subindex} Species |
{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name
[ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Free_Open_Flow [ Using Data Specification Data Spec Name ][ Pressure =
pressure |Pressure User Sub PRESSURE User Sub ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>PRESSURE User Sub</i>	string	undefined

Summary Open flow for momentum; apply the full stress

9.2.47. Constant Traction

Scope: Equation System

```
Constant Traction Flux For Cvfem_Momentum [ {of|species|subindex} Species
|{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent
Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Constant_Traction [ Using Data Specification Data Spec Name ][ X = x |Y = y
|Z = z ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>x</i>	"string"	undefined
<i>y</i>	"string"	undefined
<i>z</i>	"string"	undefined

9.2.48. Vector String Function

Scope: Equation System

```
Vector String Function Flux For Cvfem_Momentum [ {of|species|subindex}
Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh
Extent Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Vector_String_Function [ Using Data Specification Data Spec Name ][ F_X =
f_x |F_Y = f_y |F_Z = f_z ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.49. Mass Flux

Scope: Equation System

```
Mass Flux Flux For Cvfem_Momentum [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Mass_Flux [
Using Data Specification Data Spec Name ][ Total_Mdot = total_mdot |
Temperature = temperature |Pressure = pressure |Mass_Fraction_0 =
mass_fraction_0 |Mass_Fraction_1 = mass_fraction_1 |Mass_Fraction_2 =
mass_fraction_2 |Mass_Fraction_3 = mass_fraction_3 |Mass_Fraction_4 =
mass_fraction_4 |Mass_Fraction_5 = mass_fraction_5 |Mass_Fraction_6 =
mass_fraction_6 |Mass_Fraction_7 = mass_fraction_7 |Mass_Fraction_8 =
mass_fraction_8 ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>total_mdot</i>	real	undefined
<i>temperature</i>	real	undefined
<i>pressure</i>	real	undefined
<i>mass_fraction_0</i>	real	undefined
<i>mass_fraction_1</i>	real	undefined
<i>mass_fraction_2</i>	real	undefined
<i>mass_fraction_3</i>	real	undefined
<i>mass_fraction_4</i>	real	undefined
<i>mass_fraction_5</i>	real	undefined
<i>mass_fraction_6</i>	real	undefined
<i>mass_fraction_7</i>	real	undefined
<i>mass_fraction_8</i>	real	undefined

9.2.50. Rad

Scope: Equation System

```
Rad Flux For Cvfem_Energy [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Rad [ Using
Data Specification Data Spec Name ][ Data = data |T_Ref = t_ref |Crad =
crad ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>data</i>	"string"	undefined
<i>t_ref</i>	real	undefined
<i>crad</i>	real	undefined

Summary CVFEM radiative energy flux defined with constant models for emissivity, form factor and reference temperature

9.2.51. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfem_Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*] [Data = *data* | F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>data</i>	"string"	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.52. From Cht Temperature Cpt

Scope: Equation System

From Cht Temperature Cpt Disting For Cvfem_Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 From_Cht_Temperature_Cpt [Using Data Specification *Data Spec Name*] [
Twall_Field = *Twall_Field* |Variable = *variable* |Order = *order* |

Variable_Offset = *variable_offset* | C0 = *c0* | C1 = *c1* | C2 = *c2* | C3 = *c3* |
C4 = *c4* | C5 = *c5* | C6 = *c6* | C7 = *c7* | C8 = *c8*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Twall_Field</i>	"string"	undefined
<i>variable</i>	"string"	undefined
<i>order</i>	integer	undefined
<i>variable_offset</i>	real	undefined
<i>c0</i>	real	undefined
<i>c1</i>	real	undefined
<i>c2</i>	real	undefined
<i>c3</i>	real	undefined
<i>c4</i>	real	undefined
<i>c5</i>	real	undefined
<i>c6</i>	real	undefined
<i>c7</i>	real	undefined
<i>c8</i>	real	undefined

Summary CVFEM energy distinguishing condition from CHT temperature using Cp*T model

9.2.53. Open

Scope: Equation System

Open Flux For Hfem_Lumped_Projection [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [
Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Open [Using
Data Specification *Data Spec Name*] [Total_Pressure = *total_pressure* |
Pressure = *pressure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>total_pressure</i>	real	undefined
<i>pressure</i>	real	undefined

Summary Open model for projection flux

9.2.54. Simple Interp

Scope: Equation System

```
Simple Interp Flux For Hfem_Lumped_Projection [ {of|species|subindex}
Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh
Extent Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Simple_Interp [ Using Data Specification Data Spec Name ][ ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Simple interp model for projection flux

9.2.55. Open Flow

Scope: Equation System

```
Open Flow Flux For Hfem_Momentum [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Open_Flow [
Using Data Specification Data Spec Name ][ Pressure = pressure |
Total_Pressure = total_pressure ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined

Summary Open flow for momentum; enforce normal gradient to be zero

9.2.56. Darcy Slip

Scope: Equation System

Darcy Slip Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Darcy_Slip [Using Data Specification *Data Spec Name*][Vs_X = *vs_x* |Vs_Y = *vs_y* |Vs_Z = *vs_z* |K = *k*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>vs_x</i>	real	undefined
<i>vs_y</i>	real	undefined
<i>vs_z</i>	real	undefined
<i>k</i>	real	undefined

Summary Darcy slip momentum flux

9.2.57. Electric Traction

Scope: Equation System

Electric Traction Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Electric_Traction [Using Data Specification *Data Spec Name*][Sign = *sign*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>sign</i>	real	undefined

Summary Electric traction momentum flux

9.2.58. Projected Capillary

Scope: Equation System

Projected Capillary Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Projected_Capillary [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Projected capillary momentum flux

9.2.59. Flow Hydrostatic

Scope: Equation System

Flow Hydrostatic Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Flow_Hydrostatic [Using Data Specification *Data Spec Name*] [P_Ref = *p_ref* |Gx = *gx* |Gy = *gy* |Gz = *gz*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>p_ref</i>	real	undefined
<i>gx</i>	real	undefined
<i>gy</i>	real	undefined
<i>gz</i>	real	undefined

Summary Flow hydrostatic momentum flux

9.2.60. Lens Particles Pressure

Scope: Equation System

Lens Particles Pressure Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Lens_Particles_Pressure [Using Data Specification *Data Spec Name*] [Src_X = *src_x* |Dir_X = *dir_x* |Vel_X = *vel_x* |Src_Y = *src_y* |Dir_Y = *dir_y* |Vel_Y = *vel_y* |Src_Z = *src_z* |Dir_Z = *dir_z* |Vel_Z = *vel_z* |Massflowrate = *massFlowRate* |Particlespeed = *particleSpeed* |Radius = *radius* |T_Liq = *T_liq* |T_Solid = *T_solid* |T_On = *t_on* |T_Off = *t_off*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>src_x</i>	real	undefined
<i>dir_x</i>	real	undefined
<i>vel_x</i>	real	undefined
<i>src_y</i>	real	undefined
<i>dir_y</i>	real	undefined
<i>vel_y</i>	real	undefined
<i>src_z</i>	real	undefined
<i>dir_z</i>	real	undefined
<i>vel_z</i>	real	undefined
<i>massFlowRate</i>	real	undefined
<i>particleSpeed</i>	real	undefined
<i>radius</i>	real	undefined
<i>T_liq</i>	real	undefined
<i>T_solid</i>	real	undefined
<i>t_on</i>	real	undefined
<i>t_off</i>	real	undefined

Summary LENS particles pressure momentum flux

9.2.61. Non Ibp Pressure

Scope: Equation System

Non Ibp Pressure Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=

Non_Ibp_Pressure [Using Data Specification *Data Spec Name*][Pressure = *pressure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	"string"	undefined

9.2.62. Rt Pressure Darcy

Scope: Equation System

Rt Pressure Darcy Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
 Rt_Pressure_Darcy [Using Data Specification *Data Spec Name*][P = *p* |C_T = *c_t* |C_X = *c_x* |C_Y = *c_y* |C_Z = *c_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>p</i>	real	undefined
<i>c_t</i>	real	undefined
<i>c_x</i>	real	undefined
<i>c_y</i>	real	undefined
<i>c_z</i>	real	undefined

9.2.63. Pressure Darcy

Scope: Equation System

Pressure Darcy Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Pressure_Darcy
 [Using Data Specification *Data Spec Name*][User_Field_Name = *user_field_name* |Use_Bulk_Node = *use_bulk_node* |P = *p* |C_T = *c_t* |C_X = *c_x* |C_Y = *c_y* |C_Z = *c_z* |C_Cos_W = *c_cos_w* |C_Sin_W = *c_sin_w* |C1_Cos = *c1_cos* |C1_Sin = *c1_sin*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>user_field_name</i>	"string"	undefined
<i>use_bulk_node</i>	"string"	undefined
<i>p</i>	real	undefined
<i>c_t</i>	real	undefined
<i>c_x</i>	real	undefined
<i>c_y</i>	real	undefined
<i>c_z</i>	real	undefined
<i>c_cos_w</i>	real	undefined
<i>c_sin_w</i>	real	undefined
<i>cI_cos</i>	real	undefined
<i>cI_sin</i>	real	undefined

9.2.64. Constant Traction

Scope: Equation System

Constant Traction Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
Constant_Traction [Using Data Specification *Data Spec Name*] [X = *x* | Y = *y* | Z = *z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>x</i>	"string"	undefined
<i>y</i>	"string"	undefined
<i>z</i>	"string"	undefined

9.2.65. Transient Traction

Scope: Equation System

Transient Traction Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [

Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Transient_Traction [Using Data Specification *Data Spec Name*][A_X = *a_x* |
A_Y = *a_y* |A_Z = *a_z* |B_X = *b_x* |B_Y = *b_y* |B_Z = *b_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>a_x</i>	real	undefined
<i>a_y</i>	real	undefined
<i>a_z</i>	real	undefined
<i>b_x</i>	real	undefined
<i>b_y</i>	real	undefined
<i>b_z</i>	real	undefined

9.2.66. Simple Interp

Scope: Equation System

Simple Interp Flux For Cvfem_Pressure_Edge_Gradient_Projection [{of |
species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for |
in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing
OpposingMeshExtent]= Simple_Interp [Using Data Specification *Data Spec*
Name][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary CVFEM edge-based projection simple interpolation flux BC

9.2.67. Interface

Scope: Equation System

Interface Flux For Cvfem_Energy [{of |species|subindex} *Species* |{in |
material_phase} *MaterialPhase*]{@|at|for |in|on|over} *Mesh Extent Name* [
Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Interface [
Using Data Specification *Data Spec Name*][Data = *data*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>data</i>	"string"	undefined

Summary INTERFACE CVFEM energy flux

9.2.68. Porous Robin Coupled With Solid Phase Convection One Region

Scope: Equation System

Porous Robin Coupled With Solid Phase Convection One Region Flux For Cvfem_Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
Porous_Robin_Coupled_With_Solid_Phase_Convection_One_Region [Using Data Specification *Data Spec Name*][*Data = data* |Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>data</i>	"string"	undefined
<i>multiplier</i>	real	undefined

Summary Boundary condition for coupling of enthalpy to a porous region in the same region.

9.2.69. Porous Robin Coupled With Solid Phase Convection

Scope: Equation System

Porous Robin Coupled With Solid Phase Convection Flux For Cvfem_Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Porous_Robin_Coupled_With_Solid_Phase_Convection [Using Data Specification *Data Spec Name*][*Data = data* |Multiplier = *multiplier* |Enthalpy_Field = *enthalpy_field* |Enthalpy_Diffusive_Flux_Field = *enthalpy_diffusive_flux_field* |Solid_Phase_Temperature_Field =

```

solid_phase_temperature_field | Porosity_Field = porosity_field |
Averaged_Coeff_Field = averaged_coeff_field |
Volumetric_Heat_Transfer_Coeff_Field = volumetric_heat_transfer_coeff_field
| Specific_Surface_Area_Field = specific_surface_area_field ]

```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>data</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>enthalpy_field</i>	"string"	undefined
<i>enthalpy_diffusive_flux_field</i>	"string"	undefined
<i>solid_phase_temperature_field</i>	"string"	undefined
<i>porosity_field</i>	"string"	undefined
<i>averaged_coeff_field</i>	"string"	undefined
<i>volumetric_heat_transfer_coeff_field</i>	"string"	undefined
<i>specific_surface_area_field</i>	"string"	undefined

Summary Boundary condition for loose coupling of enthalpy to a porous region

9.2.70. Porous Robin Coupled One Region

Scope: Equation System

```

Porous Robin Coupled One Region Flux For Cvfem_Energy [ {of|species|
subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|
over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing
OpposingMeshExtent ]= Porous_Robin_Coupled_One_Region [ Using Data
Specification Data Spec Name ] [ Data = data ]

```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>data</i>	"string"	undefined

Summary Boundary condition for loose coupling of enthalpy to a porous region

9.2.71. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Voltage [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.72. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfem_Turbulent_Kinetic_Energy [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.73. Free Open Flow

Scope: Equation System

```
Free Open Flow Flux For Cvfem_Turbulent_Kinetic_Energy [ {of|species|
subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|
over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing
OpposingMeshExtent ]= Free_Open_Flow [ Using Data Specification Data Spec
Name ][ ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

9.2.74. Mass Flux

Scope: Equation System

```
Mass Flux Flux For Cvfem_Turbulent_Kinetic_Energy [ {of|species|subindex}
Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh
Extent Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Mass_Flux [ Using Data Specification Data Spec Name ][ Total_Mdot =
total_mdots |Inflow_Phi = inflow_phi ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>total_mdots</i>	real	undefined
<i>inflow_phi</i>	real	undefined

9.2.75. Kuntz

Scope: Equation System

```
Kuntz Flux For Energy [ {of|species|subindex} Species |{in|material_phase}
MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [ Touching
TouchingMeshExtent |Opposing OpposingMeshExtent ]= Kuntz [ Using Data
Specification Data Spec Name ][ Power_Output = power_output |Flux_Output =
```

flux_output |Toggle = *toggle* |Multiplier = *multiplier* |File = *file* |Units = *units*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>file</i>	"string"	undefined
<i>units</i>	"string"	undefined

Summary Interpolated value from tabulated data for the energy flux

9.2.76. Nat Conv

Scope: Equation System

Nat Conv Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Nat_Conv [Using Data Specification *Data Spec Name*] [Power_Output = *power_output* | Flux_Output = *flux_output* |Toggle = *toggle* |H = *h* |T_Ref = *t_ref* | Advective_Bar = *advective_bar* |Command_Block_Name = *command_block_name*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>h</i>	"string"	undefined
<i>t_ref</i>	"string"	undefined
<i>advective_bar</i>	"string"	undefined
<i>command_block_name</i>	"string"	undefined

Summary Convective energy flux defined with constant models for heat transfer coefficient and reference temperature

9.2.77. Open

Scope: Equation System

Open Flux For Cvfem_Lumped_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Open [Using Data Specification *Data Spec Name*] [Total_Pressure = *total_pressure* | Pressure = *pressure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>total_pressure</i>	real	undefined
<i>pressure</i>	real	undefined

Summary CVFEM lumped projection open flux BC

9.2.78. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfem_Lumped_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*] [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.79. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Mixture_Fraction [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh*
Extent Name [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*
]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.80. Open Flow Convection

Scope: Equation System

Open Flow Convection Flux For Mixture_Fraction [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh*
Extent Name [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Open_Flow_Convection [Using Data Specification *Data Spec Name*][
Reference_Value = *Reference_Value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Reference_Value</i>	"string"	undefined

Summary Open flow convection BC for the mixture fraction equation

9.2.81. Open Flow

Scope: Equation System

Open Flow Flux For Cvfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Open_Flow [Using Data Specification *Data Spec Name*][Pressure = *pressure* | Total_Pressure = *total_pressure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined

Summary Open flow for momentum; enforce normal gradient to be zero

9.2.82. Nat Conv

Scope: Equation System

Nat Conv Flux For Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Nat_Conv [Using Data Specification *Data Spec Name*][K = *k* |Yinf = *yinf*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>k</i>	real	undefined
<i>yinf</i>	real	undefined

Summary natconv species flux

9.2.83. Interface

Scope: Equation System

Interface Flux For Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Interface [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Flux BC model of species for moving interfaces

9.2.84. Open Adv Flow

Scope: Equation System

Open Adv Flow Flux For Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Open_Adv_Flow [Using Data Specification *Data Spec Name*] [Far_Field_Entrainment_Value = *far_field_entrainment_value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>far_field_entrainment_value</i>	real	undefined

9.2.85. Surface Stabilization

Scope: Equation System

Surface Stabilization Fluxbp For Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Surface_Stabilization [Using Data Specification *Data Spec Name*] [D = *d*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>d</i>	real	undefined

Summary surface diffusion term for species

9.2.86. Pyrolysis

Scope: Equation System

```
Pyrolysis Rotated For Cvfem_Mesh [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Pyrolysis [
Using Data Specification Data Spec Name ][ T_Ref = t_ref |K = k |K_0 = k_0
|N = n |Temperature = temperature ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_o</i>	real	undefined
<i>n</i>	real	undefined
<i>temperature</i>	"string"	undefined

Summary Pyrolysis model for rotated CVFEM_MESH boundary condition

9.2.87. Recession

Scope: Equation System

```
Recession Rotated For Cvfem_Mesh [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Recession [
Using Data Specification Data Spec Name ][ T_Ref = t_ref |K = k |K_0 = k_0
|N = n |Temperature = temperature ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_o</i>	real	undefined
<i>n</i>	real	undefined
<i>temperature</i>	"string"	undefined

Summary Recession model for rotated CVFEM_MESH boundary condition

9.2.88. Kinematic

Scope: Equation System

Kinematic Rotated For Cvfem_Mesh [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Kinematic [Using Data Specification *Data Spec Name*] [*V0 = v0* |*Shared_Normal = shared_normal* |*No_Mesh_Movement = no_mesh_movement*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>v0</i>	real	undefined
<i>shared_normal</i>	"string"	undefined
<i>no_mesh_movement</i>	"string"	undefined

Summary Kinematic model for rotated CVFEM_MESH boundary condition

9.2.89. Vector String Function

Scope: Equation System

Vector String Function Rotated For Cvfem_Mesh [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=

Vector_String_Function [Using Data Specification *Data Spec Name*][F_X = *f_x* | F_Y = *f_y* | F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.90. Porous Robin Coupled

Scope: Equation System

Porous Robin Coupled Flux For Cvfem_Mass_Fraction [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] {@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* | *Opposing OpposingMeshExtent*] = Porous_Robin_Coupled [Using Data Specification *Data Spec Name*][
 Mass_Fraction_Field = *mass_fraction_field* |
 Mass_Fraction_Diffusive_Flux_Field = *mass_fraction_diffusive_flux_field* |
 Averaged_Coeff_Field = *averaged_coeff_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>mass_fraction_field</i>	"string"	undefined
<i>mass_fraction_diffusive_flux_field</i>	"string"	undefined
<i>averaged_coeff_field</i>	"string"	undefined

Summary Boundary condition for loose coupling of scalars to a free fluid region

9.2.91. Open Adv Flow

Scope: Equation System

```
Open Adv Flow Flux For Cvfem_Mass_Fraction [ {of|species|subindex} Species
|{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent
Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Open_Adv_Flow [ Using Data Specification Data Spec Name ][ Pressure =
pressure |Total_Pressure = total_pressure |Far_Field_Entrainment_Value =
far_field_entrainment_value ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined
<i>far_field_entrainment_value</i>	real	undefined

9.2.92. Open

Scope: Equation System

```
Open Flux For Hfem_Projection [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Open [ Using
Data Specification Data Spec Name ][ Total_Pressure = total_pressure |
Pressure = pressure ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>total_pressure</i>	real	undefined
<i>pressure</i>	real	undefined

Summary Open model for projection flux

9.2.93. Simple Interp

Scope: Equation System

```
Simple Interp Flux For Hfem_Projection [ {of|species|subindex} Species |
{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name
```

[Touching *TouchingMeshExtent* | Opposing *OpposingMeshExtent*] = Simple_Interp
 [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Simple interp model for projection flux

9.2.94. Normal Capillary Stabilization

Scope: Equation System

Normal Capillary Stabilization Fluxbp For Hfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* | Opposing *OpposingMeshExtent*] = Normal_Capillary_Stabilization [Using Data Specification *Data Spec Name*] [$\mu_0 = \mu_0$ | Multiplier = *multiplier* | Use_Velocity_Correction = *use_velocity_correction*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>mu0</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>use_velocity_correction</i>	integer	undefined

Summary Momentum capillary stabilization flux BP BC

9.2.95. Ls Capillary Stabilization

Scope: Equation System

Ls Capillary Stabilization Fluxbp For Hfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* | Opposing *OpposingMeshExtent*] = Ls_Capillary_Stabilization [Using Data Specification *Data Spec Name*] [μ_0

= *mu0* |Multiplier = *multiplier* |Use_Velocity_Correction =
use_velocity_correction]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>mu0</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>use_velocity_correction</i>	integer	undefined

Summary Momentum capillary stabilization flux BP BC using level set normal

9.2.96. Pyrolysis

Scope: Equation System

Pyrolysis Disting For Mesh_Y [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [
Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Pyrolysis [
Using Data Specification *Data Spec Name*][T_Ref = *t_ref* |K = *k* |K_0 = *k_0*
|N = *n* |Temperature = *temperature*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_o</i>	real	undefined
<i>n</i>	real	undefined
<i>temperature</i>	"string"	undefined

Summary Pyrolysis model for mesh_x distinguishing condition

9.2.97. Kinematic

Scope: Equation System

Kinematic Disting For Mesh_Y [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Kinematic [Using Data Specification *Data Spec Name*][$V_0 = v_0$ |Shared_Normal = *shared_normal* |No_Mesh_Movement = *no_mesh_movement*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
v_0	real	undefined
<i>shared_normal</i>	"string"	undefined
<i>no_mesh_movement</i>	"string"	undefined

Summary Kinematic model for mesh_y distinguishing condition

9.2.98. Recession

Scope: Equation System

Recession Disting For Mesh_Y [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Recession [Using Data Specification *Data Spec Name*][$T_{Ref} = t_{ref}$ | $K = k$ | $K_0 = k_0$ | $N = n$ |Temperature = *temperature*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
t_{ref}	real	undefined
k	real	undefined
k_0	real	undefined
n	real	undefined
<i>temperature</i>	"string"	undefined

Summary Recession model for mesh_x distinguishing condition

9.2.99. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Mesh_Y [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Scalar_String_Function [Using Data Specification *Data Spec Name*][F = f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.100. Vector String Function

Scope: Equation System

Vector String Function Flux For Div_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Vector_String_Function [Using Data Specification *Data Spec Name*][F_X = *f_x* |F_Y = *f_y* |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.101. Curvature

Scope: Equation System

Curvature Flux For Div_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Curvature [Using Data Specification *Data Spec Name*][Theta = *theta*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>theta</i>	real	undefined

Summary This model has been deprecated and removed from the code.

9.2.102. Vector String Function

Scope: Equation System

Vector String Function Flux For Cvfem_Velocity_Pressure_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Vector_String_Function [Using Data Specification *Data Spec Name*][F_X = *f_x* |F_Y = *f_y* |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.103. Simple Dp Interp

Scope: Equation System

Simple Dp Interp Flux For Cvfem_Velocity_Pressure_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Simple_Dp_Interp [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Simple DP interpolation model for HFEM velocity pressure projection flux

9.2.104. Vector String Function

Scope: Equation System

Vector String Function Flux For Darcy_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Vector_String_Function [Using Data Specification *Data Spec Name*] [$F_X = f_x$ | $F_Y = f_y$ | $F_Z = f_z$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
f_x	"string"	undefined
f_y	"string"	undefined
f_z	"string"	undefined

Summary Value from a string function

9.2.105. Simple Interp

Scope: Equation System

Simple Interp Flux For Darcy_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Simple_Interp [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Darcy momentum simple interpolation flux BC

9.2.106. Vector String Function

Scope: Equation System

Vector String Function Flux For Hfem_Lumped_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Vector_String_Function [Using Data Specification *Data Spec Name*] [F_X = f_x |F_Y = f_y |F_Z = f_z]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
f_x	"string"	undefined
f_y	"string"	undefined
f_z	"string"	undefined

Summary Value from a string function

9.2.107. Open Adv Flow

Scope: Equation System

Open Adv Flow Flux For Hfem_Mixture_Fraction [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh
Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Open_Adv_Flow [Using Data Specification *Data Spec Name*][Pressure =
pressure |Total_Pressure = *total_pressure* |Value = *value* |
Far_Field_Entrainment_Value = *far_field_entrainment_value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined
<i>value</i>	real	undefined
<i>far_field_entrainment_value</i>	real	undefined

Summary HFEM mixture fraction open advective flow flux BC

9.2.108. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Hfem_Mixture_Fraction [{of|species|
subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|
over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing
OpposingMeshExtent]= Scalar_String_Function [Using Data Specification
Data Spec Name][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.109. Free Open Flow

Scope: Equation System

Free Open Flow Flux For Hfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Free_Open_Flow [Using Data Specification *Data Spec Name*][Pressure = *pressure* |Pressure User Sub *PRESSURE User Sub*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>PRESSURE User Sub</i>	string	undefined

Summary Open flow for momentum; apply the full stress

9.2.110. Vector String Function

Scope: Equation System

Vector String Function Flux For Hfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Vector_String_Function [Using Data Specification *Data Spec Name*][F_X = *f_x* |F_Y = *f_y* |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.111. Open Adv Flow

Scope: Equation System

```
Open Adv Flow Flux For Hfem_Momentum [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Open_Adv_Flow [
Using Data Specification Data Spec Name ][ Pressure = pressure |
Total_Pressure = total_pressure |Coflow_Entrainment_Value_X =
coflow_entrainment_value_x |Coflow_Entrainment_Value_Y =
coflow_entrainment_value_y |Coflow_Entrainment_Value_Z =
coflow_entrainment_value_z ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined
<i>coflow_entrainment_value_x</i>	real	undefined
<i>coflow_entrainment_value_y</i>	real	undefined
<i>coflow_entrainment_value_z</i>	real	undefined

Summary HFEM momentum open advective flow flux BC

9.2.112. Kinematic

Scope: Equation System

```
Kinematic Rotated For Mesh [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Kinematic [
Using Data Specification Data Spec Name ][ V0 = v0 |Shared_Normal =
shared_normal |No_Mesh_Movement = no_mesh_movement ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>vo</i>	real	undefined
<i>shared_normal</i>	"string"	undefined
<i>no_mesh_movement</i>	"string"	undefined

Summary Kinematic model for rotated mesh boundary condition

9.2.113. Recession

Scope: Equation System

Recession Rotated For Mesh [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Recession [Using Data Specification *Data Spec Name*][*T_Ref = t_ref* |*K = k* |*K_0 = k_0* |*N = n* |*Temperature = temperature*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_o</i>	real	undefined
<i>n</i>	real	undefined
<i>temperature</i>	"string"	undefined

Summary Recession model for rotated mesh boundary condition

9.2.114. Pyrolysis

Scope: Equation System

Pyrolysis Rotated For Mesh [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Pyrolysis [

Using Data Specification *Data Spec Name* [T_Ref = *t_ref* | K = *k* | K_0 = *k_0* | N = *n* | Temperature = *temperature*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_o</i>	real	undefined
<i>n</i>	real	undefined
<i>temperature</i>	"string"	undefined

Summary Pyrolysis model for rotated mesh boundary condition

9.2.115. Scalar String Function

Scope: Equation System

Scalar String Function Rotated For Mesh [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* | Opposing *OpposingMeshExtent*] =
 Scalar_String_Function [Using Data Specification *Data Spec Name*] [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.116. Inflow

Scope: Equation System

Inflow Flux For Cvfem_Dispersed_Continuity [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent*

Name [*Touching TouchingMeshExtent* | *Opposing OpposingMeshExtent*] = Inflow
 [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Inflow mass flux for dispersed phase continuity equation; nodal interpolation

9.2.117. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfem_Dispersed_Continuity [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] {@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* | *Opposing OpposingMeshExtent*] = Scalar_String_Function [Using Data Specification *Data Spec Name*] [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
f	"string"	undefined

Summary Value from a string function

9.2.118. Simple Inflow

Scope: Equation System

Simple Inflow Flux For Cvfem_Dispersed_Continuity [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] {@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* | *Opposing OpposingMeshExtent*] = Simple_Inflow [Using Data Specification *Data Spec Name*] [$Velocity\_X = Velocity\_X$ | $Velocity\_Y = Velocity\_Y$ | $Velocity\_Z = Velocity\_Z$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Velocity_X</i>	real	undefined
<i>Velocity_Y</i>	real	undefined
<i>Velocity_Z</i>	real	undefined

Summary Inflow mass flux for dispersed continuity equation; specified density and velocity

9.2.119. Open Flow

Scope: Equation System

Open Flow Flux For Cvfem_Dispersed_Continuity [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh
Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Open_Flow [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Open bc for dispersed continuity

9.2.120. Simple Interp

Scope: Equation System

Simple Interp Flux For Cvfem_Density_Edge_Gradient_Projection [{of|species
|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|
over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing
OpposingMeshExtent]= Simple_Interp [Using Data Specification *Data Spec
Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary CVFEM edge-based projection simple interpolation flux BC

9.2.121. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfem_Density_Edge_Gradient_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*] = Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.122. Open Adv Flow

Scope: Equation System

Open Adv Flow Flux For Cvfem_Turbulent_Kinetic_Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*] = Open_Adv_Flow [Using Data Specification *Data Spec Name*][Pressure = *pressure* |Total_Pressure = *total_pressure* |Far_Field_Entrainment_Value = *far_field_entrainment_value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined
<i>far_field_entrainment_value</i>	real	undefined

9.2.123. Recession

Scope: Equation System

Recession Disting For Level_Set [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Recession [Using Data Specification *Data Spec Name*][P_Ref = *p_ref* |K = *k* |K_0 = *k_0* |N = *n* |Pressure = *pressure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>p_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_0</i>	real	undefined
<i>n</i>	real	undefined
<i>pressure</i>	"string"	undefined

Summary This model has been deprecated and removed from the code.

9.2.124. Advection

Scope: Equation System

Advection Disting For Level_Set [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Advection [Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary This model has been deprecated and removed from the code.

9.2.125. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Level_Set [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh
Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Scalar_String_Function [Using Data Specification *Data Spec Name*][F = f
]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.126. Vector String Function

Scope: Equation System

Vector String Function Rotated For Mesh_Colloc [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh
Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Vector_String_Function [Using Data Specification *Data Spec Name*][F_X =
f_x |F_Y = *f_y* |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.127. Kinematic

Scope: Equation System

Kinematic Rotated For Mesh_Colloc [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Kinematic [Using Data Specification *Data Spec Name*][*V0 = v0* |*Shared_Normal = shared_normal* |*No_Mesh_Movement = no_mesh_movement*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>v0</i>	real	undefined
<i>shared_normal</i>	"string"	undefined
<i>no_mesh_movement</i>	"string"	undefined

Summary Kinematic model for rotated collocated mesh boundary condition

9.2.128. No Slip

Scope: Equation System

No Slip Disting For Mesh [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= No_Slip [Using Data Specification *Data Spec Name*][*V0 = v0*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>vo</i>	real	undefined

Summary No slip model for mesh distinguishing condition

9.2.129. Vector String Function

Scope: Equation System

Vector String Function Disting For Mesh [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Vector_String_Function [Using Data Specification *Data Spec Name*][F_X = f_x |F_Y = f_y |F_Z = f_z]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
f_x	"string"	undefined
f_y	"string"	undefined
f_z	"string"	undefined

Summary Value from a string function

9.2.130. Vector String Function

Scope: Equation System

Vector String Function Flux For Mesh [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Vector_String_Function [Using Data Specification *Data Spec Name*][F_X = f_x |F_Y = f_y |F_Z = f_z]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.131. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfem_Continuity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*] [F = f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.132. Inflow

Scope: Equation System

Inflow Flux For Cvfem_Continuity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Inflow [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary IBP continuity inflow; nodal interp

9.2.133. Wall Function

Scope: Equation System

Wall Function Disting For Cvfem_Turbulence_Dissipation_Rate [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Wall_Function [Using Data Specification *Data Spec Name*] [*Wall_Friction_Factor* = *Wall_Friction_Factor* |*Wall_Velocity_X* = *Wall_Velocity_X* |*Wall_Velocity_Y* = *Wall_Velocity_Y* |*Wall_Velocity_Z* = *Wall_Velocity_Z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Wall_Friction_Factor</i>	real	undefined
<i>Wall_Velocity_X</i>	real	undefined
<i>Wall_Velocity_Y</i>	real	undefined
<i>Wall_Velocity_Z</i>	real	undefined

Summary CVFEM wall function turbulence dissipation rate distinguishing condition

9.2.134. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfem_Tke_Edge_Gradient_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*] [*F = f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.135. Simple Interp

Scope: Equation System

Simple Interp Flux For Cvfem_Tke_Edge_Gradient_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Simple_Interp [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary CVFEM edge-based projection simple interpolation flux BC

9.2.136. Simple Spring Force

Scope: Equation System

Simple Spring Force Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Simple_Spring_Force [Using Data Specification *Data Spec Name*] [$K_x = k_x$ | $K_y = k_y$ | $K_z = k_z$ | $X_0 = x_0$ | $Y_0 = y_0$ | $Z_0 = z_0$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>kx</i>	real	undefined
<i>ky</i>	real	undefined
<i>kz</i>	real	undefined
<i>xo</i>	real	undefined
<i>yo</i>	real	undefined
<i>zo</i>	real	undefined

Summary This model has been deprecated and removed from the code.

9.2.137. Wall Function

Scope: Equation System

```

Wall Function Disting For Hfem_Turbulent_Kinetic_Energy [ {of|species|
subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|
over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing
OpposingMeshExtent ]= Wall_Function [ Using Data Specification Data Spec
Name ][ Scale_Factor = scale_factor |Wall_Friction_Factor =
Wall_Friction_Factor |Wall_Velocity_X = Wall_Velocity_X |Wall_Velocity_Y =
Wall_Velocity_Y |Wall_Velocity_Z = Wall_Velocity_Z ]

```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>scale_factor</i>	real	undefined
<i>Wall_Friction_Factor</i>	real	undefined
<i>Wall_Velocity_X</i>	real	undefined
<i>Wall_Velocity_Y</i>	real	undefined
<i>Wall_Velocity_Z</i>	real	undefined

Summary HFEM wall function turbulent kinetic energy distinguishing condition

9.2.138. Open Adv Flow

Scope: Equation System

Open Adv Flow Flux For Hfem_Specific_Dissipation_Rate [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Open_Adv_Flow [Using Data Specification *Data Spec Name*] [Pressure = *pressure* |Total_Pressure = *total_pressure* |Value = *value* |Far_Field_Entrainment_Value = *far_field_entrainment_value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined
<i>value</i>	real	undefined
<i>far_field_entrainment_value</i>	real	undefined

Summary HFEM specific dissipation rate open advective flow flux BC

9.2.139. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Hfem_Specific_Dissipation_Rate [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*] [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.140. Open

Scope: Equation System

Open Flux For Mass_Balance [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Open [Using Data Specification *Data Spec Name*] [Pressure = *pressure* |Entrained_Value = *entrained_value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>entrained_value</i>	real	undefined

9.2.141. Well Outflow

Scope: Equation System

Well Outflow Flux For Mass_Balance [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Well_Outflow [Using Data Specification *Data Spec Name*] [Pi = *pi* |Pref = *pref*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pi</i>	"string"	undefined
<i>pref</i>	"string"	undefined

9.2.142. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Mass_Balance [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=

Scalar_String_Function [Using Data Specification *Data Spec Name*][$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.143. Constant Velocity

Scope: Equation System

Constant Velocity Flux For Mass_Balance [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Constant_Velocity [Using Data Specification *Data Spec Name*][Mult = *Mult*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Mult</i>	real	undefined

9.2.144. Convective Outflow

Scope: Equation System

Convective Outflow Flux For Mass_Balance [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Convective_Outflow [Using Data Specification *Data Spec Name*][Ref_Frac = *ref_frac*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>ref_frac</i>	real	undefined

9.2.145. Co2 Convective Outflow

Scope: Equation System

Co2 Convective Outflow Flux For Mass_Balance [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
Co2_Convective_Outflow [Using Data Specification *Data Spec Name*] [
Ref_Frac = *ref_frac*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>ref_frac</i>	real	undefined

9.2.146. Open Flow

Scope: Equation System

Open Flow Flux For Mass_Balance [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Open_Flow [
Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

9.2.147. Mass Open

Scope: Equation System

Mass Open Flux For Mass_Balance [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Mass_Open [Using Data Specification *Data Spec Name*][Pressure = *pressure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined

9.2.148. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Current [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.149. Open Flow

Scope: Equation System

Open Flow Flux For Porous_Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Open_Flow [Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

9.2.150. Scalar String Function

Scope: Equation System

Scalar String Function Fluxbp For Continuity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*
]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.151. Electric Traction

Scope: Equation System

Electric Traction Flux For Solid [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Electric_Traction [Using Data Specification *Data Spec Name*][Sign = *sign*
]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>sign</i>	real	undefined

Summary Electric traction solid flux

9.2.152. Constant Traction

Scope: Equation System

Constant Traction Flux For Solid [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Constant_Traction [Using Data Specification *Data Spec Name*][X = x |Y = y |Z = z]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
x	"string"	undefined
y	"string"	undefined
z	"string"	undefined

Summary Constant traction solid flux

9.2.153. Transient Traction

Scope: Equation System

Transient Traction Flux For Solid [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Transient_Traction [Using Data Specification *Data Spec Name*][A_X = a_x | A_Y = a_y |A_Z = a_z |B_X = b_x |B_Y = b_y |B_Z = b_z]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>a_x</i>	real	undefined
<i>a_y</i>	real	undefined
<i>a_z</i>	real	undefined
<i>b_x</i>	real	undefined
<i>b_y</i>	real	undefined
<i>b_z</i>	real	undefined

Summary Transient traction solid flux

9.2.154. Pressure User Function

Scope: Equation System

```
Pressure User Function Flux For Solid [ {of|species|subindex} Species |{in
|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Pressure_User_Function [ Using Data Specification Data Spec Name ][ Name =
name |X = x |X_Multiplier = x_multiplier |Multiplier = multiplier |Toggle
= toggle ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>name</i>	"string"	undefined
<i>x</i>	"string"	undefined
<i>x_multiplier</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>toggle</i>	"string"	undefined

Summary Pressure user function solid flux

9.2.155. Spring Force

Scope: Equation System

Spring Force Flux For Solid [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Spring_Force [Using Data Specification *Data Spec Name*][Mult = *Mult*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Mult</i>	real	undefined

Summary Spring force solid flux

9.2.156. Shear Free

Scope: Equation System

Shear Free Flux For Solid [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Shear_Free [Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Shear-free traction solid flux

9.2.157. Capillary Force

Scope: Equation System

Capillary Force Flux For Lumped_Div_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Capillary_Force [Using Data Specification *Data Spec Name*][Theta = *theta*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>theta</i>	real	undefined

Summary This model has been deprecated and removed from the code.

9.2.158. Curvature

Scope: Equation System

Curvature Flux For Lumped_Div_Projection [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Curvature [Using Data Specification *Data Spec Name*][Theta = *theta*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>theta</i>	real	undefined

Summary This model has been deprecated and removed from the code.

9.2.159. Vector String Function

Scope: Equation System

Vector String Function Flux For Lumped_Div_Projection [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Vector_String_Function [Using Data Specification *Data Spec Name*][F_X = *f_x* |F_Y = *f_y* |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.160. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfem_Pressure_Edge_Gradient_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*] = Scalar_String_Function [Using Data Specification *Data Spec Name*] [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.161. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Enthalpy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*] = Scalar_String_Function [Using Data Specification *Data Spec Name*] [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.162. Rad

Scope: Equation System

Rad Flux For Enthalpy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Rad [Using Data Specification *Data Spec Name*][*T_Ref = t_ref* |*Crad = crad*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>crad</i>	real	undefined

Summary Radiative energy flux defined with constant models for emissivity, form factor and reference temperature

9.2.163. Latent Heat

Scope: Equation System

Latent Heat Flux For Enthalpy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Latent_Heat [Using Data Specification *Data Spec Name*][*Yinf = Yinf*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Yinf</i>	real	undefined

Summary Latent heat enthalpy flux

9.2.164. Nat Conv

Scope: Equation System

Nat Conv Flux For Enthalpy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Nat_Conv [Using Data Specification *Data Spec Name*][H = *h* |T_Ref = *t_ref*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>h</i>	real	undefined
<i>t_ref</i>	real	undefined

Summary Natural convection BC for enthalpy flux

9.2.165. Kinematic

Scope: Equation System

Kinematic Disting For Solid_Y [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Kinematic [Using Data Specification *Data Spec Name*][V0 = *v0* |Shared_Normal = *shared_normal* |No_Mesh_Movement = *no_mesh_movement*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>vo</i>	real	undefined
<i>shared_normal</i>	"string"	undefined
<i>no_mesh_movement</i>	"string"	undefined

Summary Kinematic model for SOLID_y distinguishing condition

9.2.166. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Solid_Y [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*][F = f
]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.167. Pyrolysis

Scope: Equation System

Pyrolysis Disting For Solid_Y [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Pyrolysis [Using Data Specification *Data Spec Name*][T_Ref = *t_ref* |K = *k* |K_0 = *k_0* |N = *n* |Temperature = *temperature*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_o</i>	real	undefined
<i>n</i>	real	undefined
<i>temperature</i>	"string"	undefined

Summary Pyrolysis model for SOLID_y distinguishing condition

9.2.168. Recession

Scope: Equation System

Recession Disting For Solid_Y [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Recession [Using Data Specification *Data Spec Name*][T_Ref = *t_ref* |K = *k* |K_0 = *k_o* |N = *n* |Temperature = *temperature*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_o</i>	real	undefined
<i>n</i>	real	undefined
<i>temperature</i>	"string"	undefined

Summary Recession model for SOLID_x distinguishing condition

9.2.169. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Cvfm_Specific_Dissipation_Rate [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|

in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= *Scalar_String_Function* [*Using Data Specification Data Spec Name*] [*F = f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.170. Wall Function

Scope: Equation System

Wall Function Disting For Cvfem_Specific_Dissipation_Rate [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= *Wall_Function* [*Using Data Specification Data Spec Name*] [*Wall_Friction_Factor = Wall_Friction_Factor* |*Wall_Velocity_X = Wall_Velocity_X* |*Wall_Velocity_Y = Wall_Velocity_Y* |*Wall_Velocity_Z = Wall_Velocity_Z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Wall_Friction_Factor</i>	real	undefined
<i>Wall_Velocity_X</i>	real	undefined
<i>Wall_Velocity_Y</i>	real	undefined
<i>Wall_Velocity_Z</i>	real	undefined

Summary CVFEM specific dissipation rate distinguishing condition

9.2.171. Low Reynolds

Scope: Equation System

Low Reynolds Disting For Cvfem_Specific_Dissipation_Rate [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Low_Reynolds [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

9.2.172. Recession

Scope: Equation System

Recession Disting For Extension_Speed [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Recession [Using Data Specification *Data Spec Name*] [T_Ref = *t_ref* |K = *k* |K_0 = *k_0* |N = *n* |Temperature = *temperature*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_0</i>	real	undefined
<i>n</i>	real	undefined
<i>temperature</i>	"string"	undefined

Summary Advection model for extension speed distinguishing condition

9.2.173. Pyrolysis

Scope: Equation System

Pyrolysis Disting For Extension_Speed [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Pyrolysis [

Using Data Specification *Data Spec Name* [T_Ref = *t_ref* | K = *k* | K_0 = *k_0*
| N = *n* | Temperature = *temperature*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_o</i>	real	undefined
<i>n</i>	real	undefined
<i>temperature</i>	"string"	undefined

Summary Pyrolysis model for extension speed distinguishing condition

9.2.174. Lens Deposition

Scope: Equation System

Lens Deposition Disting For Extension_Speed [{of|species|subindex} *Species*
| {in|material_phase} *MaterialPhase*] {@|at|for|in|on|over} *Mesh Extent*
Name [Touching *TouchingMeshExtent* | Opposing *OpposingMeshExtent*] =
Lens_Deposition [Using Data Specification *Data Spec Name*] [Src_X = *src_x*
| Dir_X = *dir_x* | Vel_X = *vel_x* | Src_Y = *src_y* | Dir_Y = *dir_y* | Vel_Y =
vel_y | Src_Z = *src_z* | Dir_Z = *dir_z* | Vel_Z = *vel_z* | Massflowrate =
massFlowRate | Particledensity = *particleDensity* | Radius = *radius* | T_Liq =
T_liq | T_Solid = *T_solid* | T_On = *t_on* | T_Off = *t_off*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>src_x</i>	real	undefined
<i>dir_x</i>	real	undefined
<i>vel_x</i>	real	undefined
<i>src_y</i>	real	undefined
<i>dir_y</i>	real	undefined
<i>vel_y</i>	real	undefined
<i>src_z</i>	real	undefined
<i>dir_z</i>	real	undefined
<i>vel_z</i>	real	undefined
<i>massFlowRate</i>	real	undefined
<i>particleDensity</i>	real	undefined
<i>radius</i>	real	undefined
<i>T_liq</i>	real	undefined
<i>T_solid</i>	real	undefined
<i>t_on</i>	real	undefined
<i>t_off</i>	real	undefined

Summary LENS Deposition mass source model for extension speed distinguishing condition

9.2.175. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Extension_Speed [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*][F = f
]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.176. Advection

Scope: Equation System

Advection Disting For Extension_Speed [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Advection [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary This model has been deprecated and removed from the code.

9.2.177. Solidification

Scope: Equation System

Solidification Disting For Extension_Speed [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Solidification [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Solidification model for extension speed distinguishing condition

9.2.178. Melting

Scope: Equation System

Melting Disting For Extension_Speed [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Melting [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Melting model for extension speed distinguishing condition

9.2.179. Mixed

Scope: Equation System

Mixed Flux For Spherical_Harmonic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Mixed [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Applies the MIXED scalar flux from the spherical harmonic equations.

9.2.180. Calore User Sub

Scope: Equation System

Calore User Sub Flux For Spherical_Harmonic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Calore_User_Sub [Using Data Specification *Data Spec Name*] [Name = *name* | Type = *type* | Multiplier = *multiplier* | Material_Data_Block = *material_data_block* | Data = *data* | Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

9.2.181. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Spherical_Harmonic [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*] [F = f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.182. Porous Robin One Region

Scope: Equation System

Porous Robin One Region Flux For Cvfem_Continuity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
 Porous_Robin_One_Region [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Boundary condition for loose coupling of continuity to a free fluid region

9.2.183. Interface

Scope: Equation System

```
Interface Flux For Cvfem_Continuity [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Interface [
Using Data Specification Data Spec Name ] [ ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary INTERFACE CVFEM continuity flux

9.2.184. Fluid Solid Convection Coupled

Scope: Equation System

```
Fluid Solid Convection Coupled Flux For Porous_Enthalpy [ {of|species|
subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|
over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing
OpposingMeshExtent ]= Fluid_Solid_Convection_Coupled [ Using Data
Specification Data Spec Name ] [ Multiplier = multiplier |
Fluid_Temperature_Field = fluid_temperature_field ]
```


Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>fluid_temperature_field</i>	"string"	undefined

Summary Boundary condition for loose coupling of enthalpy to a free fluid region

9.2.185. Fluid Robin Coupled With Solid Convection

Scope: Equation System

```
Fluid Robin Coupled With Solid Convection Flux For Porous_Enthalpy [ {of|
species|subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|
in|on|over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing
OpposingMeshExtent ]= Fluid_Robin_Coupled_With_Solid_Convection [ Using
Data Specification Data Spec Name ][ Enthalpy_Field = enthalpy_field |
Enthalpy_Diffusive_Flux_Field = enthalpy_diffusive_flux_field |Coeff_Field
= coeff_field ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>enthalpy_field</i>	"string"	undefined
<i>enthalpy_diffusive_flux_field</i>	"string"	undefined
<i>coeff_field</i>	"string"	undefined

Summary Boundary condition for loose coupling of enthalpy to a free fluid region

9.2.186. Simple Inflow

Scope: Equation System

```
Simple Inflow Flux For Cvfem_Continuity [ {of|species|subindex} Species |
{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name
[ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Simple_Inflow
[ Using Data Specification Data Spec Name ][ Value = value |Density =
```

Density | *Velocity_X* = *Velocity_X* | *Velocity_Y* = *Velocity_Y* | *Velocity_Z* = *Velocity_Z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>value</i>	real	undefined
<i>Density</i>	real	undefined
<i>Velocity_X</i>	real	undefined
<i>Velocity_Y</i>	real	undefined
<i>Velocity_Z</i>	real	undefined

Summary IBP continuity inflow; specified dens and u

9.2.187. Convective Outflow

Scope: Equation System

Convective Outflow Flux For Porous_Enthalpy [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* | *Opposing OpposingMeshExtent*] = Convective_Outflow [Using Data Specification *Data Spec Name*] [Ref_H = *ref_h*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>ref_h</i>	real	undefined

9.2.188. Open

Scope: Equation System

Open Flux For Porous_Enthalpy [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* | *Opposing OpposingMeshExtent*] = Open [Using Data Specification *Data Spec Name*] [Pressure = *pressure* | Entrained_Value = *entrained_value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>entrained_value</i>	real	undefined

9.2.189. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Porous_Enthalpy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*] = Scalar_String_Function [Using Data Specification *Data Spec Name*][*F = f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.190. Generalized Nat Conv

Scope: Equation System

Generalized Nat Conv Flux For Porous_Enthalpy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*] = Generalized_Nat_Conv [Using Data Specification *Data Spec Name*][Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>multiplier</i>	real	undefined

Summary Generalized natural convection flux BC

9.2.191. Fluid Robin Coupled

Scope: Equation System

```
Fluid Robin Coupled Flux For Porous_Enthalpy [ {of|species|subindex}
Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh
Extent Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Fluid_Robin_Coupled [ Using Data Specification Data Spec Name ][
Enthalpy_Field = enthalpy_field |Enthalpy_Diffusive_Flux_Field =
enthalpy_diffusive_flux_field |Coeff_Field = coeff_field ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>enthalpy_field</i>	"string"	undefined
<i>enthalpy_diffusive_flux_field</i>	"string"	undefined
<i>coeff_field</i>	"string"	undefined

Summary Boundary condition for loose coupling of enthalpy to a free fluid region

9.2.192. One Temp Multiphase Open

Scope: Equation System

```
One Temp Multiphase Open Flux For Porous_Enthalpy [ {of|species|subindex}
Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh
Extent Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
One_Temp_Multiphase_Open [ Using Data Specification Data Spec Name ][
Pressure = pressure |Entrained_Value = entrained_value ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>entrained_value</i>	real	undefined

9.2.193. User Vector Field

Scope: Equation System

```
User Vector Field Flux For Porous_Enthalpy [ {of|species|subindex} Species
|{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent
Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
User_Vector_Field [ Using Data Specification Data Spec Name ][ Name = name
|Multiplier = multiplier ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>name</i>	"string"	undefined
<i>multiplier</i>	real	undefined

Summary User vector field enthalpy flux

9.2.194. Masked Nat Conv

Scope: Equation System

```
Masked Nat Conv Flux For Energy [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Masked_Nat_Conv
[ Using Data Specification Data Spec Name ][ Power_Output = power_output |
Flux_Output = flux_output |Toggle = toggle |Multiplier = multiplier |
Masking_Field = masking_field |Scaling = scaling |Threshold = threshold
]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>masking_field</i>	"string"	undefined
<i>scaling</i>	real	undefined
<i>threshold</i>	real	undefined

Summary Masked natural convection energy flux

9.2.195. Fortran

Scope: Equation System

```
Fortran Flux For Energy [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Fortran [ Using
Data Specification Data Spec Name ][ Power_Output = power_output |
Flux_Output = flux_output |Toggle = toggle |Multiplier = multiplier |
Sub_Name = sub_name |Real_Data = real_data |Int_Data = int_data |
Resource_Name = resource_name |Data = data ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>sub_name</i>	"string"	undefined
<i>real_data</i>	"string"	undefined
<i>int_data</i>	"string"	undefined
<i>resource_name</i>	"string"	undefined
<i>data</i>	"string"	undefined

Summary Fortran subroutine energy flux

9.2.196. Vapor Cooling

Scope: Equation System

Vapor Cooling Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Vapor_Cooling [Using Data Specification *Data Spec Name*][Power_Output = *power_output* | Flux_Output = *flux_output* |Toggle = *toggle* |Tboil = *tboil*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>tboil</i>	real	undefined

Summary Vapor cooling energy flux

9.2.197. Exponential Vapor Cooling

Scope: Equation System

Exponential Vapor Cooling Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Exponential_Vapor_Cooling [Using Data Specification *Data Spec Name*][Power_Output = *power_output* |Flux_Output = *flux_output* |Toggle = *toggle* | Tboil = *tboil* |L = *l* |Pa = *pa* |Mw = *mw* |Alpha = *alpha*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>tboil</i>	real	undefined
<i>l</i>	real	undefined
<i>pa</i>	real	undefined
<i>mw</i>	real	undefined
<i>alpha</i>	real	undefined

Summary Exponential vapor cooling energy flux

9.2.198. Latent Heat

Scope: Equation System

Latent Heat Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Latent_Heat [Using Data Specification *Data Spec Name*] [Power_Output = *power_output* | Flux_Output = *flux_output* |Toggle = *toggle* |Yinf = *Yinf*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>Yinf</i>	real	undefined

Summary Latent heat energy flux

9.2.199. Scaled Nat Conv

Scope: Equation System

Scaled Nat Conv Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scaled_Nat_Conv [Using Data Specification *Data Spec Name*][Power_Output = *power_output* | Flux_Output = *flux_output* |Toggle = *toggle* |Multiplier = *multiplier* | Scaling_Field = *scaling_field* |Scaling = *scaling* |Global_Var = *global_var* |Time_Function = *time_function*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>scaling_field</i>	"string"	undefined
<i>scaling</i>	real	undefined
<i>global_var</i>	"string"	undefined
<i>time_function</i>	"string"	undefined

Summary Scaled natural convection energy flux

9.2.200. Generalized Nat Conv

Scope: Equation System

Generalized Nat Conv Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Generalized_Nat_Conv [Using Data Specification *Data Spec Name*][Power_Output = *power_output* |Flux_Output = *flux_output* |Toggle = *toggle* | Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>multiplier</i>	real	undefined

Summary Generalized natural convection energy flux

9.2.201. User Vector Field

Scope: Equation System

User Vector Field Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
User_Vector_Field [Using Data Specification *Data Spec Name*][Power_Output
= *power_output* |Flux_Output = *flux_output* |Toggle = *toggle* |Name = *name* |
Multiplier = *multiplier* |Scaling = *scaling* |Global_Var = *global_var* |
Time_Function = *time_function*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>name</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>scaling</i>	real	undefined
<i>global_var</i>	"string"	undefined
<i>time_function</i>	"string"	undefined

Summary User vector field energy flux

9.2.202. User Vector Field Influx

Scope: Equation System

```
User Vector Field Influx Flux For Energy [ {of|species|subindex} Species |
{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name
[ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
User_Vector_Field_Influx [ Using Data Specification Data Spec Name ][
Power_Output = power_output |Flux_Output = flux_output |Toggle = toggle |
Name = name |Multiplier = multiplier |Scaling = scaling |Global_Var =
global_var |Time_Function = time_function ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>name</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>scaling</i>	real	undefined
<i>global_var</i>	"string"	undefined
<i>time_function</i>	"string"	undefined

Summary User vector field influx energy flux

9.2.203. Lens

Scope: Equation System

```
Lens Flux For Energy [ {of|species|subindex} Species |{in|material_phase}
MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [ Touching
TouchingMeshExtent |Opposing OpposingMeshExtent ]= Lens [ Using Data
Specification Data Spec Name ][ Power_Output = power_output |Flux_Output =
flux_output |Toggle = toggle |Src_X = src_x |Dir_X = dir_x |Vel_X = vel_x
|Src_Y = src_y |Dir_Y = dir_y |Vel_Y = vel_y |Src_Z = src_z |Dir_Z =
dir_z |Vel_Z = vel_z |Massflowrate = massFlowRate |Particlesspeed =
particleSpeed |Particledensity = particleDensity |Masssourceradius =
massSourceRadius |T_Liq = T_liq |T_Solid = T_solid |Particletemperature =
particleTemperature |T_On = t_on |T_Off = t_off ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>src_x</i>	real	undefined
<i>dir_x</i>	real	undefined
<i>vel_x</i>	real	undefined
<i>src_y</i>	real	undefined
<i>dir_y</i>	real	undefined
<i>vel_y</i>	real	undefined
<i>src_z</i>	real	undefined
<i>dir_z</i>	real	undefined
<i>vel_z</i>	real	undefined
<i>massFlowRate</i>	real	undefined
<i>particleSpeed</i>	real	undefined
<i>particleDensity</i>	real	undefined
<i>massSourceRadius</i>	real	undefined
<i>T_liq</i>	real	undefined
<i>T_solid</i>	real	undefined
<i>particleTemperature</i>	real	undefined
<i>t_on</i>	real	undefined
<i>t_off</i>	real	undefined

9.2.204. Thermal Latent Heat

Scope: Equation System

```

Thermal Latent Heat Flux For Energy [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Thermal_Latent_Heat [ Using Data Specification Data Spec Name ][
Power_Output = power_output |Flux_Output = flux_output |Toggle = toggle
]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined

Summary Thermal latent heat energy flux

9.2.205. Generalized Nat Conv

Scope: Equation System

Generalized Nat Conv No_Coverage_Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Generalized_Nat_Conv [Using Data Specification *Data Spec Name*] [
Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>multiplier</i>	real	undefined

Summary Generalized natural convection energy flux

9.2.206. Rad

Scope: Equation System

Rad Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Rad [Using Data Specification *Data Spec Name*] [Power_Output = *power_output* |Flux_Output = *flux_output* |Toggle = *toggle* |T_Ref = *t_ref* |Crad = *crad*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>t_ref</i>	real	undefined
<i>crad</i>	real	undefined

Summary Radiative energy flux defined with constant models for emissivity, form factor and reference temperature

9.2.207. Generalized Rad

Scope: Equation System

Generalized Rad Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Generalized_Rad [Using Data Specification *Data Spec Name*][Power_Output = *power_output* | Flux_Output = *flux_output* |Toggle = *toggle* |Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>multiplier</i>	real	undefined

Summary Radiative energy flux, possibly defined with different models for emissivity, form factor and irradiation

9.2.208. Sharp Line Weld

Scope: Equation System

Sharp Line Weld Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Sharp_Line_Weld [Using Data Specification *Data Spec Name*][Power_Output = *power_output* | Flux_Output = *flux_output* |Toggle = *toggle* |Src_X = *src_x* |Dir_X = *dir_x* |Vel_X = *vel_x* |Src_Y = *src_y* |Dir_Y = *dir_y* |Vel_Y = *vel_y* |Src_Z = *src_z* |Dir_Z = *dir_z* |Vel_Z = *vel_z* |R = *r* |T_On = *t_on* |T_Off = *t_off* |Flux = *flux* |Alpha = *alpha* |Depth_Enhanced_Absorption_Data = *depth_enhanced_absorption_data* |Compute_Visibility_Field = *compute_visibility_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>src_x</i>	real	undefined
<i>dir_x</i>	real	undefined
<i>vel_x</i>	real	undefined
<i>src_y</i>	real	undefined
<i>dir_y</i>	real	undefined
<i>vel_y</i>	real	undefined
<i>src_z</i>	real	undefined
<i>dir_z</i>	real	undefined
<i>vel_z</i>	real	undefined
<i>r</i>	real	undefined
<i>t_on</i>	real	undefined
<i>t_off</i>	real	undefined
<i>flux</i>	real	undefined
<i>alpha</i>	real	undefined
<i>depth_enhanced_absorption_data</i>	"string"	undefined
<i>compute_visibility_field</i>	"string"	undefined

9.2.209. Sharp Spot Weld

Scope: Equation System

Sharp Spot Weld Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Sharp_Spot_Weld

```
[ Using Data Specification Data Spec Name ][ Power_Output = power_output |
Flux_Output = flux_output |Toggle = toggle |Src_X = src_x |Dir_X = dir_x
|Src_Y = src_y |Dir_Y = dir_y |Src_Z = src_z |Dir_Z = dir_z |R = r |T_On
= t_on |T_Off = t_off |Flux = flux ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>src_x</i>	real	undefined
<i>dir_x</i>	real	undefined
<i>src_y</i>	real	undefined
<i>dir_y</i>	real	undefined
<i>src_z</i>	real	undefined
<i>dir_z</i>	real	undefined
<i>r</i>	real	undefined
<i>t_on</i>	real	undefined
<i>t_off</i>	real	undefined
<i>flux</i>	real	undefined

9.2.210. Laser Weld

Scope: Equation System

```
Laser Weld Flux For Energy [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Laser_Weld [
Using Data Specification Data Spec Name ][ Power_Output = power_output |
Flux_Output = flux_output |Toggle = toggle |Flux = flux |R = r |
Normal_Tolerance = normal_tolerance |Path_Function = path_function ]
```


Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>flux</i>	real	undefined
<i>r</i>	real	undefined
<i>normal_tolerance</i>	real	undefined
<i>path_function</i>	"string"	undefined

9.2.211. Gaussian Spot Weld

Scope: Equation System

```
Gaussian Spot Weld Flux For Energy [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Gaussian_Spot_Weld [ Using Data Specification Data Spec Name ][
Power_Output = power_output |Flux_Output = flux_output |Toggle = toggle |
Src_X = src_x |Dir_X = dir_x |Src_Y = src_y |Dir_Y = dir_y |Src_Z = src_z
|Dir_Z = dir_z |R = r |T_On = t_on |T_Off = t_off |Flux = flux |R_Eff =
r_eff |Alpha = alpha |Depth_Enhanced_Absorption_Data =
depth_enhanced_absorption_data |Compute_Visibility_Field =
compute_visibility_field ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>src_x</i>	real	undefined
<i>dir_x</i>	real	undefined
<i>src_y</i>	real	undefined
<i>dir_y</i>	real	undefined
<i>src_z</i>	real	undefined
<i>dir_z</i>	real	undefined
<i>r</i>	real	undefined
<i>t_on</i>	real	undefined
<i>t_off</i>	real	undefined
<i>flux</i>	real	undefined
<i>r_eff</i>	real	undefined
<i>alpha</i>	real	undefined
<i>depth_enhanced_absorption_data</i>	"string"	undefined
<i>compute_visibility_field</i>	"string"	undefined

9.2.212. Gaussian Spot Power Weld

Scope: Equation System

```

Gaussian Spot Power Weld Flux For Energy [ {of|species|subindex} Species |
{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name
[ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Gaussian_Spot_Power_Weld [ Using Data Specification Data Spec Name ][
Power_Output = power_output |Flux_Output = flux_output |Toggle = toggle |
Src_X = src_x |Dir_X = dir_x |Src_Y = src_y |Dir_Y = dir_y |Src_Z = src_z
|Dir_Z = dir_z |R = r |T_On = t_on |T_Off = t_off |R_Eff = r_eff |Alpha
= alpha |Depth_Enhanced_Absorption_Data = depth_enhanced_absorption_data |
Compute_Visibility_Field = compute_visibility_field ]

```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>src_x</i>	real	undefined
<i>dir_x</i>	real	undefined
<i>src_y</i>	real	undefined
<i>dir_y</i>	real	undefined
<i>src_z</i>	real	undefined
<i>dir_z</i>	real	undefined
<i>r</i>	real	undefined
<i>t_on</i>	real	undefined
<i>t_off</i>	real	undefined
<i>r_eff</i>	real	undefined
<i>alpha</i>	real	undefined
<i>depth_enhanced_absorption_data</i>	string	undefined
<i>compute_visibility_field</i>	"string"	undefined

9.2.213. Pyrolysis

Scope: Equation System

Pyrolysis Disting For Solid_Z [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Pyrolysis [Using Data Specification *Data Spec Name*][T_Ref = *t_ref* |K = *k* |K_0 = *k_0* |N = *n* |Temperature = *temperature*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_o</i>	real	undefined
<i>n</i>	real	undefined
<i>temperature</i>	"string"	undefined

Summary Pyrolysis model for SOLID_z distinguishing condition

9.2.214. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Momentum_X [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh
Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Scalar_String_Function [Using Data Specification *Data Spec Name*][F = f
]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.215. Simple Inflow

Scope: Equation System

Simple Inflow Flux For Cvfem_Solvent_Continuity [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh
Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Simple_Inflow [Using Data Specification *Data Spec Name*][Value = *value* |
Density = *Density* |Velocity_X = *Velocity_X* |Velocity_Y = *Velocity_Y* |
Velocity_Z = *Velocity_Z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>value</i>	real	undefined
<i>Density</i>	real	undefined
<i>Velocity_X</i>	real	undefined
<i>Velocity_Y</i>	real	undefined
<i>Velocity_Z</i>	real	undefined

Summary Inflow mass flux for continuity equation; specified density and velocity

9.2.216. Inflow

Scope: Equation System

Inflow Flux For Cvfem_Solvent_Continuity [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Inflow [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Inflow mass flux for continuity equation; nodal interpolation

9.2.217. Open Flow

Scope: Equation System

Open Flow Flux For Cvfem_Solvent_Continuity [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Open_Flow [Using Data Specification *Data Spec Name*] [Pressure = *pressure* | Total_Pressure = *total_pressure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined

Summary Open bc for continuity

9.2.218. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfem_Solvent_Continuity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.219. From Temperature

Scope: Equation System

From Temperature Disting For Cvfem_Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= From_Temperature [Using Data Specification *Data Spec Name*][Variable = *variable* |Order = *order* |Variable_Offset = *variable_offset* |C0 = *c0* |C1 = *c1* |C2 = *c2* |C3 = *c3* |C4 = *c4* |C5 = *c5* |C6 = *c6* |C7 = *c7* |C8 = *c8* | Value = *value* |T = *t* |Poffset = *poffset*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>variable</i>	"string"	undefined
<i>order</i>	integer	undefined
<i>variable_offset</i>	real	undefined
<i>c0</i>	real	undefined
<i>c1</i>	real	undefined
<i>c2</i>	real	undefined
<i>c3</i>	real	undefined
<i>c4</i>	real	undefined
<i>c5</i>	real	undefined
<i>c6</i>	real	undefined
<i>c7</i>	real	undefined
<i>c8</i>	real	undefined
<i>value</i>	real	undefined
<i>t</i>	real	undefined
<i>poffset</i>	real	undefined

Summary From temperature distinguishing condition for CVFEM energy equation

9.2.220. From Cht Temperature

Scope: Equation System

```

From Cht Temperature Disting For Cvfem_Energy [ {of|species|subindex}
Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh
Extent Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
From_Cht_Temperature [ Using Data Specification Data Spec Name ][
Twall_Field = Twall_Field |Variable = variable |Order = order |
Variable_Offset = variable_offset |C0 = c0 |C1 = c1 |C2 = c2 |C3 = c3 |
C4 = c4 |C5 = c5 |C6 = c6 |C7 = c7 |C8 = c8 |Poffset = poffset ]

```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Twall_Field</i>	"string"	undefined
<i>variable</i>	"string"	undefined
<i>order</i>	integer	undefined
<i>variable_offset</i>	real	undefined
<i>c0</i>	real	undefined
<i>c1</i>	real	undefined
<i>c2</i>	real	undefined
<i>c3</i>	real	undefined
<i>c4</i>	real	undefined
<i>c5</i>	real	undefined
<i>c6</i>	real	undefined
<i>c7</i>	real	undefined
<i>c8</i>	real	undefined
<i>poffset</i>	real	undefined

Summary CVFEM energy distinguishing condition from CHT temperature using Cantera

9.2.221. Open Flow

Scope: Equation System

```
Open Flow Flux For Cvfem_Continuity [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Open_Flow [
Using Data Specification Data Spec Name ][ Pressure = pressure |
Total_Pressure = total_pressure ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined

Summary Open bc for continuity

9.2.222. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Momentum_Z [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.223. No Slip

Scope: Equation System

No Slip Disting For Cvfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= No_Slip [Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary No slip model for momentum distinguishing condition

9.2.224. Porous Robin Interface

Scope: Equation System

Porous Robin Interface Disting For Cvfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=

Porous_Robin_Interface [Using Data Specification *Data Spec Name*][Alpha = *alpha* | Permeability_Field = *permeability_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>alpha</i>	real	undefined
<i>permeability_field</i>	"string"	undefined

Summary No slip model for momentum distinguishing condition

9.2.225. Porous Robin One Region

Scope: Equation System

Porous Robin One Region Disting For Cvfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Porous_Robin_One_Region [Using Data Specification *Data Spec Name*][Alpha = *alpha*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>alpha</i>	real	undefined

Summary No slip model for momentum distinguishing condition

9.2.226. Vector String Function

Scope: Equation System

Vector String Function Fluxbp For Cvfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Vector_String_Function [Using Data Specification *Data Spec Name*][F_X = *f_x* |F_Y = *f_y* |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.227. Capillary

Scope: Equation System

Capillary Fluxbp For Cvfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Capillary [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Momentum capillary flux BP BC

9.2.228. Ls Capillary

Scope: Equation System

Ls Capillary Fluxbp For Cvfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Ls_Capillary [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Momentum capillary flux BP BC using level set normal

9.2.229. Capillary Stabilization

Scope: Equation System

Capillary Stabilization Fluxbp For Cvfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*] = Capillary_Stabilization [Using Data Specification *Data Spec Name*] [*Mu0 = mu0* |*Multiplier = multiplier* |*Use_Velocity_Correction = use_velocity_correction*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>mu0</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>use_velocity_correction</i>	integer	undefined

Summary Momentum capillary stabilization flux BP BC

9.2.230. Open Adv Flow

Scope: Equation System

Open Adv Flow Flux For Cvfem_Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*] = Open_Adv_Flow [Using Data Specification *Data Spec Name*] [*Data = data* | *Far_Field_Entrainment_Value = Far_Field_Entrainment_Value* |*Pressure = pressure* |*Total_Pressure = total_pressure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>data</i>	"string"	undefined
<i>Far_Field_Entrainment_Value</i>	real	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined

Summary CVFEM energy open advective flow flux

9.2.231. Open Adv Flow From Temperature

Scope: Equation System

```
Open Adv Flow From Temperature Flux For Cvfem_Energy [ {of|species|
subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|
over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing
OpposingMeshExtent ]= Open_Adv_Flow_From_Temperature [ Using Data
Specification Data Spec Name ][ Data = data |Temperature = temperature |
Pressure = pressure |Mass_Fraction_0 = mass_fraction_0 |Mass_Fraction_1 =
mass_fraction_1 |Mass_Fraction_2 = mass_fraction_2 |Mass_Fraction_3 =
mass_fraction_3 |Mass_Fraction_4 = mass_fraction_4 |Mass_Fraction_5 =
mass_fraction_5 |Mass_Fraction_6 = mass_fraction_6 |Mass_Fraction_7 =
mass_fraction_7 |Mass_Fraction_8 = mass_fraction_8 |Total_Pressure =
total_pressure ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>data</i>	"string"	undefined
<i>temperature</i>	real	undefined
<i>pressure</i>	real	undefined
<i>mass_fraction_0</i>	real	undefined
<i>mass_fraction_1</i>	real	undefined
<i>mass_fraction_2</i>	real	undefined
<i>mass_fraction_3</i>	real	undefined
<i>mass_fraction_4</i>	real	undefined
<i>mass_fraction_5</i>	real	undefined
<i>mass_fraction_6</i>	real	undefined
<i>mass_fraction_7</i>	real	undefined
<i>mass_fraction_8</i>	real	undefined
<i>total_pressure</i>	real	undefined

Summary CVFEM energy open advective flow from temperature flux

9.2.232. Generalized Rad

Scope: Equation System

Generalized Rad Flux For Cvfem_Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Generalized_Rad [Using Data Specification *Data Spec Name*][*Data* = *data* |Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>data</i>	"string"	undefined
<i>multiplier</i>	real	undefined

Summary Radiative energy flux, possibly defined with different models for emissivity, form factor and irradiation

9.2.233. Nat Conv

Scope: Equation System

Nat Conv Flux For Cvfem_Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Nat_Conv [Using Data Specification *Data Spec Name*][Data = *data* |H = *h* |T_Ref = *t_ref*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>data</i>	"string"	undefined
<i>h</i>	"string"	undefined
<i>t_ref</i>	"string"	undefined

Summary CVFEM convective energy flux defined with constant models for heat transfer coefficient and reference temperature

9.2.234. Generalized Nat Conv

Scope: Equation System

Generalized Nat Conv Flux For Cvfem_Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Generalized_Nat_Conv [Using Data Specification *Data Spec Name*][Data = *data* |Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>data</i>	"string"	undefined
<i>multiplier</i>	real	undefined

Summary CVFEM energy generalized natural convection flux BC

9.2.235. Wall Function From Temperature

Scope: Equation System

```
Wall Function From Temperature Flux For Cvfem_Energy [ {of|species|
subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|
over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing
OpposingMeshExtent ]= Wall_Function_From_Temperature [ Using Data
Specification Data Spec Name ][ Data = data |Value = value |T = t |
Wall_Friction_Factor = wall_friction_factor ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>data</i>	"string"	undefined
<i>value</i>	real	undefined
<i>t</i>	real	undefined
<i>wall_friction_factor</i>	real	undefined

Summary CVFEM energy wall function from temperature flux BC

9.2.236. Mass Flux

Scope: Equation System

```
Mass Flux Flux For Cvfem_Energy [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Mass_Flux [
Using Data Specification Data Spec Name ][ Data = data |Inflow_Phi =
Inflow_Phi |Total_Mdot = total_mdot ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>data</i>	"string"	undefined
<i>Inflow_Phi</i>	real	undefined
<i>total_mdot</i>	real	undefined

Summary CVFEM energy mass flux flux BC

9.2.237. Mass Flux From Temperature

Scope: Equation System

```
Mass Flux From Temperature Flux For Cvfem_Energy [ {of|species|subindex}
Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh
Extent Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Mass_Flux_From_Temperature [ Using Data Specification Data Spec Name ][
Data = data |Temperature = temperature |Pressure = pressure |
Mass_Fraction_0 = mass_fraction_0 |Mass_Fraction_1 = mass_fraction_1 |
Mass_Fraction_2 = mass_fraction_2 |Mass_Fraction_3 = mass_fraction_3 |
Mass_Fraction_4 = mass_fraction_4 |Mass_Fraction_5 = mass_fraction_5 |
Mass_Fraction_6 = mass_fraction_6 |Mass_Fraction_7 = mass_fraction_7 |
Mass_Fraction_8 = mass_fraction_8 |Total_Mdot = total_mdot ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>data</i>	"string"	undefined
<i>temperature</i>	real	undefined
<i>pressure</i>	real	undefined
<i>mass_fraction_0</i>	real	undefined
<i>mass_fraction_1</i>	real	undefined
<i>mass_fraction_2</i>	real	undefined
<i>mass_fraction_3</i>	real	undefined
<i>mass_fraction_4</i>	real	undefined
<i>mass_fraction_5</i>	real	undefined
<i>mass_fraction_6</i>	real	undefined
<i>mass_fraction_7</i>	real	undefined
<i>mass_fraction_8</i>	real	undefined
<i>total_mdot</i>	real	undefined

Summary CVFEM energy mass flux from temperature flux BC

9.2.238. Wall Function From Cht Temperature

Scope: Equation System

```
Wall Function From Cht Temperature Flux For Cvfem_Energy [ {of|species|
subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|
over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing
OpposingMeshExtent ]= Wall_Function_From_Cht_Temperature [ Using Data
```

Specification *Data Spec Name* [*Data = data* | *Wall_Friction_Factor = wall_friction_factor*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>data</i>	"string"	undefined
<i>wall_friction_factor</i>	real	undefined

Summary CVFEM energy wall function from conjugate heat transfer temperature flux BC

9.2.239. Porous Robin Coupled

Scope: Equation System

Porous Robin Coupled Flux For Cvfem_Energy [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* | *Opposing OpposingMeshExtent*] = Porous_Robin_Coupled [Using Data Specification *Data Spec Name*] [*Data = data* | *Enthalpy_Field = enthalpy_field* | *Enthalpy_Diffusive_Flux_Field = enthalpy_diffusive_flux_field* | *Averaged_Coeff_Field = averaged_coeff_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>data</i>	"string"	undefined
<i>enthalpy_field</i>	"string"	undefined
<i>enthalpy_diffusive_flux_field</i>	"string"	undefined
<i>averaged_coeff_field</i>	"string"	undefined

Summary Boundary condition for loose coupling of enthalpy to a porous region

9.2.240. Normal Capillary Stabilization

Scope: Equation System

Normal Capillary Stabilization Fluxbp For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Normal_Capillary_Stabilization [Using Data Specification *Data Spec Name*][
Mu0 = *mu0* |Multiplier = *multiplier* |Use_Velocity_Correction =
use_velocity_correction]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>mu0</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>use_velocity_correction</i>	integer	undefined

Summary Momentum capillary stabilization flux BP BC

9.2.241. Capillary Stabilization

Scope: Equation System

Capillary Stabilization Fluxbp For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Capillary_Stabilization [Using Data Specification *Data Spec Name*][Mu0 =
mu0 |Multiplier = *multiplier* |Use_Velocity_Correction =
use_velocity_correction]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>mu0</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>use_velocity_correction</i>	integer	undefined

Summary Momentum capillary stabilization flux BP BC

9.2.242. Ls Capillary Stabilization

Scope: Equation System

Ls Capillary Stabilization Fluxbp For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Ls_Capillary_Stabilization [Using Data Specification *Data Spec Name*][μ_0
= μ_0 |Multiplier = *multiplier* |Use_Velocity_Correction =
use_velocity_correction]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>mu0</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>use_velocity_correction</i>	integer	undefined

Summary Momentum capillary stabilization flux BP BC using level set normal

9.2.243. Free Open Flow

Scope: Equation System

Free Open Flow Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Free_Open_Flow
[Using Data Specification *Data Spec Name*][Pressure = *pressure* |Pressure
User Sub *PRESSURE User Sub*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>PRESSURE User Sub</i>	string	undefined

Summary Open flow for momentum; apply the full stress

9.2.244. Open Flow

Scope: Equation System

Open Flow Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Open_Flow [Using Data Specification *Data Spec Name*][Pressure = *pressure* | Total_Pressure = *total_pressure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined

Summary Open flow for momentum; enforce normal gradient to be zero

9.2.245. Vector String Function

Scope: Equation System

Vector String Function Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Vector_String_Function [Using Data Specification *Data Spec Name*][F_X = *f_x* |F_Y = *f_y* |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.246. Pressure

Scope: Equation System

Pressure Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Pressure [Using Data Specification *Data Spec Name*][User_Field_Name = *user_field_name* |Use_Bulk_Node = *use_bulk_node* |P = *p* |C_T = *c_t* |C_X = *c_x* |C_Y = *c_y* |C_Z = *c_z* |C_Cos_W = *c_cos_w* |C_Sin_W = *c_sin_w* |C1_Cos = *c1_cos* |C1_Sin = *c1_sin*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>user_field_name</i>	"string"	undefined
<i>use_bulk_node</i>	"string"	undefined
<i>p</i>	real	undefined
<i>c_t</i>	real	undefined
<i>c_x</i>	real	undefined
<i>c_y</i>	real	undefined
<i>c_z</i>	real	undefined
<i>c_cos_w</i>	real	undefined
<i>c_sin_w</i>	real	undefined
<i>c1_cos</i>	real	undefined
<i>c1_sin</i>	real	undefined

Summary Pressure momentum flux

9.2.247. Pressure User Function

Scope: Equation System

Pressure User Function Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Pressure_User_Function [Using Data Specification *Data Spec Name*][Name = *name* |X = *x* |X_Multiplier = *x_multiplier* |Multiplier = *multiplier* |Toggle = *toggle*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>name</i>	"string"	undefined
<i>x</i>	"string"	undefined
<i>x_multiplier</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>toggle</i>	"string"	undefined

Summary Pressure user function momentum flux

9.2.248. Kinematic

Scope: Equation System

Kinematic Rotated For Cvfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Kinematic [Using Data Specification *Data Spec Name*][*V0 = v0* |*Shared_Normal = shared_normal* |*No_Mesh_Movement = no_mesh_movement*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>v0</i>	real	undefined
<i>shared_normal</i>	"string"	undefined
<i>no_mesh_movement</i>	"string"	undefined

Summary Kinematic model for rotated cvfem momentum

9.2.249. Vector String Function

Scope: Equation System

Vector String Function Rotated For Cvfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=

Vector_String_Function [Using Data Specification *Data Spec Name*][F_X = *f_x* |F_Y = *f_y* |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.250. Slip Length

Scope: Equation System

Slip Length Flux For Cvfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Slip_Length [Using Data Specification *Data Spec Name*][Vs_X = *vs_x* |Vs_Y = *vs_y* |Vs_Z = *vs_z* |Beta = *beta*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>vs_x</i>	real	undefined
<i>vs_y</i>	real	undefined
<i>vs_z</i>	real	undefined
<i>beta</i>	real	undefined

Summary Slip length momentum flux

9.2.251. Wall Function

Scope: Equation System

Wall Function Flux For Cvfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [

Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Wall_Function [
Using Data Specification *Data Spec Name*][Wall_Friction_Factor =
wall_friction_factor |Wall_Velocity_X = *wall_velocity_x* |Wall_Velocity_Y =
wall_velocity_y |Wall_Velocity_Z = *wall_velocity_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>wall_friction_factor</i>	real	undefined
<i>wall_velocity_x</i>	real	undefined
<i>wall_velocity_y</i>	real	undefined
<i>wall_velocity_z</i>	real	undefined

Summary CVFEM momentum wall function flux BC

9.2.252. Interface

Scope: Equation System

Interface Flux For Cvfem_Momentum [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [
Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Interface [
Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary INTERFACE CVFEM momentum flux

9.2.253. Open Adv Flow

Scope: Equation System

Open Adv Flow Flux For Cvfem_Momentum [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [
Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Open_Adv_Flow [
Using Data Specification *Data Spec Name*][Pressure = *pressure* |

```
Total_Pressure = total_pressure | Coflow_Entrainment_Value_X =
coflow_entrainment_value_x | Coflow_Entrainment_Value_Y =
coflow_entrainment_value_y | Coflow_Entrainment_Value_Z =
coflow_entrainment_value_z ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined
<i>coflow_entrainment_value_x</i>	real	undefined
<i>coflow_entrainment_value_y</i>	real	undefined
<i>coflow_entrainment_value_z</i>	real	undefined

Summary CVFEM momentum open advective flow flux BC

9.2.254. Symmetry Flow

Scope: Equation System

```
Symmetry Flow Flux For Cvfem_Momentum [ {of|species|subindex} Species |{in
|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Symmetry_Flow [
Using Data Specification Data Spec Name ] [ ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary CVFEM momentum symmetry flow flux BC

9.2.255. Simple Interp Tensor

Scope: Equation System

```
Simple Interp Tensor Flux For Cvfem_Lumped_Div_Projection [ {of|species|
subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|
over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing
```

OpposingMeshExtent]= Simple_Interp_Tensor [Using Data Specification *Data Spec Name*][Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary CVFEM lumped divergence projection simple interpolation tensor flux BC

9.2.256. Simple Interp Vector

Scope: Equation System

Simple Interp Vector Flux For Cvfem_Lumped_Div_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Simple_Interp_Vector [Using Data Specification *Data Spec Name*][Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary CVFEM lumped divergence projection simple interpolation vector flux BC

9.2.257. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Cvfem_Level_Set [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.258. Open Adv Flow

Scope: Equation System

```
Open Adv Flow Flux For Cvfem_Level_Set [ {of|species|subindex} Species |
{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name
[ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Open_Adv_Flow
[ Using Data Specification Data Spec Name ][ Pressure = pressure |
Total_Pressure = total_pressure |Far_Field_Entrainment_Value =
far_field_entrainment_value ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined
<i>far_field_entrainment_value</i>	real	undefined

9.2.259. Open Adv Pen Flow

Scope: Equation System

```
Open Adv Pen Flow Flux For Cvfem_Level_Set [ {of|species|subindex} Species
|{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent
Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Open_Adv_Pen_Flow [ Using Data Specification Data Spec Name ][
Penalty_Factor = penalty_factor |Far_Field_Entrainment_Value =
far_field_entrainment_value ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>penalty_factor</i>	real	undefined
<i>far_field_entrainment_value</i>	real	undefined

9.2.260. Open Nc Adv Flow

Scope: Equation System

```
Open Nc Adv Flow Flux For Cvfem_Level_Set [ {of|species|subindex} Species
|{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent
Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Open_Nc_Adv_Flow [ Using Data Specification Data Spec Name ][
Far_Field_Entrainment_Value = far_field_entrainment_value ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>far_field_entrainment_value</i>	real	undefined

9.2.261. Tensor String Function

Scope: Equation System

```
Tensor String Function Flux For Cvfem_Lumped_Div_Projection [ {of|species|
subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|
over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing
OpposingMeshExtent ]= Tensor_String_Function [ Using Data Specification
Data Spec Name ][ F_Xx = f_xx |F_Yy = f_yy |F_Xy = f_xy |F_Zz = f_zz |
F_Xz = f_xz |F_Yz = f_yz |F_Yx = f_yx |F_Zx = f_zx |F_Zy = f_zy ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_{xx}</i>	"string"	undefined
<i>f_{yy}</i>	"string"	undefined
<i>f_{xy}</i>	"string"	undefined
<i>f_{zz}</i>	"string"	undefined
<i>f_{xz}</i>	"string"	undefined
<i>f_{yz}</i>	"string"	undefined
<i>f_{yx}</i>	"string"	undefined
<i>f_{zx}</i>	"string"	undefined
<i>f_{zy}</i>	"string"	undefined

Summary Value from a string function

9.2.262. Tensor String Function Symmetric

Scope: Equation System

Tensor String Function Symmetric Flux For Cvfem_Lumped_Div_Projection [{of |species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for| in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*] = Tensor_String_Function_Symmetric [Using Data Specification *Data Spec Name*] [F_{Xx} = *f_{xx}* |F_{Yy} = *f_{yy}* |F_{Xy} = *f_{xy}* | F_{Zz} = *f_{zz}* |F_{Xz} = *f_{xz}* |F_{Yz} = *f_{yz}*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_{xx}</i>	"string"	undefined
<i>f_{yy}</i>	"string"	undefined
<i>f_{xy}</i>	"string"	undefined
<i>f_{zz}</i>	"string"	undefined
<i>f_{xz}</i>	"string"	undefined
<i>f_{yz}</i>	"string"	undefined

Summary Value from a string function

9.2.263. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Hfem_Continuity [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.264. Simple Inflow

Scope: Equation System

Simple Inflow Flux For Hfem_Continuity [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Simple_Inflow [Using Data Specification *Data Spec Name*][Value = *value* |Density = *Density* |Velocity_X = *Velocity_X* |Velocity_Y = *Velocity_Y* |Velocity_Z = *Velocity_Z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>value</i>	real	undefined
<i>Density</i>	real	undefined
<i>Velocity_X</i>	real	undefined
<i>Velocity_Y</i>	real	undefined
<i>Velocity_Z</i>	real	undefined

Summary IBP continuity inflow; specified dens and u

9.2.265. Interface

Scope: Equation System

Interface Flux For Hfem_Continuity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Interface [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary INTERFACE HFEM continuity flux

9.2.266. Inflow

Scope: Equation System

Inflow Flux For Hfem_Continuity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Inflow [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary IBP continity inflow; nodal interp

9.2.267. Open Flow

Scope: Equation System

Open Flow Flux For Hfem_Continuity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Open_Flow [Using Data Specification *Data Spec Name*] [Pressure = *pressure* | Total_Pressure = *total_pressure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined

Summary Open bc for continuity

9.2.268. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Voltage [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*][*F = f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.269. Vapor Recoil Pressure

Scope: Equation System

Vapor Recoil Pressure Flux For Momentum [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
 Vapor_Recoil_Pressure [Using Data Specification *Data Spec Name*][*Tboil = tboil*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>tboil</i>	real	undefined

Summary Vapor recoil pressure momentum flux

9.2.270. Exponential Vapor Recoil Pressure

Scope: Equation System

Exponential Vapor Recoil Pressure Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Exponential_Vapor_Recoil_Pressure [Using Data Specification *Data Spec Name*] [*Tboil = tboil* | *L = l* | *Pa = pa* | *Mw = mw*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>tboil</i>	real	undefined
<i>l</i>	real	undefined
<i>pa</i>	real	undefined
<i>mw</i>	real	undefined

Summary Exponential vapor recoil pressure momentum flux

9.2.271. Oriented Slip

Scope: Equation System

Oriented Slip Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Oriented_Slip [Using Data Specification *Data Spec Name*] [*Vs_X = vs_x* | *Vs_Y = vs_y* | *Vs_Z = vs_z* | *Beta_Normal = beta_normal* | *Beta_Tangent = beta_tangent*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>vs_x</i>	real	undefined
<i>vs_y</i>	real	undefined
<i>vs_z</i>	real	undefined
<i>beta_normal</i>	real	undefined
<i>beta_tangent</i>	real	undefined

Summary Oriented slip momentum flux

9.2.272. Ls Oriented Slip

Scope: Equation System

```

Ls Oriented Slip Flux For Momentum [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Ls_Oriented_Slip [ Using Data Specification Data Spec Name ][ Vs_X = vs_x |
Vs_Y = vs_y |Vs_Z = vs_z |Beta_Normal_A = beta_normal_a |Beta_Tangent_A =
beta_tangent_a |Beta_Normal_B = beta_normal_b |Beta_Tangent_B =
beta_tangent_b ]

```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>vs_x</i>	real	undefined
<i>vs_y</i>	real	undefined
<i>vs_z</i>	real	undefined
<i>beta_normal_a</i>	real	undefined
<i>beta_tangent_a</i>	real	undefined
<i>beta_normal_b</i>	real	undefined
<i>beta_tangent_b</i>	real	undefined

Summary Oriented slip momentum flux

9.2.273. Slip Length

Scope: Equation System

Slip Length Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Slip_Length [Using Data Specification *Data Spec Name*][Vs_X = *vs_x* |Vs_Y = *vs_y* |Vs_Z = *vs_z* |Beta = *beta*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>vs_x</i>	real	undefined
<i>vs_y</i>	real	undefined
<i>vs_z</i>	real	undefined
<i>beta</i>	real	undefined

Summary Slip length momentum flux

9.2.274. Slip

Scope: Equation System

Slip Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Slip [Using Data Specification *Data Spec Name*][Vs_X = *vs_x* |Vs_Y = *vs_y* |Vs_Z = *vs_z* |Beta = *beta*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>vs_x</i>	real	undefined
<i>vs_y</i>	real	undefined
<i>vs_z</i>	real	undefined
<i>beta</i>	real	undefined

Summary Slip momentum flux

9.2.275. Ls Capillary

Scope: Equation System

Ls Capillary Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Ls_Capillary [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary LS capillary momentum flux

9.2.276. Capillary

Scope: Equation System

Capillary Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Capillary [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary LS capillary momentum flux

9.2.277. Capillary Gap

Scope: Equation System

Capillary Gap Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Capillary_Gap [Using Data Specification *Data Spec Name*] [$V\_W = v\_w$ | $G = g$ | $\Theta = \theta$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>v_w</i>	real	undefined
<i>g</i>	real	undefined
<i>theta</i>	real	undefined

Summary This model has been deprecated

9.2.278. Equilibrium Capillary Gap

Scope: Equation System

Equilibrium Capillary Gap Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Equilibrium_Capillary_Gap [Using Data Specification *Data Spec Name*] [
Theta = *theta*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>theta</i>	real	undefined

Summary This model has been deprecated

9.2.279. Simple Interp

Scope: Equation System

Simple Interp Flux For Cvfm_Lumped_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Simple_Interp [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Cvfem lumped projection simple interpolation flux BC

9.2.280. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfem_Mass_Fraction [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] { @ | at | for | in | on | over } *Mesh Extent Name* [Touching *TouchingMeshExtent* | Opposing *OpposingMeshExtent*] = Scalar_String_Function [Using Data Specification *Data Spec Name*] [F = f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.281. Mass Flux

Scope: Equation System

Mass Flux Flux For Cvfem_Mass_Fraction [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] { @ | at | for | in | on | over } *Mesh Extent Name* [Touching *TouchingMeshExtent* | Opposing *OpposingMeshExtent*] = Mass_Flux [Using Data Specification *Data Spec Name*] [Total_Mdot = *total_mdot* | Inflow_Phi = *inflow_phi*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>total_mdot</i>	real	undefined
<i>inflow_phi</i>	real	undefined

9.2.282. No Slip

Scope: Equation System

No Slip Disting For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= No_Slip [Using Data Specification *Data Spec Name*][$V_0 = v_0$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>v0</i>	real	undefined

Summary No slip model for momentum distinguishing condition

9.2.283. Vector String Function

Scope: Equation System

Vector String Function Disting For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Vector_String_Function [Using Data Specification *Data Spec Name*][$F_X = f_x$ | $F_Y = f_y$ | $F_Z = f_z$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.284. Kinematic

Scope: Equation System

Kinematic Rotated For Momentum_Colloc [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Kinematic [Using Data Specification *Data Spec Name*][*V0 = v0* |*Shared_Normal = shared_normal* |*No_Mesh_Movement = no_mesh_movement*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>v0</i>	real	undefined
<i>shared_normal</i>	"string"	undefined
<i>no_mesh_movement</i>	"string"	undefined

Summary Kinematic model for rotated collocated momentum boundary condition

9.2.285. Vector String Function

Scope: Equation System

Vector String Function Rotated For Momentum_Colloc [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Vector_String_Function [Using Data Specification *Data Spec Name*][*F_X = f_x* |*F_Y = f_y* |*F_Z = f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.286. Electroosmotic Velocity

Scope: Equation System

Electroosmotic Velocity Disting For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Electroosmotic_Velocity [Using Data Specification *Data Spec Name*][C = c
]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>c</i>	real	undefined

Summary Electro-osmotic velocity model for momentum distinguishing condition

9.2.287. Wetting Speed Blake Ls

Scope: Equation System

Wetting Speed Blake Ls Disting For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Wetting_Speed_Blake_Ls [Using Data Specification *Data Spec Name*][V_W =
v_w |G = g |Theta = *theta* |Width = *width* |Tau = *tau*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>v_w</i>	real	undefined
<i>g</i>	real	undefined
<i>theta</i>	real	undefined
<i>width</i>	real	undefined
<i>tau</i>	real	undefined

Summary Blake level set wetting speed model for momentum distinguishing condition

9.2.288. Open

Scope: Equation System

```
Open Flux For Cvfem_Projection [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Open [ Using
Data Specification Data Spec Name ][ Total_Pressure = total_pressure |
Pressure = pressure ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>total_pressure</i>	real	undefined
<i>pressure</i>	real	undefined

Summary CVFEM projection open flux BC

9.2.289. Scalar String Function

Scope: Equation System

```
Scalar String Function Disting For Energy [ {of|species|subindex} Species
|{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent
Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Scalar_String_Function [ Using Data Specification Data Spec Name ][ F = f
]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.290. Calore User Sub

Scope: Equation System

Calore User Sub Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Calore_User_Sub [Using Data Specification *Data Spec Name*][Power_Output = *power_output* | Flux_Output = *flux_output* |Toggle = *toggle* |Name = *name* |Type = *type* | Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

9.2.291. Distribution Factor

Scope: Equation System

Distribution Factor Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Distribution_Factor [Using Data Specification *Data Spec Name*][
Power_Output = *power_output* |Flux_Output = *flux_output* |Toggle = *toggle* |
Attribute_Name = *attribute_name* |Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>attribute_name</i>	"string"	undefined
<i>multiplier</i>	real	undefined

9.2.292. Gaussian Line Weld

Scope: Equation System

Gaussian Line Weld Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Gaussian_Line_Weld [Using Data Specification *Data Spec Name*][
Power_Output = *power_output* |Flux_Output = *flux_output* |Toggle = *toggle* |
Src_X = *src_x* |Dir_X = *dir_x* |Vel_X = *vel_x* |Src_Y = *src_y* |Dir_Y = *dir_y* |
Vel_Y = *vel_y* |Src_Z = *src_z* |Dir_Z = *dir_z* |Vel_Z = *vel_z* |R = *r* |T_On
= *t_on* |T_Off = *t_off* |Flux = *flux* |R_Eff = *r_eff* |Alpha = *alpha* |
Depth_Enhanced_Absorption_Data = *depth_enhanced_absorption_data* |
Compute_Visibility_Field = *compute_visibility_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>src_x</i>	real	undefined
<i>dir_x</i>	real	undefined
<i>vel_x</i>	real	undefined
<i>src_y</i>	real	undefined
<i>dir_y</i>	real	undefined
<i>vel_y</i>	real	undefined
<i>src_z</i>	real	undefined
<i>dir_z</i>	real	undefined
<i>vel_z</i>	real	undefined
<i>r</i>	real	undefined
<i>t_on</i>	real	undefined
<i>t_off</i>	real	undefined
<i>flux</i>	real	undefined
<i>r_eff</i>	real	undefined
<i>alpha</i>	real	undefined
<i>depth_enhanced_absorption_data</i>	"string"	undefined
<i>compute_visibility_field</i>	"string"	undefined

9.2.293. Enclosure Radiation

Scope: Equation System

Enclosure Radiation Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Enclosure_Radiation [Using Data Specification *Data Spec Name*] [
Power_Output = *power_output* |Flux_Output = *flux_output* |Toggle = *toggle* |
Ndof = *ndof* |Multiplier = *multiplier* |Enclosure = *enclosure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>ndof</i>	integer	undefined
<i>multiplier</i>	real	undefined
<i>enclosure</i>	"string"	undefined

9.2.294. Gaussian Line Power Weld

Scope: Equation System

```

Gaussian Line Power Weld Flux For Energy [ {of|species|subindex} Species |
{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name
[ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Gaussian_Line_Power_Weld [ Using Data Specification Data Spec Name ][
Power_Output = power_output |Flux_Output = flux_output |Toggle = toggle |
Src_X = src_x |Dir_X = dir_x |Vel_X = vel_x |Src_Y = src_y |Dir_Y = dir_y
|Vel_Y = vel_y |Src_Z = src_z |Dir_Z = dir_z |Vel_Z = vel_z |R = r |T_On
= t_on |T_Off = t_off |R_Eff = r_eff |Alpha = alpha |
Depth_Enhanced_Absorption_Data = depth_enhanced_absorption_data |
Compute_Visibility_Field = compute_visibility_field ]

```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>src_x</i>	real	undefined
<i>dir_x</i>	real	undefined
<i>vel_x</i>	real	undefined
<i>src_y</i>	real	undefined
<i>dir_y</i>	real	undefined
<i>vel_y</i>	real	undefined
<i>src_z</i>	real	undefined
<i>dir_z</i>	real	undefined
<i>vel_z</i>	real	undefined
<i>r</i>	real	undefined
<i>t_on</i>	real	undefined
<i>t_off</i>	real	undefined
<i>r_eff</i>	real	undefined
<i>alpha</i>	real	undefined
<i>depth_enhanced_absorption_data</i>	string	undefined
<i>compute_visibility_field</i>	"string"	undefined

9.2.295. Gaussian Ray Trace

Scope: Equation System

```

Gaussian Ray Trace Flux For Energy [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Gaussian_Ray_Trace [ Using Data Specification Data Spec Name ][
Power_Output = power_output |Flux_Output = flux_output |Toggle = toggle |
Path_Function = path_function |Dir_X = dir_x |Dir_Y = dir_y |Dir_Z =
dir_z |Power = power |R = r |R_Eff = r_eff |Type = type |N_Rays = n_rays
|N_R = n_r |N_Theta_Initial = n_theta_initial |N_Intersections =
n_intersections |Weight_Ratio = weight_ratio |Id = id ]

```


Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>path_function</i>	"string"	undefined
<i>dir_x</i>	real	undefined
<i>dir_y</i>	real	undefined
<i>dir_z</i>	real	undefined
<i>power</i>	real	undefined
<i>r</i>	real	undefined
<i>r_eff</i>	real	undefined
<i>type</i>	"string"	undefined
<i>n_rays</i>	integer	undefined
<i>n_r</i>	integer	undefined
<i>n_theta_initial</i>	integer	undefined
<i>n_intersections</i>	integer	undefined
<i>weight_ratio</i>	real	undefined
<i>id</i>	"string"	undefined

Summary Ray tracing implementation of a Gaussian Beam energy flux

Description type - Either radial discretization or Monte Carlo. Determines how beam will be discretized into rays. Radial discretization is deterministic and breaks beams into approximately equal area segments radially. Each segment generates one ray. The power of each ray varies based on which segment it is generated from. Monte Carlo is stochastic and will generate a user-specified number of rays distributed spatially according to the laser's Gaussian function, such that more are generated near the laser center, and each ray has equal power of $\text{power}/n_{\text{rays}}$.

n_r - Number of segments in radial direction for radial discretization.

n_theta_initial - Number of segments in theta direction in the smallest radial segment. The number of theta segments will grow as radial direction increases so segments have approximately the same area. Total number of rays will be $n_r * n_r * n_{\text{theta\_initial}}$.

n_rays - Number of rays to generate for Monte Carlo discretization.

path_function - Function giving x, y, z coordinates of laser center as function of time.

*dir_** - Direction that rays will travel initially from laser center defined by *path_function*.

power - Total laser power.

r - Laser Gaussian standard deviation.

r_eff - Laser exponential factor. Gaussian is given by $EXP\left(\frac{-r_{eff}*D^2}{r^2}\right)$, where D is the distance between a point and the laser center.

id - Optional parameter for applying same ray source to multiple mesh parts. By default, each mesh part will get its own set of rays to intersect with it. If you want to have a single set of rays that intersects with multiple mesh parts, assign the same id to each line command for each part you want to include. Id can be any string, but line commands with the same id (not case sensitive) will be grouped together. Line commands with id omitted will not be grouped.

n_intersections - Maximum number of times to intersect a ray with mesh elements due to reflections (default: 10).

weight_ratio - Fraction of initial ray power below which rays will be considered spent and no longer be traced (default: 0.001).

9.2.296. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Porous_Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.297. Mass Flux

Scope: Equation System

Mass Flux Flux For Cvfem_Mixture_Fraction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=

Mass_Flux [Using Data Specification *Data Spec Name*][Total_Mdot = *total_mdot* | Inflow_Phi = *inflow_phi*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>total_mdot</i>	real	undefined
<i>inflow_phi</i>	real	undefined

9.2.298. Open Adv Flow

Scope: Equation System

Open Adv Flow Flux For Cvfem_Mixture_Fraction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Open_Adv_Flow [Using Data Specification *Data Spec Name*][Pressure = *pressure* |Total_Pressure = *total_pressure* |Far_Field_Entrainment_Value = *far_field_entrainment_value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined
<i>far_field_entrainment_value</i>	real	undefined

9.2.299. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfem_Mixture_Fraction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.300. Free Open Flow

Scope: Equation System

Free Open Flow Flux For Cvfem_Mixture_Fraction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Free_Open_Flow [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

9.2.301. Recession

Scope: Equation System

Recession Disting For Mesh_Z [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Recession [Using Data Specification *Data Spec Name*] [T_Ref = *t_ref* |K = *k* |K_0 = *k_0* |N = *n* |Temperature = *temperature*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_o</i>	real	undefined
<i>n</i>	real	undefined
<i>temperature</i>	"string"	undefined

Summary Recession model for mesh_x distinguishing condition

9.2.302. Kinematic

Scope: Equation System

Kinematic Disting For Mesh_Z [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Kinematic [Using Data Specification *Data Spec Name*] [*V0 = v0* |*Shared_Normal = shared_normal* |*No_Mesh_Movement = no_mesh_movement*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>v0</i>	real	undefined
<i>shared_normal</i>	"string"	undefined
<i>no_mesh_movement</i>	"string"	undefined

Summary Kinematic model for mesh_z distinguishing condition

9.2.303. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Mesh_Z [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=

Scalar_String_Function [Using Data Specification *Data Spec Name*][$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.304. Suspension Traction

Scope: Equation System

Suspension Traction Flux For Div_Projection [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Suspension_Traction [Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary This model has been deprecated and removed from the code

9.2.305. Capillary Force

Scope: Equation System

Capillary Force Flux For Div_Projection [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Capillary_Force [Using Data Specification *Data Spec Name*][Theta = *theta*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>theta</i>	real	undefined

Summary This model has been deprecated and removed from the code.

9.2.306. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Solid_X [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*][F = f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.307. Surface Stabilization

Scope: Equation System

Surface Stabilization Fluxbp For Energy [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Surface_Stabilization [Using Data Specification *Data Spec Name*][D = d]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>d</i>	real	undefined

Summary surface diffusion term for energy

9.2.308. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.309. Wall Function

Scope: Equation System

Wall Function Disting For Hfem_Specific_Dissipation_Rate [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Wall_Function [Using Data Specification *Data Spec Name*][Scale_Factor = *scale_factor* |Wall_Friction_Factor = *Wall_Friction_Factor* |Wall_Velocity_X = *Wall_Velocity_X* |Wall_Velocity_Y = *Wall_Velocity_Y* |Wall_Velocity_Z = *Wall_Velocity_Z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>scale_factor</i>	real	undefined
<i>Wall_Friction_Factor</i>	real	undefined
<i>Wall_Velocity_X</i>	real	undefined
<i>Wall_Velocity_Y</i>	real	undefined
<i>Wall_Velocity_Z</i>	real	undefined

Summary HFEM specific dissipation rate distinguishing condition

9.2.310. Pyrolysis

Scope: Equation System

Pyrolysis Disting For Mesh_X [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Pyrolysis [Using Data Specification *Data Spec Name*][T_Ref = *t_ref* |K = *k* |K_0 = *k_0* |N = *n* |Temperature = *temperature*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_o</i>	real	undefined
<i>n</i>	real	undefined
<i>temperature</i>	"string"	undefined

Summary Pyrolysis model for mesh_x distinguishing condition

9.2.311. Recession

Scope: Equation System

Recession Disting For Mesh_X [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [

Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Recession [
Using Data Specification *Data Spec Name*][T_Ref = *t_ref* |K = *k* |K_0 = *k_0*
|N = *n* |Temperature = *temperature*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_o</i>	real	undefined
<i>n</i>	real	undefined
<i>temperature</i>	"string"	undefined

Summary Recession model for mesh_x distinguishing condition

9.2.312. Kinematic

Scope: Equation System

Kinematic Disting For Mesh_X [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [
Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Kinematic [
Using Data Specification *Data Spec Name*][V0 = *v0* |Shared_Normal =
shared_normal |No_Mesh_Movement = *no_mesh_movement*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>v0</i>	real	undefined
<i>shared_normal</i>	"string"	undefined
<i>no_mesh_movement</i>	"string"	undefined

Summary Kinematic model for mesh_x distinguishing condition

9.2.313. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Mesh_X [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.314. Simple Interp

Scope: Equation System

Simple Interp Flux For Cvfem_Velocity_Edge_Gradient_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Simple_Interp [Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary CVFEM edge-based projection simple interpolation flux BC

9.2.315. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfem_Velocity_Edge_Gradient_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|

```
for|in|on|over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Scalar_String_Function [ Using Data Specification Data Spec Name ] [ F = f ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.316. Ls Capillary

Scope: Equation System

```
Ls Capillary Fluxbp For Hfem_Momentum [ {of|species|subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Ls_Capillary [ Using Data Specification Data Spec Name ] [ ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Momentum capillary flux BP BC using level set normal

9.2.317. Capillary Stabilization

Scope: Equation System

```
Capillary Stabilization Fluxbp For Hfem_Momentum [ {of|species|subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Capillary_Stabilization [ Using Data Specification Data Spec Name ] [ Mu0 = mu0 |Multiplier = multiplier |Use_Velocity_Correction = use_velocity_correction ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>muo</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>use_velocity_correction</i>	integer	undefined

Summary Momentum capillary stabilization flux BP BC

9.2.318. Vector String Function

Scope: Equation System

Vector String Function Fluxbp For Hfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Vector_String_Function [Using Data Specification *Data Spec Name*] [$F_X = f_x$ | $F_Y = f_y$ | $F_Z = f_z$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
f_x	"string"	undefined
f_y	"string"	undefined
f_z	"string"	undefined

Summary Value from a string function

9.2.319. Capillary

Scope: Equation System

Capillary Fluxbp For Hfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Capillary [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Momentum capillary flux BP BC

9.2.320. Balanced Force

Scope: Equation System

Balanced Force Flux For Hfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Balanced_Force [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary HFEM momentum balanced force flux BC

9.2.321. Symmetry Flow

Scope: Equation System

Symmetry Flow Flux For Hfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Symmetry_Flow [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary HFEM momentum symmetry flow flux BC

9.2.322. Wall Function

Scope: Equation System

Wall Function Flux For Hfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Wall_Function [Using Data Specification *Data Spec Name*][Scale_Factor = *scale_factor* | Wall_Friction_Factor = *wall_friction_factor* |Wall_Velocity_X = *wall_velocity_x* |Wall_Velocity_Y = *wall_velocity_y* |Wall_Velocity_Z = *wall_velocity_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>scale_factor</i>	real	undefined
<i>wall_friction_factor</i>	real	undefined
<i>wall_velocity_x</i>	real	undefined
<i>wall_velocity_y</i>	real	undefined
<i>wall_velocity_z</i>	real	undefined

Summary HFEM momentum symmetry flow flux BC

9.2.323. Interface

Scope: Equation System

Interface Flux For Hfem_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Interface [Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary INTERFACE HFEM momentum flux

9.2.324. Pressure User Function

Scope: Equation System

```
Pressure User Function Flux For Mesh [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Pressure_User_Function [ Using Data Specification Data Spec Name ][ Name =
name |X = x |X_Multiplier = x_multiplier |Multiplier = multiplier |Toggle
= toggle ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>name</i>	"string"	undefined
<i>x</i>	"string"	undefined
<i>x_multiplier</i>	real	undefined
<i>multiplier</i>	real	undefined
<i>toggle</i>	"string"	undefined

Summary Pressure user function mesh flux

9.2.325. Pressure

Scope: Equation System

```
Pressure Flux For Mesh [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Pressure [
Using Data Specification Data Spec Name ][ User_Field_Name =
user_field_name |Use_Bulk_Node = use_bulk_node |P = p |C_T = c_t |C_X =
c_x |C_Y = c_y |C_Z = c_z |C_Cos_W = c_cos_w |C_Sin_W = c_sin_w |C1_Cos
= c1_cos |C1_Sin = c1_sin ]
```


Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>user_field_name</i>	"string"	undefined
<i>use_bulk_node</i>	"string"	undefined
<i>p</i>	real	undefined
<i>c_t</i>	real	undefined
<i>c_x</i>	real	undefined
<i>c_y</i>	real	undefined
<i>c_z</i>	real	undefined
<i>c_cos_w</i>	real	undefined
<i>c_sin_w</i>	real	undefined
<i>cI_cos</i>	real	undefined
<i>cI_sin</i>	real	undefined

Summary Pressure mesh flux

9.2.326. Transient Traction

Scope: Equation System

Transient Traction Flux For Mesh [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
Transient_Traction [Using Data Specification *Data Spec Name*] [*A_X = a_x* | *A_Y = a_y* | *A_Z = a_z* | *B_X = b_x* | *B_Y = b_y* | *B_Z = b_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>a_x</i>	real	undefined
<i>a_y</i>	real	undefined
<i>a_z</i>	real	undefined
<i>b_x</i>	real	undefined
<i>b_y</i>	real	undefined
<i>b_z</i>	real	undefined

Summary Transient traction mesh flux

9.2.327. Electric Traction

Scope: Equation System

Electric Traction Flux For Mesh [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Electric_Traction [Using Data Specification *Data Spec Name*][Sign = *sign*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>sign</i>	real	undefined

Summary Electric traction mesh flux

9.2.328. Shear Free

Scope: Equation System

Shear Free Flux For Mesh [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Shear_Free [Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Shear-free traction mesh flux

9.2.329. Constant Traction

Scope: Equation System

Constant Traction Flux For Mesh [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=

Constant_Traction [Using Data Specification *Data Spec Name*] [X = *x* | Y = *y* | Z = *z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>x</i>	"string"	undefined
<i>y</i>	"string"	undefined
<i>z</i>	"string"	undefined

Summary Constant traction mesh flux

9.2.330. Free Open Flow

Scope: Equation System

Free Open Flow Flux For Cvfem_Turbulence_Dissipation_Rate [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*] = Free_Open_Flow [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

9.2.331. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfem_Turbulence_Dissipation_Rate [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*] = Scalar_String_Function [Using Data Specification *Data Spec Name*] [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.332. Wall Function

Scope: Equation System

Wall Function Disting For Cvfem_Turbulent_Kinetic_Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Wall_Function [Using Data Specification *Data Spec Name*] [*Wall_Friction_Factor* = *Wall_Friction_Factor* |*Wall_Velocity_X* = *Wall_Velocity_X* |*Wall_Velocity_Y* = *Wall_Velocity_Y* |*Wall_Velocity_Z* = *Wall_Velocity_Z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Wall_Friction_Factor</i>	real	undefined
<i>Wall_Velocity_X</i>	real	undefined
<i>Wall_Velocity_Y</i>	real	undefined
<i>Wall_Velocity_Z</i>	real	undefined

Summary CVFEM wall function turbulent kinetic energy distinguishing condition

9.2.333. Mass Flux

Scope: Equation System

Mass Flux Flux For Cvfem_Turbulence_Dissipation_Rate [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Mass_Flux [Using Data Specification *Data Spec Name*] [*Total_Mdot* = *total_mdot* |*Inflow_Phi* = *inflow_phi*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>total_mdot</i>	real	undefined
<i>inflow_phi</i>	real	undefined

9.2.334. Open Adv Flow

Scope: Equation System

```

Open Adv Flow Flux For Cvfem_Dispersed_Momentum [ {of|species|subindex}
Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh
Extent Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Open_Adv_Flow [ Using Data Specification Data Spec Name ][
Coflow_Entrainment_ValueX = Coflow_Entrainment_ValueX |
Coflow_Entrainment_ValueY = Coflow_Entrainment_ValueY |
Coflow_Entrainment_ValueZ = Coflow_Entrainment_ValueZ ]

```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Coflow_Entrainment_ValueX</i>	real	undefined
<i>Coflow_Entrainment_ValueY</i>	real	undefined
<i>Coflow_Entrainment_ValueZ</i>	real	undefined

9.2.335. Vector String Function

Scope: Equation System

```

Vector String Function Flux For Cvfem_Dispersed_Momentum [ {of|species|
subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|
over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing
OpposingMeshExtent ]= Vector_String_Function [ Using Data Specification
Data Spec Name ][ F_X = f_x |F_Y = f_y |F_Z = f_z ]

```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.336. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Level_Set [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*][F = f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.337. Inflow Outflow

Scope: Equation System

Inflow Outflow Flux For Level_Set [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Inflow_Outflow
 [Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary This model has been deprecated and removed from the code.

9.2.338. Outflow

Scope: Equation System

Outflow Disting For Level_Set [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Outflow [Using Data Specification *Data Spec Name*] [$V0 = v0$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>v0</i>	real	undefined

Summary Outflow model for level set distinguishing condition

9.2.339. Mass Fraction Fluid Robin Coupled One Region

Scope: Equation System

Mass Fraction Fluid Robin Coupled One Region Flux For Mass_Balance [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Mass_Fraction_Fluid_Robin_Coupled_One_Region [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Boundary condition for coupling of scalars to a free fluid in the same region.

9.2.340. Mass Fraction Fluid Robin Coupled

Scope: Equation System

```
Mass Fraction Fluid Robin Coupled Flux For Mass_Balance [ {of|species|
subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|
over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing
OpposingMeshExtent ]= Mass_Fraction_Fluid_Robin_Coupled [ Using Data
Specification Data Spec Name ][ Mass_Fraction_Field = mass_fraction_field |
Mass_Fraction_Diffusive_Flux_Field = mass_fraction_diffusive_flux_field |
Coeff_Field = coeff_field ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>mass_fraction_field</i>	"string"	undefined
<i>mass_fraction_diffusive_flux_field</i>	"string"	undefined
<i>coeff_field</i>	"string"	undefined

Summary Boundary condition for loose coupling of scalars to a free fluid region

9.2.341. Fluid Robin Coupled One Region

Scope: Equation System

```
Fluid Robin Coupled One Region Flux For Mass_Balance [ {of|species|
subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|
over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing
OpposingMeshExtent ]= Fluid_Robin_Coupled_One_Region [ Using Data
Specification Data Spec Name ][ Coeff_Scaling = coeff_scaling ]
```


Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>coeff_scaling</i>	real	undefined

Summary Boundary condition for coupling of continuity to a free fluid in the same region.

9.2.342. Mass Fluid Robin Coupled

Scope: Equation System

Mass Fluid Robin Coupled Flux For Mass_Balance [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Mass_Fluid_Robin_Coupled [Using Data Specification *Data Spec Name*] [*Coeff_Scaling* = *coeff_scaling* |*P_Field* = *P_Field* |*Massflux_Field* = *MassFlux_Field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>coeff_scaling</i>	real	undefined
<i>P_Field</i>	"string"	undefined
<i>MassFlux_Field</i>	"string"	undefined

Summary Boundary condition for loose coupling of continuity to a free fluid region

9.2.343. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfm_Temperature_Edge_Gradient_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*] [*F* = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.344. Porous Robin Averaged Coeff

Scope: Equation System

Porous Robin Averaged Coeff Flux For Cvfem_Continuity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Porous_Robin_Averaged_Coeff [Using Data Specification *Data Spec Name*][*P_Field = P_Field* |*Massflux_Field = MassFlux_Field* |*Oppositecoeff_Field = OppositeCoeff_Field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>P_Field</i>	"string"	undefined
<i>MassFlux_Field</i>	"string"	undefined
<i>OppositeCoeff_Field</i>	"string"	undefined

Summary Boundary condition for loose coupling of continuity to a free fluid region

9.2.345. Simple Interp

Scope: Equation System

Simple Interp Flux For Cvfem_Temperature_Edge_Gradient_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Simple_Interp [Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary CVFEM edge-based projection simple interpolation flux BC

9.2.346. Porous Robin Coupled One Region

Scope: Equation System

Porous Robin Coupled One Region Flux For Cvfem_Mass_Fraction [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Porous_Robin_Coupled_One_Region [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Boundary condition for loose coupling of scalars to a free fluid region

9.2.347. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Species [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*] [$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.348. Open Adv Flow

Scope: Equation System

Open Adv Flow Flux For Cvfem_Turbulence_Dissipation_Rate [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Open_Adv_Flow [Using Data Specification *Data Spec Name*] [Pressure = *pressure* |Total_Pressure = *total_pressure* | Far_Field_Entrainment_Value = *far_field_entrainment_value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined
<i>far_field_entrainment_value</i>	real	undefined

9.2.349. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Hfem_Turbulent_Kinetic_Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*] [F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.350. Open Adv Flow

Scope: Equation System

Open Adv Flow Flux For Hfem_Turbulent_Kinetic_Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Open_Adv_Flow [Using Data Specification *Data Spec Name*] [Pressure = *pressure* |Total_Pressure = *total_pressure* |Value = *value* |Far_Field_Entrainment_Value = *far_field_entrainment_value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined
<i>value</i>	real	undefined
<i>far_field_entrainment_value</i>	real	undefined

Summary HFEM turbulent kinetic energy open advective flow flux BC

9.2.351. Vector String Function

Scope: Equation System

Vector String Function Flux For Hfem_Velocity_Pressure_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Vector_String_Function [Using Data Specification *Data Spec Name*] [F_X = *f_x* |F_Y = *f_y* |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.352. Simple Dp Interp

Scope: Equation System

Simple Dp Interp Flux For Hfem_Velocity_Pressure_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Simple_Dp_Interp [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Simple DP interpolation model for HFEM velocity pressure projecion flux

9.2.353. Calore User Sub

Scope: Equation System

Calore User Sub Flux For Current [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Calore_User_Sub [Using Data Specification *Data Spec Name*] [Toggle = *toggle* |Name = *name* |Type = *type* |Multiplier = *multiplier* |Material_Data_Block = *material_data_block* |Data = *data* |Scaling_Field = *scaling_field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>toggle</i>	"string"	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>scaling_field</i>	"string"	undefined

Summary Values from a Calore user subroutine

9.2.354. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Current [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*][Toggle = *toggle* |F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>toggle</i>	"string"	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.355. Kinematic

Scope: Equation System

Kinematic Rotated For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Kinematic [

Using Data Specification *Data Spec Name* [*V0 = v0* | *Shared_Normal = shared_normal* | *No_Mesh_Movement = no_mesh_movement*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>v0</i>	real	undefined
<i>shared_normal</i>	"string"	undefined
<i>no_mesh_movement</i>	"string"	undefined

Summary Kinematic model for rotated momentum

9.2.356. Constant With Cutoff Voltage

Scope: Equation System

Constant With Cutoff Voltage Flux For Current [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] {@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* | *Opposing OpposingMeshExtent*] = *Constant_With_Cutoff_Voltage* [Using Data Specification *Data Spec Name*] [*Toggle = toggle* | *Value = value* | *Cutoff_Value = cutoff_value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>toggle</i>	"string"	undefined
<i>value</i>	real	undefined
<i>cutoff_value</i>	real	undefined

Summary Apply a constant current until a cutoff voltage is crossed anywhere on the surface. After that apply o current.

9.2.357. Resistive Load

Scope: Equation System

Resistive Load Flux For Current [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] {@|at|for|in|on|over} *Mesh Extent Name* [

Touching *TouchingMeshExtent* | Opposing *OpposingMeshExtent*]= Resistive_Load
 [Using Data Specification *Data Spec Name*][Toggle = *toggle* | Area = *Area*
 | Referencevoltage = *ReferenceVoltage*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>toggle</i>	"string"	undefined
<i>Area</i>	real	undefined
<i>ReferenceVoltage</i>	real	undefined

Summary Model a boundary attached to a resistive load. The local applied current density is $V / (R \cdot A)$ where V is the local voltage, R is the specified resistance, and A is the area of the surface the BC is applied to.

9.2.358. Generalized Rad

Scope: Equation System

Generalized Rad Flux For Porous_Enthalpy [{of|species|subindex} *Species* |
 {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name*
 [Touching *TouchingMeshExtent* | Opposing *OpposingMeshExtent*]=
 Generalized_Rad [Using Data Specification *Data Spec Name*][Multiplier =
multiplier]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>multiplier</i>	real	undefined

Summary Radiative porous enthalpy flux, possibly defined with different models for emissivity, form factor and irradiation

9.2.359. Fluid Robin Coupled With Solid Convection One Region

Scope: Equation System

Fluid Robin Coupled With Solid Convection One Region Flux For
Porous_Enthalpy [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]{@|at|for|in|on|over} *Mesh Extent Name* [Touching
TouchingMeshExtent |Opposing *OpposingMeshExtent*]=
Fluid_Robin_Coupled_With_Solid_Convection_One_Region [Using Data
Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Boundary condition for loose coupling of enthalpy to a free fluid region

9.2.360. Enclosure Radiation

Scope: Equation System

Enclosure Radiation Flux For Porous_Enthalpy [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh
Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Enclosure_Radiation [Using Data Specification *Data Spec Name*][N dof =
ndof |Multiplier = *multiplier* |Enclosure = *enclosure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>ndof</i>	integer	undefined
<i>multiplier</i>	real	undefined
<i>enclosure</i>	"string"	undefined

9.2.361. Fluid Robin Coupled One Region

Scope: Equation System

Fluid Robin Coupled One Region Flux For Porous_Enthalpy [{of|species|
subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|
over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing

OpposingMeshExtent]= Fluid_Robin_Coupled_One_Region [Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Boundary condition for loose coupling of enthalpy to a free fluid region

9.2.362. Fluid Solid Convection Coupled One Region

Scope: Equation System

Fluid Solid Convection Coupled One Region Flux For Porous_Enthalpy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Fluid_Solid_Convection_Coupled_One_Region [Using Data Specification *Data Spec Name*][Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>multiplier</i>	real	undefined

Summary Boundary condition for loose coupling of enthalpy to a free fluid region

9.2.363. Mass Flux

Scope: Equation System

Mass Flux Flux For Cvfem_Continuity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Mass_Flux [Using Data Specification *Data Spec Name*][Total_Mdot = *total_mdot*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>total_mdots</i>	real	undefined

Summary Mass flux CVFEM continuity flux

9.2.364. Vector String Function

Scope: Equation System

Vector String Function Flux For Hfem_Bf_Lumped_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Vector_String_Function [Using Data Specification *Data Spec Name*][F_X = f_x |F_Y = f_y |F_Z = f_z]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
f_x	"string"	undefined
f_y	"string"	undefined
f_z	"string"	undefined

Summary Value from a string function

9.2.365. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Continuity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*][F = f]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.366. Extrapolated Pressure

Scope: Equation System

Extrapolated Pressure Flux For Continuity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Extrapolated_Pressure [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary This model has been deprecated and removed from the code.

9.2.367. Pspg

Scope: Equation System

Pspg Flux For Continuity [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Pspg [Using Data Specification *Data Spec Name*] [Tausurfacefactor = *TauSurfaceFactor* | Tausurfacejacobianfactor = *TauSurfaceJacobianFactor*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>TauSurfaceFactor</i>	real	undefined
<i>TauSurfaceJacobianFactor</i>	real	undefined

Summary Continuity PSPG flux BC

9.2.368. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Cvfem_Energy [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* | *Opposing OpposingMeshExtent*] = Scalar_String_Function [Using Data Specification *Data Spec Name*] [*F = f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.369. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Energy [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* | *Opposing OpposingMeshExtent*] = Scalar_String_Function [Using Data Specification *Data Spec Name*] [*Power_Output = power_output* | *Flux_Output = flux_output* | *Toggle = toggle* | *F = f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.370. Generalized Nat Conv

Scope: Equation System

Generalized Nat Conv Flux For Enthalpy [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Generalized_Nat_Conv [Using Data Specification *Data Spec Name*] [
Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>multiplier</i>	real	undefined

Summary Generalized natural convection enthalpy flux

9.2.371. Generalized Rad

Scope: Equation System

Generalized Rad Flux For Enthalpy [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Generalized_Rad
[Using Data Specification *Data Spec Name*] [Multiplier = *multiplier*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>multiplier</i>	real	undefined

Summary Radiative energy flux, possibly defined with different models for emissivity, form factor and irradiation

9.2.372. Convective Outflow

Scope: Equation System

Convective Outflow Flux For Enthalpy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
Convective_Outflow [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

9.2.373. Vector String Function

Scope: Equation System

Vector String Function Fluxbp For Solid [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
Vector_String_Function [Using Data Specification *Data Spec Name*] [$F_X = f_x$ | $F_Y = f_y$ | $F_Z = f_z$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.374. Capillary

Scope: Equation System

Capillary Fluxbp For Solid [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Capillary [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Solid capillary flux BP BC

9.2.375. Vector String Function

Scope: Equation System

Vector String Function Disting For Solid [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Vector_String_Function [Using Data Specification *Data Spec Name*] [F_X = *f_x* |F_Y = *f_y* |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.376. No Slip

Scope: Equation System

No Slip Disting For Solid [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= No_Slip [Using Data Specification *Data Spec Name*][$V_0 = v_0$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>v₀</i>	real	undefined

Summary No slip model for SOLID distinguishing condition

9.2.377. Vector String Function

Scope: Equation System

Vector String Function Flux For Solid [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Vector_String_Function [Using Data Specification *Data Spec Name*][$F_X = f_x$ | $F_Y = f_y$ | $F_Z = f_z$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.378. Pressure

Scope: Equation System

Pressure Flux For Solid [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Pressure [Using Data Specification *Data Spec Name*][User_Field_Name = *user_field_name* |Use_Bulk_Node = *use_bulk_node* |P = *p* |C_T = *c_t* |C_X = *c_x* |C_Y = *c_y* |C_Z = *c_z* |C_Cos_W = *c_cos_w* |C_Sin_W = *c_sin_w* |C1_Cos = *c1_cos* |C1_Sin = *c1_sin*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>user_field_name</i>	"string"	undefined
<i>use_bulk_node</i>	"string"	undefined
<i>p</i>	real	undefined
<i>c_t</i>	real	undefined
<i>c_x</i>	real	undefined
<i>c_y</i>	real	undefined
<i>c_z</i>	real	undefined
<i>c_cos_w</i>	real	undefined
<i>c_sin_w</i>	real	undefined
<i>c1_cos</i>	real	undefined
<i>c1_sin</i>	real	undefined

Summary Pressure solid flux

9.2.379. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Charge_Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*][$F = f$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
f	"string"	undefined

Summary Value from a string function

9.2.380. Nat E

Scope: Equation System

Nat E Flux For Charge_Density [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Nat_E [Using Data Specification *Data Spec Name*][$\text{Sigma} = \sigma$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
σ	"string"	undefined

Summary This model is now deprecated

9.2.381. Vector String Function

Scope: Equation System

Vector String Function Flux For Hfem_Bf_Projection [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh*
Extent Name [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Vector_String_Function [Using Data Specification *Data Spec Name*][F_X =
f_x |F_Y = *f_y* |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.382. Simple Interp

Scope: Equation System

Simple Interp Flux For Hfem_Bf_Lumped_Projection [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh*
Extent Name [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Simple_Interp [Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Simple interp model for BF projection flux

9.2.383. Simple Interp

Scope: Equation System

```
Simple Interp Flux For Hfem_Bf_Projection [ {of|species|subindex} Species
|{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent
Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Simple_Interp [ Using Data Specification Data Spec Name ] [ ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Simple interp model for BF projection flux

9.2.384. Pyrolysis

Scope: Equation System

```
Pyrolysis Disting For Solid_X [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Pyrolysis [
Using Data Specification Data Spec Name ] [ T_Ref = t_ref |K = k |K_0 = k_0
|N = n |Temperature = temperature ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_0</i>	real	undefined
<i>n</i>	real	undefined
<i>temperature</i>	"string"	undefined

Summary Pyrolysis model for SOLID_x distinguishing condition

9.2.385. Kinematic

Scope: Equation System

Kinematic Disting For Solid_X [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Kinematic [Using Data Specification *Data Spec Name*][$V_0 = v_0$ |Shared_Normal = *shared_normal* |No_Mesh_Movement = *no_mesh_movement*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>v0</i>	real	undefined
<i>shared_normal</i>	"string"	undefined
<i>no_mesh_movement</i>	"string"	undefined

Summary Kinematic model for SOLID_x distinguishing condition

9.2.386. Recession

Scope: Equation System

Recession Disting For Solid_X [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Recession [Using Data Specification *Data Spec Name*][$T_{Ref} = t_{ref}$ | $K = k$ | $K_0 = k_0$ | $N = n$ |Temperature = *temperature*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_o</i>	real	undefined
<i>n</i>	real	undefined
<i>temperature</i>	"string"	undefined

Summary Recession model for SOLID_x distinguishing condition

9.2.387. Simple Interp

Scope: Equation System

Simple Interp Flux For Cvfem_Projection [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Simple_Interp [Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary CVFEM projection simple interpolation flux BC

9.2.388. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfem_Projection [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*][*F* = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.389. From Cht Temperature

Scope: Equation System

From Cht Temperature Disting For Porous_Enthalpy [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=

From_Cht_Temperature [Using Data Specification *Data Spec Name*][
Interface_Name = *Interface_Name* | Twall_Field = *Twall_Field* | Tref_Field =
Tref_Field | H_Field = *H_Field*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Interface_Name</i>	"string"	undefined
<i>Twall_Field</i>	"string"	undefined
<i>Tref_Field</i>	"string"	undefined
<i>H_Field</i>	"string"	undefined

Summary Porous enthalpy distinguishing condition from conjugate heat transfer temperature

9.2.390. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Porous_Enthalpy [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh*
Extent Name [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*
]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.391. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfem_Specific_Dissipation_Rate [{of|
species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|
in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing

OpposingMeshExtent]= Scalar_String_Function [Using Data Specification
Data Spec Name][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.392. Open Adv Flow

Scope: Equation System

Open Adv Flow Flux For Cvfem_Specific_Dissipation_Rate [{of|species|
subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|
over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing
OpposingMeshExtent]= Open_Adv_Flow [Using Data Specification *Data Spec*
Name][Pressure = *pressure* |Total_Pressure = *total_pressure* |
Far_Field_Entrainment_Value = *far_field_entrainment_value*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined
<i>far_field_entrainment_value</i>	real	undefined

9.2.393. Mass Flux

Scope: Equation System

Mass Flux Flux For Cvfem_Specific_Dissipation_Rate [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh*
Extent Name [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Mass_Flux [Using Data Specification *Data Spec Name*][Total_Mdot =
total_mdot |Inflow_Phi = *inflow_phi*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>total_mdot</i>	real	undefined
<i>inflow_phi</i>	real	undefined

9.2.394. Pid Controlled Bidirectional

Scope: Equation System

```

Pid Controlled Bidirectional Flux For Energy [ {of|species|subindex}
Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh
Extent Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Pid_Controlled_Bidirectional [ Using Data Specification Data Spec Name ][
Power_Output = power_output |Flux_Output = flux_output |Toggle = toggle |
P = p |I = i |D = d |Band = Band |Filter_Tau = Filter_Tau |
Setpoint_Function_Name = Setpoint_Function_Name |Control_Variable =
Control_Variable |Max_Cooling_Power = Max_Cooling_Power |Max_Heating_Power
= Max_Heating_Power ]

```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>p</i>	real	undefined
<i>i</i>	real	undefined
<i>d</i>	real	undefined
<i>Band</i>	real	undefined
<i>Filter_Tau</i>	real	undefined
<i>Setpoint_Function_Name</i>	"string"	undefined
<i>Control_Variable</i>	"string"	undefined
<i>Max_Cooling_Power</i>	real	undefined
<i>Max_Heating_Power</i>	real	undefined

9.2.395. Cht Flux

Scope: Equation System

```
Cht Flux Flux For Energy [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Cht_Flux [
Using Data Specification Data Spec Name ][ Power_Output = power_output |
Flux_Output = flux_output |Toggle = toggle |Too_Field = Too_Field |
H_Field = H_Field ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>Too_Field</i>	"string"	undefined
<i>H_Field</i>	"string"	undefined

Summary Applies H(T-Too) flux for conjugate heat transfer boundary. Optional parameters are "Too_Field" and "H_Field", which default to "nodal_cht_Too" and "nodal_cht_H" respectively.

9.2.396. Face Field Scalar

Scope: Equation System

```
Face Field Scalar Flux For Energy [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Face_Field_Scalar [ Using Data Specification Data Spec Name ][ Power_Output
= power_output |Flux_Output = flux_output |Toggle = toggle |Name = name |
Multiplier = multiplier |Advective_Bar = advective_bar |Command_Block_Name
= command_block_name ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>name</i>	"string"	undefined
<i>multiplier</i>	real	undefined
<i>advective_bar</i>	"string"	undefined
<i>command_block_name</i>	"string"	undefined

Summary FACE or EDGE Field energy flux

9.2.397. Cht Dirichlet Robin

Scope: Equation System

```

Cht Dirichlet Robin Flux For Energy [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Cht_Dirichlet_Robin [ Using Data Specification Data Spec Name ][
Power_Output = power_output |Flux_Output = flux_output |Toggle = toggle |
Temperature_Field = temperature_field |Heat_Flux_Field = heat_flux_field |
Density_Field = density_field |Specific_Heat_Field = specific_heat_field |
Thermal_Conductivity_Field = thermal_conductivity_field ]

```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>temperature_field</i>	"string"	undefined
<i>heat_flux_field</i>	"string"	undefined
<i>density_field</i>	"string"	undefined
<i>specific_heat_field</i>	"string"	undefined
<i>thermal_conductivity_field</i>	"string"	undefined

Summary Applies a Dirichlet-Robin style BC for the energy equation: $F_{\text{local}} = F_{\text{bc}} + \alpha * (T_{\text{local}} - T_{\text{bc}})$, where alpha is computed based on a 1D analytical solution.

9.2.398. Cht Robin

Scope: Equation System

```
Cht Robin Flux For Energy [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Cht_Robin [
Using Data Specification Data Spec Name ][ Power_Output = power_output |
Flux_Output = flux_output |Toggle = toggle ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined

Summary Applies a Robin-style BC of the form: $J \cdot n + h * (T - T_{\text{ref}})$.

Description J, h, and Tref should be specified using the material properties BC_HEAT_FLUX, HEAT_TRANSFER_COEFFICIENT, and BC_REFERENCE_TEMPERATURE in a material that is applied to the surface.

9.2.399. Rte Sp

Scope: Equation System

```
Rte Sp Flux For Energy [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Rte_Sp [ Using
Data Specification Data Spec Name ][ Power_Output = power_output |
Flux_Output = flux_output |Toggle = toggle |Order = order ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>order</i>	integer	undefined

Summary RTE flux for energy equation with Simplified Spherical Harmonic RTE model

9.2.400. Rte Field

Scope: Equation System

```
Rte Field Flux For Energy [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Rte_Field [
Using Data Specification Data Spec Name ][ Power_Output = power_output |
Flux_Output = flux_output |Toggle = toggle ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined

Summary RTE energy flux from a field

9.2.401. Pid Controlled Cooler

Scope: Equation System

```
Pid Controlled Cooler Flux For Energy [ {of|species|subindex} Species |{in|
|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Pid_Controlled_Cooler [ Using Data Specification Data Spec Name ][
Power_Output = power_output |Flux_Output = flux_output |Toggle = toggle |
```

P = *p* | I = *i* | D = *d* | Band = *Band* | Filter_Tau = *Filter_Tau* |
Setpoint_Function_Name = *Setpoint_Function_Name* | Control_Variable =
Control_Variable | Max_Cooling_Power = *Max_Cooling_Power*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>p</i>	real	undefined
<i>i</i>	real	undefined
<i>d</i>	real	undefined
<i>Band</i>	real	undefined
<i>Filter_Tau</i>	real	undefined
<i>Setpoint_Function_Name</i>	"string"	undefined
<i>Control_Variable</i>	"string"	undefined
<i>Max_Cooling_Power</i>	real	undefined

9.2.402. Pid Controlled

Scope: Equation System

Pid Controlled Flux For Energy [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [
Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Pid_Controlled
[Using Data Specification *Data Spec Name*][Power_Output = *power_output* |
Flux_Output = *flux_output* |Toggle = *toggle* |P = *p* |I = *i* |D = *d* |Band =
Band |Filter_Tau = *Filter_Tau* |Setpoint_Function_Name =
Setpoint_Function_Name |Control_Variable = *Control_Variable* |Max_Output =
Max_Output]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>p</i>	real	undefined
<i>i</i>	real	undefined
<i>d</i>	real	undefined
<i>Band</i>	real	undefined
<i>Filter_Tau</i>	real	undefined
<i>Setpoint_Function_Name</i>	"string"	undefined
<i>Control_Variable</i>	"string"	undefined
<i>Max_Output</i>	real	undefined

9.2.403. From Cht Temperature

Scope: Equation System

```

From Cht Temperature Disting For Energy [ {of|species|subindex} Species |
{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name
[ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
From_Cht_Temperature [ Using Data Specification Data Spec Name ][
Interface_Name = Interface_Name |Twall_Field = Twall_Field |Tref_Field =
Tref_Field |H_Field = H_Field ]

```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Interface_Name</i>	"string"	undefined
<i>Twall_Field</i>	"string"	undefined
<i>Tref_Field</i>	"string"	undefined
<i>H_Field</i>	"string"	undefined

Summary Energy distinguishing condition from conjugate heat transfer temperature

9.2.404. Circle Weld

Scope: Equation System

Circle Weld Flux For Energy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Circle_Weld [Using Data Specification *Data Spec Name*][Power_Output = *power_output* | Flux_Output = *flux_output* |Toggle = *toggle* |O_X = *o_x* |O_Y = *o_y* |O_Z = *o_z* |Ro_X = *ro_x* |Ro_Y = *ro_y* |Ro_Z = *ro_z* |A_X = *a_x* |A_Y = *a_y* |A_Z = *a_z* |W = *w* |Flux = *flux* |R = *r* |Max_Degrees = *max_degrees* |T_On = *t_on* |T_Off = *t_off* |Normal_Tolerance = *normal_tolerance*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>power_output</i>	"string"	undefined
<i>flux_output</i>	"string"	undefined
<i>toggle</i>	"string"	undefined
<i>o_x</i>	real	undefined
<i>o_y</i>	real	undefined
<i>o_z</i>	real	undefined
<i>ro_x</i>	real	undefined
<i>ro_y</i>	real	undefined
<i>ro_z</i>	real	undefined
<i>a_x</i>	real	undefined
<i>a_y</i>	real	undefined
<i>a_z</i>	real	undefined
<i>w</i>	real	undefined
<i>flux</i>	real	undefined
<i>r</i>	real	undefined
<i>max_degrees</i>	real	undefined
<i>t_on</i>	real	undefined
<i>t_off</i>	real	undefined
<i>normal_tolerance</i>	real	undefined

9.2.405. Vector String Function

Scope: Equation System

Vector String Function Flux For Hfem_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh*

Extent Name [*Touching TouchingMeshExtent* | *Opposing OpposingMeshExtent*] =
 Vector_String_Function [Using Data Specification *Data Spec Name*] [*F_X* =
f_x | *F_Y* = *f_y* | *F_Z* = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.406. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Solid_Z [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] {@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* | *Opposing OpposingMeshExtent*] =
 Scalar_String_Function [Using Data Specification *Data Spec Name*] [*F* = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.407. Kinematic

Scope: Equation System

Kinematic Disting For Solid_Z [{of|species|subindex} *Species* | {in|material_phase} *MaterialPhase*] {@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* | *Opposing OpposingMeshExtent*] = Kinematic [

Using Data Specification *Data Spec Name*][*V0* = *v0* | *Shared_Normal* = *shared_normal* | *No_Mesh_Movement* = *no_mesh_movement*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>v0</i>	real	undefined
<i>shared_normal</i>	"string"	undefined
<i>no_mesh_movement</i>	"string"	undefined

Summary Kinematic model for SOLID_z distinguishing condition

9.2.408. Recession

Scope: Equation System

Recession Disting For Solid_Z [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* | *Opposing OpposingMeshExtent*]= Recession [Using Data Specification *Data Spec Name*][*T_Ref* = *t_ref* | *K* = *k* | *K_0* = *k_0* | *N* = *n* | *Temperature* = *temperature*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>t_ref</i>	real	undefined
<i>k</i>	real	undefined
<i>k_0</i>	real	undefined
<i>n</i>	real	undefined
<i>temperature</i>	"string"	undefined

Summary Recession model for SOLID_x distinguishing condition

9.2.409. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Enthalpy [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.410. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Hfem_Specific_Dissipation_Rate [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.411. Low Reynolds

Scope: Equation System

Low Reynolds Disting For Hfem_Specific_Dissipation_Rate [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing*

OpposingMeshExtent]= Low_Reynolds [Using Data Specification *Data Spec Name*][*Scale_Factor* = *scale_factor*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>scale_factor</i>	real	undefined

Summary HFEM specific dissipation rate distinguishing condition

9.2.412. Vector String Function

Scope: Equation System

Vector String Function Rotated For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
 Vector_String_Function [Using Data Specification *Data Spec Name*][*F_X* = *f_x* |*F_Y* = *f_y* |*F_Z* = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.413. Spring Force

Scope: Equation System

Spring Force Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= Spring_Force [Using Data Specification *Data Spec Name*][*Mult* = *Mult*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Mult</i>	real	undefined

Summary Spring force for momentum boundary condition

9.2.414. Node Normal Capillary

Scope: Equation System

```
Node Normal Capillary Flux For Momentum [ {of|species|subindex} Species |
{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Node_Normal_Capillary [ Using Data Specification Data Spec Name ][ ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary This model has been deprecated and removed from the code.

9.2.415. Symmetry Flow

Scope: Equation System

```
Symmetry Flow Flux For Momentum [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Symmetry_Flow [
Using Data Specification Data Spec Name ][ ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Symmetry flow momentum flux

9.2.416. Open Flow Darcy

Scope: Equation System

```
Open Flow Darcy Flux For Momentum [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Open_Flow_Darcy
[ Using Data Specification Data Spec Name ][ Pressure = pressure |
Total_Pressure = total_pressure ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined

Summary Open flow momentum flux

9.2.417. Reconstructed Curvature

Scope: Equation System

```
Reconstructed Curvature Flux For Momentum [ {of|species|subindex} Species
|{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent
Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Reconstructed_Curvature [ Using Data Specification Data Spec Name ][
Ls_Size = ls_size |Fixed_Curvature = fixed_curvature ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>ls_size</i>	integer	undefined
<i>fixed_curvature</i>	real	undefined

Summary This model has been deprecated and removed from the code.

9.2.418. Fixed Curvature

Scope: Equation System

Fixed Curvature Flux For Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Fixed_Curvature [Using Data Specification *Data Spec Name*][Curvature = *curvature*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>curvature</i>	real	undefined

Summary This model has been deprecated and removed from the code.

9.2.419. Simple Interp

Scope: Equation System

Simple Interp Flux For Cvfem_Sdr_Edge_Gradient_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Simple_Interp [Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary CVFEM edge-based projection simple interpolation flux BC

9.2.420. Scalar String Function

Scope: Equation System

Scalar String Function Flux For Cvfem_Sdr_Edge_Gradient_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing

OpposingMeshExtent]= Scalar_String_Function [Using Data Specification
Data Spec Name][F = *f*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.421. Pspg

Scope: Equation System

Pspg Fluxbp For Continuity [{of|species|subindex} *Species* |{in|
material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [
Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Pspg [Using
Data Specification *Data Spec Name*][Tausurfacefactor = *TauSurfaceFactor* |
Tausurfacejacobianfactor = *TauSurfaceJacobianFactor*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>TauSurfaceFactor</i>	real	undefined
<i>TauSurfaceJacobianFactor</i>	real	undefined

Summary Continuity PSPG flux BP BC

9.2.422. Scalar String Function

Scope: Equation System

Scalar String Function Disting For Momentum_Y [{of|species|subindex}
Species |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh
Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*
]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.423. Symmetry Flow

Scope: Equation System

Symmetry Flow Flux For Cvfem_Solvent_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Symmetry_Flow [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary CVFEM solvent momentum symmetry flow flux BC

9.2.424. Vector String Function

Scope: Equation System

Vector String Function Flux For Cvfem_Solvent_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Vector_String_Function [Using Data Specification *Data Spec Name*] [F_X = *f_x* |F_Y = *f_y* |F_Z = *f_z*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_x</i>	"string"	undefined
<i>f_y</i>	"string"	undefined
<i>f_z</i>	"string"	undefined

Summary Value from a string function

9.2.425. Open Adv Flow

Scope: Equation System

```

Open Adv Flow Flux For Cvfem_Solvent_Momentum [ {of|species|subindex}
Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh
Extent Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Open_Adv_Flow [ Using Data Specification Data Spec Name ][ Pressure =
pressure |Total_Pressure = total_pressure |Coflow_Entrainment_Value_X =
coflow_entrainment_value_x |Coflow_Entrainment_Value_Y =
coflow_entrainment_value_y |Coflow_Entrainment_Value_Z =
coflow_entrainment_value_z ]

```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined
<i>coflow_entrainment_value_x</i>	real	undefined
<i>coflow_entrainment_value_y</i>	real	undefined
<i>coflow_entrainment_value_z</i>	real	undefined

Summary CVFEM solvent momentum open advective flow flux BC

9.2.426. Open Flow

Scope: Equation System

Open Flow Flux For Cvfem_Solvent_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Open_Flow [Using Data Specification *Data Spec Name*][Pressure = *pressure* |Total_Pressure = *total_pressure*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>pressure</i>	real	undefined
<i>total_pressure</i>	real	undefined

Summary CVFEM solvent momentum open flow flux BC

9.2.427. Simple Interp Vector

Scope: Equation System

Simple Interp Vector Flux For Cvfem_Div_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Simple_Interp_Vector [Using Data Specification *Data Spec Name*][Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary CVFEM divergence projection simple interpolation vector flux BC

9.2.428. Simple Interp Tensor

Scope: Equation System

Simple Interp Tensor Flux For Cvfem_Div_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=

Simple_Interp_Tensor [Using Data Specification *Data Spec Name*][Source = *source*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary CVFEM divergence projection simple interpolation tensor flux BC

9.2.429. Tensor String Function Symmetric

Scope: Equation System

Tensor String Function Symmetric Flux For Cvfem_Div_Projection [{of | species|subindex} *Species* | {in|material_phase} *MaterialPhase*]{@|at|for| in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* | *Opposing OpposingMeshExtent*] = Tensor_String_Function_Symmetric [Using Data Specification *Data Spec Name*][$F_{Xx} = f_{xx}$ | $F_{Yy} = f_{yy}$ | $F_{Xy} = f_{xy}$ | $F_{Zz} = f_{zz}$ | $F_{Xz} = f_{xz}$ | $F_{Yz} = f_{yz}$]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
f_{xx}	"string"	undefined
f_{yy}	"string"	undefined
f_{xy}	"string"	undefined
f_{zz}	"string"	undefined
f_{xz}	"string"	undefined
f_{yz}	"string"	undefined

Summary Value from a string function

9.2.430. Tensor String Function

Scope: Equation System

Tensor String Function Flux For Cvfem_Div_Projection [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Tensor_String_Function [Using Data Specification *Data Spec Name*] [F_Xx = *f_xx* |F_Yy = *f_yy* |F_Xy = *f_xy* |F_Zz = *f_zz* |F_Xz = *f_xz* |F_Yz = *f_yz* |F_Yx = *f_yx* |F_Zx = *f_zx* |F_Zy = *f_zy*]

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f_xx</i>	"string"	undefined
<i>f_yy</i>	"string"	undefined
<i>f_xy</i>	"string"	undefined
<i>f_zz</i>	"string"	undefined
<i>f_xz</i>	"string"	undefined
<i>f_yz</i>	"string"	undefined
<i>f_yx</i>	"string"	undefined
<i>f_zx</i>	"string"	undefined
<i>f_zy</i>	"string"	undefined

Summary Value from a string function

9.2.431. Symmetry Flow

Scope: Equation System

Symmetry Flow Flux For Cvfem_Dispersed_Momentum [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Symmetry_Flow [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

9.2.432. Open Flow

Scope: Equation System

```
Open Flow Flux For Cvfm_Dispersed_Momentum [ {of|species|subindex} Species
|{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent
Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Open_Flow [ Using Data Specification Data Spec Name ][ ]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

9.2.433. Scalar String Function

Scope: Equation System

```
Scalar String Function Disting For Mass_Balance [ {of|species|subindex}
Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh
Extent Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Scalar_String_Function [ Using Data Specification Data Spec Name ][ F = f
]
```

Parameter	Value	Default
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.434. Bc Bulk Node Coupling For Density = K Factor Flow

Scope: Equation System

```
Bc Bulk Node Coupling For Density = K Factor Flow [ Flow_Rate_Limiter =
flow_rate_limiter ]
```

Parameter	Value	Default
<i>flow_rate_limiter</i>	real	undefined

Summary Volumetric flow rate, Q , calculated as $Q = K \sqrt{\frac{P_{high}-P_{low}}{\rho}}$. Absent any other sources, the maximum flow rate is defined based on the mass loss to achieve pressure equilibrium and the fluid time step. If the optional flow rate limiter is specified, the flow rate is limited by the product of the limiter factor and the maximum flow rate without any other sources.

9.2.435. Bc Bulk Node Coupling For Density = K Factor Flow With Choking

Scope: Equation System

Bc Bulk Node Coupling For Density = K Factor Flow With Choking [Critical_Pressure_Ratio = *critical_pressure_ratio* | Flow_Rate_Limiter = *flow_rate_limiter*]

Parameter	Value	Default
<i>critical_pressure_ratio</i>	real	undefined
<i>flow_rate_limiter</i>	real	undefined

Summary Volumetric flow rate, Q , calculated as $Q = K \sqrt{\frac{(P_{high}-P_{low})}{\rho}}$ for $\frac{P_{high}}{P_{low}} < R_p$, where R_p is the critical_pressure_ratio. Above R_p the flow rate is calculated as $Q = K * \sqrt{\frac{P_{high}(1-1/R_p)}{\rho}}$. Absent any other sources, the maximum flow rate is defined based on the mass loss to achieve pressure equilibrium and the fluid time step. If the optional flow rate limiter is specified, the flow rate is limited by the product of the limiter factor and the maximum flow rate without any other sources.

9.2.436. Bc Bulk Node Coupling For Species = K Factor Flow

Scope: Equation System

Bc Bulk Node Coupling For Species = K Factor Flow [Flow_Rate_Limiter = *flow_rate_limiter*]

Parameter	Value	Default
<i>flow_rate_limiter</i>	real	undefined

Summary Volumetric flow rate, Q , calculated as $Q = K \sqrt{\frac{P_{high}-P_{low}}{\rho}}$. Absent any other sources, the maximum flow rate is defined based on the mass loss to achieve pressure equilibrium and the fluid time step. If the optional flow rate limiter is specified, the flow rate is limited by the product of the limiter factor and the maximum flow rate without any other sources.

9.2.437. Bc Bulk Node Coupling For Species = K Factor Flow With Choking

Scope: Equation System

Bc Bulk Node Coupling For Species = K Factor Flow With Choking [
Critical_Pressure_Ratio = *critical_pressure_ratio* |Flow_Rate_Limiter =
flow_rate_limiter]

Parameter	Value	Default
<i>critical_pressure_ratio</i>	real	undefined
<i>flow_rate_limiter</i>	real	undefined

Summary Volumetric flow rate, Q , calculated as $Q = K \sqrt{\frac{(P_{high} - P_{low})}{\rho}}$ for $\frac{P_{high}}{P_{low}} < R_p$, where R_p is the critical_pressure_ratio. Above R_p the flow rate is calculated as $Q = K * \sqrt{\frac{P_{high}(1 - 1/R_p)}{\rho}}$. Absent any other sources, the maximum flow rate is defined based on the mass loss to achieve pressure equilibrium and the fluid time step. If the optional flow rate limiter is specified, the flow rate is limited by the product of the limiter factor and the maximum flow rate without any other sources.

9.2.438. Scalar String Function

Scope: Equation System

Scalar String Function For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [
Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*
]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.439. Darcy

Scope: Equation System

Darcy For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Darcy [Using Data Specification *Data Spec Name*] [Gx = g_x |Gy = g_y |Gz = g_z |Relative_To = *relative_to*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
g_x	real	undefined
g_y	real	undefined
g_z	real	undefined
<i>relative_to</i>	"string"	undefined

Summary This model is designed to provide the normalized fluid velocity within a matrix that itself may be moving. If the matrix phase has a velocity the fluid velocity returned will be in the lab frame. If not relative phase is provided, the matrix phase is assumed to have a velocity of zero. $u_g = v_r \phi - \frac{k_r}{\mu} \mathbf{K}_i (\nabla P_g - \rho_g \vec{g})$

9.2.440. Copied

Scope: Equation System

Copied For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Copied [Using Data Specification *Data Spec Name*] [Source = *source*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

9.2.441. From Chemeq

Scope: Equation System

From Chemeq For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= From_Chemeq [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Species fraction of one species extracted from ChemEq

9.2.442. Scalar String Function

Scope: Equation System

Scalar String Function For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*] [$F = f$]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.443. User Plugin

Scope: Equation System

User Plugin For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= User_Plugin [Using Data Specification *Data Spec Name*][Name = Name | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

9.2.444. Copied

Scope: Equation System

Copied For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Copied [Using Data Specification *Data Spec Name*][Source = *source*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

9.2.445. Copied

Scope: Equation System

Copied For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Copied [Using Data Specification *Data Spec Name*][Source = *source*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

9.2.446. User Plugin

Scope: Equation System

User Plugin For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= User_Plugin [Using Data Specification *Data Spec Name*][Name = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

9.2.447. Scalar String Function

Scope: Equation System

Scalar String Function For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Scalar_String_Function [Using Data Specification *Data Spec Name*][$F = f$
]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
f	"string"	undefined

Summary Value from a string function

9.2.448. Schloegl

Scope: Equation System

Schloegl For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Schloegl [Using Data Specification *Data Spec Name*][$K\_Phi = k\_phi$ | $F = f$ | $Gx = gx$ | $Gy = gy$ | $Gz = gz$ |Proton_Name = *proton_name*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
k_phi	real	undefined
f	real	undefined
gx	real	undefined
gy	real	undefined
gz	real	undefined
<i>proton_name</i>	"string"	undefined

9.2.449. Darcy Solvent

Scope: Equation System

Darcy Solvent For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Darcy_Solvent [Using Data Specification *Data Spec Name*][*Gx* = *gx* |*Gy* = *gy* |*Gz* = *gz* | Relative_To = *relative_to*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>gx</i>	real	undefined
<i>gy</i>	real	undefined
<i>gz</i>	real	undefined
<i>relative_to</i>	"string"	undefined

Summary This model is intended for problems where the porous species equation is being solved for pressure with a solvent species concentration as the mass term in order to solve for the velocity of that solvent species.

9.2.450. User Plugin

Scope: Equation System

User Plugin For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= User_Plugin [Using Data Specification *Data Spec Name*][*Name* = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

9.2.451. User Plugin

Scope: Equation System

User Plugin For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= User_Plugin [Using Data Specification *Data Spec Name*][Name = Name | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

9.2.452. Copied

Scope: Equation System

Copied For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Copied [Using Data Specification *Data Spec Name*][Source = source]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

9.2.453. Scalar String Function

Scope: Equation System

Scalar String Function For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Scalar_String_Function [Using Data Specification *Data Spec Name*][*F* = *f*
]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.454. Copied

Scope: Equation System

Copied For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Copied [Using Data Specification *Data Spec Name*][*Source* = *source*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

9.2.455. Melting Capillary Darcy

Scope: Equation System

Melting Capillary Darcy For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Melting_Capillary_Darcy [Using Data Specification *Data Spec Name*] [
Melt_Dt = *melt_DT* |Melt_Time = *melt_time* |Gx = *gx* |Gy = *gy* |Gz = *gz*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>melt_DT</i>	real	undefined
<i>melt_time</i>	real	undefined
<i>gx</i>	real	undefined
<i>gy</i>	real	undefined
<i>gz</i>	real	undefined

9.2.456. From Species

Scope: Equation System

From Species For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= From_Species [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Species fraction of one species from it's concentration and the overall concentration

9.2.457. Copied

Scope: Equation System

Copied For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]{@|at|for|in|on|over} *Mesh Extent Name* [Touching
TouchingMeshExtent |Opposing *OpposingMeshExtent*]= Copied [Using Data
Specification *Data Spec Name*][Source = *source*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

9.2.458. Copied

Scope: Equation System

Copied For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase}
MaterialPhase]{@|at|for|in|on|over} *Mesh Extent Name* [Touching
TouchingMeshExtent |Opposing *OpposingMeshExtent*]= Copied [Using Data
Specification *Data Spec Name*][Source = *source*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

9.2.459. Cht Robin

Scope: Equation System

```
Cht Robin For Dof Name [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Cht_Robin [
Using Data Specification Data Spec Name ][ Temperature_Field =
temperature_field ]
```

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>temperature_field</i>	"string"	undefined

Summary Dirichlet boundary condition for interface coupled with Robin style BC CHT_ROBIN. This BC computes the heat flux for the other side. Dirichlet boundary condition for interface coupled with Robin style BC CHT_ROBIN. This BC computes the heat flux for the other side.

9.2.460. Fortran User Sub

Scope: Equation System

```
Fortran User Sub For Dof Name [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]=
Fortran_User_Sub [ Using Data Specification Data Spec Name ][ Multiplier =
multiplier |Name = name |Type = type |Real_Data = real_data |Int_Data =
int_data |Resource_Name = resource_name |Data = data |Material_Data_Block
= material_data_block ]
```

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>real_data</i>	"string"	undefined
<i>int_data</i>	"string"	undefined
<i>resource_name</i>	"string"	undefined
<i>data</i>	"string"	undefined
<i>material_data_block</i>	"string"	undefined

Summary Dirichlet value from a Fortran user subroutineDirichlet value from a Fortran user subroutine

9.2.461. Scalar String Function

Scope: Equation System

Scalar String Function For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*][*F = f*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.462. Scalar String Function

Scope: Equation System

Scalar String Function For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*][$F = f$]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.463. Scalar String Function

Scope: Equation System

Scalar String Function For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*][$F = f$]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string functionValue from a string function

9.2.464. Copied

Scope: Equation System

Copied For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching

TouchingMeshExtent |Opposing *OpposingMeshExtent*]= Copied [Using Data Specification *Data Spec Name*][Source = *source*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

9.2.465. Scalar String Function

Scope: Equation System

Scalar String Function For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.466. User Plugin

Scope: Equation System

User Plugin For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= User_Plugin [Using Data Specification *Data Spec Name*][Name = *Name* |
magic_trailing_string_vector_param]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

9.2.467. User Plugin

Scope: Equation System

User Plugin For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= User_Plugin [Using Data Specification *Data Spec Name*][*Name = Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user pluginValue from a user plugin

9.2.468. User Plugin

Scope: Equation System

User Plugin For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= User_Plugin [Using Data Specification *Data Spec Name*][*Name = Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

9.2.469. User Plugin

Scope: Equation System

User Plugin For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= User_Plugin [Using Data Specification *Data Spec Name*][*Name* = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

9.2.470. Copied

Scope: Equation System

Copied For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Copied [Using Data Specification *Data Spec Name*][*Source* = *source*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

9.2.471. Mass Average

Scope: Equation System

Mass Average For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Mass_Average [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Enthalpy computed from mass average of species enthalpies

9.2.472. Copied

Scope: Equation System

Copied For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Copied [Using Data Specification *Data Spec Name*] [Source = *source*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expressionCopied value from another expression

9.2.473. From Mesh Displacement

Scope: Equation System

From Mesh Displacement For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
From_Mesh_Displacement [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

9.2.474. Scalar String Function

Scope: Equation System

Scalar String Function For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Scalar_String_Function [Using Data Specification *Data Spec Name*] [F = f]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.475. User Plugin

Scope: Equation System

User Plugin For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= User_Plugin [Using Data Specification *Data Spec Name*][Name = Name | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

9.2.476. User Plugin

Scope: Equation System

User Plugin For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= User_Plugin [Using Data Specification *Data Spec Name*][Name = Name | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_parameter</i>	string	undefined

Summary Value from a user plugin

9.2.477. Vector String Function

Scope: Equation System

Vector String Function For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
 Vector_String_Function [Using Data Specification *Data Spec Name*][$F_X = f_x$ | $F_Y = f_y$ | $F_Z = f_z$]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
f_x	"string"	undefined
f_y	"string"	undefined
f_z	"string"	undefined

Summary Value from a string function

9.2.478. Scalar String Function

Scope: Equation System

Scalar String Function For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*][$F = f$]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.479. Copied

Scope: Equation System

Copied For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Copied [Using Data Specification *Data Spec Name*][Source = *source*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

9.2.480. Copied

Scope: Equation System

Copied For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Copied [Using Data Specification *Data Spec Name*][Source = *source*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

9.2.481. User Plugin

Scope: Equation System

```
User Plugin For Dof Name [ {of|species|subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= User_Plugin [ Using Data Specification Data Spec Name ][ Name = Name | magic_trailing_string_vector_param ]
```

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

9.2.482. Cantera

Scope: Equation System

```
Cantera For Dof Name [ {of|species|subindex} Species |{in|material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [ Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Cantera [ Using Data Specification Data Spec Name ][ Poffset = poffset ]
```


Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>poffset</i>	real	undefined

Summary Cantera enthalpy

9.2.483. From Temperature

Scope: Equation System

From Temperature For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
From_Temperature [Using Data Specification *Data Spec Name*][Value = *value* |T = *t* |Poffset = *poffset*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>value</i>	real	undefined
<i>t</i>	real	undefined
<i>poffset</i>	real	undefined

Summary Cantera enthalpy computed from temperature

9.2.484. Scalar String Function

Scope: Equation System

Scalar String Function For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.485. Copied

Scope: Equation System

Copied For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Copied [Using Data Specification *Data Spec Name*] [Source = *source*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

9.2.486. Copied

Scope: Equation System

Copied For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Copied [Using Data Specification *Data Spec Name*] [Source = *source*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

9.2.487. Copied

Scope: Equation System

Copied For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Copied [Using Data Specification *Data Spec Name*][Source = *source*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>source</i>	"string"	undefined

Summary Copied value from another expression

9.2.488. Scalar String Function

Scope: Equation System

Scalar String Function For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Scalar_String_Function [Using Data Specification *Data Spec Name*][F = *f*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.489. User Plugin

Scope: Equation System

```
User Plugin For Dof Name [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= User_Plugin [
Using Data Specification Data Spec Name ][ Name = Name |
magic_trailing_string_vector_param ]
```

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

9.2.490. Calore User Sub

Scope: Equation System

```
Calore User Sub For Dof Name [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= Calore_User_Sub
[ Using Data Specification Data Spec Name ][ Multiplier = multiplier |Name
= name |Type = type |Material_Data_Block = material_data_block |Data =
data ]
```

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>multiplier</i>	real	undefined
<i>name</i>	"string"	undefined
<i>type</i>	"string"	undefined
<i>material_data_block</i>	"string"	undefined
<i>data</i>	"string"	undefined

Summary Values from a Calore user subroutineValues from a Calore user subroutine

9.2.491. From No Material Phase

Scope: Equation System

From No Material Phase For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
From_No_Material_Phase [Using Data Specification *Data Spec Name*][]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Copy the temperature from NO_MATERIAL_PHASE to the desired material phase.Copy the temperature from NO_MATERIAL_PHASE to the desired material phase.

9.2.492. Scalar String Function

Scope: Equation System

Scalar String Function For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=

Scalar_String_Function [Using Data Specification *Data Spec Name*][$F = f$]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.493. Cantera

Scope: Equation System

Cantera For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= Cantera [Using Data Specification *Data Spec Name*][*Omit_Fd_Sens* = *omit_fd_sens*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>omit_fd_sens</i>	integer	undefined

Summary Cantera enthalpy computed from temperatureCantera enthalpy computed from temperature

9.2.494. User Plugin

Scope: Equation System

User Plugin For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]= User_Plugin [Using Data Specification *Data Spec Name*][*Name* = *Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	string	undefined

Summary Value from a user plugin

9.2.495. Scalar String Function

Scope: Equation System

Scalar String Function For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*][*F = f*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.496. User Plugin

Scope: Equation System

User Plugin For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [*Touching TouchingMeshExtent* |*Opposing OpposingMeshExtent*]= User_Plugin [Using Data Specification *Data Spec Name*][*Name = Name* | *magic_trailing_string_vector_param*]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_parameter</i>	string	undefined

Summary Value from a user plugin

9.2.497. Scalar String Function

Scope: Equation System

Scalar String Function For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 Scalar_String_Function [Using Data Specification *Data Spec Name*] [F = f]

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>f</i>	"string"	undefined

Summary Value from a string function

9.2.498. From Other Phase

Scope: Equation System

From Other Phase For *Dof Name* [{of|species|subindex} *Species* |{in|material_phase} *MaterialPhase*]{@|at|for|in|on|over} *Mesh Extent Name* [Touching *TouchingMeshExtent* |Opposing *OpposingMeshExtent*]=
 From_Other_Phase [Using Data Specification *Data Spec Name*] []

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined

Summary Get the saturation from one minus the other phase saturation

9.2.499. User Plugin

Scope: Equation System

```
User Plugin For Dof Name [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= User_Plugin [
Using Data Specification Data Spec Name ][ Name = Name |
magic_trailing_string_vector_param ]
```

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_param</i>	"string"	undefined

Summary Value from a user plugin

9.2.500. User Plugin

Scope: Equation System

```
User Plugin For Dof Name [ {of|species|subindex} Species |{in|
material_phase} MaterialPhase ]{@|at|for|in|on|over} Mesh Extent Name [
Touching TouchingMeshExtent |Opposing OpposingMeshExtent ]= User_Plugin [
Using Data Specification Data Spec Name ][ Name = Name |
magic_trailing_string_vector_param ]
```

Parameter	Value	Default
<i>Dof Name</i>	string	undefined
<i>Species</i>	string	undefined
<i>MaterialPhase</i>	string	undefined
<i>Mesh Extent Name</i>	string	undefined
<i>TouchingMeshExtent</i>	string	undefined
<i>OpposingMeshExtent</i>	string	undefined
<i>Data Spec Name</i>	string	undefined
<i>Name</i>	"string"	undefined
<i>magic_trailing_string_vector_parameter</i>	string	undefined

Summary Value from a user plugin

9.2.501. Bc Interface Colloc Disting For Lubrication Height = Deforming

Scope: Equation System

Bc Interface Colloc Disting For Lubrication Height = Deforming [$H_{min} = h_{min}$]

Parameter	Value	Default
<i>hmin</i>	real	undefined

Summary Collocated distinguishing condition for the lubrication height that deforms by the displacement of the adjoining volume region.

9.3. PERIODIC BC OVERVIEW

Aria provides a periodic boundary condition capability. Two flavors of periodicity are supported, standard periodicity for surfaces separated by fixed distance and cyclic periodicity for surfaces separated through a fixed rotation angle as illustrated in Figure 9.3-1. The underlying implementation is based upon augmenting the basic governing equations with multi-point constraints on nodal DOF at the periodic boundaries and is equally applicable to scalar and vector DOF. The enforcement employs nodal DOF, hence the capability is limited to grids with conforming surface nodes, i.e. the mesh is periodic as well.

Internally, a search procedure is used in order to define master-slave node constraint pairs. Since a meshed discretization is subject to intrinsic error in the nodal coordinates, an acceptable tolerance specification is used to insure that master-slave pairings are appropriately defined. Note that application of large tolerances may lead to incorrectly defined master-slave pairings. Additional quantities required for cyclic periodicity are referenced in 9.4.7.



Figure 9.3-1.. Standard and Cyclic Periodicity

9.4. PERIODIC

Scope: Aria Region

Begin Periodic *Name*

Master {=|are|is} *Master*

Point On Axis {=|are|is} *Point*

Reference Axis {=|are|is} *Axis*

Search Tolerance {=|are|is} *SearchTolerance*

Slave {=|are|is} *Slave*

Theta {=|are|is} *Theta*

End

Summary The periodic command block is used to define periodic, or cyclic, boundary conditions.

Description For standard periodic boundary conditions, the line commands MASTER, SLAVE, SEARCH TOLERANCE should appear, while the line commands THETA, POINT ON AXIS, and REFERENCE AXIS must not appear.

Cyclic boundary conditions, the line commands MASTER, SLAVE, SEARCH TOLERANCE, THETA, POINT ON AXIS, and REFERENCE AXIS must appear.

Two self-similar side sets for the boundary condition are specified by the MASTER and SLAVE command lines. It must be possible to replicate the coordinates for the nodes in one set by a simple translation of the corresponding nodes in the other set.

A geometric check is made to determine if the side sets are self similar. The geometric check is set to a certain tolerance. This tolerance must be set to a small positive number (e.g. 10^{-4}) by using the command line SEARCH TOLERANCE. After translation each node in the set of slave nodes lies within a radius defined by the search tolerance from a

node in the set of master nodes. Additionally, upon transformation, slave nodes must lie in the interpolation space of at least one facet in the master surface. When these two conditions are satisfied the two sets are considered self-similar.

9.4.1. Master

Scope: Periodic

Master {=|are|is} *Master*

Parameter	Value	Default
<i>Master</i>	string	undefined

Summary Defines master surface for this interaction. When used in Aria and Calore, this must always be a sideset.

9.4.2. Point On Axis

Scope: Periodic

Point On Axis {=|are|is} *Point*

Parameter	Value	Default
<i>Point</i>	string	undefined

Summary This line command defines a point that lies on the reference axis.

9.4.3. Reference Axis

Scope: Periodic

Reference Axis {=|are|is} *Axis*

Parameter	Value	Default
<i>Axis</i>	string	undefined

Summary This line command defines the reference wedge axis for the periodic BC about which the master surface is rotated to transform it into the slave surface.

9.4.4. Search Tolerance

Scope: Periodic

Search Tolerance {=|are|is} *SearchTolerance*

Parameter	Value	Default
<i>SearchTolerance</i>	real	undefined

Summary This line command defines the search tolerance used to determine if two node sets are self similar.

9.4.5. Slave

Scope: Periodic

Slave {=|are|is} *Slave*

Parameter	Value	Default
<i>Slave</i>	string	undefined

Summary Defines slave surface for this interaction. When used in Aria and Calore, this may be a nodeset or a sideset.

9.4.6. Theta

Scope: Periodic

Theta {=|are|is} *Theta*

Parameter	Value	Default
<i>Theta</i>	real	undefined

Summary This line command defines the angle, in degrees, for a periodic boundary condition. A positive angle is defined by sweeping the master surface through the domain to the slave surface.

9.4.7. Cyclic Periodic BC Parameters

Cyclic periodicity requires that the user specify both Reference Axis of rotation and Point on Axis (a point on the reference axis) in the Begin Periodic command block. Here Reference Axis and Point on Axis are associated with Define Direction and Define Point respectively. These two additional quantities are usually defined at the Domain scope (outside of the Procedure).

9.4.8. Define Direction

Scope:

Define Direction *DirectName* With Vector *Components*₁ *Components*₂ *Components*₃

Parameter	Value	Default
<i>DirectName</i>	string	undefined
<i>Components</i>	real_1 real_2 real_3	undefined

Summary Defines a named spatial direction in terms of vector components.

9.4.9. Define Point

Scope:

Define Point *PointName* With Coordinates *Coordinates*₁ *Coordinates*₂ *Coordinates*₃

Parameter	Value	Default
<i>PointName</i>	string	undefined
<i>Coordinates</i>	real_1 real_2 real_3	undefined

Summary Defines a named point in space in terms of its coordinates.

9.5. COUPLING BCS FOR ORGANIC MATERIAL DECOMPOSITION

Aria provides the capability of coupling between porous (see section 5.12.2.7) and fluid blocks using flux-style boundary conditions. The boundary conditions described here are for a single region computation; for the most part, these boundary conditions can be used for a multi-region computation with the phrase ‘one_region’ omitted. These boundary conditions are imposed as Robin boundary conditions,

$$\begin{aligned} F_P &= \rho_F \mathbf{u}_F \cdot \mathbf{n} + \beta(p_g - p_F) \\ F_F &= \rho_g \mathbf{u}_g \cdot \mathbf{n} + \beta(p_F - p_g) \end{aligned} \quad (9.42)$$

where F_P is the flux into the porous region and F_F is the flux into the fluid region. The boundary conditions for the pressure mass balance equation on the porous side and the corresponding flux condition on the fluid side CVFEM continuity equation are written as

BC flux for mass_balance in gas_phase on surface = fluid_robin_coupled_one_region
BC flux for cvfem_continuity on surface = porous_robin_one_region

This boundary condition uses a penalty coefficient of the form

$$\beta = \frac{c_{scaling}\rho_g K}{\mu_g h} \quad (9.43)$$

where h is the mesh width adjacent to the interface (need to check what happens with a non-uniform mesh). The default value of $c_{scaling}$ is 0.001. If this parameter is too large, the increase in pressure might be underpredicted.

A distinguishing boundary condition is used on the fluid momentum equation,

$$u_j - (u_{j,n}^D + u_{j,t}^D) = 0, \quad (9.44)$$

where $u_{j,n}^D$ is the imposed normal component of velocity and $u_{j,t}^D$ is the imposed tangential component of velocity. The normal component is computed directly from the continuity flux at the interface,

$$u_{j,n}^D = \frac{F_F}{\rho_F} n_j. \quad (9.45)$$

The tangential component is based on a variation of the classical Beavers-Joseph-Saffman condition [21, 22] for the slip velocity which has been extended to non-planar surfaces in multidimensional flow [23], which defines a provisional model velocity

$$u_j^{BJS} = -\frac{\sqrt{\bar{K}}}{\alpha\mu} (n_i \tau_{ij}) \quad (9.46)$$

where $\bar{K}$ is the permeability of the porous region at the interface, μ is the viscosity of the local fluid at the interface, τ_{ij} is the viscous stress tensor of the fluid at the interface, and α is a dimensionless model parameter that is a function of the microstructure of the porous material, which has been found to have typical values near 0.1 [22]. The tangential component of this vector quantity is used as the tangential component of the distinguishing condition velocity, and is computed as

$$u_{j,t}^D = u_j^{BJS} - (u_k^{BJS} n_k) n_j. \quad (9.47)$$

which is written in the input file as

```
BC Disting for cvfem_momentum on surface = porous_robin_one_region
```

The flux of a species k across a porous-fluid interface is

$$\mathbf{J}_P^{Y_k} = \mathbf{J}_F^{diff} + F_P \rho_g Y_{k,PF} + \left(\frac{D_k \rho_f}{h} \right) (Y_{k,P} - Y_{k,F}) \quad (9.48)$$

where P refers to porous side, F refers to the fluid side and $Y_{k,PF}$ is the upwinded interface mass fraction, equivalent to h_{PF} from the enthalpy coupling. The mass fraction coupling boundary condition on the porous side is written as

```
BC flux for mass_balance in phase on surface = fluid_robin_coupled_one_region
```

The enthalpy coupling boundary conditions in the porous region are

```
BC flux for porous_enthalpy in phase on surface = fluid_robin_coupled_with_solid_convection_one_region
BC flux for porous_enthalpy in phase on surface = fluid_solid_convection_coupled_one_region
```

9.6. BC EDGE

Edge boundary conditions are implemented in Aria to introduce physics at the intersection between two surfaces. In 2D this is a point (the intersection of two element edges) and in 3D this is an edge (the intersection of two element faces). These edge conditions can be applied on any equation system.

9.6.1. BC EDGE = WETTING

Parameters

`theta_s = REAL`

Example

BC Edge for momentum where `surface_1` intersects `surface_2` =
wetting `theta_s = 120`.

Description This condition applies the edge BC on the momentum equation for a wetting line defined as the intersection between `surface_1` and `surface_2`. The parameter `theta_s` is the static angle between the two surfaces and must be known a priori. This edge BC applies a constant surface traction proportional to the surface tension force defined on `surface_2` in the direction of the wetting angle supplied as `theta_s`. Note that the surface tension force must be supplied in a material block and applied as a parameter for `surface_2` (see section 4.50).

This force is defined formally as:

$$\vec{f} = \gamma \hat{\tau}_i \quad (9.49)$$

where γ represents the surface tension in (N/m) and $\hat{\tau}_i$ is the unit vector defined as

$$\hat{\tau}_i = \hat{\tau}_w \cos \theta_s + \hat{n}_w \sin \theta_s \quad (9.50)$$

In the above equation, $\hat{\tau}_w$ and $\hat{n}_w$ are defined as the wall-tangent and wall-normal vectors of `surface_1`, respectively and θ_s is the wetting angle parameter.

10. DISTINGUISHING CONDITIONS

10.1. AN INTRODUCTION TO DISTINGUISHING CONDITIONS

Aria's *distinguishing condition* (DC) feature is an essential ingredient in solving many coupled physics problems. A distinguishing condition is really just another equation specification except that it typically replaces a regular equation on a subset of the domain such as a surface.

For example, in solving fluids problems with a free surface where the mesh boundary moves with the material, e.g., an ALE simulation, a kinematic condition is used to tie the mesh to the fluid on the free boundary. In this example, one of the mesh coordinates, say `MESH_DISPLACEMENTS_X`, is unknown. So, the equation that is normally used to solve for that component (the x -component of the MESH equation) is replaced with the kinematic condition: $\mathbf{n} \cdot (\mathbf{v} - \dot{\mathbf{d}}) - v_o = 0$.

An additional feature of distinguishing conditions is that multiple DCs for a given degree of freedom on a given surface are added together. This additive feature allows users to build up their own conditions from primitive ones.

An important thing to know about these conditions is that they are satisfied *weakly*. That is, the DC is multiplied by a finite element weight function and integrated over the surface. Consequently, the condition is only satisfied weakly and to within the tolerance of the nonlinear solver.

The remainder of this chapter contains a description of the primitive DCs that are available in Aria. Using the user plugin feature described in chapter 18 users can add their own, more complicated or specialized conditions. Input specification of distinguishing conditions on portions of the FEM mesh can be simplified by aggregation of mesh parts into Mesh Groups 6.26.

10.2. BC DISTING

BC DISTING for *EQNAME* [_{<Subindex>}][_{<Phase>}]
ON *MESH_PART* = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Replaces the equations for *EQNAME* on *MESH_PART* with a distinguishing condition implemented by *MODEL* .

Summary Prior to the assembly of the distinguishing conditions, the “normal” matrix and RHS entries are zeroed. So, these conditions do not rely on penalty parameters. Also, if multiple distinguishing conditions are supplied they are added together so the *sum* of the conditions is satisfied – that is, they are not individually satisfied. This allows you to construct complex expressions based on the available primitives and/or any plugins. See the POLYNOMIAL model below for an example combining two distinguishing conditions. Finally, it is worth noting that these conditions are satisfied *weakly* and so they are only satisfied to within the tolerance of the nonlinear solver.

Parent
Block(s)
ARIA REGION

10.2.1. DARCY_LEAK

Description This model implements a vector distinguishing condition that allows fluid to “leak” through a boundary according to a Darcy’s Law like relationship:

$$\mathbf{v} - \dot{\mathbf{x}} \cdot \mathbf{n} \mathbf{n} - \frac{K}{L\mu} (P - P_{ref}) \mathbf{n} = \mathbf{0}. \quad (10.1)$$

the velocity, $\dot{\mathbf{x}}$ is the time derivative of the mesh boundary position and P is the fluid pressure. K is the permeability of the boundary, μ is the viscosity, P_{ref} is a reference pressure (defaults to zero) and L is a length scale for the pressure drop (defaults to unity).

Note that the second term in [10.1](#) ensures that the resulting velocity is relative to any boundary motion that arises in moving mesh problems. For problems on fixed meshes this term is automatically excluded.

An alternate pressure field can be used by provided the optional parameter PRESSURE.

Parameters

$K = REAL$
 $[P\_REF = REAL]$
 $[L = REAL]$
 $[PRESSURE = STRING]$

Example

```
BC Disting For Momentum_A On surface_2 = Darcy_Leak K=1
BC Disting For Momentum_B On surface_2 = Darcy_Leak K=1e-7
```

10.2.2. KINEMATIC

Description This model implements the kinematic condition of the form

$$\mathbf{n} \cdot (\mathbf{v} - \dot{\mathbf{x}}) - v_o = 0 \quad (10.2)$$

where $\mathbf{n}$ is the outward unit normal to the boundary, $\mathbf{v}$ is the velocity, $\dot{\mathbf{x}}$ is the time derivative of the mesh boundary position and v_o is the mass flux per unit mass across the interface, viz. a “leak” velocity. The leak velocity can be supplied by the V0 parameter which defaults to zero.

Parameters

V0 = *REAL*

Example

BC Disting For Mesh_X On surface_2 = Kinematic v0=0

10.2.3. POLYNOMIAL

Parameters

VARIABLE = *STRING*

ORDER = *INT*

[C0 = *REAL*]

[C1 = *REAL*]

...

[CN = *REAL*]

Example

BC Disting For Mesh_Y On surface_2 = Polynomial Variable=Time
Order=1 C1=0.5

BC Disting For Mesh_Y On surface_2 = Polynomial
Variable=Mesh_Displacement_Y Order=1 C1=-1

Description Arbitrary order polynomial function of a specified scalar variable.

$$\sum_{i=0}^N C_i X^i = 0 \quad (10.3)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section 2.7.1.

In the example given above, two distinguishing conditions are combined to give a composite function. In that example, the resulting conditions is

$$\frac{1}{2}t - \mathbf{d}_y = 0 \quad (10.4)$$

or

$$\mathbf{d}_y = \frac{1}{2}t \quad (10.5)$$

10.2.4. WETTING_SPEED_BLAKE_LS

Parameters

$V\_W = REAL$

$G = REAL$

$THETA = REAL$

$WIDTH = REAL$

$[TAU = REAL]$

Example

BC Disting for Momentum_A on surface_3 = Wetting_Speed_Blake_LS

$V\_w=1e-1$ $g=1$ $Width=1$ $Theta=60$

Description


$$\mathbf{v} - \delta(F)v_w \sinh(g(\cos \theta_s - \cos \theta)) \mathbf{t}_w + \delta(F)\tau \dot{\mathbf{v}} = 0 \quad (10.6)$$

where $\mathbf{v}$ is the fluid velocity and $\mathbf{t}_w$ is the tangent to the wall. The function $\delta(F)$, where F is the level set distance field, is given by

$$\delta(F) = \frac{1}{2} \left(1 + \cos \frac{\pi F}{\alpha} \right) \quad (10.7)$$

when $|F| < \alpha$ and zero elsewhere. Here, α is the half of the `WIDTH` parameter. The term involving τ is a transient relaxation term. By default, $\tau = 0$.

This distinguishing condition is a function of the static and observed contact angles. The *static* contact angle θ_s , supplied by the `THETA` parameter, is fixed. The *observed* contact angle θ is computed from the current state of the solution as illustrated in the following diagram. The important point here is that the contact angle is measured through the *negative* side of the distance function which is denoted `PHASE_A` in Aria.



10.2.5. ELECTROOSMOTIC_VELOCITY

Parameters

$C = REAL$

Example

BC Disting for Momentum on surface_3 = Electroosmotic_Velocity

C=0.3

Description This distinguishing condition sets the velocity to simply be a constant multiple of the electric field,

$$\boldsymbol{v} - c\boldsymbol{E} = \mathbf{0} \quad (10.8)$$

where $\boldsymbol{v}$ is the fluid velocity, $\boldsymbol{E}$ is the electric field and c is the constant C supplied by the user.

11. VOLUMETRIC SOURCES

This chapter documents the Source line commands within the current version of Aria. The Source line defines a model for a volumetric source term for a given equation 6. It is important to note that with the exception of sources defined in Volume Source command blocks for thermal problems 33.1 the source term must be explicitly defined with a Source command line. For both the single line and command block syntax, input specification of volumetric sources on portions of the FEM mesh can be simplified by aggregation of element blocks into Mesh Groups 6.26.

Source command lines appear in the Region scope of the input file as illustrated below.

```
.
.
Begin Procedure My_Aria_Procedure
.
.
Begin Aria Region My_Region
.
.
EQ Energy for Temperature on block_2 with Q1 using DIFF SRC
Source for energy on block_2 = constant value = 0.2
.
.
End

End

.
.
```

11.1. POINT SOURCE FOR ...

POINT SOURCE FOR *EQNAME* ON *MESH_PART* VALUE = Q X = x [Y = y [Z = z]]

Description Arbitrary point source contributions.

Summary This adds a point source with value Q at the specified position. Currently limited to constant and scalar sources. Only supported by the voltage equation (though extending it to other equations is simple, just ask). This line command syntax needs to change since

the ON *MESH_PART* piece doesn't really make sense since you already supply the coordinates. You have to supply as many coordinate positions as the problem has dimensions.

Mathematically, the point source is represented as

$$q = Q\delta(\mathbf{x} - \mathbf{X}) \quad (11.1)$$

where $\delta()$ is the Dirac delta function which is zero everywhere except at the point $\mathbf{x} = \mathbf{X}$ where $\mathbf{x}$ is the physical coordinate and $\mathbf{X}$ is the position provided via the input. In finite elements, this source is integrated

$$\int_V Q\delta(\mathbf{x} - \mathbf{X})\phi^i dV = Q\phi^i(\mathbf{X}) \in \text{Elem}_{\mathbf{X}}. \quad (11.2)$$

Here we employ the local support of the basis functions ϕ so that this is only evaluated in the elements containing the point $\mathbf{X}$, $\text{Elem}_{\mathbf{X}}$.

Parent
Block(s)
ARIA_REGION

Example

POINT SOURCE FOR Voltage ON block_1 Value = 1 X = 0 Y = 0 Z = 0

11.2. VECTOR POINT SOURCE FOR ...

VECTOR POINT SOURCE FOR *EQNAME* ON *MESH_PART* V_X=*REAL* V_Y=*REAL* V_Z=*REAL* at X=*REAL* Y=*REAL* Z=*REAL*

Description Arbitrary vector point source contribution.

Summary This adds a vector point source with value (v_x, v_y, v_z) at the specified position. Currently limited to a constant value.

Mathematically, the point source is represented as

$$\mathbf{q} = \mathbf{Q}\delta(\mathbf{x} - \mathbf{X}) \quad (11.3)$$

where $\delta()$ is the Dirac delta function which is zero everywhere except at the point $\mathbf{x} = \mathbf{X}$ where $\mathbf{x}$ is the physical coordinate and $\mathbf{X}$ is the position provided via the input. In finite elements, this source is integrated

$$\int_V \mathbf{Q}\delta(\mathbf{x} - \mathbf{X})\phi^i dV = \mathbf{Q}\phi^i(\mathbf{X}) \in \text{Elem}_{\mathbf{X}}. \quad (11.4)$$

Here we employ the local support of the basis functions ϕ so that this is only evaluated in the elements containing the point $\mathbf{X}$, $\text{Elem}_{\mathbf{X}}$.

Parent
Block(s)
ARIA_REGION

Example

VECTOR POINT SOURCE FOR Momentum ON block_1 V_X=1 V_Y=1 V_Z=1 at
X=0 Y=0 Z=0

11.3. SOURCE FOR ENERGY

SOURCE FOR ENERGY ON *MESH_PART* = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Arbitrary source contributions for the energy equation.

Summary Adds the source provided by *MODEL* to the energy equation.

Parent
Block(s)
ARIA_REGION

11.3.1. SOURCE FOR ENERGY = CALORE_USER_SUB

Parameters

NAME = *STRING*
TYPE = *STRING*
[MULTIPLIER = *REAL*]
[SCALING_FIELD= *STRING*]
[EXPR_NAME = *STRING*]
[DATA = *STRING*]

Example

Source for Energy on block_10 = Calore_User_Sub name=w80aafftuser
type=element DATA=DataBlockName

Description NAME is the name of the user subroutine was registered with. The TYPE parameter denotes the API the user subroutine requires, TYPE = ELEMENT for source contributions.

The optional MULTIPLIER parameter (defaults to 1.0) can be supplied to scale the output of the user subroutine, i.e., the flux f will be $f = m f_{user}$ where m is the multiplier and f_{user} is the output of the user subroutine. SCALING_FIELD is similar to MULTIPLIER but here the scaling is applied by specifying the name of a user defined field.

DATA is the name of a Data Block containing Real and integer subroutine parameters, see Chapter 7.

EXPR_NAME is the name of a model entry in a material block where the subroutine is requested. The model value can then be retrieved in the user subroutine. Note: This can only be used in the context of a material block.

See Section 9.2.2 for a complete example of Calore user subroutine usage and 33.21 for a comprehensive description of the Calore_User_Sub setup.

11.3.2. SOURCE FOR ENERGY = CHEMEQ_HEATING

Parameters

MODEL = *STRING*
[POWER_OUTPUT = *STRING*]

Example

Source for Energy on block_10 = CHEMEQ_Heating model =
reaction_model power_output = VAR_NAME

Description Defines a heating source caused by chemical reaction. Here MODEL pertains to the paired CHEMEQ MODEL and CHEMEQ SOLVER command blocks that define the chemical system and how it can evolve. Chemical source contributions to the energy equation are further controlled through parameters in the CHEMEQ SOLVER command block.

When the POWER_OUTPUT option is present the energy source will be integrated over the associated element blocks and saved to the user specified global variable, VAR_NAME.

11.3.3. SOURCE FOR ENERGY = PID_CONTROLLED

Parameters

Max_Output = *REAL*
Setpoint_Function_Name = *STRING*
Control_Variable = *STRING*
[P = *REAL*]
[I = *REAL*]
[D = *REAL*]
[Band = *REAL*]
[Filter_Tau = *REAL*]

Example

Source for Energy on block_10 = PID_Controlled P=0.1 I=1e-4
Max_Output=20000 Setpoint_Function_Name=pid_setpoints1
Control_Variable=ctrlT1

Description This source term imposes an energy flux using a PID controller. The controller setpoint vs. time is defined in a user function, and the controller feedback point uses a global variable (a data probe or Encore function).

The derivative term uses a filtered error value, using a low pass filter whose time constant is specified by the user.

Like a heater, this is only capable of providing a positive influx. Even if the controller output is negative, the applied heat flux will be truncated at 0. Likewise, the applied heat flux cannot exceed the specified max flux.

The nominal scaled PID controller output (between 0 and 1) is

$$u(t) = K_p e(t) + K_i \int_0^t e(\tau) d\tau + K_d \frac{\partial e_f}{\partial t} \quad (11.5)$$

where it is important to note that the K_p coefficient does not scale the others unless you have set it using the Band argument. In some PID implementations, the K_i and K_d coefficients are internally multiplied by K_p so care must be taken to provide the correct coefficients. This output $u(t)$ which is from 0 to 1 is scaled by the specified Max_Output value to produce the applied energy flux. This means you should not include the output magnitude scaling in your P, I, or D parameters.

The P, I, and D coefficients can be specified in a number of ways:

- Just give a 'Band' argument. This calculates $P = 1/\text{Band}$ and uses the defaults of $I = 0.01 * P$ and $D = 0$.
- Give a 'Band' argument and non-defaults for I and/or D. This still multiplies whatever you give for I and D by P.
- Give a 'P' argument instead of 'Band'. NOTE: in this mode the I and D values are not scaled by P.

If you provide both P and Band, P is used, the Band argument is ignored, and I and D are not scaled.

The default values for I and D are 0.01 and 0 if not provided.

The setpoint, controller output, error, filtered error, and filtered error time derivative are all output to automatically created global variables for diagnostics and postprocessing.

11.3.4. SOURCE FOR ENERGY = PID_CONTROLLED_COOLER

Parameters

Max_Cooling_Power = *REAL*
Setpoint_Function_Name = *STRING*
Control_Variable = *STRING*
[P = *REAL*]
[I = *REAL*]
[D = *REAL*]
[Band = *REAL*]
[Filter_Tau = *REAL*]

Example

Source for Energy on block_1 = PID_Controlled_Cooler P=0.1
I=1e-4 Max_Cooling_Power=20000 Setpoint_Function_Name=pid_setpoints1
Control_Variable=ctrlT1

Description This is similar to PID_Controlled, however, the flux is applied to cool the volume instead of heat it. Max_Cooling_Power should be a positive value.

11.3.5. SOURCE FOR ENERGY = PID_CONTROLLED_BIDIRECTIONAL

Parameters

Max_Cooling_Power = *REAL*
Max_Heating_Power = *REAL*
Setpoint_Function_Name = *STRING*
Control_Variable = *STRING*
[P = *REAL*]
[I = *REAL*]
[D = *REAL*]
[Band = *REAL*]
[Filter_Tau = *REAL*]

Example

Source for Energy on block_1 = PID_Controlled_Bidirectional
P=0.1 I=1e-4 Max_Cooling_Power=20000 Max_Heating_Power=20000
Setpoint_Function_Name=pid_setpoints1 Control_Variable=ctrlT1

Description This is similar to PID_Controlled, however, the flux is applied to cool and heat the volume instead of just heating it. Max_Cooling_Power and Max_Heating_Power should both be positive values.

11.3.6. SOURCE FOR ENERGY = MELTING

Parameters

$T_s = REAL$

$T_l = REAL$

[$latent\_heat = REAL$]

Example

Source for Energy on block_1 = Melting $T_s = 400$ $T_l = 410$

$latent\_heat = 1e5$

Source for Energy on block_1 = Melting $T_s = 700$ $T_l = 725$

$latent\_heat = 1e8$

Source for Energy on block_1 = Melting $T_s = 900$ $T_l = 950$

Description Defines a heating source caused by a phase change. The phase change is modeled using a normal distribution spread over a temperature range defined by T_s and T_l . The distribution is sized so that 99% of the energy release occurs between T_s and T_l . The latent heat associated with the phase change can either be specified in-line with the optional “latent_heat” argument or by specifying the latent heat expression in the material model. If both are provided, the value specified in-line is used. The latent heat should be specified units of energy per mass (e.g. J/kg).

This model is preferable to the “Specific Heat = Use_Phase_Change” model because it does not limit the time step or create a discontinuous specific heat. It is also guaranteed to correctly capture the total energy source or sink regardless of the time step size.

Multiple phase transitions can be specified by simply adding multiple melting sources with different temperatures and latent heats.

11.3.7. SOURCE FOR ENERGY = COMPRESSIVE_WORK

Parameters

[MULTIPLIER = *REAL*]

Example

Source For Energy on block_1 = Compressive_Work

Description This source accounts for the heat generation or consumption due to compression:

$$q = -m p : \nabla \cdot \mathbf{v} \quad (11.6)$$

where p is the pressure, $\nabla \cdot \mathbf{v}$ is the divergence of the velocity field and m is a multiplier (MULTIPLIER) that defaults to 1.

11.3.8. SOURCE FOR ENERGY = CONSTANT

Parameters

VALUE = *REAL*

Example

SOURCE FOR Energy ON block_1 = Constant Value=1041.3

Description Supplies a constant energy source

11.3.9. SOURCE FOR ENERGY = CURING_FOAM_HEAT_OF_RXN

Parameters

VFRAC_SUBINDEX = *INT*

EXTENT_SUBINDEX = *INT*

H_RXN = *REAL*

Example

Source For Energy on block_1 = Curing_Foam_Heat_of_Rxn

Vfrac_Subindex=1 Extent_Subindex=2 H_rxn=250

Description This source accounts for the heat of reaction of a curing epoxy foam, specifically:

$$q = \rho (1 - \phi) \Delta H_{rxn} \frac{\partial \xi}{\partial t} \quad (11.7)$$

where ρ is the density of the fluid, ϕ is the volume fraction, ΔH_{rxn} is the heat of reaction and ξ is the extent of reaction.

NOTE: The volume fraction is assumed to be a SPECIES field with the subindex provided by the VFRAC_SUBINDEX parameter. Likewise, the extent of reaction field is assumed to be a SPECIES field with the subindex provided by the EXTENT_SUBINDEX parameter.

11.3.10. SOURCE FOR ENERGY = CURING_FOAM_LATENT_HEAT

Parameters

VFRAC_SUBINDEX = *INT*

H_EVAP = *REAL*

Example

Source For Energy on block_1 = Curing_Foam_Latent_Heat

Vfrac_Subindex=1 H_evap=15

Description This source accounts for the loss of energy due to evaporation of a curing epoxy foam, specifically:

$$q = \rho H_{evap} \frac{\partial \phi}{\partial t} \quad (11.8)$$

where ρ is the density of the fluid, H_{evap} is the latent heat of evaporation and ϕ is the volume fraction,

NOTE: The volume fraction is assumed to be a SPECIES field with the subindex provided by the VFRAC_SUBINDEX parameter.

11.3.11. SOURCE FOR ENERGY = CURING_FOAM_SPECIFIC_HEAT

Parameters

VFRAC_SUBINDEX = *INT*
 [CP_FG = *REAL*]
 [CP_E = *REAL*]
 [PHI_ZERO = *REAL*]

Example

Source For Energy on block_1 = Curing_Foam_Specific_Heat
 Vfrac_Subindex=1 Cp_fg=1 Cp_e=1 phi_zero=0.2

Description This source accounts for the loss of energy due to the variable specific heat for the special case where the specific heat material model is CURING_FOAM. See 4.48.6. Specifically, this source term is

$$q = -\rho T \left(\frac{\partial C_p}{\partial t} + \mathbf{v} \cdot \nabla C_p \right) \quad (11.9)$$

$$= -\rho T b \left(\frac{\partial \phi}{\partial t} + \mathbf{v} \cdot \nabla \phi \right) \quad (11.10)$$

where ρ is the density of the fluid, T is the temperature, $\mathbf{v}$ is the velocity, ϕ is the volume fraction and b is as defined in CURING_FOAM specific heat material model (see 4.48.6).

NOTE: The volume fraction is assumed to be a SPECIES field with the subindex provided by the VFRAC_SUBINDEX parameter.

11.3.12. SOURCE FOR ENERGY = ENCORE_FUNCTION

Parameters

NAME = *STRING*
 [EVAL_TYPE = *STRING*]

Example

SOURCE FOR Energy ON block_1 = Encore_Function
 Name=My_Function

Description Using the Encore library, you can define your own functions in a number of ways, such as analytically in the input file, based on the values of a Sierra field or your own compiled functions. See the Encore documentation for more details.

As an example, this snippet of input can be added to the domain level of your input file:

```
Begin String Function My_Function
  Value is "200 + 1.0*t"
End
```

Then, this function can be used as shown in the example above.

The optional argument EVAL_TYPE can be used to select the particular function on the Encore function object. Valid options include VALUE, DOT, GRADIENT, FLUX and STRESS. If this option is not supplied Aria will make a sensible choice depending on the resulting expressions – VALUE for NO_OP expressions, DOT for DT_OP expressions and GRADIENT for GRAD_OP expressions.

11.3.13. SOURCE FOR ENERGY = JOULE_HEATING

Parameters

[VOLTAGE_SUBINDEX = INT]

Example

SOURCE FOR Energy ON block_1 = Joule_Heating

Description This source term adds the volumetric heat source due to Joule heating, a.k.a., Ohmic heating or resistance heating.

$$H_V = J \cdot E \quad (11.11)$$

where J is the current density vector and E is the electric field vector.

When thermoelectric effects are negligible volumetric heating is effectively given by (see, Section 5.3)

$$H_V = J^2 R \quad (11.12)$$

$$= (-\sigma_e \nabla V) \cdot (-\sigma_e \nabla V) R \quad (11.13)$$

$$= (-\sigma_e \nabla V) \cdot (-\sigma_e \nabla V) \frac{1}{\sigma_e} \quad (11.14)$$

$$= \sigma_e (\nabla V \cdot \nabla V) \quad (11.15)$$

where J is the current density, R is the resistivity, $\sigma_e = 1/R$ is the electrical conductivity and V is the voltage.

If thermoelectric effects are significant then a thermoelectric current density 4.6.4 should be used instead

$$J = -\sigma_e (\nabla V + \alpha \nabla T) \quad (11.16)$$

where α is the Seebeck coefficient and T is the temperature.

11.3.14. SOURCE FOR ENERGY = POLYNOMIAL

Parameters

VARIABLE = *STRING* ORDER = *INT* [VARIABLE_OFFSET = *REAL*] [C0 = *REAL*] [C1 = *REAL*] ... [CN = *REAL*]

Example

SOURCE For Energy on block_1= Polynomial Variable=Temperature
Order=1 C0=401.0 C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$H_V = \sum_{i=0}^N C_i (X + X_o)^i \quad (11.17)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter, X_o is an optional offset (VARIABLE_OFFSET, default is zero) and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section 2.7.1.

11.3.15. SOURCE FOR ENERGY = TBC_JOULE_HEATING

Parameters

Ua = *REAL*
Ub = *REAL*
V_NS = *INT*
Ti = *REAL*
CURRENT_LOAD = *REAL*
[VOLTAGE_SUBINDEX = *INT*]

Example

SOURCE FOR Energy ON block_1 = TBC_Joule_Heating Ua=1.4251
Ub=0.0004785 V_NS=1 Ti=298 CURRENT_LOAD=0.0017

Description This source term adds the volumetric heat source due to Joule heating in a thermal battery cell volumetric heating is given by (see, Section 5.3)

$$H_V = \left(U_o - V - T_i \frac{\partial U_o}{\partial T} \right) I_o \quad (11.18)$$

Here, U_o is the open circuit potential which is given as a linear function in temperature T and U_a and U_b are the coefficients of that function. V is the cell potential which is taken as the voltage at the node given in the single-node nodeset number V_NS and I_o is cell load.

For more details, see [24].

11.3.16. SOURCE FOR ENERGY = VISCOUS DISSIPATION

Parameters

[MULTIPLIER = *REAL*]

Example

Source For Energy on block_1 = Viscous_Dissipation

Description This source accounts for the heat generation due to viscous dissipation:

$$q = m \boldsymbol{\tau} : \nabla \mathbf{v} \quad (11.19)$$

where $\boldsymbol{\tau}$ is the viscous stress tensor, $\nabla \mathbf{v}$ is the gradient of the velocity and m is a multiplier (MULTIPLIER) that defaults to 1. The exact form of $\boldsymbol{\tau}$ will depend on the MOMENTUM_STRESS model choice(s) for the material.

11.3.17. SOURCE FOR ENERGY = USER_FUNCTION

Parameters

NAME = *STRING*

X = *STRING*

Example

SOURCE For Energy on block_1 = User_Function Name=Function_Name
X=Independent_Variable

Description Source magnitude is defined by a tabular function of the independent variable X. The user specified tabular function NAME as a function of Xscalar solution variable or time. The X argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the X argument is described in section 2.7.1. Although described here for the energy equation, this source term may be defined on other scalar equations.

11.3.18. SOURCE FOR ENERGY = ELECTRODE_OBJECT

See 11.5.3 for complete description.

11.4. SOURCE FOR MOMENTUM

SOURCE FOR MOMENTUM ON *MESH_PART* = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Arbitrary source contributions for the momentum equation.

Summary Adds the source provided by *MODEL* to the momentum equation.

Parent

Block(s)

ARIA_REGION

11.4.1. SOURCE FOR MOMENTUM = CONSTANT_VECTOR

Parameters

[X = *REAL*]

[Y = *REAL*]

[Z = *REAL*]

Example

SOURCE FOR momentum ON block_1 = CONSTANT_VECTOR Z=-9.8

Description This source term only applies to the momentum equation though it is automatically applied to the continuity equation in PSPG formulations.

X, Y, Z are the components of the vector source. This vector source is *not* multiplied by the density.

11.4.2. SOURCE FOR MOMENTUM = HYDROSTATIC

Parameters

GX = *REAL*

GY = *REAL*

GZ = *REAL*

[REF_DENSITY = *REAL*]

Example

SOURCE FOR momentum ON block_1 = HYDROSTATIC gx = 0 gy = 0 gz = -980

Description This source term only applies to the momentum equation though it is automatically applied to the continuity equation in PSPG formulations.

GX, GY, GZ are the components of the gravity vector $\mathbf{g}$ and REF_DENSITY is an constant, uniform reference density ρ_o . With density ρ , the hydrostatic source is defined as $(\rho - \rho_o)\mathbf{g}$.

The default value of the reference density is 0.

11.4.3. SOURCE FOR MOMENTUM = POTENTIAL

Parameters

None

Example

SOURCE FOR momentum ON block_1 = POTENTIAL

Description This source term applies the gradient of the potential field, defined by the POTENTIAL equation, as a momentum source. It is most commonly used when the potential field is defined as the hydrostatic potential, and is used in place of the HYDROSTATIC model discussed above.

11.4.4. SOURCE FOR MOMENTUM = ROTATING_BODY_FORCE

Parameters

G = *REAL*
 FREQUENCY = *REAL*
 [PHASE_SHIFT = *REAL*]
 [REF_DENSITY = *REAL*]

Example

Source for Momentum on block_1 = Rotating_Body_Force g=9.8
 frequency=2.5 phase_shift=90

Description This source term only applies to the momentum equation though it is automatically applied to the continuity equation in PSPG formulations.

GX, GY, GZ are the components of the gravity vector $\mathbf{g}$ and REF_DENSITY is an constant, uniform reference density ρ_o . With density ρ , the hydrostatic source is defined as $(\rho - \rho_o)\mathbf{g}$.

The default value of the reference density is 0.

11.4.5. SOURCE FOR MOMENTUM = BOUSSINESQ

Parameters

TEMP_REF = *REAL*
 VOL_EXP = *REAL*
 GX = *REAL*
 GY = *REAL*
 GZ = *REAL*

Example

SOURCE FOR momentum ON block_1 = BOUSSINESQ vol_exp=0.1
 temp_ref=298.15 gx = 0 gy = 0 gz = -980

Description This source term only applies to the momentum equation though it is automatically applied to the continuity equation in PSPG formulations.

GX, GY, GZ are the components of the gravity vector $\mathbf{g}$. VOL_EXP is the volume expansion coefficient α and TEMP_REF is the reference temperature T_{ref} . With density ρ and temperature T the Boussinesq source is defined as $\rho\mathbf{g}\alpha(T - T_{ref})$.

11.5. SOURCE FOR CURRENT

SOURCE FOR CURRENT ON *MESH_PART* = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Arbitrary source contributions for the current equation.

Summary Adds the source provided by *MODEL* to the current equation.

Parent

Block(s)

ARIA_REGION

11.5.1. SOURCE FOR CURRENT = BUTLER_VOLMER_SIMPLE

Parameters

A = *REAL*

C_A = *REAL*

C_C = *REAL*

U = *REAL*

Sign = *INT*

[V1_SUBINDEX = *INT*]

[V2_SUBINDEX = *INT*]

Example

SOURCE FOR CURRENT_1 ON block_1 = Butler_Volmer_Simple A=1.0

C_a=1.0 C_c=-1.0 U=0.2 Sign=-1

SOURCE FOR CURRENT_2 ON block_1 = Butler_Volmer_Simple A=1.0

C_a=1.0 C_c=-1.0 U=0.0 Sign=+1

Description This model implements a very simple form of the Butler-Volmer reaction kinetics. It is intended for developmental and demonstrational purposes only.

This source term has the following form (see, also, equation 5.35)

$$R_{V,k} = A \left(e^{c_a(V_1 - V_2 - U)} - e^{-c_c(V_1 - V_2 - U)} \right) \quad (11.20)$$

where V_1 is the first electric potential field and V_2 is the second electric potential field. By default V_1 is VOLTAGE_1 and V_2 is VOLTAGE_2 but the subindices may be changed using the optional V1_SUBINDEX and V2_SUBINDEX options.

11.5.2. SOURCE FOR CURRENT = POLYNOMIAL

Parameters

VARIABLE = *STRING*

ORDER = *INT*

[C0 = *REAL*]

[C1 = *REAL*]

...

[CN = *REAL*]

Example

SOURCE For Current on block_1 = Polynomial Variable=Temperature
Order=1 C0=401.0 C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$H_V = \sum_{i=0}^N C_i X^i \quad (11.21)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section 2.7.1.

11.5.3. SOURCE FOR CURRENT = ELECTRODE_OBJECT

Parameters

electrodeFile = *STRING*

[F = *REAL*]

[kmolConversion = *REAL*]

[meterConversion = *REAL*]

[JConversion = *REAL*]

Example

SOURCE FOR CURRENT in SOLID_PHASE ON block_1 = ELECTRODE_OBJECT
F=96485 electrodeFile=cathode.inp kmolConversion=1000

Description This model uses the Cantera Electrode object to compute source terms for battery models. Generally this source term will need to be applied to the following equations:

- CURRENT in SOLID_PHASE
- CURRENT in LIQUID_PHASE
- POROUS_SPECIES of (SPECIES_NAME) in LIQUID_PHASE
- [ENERGY]

electrodeFile specifies the input file that will be used to initialize the Electrode objects.
 F specifies the value of Faraday's constant in the unit system of the simulation.
 kmolConversion specifies the conversion factor from kmol to the unit system of the simulation.
 meterConversion specifies the conversion factor from meters to the unit system of the simulation.
 JConversion specifies the conversion factor from Joules to the unit system of the simulation.

11.6. SOURCE FOR SPECIES

SOURCE FOR SPECIES ON *MESH_PART* = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Arbitrary source contributions for the species equation.

Summary Adds the source provided by *MODEL* to the species equation.

Parent
Block(s)
 ARIA_REGION

11.6.1. SOURCE FOR SPECIES = CURING_FOAM_EXTENT

Parameters

K = *REAL*
 E = *REAL*
 R = *REAL*
 N = *REAL*

Example

Source For Species_2 on block_1 = Curing_Foam_Extent k=1.145e5
 E=10 R=8.314472E3 n=1.3

Description This source accounts for the reaction of a curing epoxy foam, specifically:

$$q = ke^{E/RT} (1 - \xi)^n \quad (11.22)$$

where T is the temperature and ξ is the extent of reaction.

11.6.2. SOURCE FOR SPECIES = CURING_FOAM_VFRAC

Parameters

A = *REAL*

B = *REAL*

C = *REAL*

T_BOILING = *REAL*

Example

Source For Species_2 on block_1 = Curing_Foam_Vfrac a=1 b=0
c=2e-3 T_BOILING=473.15

Description This source accounts for the change in volume fraction with temperature.

$$q = (a + bT + cT^2)_{\text{exp}} \frac{\partial T}{\partial t} \quad (11.23)$$

where T is the temperature. This source term is only active when $T \geq T_{\text{boiling}}$.

11.6.3. SOURCE FOR SPECIES = POLYNOMIAL

Parameters

VARIABLE = *STRING*

ORDER = *INT*

[C0 = *REAL*]

[C1 = *REAL*]

...

[CN = *REAL*]

Example

Source For Species on block_1 = Polynomial Variable=Temperature
Order=1 C0=401.0 C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$H_V = \sum_{i=0}^N C_i X^i \quad (11.24)$$

Here, N is the order of the polynomial provided by the ORDER parameter and X is the variable supplied by the VARIABLE parameter and C_i are the supplied coefficients.

Coefficients that are not supplied default to a value of zero. The VARIABLE argument can be TIME or any internal Expression that evaluates to a scalar. For the latter case, the format of the VARIABLE argument is described in section [2.7.1](#).

11.7. SOURCE FOR POROUS_SPECIES

SOURCE FOR POROUS_SPECIES ON *MESH_PART* = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Arbitrary source contributions for the porous_species equation.

Summary Adds the source provided by *MODEL* to the porous_species equation.

Parent
Block(s)
ARIA_REGION

11.7.1. SOURCE FOR POROUS_SPECIES = ELECTRODE_OBJECT

See [11.5.3](#) for complete description.

11.8. SOURCE FOR VOLTAGE

SOURCE FOR VOLTAGE ON *MESH_PART* = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Arbitrary source contributions for the voltage equation.

Summary Adds the source provided by *MODEL* to the voltage equation.

Parent
Block(s)
ARIA_REGION

11.8.1. SOURCE FOR VOLTAGE = POLYNOMIAL

Parameters
VARIABLE = *STRING*
ORDER = *INT*
[C0 = *REAL*]
[C1 = *REAL*]
...
[CN = *REAL*]

Example

Source For Voltage on block_1 = Polynomial Variable=Temperature
Order=1 C0=401.0 C1=88.5

Description Arbitrary order polynomial function of a specified scalar variable.

$$H_V = \sum_{i=0}^N C_i X^i \quad (11.25)$$

Here, N is the order of the polynomial provided by the `ORDER` parameter and X is the variable supplied by the `VARIABLE` parameter and C_i are the supplied coefficients. Coefficients that are not supplied default to a value of zero. The `VARIABLE` argument can be `TIME` or any internal Expression that evaluates to a scalar. For the latter case, the format of the `VARIABLE` argument is described in section [2.7.1](#).

11.9. SOURCE FOR POTENTIAL

SOURCE FOR POTENTIAL ON *MESH_PART* = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Arbitrary source contributions for the potential equation.

Summary Adds the source provided by *MODEL* to the potential equation.

Parent
Block(s)
 ARIA_REGION

11.9.1. SOURCE FOR POTENTIAL = HYDROSTATIC

Parameters

GX = *REAL*
 GY = *REAL*
 GZ = *REAL*
 [REF_DENSITY = *REAL*]

Example

SOURCE FOR Potential ON block_1 = HYDROSTATIC gx = 0 gy = 0 gz =
 -980

Description This source term only applies a hydrostatic potential source term to the POTENTIAL equation, defining the potential. It can then be applied to the momentum equation through a separate potential source term in the momentum equation.

GX, GY, GZ are the components of the gravity vector $\mathbf{g}$ and REF_DENSITY is a constant, uniform reference density ρ_o . With density ρ , the hydrostatic source is defined as $(\rho - \rho_o)\mathbf{g}$.

The default value of the reference density is 0.

11.10. SOURCE FOR MESH

SOURCE FOR MESH ON *MESH_PART* = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Arbitrary source contributions for the mesh equation.

Summary Adds the source provided by *MODEL* to the mesh equation.

Parent

Block(s)

ARIA_REGION

11.10.1. SOURCE FOR MESH = HYDROSTATIC

Parameters

GX = *REAL*

GY = *REAL*

GZ = *REAL*

[REF_DENSITY = *REAL*] [DENSITY_PHASE = SOLID]

Example

SOURCE FOR Mesh ON block_1 = HYDROSTATIC gx = 0 gy = 0 gz =
-980

Description This source term applies a hydrostatic source term to the MESH equation, defining MESH_DISPLACEMENTS.
GX, GY, GZ are the components of the gravity vector $\mathbf{g}$ and REF_DENSITY is an constant, uniform reference density ρ_o . With density ρ , the hydrostatic source is defined as $(\rho - \rho_o)\mathbf{g}$. The optional DENSITY_PHASE = SOLID argument allows the source term to use the Porous Flow System solid_density command line specification as its density.

The default value of the reference density is 0.

11.10.2. SOURCE FOR MESH = MESH BODY ACCELERATION

Example

SOURCE FOR Mesh ON block_1 = MESH_BODY_ACCELERATION

MESH BODY ACCELERATION = *GENERIC_VECTOR_MODEL*

parameters

Description This source term applies a hydrostatic force to the MESH equation.

11.11. SOURCE FOR SOLID

SOURCE FOR SOLID ON *MESH_PART* = *MODEL* [param₁ = val₁, param₂ = val₂ ...]

Description Arbitrary source contributions for the solid equation.

Summary Adds the source provided by *MODEL* to the solid equation.

Parent

Block(s)

ARIA_REGION

11.11.1. SOURCE FOR SOLID = HYDROSTATIC

Parameters

GX = *REAL*

GY = *REAL*

GZ = *REAL*

[REF_DENSITY = *REAL*]

Example

SOURCE FOR Mesh ON block_1 = HYDROSTATIC gx = 0 gy = 0 gz =
-980

Description This source term only applies a hydrostatic source term to the SOLID equation, defining SOLID_DISPLACEMENTS.

GX, GY, GZ are the components of the gravity vector $\mathbf{g}$ and REF_DENSITY is an constant, uniform reference density ρ_o . With density ρ , the hydrostatic source is defined as $(\rho - \rho_o)\mathbf{g}$.

The default value of the reference density is 0.

11.11.2. SOURCE FOR SOLID = SOLID BODY ACCELERATION

Example

SOURCE FOR Mesh ON block_1 = SOLID_BODY_ACCELERATION

SOLID BODY ACCELERATION = *GENERIC_VECTOR_MODEL*

parameters

Description This source term applies an acceleration to the SOLID equation.

12. CONSTRAINT CONDITIONS

At present Aria supports only a two types of constraints. However, many problem inputs can often be partially constrained using a PID controller.

12.0.1. Suspension Average Volume Fraction

12.1. CONSTRAIN

CONSTRAIN AVERAGE_VOLUME_FRACTION phi = C_0

Description Integral constraint for the average particle volume fraction in a SUSPENSION problem.

Summary Constrains ϕ throughout the problem domain to achieve the specified value of average volume particle fraction in accordance with the relation

$$C_0 = \left[\int_{V_\phi} dV \right]^{-1} \int_{V_\phi} \phi dV \quad (12.1)$$

over element blocks where the SUSPENSION equation is defined.

Parent
Block(s)
ARIA_REGION

12.1.1. Embedded Submodel



Beta Capability: This feature is not sufficiently tested to be classified as a full production capability.

The embedded submodel is a type of constraint that enables one to independently include a shell or bar feature in an existing contiguously meshed model. Here the shell or bar DOF are constrained/tied to the DOF evaluations of the contiguous model using Multi-Point Constraints.

12.2. SUBMODEL

Scope: Equation System

Begin Submodel *SubModel_name*

Clip Isoparametric Coords

Embedded Blocks {=*|are|is*} *VolumeList...*

Enclosing Blocks {=*|are|is*} *VolumeList...*

Expand Box Percentage {=*|are|is*} *Percentage*

Field Name {=*|are|is*} *FieldName*

Interaction Output {=*|are|is*} *NonconformalOutput*

Search Method {=*|are|is*} *SearchMethod*

Search Tolerance {=*|are|is*} *Tolerance*

End

Summary Contains the commands needed to define an Aria submodel.

Description This block command is used to define the embedded block submodel.

12.2.1. Clip Isoparametric Coords

Scope: Submodel

Summary This command is no longer used. It remains available for backwards compatibility until version 4.50.

12.2.2. Embedded Blocks

Scope: Submodel

Embedded Blocks {=*|are|is*} *VolumeList...*

Parameter	Value	Default
<i>VolumeList</i>	<i>string...</i>	undefined

Summary Specifies the element blocks to be embedded within another volume.

12.2.3. Enclosing Blocks

Scope: Submodel

Enclosing Blocks {=|are|is} *VolumeList...*

Parameter	Value	Default
<i>VolumeList</i>	string...	undefined

Summary Specifies the element blocks in which EMBEDDED BLOCKS can reside.

12.2.4. Expand Box Percentage

Scope: Submodel

Expand Box Percentage {=|are|is} *Percentage*

Parameter	Value	Default
<i>Percentage</i>	real	1.0

Summary This command is no longer used. It remains available for backwards compatibility until version 4.50.

12.2.5. Field Name

Scope: Submodel

Field Name {=|are|is} *FieldName*

Parameter	Value	Default
<i>FieldName</i>	string	undefined

Summary Specifies the fields to tie constraints to (default is temperature).

12.2.6. Interaction Output

Scope: Submodel

Interaction Output {=|are|is} *NonconformalOutput*

Parameter	Value	Default
<i>NonconformalOutput</i>	{active all error none summary}	NONE

Summary When this line is present, detailed information of the contact interactions are output.

12.2.7. Search Method

Scope: Submodel

Search Method {=|are|is} *SearchMethod*

Parameter	Value	Default
<i>SearchMethod</i>	{boost kdtree}	NONE

Summary Set the search method to be used with nonconformal contact.

12.2.8. Search Tolerance

Scope: Submodel

Search Tolerance {=|are|is} *Tolerance*

Parameter	Value	Default
<i>Tolerance</i>	real	1.0

Summary Assign the normal search tolerance in the length units of the model. This will override the automatic tolerancing.

13. ELEMENT DEATH

The element death capability is used to define conditions under which elements will be excluded from the normal set of calculations. This capability is implemented in two different flavors, one where elements are explicitly removed (Standard Element Death) and another (CDFEM) in which elements are subdivided in a manner consistent with the element death criterion. While CDFEM has been shown to possess a notion of solution convergence, standard element death is only qualitatively correct. Generally speaking there is computational economy in the usage of standard element death over CVFEM death at the expense of higher resolution in front tracking. With a few exceptions both element death implementations utilize essentially the same command directives.

Element death is a dynamic process in which existing elements are identified by their state as being active (included in the simulation) or inactive/dead (excluded from the simulation). The element death capability is composed of two parts, definition of criterion and definition of its scope. Each death criterion definition must be named uniquely (DeathName) and its scope will be the specific set of mesh entities, surfaces or blocks of the input mesh to which the criterion is applied.

The element death process will result in a new discretization that may include surfaces defined by dead elements. The new discretization will be written to a results file named the same as the original results file but appended with a suffix, e.g. for an original file "t.e" the new discretization would be "t.e-sooo2". For simulations in which elements are continually being killed this results in a numbered sequence of output files. Visualization of element death differs between standard element death and CDFEM element death but is somewhat straightforward as most applications will automatically load the collection of output files to produce the appropriate model animation.

13.1. STANDARD ELEMENT DEATH

In standard element death characterization of the death state is monitored using an element variable (DEATH_STATUS) which denotes whether an element is currently active, DEATH_STATUS= 1 or inactive, DEATH_STATUS= 0. Visualization of a model with the "dead" elements removed is made possible by use of the DEATH_STATUS output variable. Since DEATH_STATUS=0 denotes dead elements, the DEATH_STATUS variable can then be used in conjunction with any visualization thresholding utility to animate element death process.

During a simulation in which standard element death is defined one can monitor the extent of element death through two values output to the log file, KILLED_ELEMENTS and TOTAL_DEAD_ELEMENTS. KILLED_ELEMENTS reports the number of elements removed from the simulation after completion of the current time step while TOTAL_DEAD_ELEMENTS is the cumulative number of elements deleted. Both KILLED_ELEMENTS and

TOTAL_DEAD_ELEMENTS are also available for output to the ExodusII database as global variables under the same name (e.g. global variables = killed_elements).

One can also monitor the extent of element death by observing the number of unknowns in the nonlinear solution step portion of the log file. More specifically, the content of the line beginning with "* Matrix:Solver:" which contains the number of unknowns on processor rank 0 but and the following line beginning with "* Mesh" will the number of elements on processor rank 0.

13.2. CDFEM ELEMENT DEATH

In CDFEM characterization of the death state is monitored directly by the contents of two element block entities, the original element block and an internally generated "death" part. The "death" part has the base name of original element block appended with "_DEAD" (e.g. the "death part" for BLOCK_3 would be BLOCK_3_DEAD). When element death occurs, elements in the original element block are removed and transitioned to the "death" part.

Since the "death" part is not part of the original mesh the user must define this part within the "Finite Element Model" command block in the same way as the original element block was defined but with its name appended with "_DEAD" (e.g. the "death part" for BLOCK_3 would be BLOCK_3_DEAD).

During a simulation in which CDFEM element death is active one can roughly monitor the extent of element death by observing the number of unknowns in the nonlinear solution step portion of the log file. Once again the content of the line beginning with "* Matrix:Solver:" which contains the number of unknowns on processor zero but changes on processors other than rank 0 are not recorded in the log file.

Visualization of a model with CDFEM element death is straightforward since a clear distinction is made between the element blocks in the original mesh and the "death" part. Hence one can proceed in the same manner as visualization of the original mesh.

13.3. GENERAL DEATH SYNTAX

Since the death criterion specification will normally involve an internally stored Field, one must use the complete name of that Field when defining element death. As an example, a standard element death command block named criteria DEATH_TEMP8 based upon the average nodal temperature solution on BLOCK_3 exceeding temperature of 322 K might be defined as:

```
Begin Element Death death_temp8
  add volume block_3
  Criterion is Avg nodal value of solution->Temperature > 322.0
End
```

The equivalent syntax for CDFEM death differs only in the command block specification, `Begin CDFEM Element death_temp8`.

When element death is applied to elements at an exposed boundary an additional step is required to preserve the application of existing boundary conditions at newly exposed surfaces resulting from element removal. This is accomplished by associating the surface of the element block where element death is applied as part of the boundary condition surface. As an example, with standard element death a flux boundary condition applied to a surface of the use case previously given would require the syntax:

```
Begin Heat Flux Boundary Condition X-face
  Add Surface surface_4
  Add Surface surface_death_temp8
  Flux = 100.
End
```

where the addition of `Add Surface surface_death_temp8` ensures that the boundary condition surface is continually updated.

In most cases the element death criteria will be evaluated based upon values computed within Aria. Here the death criteria are evaluated at the end of a solution step. With standard element death, it is also possible to evaluate the criteria based upon externally supplied "transfer" variables. In this case one can force the death criteria to be evaluated at the beginning of time step using the `TRANSFER ELEMENT DEATH` command line.

13.4. ELEMENT DEATH

Scope: Aria Region

```
Begin Element Death Death Name

  Add Volume Block Name...

  Criterion {=|are|is} DeathCriterionType Variable Name
  DeathCriterionCompareType Threshold Value

End
```

Summary Allows the specification of an element death criterion to one or more element volumes. The group of element volumes plus a death criterion make up a "death instance".

13.4.1. Add Volume

Scope: Element Death

Add Volume *Block Name...*

Parameter	Value	Default
<i>Block Name</i>	string...	undefined

Summary Specifies the names identifying an element volume to which an element death criterion is to be applied. Line can be repeated as needed to add multiple volumes. A group of element volumes plus a death criterion make up a "death instance".

13.4.2. Criterion

Scope: Element Death

Criterion {*=|are|is*} *DeathCriterionType Variable Name*
DeathCriterionCompareType Threshold Value

Parameter	Value	Default
<i>DeathCriterionType</i>	{avg nodal value of death criterion type undefined element value of max nodal value of min nodal value of}	undefined
<i>Variable Name</i>	string	undefined
<i>DeathCriterionCompareType</i>	{< <= = > >= death criterion compare type undefined}	undefined
<i>Threshold Value</i>	real	undefined

Summary The death criterion for one or more element volumes. Currently designed to support the specification of a threshold for a scalar variable defined on either a node or element. For nodal variables, various operations such as Min., Max. and Avg. are provided to reduce the nodal values to a single element value. For an element variable no operations are given as there is only one value per element. A group of element volumes plus a death criterion make up a "death instance". Currently only one criterion is allowed per death instance.

13.4.3. Transfer Element Death

Scope:

Summary Cause execution of element death to occur at beginning of a time step rather than at the end of the step.

14. SOLUTION CONTROL REFERENCE

14.1. OVERVIEW

All Aria input files must include a Solution Control Description block in the Procedure section of the input file. This description contains directives for executing either a steady-state (sequential) or transient analysis either of which can include nested nonlinear iteration or subcycling. Within the description one selects a named solution control system where the details of execution are more clearly spelled out. Because there are similarities between the Sequential, Transient, Nonlinear Iteration and Subcycling many operations are shared between these directives. However, each of these segments must be uniquely named internally so they can be properly managed under solution control.

Within each SC system, execution of a problem defined at the Region level corresponds to an Advance directive. Thus a steady-state analysis could conceivably be carried out with a single Advance directive. For transient analysis the system can contain several time blocks, each with a corresponding Advance directive. Examples of different control structures are given below.

As an example, the solution control command block for a steady-state Aria analysis would reflect the structure indicated below:

```
Begin Sierra myJob
.
. Materials, Solvers, Finite Element Model

Begin Procedure myProcedure

  Begin Solution Control Description
    Use System Main
    Begin System Main
      Begin Sequential MySolveBlock
        Advance myRegion
      End
    End
  End

Begin Aria Region myRegion
.
. ICs, BCs, equations, output instructions
.
```

```

        . myRegion output
        .
    End Aria Region myRegion

End Procedure myProcedure
.
End Sierra myJob

```

A solution control command block for steady-state analysis containing nonlinear iteration for Aria and Adagio would reflect the general structure indicated below. Note that advancement of the solution can be governed by a user specified criteria, Parameters for Nonlinear Iteration:

```

Begin Sierra myJob
.
. Materials, Solvers, Finite Element Model

Begin Procedure myProcedure

    Begin Solution Control Description
        Use System Main
        Begin System Main
            Begin Sequential MySolveBlock
                Begin Nonlinear Iteration
                    Advance myAriaRegion
                    Advance myAdagioRegion
                    transfer adagio_to_aria
                End Nonlinear Iteration
            End
        End
    End

Begin transfer adagio_to_aria
.
. transfer commands
.
End transfer adagio_to_aria

Begin Aria Region myAriaRegion
.
. ICs, BCs, equations
. myAriaRegion output
.
End Aria Region myAriaRegion

Begin Adagio Region myAdagioRegion

```

```
.  
. ICs, BCs, equations  
. myAdagioRegion output  
.   
End Adagio Region myAdagioRegion  
  
End Procedure myProcedure  
.   
End Sierra myJob
```

In the case of transient analysis the solution control command block will contain specification of times for which the analysis will be carried out. Additionally parameters defining the time integration must also be supplied by the user. Details concerning time integration parameters are included in the section on Time Integration [16](#). A simple example the solution control command block for transient analysis would resemble the structure indicated below:

```
Begin Sierra myJob
.
. Materials, Solvers, Finite Element Model
.
Begin Procedure My_Aria_Procedure

Begin Solution Control Description

Use System Main

Begin System Main
Simulation Start Time           = 0.0
Simulation Termination Time     = 10.0
Simulation Max Global Iterations = 1000

Begin Transient Time_Block_1
Advance My_Aria_Region
End
Begin Transient Time_Block_2
Advance My_Aria_Region
End

End

Begin Parameters For Transient Time_Block_1
Start Time           = 0.0
Number of steps = 8
Begin Parameters For Aria Region My_Aria_Region
Time Step Variation   = Fixed
Initial Time Step Size = 0.001
End
End

Begin Parameters For Transient Time_Block_2
Begin Parameters For Aria Region My_Aria_Region
Time Step Variation   = Adaptive
Initial Time Step Size = 0.001
Predictor-Corrector Tolerance = 1e-3
Minimum Time Step Size   = 1e-6
```

```

        End
    End

    End

    .
End Procedure My_Aria_Procedure
.
End Sierra myJob

```

Similarly subcycled iterations in a one-way coupling between Aria and Presto could also be carried out in a transient analysis. In this case Presto subcycles at a small time step, Aria has a larger time step and Aria is advanced when the two time steps arrive at the same solution time.

```

Begin Sierra myJob
.
Begin Procedure My_Aria_Procedure

    Begin Solution Control Description

        Use System Main

        Begin System Main
            Simulation Start Time          = 0.0
            Simulation Termination Time    = 10.0
            Simulation Max Global Iterations = 1000

            Begin Transient Time_Block_1
                Transfer Presto_to_Aria
                Advance My_Aria_Region
                Begin Subcycle PrestoSubcycle
                    Transfer Aria_to_Presto
                    Advance PrestoRegion
                End
            End

        End

    End

End

Begin Parameters For Transient Time_Block_1
    Start Time          = 0.0
    Number of steps = 8

    Begin Parameters For Aria Region My_Aria_Region
        Time Step Variation    = Fixed
        Initial Time Step Size = 0.001
    End

```



```

        Begin Parameters for Presto Region PrestoRegion
            initial time step = 1.0e-6
            # time step scale factor = 1.0
            time step increase factor = 10.
            # step interval = 500
        End
    End

End

.

Begin Aria Region myAriaRegion
.
.
End Aria Region myAriaRegion

Begin Presto Region myPrestoRegion
.
.
End Presto Region myPrestoRegion

End Procedure myProcedure
.
End Sierra myJob

```

It is important to note that Solution Control can orchestrate the execution of one Region or the execution of many Regions. Within a loosely-coupled code analysis SC is also used to control the movement of data between the coupled codes using the Transfer subsystem.

The outline views of various couplings include both Transfer and Advance events. In the examples above the event will always occur in the sequence specified. Alternatively one can specify that the event be carried out conditionally subject to criteria described syntactically as a "C" language *[When – expression]* where the expression criteria includes internal code variables or explicit evaluations. Here the input *[When – expression]* is parsed and transformed into an executable "C" statement. While some of the internal code variables used by a *[When – expression]* are intuitive (i.e. CURRENT_TIME and CURRENT_STEP) many others are application dependent. The most widely used explicit evaluations are measures of convergence based upon solution residuals `adagio.norm(0.0)` for solid mechanics applications and `aria.MaxResidualNorm(0.0)` for thermal-fluid applications. Other thermal-fluid evaluations used in convergence comparisons are `aria.MaxInitialNonlinearResidual()`, `aria.MaxInitialNonlinearCorrection()` and `aria.MaxInitialNonlinearRelativeCorrection()`.

Several examples of *[When – expression]* are given below noting that the "C" expression must be enclosed in quotes within the input file.

Convergence based upon comparison of application residuals:

```
Begin parameters for nonlinear converge_step_p1
  # following two lines shown must be a single input command line
  converged when $(aria.MaxResidualNorm(0.0) < 1.e-6 && adagio.norm(0.0)
    < 1.e-6) || CURRENT_STEP > 2000"
End parameters for nonlinear converge_step_p1
```

Transfer at first step and then every four steps:

```
Transfer aria_to_adagio when "(CURRENT_STEP == 1) || (CURRENT_STEP % 4 == 0)"
```

Advance the region at second step:

```
advance aria_region when "CURRENT_STEP == 2"
```

Additionally, one may also use application specific global variables in the [*When – expression*] criteria. Global variables that are generally available for use are listed as such in the simulation log file. Unfortunately these variables may not be directly accessible to the user. Hence consultation with an application developer may be required in this regard.

In the case of transient analysis it is sometimes necessary to initialize a distribution of values before the analysis actually begins. As an example, one may want to initialize a Field that will be transferred to another Region with a distribution of values with the goal of setting a reference state. For this purpose solution control provides a means of initialization, Initialize.

```
Begin Sierra myJob
.
. Materials, Solvers, Finite Element Model
.
Begin Procedure My_Aria_Procedure

Begin Initialize
  Transfer var1_Region_to_var2_My_Aria_Region
End Initialize

Begin Solution Control Description

  Use system Initialize
  Use System Main

Begin System Main
  Simulation Start Time           = 0.0
  Simulation Termination Time     = 10.0
  Simulation Max Global Iterations = 1000

  Begin Transient Time_Block_1
    Advance My_Aria_Region
    Advance var1_Region
  End
End

Begin Parameters For Transient Time_Block_1
  Start Time           = 0.0
  Number of steps = 8
  Begin Parameters For Aria Region var1_Region
    . parameter commands
  End
  Begin Parameters For Aria Region My_Aria_Region
    . parameter commands
  End
End

End

.
. Var1_Region commands
```

```

.
. My_Aria_Region commands
.
End Procedure My_Aria_Procedure
.
End Sierra myJob

```

14.2. SOLUTION CONTROL DESCRIPTION

Scope: Procedure

Begin Solution Control Description *Name*

Use System *Name*

Begin Initialize *Name*

End

Begin Parameters For

End

Begin System *Name*

End

End

Summary Contains the commands needed to execute an analysis using the arpeggio procedure that uses Solver Control.

14.2.1. Use System

Scope: Solution Control Description

Use System *Name*

Parameter <i>Name</i>	Value string	Default undefined

Summary This set the name of which system to use.

14.3. SYSTEM

Scope: Solution Control Description

Begin System *Name*

Adapt *Region_name...* Using *Field_name...* [When *When-expression*]

Compute Indicator On *Region_name...* Using *Indicator_name...* [When *When-expression*]

Event *Name...* [When *When-expression*]

Execute Postprocessor Group *Group_name...* On *Region_name...* [When *When-expression*]

Indicatemarkadapt *Region_name* Using *Indicator Marker* [When *When-expression*]

Mark *Region_name...* Using *Marker_name...* [When *When-expression*]

Markadapt *Region_name* Using *Marker* [When *When-expression*]

Output *Name* [When *When-expression*]

Simulation Max Global Iterations {=|are|is} *Number*

Simulation Start Time {=|are|is} *Number*

Simulation Termination Time {=|are|is} *Number*

Transfer *Name* [When *When-expression*]

Use Initialize *Name*

Begin Adaptivity *Name*

End

Begin Sequential *Name*

End

Begin Transient *Name*

End

End

Summary This block wraps a solver system for a given name. The NAME parameter is the name used to define the system. There can be more than one system block in the Solver Control Description block. The "use system NAME" line command controls which one is to be used.

14.3.1. Adapt

Scope: System

Adapt *Region_name...* Using *Field_name...* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string...	undefined
<i>Field_name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a mesh adaptment on the specific block should be performed.

14.3.2. Compute Indicator On

Scope: System

Compute Indicator On *Region_name...* Using *Indicator_name...* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string...	undefined
<i>Indicator_name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a mesh adaptment on the specific block should be performed.

14.3.3. Event

Scope: System

Event *Name...* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a single step that has no time associated with it. It can cause a solution transfer between regions or cause something to print.

14.3.4. Execute Postprocessor Group

Scope: System

Execute Postprocessor Group *Group_name...* On *Region_name...* [When *When-expression*]

Parameter	Value	Default
<i>Group_name</i>	string...	undefined
<i>Region_name</i>	string...	undefined

Summary Used within a Solver Control block to cause the group named *group_name* to be executed on region *region_name*.

14.3.5. Indicatemarkadapt

Scope: System

Indicatemarkadapt *Region_name* Using *Indicator Marker* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string	undefined
<i>Indicator</i>	string	undefined
<i>Marker</i>	string	undefined

Summary Shortcut line command... equivalent to: Compute Indicator On ... Mark ... Adapt ...

14.3.6. Mark

Scope: System

Mark *Region_name...* Using *Marker_name...* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string...	undefined
<i>Marker_name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a mesh adaptment on the specific block should be performed.

14.3.7. Markadapt

Scope: System

Markadapt *Region_name* Using *Marker* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string	undefined
<i>Marker</i>	string	undefined

Summary Shortcut line command... equivalent to: Mark ... Adapt ...

14.3.8. Output

Scope: System

Output *Name* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary A Solver Control Output line command which execute a perform I/O on the region.

14.3.9. Simulation Max Global Iterations

Scope: System

Simulation Max Global Iterations {=*|are|is*} *Number*

Parameter	Value	Default
<i>Number</i>	integer	undefined

Summary The Total number of Solves.

14.3.10. Simulation Start Time

Scope: System

Simulation Start Time {=*|are|is*} *Number*

Parameter	Value	Default
<i>Number</i>	real	undefined

Summary Simulation starting time. (by default 0.0)

14.3.11. Simulation Termination Time

Scope: System

Simulation Termination Time {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	real	undefined

Summary The drop dead time.

14.3.12. Transfer

Scope: System

Transfer *Name* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary A Solver Control Transfer line command which executes all transfers defined from the specified region. All transfers with a send region of 'name' will be executed.

14.3.13. Use Initialize

Scope: System

Use Initialize *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary This set the name of which initialization to use.

14.4. TRANSIENT

Scope: System

Begin Transient *Name*

Adapt *Region_name...* Using *Field_name...* [When *When-expression*]

Advance *Name...* [When *When-expression*]

Compute Indicator On *Region_name...* Using *Indicator_name...* [When *When-expression*]

Event *Name...* [When *When-expression*]

```

Execute Postprocessor Group Group_name... On Region_name... [
When When-expression ]

Indicatemarkadapt Region_name Using Indicator Marker [ When
When-expression ]

Involve Name

Mark Region_name... Using Marker_name... [ When When-expression
]

Markadapt Region_name Using Marker [ When When-expression ]

Output Name [ When When-expression ]

Transfer Name [ When When-expression ]

Begin Adaptivity Name

End

Begin Nonlinear Name

End

Begin Subcycle Name

End

End

```

Summary This block is used to wrap a time loop.

14.4.1. Adapt

Scope: Transient

```
Adapt Region_name... Using Field_name... [ When When-expression ]
```

Parameter	Value	Default
<i>Region_name</i>	string...	undefined
<i>Field_name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a mesh adaptment on the specific block should be performed.

14.4.2. Advance

Scope: Transient

Advance *Name...* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a single step that advances the solution. The name is that matches the physics.

14.4.3. Compute Indicator On

Scope: Transient

Compute Indicator On *Region_name...* Using *Indicator_name...* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string...	undefined
<i>Indicator_name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a mesh adaptment on the specific block should be performed.

14.4.4. Event

Scope: Transient

Event *Name...* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a single step that has no time associated with it. It can cause a solution transfer between regions or cause something to print.

14.4.5. Execute Postprocessor Group

Scope: Transient

Execute Postprocessor Group *Group_name...* On *Region_name...* [When *When-expression*]

Parameter	Value	Default
<i>Group_name</i>	string...	undefined
<i>Region_name</i>	string...	undefined

Summary Used within a Solver Control block to cause the group named *group_name* to be executed on region *region_name*.

14.4.6. Indicatemarkadapt

Scope: Transient

Indicatemarkadapt *Region_name* Using *Indicator Marker* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string	undefined
<i>Indicator</i>	string	undefined
<i>Marker</i>	string	undefined

Summary Shortcut line command... equivalent to: Compute Indicator On ... Mark ... Adapt ...

14.4.7. Involve

Scope: Transient

Involve *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify a physics participant to a coupled problem solved using matrix-free nonlinear.

14.4.8. Mark

Scope: Transient

Mark *Region_name...* Using *Marker_name...* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string...	undefined
<i>Marker_name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a mesh adaptment on the specific block should be performed.

14.4.9. Markadapt

Scope: Transient

Markadapt *Region_name* Using *Marker* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string	undefined
<i>Marker</i>	string	undefined

Summary Shortcut line command... equivalent to: Mark ... Adapt ...

14.4.10. Output

Scope: Transient

Output *Name* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary A Solver Control Output line command which execute a perform I/O on the region.

14.4.11. Transfer

Scope: Transient

Transfer *Name* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary A Solver Control Transfer line command which executes all transfers defined from the specified region. All transfers with a send region of 'name' will be executed.

14.5. NONLINEAR

Scope: Sequential

Begin Nonlinear *Name*

Adapt *Region_name...* Using *Field_name...* [When *When-expression*]

Advance *Name...* [When *When-expression*]

Compute Indicator On *Region_name...* Using *Indicator_name...* [When *When-expression*]

Event *Name...* [When *When-expression*]

Execute Postprocessor Group *Group_name...* On *Region_name...* [When *When-expression*]

Indicatemarkadapt *Region_name* Using *Indicator Marker* [When *When-expression*]

Involve *Name*

Mark *Region_name...* Using *Marker_name...* [When *When-expression*]

Markadapt *Region_name* Using *Marker* [When *When-expression*]

Output *Name* [When *When-expression*]

Transfer *Name* [When *When-expression*]

Begin Subcycle *Name*

End

End

Summary This block is used to wrap a nonlinear solve loop.

14.5.1. Adapt

Scope: Nonlinear

Adapt *Region_name...* Using *Field_name...* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string...	undefined
<i>Field_name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a mesh adaptment on the specific block should be performed.

14.5.2. Advance

Scope: Nonlinear

Advance *Name...* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a single step that advances the solution. The name is that matches the physics.

14.5.3. Compute Indicator On

Scope: Nonlinear

Compute Indicator On *Region_name...* Using *Indicator_name...* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string...	undefined
<i>Indicator_name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a mesh adaptment on the specific block should be performed.

14.5.4. Event

Scope: Nonlinear

Event *Name...* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a single step that has no time associated with it. It can cause a solution transfer between regions or cause something to print.

14.5.5. Execute Postprocessor Group

Scope: Nonlinear

Execute Postprocessor Group *Group_name...* On *Region_name...* [When *When-expression*]

Parameter	Value	Default
<i>Group_name</i>	string...	undefined
<i>Region_name</i>	string...	undefined

Summary Used within a Solver Control block to cause the group named *group_name* to be executed on region *region_name*.

14.5.6. Indicatemarkadapt

Scope: Nonlinear

Indicatemarkadapt *Region_name* Using *Indicator Marker* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string	undefined
<i>Indicator</i>	string	undefined
<i>Marker</i>	string	undefined

Summary Shortcut line command... equivalent to: Compute Indicator On ... Mark ... Adapt ...

14.5.7. Involve

Scope: Nonlinear

Involve *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify a physics participant to a coupled problem solved using matrix-free nonlinear.

14.5.8. Mark

Scope: Nonlinear

Mark *Region_name...* Using *Marker_name...* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string...	undefined
<i>Marker_name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a mesh adaptment on the specific block should be performed.

14.5.9. Markadapt

Scope: Nonlinear

Markadapt *Region_name* Using *Marker* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string	undefined
<i>Marker</i>	string	undefined

Summary Shortcut line command... equivalent to: Mark ... Adapt ...

14.5.10. Output

Scope: Nonlinear

Output *Name* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary A Solver Control Output line command which execute a perform I/O on the region.

14.5.11. Transfer

Scope: Nonlinear

Transfer *Name* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary A Solver Control Transfer line command which executes all transfers defined from the specified region. All transfers with a send region of 'name' will be executed.

14.6. SUBCYCLE

Scope: Nonlinear

Begin Subcycle *Name*

Adapt *Region_name...* Using *Field_name...* [When *When-expression*]

Advance *Name...* [When *When-expression*]

Compute Indicator On *Region_name...* Using *Indicator_name...* [When *When-expression*]

Event *Name...* [When *When-expression*]

Execute Postprocessor Group *Group_name...* On *Region_name...* [When *When-expression*]

Indicatemarkadapt *Region_name* Using *Indicator Marker* [When *When-expression*]

Involve *Name*

Mark *Region_name...* Using *Marker_name...* [When *When-expression*]

Markadapt *Region_name* Using *Marker* [When *When-expression*]

Output *Name* [When *When-expression*]

Transfer *Name* [When *When-expression*]

End

Summary This block is used to wrap a subcycle time loop.

14.6.1. Adapt

Scope: Subcycle

Adapt *Region_name...* Using *Field_name...* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string...	undefined
<i>Field_name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a mesh adaptment on the specific block should be performed.

14.6.2. Advance

Scope: Subcycle

Advance *Name...* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a single step that advances the solution. The name is that matches the physics.

14.6.3. Compute Indicator On

Scope: Subcycle

Compute Indicator On *Region_name...* Using *Indicator_name...* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string...	undefined
<i>Indicator_name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a mesh adaptment on the specific block should be performed.

14.6.4. Event

Scope: Subcycle

Event *Name...* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a single step that has no time associated with it. It can cause a solution transfer between regions or cause something to print.

14.6.5. Execute Postprocessor Group

Scope: Subcycle

Execute Postprocessor Group *Group_name...* On *Region_name...* [When *When-expression*]

Parameter	Value	Default
<i>Group_name</i>	string...	undefined
<i>Region_name</i>	string...	undefined

Summary Used within a Solver Control block to cause the group named *group_name* to be executed on region *region_name*.

14.6.6. Indicatemarkadapt

Scope: Subcycle

Indicatemarkadapt *Region_name* Using *Indicator Marker* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string	undefined
<i>Indicator</i>	string	undefined
<i>Marker</i>	string	undefined

Summary Shortcut line command... equivalent to: Compute Indicator On ... Mark ... Adapt ...

14.6.7. Involve

Scope: Subcycle

Involve *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify a physics participant to a coupled problem solved using matrix-free nonlinear.

14.6.8. Mark

Scope: Subcycle

Mark *Region_name...* Using *Marker_name...* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string...	undefined
<i>Marker_name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a mesh adaptment on the specific block should be performed.

14.6.9. Markadapt

Scope: Subcycle

Markadapt *Region_name* Using *Marker* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string	undefined
<i>Marker</i>	string	undefined

Summary Shortcut line command... equivalent to: Mark ... Adapt ...

14.6.10. Output

Scope: Subcycle

Output *Name* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary A Solver Control Output line command which execute a perform I/O on the region.

14.6.11. Transfer

Scope: Subcycle

Transfer *Name* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary A Solver Control Transfer line command which executes all transfers defined from the specified region. All transfers with a send region of 'name' will be executed.

14.7. SEQUENTIAL

Scope: System

Begin Sequential *Name*

Adapt *Region_name...* Using *Field_name...* [When *When-expression*]

Advance *Name...* [When *When-expression*]

Compute Indicator On *Region_name...* Using *Indicator_name...* [When *When-expression*]

Event *Name...* [When *When-expression*]

Execute Postprocessor Group *Group_name...* On *Region_name...* [When *When-expression*]

Indicatemarkadapt *Region_name* Using *Indicator Marker* [When *When-expression*]

Involve *Name*

Mark *Region_name...* Using *Marker_name...* [When *When-expression*]

Markadapt *Region_name* Using *Marker* [When *When-expression*]

Output *Name* [When *When-expression*]

Transfer *Name* [When *When-expression*]

Begin Adaptivity *Name*

End

Begin Nonlinear *Name*

End

End

Summary This block is used to wrap a sequential solution. It is used to wrap a sequence of Non-Linear or pseudo time solve step solves.

14.7.1. Adapt

Scope: Sequential

Adapt *Region_name...* Using *Field_name...* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string...	undefined
<i>Field_name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a mesh adaptment on the specific block should be performed.

14.7.2. Advance

Scope: Sequential

Advance *Name...* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a single step that advances the solution. The name is that matches the physics.

14.7.3. Compute Indicator On

Scope: Sequential

Compute Indicator On *Region_name...* Using *Indicator_name...* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string...	undefined
<i>Indicator_name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a mesh adaptment on the specific block should be performed.

14.7.4. Event

Scope: Sequential

Event *Name...* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a single step that has no time associated with it. It can cause a solution transfer between regions or cause something to print.

14.7.5. Execute Postprocessor Group

Scope: Sequential

Execute Postprocessor Group *Group_name...* On *Region_name...* [When *When-expression*]

Parameter	Value	Default
<i>Group_name</i>	string...	undefined
<i>Region_name</i>	string...	undefined

Summary Used within a Solver Control block to cause the group named *group_name* to be executed on region *region_name*.

14.7.6. Indicatemarkadapt

Scope: Sequential

Indicatemarkadapt *Region_name* Using *Indicator Marker* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string	undefined
<i>Indicator</i>	string	undefined
<i>Marker</i>	string	undefined

Summary Shortcut line command... equivalent to: Compute Indicator On ... Mark ... Adapt ...

14.7.7. Involve

Scope: Sequential

Involve *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify a physics participant to a coupled problem solved using matrix-free nonlinear.

14.7.8. Mark

Scope: Sequential

Mark *Region_name...* Using *Marker_name...* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string...	undefined
<i>Marker_name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a mesh adaptment on the specific block should be performed.

14.7.9. Markadapt

Scope: Sequential

Markadapt *Region_name* Using *Marker* [When *When-expression*]

Parameter	Value	Default
<i>Region_name</i>	string	undefined
<i>Marker</i>	string	undefined

Summary Shortcut line command... equivalent to: Mark ... Adapt ...

14.7.10. Output

Scope: Sequential

Output *Name* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary A Solver Control Output line command which execute a perform I/O on the region.

14.7.11. Transfer

Scope: Sequential

Transfer *Name* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary A Solver Control Transfer line command which executes all transfers defined from the specified region. All transfers with a send region of 'name' will be executed.

14.8. INITIALIZE

Scope: Solution Control Description

Begin Initialize *Name*

Advance *Name*... [When *When-expression*]

Event *Name*... [When *When-expression*]

Involve *Name*

Transfer *Name* [When *When-expression*]

End

Summary This block wraps a initializer for a given name. The NAME parameter is the name used to define the initialization block. There can be more than one initialize block in the Solver Control Description block. The "use initialize NAME" line command controls which one is to be used.

14.8.1. Advance

Scope: Initialize

Advance *Name*... [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a single step that advances the solution. The name is that matches the physics.

14.8.2. Event

Scope: Initialize

Event *Name*... [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a single step that has no time associated with it. It can cause a solution transfer between regions or cause something to print.

14.8.3. Involve

Scope: Initialize

Involve *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify a physics participant to a coupled problem solved using matrix-free nonlinear.

14.8.4. Transfer

Scope: Initialize

Transfer *Name* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary A Solver Control Transfer line command which executes all transfers defined from the specified region. All transfers with a send region of 'name' will be executed.

14.9. PARAMETERS FOR

Scope: Solution Control Description

Begin Parameters For

Converged When *Convergence-expression*

Incremental Number Of Steps {=*|are|is|*} *Number*

Initial Deltat {=*|are|is|*} *Number*

Number Of Adaptivity Steps {=*|are|is|*} *Number*

Number Of Steps {=*|are|is|*} *Number*

Reinitialize Transient

Start Time {=*|are|is|*} *Number*

Termination Time {=*|are|is|*} *Number*

Time Step Quantum {=*|are|is|*} *TimeStepQuantum*

Time Step Style *TimeStepStyle...*

Total Change In Time {=*|are|is|*} *Number*

Begin Parameters For Aria Region *RegionName*

End

End

Summary A Solver Control PARAMETERS block to set up control data for the SC_type parameter. Inside this block one sets the time step parameters or nonlinear parameters.

14.9.1. Converged When

Scope: Parameters For

Converged When *Convergence-expression*

Parameter	Value	Default
<i>Convergence-expression</i>	(expression)	undefined

Summary Set the convergence expression.

14.9.2. Incremental Number Of Steps

Scope: Parameters For

Incremental Number Of Steps {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	integer	undefined

Summary The incremental number steps to run the time for nonlinear loop. Number of time steps to run after restarting. NUMBER OF STEPS is total number of steps to run

14.9.3. Initial Deltat

Scope: Parameters For

Initial Deltat {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	real	undefined

Summary Assign an initial delta T

14.9.4. Number Of Adaptivity Steps

Scope: Parameters For

Number Of Adaptivity Steps {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	integer	undefined

Summary The number steps to run the time or nonlinear loop

14.9.5. Number Of Steps

Scope: Parameters For

Number Of Steps {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	integer	undefined

Summary The number steps to run the time for nonlinear loop

14.9.6. Reinitialize Transient

Scope: Parameters For

Summary Reset time and re-initialize regions each step of the adaptivity loop.

14.9.7. Start Time

Scope: Parameters For

Start Time {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	real	undefined

Summary Assign a start time.

14.9.8. Termination Time

Scope: Parameters For

Termination Time {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	real	undefined

Summary Assign a final time to stop

14.9.9. Time Step Quantum

Scope: Parameters For

Time Step Quantum {=|are|is} *TimeStepQuantum*

Parameter	Value	Default
<i>TimeStepQuantum</i>	real	undefined

Summary Set the time stepping quantum time for SNAP style stepping.

14.9.10. Time Step Style

Scope: Parameters For

Time Step Style *TimeStepStyle...*

Parameter	Value	Default
<i>TimeStepStyle</i>	{clip noclip nosnap snap}	CLIP NOSNAP

Summary Set the time stepping style.

When CLIP is specified, the time step size will be clipped at the last step of the transient loop so that it ends at the transient loop's end time. If clip is not specified, the last time is allowed to exceed to the transient loop's end time and the following transient loop will start at the exceeded end time.

When SNAP is specified, the time step is broken down into "quantum" time units. By default this quantum time is 12 orders of magnitude down from the difference between the start and end time for the transient loop. This value can be overridden using the TIME STEP QUANTUM line command. All time values are "snapped" to multiples of the quantum time by rounding to the nearest quantum multiple.

14.9.11. Total Change In Time

Scope: Parameters For

Total Change In Time {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	real	undefined

Summary Use this number and the initial time to compute termination time.

14.9.12. Advance

Scope:

Advance *Name...* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a single step that advances the solution. The name is that matches the physics.

14.9.13. Converged When

Scope:

Converged When *Convergence-expression*

Parameter	Value	Default
<i>Convergence-expression</i>	(expression)	undefined

Summary Set the convergence expression.

14.9.14. Event

Scope:

Event *Name...* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string...	undefined

Summary Used within a Solver Control block to indicate a single step that has no time associated with it. It can cause a solution transfer between regions or cause something to print.

14.9.15. Initial Deltat

Scope:

Initial Deltat {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	real	undefined

Summary Assign an initial delta T

14.9.16. Involve

Scope:

Involve *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify a physics participant to a coupled problem solved using matrix-free nonlinear.

14.9.17. Number Of Adaptivity Steps

Scope:

Number Of Adaptivity Steps {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	integer	undefined

Summary The number steps to run the time or nonlinear loop

14.9.18. Number Of Steps

Scope:

Number Of Steps {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	integer	undefined

Summary The number steps to run the time for nonlinear loop

14.9.19. Output

Scope:

Output *Name* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary A Solver Control Output line command which execute a perform I/O on the region.

14.9.20. Reinitialize Transient

Scope:

Summary Reset time and re-initialize regions each step of the adaptivity loop.

14.9.21. Simulation Max Global Iterations

Scope:

Simulation Max Global Iterations {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	integer	undefined

Summary The Total number of Solves.

14.9.22. Simulation Start Time

Scope:

Simulation Start Time {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	real	undefined

Summary Simulation starting time. (by default 0.0)

14.9.23. Simulation Termination Time

Scope:

Simulation Termination Time {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	real	undefined

Summary The drop dead time.

14.9.24. Start Time

Scope:

Start Time {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	real	undefined

Summary Assign a start time.

14.9.25. Termination Time

Scope:

Termination Time {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	real	undefined

Summary Assign a final time to stop

14.9.26. Time Step Quantum

Scope:

Time Step Quantum {=|are|is} *TimeStepQuantum*

Parameter	Value	Default
<i>TimeStepQuantum</i>	real	undefined

Summary Set the time stepping quantum time for SNAP style stepping.

14.9.27. Time Step Style

Scope:

Time Step Style *TimeStepStyle...*

Parameter	Value	Default
<i>TimeStepStyle</i>	{clip noclip nosnap snap}	CLIP NOSNAP

Summary Set the time stepping style.

When CLIP is specified, the time step size will be clipped at the last step of the transient loop so that it ends at the transient loop's end time. If clip is not specified, the last time is allowed to exceed to the transient loop's end time and the following transient loop will start at the exceeded end time.

When SNAP is specified, the time step is broken down into "quantum" time units. By default this quantum time is 12 orders of magnitude down from the difference between the start and end time for the transient loop. This value can be overridden using the TIME STEP QUANTUM line command. All time values are "snapped" to multiples of the quantum time by rounding to the nearest quantum multiple.

14.9.28. Total Change In Time

Scope:

Total Change In Time {=|are|is} *Number*

Parameter	Value	Default
<i>Number</i>	real	undefined

Summary Use this number and the initial time to compute termination time.

14.9.29. Transfer

Scope:

Transfer *Name* [When *When-expression*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary A Solver Control Transfer line command which executes all transfers defined from the specified region. All transfers with a send region of 'name' will be executed.

14.9.30. Use Initialize

Scope:

Use Initialize *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary This set the name of which initialization to use.

14.9.31. Use System

Scope:

Use System *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary This set the name of which system to use.

15. TRANSFER REFERENCE

15.1. OVERVIEW

The Sierra Transfer utility provides the means by which to communicate data between two Sierra application Regions. The utility is fairly flexible as it provides the ability to move data directly onto another problem domain either by direct copy or by interpolation. Analysts without prior experience with transfer are often uncertain as to which type of transfer to use. The two capabilities function exactly as their names imply but understanding which method to use requires a basic understanding of how each method works.

Copy transfer assumes that the discretization for applications involved in the transfer are identical. Moreover, copy transfer also assumes that the mesh is identical so that global IDs of nodes and elements within each mesh are the same. Under these assumptions a geometric search of source to destination locations is not necessary and a simple algorithm is able to perform the data transfer in a straightforward manner.

Interpolation transfer is much more general than copy transfer since it assumes only that data from one application must be geometrically mapped for use in another application. A mathematical definition of this mapping is made possible using the results from a geometric search of points on the destination mesh and their image on the sending mesh. With regard to code performance, copy transfer will always be more efficient than interpolation transfer but is rarely applicable in mainstream simulations.

Interpolation transfer is designed to deal with complications that arise in mapping data from one application to the other and is more reliable. As a rule, one should always use interpolation transfer and not copy transfer. At the same time, an analyst should strategize model construction in order to offset some of the performance costs of interpolation transfer.

Even with a basic understanding of transfer, proper and improper use of these transfer operations should be visualized. Several proper transfer source and destinations are illustrated in Figure 15.1-1. The numbers on the figures correspond to the ExodusII global IDs of nodes or elements.

Problematic transfer source and destination configurations are illustrated in Figure 15.1-2. Once again the numbers on the figures correspond to the ExodusII global IDs of nodes or elements.

In using the transfer utility one must clearly define the sending region (where the data resides) and the the receiving region (the data destination). Additionally one must also specify the general geometric location of data sender and receiver based upon existing mesh entities (blocks or surfaces). Sender and receiver need not be of same topology but the source and target destinations should overlap geometrically. Clearly the definition mesh entities influences time spent in the geometric search process and should be a key consideration in model construction.




Figure 15.1-1.. Valid Transfer Operations


Both Aria solution Fields and User Fields [2.10](#) can be transferred to/from other Sierra application Regions. Transfer of data into Aria requires that provision be made for a Field storage on the Aria Region. Storage for solution Field (DOF) transfer into Aria is implicitly provided by the presence of an Aria equation command line with term type of XFER (Chapter [6](#)). Storage for non-DOF Fields is implicitly provided through the presence of a User Field command line [2.11](#). These non-DOF Fields are internally used or modified by virtue of being referenced in other command lines such as material models, boundary conditions, initial conditions or source terms.

The following section outlines the commands to be used in setting up transfer operations. Special attention should be paid to the syntax of the SEND command line since it differs between COPY and INTERPOLATION transfer.

Since several different uses of transfer can arise and several of those examples for steady problems are included below. The same basic setup of transfer would apply to transient problems as well.

A skeleton outline of one-way transfer from Region_1 to Region_2 in a steady-state problem would be:

```
Begin Sierra
.
Begin Transfer my_transfer
.
transfer commands for first_region to second_region
```



End

Begin Procedure My_Aria_Procedure

Begin Solution Control Description

Use System Main

Begin System Main

Begin Sequential MySolveBlock

Advance first_Region

transfer my_transfer

Advance second_Region

End

End

```

End

Begin Aria Region first_region
.
eq energy for temperature On block_1 using q1 with lumped_mass diff
.
End

Begin Aria Region second_region
.
eq energy for temperature On block_1 using q1 with xfer
.
End

End
.
End Sierra

```

A skeleton outline of two-way transfer between Region_1 to Region_2 in a steady-state problem would be:

```
Begin Sierra
```

```
.
Begin Transfer my_first_transfer
.
  transfer commands for first_region to second_region
.
End
```

```
.
Begin Transfer my_second_transfer
.
  transfer commands for second_region to first_region
.
End
```

```
.
Begin Procedure My_Aria_Procedure
.
  Begin Solution Control Description
    Use System Main
    Begin System Main
      Begin Sequential MySolveBlock
        Advance first_Region
        transfer my_first_transfer
        Advance second_Region
        transfer my_second_transfer
      End
    End
  End
End
```

```
Begin Aria Region first_region
.
  eq energy for temperature On block_1 using q1 with diff
  eq species_3 for temperature On block_1 using q1 with xfer
.
End
```

```
Begin Aria Region second_region
.
  eq energy for temperature On block_1 using q1 with xfer
  eq species_3 for species_3 On block_1 using q1 with diff
.
End
```


End

.

End Sierra

Assume an input mesh for an Input_Output Region [26.1](#) contains a nodal variable ConvCoeff. In this case a skeleton outline for one-way transfer of ConvCoeff to to Region_2 in a steady-state problem would be:

```

Begin Sierra
.
Begin Transfer my_first_transfer
.
  transfer commands for input_output_region to second_region
.
  SEND field hNd state none TO ConvCoeff state none
.
End
.
Begin Procedure My_Aria_Procedure
.
  Begin Solution Control Description
    Use System Main
    Begin System Main
      Begin Sequential MySolveBlock
        Advance first_Region
        transfer my_first_transfer
        Advance second_Region
      End
    End
  End
End

Begin Input_Output io_region
  USE FINITE ELEMENT MODEL my_input_transfer
End

Begin Aria Region second_region
.
  USER FIELD REAL NODE SCALAR ConvCoeff on surface_1
.
End

End
.
End Sierra

```

15.2. TRANSFER

Scope: Procedure

Begin Transfer *Transfer_name*

Abort If Field Not Defined On Copy Transfer Send Or Receive Object

All Fields

Copy *Option1 Option2* From *From_region_name* To *To_region_name*

Distance Function Is Closest Receive Node To Send Centroid

Exclude Ghosted

From *Option1* To *Option2*

Gauss Point Integration Order {=|are|is} *Order*

Interpolate *Option1 Option2* From *From_region_name* To
To_region_name

Interpolation Function *User_Subroutine*

Nodes Outside Region {=|are|is} *Option*

Search Coordinate Field *Source_field_name* State *Option1* To
Destination_field_name State *Option2*

Search Geometric Tolerance {=|are|is} *Geometric_tolerance*

Search Surface Gap Tolerance {=|are|is} *Surface_gap_tolerance* [Or
Less]

Search Type {=|are|is} [*Option1 Option2 Option3*]

Select One Receiver For Each Send Object

Select One Unique Receiver For Each Send Object

Send *Predefined-transfer* Fields

Send Block *From_blocks...* To *To_blocks...*

Send Field *Source_field_name* State *Option1* To
Destination_field_name State *Option2* [Lower Bound *Lower_bound*
Upper Bound *Upper_bound*]

Begin Receive Blocks

End

Begin Send Blocks

End

End

Summary transfer region/mesh information. the mechanics/variables information will get sorted out by the calling procedure.

15.2.1. Abort If Field Not Defined On Copy Transfer Send Or Receive Object

Scope: Transfer

Summary For testing purposes only. Normally mesh objects in the send or receive mesh which do not have the specified field defined on them are just ignored. This line command allows the construction of tests in which it is known that every mesh object should have the specified field defined on it and to abort if that field is not found.

15.2.2. All Fields

Scope: Transfer

Summary Select all fields for transfer that have same name and state for source and destination regions.

15.2.3. Copy

Scope: Transfer

Copy *Option1 Option2* From *From_region_name* To *To_region_name*

Parameter	Value	Default
<i>Option1</i>	{surface volume}	undefined
<i>Option2</i>	{constraints elements nodes}	undefined
<i>From_region_name</i>	string	undefined
<i>To_region_name</i>	string	undefined

Summary Copy transfer elements, nodes or constraints from one region to another. The copy transfer is very specific in that the sending and receiving mesh parts must have identical global ids for every element to be copied. The copy transfer works by iterating over all the mesh objects in the receiving mesh and using the global id of the receiving mesh object to find a mesh object in the sending mesh with the same global id. The field to transfer is then copied from the sending to receiving objects. There is no interpolation and the actual coordinates of the sending and receiving objects are not used and could be very different. The copy transfer is used in very special cases where the same mesh was read into both the sending and receiving meshes, there was no element death and there was no adaptivity. In this special case, a copy transfer can be much faster than an interpolation transfer.

15.2.4. Distance Function Is Closest Receive Node To Send Centroid

Scope: Transfer

Summary To be used in conjunction with "SELECT ONE UNIQUE RECEIVER FOR EACH SEND OBJECT". This helped in the case where the sending and receiving element blocks did not overlap and an element transfer was using element centroids for the distance computation. The elements were very distorted so that a centroid of a surface element could be far from the surface. It was wanted that the receiving element be the one close to the surface of the block and close to the sending element in the adjacent block. Using the corner nodes was enough since it was a tet mesh with plane faces. In this particular and unusual case this alternative method of matching sending and receiving elements was useful, but it is not expected to be used often or maybe never again.

15.2.5. Exclude Ghosted

Scope: Transfer

Summary exclude ghosted nodes from a copy transfer

15.2.6. From

Scope: Transfer

From *Option1* To *Option2*

Parameter	Value	Default
<i>Option1</i>	{constraints elements nodes}	undefined
<i>Option2</i>	{constraints elements gauss_points nodes}	undefined

Summary Allows the send/receive mesh objects to be different.

15.2.7. Gauss Point Integration Order

Scope: Transfer

Gauss Point Integration Order {= | are | is} *Order*

Parameter	Value	Default
<i>Order</i>	integer	undefined

Summary Integration order to use when transferring to Gauss points.

15.2.8. Interpolate

Scope: Transfer

Interpolate *Option1 Option2 From From_region_name To To_region_name*

Parameter	Value	Default
<i>Option1</i>	{surface volume}	undefined
<i>Option2</i>	{constraints elements nodes}	undefined
<i>From_region_name</i>	string	undefined
<i>To_region_name</i>	string	undefined

Summary Interpolate will transfer elements, nodes or constraints from one mesh to another. The interpolation transfer is very general in that the field values to transfer will be interpolated from the sending to receiving mesh based on the coordinates of the sending and receiving mesh objects.

Many line commands can be used to modify the behavior of the interpolation transfer but the basic algorithm is straightforward. Every mesh object in the receiving mesh is converted into a point. For elements this is the average of the nodal coordinates. An element in the sending mesh containing this point is found. If the field to transfer is nodal, the element shape functions are used to interpolate the nodal field to the receiving point. If the field to transfer is elemental, a bi-linear least squares fit based upon neighboring elements is first performed and then used to define the interpolation of the element field at the receiving point.

15.2.9. Interpolation Function

Scope: Transfer

Interpolation Function *User_Subroutine*

Parameter	Value	Default
<i>User_Subroutine</i>	string	undefined

Summary Allows an application defined subroutine to be used for the interpolation. Normally the interpolation transfer will determine the best type of interpolation to use: Basis functions for nodal fields and a neighborhood least squares fit for element fields. This line command can be used to override this if needed. It also allows an application to register it's own special interpolation functions that can then be used if the special name it was registered with is known.

15.2.10. Nodes Outside Region

Scope: Transfer

Nodes Outside Region {=|are|is} *Option*

Parameter <i>Option</i>	Value {extrapolate ignore project truncate}	Default undefined

Summary This line command defines what to do when a receiving point is outside the scope of the sending mesh.

IGNORE - The receiving mesh object can be ignored and will receive no value. This is almost never a good idea as it can cause mesh objects just outside to have a zero value when the nodes just inside the mesh might have very large values. This can result in a discontinuous receiving field.

EXTRAPOLATE - This is the default behavior. The sending field is extrapolated beyond the bounds of the sending mesh. This can lead to extrapolation error, such as when a large gradient at the surface causes a negative values when only positive values are acceptable. If this happens to the upper and lower bounds that can be placed on the fields to be transferred with the SEND FIELD command.

TRUNCATE - The receiving coordinate is projected back to the surface of the sending mesh to determine a value. This ensures that the receiving value is outside of the field values in the sending mesh.

PROJECT - This option is similar to TRUNCATE in which the receiving coordinate is projected back to the surface of the sending mesh to determine a value. In this case more effort is made to make sure that the projection is normal to the surface in the sending mesh. Sometimes gives a better result than Truncate but is a little more expensive to compute.

If the PROJECT option is used in transferring of surface values, the sending mesh should envelope the receiving mesh. Failure to satisfy this condition will generally result in failure of the transfer.

15.2.11. Search Coordinate Field

Scope: Transfer

Search Coordinate Field *Source_field_name* State *Option1* To
Destination_field_name State *Option2*

Parameter	Value	Default
<i>Source_field_name</i>	string	undefined
<i>Option1</i>	{new nm1 nm2 nm3 nm4 none old}	undefined
<i>Destination_field_name</i>	string	undefined
<i>Option2</i>	{new nm1 nm2 nm3 nm4 none old}	undefined

Summary Normally the interpolation transfers use the default coordinate field to determine geometry information. This line command can be used to specify an alternate field.

15.2.12. Search Geometric Tolerance

Scope: Transfer

Search Geometric Tolerance {=|are|is} *Geometric_tolerance*

Parameter	Value	Default
<i>Geometric_tolerance</i>	real	undefined

15.2.13. Search Surface Gap Tolerance

Scope: Transfer

Search Surface Gap Tolerance {=|are|is} *Surface_gap_tolerance* [Or Less]

Parameter	Value	Default
<i>Surface_gap_tolerance</i>	real	undefined

Summary This is the dimensional tolerance applied during the initial (coarse) search. If specified, all the coarse search boxes are padded by this value. The default behavior is for this to be 1e-9 times the problem bounding box size (diagonal) plus a 10 percent relative expansion per element. If a value is specified for this, it is used as a padding in place of the default with no relative box expansion.

This is a tricky parameter best ignored, let it default to something based on the problem size. During the interpolation transfer there is a geometric search based on the coordinates of the send and receive objects. As part of this search, an axis aligned bounding box is contracted for each sending object and SEARCH GAP TOLERANCE is used to make this box bigger than just a tight bounding box. Lists of receiving points are then quickly found within these axis aligned boxes.

If all points in the receiving mesh are within at least one box, no additional searching needs to be done and the search algorithm is fast. If there are still points in the receiving mesh that were outside of EVERY box, then a warning message will be issued about an "expensive search for extrapolation" for these points. This "expensive search" can be very costly if a large number of receiving objects fall into this category and this line command is provided for those special cases.

The OR LESS optional parameter is used when the tolerance must be set to large value for one part of the mesh but much of the mesh needs a much smaller value. In some cases it is necessary for the tolerance to be set to the actual largest surface gap tolerance which may be far too large a gap for the rest of the mesh. Setting OR LESS allows the search tolerance to be reduced in areas of the mesh thus resulting in a faster search.

15.2.14. Search Type

Scope: Transfer

15.2.15. Select One Receiver For Each Send Object

Scope: Transfer

Summary This option will cause each sending object to be used once and only once. This will have the side effect of some receiving objects not getting any value at all. If you use this option, you will also want to set NODES OUTSIDE REGION IGNORE The example which necessitated this option was a case in which there was a delta function defined on an element in the sending mesh. It was desirable that the delta functions be summed into the receiving mesh such that the total value of the sending was conserved. It was better to have only a single element on the receiving side have a non-zero value that was the sum of sending values and not worry about how close the receiving element was to the sending element. A check that this option is working is to use Encore to computer the sum of the values of the sending and receiving fields to make sure the total sum is the same.

15.2.16. Select One Unique Receiver For Each Send Object

Scope: Transfer

Summary An unusual flag to get around an odd problem. Normally each receive object transfers from the nearest sending object so it is almost always the case that a send object will be used multiple times to define a receiving value. This option will cause each sending object to be used only once. This will have the side effect of some receiving objects not getting any value at all. If you use this option, you will also want to set NODES OUTSIDE REGION IGNORE or else the uniqueness will be lost for nodes outside the sending region. The example which necessitated this option was a case in which there was a delta function defined on an element in the sending mesh. It was desirable that the delta function be defined on the receiving mesh for only a single element in the neighborhood of the sending element. The analysis was more sensitive to the number of delta functions on the receiving side than the location. So it was better to have only a single element on the receiving side have a non-zero value and not worry about how close the receiving element was to the sending element.

15.2.17. Send

Scope: Transfer

Send *Predefined-transfer* Fields

Parameter	Value	Default
<i>Predefined-transfer</i>	{}	undefined

Summary Use predefined transfer semantics provided by the specified name.

15.2.18. Send Block

Scope: Transfer

Send Block *From_blocks...* To *To_blocks...*

Parameter	Value	Default
<i>From_blocks</i>	string...	undefined
<i>To_blocks</i>	string...	undefined

Summary Add element blocks to a particular same mesh element copy transfer operator.

The copy transfer can have multiple of these lines to define many blocks, but each line sends a single block to a single block: SEND BLOCK block_1 TO block_1 SEND BLOCK block_101 TO block_101

The interpolation transfer can have only a single SEND BLOCK line, but can define many from/to blocks: SEND BLOCK block_3 block_5 block_6 TO block_3 block_5

15.2.19. Send Field

Scope: Transfer

Send Field *Source_field_name* State *Option1* To *Destination_field_name* State *Option2* [Lower Bound *Lower_bound* Upper Bound *Upper_bound*]

Parameter	Value	Default
<i>Source_field_name</i>	string	undefined
<i>Option1</i>	{new nm1 nm2 nm3 nm4 none old}	undefined
<i>Destination_field_name</i>	string	undefined
<i>Option2</i>	{new nm1 nm2 nm3 nm4 none old}	undefined

Summary Specifies the mapping between source and destination field names. Vector and tensor fields can be subscripted using parenthesis and i's based or brackets and o based. Notes on subscripting: (o) Does not work for COPY transfers, only INTERPOLATION type transfers. (1) If the field name itself actually contains either parenthesis or brackets then we are in trouble and an error is going to be thrown due to a syntax error in index specification. (2) Only a single subscript is allowed so vectors of vectors or higher order tensors can not use double subscripts. But it should be possible to determine the correct offset within the field and pick out the correct value with a little effort. (3) Once subscripted, only a single value will be transferred. It is not possible to transfer multiple values starting at a certain index, instead multiple line commands must be used, as shown above. (4) The indexes can be o based with brackets or i based when using parenthesis. Although this could be very confusing if mixed within a single line command. (5) Both the from and to fields can be subscripted independently on the same line.

example SEND FIELD velocity TO velocity SEND FIELD temp TO temperature lower bound o SEND FIELD x TO y lower bound 10 upper bound 100 SEND FIELD A(2) TO B(3) lower bound 10 upper bound 100 SEND FIELD A[1] TO B[2] lower bound 10 upper bound 100

16. TIME INTEGRATION COMMANDS

16.1. SETTING UP A TRANSIENT PROBLEM

All Aria input files must include a Solution Control Description block in the Procedure section of the input file. The following example illustrates use of the solution control command block. This example demonstrates that time stepping for transient analysis can be carried out with either fixed [16.3](#) or adaptive time stepping [16.4](#).

```
.  
.   
.   
Begin Procedure My_Aria_Procedure  
  
    Begin Solution Control Description  
  
        Use System Main  
  
        Begin System Main  
            Simulation Start Time          = 0.0  
            Simulation Termination Time    = 10.0  
            Simulation Max Global Iterations = 1000  
  
            Begin Transient Time_Block_1  
                Advance My_Aria_Region  
            End  
            Begin Transient Time_Block_2  
                Advance My_Aria_Region  
            End  
  
        End  
  
        Begin Parameters For Transient Time_Block_1  
            Start Time          = 0.0  
            Number of steps = 8  
            Begin Parameters For Aria Region My_Aria_Region  
                Time Step Variation    = Fixed  
                Initial Time Step Size = 0.001
```

```

        End
    End

    Begin Parameters For Transient Time_Block_2
        Begin Parameters For Aria Region My_Aria_Region
            Time Step Variation          = Adaptive
            Initial Time Step Size       = 0.001
            Predictor-Corrector Tolerance = 1e-3
            Minimum Time Step Size       = 1e-6
        End
    End

End

.
.
.

```

It is worth pointing out that for each named "Begin Transient" command block there should be a corresponding named "Begin Parameters for Transient" command block. This correlation establishes the mapping between a time block and its associated parameters. The intent of time block parameters is often misunderstood thus it is worth describing some of the underlying detail how the parameters are used.

16.2. INITIAL TIME STEP ESTIMATION FOR THERMAL PROBLEMS

The analysis of a transient diffusion problem requires the selection of a suitable time step for the integration procedure. This process can be automated with the time step being adaptively selected to preserve a specified time truncation error. Aria provides an adaptive time-stepping functionality, as described in Section 16.4. However, the time step selection process is not self-starting and some initial estimate of an appropriate time step is still required. In the following the discussion is primarily limited to implicit integration methods, since these methods are usually the methods of choice for most conduction models.

The selection of too *large* an initial time step can result in the loss of temporal accuracy in the solution and produce a nonphysical oscillatory response. Likewise, an inappropriately *small* initial time step may produce nonphysical, spatial oscillations in the early time temperature field due to the limited resolution ability (of temperature gradients) of the finite element mesh. Either of these difficulties may lead to stability problems if the boundary value problem is nonlinear. In any event, the solution during the oscillatory period is not accurate and these occurrences are to be avoided. A method for estimating an appropriate initial time step is outlined below. This procedure is originally due to Levi ([25]) though it has been discussed by several other authors ([26, 27, 28]).

In the following development, it is assumed that a finite element mesh has been constructed that will adequately model the thermal phenomena of interest (e.g., thermal shock problems will require a fine mesh near a boundary while slower thermal transient will be less demanding on mesh refinement). For a given spatial discretization, a local characteristic length, Δx , is chosen based on element size. Typically, this characteristic length is measured normal to a boundary on which a temperature or heat flux (source) disturbance occurs. Based on the characteristic length, the local heat transfer coefficient, h , and the local thermal conductivity, k , a local element Biot number ($Bi = h\Delta x/k$) can be computed. Note that for a prescribed temperature, heat flux or heat source boundary condition, the heat transfer coefficient, h , is assumed to be large leading to a large Biot number.

In order to bound the thermal gradient that will occur at the boundary in the first time step, the ratio of the temperature at a distance Δx (characteristic length) from the boundary to the temperature on the boundary is selected. Let this ratio be defined by $\Theta = T(\Delta x)/T_{surface}$. Typical values of Θ will range from 0.10 to 0.25. With the estimated values for local Biot number and temperature ratio Θ , a local Fourier number ($Fo = \alpha \Delta t / \Delta x^2$) may be found from the charts in Figures 16.2-2 and 16.2-3. These graphs are based on an analytic solution for one-dimensional conduction with a convective boundary condition ([29]). A value of the local Fourier number and values for the characteristic length and thermal diffusivity, α , then allow a time step to be computed.

As an example of the procedure outlined above consider the transient problem described in the following example:

Consider the transient thermal response of a finned tube radiator, as shown in Figure 16.2-1(a). Thermal properties for the radiator are as follows: $\rho = 2.7071 \times 10^3 \text{ kg/m}^3$, $C = 870.854 \text{ J/kg}\cdot\text{K}$, $k = 207.566 \text{ W/m}\cdot\text{K}$, and $\alpha = 8.806 \times 10^{-5} \text{ m}^2/\text{s}$. The characteristic size is based in the average size of the elements along the radiator fin, as shown in Figure 16.2-1(b), and is equal to $\Delta x = 3.175 \times 10^{-3} \text{ m}$. The boundary condition is an applied heat flux, so the Biot number is assumed large (infinite). Using a temperature ratio of $\Theta = 0.10$, then Figure 16.2-2 yields a Fourier number of $Fo \approx 0.20$. Thus,

$$\Delta t = \frac{(Fo)(\Delta x^2)}{(\alpha)} = \frac{(0.20)(3.175 \times 10^{-3})^2}{(8.806 \times 10^{-5})} = 0.023 \text{ seconds.} \quad (16.1)$$




Figure 16.2-1.. Geometry and mesh of finned radiator problem. Dimensions are in inches.




Figure 16.2-2.. Temperature ratio versus Fourier number for various Biot numbers.

The above procedure can also be used to estimate the overall response time for a region. In this case the length scale is a characteristic length for the entire region and the temperature ratio should be order unity. The Fourier number will then produce the approximate time interval required to reach equilibrium.

16.3. FIXED TIME STEP SELECTION

Since Aria supports both adaptive and fixed time stepping it follows that this behavior be explicitly called out in the input file. For any given time block fixed time stepping is invoked via the combination of:

TIME STEP VARIATION = FIXED

INITIAL TIME STEP SIZE = *value*

PREDICTOR ORDER = 0

command lines within the Parameters for Transient command block. These command lines are further described in the adaptive time step selection section [16.4](#). Note that omission of the PREDICTOR ORDER = 0 command line for fixed time stepping will result in a default predictor error criteria to be




Figure 16.2-3.. Temperature ratio versus Fourier number for various Biot numbers.

considered in time step selection and may lead to unexpected results for presumed fixed time stepping scheme.

16.4. ADAPTIVE TIME STEP SELECTION

Time step failure in Aria is defined as a Newton solution step that has not converged when the solution time was advanced. Aria time step selection is carried out by first addressing possible time step failures and then applying the type of time stepping requested, fixed or adaptive. If adaptive time stepping is requested then a number of criteria can be considered when selecting the next time step with a primary objective of controlling solution error. Optimistically, use of the adaptive time step selection will result in a converged Newton step solution satisfying a user specified solution error tolerance and the solution time can again be advanced. Additional adaptive time stepping criteria are considered secondary relative to the error based criteria.

Foundationally, error based adaptive time stepping is based upon a solution error obtained using a predicted solution obtained from successful solves. Thus the time integration method often dictates how many solution steps into a simulation adaptive time stepping can begin. In most cases one must be able to obtain at least two successive solves using a fixed initial time step before adaptive time stepping

begins. In many fluid simulations one routinely increases this number of constant steps to three or four using the PREDICTOR-CORRECTOR BEGIN AFTER STEP command line.

Certain model features like chemistry 36.2 will require that the phenomenological behavior within the current time step be considered when advancing the time step. We note that when adaptive time step selection is used, the subcycled chemistry timestep cannot be included directly in the adaptive time step selection as the chemistry time step will seldom satisfy the MINIMUM TIME STEP SIZE RATIO criteria 16.4.2.4. Here the minimum subcycled chemistry time step is modified to be comparable with other adaptive time step criteria 36.5. Additionally, the adaptive time step selection can also be overridden by user requests for output to occur at specific times.

One of the quantities used in the selection of time steps is the time step size ratio $r = \Delta t_{new} / \Delta t_{old}$, the ratio of a proposed (new) time step to the current (old) time step. Experience tells us that for a first and second order integrator bounding the time step size ratio, $0.5 \leq r \leq 2.0$. While maintaining these bounds usually minimizes the time truncation error, a user is permitted to manually alter these bounds. For the BDF2 integrator the suggested theoretical bounds are $0.5 \leq r \leq 2.14$, where the upper bound is strictly enforced to ensure stability of the integrator. The approach used in Aria to control time stepping strictly relevant to physical phenomena such as phase change is to artificially modify r via a Phase Change Relaxation Factor.

16.4.1. Time Step Failure

Aria transient simulations are monitored for time step failure. For each solution time step we expect that the the specified nonlinear tolerance will be achieved in the specified number of nonlinear iterations within a Newton step. If the convergence condition is not met the time step is said to have "Failed" and solution time will not be allowed to advance unless the user has explicitly stated that failed time steps will be accepted with the (ACCEPT SOLUTION AFTER MAXIMUM NONLINEAR ITERATIONS = TRUE) command line. If the non-converged solution is not accepted, a failed time step counter is incremented, the time step is reduced by a factor determined using the *time step size ratio*. Similarly, when using adaptive time stepping the *time step size ratio* is also used to define upper bounds on the adaptive time step when the solution step is converged.

When using adaptive time stepping, a time step size ratio r is used to compute a new time step Δt_{n+1} based upon the evaluation

$$r = \frac{\Delta t_{n+1}}{\Delta t_n}$$

where Δt_{n+1} is the minimum time step provided from the adaptive time step selection process 16.4.2 and Δt_n is the timestep in the current time step. When a time step fails the step will be repeated using a value defined using a FAILED TIME STEP SIZE RATIO (default 0.5) and the Newton step will be retried with the revised time step

$$\Delta t_{n+1} = r \Delta t_n .$$

This process of updating Δt_{n+1} will be repeated until either a convergence condition is reached (convergence is achieved) or when the trial time step satisfies the FAIL TIME STEP WHEN TIME STEP SIZE RATIO IS BELOW criteria is reached (no convergence). In the former case the time step is advanced and in the latter case the simulation will be terminated.

During phase change, the model using the energy equation for temperature employs a mushy zone formulation hence it is important that the the temperature field values not bypass the range of the mushy zone so that the heat of fusion be accounted for. In this case an additional algorithm is used to detect when a nodal temperature has bypassed the mushy zone. When the mushy zone has been bypassed within a timestep, the Newton step will be marked as failed and the current time step will be scaled by a user specified PHASE CHANGE RELAXATION FACTOR in the same way that the failed time step size ratio is applied.

In some simulations a user may wish to interrupt the Newton step (fail the step) based upon the residual behavior. For many problems an aberrant behavior is recognized early on by noting the ratio of the current residual to the first residual. In cases where this ratio continues to grow it may be appropriate to terminate the Newton step and re-try with a different time step. This ratio can be specified by the user with the MAXIMUM LINEAR RESIDUAL RATIO.

16.4.2. Adaptive Time Step Selection

Adaptive time step selection consists of applying different criteria in the selection process. Each of the criteria are first described before linking them to the final selection procedure [16.4.3](#)

16.4.2.1. Predictor Corrector

Let the predictor corrector tolerance, ϵ , be specified from the input file.

$$\frac{\Delta t_{n+1}}{\Delta t_n} = \left(b \frac{\epsilon}{d_{n+1}} \right)^m$$

For 1st order time integrator $m = 1/2$, $b = 2.0$. For 2nd order time integrator $m = 1/3$

$$b = 3 \left(1 + \frac{\Delta t_{n-1}}{\Delta t_n} \right)$$

$$d_{n+1} = \frac{1}{U_{max}} \left[\sum_{i=1}^N \left(U_{i(n+1)} - U_{i(n+1)}^p \right)^2 \right]^{1/2}$$

so that the timestep based on predictor criteria is

$$\Delta t^{Pred} = \Delta t_{n+1} = \Delta t_n \left(b \frac{\epsilon}{d_{n+1}} \right)^m .$$

16.4.2.2. *Max_CFL*

In some instances the stability of a flow simulation can be governed by a Courant-Freidrichs-Levy (CFL) number, CFL_{max} for the flow. If a user specifies that a CFL number be carried out over the model then a candidate time step can be computed as $\Delta t_{maxCFL} = CFL_{lim} \Delta t_n / CFL_{max}$, where CFL_{lim} is provided using the COURANT LIMIT command line. The CFL criteria possibly considered for Δt are

Δt_{maxCFL} standard fluid

Δt_{maxCFL} standard fluid phase A

Δt_{maxCFL} standard fluid phase B

Δt_{maxCFL} standard fluid phase C

Δt_{maxCFL} level set.

16.4.2.3. *Minimum Timestep Based Upon MAXIMUM TIME STEP SIZE RATIO*

A time step size ratio involving the future time step and the current time step is $r = \Delta t_{n+1} / \Delta t_n$. Letting r_{max} be the user specified maximum time step size ratio then the largest timestep achievable with r_{max} is $\Delta t = \Delta t_n * r_{max}$.

16.4.2.4. *Minimum Timestep Based Upon MINIMUM ACCEPTABLE TIME STEP SIZE RATIO*

A time step size ratio involving the adaptive time step and the current time step is $r = \Delta t_a / \Delta t_n$. Letting r_{min} be the user specified minimum acceptable time step size ratio then we require that $r > r_{min}$ else the time step is considered to be failed, the proposed time step is too small.

16.4.2.5. *Maximum Solution Increment*

Let the user specified maximum increment in any solution DOF be $(\Delta U)_{Max}$. From a previous successful solution we compute the maximum change in any DOF $(\Delta U)_{MaxSoln}$ and use it to compute an estimate of its corresponding maximum derivative in the previous time step as $\dot{U}_{max} = (\Delta U)_{MaxSoln} / \Delta t_n$. For a new time step $\hat{t}_n$ we might expect that the maximum value of U in the next step might reach $(\Delta \hat{U})_{max} = \hat{t}_n \dot{U}_{max}$. Now if $(\Delta \hat{U})_{max} < (\Delta U)_{Max}$ we retain $\hat{t}_n$ otherwise we propose a new time step $\Delta t_n = 0.95 * (\Delta U)_{Max} / \dot{U}_{max}$ with the hope that the solution increment $(\Delta U)_{Max}$ will not be exceeded in the next time plane. The same process is repeated for all solution DOF to produce a representative Δt_n for the given problem. Although adaptive time stepping with Solution Increment requires at least one successful solve here we require at least two successful solves since control of solution error is the primary objective.

16.4.3. Calculate Adaptive Timestep

We now proceed to select an adaptive time step t_a based upon the minimum value associated with:

- Δt^{Pred} [16.4.2.1](#)
- Courant Limit, Δt_{cfl} [16.4.2.2](#)
- Maximum Time Step Size, Δt_{max}
- Maximum Time Step Size Ratio, r_{max} [16.4.2.3](#)
- Maximum Solution Increment [16.4.2.5](#)
- Minimum Time Step Size
- Note: If chemistry is present, it will take precedence over all other candidates above

Let n_{tb} be the timeblock counter (step within the current timeblock).

Let n_{Pred0} be the user specified number of constant steps that begin any timeblock (default minimum is 2).

Let the current timestep be Δt_n (INITIAL TIME STEP SIZE when starting a simulation), the adaptive timestep be $\Delta t_a = \text{Real\_Max}$, and predictor corrector timestep be $\Delta t^{Pred} = \text{Real\_Max}$.

Let Δt_{max} be the user specified MAXIMUM TIME STEP SIZE and Δt_{min} the MINIMUM RESOLVED TIMESTEP SIZE.

To begin the timestep selection we first compute the desired predictor corrector timestep $\hat{\Delta t}^{Pred}$ ([16.4.2.1](#)) with the understanding that we wish to obtain a nominal value Δt^{Pred} which may not be the same as $\hat{\Delta t}^{Pred}$.

```

if  $n_{tb} < n_{Pred0}$ 
    compute predictor error
     $\Delta t^{Pred} = \Delta t_n$ 
else
    if  $\hat{\Delta t}^{Pred} < \Delta t_{min}$  then
        if  $\Delta t_n > \Delta t_{min}$  then
             $\Delta t^{Pred} = \Delta t_{min}$ 
        else
            if  $\hat{\Delta t}^{Pred} < \Delta t_n$  then
                 $\Delta t^{Pred} = \Delta t_n$ 
            else
                 $\Delta t^{Pred} = \hat{\Delta t}^{Pred}$ 
    else
         $\Delta t^{Pred} = \hat{\Delta t}^{Pred}$ 

```

Finally, the candidate t_a value must then satisfy the MINIMUM ACCEPTABLE TIME STEP SIZE RATIO, r_{min} , [16.4.2.4](#) to be accepted as a viable time step.

The overall time stepping procedure is demonstrated in the figure below [16.4-1](#).




Figure 16.4-1.. Time Step Selection Schematic.

Time integration is currently defined in the same way for the various physics contained within Aria. The command lines used to specify parameters used in that definition are described in what follows.

16.4.4. Debugging Adaptive Time Step Failure

Debugging of time step failure involves straightforward interpretation of the log file output. The debugging process is best illustrated with an example of adaptive timestepping failure with the corresponding log file output which follows. Here the MINIMUM TIME STEP SIZE RATIO defaults to 0.5 and the previous timestep is $\Delta t_n = 2.84\text{E-}01$. After convergence of the solution the adaptive time step criteria are applied to obtain candidate time steps for the next time step. The minimum candidate time step is selected from those criteria hence $\Delta t_{n+1} = 3.661\text{E-}02$ based upon the Predictor-Corrector Tolerance.

Using the Adaptive time stepping result the current time step size ratio is

$$r = \frac{3.661\text{E-}02}{2.84\text{E-}01} = 0.129 < 0.5 .$$

Since the current time step size ratio is less than the minimum time step ratio (0.5) the step cannot be advanced and the time step will be retried using a time step corresponding to the MINIMUM TIME

STEP SIZE RATIO.

$$\Delta t_{n+1} = r \Delta t_n = (0.5)(2.84E-01) = 1.42E-01$$

If one expects that time step should be reduced as solution time increases one may opt to abandon the default MINIMUM TIME STEP SIZE RATIO and set it to an appropriate lower value in the input file.

Note that failure of a time step due owing to violation of time step size ratio is an artifact of the adaptive time stepping selection criteria. Hence one should consider whether any of the selection criteria values can be modified by settings in the time step parameters command block.

```
----- For equation system name: main -----
Global predictor error = 5.301e-05
Time step selection: dt <= 3.661e-02 (based on Predictor-Corrector Tolerance).
Time step selection: dt <= 2.839e+00 (based on Maximum Time Step Size Ratio).
Time step selection: dt <= 1.000e+03 (based on Maximum Time Step Size).
Time step selection: dt = 2.512e+00 (Minimum Chemistry timestep block_284).
Time step selection: dt = 3.661e-02 (Adaptive time stepping result).
Region::execute() time for my_region: 1.300e-02 sec.
Transient TimeBlock failed, step 284, time 3.0000e+01, time step 2.8394e-01
ERROR: Adaptive time stepping result yields a time step size ratio = 0.129
       which is less than the specified Minimum Time Step Size Ratio 0.5.
       Retrying step with a time step corresponding to time step size ratio of 0.5
```

In the approach shown, time step reduction is based upon relative change of the time step. Unfortunately, in problems where the adaptive time step drops dramatically at some point in the simulation the criteria previously described may cause the time step to fail repeatedly before the simulation step finally advances thus increasing the overall simulation time. In this case one can instead specify a lower bound on time step size ratio using the FAIL TIME STEP WHEN TIME STEP SIZE RATIO IS BELOW directive. Since the adaptive time stepping result is 0.129 then applying this approach to the example shown one could use

```
FAIL TIME STEP WHEN TIME STEP SIZE RATIO IS BELOW 0.1
```

to obtain more reasonable behavior.

16.5. PARAMETERS FOR ARIA REGION

Scope: Parameters For

```
Begin Parameters For Aria Region RegionName

Allow Order Switch For HowMany Steps

Courant Limit {=|are|is} Courant_limit

Fail Time Step On Bad Aztec Solver Status

Fail Time Step When Time Step Size Ratio Is Below Ratio
```

Failed Time Step Size Ratio {=|are|is} *Ratio*

Initial Nonlinear Residual Tolerance For Time Step Control {=|are|is} *tolerance*

Initial Time Step Size {=|are|is} *Dt*

Interface Courant Limit {=|are|is} *Interface Courant_limit*

Known Time Discontinuities {=|are|is} *times...*

Limit Solution Increment *Field_name* {=|are|is} *Value* [*Action*]

Maximum Acceptable Linear Residual Ratio {=|are|is} *Ratio*

Maximum Consecutive Time Step Failures {=|are|is} *NumFails*

Maximum Global Var Limit *Encore_name* {=|are|is} *Value* [*Action*]

Maximum Linear Residual Ratio {=|are|is} *Ratio*

Maximum Solution Limit *Field_name* {=|are|is} *Value* [*Action*]

Maximum Time Step Size {=|are|is} *Dt*

Maximum Time Step Size Ratio {=|are|is} *Ratio*

Minimum Global Var Limit *Encore_name* {=|are|is} *Value* [*Action*]

Minimum Resolved Time Step Size {=|are|is} *Dt*

Minimum Solution Limit *Field_name* {=|are|is} *Value* [*Action*]

Minimum Time Step Size {=|are|is} *Dt*

Predictor Order {=|are|is} *order*

Predictor-Corrector Begin After Step {=|are|is} *Step*

Predictor-Corrector Field Normalization {@|at|for|in|on|over} *Field_name* {=|are|is} *Norm_type* [*Scaling*]

Predictor-Corrector Normalization {=|are|is} *Normalization* [*Scaling*]

Predictor-Corrector Tolerance {=|are|is} *Predictor_corrector_tolerance*

Reset Initial Time Step Size

Slope Of Time Step Size {=|are|is} *slope*

Stop When Initial Nonlinear Residual Is Below *Tol*

Time Integration Method {=|are|is} *Time_integration_method*

Time Step Variation {=|are|is} *Time_step_variation*

Use Initial Nonlinear Residual For Time Step Control {=|are|is}
enable

End

Summary Defines region specific time stepping data

16.5.1. Allow Order Switch For

Scope: Parameters For Aria Region

Allow Order Switch For *HowMany* Steps

Parameter	Value	Default
<i>HowMany</i>	integer	undefined

Summary Allow the switching of time integration order from a higher order to first order.

Description This command allows for the switching of a higher order method to a first order method for a specified number of steps in order to improve the robustness of the simulation especially in the region of discontinuities such as chemistry shutoff. This command is mostly useful in the context of a SECOND_ORDER time integration method.

16.5.2. Courant Limit

Scope: Parameters For Aria Region

Courant Limit {=|are|is} *Courant_limit*

Parameter	Value	Default
<i>Courant_limit</i>	real	0.0

Summary The Courant Number limit. A value of 0.0 denotes INACTIVE.

16.5.3. Fail Time Step On Bad Aztec Solver Status

Scope: Parameters For Aria Region

Summary OPT to fail time the time step when the AZTEC solver status is -2 (Numerical Breakdown) or -3 (Loss of Precision).

16.5.4. Fail Time Step When Time Step Size Ratio Is Below

Scope: Parameters For Aria Region

Fail Time Step When Time Step Size Ratio Is Below *Ratio*

Parameter	Value	Default
<i>Ratio</i>	real	undefined

Summary Specify lower bound for adaptive time step size ratio failure criteria.

If the adaptive time step size ratio falls below this value, Aria will fail the time step. This criteria is specified in terms of the size of the time step size ratio, defined as dt_{n+1}/dt_n . When the adaptive time stepper senses the time step being cut back too much, the time step fails. The default is equal to the FAILED TIME STEP SIZE RATIO.

In simulations where the predicted time step is reduced substantially, a time step may fail repeatedly on this criterion. In that event the user may want to set this Ratio to a small positive value, possibly even zero.

16.5.5. Failed Time Step Size Ratio

Scope: Parameters For Aria Region

Failed Time Step Size Ratio {=|are|is} *Ratio*

Parameter	Value	Default
<i>Ratio</i>	real	0.5

Summary Specifies the factor used to cut the time step size when a step fails.

When a time step fails, the time step size is reduced by this factor.

16.5.6. Initial Nonlinear Residual Tolerance For Time Step Control

Scope: Parameters For Aria Region

Initial Nonlinear Residual Tolerance For Time Step Control {=|are|is} *tolerance*

Parameter	Value	Default
<i>tolerance</i>	real	1.0

Summary Set initial nonlinear residual tolerance for time step control.

Description Sets the tolerance on the initial nonlinear residual to be used for time step control.

16.5.7. Initial Time Step Size

Scope: Parameters For Aria Region

Initial Time Step Size $\{=|are|is\}$ Dt

Parameter	Value	Default
Dt	real	undefined

Summary Specifies the initial time step size for the given parameter block.

The initial time step size should always be specified for FIXED time stepping and for the starting time block of ADAPTIVE time stepping. When no other command lines affecting timestep are provided in the time step parameter block the time step will remain constant over the time extent of the parameter block.

16.5.8. Interface Courant Limit

Scope: Parameters For Aria Region

Interface Courant Limit $\{=|are|is\}$ *Interface Courant_limit*

Parameter	Value	Default
<i>Interface Courant_limit</i>	real	0.0

Summary The Interface Courant Number limit. Applies to both diffuse level set and CDFEM problems. A value of 0.0 denotes INACTIVE.

16.5.9. Known Time Discontinuities

Scope: Parameters For Aria Region

Known Time Discontinuities $\{=|are|is\}$ *times...*

Parameter	Value	Default
<i>times</i>	real...	undefined

Summary Specifies known time discontinuities in the solution that the adaptive time stepping procedure must capture.

Description Allows user to specify certain times that the adaptive time stepper must solve at because the solution is known to have a discontinuity there. This is useful for problems where the boundary conditions change suddenly for example.

16.5.10. Limit Solution Increment

Scope: Parameters For Aria Region

Limit Solution Increment *Field_name* {=|are|is} *Value* [*Action*]

Parameter	Value	Default
<i>Field_name</i>	string	undefined
<i>Value</i>	real	REAL_MAX

Summary Provides user control for limiting maximum change in a chosen solution Field over a timestep. When action is PREDICT a time step estimation is computed based upon the predicted solution change. When action is FAIL_STEP the time step is still predicted but the the time step will also fail if the suggested solution increment is exceeded.

Description This command allows one to roughly specify the maximum magnitude that a solution Field can change within a step. A solution increment is estimated based upon the maximum change in the Field in the previous timestep and the proposed adaptive timestep. When the specified value of maximum solution increment is exceeded, the proposed adaptive timestep is reduced in an attempt to limit the solution increment.

One command line should be supplied for each solution Field one wishes to restrict. The restriction is applied directly to the solution Field values, no scaling is invoked.

16.5.11. Maximum Acceptable Linear Residual Ratio

Scope: Parameters For Aria Region

Maximum Acceptable Linear Residual Ratio {=|are|is} *Ratio*

Parameter	Value	Default
<i>Ratio</i>	real	undefined

Summary Specifies a failure criterion for a nonlinear step based on the ratio of the final linear residual to a nonlinear residual.

The ratio must be greater than zero and less than one.

16.5.12. Maximum Consecutive Time Step Failures

Scope: Parameters For Aria Region

Maximum Consecutive Time Step Failures {=|are|is} *NumFails*

Parameter	Value	Default
<i>NumFails</i>	integer	20

Summary Specifies a maximum consecutive of time step failures before a simulation is terminated. This prevents the application from continued cutback of the time step when recovery of the solution is unlikely.

16.5.13. Maximum Global Var Limit

Scope: Parameters For Aria Region

Maximum Global Var Limit *Encore_name* {=|are|is} *Value* [*Action*]

Parameter	Value	Default
<i>Encore_name</i>	string	undefined
<i>Value</i>	real	undefined

Summary This command allows the simulation to continue only when the given Encore variable is lower than a certain magnitude. Inclusion of the optional argument RETRY will cause the solution step to fail and the time step to be reduced. This sequence will be carried out a maximum of three steps, after which the simulation will be terminated.

Description This command allows the simulation to continue only when the given Encore variable is lower than a certain magnitude.

16.5.14. Maximum Linear Residual Ratio

Scope: Parameters For Aria Region

Maximum Linear Residual Ratio {=|are|is} *Ratio*

Parameter	Value	Default
<i>Ratio</i>	real	undefined

Summary Specifies a failure criterion for a nonlinear step based on the ratio of a nonlinear residual to the initial nonlinear residual.

NOTE: The linear residual is not utilized with this check.

This criteria is not be used unless requested by the user.

16.5.15. Maximum Solution Limit

Scope: Parameters For Aria Region

Maximum Solution Limit *Field_name* {=|are|is} *Value* [*Action*]

Parameter	Value	Default
<i>Field_name</i>	string	undefined
<i>Value</i>	real	REAL_MAX

Summary Provides user control for limiting maximum value of a Field solution over a time step. Optional parameters are continue or terminate. When a step fails the step will be cut back and and the optional behavior is invoked when three consecutive fails have occurred. Default behavior is to terminate.

Description This command allows one to restrict the maximum magnitude that a solution Field can achieve within a simulation by causing the time step to fail when the Field value exceeds a user specified magnitude.

Oftentimes the maximum value will be tied to an event that occurs at a particular magnitude of the Field. This command can be used to impose a different solution behavior when this magnitude of the Field is realized by forcing a failure of the solution step. When the step is failed due to solution limit then cutback of the time step is allowed to occur for two consecutive steps. If the time step is cut back a third time in succession, the specified action of the command will be invoked.

By default the simulation will terminate when the maximum value is reached. If the optional argument is "continue" then time step failure will be over-ridden and the solution sequence will continue, presumably evolving toward lower magnitude values of the Field. This behavior may enable one to overcome large reductions in time step at discontinuous events which may occur for maximum values of the Field.

16.5.16. Maximum Time Step Size

Scope: Parameters For Aria Region

Maximum Time Step Size {=|are|is} *Dt*

Parameter	Value	Default
<i>Dt</i>	real	REAL_MAX

Summary Specifies the maximum time step size for this parameter block.

The time step will not be allowed to exceed this value, regardless of adaptive time step selection and regardless of time step requests for other regions (for loosely coupled simulations).

16.5.17. Maximum Time Step Size Ratio

Scope: Parameters For Aria Region

Maximum Time Step Size Ratio {=|are|is} *Ratio*

Parameter	Value	Default
<i>Ratio</i>	real	2.0/2.4

Summary Specifies the maximum allowable growth rate of the adaptive time step size.

If the time step selection computes a new time step size that exceeds the previous step size by more than this amount, then the new step size is limited to the product of this factor and the previous step size.

The default is 2.0 for FIRST_ORDER and SECOND_ORDER integration methods.

For BDF2 a value of 2.4 is imposed to enforce stability of the integrator.

16.5.18. Minimum Global Var Limit

Scope: Parameters For Aria Region

Minimum Global Var Limit *Encore_name* {=|are|is} *Value* [*Action*]

Parameter	Value	Default
<i>Encore_name</i>	string	undefined
<i>Value</i>	real	undefined

Summary This command allows the simulation to continue only when the given Encore variable is higher than a certain magnitude. Inclusion of the optional argument, RETRY, will cause the solution step to fail and the time step to be reduced. This sequence will be carried out a maximum of three steps, after which the simulation will be terminated.

Description This command allows the simulation to continue only when the given Encore variable is higher than a certain magnitude.

16.5.19. Minimum Resolved Time Step Size

Scope: Parameters For Aria Region

Minimum Resolved Time Step Size {=|are|is} *Dt*

Parameter	Value	Default
<i>Dt</i>	real	0.0

Summary Specifies the minimum resolved time step size. If the time step size lies below this value, the step will not fail when the time step size ratio falls too low.

This setting serves as a floor value since the adaptive time stepper will not select a time step size below this value, and any predictor-corrector errors are neglected when the time step size falls below this value.

16.5.20. Minimum Solution Limit

Scope: Parameters For Aria Region

Minimum Solution Limit *Field_name* {=|are|is} *Value* [*Action*]

Parameter	Value	Default
<i>Field_name</i>	string	undefined
<i>Value</i>	real	undefined

Summary Provides user control for limiting minimum value of a Field solution over a time step. Optional parameters are continue or terminate. When a step fails the step will be cut back and the optional behavior is invoked when three consecutive fails have occurred. Default behavior is to terminate.

Description By default the solution minimum limit for all Fields is not active. This command allows one to restrict the minimum magnitude that a solution Field can achieve within a simulation by causing the time step to fail when the Field value goes below a user specified value

See MAXIMUM SOLUTION LIMIT command for more info.

16.5.21. Minimum Time Step Size

Scope: Parameters For Aria Region

Minimum Time Step Size {=|are|is} *Dt*

Parameter	Value	Default
<i>Dt</i>	real	1.0e-16

Summary Specifies the minimum time step size for the given parameter block. The time step will not be allowed to fall below this value, regardless of adaptive time step selection and regardless of time step requests from other regions (for loosely coupled simulations).

16.5.22. Predictor Order

Scope: Parameters For Aria Region

Predictor Order {=|are|is} *order*

Parameter	Value	Default
<i>order</i>	integer	undefined

Summary Specifies the order of the extrapolation used to predict the solution in transient simulations. An order of 0 corresponds to no extrapolation, instead copying the previous solution into the predicted solution.

Description This command sets the order of extrapolation in the predictor for transient problems. A value of 0 basically turns off the extrapolation, and instead copies to old solution to the predicted solution.

The PREDICTOR ORDER defaults to 0 for problems if Gas Dynamics equations are defined. Otherwise, it is set to the order of the time integrator for the current time block i.e 1 for first order and 2 for second order

16.5.23. Predictor-Corrector Begin After Step

Scope: Parameters For Aria Region

Predictor-Corrector Begin After Step {=|are|is} *Step*

Parameter	Value	Default
<i>Step</i>	integer	2 / 3

Summary Specifies after which solution step the Predictor-Corrector timestep calculation will begin to be used in computing an adaptive timestep. Predictor error will always be computed but will not actually be used until the prescribed step is reached.

Default value is 2 for first-order time integration and 3 for second-order time integration. Thus for first-order time integration, a candidate predictor-corrector timestep could appear in step 3.

16.5.24. Predictor-Corrector Field Normalization

Scope: Parameters For Aria Region

Predictor-Corrector Field Normalization {@|at|for|in|on|over} *Field_name*
{=|are|is} *Norm_type* [*Scaling*]

Parameter	Value	Default
<i>Field_name</i>	string	undefined
<i>Norm_type</i>	{courant max mesh none user}	MAX

Summary Allows user to change the predictor-corrector normalization type for a given field variable separately from the global option.

Description Allows user to change the predictor-corrector normalization type for a given field variable separately from the global option.

Normalization types are:

- NONE: Scale by unity
- MAX (default): Scale by the maximum field value
- USER: Scale by a constant (user-supplied) value

16.5.25. Predictor-Corrector Normalization

Scope: Parameters For Aria Region

Predictor-Corrector Normalization {=|are|is} *Normalization* [*Scaling*]

Parameter	Value	Default
<i>Normalization</i>	{courant max mesh none user}	MAX

Summary Provides the ability to specify how the predictor-corrector error is normalized.

Currently supported values are MAX, NONE, and USER. If desired, L2 could be added easily. A possibly better method would be to allow user-specified scales for the variables but that's not yet supported.

The reason for allowing NONE (or even better, a user-specified scale) is to better handle problems that involve something that is zero-based with finite changes. This can happen in ALE problems where the adaptive time stepper is overly restrictive initially when the displacements are all nearly zero, but growing to some finite value.

Default is MAX.

16.5.26. Predictor-Corrector Tolerance

Scope: Parameters For Aria Region

Predictor-Corrector Tolerance {=|are|is} *Predictor_corrector_tolerance*

Parameter	Value	Default
<i>Predictor_corrector_tolerance</i>	real	0.001

Summary Specifies the tolerance for the difference between the predicted solution and the implicitly solved corrector solution used in adaptive time step selection.

The adaptive time step selection formula is

$$\Delta t_{n+1} = \Delta t_n \left(b \frac{\epsilon}{d_{n+1}} \right)^m \quad (16.2)$$

where $\Delta t_n \equiv t_{n+1} - t_n$ is the time step size from the most recent solution, $\Delta t_{n+1} \equiv t_{n+2} - t_{n+1}$ is the new time step size, ϵ is the predictor-corrector tolerance and d_{n+1} is the norm of the difference between the predicted and actual solutions at time t_{n+1} . For first order time integration $m = 1/2$ and $b = 2$. For second order time integration $m = 1/3$ and $b = 3(1 + \Delta t_{n-1}/\Delta t_n)$. See [30].

16.5.27. Reset Initial Time Step Size

Scope: Parameters For Aria Region

Summary Enforce use of initial time step size specification.

Description When using adaptive time stepping with restart the initial time step size is taken from the restart file rather than the INITIAL TIME STEP SIZE specification. This choice of time step can be problematic if one wishes to change model features at the beginning of a restart. This command forces the time step selection to respect an initial time step size specification.

16.5.28. Slope Of Time Step Size

Scope: Parameters For Aria Region

Slope Of Time Step Size {=|are|is} *slope*

Parameter	Value	Default
<i>slope</i>	real	undefined

Summary Specifies the linear growth rate of the time step size for the given parameter block. The time step size will grow by this amount at each step unless limited by other factors.

16.5.29. Stop When Initial Nonlinear Residual Is Below

Scope: Parameters For Aria Region

Stop When Initial Nonlinear Residual Is Below *Tol*

Parameter	Value	Default
<i>Tol</i>	real	undefined

Summary Specify time block termination criteria based upon nonlinear residual value. If the initial nonlinear residual falls below this value, Aria will end the time block. This is useful for obtaining pseudo-transient solutions of steady-state problems.

16.5.30. Time Integration Method

Scope: Parameters For Aria Region

Time Integration Method {=|are|is} *Time_integration_method*

Parameter	Value	Default
<i>Time_integration_method</i>	{average_acceleration backward_euler bdf2 first_order midpoint_rule second_order}	undefined

Summary Specifies the order of time integration.

Valid options are BACKWARD_EULER, FIRST_ORDER, SECOND_ORDER, BDF2, MIDPOINT_RULE and AVERAGE_ACCELERATION.

Note that the stability criteria of BDF2 will restrict the timestep growth by imposing a MAXIMUM TIME STEP SIZE RATIO of 2.14.

16.5.31. Time Step Variation

Scope: Parameters For Aria Region

Time Step Variation {=|are|is} *Time_step_variation*

Parameter	Value	Default
<i>Time_step_variation</i>	{adaptive fixed}	undefined

Summary Specifies how the time step sizes are to be derived. Choose between FIXED and ADAPTIVE time step selection methods.

When the time step is ADAPTIVE the time step is determined using a predictor-corrector error criteria.

16.5.32. Use Initial Nonlinear Residual For Time Step Control

Scope: Parameters For Aria Region

Use Initial Nonlinear Residual For Time Step Control {=|are|is} *enable*

Parameter	Value	Default
<i>enable</i>	{false true}	undefined

Summary Enable use of initial nonlinear residual as an error estimate to control timestep for loosely coupled problems.

Description When enabled this option will treat the initial non-linear residual as a proxy for the error in region-region convergence for loosely coupled problems. The time step will be controlled using a predictor-corrector like algorithm.

16.6. OTHER TIMESTEP RELATED COMMANDS

Because Aria can solve for many solution Fields it is inappropriate to include Field specific commands within the time block parameters. Because interaction of time stepping with particular simulation physics is often required, these interactions are handled via command lines appearing at the Region scope as illustrated below.

```
.  
.   
.   
Begin Procedure My_Aria_Procedure  
  
    Begin Solution Control Description  
        .  
        time stepping related commands  
        .  
    End  
    .  
    .  
    Begin Aria Region My_Region  
        .  
        .  
        other physics timestep related commands  
        .  
        .  
    End  
  
End  
.  
.
```

16.6.1. Phase Change Relaxation Factor

Scope:

Phase Change Relaxation Factor {=|are|is} *Prf*

Parameter	Value	Default
<i>Prf</i>	real	0.5

Summary In versions > 4.52 this command has no effect. It was previously used with the deprecated "USE_PHASE_CHANGE" model for specific heat and is now only left for backwards compatibility.

16.7. PREDICTOR RELATED COMMANDS

Because Aria can solve for many solution Fields it is inappropriate to include Field specific commands within the time block parameters. Nevertheless, since interaction of time stepping with solution prediction is required, these interactions are handled via command lines appearing at the Region scope as illustrated below.

```
.  
.   
.   
Begin Procedure My_Aria_Procedure  
  
    Begin Solution Control Description  
        .  
        time stepping related commands  
        .  
    End  
    .  
    .  
    Begin Aria Region My_Region  
        .  
        .  
        predictor related commands  
        .  
        .  
    End  
  
End  
.  
.
```

16.7.1. Display Truncation Error For

Scope:

Display Truncation Error For *Solution_dof* [With *HowMany* Entries]

Parameter	Value	Default
<i>Solution_dof</i>	string	undefined

Summary Provides ability to request log file output of the maximum computed truncation error values.

Description This command allows one to request the maximum magnitudes of predictor error at a small number of DOF to the log file. For vector Fields only the magnitude over all components is considered. Note that additional log file output can be IO intensive so use of this command line should be restricted to debugging of a model.

Default is 5 values.

16.7.2. Maximum Number Of Rebalances

Scope:

Maximum Number Of Rebalances {=*|are|is*} *Count*

Parameter	Value	Default
<i>Count</i>	integer	undefined

Summary Specify the maximum number of times to perform a mesh rebalance.

16.7.3. Predictor Fields

Scope:

Predictor Fields {=*|are|is*} *Field_names...*

Parameter	Value	Default
<i>Field_names</i>	string...	undefined

Summary Specification of active fields to be used in predictor algorithm.

Description Specifies which fields to examine or ignore in the algorithm for adaptive time step selection. Fields that are *not* predictor fields will not be predicted solutions for the first two time steps. This is important for fields like pressure and electrostatic potential which may exhibit large jumps in their solutions between the initial conditions and the first solutions owing to the absence of time dependent terms in their governing equations during startup.

The selected fields will contribute to the d_{n+1} norm discussed in the TIME TRUNCATION ERROR time block command. This command line can be provided multiple times with cumulative results.

By default all fields are included. All field names following the optional "NOT" keyword will be excluded from the selection algorithm.

17. NONLINEAR SOLUTION STRATEGY

17.1. EQUATION SYSTEM OVERVIEW

In coupled physics problems one is tasked with solving a set of nonlinear coupled equations and ideally one would solve these equations as a fully-coupled monolithic system. In practice solving the set of equations monolithically may prove impractical owing to large linear system memory requirements and difficulty in locating a small radius of convergence. Thus in some cases one may wish to perform a segregated solve of the equations where each set of equations can be solved in a slightly different manner. This ability to solve subsets of the entire equation set is supported through a feature called Equation System by which criteria for solving a set of nonlinear equations can be applied to a select group of equations.

By default a single set of coupled equations is treated internally as an Equation System without need of additional input syntax. Here the solution strategy for the Equation System is solely determined by a collection of Nonlinear Solution Specifications [17.3](#). A typical setup for a single equation system might be

```
Begin Aria Region myRegion
.
Use Linear Solver solve_temperature
.
eq energy for temperature On block_1 using q1 with lumped_mass diff
.
nonlinear solution strategy = newton
use dof averaged nonlinear residual
maximum nonlinear iterations = 20
nonlinear residual tolerance = 1.e-6
.
.
End Aria Region myRegion
```

Simulations in which different subsets of the coupled equations are solved in a segregated manner require that each subset be explicitly defined as an Equation System with a corresponding solution strategy which may differ for each equation system. When multiple Equation Systems are present, the overall segregated solution is governed by iteration and convergence criteria at a global/outer level

[17.2](#).

A typical setup for segregated solution of multiple equation systems might be

```
Begin Aria Region myRegion
.
Segregated global nonlinear residual tolerance = 6.0e-9
.
Begin Equation System temperature
.
  eq energy for temperature On block_1 using q1 with lumped_mass diff
  Use Linear Solver solve_temperature
.
  nonlinear solution strategy = newton
  use dof averaged nonlinear residual
  maximum nonlinear iterations = 20
  nonlinear residual tolerance = 1.e-6
.
End Equation System temperature
.
Begin Equation System species
.
  eq species for species_0 On block_1 using q1 with diff
.
  Use Linear Solver solve_species
.
  nonlinear solution strategy = newton
  use dof averaged nonlinear residual
  maximum nonlinear iterations = 10
  nonlinear residual tolerance = 1.e-8
.
End Equation System species
.
End Aria Region myRegion
```

17.2. GLOBAL SOLUTION FOR EQUATION SYSTEMS

The global solution for a set of Equation Systems is controlled by a set of segregated solve criteria. A simulation will advance to the next time step when these criteria are satisfied.

17.2.1. Segregated Global Minimum Convergence Rate

Scope:

Segregated Global Minimum Convergence Rate $\{=|are|is\}$ *MinRate* [Number Of Steps $\{=|are|is\}$ *MinSteps*]

Parameter	Value	Default
<i>MinRate</i>	real	undefined

Summary Set a minimum convergence rate based on the initial nonlinear residual of each equation system in the problem. At each segregated iteration the equation system with the largest initial residual is tested using $r_N/r_{N-MinSteps} < MinRate^{MinSteps}$. If that condition is not met then the time step fails and is retried with a shorter dt.

17.2.2. Segregated Global Nonlinear Initial Residual Tolerance

Scope:

Segregated Global Nonlinear Initial Residual Tolerance $\{=|are|is\}$ *Pt*

Parameter	Value	Default
<i>Pt</i>	real	undefined

Summary Convergence tolerance for global segregated nonlinear residual for the iteration. The iteration is considered finished when all of the individual equation systems have an initial nonlinear residual less than the given tolerance. This is cheaper than other tests that require recomputing the nonlinear residual. However, care should be taken since the initial nonlinear residual of the individual equation systems might not be a good measure of the final nonlinear residual of those systems due to deltas produced by other equation systems.

17.2.3. Segregated Global Nonlinear Number Of Steps

Scope:

Segregated Global Nonlinear Number Of Steps $\{=|are|is\}$ *Number_of_steps* [Fail Step $\{=|are|is\}$ *failValue*]

Parameter	Value	Default
<i>Number_of_steps</i>	integer	undefined

Summary Maximum number of segregated solution steps within a time step. Depending on the failValue the solution will either be accepted, or the time step will fail when the maximum number of steps is reached.

17.2.4. Segregated Global Nonlinear Relative Residual Tolerance

Scope:

Segregated Global Nonlinear Relative Residual Tolerance {=|are|is} *Pt*

Parameter	Value	Default
<i>Pt</i>	real	undefined

Summary Convergence tolerance for global segregated nonlinear residual for the iteration. Satisfaction of this criterion is sufficient for the iteration to be considered finished. This line command can be used when the user desires to enforce a global relative residual tolerance for the entire segregated system that may be different from the individual equation systems value

17.2.5. Segregated Global Nonlinear Residual Tolerance

Scope:

Segregated Global Nonlinear Residual Tolerance {=|are|is} *Pt* [Minimum Steps {=|are|is} *minStepsValue*]

Parameter	Value	Default
<i>Pt</i>	real	undefined

Summary Convergence tolerance for global segregated nonlinear residual for the iteration. Satisfaction of this criterion is sufficient for the iteration to be considered finished. This line command can be used when the user desires to enforce a global residual enforcement for the entire segregated system that may be different from the individual equation systems value

17.2.6. Segregated Global Nonlinear Target Number Of Steps Per Time Step

Scope:

Segregated Global Nonlinear Target Number Of Steps Per Time Step {=|are|is} *target_ iterations*

Parameter	Value	Default
<i>target_ iterations</i>	integer	undefined

Summary Set a target number of segregated iterations per time step to use for time step control. If more than the specified number of iterations are required to converge a time step the next time step size will be decreased proportional to the ratio of the target number and the number taken. If a maximum number of allowed segregated iterations is set it is recommended to set the target to 1-2 fewer iterations to avoid an excessive number of failed time steps.

17.3. NONLINEAR SOLUTION SPECIFICATIONS

The general solution strategy used in Aria is to solve the requested system of equations for solution variables ϕ incrementally. In the context of a Newton formulation then within the Newton step one will solve

$$J\Delta\phi = -R(\phi)$$

where J is the Jacobian matrix, $\Delta\phi$ is the solution increment and $R(\phi)$ is the system residual for the governing equations described in Chapter 5. This chapter describes basic nonlinear solution command line settings that influence how a converged solution will be obtained. For transient solutions these settings are used in combination with time integration settings described in Chapter 16 for advancing a solution to the next time step.

It is instructive here to review a typical log file output of the Aria solution summary in order to establish how a user might influence the solution procedure.

Equation System AriaRegion->main:

```
* Step : Transient, Strategy: NEWTON, Time: 2.20e+03, Step: 5.29e+00
* Matrix: Solver: "Solve_Temperature", Unknowns: 1360, Nonzeros: 11578
* Mesh : Processor 0 of 1: 1253 of 1253 elems, 1363 of 1363 nodes
* Computing View Factors for enclosure space
```

N O N L I N E A R			L I N E A R			
Step	Resid	Delta	Itns	Status	Resid	Asm/Slv Time
1	6.37e-02	1.10e+01	59	ok	8.23e-07	7.0e-03/2.0e-03
2	1.10e-04	8.18e-03	58	ok	1.19e-09	7.0e-03/2.0e-03
3	3.06e-07	8.81e-05	61	ok	3.68e-12	6.0e-03/2.0e-03

Termination reason: 8.80515e-05 < nonlinear_correction_tolerance(0.001)

In the log file output shown above, columns under the N O N L I N E A R heading are related to the command lines described in this chapter. The columns Resid and Delta represent L2 norms of an aggregate residual $R^*(\phi)$ and solution increment vector $\Delta\phi$ while the column denoted Step denotes the iteration within this Newton step. Columns under the L I N E A R heading represent the number of linear solver iterations (Itns), the Resid column represents the linear system residual $R^*(\Delta\phi)$. Here $R^*(\Delta\phi) = J\Delta\phi + R(\phi)$, the residual for the assembled system of equations, is solved for $\Delta\phi$ to the tolerance requested in the Linear Solver specifications 20. The column labeled Status indicates whether the linear solve completed successfully, ok or fail, within the allowable number of iterations defined in the Linear Solver specifications. The column labeled Asm/Slv Time contain assembly and solution times for the system of equations.

Given a current value of ϕ then within each Newton step the residual $R^*(\Delta\phi)$ is first evaluated using $\Delta\phi = 0$ and tested for convergence. Here the convergence conditions are satisfied when either the NONLINEAR RESIDUAL TOLERANCE or NONLINEAR CORRECTION TOLERANCE are achieved. If the solution is not yet converged, the system of equations is turned over to the equation solver where it is solved for a new $\Delta\phi$ subject to the Linear Solver specifications. Then the Solver solution is used to

update the nonlinear solution $\phi = \phi_{old} + \Delta\phi$ and the process begins anew subject to a user supplied MAXIMUM NONLINEAR ITERATIONS.

Within the Newton step a solution is said to FAIL if it is not converged within MAXIMUM NONLINEAR ITERATIONS and this occurrence will be noted in the log file. For transient simulations one will normally repeat the solution procedure with a smaller time step as described in Chapter 16. In some cases the user may chose to override the FAIL condition using the ACCEPT SOLUTION AFTER MAXIMUM NONLINEAR ITERATIONS command line but *one is cautioned that this option should be used with discretion as it may discredit any expectation of accuracy in transient results*. For completeness, a summary of pass, fail, and fail but accepted steps are included at the end of the log file.

For most applications the default NONLINEAR RESIDUAL TOLERANCE (1e-6) is adequate when accompanied by a Linear Solver specification of RESIDUAL NORM TOLERANCE minimum of 1.0e-8. Inclusion of the command line USE DOF AVERAGED NONLINEAR RESIDUAL is highly recommended, particularly when performing uniform mesh refinement studies. A summary of these and other nonlinear solution related command lines is given in what follows.

17.3.1. Accept Solution After Maximum Nonlinear Iterations

Scope:

Accept Solution After Maximum Nonlinear Iterations {=|are|is} Bool

Parameter	Value	Default
Bool	{false true}	FALSE

Summary Specifies whether solution is considered to be converged after MAXIMUM NONLINEAR ITERATIONS even if none of the convergence criteria are satisfied.

17.3.2. Filter Nonlinear Solution

Scope:

Filter Nonlinear Solution For AssociatedDoF FilterType {=|are|is} Values...

Parameter	Value	Default
AssociatedDoF	string	undefined
FilterType	string	undefined
Values	string...	undefined

Summary Restrict the value of a solution variable used in the nonlinear solver iterations of a solution step.

Description The nonlinear solution can be restricted to a range with upper and lower limits using the FILTER_TYPE = RANGE while supplying two bounding values. To set an upper or lower bound use FILTER_TYPE = MAXIMUM or FILTER_TYPE = MINIMUM while supplying a single bounding value.

17.3.3. Maximum Accepted Nonlinear Correction

Scope:

Maximum Accepted Nonlinear Correction {=|are|is} *mnlc*

Parameter	Value	Default
<i>mnlc</i>	real	1e16

Summary Maximum allowed nonlinear correction tolerance during residual acceptance.

17.3.4. Maximum Accepted Nonlinear Residual

Scope:

Maximum Accepted Nonlinear Residual {=|are|is} *mnlr*

Parameter	Value	Default
<i>mnlr</i>	real	1e16

Summary Maximum allowed nonlinear residual tolerance during nonlinear correction acceptance.

17.3.5. Maximum Line Search Steps

Scope:

Maximum Line Search Steps {=|are|is} *MaxSteps*

Parameter	Value	Default
<i>MaxSteps</i>	integer	10

Summary Maximum number of line search steps per nonlinear iteration.

Description Only applicable when the LINE_SEARCH nonlinear solution strategy is used.

17.3.6. Maximum Nonlinear Iterations

Scope:

Maximum Nonlinear Iterations {=|are|is} *Np*

Parameter	Value	Default
<i>Np</i>	integer	20

Summary Number of allowable nonlinear iterations in one linear solution step.

Description The solution step will terminate when the number of nonlinear iterations are exceeded.
Default value = 20.

17.3.7. Minimum Nonlinear Solves

Scope:

Minimum Nonlinear Solves {=|are|is} *Np*

Parameter	Value	Default
<i>Np</i>	integer	1

Summary Minimum number of actual nonlinear solves that are required.

Description Each nonlinear iteration involves first assembling the nonlinear residual and Jacobian matrix and second solving the linear system for a nonlinear correction that is applied to the estimate of the nonlinear solution.

The nonlinear solver will continue iterating until this minimum number of solves are performed. The default value is one (1) but setting this to zero can be useful in some situations.

17.3.8. Nonlinear Correction Ratio Tolerance

Scope:

Nonlinear Correction Ratio Tolerance {=|are|is} *Pt*

Parameter	Value	Default
<i>Pt</i>	real	undefined

Summary Convergence tolerance for the nonlinear correction. It is satisfied if the nonlinear correction is less than this specified multiple of the initial nonlinear correction.

17.3.9. Nonlinear Correction Scaling

Scope:

Nonlinear Correction Scaling {=|are|is} *Strategy*

Parameter	Value	Default
<i>Strategy</i>	{dof_amax none}	NONE

Summary Specifies how to scale the nonlinear correction norm.

Description NONE (default) - The unscaled nonlinear corrections will be used.

DOF_AMAX (recommended) - The corrections for each equation will be scaled by $\max(1, \text{abs}(\max(\text{solution\_N})))$

17.3.10. Nonlinear Correction Tolerance

Scope:

Nonlinear Correction Tolerance $\{=|are|is\}$ *Pt*

Parameter	Value	Default
<i>Pt</i>	real	1.0e-6

Summary Convergence tolerance of nonlinear correction norm for the iteration. Satisfaction of this criterion is sufficient for the iteration to be considered finished.

17.3.11. Nonlinear Relaxation Factor

Scope:

Nonlinear Relaxation Factor $\{=|are|is\}$ *Prf*

Parameter	Value	Default
<i>Prf</i>	"string"	1.0

Summary Weighting factor for fraction of a new nonlinear solution that will be applied to the linear solution update. Weighting factor must lie in the range 0.0 to 1.0.

Functions of iteration count (i) are also supported. The function string must be enclosed in quotes if it has spaces or commas.

17.3.12. Nonlinear Residual Minimum Convergence Rate

Scope:

Nonlinear Residual Minimum Convergence Rate $\{=|are|is\}$ *MinRate* [Number Of Steps $\{=|are|is\}$ *MinSteps*]

Parameter	Value	Default
<i>MinRate</i>	real	undefined

Summary Set a minimum convergence rate based on the nonlinear residual At each nonlinear iteration the condition $resid_N/resid_{N-MinSteps} < MinRate^{MinSteps}$. If that condition is not met then the time step fails and is retried with a shorter dt. The usage of this test is modified if the command "USE SECONDARY LINEAR SOLVER" is specified. See the description of that command for details.

17.3.13. Nonlinear Residual Ratio Tolerance

Scope:

Nonlinear Residual Ratio Tolerance {=|are|is} *Pt*

Parameter	Value	Default
<i>Pt</i>	real	0.0

Summary Convergence tolerance for the ratio of the nonlinear residual to the initial nonlinear residual for the solution iteration. Convergence is satisfied if the ratio is less than this specified multiple of the initial nonlinear residual.

17.3.14. Nonlinear Residual Scaling

Scope:

Nonlinear Residual Scaling {=|are|is} *Strategy*

Parameter	Value	Default
<i>Strategy</i>	{dof_amax none}	NONE

Summary Specifies how to scale the nonlinear residuals.

Description NONE - The unscaled nonlinear residuals will be used.

DOF_AMAX (recommended) - The residuals for each equation will be scaled by $\max(1, \text{abs}(\max(\text{solution\_N})))$

This option will only affect problems using Tpetra-based linear solvers.

17.3.15. Nonlinear Residual Tolerance

Scope:

Nonlinear Residual Tolerance {=|are|is} *Pt*

Parameter	Value	Default
<i>Pt</i>	real	1.0e-6

Summary Convergence tolerance of nonlinear residual for the iteration. Satisfaction of this criterion is sufficient for the iteration to be considered finished.

17.3.16. Nonlinear Solution Strategy

Scope:

Nonlinear Solution Strategy {=*|are|is*} *Strategy* [*FormulationType*]

Parameter	Value	Default
<i>Strategy</i>	{ <i>line_search</i> <i>newton</i> <i>newton_finite_difference</i> <i>newton_lagged</i> }	undefined

Summary Specifies the nonlinear solution strategy.

Description There is no default value so this line command is required.

17.3.17. Use Dof Averaged Nonlinear Residual

Scope:

Summary Select whether to use a nonlinear residual normalized by the number of degrees of freedom instead of the raw global residual reported by the linear system.

Description Specifies that the reported nonlinear residual is scaled (divided by) the number of DOF in the problem. In selecting appropriate values for the NONLINEAR RESIDUAL TOLERANCE users are cautioned that the average nonlinear residual reported values may be several orders of magnitude smaller than when using the global nonlinear residual. This option is provided to allow comparison with residual values from other applications.

17.3.18. Use Linear Solver

Scope:

Use Linear Solver *Solver* [*SolverName*]

Parameter	Value	Default
<i>Solver</i>	string	undefined

Summary Specifies which solver to use with this region, optionally providing a name for the solver (default: the_linear_solver)

17.3.19. Use Secondary Linear Solver

Scope:

Use Secondary Linear Solver *Solver* [For *NumSteps* Steps]

Parameter <i>Solver</i>	Value string	Default undefined
Summary	Specifies which secondary solver to use with this region. Every nonlinear solve will begin employing the primary solver specified by the command "USE LINEAR SOLVER". This will take over for the primary solver in two cases. First, if the primary linear solver fails due to a numerical issue (e.g. GMRES loss of accuracy). Second, if the command "NONLINEAR RESIDUAL MINIMUM CONVERGENCE RATE" is given, a failure of that test when employing the primary linear solver will trigger a switch to the secondary solver. If the test later fails when employing the secondary solver, the time step will fail. This allows for a direct solver or more robust iterative solver to be used if the primary solver struggles to converge at some point in a simulation. This only functions if both the primary and secondary solvers are Tpetra-based. This should be considered a feature for expert users. By default this is active for 10 time steps once it has been activated. You can change that by adding the optional "FOR X STEPS" command suffix.	



Beta Capability: Usage of secondary solvers is not well tested and should not be considered a production capability.

18. WRITING USER PLUGINS

18.1. ABOUT PLUGINS

Users are free to extend Aria’s library of material models, constitutive equations, boundary conditions, distinguishing conditions and source terms through the use of *plugins*. In order to do this, a user writes the C++ code to implement an Expression class. Thus *plugins* should not be confused with *user_subroutines* 33.20. Before delving into Aria plugins it’s worth reading section 44.2 and scanning section 44.5 for an introduction to Aria’s Expression system.

When a user supplies their own plugin it becomes a legitimate piece of Aria. Plugins have no performance penalty over Aria’s built-in functionality and plugins have no added restrictions over built-in Expression regarding what can and can’t be done. In fact, taking a user plugin and adding it to Aria proper (so that it becomes “owned” by Aria) is a fairly straightforward process.

It’s worth re-stating here that since Aria employs a Newton formulation, many of the algorithms make use of DOF sensitivities, i.e., Aria often needs to know the derivative of your model with respect to all of the unknowns in the problem. There are three ways to supply the sensitivities in Aria: manually code them, use a numerical finite-difference function, or use (forward) automatic differentiation (FAD). The FAD method is ideal for plugins because the sensitivities are performed analytically and exact, though there may be a small performance degradation. However, if only a few models use FAD there may be no measurable performance penalty. For that reason, we’ve designed our plugin system to use FAD by default. If one has different needs, please contact the user support group sierra-helpsandia.gov for help.

18.2. COMPILING AND USING PLUGINS WITH DYNAMICALLY LOADED LIBRARIES

The easiest and most efficient way to compile and use plugins with Aria is to compile them into a dynamically loaded library that a pre-built aria executable is able to load at runtime.

18.2.1. Compiling a Plugin into a Shared Library

The easiest way to compile your plugin into a share library (.so file) is to use the `jamsb` tool. Within SNL, this tool is normally located in the `/sierra/Dev/tools/` directory. It’s pretty simple to use:

```
$ jansub -P aria -sierradir /path/to/sierra/project
```

If you happen to be working in a Sierra project that contains the Aria you'd like to build against then one can skip the `-sierradir` option. You can use the `-s` option to override the system for which you want to build; see the help (`-h`) for more options.

This command will find all of the `.C` files in the current directory and compile them into a file of the same name but with the `.so` extension. Note that you do not have to put your `.C` files in the Aria source directories – they can live with your problem input files in any working directory.

In the event one is not building on a standard Linux machine, the command line must also reference the target platform as follows:

For code versions before 4.26,

```
$ module load sierra
```

```
$ jansub -P aria -sierradir /path/to/sierra/project/target_code_version
```

this will compile all plugins in the current directory.

For code versions 4.26 and beyond,

```
$ module load sierra-devel
```

```
$ module load sierra-apps/target_code_version
```

```
$ sierra -make aria -i input_filename.i
```

here the input file is first scanned and only the needed plugins will be compiled.

Running the above command line with an invalid platform name will provide the available platforms for which one can build an Aria executable.

18.2.2. Pointing to a Plugin form your Aria Input File

```
Begin Sierra My_Sierra_Job
  Load User Plugin file ./My_Density_Plugin.so
  Load User Plugin file ./My_Viscosity_Plugin.so
  .
  .
  .
```

18.2.3. Running Aria with Dynamically Loaded Plugins

The Aria executable is built to accommodate dynamically loaded libraries. Execution when using plugins is handled in the same way as when plugins are not being used:

```
$ sierra aria -i use_my_density.i -x /path/to/sierra/project
```

18.3. AN IMPORTANT NOTE ABOUT MODEL NAMES

In order to avoid name clashes, model names always end with the generic name of the quantity they provide. So, density model names always end in `_DENSITY`, viscosity model names end in `_VISCOSITY`, source model names end in `_SOURCE`, etc. For material models, it's easy to know what that ending is because it's the same as the left-hand side of the "=" sign in the material input block (with spaces replaced by an underscore "_"). Clearly, it's important to keep this in mind when naming and referring to your plugin model or else Aria won't be able to find it properly.

In this example, we'll name our density `MY_MODEL_DENSITY` (recall, it must end in `_DENSITY`) so in the input file we'll have to refer to it as `MY_MODEL` since the ending is automatically added.

18.4. THE INPUT FILE

As of version 4.48 there is a difference between referencing plugins for material models vs source terms or boundary conditions. Source or BC plugins can be referenced in the input file similar to the way Aria's built-in Expressions are referenced. The name of the model is just whatever your plugin is named without the file extension, e.g., `MY_MODEL`. Material model plugins use the `User_Plugin` model type and provide the plugin name as the name parameter.

```
Begin Aria Material Kryptonite
  Density = User_Plugin name=My_Model a=1.0 b=-0.01
  ...
End

...

Begin Aria Region Region
  ...
  Source for Energy on block_1 = My_Source_Plugin

  BC flux for Energy on surface_1 = My_Flux_Plugin d=5.
  ...
End
```

It's important to note that the plugin name must not conflict with model names used internally by Aria (the outcome would be, at least to users, ambiguous). Aria will verify this and produce an error if there's a name clash.

18.5. EXAMPLE PLUGIN CODE: MY_DENSITY.C

In this section we'll write the code to supply a density function which is a cubic polynomial in temperature (T),

$$\rho = a + bT + cT^2 + dT^3.$$

Normally, writing C++ code requires using a header (.h) file and an implementation (.C) file but since no other code needs to see our class definition, we can skip the header file and place the definition right in the .C file.

The first thing we need to do is include a header file which will give us all we need to write an Expression. Since our plugin will live in isolation, we'll also add a using declaration to make life easier on ourselves; without it we'd have to declare the namespaces or prepend `sierra::Aria::` to lots of data types. So far, we have this:

```
#include <Aria_Plugin_Expression.h>
using namespace sierra::Aria;
```

Next we need the basic declaration of our class. This tells the compiler which methods and data members we want to have. Here's ours:

```
// Class definition -- could go in a header file.
class My_Density : public FAD_Expression
{
public:
    My_Density(Expression_Manager * const manager,
                const sierra::Identifier & expr_model_name,
                const Subdomain_Tag & subdomain_tag,
                const Int & subindex,
                const Phase_Label & phase_label,
                const sierra::String & params);
    virtual ~My_Density() {}
    virtual void compute_FAD_values(const ElementRange & elem_range);
private:
    Real a;
    Real b;
    Real c;
    Real d;

    Scalar_FAD_Expression_Handle values;
    Scalar_FAD_Expression_Handle temperature;
};
```

This is mostly boiler-plate code. Here we declare a constructor and an empty destructor and the method needed for computing our density's values. We also add some private data to store our polynomial coefficients.

Now it's time to write some code. First, we write the constructor which tells Aria, in a generic sense, what we provide (density), what we depend on (temperature) and what parameters we require from the user (a , b , c and d).

```
My_Density::My_Density(Expression_Manager * const manager,
                        const sierra::Identifier & expr_model_name,
                        const Subdomain_Tag & subdomain_tag,
                        const Int & subindex,
                        const Phase_Label & phase_label,
                        const sierra::String & params) :
    FAD_Expression(manager, subdomain_tag, subindex, phase_label, params)
{
    my_tensor_order      = 0;
    my_expression_tag     = Expression_Tag(EXPR::DENSITY, NO_OP, subindex, phase_label);
    my_expression_model_name = expr_model_name;

    // List the expressions that are required for this model.
    const Expression_Tag temperature_tag(EXPR::TEMPERATURE, NO_OP, subindex, phase_label);

    add_prereq(temperature_tag, temperature);

    // Get my model parameters.
    a = b = c = d = 0.0;
    get_optional_param("A", a);
    get_optional_param("B", b);
    get_optional_param("C", c);
    get_optional_param("D", d);

    if(a == 0.0 && b == 0.0 && c == 0.0 && d == 0.0)
    {
        throw sierra::RuntimeUserError() << "ERROR: All MY_MODEL_DENSITY parameters are zero";
    }

    // Make myself known to the manager.
    register_myself(values);
}
```

The `my_tensor_order` tells Aria what kind of field your Expression creates, viz. scalar, vector or tensor, tensor order 0, 1 or 2. If left unspecified, the default type is scalar (`my_tensor_order == 0`). Your expression also has a variable called `my_tensor_dimension` which is dimensionality of each tensor order. By default, `my_tensor_dimension` is set to the physical dimension of the problem, i.e.,

2 for 2D and 3 for 3D. This variable is also set for scalar fields. Combined, these variables define the number of values required to fully specify your Expression at a point on the element: `pow(my_tensor_dimension, my_tensor_order)`. These also define the expected signature of the values data used below.

Next, we write the code that implements our density function. Important note: the values arrays are always initialized to zero before this method is called. Here `FAD_DoubleType` variables are used for non-constant values related to the values calculation.

```
void My_Density::compute_FAD_values(const ElementRange & elem_range)
{
    for (auto elem : elem_range)
    {
        for(auto point : my_sizes.get_points())
        {
            const FAD_DoubleType & T = temperature(elem,point);
            values(elem,point) = a + T*(b + T*(c + T*(d)));
        }
    }
}
```

Note that since our Expression is a scalar in this example, the signature of values is `values(elem,point)`. If our result was a vector or tensor, the signature would be `values(elem,point,r)` and `values(elem,point,r,s)`, respectively, where $0 \leq r, s < \text{my\_tensor\_dimension}$.

The last thing we need to do is the actual plugin step. This one line of code,

```
ExprPluginFactory<My_Density> my_density_creator("MY_MODEL_DENSITY");
```

takes care of making your Expression known to Aria. The quoted string is the string that is used in your input file (except for the ending part, see section 18.3. If this string has any spaces in it, Aria will automatically replace them with an underscore.

For completeness the entire plugin code is given here.

```
#include <Aria_Plugin_Expression.h>

using namespace sierra::Aria;

// Class definition -- could go in a header file.
class My_Density : public FAD_Expression
{
public:
    My_Density(Expression_Manager * const manager,
```



```

        const sierra::Identifier & expr_model_name,
        const Subdomain_Tag & subdomain_tag,
        const Int & subindex,
        const Phase_Label & phase_label,
        const sierra::String & params);
virtual ~My_Density() {}
virtual void compute_FAD_values(const ElementRange & elem_range);
private:
    Real a;
    Real b;
    Real c;
    Real d;

    Scalar_FAD_Expression_Handle values;
    Scalar_FAD_Expression_Handle temperature;
};

My_Density::My_Density(Expression_Manager * const manager,
        const sierra::Identifier & expr_model_name,
        const Subdomain_Tag & subdomain_tag,
        const Int & subindex,
        const Phase_Label & phase_label,
        const sierra::String & params) :
    FAD_Expression(manager,subdomain_tag,subindex,phase_label,params)
{
    my_expression_tag    = Expression_Tag(EXPR::DENSITY,NO_OP,subindex,phase_label);
    my_expression_model_name = expr_model_name;

    // List the expressions that are required for this model.
    const Expression_Tag temperature_tag(EXPR::TEMPERATURE,NO_OP,subindex,phase_label);

    add_prereq(temperature_tag,temperature);

    // Get my model parameters.
    a = b = c = d = 0.0;
    get_optional_param("A",a);
    get_optional_param("B",b);
    get_optional_param("C",c);
    get_optional_param("D",d);

    if(a == 0.0 && b == 0.0 && c == 0.0 && d == 0.0)
    {
        throw sierra::RuntimeUserError() << "ERROR: All PLUGIN DENSITY parameters are zero
    }

```

```

    // Make myself known to the manager.
    register_myself(values);
}

void My_Density::compute_FAD_values(const ElementRange & elem_range)
{
    for (auto elem : elem_range)
    {
        for (auto point : my_sizes.get_points())
        {
            const FAD_DoubleType & T = temperature(elem, point);
            values(elem, point) = a + T*(b + T*(c + T*(d)));
        }
    }
}

ExprPluginFactory<My_Density> my_density_creator("MY_MODEL_DENSITY");

```

18.6. TESTING YOUR PLUGIN

There are two good tests you can perform to test your plugin. The first is to run Aria in debug mode. To do this, add `-o dbg` to your build command line to build a debug executable. Then, add `-d` to your `sierra` command line to run the debug executable. In debug mode Aria will, among other things, perform bounds checking on your `FAD_MDArray` objects like `values(...)`, `dself(...)` and `sens(...)` in this example.

Secondly, if you hand-code your Newton sensitivities (not done in this example), you can test the coding of your sensitivities by adding `-arialog sens_check` to your `sierra` command line. This will cause Aria to compare the computed sensitivity values with numerical approximations. The sensitivity checker will cause your code to run slower but it will work in either debug or optimized mode. Aria's sensitivity checker is designed to only report discrepancies that have a high probability of being true errors so it's possible that it may miss some small errors. However, reported errors are most probably real.

Oftentimes the easiest way to debug your code is to print information to the screen. Aria provides a facility to support this. To print information to the log file, use the `arialog C++` output stream. For example,

```

for (auto elem : elem_range)
{
    for(auto point : my_sizes.get_points())
    {
        ...
        values(elem,point) = ...
    }
}

```

```

    arialog.m(LOG_PLUGIN) << "value(" << point << ") = " << value(elem,point) << endl;
  }
}

```

Then, you can activate this output by adding the option `-arialog plugin` to your `sierra` command line. If you leave off the `.m(LOG_PLUGIN)` part then it will always write your output to the log file. There's a performance penalty for having this code option present (even if out don't turn the logging on) so you probably want to remove it once you're done debugging.

19. DYNAMIC LOAD BALANCING

Aria supports dynamic load balancing of elements using the STK rebalance interface to Zoltan and Zoltan2. This is particularly useful for simulations with any of:

- Different equations solved on different mesh blocks (including thermal problems with chemistry source terms only on some blocks).
- Mesh adaptivity (either standard AMR or CDFEM)
- Multiple equation systems

By default when rebalance is enabled Aria will assign each element in the mesh a load based on the amount of time it takes to assemble its matrix contributions, and will use a multi-criteria rebalance in order to balance the load of each equation system simultaneously. The frequency that the load balance is checked can be controlled with the "REBALANCE TIME STEP FREQUENCY" and "MAXIMUM NUMBER OF LOAD BALANCES" line commands. Generally for problems without adaptivity performing a single rebalance after the first time step is sufficient, and for cases with significant differences in computational cost per element or multiple equation systems has been seen to provide a 50-100% speed-up in parallel in some cases.

Use of the dynamic load balancing capability has been tested with adaptive mesh refinement, CDFEM, contact, bulk nodes, pressurization models, and enclosure radiation.



Known Issue: Using rebalance with enclosure radiation requires that the viewfactors be recalculated every time the mesh is rebalanced. It is only compatible with reading viewfactors from a file when they were stored using the PNETCDF format.

See, also, the Zoltan [homepage](#) [31], the Zoltan [User's Guide](#) [32] and an overview of Zoltan [33].

19.1. ENABLE REBALANCE

ENABLE REBALANCE [WITH THRESHOLD = *REAL*]

Description Enables load balancing for parallel simulations.

Summary This command causes Aria to occasionally redistribute the mesh across the processors in a parallel run in order to (hopefully) balance the work. In order to perform this balancing, Aria must supply a "load" for each element on each processor to the Zoltan library. See the REBALANCE LOAD MEASURE command (19.2) for load measuring options.

The loads can be output to the results database by adding the following line to the RESULTS OUTPUT block in the input file:

```
Element Variables = rebalance->element_load as Load
```

The number optionally supplied as a threshold determines how far out of balance the load can become before load balancing is performed and defaults to 1.05.



Known Issue: Prior versions of Aria allowed the specification of a "Zoltan Parameters" block for rebalance. That has been deprecated and will not impact the simulation any more, however the parser will accept it for backwards compatibility.

Parent
Block(s)
ARIA_REGION

19.2. REBALANCE LOAD MEASURE

REBALANCE LOAD MEASURE = *STRING*

Description Selects the method for measuring element loads for rebalancing.

Summary Valid options are ELEMENT (default), PROCESSOR and CONSTANT.

ELEMENT : (default) assigns an element weight equal to the total cost of assembling the element for a timestep divided by the number of nonlinear iterations.

PROCESSOR : assigns same weight to all elements on a processor equal to the average cost of assembling an element for a timestep divided by the number of nonlinear iterations.

CONSTANT : assigns the same weight to each element, and is useful for regression testing.

Parent
Block(s)
ARIA_REGION

19.3. MAXIMUM NUMBER OF REBALANCES

MAXIMUM NUMBER OF REBALANCES = *INT*

Description Disables dynamics mesh rebalancing after the specified number of mesh rebalances have been performed.

Summary The number of rebalances only increments if elements are actually migrated across processors. By default, Aria will rebalance as many times as needed.

Parent
Block(s)
ARIA_REGION

19.4. REBALANCE TIME STEP FREQUENCY

REBALANCE TIME STEP FREQUENCY = *INT*

Description Causes Aria to only examine the load balance every N steps, where N is the number supplied by this command line.

Summary By default, Aria will check the load balance every time step.

Parent
Block(s)
ARIA_REGION

20. LINEAR SOLVER REFERENCE

20.1. OVERVIEW

Aria supports several choices of linear solver packages. Currently the Trilinos and Aztec solver packages are the best supported and tested and are recommended for production use.

Within the input file linear solver command block will appear at the Domain scope as illustrated below. Note that different linear solvers can be used for different equation systems. Furthermore, a solver command block can appear in the input but not be used.

```
Begin Sierra
.
Begin Trilinos Equation Solver first_solver
.
  Trilinos linear solver commands
.
End
.
.
Begin Aztec Equation Solver second_solver
.
  Aztec linear solver commands
.
End
.
Begin Tpetra Equation Solver third_solver
.
  Tpetra linear solver commands
.
End
.
Begin Procedure My_Aria_Procedure
.
  Begin Aria Region My_Region
  .
    use linear solver first_solver
  .
.
```

```

End

Begin Aria Region My_Other_Region
.
  use linear solver third_solver
.
End

End

.
End Sierra

```

20.1.1. Tpetra Solver Overview



Beta Capability: Usage of the Tpetra-based solvers is under active development.

The syntax for specifying a Tpetra-based solver uses a nested command block structure. The outermost level at the Sierra scope is the "BEGIN TPETRA EQUATION SOLVER" block. This block must contain a single nested solver block corresponding to your desired solver type. Several types of direct and iterative linear solvers are provided through the Amesos2 and Belos packages of Trilinos. The supported solver blocks are listed in Section 20.2.4. If one of the iterative solvers is selected, it must also have a nested preconditioner block. A variety of preconditioners are supported through the Ifpack2 and MueLu Trilinos packages. See Section 20.2.5 for details on the supported preconditioners and their available options.

20.1.1.1. Expert Syntax

The standard solver and preconditioner blocks only support a subset of the commonly used options that are supported by the underlying Trilinos packages. The subset was chosen to cover the vast majority of linear solver use cases within Aria simulations, but an alternative approach is provided for expert users who would like to be able to pass parameters directly to the underlying Belos, Ifpack2, and MueLu packages. This expert interface is used by providing the path to an XML file containing the definition for a Teuchos::ParameterList that is supported by the underlying Trilinos package in one of the "BEGIN EXPERT BELOS SOLVER", "BEGIN EXPERT IFPACK2 PRECONDITIONER", or "BEGIN MUELU PRECONDITIONER" blocks as desired.

Sample XML for expert Belos solver:

```
<ParameterList>
  <Parameter name="solution method" type="string" value="CG"/>
  <ParameterList name="Belos-Tpetra">
    <Parameter name="Convergence Tolerance" type="double" value="1.e-12"/>
    <Parameter name="Maximum Iterations" type="int" value="1000"/>
  </ParameterList>
</ParameterList>
```

The "solution method" parameter is required. Any additional parameters that are not specified in the "Belos-Tpetra" sublist will use their default values as defined by Belos.

Sample XML for expert Ifpack2 preconditioner:

```
<ParameterList>
  <Parameter name="preconditioner type:" type="string" value="ILUT"/>
  <Parameter name="fact: ilut level-of-fill" type="double" value="1.0"/>
  <Parameter name="fact: drop tolerance" type="double" value="0.0"/>
</ParameterList>
```

The "preconditioner type:" parameter is required. Any additional parameters that are not specified will use their default values as defined by Ifpack2.

Sample XML for expert MueLu preconditioner:

```
<ParameterList name="MueLu-Tpetra">
  <Parameter      name="verbosity"                type="string"    value="high"
  <Parameter      name="coarse: type"              type="string"    value="ILUT"
  <Parameter      name="coarse: max size"          type="int"       value="1000"
  <Parameter      name="max levels"                type="int"       value="4"/>
  <Parameter      name="smoother: type"            type="string"    value="CHEBY
  <ParameterList  name="smoother: params">
    <Parameter name="chebyshev: degree"                type="int"       value="2"/>
    <Parameter name="chebyshev: ratio eigenvalue"      type="double"    value="20"/>
    <Parameter name="chebyshev: min eigenvalue"        type="double"    value="1.0"/>
    <Parameter name="chebyshev: zero starting solution" type="bool"      value="true"
    <Parameter name="chebyshev: eigenvalue max iterations" type="int"       value="15"/>
  </ParameterList>
  <Parameter      name="aggregation: type"          type="string"    value="uncou
  <Parameter      name="aggregation: drop tol"      type="double"    value="0.02"

  <Parameter      name="repartition: enable"        type="bool"      value="true"
  <Parameter      name="repartition: min rows per proc" type="int"       value="1000"
  <Parameter      name="repartition: start level"    type="int"       value="2"/>
  <Parameter      name="repartition: max imbalance" type="double"    value="1.327
  <Parameter      name="repartition: partitioner"    type="string"    value="zolta
</ParameterList>
```

Unspecified parameters will use their default values as defined by MueLu.

For further documentation of the parameters supported by each Trilinos package please see the corresponding documentation on trilinos.org.

20.2. TPETRA EQUATION SOLVER

Scope: Sierra

Begin Tpetra Equation Solver *Solver Name*

Bc Enforcement {=|are|is} *value*

Matrix Output {=|are|is} *value*

Matrix Scaling {=|are|is} *value*

Begin Bicgstab Solver

End

Begin Cg Solver

End

Begin Expert Belos Solver

End

Begin Gmres Solver

End

Begin Klu2 Solver

End

Begin Preset Solver

End

Begin Superlu Solver

End

Begin Umfpack Solver

End

End

Summary Use a Tpetra-based linear solver.

20.2.1. Bc Enforcement

Scope: Tpetra Equation Solver

Bc Enforcement {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	{exact exact_no_column_mod remove solver solver_no_column_mod}	undefined

Summary Control how Dirichlet BC's are enforced. Fuego only.

20.2.2. Matrix Output

Scope: Tpetra Equation Solver

Matrix Output {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	string	undefined

Summary Output the matrix to the specified file name.

20.2.3. Matrix Scaling

Scope: Tpetra Equation Solver

Matrix Scaling `{=|are|is} value`

Parameter <i>value</i>	Value <code>{diagonal one_norm}</code>	Default undefined

Summary Apply a pre-solve scaling to the matrix.

Description In some problems scaling the matrix prior to the linear solve can help reduce the condition number of the matrix. This should be used in addition to an appropriate preconditioner.

20.2.4. Solvers

20.2.4.1. Bicgstab Solver

Scope: Tpetra Equation Solver

Begin Bicgstab Solver

Convergence Tolerance `{=|are|is} value`

Maximum Iterations `{=|are|is} value`

Residual Scaling `{=|are|is} value`

Begin Dd-Ilu Preconditioner

End

Begin Dd-Ilut Preconditioner

End

Begin Expert Ifpack2 Preconditioner

End

Begin Jacobi Preconditioner

End

Begin Muelu Preconditioner

End

Begin Sgs Preconditioner

End

End

Summary Use a bicgstab solver.

Convergence Tolerance

Scope: Bicgstab Solver

Convergence Tolerance {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	real	1e-06

Summary Set the convergence tolerance for the linear solver

Maximum Iterations

Scope: Bicgstab Solver

Maximum Iterations {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	integer	300

Summary Set the maximum number of iterations taken by the linear solver

Residual Scaling

Scope: Bicgstab Solver

Residual Scaling {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	{none preconditioned_r0 r0 rhs}	r0

Summary Set the residual scaling for the linear solver

20.2.4.2. Expert Belos Solver

Scope: Tpetra Equation Solver

Begin Expert Belos Solver

 Xml File {=|are|is} *value*

 Begin Dd-Ilu Preconditioner

 End

 Begin Dd-Ilut Preconditioner

 End

```
Begin Expert Ifpack2 Preconditioner
```

```
End
```

```
Begin Jacobi Preconditioner
```

```
End
```

```
Begin Muelu Preconditioner
```

```
End
```

```
Begin Sgs Preconditioner
```

```
End
```

```
End
```

Summary Use a Belos solver with parameters specified in an XML file.

Xml File

Scope: Expert Belos Solver

Xml File {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	string	undefined

Summary Supply the name of an XML file containing a Belos parameter list.

Description The supplied XML file must contain a ParameterList with a "solution method" string parameter corresponding to the desired type of Belos solver. Any additional parameters that should be passed on to Belos should be part of a nested ParameterList with name="Belos-Tpetra".

20.2.4.3. Superlu Solver

Scope: Tpetra Equation Solver

```
Begin Superlu Solver
```

```
End
```

Summary Use a SUPERLU direct solver.

20.2.4.4. Gmres Solver

Scope: Tpetra Equation Solver

Begin Gmres Solver

Convergence Tolerance {=|are|is} *value*

Maximum Iterations {=|are|is} *value*

Residual Scaling {=|are|is} *value*

Restart Iterations {=|are|is} *value*

Begin Dd-Ilu Preconditioner

End

Begin Dd-Ilut Preconditioner

End

Begin Expert Ifpack2 Preconditioner

End

Begin Jacobi Preconditioner

End

Begin Muelu Preconditioner

End

Begin Sgs Preconditioner

End

End

Summary Use a GMRES solver.

Convergence Tolerance

Scope: Gmres Solver

Convergence Tolerance {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	real	1e-06

Summary Set the convergence tolerance for the linear solver

Maximum Iterations

Scope: Gmres Solver

Maximum Iterations {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	integer	300

Summary Set the maximum number of iterations taken by the linear solver

Residual Scaling

Scope: Gmres Solver

Residual Scaling {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	{none preconditioned_r0 r0 rhs}	r0

Summary Set the residual scaling for the linear solver

Restart Iterations

Scope: Gmres Solver

Restart Iterations {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	integer	30

Summary Set the number of iterations between GMRES restarts.

20.2.4.5. Preset Solver

Scope: Tpetra Equation Solver

Begin Preset Solver

Convergence Tolerance {=|are|is} *value*

Maximum Iterations {=|are|is} *value*

Residual Scaling {=|are|is} *value*

Solver Type {=|are|is} *value*

End

Summary Use a preset solver for a specific linear system type.

Description The preset solver for a given linear system type is intended to provide reasonable behavior for many problems of that type. If this proves to be insufficient, the user must provide more fine-grained control over solver settings. The equivalent command which produces the solver will be output to the log file, and this may be used as a starting point from which changes for robustness may be made (i.e. increasing GMRES subspace size or changing the preconditioner).

Convergence Tolerance

Scope: Preset Solver

Convergence Tolerance {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	real	1e-06

Summary Set the convergence tolerance for the linear solver

Maximum Iterations

Scope: Preset Solver

Maximum Iterations {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	integer	300

Summary Set the maximum number of iterations taken by the linear solver

Residual Scaling

Scope: Preset Solver

Residual Scaling {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	{none preconditioned_r0 r0 rhs}	r0

Summary Set the residual scaling for the linear solver

Solver Type

Scope: Preset Solver

Solver Type {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	{continuity multiphysics scalar_transport thermal thermal_bicgstab thermal_symmetric}	undefined

Summary Set the preset solver type

20.2.4.6. Klu2 Solver

Scope: Tpetra Equation Solver

```
Begin Klu2 Solver
```

```
End
```

Summary Use a KLU2 direct solver.

20.2.4.7. Umfpack Solver

Scope: Tpetra Equation Solver

```
Begin Umfpack Solver
```

```
End
```

Summary Use a UMFPACK direct solver.

20.2.4.8. Cg Solver

Scope: Tpetra Equation Solver

```
Begin Cg Solver
```

```
Convergence Tolerance {=|are|is} value
```

```
Maximum Iterations {=|are|is} value
```

```
Residual Scaling {=|are|is} value
```

```
Begin Dd-Ilu Preconditioner
```

```
End
```

```
Begin Dd-Ilut Preconditioner
```

```
End
```

```
Begin Expert Ifpack2 Preconditioner
```

```
End
```

```
Begin Jacobi Preconditioner
```

```
End
```

```
Begin Muelu Preconditioner
```

```
End
```

```
Begin Sgs Preconditioner
```

End

End

Summary Use a conjugate gradient solver.

Convergence Tolerance

Scope: Cg Solver

Convergence Tolerance {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	real	1e-06

Summary Set the convergence tolerance for the linear solver

Maximum Iterations

Scope: Cg Solver

Maximum Iterations {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	integer	300

Summary Set the maximum number of iterations taken by the linear solver

Residual Scaling

Scope: Cg Solver

Residual Scaling {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	{none preconditioned_r0 r0 rhs}	r0

Summary Set the residual scaling for the linear solver

20.2.5. Preconditioners

20.2.5.1. Dd-Ilu Preconditioner

Scope: Bicgstab Solver

```
Begin Dd-Ilu Preconditioner

    Fill Level {=|are|is} value

    Reordering {=|are|is} value

    Subdomain Overlap Level {=|are|is} value

End
```

Summary Use a domain-decomposition ILU(k) preconditioner.

Fill Level

Scope: Dd-Ilu Preconditioner

```
Fill Level {=|are|is} value
```

Parameter	Value	Default
<i>value</i>	integer	0

Summary Set the level of fill, k, for ILU(k).

Reordering

Scope: Dd-Ilu Preconditioner

```
Reordering {=|are|is} value
```

Parameter	Value	Default
<i>value</i>	{off on}	ON

Summary Determine whether or not to apply an RCM reordering.

Subdomain Overlap Level

Scope: Dd-Ilu Preconditioner

```
Subdomain Overlap Level {=|are|is} value
```

Parameter	Value	Default
<i>value</i>	integer	0

Summary Set the level of subdomain overlap used in constructing the preconditioner.

20.2.5.2. Expert Ifpack2 Preconditioner

Scope: Bicgstab Solver

```
Begin Expert Ifpack2 Preconditioner
```

```
    Xml File {=|are|is} value
```

```
End
```

Summary Use an Ifpack2 preconditioner with parameters specified in an XML file.

Xml File

Scope: Expert Ifpack2 Preconditioner

```
Xml File {=|are|is} value
```

Parameter	Value	Default
<i>value</i>	string	undefined

Summary Supply the name of an XML file containing an Ifpack2 parameter list.

Description The supplied XML file must contain a ParameterList with a "preconditioner type:" string parameter corresponding to the desired type of Ifpack2 preconditioner as well as any additional parameters for that preconditioner.

20.2.5.3. Sgs Preconditioner

Scope: Bicgstab Solver

```
Begin Sgs Preconditioner
```

```
    Number Of Sweeps {=|are|is} value
```

```
End
```

Summary Use a symmetric Gauss-Seidel preconditioner.

Number Of Sweeps

Scope: Sgs Preconditioner

```
Number Of Sweeps {=|are|is} value
```

Parameter	Value	Default
<i>value</i>	integer	3

Summary Set the number of relaxation sweeps to perform.

20.2.5.4. Muelu Preconditioner

Scope: Bicgstab Solver

```
Begin Muelu Preconditioner
    Xml File {=|are|is} value
End
```

Summary Use a MueLu preconditioner.

Xml File

Scope: Muelu Preconditioner

Xml File {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	string	undefined

Summary Supply the name of an XML file containing a MueLu parameter list.

20.2.5.5. Dd-Ilut Preconditioner

Scope: Bicgstab Solver

```
Begin Dd-Ilut Preconditioner
    Drop Tolerance {=|are|is} value
    Fill Fraction {=|are|is} value
    Reordering {=|are|is} value
    Subdomain Overlap Level {=|are|is} value
End
```

Summary Use a domain-decomposition ILUT preconditioner.

Drop Tolerance

Scope: Dd-Ilut Preconditioner

Drop Tolerance {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	real	0

Summary Set the drop tolerance for ilut.

Description Off-diagonal entries of the incomplete factorization smaller than the specified tolerance will be dropped.

Fill Fraction

Scope: Dd-Ilut Preconditioner

Fill Fraction {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	real	1

Summary Set the fill fraction for ilut.

Description This parameter controls the number of nonzero entries that are kept in each row of the incomplete factorization. Larger values will use more memory and runtime, but may result in a more effective preconditioner.

Reordering

Scope: Dd-Ilut Preconditioner

Reordering {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	{off on}	ON

Summary Determine whether or not to apply an RCM reordering.

Subdomain Overlap Level

Scope: Dd-Ilut Preconditioner

Subdomain Overlap Level {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	integer	0

Summary Set the level of subdomain overlap used in constructing the preconditioner.

20.2.5.6. Jacobi Preconditioner

Scope: Bicgstab Solver

Begin Jacobi Preconditioner

Number Of Sweeps {=|are|is} *value*

End

Summary Use a Jacobi preconditioner.

Number Of Sweeps

Scope: Jacobi Preconditioner

Number Of Sweeps {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	integer	3

Summary Set the number of relaxation sweeps to perform.

20.3. TRILINOS EQUATION SOLVER

Scope: Sierra

Begin Trilinos Equation Solver *SolverName*

Bc Enforcement {=|are|is} *BcEnforcement*

Debug Output Level {=|are|is} *Level*

Debug Output Path {=|are|is} *DebugOutput*

Determine Sharing {=|are|is} *FeiDetermineSharing*

Fei Error Behavior {=|are|is} *FeiErrorBehavior*

Fei Output Level {=|are|is} *FeiOutputLevels*

Ilu Fill {=|are|is} *ilu_fill_level*

Ilu Threshold {=|are|is} *Threshold*

Matrix Format {=|are|is} *MatrixFormat*

Matrix Reduction {=|are|is} *AztecReductionType*

Matrix Scaling {=|are|is} *MatrixScaling*

Matrix Viewer {=|are|is} *Machine:port*

Maximum Iterations {=|are|is} *max_iterations*

Num Levels {=|are|is} *Num_levels*

Param-Bool *Parameter_name* Value *Bool*

Param-Int *Parameter_name* Value *integer_value*

Param-Real *Parameter_name* Value *Real_value*

Param-String *Parameter_name* Value *String_value*

Polynomial Order {=|are|is} *polynomial_order*

Preconditioner Subdomain Overlap {=|are|is} *Overlap*


```

Preconditioning Method {=|are|is} TrilinosPrecondMethods

Preconditioning Steps {=|are|is} preconditioning_steps

Residual Norm Scaling {=|are|is} AztecResidualNormScaling

Residual Norm Tolerance {=|are|is} residual_norm_tolerance

Restart Iterations {=|are|is} restart_iterations

Row Ordering {=|are|is} RowOrdering

Shared Ownership Rule {=|are|is} SharedOwnershipRule

Solution Method {=|are|is} TrilinosSolverMethods

Solve Transpose {=|are|is} Option

Select Fei {=|are|is} WhichFEI

Begin Teuchos Parameter Block Teuchos Parameter Block Name

End

```

End

Summary A set of solver parameters for Trilinos equation solver.

20.3.1. Bc Enforcement

Scope: Trilinos Equation Solver

Bc Enforcement {=|are|is} *BcEnforcement*

Parameter	Value	Default
<i>BcEnforcement</i>	{exact exact_no_column_mod remove solver solver_no_column_mod}	undefined

Summary Controls the way Dirichlet BCs are enforced.

Description Valid values for this line-command are contained in the BcEnforcement enum.

20.3.2. Debug Output Level

Scope: Trilinos Equation Solver

Debug Output Level `{=|are|is}` *Level*

Parameter	Value	Default
<i>Level</i>	integer	undefined

Summary Output level for debugging. Generally 0 means no solver screen output, and higher values of this parameter correspond to more screen output.

20.3.3. Debug Output Path

Scope: Trilinos Equation Solver

Debug Output Path `{=|are|is}` *DebugOutput*

Parameter	Value	Default
<i>DebugOutput</i>	string	undefined

Summary Specify path where debug-logs and other debug output files will be placed.

20.3.4. Determine Sharing

Scope: Trilinos Equation Solver

Determine Sharing `{=|are|is}` *FeiDetermineSharing*

Parameter	Value	Default
<i>FeiDetermineSharing</i>	<code>{fei sierra}</code>	undefined

Summary Whether FEI should determine sharing internally or receive the info from Sierra.

Description By default the `Eqns::LinearSystem` class tells the fei layer which nodes are shared and which processors share them. If this option is set to on, then the fei layer internally determines the sharing info. Requires the fei layer to perform extra communication during the initialize phase.

20.3.5. Fei Error Behavior

Scope: Trilinos Equation Solver

Fei Error Behavior {=|are|is} *FeiErrorBehavior*

Parameter	Value	Default
<i>FeiErrorBehavior</i>	{abort returncode}	undefined

Summary Set FEI error behavior to abort (rather than the default which is to simply print a message and return an integer error code).

Description This is becoming less relevant starting with FEI version 2.11, as the FEI begins to adopt exception handling and abandon the antiquated int-error-code interfaces.

20.3.6. Fei Output Level

Scope: Trilinos Equation Solver

Fei Output Level {=|are|is} *FeiOutputLevels*

Parameter	Value	Default
<i>FeiOutputLevels</i>	{all brief_logs full_logs matrix_files none stats}	undefined

Summary Control the amount of output produced by FEI.

Description Output level controls the amount of debugging information (screen output, matrix/vector files and log files) produced by FEI. The *FeiOutputLevels* enum contains the valid values for this line-command. The location of files can be controlled by the 'debug output path' line-command.

20.3.7. Ilu Fill

Scope: Trilinos Equation Solver

Ilu Fill {=|are|is} *ilu_fill_level*

Parameter	Value	Default
<i>ilu_fill_level</i>	integer	undefined

Summary Fill-in parameter for incomplete factorizations.

20.3.8. Ilu Threshold

Scope: Trilinos Equation Solver

Ilu Threshold {= | are | is} *Threshold*

Parameter	Value	Default
<i>Threshold</i>	real	undefined

Summary Threshold parameter for incomplete factorizations.

20.3.9. Matrix Format

Scope: Trilinos Equation Solver

Matrix Format {= | are | is} *MatrixFormat*

Parameter	Value	Default
<i>MatrixFormat</i>	{csr msr vbr}	undefined

Summary Storage format for the matrix.

Description This parameter only applies to Trilinos and Aztec.

20.3.10. Matrix Reduction

Scope: Trilinos Equation Solver

Matrix Reduction {= | are | is} *AztecReductionType*

Parameter	Value	Default
<i>AztecReductionType</i>	{fei-remove-slaves}	undefined

Summary Remove constraint equations from matrix.

Description Dependent degrees of freedom in constraints are projected out of the equation space, yielding a linear system with smaller dimension, and retaining positive definiteness (whereas the alternative, an augmented matrix arising from the lagrange multiplier formulation, is indefinite).

20.3.11. Matrix Scaling

Scope: Trilinos Equation Solver

Matrix Scaling {=|are|is} *MatrixScaling*

Parameter	Value	Default
<i>MatrixScaling</i>	{block-jacobi jacobi none row-sum symmetric-diagonal symmetric-row-sum user supplied}	undefined

Summary Scaling to be applied to the matrix.

Description Matrix scaling is a pre-solve operation, typically modifying the matrix in place, whereas preconditioning is performed at each iteration during the solve and doesn't modify the actual matrix.

20.3.12. Matrix Viewer

Scope: Trilinos Equation Solver

Matrix Viewer {=|are|is} *Machine:port*

Parameter	Value	Default
<i>Machine:port</i>	string	undefined

Summary Host and port-number where matvis is running.

20.3.13. Maximum Iterations

Scope: Trilinos Equation Solver

Maximum Iterations {=|are|is} *max_iterations*

Parameter	Value	Default
<i>max_iterations</i>	integer	undefined

Summary Maximum number of solution method iterations.

20.3.14. Num Levels

Scope: Trilinos Equation Solver

Num Levels {=|are|is} *Num_levels*

Parameter	Value	Default
<i>Num_levels</i>	integer	undefined

Summary Number of levels for multi-level/multi-grid solvers.

20.3.15. Param-Bool

Scope: Trilinos Equation Solver

Param-Bool *Parameter_name* Value *Bool*

Parameter	Value	Default
<i>Parameter_name</i>	"string"	undefined
<i>Bool</i>	{false true}	undefined

Summary String-Key/Boolean-Value pair to be passed to solver.

Description Syntax: 'PARAM-BOOL "some-name" VALUE true | false'

20.3.16. Param-Int

Scope: Trilinos Equation Solver

Param-Int *Parameter_name* Value *integer_value*

Parameter	Value	Default
<i>Parameter_name</i>	"string"	undefined
<i>integer_value</i>	integer	undefined

Summary String-Key/Integer-Value pair to be passed to solver.

Description Syntax: 'PARAM-INT "some-name" VALUE 123' Primarily used for passing values to the ML package. ML has a large number of parameters which haven't been individually incorporated into our parameter-parsing system. Can also be used to pass parameters to Aztec, e.g.:

PARAM-REAL "AZ_ilut_fill" VALUE 3

20.3.17. Param-Real

Scope: Trilinos Equation Solver

Param-Real *Parameter_name* Value *Real_value*

Parameter	Value	Default
<i>Parameter_name</i>	"string"	undefined
<i>Real_value</i>	real	undefined

Summary String-Key/Real-Value pair to be passed to solver.

Description Syntax: 'PARAM-REAL "some-name" VALUE 1.23' Primarily used for passing values to the ML package. ML has a large number of parameters which haven't been individually incorporated into our parameter-parsing system. Can also be used to pass parameters to Aztec, e.g.:

PARAM-REAL "AZ_drop" VALUE 1.e-8

20.3.18. Param-String

Scope: Trilinos Equation Solver

Param-String *Parameter_name* Value *String_value*

Parameter	Value	Default
<i>Parameter_name</i>	"string"	undefined
<i>String_value</i>	"string"	undefined

Summary Key/Value string-pair to be passed to solver.

Description Syntax: 'PARAM-STRING "some-name" VALUE "some-value"' (Primarily used for passing values to the ML package. ML has a large number of parameters which haven't been individually incorporated into our parameter-parsing system.)

20.3.19. Polynomial Order

Scope: Trilinos Equation Solver

Polynomial Order {=|are|is} *polynomial_order*

Parameter	Value	Default
<i>polynomial_order</i>	integer	undefined

Summary Polynomial order of preconditioning method.

20.3.20. Preconditioner Subdomain Overlap

Scope: Trilinos Equation Solver

Preconditioner Subdomain Overlap {=|are|is} *Overlap*

Parameter	Value	Default
<i>Overlap</i>	integer	undefined

Summary Overlap of Schwarz subdomains (eg, 0,1 or 2).

20.3.21. Preconditioning Method

Scope: Trilinos Equation Solver

Preconditioning Method {=|are|is} *TrilinosPrecondMethods*

Parameter	Value	Default
<i>TrilinosPrecondMethods</i>	{dd-bilu dd-icc dd-ilu dd-ilut dd-lu dd-rilu jacobi least-squares multilevel neumann none}	undefined

Summary Selection of the preconditioning method.

Description Valid values for this are contained in the TrilinosPrecondMethods enum.

20.3.22. Preconditioning Steps

Scope: Trilinos Equation Solver

Preconditioning Steps {=|are|is} *preconditioning_steps*

Parameter	Value	Default
<i>preconditioning_steps</i>	integer	undefined

Summary Number of Jacobi, Gauss-Seidel, or other preconditioning methods' applications per iteration.

20.3.23. Residual Norm Scaling

Scope: Trilinos Equation Solver

Residual Norm Scaling {=|are|is} *AztecResidualNormScaling*

Parameter	Value	Default
<i>AztecResidualNormScaling</i>	{anorm none r0 rhs}	undefined

Summary Scaling method for the residual norm.

Description Determines the residual expression used in convergence checks and printing.

20.3.24. Residual Norm Tolerance

Scope: Trilinos Equation Solver

Residual Norm Tolerance {=|are|is} *residual_norm_tolerance*

Parameter	Value	Default
<i>residual_norm_tolerance</i>	real	undefined

Summary Iterative solution method relative residual convergence tolerance.

20.3.25. Restart Iterations

Scope: Trilinos Equation Solver

Restart Iterations {=|are|is} *restart_iterations*

Parameter	Value	Default
<i>restart_iterations</i>	integer	undefined

Summary Number of iterations between GMRES restarts.

20.3.26. Row Ordering

Scope: Trilinos Equation Solver

Row Ordering {=|are|is} *RowOrdering*

Parameter	Value	Default
<i>RowOrdering</i>	{rows_with_local_cols_first}	undefined

Summary Specify that rows with only local columns should come first in the ordering.

20.3.27. Shared Ownership Rule

Scope: Trilinos Equation Solver

Shared Ownership Rule {=|are|is} *SharedOwnershipRule*

Parameter	Value	Default
<i>SharedOwnershipRule</i>	{low-numbered-proc proc-with-local-elem sierra_specifies}	undefined

Summary Controls the way owning processors are chosen for shared nodes in the FEL.

Description 'low-numbered-proc' is the default.

 'proc-with-local-elem' is another valid value.

 'sierra_specifies' is the other valid value

20.3.28. Solution Method

Scope: Trilinos Equation Solver

Solution Method `{=|are|is}` *TrilinosSolverMethods*

Parameter	Value	Default
<i>TrilinosSolverMethods</i>	{amesos-klu amesos-superlu amesos-umfpack bicgstab cg cgs gmres lu tfqmr}	undefined

Summary Selection of the linear-system solution algorithm.

Description The TrilinosSolverMethods enum contains valid values for this line-command. There are several iterative methods (Krylov subspace algorithms), as well as some sparse direct methods available through the Amesos interface package. At this time (Oct'05) not all of the listed direct solvers are available. See the specific entries in the TrilinosSolverMethods enum below for more information.

20.3.29. Solve Transpose

Scope: Trilinos Equation Solver

Solve Transpose `{=|are|is}` *Option*

Parameter	Value	Default
<i>Option</i>	string	undefined

Summary Whether to solve for transpose of system matrix.

20.3.30. Select Fei

Scope: Trilinos Equation Solver

Select Fei `{=|are|is}` *WhichFEI*

Parameter	Value	Default
<i>WhichFEI</i>	{new old}	undefined

Summary Selection of old vs new fei.

Description This parameter will be deprecated, it is used as a transition aid during some FEI refactoring.

20.4. AZTEC EQUATION SOLVER

Scope: Sierra

Begin Aztec Equation Solver *Solver Name*

Bc Enforcement {=|are|is} *BcEnforcement*

Debug Output Level {=|are|is} *Level*

Debug Output Path {=|are|is} *DebugOutput*

Determine Sharing {=|are|is} *FeiDetermineSharing*

Fei Error Behavior {=|are|is} *FeiErrorBehavior*

Fei Output Level {=|are|is} *FeiOutputLevels*

Ilu Fill {=|are|is} *ilu_fill_level*

Ilu Omega {=|are|is} *Value*

Ilu Threshold {=|are|is} *Threshold*

Matrix Format {=|are|is} *MatrixFormat*

Matrix Reduction {=|are|is} *AztecReductionType*

Matrix Scaling {=|are|is} *MatrixScaling*

Matrix Viewer {=|are|is} *Machine:port*

Maximum Iterations {=|are|is} *max_iterations*

Num Levels {=|are|is} *Num_levels*

Orthog Method {=|are|is} *OrthogMethod*

Param-Int *Parameter_name* Value *integer_value*

Param-Real *Parameter_name* Value *Real_value*

Param-String *Parameter_name* Value *String_value*

Polynomial Order {=|are|is} *polynomial_order*

Preconditioner Subdomain Overlap {=|are|is} *Overlap*

Preconditioning Method {=|are|is} *AztecPrecondMethods*

Preconditioning Steps {=|are|is} *preconditioning_steps*

Residual Norm Scaling {=|are|is} *AztecResidualNormScaling*

Residual Norm Tolerance {=|are|is} *residual_norm_tolerance*

Restart Iterations {=|are|is} *restart_iterations*

Shared Ownership Rule {=|are|is} *SharedOwnershipRule*

Solution Method {=|are|is} *AztecSolverMethods*

Select Fei {=|are|is} *WhichFEI*

End

Summary A set of solver parameters for Aztec equation solver.

20.4.1. Bc Enforcement

Scope: Aztec Equation Solver

Bc Enforcement {=|are|is} *BcEnforcement*

Parameter	Value	Default
<i>BcEnforcement</i>	{exact exact_no_column_mod remove solver solver_no_column_mod}	undefined

Summary Controls the way Dirichlet BCs are enforced.

Description Valid values for this line-command are contained in the BcEnforcement enum.

20.4.2. Debug Output Level

Scope: Aztec Equation Solver

Debug Output Level {=|are|is} *Level*

Parameter	Value	Default
<i>Level</i>	integer	undefined

Summary Output level for debugging. Generally 0 means no solver screen output, and higher values of this parameter correspond to more screen output.

20.4.3. Debug Output Path

Scope: Aztec Equation Solver

Debug Output Path {=|are|is} *DebugOutput*

Parameter	Value	Default
<i>DebugOutput</i>	string	undefined

Summary Specify path where debug-logs and other debug output files will be placed.

20.4.4. Determine Sharing

Scope: Aztec Equation Solver

Determine Sharing {= | are | is} *FeiDetermineSharing*

Parameter	Value	Default
<i>FeiDetermineSharing</i>	{fei sierra}	undefined

Summary Whether FEI should determine sharing internally or receive the info from Sierra.

Description By default the Eqns::LinearSystem class tells the fei layer which nodes are shared and which processors share them. If this option is set to on, then the fei layer internally determines the sharing info. Requires the fei layer to perform extra communication during the intialize phase.

20.4.5. Fei Error Behavior

Scope: Aztec Equation Solver

Fei Error Behavior {= | are | is} *FeiErrorBehavior*

Parameter	Value	Default
<i>FeiErrorBehavior</i>	{abort returncode}	undefined

Summary Set FEI error behavior to abort (rather than the default which is to simply print a message and return an integer error code).

Description This is becoming less relevant starting with FEI version 2.11, as the FEI begins to adopt exception handling and abandon the antiquated int-error-code interfaces.

20.4.6. Fei Output Level

Scope: Aztec Equation Solver

Fei Output Level {= | are | is} *FeiOutputLevels*

Parameter	Value	Default
<i>FeiOutputLevels</i>	{all brief_logs full_logs matrix_files none stats}	undefined

Summary Control the amount of output produced by FEI.

Description Output level controls the amount of debugging information (screen output, matrix/vector files and log files) produced by FEI. The FeiOutputLevels enum contains the valid values for this line-command. The location of files can be controlled by the 'debug output path' line-command.

20.4.7. Ilu Fill

Scope: Aztec Equation Solver

Ilu Fill {=|are|is} *ilu_fill_level*

Parameter	Value	Default
<i>ilu_fill_level</i>	integer	undefined

Summary Fill-in parameter for incomplete factorizations.

20.4.8. Ilu Omega

Scope: Aztec Equation Solver

Ilu Omega {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Omega parameter, dd-rilu uses ILU(k,w), w==omega

20.4.9. Ilu Threshold

Scope: Aztec Equation Solver

Ilu Threshold {=|are|is} *Threashold*

Parameter	Value	Default
<i>Threashold</i>	real	undefined

Summary Threshold parameter for incomplete factorizations.

20.4.10. Matrix Format

Scope: Aztec Equation Solver

Matrix Format {=|are|is} *MatrixFormat*

Parameter	Value	Default
<i>MatrixFormat</i>	{csr msr vbr}	undefined

Summary Storage format for the matrix.

Description This parameter only applies to Trilinos and Aztec.

20.4.11. Matrix Reduction

Scope: Aztec Equation Solver

Matrix Reduction `{=|are|is}` *AztecReductionType*

Parameter	Value	Default
<i>AztecReductionType</i>	<code>{fei-remove-slaves}</code>	undefined

Summary Remove constraint equations from matrix.

Description Dependent degrees of freedom in constraints are projected out of the equation space, yielding a linear system with smaller dimension, and retaining positive definiteness (whereas the alternative, an augmented matrix arising from the lagrange multiplier formulation, is indefinite).

20.4.12. Matrix Scaling

Scope: Aztec Equation Solver

Matrix Scaling `{=|are|is}` *MatrixScaling*

Parameter	Value	Default
<i>MatrixScaling</i>	<code>{block-jacobi jacobi none row-sum symmetric-diagonal symmetric-row-sum user supplied}</code>	undefined

Summary Scaling to be applied to the matrix.

Description Matrix scaling is a pre-solve operation, typically modifying the matrix in place, whereas preconditioning is performed at each iteration during the solve and doesn't modify the actual matrix.

20.4.13. Matrix Viewer

Scope: Aztec Equation Solver

Matrix Viewer `{=|are|is}` *Machine:port*

Parameter	Value	Default
<i>Machine:port</i>	string	undefined

Summary Host and port-number where matvis is running.

20.4.14. Maximum Iterations

Scope: Aztec Equation Solver

Maximum Iterations {=|are|is} *max_iterations*

Parameter	Value	Default
<i>max_iterations</i>	integer	undefined

Summary Maximum number of solution method iterations.

20.4.15. Num Levels

Scope: Aztec Equation Solver

Num Levels {=|are|is} *Num_levels*

Parameter	Value	Default
<i>Num_levels</i>	integer	undefined

Summary Number of levels for multi-level/multi-grid solvers.

20.4.16. Orthog Method

Scope: Aztec Equation Solver

Orthog Method {=|are|is} *OrthogMethod*

Parameter	Value	Default
<i>OrthogMethod</i>	{classical modified}	undefined

Summary User can choose orthogonalization method used by Aztec GMRES.

Description Valid values for this line-command are contained in the OrthogMethod enum.

20.4.17. Param-Int

Scope: Aztec Equation Solver

Param-Int *Parameter_name* Value *integer_value*

Parameter	Value	Default
<i>Parameter_name</i>	"string"	undefined
<i>integer_value</i>	integer	undefined

Summary String-Key/Integer-Value pair to be passed to solver.

Description Syntax: 'PARAM-INT "some-name" VALUE 123' Primarily used for passing values to the ML package. ML has a large number of parameters which haven't been individually incorporated into our parameter-parsing system. Can also be used to pass parameters to Aztec, e.g.:

```
PARAM-REAL "AZ_ilut_fill" VALUE 3
```

20.4.18. Param-Real

Scope: Aztec Equation Solver

Param-Real *Parameter_name* Value *Real_value*

Parameter	Value	Default
<i>Parameter_name</i>	"string"	undefined
<i>Real_value</i>	real	undefined

Summary String-Key/Real-Value pair to be passed to solver.

Description Syntax: 'PARAM-REAL "some-name" VALUE 1.23' Primarily used for passing values to the ML package. ML has a large number of parameters which haven't been individually incorporated into our parameter-parsing system. Can also be used to pass parameters to Aztec, e.g.:

```
PARAM-REAL "AZ_drop" VALUE 1.e-8
```

20.4.19. Param-String

Scope: Aztec Equation Solver

Param-String *Parameter_name* Value *String_value*

Parameter	Value	Default
<i>Parameter_name</i>	"string"	undefined
<i>String_value</i>	"string"	undefined

Summary Key/Value string-pair to be passed to solver.

Description Syntax: 'PARAM-STRING "some-name" VALUE "some-value"' (Primarily used for passing values to the ML package. ML has a large number of parameters which haven't been individually incorporated into our parameter-parsing system.)

20.4.20. Polynomial Order

Scope: Aztec Equation Solver

Polynomial Order {=|are|is} *polynomial_order*

Parameter	Value	Default
<i>polynomial_order</i>	integer	undefined

Summary Polynomial order of preconditioning method.

20.4.21. Preconditioner Subdomain Overlap

Scope: Aztec Equation Solver

Preconditioner Subdomain Overlap {=|are|is} *Overlap*

Parameter	Value	Default
<i>Overlap</i>	integer	undefined

Summary Overlap of Schwarz subdomains (eg, 0,1 or 2).

20.4.22. Preconditioning Method

Scope: Aztec Equation Solver

Preconditioning Method {=|are|is} *AztecPrecondMethods*

Parameter	Value	Default
<i>AztecPrecondMethods</i>	{dd-bilu dd-icc dd-ilu dd-ilut dd-lu dd-rilu jacobi least-squares neumann none symmetric-gauss-seidel}	undefined

Summary Selection of the equation preconditioning method.

Description Valid values for this are contained in the AztecPrecondMethods enum.

20.4.23. Preconditioning Steps

Scope: Aztec Equation Solver

Preconditioning Steps {=|are|is} *preconditioning_steps*

Parameter	Value	Default
<i>preconditioning_steps</i>	integer	undefined

Summary Number of Jacobi, Gauss-Seidel, or other preconditioning methods' applications per iteration.

20.4.24. Residual Norm Scaling

Scope: Aztec Equation Solver

Residual Norm Scaling {=|are|is} *AztecResidualNormScaling*

Parameter	Value	Default
<i>AztecResidualNormScaling</i>	{anorm none r0 rhs}	undefined

Summary Scaling method for the residual norm.

Description Determines the residual expression used in convergence checks and printing.

20.4.25. Residual Norm Tolerance

Scope: Aztec Equation Solver

Residual Norm Tolerance {=|are|is} *residual_norm_tolerance*

Parameter	Value	Default
<i>residual_norm_tolerance</i>	real	undefined

Summary Iterative solution method relative residual convergence tolerance.

20.4.26. Restart Iterations

Scope: Aztec Equation Solver

Restart Iterations {=|are|is} *restart_iterations*

Parameter	Value	Default
<i>restart_iterations</i>	integer	undefined

Summary Number of iterations between GMRES restarts.

20.4.27. Shared Ownership Rule

Scope: Aztec Equation Solver

Shared Ownership Rule {=|are|is} *SharedOwnershipRule*

Parameter	Value	Default
<i>SharedOwnershipRule</i>	{low-numbered-proc proc-with-local-elem sierra_specifies}	undefined

Summary Controls the way owning processors are chosen for shared nodes in the FEI.

Description 'low-numbered-proc' is the default.
'proc-with-local-elm' is another valid value.
'sierra_specifies' is the other valid value

20.4.28. Solution Method

Scope: Aztec Equation Solver

Solution Method {=|are|is} *AztecSolverMethods*

Parameter	Value	Default
<i>AztecSolverMethods</i>	{bicgstab cg cgs gmres lu tfqmr}	undefined

Summary Selection of the linear-system solution algorithm.

Description The AztecSolverMethods enum contains valid values for this line-command. They are mostly iterative methods (Krylov subspace algorithms), except for 'lu' which is a serial direct solver provided by the 'Y12M' library.

20.4.29. Select Fei

Scope: Aztec Equation Solver

Select Fei {=|are|is} *WhichFEI*

Parameter	Value	Default
<i>WhichFEI</i>	{new old}	undefined

Summary Selection of old vs new fei.

Description This parameter will be deprecated, it is used as a transition aid during some FEI refactoring.

20.5. GDSW EQUATION SOLVER

Scope: Sierra

Begin Gdsw Equation Solver *Solver Name*

Debug Output Level {=|are|is} *Level*

Debug Output Path {=|are|is} *DebugOutput*

Fei Error Behavior {=|are|is} *FeiErrorBehavior*

Fei Output Level {=|are|is} *FeiOutputLevels*

Gdsw Version {=|are|is} *gdsw_version*

Maximum Iterations {=|are|is} *max_iterations*

Param-Int *Parameter_name* Value *integer_value*

Param-Real *Parameter_name* Value *Real_value*

Param-String *Parameter_name* Value *String_value*

Residual Norm Tolerance {=|are|is} *residual_norm_tolerance*

End

Summary A set of solver parameters for GDSW equation solver.

20.5.1. Debug Output Level

Scope: Gdsw Equation Solver

Debug Output Level {=|are|is} *Level*

Parameter	Value	Default
<i>Level</i>	integer	undefined

Summary Output level for debugging. Generally 0 means no solver screen output, and higher values of this parameter correspond to more screen output.

20.5.2. Debug Output Path

Scope: Gdsw Equation Solver

Debug Output Path {=|are|is} *DebugOutput*

Parameter	Value	Default
<i>DebugOutput</i>	string	undefined

Summary Specify path where debug-logs and other debug output files will be placed.

20.5.3. Fei Error Behavior

Scope: Gdsw Equation Solver

Fei Error Behavior {=|are|is} *FeiErrorBehavior*

Parameter	Value	Default
<i>FeiErrorBehavior</i>	{abort returncode}	undefined

Summary Set FEI error behavior to abort (rather than the default which is to simply print a message and return an integer error code).

Description This is becoming less relevant starting with FEI version 2.11, as the FEI begins to adopt exception handling and abandon the antiquated int-error-code interfaces.

20.5.4. Fei Output Level

Scope: Gdsw Equation Solver

Fei Output Level {=|are|is} *FeiOutputLevels*

Parameter	Value	Default
<i>FeiOutputLevels</i>	{all brief_logs full_logs matrix_files none stats}	undefined

Summary Control the amount of output produced by FEI.

Description Output level controls the amount of debugging information (screen output, matrix/vector files and log files) produced by FEI. The *FeiOutputLevels* enum contains the valid values for this line-command. The location of files can be controlled by the 'debug output path' line-command.

20.5.5. Gdsw Version

Scope: Gdsw Equation Solver

Gdsw Version {=|are|is} *gdsw_version*

Parameter	Value	Default
<i>gdsw_version</i>	integer	undefined

Summary This is the version of the GDSW solver (either 1 or 2).

20.5.6. Maximum Iterations

Scope: Gdsw Equation Solver

Maximum Iterations {=|are|is} *max_iterations*

Parameter	Value	Default
<i>max_iterations</i>	integer	undefined

Summary Maximum number of solution method iterations.

20.5.7. Param-Int

Scope: Gdsw Equation Solver

Param-Int *Parameter_name* Value *integer_value*

Parameter	Value	Default
<i>Parameter_name</i>	"string"	undefined
<i>integer_value</i>	integer	undefined

Summary String-Key/Integer-Value pair to be passed to solver.

Description Syntax: 'PARAM-INT "some-name" VALUE *i23*' Primarily used for passing values to the ML package. ML has a large number of parameters which haven't been individually incorporated into our parameter-parsing system. Can also be used to pass parameters to Aztec, e.g.:

PARAM-REAL "AZ_ilut_fill" VALUE 3

20.5.8. Param-Real

Scope: Gdsw Equation Solver

Param-Real *Parameter_name* Value *Real_value*

Parameter	Value	Default
<i>Parameter_name</i>	"string"	undefined
<i>Real_value</i>	real	undefined

Summary String-Key/Real-Value pair to be passed to solver.

Description Syntax: 'PARAM-REAL "some-name" VALUE *i.e23*' Primarily used for passing values to the ML package. ML has a large number of parameters which haven't been individually incorporated into our parameter-parsing system. Can also be used to pass parameters to Aztec, e.g.:

PARAM-REAL "AZ_drop" VALUE *i.e-8*

20.5.9. Param-String

Scope: Gdsw Equation Solver

Param-String *Parameter_name* Value *String_value*

Parameter	Value	Default
<i>Parameter_name</i>	"string"	undefined
<i>String_value</i>	"string"	undefined

Summary Key/Value string-pair to be passed to solver.

Description Syntax: 'PARAM-STRING "some-name" VALUE "some-value"' (Primarily used for passing values to the ML package. ML has a large number of parameters which haven't been individually incorporated into our parameter-parsing system.)

20.5.10. Residual Norm Tolerance

Scope: Gdsw Equation Solver

Residual Norm Tolerance {=|are|is} *residual_norm_tolerance*

Parameter	Value	Default
<i>residual_norm_tolerance</i>	real	undefined

Summary Iterative solution method relative residual convergence tolerance.

21. POSTPROCESSING OPERATIONS

21.1. OVERVIEW

Aria supports postprocessing of solution information partially through Aria itself and alternatively through the Encore library [34]. Native postprocessing through Aria is invoked using a single command line, for example:

```
Postprocess density on block_1
```

This creates a Field variable "pp->density" that is available for output from the Results Output Command Block 25.1. Any expression created during the calculation may be "POSTPROCESS"ed. Of particular interest are properties defined in the material block input 4 and source terms present for any equation. In addition single components of any tensor quantity can be postprocessed by appending the suffix for the desired component (e.g. "_XX", "_XY", etc.) to the end of the expression name used in the "Postprocess" line command. Similarly, the Frobenius norm of a tensor may be postprocessed by using the "_NORM" suffix.

In addition to the *pp* postprocessing command another means of postprocessing called *Solution Options* is also available. Whereas *pp* can be used for material parameters, the use of *Solution Options* usually implies that the postprocessing variable is the result of an algorithmic computation. Use of postprocessing will follow two distinct patterns, depending upon whether or not Equation Systems 17.1 are employed in the simulation.

When Equation Systems are not being used then within the input file postprocessing command lines will appear at the Region scope as illustrated below.

```
.
Begin Procedure My_Aria_Procedure
.
  Begin Aria Region My_Region
  .
    postprocess ENERGY_SOURCE on block_2
  .
    Begin Solution Options
    .
      post process nodal normalized HEAT_TRANSFER_COEFFICIENT on surface_5 as h5
    .
  .
.
```

```

    End Solution Options
.
End Aria Region My_Region
.
End Procedure My_Aria_Procedure
.

```

When Equation Systems are being used in a simulation then postprocessing command lines must appear within scope of the Equation System in which the quantities to be postprocessed are available/computed. As an example, a convective flux boundary condition may lie within an Equation System Energy hence postprocessing of the heat transfer coefficient would be defined within that scope.

When using postprocessing commands specific to *solution options* the SOLUTION OPTIONS command block must appear at the region scope. Once the Solution Options command block is present then individual solution options commands can appear within the appropriate Equation System. As an example suppose one wishes to include a general specification of quantities generally defined for the entire simulation, i.e. mass and volume, as well as a normalized heat transfer coefficient. Here mass and volume are processed at processed at the Region scope and the heat transfer postprocessing is done at Equation System scope as illustrated below.

```

.
Begin Procedure My_Aria_Procedure
.
Begin Aria Region My_Region
.
Begin Equation System Energy
.
    postprocess ENERGY_SOURCE on block_2
.
    # no Begin Solution Options required
    post process nodal normalized HEAT_TRANSFER_COEFFICIENT on surface_5 as h5
.
End Equation System Energy
.
Begin Solution Options
.
    post process volume
    post process mass
.
End Solution Options
End Aria Region My_Region
.
End Procedure My_Aria_Procedure
.

```

Note that for simulations with Equation Systems where physics related postprocessing is desired but no general postprocessing is required, i.e. no mass or volume calculation, the Begin Solution Options command block must be appear but it can be empty.

Aria postprocessing with Encore is usually accomplished using Encore specific commands [34]. Input commands for both *pp* and *solution options* postprocessing are included in what follows.

21.1.1. Postprocess

Scope:

```
Postprocess Expression [ {of|species} SpeciesName |{in|material_phase}
MaterialPhaseName ]{@|at|for|in|on|over} MeshPartIdentifier [ Using
ElementType |Averaging Method {=|are|is} AveragingMethod ]
```

Parameter	Value	Default
<i>Expression</i>	string	undefined
<i>SpeciesName</i>	string	undefined
<i>MaterialPhaseName</i>	string	undefined
<i>MeshPartIdentifier</i>	string	undefined
<i>ElementType</i>	string	undefined
<i>AveragingMethod</i>	{simple support_averaged support_weighted}	undefined

Summary Postprocess Expression on a mesh part (block, surface, etc.). By default, the quantity is computed on the grid element nodes. If the optional arguments "using ElementType" are provided, the postprocessed field will be computed on that element. If the ElementType is Po then the quantity is computed as a constant element value. By default the nodal field value is calculated using a weighted average of the value in each element at the node location where the element contributions are weighted by $\int w_{node} d\Omega$, This is the SUPPORT_WEIGHTED averaging method. Two alternative averaging methods are available. SUPPORT_AVERAGED integrates $\int \phi w_{node} d\Omega$ (where ϕ is the expression being postprocessed) over all supporting elements and normalizes by $\int w_{node} d\Omega$ over all supporting elements. SIMPLE just takes the mean of the element values at the node location.

21.2. SOLUTION OPTIONS

Scope: Aria Region

Begin Solution Options *OptionsName*

Check Matrix For Discrete Maximum Principle

Post Process *PostProcessType* *VariableName* On *IoPartList...* As *OutputName* [Using *WeightList...* *Weight*]

Post Process Flux *fluxName* On *ioPartList...* As *outputName* [Restricted To *restrictPartList...*]

Post Process Mass

Post Process Nodal *PostProcessType* *VariableName* On *IoPartList...* As *OutputName* [Using *WeightList...* *Weight*]

Post Process Volume

Begin Cvfem Algorithm Specification *PStabName*

End

Begin Edc Model Specification *EdcSpecName*

End

Begin Hdiff Model Specification *HdiffOptionsName*

End

Begin Porous Flow Options *blockName*

End

Begin Species Options *blockName*

End

Begin Turbulence Model Specification *TurbSpecName*

End

End

Summary Specify information regarding the governing equations to be solved.

21.2.1. Check Matrix For Discrete Maximum Principle

Scope: Solution Options

Summary Examine rows of the system matrix before boundary conditions are applied and check if the diagonal entries are non-negative, the off-diagonal entries are non-positive, the row-sum is non-negative. If these conditions fail, it is possible the solution will contain non-physical values, and the discrete maximum principle is not satisfied by the matrix. If any of these conditions fail, a warning is printed to the log file. More output can be obtained with turning on debug logging.

21.2.2. Post Process

Scope: Solution Options

```
Post Process PostProcessType VariableName On IoPartList... As OutputName [  
Using WeightList... Weight ]
```

Parameter	Value	Default
<i>PostProcessType</i>	{integral normalized}	undefined
<i>VariableName</i>	string	undefined
<i>IoPartList</i>	string...	undefined
<i>OutputName</i>	string	undefined

Summary Post process an Aria variable and save it to a global variable.

Description Post process Aria variable *VariableName* and save it to a global variable *OutputName*. The global *OutputName* will be written to the log file and is also available for output to an ExodusII database. During post processing the variable a product is formed from *VariableName* and the evaluation of *WeightList* items. The keyword WEIGHT terminates the Weightlist items.

21.2.3. Post Process Flux

Scope: Solution Options

```
Post Process Flux fluxName On ioPartList... As outputName [ Restricted To  
restrictPartList... ]
```

Parameter	Value	Default
<i>fluxName</i>	string	undefined
<i>ioPartList</i>	string...	undefined
<i>outputName</i>	string	undefined

Summary Post process an Aria flux and save the integrated results to a global Aria Field.

Description Post process Aria flux *FluxName* and save the integrated flux to a global Field variable *OutputName*. The resultant variable *OutputName* will be available for output to an ExodusII database. Examples of *FluxName* are heat_conduction and current_density.

21.2.4. Post Process Mass

Scope: Solution Options

Summary Post process both the total mass for all blocks and per-block mass. By default these values will be output to log file.

Additionally these values are available as global variables which can be output to the ExodusII database. Naming convention of these values are TOTAL_MASS for the aggregate mass and MASS_mesh_entity_name (e.g. MASS_BLOCK_1) for individual blocks.

21.2.5. Post Process Nodal

Scope: Solution Options

Post Process Nodal *PostProcessType* *VariableName* On *IoPartList...* As *OutputName* [Using *WeightList...* *Weight*]

Parameter	Value	Default
<i>PostProcessType</i>	{integral normalized}	undefined
<i>VariableName</i>	string	undefined
<i>IoPartList</i>	string...	undefined
<i>OutputName</i>	string	undefined

Summary Post process an Aria nodal variable and save the results to another Aria Field.

Description Post process Aria variable *VariableName* and save it to another nodal Field variable *OutputName*. The resultant variable *OutputName* will be available for output to an ExodusII database. *PostProcessType* is NORMALIZED so that during post processing the variable a product is formed from *VariableName* and the evaluation of *WeightList* items. The keyword WEIGHT terminates the Weightlist items.

21.2.6. Post Process Volume

Scope: Solution Options

Summary Post process both the total volume and and per-block volume. By default these values will be output to log file.

Additionally these values are available as global variables which can be output to the ExodusII database. Naming convention of these values are TOTAL_VOLUME for the aggregate volume and VOLUME_mesh_entity_name (e.g. VOLUME_BLOCK_1) for individual blocks.

21.3. RESIDUAL BASED INTEGRATED SURFACE FLUX CALCULATIONS

Oftentimes one needs to require the evaluation of surface flux over some portion of the problem domain. Examples of such evaluations include the net thermal energy through a surface or the net force on a body. While the evaluation can be carried out in a variety of ways one method of carrying out an accurate evaluation of these quantities is to employ a residual approach. The general approach is described here for problems involving scalar variables but the technique applies equally as well to vector variables.

Governing partial differential equations for scalar potential u are often of the form

$$C \frac{Du}{Dt} = \nabla \cdot \mathbf{q} + Q \quad (21.1)$$

where C is storage coefficient, $\mathbf{q}$ is the flux of u , Q is a volumetric source and the substantial derivative $D()/Dt$ accounts for material motion. The flux of u is oftentimes a simple function of the potential gradient

$$\mathbf{q} = -k \nabla u \quad (21.2)$$

where k is a diffusion tensor. In many cases k is isotropic so it is treated as a constant coefficient.

To obtain solutions of scalar PDE (21.1) using finite elements, one forms a weighted residual over a spatial discretization of elements of the problem domain Γ . Integration by parts, then yields a general form of the nodal residual

$$R^i = \int_{\Omega} \left[\left(C \frac{Du}{Dt} - Q \right) \phi^i - \mathbf{q} \cdot \nabla \phi^i \right] d\Omega + \int_{\Gamma} \mathbf{n} \cdot \mathbf{q} \phi^i d\Gamma \quad (21.3)$$

where i denotes a node of the meshed discretization, ϕ^i is the finite element weight function for node i . The collection of nodal residual equations over Ω form a linear system of equations for which we seek to minimize the nodal residuals, $R^i = 0$ over the solution domain.

Dirichlet boundary conditions on (21.3) for specific nodes can be eliminated from the system and the unknown temperature is assigned directly. For flux boundary conditions, the term $\mathbf{n} \cdot \mathbf{q}$ is replaced with a model of the surface normal flux. Surface contact boundary conditions can also be accounted for through a special implementation of this surface integral as outlined in the Aria user manual.

In some problems there is need of computing the surface flux f_n over a subset of the domain boundary Γ and one might consider evaluating

$$f_n = \int_{\Gamma_n} \mathbf{n} \cdot \mathbf{q} d\Gamma_n \quad (21.4)$$

This approach requires the evaluation of finite element gradients on element boundaries as per (21.2) but is known to be problematic since gradients of the finite element solutions in terms of the basis

functions ϕ^i are of lower order than the finite element solution. An alternative is to evaluate the flux over Γ_n using the volumetric term of (21.3)

$$f_n^i = - \int_{\Omega_n} \left[\left(C \frac{Du}{Dt} - Q \right) \phi^i - \mathbf{q} \cdot \nabla \phi^i \right] d\Omega_n \quad (21.5)$$

which must be computed while forming the linear system of equations and is known to be second order accurate. Note that f^i is the integrated surface flux contribution at a node, not a flux per unit area. The area over which f_n^i is computed is of course mesh dependent and is given by the finite element support for node i .

In order to obtain the nodal flux (21.5), we proceed with our typical FEM assembly procedure in the evaluation of (21.3) where the volume and surface contributions are handled in separate portions of the code. Using the `Save Residuals = Before_BCs` input command line in Aria, we request that intermediate values of the residuals be stored after the volumetric terms are calculated but before the surface contributions are computed. These integrated nodal flux values are stored in a field named `residual->dof_name`, where `dof_name` corresponds to the solution variable u for a given equation.

The total flux along a portion of the boundary Γ_n is obtained by summing the residual values for all nodes along the surface

$$f_n = - \sum_{i \in \Gamma_n} - \int_{\Omega_n} \left[\left(C \frac{Du}{Dt} - Q \right) \phi^i - \mathbf{q} \cdot \nabla \phi^i \right] d\Omega_n \quad (21.6)$$

Computation of the total flux over Γ_n is illustrated for the energy equation with solution variable temperature. To perform this calculation using Aria one first needs to enable the saving of residuals. In the Aria Region block we add the command line

```
Save Residuals = Before_BCs
```

This instructs Aria to store the result of (21.3) in a field named `residual->temperature`. Next, to perform the summation in (21.6) on a portion of the surface, say `sideset_12` one can add an Encore summation postprocessor block at the domain scope:

```
Begin Summation Postprocessor flux_12
  Use Function residual->temperature
  Surfaces surface_12
End
```

To execute this postprocessor, one adds an additional command line to the Aria Region scope:

```
Evaluate Postprocessor flux_12
```

This will create a global variable named `flux_12` whose result will be written to the Aria log file for each successful solution step. Finally, one can output the result `flux_12` to the Exodus results output database file by adding the following line to the appropriate output block:

```
global variables = flux_12
```

Similarly the global variable can be written to the heartbeat output file by adding the line

```
variable = global flux_12
```

to the Heartbeat file command block.

21.4. POSTPROCESSING FLUX GLOBAL VARIABLES AND FIELDS ON SPECIFIED SIDESETS

In this section, an alternative method of obtaining nodal flux quantities is described. This approach uses the residual based volume assembly to provide nodal flux at surfaces as described in Section 21.3, but instead of evaluating (and re-assembling) the linear system on the entire volume mesh, we instead evaluate the underlying kernel responsible for the volume assembly of the equation system (energy, for example) on blocks touching the user specified surface. This is more economical than the

```
Save Residuals = Before_BCs
```

command, but functionally equivalent, as it only computes the volume assembly on blocks touching the specified sideset or surface (without re-assembling the linear system), as opposed to all blocks in the equation system. Additionally, there is no need to use an Encore postprocessor.

The command block is as follows

21.4.1. Postprocess

Scope:

```
Postprocess FluxReductionType {for|of} EquationName [ {of|species}  
SpeciesName ] [ {in|material_phase} MatPhase ] On IoPart As OutputName [  
Multiplier {=|are|is} Multiplier ]
```

Parameter	Value	Default
<i>FluxReductionType</i>	{averaged_flux flux_scalar_field flux_vector_field integrated_flux}	undefined
<i>EquationName</i>	string	undefined
<i>SpeciesName</i>	string	undefined
<i>MatPhase</i>	string	undefined
<i>IoPart</i>	string	undefined
<i>OutputName</i>	string	undefined

Summary Post flux quantities in Aria using the residual

Description This command allows you to postprocess flux quantities on specified sideset/surfaces. It is analogous to using the residual to calculate the flux for a specified equation system (e.g. save residuals = before_bcs), without the extra cost of re-assembly of the linear system. All flux reductions use a combination of the nodal residual and nodal area R_i and A_i respectively. The units of the residual to calculate the flux will always be the same as the time-derivative term for whatever equation system. For instance, the energy equation will be in J/s, the conservation of mass equation will have units of kg/s, momentum equation will be in units of force (Newtons), etc.

Four types of reductions are available:

INTEGRATED_FLUX - Returns a global summation of the residual $\sum_{i=0}^N R_i$ (units of flow, e.g. J/s for energy)

AVERAGED_FLUX - Returns a global averaged flux $\sum_{i=0}^N R_i / \sum_{i=0}^N A_i$ (units of flux, e.g. (J/s)/m² for energy)

FLUX_SCALAR_FIELD - Calculate a scalar field which is the flux at each node i
 $Flux_i = R_i / A_i$ (units of flux, e.g. (J/s)/m² for energy)

INTEGRATED_FLUX - Calculate a vector field which is the nodal scalar flux times the nodal surface normal (units of flux, e.g. (J/s)/m² for energy)

For example, if you want to calculate the total flow of energy (in Watts) over surface_1 and output this quantity as a global variable:

```
POSTPROCESS INTEGRATED_FLUX FOR ENERGY ON SURFACE_1 AS TOTAL_FLOW
```

This will compute the integrated flux of energy over surface_1 and output it as the global variable TOTAL_FLOW.

Other commands which may be used are:

```
POSTPROCESS AVERAGED_FLUX FOR ENERGY ON SURFACE_1 AS AVERAGED_SURFACE_FLUX
POSTPROCESS FLUX_SCALAR_FIELD FOR ENERGY ON SURFACE_1 AS ENERGY_FLUX_SCALAR_FIELD
POSTPROCESS FLUX_VECTOR_FIELD FOR ENERGY ON SURFACE_1 AS ENERGY_FLUX_VECTOR_FIELD
```

The first command will output a global variable AVERAGED_SURFACE_FLUX. The second command will output a nodal field named ENERGY_FLUX_SCALAR_FIELD which is a scalar field. The third command will output a nodal field named ENERGY_FLUX_VECTOR_FIELD which is a vector field, and has as many components as the dimension of your mesh.

For vector equations (such as fluid momentum):

```
POSTPROCESS INTEGRATED_FLUX FOR MOMENTUM ON SURFACE_1 AS TOTAL_FLOW
```

Will again calculate the integrated flux of momentum on surface_1 and output two or three global variables (corresponding to the dimensionality of your problem) as

TOTAL_FLOW_X
TOTAL_FLOW_Y
TOTAL_FLOW_Z

which corresponds to each dimension of your vector equation (in this case three-dimensional).

Note: Tensor equations are not supported for this post processor, and the FLUX_VECTOR_FIELD option is not supported for vector equations such as momentum.

22. ENCLOSURE RADIATION REFERENCE

22.1. ENCLOSURE RADIATION

Modeling of enclosure radiation requires determination of the energy transport between all surface facets that comprise the enclosure, an NXN description of global interactions. Since direct coupling the NXN problem with the Finite Element Method (FEM) would prevent an efficient solution of the FEM equations, the strategy is instead to solve the enclosure radiation and FEM independently but coupled through the boundary conditions. Here the FEM temperature is a boundary condition for the enclosure radiation problem and the enclosure radiation flux provides a boundary condition for the FEM as per 5.11. This requires that the enclosure surface temperatures from the FEM solution of the energy equation and the enclosure flux solution correspond to a state of radiative thermal equilibrium. Hence the key to setting up the enclosure radiation model is knowing that one will be solving for flux given an implicit specification of temperature by the FEM solution.

When energy radiates from one portion of a surface to another, and the intermediate medium is transparent (i.e., it does not absorb any energy), then enclosure radiation may be used to model the heat flux on the surface. Using the net radiation method [35], the normal flux at a particular location on the surface may be written as the difference between the emitted radiative heat flux leaving the surface, and the absorbed incident radiative flux due to the rest of the enclosure, namely

$$q_n = \sigma \epsilon T^4 - \alpha G, \quad (22.1)$$

where T is the temperature, α denotes the absorptivity of the surface, and G represents the surface irradiation. Under the additional assumption that the emissivity, absorptivity, and reflectivity are independent of direction and wavelength, we may write

$$\epsilon = \alpha = 1 - \rho, \quad (22.2)$$

where we have used the conventional symbol ρ for reflectivity. In this section, ρ always refers to reflectivity and not density.

Without loss of generality, we can regard the enclosure, $\Gamma_{\mathcal{E}}$, as a union of E surfaces,

$$\Gamma_{\mathcal{E}} = \Gamma_1 \cup \Gamma_2, \dots \Gamma_{E-1} \cup \Gamma_E$$

This situation is illustrated in Figure 22.1-1, where the radiosity for surface i in the enclosure is defined to be

$$J_i = \sigma \epsilon_i T_i^4 + \rho_i G_i, \quad (22.3)$$

where u_i is the spatially constant temperature on Γ_i . The surface irradiation for surface i is determined by the radiosity of all the other surfaces in the enclosure through the relation

$$G_i = \sum_{j=1}^E F_{ij} J_j, \quad (22.4)$$

where F_{ij} denotes the geometric viewfactor of surface i with respect to surface j . The viewfactor may be considered the fraction of energy that leaves surface i and arrives at surface j .




Figure 22.1-1.. Two arbitrary facets radiating energy to one another in a radiation enclosure. The energy exchanged depends on: the shape, orientation, distance, area A_i , A_j , temperatures T_i , T_j , and radiative properties of the facets ϵ_i , ϵ_j .

Upon substitution of equations (22.4) and (22.2) into (22.3), the radiosity may be written as

$$J_i - (1 - \epsilon_i) \sum_{j=1}^N F_{ij} J_j = \sigma \epsilon_i T_i^4, \quad (22.5)$$

Finally, the first J_i term in (22.5) may be moved inside the summation to yield

$$\sum_{j=1}^N [\delta_{ij} - (1 - \epsilon_i) F_{ij}] J_j = \sigma \epsilon_i T_i^4, \quad (22.6)$$

where

$$\delta_{ij} = \begin{cases} 1 & \text{if } i = j \\ 0 & \text{if } i \neq j \end{cases} \quad (22.7)$$

(22.6) is a nonlinear system of equations for the radiosities that must be solved simultaneously with (at least) the energy transport equations (see 5.3). Finally, we may rewrite (22.1) to express the normal flux boundary condition on surface i as

$$q_n = \sigma \epsilon T^4 - \epsilon G_i, \quad (22.8)$$

where G_i is given by (22.4).

22.2. ENCLOSURE RADIATION SURFACE FLUX

The enclosure radiation boundary condition given by (22.1) enters our weak statement in a manner similar to that of the surface radiation flux described in 9.2.19 The enclosure radiation flux was written as (22.1), which we repeat here for convenience:

$$q_n(T) = \sigma \epsilon T^4 - \epsilon G, \quad (22.9)$$

This flux and the surface radiation flux are both nonlinear, and vary as the fourth power of the temperature, but there are important differences. First, instead of a known reference temperature T_r , the surface irradiation, G , appears in (22.9), and must be calculated as part of the solution process. To begin, let Γ_ε^e be an arbitrary finite element on the enclosure. We call Γ_ε^e a facet, and let Γ_ε consist of a total of E facets. Furthermore, the flux (22.9) is constant on a facet; to emphasize this, let us rewrite it as

$$q_n^e(T) = \sigma \epsilon [T^e]^4 - \epsilon G_e(T^e), \quad (22.10)$$

where T^e is some average facet temperature, and $G_e(T^e)$ is the irradiation on facet e , which is determined by the combined effects of all the other facets in the enclosure. Recall that this was expressed in Section 22.1 as

$$G_e(T^e) = \sum_{f=1}^E F_{ef} J_f(T^e). \quad (22.11)$$

Details of our nonlinear solution strategy are not included here but it is important to note here that the unknown radiosities, J_f , depend upon the solution of the temperature. We use a decoupled approach, and calculate the viewfactors, F_{ef} , and radiosities, J_f , via the Chaparral library [36]. Recall that the radiosities are obtained by solving the system of equations

$$\sum_{f=1}^N [\delta_{ef} - (1 - \epsilon_e) F_{ef}] J_f = \sigma \epsilon_e [T^e]^4 \quad (22.12)$$

In (22.12), it is important to realize that the J_f and T^e are constant values associated with a given facet. But in our finite element approximation, the temperatures are associated with the nodes. Therefore, the facet temperature should be considered a projection, or averaging of the temperature found at the nodes of a given facet. Hence, we define the facet temperature as

$$T^e = \frac{\sum_{i=1}^N T_i \int_{\Gamma_\varepsilon^e} \psi_i^e d\Gamma}{\int_{\Gamma_\varepsilon^e} d\Gamma} \quad (22.13)$$

It is now convenient to define the projection vector $\mathbf{P}^e$, where row i is defined by

$$P_i^e = \frac{1}{A^e} \int_{\Gamma_\varepsilon^e} \psi_i^e d\Gamma, \quad (22.14)$$

and A^e is the area of facet e . Thus, (22.13) may be written as

$$T^e = \sum_{i=1}^N P_i^e T_i \quad (22.15)$$

22.3. SOLUTION STRATEGY

When using Newton's method one can employ the surface radiation flux 22.9 directly to obtain Jacobian and residual contributions to the linear system of equations. Solution convergence of enclosure radiation problems by successive substitution is improved by employing a linearization of the surface radiation flux as described in what follows.

Now that we have appropriately defined the facet temperature, we may linearize the flux given in (22.10). Expanding $q_n(T)$ in a Taylor series about a known state T_*^e , we obtain

$$q_n(T_* + \delta T) = \sigma \epsilon [T_*^e]^4 - \epsilon G_e(T_*^e) + 4\sigma \epsilon [T_*^e]^3 \delta T \quad (22.16)$$

where $\delta T = T^e - T_*^e$, and we have chosen to evaluate the irradiation at the known state, T_*^e . If we collect terms involving the known T_*^e and unknown T^e , (22.16) may be rearranged and written as

$$q_n(T_* + \delta T) = 4\sigma \epsilon [T_*^e]^3 T^e - 3\sigma \epsilon [T_*^e]^4 - \epsilon G_e(T_*^e) \quad (22.17)$$

In order to apply this flux in our weak statement, we must integrate it against the test function, ψ_i^e . Therefore, we have

$$\int_{\Gamma_\varepsilon^e} \psi_i^e q_n(T) d\Gamma = \int_{\Gamma_\varepsilon^e} \psi_i^e \{4\sigma \epsilon [T_*^e]^3 T^e - 3\sigma \epsilon [T_*^e]^4 - \epsilon G_e(T_*^e)\} d\Gamma \quad (22.18)$$

Exploiting the fact that all quantities on a given facet are constant, except for the shape functions, (22.18) becomes

$$\begin{aligned} \int_{\Gamma_\varepsilon^e} \psi_i^e q_n(T) d\Gamma &= \int_{\Gamma_\varepsilon^e} \psi_i^e d\Gamma \{4\sigma \epsilon [T_*^e]^3 T^e\} \\ &\quad - \int_{\Gamma_\varepsilon^e} \psi_i^e d\Gamma \{3\sigma \epsilon [T_*^e]^4 + \epsilon G_e(T_*^e)\} \end{aligned} \quad (22.19)$$

If we introduce the definitions (22.15) and (22.14) into (22.19), we see that the linearized form of the element matrix contribution is

$$K_{ij}^e = 4\sigma \epsilon [T_*^e]^3 A^e P_i^e P_j^e \quad (22.20)$$

and the contribution to the source vector is

$$F_i^e = A^e \epsilon \{3\sigma [T_*^e]^4 + G_e(T_*^e)\} P_i^e \quad (22.21)$$

We remark that, when calculating terms in Equations (22.20) and (22.21), experience has shown that it is important to project the exponential power of the temperature, as opposed to projecting the temperature, then raising it to some exponential power. In other words, spurious oscillations are less likely to occur if

$$[T^e]^4 = \sum_{i=1}^N P_i^e T_i^4$$

is used instead of

$$[T^e]^4 = \left[\sum_{i=1}^N P_i^e T_i \right]^4$$

22.4. BANDED WAVELENGTH ENCLOSURE RADIATION

The enclosure radiation model previously presented considers a net response over all wavelengths assuming that all surfaces behave as grey bodies. Here the surface response with regard to different wavelengths is implicitly included in the model by using temperature dependent emissivities and allowing the surfaces to emit as grey bodies. In this case the surface flux previously mentioned 22.1 can be alternatively expressed as

$$q_n = \int_0^{\infty} q(\lambda) d\lambda . \quad (22.22)$$

In many applications engineering materials respond differently to different portions of the thermal energy spectrum. Thus modeling the thermal radiation response of these materials using the entire blackbody spectrum results in poor characterization of the enclosure response. For this purpose more specialized approaches for radiation modeling of wavelength dependent surfaces have been developed using continuous representations of emissivity as a function of wavelength and temperature while integrating over the wavelength spectrum. For numerical modeling the simplest approach involves discretization of the wavelength spectrum into a few representative bands N_b and integrating over each of the k bands. Using this approach the methods previously described follow directly except that the emissivity and emissive power now have independent representations in a wavelength band, each of which contributes some surface flux Δq_k thus

$$q_n = \sum_{k=1}^{N_b} \Delta q_{k\lambda} . \quad (22.23)$$

Recalling that flux can also be expressed in terms of radiosity then similarly the radiosities are obtained by solving a system of equations

$$\sum_{k=1}^{N_b} \sum_{f=1}^N [\delta_{(ek)f} - (1 - \epsilon_{(ek)})F_{ef}] \Delta J_{fk} \Delta \lambda_k = \sum_{k=1}^{N_b} F_{\Delta \lambda_k T} \sigma \epsilon_{(ek)} [T^e]^4 \Delta \lambda_k \quad (22.24)$$

where ΔJ_{fk} is the incremental radiosity and $F_{\Delta \lambda_k}$ is the blackbody fraction for band k . Finally we note that given a fixed facet temperature field this solution can be carried out independently for each wavelength band and the radiosities ΔJ_{fk} can be accumulated to obtain the net facet radiosity J_f and net flux q_n . Thus the banded wavelength model very much resembles the more simplified enclosure radiation model 22.1. From a simulation point of view, the major difference being that the modeler must supply information describing the band discretization in addition to emissivity models for each band.

Construction of the banded wavelength model begins by first prescribing the emissivity variation for each surface of the enclosure as a function of wavelength λ . The overall band discretization is then obtained by collective consideration of the wavelengths at which the emissivity changes on any of the given surfaces. Thus the number of bands for the enclosure will likely be more than those for any single surface and is demonstrated in Figure 22.4-1 below. It is important to note that for each modeled band an emissivity model must be supplied for each surface, even when its emissivity is not changing.




Figure 22.4-1.. Emissivity Bands For Two-Surface Problem

22.5. ENCLOSURE RADIATION MODELING

Enclosure radiation modeling is normally performed in several steps,

- Compute the viewfactors or read in pre-computed viewfactors.
- Radiosity solve.
- Perform the coupled finite element solve.

The last step is handled implicitly once boundary conditions on the finite element model have been defined. To facilitate the first three steps the analyst must first define the enclosure. For complex enclosures smoothing (conditioning) of the viewfactors is often required to ensure the quality of the viewfactors before proceeding to the radiosity solve and a facility for performing this operation is also provided. As part of this enclosure definition details concerning both computation of viewfactors, and the radiosity solve must be included. Full details of enclosure definition, viewfactor calculation, viewfactor smoothing and radiosity solve are specified in separate input command blocks. Additional input command blocks must also be supplied in order to employ the banded-wavelength enclosure model. Individual directives appearing within the aforementioned command blocks are described in the sections which follow.

In all cases the enclosure is viewed as a closed surface. As illustrated in Figure 22.5-1 the discretization may need to be modified in order to properly define the closed surface.




Figure 22.5-1.. Discretization and Associated Closed Enclosure Surface.

For problems in which the enclosure surface is not entirely meshed, it can be implicitly closed by defining a partial enclosure and its associated properties within the enclosure definition command block. The partial enclosure is demonstrated in Figure 22.5-2. Note that the partial enclosure approach is a model simplification and is no substitute for a fully-meshed enclosure. Best results with partial enclosures are obtained when most of the enclosure model facets have the same view of the partial enclosure area and temperature.

As part of the partial enclosure description one must supply a partial enclosure area but for many problems it may be difficult to initially compute or even estimate the partial enclosure area. For these cases provision is made within Aria to internally compute the minimum area that should be used. To obtain the minimum area one temporarily assigns a small number for the partial enclosure, starts the problem and terminates it after one step. The minimum partial enclosure area can then be obtained from the .output file. Further discussion of the partial enclosure is given in a section which follows 22.5.1.




Figure 22.5-2.. Discretization and Associated Partial Enclosure Surface.

It is worth mentioning that the viewfactor between two facets is roughly proportional to $1/r^2$ where r is the distance between facet centroids. Thus it follows directly that facets which are nearly parallel may adversely affect the viewfactor calculation. Similar statements apply to poorly equivalenced surface intersections leading to slivered surfaces becoming part of an enclosure. In the worst of circumstances the viewfactor will simply fail when the distance between facets is too small and the mesh may need to be repaired.



Beta Capability: The Dash capability for automatically detecting enclosures is under active development and has some known deficiencies. It should be used with caution.

At the user's request some attempt can be made to remedy these situations by preprocessing of the surface facets to remove these defects, via an algorithm denoted as DASH. This algorithm can be applied universally to all the enclosures or to each enclosure independently. The use of DASH for the construction of enclosures is functionally equivalent to the standard prescription of surfaces except in

the case where partial enclosures are present. DASH presents a powerful mechanism for automatically generating enclosures but the user has to ensure that the problem being addressed is appropriate such as cases where the entire set of element blocks is used to generate the enclosures but the user is only interested in a subset.

One measure of how accurately the viewfactors are being computed is the rowsum value. For each surface facet in a fully-closed enclosure The rowsum value should approach one, thus the total rowsum value is always the number of facets. In cases where the target rowsum is not equal to one the surface may not be fully-closed or the view factor calculation may be inaccurate for some other reason. In either event the analyst should consider investigate possible causes of the discrepancy. The viewfactor calculation is often followed by a smoothing process which may offset some of the errors indicated by the rowsum values. Note that while use of the Dash algorithm can be useful to overcome inaccuracies, there is no substitute for repair of any mesh defects.

Spatial discretization of the enclosure consists of surfaces as illustrated in Figure 22.1-1 where the surfaces respect an inward facing normal orientation. For most cases the enclosure is devoid of interior mesh discretization. In the event that the enclosure interior is meshed, the interior mesh can be ignored by using the OMIT_VOLUME command line in the FINITE_ELEMENT_MODEL command block.



Beta Capability: Overlapping enclosures are not fully tested and are not considered to be a production capability

The objective in solving the enclosure radiation problem is to obtain flux values at the enclosure cavity surfaces for later application to the finite element model. In a special class of closed enclosure problems one may wish to superpose flux contributions from different enclosure radiation problems overlying the same surfaces as depicted in Figure 22.5-3. This situation often arises in cases where the enclosure thermal response is wavelength dependent. For any given enclosure, unique descriptions of the radiation enclosure surfaces are provided to the Chaparral library. When enclosure radiation surfaces overlap special provision must be made in order to uniquely define these surfaces for the Chaparral library. Here the distinction between surfaces is made by denoting an enclosure overlying another enclosure as an OVERLAPPING ENCLOSURE. In the example, two consistent definitions of OVERLAPPING ENCLOSURE are possible. Enclosure 2 can be denoted as the overlapping enclosure since it overlaps enclosures 1 and 3. Likewise enclosures 1 and 3 could be denoted as overlapping enclosures since they overlap Enclosure 2.

In certain simulations one might require an interior mesh to represent other coupled physics within the cavity area of the enclosure. In this case one must use the MESHED_ENCLOSURE command within the enclosure definition command block to exclude the meshed block (and its surface) from the enclosure radiation problem. For simulations in which enclosure radiation approaches the optically-thick limit one might consider utilizing a meshed enclosure in conjunction with the OPTICALLY_THICK thermal conductivity model 4.52.6 in lieu of the enclosure radiation problem.

Once a simulation has begun the enclosure radiation problem is solved for each enclosure in the order they appear in the input file. First the viewfactors are obtained, then followed by a radiosity solve for that enclosure. If any errors are encountered while resolving viewfactors or during a radiosity solve, the




Figure 22.5-3.. Superposed Radiation Enclosures.

solution is terminated with appropriate diagnostics. After all the individual enclosure radiation problems have been solved, those results are then coupled with the finite element solution. In most simulations involving enclosure radiation computation of the viewfactors represents a large portion of the overall solution time. If the same geometric model will be used for different analyses saving the viewfactors to file and reusing them is highly recommended. Code facilities for writing the viewfactor files and for reading them in are provided specifically for this purpose.

After performing a simulation the analyst will often interpret the results by post-processing of the output data. To assist in this task the analyst is able to request output of the enclosure surface flux, q_n and irradiation G of equation 22.1 as well as the radiosity J 22.3. If these variables are of interest their output can be requested by including the names RAD_FLUX, IRRADIANCE, or RADIOSITY in the results output block described in a chapter 25. When using the banded-wavelength model the flux, irradiation and radiosity can be output on each band by prefacing the names with ENCLOSURE_EID, where EID is the enclosure index (the order index corresponding to where the enclosure definition appears in the input command file). In this case the values corresponding to each band will be output. All enclosure surface output is written as face variables in 3D and edge variables in 2D. Because solution variables for the partial enclosure, RAD_FLUX, IRRADIANCE, or RADIOSITY can have some relevance, their output can also be requested. However, unlike the variables corresponding to part of the surface mesh, partial enclosure variable output is requested from the enclosure definition command block and is written to a global variable.

22.5.1. Partial Enclosures

The concept of a partial enclosure is best demonstrated by use of a simplified view of radiative transfer system between surfaces 1 and 2 surrounded by free space as shown in Figure 22.5-4.

If radiative transfer occurs between the two bodies and the view factor between the two bodies is readily accessible a simplified network representation of the interaction, Figure 22.5-5 may suffice but here the interest lies in analyzing the system using enclosure radiation.




Figure 22.5-4.. Two-Body Radiative Transfer Model




Figure 22.5-5.. Two Surface Network Model

Recall that the enclosure view factors F_{ij} are computed as

$$F_{ij} = \frac{1}{A_i} \int_{A_i} \int_{A_j} \frac{\cos \theta_i \cos \theta_j}{\pi r^2} \delta_{ij} dA_i dA_j \quad .$$

Determination of the view factors is a compute intensive endeavor and within most code implementations extraneous calculations are eliminated based upon the geometry. One example of this would be excluding this calculation for surfaces which are not visible to each other. Moreover, from a geometric view of enclosure surfaces, Figure 22.5-6, one can conclude that legitimate interactions between surfaces are those for which n_i and n_j are opposed. Thus an important feature of the enclosure model is the notion of inward facing normals. This convention effectively defines the interaction between the enclosure subfacets. A notable metric of the view factor calculation for closed surfaces (watertight enclosures) is that for each facet i the row-sum over all surface facets k , $\sum_{j=0}^{j=k} F_{ij} = 1.0$.




Figure 22.5-6.. View Factor Configuration

In many cases a more complete model of the two-body configuration will include radiative transfer with the surroundings. Including these interactions requires introduction of an additional enclosure surface as shown in Figure 22.5-7.

Surface 3 known as the "partial enclosure" is artificially added to the numerical model (i.e. not included in the meshed discretization). Introduction of the partial enclosure is necessary in order to apply conventional approaches for numerical evaluation of the system view factors. Here we note that algorithmically, failure to add the partial enclosure surface would be manifest in bad row-sum metrics.




Figure 22.5-7.. Partial Enclosure Radiative Transfer Model

Introduction of the partial enclosure leads to the thermal network representation shown in Figure 22.5-8 in which the partial enclosure interacts with the other bodies of the system. Since the partial




Figure 22.5-8.. Three Surface Network Model

enclosure is modeled in the same way as a real surface questions often arise concerning characterization of the partial enclosure in terms of its temperature, area and emissivity. The temperature must of course must represent the surroundings. The area should be an area that envelopes the true surfaces of the enclosures. The partial enclosure emissivity should be chosen in a manner consistent with the relationship of surface radiosity J with the emission, σT_3^4 and irradiance, G

$$J = \varepsilon \sigma T^4 - (1 - \varepsilon)G .$$

As examples of this we consider the consequence of selecting a partial emissivity at two extremes, $\varepsilon = 0$ and $\varepsilon = 1$, both of which which reduce the network model of Figure 22.5-8 to that of 22.5-9. For $\varepsilon = 0$ from the network interaction between $\sigma T_3^4 - J_3$ we find that the resistance becomes infinite thus eliminating any system interaction with T_3 as all the incident energy is reflected. This results in a modified version of the two-surface network 22.5-5, albeit with more attenuation. For $\varepsilon = 1$ and the network interaction between between $\sigma T_3^4 - J_3$ is eliminated. However, now the radiative transfer system sees the emissive power of the surroundings since from 22.5.1, $J = \sigma T^4$. Clearly there are no obvious choices for partial enclosure emissivity other than that it should be chosen to enable interaction of the system with the surroundings.




Figure 22.5-9.. Three Surface Network Model ($\varepsilon_3 = 0$ and $\varepsilon_3 = 1$)

22.6. VIEWFACTOR CALCULATION

Scope: Equation System

Begin Viewfactor Calculation *Vf_calc*

Bsp Tree Max Depth {=|are|is} *depth* And Min List Length {=|are|is} *l*

Compute Rule {=|are|is} *VFComputeRule*

Geometric Tolerance {=|are|is} *n*

Hemicube Max Subdivides {=|are|is} *n*

Hemicube Min Separation {=|are|is} *n*

Hemicube Resolution {=|are|is} *n*

Number Of Rotations {=|are|is} *n*

Output Rule {=|are|is} *OutputRule*

Pairwise Monte Carlo Sample Rule {=|are|is} *AMCSampleRule*

Pairwise Monte Carlo Tol1 {=|are|is} *Real_value*

Pairwise Monte Carlo Tol2 {=|are|is} *Real_value*

Pairwise Number Of Monte Carlo Samples {=|are|is} *n*

Pairwise Number Of Visibility Samples {=|are|is} *n*

Pairwise Visibility Sample Rule {=|are|is} *AVSampleRule*

X-Y Plane Symmetry

X-Z Plane Symmetry

Y-Z Plane Symmetry

End

Summary This block command specifies a radiation enclosure and is used to define a method for calculating view factors. The parameter for this block corresponds to an instance of a radiation enclosure mechanics.

22.6.1. Bsp Tree Max Depth

Scope: Viewfactor Calculation

Bsp Tree Max Depth {=|are|is} *depth* And Min List Length {=|are|is} *l*

Parameter	Value	Default
<i>depth</i>	integer	12
<i>l</i>	integer	25

Summary This line command sets the BSP tree parameters.

Description This line command sets the parameters for the Binary Space Partitioning (BSP) tree. This data structure is used to accelerate the geometric operations associated with visibility to calculate the view factors. The maximum depth of the tree will set the maximum number of partitioning boxes created for a given enclosure. The minimum list length will set the desired number faces to be contained in a box. The depth of the tree will be increased until the minimum list length is met of the maximum depth is reached. It is suggested that these parameters not be adjusted from their default values.

22.6.2. Compute Rule

Scope: Viewfactor Calculation

Compute Rule {=|are|is} *VFComputeRule*

Parameter	Value	Default
<i>VFComputeRule</i>	{hemicube pairwise read}	HEMICUBE

Summary This line command sets the method for computing the view factors for this enclosure.

22.6.3. Geometric Tolerance

Scope: Viewfactor Calculation

Geometric Tolerance {=|are|is} *n*

Parameter	Value	Default
<i>n</i>	real	1.0e-6

Summary Set the geometric tolerance

Description This line command sets the spatial geometry tolerance for use in all geometry-related comparisons. This value should correspond to the known minimum geometric size of the element faces used to define the enclosure.

22.6.4. Hemicube Max Subdivides

Scope: Viewfactor Calculation

Hemicube Max Subdivides {= | are | is} *n*

Parameter	Value	Default
<i>n</i>	integer	2

Summary Set the upper limit of hemicube subdivides

Description This line command sets the upper limit of the number of element-face subdivides that will occur when the proximity criteria limit is exceeded (see the HEMICUBE MIN SEPARATION line command).

22.6.5. Hemicube Min Separation

Scope: Viewfactor Calculation

Hemicube Min Separation {= | are | is} *n*

Parameter	Value	Default
<i>n</i>	real	5

Summary Set the hemicube minimum separation

Description This line command sets a nondimensional minimum-separation distance allowed between element faces for the HEMICUBE method before the face is subdivided. The accuracy of the hemicube method degrades rapidly if the element faces are in close proximity to each other. This tolerance is based on dividing the normal distance between the center of the element faces by the effective diameter of the element face.

22.6.6. Hemicube Resolution

Scope: Viewfactor Calculation

Hemicube Resolution {= | are | is} *n*

Parameter	Value	Default
<i>n</i>	integer	400

Summary Set the hemicube resolution

Description This line command sets the number of uniform subpatches into which the hemicube will be divided.

22.6.7. Number Of Rotations

Scope: Viewfactor Calculation

Number Of Rotations `{=|are|is} n`

Parameter	Value	Default
<i>n</i>	integer	1

Summary Set the number of internal rotations for 2D axisymmetric geometry or 3D geometry with rotation symmetry.

22.6.8. Output Rule

Scope: Viewfactor Calculation

Output Rule `{=|are|is} OutputRule`

Parameter	Value	Default
<i>OutputRule</i>	<code>{more verbose none summary verbose}</code>	SUMMARY

Summary Selects the amount of information printed describing the view factor calculation

Description By default a summary of the input values are output. The MORE VERBOSE option will print both the summary information and progress of the view factor calculation in percent done. The percent done is useful in estimating how much runtime should be allotted for the calculation.

22.6.9. Pairwise Monte Carlo Sample Rule

Scope: Viewfactor Calculation

Pairwise Monte Carlo Sample Rule `{=|are|is} AMCSampleRule`

Parameter	Value	Default
<i>AMCSampleRule</i>	<code>{halton jitter random uniform}</code>	HALTON

Description This line command selects the method for the distribution of Monte Carlo integration sample points on the surface for view-factor quadrature.

22.6.10. Pairwise Monte Carlo Tol1

Scope: Viewfactor Calculation

Pairwise Monte Carlo Tol1 {=|are|is} *Real_value*

Parameter	Value	Default
<i>Real_value</i>	real	1.0e-5

Summary Set first of two convergence checks for Monte Carlo integration

Description This line command sets one of the two convergence checks used by the Monte Carlo integration algorithm for the PAIRWISE method. If the standard deviation of the view factor divided by the value of the view factor is less than this tolerance, the Monte Carlo integration will terminate i.e

$$\frac{\text{Std. Dev. of } F_{ij}}{F_{ij}} < tol_1$$

22.6.11. Pairwise Monte Carlo Tol2

Scope: Viewfactor Calculation

Pairwise Monte Carlo Tol2 {=|are|is} *Real_value*

Parameter	Value	Default
<i>Real_value</i>	real	1.0e-5

Summary Set second of two convergence checks for Monte Carlo integration

Description This line command sets one of the two convergence checks used by the Monte Carlo integration algorithm for the PAIRWISE method. If the standard deviation of the view factor is less than this tolerance, the Monte Carlo integration will terminate i.e

$$\text{Std. Dev. of } F_{ij} < tol_2$$

22.6.12. Pairwise Number Of Monte Carlo Samples

Scope: Viewfactor Calculation

Pairwise Number Of Monte Carlo Samples {=|are|is} *n*

Parameter	Value	Default
<i>n</i>	integer	1000

Summary Set the pairwise number of Monte Carlo sample points

Description This line command specifies the number of Monte Carlo integration sample points when Monte Carlo integration is activated during the PAIRWISE view-factor-calculation algorithm.

22.6.13. Pairwise Number Of Visibility Samples

Scope: Viewfactor Calculation

Pairwise Number Of Visibility Samples {=|are|is} *n*

Parameter	Value	Default
<i>n</i>	integer	25

Summary Set the pairwise number visibility sample points

Description This line command will set the number of sample points to use for evaluating visibility between element faces for the PAIRWISE view-factor-calculation algorithm. Visibility is used to select the method for calculating the view factors. If the two element faces are completely visible to each other, the view factor is calculated using Gauss quadrature or an analytic method. If the element faces are partially visible, Monte Carlo integration is used.

22.6.14. Pairwise Visibility Sample Rule

Scope: Viewfactor Calculation

Pairwise Visibility Sample Rule {=|are|is} *AVSampleRule*

Parameter	Value	Default
<i>AVSampleRule</i>	{halton jitter random uniform}	UNIFORM

Summary Set the pairwise visibility sample rule

Description This line command selects the method for distributing the visibility sample points on the surface.

22.6.15. X-Y Plane Symmetry

Scope: Viewfactor Calculation

Summary Specifies symmetry about the X-Y plane.

22.6.16. X-Z Plane Symmetry

Scope: Viewfactor Calculation

Summary Specifies symmetry about the X-Z plane.

22.6.17. Y-Z Plane Symmetry

Scope: Viewfactor Calculation

Summary Specifies symmetry about the Y-Z plane.

22.7. VIEWFACTOR SMOOTHING

Scope: Equation System

```
Begin Viewfactor Smoothing Vf_smooth

Convergence Tolerance {=|are|is} Param1

Maximum Iterations {=|are|is} n

Method {=|are|is} VFSmoothMethod

Output Rule {=|are|is} OutputRule

Reciprocity Rule {=|are|is} VFMatrixSymmRule

Weight Power {=|are|is} Param1

End
```

Summary Defines a view factor smoothing scheme and its associated parameters.

Description This block command is used to define a method for smoothing the view factors. The defined method will be used for view factor smoothing only when requested with the USE VIEWFACTOR SMOOTHING line command in the ENCLOSURE DEFINITION command block.

When VIEWFACTOR SMOOTHING is requested a two step sequence is initiated

- 1) Reciprocity enforcement using the specified RECIPROCITY RULE
- 2) Rowsum enforcement as per the specified METHOD

In both steps the viewfactor matrix will be modified as prescribed.

****Note****

In step 1 the appropriate modifications are always applied. However, if the rowsum enforcement criteria of step 2 are not satisfied the viewfactor matrix supplied to the enclosure radiation calculation will be the viewfactor matrix resulting from step 1 and -not- the raw viewfactor matrix.

22.7.1. Convergence Tolerance

Scope: Viewfactor Smoothing

Convergence Tolerance $\{=|are|is\}$ *Param1*

Parameter	Value	Default
<i>Param1</i>	real	1.0e-8

Summary Sets convergence tolerance.

Description This line command sets the convergence tolerance for both the SIMPLE and LEAST-SQUARES smoothing algorithms based on the following:

1) SIMPLE: $|1 - \sum F_{ij}| < tol$ 2) LEAST-SQUARES: $\|r\| < tol$

where r is the residual of the Lagrange multiplier matrix problem.

22.7.2. Maximum Iterations

Scope: Viewfactor Smoothing

Maximum Iterations $\{=|are|is\}$ *n*

Parameter	Value	Default
<i>n</i>	integer	500

Summary Set maximum iterations.

Description This line command sets the maximum number of iterations that the SIMPLE smoothing algorithm will take.

22.7.3. Method

Scope: Viewfactor Smoothing

Method $\{=|are|is\}$ *VFSmoothMethod*

Parameter	Value	Default
<i>VFSmoothMethod</i>	{least-squares none simple}	LEAST-SQUARES

Summary Defines view factor smoothing method.

Description This line command defines the algorithm for smoothing the view factors. Smoothing is a term used to describe the process of enforcing the row-sum property of the view-factor matrix given by

$$\sum F_{ij} = 1.0$$

and the reciprocity property of view factors given by

$$A_i F_{ij} = A_j F_{ji}.$$

The HEMICUBE method guarantees the row-sum property, but not necessarily the reciprocity property. The PAIRWISE method will guarantee the reciprocity property (lower diagonal is calculated and the upper triangular is filled in using reciprocity), but not necessarily the row-sum property. If these two properties are not met by the view-factor matrix, energy conservation will not be achieved.

22.7.4. Output Rule

Scope: Viewfactor Smoothing

Output Rule {=|are|is} *OutputRule*

Parameter	Value	Default
<i>OutputRule</i>	{more verbose none summary verbose}	SUMMARY

Summary Set the amount of output.

Description This line command sets the amount of information reported to the output screen about the view-factor smoothing.

22.7.5. Reciprocity Rule

Scope: Viewfactor Smoothing

Reciprocity Rule {=|are|is} *VFMatrixSymmRule*

Parameter	Value	Default
<i>VFMatrixSymmRule</i>	{addition average none subtraction}	AVERAGE

Summary Selects reciprocity enforcement rule.

Description This line command determines the method for enforcing reciprocity,

$$A_i F_{ij} = A_j F_{ji}$$

during smoothing. This command is only required for the HEMICUBE algorithm. The PAIRWISE algorithm uses reciprocity to fill in the lower triangular part of the view-factor matrix. If both of the view factors, F_{ij} and F_{ji} , are nonzero, these factors are adjusted by averaging $A_i F_{ij}$ and $A_j F_{ji}$.

22.7.6. Weight Power

Scope: Viewfactor Smoothing

Weight Power {=|are|is} *Param1*

Parameter	Value	Default
<i>Param1</i>	real	2.0

Summary Sets weight power.

Description This line command sets the power, p , used for the weights in the LEAST-SQUARES smoothing algorithm

$$w_{ij} = F_{ij}^p.$$

22.8. RADIOSITY SOLVER

Scope: Equation System

Begin Radiosity Solver *Boundary condition instance name*

Convergence Tolerance {=|are|is} *Tolerance*

Coupling {=|are|is} *RadCouplingRule*

Maximum Iterations {=|are|is} *m*

Output Rule {=|are|is} *OutputRule*

Solver {=|are|is} *RadSolveRule*

End

Summary Specifies a radiation enclosure. Corresponds to an instance of radiation enclosure mechanics.

Description This block command contains methods associated with the solution of the radiosity system and the linearization method for applying the radiative heat flux to the thermal model. Note that the parameter for this block command will be used with the USE RADIOSITY SOLVER line command in the ENCLOSURE DEFINITION command block.

22.8.1. Convergence Tolerance

Scope: Radiosity Solver

Convergence Tolerance {=|are|is} *Tolerance*

Parameter	Value	Default
<i>Tolerance</i>	real	1.0e-6

Summary Sets convergence tolerance.

Description This line command sets the convergence tolerance for the iterative solution of the radiosity system. The iterative solution will stop when the ratio of the current residual to the initial residual is less than the specified tolerance:

$$\frac{\|r\|}{\|r_0\|} < tol$$

22.8.2. Coupling

Scope: Radiosity Solver

Coupling {=|are|is} *RadCouplingRule*

Parameter	Value	Default
<i>RadCouplingRule</i>	{lagged mason smoothed}	MASON

Summary Specifies linearization method.

Description This line command specifies the linearization method used to apply the radiative heat flux to the thermal model.

22.8.3. Maximum Iterations

Scope: Radiosity Solver

Maximum Iterations {=|are|is} *m*

Parameter	Value	Default
<i>m</i>	integer	300

Summary Sets maximum number of iterations.

Description This line command sets the maximum number of iterations allowed for the iterative solution of the radiosity equations. If the maximum number of iterations is exceeded, the calculation will fail and the thermal simulation will stop.

22.8.4. Output Rule

Scope: Radiosity Solver

Output Rule {=*|are|is|*} *OutputRule*

Parameter	Value	Default
<i>OutputRule</i>	{ <i>more verbose none summary verbose</i> }	NONE

Summary Sets the information reporting level.

Description This line command will set the amount of information reported to the output screen about the radiosity solution.

22.8.5. Solver

Scope: Radiosity Solver

Solver {=*|are|is|*} *RadSolveRule*

Parameter	Value	Default
<i>RadSolveRule</i>	{ <i>chaparral cg chaparral gmres coupled</i> }	CHAPARRAL CG

Summary Chaparral solver selection for radiosity system.

Description This line command selects the method for solving the linear system of radiosity equations. The currently available methods are iterative linear solvers.

22.9. ENCLOSURE DEFINITION

Scope: Equation System

Begin Enclosure Definition *Boundary condition instance name*

Activate Mean Beam Model With Bulk Node *Model*

Add Surface *SurfaceList...*

Area Output *VariableName*

Blocking Surfaces

Dash Closure Metric Samples {=*|are|is|*} *NumSamp* [*Tol* {=*|are|is|*} *Value*]

Dash Solve Enclosures {=*|are|is|*} *Values...*

Dash Subfaceting Algorithm {=*|are|is|*} *Type*

Database Name {=*|are|is|*} *Filename* In *VFileFormat* Format

Disable Parallel Redistribution
 Emissivity {=|are|is} *Value* [On *SurfaceName*]
 Emissivity Function {=|are|is} *FunctionName* [On *SurfaceName*]
 Emissivity Subroutine {=|are|is} *MySub* [On *SurfaceName*]
 Emissivity Time Function {=|are|is} *FunctionName* [On *SurfaceName*]
 Enable Parallel Redistribution
 Input Database Name {=|are|is} *Filename*
 Integrated Flux Output *VariableName*
 Integrated Power Output *VariableName*
 Matched Flux On *SurfaceName* {=|are|is} *FluxType* [Phase {=|are|is} *MaterialPhaseName*]
 Mean Beam Length {=|are|is} *l* [*Parameters*]...
 Meshed Enclosure Is *BlockList*...
 Nonblocking Surfaces
 Output Database Name {=|are|is} *Filename* In *VFfileFormat* Format
 Overlapping Enclosure {=|are|is} *Bool*
 Partial Enclosure Area {=|are|is} *a*
 Partial Enclosure Area Subroutine {=|are|is} *FName*
 Partial Enclosure Area Time Function {=|are|is} *FName*
 Partial Enclosure Emissivity {=|are|is} *e*
 Partial Enclosure Emissivity Subroutine {=|are|is} *FName*
 Partial Enclosure Emissivity Time Function {=|are|is} *FName*
 Partial Enclosure Flux Output *VariableName*
 Partial Enclosure Irradiance Output *VariableName*
 Partial Enclosure Radiosity Output *VariableName*
 Partial Enclosure Temperature {=|are|is} *t*
 Partial Enclosure Temperature Subroutine {=|are|is} *FName*
 Partial Enclosure Temperature Time Function {=|are|is} *FName*
 Preprocess Enclosures [*Options*...]
 Radiosity Database Name {=|are|is} *Filename*

```

Rowsum Database Name {=|are|is} Filename

Topology Database Name {=|are|is} Filename

Use Banded Wavelength Model ModelName

Use Dash Enclosures [ type tol {=|are|is} Params... ]

Use Radiosity Solver Param0

Use Toggle Block ToggleName [ {@|at|for|in|on|over}
ElementBlockList... ]

Use Viewfactor Calculation Param0

Use Viewfactor Smoothing Param0

Viewfactor Update {=|are|is} UpdateMethod [ Using Params... ]

Viewfactor Update Start Time Is Start_time

Begin Band BandName

End

```

End

Summary Specifies a radiation enclosure. Corresponds to an instance of radiation enclosure mechanics.

Description This block command is used to define an enclosure for the thermal model. There may be more than one enclosure defined for any thermal model. An enclosure definition includes the geometric aspects (list of element faces forming the surface), material properties, and setting of the algorithms for calculating the view factors between the element faces in the enclosure and the radiosity solution. The name of the enclosure is specified by the user.

**** NOTE **** Enclosure names cannot begin with any sequence of numeric symbols (i.e. 0-9). This will cause a model to fail with very little in the way of error reporting.

22.9.1. Activate Mean Beam Model With Bulk Node

Scope: Enclosure Definition

Activate Mean Beam Model With Bulk Node *Model*

Parameter	Value	Default
<i>Model</i>	string	undefined

Summary Sets the bulk element representing the PMR material for the MBL (mean beam length) enclosure.

22.9.2. Add Surface

Scope: Enclosure Definition

Add Surface *SurfaceList...*

Parameter	Value	Default
<i>SurfaceList</i>	string...	undefined

Summary Adds surfaces, by name, to a boundary condition's extent.

Description This line command is used to add surfaces to the extent of a boundary condition. In Exodus II, surfaces are specified as side sets, that have a global integer identifier. For example, side set 12 would be added by this line command using the surface name `surface_12`. Note that in SIERRA, each element of an array of strings must be separated by whitespace.

22.9.3. Area Output

Scope: Enclosure Definition

Area Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Output the area associated with this flux boundary condition.

Description This line triggers output of the enclosure area and volume.

22.9.4. Blocking Surfaces

Scope: Enclosure Definition

Summary Specifies a blocking enclosure

Description This is the default behavior if neither this line command, nor the NONBLOCKING SURFACES line command are present. This line command informs Chaparral to consider blocking surfaces during the calculation of view factors. A blocking surface is defined as one or more element faces that occlude the view from any pair of element faces within the enclosure. If it is known that no blocking surfaces exist in the enclosure, the NONBLOCKING SURFACES line command can be included in the enclosure definition to reduce the compute time for view factors. Note that the BLOCKING SURFACES line command should be included if there is any doubt whether there are blocking surfaces in the enclosure.

22.9.5. Dash Closure Metric Samples

Scope: Enclosure Definition

Dash Closure Metric Samples {=*|are|is*} *NumSamp* [*Tol* {=*|are|is*} *Value*]

Parameter	Value	Default
<i>NumSamp</i>	integer	undefined

Summary Specify number of samples for DASH closure metric and possibly an acceptable tolerance.

Description When using DASH enclosures one may wish to assign the number of sample points used in determining closure. Optionally, one can set the acceptable value of closure metric associated with closure.

22.9.6. Dash Solve Enclosures

Scope: Enclosure Definition

Dash Solve Enclosures {=*|are|is*} *Values...*

Parameter	Value	Default
<i>Values</i>	integer...	undefined

Summary List of integer index values for Dash enclosures to perform solution. The index values must be obtained by a preprocessing step using both PREPROCESS ENCLOSURE TOPOLOGY command line at the Region level and the PREPROCESS ENCLOSURES command line in the Enclosure Definition command block.

22.9.7. Dash Subfaceting Algorithm

Scope: Enclosure Definition

Dash Subfaceting Algorithm {=*|are|is*} *Type*

Parameter	Value	Default
<i>Type</i>	{dash_dicing symmetric_imprinting}	undefined

Summary Specify the subfaceting algorithm type. This is a developer command.

22.9.8. Database Name

Scope: Enclosure Definition

Database Name {=*|are|is*} *Filename* In *VFfileFormat* Format

Parameter	Value	Default
<i>Filename</i>	string	undefined
<i>VFfileFormat</i>	{ascii binary pnetcdf}	undefined

Summary Specifies common filename to read/write viewfactors

Description This line command specifies the database name for both input and output of the view factors for this enclosure. The file name is provided by the user, and one of three file formats is specified.

The ASCII format should be used only for small enclosures. This format is useful when the analyst wants to examine the values of the view factors that have been evaluated.

The BINARY format will produce a machine-dependent file. This view-factor file can only be read on the same machine in subsequent calculations.

Both the ASCII and BINARY file formats may only be read on the same number of processors as they were written with, and are deprecated as of Aria version 4.43.5. The replacement PNETCDF format produces a single machine-independent file that may be written or read in runs using any number of processors.

22.9.9. Disable Parallel Redistribution

Scope: Enclosure Definition

Summary Disable parallel redistribution of viewfactor matrix.

Description Ensures that the default distribution of the viewfactor matrix is distribution of rows across MPI ranks is enforced - no parallel distribution of the view factor matrix.

22.9.10. Emissivity

Scope: Enclosure Definition

Emissivity {=*|are|is*} *Value* [On *SurfaceName*]

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Sets a constant value of emissivity for a defined surface. If the optional parameters are not included, then this is the default emissivity for the enclosure. Otherwise it is only applied to the indicated surface.

****Note** that if a surface is called out more than once, the emissivity definition it is overwritten: last one in wins.

22.9.11. Emissivity Function

Scope: Enclosure Definition

Emissivity Function {=|are|is} *FunctionName* [On *SurfaceName*]

Parameter	Value	Default
<i>FunctionName</i>	string	undefined

Summary Sets a emissivity function for a defined surface. If the optional parameters are not included, then this is the default emissivity for the enclosure. Otherwise it is only applied to the indicated surface.

****Note** that if a surface is called out more than once, the emissivity definition it is overwritten: last one in wins.

22.9.12. Emissivity Subroutine

Scope: Enclosure Definition

Emissivity Subroutine {=|are|is} *MySub* [On *SurfaceName*]

Parameter	Value	Default
<i>MySub</i>	string	undefined

Summary Sets a emissivity user subroutine for a defined surface. If the optional parameters are not included, then this is the default emissivity for the enclosure. Otherwise it is only applied to the indicated surface.

Also, the software supports using locally scoped user data for most user subroutines, but I haven't figured out a syntax for it here yet. So it is not yet supported. If you need to get data into this subroutine, use the region's "REAL DATA" and "INTEGER DATA" line commands.

****Note** that if a surface is called out more than once, the emissivity definition it is overwritten: last one in wins.

22.9.13. Emissivity Time Function

Scope: Enclosure Definition

Emissivity Time Function {=|are|is} *FunctionName* [On *SurfaceName*]

Parameter	Value	Default
<i>FunctionName</i>	string	undefined

Summary Sets a emissivity function of time for a defined surface. If the optional parameters are not included, then this is the default emissivity for the enclosure. Otherwise it is only applied to the indicated surface.

****Note** that if a surface is called out more than once, the emissivity definition it is overwritten: last one in wins.

22.9.14. Enable Parallel Redistribution

Scope: Enclosure Definition

Summary Enables parallel redistribution of viewfactor matrix.

Description Invokes redistribution of the view factor matrix from a distribution of matrix rows across MPI ranks to a 2D distribution of row and column blocks to achieve better performance in parallel. A current limitation of this option is that the Tpetra redistribution capability will use more memory than necessary and may not be a appropriate if one is memory constrained on a platform.

22.9.15. Input Database Name

Scope: Enclosure Definition

Input Database Name {=|are|is} *Filename*

Parameter	Value	Default
<i>Filename</i>	string	undefined

Summary Specifies filename to read viewfactors from

Description This line command provides the name of the view-factor file. If this line command is present, the file containing the given view-factor matrix will be opened and read. The calculation of view factors will not take place. Note that you must also specify a value of READ for the COMPUTE RULE command in the associated VIEWFACTOR CALCULATION command block.

22.9.16. Integrated Flux Output

Scope: Enclosure Definition

Integrated Flux Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Calculate the average flux associated with this flux boundary condition.

Description This line command specifies that, as a postprocess, the normal flux associated with this boundary condition be integrated over the surface to obtain the total power. This power is then divided by the total area of the surface to obtain the average flux on the surface, and stored in a global variable named "variableName". This global variable may then be output to history files, or accessed in user subroutines, etc.

22.9.17. Integrated Power Output

Scope: Enclosure Definition

Integrated Power Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Calculate the total power associated with this flux boundary condition.

Description This line command specifies that, as a postprocess, the normal flux associated with this boundary condition be integrated over the surface to obtain the total power which is then stored into a global variable named "variableName". This global variable may then be output to history files, or accessed in user subroutines, etc.

22.9.18. Matched Flux On

Scope: Enclosure Definition

Matched Flux On *SurfaceName* {=|are|is} *FluxType* [Phase {=|are|is} *MaterialPhaseName*]

Parameter	Value	Default
<i>SurfaceName</i>	string	undefined
<i>FluxType</i>	string	undefined

Summary Indicates an equivalent matching flux for surfaces within the enclosure that border element blocks which do not have the ENERGY equation defined but do have an equivalent equation (such as ENTHALPY) defined. The primary use for this is in OMD simulations and should be considered at the same reliability level as OMD.

22.9.19. Mean Beam Length

Scope: Enclosure Definition

Mean Beam Length `{=|are|is} l [Parameters]...`

Parameter	Value	Default
<i>l</i>	string	undefined
<i>Parameters</i>	[string]...	undefined

Summary Sets the expression for the radiant decay length L for the MBL (mean beam length) enclosure.

22.9.20. Meshed Enclosure

Scope: Enclosure Definition

Meshed Enclosure Is *BlockList*...

Parameter	Value	Default
<i>BlockList</i>	string...	undefined

Summary Adds blocks, by name, to the meshed enclosure extent.

Description In the event one wishes to solve a conduction problem within an enclosure as well as the radiation problem the interior discretization must be defined. This line command is used to add blocks to the extent of a enclosure interior. In Exodus II, surfaces are specified as side sets, that have a global integer identifier. For example, block 12 would be added by this line command using the surface name block_12. Note that in SIERRA, each element of an array of strings must be separated by whitespace.

22.9.21. Nonblocking Surfaces

Scope: Enclosure Definition

Summary Specifies a non-blocking enclosure

Description See the BLOCKING SURFACES command for a complete description.

22.9.22. Output Database Name

Scope: Enclosure Definition

Output Database Name {=|are|is} *Filename* In *VFfileFormat* Format

Parameter	Value	Default
<i>Filename</i>	string	undefined
<i>VFfileFormat</i>	{ascii binary pnetcdf}	undefined

Summary Specify filename to write viewfactors to

Description This line command activates the output of the view factors calculated during a simulation. The file name is provided by the user, and one of three file formats is specified. See the "DATABASE NAME" line command description for more detail on the file formats.

22.9.23. Overlapping Enclosure

Scope: Enclosure Definition

Overlapping Enclosure {=|are|is} *Bool*

Parameter	Value	Default
<i>Bool</i>	{false true}	undefined

Summary Designates this enclosure as overlapping other enclosures.

Description On occasion one might want to define an enclosure radiation problem as a superposition of several enclosures. In this case one must designate one of the enclosures as overlapping the others in order to distinguish it from the other enclosures. This command adds a qualifier to the enclosure definition to enable making this distinction possible.

22.9.24. Partial Enclosure Area

Scope: Enclosure Definition

Partial Enclosure Area {=|are|is} *a*

Parameter	Value	Default
<i>a</i>	real	undefined

Summary Constant value for the partial enclosure area associated with this enclosure radiation flux boundary condition.

22.9.25. Partial Enclosure Area Subroutine

Scope: Enclosure Definition

Partial Enclosure Area Subroutine {=|are|is} *FName*

Parameter	Value	Default
<i>FName</i>	string	undefined

Summary User-defined function name for the partial enclosure area associated with this enclosure radiation flux boundary condition.

22.9.26. Partial Enclosure Area Time Function

Scope: Enclosure Definition

Partial Enclosure Area Time Function {=|are|is} *FName*

Parameter	Value	Default
<i>FName</i>	string	undefined

Summary Time-dependent function name for the partial enclosure area associated with this enclosure radiation flux boundary condition.

22.9.27. Partial Enclosure Emissivity

Scope: Enclosure Definition

Partial Enclosure Emissivity {=|are|is} *e*

Parameter	Value	Default
<i>e</i>	real	undefined

Summary Constant value for the partial enclosure emissivity associated with this enclosure radiation flux boundary condition.

22.9.28. Partial Enclosure Emissivity Subroutine

Scope: Enclosure Definition

Partial Enclosure Emissivity Subroutine {=|are|is} *FName*

Parameter	Value	Default
<i>FName</i>	string	undefined

Summary User-defined function name for the partial enclosure emissivity associated with this enclosure radiation flux boundary condition.

22.9.29. Partial Enclosure Emissivity Time Function

Scope: Enclosure Definition

Partial Enclosure Emissivity Time Function {=|are|is} *FName*

Parameter	Value	Default
<i>FName</i>	string	undefined

Summary Time-dependent function name for the partial enclosure emissivity associated with this enclosure radiation flux boundary condition.

22.9.30. Partial Enclosure Flux Output

Scope: Enclosure Definition

Partial Enclosure Flux Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Output the flux associated with the partial enclosure.

Description During the simulation the flux associated with the partial enclosure is output to the ExodusII file as a global variable.

22.9.31. Partial Enclosure Irradiance Output

Scope: Enclosure Definition

Partial Enclosure Irradiance Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Output the irradiance associated with the partial enclosure.

Description During the simulation the irradiance associated with the partial enclosure is output to the ExodusII file as a global variable.

22.9.32. Partial Enclosure Radiosity Output

Scope: Enclosure Definition

Partial Enclosure Radiosity Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Output the radiosity associated with the partial enclosure.

Description During the simulation the radiosity associated with the partial enclosure is output to the ExodusII file as a global variable.

22.9.33. Partial Enclosure Temperature

Scope: Enclosure Definition

Partial Enclosure Temperature {=*|are|is*} *t*

Parameter	Value	Default
<i>t</i>	real	undefined

Summary Constant value for the partial enclosure temperature associated with this enclosure radiation flux boundary condition.

22.9.34. Partial Enclosure Temperature Subroutine

Scope: Enclosure Definition

Partial Enclosure Temperature Subroutine {=*|are|is*} *FName*

Parameter	Value	Default
<i>FName</i>	string	undefined

Summary User-defined function name for the partial enclosure temperature associated with this enclosure radiation flux boundary condition.

22.9.35. Partial Enclosure Temperature Time Function

Scope: Enclosure Definition

Partial Enclosure Temperature Time Function {=*|are|is*} *FName*

Parameter	Value	Default
<i>FName</i>	string	undefined

Summary Time-dependent function name for the partial enclosure temperature associated with this enclosure radiation flux boundary condition.

22.9.36. Preprocess Enclosures

Scope: Enclosure Definition

Summary Preprocess enclosures subject to options: ORIGINAL_FACES, ENCLOSURE_FACETS, ENCLOSURE_FACET_EDGES, CONTACT_FACETS, CONTACT_FACET_EDGES and COARSE_MESH. When invoked at Region preprocessing is performed and the simulation will terminate.

Description For debug and inspection purposes the surfaces defined in the enclosure definitions will be processed, then output to the exodus database before terminating the simulation. If no options are chosen the default is to select all the available information. Options are: ORIGINAL_FACES, ENCLOSURE_FACETS, ENCLOSURE_FACET_EDGES, CONTACT_FACETS, CONTACT_FACET_EDGES and COARSE_MESH. Facets are output as triangle elements, edges as bars and faces as shell elements.

22.9.37. Radiosity Database Name

Scope: Enclosure Definition

Radiosity Database Name {=|are|is} *Filename*

Parameter	Value	Default
<i>Filename</i>	string	undefined

Summary Specify filename to write enclosure rowsum error and radiosity results to

Description This line command activates the output of the view factor rowsum error calculated during a simulation. Additionally, this file will be used to also output the radiosity and flux values during subsequent calls to the radiosity solver. The file name is provided by the user and the output format is ExodusII. This file is useful when the analyst wants to where in the enclosure the maximum errors are occurring. The rowsum error is given by

$$1 - \sum_{j=1}^{N_{facets}} F_{ij}$$

for each row *i* in the view-factor matrix (which corresponds to a face in the enclosure). Use of this option will negatively affect performance and is intended for use by developers.

22.9.38. Rowsum Database Name

Scope: Enclosure Definition

Rowsum Database Name {=|are|is} *Filename*

Parameter	Value	Default
<i>Filename</i>	string	undefined

Summary Specify filename to write enclosure rowsum error results to

Description This line command activates the output of the view factor rowsum error calculated during a simulation. The file name is provided by the user and the output format is ExodusII. This file is useful when the analyst wants to where in the enclosure the maximum errors are occurring. The rowsum error is given by

$$1 - \sum_{j=1}^{N_{facets}} F_{ij}$$

for each row i in the view-factor matrix (which corresponds to a face in the enclosure).

22.9.39. Topology Database Name

Scope: Enclosure Definition

Topology Database Name {=|are|is} *Filename*

Parameter	Value	Default
<i>Filename</i>	string	undefined

Summary Specify filename to write enclosure topology to

Description This line command activates the output of the enclosure topology, taking into account all specified symmetry. The file name is provided by the user and the output format is ExodusII.

22.9.40. Use Banded Wavelength Model

Scope: Enclosure Definition

Use Banded Wavelength Model *ModelName*

Parameter	Value	Default
<i>ModelName</i>	string	undefined

Summary Use a specified banded wavelength model for use in enclosure radiation.

Description Requests that a specific banded wavelength model named modelName, be associated with an enclosure, where the modelName is defined outside of the enclosure definition block. Only one BANDED WAVELENGTH MODEL can be used for an enclosure.

22.9.41. Use Dash Enclosures

Scope: Enclosure Definition

Summary Perform DASH contact search on the enclosure surfaces.

Description Performing a DASH contact search on the enclosure surfaces will prevent any faces in contact from being processed as part of an enclosure. Optionally one may define a relative tolerance based upon the characteristic element length, or absolute tolerances in positive and negative directions from the enclosure surface.

22.9.42. Use Radiosity Solver

Scope: Enclosure Definition

Use Radiosity Solver *Param0*

Parameter	Value	Default
<i>Param0</i>	string	undefined

Summary Specifies which radiosity solver to use.

Description This line command is used to identify the radiosity solver for use with this enclosure radiation problem. The details of the radiosity solver are defined using the RADIOSITY SOLVER command block. The parameter for this line command is the parameter used with the RADIOSITY SOLVER block command.

22.9.43. Use Toggle Block

Scope: Enclosure Definition

Use Toggle Block *ToggleName* [{@|at|for|in|on|over} *ElementBlockList...*]

Parameter	Value	Default
<i>ToggleName</i>	string	undefined

Summary Specification for toggling entities in the computational model based on Toggle Block parameters. When used at the region level, the list of element blocks to be toggled must be provided. Otherwise a listing of entities is not needed as the Toggle Block will be associated with the command line or the enclosing command block.

22.9.44. Use Viewfactor Calculation

Scope: Enclosure Definition

Use Viewfactor Calculation *Param0*

Parameter	Value	Default
<i>Param0</i>	string	undefined

Summary Specifies which view factor calculation to use.

Description This line command is used to specify the name of a method for calculating view factors defined using the VIEWFACTOR CALCULATION command block. The parameter for this line command is the parameter used to name the VIEWFACTOR CALCULATION block command.

22.9.45. Use Viewfactor Smoothing

Scope: Enclosure Definition

Use Viewfactor Smoothing *Param0*

Parameter	Value	Default
<i>Param0</i>	string	undefined

Summary Specifies which view factor smoother to use.

Description This line command is used to specify the name of a method for smoothing view factors defined using the VIEWFACTOR SMOOTHING command block. The parameter for this line command is the parameter used with the VIEWFACTOR SMOOTHING block command.

22.9.46. Viewfactor Update

Scope: Enclosure Definition

Viewfactor Update {=*|are|is*} *UpdateMethod* [Using *Params...*]

Parameter	Value	Default
<i>UpdateMethod</i>	{ <i>affected_area</i> <i>continuous</i> <i>freeze</i> <i>interval</i> <i>standard</i> <i>times</i> }	STANDARD

Summary Specify the viewfactor re-compute strategy.

Description The view factor calculation oftentimes dominates the computational cost of a thermal analysis. Thus for cases in which only the geometry changes due to surface deformation and the analyst views the change to be small enough so as to not affect the view factors greatly, one can select one of the strategies below for update of the view factors.



Known Issue: This command has only been enabled to work with models with mesh motion and will not work with standard element death.

`standard` is the default re-compute strategy, update on mesh change.

`freeze` means the view factor update is deactivated for subsequent updates. Thus the first view factor calculation determines the view factors used throughout the simulation.

`continuous` means the view factors will be computed every time step of a transient simulation.

`affected_area` is relevant only when used with Element Death. For every view factor calculation the enclosure surface area is computed and stored as a reference area. At subsequent solution steps the area corresponding to elements which are candidates for Element Death is accumulated. The ratio of candidate death element area to the original area is used as the criteria of whether Element Death and a new view factor update will occur. If `affected_area` is chosen and Element Death is not present the re-compute strategy will revert to `standard`. Here the Params value is the ratio of affected area to total area for which element death can occur.



Known Issue: The `affected_area` option has not yet been enabled for use and will not control the viewfactor update frequency.

`interval` specifies the time interval between view factor updates. Here Params is a single value time increment.

`times` selects specific times at which the view factors are recalculated. Here Params can be several discrete time values.

For `interval` and `times`, one can also select a time at which view factor updates are considered using the `view factor update start time` command line.

22.9.47. Viewfactor Update Start Time

Scope: Enclosure Definition

Viewfactor Update Start Time Is *Start_time*

Parameter	Value	Default
<i>Start_time</i>	real	0.0

Summary Specify start time for possible re-compute of viewfactors.

Description Specify the time after which viewfactor re-compute can occur. Command is active only for UPDATE FACTOR method = TIMES or INTERVAL.

22.10. BANDED WAVELENGTH MODEL

Scope: Equation System

Begin Banded Wavelength Model	<i>ModelName</i>
Band	<i>BandName</i> {= are is} <i>LowValue</i> <i>HighValue</i>
End	

Summary This command block specifies the wavelength distribution for a banded wavelength model.

Description Defines a piecewise constant banded wavelength discretization model of the thermal wavelength spectrum and associate it with name modelName. The same modelName can be used for different boundary conditions.

22.10.1. Band

Scope: Banded Wavelength Model

Band	<i>BandName</i> {= are is} <i>LowValue</i> <i>HighValue</i>

Parameter	Value	Default
<i>BandName</i>	string	undefined
<i>LowValue</i>	real	0.0
<i>HighValue</i>	real	REAL_MAX

Summary Specify the range of a wavelength band in microns μm for a surface or collection of surfaces undergoing radiative heat transfer.

Description Defines the upper and lower limits of a wavelength band in microns μm . Upper and lower limit values can intersect those of adjacent bands but cannot overlap into previously a defined BAND.

22.11. BAND

Scope: Enclosure Definition

Begin Band *BandName*

Emissivity {=|are|is} *Value* [On *SurfaceName*]

Emissivity Function {=|are|is} *FunctionName* [On *SurfaceName*]

Emissivity Subroutine {=|are|is} *MySub* [On *SurfaceName*]

Emissivity Time Function {=|are|is} *FunctionName* [On *SurfaceName*]

End

Summary This nested command block specifies the emissivity distribution for the surfaces in the enclosure for the given band.

Description Defines the emissivity distribution for the surfaces and/or default values for the band with name *bandName*.

22.11.1. Emissivity

Scope: Band

Emissivity {=|are|is} *Value* [On *SurfaceName*]

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Sets a constant value of emissivity for a defined surface. If the optional parameters are not included, then this is the default emissivity for the enclosure. Otherwise it is only applied to the indicated surface.

****Note** that if a surface is called out more than once, the emissivity definition it is overwritten: last one in wins.

22.11.2. Emissivity Function

Scope: Band

Emissivity Function {=|are|is} *FunctionName* [On *SurfaceName*]

Parameter	Value	Default
<i>FunctionName</i>	string	undefined

Summary Sets a emissivity function for a defined surface. If the optional parameters are not included, then this is the default emissivity for the enclosure. Otherwise it is only applied to the indicated surface.

****Note** that if a surface is called out more than once, the emissivity definition it is overwritten: last one in wins.

22.11.3. Emissivity Subroutine

Scope: Band

Emissivity Subroutine {=|are|is} *MySub* [On *SurfaceName*]

Parameter	Value	Default
<i>MySub</i>	string	undefined

Summary Sets a emissivity user subroutine for a defined surface. If the optional parameters are not included, then this is the default emissivity for the enclosure. Otherwise it is only applied to the indicated surface.

Also, the software supports using locally scoped user data for most user subroutines, but I haven't figured out a syntax for it here yet. So it is not yet supported. If you need to get data into this subroutine, use the region's "REAL DATA" and "INTEGER DATA" line commands.

****Note** that if a surface is called out more than once, the emissivity definition it is overwritten: last one in wins.

22.11.4. Emissivity Time Function

Scope: Band

Emissivity Time Function {=|are|is} *FunctionName* [On *SurfaceName*]

Parameter	Value	Default
<i>FunctionName</i>	string	undefined

Summary Sets a emissivity function of time for a defined surface. If the optional parameters are not included, then this is the default emissivity for the enclosure. Otherwise it is only applied to the indicated surface.

****Note** that if a surface is called out more than once, the emissivity definition it is overwritten: last one in wins.

22.11.5. Dash Closure Metric Samples

Scope:

Dash Closure Metric Samples {=|are|is} *NumSamp* [*Tol* {=|are|is} *Value*]

Parameter	Value	Default
<i>NumSamp</i>	integer	undefined

Summary Specify number of samples for DASH closure metric and possibly an acceptable tolerance.

Description When using DASH enclosures one may wish to assign the number of sample points used in determining closure. Optionally, one can set the acceptable value of closure metric associated with closure.

22.11.6. Dash Closure Metric Samples

Scope:

Dash Closure Metric Samples {=|are|is} *NumSamp* [*Tol* {=|are|is} *Value*]

Parameter	Value	Default
<i>NumSamp</i>	integer	undefined

Summary Specify number of samples for DASH closure metric and possibly an acceptable tolerance.

Description When using DASH enclosures one may wish to assign the number of sample points used in determining closure. Optionally, one can set the acceptable value of closure metric associated with closure.

22.11.7. Preprocess Enclosures

Scope:

Summary Preprocess enclosures subject to options: ORIGINAL_FACES, ENCLOSURE_FACETS, ENCLOSURE_FACET_EDGES, CONTACT_FACETS, CONTACT_FACET_EDGES and COARSE_MESH. When invoked at Region preprocessing is performed and the simulation will terminate.

Description For debug and inspection purposes the surfaces defined in the enclosure definitions will be processed, then output to the exodus database before terminating the simulation. If no options are chosen the default is to select all the available information. Options are: ORIGINAL_FACES, ENCLOSURE_FACETS, ENCLOSURE_FACET_EDGES, CONTACT_FACETS, CONTACT_FACET_EDGES and COARSE_MESH. Facets are output as triangle elements, edges as bars and faces as shell elements.

22.11.8. Use Dash Enclosures

Scope:

Summary Perform DASH contact search on the enclosure surfaces.

Description Performing a DASH contact search on the enclosure surfaces will prevent any faces in contact from being processed as part of an enclosure. Optionally one may define a relative tolerance based upon the characteristic element length, or absolute tolerances in positive and negative directions from the enclosure surface.

23. SPN RADIATION REFERENCE

23.1. RADIATIVE TRANSPORT

Radiative transport, which is another mode of heat transfer, describes the spatial variation of radiative intensity corresponding to a given direction and at a given wavelength within a radiatively participating medium. This is governed by the Boltzmann Equation or Radiative Transport Equation (RTE) which represents a balance between absorption, emission and scattering. For the purpose of thermal analysis, we make certain assumptions that simplify the RTE. These are

1. Gray Media: The optical properties of the material medium are not a function of wavelength i.e no spectral banding.
2. Steady State: Energy transport is propagated by photons which travel at the speed of light. This means that there are no transient effects relative to the time scale of other physics.
3. Isotropic Scattering: Since the scattering phase function is rarely known, we simply assume isotropic scattering where the probability of intensity being propagated in a given direction has equal probability of being scattered in another direction.

Given the above assumptions, we may write the RTE as

$$\Omega \cdot \nabla I(\Omega) + (\sigma_A + \sigma_S) I(\Omega) = \sigma_A I_b + \frac{\sigma_S}{4\pi} G, \quad (23.1)$$

where σ_A is the absorption coefficient, σ_S is the scattering coefficient, $I(\Omega)$ is the intensity along the direction Ω , T is the temperature and the angle-integrated intensity is $G = \int_{4\pi} I(\Omega) d\Omega$. The black body radiation, I_b is defined by $\frac{\sigma T^4}{\pi}$. Note that for situations in which the scattering coefficient is zero, the RTE reduces to a set of linear, decoupled equations for each intensity to be solved. Discrete Ordinate (DO) methods such as S_N have been developed to help solve this set of coupled equations by selecting a set of prescribed directions Ω_k , solving for the discrete intensities I_k and combining these intensities to represent the radiative field. These methods suffer from high computational cost due to the fact that a large number of ordinate directions is required to adequately resolve the intensity field and avoid “ray effects”. For a given quadrature order N , the number of ordinate directions scales as N^2 .

23.1.1. Simplified Spherical Harmonics (SP_N) Equations



Beta Capability: SP_N is not well tested and should not be considered a production capability

The simplified spherical harmonics (SP_N) approximation to the radiative transport equation (RTE) was first proposed by Gelbard for reactor analysis in the early 1960s. The initial derivation involved replacing the spatial derivatives in the 1D spherical harmonics (P_N) approximation with their 3D analogs. It was later shown that a more rigorous theoretical basis was possible and that the SP_N equations may be derived as either an asymptotic correction to the diffusion limit or from the use of certain trial functions in the self-adjoint variational characterization of the even-parity form of the RTE. There are a number of equivalent forms for the SP_N equations in the literature. We choose to use the “canonical” form which is derived from the 1D even-parity discrete ordinates equations.

$$-\nabla \cdot \left(\frac{\mu_n^2}{\sigma_T} \nabla I_n \right) + \sigma_T I_n = 4\pi \sigma_S \sum_{m=1}^{\frac{N+1}{2}} w_m I_m + \sigma_A I_b \quad (23.2)$$

where

- σ_T is the extinction coefficient, $\sigma_T = \sigma_A + \sigma_S$
- μ_n is the n th quadrature point in a $(N+1)$ -point Gauss set on $[-1, 1]$
- I_n is the angular intensity at quadrature point n
- w_n is the n^{th} quadrature weight

The appropriate boundary conditions for the “canonical” SP_N equations are derived from the boundary conditions for the 1D even-parity discrete ordinates equations. We consider a Mark boundary condition of the 1st order intensity BC

$$I_n = \epsilon I_b + (1 - \epsilon) \sum_{\vec{n} \cdot \vec{\Omega}_j < 0} I_j w_j \left| \vec{n} \cdot \vec{\Omega}_j \right| \quad (23.3)$$

such that in canonical form, it yields

$$-\frac{\mu_n}{\sigma_T} \nabla I_n \cdot \vec{n} = \frac{\epsilon}{2 - \epsilon} (I_n - I_b) + \frac{1 - \epsilon}{2 - \epsilon} \left[\frac{\sum_k \left(I_k - \frac{\mu_k}{\sigma_T} \nabla I_k \cdot \vec{n} \right) \mu_k w_k}{\sum \mu_k w_k} - I_n + \frac{\mu_n}{\sigma_T} \nabla I_n \cdot \vec{n} \right] \quad (23.4)$$

where

- ϵ is the emissivity
- $\vec{n}$ is the surface normal

The SP_N equations are solved for the unknown intensities to provide an approximate solution to the RTE. The angle-integrated intensity is then found and used in the source term for the material energy equation. It is to be noted from the form of the SP_N equations that this cannot be used in vacuum or near-vacuum situations where $\sigma_T \rightarrow 0$. Also analysis by Zheng et al shows that the existence of a unique solution may be proved when absorption effects are non-negligible and the geometry is small.

24. CONTACT REFERENCE

24.1. CONTACT OVERVIEW

The term "contact" refers to a situation where a simulation needs to be performed that spans a non-contiguously meshed interface, i.e. a nonconformal interface. One example of a nonconformal interface is one that has adjacent blocks and there appears to be a single node at a certain location in space on the interfaces between blocks, but in fact there are distinct nodes that have identical, or nearly identical coordinates. In other words, the mesh nodes have not been merged or equivalenced. More generally, a nonconformal interface does not require that mesh lines match at the interface between block boundaries.

There are two modeling situations that lead to the use of nonconformal interfaces in thermal analysis. The first occurs when compatibility conditions are enforced at the interface to require that the temperature be continuous across the interface. This situation arises as a convenient way to generate the mesh for particularly complex geometries since both parts can be meshed independently. The second modeling situation that occurs is not a matter of convenience, but of physics. It may be that two parts are known to fit imperfectly, so that there is a gap between the two parts that has a certain known resistance. In this case, the enforcement is known as gap conductance (or resistance) and enforces a discontinuous solution across the gap by modeling the energy flux that is "lost" across the gap.

In Aria, all contact is implemented via the nonconformal contact algorithm, and various enforcement strategies exist within this algorithm (see section on enforcement below). The enforcement strategies are similar to those that existed via the legacy generalized contact.



Warning: Nonconformal contact is now the default and recommended behavior for contact within aria. The legacy contact methods will be supported through release 4.50. Documentation for legacy versions of contact can be found in previous versions of the user manual.

The nonconformal contact method uses stk search and the dash library to identify surfaces in proximity to one another. The enforcement strategy is based on a discontinuous Galerkin approach that expresses the interaction as two surface integrals along the contact interface. The exact enforcement form depends on the chosen enforcement model. For a thermal problem with TIED_TEMPERATURE enforcement, one term in the surface integral penalizes the jump in the temperature weighted by an appropriate average surface conductance coefficient. The second term in the surface integral imposes the energy flux at the surface boundary, which is taken as the average energy flux on both surfaces as to be weakly conservative. If the mesh aligns perfectly at the interface such that the quadrature points of the two

facets match, i.e., no interpolation is needed, this method is also discretely conservative. Errors in conservation will exist in the general case due to the discrete nature approximating the integral, although this error should decrease with the same order as the underlying numerical method. Details of the contact specification and relevant options are in subsequent sections below.

Most common cases model contact between surfaces of standard volume elements (2D quadrilateral, 2D triangle, 3D tetrahedron or 3D hexahedron). When considering contact of shell elements with nonconformal interfaces, it is assumed that the shell nodes are coincident with nodes of a standard volume element on one side of the contact under consideration.



Warning: Shell support is limited in nonconformal contact. Specifically, contact along the edge of a shell element is not supported, i.e., a shell element that is perpendicular to another surface does not transmit a flux through the singular axis of the shell.

For a more detailed discussion of the mathematical basis of the nonconformal interface and enforcement strategies, please see the Aria Theory Manual.

24.1.1. Search and Contact Tolerance Calculation

The enforcement selected only acts upon surfaces that are defined to be in contact. Whether or not surfaces are in contact is determined via a normal tolerance that is either 1) set within the search options block of the contact definition (see syntax reference following this section), or 2) set via an automatic tolerancing operation. This normal tolerance is used on a per-integration-point projection to the closest surface, as shown in Figure 24.1-1.




Figure 24.1-1.. Calculation of contact distance per integration point.

In more detail: For a given surface that may be in contact, the enforcement strategy is expressed in terms of a surface integral on both surfaces (surface a and surface b in Figure 24.1-1). For evaluating the

enforcement kernel on surface a , the surface facets are iterated, as are the integration points within each facet. The closest surface is found, as defined by the smallest distance, L , from the integration point to the surface intersection along the normal direction (L in Figure 24.1-1). If $L < tol$, where tol is the contact normal tolerance, then that integration point is in contact and the enforcement kernel is evaluated. If no global or interaction specific contact normal tolerance is specified, the automatically calculated contact normal tolerance is used, which is calculated as the minimum elemental characteristic length over all surface elements in a given contact surface. The elemental characteristic length is defined as the minimum length between any two nodes on the surface element.

24.1.2. Contact Enforcement

Contact enforcement strategies are discussed in detail in the following enforcement sections; however, the Thermal-Fluids Team would like to provide guidance as to the thermal enforcement strategies with the highest pedigree of code testing, verification, and validation. For cases where there is no contact resistance, i.e., the physical temperature field is contiguous, the team recommends using the TIED_TEMPERATURE enforcement strategy. For cases with imperfect contact that can be modeled according to a contact resistance scheme, the team recommends using the GAP_CONDUCTANCE enforcement strategy.

24.2. CONTACT DEFINITION

Scope: Equation System

Begin Contact Definition *Contact_name*

Contact Smooth Surface *Surface_name* [Contains *List_of_instances...*]

Contact Surface *Surface_name* [Contains *List_of_instances...*]

Opposed Normal Threshold Angle {=|are|is} *Angle*

Output Rule {=|are|is} *OutputRule*

Search {=|are|is} *Type*

Skin All Blocks {=|are|is} *Option* [Exclude *Blocks_to_exlude...*]

Update Search Every n Steps

Visualize Contact

Begin Enforcement *Enforcement_name*

End

Begin Interaction *Interaction_name*

End

Begin Interaction Defaults

End

Begin Search Options *Search_options_name*

End

End

Summary Contains the commands needed to define contact for an analysis.

Description This block command defines a scenario for the contact model. The contact surfaces are defined, the interactions are set, and the type of contact enforcement is defined.

24.2.1. Contact Smooth Surface

Scope: Contact Definition

Contact Smooth Surface *Surface_name* [Contains *List_of_instances...*]

Parameter	Value	Default
<i>Surface_name</i>	string	undefined

Summary Defines a smooth surface made up of a set of sidesets in the mesh file to consider for contact.

24.2.2. Contact Surface

Scope: Contact Definition

Contact Surface *Surface_name* [Contains *List_of_instances...*]

Parameter	Value	Default
<i>Surface_name</i>	string	undefined

Summary Defines a surface made up of a set of surfaces in the mesh file to consider for contact. Specification of an element block implies that block skinning of the element block is to take place. The specific implementation of block skinning depends on the application.

24.2.3. Opposed Normal Threshold Angle

Scope: Contact Definition

Opposed Normal Threshold Angle `{=|are|is} Angle`

Parameter	Value	Default
<i>Angle</i>	real	90.0

Summary Assign the angle, in degrees, for which surface normals are considered to be opposed.

Description Prescribed angle must be greater or equal to 90 degrees.

Warning: This option is not recommended for general use but serves as a temporary patch that can be used for some problems.

24.2.4. Output Rule

Scope: Contact Definition

Output Rule `{=|are|is} OutputRule`

Parameter	Value	Default
<i>OutputRule</i>	{more verbose none summary verbose}	NONE

Summary Toggle amount of information output from the search.

24.2.5. Search

Scope: Contact Definition

Search `{=|are|is} Type`

Parameter	Value	Default
<i>Type</i>	{acme ars dash}	undefined

Summary Specify contact search algorithm. ACME-use acme node/face contact library DASH-use dash face/face contact methods inside of Presto. ARS-use ars node/face contact methods inside Adagio/Presto.

24.2.6. Skin All Blocks

Scope: Contact Definition

Skin All Blocks {=*|are|is|*} *Option* [Exclude *Blocks_to_exlude...*]

Parameter	Value	Default
<i>Option</i>	{off on}	undefined

Summary Informs the contact algorithms to skin all element blocks and then use the resulting surfaces in contact computations.

24.2.7. Update Search Every

Scope: Contact Definition

Update Search Every *n* Steps

Parameter	Value	Default
<i>n</i>	integer	undefined

Summary Force an updating of the contact search every N steps.

Description This command is useful if, for example, Aria is coupled to Adagio and the likelihood is strong that the mesh coordinates have changed significantly. Because contact surfaces may also appear in the definition of boundary conditions the application must selectively apply contact relations and boundary conditions appropriately. These issues are resolved automatically within the application code using the contact surface definitions and internal data masks.

24.2.8. Visualize Contact

Scope: Contact Definition

Summary Output contact surfaces with facets marked with 1 where contact is applied and 0 otherwise.

Description Enables output of surfaces where contact is active. Surface facets will be marked by whether contact constraints are applied on the facet - 1 or 0 otherwise.

Note: Visualization is enabled by default for contact defined using surface sidesets.

Warning: Use of this option is primarily for debugging purposes as the Results Output and History file will contain a skinned version of the contact element blocks. This may constitute a large amount of information for discontinuously meshed models.

24.3. ENFORCEMENT

Scope: Contact Definition

```
Begin Enforcement Enforcement_name

    Conductance Coefficient {=|are|is} Coeff

    Conductance Coefficient Contact Pressure Function {=|are|is} FName
    Using VarName

    Conductance Coefficient For EquationName {=|are|is} Model [
    ModelParams... ]

    Conductance Coefficient Fortran Subroutine {=|are|is} Name

    Conductance Coefficient Subroutine {=|are|is} FName

    Conductance Coefficient Temperature Function {=|are|is} FName

    Conductance Coefficient Time Function {=|are|is} FName

    Conductance Coefficient Voltage Function {=|are|is} FName

    Dash Penalty Factor {=|are|is} value

    Enforcement For EquationName {=|are|is} EnforcementModel [
    ModelParams... ]

    Integer Data Values...

    Real Data Values...

    Slave Variable Slave_field To Master_field

    Use Toggle Block ToggleName [ {@|at|for|in|on|over}
    ElementBlockList... ]

End
```

Summary Contains the commands needed to define contact enforcement for an analysis in Aria.

Description This block command is used to define the type of contact between the surfaces. The name of the enforcement is specified by the user. When the contact includes some contact resistance, the conductance coefficient for the contact between the two surfaces must be specified.

24.3.1. Conductance Coefficient

Scope: Enforcement

Conductance Coefficient {=|are|is} *Coeff*

Parameter	Value	Default
<i>Coeff</i>	real	undefined

Summary Set the constant valued contact conductance coefficient used by the GAP_CONDUCTANCE and CONDUCTANCE contact models.

Description This line command defines the value of the effective heat-transfer coefficient, h_c , for the interface condition between the two surfaces. The temperature drop across the interface, due to the contact resistance, is modeled using

$$q_i n_i|_{\Gamma_{m_1}} = h_c(T_{\Gamma_{m_1}} - T_{\Gamma_{m_2}}) = q_i n_i|_{\Gamma_{m_2}}$$

where the contact coefficient or contact conductance, $h_c(x_i, t, T_{\Gamma_{m_1}}, T_{\Gamma_{m_2}})$, is modeled using a correlation that is dependent upon the two surface temperatures, location, and interface conditions. Note that smaller values of CONDUCTANCE COEFFICIENT correspond to resistance contact while larger values tend toward tied contact.

24.3.2. Conductance Coefficient Contact Pressure Function

Scope: Enforcement

Conductance Coefficient Contact Pressure Function {=|are|is} *FName* Using *VarName*

Parameter	Value	Default
<i>FName</i>	string	undefined
<i>VarName</i>	string	undefined

Summary Gap conductance coefficient from a user function in VarName

Description See CONDUCTANCE COEFFICIENT line command.

24.3.3. Conductance Coefficient For

Scope: Enforcement

Conductance Coefficient For *EquationName* {=|are|is} *Model* [*ModelParams...*]

Parameter	Value	Default
<i>EquationName</i>	string	undefined
<i>Model</i>	string	undefined

Summary Choose the model for the conductance coefficient for the specified equation to be used in generalized contact.

Description Choose the model for the conductance coefficient for the specified equation to be used in generalized contact.

24.3.4. Conductance Coefficient Fortran Subroutine

Scope: Enforcement

Conductance Coefficient Fortran Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of a FORTRAN user subroutine that will be used to calculate the conductance coefficient.

24.3.5. Conductance Coefficient Subroutine

Scope: Enforcement

Conductance Coefficient Subroutine {=|are|is} *FName*

Parameter	Value	Default
<i>FName</i>	string	undefined

Summary Set the user defined contact conductance coefficient. See CONDUCTANCE COEFFICIENT line command for details.

Description The subroutine must satisfy the element signature. The subroutine is passed a pair of faces that are in contact, and is expected to populate a single value for the coefficient. The temperature at the current integration point and its projection onto the face across the interface is provided. The contact interface is processed twice—once from the left side and once from the right. Note that to ensure conservation, the subroutine should calculate the same value of the gap conductance on both sides of the interface.

24.3.6. Conductance Coefficient Temperature Function

Scope: Enforcement

Conductance Coefficient Temperature Function {=|are|is} *FName*

Parameter	Value	Default
<i>FName</i>	string	undefined

Summary Set the temperature dependent contact conductance coefficient.

Description See CONDUCTANCE COEFFICIENT line command.

24.3.7. Conductance Coefficient Time Function

Scope: Enforcement

Conductance Coefficient Time Function {=|are|is} *FName*

Parameter	Value	Default
<i>FName</i>	string	undefined

Summary Set the time dependent contact conductance coefficient.

Description See CONDUCTANCE COEFFICIENT line command.

24.3.8. Conductance Coefficient Voltage Function

Scope: Enforcement

Conductance Coefficient Voltage Function {=|are|is} *FName*

Parameter	Value	Default
<i>FName</i>	string	undefined

Summary Set the temperature dependent contact conductance coefficient.

Description See CONDUCTANCE COEFFICIENT line command.

24.3.9. Dash Penalty Factor

Scope: Enforcement

Dash Penalty Factor {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	real	undefined

Summary Defines a penalty factor to use for the dash constraints

24.3.10. Enforcement For

Scope: Enforcement

Enforcement For *EquationName* {=|are|is} *EnforcementModel* [*ModelParams...*]

Parameter	Value	Default
<i>EquationName</i>	string	undefined
<i>EnforcementModel</i>	string	undefined

Summary Defines the model for enforcement for the command block interactions, either tied or resistance/conductance contact. Tied contact can be of type generalized or Lagrange multiplier/MPC, where generalized contact is the preferred contact algorithm. [24.4](#)

Description This command line sets the type of contact problem for interactions defined in the current CONTACT DEFINITION command block and the equation to which the enforcement applies.

The Generalized contact enforcement model can be either GAP_CONDUCTANCE, CONDUCTANCE or TIED_DOF. In the case of resistance contact one must define a CONDUCTANCE COEFFICIENT model. To specify that TIED contact will be enforced for DOF my_DOF_name, the enforcement model will be TIED_my_DOF_name, where the solution DOF for Equationname is defined in the EQ command line.

Lagrange multiplier enforcement is specified simply as model TIED and must be accompanied by a SLAVE VARIABLE command line within the ENFORCEMENT command block. MPC contact requires that one supply MASTER and SLAVE surface definitions in the INTERACTION command block. Additionally one should consider using the MATRIX REDUCTION = FEI-REMOVE-SLAVES in the equation solver command block for MPC constraint reduction.

DASH contact enforcement will be enforced only in a TIED sense.

24.3.11. Integer Data

Scope: Enforcement

Integer Data *Values...*

Parameter	Value	Default
<i>Values</i>	integer...	undefined

Summary List of integer data values to be used by the FORTRAN user subroutine. Copies of these values are provided to the subroutine hence changes to these values within the subroutine are not saved.

24.3.12. Real Data

Scope: Enforcement

Real Data *Values...*

Parameter	Value	Default
<i>Values</i>	real...	undefined

Summary List of real data values to be used by the FORTRAN user subroutine. Copies of these values are provided to the subroutine hence changes to these values within the subroutine are not saved.

24.3.13. Slave Variable

Scope: Enforcement

Slave Variable *Slave_field* To *Master_field*

Parameter	Value	Default
<i>Slave_field</i>	string	undefined
<i>Master_field</i>	string	undefined

Summary Defines the variables involved in enforcement for this interaction.

Description This line command sets the master and slave variables involved in the current tied contact definition.

24.3.14. Use Toggle Block

Scope: Enforcement

Use Toggle Block *ToggleName* [{@|at|for|in|on|over} *ElementBlockList...*]

Parameter	Value	Default
<i>ToggleName</i>	string	undefined

Summary Specification for toggling entities in the computational model based on Toggle Block parameters. When used at the region level, the list of element blocks to be toggled must be provided. Otherwise a listing of entities is not needed as the Toggle Block will be associated with the command line or the enclosing command block.

24.4. ENFORCEMENT MODELS

24.4.1. Enforcement For Continuity = Tied Ip Continuity

Scope: Enforcement

24.4.2. Enforcement For Current = Bulter Volmer

Scope: Enforcement

Enforcement For Current = Bulter Volmer [Toggle = *toggle* | F = *f* | R = *r* | Alpha_A = *alpha_a* | Alpha_C = *alpha_c*]

Parameter	Value	Default
<i>toggle</i>	"string"	undefined
<i>f</i>	real	undefined
<i>r</i>	real	undefined
<i>alpha_a</i>	real	undefined
<i>alpha_c</i>	real	undefined

24.4.3. Enforcement For Current = Conductance

Scope: Enforcement

Enforcement For Current = Conductance [Toggle = *toggle*]

Parameter	Value	Default
<i>toggle</i>	"string"	undefined

Summary Applies a contact current flux of the form $C(V_1 - V_2)$ to sides 1 and 2 of the contact interface where C is a user specified conductance coefficient. Used in conjunction with a CONDUCTANCE COEFFICIENT model.

24.4.4. Enforcement For Current = Gap Conductance

Scope: Enforcement

Enforcement For Current = Gap Conductance [Toggle = *toggle*]

Parameter	Value	Default
<i>toggle</i>	"string"	undefined

Summary Applies a contact current flux of the form $\alpha(\sigma_1 \nabla V_1 \cdot n_1 + \sigma_2 \nabla V_2 \cdot n_2 + \tilde{C}(V_1 - V_2))/2$ to sides 1 and 2 of the contact interface where $\alpha = 1 - \bar{C}/2C$. With C , a user defined coefficient and $\bar{C}$, an average conductance coefficient, then $\tilde{C} = 2C$ for $C \ll \bar{C}$ and $\bar{C}$ otherwise. Used in conjunction with a CONDUCTANCE COEFFICIENT model.

24.4.5. Enforcement For Current = Tied Voltage

Scope: Enforcement

Enforcement For Current = Tied Voltage [Toggle = *toggle* | Co_Field = *co_field*]

Parameter	Value	Default
<i>toggle</i>	"string"	undefined
<i>co_field</i>	integer	undefined

Summary Applies a contact current flux of the form $(\sigma_1 \nabla V_1 \cdot n_1 + \sigma_2 \nabla V_2 \cdot n_2 + \bar{C}(V_1 - V_2))/2$ to sides 1 and 2 of the contact interface where σ is the electrical conductivity and $\bar{C}$ is an average conductance coefficient.

24.4.6. Enforcement For Cvfem Continuity = Tied Continuity

Scope: Enforcement

24.4.7. Enforcement For Cvfem Energy = Conductance

Scope: Enforcement

Enforcement For Cvfem Energy = Conductance [Toggle = *toggle* | Bulk_Node = *bulk_node*]

Parameter	Value	Default
<i>toggle</i>	"string"	undefined
<i>bulk_node</i>	"string"	undefined

Summary Applies a contact heat flux of the form $C(T_1 - T_2)$ to sides 1 and 2 of the contact interface where C is a user specified conductance coefficient. Used in conjunction with a CONDUCTANCE COEFFICIENT model.

24.4.8. Enforcement For Cvfem Energy = Gap Conductance

Scope: Enforcement

Enforcement For Cvfem Energy = Gap Conductance [Toggle = *toggle*]

Parameter	Value	Default
<i>toggle</i>	"string"	undefined

Summary Applies a contact heat flux of the form $\alpha(k_1 \nabla T_1 \cdot n_1 + k_2 \nabla T_2 \cdot n_2 + \tilde{h}(T_1 - T_2))/2$ to sides 1 and 2 of the contact interface where $\alpha = 1 - \bar{h}/2h$. With h , a user defined coefficient and $\bar{h}$, an average conductance coefficient, then $\tilde{h} = 2h$ for $h \ll \bar{h}$ and $\bar{h}$ otherwise. Used in conjunction with a CONDUCTANCE COEFFICIENT model.

24.4.9. Enforcement For Cvfem Energy = Tied Temperature

Scope: Enforcement

Enforcement For Cvfem Energy = Tied Temperature [Toggle = *toggle* | Co_Field = *co_field*]

Parameter	Value	Default
<i>toggle</i>	"string"	undefined
<i>co_field</i>	integer	undefined

Summary Applies a contact heat flux of the form $(k_1 \nabla T_1 \cdot n_2 + k_2 \nabla T_2 \cdot n_2 + \bar{h}(T_1 - T_2))/2$ to sides 1 and 2 of the contact interface where k is the thermal conductivity and $\bar{h}$ is an average conductance coefficient.

24.4.10. Enforcement For Cvfem Lumped Projection = Tied Gradp

Scope: Enforcement

24.4.11. Enforcement For Cvfem Momentum = Tied Momentum

Scope: Enforcement

24.4.12. Enforcement For Cvfem Projection = Tied Gradp

Scope: Enforcement

24.4.13. Enforcement For Cvfem Specific Dissipation Rate = Tied Sdr

Scope: Enforcement

Summary Tied_Sdr contact flux; CVFEM pressure stabilization included

24.4.14. Enforcement For Cvfem Turbulent Kinetic Energy = Tied Tke

Scope: Enforcement

Summary Tied_Tke contact flux; CVFEM pressure stabilization included

24.4.15. Enforcement For Energy = Cht Robin

Scope: Enforcement

```
Enforcement For Energy = Cht Robin [ Toggle = toggle |  
Opposite_Material_Phase = opposite_material_phase | Opposite_Flux_Name =  
opposite_flux_name | Coeff_Scaling = coeff_scaling ]
```

Parameter	Value	Default
<i>toggle</i>	"string"	undefined
<i>opposite_material_phase</i>	"string"	undefined
<i>opposite_flux_name</i>	"string"	undefined
<i>coeff_scaling</i>	real	undefined

Summary Applies a Robin-style BC for the energy equation: $F_{local} = F_{bc} + \alpha(T_{local} - T_{bc})$.

24.4.16. Enforcement For Energy = Conductance

Scope: Enforcement

```
Enforcement For Energy = Conductance [ Toggle = toggle ]
```

Parameter	Value	Default
<i>toggle</i>	"string"	undefined

Summary Applies a contact heat flux of the form $C(T_1 - T_2)$ to sides 1 and 2 of the contact interface where C is a user specified conductance coefficient. Used in conjunction with a CONDUCTANCE COEFFICIENT model.

24.4.17. Enforcement For Energy = Conductance Salgon

Scope: Enforcement

```
Enforcement For Energy = Conductance Salgon [ Toggle = toggle | A = a | B =  
b | Xi = xi ]
```

Parameter	Value	Default
<i>toggle</i>	"string"	undefined
<i>a</i>	real	undefined
<i>b</i>	real	undefined
<i>xi</i>	real	undefined

Summary Applies a contact heat flux of the form $(2\hat{k}a)/(\pi b^2(1 - 1, 14\xi))(T_1 - T_2)$ to sides 1 and 2 of the contact interface where k is the thermal conductivity, $\hat{k} = (k_1 + k_2)/(k_1 k_2/)$ and ξ is a user specified parameter (Salgon,1997).

24.4.18. Enforcement For Energy = Contact Resistance

Scope: Enforcement

Enforcement For Energy = Contact Resistance [Toggle = *toggle* |
Opposite_Material_Phase = *opposite_material_phase*]

Parameter	Value	Default
<i>toggle</i>	"string"	undefined
<i>opposite_material_phase</i>	"string"	undefined

Summary Applies a contact heat flux of the form $h(T - T_{opp})$ where h is the gap conductance coefficient defined for the surface material and the material phase of T_{opp} is optionally specified.

24.4.19. Enforcement For Energy = Gap Conductance

Scope: Enforcement

Enforcement For Energy = Gap Conductance [Toggle = *toggle*]

Parameter	Value	Default
<i>toggle</i>	"string"	undefined

Summary Applies a contact heat flux of the form $\alpha(k_1 \nabla T_1 \cdot n_1 + k_2 \nabla T_2 \cdot n_2 + \tilde{h}(T_1 - T_2))/2$ to sides 1 and 2 of the contact interface where $\alpha = 1 - \bar{h}/2h$. With h , a user defined coefficient and $\bar{h}$, an average conductance coefficient, then $\tilde{h} = 2h$ for $h \ll \bar{h}$ and $\bar{h}$ otherwise. Used in conjunction with a CONDUCTANCE COEFFICIENT model.

24.4.20. Enforcement For Energy = Nitsche Tied

Scope: Enforcement

Enforcement For Energy = Nitsche Tied [Toggle = *toggle* | Co_Field = *co_field*
| Multiplier = *multiplier*]

Parameter	Value	Default
<i>toggle</i>	"string"	undefined
<i>co_field</i>	integer	undefined
<i>multiplier</i>	real	undefined

Summary Applies a contact heat flux as described in "A robust Nitsches formulation for interface problems" by Annavarapu et al. 2012.

24.4.21. Enforcement For Energy = Phase Change

Scope: Enforcement

Enforcement For Energy = Phase Change [Toggle = *toggle*]

Parameter	Value	Default
<i>toggle</i>	"string"	undefined

Summary Applies a energy flux to an interface based on phase change, as $q = v\rho_s(T_s C_{p,s} - T_g C_{p,g} + L)$ to sides *s* and *g* of the contact interface where *v* is the velocity ρ is the interface density C_p is the specific heat and *L* is the latent heat of fusion.

24.4.22. Enforcement For Energy = Tied D Style Rad Temperature

Scope: Enforcement

Enforcement For Energy = Tied D Style Rad Temperature [Toggle = *toggle* | Lambda_Scaling = *lambda_scaling*]

Parameter	Value	Default
<i>toggle</i>	"string"	undefined
<i>lambda_scaling</i>	real	undefined

Summary Applies a contact heat flux of the form $\lambda\sigma\epsilon(T_1^4 - T_2^4)$ to sides 1 and 2 of the contact interface where λ is a scaling parameter, σ is the stefan boltzmann constant ϵ is the emissivity. This model is similar to the DASH_TIED model but for radiation rather than convection.

24.4.23. Enforcement For Energy = Tied D Style Temperature

Scope: Enforcement

Enforcement For Energy = Tied D Style Temperature [Toggle = *toggle* | Lambda_Scaling = *lambda_scaling*]

Parameter	Value	Default
<i>toggle</i>	"string"	undefined
<i>lambda_scaling</i>	real	undefined

Summary Applies a contact heat flux of the form $\lambda\bar{h}(T_1 - T_2)$ to sides 1 and 2 of the contact interface where λ is a penalty parameter, $\bar{h}$ is an average conductance coefficient. This model is similar to the DASH_TIED model.

24.4.24. Enforcement For Energy = Tied Ip Temperature

Scope: Enforcement

Enforcement For Energy = Tied Ip Temperature [Toggle = *toggle* | Co_Field = *co_field*]

Parameter	Value	Default
<i>toggle</i>	"string"	undefined
<i>co_field</i>	integer	undefined

Summary Applies a contact heat flux of the form $(k_1 \nabla T_1 \cdot n_1 + k_2 \nabla T_2 \cdot n_2 + \bar{h}(T_1 - T_2))/2$ to sides 1 and 2 of the contact interface where k is the thermal conductivity and $\bar{h}$ is an average conductance coefficient. Additionally an interior penalty jump term is also applied.

24.4.25. Enforcement For Energy = Tied Temperature

Scope: Enforcement

Enforcement For Energy = Tied Temperature [Toggle = *toggle* | Co_Field = *co_field*]

Parameter	Value	Default
<i>toggle</i>	"string"	undefined
<i>co_field</i>	integer	undefined

Summary Applies a contact heat flux of the form $(k_1 \nabla T_1 \cdot n_1 + k_2 \nabla T_2 \cdot n_2 + \bar{h}(T_1 - T_2))/2$ to sides 1 and 2 of the contact interface where k is the thermal conductivity and $\bar{h}$ is an average conductance coefficient.

24.4.26. Enforcement For Hfem Continuity = Tied Ip Continuity

Scope: Enforcement

24.4.27. Enforcement For Hfem Momentum = Tied Ip Momentum

Scope: Enforcement

24.4.28. Enforcement For Hfem Momentum = Tied Momentum

Scope: Enforcement

24.4.29. Enforcement For Lubrication Height = Deforming

Scope: Enforcement

Enforcement For Lubrication Height = Deforming [Hmin = *hmin*]

Parameter	Value	Default
<i>hmin</i>	real	undefined

Summary Lubrication height that deforms by the displacement of the adjoining volume region.

24.4.30. Enforcement For Mass Balance = Bulk Node Mass Open

Scope: Enforcement

Enforcement For Mass Balance = Bulk Node Mass Open [Bulk_Node = *bulk_node*]

Parameter	Value	Default
<i>bulk_node</i>	"string"	undefined

Summary Open BC between a porous medium and a bulk node

24.4.31. Enforcement For Mass Balance = Bulk Node Open

Scope: Enforcement

Enforcement For Mass Balance = Bulk Node Open [Bulk_Node = *bulk_node*]

Parameter	Value	Default
<i>bulk_node</i>	"string"	undefined

24.4.32. Enforcement For Mass Balance = Bulk Node Species Open

Scope: Enforcement

Enforcement For Mass Balance = Bulk Node Species Open [Bulk_Node = *bulk_node*]

Parameter	Value	Default
<i>bulk_node</i>	"string"	undefined

24.4.33. Enforcement For Mass Balance = Conserved Mass

Scope: Enforcement

Enforcement For Mass Balance = Conserved Mass [Co_Field = *co_field*]

Parameter	Value	Default
<i>co_field</i>	integer	undefined

Summary Continuous mass balance and capillary pressure, discontinuous nonwetting phase saturation.

24.4.34. Enforcement For Mesh = Lubrication Pressure

Scope: Enforcement

Summary Lubrication pressure mesh flux

24.4.35. Enforcement For Momentum = Tied Ip Momentum

Scope: Enforcement

24.4.36. Enforcement For Momentum = Tied Momentum

Scope: Enforcement

24.4.37. Enforcement For Porous Enthalpy = Bulk Node Open

Scope: Enforcement

Enforcement For Porous Enthalpy = Bulk Node Open [Bulk_Node = *bulk_node*]

Parameter	Value	Default
<i>bulk_node</i>	"string"	undefined

24.4.38. Enforcement For Porous Enthalpy = Bulk Node Open Uncoupled

Scope: Enforcement

```
Enforcement For Porous Enthalpy = Bulk Node Open Uncoupled [ Bulk_Node =  
bulk_node ]
```

Parameter	Value	Default
<i>bulk_node</i>	"string"	undefined

24.4.39. Enforcement For Porous Enthalpy = Contact Resistance

Scope: Enforcement

```
Enforcement For Porous Enthalpy = Contact Resistance [  
Opposite_Material_Phase = opposite_material_phase | Bulk_Node = bulk_node  
]
```

Parameter	Value	Default
<i>opposite_material_phase</i>	"string"	undefined
<i>bulk_node</i>	"string"	undefined

Summary Applies a heat flux of the form $J \cdot n = h(T - T_{opp})$ where h is the gap conductance coefficient defined for the surface material and the material phase of T_{opp} is optionally specified.

24.4.40. Enforcement For Porous Species = Bulk Node Open All Inflow

Scope: Enforcement

```
Enforcement For Porous Species = Bulk Node Open All Inflow [ Bulk_Node =  
bulk_node ]
```

Parameter	Value	Default
<i>bulk_node</i>	"string"	undefined

24.4.41. Enforcement For Voltage = Tied Voltage

Scope: Enforcement

Enforcement For Voltage = Tied Voltage [Toggle = *toggle* | Co_Field = *co_field*]

Parameter	Value	Default
<i>toggle</i>	"string"	undefined
<i>co_field</i>	integer	undefined

Summary Applies a contact electric displacement flux of the form $(\epsilon_1 \nabla V_1 \cdot n_1 + \epsilon_2 \nabla V_2 \cdot n_2 + \bar{C}(V_1 - V_2))/2$ to sides 1 and 2 of the contact interface where ϵ is the electrical permittivity and $\bar{C}$ is an average conductance coefficient.

24.5. INTERACTION

Scope: Contact Definition

Begin Interaction *Interaction_name*

Normal Tolerance {=|are|is} *Distance*

Surfaces {=|are|is} *Surfaces...*

End

Summary Contains the commands needed to define a surface-surface interaction.

24.5.1. Normal Tolerance

Scope: Interaction

Normal Tolerance {=|are|is} *Distance*

Parameter	Value	Default
<i>Distance</i>	real	undefined

Summary Set distance of normal tolerance.

24.5.2. Surfaces

Scope: Interaction

Surfaces {=|are|is} *Surfaces...*

Parameter	Value	Default
<i>Surfaces</i>	string...	undefined

Summary Defines a pairwise set of surfaces for which to turn on interactions

24.5.3. Normal Tolerance

Scope:

Normal Tolerance {=|are|is} *Distance*

Parameter	Value	Default
<i>Distance</i>	real	undefined

Summary Set distance of normal tolerance.

24.6. SEARCH OPTIONS

Scope: Contact Definition

Begin Search Options *Search_options_name*

Developer Command: Ngp Search {=|are|is} *Option*

Normal Tolerance {=|are|is} *Distance*

Search Method {=|are|is} *SearchMethod*

End

Summary Contains the commands to set the search options

24.6.1. Developer Command: Ngp Search

Scope: Search Options

Developer Command: Ngp Search {=|are|is} *Option*

Parameter	Value	Default
<i>Option</i>	{off on}	undefined

Summary Turn on the GPU based bounding box search when running on a GPU platform.

24.6.2. Normal Tolerance

Scope: Search Options

Normal Tolerance {=|are|is} *Distance*

Parameter	Value	Default
<i>Distance</i>	real	undefined

Summary Set distance of normal tolerance.

24.6.3. Search Method

Scope: Search Options

Search Method {=|are|is} *SearchMethod*

Parameter	Value	Default
<i>SearchMethod</i>	{boost kdtree}	NONE

Summary Set the search method to be used with nonconformal contact.

24.6.4. Normal Tolerance

Scope:

Normal Tolerance {=|are|is} *Distance*

Parameter	Value	Default
<i>Distance</i>	real	undefined

Summary Set distance of normal tolerance.

25. OUTPUT REFERENCE

25.1. OUTPUT OVERVIEW

Output is divided into three major categories, Results output, Heartbeat output and Restart output. Results output contains binary format simulation results in a form suitable for visualization. While the Results output usually corresponds to the entire model, it can also be applied to portions of the model. Heartbeat output is generally written to a text file and provides a convenient means of monitoring intermediate simulation results. Restart output (Restart Data) is specialized for use in analyses that may not complete in a single job submission but might complete when continued from a previous termination time.

When using Results output or Heartbeat output one should note that the output request must be made using the internal Field name [2.10](#), most frequently solution->field_name or pp->postprocess_name. If the internal Field name is not used in the these requests output cannot be generated for that Field and a warning to that effect will be written to the log file. Global variables may also be output to the Results and Heartbeat output files. A list of all fields and global variables available for output in a particular model is output to the log file immediately after the mesh is read. This list can be previewed by running aria with the -check-input option that will load verify the input syntax, read the mesh, print the variables available for output, and then exit.

Depending upon the application one may wish to define multiple Results output or Heartbeat output command blocks. In doing so one must recognize that output time or output interval specifications are cumulative over the various output requests. Note that because time stepping accommodates simulation output requests, inconsistency of output frequency specification among multiple Results output blocks can produce unexpected/undesirable behavior in the solution time stepping.

Commands pertinent to the definition of Restart are included in this section. These commands describe management of restart files and content of the files. The intent of restart is to begin a new sequence of calculations using the entire content of the restart file. Those wishing to restart a simulation using only part of the results may wish to consider using the IC READ_FILE option [8.7](#). The invocation of restart within a simulation (specifying when it should start) is outlined elsewhere in this document [3.10](#).

Within the input file Output command blocks will appear at the Region scope as illustrated below.

```
.  
.   
.   
Begin Procedure My_Aria_Procedure  
.
```

```

.
Begin Aria Region My_Region
.
.
Begin Results output my_output
.
.
End Results Output my_output

Begin Heartbeat Output my_values
.
.
End Heartbeat Output

Begin Restart output go_again
.
.
End Restart output
.
.
End

End
.
.

```

25.2. RESULTS OUTPUT

Scope: Encore Region

```

Begin Results Output Label

    Additional Steps {=|are|is} List_of_steps...
    Additional Times {=|are|is} List_of_times...
    At Step n Option {=|are|is} m
    At Time Dt1 Option {=|are|is} Dt2
    Component Separator Character {=|are|is} Separator
    Database Name {=|are|is} StreamName
    Database Type {=|are|is} DatabaseType
    Edge [ VariableList... ]
    Edge Variables {=|are|is} [ VariableList... ]

```

Element [*VariableList...*]
 Element Variables {=|are|is} [*VariableList...*]
 Enable Large Ids
 Exclude {=|are|is} [*ElementBlockList...*]
 Exists *Option1 Option2*
 Face [*VariableList...*]
 Face Variables {=|are|is} [*VariableList...*]
 Global [*Variables...*]
 Global Variables {=|are|is} [*Variables...*]
 Include {=|are|is} [*ElementBlockList...*]
 Nodal [*VariableList...*]
 Nodal Variables {=|are|is} [*VariableList...*]
 Node [*VariableList...*]
 Node Variables {=|are|is} [*VariableList...*]
 Nodeset [*VariableList...*]
 Nodeset Variables {=|are|is} [*VariableList...*]
 Output Mesh {=|are|is} *OutputMesh*
 Output On Signal {=|are|is} *Signals*
 Overwrite *Option1 Option2*
 Property *PropertyName* {=|are|is} *PropertyValue*
 Sideset [*VariableList...*]
 Sideset Variables {=|are|is} [*VariableList...*]
 Start Time {=|are|is} *Start_time*
 Surface [*VariableList...*]
 Surface Variables {=|are|is} [*VariableList...*]
 Synchronize Output
 Termination Time {=|are|is} *Final_time*
 Timeseries Name {=|are|is} *filename*
 Timestep Adjustment Interval {=|are|is} *Nsteps*
 Title


```

Use External Control
Use Output Scheduler Timer_name
Begin Catalyst Label
End

```

End

Summary Describes the location and type of the output stream used for outputting results for the enclosing region.

25.2.1. Additional Steps

Scope: Results Output

Additional Steps {=*|are|is|*} *List_of_steps...*

Parameter	Value	Default
<i>List_of_steps</i>	integer...	undefined

Summary Additional simulation steps when output should occur.

25.2.2. Additional Times

Scope: Results Output

Additional Times {=*|are|is|*} *List_of_times...*

Parameter	Value	Default
<i>List_of_times</i>	real...	undefined

Summary Additional simulation times when output should occur.

25.2.3. At Step

Scope: Results Output

At Step *n Option* {=*|are|is|*} *m*

Parameter	Value	Default
<i>n</i>	integer	undefined
<i>Option</i>	{increment interval}	undefined
<i>m</i>	integer	undefined

Summary Specify an output interval in terms of the internal iteration step count. The first step specifies the step count at the beginning of this interval and the second step specifies the output frequency to be used within this interval.

25.2.4. At Time

Scope: Results Output

At Time *Dt1 Option* {=|are|is} *Dt2*

Parameter	Value	Default
<i>Dt1</i>	real	undefined
<i>Option</i>	{increment interval}	undefined
<i>Dt2</i>	real	undefined

Summary Specify an output interval in terms of the internal simulation time. The first time specifies the time at the beginning of this time interval and the second time specifies the output frequency to be used within this interval.

25.2.5. Component Separator Character

Scope: Results Output

Component Separator Character {=|are|is} *Separator*

Parameter	Value	Default
<i>Separator</i>	string	undefined

Summary The separator is the single character used to separate the output variable basename (e.g. "stress") from the suffices (e.g. "xx", "yy") when displaying the names of the individual variable components. For example, the default separator is "_", which results in names similar to "stress_xx", "stress_yy", ... "stress_zx". To eliminate the separator, specify an empty string ("") or NONE.

25.2.6. Database Name

Scope: Results Output

Database Name {=|are|is} *StreamName*

Parameter	Value	Default
<i>StreamName</i>	string	undefined

Summary The base name of the database containing the output results. If the filename begins with the '/' character, it is an absolute path; otherwise, the path to the current directory will be prepended to the name. If this line is omitted, then a filename will be created from the basename of the input file with a ".e" suffix appended.

25.2.7. Database Type

Scope: Results Output

Database Type {=|are|is} *DatabaseType*

Parameter	Value	Default
<i>DatabaseType</i>	{catalyst dof dof_exodus exodus exodusii generated genesis parallel_exodus}	undefined

Summary The database type/format to be used for the output results.

25.2.8. Edge

Scope: Results Output

Summary Define the variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line. The entities that this variable are written to can also be limited or specified with "exclude list_of_entities" or "include list_of_entities". Edge variables are not supported for all database types.

25.2.9. Edge Variables

Scope: Results Output

Summary Define the variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line. The entities that this variable are written to can also be limited or specified with "exclude list_of_entities" or "include list_of_entities". Edge variables are not supported for all database types.

25.2.10. Element

Scope: Results Output

Summary Define the variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line. The entities that this variable are written to can also be limited or specified with "exclude list_of_entities" or "include list_of_entities"

25.2.11. Element Variables

Scope: Results Output

Summary Define the variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line. The entities that this variable are written to can also be limited or specified with "exclude list_of_entities" or "include list_of_entities"

25.2.12. Enable Large Ids

Scope: Results Output

Summary Enable 64 bit entity IDs for output

25.2.13. Exclude

Scope: Results Output

Summary Specify that the results file will only contain a subset of the element blocks in the analysis model. The element_block_list lists only the blocks which will not be output to the results database.

25.2.14. Exists

Scope: Results Output

Exists *Option1* *Option2*

Parameter	Value	Default
<i>Option1</i>	{= is}	undefined
<i>Option2</i>	{abort add_suffix append overwrite}	undefined

Summary Specify the behavior when creating this database and there is an existing file with the same name. The default behavior is "OVERWRITE" which deletes the existing file and creates a new file of the same name. "APPEND" will (if possible) append the new data to the end of the existing file. "ABORT" will print an error message and end the analysis. "ADD_SUFFIX" will add a -s??? suffix where the ??? is replaced by a sequential number starting at 0002.

25.2.15. Face

Scope: Results Output

Summary Define the variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line. The entities that this variable are written to can also be limited or specified with "exclude list_of_entities" or "include list_of_entities". Face variables are not supported for all database types.

25.2.16. Face Variables

Scope: Results Output

Summary Define the variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line. The entities that this variable are written to can also be limited or specified with "exclude list_of_entities" or "include list_of_entities". Face variables are not supported for all database types.

25.2.17. Global

Scope: Results Output

Summary Define the global variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line.

25.2.18. Global Variables

Scope: Results Output

Summary Define the global variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line.

25.2.19. Include

Scope: Results Output

Summary Specify that the results file will only contain a subset of the element blocks in the analysis model. The element_block_list lists only the blocks which will be output to the results database.

25.2.20. Nodal

Scope: Results Output

Summary Define the nodal variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line.

25.2.21. Nodal Variables

Scope: Results Output

Summary Define the nodal variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line.

25.2.22. Node

Scope: Results Output

Summary Define the nodal variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line.

25.2.23. Node Variables

Scope: Results Output

Summary Define the nodal variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line.

25.2.24. Nodeset

Scope: Results Output

Summary Define the variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line. The entities that this variable are written to can also be limited or specified with "exclude list_of_entities" or "include list_of_entities". Nodeset variables are not supported for all database types.

25.2.25. Nodeset Variables

Scope: Results Output

Summary Define the variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line. The entities that this variable are written to can also be limited or specified with "exclude list_of_entities" or "include list_of_entities". Nodeset variables are not supported for all database types.

25.2.26. Output Mesh

Scope: Results Output

Output Mesh {= | are | is} *OutputMesh*

Parameter	Value	Default
<i>OutputMesh</i>	{exposed surface refined unrefined}	undefined

Summary Use this command to turn on "unrefined" as the output mesh. The default behavior is "refined", in which field variables are output on the current mesh, which may have been refined (either uniformly or adaptively) or had its topology altered in some way (e.g., dynamic load balancing) with respect to the original mesh read from the input file. By specifying "Output Mesh = unrefined", all output variables are output only on the original mesh objects read from the input file.

25.2.27. Output On Signal

Scope: Results Output

Output On Signal {= | are | is} *Signals*

Parameter	Value	Default
<i>Signals</i>	{sigabrt sigalrm sigfpe sighup sigill sigint sigkill sigpipe sigquit sigsegv sigterm sigusr1 sigusr2}	undefined

Summary When the specified signal is raised, the output stream associated with this block will be output.

25.2.28. Overwrite

Scope: Results Output

Overwrite *Option1 Option2*

Parameter	Value	Default
<i>Option1</i>	{= is}	undefined
<i>Option2</i>	{false no off on true yes}	undefined

Summary (DEPRECATED, Use EXISTS) Specify whether the database should be overwritten if it exists. The default behavior is to overwrite unless this command is specified in the output block and either off, false, or no is specified.

25.2.29. Property

Scope: Results Output

Property *PropertyName* {=|are|is} *PropertyValue*

Parameter	Value	Default
<i>PropertyName</i>	string	undefined
<i>PropertyValue</i>	string	undefined

Summary Define a database property named "PropertyName" with the value "PropertyValue". If PropertyValue consists of all digits, it will define an integer property. If PropertyValue is "true" or "yes" or "false" or "no", it will define a logical property; otherwise it will define a string property. Supported properties are typically database dependent; Current properties are: COMPRESSION_LEVEL = [0..9] (off) COMPRESSION_SHUFFLE = true|false|on|off (off) FILE_TYPE = netcdf4 (forces use of netcdf-4 hdf5-based file) (netcdf3) INTEGER_SIZE_DB = 4|8 (4) INTEGER_SIZE_API = 4|8 (4) REAL_SIZE_DB = 4|8 (8 is default) LOGGING = true|false|on|off (off) MAX_NAME_LENGTH = value (32)

25.2.30. Sideset

Scope: Results Output

Summary Define the variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line. The entities that this variable are written to can also be limited or specified with "exclude list_of_entities" or "include list_of_entities". Face variables are not supported for all database types.

25.2.31. Sideset Variables

Scope: Results Output

Summary Define the variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line. The entities that this variable are written to can also be limited or specified with "exclude list_of_entities" or "include list_of_entities". Face variables are not supported for all database types.

25.2.32. Start Time

Scope: Results Output

Start Time {=|are|is} *Start_time*

Parameter	Value	Default
<i>Start_time</i>	real	undefined

Summary Specify the time to start outputting results from this output request block. This time overrides all 'at time' and 'at step' specifications.

25.2.33. Surface

Scope: Results Output

Summary Define the variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line. The entities that this variable are written to can also be limited or specified with "exclude list_of_entities" or "include list_of_entities". Face variables are not supported for all database types.

25.2.34. Surface Variables

Scope: Results Output

Summary Define the variables that should be written to the results database. If "variable" is entered, then its name will be used on the output database. If "variable as db_name" is entered, then "db_name" will be the name used on the database for the internal variable "variable". Multiple "variable" or "variable as db_name" entries are allowed on the same line. The entities that this variable are written to can also be limited or specified with "exclude list_of_entities" or "include list_of_entities". Face variables are not supported for all database types.

25.2.35. Synchronize Output

Scope: Results Output

Summary In an analysis with multiple regions, it is sometimes desirable to synchronize the output of results data between the regions. This can be done by adding the SYNCHRONIZE OUTPUT command line to the results output block. If a results block has this set, then it will write output whenever a previous region writes output. The ordering of regions is based on the order in the input file, algorithmic considerations, or by solution control specifications.

Although the USE OUTPUT SCHEDULER command line can also synchronize output between regions, the SYNCHRONIZE OUTPUT command line will synchronize the output with regions where the output frequency is not under the direct control of the Sierra IO system. Examples of this are typically coupled applications where one or more of the codes are not Sierra-based applications such as Alegra and CTH. A results block with SYNCHRONIZE OUTPUT specified will also synchronize its output with the output of the external code.

The SYNCHRONIZE OUTPUT command can be used with other output scheduling commands such as time-based or step-based output specifications.

25.2.36. Termination Time

Scope: Results Output

Termination Time {=|are|is} *Final_time*

Parameter	Value	Default
<i>Final_time</i>	real	undefined

Summary Specify the time to stop outputting results from this output request block.

25.2.37. Timeseries Name

Scope: Results Output

Timeseries Name {=|are|is} *filename*

Parameter	Value	Default
<i>filename</i>	string	undefined

Summary Optionally specify a filename for a timeseries file that outputs the root database filename in the order that they are written. This is useful when running on large numbers of processors with many mesh-modes that cause simple disk operations to hang.

25.2.38. Timestep Adjustment Interval

Scope: Results Output

Timestep Adjustment Interval `{=|are|is} Nsteps`

Parameter	Value	Default
<i>Nsteps</i>	integer	undefined

Summary Specify the number of steps to 'look ahead' and adjust the timestep to ensure that the specified output times or simulation end time will be hit 'exactly'.

25.2.39. Title

Scope: Results Output

Summary Specify the title to be used for this specific output block.

25.2.40. Use External Control

Scope: Results Output

Summary Do not schedule any results output but instead depend on an externally coupled application to explicitly call for results output.

25.2.41. Use Output Scheduler

Scope: Results Output

Use Output Scheduler *Timer_name*

Parameter	Value	Default
<i>Timer_name</i>	string	undefined

Summary Associates a predefined output scheduler with this output block (results, restart, heartbeat, or history).

25.3. HEARTBEAT

Scope: Encore Region

Begin Heartbeat *Label*

Additional Steps {=|are|is} *List_of_steps...*

Additional Times {=|are|is} *List_of_times...*

Append {=|are|is} *Option*

At Step *n* *Option* {=|are|is} *m*

At Time *Dt1* *Option* {=|are|is} *Dt2*

Element [*VariableList...*]

Exists *Option1* *Option2*

Face [*VariableList...*]

Flush Interval {=|are|is} *Option*

Format {=|are|is} *StreamTypes*

Global [*Variables...*]

Labels {=|are|is} *Option*

Legend {=|are|is} *Option*

Monitor *Equals* *Option*

Nodal [*VariableList...*]

Node [*VariableList...*]

Nodeset [*VariableList...*]

Output On Signal {=|are|is} *Signals*

Precision {=|are|is} *Precision*

Start Time {=|are|is} *Start_time*

Stream Name {=|are|is} *OutputFilename*

Synchronize Output

Termination Time {=|are|is} *Final_time*

Timestamp Format

Timestep Adjustment Interval {=|are|is} *Nsteps*

Use Output Scheduler *Timer_name*

Variable {=|are|is} *Option* *Variable_list...*

End

Summary Describes the location and type of the output stream used for outputting the heartbeat information for the enclosing region.

25.3.1. Additional Steps

Scope: Heartbeat

Additional Steps {=|are|is} *List_of_steps...*

Parameter	Value	Default
<i>List_of_steps</i>	integer...	undefined

Summary Additional simulation steps when output should occur.

25.3.2. Additional Times

Scope: Heartbeat

Additional Times {=|are|is} *List_of_times...*

Parameter	Value	Default
<i>List_of_times</i>	real...	undefined

Summary Additional simulation times when output should occur.

25.3.3. Append

Scope: Heartbeat

Append {=|are|is} *Option*

Parameter	Value	Default
<i>Option</i>	{false off on true}	undefined

Summary Specifies whether the heartbeat file is appended if it exists. By default, the file is appended if restart is requested and not if restart is not requested. This option does not work for automatic restarts because a new heartbeat file is written with each auto restart.

25.3.4. At Step

Scope: Heartbeat

At Step n *Option* {=|are|is} m

Parameter	Value	Default
n	integer	undefined
<i>Option</i>	{increment interval}	undefined
m	integer	undefined

Summary Specify an output interval in terms of the internal iteration step count. The first step specifies the step count at the beginning of this interval and the second step specifies the output frequency to be used within this interval.

25.3.5. At Time

Scope: Heartbeat

At Time $Dt1$ *Option* {=|are|is} $Dt2$

Parameter	Value	Default
$Dt1$	real	undefined
<i>Option</i>	{increment interval}	undefined
$Dt2$	real	undefined

Summary Specify an output interval in terms of the internal simulation time. The first time specifies the time at the beginning of this time interval and the second time specifies the output frequency to be used within this interval.

25.3.6. Element

Scope: Heartbeat

Summary Define the element variables that should be written to the heartbeat database. The syntax is: "element internal_name at element id as DBname" or "element internal_name nearest location X, Y, Z as DBname".

Where internal_name is the name of the variable in the Sierra application; and DBname is the name as it should appear on the heartbeat database.

25.3.7. Exists

Scope: Heartbeat

Exists *Option1 Option2*

Parameter	Value	Default
<i>Option1</i>	{= is}	undefined
<i>Option2</i>	{abort append overwrite}	undefined

Summary Specify the behavior when creating this database and there is an existing file with the same name. The default behavior is "OVERWRITE" which deletes the existing file and creates a new file of the same name. "APPEND" will (if possible) append the new data to the end of the existing file. "ABORT" will print an error message and end the analysis.

25.3.8. Face

Scope: Heartbeat

Summary Define the face variables that should be written to the heartbeat database. The syntax is: "face internal_name at face id as DBname" or "face internal_name nearest location X, Y, Z as DBname".

Where internal_name is the name of the variable in the Sierra application; and DBname is the name as it should appear on the heartbeat database.

25.3.9. Flush Interval

Scope: Heartbeat

Flush Interval {= | are | is} *Option*

Parameter	Value	Default
<i>Option</i>	integer	10

Summary The minimum time interval (in seconds) at which the heartbeat output will be explicitly flushed to disk. The default is 10 seconds.

25.3.10. Format

Scope: Heartbeat

Format {=|are|is} *StreamTypes*

Parameter	Value	Default
<i>StreamTypes</i>	{csv original spyhis}	undefined

Summary The stream type/format to be used for the output results. The only three options at this time are 'Original' which is the old default Sierra heartbeat format; 'SpyHis' which mimics the CTH Spyhis history output format; and 'CSV'

25.3.11. Global

Scope: Heartbeat

Summary Define the global/reduction variables that should be written to the heartbeat database. The syntax is: "global internal_name as DBname".

Where internal_name is the name of the variable in the Sierra application; and DBname is the name as it should appear on the heartbeat database.

25.3.12. Labels

Scope: Heartbeat

Labels {=|are|is} *Option*

Parameter	Value	Default
<i>Option</i>	{off on}	on

Summary Specifies whether labels will be displayed or just the value of the variable. Labels will be shown if this line is not present.

25.3.13. Legend

Scope: Heartbeat

Legend {=|are|is} *Option*

Parameter	Value	Default
<i>Option</i>	{off on}	on

Summary Specifies whether a legend will be displayed prior to outputting any variables. The legend will not be shown unless this line is present. The legend shows the names of the variables that will be written to the heartbeat output stream. If the variable has multiple components, then the component count is shown after the variable e.g., velocity(3).

25.3.14. Monitor

Scope: Heartbeat

Monitor *Equals Option*

Parameter	Value	Default
<i>Equals</i>	{= the}	undefined
<i>Option</i>	{history restart results}	undefined

Summary Specifies whether a line will be written to the heartbeat stream when either the results, history, and/or restart data are output.

25.3.15. Nodal

Scope: Heartbeat

Summary Define the nodal variables that should be written to the heartbeat database. The syntax is: "nodal internal_name at node id as DBname" or "nodal internal_name nearest location X, Y, Z as DBname".

Where internal_name is the name of the variable in the Sierra application; and DBname is the name as it should appear on the heartbeat database.

25.3.16. Node

Scope: Heartbeat

Summary Define the nodal variables that should be written to the heartbeat database. The syntax is: "node internal_name at node id as DBname" or "node internal_name nearest location X, Y, Z as DBname".

Where internal_name is the name of the variable in the Sierra application; and DBname is the name as it should appear on the heartbeat database.

25.3.17. Nodeset

Scope: Heartbeat

Summary Define the nodeset variables that should be written to the heartbeat database. The syntax is: "nodeset internal_name at node id as DBname" or "nodeset internal_name nearest location X, Y, Z as DBname".

Where internal_name is the name of the variable in the Sierra application; and DBname is the name as it should appear on the heartbeat database.

25.3.18. Output On Signal

Scope: Heartbeat

Output On Signal {=*|are|is*} *Signals*

Parameter	Value	Default
<i>Signals</i>	{sigabrt sigalrm sigfpe sighup sigill sigint sigkill sigpipe sigquit sigsegv sigterm sigusr1 sigusr2}	undefined

Summary When the specified signal is raised, the output stream associated with this block will be output.

25.3.19. Precision

Scope: Heartbeat

Precision {=*|are|is*} *Precision*

Parameter	Value	Default
<i>Precision</i>	integer	5

Summary The precision to be used for the output of real variables (default=5).

25.3.20. Start Time

Scope: Heartbeat

Start Time {=*|are|is*} *Start_time*

Parameter	Value	Default
<i>Start_time</i>	real	undefined

Summary Specify the time to start outputting results from this output request block. This time overrides all 'at time' and 'at step' specifications.

25.3.21. Stream Name

Scope: Heartbeat

Stream Name {=*|are|is*} *OutputFilename*

Parameter	Value	Default
<i>OutputFilename</i>	string	undefined

Summary The filename of where the heartbeat data should be written. If the filename begins with the '/' character, it is an absolute path; otherwise, the path to the current directory will be prepended to the name. In addition, there are several predefined streams that can be specified. The predefined streams are 'cout' or 'stdout' specifies standard output; 'cerr', 'stderr', 'clog', or 'log' specifies standard error; 'output' or 'outputPo' specifies Sierra's standard output which is redirected to the file specified by the '-o' option on the command line. If the file already exists, it is overwritten. If this line is omitted, then a filename will be created from the basename of the input file with a ".hrt" suffix appended.

25.3.22. Synchronize Output

Scope: Heartbeat

Summary In an analysis with multiple regions, it is sometimes desirable to synchronize the output of results data between the regions. This can be done by adding the SYNCHRONIZE OUTPUT command line to the results output block. If a results block has this set, then it will write output whenever a previous region writes output. The ordering of regions is based on the order in the input file, algorithmic considerations, or by solution control specifications.

Although the USE OUTPUT SCHEDULER command line can also synchronize output between regions, the SYNCHRONIZE OUTPUT command line will synchronize the output with regions where the output frequency is not under the direct control of the Sierra IO system. Examples of this are typically coupled applications where one or more of the codes are not Sierra-based applications such as Alegra and CTH. A results block with SYNCHRONIZE OUTPUT specified will also synchronize its output with the output of the external code.

The SYNCHRONIZE OUTPUT command can be used with other output scheduling commands such as time-based or step-based output specifications.

25.3.23. Termination Time

Scope: Heartbeat

Termination Time {=|are|is} *Final_time*

Parameter	Value	Default
<i>Final_time</i>	real	undefined

Summary Specify the time to stop outputting results from this output request block.

25.3.24. Timestamp Format

Scope: Heartbeat

Summary The format to be used for the timestamp. See 'man strftime' for more information.

25.3.25. Timestep Adjustment Interval

Scope: Heartbeat

Timestep Adjustment Interval {=|are|is} *Nsteps*

Parameter	Value	Default
<i>Nsteps</i>	integer	undefined

Summary Specify the number of steps to 'look ahead' and adjust the timestep to ensure that the specified output times or simulation end time will be hit 'exactly'.

25.3.26. Use Output Scheduler

Scope: Heartbeat

Use Output Scheduler *Timer_name*

Parameter	Value	Default
<i>Timer_name</i>	string	undefined

Summary Associates a predefined output scheduler with this output block (results, restart, heartbeat, or history).

25.3.27. Variable

Scope: Heartbeat

Variable {=|are|is} *Option Variable_list...*

Parameter	Value	Default
<i>Option</i>	{edge element face global nodal node}	undefined
<i>Variable_list</i>	string...	undefined

Summary Define the variables that should be written to the heartbeat output. The user can request that the values of certain variables be output on the heartbeat line. These variables are limited to region and framework control data currently. The syntax is:

```

variable = {entity_type} {internal_name} at
           {entity_type} {entity_id}      as {external_name}
variable = {entity_type} {internal_name} nearest location
           {x,y,z} as {external_name}

```

For global variables, use:

```
variable = global {internal_name} [as {external_name}]
```

Where:

```

entity_type = node, element, face, edge, global
internal_name = Sierra variable name
entity_id = id of the node, element, face, edge that you want
            the specified variable output at.
external_name = name of variable on the database.

```

The names 'timestep', and 'time' can be specified as variables also. They are the current timestep and simulation time. This line can appear multiple times.

25.4. HISTORY OUTPUT

Scope: Encore Region

```

Begin History Output Label

Additional Steps {=|are|is} List_of_steps...
Additional Times {=|are|is} List_of_times...
At Step n Option {=|are|is} m
At Time Dt1 Option {=|are|is} Dt2
Database Name {=|are|is} StreamName
Database Type {=|are|is} DatabaseTypes
Element [ VariableList... ]
Exists Option1 Option2
Face [ VariableList... ]
Global [ Variables... ]
Nodal [ VariableList... ]
Node [ VariableList... ]
Nodeset [ VariableList... ]
Output On Signal {=|are|is} Signals

```

```

Overwrite Option1 Option2

Property PropertyName {=|are|is} PropertyValue

Start Time {=|are|is} Start_time

Synchronize Output

Termination Time {=|are|is} Final_time

Timestep Adjustment Interval {=|are|is} Nsteps

Title

Use Output Scheduler Timer_name

Variable {=|are|is} Option Variable_list...

```

End

Summary Describes the location and type of the output stream used for outputting history for the enclosing region.

25.4.1. Additional Steps

Scope: History Output

Additional Steps {=*|are|is*} *List_of_steps...*

Parameter	Value	Default
<i>List_of_steps</i>	integer...	undefined

Summary Additional simulation steps when output should occur.

25.4.2. Additional Times

Scope: History Output

Additional Times {=*|are|is*} *List_of_times...*

Parameter	Value	Default
<i>List_of_times</i>	real...	undefined

Summary Additional simulation times when output should occur.

25.4.3. At Step

Scope: History Output

At Step n *Option* {=|are|is} m

Parameter	Value	Default
n	integer	undefined
<i>Option</i>	{increment interval}	undefined
m	integer	undefined

Summary Specify an output interval in terms of the internal iteration step count. The first step specifies the step count at the beginning of this interval and the second step specifies the output frequency to be used within this interval.

25.4.4. At Time

Scope: History Output

At Time $Dt1$ *Option* {=|are|is} $Dt2$

Parameter	Value	Default
$Dt1$	real	undefined
<i>Option</i>	{increment interval}	undefined
$Dt2$	real	undefined

Summary Specify an output interval in terms of the internal simulation time. The first time specifies the time at the beginning of this time interval and the second time specifies the output frequency to be used within this interval.

25.4.5. Database Name

Scope: History Output

Database Name {=|are|is} *StreamName*

Parameter	Value	Default
<i>StreamName</i>	string	undefined

Summary The base name of the database containing the output history. If the filename begins with the '/' character, it is an absolute path; otherwise, the path to the current directory will be prepended to the name. If this line is omitted, then a filename will be created from the basename of the input file with a ".h" suffix appended.

25.4.6. Database Type

Scope: History Output

Database Type {= | are | is} *DatabaseTypes*

Parameter	Value	Default
<i>DatabaseTypes</i>	{catalyst dof dof_exodus exodus exodusii generated genesis parallel_exodus}	undefined

Summary The database type/format to be used for the output history.

25.4.7. Element

Scope: History Output

Summary Define the element variables that should be written to the history database. The syntax is: "element internal_name at element id as DBname" or "element internal_name nearest location X, Y, Z as DBname".

Where internal_name is the name of the variable in the Sierra application; and DBname is the name as it should appear on the history database.

25.4.8. Exists

Scope: History Output

Exists *Option1 Option2*

Parameter	Value	Default
<i>Option1</i>	{= is}	undefined
<i>Option2</i>	{abort add_suffix append overwrite}	undefined

Summary Specify the behavior when creating this database and there is an existing file with the same name. The default behavior is "OVERWRITE" which deletes the existing file and creates a new file of the same name. "APPEND" will (if possible) append the new data to the end of the existing file. "ABORT" will print an error message and end the analysis. "ADD_SUFFIX" will add a -s???? suffix where the ???? is replaced by a sequential number starting at 0002.

25.4.9. Face

Scope: History Output

Summary Define the face variables that should be written to the history database. The syntax is: "face internal_name at face id as DBname" or "face internal_name nearest location X, Y, Z as DBname".

Where internal_name is the name of the variable in the Sierra application; and DBname is the name as it should appear on the history database.

25.4.10. Global

Scope: History Output

Summary Define the global/reduction variables that should be written to the history database. The syntax is: "global internal_name as DBname".

Where internal_name is the name of the variable in the Sierra application; and DBname is the name as it should appear on the history database.

25.4.11. Nodal

Scope: History Output

Summary Define the nodal variables that should be written to the history database. The syntax is: "nodal internal_name at node id as DBname" or "nodal internal_name nearest location X, Y, Z as DBname".

Where internal_name is the name of the variable in the Sierra application; and DBname is the name as it should appear on the history database.

25.4.12. Node

Scope: History Output

Summary Define the nodal variables that should be written to the history database. The syntax is: "node internal_name at node id as DBname" or "node internal_name nearest location X, Y, Z as DBname".

Where internal_name is the name of the variable in the Sierra application; and DBname is the name as it should appear on the history database.

25.4.13. Nodeset

Scope: History Output

Summary Define the nodeset variables that should be written to the history database. The syntax is: "nodeset internal_name at node id as DBname" or "nodeset internal_name nearest location X, Y, Z as DBname".

Where internal_name is the name of the variable in the Sierra application; and DBname is the name as it should appear on the history database.

25.4.14. Output On Signal

Scope: History Output

Output On Signal {=|are|is} *Signals*

Parameter	Value	Default
<i>Signals</i>	{sigabrt sigalrm sigfpe sighup sigill sigint sigkill sigpipe sigquit sigsegv sigterm sigusr1 sigusr2}	undefined

Summary When the specified signal is raised, the output stream associated with this block will be output.

25.4.15. Overwrite

Scope: History Output

Overwrite *Option1 Option2*

Parameter	Value	Default
<i>Option1</i>	{= is}	undefined
<i>Option2</i>	{false no off on true yes}	undefined

Summary (DEPRECATED, Use EXISTS) Specify whether the database should be overwritten if it exists. The default behavior is to overwrite unless this command is specified in the output block and either off, false, or no is specified.

25.4.16. Property

Scope: History Output

Property *PropertyName* {=|are|is} *PropertyValue*

Parameter	Value	Default
<i>PropertyName</i>	string	undefined
<i>PropertyValue</i>	string	undefined

Summary Define a database property named "PropertyName" with the value "PropertyValue". If PropertyValue consists of all digits, it will define an integer property. If PropertyValue is "true" or "yes" or "false" or "no", it will define a logical property; otherwise it will define a string property. Supported properties are typically database dependent; Some history-related properties are: VARIABLE_NAME_CASE = upper|lower
MAX_NAME_LENGTH = value (32)

25.4.17. Start Time

Scope: History Output

Start Time {=|are|is} *Start_time*

Parameter	Value	Default
<i>Start_time</i>	real	undefined

Summary Specify the time to start outputting results from this output request block. This time overrides all 'at time' and 'at step' specifications.

25.4.18. Synchronize Output

Scope: History Output

Summary In an analysis with multiple regions, it is sometimes desirable to synchronize the output of results data between the regions. This can be done by adding the SYNCHRONIZE OUTPUT command line to the results output block. If a results block has this set, then it will write output whenever a previous region writes output. The ordering of regions is based on the order in the input file, algorithmic considerations, or by solution control specifications.

Although the USE OUTPUT SCHEDULER command line can also synchronize output between regions, the SYNCHRONIZE OUTPUT command line will synchronize the output with regions where the output frequency is not under the direct control of the Sierra IO system. Examples of this are typically coupled applications where one or more of the codes are not Sierra-based applications such as Alegra and CTH. A results block with SYNCHRONIZE OUTPUT specified will also synchronize its output with the output of the external code.

The SYNCHRONIZE OUTPUT command can be used with other output scheduling commands such as time-based or step-based output specifications.

25.4.19. Termination Time

Scope: History Output

Termination Time `{=|are|is} Final_time`

Parameter	Value	Default
<i>Final_time</i>	real	undefined

Summary Specify the time to stop outputting results from this output request block.

25.4.20. Timestep Adjustment Interval

Scope: History Output

Timestep Adjustment Interval `{=|are|is} Nsteps`

Parameter	Value	Default
<i>Nsteps</i>	integer	undefined

Summary Specify the number of steps to 'look ahead' and adjust the timestep to ensure that the specified output times or simulation end time will be hit 'exactly'.

25.4.21. Title

Scope: History Output

Summary Specify the title to be used for this specific output block.

25.4.22. Use Output Scheduler

Scope: History Output

Use Output Scheduler *Timer_name*

Parameter	Value	Default
<i>Timer_name</i>	string	undefined

Summary Associates a predefined output scheduler with this output block (results, restart, heartbeat, or history).

25.4.23. Variable

Scope: History Output

Variable {=|are|is} *Option Variable_list...*

Parameter	Value	Default
<i>Option</i>	{edge element face global nodal node}	undefined
<i>Variable_list</i>	string...	undefined

Summary Define the variables that should be written to the history database. The syntax is: "variable = entity internal_name at entity id as DBname" or "variable = entity internal_name nearest location X, Y, Z as DBname" or "variable = entity internal_name at location X, Y, Z as DBname".

Where entity is 'node', 'element', 'face', or 'edge'; internal_name is the name of the variable in the Sierra application; and DBname is the name as it should appear on the history database.

25.5. DATA PROBE

Scope: Equation System

Begin Data Probe *probeName*

Nodal_Id *fieldName* Node_Id {=|are|is} *node_id* [Label *label*]

Nodal_Location *fieldName* Location {=|are|is} *location₁* *location₂* [*location₃*] [Label *label*]

Parametric Tolerance *parametric_tolerance...*

Restriction Parts *restriction_parts...*

Search Method {=|are|is} *SearchMethod*

At Step *startingStep* Increment {=|are|is} *increment*

Output To File [*fileName*]

End

Summary The Aria Data Probe capability allows the analyst to query data for fields of interest (e.g. temperature, pressure) during a simulation at times and locations specified by the analyst.

Within the Data Probe a user can request multiple probes but each Data Probe command block is restricted to processing of a single field.

Each individual probe within the Data Probe can be assigned a unique label by which can be used to access the probed value as a global variable. If a probe label is not defined then

the probe will be internally labeled as the Data Probe name appended with an counter index (`_index`) that reflects the order in which the unnamed probe was parsed.

This command creates an Aria Data Probe with the name given by `probeName` and each probe point can be accessed and output as a global variable.

In problems of mesh motion only `Nodal_Id` probe points are supported.

25.5.1. Nodal_Id

Scope: Data Probe

```
Nodal_Id fieldName Node_Id {=|are|is} node_id [ Label label ]
```

Parameter	Value	Default
<i>fieldName</i>	string	undefined
<i>node_id</i>	integer	undefined

Summary Defines data probe for a point specified by the global id of a node.

Description Sets the nodal field name, node global id, and optionally the label for each probe point.

Probe requests of solution DOF will require the appropriate prefix, *solution-* > or *nonlinear_solution-* >.

The `field_data` at the specified node (and only that node) is associated with the probe point and its corresponding global variable.

If a label is provided, a global variable with that name will be created. If no label is provided, a global variable will be created with a name that is the concatenation of the Data Probe name and the index of the probe point.

25.5.2. Nodal_Location

Scope: Data Probe

```
Nodal_Location fieldName Location {=|are|is} location1 location2 [location3] [ Label label ]
```

Parameter	Value	Default
<i>fieldName</i>	string	undefined
<i>location</i>	real_1 real_2[real_3]	undefined

Summary Defines data probe for a point specified by location (x,y,z).

Description Sets the nodal field name, spatial location, and optionally the label for this probe point.

Probe requests of solution DOF will require the appropriate prefix, *solution-* > or *nonlinear_solution-* >.

If the point lies within an element within the set of element blocks defined using RESTRICTION PARTS, the given field will be interpolated in that element. If the point lies outside the mesh, but within the PARAMETRIC TOLERANCE then the point is projected to the nearest location on the nearest element (face, edge, or vertex), and interpolation is used to compute the value of the field.

If a label is provided, a global variable with that name will be created. If no label is provided, a global variable will be created with a name that is the concatenation of the Data Probe name and the index of the probe point.

The NODAL LOCATION probe is not supported in problems with mesh motion.

25.5.3. Parametric Tolerance

Scope: Data Probe

Parametric Tolerance *parametric_tolerance...*

Parameter	Value	Default
<i>parametric_tolerance</i>	real...	undefined

Summary The user may specify a parametric tolerance that is used to determine whether or not the data probe point is close enough to an element for the probe point to be considered valid. The parametric tolerance is a numeric value that indicates the maximum allowed parametric coordinate of the data probe point with respect to the closest element found during the search. The closest element of interest is transposed into isoparametric coordinates in the range of $[-1,1]$ and the parametric distance is set as the maximum value. For an high aspect ratio hexahedron element, the parametric distance may look suspect as it will be calculated based on the shortest element edge. For instance, if the parametric tolerance is set to 2.0, the data probe point is allowed to have a parametric coordinate of up to 2.0 with respect to the closest element that is found. However, if the parametric coordinate of the point with respect to this element is > 2.0 , the tolerance check will fail and the simulation will end with an error describing this failure. For convenience, all points within a probe are checked for the parametric tolerance condition, and if any failures are found, they are all reported together rather than the simulation halting on the first failure of this condition.

25.5.4. Restriction Parts

Scope: Data Probe

Restriction Parts *restriction_parts...*

Parameter	Value	Default
<i>restriction_parts</i>	string...	undefined

Summary Element blocks for which data probe will be applied. If the restriction part is a surface all element blocks touching the surface will be searched. Only elements within these parts will be searched for data probe points. If no restriction parts are provided, all element blocks will be searched.

25.5.5. Search Method

Scope: Data Probe

Search Method {=|are|is} *SearchMethod*

Parameter	Value	Default
<i>SearchMethod</i>	{boost_rtree gtk_search morton_linearized_bvh octree}	BOOST_RTREE

Summary Optionally select the search method used for finding the element containing the data probe point. Defaults to BOOST_RTREE.

25.5.6. At Step

Scope: Data Probe

At Step *startingStep* Increment {=|are|is} *increment*

Parameter	Value	Default
<i>startingStep</i>	integer	undefined
<i>increment</i>	integer	undefined

Summary Write the results of the data probe beginning at step (*startingStep*) and output every specified number of steps (*increment*).

25.5.7. Output To File

Scope: Data Probe

Summary Enable data output to file specified by filename. Data Probe Point values are additionally sent to the Aria log file.

25.6. RESTART OVERVIEW

Convenient utilities are provided for restarting an analysis from previous results. The most general capability supplements the results of a previous analysis with internal state variables to continue an analysis. In this case the input mesh is supplied from the Input Database Name from the Finite Element Model command block [3.1](#) and the restart information is obtained from the the Input Database Name from the Restart Data command block. Continuation of a job from a solution plane is invoked using the RESTART TIME command line.

Note that special considerations are warranted when initializing problems utilizing bulk volume elements [31.4](#) with restart files not containing the bulk volume elements.

25.7. RESTART DATA

Scope: Encore Region

Begin Restart Data *Label*

Additional Steps {=|are|is} *List_of_steps...*

Additional Times {=|are|is} *List_of_times...*

At Step *n Option* {=|are|is} *m*

At Time *Dt1 Option* {=|are|is} *Dt2*

At Wall Time *Dt1 Option* {=|are|is} *Dt2*

Component Separator Character *Option Separator*

Cycle Count {=|are|is} *Count*

Database Name {=|are|is} *StreamName*

Database Type {=|are|is} *DatabaseTypes*

Debug Dump

Decomposition Method {=|are|is} *Method*

Exists *Option1 Option2*

File Cycle Count {=|are|is} *Count*

Input Database Name {=|are|is} *StreamName*

Optional

Output Database Name {=|are|is} *StreamName*

Output On Signal {=|are|is} *Signals*

Overlay Count {=|are|is} *Count*

```

Overwrite Option1 Option2

Property PropertyName {=|are|is} PropertyValue

Restart {=|are|is} RestartOption

Restart Time {=|are|is} Time

Start Time {=|are|is} Start_time

Synchronize Output

Termination Time {=|are|is} Final_time

Timestep Adjustment Interval {=|are|is} Nsteps

Use External Control

Use Output Scheduler Timer_name

End

```

Summary Describes the data required to output and input restart data for the enclosing region.

25.7.1. Additional Steps

Scope: Restart Data

```
Additional Steps {=|are|is} List_of_steps...
```

Parameter	Value	Default
<i>List_of_steps</i>	integer...	undefined

Summary Additional simulation steps when output should occur.

25.7.2. Additional Times

Scope: Restart Data

```
Additional Times {=|are|is} List_of_times...
```

Parameter	Value	Default
<i>List_of_times</i>	real...	undefined

Summary Additional simulation times when output should occur.

25.7.3. At Step

Scope: Restart Data

At Step n *Option* {=*are*|*is*} m

Parameter	Value	Default
n	integer	undefined
<i>Option</i>	{increment interval}	undefined
m	integer	undefined

Summary Specify an output interval in terms of the internal iteration step count. The first step specifies the step count at the beginning of this interval and the second step specifies the output frequency to be used within this interval.

25.7.4. At Time

Scope: Restart Data

At Time $Dt1$ *Option* {=*are*|*is*} $Dt2$

Parameter	Value	Default
$Dt1$	real	undefined
<i>Option</i>	{increment interval}	undefined
$Dt2$	real	undefined

Summary Specify an output interval in terms of the internal simulation time. The first time specifies the time at the beginning of this time interval and the second time specifies the output frequency to be used within this interval.

25.7.5. At Wall Time

Scope: Restart Data

At Wall Time $Dt1$ *Option* {=*are*|*is*} $Dt2$

Parameter	Value	Default
$Dt1$	string	undefined
<i>Option</i>	{increment interval}	undefined
$Dt2$	string	undefined

Summary Write a restart file at a specific wall time since the start of the run. Time string format allows s, m, h, d for seconds, minutes, hours, days

25.7.6. Component Separator Character

Scope: Restart Data

Component Separator Character *Option Separator*

Parameter	Value	Default
<i>Option</i>	{= is}	undefined
<i>Separator</i>	string	undefined

Summary The separator is the single character used to separate the output variable basename (e.g. "stress") from the suffices (e.g. "xx", "yy") when displaying the names of the individual variable components. For example, the default separator is "_", which results in names similar to "stress_xx", "stress_yy", ... "stress_zx". To eliminate the separator, specify an empty string ("") or NONE.

25.7.7. Cycle Count

Scope: Restart Data

Cycle Count {= | are | is} *Count*

Parameter	Value	Default
<i>Count</i>	integer	undefined

Summary Specify the number of restart steps which will be written to the restart database before previously written steps are overwritten. For example, if the cycle count is 5 and restart is written every 0.1 seconds, the restart system will write 0.1, 0.2, 0.3, 0.4, 0.5 to the database. It will then overwrite the first step with data from time 0.6, the second with time 0.7. At time 0.8, the database would contain data at times 0.6, 0.7, 0.8, 0.4, 0.5. Note that time will not necessarily be monotonically increasing on a database that specifies the cycle count.

25.7.8. Database Name

Scope: Restart Data

Database Name {= | are | is} *StreamName*

Parameter	Value	Default
<i>StreamName</i>	string	undefined

Summary The database containing the input and/or output restart data. If this analysis is being restarted, restart data will be read from this file. If the analysis is writing restart data, the data will be written to this file. It will be overwritten if it exists (after being read if applicable). If the filename begins with the '/' character, it is an absolute path; otherwise, the path to the current directory will be prepended to the name. See also the 'Input Database' and 'Output Database' commands.

25.7.9. Database Type

Scope: Restart Data

Database Type `{=|are|is}` *DatabaseTypes*

Parameter	Value	Default
<i>DatabaseTypes</i>	<code>{catalyst dof dof_exodus exodus exodusii generated genesis parallel_exodus}</code>	undefined

Summary The database type/format used for the restart file.

25.7.10. Debug Dump

Scope: Restart Data

Summary Specify whether the restart system will write the restart data immediately after reading the restart data if the run is restarting. The output data can be compared with the restart input data to determine whether they match.

25.7.11. Decomposition Method

Scope: Restart Data

Decomposition Method `{=|are|is}` *Method*

Parameter	Value	Default
<i>Method</i>	<code>{block cyclic external geom_kway hsfc kway kway_geom linear metis_sfc random rcb rib}</code>	undefined

Summary The decomposition algorithm to be used to partition elements to each processor in a parallel run.

25.7.12. Exists

Scope: Restart Data

Exists *Option1 Option2*

Parameter	Value	Default
<i>Option1</i>	<code>{= is}</code>	undefined
<i>Option2</i>	<code>{abort add_suffix append overwrite}</code>	undefined

Summary Specify the behavior when creating this database and there is an existing file with the same name. The default behavior is "OVERWRITE" which deletes the existing file and creates a new file of the same name. "APPEND" will (if possible) append the new data to the end of the existing file. "ABORT" will print an error message and end the analysis. "ADD_SUFFIX" will add a suffix to the file name and output to that file.

25.7.13. File Cycle Count

Scope: Restart Data

File Cycle Count {=|are|is} *Count*

Parameter	Value	Default
<i>Count</i>	integer	undefined

Summary Each restart dump will be written to a separate file suffixed with A,B, ... The count specifies how many separate files are used before the cycle repeats. For example, if "FILE CYCLE COUNT = 3" is specified, the restart dumps would be written to file-A.rs, file-B.rs, file-C.rs, file-A.rs, ... The maximum value for the cycle count is 26.

25.7.14. Input Database Name

Scope: Restart Data

Input Database Name {=|are|is} *StreamName*

Parameter	Value	Default
<i>StreamName</i>	string	undefined

Summary The database containing the input restart data. If this analysis is being restarted, restart data will be read from this file. See also the 'Database' and 'Output Database' commands.

25.7.15. Optional

Scope: Restart Data

Summary The database will be read if it exists, but it is not an error if there is no restart database to read for this region during a restarted analysis.

25.7.16. Output Database Name

Scope: Restart Data

Output Database Name {=|are|is} *StreamName*

Parameter	Value	Default
<i>StreamName</i>	string	undefined

Summary The database containing the output restart data. If the analysis is writing restart data, the data will be written to this file. It will be overwritten if it exists. See also the 'Database' and 'Input Database' commands.

25.7.17. Output On Signal

Scope: Restart Data

Output On Signal {=|are|is} *Signals*

Parameter	Value	Default
<i>Signals</i>	{sigabrt sigalrm sigfpe sighup sigill sigint sigkill sigpipe sigquit sigsegv sigterm sigusr1 sigusr2}	undefined

Summary When the specified signal is raised, the output stream associated with this block will be output.

25.7.18. Overlay Count

Scope: Restart Data

Overlay Count {=|are|is} *Count*

Parameter	Value	Default
<i>Count</i>	integer	undefined

Summary Specify the number of restart outputs which will be overlayed on top of the last written step. For example, if restarts are being output every 0.1 seconds and the overlay count is specified as 2, then restart will write times 0.1 to step 1 of the database. It will then write 0.2 and 0.3 also to step 1. It will then increment the database step and write 0.4 to step 2; overlay 0.5 and 0.6 on step 2... At the end of the analysis, assuming it runs to completion, the database would have times 0.3, 0.6, 0.9, ... However, if there were a problem during the analysis, the last step on the database would contain an intermediate step.

25.7.19. Overwrite

Scope: Restart Data

Overwrite *Option1 Option2*

Parameter	Value	Default
<i>Option1</i>	{= is}	undefined
<i>Option2</i>	{false no off on true yes}	undefined

Summary (DEPRECATED, Use EXISTS) Specify whether the restart database should be overwritten if it exists. The default behavior is to overwrite unless this command is specified in the restart block and either off, false, or no is specified.

25.7.20. Property

Scope: Restart Data

Property *PropertyName* {= | are | is} *PropertyValue*

Parameter	Value	Default
<i>PropertyName</i>	string	undefined
<i>PropertyValue</i>	string	undefined

Summary Define a database property named "PropertyName" with the value "PropertyValue". If PropertyValue consists of all digits, it will define an integer property. If PropertyValue is "true" or "yes" or "false" or "no", it will define a logical property; otherwise it will define a string property. If PropertyName consists of multiple strings, they will be concatenated together with " " separating the individual words. Supported properties are typically database dependent; Current properties are: COMPRESSION_LEVEL = [0..9] COMPRESSION_SHUFFLE = true|false|on|off FILE_TYPE = netcdf4 (forces use of netcdf-4 hdf5-based file) INTEGER_SIZE_DB = 4|8 INTEGER_SIZE_API = 4|8 LOGGING = true|false|on|off MAX_NAME_LENGTH = value

25.7.21. Restart

Scope: Restart Data

Restart {= | are | is} *RestartOption*

Parameter	Value	Default
<i>RestartOption</i>	{auto automatic}	undefined

Summary Specify automatic restart file read.

Description NOTE: This command must be placed at the Sierra scope of the input file.

Specify that the analysis should be restarted from the last common time on all restart databases for each Region in the analysis. In addition to this line command, each Region in the analysis (strictly, only the region(s) that will be restarted) must have a restart block specifying the database to read the restart state data.

By default, use of this command will not cause output files (e.g., results, history, heartbeat, restart) to be overwritten. Instead output files will be written with the same basename and the suffix -s000*. Common visualization packages are written to handle this file organization gracefully in order for the user to view all results seamlessly.

25.7.22. Restart Time

Scope: Restart Data

Restart Time {=|are|is} *Time*

Parameter	Value	Default
<i>Time</i>	<i>real</i>	<i>undefined</i>

Summary Specify restart file read at a specified time.

Description NOTE: This command must be placed at the Sierra scope of the input file.

Specify the time that the analysis will be restarted. In addition to this line command, each Region in the analysis (strictly, only the region(s) that will be restarted) must have a restart block specifying the database to read the restart state data. The restart 'time' must be greater than zero and less than or equal to the termination time.

By default, use of this command will cause previous output files (e.g., results, history, heartbeat, restart) to be overwritten. If this command is chosen, the onus is placed on the user to ensure that previous output files are not overwritten.

25.7.23. Start Time

Scope: Restart Data

Start Time {=|are|is} *Start_time*

Parameter	Value	Default
<i>Start_time</i>	<i>real</i>	<i>undefined</i>

Summary Specify the time to start outputting results from this output request block. This time overrides all 'at time' and 'at step' specifications.

25.7.24. Synchronize Output

Scope: Restart Data

Summary In an analysis with multiple regions, it is sometimes desirable to synchronize the output of results data between the regions. This can be done by adding the SYNCHRONIZE OUTPUT command line to the results output block. If a results block has this set, then it will write output whenever a previous region writes output. The ordering of regions is based on the order in the input file, algorithmic considerations, or by solution control specifications.

Although the USE OUTPUT SCHEDULER command line can also synchronize output between regions, the SYNCHRONIZE OUTPUT command line will synchronize the output with regions where the output frequency is not under the direct control of the Sierra IO system. Examples of this are typically coupled applications where one or more of the codes are not Sierra-based applications such as Alegra and CTH. A results block with SYNCHRONIZE OUTPUT specified will also synchronize its output with the output of the external code.

The SYNCHRONIZE OUTPUT command can be used with other output scheduling commands such as time-based or step-based output specifications.

25.7.25. Termination Time

Scope: Restart Data

Termination Time {=|are|is} *Final_time*

Parameter	Value	Default
<i>Final_time</i>	real	undefined

Summary Specify the time to stop outputting results from this output request block.

25.7.26. Timestep Adjustment Interval

Scope: Restart Data

Timestep Adjustment Interval {=|are|is} *Nsteps*

Parameter	Value	Default
<i>Nsteps</i>	integer	undefined

Summary Specify the number of steps to 'look ahead' and adjust the timestep to ensure that the specified output times or simulation end time will be hit 'exactly'.

25.7.27. Use External Control

Scope: Restart Data

Summary Do not schedule any results output but instead depend on an externally coupled application to explicitly call for results output.

25.7.28. Use Output Scheduler

Scope: Restart Data

Use Output Scheduler *Timer_name*

Parameter	Value	Default
<i>Timer_name</i>	string	undefined

Summary Associates a predefined output scheduler with this output block (results, restart, heartbeat, or history).

25.7.29. Restart Time

Scope:

Restart Time {=|are|is} *Time*

Parameter	Value	Default
<i>Time</i>	real	undefined

Summary Specify restart file read at a specified time.

Description NOTE: This command must be placed at the Sierra scope of the input file.

Specify the time that the analysis will be restarted. In addition to this line command, each Region in the analysis (strictly, only the region(s) that will be restarted) must have a restart block specifying the database to read the restart state data. The restart 'time' must be greater than zero and less than or equal to the termination time.

By default, use of this command will cause previous output files (e.g., results, history, heartbeat, restart) to be overwritten. If this command is chosen, the onus is placed on the user to ensure that previous output files are not overwritten.

26. INPUT OUTPUT REGION REFERENCE

26.1. INPUT_OUTPUT REGION OVERVIEW

For some coupled simulations one can approximate part of the problem physics independent of the entire problem physics. In order to facilitate this type of loose application coupling, the ability to input datasets that include the output of other simulations is provided. An application can then make requests of information from these datasets. In fulfilling these requests, data can be extracted from these datasets and be copied or interpolated to another problem domain. Moreover these requests can be satisfied by data interpolated through time. The mechanism provided to achieve this end goal is known as the Input_Output Region and its usage is described in what follows.

The input_output region works in tandem with transfer [15.1](#) and solution control [14](#). Here transfer carries out the communication of data and solution control provides synchronization of the data transfer. Note that just like other Sierra Regions the input_output region must have its own Finite Element model command block defined.

As an example, let us assume that an input mesh for an Input_Output Region contains a nodal variable ConvCoeff that we wish to use in another Region. In this case an outline for one-way transfer of ConvCoeff to to a Region, *second_region*, in a steady-state problem would be:

```
Begin Sierra
.
Begin Finite Element Model input_transfer
.
End
.
Begin Transfer my_first_transfer
.
transfer commands for input_output_region to second_region
.
SEND field hNd state none TO ConvCoeff state none
.
End
.
Begin Procedure My_Aria_Procedure
.
```

```

Begin Solution Control Description
  Use System Main
  Begin System Main
    Begin Sequential MySolveBlock
      Advance io_region
      transfer my_first_transfer
      Advance second_Region
    End
  End
End

Begin Input_Output io_region
  USE FINITE ELEMENT MODEL my_input_transfer
End

Begin Aria Region second_region
  .
  use Finite Element Model input_transfer
  .
  USER FIELD REAL NODE SCALAR ConvCoeff on surface_1
  .
End

End
.
End Sierra

```

26.2. INPUT_OUTPUT REGION

Scope: Procedure

```

Begin Input_Output Region Parameter_block_name

  Create Element Field Field_name Of Type Option And Dimension
  Dimension [ Value {=|are|is} Number... ]

  Create Nodal Field Field_name Of Type Option And Dimension
  Dimension [ Value {=|are|is} Number... ]

  Fixed Time [ {=|are|is} Fixed_time ]

  Offset Time {=|are|is} Period_offset_time

  Periodicity Time {=|are|is} Periodicity_time

  Start Time {=|are|is} Start_time

```

Use Finite Element Model *ModelName* [Model Coordinates Are
Nodal_variable_name]

Begin Heartbeat *Label*

End

Begin History Output *Label*

End

Begin Restart Data *Label*

End

Begin Results Output *Label*

End

End

Summary BEGIN INPUT TRANSFER *model_name* USE FINITE ELEMENT MODEL fred
START TIME is 0 OFFSET TIME is 1 PERIODICITY TIME is 10 END INPUT
TRANSFER *model_name*

26.2.1. Create Element Field

Scope: Input_Output Region

Create Element Field *Field_name* Of Type *Option* And Dimension *Dimension* [*Value* {=|are|is} *Number...*]

Parameter	Value	Default
<i>Field_name</i>	string	undefined
<i>Option</i>	{asym_tensor_03 complex full_tensor_22 full_tensor_36 integer long_integer matrix_22 matrix_33 real sym_tensor_21 sym_tensor_31 sym_tensor_33 unsigned_integer unsigned_integer_64 vector_2d vector_3d}	undefined
<i>Dimension</i>	integer	undefined

Summary Creates a Element Field name *field_name* on the region.

26.2.2. Create Nodal Field

Scope: Input_Output Region

Create Nodal Field *Field_name* Of Type *Option* And Dimension *Dimension* [
Value {=|are|is} *Number...*]

Parameter	Value	Default
<i>Field_name</i>	string	undefined
<i>Option</i>	{asym_tensor_03 complex full_tensor_22 full_tensor_36 integer long_integer matrix_22 matrix_33 real sym_tensor_21 sym_tensor_31 sym_tensor_33 unsigned_integer unsigned_integer_64 vector_2d vector_3d}	undefined
<i>Dimension</i>	integer	undefined

Summary Creates a Nodal Field name *field_name* on the region.

26.2.3. Fixed Time

Scope: Input_Output Region

Summary The line specifies that the database will be read for a single, fixed time. Specifying the actual time is optional. If the time is not specified, the final time plane in the database will be read.

NOTE: This option take precedence over the periodic specifications given by START TIME, PERIODICITY TIME, and OFFSET TIME.

if FIXED TIME is specified then if FIXED TIME value is given then (eg., FIXED TIME is 1.) DATABASE TIME = FIXED TIME else (eg., FIXED TIME) DATABASE TIME = last time in database else if PERIODICITY TIME greater than 0 then if APPLICATION TIME less than or equal to START TIME then DATABASE TIME = APPLICATION TIME else DATABASE TIME = START TIME + (APPLICATION TIME - START TIME) modulo PERIODICITY TIME else DATABASE TIME = APPLICATION TIME now add OFFSET TIME to the computed DATABASE TIME

26.2.4. Offset Time

Scope: Input_Output Region

Offset Time {=|are|is} *Period_offset_time*

Parameter	Value	Default
<i>Period_offset_time</i>	real	undefined

Summary This value is added to the application time to determine what database time slice to input. If OFFSET TIME were 15 than at application time 0 database time slice 15 would be read from the file and used for the initial values. At application time 1, database time slice 16 would be read. NOTE: The OFFSET TIME is added in after the START TIME and PERIODICITY TIME are used. The FIXED TIME option take precedence over this option.

if FIXED TIME is specified then if FIXED TIME value is given then (eg., FIXED TIME is 1.) DATABASE TIME = FIXED TIME else (eg., FIXED TIME) DATABASE TIME = last time in database else if PERIODICITY TIME greater than 0 then if APPLICATION TIME less than or equal to START TIME then DATABASE TIME = APPLICATION TIME else DATABASE TIME = START TIME + (APPLICATION TIME - START TIME) modulo PERIODICITY TIME else DATABASE TIME = APPLICATION TIME now add OFFSET TIME to the computed DATABASE TIME

26.2.5. Periodicity Time

Scope: Input_Output Region

Periodicity Time {=|are|is} *Periodicity_time*

Parameter	Value	Default
<i>Periodicity_time</i>	real	undefined

Summary START TIME and PERIODICITY TIME taken together give the time frame from the input database to use to initialize the application values. If START TIME is 25 and PERIODICITY TIME is 10, then time slices from 25 to 35 will be used over and over again as the application time runs from 0 to whatever. In general DATABASE TIME is (APPLICATION TIME - START TIME) modulo PERIODICITY TIME after the application time reaches the START TIME.

NOTE: The OFFSET TIME is added in after the START TIME and PERIODICITY TIME are used. The FIXED TIME option take precedence over this option.

if FIXED TIME is specified then if FIXED TIME value is given then (eg., FIXED TIME is 1.) DATABASE TIME = FIXED TIME else (eg., FIXED TIME) DATABASE TIME = last time in database else if PERIODICITY TIME greater than 0 then if APPLICATION TIME less than or equal to START TIME then DATABASE TIME = APPLICATION TIME else DATABASE TIME = START TIME + (APPLICATION TIME - START TIME) modulo PERIODICITY TIME else DATABASE TIME = APPLICATION TIME now add OFFSET TIME to the computed DATABASE TIME

26.2.6. Start Time

Scope: Input_Output Region

Start Time {=|are|is} *Start_time*

Parameter	Value	Default
<i>Start_time</i>	real	undefined

Summary The time in which to start applying PERIODICITY TIME. If PERIODICITY TIME is not specified then START TIME is ignored.

NOTES: The OFFSET TIME is added in after the START TIME and PERIODICITY TIME are used. The FIXED TIME option take precedence over this option.

if FIXED TIME is specified then if FIXED TIME value is given then (eg., FIXED TIME is 1.) DATABASE TIME = FIXED TIME else (eg., FIXED TIME) DATABASE TIME = last time in database else if PERIODICITY TIME greater than 0 then if APPLICATION TIME less than or equal to START TIME then DATABASE TIME = APPLICATION TIME else DATABASE TIME = START TIME + (APPLICATION TIME - START TIME) modulo PERIODICITY TIME else DATABASE TIME = APPLICATION TIME now add OFFSET TIME to the computed DATABASE TIME

26.2.7. Use Finite Element Model

Scope: Input_Output Region

Use Finite Element Model *ModelName* [Model Coordinates Are *Nodal_variable_name*]

Parameter	Value	Default
<i>ModelName</i>	string	undefined

Summary Associates a predefined finite element model with this region.

27. LOG FILE OUTPUT

27.1. INTRODUCTION

Aria, as well as all other Sierra codes, provides log file output capability which aids users in performing such actions as viewing run information, runtime/performance monitoring, and verifying input file accuracy. While much of the log file output is standardized for the Sierra codes, there are sections, especially in runtime monitoring, that are specific to Aria. This chapter will discuss the different sections of the log file and give examples of these sections in order to help the user assimilate and make the best use of the information that is output.

For this explanation, the Aria Foam Decomposition example problem will be used and can be found on the [Sandia Computational Simulation webpage](#). This example was chosen due to its use of several different types of physics, such as element death, enclosure radiation, and chemistry modeling, as well as its use of adaptive time stepping.

27.2. PREAMBLE

The log file preamble contains useful information about run information, input file parsing, and model setup.

27.2.1. Run Information

At the very beginning of the log file is printed information about the selected Sierra executable, where and when the model is run, and specific version information. Below is a section of the log file preamble which shows this information.

```
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
                                     Aria

      Coupled multiphysics including Navier-Stokes,
      elasticity, energy transport, species transport,
      electrostatics; free and moving boundaries;
      transient or steady state.
```

Version 4.33.1-398-gaeb9bfbb

With coupled mechanics support for
Aria - Coupled multiphysics
Encore - Solution Verification Analysis Region

Sandia National Laboratories
Albuquerque, New Mexico and Livermore, California

Please email questions and comments to
sierra-help@sandia.gov

Notice: This computer software was prepared by
Sandia Corporation, hereinafter the Contractor,
under Contract DE-AC04-94AL85000 with the
Department of Energy (DOE). All rights in the
computer software are reserved by DOE on behalf
of the United States Government and the
Contractor as provided in the Contract. You are
authorized to use this computer software for
Governmental purposes but it is not to be
released or distributed to the public. NEITHER
THE U.S. GOVERNMENT NOR THE CONTRACTOR MAKES
ANY WARRANTY, EXPRESS OR IMPLIED, OR ASSUMES ANY
LIABILITY FOR THE USE OF THIS SOFTWARE.

+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----

Directory /home/rpshaw/foamDecomposition/
Executable /projects/sierra/linux_rh6/install/master/bin/aria
Built May 12 2014 18:46:01
Build Options linux intel-12.1 release
Run Started May 14 2014 11:04:22
User rpshaw
Architecture cee-build001
Host cee-build001
Hardware x86_64
Running Linux
Processors 1
Processing foamDecomposition.i

Product	Version	Qualifier

ACME	2.9.0	

```

        Aria 4.33.1-398-gaeb9bfbb
    Chaparral 3.3.1 development          unreleased
        Encore 4.33.1-398-gaeb9bfbb
        FEI 2.24.02
        GDSW Dev
        Linux 2.6.32-358.2.1.el6.x86_64
        MPIH 4.33.1-398-gaeb9bfbb
SIERRA Framework 4.33.1-398-gaeb9bfbb
        Trilinos 11.9.0
Trilinos|Aztec00 11.9.0
        UtilityLib 4.33.1-398-gaeb9bfbb
        Zoltan 3.8

```

Here, it can be seen that Aria version 4.33.1-398-gaeb9bfbb is used, and further, it can be seen that the master (i.e., Version-of-the-Day/VOTD) version is used based on the executable directory:

```
Executable /projects/sierra/linux_rh6/install/master/bin/aria
```

It can also be seen that the run was started at May 14 2014 11:04:22 on cee-build001 with 1 processor in /home/rpshaw/foamDecomposition/.

More specific version information for each product that Aria uses is shown at the bottom of this section, for those who are interested in or concerned with more detail about how their model is being run.

27.2.2. Input File

The log file next contains a complete copy of the input file which is used to run the model, directly following the lines shown below:

```

+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
Reading foamDecomposition.i                                     May 14 2014 11:04:26

```

Note that the input file shown is the one that is used for parsing, so any pre-processing operations such as aprepro will have already been completed in the input file shown in the log file. Also, this section will be where parsing errors show up, if there are any in the input file.

In the event of misplacement of an input file, one can also extract the input file from the log file, which can save a considerable amount of time.

27.2.3. Instantiation

After the input file has been parsed, Aria will then instantiate all systems required to run the input file and will output the results of the instantiation to the log file. The instantiation begins with the lines

```
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
```

Instantiating systemMay 14 2014 11:04:26

This section of the log file is not often used by analysts, but can be useful in debugging non-obvious issues. The following is a list of common items that may be seen in the instantiation section:

- Setting of default values for unspecified variables

Example DEFAULTING FAILED_TIME_STEP_SIZE_RATIO = 0.500000 for region
AriaRegion in time block Transient_time_block_1

- Configuration of mesh parts as needed by different inputs

Example Adding death bc iopart for element death with name
surface_death_temp1

- Creation of edge/element mechanics

Example Configuring Element mechanics for region "AriaRegion" equation system "main"...

- Configuration of boundary/initial condition mechanics

Example Configuring Convective Flux for region "AriaRegion" equation system "main"...

- Configuration of other mechanics such as enclosure radiation and chemistry

Example Configuring Enclosure Radiation BC mechanics for region "AriaRegion" equation system "main"...

The very end of this section of the log file contains the number of errors and warnings that were found during the parsing of the input file. This can be helpful in helping users pinpoint if they incorrectly set up some parameter that still allows the simulation to continue.

27.2.4. Procedure Initialization

This section of the log file begins with the following lines:

[illegible]

The most useful portion of this section is the list of variables available for output. These variables are shown for each Region that is found in the input file and are separated by the type of field on which they reside, e.g., nodes, elements, edges, and faces. Global variables that may be output are also listed.

27.3. RUN-TIME REPORTING

After the preamble of the log file comes the actual execution of the model, including linear and nonlinear solver information, time stepping, and variable calculation. The information contained in this section can assist the user in determining whether the model is stable and if the correct results are being obtained. To illustrate this section of the log file, one time step of the run is shown below and will be further explained in the following sections.

```
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
Minimum Time Step Selection:
      min              max
Time step selection: dt = 5.287e+00 (Chemistry minimum timestep).
      1.000e-02      5.287e+00      AriaRegion
Transient Time_Block_2: dt = 5.287
-----
Transient Time_Block_2, step 169, time 2.1985e+03, time step 5.2875e+00, 61.06% complete
-----
Advance AriaRegion, time 2198, time step 5.287

Memory Usage: current = 209186816 (199.5 M), high-water-mark = 217268224 (207.2 M)

Equation System AriaRegion->main:
* Step : Transient, Strategy: NEWTON, Time: 2.20e+03, Step: 5.29e+00
* Matrix: Solver: "Solve_Temperature", Unknowns: 1360, Nonzeros: 11578
* Mesh : Processor 0 of 1: 1253 of 1253 elems, 1363 of 1363 nodes
* Computing View Factors for enclosure space
  N O N L I N E A R              L I N E A R
-----
Step  Resid      Delta      Itns Status  Resid      Asm/Slv Time
-----
1      6.37e-02  1.10e+01   59   ok      8.23e-07  7.0e-03/2.0e-03
2      1.10e-04  8.18e-03   58   ok      1.19e-09  7.0e-03/2.0e-03
3      3.06e-07  8.81e-05   61   ok      3.68e-12  6.0e-03/2.0e-03
Termination reason: 8.80515e-05 < nonlinear_correction_tolerance(0.001)

Field              min      @ id      max      @ id max-chg  @ id pred-err  pred-min  @ id pr
-----
* TEMPERATURE 3.8650e+02  412 8.4155e+02  512 3.93e+00 1443 3.53e-04 3.8650e+02  412 8.4
```

DT_TEMPERATURE : MIN(value,loc) = (-1.18e+00, 1443) : MAX(value,loc) = (9.68e-01, 249)
 Segregated solution procedure converged after 1 iterations.

----- For equation system name: main -----

Global predictor error = 3.531e-04

Time step selection: dt <= 2.326e+01 (based on Predictor-Corrector Tolerance).

Time step selection: dt <= 1.057e+01 (based on Maximum Time Step Size Ratio).

Time step selection: dt <= 6.000e+01 (based on Maximum Time Step Size).

Time step selection: dt = 5.277e+00 (Minimum Chemistry timestep block_6).

Time step selection: dt <= 1.277e+01 (based on Stability limit for dt Ratio).

Time step selection: dt = 1.057e+01 (Adaptive time stepping result).

Killed 1 elements this timestep, for a total of 87 dead.

Global Variable	Value
Conv_ipo	189.224
Conv_ipo_surface_block_2_edge2_2	0
Conv_ipo_surface_block_3_edge2_2	0
killed_elements	1
space_area	0.155955
Tmax	386.498 841.553
total_dead_elements	87

Region::execute() time for AriaRegion: 3.537e+00 sec.

27.3.1. Current Temporal Information

The first part of the above section deals with the time step and temporal information about the running model. This section can be seen below:

+---

Minimum Time Step Selection:

min	max	
1.000e-02	5.287e+00	AriaRegion

Transient Time_Block_2: dt = 5.287

 Transient Time_Block_2, step 169, time 2.1985e+03, time step 5.2875e+00, 61.06% complete

 Advance AriaRegion, time 2198, time step 5.287

Aria determined the current time step size based on factors from the previous time step. Here, the maximum allowed time step size is 5.287, which is based on the minimum time step allowed for the chemistry model. It can also be seen that the run is currently in Time_Block_2 as is set up in Solution Control.

The information contained within the dotted lines allows one to gauge how far along a simulation is. In that one line, one can find the current time block, the iteration number, current simulation time, current time step, and the percent completion of the current time block.

27.3.2. Memory Reporting

One factor that determines the efficiency of a simulation is the amount of memory that is utilized. Each Sierra application will periodically output the current memory utilization - an example of this is shown below:

Memory Usage: current = 209186816 (199.5 M), high-water-mark = 217268224 (207.2 M)

One can see that at this time, 199.5 MB is currently being utilized, with a historical maximum of 207.2 MB during the course of the simulation.

27.3.3. Linear/Nonlinear Solves

The next part of the runtime information deals with the linear and nonlinear solution:

Equation System AriaRegion->main:

```
* Step : Transient, Strategy: NEWTON, Time: 2.20e+03, Step: 5.29e+00
* Matrix: Solver: "Solve_Temperature", Unknowns: 1360, Nonzeros: 11578
* Mesh : Processor 0 of 1: 1253 of 1253 elems, 1363 of 1363 nodes
* Computing View Factors for enclosure space
```

N O N L I N E A R

L I N E A R

Step	Resid	Delta	Itns	Status	Resid	Asm/Slv Time
1	6.37e-02	1.10e+01	59	ok	8.23e-07	7.0e-03/2.0e-03
2	1.10e-04	8.18e-03	58	ok	1.19e-09	7.0e-03/2.0e-03
3	3.06e-07	8.81e-05	61	ok	3.68e-12	6.0e-03/2.0e-03

Termination reason: 8.80515e-05 < nonlinear_correction_tolerance(0.001)

Field	min	@ id	max	@ id	max-chg	@ id	pred-err	pred-min	@ id	pr
* TEMPERATURE	3.8650e+02	412	8.4155e+02	512	3.93e+00	1443	3.53e-04	3.8650e+02	412	8.4

DT_TEMPERATURE : MIN(value,loc) = (-1.18e+00, 1443) : MAX(value,loc) = (9.68e-01, 249)
Segregated solution procedure converged after 1 iterations.

Each bullet point here gives some information as to the solution time and strategy, as well as some information about the matrix being solved. The line `Computing View Factors . . .` indicates that enclosure radiation viewfactors are being solved - more information about enclosure radiation diagnostics can be found in Section [27.3.6](#).

Each column of the NONLINEAR/LINEAR table deserves some explanation.

Step The nonlinear step being taken - here there are three nonlinear steps in the timestep

Resid Nonlinear residual at the end of each nonlinear step and before the linear steps are taken

Delta Difference in the solution variable(s) compared to the last nonlinear solution

Itns Number of linear iterations per nonlinear step

Status Whether linear solver completed successfully (output is either `ok` or `fail`)

Resid Linear residual at the end of the linear iterations

Asm/Slv Time Linear system assembly/solve times

A more complete description of this table is included in the Nonlinear Solution Specifications chapter `refch:nlsolv`.

As an example of how to interpret the output from this table, nonlinear step 2 will be translated to text: “During nonlinear step 2, the iterative linear solver took 7.0ms to assemble and 2.0ms to solve the linear system. It completed the solve in 58 iterations and exited with a linear residual of $1.19\text{e-}09$. The nonlinear residual at the end of the nonlinear step was $1.10\text{e-}04$, which was a change of $8.18\text{e-}03$ from the previous nonlinear step.” This section of the log file also shows the reason why the time step exited - usually due to reaching some desired tolerance or failure to converge. Here, the solution was reached when the change in temperature from the previous nonlinear step ($\text{Delta} = 8.81\text{e-}05$) was less than the nonlinear correction tolerance of 0.001. For more information on what linear and nonlinear residuals mean, refer to the Aria Theory Manual for how the equations and linear matrix are solved.

The lines below the table also show useful output on the fields being solved - here, for temperature. Here, we can see that the minimum temperature is 386.5 at node 412, and the maximum temperature is 841.6 at node 512. Information about the predictor-corrector errors are also shown, as well as the time derivative of temperature.

27.3.4. Timestep Determination

Based on the solution at the current step, the timestep is re-calculated. This is shown in the following lines:

```
----- For equation system name: main -----
Global predictor error = 3.531e-04
Time step selection: dt <= 2.326e+01 (based on Predictor-Corrector Tolerance).
Time step selection: dt <= 1.057e+01 (based on Maximum Time Step Size Ratio).
Time step selection: dt <= 6.000e+01 (based on Maximum Time Step Size).
Time step selection: dt = 5.277e+00 (Minimum Chemistry timestep block_6).
Time step selection: dt <= 1.277e+01 (based on Stability limit for dt Ratio).
Time step selection: dt = 1.057e+01 (Adaptive time stepping result).
```

These restrictions will change based on the method in which the solution is solved as well as the physics being solved. Here, the timestep may be limited by adaptive time stepping restrictions (predictor-corrector tolerance, maximum timestep ratio, and maximum time step size), chemistry timestep, and BDF2 stability limit. To put this block in sentence format, “The next timestep must be: less than or equal to 23.3s based on the predictor-corrector tolerance, less than or equal to 10.57s based on the maximum timestep ratio, less than or equal to 60s based on the maximum time step size, equal to 5.28s based on the ChemEQ solution, and less than or equal to 12.77s based on timestep stability.” After looking at it in this manner, one can see that the Chemistry timestep of 5.28s is the limiting timestep, and this will be the timestep size which is used in the next timestep, similar to what was explained in Section 27.3.1.

27.3.5. Global Variable Output

At the end of each timestep, a summary is given of the global variables in the model. If there are global variables that the user does not wish to output the “GLOBAL VARIABLES EXCLUDED FROM LOG FILE = [list of variables]” input deck line may be used.

Killed 1 elements this timestep, for a total of 87 dead.

Global Variable	Value
Conv_ipo	189.224
Conv_ipo_surface_block_2_edge2_2	0
Conv_ipo_surface_block_3_edge2_2	0
killed_elements	1
space_area	0.155955
Tmax	386.498 841.553
total_dead_elements	87

Region::execute() time for AriaRegion: 3.537e+00 sec.

This section is useful for run-time monitoring of key values, as well as how long the execution time was, in order to locate any slow-running parts of the model through time.

27.3.6. Chaparral Output - Enclosure Radiation

When enclosure radiation is defined and set up in the input file, an external library called Chaparral is utilized. Chaparral output is not automatically sent to the Sierra log file, but rather is sent to standard output (on Sandia HPC platforms, the slurm output file). Chaparral will output useful information regarding the viewfactor calculation, matrix smoothing, and the radiosity solver. Each section below will describe the output one may expect from Chaparral.

27.3.6.1. Instantiation

This output only occurs at the very start of the Chaparral output, but can help a user remember the number of processors used and the number of enclosures in the model:

```
*****
C H A P A R R A L  --  Version 3.3.1 development  --  unreleased
*****
```

```
Initializing for:
  number of processors = 1
  number of enclosures = 1
  max number of patches = 1000
```

27.3.6.2. Viewfactor Calculation

At the beginning of the viewfactor calculation, a banner will be displayed which shows the current simulation step and time, which is useful in correlating the Chaparral output to Aria output, as well as an estimate of the rowsum for each enclosure:

```
*****
C O M P U T E    V I E W F A C T O R S
Step = 214    Time = 2425.53
*****
```

The next section actually deals with the calculation of the radiation enclosure viewfactors:

```
*****
V I E W F A C T O R    C A L C U L A T I O N
*****
```

```
Calculating viewfactors for enclosure <space>
  enclosure geometry:    axisymmetric
  enclosure type:        partial (area=100), blocking
  # of rotations:        16
```

```

# of patches:          62
# of facets:           976
# of nodes:            63
spatial tolerance:     1e-06
BSP target max depth:  10
BSP target min length: 50
BSP Tree num leafs:    28
BSP Tree max depth:    5
BSP Tree min length:   27
BSP Tree max length:   45
output level:          2

```

Data segment memory size = 0.00Mb

Calling VF_Hemicube()...

```

resolution      = 400
max subdivisions = 4
min separation   = 5

```

Minimum Partial Enclosure Area = 0.151296

```

Minimum effective surface radius    = 0.00916667
Minimum separation distance          = 0.00558985
Maximum desired surface subdivision = 9, 46
Actual maximum surface subdivision  = 4

```

Data segment memory size = 0.00Mb

Elapsed time = 3.92

While some of this output is merely a summary of user-specified or default tolerances, some information is useful during the simulation or for debugging. First, the user-defined name of the enclosure is shown in < > brackets (i.e., space). The number of facets and nodes that participate in the enclosure can also be useful in determining if the enclosure is complete in some instances. Last, if one is specifying a partial enclosure, then the Minimum Partial Enclosure Area is useful in correct specification of the corresponding parameter in the input file.

For simulations in which the enclosure does not change through time, the viewfactor calculation and corresponding text output will only appear once per enclosure after instantiation.

27.3.6.3. Viewfactor Smoothing

If viewfactor smoothing is specified, information about this step is also output. An example is shown below:

```
*****
V I E W F A C T O R   M A T R I X   S M O O T H I N G
*****
```

Smoothing of viewfactor matrix for enclosure <space>

```
PCG Solver, wt = 2.0
Max iterations = 500
Tolerance      = 1e-07
```

Enforcing reciprocity by addition...

```
Nonzero lower triangular entries = 688 changed to 688
Nonzero upper triangular entries = 687 changed to 688
Elapsed time                      = 0.00
Number of passes                  = 1
Number of iterations              = 26
Elapsed time                      = 0.00
```

Again, the enclosure name is denoted within the < > brackets, with another summary of defined values. This section is useful for debugging problematic enclosures, since viewfactor smoothing can fail when the enclosure is ill-defined.

27.3.6.4. Viewfactor Summary

Once the viewfactors have been computed and smoothing has been applied, Chaparral will output the summary of how well the operations have done. This is shown in the Viewfactor Matrix Summary:

```
*****
V I E W F A C T O R   M A T R I X   S U M M A R Y
*****
```

Viewfactor matrix summary for enclosure <space>

```
Target rowsum                = 62
Raw rowsum total              = 62.000000
Raw rowsum error min         = -1.1479e-07
Raw rowsum error max         = 1.1025e-07
Raw rowsum error mean        = 4.9383e-09 +/- 4.9314e-08
Smoothed rowsum total         = 62.000000
Smoothed rowsum error min     = -7.0897e-08
Smoothed rowsum error max     = 5.9255e-08
Smoothed rowsum error mean    = 2.8875e-10 +/- 2.7300e-14
```

Viewfactor matrix is 36.19% dense

```
Total elapsed time = 3.93 (sec)
  (Initialization) = 0.01
  (Calculation)    = 3.92
  (Smoothing)      = 0.00
```

```
Data segment memory size = 0.00Mb
```

Here one can see that for the space enclosure, the computed rowsum closely matched the target rowsum, with and without smoothing. If one is also concerned about timing, an itemized timing summary is given for the viewfactor matrix setup. This is probably the most useful section to look at if one is concerned about issues with certain enclosures, as well as judging the cost and usefulness of viewfactor smoothing.

27.3.6.5. Radiosity Solution

After the viewfactor matrix has been populated, Chaparral will use this to compute the radiosity matrix. Output for one iteration of the radiosity matrix solver is shown below:

```
*****
R A D I O S I T Y    S O L V E S
Step = 214    Time = 2425.53 Time_Step = 6.18025 Iteration = 1
*****

*****
R A D I O S I T Y    M A T R I X    S O L V E R
*****

Solving radiosity equations with GMRES for enclosureID <space>

Initial residual = 1.553372e+03    tol = 2.000000e-07
iter:    0    residual = 1.553372e+03
iter:    1    residual = 2.657621e+04
iter:    2    residual = 6.553812e+03
iter:    3    residual = 1.226445e+03
iter:    4    residual = 3.526103e+02
iter:    5    residual = 8.437261e+01
iter:    6    residual = 3.212877e+01
iter:    7    residual = 8.262992e+00
iter:    8    residual = 2.397060e+00
iter:    9    residual = 3.692025e-01
iter:   10    residual = 1.010501e-01
iter:   11    residual = 3.528043e-02
```

```

iter:   12   residual = 6.867475e-03
iter:   13   residual = 1.206750e-03
iter:   14   residual = 9.768426e-05
iter:   15   residual = 1.063625e-05
iter:   16   residual = 1.902986e-06
iter:   17   residual = 3.433117e-07
iter:   18   residual = 9.218341e-08

```

```

Real residual is 1.48685e-09
Computing final fluxes

```

```

Total iterations:      18
Total elapsed time:    0.00 (sec.)
  GMRES setup time:    0.00 (sec.)
  GMRES solve time:    0.00 (sec.)
Residual L2 norm:      1.48685e-09
Flux Integration:      -0.219045
Minimum Emissivity:    0.3
Maximum Emissivity:    1
Minimum Temperature:   443.752, Element: 778
Maximum Temperature:   1200, Element: 415

```

This output is somewhat similar to the Aria run-time output, in that the linear iteration count is given along with the linear residual, though the Chaparral output is more detailed, as it gives the linear residual at each linear step instead of a summary. Minimum and maximum values of emissivity and temperature in the enclosure can also help in understanding the behavior of the radiosity solve through time.

27.4. RUN SUMMARY

At the end of a completed run, a summary is printed to the log file, which starts with something along the lines of the following:

```

Procedure AriaProcedure complete                               May 14 2014 11:19:44
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
Execution complete

```

The different sections of the run summary will be described below.

27.4.1. Timing

The Sierra code as well as Aria contain many timers which encapsulate certain operations of each simulation. The timing summary shows the results of these timers and are organized so that aspects of

the model that take more time can be found. A sample timing summary can be seen below and will be further explained:

Timing summary of 1 processor

Timer	Count	CPU Time	Wall Time
-----	-----	-----	-----
Sierra	1	15:14.415 (100.0%)	15:19.072 (100.0%)
Procedure AriaProcedure			
Initialize	1	0.017 (<0.01%)	0.017 (<0.01%)
Execute	1	15:13.010 (99.85%)	15:17.659 (99.85%)
Mesh input	1	0.168 (0.02%)	0.170 (0.02%)
Mesh output	357	0.905 (0.10%)	1.196 (0.13%)
Region AriaRegion			
Initialize	1	0.015 (<0.01%)	0.017 (<0.01%)
Execute	357	15:11.364 (99.67%)	15:15.619 (99.62%)
Nonlinear Iteration	997	16.482 (1.80%)	16.568 (1.80%)
Preprocessing	997	6.811 (0.74%)	6.865 (0.75%)
Chemistry Kinetics	997	6.768 (0.74%)	6.820 (0.74%)
LinSys Assembly	997	6.091 (0.67%)	6.119 (0.67%)
LinSys Solve	997	2.458 (0.27%)	2.472 (0.27%)
LinSys Scatter	997	0.276 (0.03%)	0.273 (0.03%)
Nonlinear Utilities	3988	0.668 (0.07%)	0.669 (0.07%)
Postprocessing	358	0.034 (<0.01%)	0.046 (<0.01%)
Utilities	2144	14:51.790 (97.53%)	14:54.651 (97.34%)
Parallel Sync	5776	0.012 (<0.01%)	0.010 (<0.01%)
Chaparral Viewfactor	357	14:51.546 (97.50%)	14:54.417 (97.32%)
Chaparral Radiosity	997	0.629 (0.07%)	0.623 (0.07%)
Chemistry Utilities	3062	0.085 (<0.01%)	0.079 (<0.01%)
Contact Search	357	0.003 (<0.01%)	0.000 (<0.01%)
Tmax	1074	0.259 (0.03%)	0.372 (0.04%)
Tmax	358	0.275 (0.03%)	0.277 (0.03%)
Mesh input	1	0.168 (0.02%)	0.170 (0.02%)
Mesh output	357	0.904 (0.10%)	1.196 (0.13%)
Results output	358	0.326 (0.04%)	0.420 (0.05%)
Restart output	358	0.549 (0.06%)	0.729 (0.08%)
History output	358	0.015 (<0.01%)	0.027 (<0.01%)
Heartbeat output	358	0.020 (<0.01%)	0.036 (<0.01%)
Control	109	0.001 (<0.01%)	0.005 (<0.01%)
Vis output	358	0.001 (<0.01%)	0.000 (<0.01%)
Perf: RunSierra	1	1.218 (0.13%)	1.225 (0.13%)
Perf: RunSierra::parse	1	1.218 (0.13%)	1.225 (0.13%)
Perf: RunSierra::Domain::execute	1	15:13.197 (99.87%)	15:17.846 (99.87%)

Each entry shows the CPU and Wall Times associated with it, along with a percentage, which is the percentage of the total run time. One can also see where a timer resides with respect to the Procedure,

Region, etc. by the level of indentation in the timing summary. For example, one can see by the indentation that `Nonlinear Iteration` is a part of `Execute`, which resides in the `Region` area `Region`. The sum of timers of all entries on a certain indentation level should be less than or equal to the timer of the parent entry, since the parent timer is a wrapper around the children timers and the corresponding code execution. For example, `Preprocessing`, `LinSys Assembly`, `LinSys Solve`, `LinSys Scatter`, and `Nonlinear Utilities` timers are equal to 16.304s of CPU time, which is less than the 16.482s of `Nonlinear Iteration`.

Here is a general description of what each timer means:

Sierra	Complete encapsulation of the simulation
Procedure	Procedure-level of the simulation, including Solution Control and Regions
Initialize	Initialization of the Procedure
Execute	Execution time for the procedure; in a simple one-region simulation, this will be very similar to Region Execute
Mesh Input	Time to read in the input Genesis mesh
Mesh Output	Time required to output any results, e.g., Results, Restart, History, Heartbeat Output
Region	Region scope of the simulation, including physics setup
Initialize	Initialization of the Region
Execute	Execution time for the Region
Nonlinear Iteration	Performance of the nonlinear solves
Preprocessing	Setup for the nonlinear iterations
Chemistry Kinetics	Setup of chemistry volume source and ODE solver
LinSys Assembly	Assembly of the Linear system of matrices
LinSys Solve	Solution of the linear system of matrices
LinSys Scatter	Division of the linear system of matrices in parallel
Nonlinear Utilities	A combination of several utilities (e.g., chemistry, radiation) that occur during the nonlinear step
Postprocessing	Execution of user-requested post-processing fields
Utilities	Wrapper around utilities required for system of equations
Parallel Sync	Communication required between processors for simulations run in parallel
Chaparral Viewfactor	Viewfactor calculation for enclosure radiation
Chaparral Radiosity	Radiosity calculation for enclosure radiation
Chemistry Utilities	Chemistry solve which occurs outside of the nonlinear loop

Contact Search Search required to find contact interactions
 Tmax Determination via Encore of Tmax postprocessor
 Mesh input Time to read in the Genesis mesh
 Mesh output Time to output results
 Results output Time to output Results Output block(s)
 Restart output Time to output Restart Output block(s)
 History output Time to output History Output block(s)
 Heartbeat output Time to output Heartbeat Output block(s)
 Control Determination of when to output
 Vis output Time to output in-situ visualization output
 Perf: Sierra performance-related timers

It can be seen that in this simulation, the bulk of the time is spent in Chaparral Viewfactor. This is due to the fact that this simulation involves element death, and the radiation enclosure is updated each time that elements are killed.

27.4.2. Memory

In addition to the run-time memory statistics, there is a memory summary printed at the end of the log file. An example of this is shown below:

```

Memory summary of 1 processor
      Metric                Largest      Processor      Smallest      Processor
-----
Dynamically Allocated (Heap)  73.8 MB on 0 at 13:33.348  73.8 MB on 0 at 13:33.348
Largest Free Fragment (Heap)  43.0 MB on 0 at 13:33.348  43.0 MB on 0 at 13:33.348
      Total Memory In Use  398.1 MB on 0                398.1 MB on 0
      Major Page Faults    0 flts on 0                0 flts on 0
  
```

The output of this memory summary becomes more varied for a parallel simulation, where the model may not be evenly distributed amongst processors.

Another useful piece of information related to memory reporting is contained in the Performance metric summary:

Avg Available memory per processor 4036.1 MB

Here one can see the simulation memory high-water mark, as well as the available memory per processor on the system on which the simulation was run. This information becomes important when one would like to maximize the amount of memory is used, which can reduce the number of processors required. For example, in a large series of uncertainty quantification simulations, reduction of processor count can increase throughput on HPC platforms with queuing systems.

27.5. SUMMARY

Though it can be difficult to interpret the sometimes large amounts of data that are output via log files, this information can be useful in ascertaining a simulation's performance and can also be used to improve the manner in which it is run. Though some of the information presented here is Aria-specific, much of it is also applicable when using other Sierra applications and can aid in use of those codes as well.

28. DIAGNOSTIC OUTPUT

28.1. ABOUT DIAGNOSTIC STREAMS

Aria is instrumented with a diagnostic output capability that can be very useful when you're debugging problems. You can tell Aria to write additional information to the log file by enabling different *print masks*. The list of available print masks is summarized in table 28.1; this list is also supplied in the Aria runtime help which is printed if you add `-h` to your `sierra` command line.

There are two ways to activate a print mask for diagnostic printing. The first is to use the `-arialog` command line option. When you're using the `sierra` script this is a little odd because you have to pass that option as an option to the script. By example, if you want to enable the sensitivity checker you can do that like this

```
sierra aria ...-arialog sens_check
```

where ... all of the other command line options you typically use.

The second way to enable a print mask is more versatile and is done through your `aria` input file. At the highest level of the input file – somewhere in the `BEGIN SIERRA` block – you can add a `DIAGNOSTIC CONTROL` block. This enables you to specify intervals in time or time step number over which print masks should be enabled. As a simple example, let's say you want to enable the sensitivity checker (see `sens_check` in 28.1) around time step number 47. Here's an example input file snippet that allows you to do that:

```
Begin Diagnostic Control arialog
  From Step 46 to 48 enable sens_check
End
```

With this, the sensitivity checker will only be active for those three time steps (it's also valid to say `From Step 47 to 47 ...`). The end of this chapter includes a detailed command reference for that input.

Lastly, I'll just mention here for now that there are additional capabilities for logging, such as per-processor log files (by default only processor zero logs output). If you need more advanced diagnostics contact the Aria developers for help.

Print Mask	Description
bc	Display boundary condition information
debug	Display debug diagnostic information
eq	Display equation information
expression	Display expression information
hadapt	Display h-adapt diagnostic information
finite_check	Display warning messages about any non-finite expression values or sensitivities
nonlinear	Display nonlinear solver information
pp	Display postprocessor diagnostic information
sens_check	Display messages generated by expression sensitivity checker
fast_sens_check	Display messages generated by sensitivity checker (skipping FAD, element, and kernel expressions)
species	Display species information
transfer	Display transfer information
dualsolve	Display dual solve information
plugin	Display plugin information
chaparral	Display chaparral information
utility	Display equation system utility information

Table 28.1-1.. Aria diagnostic output print masks.

28.2. DIAGNOSTIC OUTPUT COMMAND REFERENCE

28.3. DIAGNOSTIC CONTROL

Scope: Sierra

Begin Diagnostic Control <i>Name</i>
Enable <i>Printmask</i>
From Step <i>StartStep</i> To <i>EndStep</i> Enable <i>Printmask</i>
Set Information Stream Path <i>File_path</i>
End

Summary Specifies the diagnostic writer to set output control features.

Description The diagnostic and informational output can be selectively enabled based on time, step or an application specified condition. During the application's procedure execution loop, the diagnostic controller evaluates the enclosed line commands in the order specified in the input deck. The diagnostic options specified in the first line command that meets its criteria are applied.

Since control parameters are only applied when the criteria is met, it is important to include an ENABLE line command with the base settings to be applied as a baseline. Refer the '-h' output for a complete list of diagnostic writers and available values.

fmwkout Specify a comma separated list of: contact Display contact diagnostic information coverage Collect and display traceable function usage coverage dump-load Dump domain atfer mesh load dump-setup Dump domain after setup input-check Check input deck and mesh load, does not execute members Display data structure members messages parameters Display parameter diagnostic information scontrol Display solver control diagnostic information search Display search diagnostic information syntax-check Check syntax of input deck, does not load mesh or execute trace Display execution trace trace-stats Display execution time and memory usage during trace transfer Display transfer diagnostic information warning Display warning messages

iossdebug Specify a comma separated list of: coverage Collect and display traceable function usage coverage error Display error messages members Display data structure members messages mesh Display mesh I/O diagnostic information restart Display restart I/O diagnostic information results Display results I/O diagnostic information serialized Display serialized I/O information trace Display execution trace trace-stats Display execution time and memory usage during trace warning Display warning messages

prsrdebug Specify a comma separated list of: coverage Collect and display traceable function usage coverage error Display error messages members Display data structure members messages parser Display parser diagnostic information trace Display execution trace trace-stats Display execution time and memory usage during trace warning Display warning messages

The options which may be enabled varies for each applicaiton, diagnostic and information writer. To obtain a list of available options, use the sierra app -i -O -h command.

See Diagnostic Stream for specifying the output destination.

28.3.1. Enable

Scope: Diagnostic Control

Enable *Printmask*

Parameter	Value	Default
<i>Printmask</i>	"string"	undefined

Summary Specifies the options to enable when no other control option criteria are satisfied.

28.3.2. From Step

Scope: Diagnostic Control

From Step *StartStep* To *EndStep* Enable *Printmask*

Parameter	Value	Default
<i>StartStep</i>	integer	undefined
<i>EndStep</i>	integer	undefined
<i>Printmask</i>	"string"	undefined

Summary Specifies the options to enable when the step is within the specified range.

28.3.3. Set Information Stream Path

Scope: Diagnostic Control

Set Information Stream Path *File_path*

Parameter	Value	Default
<i>File_path</i>	string	undefined

Summary File path to information stream information to.

28.3.4. Diagnostic Stream

Scope:

Diagnostic Stream *File_name* [*Indent-streambuf-flags₁* [*Indent-streambuf-flags₂*]]

Parameter	Value	Default
<i>File_name</i>	string	undefined

Summary File path to write diagnostic messages to.

28.3.5. Enable

Scope:

Enable *Printmask*

Parameter	Value	Default
<i>Printmask</i>	"string"	undefined

Summary Specifies the options to enable when no other control option criteria are satisfied.

28.3.6. From Step

Scope:

From Step *StartStep* To *EndStep* Enable *Printmask*

Parameter	Value	Default
<i>StartStep</i>	integer	undefined
<i>EndStep</i>	integer	undefined
<i>Printmask</i>	"string"	undefined

Summary Specifies the options to enable when the step is within the specified range.

28.3.7. Set Information Stream Path

Scope:

Set Information Stream Path *File_path*

Parameter	Value	Default
<i>File_path</i>	string	undefined

Summary File path to information stream information to.

29. LEVEL SET REFERENCE

29.1. LEVEL SET OVERVIEW

Aria employs a level set capability supported by the Krino library. Here the basic Krino capability is used to define the level set interface and the problem physics is handled with equations native to Aria.

To use this capability one would define `Level_Set` for the DOF on a particular volume mesh entity (block) as described in 6.5. Then the level set interface would be defined using the `LEVEL SET INTERFACE` commands. In tracking the level set interface the Narrow Band Width is the distance over which the level set distance is calculated. Outside this narrow band, the distance is clipped when the redistancing calculation is performed. Advection algorithms in Aria apply over the entire domain, but the redistancing algorithms in Krino support this clipping. Tailoring the Narrow Band Width to one's problem can help reduce the cost of redistancing and reduce solution artifacts away from the interface.

29.2. LEVEL SET INTERFACE

Scope: Aria Region

```
Begin Level Set Interface InterfaceName
  Composite Name {=|are|is} Variable
  Distance Variable {=|are|is} Variable
  Extension Velocity {=|are|is} Value...
  Initial Offset Distance {=|are|is} Offset
  Initial Scale Factor {=|are|is} Scale
  Max Feature Size On Surfaces {=|are|is} Value
  Narrow Band Element Size Multiplier {=|are|is} Value
  Narrow Band Width {=|are|is} Value
  Perform Initial Redistance {=|are|is} performInitialRedistance
  Redistance Method {=|are|is} RedistanceMethodType
  Reinitialize Every Step
```

Simple Max Feature Size On Surfaces {=|are|is} *Value*

Begin Analytic Initial Condition *BlockName*

End

Begin Compute_Surface_Distance *SurfaceName*

End

Begin Motion Specification *Motion*

End

End

Summary Main block for krino level set interface control mechanics.

Description This is the main block for the level set interface control mechanics. This block specifies a level set interface that is integrated in time using an extension velocity. The plan is that the physics application code will see only this mechanics, although there may be several other supporting mechanics that are plugged in.

29.2.1. Composite Name

Scope: Level Set Interface

Composite Name {=|are|is} *Variable*

Parameter	Value	Default
<i>Variable</i>	string	undefined

Summary Optionally specify a composite level set name which may be used across multiple level sets to define composite phases.

29.2.2. Distance Variable

Scope: Level Set Interface

Distance Variable {=|are|is} *Variable*

Parameter	Value	Default
<i>Variable</i>	string	undefined

Summary Specify the distance variable name.

29.2.3. Extension Velocity

Scope: Level Set Interface

Extension Velocity {=|are|is} *Value...*

Parameter	Value	Default
<i>Value</i>	real...	undefined

Summary Specify the extension velocity used to evolve the level set field. Default is 0 0 0.

29.2.4. Initial Offset Distance

Scope: Level Set Interface

Initial Offset Distance {=|are|is} *Offset*

Parameter	Value	Default
<i>Offset</i>	real	undefined

Summary Specify an offset distance to be applied to the initial level set. Allows the user to grow or shrink the initialized level set.

29.2.5. Initial Scale Factor

Scope: Level Set Interface

Initial Scale Factor {=|are|is} *Scale*

Parameter	Value	Default
<i>Scale</i>	real	undefined

Summary Specify a scale factor to be applied to the initial level set. Allows the user to multiple the entire level set by a constant, primarily useful for nested (concentric) level sets. This modifier gets applied after the INITIAL OFFSET DISTANCE, if there is one.

29.2.6. Max Feature Size On Surfaces

Scope: Level Set Interface

Max Feature Size On Surfaces {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specify the maximum feature size on surfaces, features smaller than this will be destroyed near all surfaces. IN BETA TESTING!

29.2.7. Narrow Band Element Size Multiplier

Scope: Level Set Interface

Narrow Band Element Size Multiplier {=*|are|is*} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specify the width of the narrow band width used for the level set field as the given multiplier times the maximum element length scale. If this command is omitted, the distance will be computed throughout the entire domain, but this is not generally scalable in terms of memory or cpu time.

29.2.8. Narrow Band Width

Scope: Level Set Interface

Narrow Band Width {=*|are|is*} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specify the width of the narrow band. This form is deprecated. Use NARROW BAND ELEMENT SIZE MULTIPLIER instead.

29.2.9. Perform Initial Redistance

Scope: Level Set Interface

Perform Initial Redistance {=*|are|is*} *performInitialRedistance*

Parameter	Value	Default
<i>performInitialRedistance</i>	{false true}	FALSE

Summary Perform redistancing operation just after intial conditions are applied.

29.2.10. Redistance Method

Scope: Level Set Interface

Redistance Method {=*|are|is*} *RedistanceMethodType*

Parameter	Value	Default
<i>RedistanceMethodType</i>	{closest_point fast_marching}	CLOSEST_POINT

Summary Specify the algorithm to be used for redistancing.

29.2.11. Reinitialize Every Step

Scope: Level Set Interface

Summary Specify that this level set interface should be re-initialized every time step. For example this can be combined with an analytic mesh surface initial condition that is moving due to applied displacements to move the CDFEM interface location with the mesh surface.

29.2.12. Simple Max Feature Size On Surfaces

Scope: Level Set Interface

Simple Max Feature Size On Surfaces {=*|are|is*} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specify the maximum feature size on surfaces, features smaller than this will be destroyed near all surfaces (simple version) IN BETA TESTING!

29.2.13. Narrow Band Width

Scope:

Narrow Band Width {=*|are|is*} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specify the width of the narrow band. This form is deprecated. Use NARROW BAND ELEMENT SIZE MULTIPLIER instead.

29.3. LEVEL SET INITIAL CONDITIONS

As previously stated one can use the Aria initial condition definitions described in 8 by using Level_Set as the DOF.

Alternatively, one can also use the the level set initial condition support provided by the Krino library. In a multi-region analyses where one has a level set region whose level result is being transferred to another region which controls output of the results, synchronization of the initial state may become an issue. In this event the initial conditions being transferred from the Krino region can be overwritten by the region controlling output. This problem can be dealt with by orchestration of initialization by Solution Control using the command structure included below wherein LS_Region is the level set region.

If one chooses to use the initial conditions from within Aria instead, the command line for the Initialize command block is not used and the "Use Initialize" command line would not appear in the Solution Control "System" command block.

```

Begin Solution Control Description
  Use System Main
  .
  .
  Begin Initialize The_Init_Block
    Advance LS_Region
    Event LS_Region_REINITIALIZE_LEVELSETS
  End
  Begin System Main
    Use Initialize The_Init_Block
    .
    .
  End System Main
  .
  .
End Solution Control Description

```

29.4. ANALYTIC INITIAL CONDITION

Scope: Level Set Interface

```

Begin Analytic Initial Condition BlockName

  Composition Method {=|are|is} CompositionMethod

  Compute Time Of Arrival On BlockName Speed {=|are|is} BlockSpeed

  Compute Time Of Arrival With Element Speed {=|are|is}
  ElementSpeedFieldName

  Cylinder P1 {=|are|is} Param21 Param22 Param23 P2 {=|are|is}
  Param51 Param52 Param53 Radius {=|are|is} Param8 [ Sign = Sign |
  Motion = Motion ]

  Ellipsoid Center {=|are|is} Param11 Param12 Param13 Semiaxes {=|
  are|is} Param21 Param22 Param23

  Facets Format {=|are|is} Facet_format Filename {=|are|is}
  Facet_filename [ Scale = ScaleFactor |Sign = Sign |Motion =
  Motion ]

  Mesh Surfacename [ Sign {=|are|is} Sign ]

  Plane Normal {=|are|is} Param21 Param22 Param23 Offset {=|are|is}
  Param5 [ Sign {=|are|is} Sign ]

  Random [ Seed {=|are|is} Seed ]

```

Sphere Center {=|are|is} *Param2₁ Param2₂ Param2₃* Radius {=|are|is}
Param5 [Sign = *Sign* | Motion = *Motion*]

End

Summary Allows the specification of analytic initial condition blocks. Must specify at least one analytic shape. Can have one to many analytic shapes in any combination on a single level set interface.

29.4.1. Composition Method

Scope: Analytic Initial Condition

Composition Method {=|are|is} *CompositionMethod*

Parameter	Value	Default
<i>CompositionMethod</i>	{maximum_signed_distance minimum_signed_distance}	undefined

Summary Specify the method used to combine the results of the individual surface distance calculations. Using MINIMUM_SIGNED_DISTANCE, the resulting negative region will be the union of the negative regions of the individual surfaces. The positive region will be the intersection of the positive regions of the individual surfaces. Using MAXIMUM_SIGNED_DISTANCE, the resulting negative region will be the intersection of the negative regions of the individual surfaces. The positive region will be the union of the positive regions of the individual surfaces. The default is MINIMUM_SIGNED_DISTANCE.

29.4.2. Compute Time Of Arrival On

Scope: Analytic Initial Condition

Compute Time Of Arrival On *BlockName* Speed {=|are|is} *BlockSpeed*

Parameter	Value	Default
<i>BlockName</i>	string	undefined
<i>BlockSpeed</i>	real	undefined

Summary Specify that the level set field should be initialized to the time-of-arrival of the interface to each point in space where the level set field is defined. This calculation uses the given speed to indicate the speed at which the interface moves through the given block. The zero contour of the field is the initial location of the interface and is specified via the surfaces in the initial condition.

29.4.3. Compute Time Of Arrival With Element Speed

Scope: Analytic Initial Condition

Compute Time Of Arrival With Element Speed {=*|are|is*}
ElementSpeedFieldName

Parameter	Value	Default
<i>ElementSpeedFieldName</i>	string	undefined

Summary Specify that the level set field should be initialized to the time-of-arrival of the interface to each point in space where the level set field is defined. This calculation uses a element-based field that indicates the speed at which the interface moves through the element. The zero contour of the field is the initial location of the interface and is specified via the surfaces in the initial condition.

29.4.4. Cylinder

Scope: Analytic Initial Condition

Cylinder P1 {=*|are|is*} *Param2*₁ *Param2*₂ *Param2*₃ P2 {=*|are|is*} *Param5*₁
*Param5*₂ *Param5*₃ Radius {=*|are|is*} *Param8* [Sign = *Sign* | Motion = *Motion*
]

Parameter	Value	Default
<i>Param2</i>	real_1 real_2 real_3	undefined
<i>Param5</i>	real_1 real_2 real_3	undefined
<i>Param8</i>	real	undefined
<i>Sign</i>	integer	undefined
<i>Motion</i>	string	undefined

Summary Specify cylinder as interface surface, with given radius and two endpoints of axis p1 and p2. The length of the cylinder is norm(p2 - p1).

29.4.5. Ellipsoid

Scope: Analytic Initial Condition

Ellipsoid Center {=*|are|is*} *Param1*₁ *Param1*₂ *Param1*₃ Semiaxes {=*|are|is*}
*Param2*₁ *Param2*₂ *Param2*₃

Parameter	Value	Default
<i>Param1</i>	real_1 real_2 real_3	undefined
<i>Param2</i>	real_1 real_2 real_3	undefined

Summary Specify Ellipsoid as interface surface with given center and semiaxes. Note the result is not an exact distance function except in the case of a sphere (equal semiaxes).

29.4.6. Facets

Scope: Analytic Initial Condition

Facets Format {=*|are|is*} *Facet_format* Filename {=*|are|is*} *Facet_filename*
[*Scale* = *ScaleFactor* | *Sign* = *Sign* | *Motion* = *Motion*]

Parameter	Value	Default
<i>Facet_format</i>	{ <i>exo fac ply stl</i> }	undefined
<i>Facet_filename</i>	string	undefined
<i>ScaleFactor</i>	real	undefined
<i>Sign</i>	integer	undefined
<i>Motion</i>	string	undefined

Summary Specify a file containing a surface from which the level set should be initialized.

29.4.7. Mesh

Scope: Analytic Initial Condition

Mesh *Surfacename* [*Sign* {=*|are|is*} *Sign*]

Parameter	Value	Default
<i>Surfacename</i>	string	undefined

Summary Specify a mesh surface as interface surface.

29.4.8. Plane

Scope: Analytic Initial Condition

Plane Normal {=*|are|is*} *Param2*₁ *Param2*₂ *Param2*₃ Offset {=*|are|is*} *Param5* [*Sign* {=*|are|is*} *Sign*]

Parameter	Value	Default
<i>Param2</i>	<i>real</i> ₁ <i>real</i> ₂ <i>real</i> ₃	undefined
<i>Param5</i>	real	undefined

Summary Specify plane as interface surface with given normal and offset. Equation of plane is $o = \text{normal}/\text{mag}(\text{normal}) \cdot x + \text{offset}$. Given the vector r to a point on the plane, the offset is $-\text{normal}/\text{mag}(\text{normal}) \cdot r$.

29.4.9. Random

Scope: Analytic Initial Condition

Summary Specify initial condition to pseudorandom field between -1 and 1.

29.4.10. Sphere

Scope: Analytic Initial Condition

Sphere Center {=*are*|is} *Param2*₁ *Param2*₂ *Param2*₃ Radius {=*are*|is} *Param5*
[Sign = *Sign* |Motion = *Motion*]

Parameter	Value	Default
<i>Param2</i>	real_1 real_2 real_3	undefined
<i>Param5</i>	real	undefined
<i>Sign</i>	integer	undefined
<i>Motion</i>	string	undefined

Summary Specify sphere as interface surface with given center and radius.

30. LOCAL COORDINATE SYSTEM REFERENCE

30.1. LOCAL COORDINATE SYSTEMS

Aria provides utilities for convenient transformation of model specific information to the computational coordinate frame. Several common local coordinate systems - rectangular, cylindrical, spherical and conical - are pre-defined in Aria.



Known Issue: It has been determined that the conical local coordinate system has not been correctly implemented. Users should avoid use of this coordinate system until this has been corrected.

Figure 30.1 shows how each of the afore-mentioned local coordinate systems are constructed using the information supplied in the LOCAL COORDINATE SYSTEM command block. As a general rule, ORIGIN defines the origin of the local coordinate system, VECTOR defines the z-axis of the local coordinate system, and POINT is used to create the x-axis of the local coordinate system. The y-axis is then constructed via a cross-product of the x- and z- axes.

Given ORIGIN **O**, VECTOR **V**, and POINT **P** for any local coordinate system, internal initialization of geometric data is achieved via the following pseudo-code in 3D:

```
CoordinateSystem::setLocalCoordinateAxes(Origin O, Vector V, Point P)
{
    e3 = unit_vector(V)           # z axis
    D1 = P - O                   # vector from origin to to point
    D2 = projected_vector(D1, e3) # project D1 in direction of e3
    D3 = D1 - D2                 # orthogonal component of D1 to e3
    e1 = unit_vector(D3)         # x axis
    e2 = cross_product(e3, e1)   # y axis

    # Saved variables
    origin = O                   # origin
    x_axis = e1
    y_axis = e2
    z_axis = e3
}
```




Figure 30.1-1.. A depiction of the available local coordinate system options and how they are constructed given ORIGIN, VECTOR, and POINT.

At point **P**, a local z-axis e_3 is defined as the unit vector in the direction of vector **V**. The local x-axis e_1 is then defined as an orthogonal projection from point **P** to e_3 and finally, the local y-axis e_2 is defined based on the cross product of e_3 and e_1 .

Classical transformations consider the evaluation of vector or tensor components from one basis, e_i , in an alternative basis e'_i . By supplying parameters for the pre-defined coordinate system in the LOCAL COORDINATE SYSTEM command block one in effect defines the orientation of the local coordinate system block relative to the computational coordinate directions. Using this information any appropriate transformations can be computed internal to the code. Finally, each local coordinate system can be associated with multiple element blocks using the LOCAL COORDINATE SYSTEM line command.

Local coordinate systems are particularly useful for tensor material properties defined using their local principal values. In this case one must select a "generalized" material model in order to fully utilize the principal component values. Current support of this feature is currently limited to material diffusive coefficients - however, further support is planned.

Given any point $\mathbf{P}$ in space at which the global value of a given tensor based material property $[\mathbf{K}]$ is to be evaluated, the local principal axes based on the initialization described previously must be computed. This can be represented for the various local coordinate systems by the following pseudo-code:

```
CartesianCoordinateSystem::getPrincipalAxes(Point P, Vector e1, Vector e2, Vector e3)
{
    e1 = x_axis          # principal x axis
    e2 = y_axis          # principal y axis
    e3 = z_axis          # principal z axis
}
```

```
CylindricalCoordinateSystem::getPrincipalAxes(Point P, Vector e1, Vector e2, Vector e3)
{
    e3 = z_axis          # principal z axis = same as LCS z axis
    D1 = P - origin      # vector from origin to to point
    D2 = projected_vector(D1, e3) # project D1 in direction of e3
    D3 = D1 - D2         # orthogonal component of D1 to e3
    e1 = unit_vector(D3) # principal x axis in r
    e2 = cross_product(e3, e1) # principal y axis in theta
}
```

```
SphericalCoordinateSystem::getPrincipalAxes(Point P, Vector e1, Vector e2, Vector e3)
{
    D1 = P - origin      # vector from origin to to point
    e1 = unit_vector(D1) # principal x axis in r
    e2 = cross_product(z_axis, e1) # principal y axis in theta
    e3 = cross_product(e1, e2)    # principal z axis in phi
}
```

If the principal values K_{11} , K_{22} and K_{33} are provided, these correspond to principal directions $\mathbf{e}_1$, $\mathbf{e}_2$ and $\mathbf{e}_3$ respectively. Given $[\mathbf{K}]$ defined locally in the local coordinate system, the transformation matrix $[\mathbf{M}]$ that rotates the orthogonal triplet $\{\mathbf{e}_1, \mathbf{e}_2, \mathbf{e}_3\}$ into the global coordinate space $\{x, y, z\}$ is computed and the material property in global coordinates is defined as

$$[\mathbf{K}_g] = [\mathbf{M}]^T [\mathbf{K}] [\mathbf{M}] \quad (30.1)$$

30.2. LOCAL COORDINATE SYSTEM

Scope: Sierra

Begin Local Coordinate System *Coordinate_System_Name*

Origin {=|are|is} *Value...*

```

Point {=|are|is} Value...
Type {=|are|is} CoordType
Vector {=|are|is} Value...

```

End

Summary Defines the local coordinate system parameters.

Description This Command Block allows the definition of a coordinate system that can be used to transform values for output or field calculations. For any specific local coordinate system three pieces of information are required for completely defining a coordinate system are the origin, a coordinate axis vector and a point lying on one of the other axes. Using this information a transformation from the local coordinate system to the computational coordinate system can be determined.

30.2.1. Origin

Scope: Local Coordinate System

```
Origin {=|are|is} Value...
```

Parameter	Value	Default
<i>Value</i>	<i>real...</i>	undefined

Summary Local coordinate system origin.

Description Specifies the point as the origin of a local coordinate system. The number of coordinates may be either 2 or 3 depending on the spatial dimension. By default, a value of $z=0.0$ is used for 2D.

30.2.2. Point

Scope: Local Coordinate System

```
Point {=|are|is} Value...
```

Parameter	Value	Default
<i>Value</i>	<i>real...</i>	undefined

Summary Local coordinate alternative point.

Description Declare the point that lies on an alternate axis and is in the plane subtended by the specified VECTOR and the vector defined by the point and the origin.

30.2.3. Type

Scope: Local Coordinate System

Type {=|are|is} *CoordType*

Parameter	Value	Default
<i>CoordType</i>	{cartesian conical cylindrical spherical}	undefined

Summary Local coordinate system type.

Description This line command selects the coordinate system type.

30.2.4. Vector

Scope: Local Coordinate System

Vector {=|are|is} *Value...*

Parameter	Value	Default
<i>Value</i>	real...	undefined

Summary Local coordinate axis vector.

Description Declare the vector that defines one of the coordinate axes. The specific usage depends on the selected coordinate system type.

30.2.5. Local Coordinate System

Scope:

Local Coordinate System {=|are|is} *Mesh Entities*

Parameter	Value	Default
<i>Mesh Entities</i>	string	undefined

Summary Associate coordinate system with mesh entity.

Description Specify the local coordinate system to be used in conjunction with given element blocks.

31. BULK VOLUME REFERENCE

31.1. BULK VOLUME ELEMENT



Beta Capability: The bulk volume capability is under active development hence the capability should be used with some caution.

For some engineering problems the variation of a field variable over the problem domain can be roughly represented by some average behavior. In these cases it may be more appropriate to understand the averaged behavior rather than to resolve the behavior in fine detail. When numerically modeling these types of problems, it is convenient to devise lumped parameter models that simulate this averaged behavior. One such modeling strategy, a bulk volume model, is employed to capture bulk fluid behavior without regard to spatial resolution. Herein the bulk volume model is described within the context of a Galerkin finite element model where the terms bulk volume element and bulk node are often used synonymously.

Following standard finite element method procedures, balance equations are written for a physical region surrounding the bulk volume where the equations possibly include contributions from unknowns associated with the bulk volume. Similarly a general conservation equation is written for a bulk volume system with flux contributions provided from bounding surfaces of the finite element method discretization [5](#). Under the assumption that the volume is known in a quasi-static sense, the spatial dependence is eliminated from equation terms containing temporal derivatives. The conservation equation for the bulk volume system is defined in the same manner as for other element blocks [6](#) except that it may be specified from a command block that specifically describes the bulk volume system. This balance relation provides closure for the discretized system of equations.

It is important to note that the bulk volume element interacts with the meshed model through boundary conditions and thus serves as an intervening media whose characterization has yet to be determined. Hence the methodology does not apply to problems in which the nature of interaction is known a priori. One example for which the interaction is known a priori would be convective heat transfer between two parallel surfaces of different fixed temperatures. Here heat transfer occurs directly between the two surfaces and need not be partitioned. In this case use of the bulk volume element would wrongfully introduce an additional resistance to flow of heat between the two surfaces.

Since the bulk volume degree-of-freedom is defined in terms of a time derivative, its transient evolution follows naturally. For steady problems not requiring solution converged parameter updates it is possible

to solve for the bulk volume degree-of-freedom directly. Otherwise the steady-state solution for bulk volume degree-of-freedom must be obtained using a false transient simulation.

Usage of the bulk volume capability is outlined below.

```
Begin Sierra myJob
.
Begin Aria Material a_bulk_volume
.
properties for bulk volume

End
.
Begin Procedure My_Aria_Procedure
.
Begin Solution Control Description
.
transient solution control commands
.
End
.
Begin Aria Region My_Region
.
Begin bulk volume bulk_volume_name
material = a_bulk_volume
EQ bulk_volume_name for bulk_volume_dof with P0 using mass
.
bulk volume specific definitions
.
End
.
other Region level commands
.
End
.
End
.
End Sierra myJob
```

31.1.1. Boundary Conditions

At present there are two supported methods for applying boundary conditions that couple equations on a bulk volume element to volumetric equations. For heat transfer problems where the energy equation is being solved for temperature on both the volume and the bulk volume element then either a

convective or a radiative boundary condition block can be coupled to the bulk volume element. For either type of boundary condition the "USE BULK ELEMENT" line command should be added to the input block, further details can be found in Chapter 33.

For other equations boundary conditions may be applied by using a line command of the form:

```
BC BULKNODE_FLUX FOR volume_equation ON surface_name = model_name BULK_NODE=bulk_node_
```

In some cases it is desirable to couple equations being solved for different degrees of freedom on the volume and the bulk volume element. For example coupling a porous media equation for the gas phase temperature on a volume block to an overall temperature on the bulk volume element, or an equation solved for enthalpy to an equation solved for temperature. If the same degree of freedom is not present on the bulk node and the volume then the following mappings are checked for:

- Same degree of freedom (e.g. temperature, pressure, mass fraction) but without a material phase specification on the bulk node when one is present on the volume block.
- Temperature degrees of freedom on the volume will check for enthalpy in either the same material phase or no material phase on the bulk node (and vice versa for an enthalpy degree of freedom on the volume). Additional mappings can be supported where they make sense, please email sierra-help@sandia.gov if you have such a use case.

If either no valid mapping or multiple valid mappings are found the simulation will terminate during initialization.

31.2. BULK FLUID ELEMENT

Scope: Equation System

Begin Bulk Fluid Element *Name*

Bulk Coordinates {=*|are|is*} *Parameters...*

Bulk Element Pressure {=*|are|is*} *VolType [Parameters]...*

Bulk Element Volume {=*|are|is*} *VolType [Parameters]...*

Bulk Eq *EquationName* For *AssociatedDoF* [{*of|species*} *SpeciesName*
| {*in|material_phase*} *MaterialPhaseName*]Using *ElementType* With
Terms...

Bulk Source For *EquationName* {=*|are|is*} *SrcType [Parameters]...*

Calculate Volume From Enclosing Surface

Initial Pressure {=*|are|is*} *p*

Initial Temperature {=*|are|is*} *t*

Material {=*|are|is*} *MatName*

```

Reinitialize Dof Name {=|are|is} value

Temperature Is Celsius

Update Bulk Volume Pressure [ Atmospheric {=|are|is} Value ]

Use Block BlockName

End

```

Summary Defines a bulk fluid element that can be used by a convective flux boundary condition.

Description Generally speaking, the reference temperature used in Newton's Law of Cooling and is a known quantity because the fluid with which it is associated is modeled as an infinite reservoir. However, if the size of this reservoir is finite, then its temperature can be affected by the energy transfer across the surface in question. This situation can be modeled by the bulk fluid element, wherein the energy of the reservoir is determined by a finite volume conservation equation.

For a bulk fluid element with a name specified as *name*, the thermodynamic properties such as density, volume and temperature may be accessed via global variables. Density is accessed using *name_RHO*, volume by *name_V*, temperature at the current state by *name_T* and temperature at the old state by *name_TOld*.

31.2.1. Bulk Coordinates

Scope: Bulk Fluid Element

```
Bulk Coordinates {=|are|is} Parameters...
```

Parameter	Value	Default
<i>Parameters</i>	real...	undefined

Summary Specifies the physical coordinates for the bulk node.

31.2.2. Bulk Element Pressure

Scope: Bulk Fluid Element

```
Bulk Element Pressure {=|are|is} VolType [Parameters]
```

Parameter	Value	Default
<i>VolType</i>	string	undefined
<i>Parameters</i>	[string]...	undefined

Summary Specifies the pressure of the bulk element with type Pressure Type (CONSTANT, USER) for bulk element defined by the specifications of the parameter list.

This command should not be used when the bulk element is associated with a pressurization zone model since initial pressure will instead be associated with the pressurization zone as a whole.

31.2.3. Bulk Element Volume

Scope: Bulk Fluid Element

Bulk Element Volume {=|are|is} *VolType* [*Parameters*]...

Parameter	Value	Default
<i>VolType</i>	string	undefined
<i>Parameters</i>	[string]...	undefined

Summary Specifies the volume of the bulk element with type VolType (CONSTANT, USER) for bulk element defined by the specifications of the parameter list.

For problems in which the mesh is deforming one should consider using CALCULATE VOLUME FROM ENCLOSING SURFACE instead.

31.2.4. Bulk Eq

Scope: Bulk Fluid Element

Bulk Eq *EquationName* For *AssociatedDoF* [{of|species} *SpeciesName* |{in|material_phase} *MaterialPhaseName*]Using *ElementType* With *Terms*...

Parameter	Value	Default
<i>EquationName</i>	string	undefined
<i>AssociatedDoF</i>	string	undefined
<i>SpeciesName</i>	string	undefined
<i>MaterialPhaseName</i>	string	undefined
<i>ElementType</i>	string	undefined
<i>Terms</i>	string...	undefined

Summary Specifies an equation to solve on the bulk node. User provides the degree of freedom associated with the equation, the element type, and the terms in the equation that are active.

31.2.5. Bulk Source For

Scope: Bulk Fluid Element

Bulk Source For *EquationName* {=|are|is} *SrcType* [*Parameters*]...

Parameter	Value	Default
<i>EquationName</i>	string	undefined
<i>SrcType</i>	string	undefined
<i>Parameters</i>	[string]...	undefined

Summary Indicates a source term of model type (i.e. CONSTANT, USER, CALORE_USER_SUB) and associated model Parameters for the given EquationName on the bulk element.

31.2.6. Calculate Volume From Enclosing Surface

Scope: Bulk Fluid Element

Summary Specifies that the volume of the bulk element is to be calculated at each timestep from an enclosing surface. The surface must be closed (although Aria currently does not currently check for this) and is defined by the extent of the flux boundary condition which uses this bulk element.

31.2.7. Initial Pressure

Scope: Bulk Fluid Element

Initial Pressure {=|are|is} *p*

Parameter	Value	Default
<i>p</i>	real	0.0

Summary Specifies the initial pressure of the bulk node.

This command should not be used when the bulk element is associated with a pressurization zone model since initial pressure will instead be associated with the pressurization zone as a whole.

31.2.8. Initial Temperature

Scope: Bulk Fluid Element

Initial Temperature {=*|are|is*} *t*

Parameter	Value	Default
<i>t</i>	real	REAL_MAX

Summary Specifies the initial temperature of the bulk node.

31.2.9. Material

Scope: Bulk Fluid Element

Material {=*|are|is*} *MatName*

Parameter	Value	Default
<i>MatName</i>	string	undefined

Summary Specifies that the material properties of the bulk element are defined in the material block named *matName*.

31.2.10. Reinitialize Dof

Scope: Bulk Fluid Element

Reinitialize Dof *Name* {=*|are|is*} *value*

Parameter	Value	Default
<i>Name</i>	string	undefined
<i>value</i>	real	undefined

Summary Requests reinitialization of a bulk node DOF. This will allow override of the file supplied bulk node DOF value when using an initial condition from file. Here the initial value supplied from file will be replaced by a specified value.

31.2.11. Temperature Is Celsius

Scope: Bulk Fluid Element

Summary Specifies the initial temperature of the bulk node is given in degrees Celsius. Internal to the code this is relevant only when performing updates of the bulk element pressure via an ideal gas law which requires an absolute temperature.

31.2.12. Update Bulk Volume Pressure

Scope: Bulk Fluid Element

Summary If a bulk volume is filled with an ideal gas then the pressure can be calculated at each timestep provided that the initial temperature and pressure are given. Here it is assumed that the associated volume is closed and that the volume has been defined as constant or is being computed. If the bulk volume is being computed then one must also include the CALCULATE VOLUME FROM ENCLOSING SURFACE command line.

This command should not be used when the bulk element is associated with a pressurization zone model since pressure is instead associated with the pressurization zone as a whole. The pressurization zone model also allows for gas models other than ideal gas.

31.2.13. Use Block

Scope: Bulk Fluid Element

Use Block *BlockName*

Parameter	Value	Default
<i>BlockName</i>	string	undefined

Summary Specifies that the given element block should be used for the bulk node. The caveat here is that there must be only one element, one node and they must all satisfy the proper mesh object topologies. This option is used only if an element block for the bulk element is already present in the mesh. If the bulk element does not exist on the input mesh, the element block will be created and will exist on the output mesh.

31.3. CLOSED SURFACE VOLUME

Scope: Equation System

```
Begin Closed Surface Volume ModelName
    Add Surface SurfaceList...
    Utility Group {=|are|is} Frequency
End
```

Summary This command block defines the parameters for computation of the volume of a closed surface. The computed volume is available as a global variable with name *modelName*.

Description Defines a means for computing the volume of a closed surface and associate it with name *modelName*.

31.3.1. Add Surface

Scope: Closed Surface Volume

Add Surface *SurfaceList...*

Parameter	Value	Default
<i>SurfaceList</i>	string...	undefined

Summary Adds surfaces by name, (*surface_id*), to a mesh extent list.

Description This line command is used to add surfaces to a mesh extent list. In Exodus II, surfaces are specified as side sets, that have a global integer identifier. For example, side set 12 would be added by this line command using the surface name *surface_12*. Note that in SIERRA, each element of an array of strings must be separated by whitespace.

31.3.2. Utility Group

Scope: Closed Surface Volume

Utility Group {=*|are|is*} *Frequency*

Parameter	Value	Default
<i>Frequency</i>	{begin_nonlinear_solve end_nonlinear_solve manually_run post_accept_solution post_iterate post_linear_solve post_nonlinear_solve pre_iterate pre_linear_solve pre_nonlinear_solve run_initially run_once run_post_linear_system_initialization run_post_mesh_mod}	undefined

Summary Sets the point in the execution to evaluate utility

31.4. RESTARTING WITH BULK VOLUME ELEMENT

The bulk volume element capability is supported for restarted simulations [3.10](#). It is worth noting that while bulk volume element is generally not part of the original mesh discretization the element is being created internal to the code and is also being added to the results file as well as the restart file if defined. In some cases one may wish to initialize a simulation from a previous restart file that does not contain the bulk volume element. In this case provision must be made to ignore the fact that the initialization does not include the bulk volume element so that the bulk volume element can be created anew.

Input for restart jobs subsequent to the bulk volume element being added to a model *should not* contain the BULK NODES IGNORE RESTART command line.

31.4.1. Bulk Nodes Ignore Restart

Scope:

Summary Causes bulk nodes to ignore the restart file.

31.5. BULK NODE COUPLING

Scope: Equation System

Begin Bulk Node Coupling *Name*

Additional Parameter *PropertyName* {=|are|is} *ModelName*
[*Parameters*]...

Bulk Nodes {=|are|is} *Names₁* *Names₂*...

Couple *DofName* Model {=|are|is} *ModelName* [*Parameters*]...

End

Summary Defines a coupling between equations on two bulk nodes.

Description This block command allows a user to couple equations on different bulk nodes to one another. For example, the density of gas on two bulk nodes can be coupled using a flow coefficient based on the relative pressure of the two bulk nodes. The same degree of freedom must be present on both bulk nodes, and both have to be in the same equation system in order for the coupling to be possible.

31.5.1. Additional Parameter

Scope: Bulk Node Coupling

Additional Parameter *PropertyName* {=|are|is} *ModelName* [*Parameters*]...

Parameter	Value	Default
<i>PropertyName</i>	string	undefined
<i>ModelName</i>	string	undefined
<i>Parameters</i>	[string]...	undefined

Summary Declare an additional parameter for the coupling models present. For example, the "K_FACTOR_FLOW" model for density or species coupling requires that a "K_FACTOR" be provided using this line command.

31.5.2. Bulk Nodes

Scope: Bulk Node Coupling

Bulk Nodes {=|are|is} *Names₁ Names₂...*

Parameter	Value	Default
<i>Names</i>	string_1 string_2...	undefined

Summary Specify the name of the bulk nodes involved in the coupling.

31.5.3. Couple

Scope: Bulk Node Coupling

Couple *DofName* Model {=|are|is} *ModelName* [*Parameters*]...

Parameter	Value	Default
<i>DofName</i>	string	undefined
<i>ModelName</i>	string	undefined
<i>Parameters</i>	[string]...	undefined

Summary Specify what degree of freedom to couple between the bulk nodes, and what model to use for the coupling.

32. TOGGLE REFERENCE

32.1. FEATURE TOGGING

For transient analysis Aria provides a mechanism for enabling and disabling certain aspects of a model like boundary conditions, contact conditions, source contributions and element block physics during selected time periods. This option is useful when modeling a time sequence of discontinuous events and the capability will be subsequently referred to as "toggling". Toggling as applied to simple electric switches means that one either opens or closes the switch (i.e. the switch is on or off). Similarly, from an analysis perspective one simply defines a specific model feature to be either active or inactive. Toggling does not imply the ability to swap in another physics model or to apply different model parameters.

Generally speaking the use of toggling is justified when a change in model physics will result in a change to the structure of the system matrix or to the structure of linear system contributions. For example, change of a flux boundary condition to a Dirichlet boundary condition requires a change to the structure of the matrix contribution since unknown values are now specified and need not be computed. Similarly, deactivation of a element block will remove degrees-of-freedom (rows and columns) from the Jacobian matrix thus reducing the number of system unknowns. Note that a change of flux boundary condition input parameters (e.g. the convective coefficient) will modify the system matrix coefficients but not affect the structure of the associated linear system matrix contributions so feature toggling is not justified in this case. Instead parameter changes in time should be accounted for through the parameter model definition.

In order to invoke this option one needs to consider its possible effect on results. Toggling of a model feature makes its usage take on a different character than expected for standard use. In particular, invocation of toggling for a simulation feature requires that the analyst prescribe the active/inactive state of the feature for the time periods of interest. Syntactically speaking the definition of feature toggling consists of two parts, the toggle block and selection of its usage.

The active/inactive state history of a feature is defined using a TOGGLE BLOCK command block. Within the Aria input file the TOGGLE BLOCK command block appears outside of the application scope, i.e. outside of the Procedure definition. Here the time period aspect of this specification is handled by mapping the desired state to a time block of the simulation. On the other hand specific usage of the toggle feature will appear within the Region scope.

For boundary conditions, contact conditions and source contributions the association between a particular model feature is prescribed by referencing the named TOGGLE BLOCK in the definition of a model feature. For native Aria model feature toggling the association with a named TOGGLE BLOCK is made by supplying an argument *toggle = toggle_block_name* to the feature (IC, BC or Source term) command line. To define toggling with Calore style input command blocks [33.1](#) the association

between a model feature is prescribed by including a USE TOGGLE BLOCK command line within that command block.

For element block toggling (toggling of all element block physics), the association between the block and a named TOGGLE BLOCK is established via a standalone USE TOGGLE BLOCK command line within the Region scope. For toggling of the element block associated with a bulk fluid element [31.1](#) we note that the corresponding element block name is `BLOCK_FOR_bulk_element_name`.

Toggling is supported for flux boundary conditions, contact conditions and source terms by simply zeroing out their contributions. Thus the number of DOF in the linear system will not change.

Toggling of Dirichlet boundary conditions and element blocks is currently supported by removing the element DOF from the linear system.

Oftentimes one may wish to toggle off a surface boundary condition and toggle on a variant of the same boundary condition. As an example, one might replace a convective flux boundary condition with constant reference temperature with one having a reference temperature defined by a tabular function. Since the original boundary condition still exists (but it's toggled off) it will conflict with the new boundary condition. Cases such as this will require that the second boundary condition be applied to a different surface (differently named) that overlies the surface used in the original boundary condition in order to resolve this conflict.

Toggling has been proven to be unsupported for material properties or enclosure definitions.

Usage of toggling is demonstrated in the outline below where we note that the time period within the TOGGLE BLOCK corresponds to one of the time periods defined within the Solution Control [14](#) command block.

```
Begin Sierra myJob
.
Begin Toggle Block first_toggle
  period = a_time_period_2
  state = active
End
.
Begin Toggle Block second_toggle
  period = a_time_period_3
  state = inactive
End
.
Begin Procedure My_Aria_Procedure
.
  Begin Solution Control Description
    Use system main
    Begin system main
      Simulation start time = 0.0
      Simulation termination time = 3600.0
```

```

    Begin transient a_time_period_1
      advance My_Region
    End
    Begin transient a_time_period_2
      advance My_Region
    End
    Begin transient a_time_period_3
      advance My_Region
    End
  End

  Begin parameters for transient a_time_period_2
    start time = 0.0
    termination time = 2.0
    Begin parameters for Aria region My_Region
      .
    End parameters for Aria region My_Region
  End parameters for transient a_time_period_2

  Begin parameters for transient a_time_period_2
    start time = 2.0
    termination time = 5.0
    Begin parameters for Aria region My_Region
      .
    End parameters for Aria region My_Region
  End parameters for transient a_time_period_2

End

.
Begin Aria Region My_Region
.
Use toggle block first_toggle for block_8
.
Begin command block ablock
.
  Use toggle block second_toggle
End
.
End

.
End

.
End Sierra myJob

```

Note that if one wishes to replace a boundary condition (the physics model) then one can do so by first

adding a duplicate surface mesh entity and adding a new toggle block corresponding to usage of the new physics model.

It is important to note that within a TOGGLE BLOCK only one event (active or inactive) can be specified for the selected time period(s). Time periods other than the ones specified within the TOGGLE BLOCK command block will assume the opposite character (active/inactive). With reference to the previous outline this behavior is demonstrated by simple examples.

For the following toggle block

```
Begin Toggle Block my_toggle
  period = a_time_period_2
  state = active
End
```

a feature is active for a_time_period_2 and inactive for a_time_period_1 and a_time_period_3. Similarly the same behavior could be obtained using

```
Begin Toggle Block my_toggle
  period = a_time_period_1 a_time_period_3
  state = inactive
End
```

32.2. TOGGLE BLOCK

Scope: Sierra

```
Begin Toggle Block modelName

  Freeze Element Block Solution State

  Period {=|are|is} Period_list...

  State {=|are|is} ToggleState

End
```

Summary This command block defines the period(s), state and initial conditions for model feature toggling.

Description Defines a generic entity toggling specification and associate it with name *modelName*. The same *modelName* can be used for various model features such as element blocks, boundary conditions, contact and volumetric sources.

32.2.1. Freeze Element Block Solution State

Scope: Toggle Block

Summary Specify that the solution state remain the same when an element block has been toggled on.

Description Specifies that the initial condition is not reset on any associated element block that has been toggled. The default behavior is to have the initial conditions reset on element blocks that have been toggled back on.

32.2.2. Period

Scope: Toggle Block

Period {=|are|is} *Period_list...*

Parameter	Value	Default
<i>Period_list</i>	string...	undefined

Summary Specify the periods over which this toggling model is to be used.

Description Defines the time periods over which this toggling model is to be used. Note that more than one PERIOD can be appear in the command block.

32.2.3. State

Scope: Toggle Block

State {=|are|is} *ToggleState*

Parameter	Value	Default
<i>ToggleState</i>	{active inactive}	undefined

Summary Specify the state for this toggling model over the periods it is to be used.

Description Defines the toggle state for the time periods over which this toggling model is to be used. Note that more than one STATE can be appear in the command block.

32.2.4. Use Toggle Block

Scope:

```
Use Toggle Block ToggleName [ {@|at|for|in|on|over} ElementBlockList...
]
```

Parameter	Value	Default
<i>ToggleName</i>	string	undefined

Summary Specification for toggling entities in the computational model based on Toggle Block parameters. When used at the region level, the list of element blocks to be toggled must be provided. Otherwise a listing of entities is not needed as the Toggle Block will be associated with the command line or the enclosing command block.

33. THERMAL ANALYSIS REFERENCE

33.1. GENERAL THERMAL ANALYSIS

Aria supports the solution of the energy equation for temperature as described in an earlier section [5.3](#), following the paradigm of native Aria input. Here a user can also utilize any of the standard Aria input commands previously described in the initial conditions Chapter [8](#), boundary conditions Chapter [9](#) and volumetric source terms Chapter [11](#).

Previous users of the Calore code will find that many of the general input file commands for initial conditions, boundary conditions and volume sources are in fact recognized by Aria. However, there exist major differences between the two code inputs with regard to the material property definitions. Users transitioning from the Calore to Aria should review the chapter on Aria Material properties [4](#). While most of the property specifications differ only slightly, the most striking difference between the two command blocks is that the Aria material input requires an additional command line definition of a heat conduction model [4.15](#).

The Calore and Aria code inputs also differ slightly in the nonlinear solution strategy. Generally speaking, a solution step in Aria cannot be advanced until the linear system is fully converged whereas in Calore the solution need not be converged for the step to advance. Calore and Aria also differ in the method of residual norm evaluation. Here Calore uses a residual norm scaled by the DOF whereas Aria uses an unscaled residual norm. Provisions are made in Aria to mimic the Calore code in the aforementioned behavior by use of additional input instructions, `ACCEPT SOLUTION AFTER MAXIMUM NONLINEAR ITERATIONS` and `USE DOF AVERAGED NONLINEAR RESIDUAL` described in a section on nonlinear solution specification [17.3](#).

Aria also provides support of user subroutines for initial condition, volumetric source, boundary condition or material property. When a user subroutine is named within a standard thermal analysis command block it must be referred to as a `Calore_User_Sub`. Usage of input file data within these user subroutines is facilitated by use of named Data Blocks that can be made available to the user subroutines. These Data Blocks fill the role formerly occupied by `Real` and `Int` command lines in the Calore.

As previously mentioned, one may setup the solution of a thermal problem using either Calore style input commands or native Aria input commands. It is worth noting that when using the native Aria commands for heat flux, the sign convention for heat flux in the boundary condition commands for constant flux [9.2.1](#) and `user_function` flux [9.2.35](#) differs from that in the Calore style of heat flux in that they are of opposite sign.

Aria supports a number of non-native (Calore style) command line blocks to facilitate definition of the thermal problem to be solved. These command blocks are defined in the sections which follow. Here input specification on portions of the FEM mesh can be simplified by aggregation of the parts into Mesh Groups [6.26](#).

33.2. CHECKING CONSERVATION

Aria has a builtin energy conservation check that can be activated for the energy equation. This is accomplished by adding the following line to whatever block you specify the energy equation in (either an Equation System block or the Region block):

```
Check Conservation of Energy
```

When this is active, after each time step the accumulated internal energy is compared with the energy added from all boundaries and sources and the level of conservation is printed in the log file.

This is a conservation check targeted towards conduction problems. The balance calculations do not currently include advection or divergence sources and will not be accurate for compressible fluids or domains with advection at the boundaries.

33.3. NON-PHYSICAL TEMPERATURE SOLUTIONS

The conservation of energy equation in its continuous form (and in the absence of source terms) satisfies a maximum principle. That is, for a steady-state problem the maximum and minimum temperatures in the domain must occur on the boundary of the domain, and for a transient problem on either the boundary or the initial condition. However, the discretized form of the energy equation does not necessarily satisfy a discrete version of the maximum principle (DMP). In particular for the standard Galerkin finite element method used in Aria there are conditions on the mesh quality that must be met for the diffusion operator to satisfy a DMP. For linear tetrahedral elements the condition is that there are no obtuse dihedral angles between faces of elements in the mesh [\[37\]](#). Anisotropic thermal conductivity can also contribute to this effect [\[38\]](#). Additionally, the consistent mass term can also lead to DMP violations in transient problems [\[39\]](#). In practice this can lead to non-physical temperatures appearing in the solutions generated by Aria, most commonly when large heat fluxes are applied to an initially cold domain with a low thermal conductivity.

If non-physical temperature solutions are observed Aria supports an option to apply a nonlinear flux correction based on the work of Kuzmin et al. that restores a DMP on arbitrary meshes with arbitrary material properties [\[39, 40\]](#). This option may be activated by using the "APPLY FLUX LIMITER STABILIZATION" line command, [4.1.1](#). For transient problems it is also essential to use the LUMPED_MASS form of the time derivative term. At present, this option is only intended for use with linear elements, not second order 10 node tetrahedral elements or 27 node hexahedral elements. Source terms also do not have any limiters applied to them at present, as a result they may still cause non-physical temperatures in some cases.

Additionally, applying the stabilization has several downsides so that we only recommend enabling it if problematic non-physical temperatures are observed without it. Solutions with the stabilization activated are more diffusive and have higher error than unstabilized solutions (though they do converge at the same order with mesh refinement). The stabilization operator is also nonlinear and can adversely affect the convergence of the Newton-Raphson iteration within each time step. Combined with the cost of calculating the stabilization terms this can have noticeable impact on simulation runtime.

33.4. INITIAL CONDITION

Scope: Aria Region

```
Begin Initial Condition BlockName
```

```
    Add Surface PartList...
```

```
    Add Volume PartList...
```

```
    All Volumes
```

```
    Node Subroutine {=|are|is} Name
```

```
    Temperature {=|are|is} t0
```

```
    Use Data Block Name
```

```
    Use File Variable File_variable_name For Aria_variable_name [ {of|
species} SpeciesName |{in|material_phase} MaterialPhaseName ][ At
Time Value ]
```

```
End
```

Summary Allows the specification of a user-defined initial conditions on any combination of volumes, surfaces and nodes.

Description There are three methods for setting the initial conditions of the thermal model. The temperature specification must be of exactly one type: e.g., constant, defined in a user subroutine, or read from a solution database file. If a user subroutine is used, real and integer data may be declared that will be local in scope to this instance of the boundary condition. This data may be accessed using a user query function.

33.4.1. Add Surface

Scope: Initial Condition

Add Surface *PartList...*

Parameter	Value	Default
<i>PartList</i>	string...	undefined

Summary Surface name to which this initial condition applies. May specify a space-delimited list.

33.4.2. Add Volume

Scope: Initial Condition

Add Volume *PartList...*

Parameter	Value	Default
<i>PartList</i>	string...	undefined

Summary Block names to which this initial condition applies. May specify a space-delimited list.

33.4.3. All Volumes

Scope: Initial Condition

Summary Apply this command block to all volumes in the mesh file.

33.4.4. Node Subroutine

Scope: Initial Condition

Node Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies that the named user-defined subroutine be used. At most one subroutine name may be specified for a given quantity. This subroutine must conform to the "node signature" argument list type.

33.4.5. Temperature

Scope: Initial Condition

Temperature {=|are|is} *t0*

Parameter	Value	Default
<i>t0</i>	real	undefined

Summary Set the initial temperature to a constant value.

33.4.6. Use Data Block

Scope: Initial Condition

Use Data Block *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Reference to predefined data to be used by the user subroutine. These values may be changed by the user subroutine.

33.4.7. Use File Variable

Scope: Initial Condition

Use File Variable *File_variable_name* For *Aria_variable_name* [{of|species} *SpeciesName* |{in|material_phase} *MaterialPhaseName*][At Time *Value*]

Parameter	Value	Default
<i>File_variable_name</i>	string	undefined
<i>Aria_variable_name</i>	string	undefined
<i>SpeciesName</i>	string	undefined
<i>MaterialPhaseName</i>	string	undefined

Summary Assign file nodal variable to valid registered nodal variable for initial condition.

Description This line command specifies that the named Aria variable be initialized from a variable contained in the mesh file that is assigned to the region. For example, this line command may be used to initialize a transient calculation from a previously performed steady-state calculation in the following way. Perform the steady-state calculation and output the temperature. Then copy that output file and use it as a mesh file for the transient calculation. Finally, use this line command to tie the variable named "file_variable_name" in the mesh file to the aria variable named "aria_variable_name". Here "aria_variable_name" must be set to nonlinear_solution->temperature.

The closest time step to the time value found the IO database will be used for the assignment. For an initial condition taken from a steady state results file, omit the

optional time command. The optional command is necessary if the initial condition is coming from a file with multiple timesteps.

NOTES: 1) Current framework services do not allow restricting this initialization by mesh subset. e.g., if you want to initialize the temperature, then all nodes in the mesh will be initialized. 2) This command line syntax only supports initialization of temperature field. This restriction may be removed in the future so that chemistry variables or user-defined variables may also be initialized. 3) Sierra Mechanics uses a DOF naming convention which distinguishes vector fields from scalar fields using an underscore plus component notation (e.g. `field_variable_base_name_I`, `field_variable_base_name_X`). Hence use of external scalar field variable names that include an indexed notation will require that the file variable be renamed in order to be processed correctly as a scalar field in the IC READ_FILE setup.

33.5. TEMPERATURE BOUNDARY CONDITION

Scope: Equation System

```
Begin Temperature Boundary Condition BC name
  Add Surface SurfaceList...
  Field {=|are|is} VariableName
  Integer Data Values...
  Node Subroutine {=|are|is} Name
  Real Data Values...
  Temperature {=|are|is} Value
  Temperature Fortran Subroutine {=|are|is} Name
  Temperature Node Variable {=|are|is} Name
  Temperature Scale Factor {=|are|is} Magnitude
  Temperature Time Function {=|are|is} FunctionName
  Use Data Block Name
  Use Death Name
  Use Toggle Block ToggleName [ {@|at|for|in|on|over}
    ElementBlockList... ]
  Value {=|are|is} VariableValue
End
```

Summary Specified temperature boundary condition.

Description For this boundary condition, the conservation equations are discarded, and the temperature is completely determined by this boundary condition. The temperature specification must be of exactly one type: e.g., constant, time-dependent, or defined in a user subroutine. If a user subroutine is used, real and integer data may be declared that will be local in scope to this instance of the boundary condition. This data may be accessed using a user query function.

33.5.1. Add Surface

Scope: Temperature Boundary Condition

Add Surface *SurfaceList...*

Parameter	Value	Default
<i>SurfaceList</i>	string...	undefined

Summary Adds surfaces, by name, to a boundary condition's extent.

Description This line command is used to add surfaces to the extent of a boundary condition. In Exodus II, surfaces are specified as side sets, that have a global integer identifier. For example, side set 12 would be added by this line command using the surface name `surface_12`. Note that in SIERRA, each element of an array of strings must be separated by whitespace.

33.5.2. Field

Scope: Temperature Boundary Condition

Field {=|are|is} *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary This command can be used with Dirichlet conditions for any solution unknown used in Aria. The FIELD command argument defines the name of the variable to be specified with this boundary condition.

33.5.3. Integer Data

Scope: Temperature Boundary Condition

Integer Data *Values...*

Parameter	Value	Default
<i>Values</i>	integer...	undefined

Summary List of integer data values to be used by the FORTRAN user subroutine. Copies of these values are provided to the subroutine hence changes to these values within the subroutine are not saved.

33.5.4. Node Subroutine

Scope: Temperature Boundary Condition

Node Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies that the named user-defined subroutine be used. At most one subroutine name may be specified for a given quantity. This subroutine must conform to the "node signature" argument list type.

33.5.5. Real Data

Scope: Temperature Boundary Condition

Real Data *Values...*

Parameter	Value	Default
<i>Values</i>	real...	undefined

Summary List of real data values to be used by the FORTRAN user subroutine. Copies of these values are provided to the subroutine hence changes to these values within the subroutine are not saved.

33.5.6. Temperature

Scope: Temperature Boundary Condition

Temperature {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specify the constant value of the temperature. Using this command is equivalent to using both the FIELD = temperature and VALUE = real_value command lines.

33.5.7. Temperature Fortran Subroutine

Scope: Temperature Boundary Condition

Temperature Fortran Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of a FORTRAN user subroutine that will be used to calculate the nodal temperature boundary condition.

33.5.8. Temperature Node Variable

Scope: Temperature Boundary Condition

Temperature Node Variable {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of the node variable to use for the temperature associated with this boundary condition.

Description The indicated node variable must be a legal Aria variable. This variable is defined from the input file in the USER VARIABLE command block or with the USER FIELD command. Two distinct use cases may arise, 1) the variable is calculated in another SIERRA region, e.g., Fuego, and transferred to Aria 2) the variable exists in the input grid file and is populated using the READ VARIABLE command from within the USER FIELD command block.

33.5.9. Temperature Scale Factor

Scope: Temperature Boundary Condition

Temperature Scale Factor {=|are|is} *Magnitude*

Parameter	Value	Default
<i>Magnitude</i>	real	undefined

Summary Specifies the magnitude by which the distribution factors will be multiplied in order to determine the boundary condition. If this line command is used, node distribution factors must be defined in the input mesh for all nodesets which are associated with this boundary condition.

Description If this line command is used, node distribution factors must be defined in the input mesh for all nodesets which are associated with this boundary condition. There is currently an inconsistency with respect to temperature boundary conditions and distribution factors: It is not legal to specify sideset distribution factors with the temperature boundary condition: nodesets must be used. Distribution factors also do not work with h-adaptivity, as their values are not currently interpolated to the new nodes. In any case, for temperature boundary conditions, in order for this interpolation to occur, then a sideset would have to be used, which is not supported at this time.

33.5.10. Temperature Time Function

Scope: Temperature Boundary Condition

Temperature Time Function {=|are|is} *FunctionName*

Parameter	Value	Default
<i>FunctionName</i>	string	undefined

Summary Name of the time-dependent function that specifies the temperature.

33.5.11. Use Data Block

Scope: Temperature Boundary Condition

Use Data Block *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Reference to predefined data to be used by the user subroutine. These values may be changed by the user subroutine.

33.5.12. Use Death

Scope: Temperature Boundary Condition

Use Death *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Associates this boundary condition with element faces that are created as a result of element death due to the specified element death command block. Note that this line command makes the owning boundary condition have a dynamic extent that changes as elements die.

Description This line command specifies that the faces that are created as a result of the element death criterion in the named element death command block are added to the extent of this boundary condition. A boundary condition may specify an extent via the "add surface" line command, or the "use death" line command. In this way it is possible to have a boundary condition that is initially empty and then grows dynamically with the surface created as a result of the element death. At least one of these methods must be used.

A boundary condition may be associated with more than one death command block by including this line command more than once. However, to avoid issues of precedence, there is a rule that a given element may not die for more than one reason.

33.5.13. Use Toggle Block

Scope: Temperature Boundary Condition

Use Toggle Block *ToggleName* [{*@*|*at*|*for*|*in*|*on*|*over*} *ElementBlockList...*]

Parameter	Value	Default
<i>ToggleName</i>	string	undefined

Summary Specification for toggling entities in the computational model based on Toggle Block parameters. When used at the region level, the list of element blocks to be toggled must be provided. Otherwise a listing of entities is not needed as the Toggle Block will be associated with the command line or the enclosing command block.

33.5.14. Value

Scope: Temperature Boundary Condition

Value {*=*|*are*|*is*} *VariableValue*

Parameter	Value	Default
<i>VariableValue</i>	string	undefined

Summary This command is used in conjunction with the FIELD command. A constant value of the variable given in the FIELD command is specified with this boundary condition.

33.6. HEAT FLUX BOUNDARY CONDITION

Scope: Equation System

Begin Heat Flux Boundary Condition *Name*

Add Surface *SurfaceList...*

Element Subroutine {*=*|*are*|*is*} *Name*

Equation {=|are|is} *EquationName*

Field Scaling {=|are|is} *Scale_factor*

Flux {=|are|is} *Value*

Flux Encore Function {=|are|is} *Name*

Flux Fortran Subroutine {=|are|is} *Name*

Flux Node Variable {=|are|is} *Name* [*Multiplier* {=|are|is} *Value*]

Flux Scale Factor {=|are|is} *Value*

Flux Temperature Function {=|are|is} *Namep*

Flux Time Function {=|are|is} *Name*

Flux Vector Node Variable {=|are|is} *Name* [*Multiplier* {=|are|is} *Value*]

Ignore Flux Coverage

Influx Vector Node Variable {=|are|is} *Name* [*Multiplier* {=|are|is} *Value*]

Integer Data *Values...*

Integrated Flux Output *VariableName*

Integrated Power Output *VariableName*

Real Data *Values...*

Scaling Time Function {=|are|is} *Function*

Scaling With Global Variable {=|are|is} *name*

Use Data Block *Name*

Use Toggle Block *ToggleName* [{@|at|for|in|on|over} *ElementBlockList...*]

End

Summary This command block specifies that a known heat flux is to be applied normal to the given surface.

Description The flux can vary in arbitrary way, e.g. it may be a specified constant, a function of temperature, time etc. You may only specify one kind of flux e.g it is not legal to specify a constant value and a time dependent function. If you want to add two such fluxes on a single surface, then either write a user subroutine or use two different command blocks. If a function name is given then the function must be defined in a function definition command block.

33.6.1. Add Surface

Scope: Heat Flux Boundary Condition

Add Surface *SurfaceList*...

Parameter	Value	Default
<i>SurfaceList</i>	string...	undefined

Summary Adds surfaces, by name, to a boundary condition's extent.

Description This line command is used to add surfaces to the extent of a boundary condition. In Exodus II, surfaces are specified as side sets, that have a global integer identifier. For example, side set i2 would be added by this line command using the surface name *surface_i2*. Note that in SIERRA, each element of an array of strings must be separated by whitespace.

33.6.2. Element Subroutine

Scope: Heat Flux Boundary Condition

Element Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies that the named user-defined subroutine be used. At most one subroutine name may be specified for a given quantity. This subroutine must conform to the "element signature" argument list type.

33.6.3. Equation

Scope: Heat Flux Boundary Condition

Equation {=|are|is} *EquationName*

Parameter	Value	Default
<i>EquationName</i>	string	undefined

Summary This command can be used to apply the Heat Flux conditions for an equation other than the ENERGY equation.

33.6.4. Field Scaling

Scope: Heat Flux Boundary Condition

Field Scaling {=*|are|is*} *Scale_factor*

Parameter	Value	Default
<i>Scale_factor</i>	real	undefined

Summary This command is only relevant when the FLUX NODE VARIABLE, FLUX VECTOR NODE VARIABLE or INFLUX VECTOR NODE VARIABLE command line option is present. The command enables scaling of the Field by a single value for the surfaces defined within the scope of the current Heat Flux command block. For vector Fields all components will be scaled by the provided value.

33.6.5. Flux

Scope: Heat Flux Boundary Condition

Flux {=*|are|is*} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary This line command specifies a constant value of heat flux.

33.6.6. Flux Encore Function

Scope: Heat Flux Boundary Condition

Flux Encore Function {=*|are|is*} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of an Encore function that will be used to calculate the flux boundary condition. Note that the sign convention for flux into the domain requires that the Encore function be negatively signed.

33.6.7. Flux Fortran Subroutine

Scope: Heat Flux Boundary Condition

Flux Fortran Subroutine {=*|are|is*} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of a FORTRAN user subroutine that will be used to calculate the flux boundary condition.

33.6.8. Flux Node Variable

Scope: Heat Flux Boundary Condition

Flux Node Variable {=*|are|is*} *Name* [*Multiplier* {=*|are|is*} *Value*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of the node variable to use for the flux that is associated with this boundary condition. Here the node variable is assumed to be the product of the surface unit normal vector with the nodal heat flux. Optionally, the value can be scaled by product of Multiplier value and FIELD SCALING.

Description The indicated node variable must be a legal Aria variable. In most cases this variable is defined by the user in the user variable definition command block. The node variable is interpolated to the quadrature points during the evaluation of flux term contributions. If need be, both the sign and magnitude of the node variable can be modified by using the FIELD SCALING command line. Typically, the node variable would be calculated in another SIERRA region, e.g., Fuego, and transferred to Aria.

33.6.9. Flux Scale Factor

Scope: Heat Flux Boundary Condition

Flux Scale Factor {=*|are|is*} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specifies the magnitude by which the distribution factors will be multiplied in order to determine the boundary condition. If this line command is used, sideset distribution factors must be defined in the input mesh for all surfaces which are associated with this boundary condition.

Description The flux on each face is computed by interpolating the distribution factors to the Gauss points and then multiplying the result by the given magnitude. Distribution factors do not currently work with h-adaptivity, since their values are not currently interpolated to the new nodes.

33.6.10. Flux Temperature Function

Scope: Heat Flux Boundary Condition

Flux Temperature Function {=*|are|is*} *Namep*

Parameter	Value	Default
<i>Namep</i>	string	undefined

Summary Specifies the name of a temperature dependent heat flux function that is used to calculate the normal flux.

33.6.11. Flux Time Function

Scope: Heat Flux Boundary Condition

Flux Time Function {=*|are|is*} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies the name of a time dependent heat flux function that is used to calculate the normal flux.

33.6.12. Flux Vector Node Variable

Scope: Heat Flux Boundary Condition

Flux Vector Node Variable {=*|are|is*} *Name* [*Multiplier* {=*|are|is*} *Value*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of the vector node variable to use for the flux that is associated with this boundary condition. Here the flux contribution for a surface will be evaluated by forming a dot product of the unit normal vector with the vector node variable, without regard to the sign of the dot product. Optionally, the vector values can be scaled by product of Multiplier value and FIELD SCALING.

Description The indicated node variable must be a legal Aria vector variable. In most cases this variable is defined by the user in the user variable definition command block. The node variable is interpolated to the quadrature points during the evaluation of flux term contributions. If need be, both the sign and magnitude of the node variable can be modified by using the FIELD SCALING command line. Typically, the vector node variable would be calculated in another SIERRA region, e.g., Fuego, and transferred to Aria.

33.6.13. Ignore Flux Coverage

Scope: Heat Flux Boundary Condition

Summary This command causes the code to ignore the flux coverage Field when contact is present. Thus the flux will be applied even if the BC is being set on a contact surface.

33.6.14. Influx Vector Node Variable

Scope: Heat Flux Boundary Condition

Influx Vector Node Variable {=|are|is} *Name* [*Multiplier* {=|are|is} *Value*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of the node variable to use for the flux that is associated with this boundary condition. Here the applied flux will be formed by the dot product of the surface unit normal vector with the nodal variable which produce an influx contribution. Optionally, the value can be scaled by product of Multiplier value and FIELD SCALING.

Description The indicated node variable must be a legal Aria variable. In most cases this variable is defined by the user in the User Variable definition command block. The node variable is interpolated to the quadrature points during the evaluation of flux term contributions. If need be, both the sign and magnitude of the node variable can be modified by using the FIELD SCALING command line. Typically, the node variable would be calculated in another SIERRA region, e.g., Fuego, and transferred to Aria.

33.6.15. Integer Data

Scope: Heat Flux Boundary Condition

Integer Data *Values...*

Parameter	Value	Default
<i>Values</i>	integer...	undefined

Summary List of integer data values to be used by the FORTRAN user subroutine. Copies of these values are provided to the subroutine hence changes to these values within the subroutine are not saved.

33.6.16. Integrated Flux Output

Scope: Heat Flux Boundary Condition

Integrated Flux Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Calculate the average flux associated with this flux boundary condition.

Description This line command specifies that, as a postprocess, the normal flux associated with this boundary condition be integrated over the surface to obtain the total power. This power is then divided by the total area of the surface to obtain the average flux on the surface, and stored in a global variable named "variableName". This global variable may then be output to history files, or accessed in user subroutines, etc.

33.6.17. Integrated Power Output

Scope: Heat Flux Boundary Condition

Integrated Power Output <i>VariableName</i>		
Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Calculate the total power associated with this flux boundary condition.

Description This line command specifies that, as a postprocess, the normal flux associated with this boundary condition be integrated over the surface to obtain the total power which is then stored into a global variable named "variableName". This global variable may then be output to history files, or accessed in user subroutines, etc.

33.6.18. Real Data

Scope: Heat Flux Boundary Condition

Real Data <i>Values...</i>		
Parameter	Value	Default
<i>Values</i>	real...	undefined

Summary List of real data values to be used by the FORTRAN user subroutine. Copies of these values are provided to the subroutine hence changes to these values within the subroutine are not saved.

33.6.19. Scaling Time Function

Scope: Heat Flux Boundary Condition

Scaling Time Function {= are is} <i>Function</i>		
Parameter	Value	Default
<i>Function</i>	string	undefined

Summary This command is only relevant when the FLUX NODE VARIABLE, FLUX VECTOR NODE VARIABLE or INFLUX VECTOR NODE VARIABLE command line option is present. This command enables time function scaling of the field variable for the surfaces defined within the scope of the current Heat Flux command block.

33.6.20. Scaling With Global Variable

Scope: Heat Flux Boundary Condition

Scaling With Global Variable {=|are|is} *name*

Parameter	Value	Default
<i>name</i>	string	undefined

Summary This command is only relevant when the FLUX NODE VARIABLE, FLUX VECTOR NODE VARIABLE or INFLUX VECTOR NODE VARIABLE command line option is present. The command enables scaling of the Field by a global variable for the surfaces defined within the Heat Flux command block. For vector Fields all components will be scaled by the named scalar global variable. The scalar global variable itself must be defined at the Region scope as type Real with length 1.

33.6.21. Use Data Block

Scope: Heat Flux Boundary Condition

Use Data Block *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Reference to predefined data to be used by the user subroutine. These values may be changed by the user subroutine.

33.6.22. Use Toggle Block

Scope: Heat Flux Boundary Condition

Use Toggle Block *ToggleName* [{@|at|for|in|on|over} *ElementBlockList...*]

Parameter	Value	Default
<i>ToggleName</i>	string	undefined

Summary Specification for toggling entities in the computational model based on Toggle Block parameters. When used at the region level, the list of element blocks to be toggled must be provided. Otherwise a listing of entities is not needed as the Toggle Block will be associated with the command line or the enclosing command block.

33.7. LASER HEAT FLUX BOUNDARY CONDITION

Scope: Equation System

Begin Laser Heat Flux Boundary Condition *Name*

Absorption Coefficient {=*|are|is*} *value*

Absorption Coefficient Data File {=*|are|is*} *Filename*

Add Surface *SurfaceList...*

Angular Velocity {=*|are|is*} *value*

Beam Diameter {=*|are|is*} *laser_diameter*

Beam Radius {=*|are|is*} *value*

Circular Path Center {=*|are|is*} *Point...*

Circular Path Start Vector {=*|are|is*} *Value...*

Compute Visibility Field {=*|are|is*} *FieldName*

Effective Beam Radius {=*|are|is*} *value*

Element Subroutine {=*|are|is*} *Name*

Flux {=*|are|is*} *Value*

Flux Fortran Subroutine {=*|are|is*} *Name*

Flux Type {=*|are|is*} *LaserDistributionType*

Integer Data *Values...*

Integrated Flux Output *VariableName*

Integrated Power Output *VariableName*

Max Degrees {=*|are|is*} *value*

Path Function {=*|are|is*} *Function*

Path Radius {=*|are|is*} *value*

Power {=*|are|is*} *laser_power*

Power Encore Function {=*|are|is*} *Function*

Power Time Function {=*|are|is*} *Function*

Real Data *Values...*

Rotation Axis Vector {=*|are|is*} *Value...*

Source Direction Vector {=*|are|is*} *Value...*

Source Start Location {=*|are|is*} *Point...*

Source Velocity Vector {=*|are|is*} *Value...*

Start Time {=*|are|is*} *Value*

Stop Time {=*|are|is*} *Value*

Use Data Block *Name*

Use Toggle Block *ToggleName* [{*@|at|for|in|on|over*}
ElementBlockList...]

End

Summary This command block specifies that a laser heat flux is to be applied on the given surface.

Description The laser heat flux depends upon the laser beam characteristics and will vary with time and space in arbitrary manner as specified by the path description and its position relative to the surface normal.

33.7.1. Absorption Coefficient

Scope: Laser Heat Flux Boundary Condition

Absorption Coefficient {=*|are|is*} *value*

Parameter	Value	Default
<i>value</i>	real	undefined

Summary Specifies the surface absorption coefficient.

33.7.2. Absorption Coefficient Data File

Scope: Laser Heat Flux Boundary Condition

Absorption Coefficient Data File {=*|are|is*} *Filename*

Parameter	Value	Default
<i>Filename</i>	string	undefined

Summary Specifies filename to read absorption coefficient data from.

33.7.3. Add Surface

Scope: Laser Heat Flux Boundary Condition

Add Surface *SurfaceList...*

Parameter	Value	Default
<i>SurfaceList</i>	string...	undefined

Summary Adds surfaces, by name, to a boundary condition's extent.

Description This line command is used to add surfaces to the extent of a boundary condition. In Exodus II, surfaces are specified as side sets, that have a global integer identifier. For example, side set 12 would be added by this line command using the surface name *surface_12*. Note that in SIERRA, each element of an array of strings must be separated by whitespace.

33.7.4. Angular Velocity

Scope: Laser Heat Flux Boundary Condition

Angular Velocity {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	real	undefined

Summary Specifies angular velocity of laser movement in revolutions per unit of time.

33.7.5. Beam Diameter

Scope: Laser Heat Flux Boundary Condition

Beam Diameter {=|are|is} *laser_diameter*

Parameter	Value	Default
<i>laser_diameter</i>	real	undefined

Summary Specifies laser spot size.

33.7.6. Beam Radius

Scope: Laser Heat Flux Boundary Condition

Beam Radius {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	real	undefined

Summary Specifies radius of laser beam.

33.7.7. Circular Path Center

Scope: Laser Heat Flux Boundary Condition

Circular Path Center {=|are|is} *Point...*

Parameter	Value	Default
<i>Point</i>	real...	undefined

Summary Specifies the center of circular path for laser source travel.

33.7.8. Circular Path Start Vector

Scope: Laser Heat Flux Boundary Condition

Circular Path Start Vector {=|are|is} *Value...*

Parameter	Value	Default
<i>Value</i>	real...	undefined

Summary Specifies the starting location on circular path, a radius vector relative to CIRCULAR PATH CENTER.

33.7.9. Compute Visibility Field

Scope: Laser Heat Flux Boundary Condition

Compute Visibility Field {=|are|is} *FieldName*

Parameter	Value	Default
<i>FieldName</i>	string	undefined

Summary Specifies visibility Field to be computed.

33.7.10. Effective Beam Radius

Scope: Laser Heat Flux Boundary Condition

Effective Beam Radius {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	real	undefined

Summary Specifies effective radius of laser beam.

33.7.11. Element Subroutine

Scope: Laser Heat Flux Boundary Condition

Element Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies that the named user-defined subroutine be used. At most one subroutine name may be specified for a given quantity. This subroutine must conform to the "element signature" argument list type.

33.7.12. Flux

Scope: Laser Heat Flux Boundary Condition

Flux {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary This line command specifies a constant value of heat flux.

33.7.13. Flux Fortran Subroutine

Scope: Laser Heat Flux Boundary Condition

Flux Fortran Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of a FORTRAN user subroutine that will be used to calculate the flux boundary condition.

33.7.14. Flux Type

Scope: Laser Heat Flux Boundary Condition

Flux Type {=|are|is} *LaserDistributionType*

Parameter	Value	Default
<i>LaserDistributionType</i>	{circle_weld gaussian_line_power_weld gaussian_line_weld gaussian_spot_power_weld gaussian_spot_weld laser laser_weld sharp_line_weld sharp_spot_weld}	LASER

Summary Selects the laser flux distribution model applied to a portion of the underlying surface as defined by a geometric path function. Flux types produce either a Gaussian flux with maximum intensity at the center of the laser spot or constant flux.

33.7.15. Integer Data

Scope: Laser Heat Flux Boundary Condition

Integer Data *Values...*

Parameter	Value	Default
<i>Values</i>	integer...	undefined

Summary List of integer data values to be used by the FORTRAN user subroutine. Copies of these values are provided to the subroutine hence changes to these values within the subroutine are not saved.

33.7.16. Integrated Flux Output

Scope: Laser Heat Flux Boundary Condition

Integrated Flux Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Calculate the average flux associated with this flux boundary condition.

Description This line command specifies that, as a postprocess, the normal flux associated with this boundary condition be integrated over the surface to obtain the total power. This power is then divided by the total area of the surface to obtain the average flux on the surface, and stored in a global variable named "variableName". This global variable may then be output to history files, or accessed in user subroutines, etc.

33.7.17. Integrated Power Output

Scope: Laser Heat Flux Boundary Condition

Integrated Power Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Calculate the total power associated with this flux boundary condition.

Description This line command specifies that, as a postprocess, the normal flux associated with this boundary condition be integrated over the surface to obtain the total power which is then stored into a global variable named "variableName". This global variable may then be output to history files, or accessed in user subroutines, etc.

33.7.18. Max Degrees

Scope: Laser Heat Flux Boundary Condition

Max Degrees {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	real	undefined

Summary Specifies maximum degrees of laser rotational motion.

33.7.19. Path Function

Scope: Laser Heat Flux Boundary Condition

Path Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies a time and position function for which a laser source is applied in the named volume.

33.7.20. Path Radius

Scope: Laser Heat Flux Boundary Condition

Path Radius {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	real	undefined

Summary Specifies radius for circular laser path.

33.7.21. Power

Scope: Laser Heat Flux Boundary Condition

Power {=|are|is} *laser_power*

Parameter	Value	Default
<i>laser_power</i>	real	undefined

Summary Specifies strength of the laser source.

33.7.22. Power Encore Function

Scope: Laser Heat Flux Boundary Condition

Power Encore Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies that power be applied with the named Encore function in the named volume.

33.7.23. Power Time Function

Scope: Laser Heat Flux Boundary Condition

Power Time Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies that power be applied as a function of time in the named volume.

33.7.24. Real Data

Scope: Laser Heat Flux Boundary Condition

Real Data *Values...*

Parameter	Value	Default
<i>Values</i>	real...	undefined

Summary List of real data values to be used by the FORTRAN user subroutine. Copies of these values are provided to the subroutine hence changes to these values within the subroutine are not saved.

33.7.25. Rotation Axis Vector

Scope: Laser Heat Flux Boundary Condition

Rotation Axis Vector {=|are|is} *Value...*

Parameter	Value	Default
<i>Value</i>	real...	undefined

Summary Specifies the axis of rotation for circular source travel, relative to CIRCULAR PATH CENTER.

33.7.26. Source Direction Vector

Scope: Laser Heat Flux Boundary Condition

Source Direction Vector {=|are|is} *Value...*

Parameter	Value	Default
<i>Value</i>	<i>real...</i>	undefined

Summary Specifies the vector orientation of the laser source.

33.7.27. Source Start Location

Scope: Laser Heat Flux Boundary Condition

Source Start Location {=|are|is} *Point...*

Parameter	Value	Default
<i>Point</i>	<i>real...</i>	undefined

Summary Specifies the physical coordinate location of the laser source.

33.7.28. Source Velocity Vector

Scope: Laser Heat Flux Boundary Condition

Source Velocity Vector {=|are|is} *Value...*

Parameter	Value	Default
<i>Value</i>	<i>real...</i>	undefined

Summary Specifies the velocity vector of laser source motion.

33.7.29. Start Time

Scope: Laser Heat Flux Boundary Condition

Start Time {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	<i>real</i>	undefined

Summary Specifies the time at which the laser beam is activated.

33.7.30. Stop Time

Scope: Laser Heat Flux Boundary Condition

Stop Time {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specifies the time at which the laser beam is deactivated.

33.7.31. Use Data Block

Scope: Laser Heat Flux Boundary Condition

Use Data Block *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Reference to predefined data to be used by the user subroutine. These values may be changed by the user subroutine.

33.7.32. Use Toggle Block

Scope: Laser Heat Flux Boundary Condition

Use Toggle Block *ToggleName* [{@|at|for|in|on|over} *ElementBlockList*...]

Parameter	Value	Default
<i>ToggleName</i>	string	undefined

Summary Specification for toggling entities in the computational model based on Toggle Block parameters. When used at the region level, the list of element blocks to be toggled must be provided. Otherwise a listing of entities is not needed as the Toggle Block will be associated with the command line or the enclosing command block.

33.8. CONVECTION HEAT TRANSFER

A broad class of thermal applications involve heat transfer between a solid volume and a surrounding fluid. In numerical simulations these interactions are modeled using various surface boundary conditions depending upon the detail to which the fluid flow is resolved. If both heat transfer in the solid model and fluid flow are explicitly modeled then it is often appropriate to solve the conjugate heat transfer problem. However, in many cases the expense of this calculation may not be justified and one reverts to alternative methods of modeling these effects.

In many situations it may be appropriate to simply characterize a bulk behavior of the fluid and employ a convective flux boundary condition of the form

$$q = h(T)(T_s - T_b)$$

where q is the heat flux per unit surface area, $h(T)$ is the surface heat transfer coefficient or convection coefficient, T_s is the surface temperature and T_b is the bulk fluid temperature. Many of the engineering models based upon experimental data for given configurations include variations of the values that enter into the expression above. In particular the values of $h(T)$ and T_b are often linked to representative fluid flow conditions.

For quick estimates of heat transfer, textbooks provide a tabulated range of surface heat transfer coefficients for general conditions. Furthermore, heat transfer handbooks provide a collection of heat transfer correlations from which convective coefficients can be computed. These correlations include empirical constants and are functions dimensionless numbers which characterize the bulk fluid flow and the bulk fluid temperature.

The Sierra Thermal module includes a number of different ways for specifying $h(T)$ and T_b . Additionally module provides a catalog of heat transfer correlations [34.1](#).

33.9. CONVECTIVE FLUX BOUNDARY CONDITION

Scope: Equation System

Begin Convective Flux Boundary Condition *Name*

Add Surface *SurfaceList...*

Convective Coefficient {=*|are|is*} *Value*

Convective Coefficient Encore Function {=*|are|is*} *Name*

Convective Coefficient Fortran Subroutine {=*|are|is*} *Name*

Convective Coefficient Node Variable {=*|are|is*} *Name*

Convective Coefficient Scale Factor {=*|are|is*} *Magnitude*

Convective Coefficient Subroutine {=*|are|is*} *Name*

Convective Coefficient Temperature Function {=*|are|is*} *NName*

Convective Coefficient Time Function {=|are|is} *Name*
 Equation {=|are|is} *EquationName*
 Ignore Flux Coverage
 Integer Data *Values...*
 Integrated Flux Output *VariableName*
 Integrated Power Output *VariableName*
 Real Data *Values...*
 Ref Temp Convective Coefficient Subroutine {=|are|is} *Name* [
UsingRefTemp]
 Reference Temperature {=|are|is} *Value*
 Reference Temperature Fortran Subroutine {=|are|is} *Name*
 Reference Temperature Global Variable {=|are|is}
GlobalVariableName
 Reference Temperature Node Variable {=|are|is} *Name*
 Reference Temperature Subroutine {=|are|is} *Name*
 Reference Temperature Temperature Function {=|are|is} *Name*
 Reference Temperature Time Function {=|are|is} *FunctionName*
 Scaled Convective Coefficient Subroutine {=|are|is} *Name* *FieldName*
 {=|are|is} *Field*
 Scaled Ref Temp Convective Coefficient Subroutine {=|are|is} *Name*
FieldName {=|are|is} *Field*
 Uq Flux Multiplier {=|are|is} *Value*
 Use Advective Bar *Name* [*BulkNodes*]
 Use Bulk Element *Name*
 Use Correlation Convection Model *Name*
 Use Data Block *Name*
 Use Enclosure *Name*
 Use Toggle Block *ToggleName* [{@|at|for|in|on|over}
ElementBlockList...]
 User Field Mask {=|are|is} *Name* [*Threshold* {=|are|is} *Value*]
 User Field Scaling {=|are|is} *Name*

Summary This command block specifies heat transfer on a boundary surface that can be modeled using Newton's law of cooling.

Description Newton's law of cooling specifies that the heat flux normal to a surface is proportional to the difference between the unknown temperature of the surface and some reference temperature of the fluid in which the surface is immersed: $q_n = h(T - T_r)$. The convection coefficient, h , and the reference temperature, T_r , may be specified in several ways as explained in detail below. In particular, note that the reference temperature is usually a known quantity, because the fluid with which it is associated is modeled as an infinite reservoir. However, if the size of this reservoir is finite, then its temperature can be affected by the energy transfer across the surface in question. This situation can be modeled by the bulk fluid element, wherein the energy of the reservoir is determined by a finite volume conservation equation.

You must specify exactly one convection coefficient, and either exactly one reference temperature or exactly one bulk fluid element name.

33.9.1. Add Surface

Scope: Convective Flux Boundary Condition

Add Surface *SurfaceList*...

Parameter	Value	Default
<i>SurfaceList</i>	string...	undefined

Summary Adds surfaces, by name, to a boundary condition's extent.

Description This line command is used to add surfaces to the extent of a boundary condition. In Exodus II, surfaces are specified as side sets, that have a global integer identifier. For example, side set i2 would be added by this line command using the surface name surface_i2. Note that in SIERRA, each element of an array of strings must be separated by whitespace.

33.9.2. Convective Coefficient

Scope: Convective Flux Boundary Condition

Convective Coefficient {= | are | is} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specify a constant convective coefficient for this boundary condition.

33.9.3. Convective Coefficient Encore Function

Scope: Convective Flux Boundary Condition

Convective Coefficient Encore Function {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of an Encore function that will be used to calculate the convective coefficient for this boundary condition.

33.9.4. Convective Coefficient Fortran Subroutine

Scope: Convective Flux Boundary Condition

Convective Coefficient Fortran Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of a FORTRAN user subroutine that will be used to calculate the convective coefficient for this boundary condition.

33.9.5. Convective Coefficient Node Variable

Scope: Convective Flux Boundary Condition

Convective Coefficient Node Variable {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of the node variable to use for the convective coefficient that is associated with this boundary condition.

Description The indicated node variable must be a legal Aria variable. Typically, this variable is defined by the user in the user definition command block. The node variable is interpolated to the integration points during the integration of the flux term. Typically, this variable would be calculated in another SIERRA region, e.g., Fuego, and transferred to Aria.

33.9.6. Convective Coefficient Scale Factor

Scope: Convective Flux Boundary Condition

Convective Coefficient Scale Factor {=|are|is} *Magnitude*

Parameter	Value	Default
<i>Magnitude</i>	real	undefined

Summary Specify that the convective coefficient is to be computed using sideset distribution factors that must be defined in the mesh database.

Description The coefficient on each face is computed by interpolating the distribution factors to the Gauss points and then multiplying the result by the given magnitude. Distribution factors do not currently work with h-adaptivity, since their values are not currently interpolated to the new nodes.

33.9.7. Convective Coefficient Subroutine

Scope: Convective Flux Boundary Condition

Convective Coefficient Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of a user subroutine that is to be used to calculate the convective coefficient for this boundary condition.

If the user subroutine employs a user specified reference temperature model to compute the heat transfer coefficient then optional arguments USING_REF_TEMP must also appear at the end of the command line.

33.9.8. Convective Coefficient Temperature Function

Scope: Convective Flux Boundary Condition

Convective Coefficient Temperature Function {=|are|is} *NName*

Parameter	Value	Default
<i>NName</i>	string	undefined

Summary Specify the name of a temperature-dependent function that is to be used to calculate the convective coefficient for this boundary condition.

33.9.9. Convective Coefficient Time Function

Scope: Convective Flux Boundary Condition

Convective Coefficient Time Function {=*|are|is*} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of a time-dependent function that is used to calculate the convective coefficient for this boundary condition.

33.9.10. Equation

Scope: Convective Flux Boundary Condition

Equation {=*|are|is*} *EquationName*

Parameter	Value	Default
<i>EquationName</i>	string	undefined

Summary This command can be used to apply the Convective Flux conditions for an equation other than the ENERGY equation.

33.9.11. Ignore Flux Coverage

Scope: Convective Flux Boundary Condition

Summary This command causes the code to ignore the flux coverage Field when contact is present. Thus the flux will be applied even if the BC is being set on a contact surface.

33.9.12. Integer Data

Scope: Convective Flux Boundary Condition

Integer Data *Values...*

Parameter	Value	Default
<i>Values</i>	integer...	undefined

Summary List of integer data values to be used by the FORTRAN user subroutine. Copies of these values are provided to the subroutine hence changes to these values within the subroutine are not saved.

33.9.13. Integrated Flux Output

Scope: Convective Flux Boundary Condition

Integrated Flux Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Calculate the average flux associated with this flux boundary condition.

Description This line command specifies that, as a postprocess, the normal flux associated with this boundary condition be integrated over the surface to obtain the total power. This power is then divided by the total area of the surface to obtain the average flux on the surface, and stored in a global variable named "variableName". This global variable may then be output to history files, or accessed in user subroutines, etc.

33.9.14. Integrated Power Output

Scope: Convective Flux Boundary Condition

Integrated Power Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Calculate the total power associated with this flux boundary condition.

Description This line command specifies that, as a postprocess, the normal flux associated with this boundary condition be integrated over the surface to obtain the total power which is then stored into a global variable named "variableName". This global variable may then be output to history files, or accessed in user subroutines, etc.

33.9.15. Real Data

Scope: Convective Flux Boundary Condition

Real Data *Values...*

Parameter	Value	Default
<i>Values</i>	real...	undefined

Summary List of real data values to be used by the FORTRAN user subroutine. Copies of these values are provided to the subroutine hence changes to these values within the subroutine are not saved.

33.9.16. Ref Temp Convective Coefficient Subroutine

Scope: Convective Flux Boundary Condition

Ref Temp Convective Coefficient Subroutine {=|are|is} *Name* [*UsingRefTemp*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of a user subroutine that is to be used to calculate the convective coefficient for this boundary condition. Use of this command line will enable the reference temperature to be supplied to the subroutine interface.

33.9.17. Reference Temperature

Scope: Convective Flux Boundary Condition

Reference Temperature {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specify a constant reference temperature for this boundary condition.

33.9.18. Reference Temperature Fortran Subroutine

Scope: Convective Flux Boundary Condition

Reference Temperature Fortran Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies the name of a FORTRAN user-defined subroutine that will be used to calculate the reference temperature associated with this boundary condition.

33.9.19. Reference Temperature Global Variable

Scope: Convective Flux Boundary Condition

Reference Temperature Global Variable {=|are|is} *GlobalVariableName*

Parameter	Value	Default
<i>GlobalVariableName</i>	string	undefined

Summary Specify a global variable to be used for reference temperature.

33.9.20. Reference Temperature Node Variable

Scope: Convective Flux Boundary Condition

Reference Temperature Node Variable {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of the node variable to use for the reference temperature that is associated with this boundary condition.

Description The indicated node variable must be a legal Aria variable. Typically, this variable is defined by the user in the user definition command block. The node variable is interpolated to the integration points during the integration of the flux term. Typically, this variable would be calculated in another SIERRA region, e.g., Fuego, and transferred to Aria.

33.9.21. Reference Temperature Subroutine

Scope: Convective Flux Boundary Condition

Reference Temperature Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies the name of a user-defined subroutine that is to be used to calculate the reference temperature associated with this boundary condition.

33.9.22. Reference Temperature Temperature Function

Scope: Convective Flux Boundary Condition

Reference Temperature Temperature Function {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies the name of the temperature-dependent function that is to be used to calculate the reference temperature associated with this boundary condition.

33.9.23. Reference Temperature Time Function

Scope: Convective Flux Boundary Condition

Reference Temperature Time Function {=|are|is} *FunctionName*

Parameter	Value	Default
<i>FunctionName</i>	string	undefined

Summary Specify the name of a time-dependent function for the reference temperature for this boundary condition.

33.9.24. Scaled Convective Coefficient Subroutine

Scope: Convective Flux Boundary Condition

Scaled Convective Coefficient Subroutine {=|are|is} *Name* *FieldName* {=|are|is} *Field*

Parameter	Value	Default
<i>Name</i>	string	undefined
<i>FieldName</i>	string	undefined
<i>Field</i>	string	undefined

Summary Specify the name of a user subroutine that is to be used to calculate the scaled convective coefficient for this boundary condition. The interpolated scaling *Field* is supplied directly to the user subroutine.

33.9.25. Scaled Ref Temp Convective Coefficient Subroutine

Scope: Convective Flux Boundary Condition

Scaled Ref Temp Convective Coefficient Subroutine {=|are|is} *Name* *FieldName* {=|are|is} *Field*

Parameter	Value	Default
<i>Name</i>	string	undefined
<i>FieldName</i>	string	undefined
<i>Field</i>	string	undefined

Summary Specify the name of a user subroutine that is to be used to calculate the scaled convective coefficient for this boundary condition. Use of this command will enable the reference temperature to be supplied to the user subroutine. Additionally interpolated values of the scaling *Field* will be delivered to the subroutine.

33.9.26. Uq Flux Multiplier

Scope: Convective Flux Boundary Condition

Uq Flux Multiplier {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	1.0

Summary Specify constant scaling of the convective flux.

Description Intended use of this scaling parameter is primarily for evaluation of model sensitivities.

33.9.27. Use Advective Bar

Scope: Convective Flux Boundary Condition

Use Advective Bar *Name* [*BulkNodes*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Use the named advective bar to model the reference temperature.

Description This line command specifies the name of an advective bar that has been defined using the advective bar command block. The temperature of the advective bar is used as the reference temperature, T_r , for the convective heat transfer and this is computed based on a geometric coupling algorithm. Note that it is illegal to specify both a reference temperature and an advective bar.

33.9.28. Use Bulk Element

Scope: Convective Flux Boundary Condition

Use Bulk Element *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Use the named bulk element to model the reference temperature.

Description This line command specifies the name of a bulk fluid element that has been defined using the bulk fluid command block. The temperature of the bulk fluid element is used as the reference temperature, T_r , for the convective heat transfer. Note that it is illegal to specify both a reference temperature and a bulk element.

33.9.29. Use Correlation Convection Model

Scope: Convective Flux Boundary Condition

Use Correlation Convection Model *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies correlation model for convection coefficient

33.9.30. Use Data Block

Scope: Convective Flux Boundary Condition

Use Data Block *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Reference to predefined data to be used by the user subroutine. These values may be changed by the user subroutine.

33.9.31. Use Enclosure

Scope: Convective Flux Boundary Condition

Use Enclosure *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Use the named enclosure to define the surface list and possibly model the reference temperature using the MBL bulk node of the enclosure.

Description This line command specifies the name of an enclosure that has been defined using the enclosure definition command block. The list of surfaces for this convective BC is taken from the enclosure surfaces and it is illegal to specify both an enclosure and a surface list. If the enclosure has the Mean Beam Length (MBL) model activated, then this convective BC is linked to the bulk fluid element associated with the MBL model. The temperature of the bulk fluid element is used as the reference temperature, T_r , for the convective heat transfer. Note that it is illegal to specify both a reference temperature and an enclosure with an MBL bulk element.

33.9.32. Use Toggle Block

Scope: Convective Flux Boundary Condition

Use Toggle Block *ToggleName* [{*@*|*at*|*for*|*in*|*on*|*over*} *ElementBlockList...*]

Parameter	Value	Default
<i>ToggleName</i>	string	undefined

Summary Specification for toggling entities in the computational model based on Toggle Block parameters. When used at the region level, the list of element blocks to be toggled must be provided. Otherwise a listing of entities is not needed as the Toggle Block will be associated with the command line or the enclosing command block.

33.9.33. User Field Mask

Scope: Convective Flux Boundary Condition

User Field Mask {*=*|*are*|*is*} *Name* [*Threshold* {*=*|*are*|*is*} *Value*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify that the convective boundary condition is to be masked by nonzero values of a user defined Field.

Description The convective boundary condition is applied in a conventional manner but then masked by nonzero values of an interpolated user defined Field. In most cases the user Field is transferred to Aria but it could also be computed. Default threshold for the masked value is 0.0, i.e. mask value equals 1.0 for values greater than zero.

33.9.34. User Field Scaling

Scope: Convective Flux Boundary Condition

User Field Scaling {*=*|*are*|*is*} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify that the convective boundary condition is to be scaled by a user defined Field.

Description The convective boundary condition is applied in a conventional manner but then scaled by an interpolated user defined Field. In most cases the user Field is transferred to Aria and acts as a weighting of the flux condition.

33.10. AERODYNAMIC CONVECTION HEAT TRANSFER

High-speed flows about bodies are often characterized by large temperature gradients and large variations of the flow properties through the boundary layer. The problem of heat transfer about the body is often addressed using numerical techniques of CFD to resolve the thermal transport through the boundary layer. Because CFD resources may not be readily applied at the design stage researchers often apply simplifying assumptions to arrive at alternative models for solving the problem of heat transfer about bodies exposed to high-speed flow. One common modeling approach is to define a convection coefficient and reference temperature that depend upon flight conditions. The aero heat flux boundary condition provides a means for supplying details of the flight conditions to arrive at a representative convection coefficient and reference temperature for two heat flux models, one derived by [41] and one that varies only with altitude.

The model by Eckert suggests that a convective heat transfer approach ignoring boundary layer temperature gradients may be used if the properties are evaluated at an alternative reference temperature representative of the averaged flow conditions. Syntax for typical usage of this model is shown below.

```
Begin AERO HEAT FLUX BOUNDARY CONDITION body_heating
  START TIME = 0.0
  STOP TIME = 20.0
  freestream temperature = 233.15
  freestream pressure    = 5.066e3
  mach number = 3.0
  fluid viscosity temperature function      = air_viscosity
  fluid specific heat temperature function  = air_specheat
  fluid thermal conductivity temperature function = air_cond
  fluid gamma = 1.4
  adiabatic wall temperature from recovery factor
  eckert convective coefficient
  COORDINATE OFFSET AXIS = x
  cone length = 0.0
  add surface surface_1
  integrated power output total_heating
End
```

Another aerodynamic heat flux model defines a convective coefficient that relies upon the variation of density with altitude. Syntax for typical usage of this model is shown below.

```
Begin AERO HEAT FLUX BOUNDARY CONDITION body_heating
  START TIME = 0.0
  STOP TIME = 20.0
  Density Ratio Convective Coefficient
  Freestream Density Altitude Function = density_func
  Altitude time function = altitude_time_func
```

```

Reference Density = 1.15
Reference HTC = 25.0
Density Ratio exponent = 0.6
reference temperature time function = ref_temp_func
add surface surface_1
integrated power output total_heating
End

```

A more complete description of syntax for the aero heating models is described in the section which follows.

33.11. AERO HEAT FLUX BOUNDARY CONDITION

Scope: Equation System

Begin Aero Heat Flux Boundary Condition *Name*

Add Surface *SurfaceList...*

Adiabatic Wall Temperature {=*|are|is*} *Value*

Adiabatic Wall Temperature Altitude Function {=*|are|is*} *Function*

Adiabatic Wall Temperature From Recovery Factor

Adiabatic Wall Temperature Time Function {=*|are|is*} *Function*

Altitude {=*|are|is*} *Value*

Altitude Time Function {=*|are|is*} *Function*

Cone Length {=*|are|is*} *Value*

Coordinate Offset {=*|are|is*} *Value*

Coordinate Offset Axis {=*|are|is*} *axis*

Density Ratio Convective Coefficient

Density Ratio Exponent {=*|are|is*} *Value*

Eckert Convective Coefficient

Fluid Gamma {=*|are|is*} *Value*

Fluid Gas Constant {=*|are|is*} *Value*

Fluid Properties Temperature Function {=*|are|is*} *Function*

Fluid Specific Heat Temperature Function {=*|are|is*} *Function*

Fluid Thermal Conductivity Temperature Function {=*|are|is*}
Function

Fluid Viscosity Temperature Function {=|are|is} *Function*
 Freestream Density Altitude Function {=|are|is} *Function*
 Freestream Pressure {=|are|is} *Value*
 Freestream Pressure Altitude Function {=|are|is} *Function*
 Freestream Pressure Time Function {=|are|is} *Function*
 Freestream Temperature {=|are|is} *Value*
 Freestream Temperature Altitude Function {=|are|is} *Function*
 Freestream Temperature Time Function {=|are|is} *Function*
 Integrated Flux Output *VariableName*
 Integrated Power Output *VariableName*
 Mach Number {=|are|is} *Value*
 Mach Number Time Function {=|are|is} *Function*
 Reference Density {=|are|is} *Value*
 Reference Htc {=|are|is} *Value*
 Reference Temperature {=|are|is} *Value*
 Reference Temperature Time Function {=|are|is} *FunctionName*
 Start Time {=|are|is} *Value*
 Stop Time {=|are|is} *Value*
 Uq Flux Multiplier {=|are|is} *Value*
 Use Toggle Block *ToggleName* [{@|at|for|in|on|over}
ElementBlockList...]

End

Summary This command block defines a distributed convective heat flux about a body based upon aerodynamic flight conditions applied on the given surface.

Description The aerodynamic heat flux depends upon characterization of flight conditions prescribed using data tables and spatial location on the body of interest.

33.11.1. Add Surface

Scope: Aero Heat Flux Boundary Condition

Add Surface *SurfaceList*...

Parameter	Value	Default
<i>SurfaceList</i>	string...	undefined

Summary Adds surfaces, by name, to a boundary condition's extent.

Description This line command is used to add surfaces to the extent of a boundary condition. In Exodus II, surfaces are specified as side sets, that have a global integer identifier. For example, side set 12 would be added by this line command using the surface name `surface_12`. Note that in SIERRA, each element of an array of strings must be separated by whitespace.

33.11.2. Adiabatic Wall Temperature

Scope: Aero Heat Flux Boundary Condition

Adiabatic Wall Temperature `{=|are|is}` *Value*

Parameter	Value	Default
<i>Value</i>	real	0.0

Summary Specifies a constant adiabatic wall temperature. Usage: ECKERT CONVECTIVE COEFFICIENT.

FREESTREAM TEMPERATURE and fluid properties consistent with this ADIABATIC WALL TEMPERATURE must also be provided.

33.11.3. Adiabatic Wall Temperature Altitude Function

Scope: Aero Heat Flux Boundary Condition

Adiabatic Wall Temperature Altitude Function `{=|are|is}` *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the adiabatic wall temperature versus altitude function for climate condition. Usage: ECKERT CONVECTIVE COEFFICIENT.

FREESTREAM TEMPERATURE and fluid properties consistent with this ADIABATIC WALL TEMPERATURE must also be provided.

33.11.4. Adiabatic Wall Temperature From Recovery Factor

Scope: Aero Heat Flux Boundary Condition

Summary Specifies that the adiabatic wall temperature be computed using the recovery factor, the stagnation temperature and the freestream temperature. Usage: ECKERT CONVECTIVE COEFFICIENT.

Description The adiabatic wall temperature T_{aw} is computed as

$$T_{aw} = rT_o + (1 - r)T_\infty$$

where r is the recovery factor, T_o is the stagnation temperature and T_∞ is the freestream temperature. The user must provide specification of MACH NUMBER, FREESTREAM TEMPERATURE, FREESTREAM PRESSURE and FLUID_GAMMA models. Stagnation temperature and flow velocity v will be internally computed from the MACH NUMBER. The recovery factor is given in terms of the freestream Prandtl number ($C_p\mu/K$) as

$$r = \begin{cases} Pr^{1/2} & \text{laminar flow} \\ Pr^{1/3} & \text{turbulent flow } Re > 5 \times 10^5 \end{cases}$$

Hence one must provide functions for specific heat, dynamic viscosity and thermal conductivity as a function of temperature. The flow regime varies spatially in the COORDINATE OFFSET direction as determined using the local Reynolds number

$$Re_x = \frac{\rho vx}{\mu}$$

Here the pressure P will vary with altitude hence density is evaluated using the ideal gas law

$$\rho = \frac{P}{RT_\infty}$$

33.11.5. Adiabatic Wall Temperature Time Function

Scope: Aero Heat Flux Boundary Condition

Adiabatic Wall Temperature Time Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the name of adiabatic wall temperature versus time function. Usage: ECKERT CONVECTIVE COEFFICIENT.

FREESTREAM TEMPERATURE and fluid properties consistent with this ADIABATIC WALL TEMPERATURE must also be provided.

33.11.6. Altitude

Scope: Aero Heat Flux Boundary Condition

Altitude {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	0.0

Summary Specifies a constant altitude.

Used in conjunction with FREESTREAM TEMPERATURE ALTITUDE FUNCTION, FREESTREAM TEMPERATURE FUNCTION and ECKERT CONVECTIVE COEFFICIENT. Alternative usage with FREESTREAM DENSITY ALTITUDE FUNCTION and DENSITY RATIO CONVECTIVE COEFFICIENT.

33.11.7. Altitude Time Function

Scope: Aero Heat Flux Boundary Condition

Altitude Time Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the altitude versus time function for a given flight. The tabulated time is defined relative to the START TIME.

Used in conjunction with FREESTREAM TEMPERATURE ALTITUDE FUNCTION, FREESTREAM TEMPERATURE FUNCTION and ECKERT CONVECTIVE COEFFICIENT. Alternative usage with FREESTREAM DENSITY ALTITUDE FUNCTION and DENSITY RATIO CONVECTIVE COEFFICIENT.

33.11.8. Cone Length

Scope: Aero Heat Flux Boundary Condition

Cone Length {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	0.0

Summary Specifies the length at which the body profile transitions to a constant diameter. Usage: ECKERT CONVECTIVE COEFFICIENT.

33.11.9. Coordinate Offset

Scope: Aero Heat Flux Boundary Condition

Coordinate Offset {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	0.0

Summary Specifies the coordinate offset from which the spatial position will be defined in the ECKERT CONVECTIVE COEFFICIENT calculations $x = X - \text{offset}$ where X is the Cartesian model coordinate from the mesh prescribed using COORDINATE OFFSET AXIS and is assumed to define the leading edge. The value of x is used in computation of the Reynolds number $Re_x^* = \frac{\rho^* v x}{\mu}$ hence the evaluation of x must provide values greater than zero.

33.11.10 Coordinate Offset Axis

Scope: Aero Heat Flux Boundary Condition

Coordinate Offset Axis {=|are|is} *axis*

Parameter	Value	Default
<i>axis</i>	string	none

Summary Specifies the Cartesian coordinate axis (X, Y or Z) from which spatial position will be defined when using the ECKERT CONVECTIVE COEFFICIENT. The surface heat transfer coefficient will be computed spatially relative to zero on this axis.

For models in which the geometry is offset from a zero reference one must define the COORDINATE OFFSET.

33.11.11 Density Ratio Convective Coefficient

Scope: Aero Heat Flux Boundary Condition

Summary Specifies a density ratio heat transfer coefficient model. Requires that FREESTREAM DENSITY ALTITUDE FUNCTION, REFERENCE DENSITY, REFERENCE HTC, DENSITY RATIO EXPONENT, START TIME and STOP TIME specifications be supplied.

Description The heat transfer coefficient that varies as

$$h = h_o \left[\frac{\rho(A)}{\rho_o} \right]^n$$

where h_o is the reference heat transfer coefficient, $\rho(A)$ is the altitude dependent density, ρ_o is the reference density and n is the density ratio exponent. Here the model parameters h_o , ρ_o and n are calibrated based upon measured temperature data.

33.11.12 Density Ratio Exponent

Scope: Aero Heat Flux Boundary Condition

Density Ratio Exponent {=|are|is} *Value*

Parameter <i>Value</i>	Value real	Default 0.0

Summary Specifies the density ratio exponent value for the density ratio heat transfer coefficient model. Usage: DENSITY RATIO CONVECTIVE COEFFICIENT.

33.11.13 Eckert Convective Coefficient

Scope: Aero Heat Flux Boundary Condition

Summary Specifies use of the Eckert heat transfer coefficient model for high-speed flow. Requires that freestream FLUID PROPERTY TEMPERATURE FUNCTIONS, START TIME, STOP TIME, FREESTREAM PRESSURE and ADIABATIC WALL TEMPERATURE specifications be supplied.

Description A constant property heat transfer coefficient approach in which properties are evaluated at an alternative temperature

$$T^* = T_\infty + 0.5(T - T_\infty) + 0.22(T_{aw} - T_\infty)$$

where T_∞ is the freestream temperature, T is the surface temperature, T_{aw} is the adiabatic wall temperature. T_{aw} will vary spatially depending upon the local Reynolds number

$$Re_x^* = \frac{\rho^* v x}{\mu}$$

where μ is evaluated at T^* and the coordinate $x > 0$. The FREESTREAM PRESSURE varies with altitude hence the density ρ^* is evaluated using the ideal gas law

$$\rho^* = \frac{P}{RT^*}.$$

The Stanton number represents the ratio of heat transferred into the fluid flow to the thermal capacity of the fluid. By developing the relationship between fluid friction and heat transfer frictional resistance, the heat transfer can be expressed in terms of the Stanton number to arrive at an approximate heat transfer coefficient for various portions of the flow regime

$$St_x^* Pr^{*2/3} = \begin{cases} 0.332 (Re_x^*/f_M)^{-1/2} & Re_x^* < 5 \times 10^5 \text{ laminar} \\ 0.0296 (Re_x^*/f_M)^{-1/5} & 5 \times 10^5 < Re_x^* < 10^7 \text{ turbulent} \\ 0.185 [\log_{10}(Re_x^*/f_M)]^{-2.584} & 10^7 < Re_x^* < 10^9 \text{ turbulent} \\ 0.00063 & Re_x^* > 10^9 \text{ turbulent} \end{cases}$$

The parameter f_M is the Mangler transformation for cone geometry

$$f_M = \begin{cases} 3 & \text{cone geometry} & \text{laminar} \\ 2 & \text{cone geometry} & \text{turbulent} \\ 1 & \text{flat plate geometry} & \text{laminar} \end{cases}$$

While Eckert's approach considers an average heat transfer coefficient over portions of a surface, here we consider a local heat transfer coefficient, $h(x)$ based upon the above relations that can be applied directly to the surface discretization

$$h(x) = \rho^* C_p^* U_\infty St_x^*$$

33.11.14 Fluid Gamma

Scope: Aero Heat Flux Boundary Condition

Fluid Gamma {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	1.4

Summary Specifies a constant specific heat ratio of the fluid medium. Usage: ECKERT CONVECTIVE COEFFICIENT.

Only constant values of γ are allowed.

33.11.15 Fluid Gas Constant

Scope: Aero Heat Flux Boundary Condition

Fluid Gas Constant {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	none

Summary Specifies the gas constant of the fluid medium. Usage: ECKERT CONVECTIVE COEFFICIENT.

33.11.16 Fluid Properties Temperature Function

Scope: Aero Heat Flux Boundary Condition

Fluid Properties Temperature Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies a multi-column function containing fluid properties density, specific heat, conductivity and dynamic viscosity versus temperature with respective property columns named CP, K and MU. Usage: ECKERT CONVECTIVE COEFFICIENT.

33.11.17 Fluid Specific Heat Temperature Function

Scope: Aero Heat Flux Boundary Condition

Fluid Specific Heat Temperature Function {=*|are|is|*} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the name of a user tabular function for specific heat as a function of temperature. Usage: ECKERT CONVECTIVE COEFFICIENT.

33.11.18 Fluid Thermal Conductivity Temperature Function

Scope: Aero Heat Flux Boundary Condition

Fluid Thermal Conductivity Temperature Function {=*|are|is|*} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the name of a user tabular function for thermal conductivity as a function of temperature. Usage: ECKERT CONVECTIVE COEFFICIENT.

33.11.19 Fluid Viscosity Temperature Function

Scope: Aero Heat Flux Boundary Condition

Fluid Viscosity Temperature Function {=*|are|is|*} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the name of a user tabular function for dynamic viscosity as a function of temperature. Usage: ECKERT CONVECTIVE COEFFICIENT.

33.11.20 Freestream Density Altitude Function

Scope: Aero Heat Flux Boundary Condition

Freestream Density Altitude Function {=*|are|is|*} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the freestream density versus altitude function for climate condition. Usage: DENSITY RATIO CONVECTIVE COEFFICIENT.

Requires that one supply an ALTITUDE model.

33.11.21 Freestream Pressure

Scope: Aero Heat Flux Boundary Condition

Freestream Pressure {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	0.0

Summary Specifies a constant freestream pressure.

33.11.22 Freestream Pressure Altitude Function

Scope: Aero Heat Flux Boundary Condition

Freestream Pressure Altitude Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the freestream pressure versus altitude function for climate condition.

33.11.23 Freestream Pressure Time Function

Scope: Aero Heat Flux Boundary Condition

Freestream Pressure Time Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the name of freestream pressure versus time function.

33.11.24 Freestream Temperature

Scope: Aero Heat Flux Boundary Condition

Freestream Temperature {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	0.0

Summary Specifies a constant freestream temperature. Usage: ECKERT CONVECTIVE COEFFICIENT.

33.11.25 Freestream Temperature Altitude Function

Scope: Aero Heat Flux Boundary Condition

Freestream Temperature Altitude Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the freestream temperature versus altitude function for climate condition. Usage: ECKERT CONVECTIVE COEFFICIENT.

33.11.26 Freestream Temperature Time Function

Scope: Aero Heat Flux Boundary Condition

Freestream Temperature Time Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the name of freestream temperature versus time function. Usage: ECKERT CONVECTIVE COEFFICIENT.

33.11.27 Integrated Flux Output

Scope: Aero Heat Flux Boundary Condition

Integrated Flux Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Calculate the average flux associated with this flux boundary condition.

Description This line command specifies that, as a postprocess, the normal flux associated with this boundary condition be integrated over the surface to obtain the total power. This power is then divided by the total area of the surface to obtain the average flux on the surface, and stored in a global variable named "variableName". This global variable may then be output to history files, or accessed in user subroutines, etc.

33.11.28 Integrated Power Output

Scope: Aero Heat Flux Boundary Condition

Integrated Power Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Calculate the total power associated with this flux boundary condition.

Description This line command specifies that, as a postprocess, the normal flux associated with this boundary condition be integrated over the surface to obtain the total power which is then stored into a global variable named "variableName". This global variable may then be output to history files, or accessed in user subroutines, etc.

33.11.29 Mach Number

Scope: Aero Heat Flux Boundary Condition

Mach Number {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	0.0

Summary Specifies a constant Mach number. Usage: ECKERT CONVECTIVE COEFFICIENT.

33.11.30 Mach Number Time Function

Scope: Aero Heat Flux Boundary Condition

Mach Number Time Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the Mach number versus time function for a given flight. The tabulated time is defined relative to the START TIME. Usage: ECKERT CONVECTIVE COEFFICIENT.

33.11.31 Reference Density

Scope: Aero Heat Flux Boundary Condition

Reference Density {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specifies the reference density value for the density ratio heat transfer coefficient model.
Usage: DENSITY RATIO CONVECTIVE COEFFICIENT.

33.11.32 Reference Htc

Scope: Aero Heat Flux Boundary Condition

Reference Htc {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specifies the reference heat transfer coefficient value for the density ratio heat transfer coefficient model. Usage: DENSITY RATIO CONVECTIVE COEFFICIENT.

33.11.33 Reference Temperature

Scope: Aero Heat Flux Boundary Condition

Reference Temperature {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specify a constant reference temperature for this boundary condition.

33.11.34 Reference Temperature Time Function

Scope: Aero Heat Flux Boundary Condition

Reference Temperature Time Function {=|are|is} *FunctionName*

Parameter	Value	Default
<i>FunctionName</i>	string	undefined

Summary Specify the name of a time-dependent function for the reference temperature for this boundary condition.

33.11.35 Start Time

Scope: Aero Heat Flux Boundary Condition

Start Time {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	0.0

Summary Specifies the analysis time at which the flight begins and the AERO heat flux will be applied.

33.11.36 Stop Time

Scope: Aero Heat Flux Boundary Condition

Stop Time {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	none

Summary Specifies the analysis time at which the flight ends and the AERO heat flux BC becomes inactive.

33.11.37 Uq Flux Multiplier

Scope: Aero Heat Flux Boundary Condition

Uq Flux Multiplier {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	1.0

Summary Specify constant scaling of the convective flux.

Description Intended use of this scaling parameter is primarily for evaluation of model sensitivities.

33.11.38 Use Toggle Block

Scope: Aero Heat Flux Boundary Condition

Use Toggle Block *ToggleName* [{@|at|for|in|on|over} *ElementBlockList...*]

Parameter	Value	Default
<i>ToggleName</i>	string	undefined

Summary Specification for toggling entities in the computational model based on Toggle Block parameters. When used at the region level, the list of element blocks to be toggled must be provided. Otherwise a listing of entities is not needed as the Toggle Block will be associated with the command line or the enclosing command block.

33.12. ADVECTIVE BAR



Beta Capability: The advective bar feature has not been fully tested and optimized for production use. Use this capability with caution.

For problems in which convection heat transfer occurs at the surface the analyst must supply some judgment about the fluid flow that gives rise to convection. While this information usually by performing a coupled conjugate heat transfer analysis including details of the fluid flow. In many cases the cost of such an analysis may be prohibitive so the analyst must resort to alternative lower order models. One such model, the advective bar, can be applied to cases in which the convective heat transfer is driven by a flow internal to the body of interest as in Figure 33.12-1. The bar model includes a simplified description of forced flow and flow section along the length of a one-dimensional discretization, where the advected flow is directly coupled with a corresponding energy equation. The bar temperatures define the far-field temperature distribution for convective heat transfer to the two or three-dimensional thermal solid model. The advantage gained by using the simplified velocity and temperature representation is that the velocity can be used to define both laminar and turbulent convective heat transfer appropriate to the specific problem using empirical heat transfer coefficients 34.1.




Figure 33.12-1.. Interior Body Flow

A bar model coordinate system facilitates user specification of the flow section properties. Here the bar coordinate system can be aligned with one of a Cartesian coordinate X,Y,Z directions. Optional use of an S coordinate system tied directly to the bar discretization enables modelling of flow along a circuitous path.

Entrance length effects are supported for a limited number of empirical correlations. By default, influence of the entrance length effect is aligned with the bar model coordinates. Cases in which these effects are significant only over a portion of the flow can be modeled using an offset of the bar model coordinate [33.12-2](#).




Figure 33.12-2.. Flow Entrance Effect Coordinate

Use of the advective bar model requires that it be referenced by name in a Convective Flux Boundary Condition along with the corresponding named Heat Transfer Coefficient Correlation.

```
Begin Sierra myJob
.
Begin Procedure My_Aria_Procedure
.
Begin Aria Region My_Region
.
Begin ADVECTIVE bAR NETWORK airBar
.
End ADVECTIVE BAR NETWORK airBar
.
Begin HEAT TRANSFER CORRELATION COEFFICIENT channel
.
End HEAT TRANSFER CORRELATION COEFFICIENT channel
.
begin convective flux boundary condition inside
.
USE CORRELATION CONVECTION MODEL channel
USE ADVECTIVE BAR airbar
.
end convective flux boundary condition inside
.
End
.
```

End
.
End Sierra myJob

33.13. ADVECTIVE BAR NETWORK

Scope: Equation System

Begin Advection Bar Network *Name*

Add Volume *Parameters...*

Annulus Diameter Ratio Function {=*|are|is|*} *Function*

Annulus Diameter Ratio Threshold {=*|are|is|*} *Threshold*

Coordinate Reference {=*|are|is|*} *Nodelist* Component *xyzs*

Entrance Effect Starting Node Id {=*|are|is|*} *NodeID* [*Offset* {=*|are|is|*} *Value*]

Flow Cross Sectional Area Function {=*|are|is|*} *Function*

Fluid Density {=*|are|is|*} *Value*

Fluid Density Function {=*|are|is|*} *Function*

Fluid Viscosity {=*|are|is|*} *Value*

Hydraulic Diameter Function {=*|are|is|*} *Function*

Initial Temperature {=*|are|is|*} *t*

Mass Flow Rate {*@|at|for|in|on|over|*} *Nodelist* {=*|are|is|*} *Value*

Mass Flow Rate Function {*@|at|for|in|on|over|*} *Nodelist* {=*|are|is|*} *Function*

Maximum Pressure Solve Iterations {=*|are|is|*} *Iterations*

Maximum Search Tolerance {=*|are|is|*} *Tolerance*

Pressure Bc {*@|at|for|in|on|over|*} *Nodelist* {=*|are|is|*} *Pres*

Pressure Solve Tolerance {=*|are|is|*} *Tolerance*

Search Interval {=*|are|is|*} *Interval*

Solve Pressure

Surface Roughness {=*|are|is|*} *Roughness*

Velocity Bc {*@|at|for|in|on|over|*} *Nodelist* {=*|are|is|*} *Velocity*

Visualization *OnOff*

End

Summary Defines an advective bar that can be used by a convective flux boundary condition.

Description Newton's law of cooling specifies that the heat flux normal to a surface is proportional to the difference between the unknown temperature of the surface and some reference temperature of the fluid in which the surface is immersed: $q_n = h(T - T_r)$. The convection coefficient, h , and the reference temperature, T_r , may be specified in several ways. Of particular interest is the situation where the fluid flow can be reduced to a simple 1D flow. In this case, heat transfer between the surface and the fluid is modeled with an advective bar model where each segment on the bar and each facet on the surface assumes a constant heat flux based on a constant h , T and T_r .

33.13.1. Add Volume

Scope: Advective Bar Network

Add Volume *Parameters...*

Parameter	Value	Default
<i>Parameters</i>	string...	undefined

Summary Adds bar element volumes, by name, to a boundary condition's extent.

33.13.2. Annulus Diameter Ratio Function

Scope: Advective Bar Network

Annulus Diameter Ratio Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the name of a user tabular function for annulus diameter ratio.

33.13.3. Annulus Diameter Ratio Threshold

Scope: Advective Bar Network

Annulus Diameter Ratio Threshold {=|are|is} *Threshold*

Parameter	Value	Default
<i>Threshold</i>	real	0.05

Summary Specifies the minimum value for annulus diameter ratio. This is used with both automatic calculation as well as user tabular function.

33.13.4. Coordinate Reference

Scope: Advective Bar Network

Coordinate Reference {=*|are|is*} *Nodelist* Component *xyzs*

Parameter	Value	Default
<i>Nodelist</i>	string	undefined
<i>xyzs</i>	{s x y z}	undefined

Summary Specifies the reference nodelist and direction for bar coordinates.

33.13.5. Entrance Effect Starting Node Id

Scope: Advective Bar Network

Entrance Effect Starting Node Id {=*|are|is*} *NodeID* [*Offset* {=*|are|is*} *Value*]

Parameter	Value	Default
<i>NodeID</i>	integer	0

Summary Specifies the node in the advective bar that corresponds to the position where entrance effects begin with pipe and annular flow correlations (Types 23, 25, 72-74).

Description Pipe and annular flow correlations support an entrance effect correction factor that will adjust the local heat transfer coefficient based on how far a point is from the inlet of the pipe or annulus. By default the inlet of the pipe is assumed to be at the first node of the advective bar. This option allows the user to specify a different node ID as the pipe entrance for calculating the entrance effect. This node ID must be part of the advective bar network.

Optionally, in cases where the entrance effect begins at a point not exactly aligned with the STARTING NODE one may specify an offset that will align the entrance effect to the correct coordinate. Here the offset is defined in the COORDINATE REFERENCE direction.

33.13.6. Flow Cross Sectional Area Function

Scope: Advective Bar Network

Flow Cross Sectional Area Function {=*|are|is*} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the name of a user tabular function for cross-sectional flow area.

33.13.7. Fluid Density

Scope: Advective Bar Network

Fluid Density {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specifies bar fluid density.

33.13.8. Fluid Density Function

Scope: Advective Bar Network

Fluid Density Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the name of a user tabular function of temperature for density.

33.13.9. Fluid Viscosity

Scope: Advective Bar Network

Fluid Viscosity {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specifies bar fluid absolute viscosity.

33.13.10Hydraulic Diameter Function

Scope: Advective Bar Network

Hydraulic Diameter Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the name of a user tabular function for hydraulic diameter.

33.13.11 Initial Temperature

Scope: Advective Bar Network

Initial Temperature {=|are|is} *t*

Parameter	Value	Default
<i>t</i>	real	undefined

Summary Specifies the initial temperature of the bulk node.

33.13.12 Mass Flow Rate

Scope: Advective Bar Network

Mass Flow Rate {@|at|for|in|on|over} *Nodelist* {=|are|is} *Value*

Parameter	Value	Default
<i>Nodelist</i>	string	undefined
<i>Value</i>	real	undefined

Summary Specifies the mass flow rate at a node.

33.13.13 Mass Flow Rate Function

Scope: Advective Bar Network

Mass Flow Rate Function {@|at|for|in|on|over} *Nodelist* {=|are|is} *Function*

Parameter	Value	Default
<i>Nodelist</i>	string	undefined
<i>Function</i>	string	undefined

Summary Specifies the mass flow rate as a function of time at a node with a user function.

33.13.14 Maximum Pressure Solve Iterations

Scope: Advective Bar Network

Maximum Pressure Solve Iterations {=|are|is} *Iterations*

Parameter	Value	Default
<i>Iterations</i>	integer	undefined

Summary Specifies maximum number of bar pressure solve iterations.

33.13.15 Maximum Search Tolerance

Scope: Advective Bar Network

Maximum Search Tolerance {=|are|is} *Tolerance*

Parameter	Value	Default
<i>Tolerance</i>	real	0.5

Summary Specifies the maximum search tolerance for bar/facet geometric coupling search and this must be between 0 and 1. For an idealized case of a curved bar with a constant curvature (R) and a facet that is at a distance (d) from the bar, the analytical solution tolerance is given by

$$tol = \frac{d}{2R}$$

Note that for a straight bar with infinite radius of curvature, this gives a tolerance of 0.

33.13.16 Pressure Bc

Scope: Advective Bar Network

Pressure Bc {@|at|for|in|on|over} *Nodelist* {=|are|is} *Pres*

Parameter	Value	Default
<i>Nodelist</i>	string	undefined
<i>Pres</i>	real	undefined

Summary Specifies bar inlet pressure.

33.13.17 Pressure Solve Tolerance

Scope: Advective Bar Network

Pressure Solve Tolerance {=|are|is} *Tolerance*

Parameter	Value	Default
<i>Tolerance</i>	real	undefined

Summary Specifies bar pressure solution convergence tolerance.

33.13.18 Search Interval

Scope: Advective Bar Network

Search Interval {=|are|is} *Interval*

Parameter	Value	Default
<i>Interval</i>	integer	5

Summary Specifies the number of search intervals for bar/facet geometric coupling search. This is used in conjunction with the maximum search tolerance to generate search tolerances from 0.0 to the maximum search tolerance specified. Must be greater than 0

33.13.19 Solve Pressure

Scope: Advective Bar Network

Summary Invoke pressure solution. This capability is not currently enabled for split network solutions.

33.13.20 Surface Roughness

Scope: Advective Bar Network

Surface Roughness {=|are|is} *Roughness*

Parameter	Value	Default
<i>Roughness</i>	real	undefined

Summary Specifies roughness coefficient of surface.

33.13.21 Velocity Bc

Scope: Advective Bar Network

Velocity Bc {@|at|for|in|on|over} *Nodelist* {=|are|is} *Velocity*

Parameter	Value	Default
<i>Nodelist</i>	string	undefined
<i>Velocity</i>	real	undefined

Summary Specifies bar inlet velocity.

33.13.22 Visualization

Scope: Advective Bar Network

Visualization *OnOff*

Parameter	Value	Default
<i>OnOff</i>	{off on}	Off

Summary Specifies Exodus output toggling of the created subsetted surfaces which are directly affected by the bulk nodes on the advective bar.

33.13.23 Wetted Perimeter Function

Scope: Advective Bar Network

Wetted Perimeter Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the name of a user tabular function for wetted perimeter.

33.14. RADIATIVE FLUX BOUNDARY CONDITION

Scope: Equation System

Begin Radiative Flux Boundary Condition *Name*

Add Surface *SurfaceList...*

Emissivity {=|are|is} *Value* [On *SurfaceName*]

Emissivity For Bands {=|are|is} *Emissivity...*

Emissivity Fortran Subroutine {=|are|is} *Name*

Emissivity Function {=|are|is} *FunctionName* [On *SurfaceName*]

Emissivity Subroutine {=|are|is} *MySub* [On *SurfaceName*]

Emissivity Time Function {=|are|is} *FunctionName* [On *SurfaceName*]

Equation {=|are|is} *EquationName*

Form Factor Fortran Subroutine {=|are|is} *Name*

Ignore Flux Coverage

Integer Data *Values...*

Integrated Flux Output *VariableName*

Integrated Power Output *VariableName*
 Irradiation Node Variable {=|are|is} *Name*
 Irradiation Subroutine {=|are|is} *Name*
 Irradiation Time Function {=|are|is} *Name*
 Radiation Form Factor {=|are|is} *Value*
 Radiation Form Factor Subroutine {=|are|is} *Name*
 Radiation Form Factor Temperature Function {=|are|is} *Name*
 Radiation Form Factor Time Function {=|are|is} *Name*
 Real Data *Values...*
 Reference Temperature {=|are|is} *Value*
 Reference Temperature Fortran Subroutine {=|are|is} *Name*
 Reference Temperature Global Variable {=|are|is}
GlobalVariableName
 Reference Temperature Subroutine {=|are|is} *Name*
 Reference Temperature Temperature Function {=|are|is} *Name*
 Reference Temperature Time Function {=|are|is} *FunctionName*
 Use Advective Bar *Name* [*BulkNodes*]
 Use Banded Wavelength Model *ModelName*
 Use Bulk Element *Name*
 Use Data Block *Name*
 Use Toggle Block *ToggleName* [{@|at|for|in|on|over}
ElementBlockList...]

End

Summary Radiative heat flux boundary condition. You must specify either a reference temperature or provide a nodal field for irradiation.

Description This boundary condition models the radiative heat transfer from a specified surface to a surrounding surface. The temperature of the surrounding surface is assumed to have enough thermal mass that its temperature is unaffected by changes in computed temperature, and is therefore known. The heat flux normal to the surface is given by $q_n = \varepsilon F(\sigma T^4 - G)$, where the incident radiative flux, or irradiation, G , may either be specified directly as a nodal field, or may be specified through a reference temperature, $G = \sigma T_r^4$. The Stefan-Boltzmann constant, σ , is defined in a Global Constants command block, ε is the surface emissivity, and F is the form factor.

With the exception of σ , each of these parameters may vary in one of several ways, as defined below. The emissivity, if left unspecified, is determined locally from the material associated with the element that underlies each face on the surface. In the case of faces that are created as a result of element death, the emissivity is always determined by the underlying element.

33.14.1. Add Surface

Scope: Radiative Flux Boundary Condition

Add Surface *SurfaceList*...

Parameter	Value	Default
<i>SurfaceList</i>	string...	undefined

Summary Adds surfaces, by name, to a boundary condition's extent.

Description This line command is used to add surfaces to the extent of a boundary condition. In Exodus II, surfaces are specified as side sets, that have a global integer identifier. For example, side set 12 would be added by this line command using the surface name *surface_12*. Note that in SIERRA, each element of an array of strings must be separated by whitespace.

33.14.2. Emissivity

Scope: Radiative Flux Boundary Condition

Emissivity {=*|are|is*} *Value* [On *SurfaceName*]

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Sets a constant value of emissivity for a defined surface. If the optional parameters are not included, then this is the default emissivity for the enclosure. Otherwise it is only applied to the indicated surface.

****Note** that if a surface is called out more than once, the emissivity definition it is overwritten: last one in wins.

33.14.3. Emissivity For Bands

Scope: Radiative Flux Boundary Condition

Emissivity For Bands {=|are|is} *Emissivity...*

Parameter	Value	Default
<i>Emissivity</i>	real...	undefined

Summary Specify the constant emissivities for each wavelength band.

33.14.4. Emissivity Fortran Subroutine

Scope: Radiative Flux Boundary Condition

Emissivity Fortran Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of a FORTRAN user subroutine that will be used to calculate the convective coefficient for this boundary condition.

33.14.5. Emissivity Function

Scope: Radiative Flux Boundary Condition

Emissivity Function {=|are|is} *FunctionName* [On *SurfaceName*]

Parameter	Value	Default
<i>FunctionName</i>	string	undefined

Summary Sets a emissivity function for a defined surface. If the optional parameters are not included, then this is the default emissivity for the enclosure. Otherwise it is only applied to the indicated surface.

****Note** that if a surface is called out more than once, the emissivity definition it is overwritten: last one in wins.

33.14.6. Emissivity Subroutine

Scope: Radiative Flux Boundary Condition

Emissivity Subroutine {=|are|is} *MySub* [On *SurfaceName*]

Parameter	Value	Default
<i>MySub</i>	string	undefined

Summary Sets a emissivity user subroutine for a defined surface. If the optional parameters are not included, then this is the default emissivity for the enclosure. Otherwise it is only applied to the indicated surface.

Also, the software supports using locally scoped user data for most user subroutines, but I haven't figured out a syntax for it here yet. So it is not yet supported. If you need to get data into this subroutine, use the region's "REAL DATA" and "INTEGER DATA" line commands.

****Note** that if a surface is called out more than once, the emissivity definition it is overwritten: last one in wins.

33.14.7. Emissivity Time Function

Scope: Radiative Flux Boundary Condition

Emissivity Time Function {=|are|is} *FunctionName* [On *SurfaceName*]

Parameter	Value	Default
<i>FunctionName</i>	string	undefined

Summary Sets a emissivity function of time for a defined surface. If the optional parameters are not included, then this is the default emissivity for the enclosure. Otherwise it is only applied to the indicated surface.

****Note** that if a surface is called out more than once, the emissivity definition it is overwritten: last one in wins.

33.14.8. Equation

Scope: Radiative Flux Boundary Condition

Equation {=|are|is} *EquationName*

Parameter	Value	Default
<i>EquationName</i>	string	undefined

Summary This command can be used to apply the Radiative Flux conditions for an equation other than the ENERGY equation.

33.14.9. Form Factor Fortran Subroutine

Scope: Radiative Flux Boundary Condition

Form Factor Fortran Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of a FORTRAN user subroutine that will be used to calculate the form factor for this boundary condition.

33.14.10 Ignore Flux Coverage

Scope: Radiative Flux Boundary Condition

Summary This command causes the code to ignore the flux coverage Field when contact is present. Thus the flux will be applied even if the BC is being set on a contact surface.

33.14.11 Integer Data

Scope: Radiative Flux Boundary Condition

Integer Data *Values...*

Parameter	Value	Default
<i>Values</i>	integer...	undefined

Summary List of integer data values to be used by the FORTRAN user subroutine. Copies of these values are provided to the subroutine hence changes to these values within the subroutine are not saved.

33.14.12 Integrated Flux Output

Scope: Radiative Flux Boundary Condition

Integrated Flux Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Calculate the average flux associated with this flux boundary condition.

Description This line command specifies that, as a postprocess, the normal flux associated with this boundary condition be integrated over the surface to obtain the total power. This power is then divided by the total area of the surface to obtain the average flux on the surface, and stored in a global variable named "variableName". This global variable may then be output to history files, or accessed in user subroutines, etc.

33.14.13 Integrated Power Output

Scope: Radiative Flux Boundary Condition

Integrated Power Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Calculate the total power associated with this flux boundary condition.

Description This line command specifies that, as a postprocess, the normal flux associated with this boundary condition be integrated over the surface to obtain the total power which is then stored into a global variable named "variableName". This global variable may then be output to history files, or accessed in user subroutines, etc.

33.14.14 Irradiation Node Variable

Scope: Radiative Flux Boundary Condition

Irradiation Node Variable {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies the name of the node variable in which the incident radiative flux associated with this boundary condition is stored.

Description The indicated node variable must be a valid user variable. Typically, this variable is defined by the user within the Region scope. The node variable is interpolated to the integration points during the integration of the flux term. Typically, this variable would be calculated in another SIERRA region, e.g., Fuego, and populated by transfer in the appropriate Region.

33.14.15 Irradiation Subroutine

Scope: Radiative Flux Boundary Condition

Irradiation Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of a user subroutine used to evaluate the irradiation for this boundary condition.

33.14.16Irradiation Time Function

Scope: Radiative Flux Boundary Condition

Irradiation Time Function {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies the name of a time-dependent function that is used to calculate the irradiation associated with this boundary condition.

33.14.17Radiation Form Factor

Scope: Radiative Flux Boundary Condition

Radiation Form Factor {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specifies a constant value for the radiation form factor for this boundary condition.

Description For two surfaces, the BC surface (1) and far-field surface (2), ε denoting emissivity, A denoting area, and F_{12} is the view factor.

$$F = \begin{cases} 1 & \text{if } A_2 \gg A_1 \\ F_{12}/[(1 - \varepsilon_1)F_{12} + \varepsilon_1] & \text{for } \varepsilon_1 = 1 \text{ and } A_2 \text{ not } \gg A_1 \\ F_{12} & \text{if } \varepsilon_1 = \varepsilon_2 = 1 \end{cases}$$

33.14.18Radiation Form Factor Subroutine

Scope: Radiative Flux Boundary Condition

Radiation Form Factor Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies the name of a user subroutine that is used to calculate the radiation form factor associated with this boundary condition.

33.14.19 Radiation Form Factor Temperature Function

Scope: Radiative Flux Boundary Condition

Radiation Form Factor Temperature Function {=*|are|is*} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies the name of a temperature-dependent function that is used to calculate the radiation form factor associated with this boundary condition.

33.14.20 Radiation Form Factor Time Function

Scope: Radiative Flux Boundary Condition

Radiation Form Factor Time Function {=*|are|is*} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies the name of a time-dependent function that is used to calculate the form factor associated with this boundary condition.

33.14.21 Real Data

Scope: Radiative Flux Boundary Condition

Real Data *Values...*

Parameter	Value	Default
<i>Values</i>	real...	undefined

Summary List of real data values to be used by the FORTRAN user subroutine. Copies of these values are provided to the subroutine hence changes to these values within the subroutine are not saved.

33.14.22 Reference Temperature

Scope: Radiative Flux Boundary Condition

Reference Temperature {=*|are|is*} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Specify a constant reference temperature for this boundary condition.

33.14.23 Reference Temperature Fortran Subroutine

Scope: Radiative Flux Boundary Condition

Reference Temperature Fortran Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies the name of a FORTRAN user-defined subroutine that will be used to calculate the reference temperature associated with this boundary condition.

33.14.24 Reference Temperature Global Variable

Scope: Radiative Flux Boundary Condition

Reference Temperature Global Variable {=|are|is} *GlobalVariableName*

Parameter	Value	Default
<i>GlobalVariableName</i>	string	undefined

Summary Specify a global variable to be used for reference temperature.

33.14.25 Reference Temperature Subroutine

Scope: Radiative Flux Boundary Condition

Reference Temperature Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies the name of a user-defined subroutine that is to be used to calculate the reference temperature associated with this boundary condition.

33.14.26 Reference Temperature Temperature Function

Scope: Radiative Flux Boundary Condition

Reference Temperature Temperature Function {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies the name of the temperature-dependent function that is to be used to calculate the reference temperature associated with this boundary condition.

33.14.27 Reference Temperature Time Function

Scope: Radiative Flux Boundary Condition

Reference Temperature Time Function {=|are|is} *FunctionName*

Parameter	Value	Default
<i>FunctionName</i>	string	undefined

Summary Specify the name of a time-dependent function for the reference temperature for this boundary condition.

33.14.28 Use Advective Bar

Scope: Radiative Flux Boundary Condition

Use Advective Bar *Name* [*BulkNodes*]

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Use the named advective bar to model the reference temperature.

Description This line command specifies the name of an advective bar that has been defined using the advective bar command block. The temperature of the advective bar is used as the reference temperature, T_r , for the convective heat transfer and this is computed based on a geometric coupling algorithm. Note that it is illegal to specify both a reference temperature and an advective bar.

33.14.29 Use Banded Wavelength Model

Scope: Radiative Flux Boundary Condition

Use Banded Wavelength Model *ModelName*

Parameter	Value	Default
<i>ModelName</i>	string	undefined

Summary Use a specified banded wavelength model for use in enclosure radiation.

Description Requests that a specific banded wavelength model named *modelName*, be associated with an enclosure, where the *modelName* is defined outside of the enclosure definition block. Only one BANDED WAVELENGTH MODEL can be used for an enclosure.

33.14.30 Use Bulk Element

Scope: Radiative Flux Boundary Condition

Use Bulk Element *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Use the named bulk element to model the reference temperature.

Description This line command specifies the name of a bulk fluid element that has been defined using the bulk fluid command block. The temperature of the bulk fluid element is used as the reference temperature, T_r , for the convective heat transfer. Note that it is illegal to specify both a reference temperature and a bulk element.

33.14.31 Use Data Block

Scope: Radiative Flux Boundary Condition

Use Data Block *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Reference to predefined data to be used by the user subroutine. These values may be changed by the user subroutine.

33.14.32 Use Toggle Block

Scope: Radiative Flux Boundary Condition

Use Toggle Block *ToggleName* [{@|at|for|in|on|over} *ElementBlockList*...]

Parameter	Value	Default
<i>ToggleName</i>	string	undefined

Summary Specification for toggling entities in the computational model based on Toggle Block parameters. When used at the region level, the list of element blocks to be toggled must be provided. Otherwise a listing of entities is not needed as the Toggle Block will be associated with the command line or the enclosing command block.

33.15. USER VARIABLE

Scope: Equation System

Begin User Variable *Name*

Add Part *part...*

Get Global From Region *other_region RemoteVariable Index*

Global Operator {=|are|is} *UserVarOperator*

Initial Value {=|are|is} *Value...*

Read Variable {=|are|is} *Variable* [At Time *TimeValue*]

Reset On *Assign*

Type {=|are|is} *UserVarMeshObject UserVarType* [Length {=|are|is} *Length*]

Use With Restart

End

Summary Defines user-named registered variables for this region. The name of the variable is specified by the line parameter 'name'.

Description This command block allows the user to define their own variables, which have the same status as pre-existing variables. For example, they may be output in the same way as other Aria variables, and may participate in SIERRA restart services. This feature is useful when a user has a need to store data on each mesh object (e.g. nodes) or wishes to evaluate a scalar quantity that requires parallel reduction across processors (e.g. a sum). Typically, a user variable would be set by a SIERRA framework transfer service from another region, or via user subroutines.

33.15.1. Add Part

Scope: User Variable

Add Part *part...*

Parameter	Value	Default
<i>part</i>	string...	undefined

Summary Adds surface, block or mesh group, by name, to a user variable's extent.

Description This line command is used to add surfaces or blocks to the extent of a user variable. In Exodus II, surfaces are specified as side sets, that have a global integer identifier. For example, side set 12 would be added by this line command using the surface name `surface_12`. Similarly element blocks also have a global identifier. Note that in SIERRA, each element of an array of strings must be separated by whitespace.

33.15.2. Get Global From Region

Scope: User Variable

Get Global From Region *other_region RemoteVariable Index*

Parameter	Value	Default
<i>other_region</i>	string	undefined
<i>RemoteVariable</i>	string	undefined
<i>Index</i>	integer	undefined

Summary Specifies the user global variable value will be assigned the value of the named RemoteVariable retrieved from another application Region. Index is an offset into the RemoteVariable.

33.15.3. Global Operator

Scope: User Variable

Global Operator {=|are|is} *UserVarOperator*

Parameter	Value	Default
<i>UserVarOperator</i>	{max min sum}	undefined

Summary REQUIRED for GLOBAL variables. Since global variables are often used in user subroutines a need arises in parallel simulations to resolve a representative single GLOBAL variable value across processors. The choice of operator determines how the single global value is to be resolved from each of the individual processor local values of the variable.

For SUM the local global variable values on each processor are summed to obtain a single value of the global variable.

For MIN the local global variable values on each processor are compared and the minimum value over all processors is assigned to the global variable.

For MAX the local global variable values on each processor are compared and the maximum value over all processors is assigned to the global variable.

Parallel synchronization of the single global variables will occur both at the beginning of a nonlinear solution iteration and at the completion of a nonlinear step. Once the synchronization has occurred the local global variable is reset to its initial value.

33.15.4. Initial Value

Scope: User Variable

Initial Value {=*|are|is*} *Value...*

Parameter	Value	Default
<i>Value</i>	<i>real...</i>	undefined

Summary Optional. Specifies the initial value of the user variable. The number of initial values specified with this line command must match the length of the variable specified in the "TYPE" command. If this command is present the specified initial value will automatically be applied to the user variable.

33.15.5. Read Variable

Scope: User Variable

Read Variable {=*|are|is*} *Variable* [At Time *TimeValue*]

Parameter	Value	Default
<i>Variable</i>	<i>string</i>	undefined

Summary Requests that the variable will be assigned from a time plane of the input ExodusII database. If an AT TIME is not specified, the time plane defaults to the last time plane in the database.

33.15.6. Reset On

Scope: User Variable

Reset On *Assign*

Parameter	Value	Default
<i>Assign</i>	<i>{iteration step}</i>	undefined

Summary Specifies when the user global variable will be reset. By default global variable will be reset after the nonlinear step has converged.

33.15.7. Type

Scope: User Variable

Type {=*|are|is*} *UserVarMeshObject UserVarType* [Length {=*|are|is*} *Length*]

Parameter	Value	Default
<i>UserVarMeshObject</i>	{ <i>edge element face global node</i> }	undefined
<i>UserVarType</i>	{ <i>integer real real_tensor real_vector</i> }	undefined

Summary This line command is required. The type of user variable is either real or integer, and is either a single, global value, or is associated with each mesh object of the specified kind. Global variables must have a 'GLOBAL OPERATOR' command associated with them to define its synchronization. The default length is 1. The default initial value for global variables is 0.

33.15.8. Use With Restart

Scope: User Variable

Summary Optional. The default behavior is for user-defined variables to not be preserved across a restart. The presence of this line command specifies that the variable is to be written to and restored from the restart file.

33.16. VOLUME HEATING

Scope: Equation System

Begin Volume Heating *Name*

Add Volume *VolumeList...*

Chemeq {=*|are|is*} *Model*

Element Subroutine {=*|are|is*} *Name*

Element Variable {=*|are|is*} *Name*

Encore Function {=*|are|is*} *Function*

Field Scaling {=*|are|is*} *Scale_factor*

Integer Data *Values...*

Integrated Power Output *VariableName*

Joule Heating

Nodal Variable {=*|are|is*} *Name*

Real Data *Values...*

Scaling Time Function {=*|are|is*} *Function*

Scaling With Global Variable {=*|are|is*} *name*

Source Fortran Subroutine {=*|are|is*} *Name*

Temperature Function {=*|are|is*} *Function*

Time Function {=*|are|is*} *Function*

Use Data Block *Name*

Use Toggle Block *ToggleName* [{*@|at|for|in|on|over*}
ElementBlockList...]

Use Verdi

Value {=*|are|is*} *vals*

Verdi Qdot Scaling {=*|are|is*} *Scale_factor* For *Keyval...*

End

Summary Defines a volumetric heat source. Exactly one heating type specification is allowed.

Description The volumetric heating must be applied to at least one volume. If a user subroutine is specified, then real and integer data may be declared that will be local in scope to this instance of the volume heating.

33.16.1. Add Volume

Scope: Volume Heating

Add Volume *VolumeList...*

Parameter	Value	Default
<i>VolumeList</i>	string...	undefined

Summary Specifies the mesh volume to which this code feature is to be applied. More than one volume name may be specified, as a space-delimited list.

33.16.2. Chemeq

Scope: Volume Heating

Chemeq {=|are|is} *Model*

Parameter	Value	Default
<i>Model</i>	string	undefined

Summary Specifies that volume heating is due to chemical reaction. Here MODEL pertains to the paired CHEMEQ MODEL and CHEMEQ SOLVER command blocks that define the chemical system and how it can evolve. Chemical heating source contributions are further controlled through parameters in the CHEMEQ SOLVER command block.

33.16.3. Element Subroutine

Scope: Volume Heating

Element Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies that the named user-defined subroutine be used. At most one subroutine name may be specified for a given quantity. This subroutine must conform to the "element signature" argument list type.

33.16.4. Element Variable

Scope: Volume Heating

Element Variable {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies the name of an element variable in which the volumetric heat source is stored. The units of this term are power per unit volume. Currently, this must be constant in space over each finite element.

33.16.5. Encore Function

Scope: Volume Heating

Encore Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies that volumetric heating be applied with the named Encore function.

33.16.6. Field Scaling

Scope: Volume Heating

Field Scaling {=*|are|is*} *Scale_factor*

Parameter	Value	Default
<i>Scale_factor</i>	real	undefined

Summary This command is only relevant when the NODAL VARIABLE or ELEMENT VARIABLE command line option is present. The command enables scaling of the Field variable for the element blocks within this Volume Heat command block.

33.16.7. Integer Data

Scope: Volume Heating

Integer Data *Values...*

Parameter	Value	Default
<i>Values</i>	integer...	undefined

Summary List of integer data values to be used by the FORTRAN user subroutine. Copies of these values are provided to the subroutine hence changes to these values within the subroutine are not saved.

33.16.8. Integrated Power Output

Scope: Volume Heating

Integrated Power Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Calculate the total power associated with this flux boundary condition.

Description This line command specifies that, as a postprocess, the normal flux associated with this boundary condition be integrated over the surface to obtain the total power which is then stored into a global variable named "variableName". This global variable may then be output to history files, or accessed in user subroutines, etc.

33.16.9. Joule Heating

Scope: Volume Heating

Summary Specifies that Joule heating will be applied. This model requires that either a VOLTAGE or CURRENT Equation be defined on the specified element block(s). Additionally the corresponding electrical conductivity must be defined.

33.16.10 Nodal Variable

Scope: Volume Heating

Nodal Variable {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies the name of a nodal variable in which the volumetric heat source is stored. The units of this term are power per unit volume.

Description The nodal variable could be user defined, which could originate from a transfer in the case of coupled mechanics, or from some user subroutine. The nodal values are interpolated to the Gauss points and then integrated over each element.

33.16.11 Real Data

Scope: Volume Heating

Real Data *Values...*

Parameter	Value	Default
<i>Values</i>	real...	undefined

Summary List of real data values to be used by the FORTRAN user subroutine. Copies of these values are provided to the subroutine hence changes to these values within the subroutine are not saved.

33.16.12 Scaling Time Function

Scope: Volume Heating

Scaling Time Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary This command is only relevant when the NODAL VARIABLE or ELEMENT VARIABLE command line option is present. This command enables time function scaling of the field variable for the element blocks within this Volume Heat command block.

33.16.13 Scaling With Global Variable

Scope: Volume Heating

Scaling With Global Variable {=|are|is} *name*

Parameter	Value	Default
<i>name</i>	string	undefined

Summary This command is only relevant when the NODE VARIABLE or ELEMENT VARIABLE command line option is present. The command enables scaling of the source Field by a global variable for the surfaces within the Volume Heat command block. The scalar global variable itself must be defined at the Region scope as type double with length 1.

33.16.14 Source Fortran Subroutine

Scope: Volume Heating

Source Fortran Subroutine {=|are|is} *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specify the name of a FORTRAN user subroutine that will be used to calculate the volumetric source.

33.16.15 Temperature Function

Scope: Volume Heating

Temperature Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies a temperature dependent function name for a volumetric heat source to be applied in the named volume.

33.16.16Time Function

Scope: Volume Heating

Time Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies a time function dependent name for a volumetric heat source to be applied in the named volume.

33.16.17Use Data Block

Scope: Volume Heating

Use Data Block *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Reference to predefined data to be used by the user subroutine. These values may be changed by the user subroutine.

33.16.18Use Toggle Block

Scope: Volume Heating

Use Toggle Block *ToggleName* [{@|at|for|in|on|over} *ElementBlockList*...]

Parameter	Value	Default
<i>ToggleName</i>	string	undefined

Summary Specification for toggling entities in the computational model based on Toggle Block parameters. When used at the region level, the list of element blocks to be toggled must be provided. Otherwise a listing of entities is not needed as the Toggle Block will be associated with the command line or the enclosing command block.

33.16.19Use Verdi

Scope: Volume Heating

Summary Specifies that the external Goodyear code VERDI should be used to calculate the volumetric heating source term. The value is assumed to be constant in space over each finite element. **WARNINGS:** There are some caveats: the code will abort (1) with multi-processor runs, since Verdi is inherently serial; (2) with 3-d simulations, since Verdi expects a 2D heat problem to be solved; (3) whenever mesh adaptivity is in use, since Verdi uses three different meshes in its work that must remain very closely related; and (4) whenever Verdi is called from an executable other than eagle (including Calore), since only eagle links against Verdi.

33.16.20Value

Scope: Volume Heating

Value {=|are|is} *vh*s

Parameter	Value	Default
<i>vh</i> s	real	undefined

Summary Specifies a constant value for a volumetric heat source to be applied in the named volume.

33.16.21Verdi Qdot Scaling

Scope: Volume Heating

Verdi Qdot Scaling {=|are|is} *Scale_factor* For *Keyval*...

Parameter	Value	Default
<i>Scale_factor</i>	real	undefined
<i>Keyval</i>	string...	undefined

Summary This command is only relevant when the USE VERDI command line option is present. The command enables scaling of the element Qdot scale factor for a collection of element blocks. This command can appear within the command block several times with different scaling factors for each set of elements. Qdot scaling for element blocks not appearing in a VERDI QDOT SCALING command line is set to unity.

33.17. LASER HEATING

Scope: Equation System

Begin Laser Heating *Name*

Absorption Coefficient {=*|are|is*} *value*

Absorption Coefficient Encore Function {=*|are|is*} *Function*

Activation {=*|are|is*} *Value*

Activation Temperature {=*|are|is*} *Value*

Add Volume *VolumeList...*

Aft Semi Axis {=*|are|is*} *aft_semiaxis*

Beam Diameter {=*|are|is*} *laser_diameter*

Beam Diameter At Depth {=*|are|is*} *diameter_at_depth*

Depth Direction {=*|are|is*} *Function*

Depth Semi Axis {=*|are|is*} *depth_semiaxis*

Distribution {=*|are|is*} *LaserSourceDistributionType*

Effective Beam Radius {=*|are|is*} *value*

Efficiency {=*|are|is*} *Efficiency*

Integrated {=*|are|is*} *Value*

Integrated Power Output *VariableName*

Path Function {=*|are|is*} *Function*

Penetration Depth {=*|are|is*} *penetration_depth*

Power {=*|are|is*} *laser_power*

Power Encore Function {=*|are|is*} *Function*

Power Time Function {=*|are|is*} *Function*

Source Type {=*|are|is*} *LaserSourceType*

Spatial Influence Factor {=*|are|is*} *Value*

Speed {=*|are|is*} *EquationName*

Start Time {=*|are|is*} *Value*

Stop Time {=*|are|is*} *Value*

Travel Semi Axis {=*|are|is*} *travel_semiaxis*

Use Old Temperature {=*|are|is*} *Value*

Use Toggle Block *ToggleName* [{*@*|*at*|*for*|*in*|*on*|*over*}
ElementBlockList...]

Width Semi Axis {=*|are|is*} *width_semiaxis*

End

Summary Defines a moving laser volumetric heat source. Exactly one heating type specification is allowed.

Description The laser volumetric heating must be applied to at least one volume. If a user subroutine is specified, then real and integer data may be declared that will be local in scope to this instance of the volume heating.

33.17.1. Absorption Coefficient

Scope: Laser Heating

Absorption Coefficient {=*|are|is*} *value*

Parameter	Value	Default
<i>value</i>	real	undefined

Summary Specifies the surface absorption coefficient.

33.17.2. Absorption Coefficient Encore Function

Scope: Laser Heating

Absorption Coefficient Encore Function {=*|are|is*} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies that absorption coefficient be applied with the named Encore function.

33.17.3. Activation

Scope: Laser Heating

Activation {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	{false true}	undefined

Summary Whether or not to maintain an activation field for elements that have gone over the activation temperature

Description If true, elements within a geometric region bounded using SPATIAL INFLUENCE FACTOR will be activated when ACTIVATION TEMPERATURE is exceeded.

33.17.4. Activation Temperature

Scope: Laser Heating

Activation Temperature {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	Real_Max

Summary Defines temperature at which an element may be activated.

Description Elements within a geometric region bounded using SPATIAL INFLUENCE FACTOR will be activated when this temperature is exceeded. Used in conjunction with ACTIVATION_HEMISPHERE or ACTIVATION_SPHERES in addition to the ACTIVATION_USER_FUNCTION thermal conductivity model.

33.17.5. Add Volume

Scope: Laser Heating

Add Volume *VolumeList...*

Parameter	Value	Default
<i>VolumeList</i>	string...	undefined

Summary Specifies the mesh volume to which this code feature is to be applied. More than one volume name may be specified, as a space-delimited list.

33.17.6. Aft Semi Axis

Scope: Laser Heating

Aft Semi Axis {=*|are|is*} *aft_semiaxis*

Parameter	Value	Default
<i>aft_semiaxis</i>	real	undefined

Summary Defines the aft direction semiaxis for the double ellipsoidal and double ellipsoidal laser source model.

33.17.7. Beam Diameter

Scope: Laser Heating

Beam Diameter {=*|are|is*} *laser_diameter*

Parameter	Value	Default
<i>laser_diameter</i>	real	undefined

Summary Specifies laser spot size.

33.17.8. Beam Diameter At Depth

Scope: Laser Heating

Beam Diameter At Depth {=*|are|is*} *diameter_at_depth*

Parameter	Value	Default
<i>diameter_at_depth</i>	real	undefined

Summary Specifies the effective diameter at depth.

33.17.9. Depth Direction

Scope: Laser Heating

Depth Direction {=*|are|is*} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies the depth coordinate direction, X, Y, or Z, the directional axis in which laser is applied. For the ellipsoidal source model may select an additional option, FROM_PATH_NORMAL in which case the depth direction is defined in the opposite direction of the path normal defined by NX, NY, NZ components of the PATH_FUNCTION.

33.17.10Depth Semi Axis

Scope: Laser Heating

Depth Semi Axis {=|are|is} *depth_semiaxis*

Parameter	Value	Default
<i>depth_semiaxis</i>	real	undefined

Summary Defines the depth direction semiaxis for the ellipsoidal, double ellipsoidal and rectangular source model.

33.17.11Distribution

Scope: Laser Heating

Distribution {=|are|is} *LaserSourceDistributionType*

Parameter	Value	Default
<i>LaserSourceDistributionType</i>	{gaussian uniform}	GAUSSIAN

Summary Specifies the spatial distribution of applied laser energy.

Description Defines how the laser energy is deposited onto the source geometry. Generally speaking the spatial distribution is GAUSSIAN centered on the source point but for fiber bundles one may opt for the top hat or UNIFORM distribution.

33.17.12Effective Beam Radius

Scope: Laser Heating

Effective Beam Radius {=|are|is} *value*

Parameter	Value	Default
<i>value</i>	real	undefined

Summary Specifies effective radius of laser beam.

33.17.13Efficiency

Scope: Laser Heating

Efficiency {=|are|is} *Efficiency*

Parameter	Value	Default
<i>Efficiency</i>	real	undefined

Summary Defines the transmission efficiency of the available laser power.

33.17.14 Integrated

Scope: Laser Heating

Integrated {= | are | is} *Value*

Parameter	Value	Default
<i>Value</i>	{false true}	undefined

Summary Whether or not to integrate the source over the time-step to allow for larger time-steps

Description If true, the source will be integrated over the time-step and the time-average applied

33.17.15 Integrated Power Output

Scope: Laser Heating

Integrated Power Output *VariableName*

Parameter	Value	Default
<i>VariableName</i>	string	undefined

Summary Calculate the total power associated with this flux boundary condition.

Description This line command specifies that, as a postprocess, the normal flux associated with this boundary condition be integrated over the surface to obtain the total power which is then stored into a global variable named "variableName". This global variable may then be output to history files, or accessed in user subroutines, etc.

33.17.16 Path Function

Scope: Laser Heating

Path Function {= | are | is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies a time and position function for which a laser source is applied in the named volume.

33.17.17 Penetration Depth

Scope: Laser Heating

Penetration Depth {=|are|is} *penetration_depth*

Parameter	Value	Default
<i>penetration_depth</i>	real	undefined

Summary Specifies the depth of beam penetration.

33.17.18 Power

Scope: Laser Heating

Power {=|are|is} *laser_power*

Parameter	Value	Default
<i>laser_power</i>	real	undefined

Summary Specifies strength of the laser source.

33.17.19 Power Encore Function

Scope: Laser Heating

Power Encore Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies that power be applied with the named Encore function in the named volume.

33.17.20 Power Time Function

Scope: Laser Heating

Power Time Function {=|are|is} *Function*

Parameter	Value	Default
<i>Function</i>	string	undefined

Summary Specifies that power be applied as a function of time in the named volume.

33.17.21 Source Type

Scope: Laser Heating

Source Type {=|are|is} *LaserSourceType*

Parameter	Value	Default
<i>LaserSourceType</i>	{activation_hemisphere activation_parallelepiped activation_sphere beer_lambert conical ellipsoidal hemisphere integrated_activation_hemisphere integrated_hemisphere parallelepiped sphere}	HEMISPHERE

Summary Selects the laser source model applied to a portion of the underlying volume as defined by a geometric function. When used with a Gaussian DISTRIBUTION all source types produce maximum intensity at the center of the laser spot. Aside from the ACTIVATION SPHERE model these sources are currently limited to paths aligned with the x,y,z coordinate directions.

33.17.22 Spatial Influence Factor

Scope: Laser Heating

Spatial Influence Factor {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	0.0

Summary Defines a distance from beam focus for which an element may be activated.

Description A multiplier which expands the bounding source geometry. When used with ACTIVATION TEMPERATURE and ACTIVATION_USER_FUNCTION thermal conductivity elements within bounded region become candidates for temperature activation. Used in conjunction with ACTIVATION_HEMISPHERE or ACTIVATION_SPHERE source models.

33.17.23 Speed

Scope: Laser Heating

Speed {=|are|is} *EquationName*

Parameter	Value	Default
<i>EquationName</i>	string	undefined

Summary Specifies the rate at which the laser beam moves across the body.

Description The speed at which the beam moves in traversing the specified geometric path. When a geometric path function is provided the speed is internally computed based upon the START TIME and STOP TIME.

33.17.24Start Time

Scope: Laser Heating

Start Time {=*|are|is*} *Value*

Parameter	Value	Default
<i>Value</i>	<i>real</i>	<i>undefined</i>

Summary Specifies the time at which the laser beam is activated.

33.17.25Stop Time

Scope: Laser Heating

Stop Time {=*|are|is*} *Value*

Parameter	Value	Default
<i>Value</i>	<i>real</i>	<i>undefined</i>

Summary Specifies the time at which the laser beam is deactivated.

33.17.26Travel Semi Axis

Scope: Laser Heating

Travel Semi Axis {=*|are|is*} *travel_semiaxis*

Parameter	Value	Default
<i>travel_semiaxis</i>	<i>real</i>	<i>undefined</i>

Summary Defines the travel direction semiaxis for the ellipsoidal, double ellipsoidal and rectangular source model.

33.17.27 Use Old Temperature

Scope: Laser Heating

Use Old Temperature `{=|are|is}` *Value*

Parameter	Value	Default
<i>Value</i>	<code>{false true}</code>	undefined

Summary Whether or not to use the previous time-step temperature to calculate the activation

Description If true, the previous time-step temperature will be used instead of the current temperature in updating the activation field. Prevents the thermal conductivity field from varying iteration to iteration

33.17.28 Use Toggle Block

Scope: Laser Heating

Use Toggle Block *ToggleName* [`{@|at|for|in|on|over}` *ElementBlockList...*]

Parameter	Value	Default
<i>ToggleName</i>	string	undefined

Summary Specification for toggling entities in the computational model based on Toggle Block parameters. When used at the region level, the list of element blocks to be toggled must be provided. Otherwise a listing of entities is not needed as the Toggle Block will be associated with the command line or the enclosing command block.

33.17.29 Width Semi Axis

Scope: Laser Heating

Width Semi Axis `{=|are|is}` *width_semiaxis*

Parameter	Value	Default
<i>width_semiaxis</i>	real	undefined

Summary Defines the width direction semiaxis for the ellipsoidal, double ellipsoidal and rectangular laser source model.

33.18. CLOSED SURFACE VOLUME

Scope: Equation System

Begin Closed Surface Volume *ModelName*

Add Surface *SurfaceList...*

Utility Group {=|are|is} *Frequency*

End

Summary This command block defines the parameters for computation of the volume of a closed surface. The computed volume is available as a global variable with name *modelName*.

Description Defines a means for computing the volume of a closed surface and associate it with name *modelName*.

33.18.1. Add Surface

Scope: Closed Surface Volume

Add Surface *SurfaceList...*

Parameter	Value	Default
<i>SurfaceList</i>	string...	undefined

Summary Adds surfaces by name, (*surface_id*), to a mesh extent list.

Description This line command is used to add surfaces to a mesh extent list. In Exodus II, surfaces are specified as side sets, that have a global integer identifier. For example, side set 12 would be added by this line command using the surface name *surface_12*. Note that in SIERRA, each element of an array of strings must be separated by whitespace.

33.18.2. Utility Group

Scope: Closed Surface Volume

Utility Group {=|are|is} *Frequency*

Parameter	Value	Default
<i>Frequency</i>	{begin_nonlinear_solve end_nonlinear_solve manually_run post_accept_solution post_iterate post_linear_solve post_nonlinear_solve pre_iterate pre_linear_solve pre_nonlinear_solve run_initially run_once run_post_linear_system_initialization run_post_mesh_mod}	undefined

Summary Sets the point in the execution to evaluate utility

33.19. REAL AND INTEGER DATA ACCESS - DATA BLOCK

Aria provides a means by which a user can define problem dependent real and integer data to be used by user subroutines. General commands for usage of this capability are described in the chapter on Data Block [7](#). For users of the Calore code, these data blocks occupy the role formerly served by REAL DATA and INTEGER DATA commands in that code while providing some additional flexibility. Data Blocks can be used both within Calore-style boundary condition, initial condition, volume heat command blocks as well as in Calore-style user subroutines.

Data Block information can be accessed by Calore-style subroutines in two ways. The information can be directly accessed through user query functions referencing the Data Block by name within a user subroutine or referencing indirectly by implicit association with a command block, again through user queries.

In either event, data extraction within the user subroutine is accomplished in the same manner but using different interfaces. Accessing Data Block values from a user subroutine involves a simple three-step extraction sequence

1. Define a variable of data type associated with the values one wishes to extract from the Data Block.
2. Define a string with the name of the values to be extracted.
3. Perform a user_query request to retrieve the data from the Data Block.

For FORTRAN-like C subroutines the data type translates to RealArray1d, RealArray2d, IntArray1d or IntArray2d. Usage of this information within a user subroutine is best described using simple examples that use single values from the data block. What remains here is to describe the various user_query requests of data block information for FORTRAN-like C subroutines. Use of Data Block in FORTRAN subroutines is discussed in Section [33.26](#).

33.19.1. Data Block Referenced From Command Block

In order to reference a Data Block from a command block the Data Block must first be bound to the scope of the command block by including the *USE DATA BLOCK* directive within the scope of the command block. The choice of scope will dictate the type of user query function used to access the Data Block information.

33.19.1.1. Data Block Referenced From Region Command Block

When the Data Block is defined within the Region scope this information can be made available to the user subroutine system by supplying the *USE DATA BLOCK* directive at the Region scope. From the user subroutine, this data can then be retrieved for usage without knowledge of the data block name. Let the input file contain a data block definition within the Region scope

```
Begin Procedure my_procedure
.
begin data block flux_data
    real flux = -0.05
end data block flux_data
.
Begin Aria Region myregion
.
    use data block flux_data
.
    Begin heat flux boundary condition freddy
        add surface surface_4
        element subroutine = aocal_heat_flux
    End
.
End Aria Region

End Procedure
```

Within the user subroutine source code the values can then be retrieved from the Data Block by following the extraction sequence targeting Region data

```
RealArray1d real_array;
sierra::String flux_label("flux");

user_query.getUserRealRegionData(real_array, flux_label);

Real flux_value = real_array(0);
```

Here we note the presence of *Region* in the user_query and the user subroutine becomes

```

int
aocal_heat_flux(
UserQuery &                user_query,
ElementIds                 element_ids,
Int                        num_elements,
Int                        num_integration_points,
Int                        spatial_dimension,
CoordinateElementIntegrationPoints coordinates,
TemperatureElementIntegrationPoints temperature,
ScalarElementIntegrationPoints scalar)
{
  RealArray1d real_array;
  sierra::String flux_label("flux");

  user_query.getUserRealRegionData(real_array, flux_label);

  Real flux_value = real_array(0);

  for (int q = 0; q < num_integration_points; ++q)
  {
    for (int i = 0; i < num_elements; ++i)
    {
      scalar(i, q) = flux_value;
    }
  }
  return 0;
}

```

Here we note that the Data Block name, *flux_data*, appeared only at the Region scope of the input.

33.19.1.2. Data Block Referenced From BC, IC or Volume Source Command Block

Data Block information can be made accessible to boundary condition, initial condition or volumetric source user subroutines defined within command blocks. This is accomplished by simply supplying the *USE DATA BLOCK* directive at the command block scope. Returning to the example, the *USE DATA BLOCK* enables the association of *flux_data* with the *aocal_heat_flux* user subroutine.

```

Begin Procedure my_procedure
.
  begin data block flux_data
    real flux = -0.05
  end data block flux_data
.
  Begin Aria Region myregion

```



```

      .
      use data block flux_data
      .
      Begin heat flux boundary condition freddy
        add surface surface_4
        element subroutine = aocal_heat_flux
        use data block flux_data
      End
      .
End Aria Region

End Procedure

```

Within the user subroutine source code the values can then be retrieved from the Data Block by following the extraction sequence

```

RealArray1d real_array;
sierra::String flux_label("flux");

user_query.getUserRealInstanceData(real_array, flux_label);

Real flux_value = real_array(0);

```

Here we note the presence of *Instance* in the user_query and the user subroutine becomes

```

int
aocal_heat_flux(
  UserQuery &                user_query,
  ElementIds                element_ids,
  Int                      num_elements,
  Int                      num_integration_points,
  Int                      spatial_dimension,
  CoordinateElementIntegrationPoints coordinates,
  TemperatureElementIntegrationPoints temperature,
  ScalarElementIntegrationPoints scalar)
{
  RealArray1d real_array;
  sierra::String flux_label("flux");

  user_query.getUserRealInstanceData(real_array, flux_label);

  Real flux_value = real_array(0);

  for (int q = 0; q < num_integration_points; ++q)

```

```

{
  for (int i = 0; i < num_elements; ++i)
  {
    scalar(i, q) = flux_value;
  }
}
return 0;
}

```

33.19.1.3. Data Block Referenced From Material Command Block

The Data Block information can be made automatically available for material property evaluations employing user subroutines.

```

Begin Procedure my_procedure
.
begin data block k_data
  real my_K = 4.0
end data block k_data

begin Aria material my_material
.
  use data block flux_data
  thermal conductivity = calore_user_sub name = aocal_elem_cond type=element
.
end Aria material my_material
.
Begin Aria Region myregion
.
.
.
End Aria Region

End Procedure

```

Within the user subroutine source code the values can then be retrieved from the Data Block by following the extraction sequence

```

RealArray1d real_array;
sierra::String k_label("my_k");

user_query.getUserRealMaterialData(real_array, k_label);

Real k_value = real_array(0);

```

Here we note the presence of *Material* in the user_query and the user subroutine becomes

```
int
aocal_elem_cond(
  UserQuery & user_query,
  ElementIds element_ids,
  Int num_elements,
  Int num_integration_points,
  Int spatial_dimension,
  CoordinateElementIntegrationPoints coordinates,
  TemperatureElementIntegrationPoints temperature,
  ScalarElementIntegrationPoints cond)
{
  RealArray1d real_array;
  sierra::String k_label("my_k");

  user_query.getUserRealMaterialData(real_array, k_label);

  Real k_value = real_array(0);

  for (int q = 0; q < num_integration_points; ++q)
  {
    for (int i = 0; i < num_elements; ++i)
    {
      cond(i, q) = k_value(i);
    }
  }
  return 0;
}
```

The previous examples demonstrated association of Data Block information with the scope of a command block in order to avoid explicit specification of the Data Block name. However, alternative access methods also allow one to retrieve Data Block information more directly by explicitly supplying the Data Block name in the user_query operation rather than by supplying the *USE DATA BLOCK* directive at a given scope. A complete list of the various query operations is included in the section on For the examples previously described this style of queries translate to

```
user_query.getUserRealData(real_array, flux_label, "flux_data");
and
user_query.getUserRealData(real_array, k_label, "k_data");
```

For the simple examples provided the type of user_query is a personal choice. However, an overall strategy for usage of Data Block information within user subroutines often dictates the type of user_query employed. Considerations in this strategy often include the number of subroutines that will

be supported and how the subroutines are managed. As an example one could configure all input files in the same way and selectively load subroutines that employ the same interface. Again we emphasize that the different methods of accessing Data Block information differ only by the interface used to obtain the data definition.

33.19.2. Data Block Referenced By Line Command

For commands not defined within a Command Block the Data Block can still be used to specify parameters for that line command using the *USE DATA BLOCK* directive. The data block parameters are placed in the line command as if it was a command block.

Creating the data block in the region using the data block command block:

```
begin data block bc_flux
  real h = 300.0
  integer t_ref = 1
end
```

its data can be accessed using a command line like

```
BC Flux for Energy on no_slip_boundary = Nat_Conv use data block bc_flux
```

which is equivalent to

```
BC Flux for Energy on no_slip_boundary = Nat_Conv H=300.0 T_ref=1
```

This architecture allows the data to be consistently used with boundary conditions for several equations.

33.20. USER SUBROUTINES AND VARIABLES

Aria offers support of C language Calore-style user subroutines and FORTRAN user subroutines through fixed-interface signatures. Callback data query requests from the subroutines are also supported, again through fixed-interface function signatures. It is important to note that Calore-style subroutines provide some level of variable-type safety and bounds checking that is not supported with FORTRAN subroutines.

Some of the subroutine interface callback function calls enable writing to user defined node, element or face Fields, which can be used internal to the code or output to the results file. Generally speaking, values made available to a subroutine through its calling interface are quadrature point values. Internally the application code can either process all quadrature points at one time or all at once. Hence

in order to save user fields that are populated within the subroutine one should understand exactly how the subroutine is being processed before relying upon data saved from within the subroutine.

Usage of both C language Calore-style [33.21](#) and FORTRAN subroutines [33.25](#) within Aria are described in the sections which follow.

33.21. C CALORE-STYLE USER SUBROUTINES AND VARIABLES

Aria supports the use of C language user subroutines. Historically, the Calore heat transfer code supported only FORTRAN subroutines. In later releases of Calore, support of FORTRAN subroutines has continued but now C language style user functions are supported as well. With only minor syntactical changes these C language user functions support the full functionality of FORTRAN subroutines. When written in a general manner, the C Calore-style user functions can be used in either Calore or Aria. The overall nature of the Calore style user function is described below and is followed by a simple example of its use with the DATA_BLOCK utility. In what follows, the terms "signature", "argument list", and "interface" are synonyms for the list of variables and arrays that are passed into a user subroutine. Furthermore, the term Calore style user subroutine will be loosely associated with the term Calore style user functions.

An Aria Calore-style user subroutine must be a text file of suffix .C. In contrast to the static link approach formerly used in the Calore code, here the file contents are made available to the application as a dynamically linked function using the same procedure as for Aria User Plugin functions [18](#). For example, a file named Aocal_density.C the file will be referenced from the Aria input file using the line command

```
load user plugin file ./Aocal_Density.so
```

Note that, since Aocal_density.C is a filename, its input file name is case-sensitive, and considerations must be made concerning its location path. The user is free to name the file and subroutines in any way, provided the name is consistent with compiler and operating system limitations. For example, special characters such as '*' and ';' should be avoided. Finally actual use of the function by the application is triggered by association of the "model name", calore_user_sub and the user subroutine name in particular command line, i.e. initial condition, source or boundary condition.

Multiple user subroutines for a given parameter, e.g. conductivity, may be defined. If user conductivity for two materials, say gold and silver was needed then one could write a subroutine for each of the two conductivities. Each subroutine must have a different name in order to be properly referenced, and each must conform to the required call signature. This approach eliminates the need for "if-then-else if" subroutine constructs defining specific behavior for a particular material, volume or surface.

Regardless of the information included in the call signature, the need will arise to access data that is not currently provided by the subroutine arguments. Altering the call signature to fulfill that need would require extensive changes to Calore style user subroutines. Furthermore, backward compatibility

between code versions would be lost, since all subroutines currently using an older interface would no longer function properly with a newer interface.

For reasons previously stated, the design philosophy behind the user subroutine capability in both Calore and Aria is that the call signature will kept to a minimum. An advantage of this approach is that it provides a clean, simple interface. A disadvantage is that it limits the information that a user may access. This inherent disadvantage is addressed by employing query functions for use within the subroutines. Thus if one wishes to access additional information from the user subroutine, it becomes a relatively straightforward task to implement a new query function to provides the required data. In this way, no changes are required of the subroutine signature, and backward compatibility is maintained. Users having specialized needs of data access should consider implementations of native Aria user plugin functions instead [18](#).

An attempt has been made to ease the transition from Calore user subroutines to Calore style user subroutines in Aria by providing common C interfaces to the two codes. Two versions of the subroutine signatures are provided here, the first more reminiscent of a FORTRAN interface and the other being a C language interface.

In many applications several user subroutines are being used in a single simulation. In this regard it is worth mentioning that with both the FORTRAN and C-style usage one must register the various subroutines/functions with the application before they can be recognized and accessed by the application. This registration establishes an association between the a code interface, function signature and the name by which the function will be referenced from the input file command lines. For the Aria C-style subroutines the registration can be done in one of two ways, with individual registration lines for each subroutine or by using a single function to register one or more subroutines.

Subroutine registration amounts to adding a line to the subroutine source file with a line declaring the signature corresponding to the subroutine containing its registered name and a pointer to the user subroutine. As an example, if a user subroutine file named Aocal_Density.C contained a function named my_density and one wished to reference the function as bulk_density one could register the subroutine as:

```
RegisterFunction(ElemUserSubC, my_density, "bulk_density");
```

Alternatively one could also use a more obscure form of the registration

```
sierra::Aria::AcalElemUserSubC<&my_density>::Register distr_register("bulk_density");
```

Again we note that both registration methods contain the application interface signature, the function pointer and the name one wishes to associate the function with from the input file. This registration causes the subroutine to be recognized within the function name registry. Since the compiled function name is not available prior to compilation, the registration line should appear after the subroutine function in the subroutine source code.

Access to the subroutine from within the application is enabled using the following command line:

```
load user plugin file ./Aocal_Density.so
```

Subroutine registration using a single function can be performed simply by wrapping the individual registrations previously described in a function. Using the subroutine name previously discussed the corresponding registration using a function call could be obtained using the following module

```
extern "C"
void
bulk_prop_subs()
{
    RegisterFunction(ElemUserSubC, my_density, "bulk_density");
}
```

As in the case of single line subroutine registration compiled function names are not available prior to compilation, thus the registration function must appear in the subroutine source code after the subroutine function being registered.

Access to the subroutine from within the application is enabled using the following command line:

```
load user plugin file ./Aucal_Density.so using function bulk_prop_subs
```

One can also avoid using a named registration module by using the default function name *dl_register*,

```
extern "C"
void
dl_register()
{
    RegisterFunction(ElemUserSubC, my_density, "bulk_density");
}
```

where once again access to the subroutine from within the application is enabled without using a function name

```
load user plugin file ./Aucal_Density.so
```

Finally in order to access the subroutine from the input file according to its usage from the Aria material command block one would reference the subroutine as

```
Begin Aria Material bulk
.
.
density = Calore_User_Sub name=bulk_density type = element
.
End Aria Material bulk
```

33.22. FORTRAN-LIKE C INTERFACES

While Calore style user subroutines could be defined to supply many different parameters, only five different signatures are provided in Aria. These signatures characterize the argument lists by which the subroutine interacts with the code. The various subroutine signatures are denoted as:

- node signature [33.22.1](#)
- element signature [33.22.2](#)
- scaled element signature [33.22.3](#)
- reference temperature dependent element signature [33.22.4](#)
- scaled, reference temperature dependent element signature [33.22.5](#)
- tensor thermal conductivity signature [33.22.6](#)
- transformed tensor thermal conductivity signature [33.22.7](#)
- reaction rate signature [33.22.8](#)
- auxiliary variable signature [33.22.9](#).

The node subroutine signature is generally used for Dirichlet boundary conditions. The element signature is used to define material properties, heat flux and heat transfer coefficients. The reference temperature dependent signatures are used primarily for defining heat transfer coefficients. The last two signatures are specific to the CHEMEQ chemistry package. Scaled signatures are used to combine the basic user subroutine functionality combined with Field variable scaling. The different subroutine call signatures are outlined below. With the exception of the *node* signature, these signatures will be used for subroutines that operate on quadrature point values.

It is worth noting that the purpose of the user subroutine is simply to provide an evaluation of needed values based upon the data supplied through the subroutine interface. In many cases the data supplied to the user subroutine is more than what is necessary for the targeted evaluation. Here the user is free to perform the evaluation using only the information needed to perform the target evaluation. Note that only the last argument of the interface is associated with values returned to the application code, the remaining arguments represent non-modifiable data local to the element, face or node being processed.

33.22.1. Node Signature

For example, to specify a temperature Dirichlet boundary condition, the node signature is

```
/**
 * Prototype for the nodal signature.
 *
 * user_query: query function
 * node_id:    array of global ids of the nodes
```



```

* num_nodes:          number of nodes in the array
* spatial_dimension:  number of nodes in the array
* coordinate_array:   array of coordinates of the current nodes
* node_data_array:    array of value to be calculated
*/
Int
AcalNodeUserSubC(
    UserQuery &      user_query,
    Int              node_id,
    Int              num_nodes,
    Int              spatial_dimension,
    CoordinateNodes  coordinate_array,
    DataNodes        node_data_array);

```

The node subroutine for a Dirichlet boundary condition could be invoked using a command line:

```
BC Dirichlet for Temperature on surface_4 = Calore_User_Sub name=dirich_bc type=node
```

A simple example using the nodal signature subroutine is as follows:

```

#include <utility>
#include "math.h"

#include "Aria_Calore_User_Sub_Support.h"

int
dirichsub(
    UserQuery &              user_query,
    Int nodeid,
    Int nnode,
    Int spatial_dimension,
    CoordinateNodes coords,
    DataNodes temperature)
{
    for (int i = 0; i < nnode; ++i) {
        Real ynode = coords(1,i);
        if ( ynode < 0.5 ) {
            temperature(i) = 1.5;
        } else {
            temperature(i) = 0.1;
        }
    }
    return 0;
}

```

```
RegisterFunction(NodeUserSubC, dirichsub, "dirich_bc");
```

33.22.2. Element Signature

For density, specific heat, volumetric heat source, surface heat flux and most surface heat transfer coefficients defined via user subroutine one will use an element based call signature. Additionally, for problems with isotropic thermal conductivity one can supply the single value of conductivity using the element signature. In either case the subroutine will be used to assign quadrature point evaluations. That is, the coordinate_array values can be used to compute node_data_array values. The call signature for scalar element-based user subroutines is

```
/**
 * Prototype for the scalar element signature.
 *
 * user_query: query function
 * elem_ids: pointer to the global id of the current element
 * num_elements: pointer to the number of elements in the workset
 * nint: pointer to the number of gauss points
 * coordinate_array: pointer to the coordinates of the current node (3, nelem, nint)
 * temperature_array: pointer to the temperature (nelem, nint)
 * elem_data_array: pointer to the values to be calculated (nelem, nint)
 */
Int
AcalElemUserSubC(
    UserQuery &                user_query,
    ElementIds elem_ids,
    Int                        num_elements,
    Int                        nint,
    Int                        spatial_dimension,
    CoordinateElementIntegrationPoints coordinate_array,
    TemperatureElementIntegrationPoints temperature_array,
    ScalarElementIntegrationPoints element_data_array)
```

The scalar element subroutine signature is supported for all element-centric evaluations. An example of specifying the element user subroutine to be used for density is as follows:

```
Begin Aria Material sticky_icky
    density = calore_user_sub name = aocal_density type=element
    specific heat = constant cp = 385.0
    thermal conductivity = constant k = 400.0
    heat conduction = basic
End Aria Material sticky_icky
```

A simple example using the scalar element signature subroutine is as follows:

```
#include <utility>
#include "math.h"

#include "Aria_Calore_User_Sub_Support.h"

int
aucal_density(
    UserQuery &                user_query,
    ElementIds                elemid,
    Int                        nelem,
    Int                        nint,
    Int                        spatial_dimension,
    CoordinateElementIntegrationPoints coords,
    TemperatureElementIntegrationPoints temp,
    ScalarElementIntegrationPoints rho)
{
    // Load the density array
    for (int j = 0; j < nint; ++j) {
        for (int i = 0; i < nelem; ++i) {
            rho(i,j) = 0.1 + temp(i,j);
        }
    }
    return 0;
}

RegisterFunction(ElemUserSubC, aucal_density, "aucal_density");
```

The same methodology used in the previous example is valid when defining isotropic thermal conductivity that depends upon other local state information. Here all directions are material principal directions so thermal conductivity will be a single value for each quadrature points of an element.

Note that in this example the user subroutine name is specified within quotation marks. As per [2.6.1.3](#) the quotation marks are only required when the name by which the subroutine is referenced by from the input file begins with a number. Otherwise quotation marks are not needed in the specification of user subroutine name.

```
BEGIN ARIA MATERIAL my_mat
    density = constant rho = 0.1
    specific heat = constant cp = 385.0
    thermal conductivity = calore_user_sub name="2Dcond" type = element
    heat conduction = basic
END ARIA MATERIAL my_mat
```

For isotropic conductivity an example of the associated user subroutine and its function registration would be:

```
#include <utility>
#include "math.h"

#include "Aria_Calore_User_Sub_Support.h"

int
mycond(
    UserQuery & user_query,
    ElementIds element_ids,
    Int num_elements,
    Int num_integration_points,
    Int spatial_dimension,
    CoordinateElementIntegrationPoints coordinates,
    TemperatureElementIntegrationPoints temperature,
    ScalarElementIntegrationPoints cond)
{
    for (int q = 0; q < num_integration_points; ++q)
    {
        for (int i = 0; i < num_elements; ++i)
        {
            cond(i, q) = 400.0;
        }
    }

    return 0;
}

RegisterFunction(ElemUserSubC, mycond, "2Dcond");
```

33.22.3. Scaled Element Signature

A variant of the element subroutine employs an additional Field variable that is supplied through the user interface. Here the Field variable is used to perform some logical decision on how the result is assigned and the name of the Field variable to be used is specified from the input file. The call signature for scaled scalar element-based user subroutines is

```
/**
 * Prototype for the scaled scalar element signature.
 *
 * user_query: query function
 * elem_ids: pointer to the global id of the current element
```

```

* num_elements: pointer to the number of elements in the workset
* nint: pointer to the number of gauss points
* coordinate_array: pointer to the coordinates of the current node (3, nelelem, nint)
* temperature_array: pointer to the temperature (nelem, nint)
* scaling_array: pointer to the scaling array(nelem, nint)
* elem_data_array: pointer to the values to be calculated (nelem, nint)
*/
Int
AcalScaledElemUserSubC(
    UserQuery &                                user_query,
    ElementIds elem_ids,
    Int                                                num_elements,
    Int                                                nint,
    Int                                                spatial_dimension,
    CoordinateElementIntegrationPoints coordinate_array,
    TemperatureElementIntegrationPoints temperature_array,
    ScalarElementIntegrationPoints scaling_array,
    ScalarElementIntegrationPoints element_data_array)

```

The Scaled Element Signature is supported only for all element property evaluations. A corresponding entry in the convective flux boundary condition command block might be:

```

begin convective flux boundary condition convect
  add surface surface_2
  reference temperature = 180.0
  scaled convective coefficient subroutine is aocal_htcoef fieldname = c0
end convective flux boundary condition convect

```

An example of the scaled scalar element signature subroutine is as follows:

```

#include <utility>
#include "math.h"

#include "Aria_Calore_User_Sub_Support.h"

int
aocal_htcoef(
    UserQuery &                                user_query,
    ElementIds faceid,
    int nelemf,
    int nint,
    int dimension,
    CoordinateElementIntegrationPoints coords,
    TemperatureElementIntegrationPoints t,

```

```

    ScalarElementIntegrationPoints scaling,
    ScalarElementIntegrationPoints htc)
{
    for (int j = 0; j < nint; ++j)
    {
        for (int i = 0; i < nelemf; ++i)
        {
            Real x = coords(0,i,j);
            Real y = coords(1,i,j);
            Real r = std::sqrt(x*x+y*y);
            Real val = 0.0;
            Real c0 = scaling(i,j);
            if( c0 > 0.1 ) {
                val = 45.0;
            } else {
                val = 20.0 * r;
            }
            htc(i,j) = val;
        }
    }

    return 0;
}

RegisterFunction(ScaledElemUserSubC, aocal_htcoef, "aocal_htcoef");

```

One should note that the number of arguments for the Scaled Element Signature and Reference Temperature Dependent Element Signature are identical. Attempts to use a user subroutine in the wrong context will be detected while parsing the input file.

33.22.4. Reference Temperature Dependent Element Signature

In some problems the surface heat transfer coefficient is determined to be a function of reference temperature rather than just the surface temperature. One example of this would be when modeling problems of natural convection where one computes a Rayleigh number based upon the difference between surface temperature and reference temperature to determine the local Nusselt number and a local heat transfer coefficient. In these cases it is sometimes more convenient to utilize an existing model for reference temperature and use those values to evaluate the heat transfer coefficient based upon additional criteria within a user subroutine. Here the interface for the Element Signature is modified to also supply interpolated values of the heat transfer coefficient at the quadrature points with the following call signature

```
/**
```

```

* Prototype for the scalar reference temperature dependent
* heat transfer coefficient signature.
*
* user_query: query function
* elem_ids: pointer to the global id of the current element
* num_elements: pointer to the number of elements in the workset
* nint: pointer to the number of gauss points
* coordinate_array: pointer to the coordinates of the current node (3, nelem, nint)
* ref_temperature_array: pointer to the reference temperature (nelem, nint)
* temperature_array: pointer to the temperature (nelem, nint)
* elem_data_array: pointer to the values to be calculated (nelem, nint)
*/
Int
AcalElemUserSubHtC(
    UserQuery &                user_query,
    ElementIds elem_ids,
    Int                        num_elements,
    Int                        nint,
    Int                        spatial_dimension,
    CoordinateElementIntegrationPoints coordinate_array,
    ScalarElementIntegrationPoints ref_temperature_array,
    TemperatureElementIntegrationPoints temperature_array,
    ScalarElementIntegrationPoints element_data_array)

```

The Reference Temperature Dependent Element Signature is currently supported only for the heat transfer coefficient. A corresponding entry in the convective flux boundary condition command block might be:

```

begin convective flux boundary condition convect
  add surface surface_2
  reference temperature = 180.0
  ref temp convective coefficient subroutine is aocal_htcoef
end convective flux boundary condition convect

```

The corresponding implementation of the reference temperature heat transfer coefficient subroutine is shown below.

```

#include <utility>
#include "math.h"

#include "Aria_Calore_User_Sub_Support.h"

int
aocal_htcoef(

```

```

UserQuery &                                user_query,
ElementIds faceid,
int nelemf,
int nint,
int dimension,
CoordinateElementIntegrationPoints coords,
ScalarElementIntegrationPoints ref_temp,
TemperatureElementIntegrationPoints temp,
ScalarElementIntegrationPoints htc)
{
  Real c1 = 1.0+std::pow(std::pow((0.492/.68),(9./16.)),(8./27));
  Real c2 = 30.0e-3/2.2;
  for (int j = 0; j < nint; ++j)
  {
    for (int i = 0; i < nelemf; ++i)
    {
      Real Ra = 9.0e6*(temp(i,j)-ref_temp(i,j));
      Real Nu = std::pow((0.825+ 0.387*std::pow(Ra,(1./6)))/c1),2.0);
      htc(i,j) = c2 * Nu;
    }
  }
  return 0;
}

RegisterFunction(ElemUserSubHtcC, aocal_htcoef, "aocal_htcoef");

```

33.22.5. Scaled Reference Temperature Dependent Element Signature

In cases where the surface heat transfer coefficient is a function of reference temperature the coefficient and one wishes to either scale the heat transfer coefficient or assign it based upon values of another variable, the heat transfer coefficient can be defined via user subroutine using yet another alternative call signature is

```

/**
 * Prototype for the scaled scalar reference temperature dependent
 * heat transfer coefficient signature.
 *
 * user_query: query function
 * elem_ids: pointer to the global id of the current element
 * num_elements: pointer to the number of elements in the workset
 * nint: pointer to the number of gauss points
 * coordinate_array: pointer to the coordinates of the current node (3, nele, nint)

```



```

* ref_temperature_array: pointer to the reference temperature (nelem, nint)
* temperature_array: pointer to the temperature (nelem, nint)
* scale_elem_data_array: pointer to the scaling values (nelem, nint)
* elem_data_array: pointer to the values to be calculated (nelem, nint)
*/
Int
AcalScaledElemUserSubHtcc(
    UserQuery &                                user_query,
    ElementIds element_ids,
    Int                                              num_elements,
    Int                                              num_integration_points,
    Int                                              spatial_dimension,
    CoordinateElementIntegrationPoints coordinate_array,
    ScalarElementIntegrationPoints ref_temperature_array,
    TemperatureElementIntegrationPoints temperature_array,
    ScalarElementIntegrationPoints scaling_array,
    ScalarElementIntegrationPoints flux_array)

```

The Scaled Reference Temperature Dependent Element Signature is currently supported only for the heat transfer coefficient. A corresponding entry in the convective flux boundary condition command block might be:

```

begin convective flux boundary condition convect1
  add surface surface_1
  reference temperature = 215.0
  scaled ref_temp convective coefficient subroutine = aocal_htcoef fieldname = c0
end convective flux boundary condition convect1

```

A simple example using the scaled reference temperature heat transfer coefficient signature subroutine is as follows:

```

#include <utility>
#include "math.h"

#include "Aria_Calore_User_Sub_Support.h"

int
aocal_htcoef(
    UserQuery &                                user_query,
    ElementIds faceid,
    int nelem,
    int nint,
    int dimension,
    CoordinateElementIntegrationPoints coords,

```

```

ScalarElementIntegrationPoints ref_temp,
TemperatureElementIntegrationPoints temp,
ScalarElementIntegrationPoints scaling,
ScalarElementIntegrationPoints htc)
{
    for (int j = 0; j < nint; ++j)
    {
        for (int i = 0; i < nelem; ++i)
        {
            Real val = 0.0;
            Real c0 = scaling(i,j);
            Real tref = ref_temp(i,j);
            if( c0 > 0.1 ) {
                val = 45.0*tref*c0;
            } else {
                val = 10.0 * tref;
            }
            htc(i,j) = val;
        }
    }

    return 0;
}

```

```

RegisterFunction(ScaledElemUserSubHtcC, aocal_htcoef, "aocal_htcoef");

```

33.22.6. Tensor Thermal Conductivity Signature

When the thermal conductivity is anisotropic and can be easily defined in the Cartesian coordinate frame one can specify the thermal conductivity tensor with a user subroutine. The call signature for anisotropic tensor thermal conductivity user subroutines is

```

/**
 * Prototype for the tensor element conductivity signature.
 *
 * user_query: query function
 * elem_ids: pointer to the global id of the current element
 * num_elements: pointer to the number of elements in the workset
 * nint: pointer to the number of gauss points
 * coordinate_array: pointer to the coordinates of the current node (3, nelem, nint)
 * temperature_array: pointer to the temperature (nelem, nint)
 * conductivity_array: pointer to the output principal conductivities (3, 3, nelem, nint)
 */
Int

```

```

AcalElemTensorUserSubC(
    UserQuery &                                user_query,
    ElementIds elem_ids,
    Int                                                num_elements,
    Int                                                nint,
    Int                                                spatial_dimension,
    CoordinateElementIntegrationPoints coordinate_array,
    TemperatureElementIntegrationPoints temperature_array,
    TensorElementIntegrationPoints conductivity_array);

```

In order to use this signature to assign the tensor thermal conductivity for a two dimensional problem the subroutine is first specified in the Aria material command block. Note that a tensor conductivity requires a generalized model of heat conduction.

```

Begin Aria Material mat1
.
    tensor thermal conductivity = calore_user_sub name = aocal_tensor_cond type=element_te
.
    heat conduction = generalized
End Aria Material mat1

```

A sample implementation of the corresponding user subroutine could be as shown below.

```

#include <utility>
#include "math.h"

#include "Aria_Calore_User_Sub_Support.h"

int
aocal_tensor_cond(
    UserQuery & user_query,
    ElementIds elemid,
    Int nelelem,
    Int nint,
    Int spatial_dimension,
    CoordinateElementIntegrationPoints coords,
    TemperatureElementIntegrationPoints temp,
    TensorElementIntegrationPoints cond)
{
    cond.fill(0.0);

    for (int j = 0; j < nint; ++j) {
        for (int i = 0; i < nelelem; ++i) {
            cond(0,0,i,j) = 400.0;

```

```

        cond(1,1,i,j) = 300.0;
    }
}
return 0;
}

```

```
RegisterFunction(ElemTensorUserSubC, aocal_tensor_cond, "aocal_tensor_cond");
```

Note that one could have just as easily defined this conductivity from the Aria material command block as:

```

BEGIN ARIA MATERIAL my_mat
.
    tensor thermal conductivity = constant t11=400.0 t22=300.0
    heat conduction = generalized
END ARIA MATERIAL my_mat

```

33.22.7. Transformed Tensor Thermal Conductivity Signature

When the thermal conductivity is anisotropic only in the reference frame of local coordinates the conductivity tensor must be transformed into the Cartesian reference frame for computation. Here the user subroutine will define the thermal conductivity tensor components and the principal directions associated with those components. The call signature for anisotropic tensor thermal conductivity user subroutines is

```

/**
 * Prototype for the tensor element principal conductivity
 * and principle direction orientation signature.
 *
 * user_query: query function
 * elem_ids: pointer to the global id of the current element
 * num_elements: pointer to the number of elements in the workset
 * nint: pointer to the number of gauss points
 * coordinate_array: pointer to the coordinates of the current node (3, nelem, nint)
 * temperature_array: pointer to the temperature (nelem, nint)
 * conductivity_array: pointer to the output principal conductivities (3, 3, nelem, nint)
 * principle_direction_array: pointer to the output principal directions (2, 3, nelem, nint)
 */
Int
AcalCondUserSubC(
    UserQuery &          user_query,
    ElementIds            elem_ids,
    Int                   num_elements,

```

```

Int                                nint,
Int                                spatial_dimension,
CoordinateElementIntegrationPoints coordinate_array,
TemperatureElementIntegrationPoints temperature_array,
ConductivityElementIntegrationPoints conductivity_array,
DirectionElementIntegrationPoints  principle_direction_array);

```

Usage of the transformed tensor conductivity subroutine is considerably more detailed than other subroutines. Here we consider an example where the conductivity is known within an element and the orientation of principle directions relative to the Cartesian frame is also known.




Figure 33.22-1.. Anisotropic conductivity Orientation within Cartesian frame.

Anisotropic Conductivity and Orientation from Input Data:

Note that here the data block is associated with thermal conductivity via the `data = cond_values` argument to thermal conductivity command line.

```
load user plugin file ./aniso.so
```

```
Begin data block cond_values
```

```
  real cond_data = ( 400.0, 200.0, 400.0, 0.0, 0.0, 0.0 )
```

```
  real cond_vec1 = ( 0.707107, 0.707107, 0.0 )
```

```
  real cond_vec2 = ( -0.707107, 0.707107, 0.0 )
```

```
End data block
```

```
Begin Aria Material my_material
```

```
  density = constant rho = 0.1
```

```
  tensor thermal conductivity = calore_user_sub name = aocal_aniso_cond \
```

```
    type = element_direction_tensor data = cond_values
```

```

    specific heat = constant cp = 385.0
    heat conduction = generalized
End Aria Material my_material

```

Included below is an example user subroutine implementation of anisotropic thermal conductivity. In this implementation the vectors are indicated as being supplied from the code interface, either from input file data or from the mesh database. Alternatively, one could conditionally define the orientation vector and thermal conductivity within the user subroutine itself. This approach potentially requires selection/identification of each element by spatial location.

Note that each of the modules contains the essential features, orientation vectors, normalization and conductivity values. Once these values are supplied then the transformation operations can be performed internal to the code. This examples also demonstrates the subroutine registration process.

```

Int
aocal_aniso_cond(
    UserQuery &                user_query,
    ElementIds                  objid,
    Int                          nelem,
    Int                          nint,
    Int                          spatial_dimension,
    CoordinateElementIntegrationPoints coords,
    TemperatureElementIntegrationPoints temperature,
    ConductivityElementIntegrationPoints elemCond,
    DirectionElementIntegrationPoints elemVec)
{
    RealArray1d cond_data(6);
    RealArray1d cond_vec2(3);
    RealArray1d cond_vec1(3);

    user_query.getUserRealInstanceData(cond_data, "cond_data");
    user_query.getUserRealInstanceData(cond_vec1, "cond_vec1");
    user_query.getUserRealInstanceData(cond_vec2, "cond_vec2");

    //      normalize the vectors
    Real rlen = std::sqrt(cond_vec1(0)*cond_vec1(0)
                          +cond_vec1(1)*cond_vec1(1)
                          +cond_vec1(2)*cond_vec1(2));

    cond_vec1(0) = cond_vec1(0) / rlen;
    cond_vec1(1) = cond_vec1(1) / rlen;
    cond_vec1(2) = cond_vec1(2) / rlen;

    rlen = std::sqrt(cond_vec2(0)*cond_vec2(0)
                    +cond_vec2(1)*cond_vec2(1)

```

```

        +cond_vec2(2)*cond_vec2(2));

cond_vec2(0) = cond_vec2(0) / rlen;
cond_vec2(1) = cond_vec2(1) / rlen;
cond_vec2(2) = cond_vec2(2) / rlen;

//    check orthonormality
Real rdot =  cond_vec1(0)*cond_vec2(0) + cond_vec1(1)*cond_vec2(1)
            + cond_vec1(2)*cond_vec2(2);

if( std::abs(rdot) > 1.0e-5 ) {
    arialog << "[ERROR] Principal directions specified "
            << " are not orthonormal" << endl;
    return;
}

for( Int e = 0; e<nelem; ++e )
{
    for( Int n=0; n<nint; ++n )
    {
        elemCond(0, 0, e, n) = cond_data(0);
        elemCond(1, 1, e, n) = cond_data(1);
        elemCond(2, 2, e, n) = cond_data(2);
        // these assignments are not necessary
        //    since the elemCond data is zeroed when subroutine is called
        elemCond(0, 1, e, n) = cond_data(3);
        elemCond(1, 0, e, n) = cond_data(3);
        elemCond(0, 2, e, n) = cond_data(4);
        elemCond(2, 0, e, n) = cond_data(4);
        elemCond(1, 2, e, n) = cond_data(5);
        elemCond(2, 1, e, n) = cond_data(5);

        elemVec(0, 0, e, n) = cond_vec1(0);
        elemVec(0, 1, e, n) = cond_vec1(1);
        elemVec(0, 2, e, n) = cond_vec1(2);

        elemVec(1, 0, e, n) = cond_vec2(0);
        elemVec(1, 1, e, n) = cond_vec2(1);
        elemVec(1, 2, e, n) = cond_vec2(2);
    }
}

return;
}

```

```
RegisterFunction(CondUserSubC, aocal_aniso_cond, "aocal_aniso_cond");
```

33.22.8. Chemistry Reaction Rate Signature

The call signature for the chemistry reaction rate subroutine is

```
/**
 * Prototype for the chemical reaction rate signature.
 *
 * user_query: query function
 * elem_id: element id
 * reaction_rates_array: reaction rates (output)
 * ak_array: kinetics coefficients (output)
 * temperature_array: temperature at the gauss points
 * species_array: species array
 * nint: number of gauss points on this element
 * num_species: number of species on this element
 * num_reactions: number of reactions on this element
 * steric_array: steric factors for each reaction
 * prex_array: log pre-exponential factors
 * aenergy_array: activation energies
 * amusp_array: concentration exponents
 */
Int
AcalChemRRUserSubC(
    UserQuery & user_query,
    Int elem_id,
    ReactionIntegrationPoints reaction_rates_array,
    ReactionIntegrationPoints ak_array,
    ConstIntegrationPoints temperature_array,
    ConstSpeciesIntegrationPoints species_array,
    Int nint,
    Int num_species,
    Int num_reactions,
    ConstReactions steric_array,
    ConstReactions prex_array,
    ConstReactions aenergy_array,
    ConstSpeciesReactions amusp_array);
```

33.22.9. Chemistry Auxiliary Variables Signature

The other chemistry subroutine type is the one that is used to manipulate auxiliary variables. The call signature for this subroutine is as follows


```

/**
 * This is the prototype for the chemical aux variable signature.
 *
 * user_query: query function
 * elem_id: element id
 * temperature_array: temperature at the gauss points
 * species_array: species array
 * aux_variables_array: auxiliary variable array (output)
 * nint: number of gauss points on this element
 * num_species: number of species on this element
 * num_reactions: number of reactions on this element
 * num_aux_variables: number of auxiliary variables on this element
 */
Int
AcalChemAVUserSubC(
    UserQuery & user_query,
    Int elem_id,
    ConstIntegrationPoints temperature_array,
    ConstSpeciesIntegrationPoints species_array,
    AuxVariablesIntegrationPoints aux_variables_array,
    Int nint,
    Int num_species,
    Int num_reactions,
    Int num_aux_variables);

```

We note that each of the chemistry subroutines operate on a single element at a time.

33.23. FORTRAN-LIKE C INTERFACE FUNCTIONS

A number of utility functions are supplied for use in the FORTRAN-like C functions. These utilities provide access to internal variables that one might wish to use in the C functions and enables manipulation of these Real and Integer variables to a certain extent. Examples of interface functions used to modify values would be for assignment of boundary condition, material data or global variables. Additionally, the interface functions provide access to values associated with data blocks. Details for usage of data block variables with user functions is briefly detailed in the paragraphs which follow.

Within the Aria code data blocks are generically known as *Resources* and the usage of specific *Resources* within the code are referred to as *Region* or *Instance*. Thus the appearance of *Resources*, *Region* or *Instance* in either the name or call signature of the interface function implies usage of a data block.

If an interface function is referenced within the input file with a `USE DATA BLOCK data_block_name` then that data block is in some sense bound to that scope and the data block variables become accessible without explicit reference to the data block name. When the `USE DATA BLOCK DATA data_block_name` specification appears in the Region scope a user subroutine

function can access the `data_block_name` variables using *Region* type call signatures. Likewise if the if the `USE DATA BLOCK data_block_name` specification appears within a material property, boundary condition or volume heat command block then user subroutine functions defined within that command block can access the `data_block_name` variables using *Instance* type call signatures.

A more general usage of data block variables within user subroutine functions requires explicit reference to the data block, a *Resource* argument, within the user interface function call signature. This type of interface call proves useful when one wishes to access data from more than one data block or when one wants to ensure which data block will be used.

When more than one data block will be used within a command block an alternative would be to provide the data block as a `data = data_block_name` argument in the feature specification. For example:

`Heat Transfer Coefficient = Calore_User_Sub name=hcoeff type=element data=data_block_name`. Of course, one could always employ this approach exclusively when dealing with data block variables in lieu of the `use data block data_block_name` model usage.

Some of the remaining user interface function calls will reference specific program variables such as time or spatial dimension which cannot be altered (i.e. they will return non-mutable, `const`, program data). In most cases the interface functions will either retrieve values for use in the subroutine or populate values that are communicated back to the code. Here any variables not supplied through the subroutine interface must be explicitly declared within the user subroutine. Access of internal variable values is accomplished using the name associated with the values.

User interface function calls are part of the application code that are accessible to the user subroutine only through the `user_query` facility. Note that many of the access functions are specific to the Aria Region, a material or a feature (i.e. boundary conditions or sources). As an example, in order to reference the `currentTime()` function the subroutine body would contain a call as indicated here.

```
int
your_subroutine_interface( UserQuery & user_query,
                           more_subroutine_arguments, . , . , . , . )
{
    int ierror = 0;
    .
    Real time = user_query.currentTime();
    .
    statements referencing time
    .
    return ierror;
}
```

Call signatures to the various user interface functions are provided below.

- Return the current solution time
double currentTime() const;

- Return the current time step size
double currentTimeStepSize() const;

- Return Instance Resource name
- Evaluate a user function (#values, x, y, function name)
void getFunctionValues(int, double *, double *, const String & name);

- Return Region Data Block values
void getUserRegionData(RealArray1d &real_array, const String & real_label,
 IntArray1d &int_array, const String & int_label);

- Update Region Data Block values
void putUserRegionData(RealArray1d &real_array, const String & real_label,
 IntArray1d &int_array, const String & int_label);

- Return Region Data Block double values
void getUserRealRegionData(RealArray1d &real_array, const String & real_label);

- Update Region Data Block double values
void putUserRealRegionData(RealArray1d &real_array, const String & real_label);

- Return Region Data Block Integer
void getUserIntRegionData(IntArray1d &int_array, const String & int_label);

- Update Region Data Block Integer values
void putUserIntRegionData(IntArray1d &int_array, const String & int_label);

- Return Feature Data Block values
void getUserInstanceData(RealArray1d &real_array, const String & real_label,
 IntArray1d &int_array, const String & int_label);

- Update Feature Data Block values
void putUserInstanceData(RealArray1d &real_array, const String & real_label,
 IntArray1d &int_array, const String & int_label);

- Return Feature Data Block double values
void getUserRealInstanceData(RealArray1d &real_array, const String & real_label);

- Update Feature Data Block double values
void putUserRealInstanceData(RealArray1d &real_array, const String & real_label);

- Return Feature Data Block Integer values

```

void getUserIntInstanceData(IntArray1d &int_array, const String & int_label);

- Update Feature Data Block Integer values
void putUserIntInstanceData(IntArray1d &int_array, const String & int_label);

- Return Material Data Block values
void getUserMaterialData(RealArray1d &real_array, const String & real_label,
                        IntArray1d &int_array, const String & int_label);

- Update Material Data Block values
void putUserMaterialData(RealArray1d &real_array, const String & real_label,
                        IntArray1d &int_array, const String & int_label);

- Return Material Data Block double values
void getUserRealMaterialData(RealArray1d &real_array, const String & real_label);

- Update Material Data Block double values
void putUserRealMaterialData(RealArray1d &real_array, const String & real_label);

- Return Material Data Block Integer values
void getUserIntMaterialData(IntArray1d &int_array, const String & int_label);

- Update Material Data Block Integer values
void putUserIntMaterialData(IntArray1d &int_array, const String & int_label);

- Return Material Data Block double values
void getUserRealMaterialData(double & real_value, const String & label);

- Update Material Data Block double values
void putUserRealMaterialData(double & real_value, const String & label);

- Return Material Data Block Integer values
void getUserIntMaterialData(int & int_value, const String & label);

- Update Material Data Block Integer values
void putUserIntMaterialData(int & int_value, const String & label);

- Retrieve a double face variable by name to an array
void getRealFaceVar(int id, const String & name, double * s);

- Retrieve a double element variable by name to an array
void getRealElemVar(int id, const String & name, double * s);

- Retrieve a double node variable by name to an array
void getRealNodeVar(int id, const String & name, double * s);

```

- Retrieve an Integer face variable by name to an array
`void getIntFaceVar(int id, const String & name, int * s);`

- Retrieve an Integer element variable by name to an array
`void getIntElemVar(int id, const String & name, int * s);`

- Retrieve an Integer node variable by name to an array
`void getIntNodeVar(int id, const String & name, int * s);`

- Update a double face variable by name from an array
`void putRealFaceVar(int id, const String & name, double * s);`

- Update a double element variable by name from an array
`void putRealElemVar(int id, const String & name, double * s);`

- Update a double node variable by name from an array
`void putRealNodeVar(int id, const String & name, double * s);`

- Update an Integer face variable by name from an array
`void putIntFaceVar(int id, const String & name, int * s);`

- Update an Integer element variable by name from an array
`void putIntElemVar(int id, const String & name, int * s);`

- Update an Integer node variable by name from an array
`void putIntNodeVar(int id, const String & name, int * s);`

- Retrieve the current time step number
`int currentTimeStepIndex();`

- Retrieve the spatial dimension
`int getSpatialDimension();`

- Retrieve the material name for the block or sideset being processed
`void materialName(String & meshpart_name);`

- Retrieve the name of the block or sideset being processed
`String getPartName(){ return m_block_name; }`

- Retrieve the material name of the contact sideset being processed
`void getContactMaterialName(int, String &);`

- Retrieve the material name of the contact sideset being processed
`void getContactElement(const int *, int *, int *);`

- Retrieve the predicted temperature in this solution step
void nodePredT(int id, double *);

- Retrieve the temperature in the previous solution step
void nodePrevT(int id, double *);

- Retrieve the temperature time derivative at the Gauss points
void TDotElementGauss(int id, double * tDot);

- Retrieve the double auxiliary variable values
void getAuxVar(int id, double * a);

- Set the double auxiliary variable values
void setAuxVar(AuxVariablesIntegrationPoints aux);

- Return the number of auxiliary variable
int getNumAuxVars();

- Return the species variables
void getSpecies(int id, double * s);

- Return the volume of the current volume element
bool getElementVolume(int id, double * value);

- Return the mass of the current volume element
bool getElementMass(int id, double * value);

- Return the index of a field within a set of auxiliary variables
bool getFieldIndex(const double * fieldPtr, int * index, const String & name);

- Return a single Encore global variable
Real or Int getEncoreGlobalVariable(const String &name)

- Return a vector Encore global variable
void getEncoreGlobalVariable(Real or Int value, const String &name)

- Return a global variable
Real or Int getGlobalVariable(const String &name)

- Return a global variable to the given value storage
void getGlobalVariable(Real or Int value, const String &name)

- Update the locally stored global variable
void locallyUpdateUserGlobalVariable(Real or Int value, const String &name)

```

void getUserRealData(RealArray1d &real_array, const String & real_label,
                    const String & resource,
                    const String & user_sub_name );

void putUserRealData(RealArray1d &real_array, const String & real_label,
                    const String & resource, const String & origin,
                    const String & user_sub_name );

void getUserRealData(double & real_value,
                    const String & real_label,
                    const String & resource,
                    const String & user_sub_name);

void putUserRealData(double & real_value,
                    const String & real_label,
                    const String & resource,
                    const String & origin,
                    const String & user_sub_name);

void getUserIntData(int & int_value,
                    const String & int_label,
                    const String & resource,
                    const String & user_sub_name);

void putUserIntData(int & int_value,
                    const String & int_label,
                    const String & resource,
                    const String & origin,
                    const String & user_sub_name);

void getUserIntData(IntArray1d &int_array, const String & int_label,
                    const String & resource,
                    const String & user_sub_name );

void putUserIntData(IntArray1d &int_array, const String & int_label,
                    const String & resource, const String & origin,
                    const String & user_sub_name );

- Return the local face, element or node currently being processed
Region * getRegion(void);

void push_query(UserQuery *query)
void pop_query(UserQuery *query)

```

33.23.1. CHEMEQ Species Variable Access

Occasionally one may wish to access the values of species from the CHEMEQ system within the FORTRAN-like C subroutine using the `getSpecies(Int elem_id, Real species *)` interface. In this case some knowledge of the returned data layout is required in order to access the correct values. Internal to the code species values for an element are defined at each of the element quadrature points and stored collectively in a single flat array. Thus in order to access species values for a specific component one must stride into the flat array of values.

As an example, consider the case of three species, `num_species = 3`, chemistry on a 2D quadrilateral which has four quadrature points. Within the subroutine storage must be provided for an array of length 12 denoted here as `s`,

`RealArray1D s(12);`

This implies the species data layout shown below

$$\underbrace{s(0) \ s(1) \ s(2)}_{qpt_1} \underbrace{s(3) \ s(4) \ s(5)}_{qpt_2} \underbrace{s(6) \ s(7) \ s(8)}_{qpt_3} \underbrace{s(9) \ s(10) \ s(11)}_{qpt_4} .$$

We note that if one is interested in the values for the second species these values, $s(1)$, $s(4)$, $s(7)$, $s(10)$, are offset by 1 into each subset of quadrature point values. For a given element id, `eid`, the species values for that element are obtained with the user_query `getSpecies( eid, &s )`. Then to access each of the i th quadrature point values ($i=0,1,2,3$) for the desired species one must stride into an appropriate offset position, `index = 1`, so that the species quadrature point value is

$$\text{value} = s(\text{num\_species} * i + \text{index}) .$$

33.24. DEBUG OUTPUT FROM USER SUBROUTINES

Oftentimes one finds it instructive to output diagnostic information to file from the user subroutine. Aria provides three different ways of generating this output, output directly to a user specified file, output to the log file for all time and selective output to the log file. Each of these options has both advantages and disadvantages. In each of the cases information could be written each time the subroutine is called so the user must provide some code logic to limit the amount of output.

Outputting directly to a user specified file is most straightforward approach but then program output will be split over multiple files. Output to the log file is convenient but in this case the subroutine output will be interlaced with log file output that one would normally expect. Outputting to the log file for all time is appropriate only when diagnostics are always needed. Selective output to the log file is preferred in most cases since the amount of output is restricted to special instances. As an example of each approach the subroutine appearing in a previous section is augmented with the appropriate code. Here direct output to file is demonstrated with both C file specification and C++ file specification.

```
Int
aocal_aniso_cond(
```



```

UserQuery &                                user_query,
ElementIds                                objid,
Int                                        nelem,
Int                                        nint,
Int                                        spatial_dimension,
CoordinateElementIntegrationPoints        coords,
TemperatureElementIntegrationPoints        temperature,
ConductivityElementIntegrationPoints      elemCond,
DirectionElementIntegrationPoints         elemVec)
{
    // main ingredients for separate file output

    // C file specification

    static FILE *file_pointer = NULL;
    if(NULL == file_pointer ) // only open the file once
    {
        file_pointer = fopen("c.out", "w");
        ThrowRequire(file_pointer);
    }

    // C++ file specification
    static bool have_ofs = false;
    static std::ofstream ofs;

    if( !have_ofs )
    {
        ofs.open("cpp.out", std::ios::out );
        have_ofs = true;
    }

    RealArray1d cond_data(6);
    RealArray1d cond_vec2(3);
    RealArray1d cond_vec1(3);

    user_query.getUserRealInstanceData(cond_data, "cond_data");
    user_query.getUserRealInstanceData(cond_vec1, "cond_vec1");
    user_query.getUserRealInstanceData(cond_vec2, "cond_vec2");

    //      normalize the vectors
    Real rlen = std::sqrt(cond_vec1(0)*cond_vec1(0)
                          +cond_vec1(1)*cond_vec1(1)
                          +cond_vec1(2)*cond_vec1(2));

    cond_vec1(0) = cond_vec1(0) / rlen;

```

```

cond_vec1(1) = cond_vec1(1) / rlen;
cond_vec1(2) = cond_vec1(2) / rlen;

rlen = std::sqrt(cond_vec2(0)*cond_vec2(0)
                 +cond_vec2(1)*cond_vec2(1)
                 +cond_vec2(2)*cond_vec2(2));

cond_vec2(0) = cond_vec2(0) / rlen;
cond_vec2(1) = cond_vec2(1) / rlen;
cond_vec2(2) = cond_vec2(2) / rlen;

//    check orthonormality
Real rdot = cond_vec1(0)*cond_vec2(0) + cond_vec1(1)*cond_vec2(1)
           + cond_vec1(2)*cond_vec2(2);

// orthonormality diagnostics
if( std::abs(rdot) > 1.0e-5 ) {
    // Information is always output to the c.out file C style
    fprintf(file_pointer, "[ERROR] Principal directions specified are not orthonormal\n");
    // Information is always output to the cpp.out file C++ style
    ofs << "[ERROR] Principal directions specified "
          << " are not orthonormal" << std::endl;
    // Information is always output to log file
    arialog << "[ERROR] Principal directions specified "
            << " are not orthonormal" << endl;
    // Information is conditionally output to log file by supplying the
    // -0 "-arialog user-sub" arguments to sierra command
    debuglog << "[ERROR] Principal directions specified "
            << " are not orthonormal" << endl;
    return;
}

for( Int e = 0; e<nelem; ++e )
{
    for( Int n=0; n<nint; ++n )
    {
        elemCond(0, 0, e, n) = cond_data(0);
        elemCond(1, 1, e, n) = cond_data(1);
        elemCond(2, 2, e, n) = cond_data(2);
        // these assignments are not necessary
        // since the elemCond data is zeroed when subroutine is called
        elemCond(0, 1, e, n) = cond_data(3);
        elemCond(1, 0, e, n) = cond_data(3);
        elemCond(0, 2, e, n) = cond_data(4);
        elemCond(2, 0, e, n) = cond_data(4);
    }
}

```

```

        elemCond(1, 2, e, n) = cond_data(5);
        elemCond(2, 1, e, n) = cond_data(5);

        elemVec(0, 0, e, n) = cond_vec1(0);
        elemVec(0, 1, e, n) = cond_vec1(1);
        elemVec(0, 2, e, n) = cond_vec1(2);

        elemVec(1, 0, e, n) = cond_vec2(0);
        elemVec(1, 1, e, n) = cond_vec2(1);
        elemVec(1, 2, e, n) = cond_vec2(2);
    }
}

return;
}

RegisterFunction(ElemTensorUserSubC, aucal_aniso_cond, "aucal_aniso_cond");

```

In some instances one might wish to terminate execution when certain conditions arise in the user subroutine. Here the user can provide a diagnostic for termination when causing the program to stop including a conditional such as the one shown below.

```

if( condvec(2) == 0 )
    throw sierra::RuntimeError() << "condvec(2) = 0 on " << objid;

```

33.25. FORTRAN USER SUBROUTINES

An Aria FORTRAN user subroutine must be a text file of suffix `.F` or `.f`. The FORTRAN file content is made available to the application by either compiling the module and statically linking it to the application archive or by dynamically linking the module to the executable at run time. The static link approach is often preferred on capability high-performance computing platforms, where dynamically linked subroutines are either not supported or suffer a penalty in performance. User selection of static or dynamic linking is determined by a combination of commands used for job execution and input command lines.

For the static link approach consider the use of a FORTRAN subroutine module file named `Aucal_ConvFlux.F`. In order to use this module the input file must contain an input command line such as

```
user subroutine file = Aucal_ConvFlux.F
```

A static link of the module is then initiated by use the job command

```
sierra -make aria -i input.i
```

This command will invoke creation of an auxiliary FORTRAN module used to perform a registration of the subroutine in the executable. Then the subroutine and auxiliary module are compiled followed by a static link with the existing archive to create an executable written to a `UserSubsProject/bin` subdirectory. This executable must then be specifically called out in the job execution command.

For the dynamic link approach the user must supply the auxiliary FORTRAN module used for subroutine registration. Most often the auxiliary module is included in the subroutine file but can also be provided as a standalone file. In order to use this module the input file must contain an input command line such as

```
load user plugin file Aucal_ConvFlux.so using function conv_flux_register
```

where `conv_flux_register` is the name of the auxiliary module used for subroutine registration. An example of the auxiliary module is given in the section which follows [33.26](#). Note that this registration is equivalent to that of Aria User Plugin function registration [18](#). Invocation of the job command

```
sierra -make aria -i input.i
```

initiates a compilation that leads to creation of a shared object, `Aucal_ConvFlux . so`. During execution of the job the shared object will be automatically loaded and used in the execution.

Note that, since `Aucal_ConvFlux . F` is a filename, its input file name is case-sensitive, and considerations must be made concerning its location path. The user is free to name the file and subroutines in any way chosen, provided it is consistent with compiler and operating system limitations. For example, special characters such as `''` and `,` should be avoided. Finally actual use of the function by the application is triggered by association of the the user subroutine name in a particular command line, presently only Dirichlet boundary conditions, flux boundary conditions and material property evaluations.

33.26. FORTRAN INTERFACES

While FORTRAN user subroutines could be defined to supply many different parameters, only two different signatures are currently provided in Aria. These signatures characterize the argument lists by which the subroutine interacts with the code. The various subroutine signatures are denoted as:

- node signature [33.26.1](#)
- element signature [33.26.2](#)

Generally speaking FORTRAN subroutines function in the same way as C-Style subroutines with emphasis placed on providing one data set or material property through the element signature interface. Element subroutines operate strictly upon quadrature point values whereas the node subroutine can only operate on nodal values. The different subroutine call signatures are outlined below. The FORTRAN user subroutines must be registered with a function signature similar to the element subroutine example below.

```

c
c  fortran subroutine registration
c
      subroutine conv_flux_register
c
      implicit none
      external aocal_fort_elem_sub
      external ht_coeff_test
      external t_ref_test
c
      call fmwkusersub(aocal_fort_elem_sub, ht_coeff_test,
&                    'ht_coeff_test')
      call fmwkusersub(aocal_fort_elem_sub, t_ref_test,
&                    't_ref_test')
c
      end

```

Here the first argument to *fmwkusersub* is the internally defined interface signature name. The second argument is the name of the FORTRAN function (subroutine) and the third is the name to be associated with the subroutine from within the input file. Note that the Fortran function must be declared *external* in order to be recognized by the registration function.

Perhaps the biggest difference between C-Style subroutines and FORTRAN subroutines will be the difference in how problem specific input file data is provided to the user subroutine. For FORTRAN and FORTRAN-like C-style subroutines parameters can be provided through use of arbitrary DATA_BLOCKS 33.19. For boundary conditions, source terms and initial condition the FORTRAN subroutine parameters can also be provided with REAL DATA or INT DATA command lines within the respective command block. However, parameters for material property subroutines can only be provided through the DATA_BLOCK construct. It is important to note that DATA_BLOCK parameter retrieval from within a FORTRAN subroutine is considered to be somewhat awkward and is demonstrated in an example of a material property subroutine.

33.26.1. FORTRAN Node Subroutine

The FORTRAN Node subroutine is used primarily for applying Dirichlet boundary conditions and is designed to operate on sidesets. The Node subroutine is registered in the same way as an element subroutine but with an *aocal_fort_node_sub* signature. For example the subroutine call could be invoked using the following input command block:

```

Begin Temperature Boundary Condition bcblock1
  Temperature fortran subroutine = dirich_test
  Add surface surface_2
End Temperature Boundary Condition bcblock1

```

Here we demonstrate the node user subroutine in which the user supplied subroutine nodal values are assigned as constants. Note that time and coordinates are being supplied to the subroutine so the assigned values could also be functions of the supplied variables.

```

c
c   Subroutine to handle coordinate and time-dependent
c   Temperature Dirichlet BC
c
c   subroutine dirich_test(objid,nnodes,coords,temperature,
&                               time,rdat,idat,ierror)
c   implicit none
c   integer nnodes
c   integer objid
c   double precision coords(2,nnodes)
c   double precision temperature(nnodes)
c   double precision time
c   integer ierror

c   Note: rdat and idat must be sized at least 1,
c   even when not used
c   otherwise they must be sized consistent with the
c   data being provided from the input file

c   double precision rdat(1)
c   integer idat(1)

c
c   INPUT ARGUMENTS:
c   objid(nelem): array of mesh object ID's. Useful for passing through
c   to query methods
c   nelem: number of elements in the workset
c   nint: Number of integration points per element in the workset
c   coords(2,n,nint): array of the coordinates (x,y,z) of the Gauss points
c   rdat() real parameter data
c   idat() integer data
c
c   OUTPUT ARGUMENTS:
c   temperature: temperature at the node
c   ierror: user defined error code for calcore to test.
c   zero means success.
c
c   integer i, j

c   ierror = 0

c   do i=1,nnodes

```

```

        if( coords(2,i) .lt. 0.5 ) then
            temperature(i) = 1.5
        else
            temperature(i) = 0.1
        end if

    end do

    return
end

```

33.26.2. FORTRAN Element Subroutine

The FORTRAN element subroutine can be used to compute coefficients or material properties associated with either surface or volume elements. While the example given here it is associated with surface flux conditions, it is important to note that the element subroutine can be more broadly applied.

The FORTRAN element subroutine is used to applying a flux boundary condition and is here defined to operate on sidesets. For example the subroutine call could be invoked using the following input command block:

```

Begin Heat Flux Boundary Condition C1
  Add Surface surface_1
  Flux Fortran Subroutine = ht_flux_test
  integer data 8, 12, 14
  real data 1.0 2.0
end

```

Here we demonstrate the flux user subroutine in which the user supplied subroutine heat flux values are assigned as constants. Note that temperature, time and coordinates are being supplied to the subroutine so the assigned values could also be functions of the supplied variables.

```

c
c      Subroutine to handle coordinate, time and temperature
c      dependent flux
c
      subroutine flux_test(objid,nelem,nint,coords,temperature,
&                          flux,time,rdat,idat,ierror)
      implicit none
      integer nelem, nint
      integer objid(nelem)
      double precision coords(3,nelem,nint)

```

```

double precision temperature(nelem,nint)
double precision flux(nelem,nint)
double precision time
integer ierror

c
c Note: rdat and idat must be sized at least 1,
c       even when not used
c       otherwise they must be sized consistent with the
c       data being provided from the input file
c
c       Here the rdat and idat are provided but are not used.
double precision rdat(2)
integer idat(3)

c
c INPUT ARGUMENTS:
c   objid(nelem): array of mesh object ID's. Useful for passing through
c                 to query methods
c   nelem: number of elements in the workset
c   nint: Number of integration points per element in the workset
c   coords(3,n,nint): array of the coordinates (x,y,z) of the Gauss points
c   temperature(n,nint): temperature at the Gauss points
c   rdat() real parameter data
c   idat() integer data
c
c OUTPUT ARGUMENTS:
c   flux: array of length ( n, nint) containing
c         the heat flux coefficient
c         at integration points
c   ierror: user defined error code for calore to test.
c          zero means success.
c
integer i, j

ierror = 0

do i=1,nelem

  do j=1,nint
    if( coords(3,i,j) .gt. 4.0 ) then
      flux(i,j) = 4000.0
    else
      flux(i,j) = 0.0
    end if
  end do

end do

```



```

end do

return
end

```

Material model support from within the Aria Material command block for FORTRAN subroutines is currently limited to a few thermal properties, density, specific heat, scalar thermal conductivity and emissivity where the material model designation is simply FORTRAN. Note that the ability to supply FORTRAN subroutine parameters is limited to the use of a DATA BLOCK [33.19](#).

An example of the material input for a FORTRAN density model subroutine input is shown below followed by the subroutine implementation. In this example the density will take on different constant values above and below a threshold temperature.

```

begin data block my_data
  real real_data = ( 287 1.1 0.9 )
end data block my_data

Begin Aria Material testuser
  Density = Fortran SUB_NAME = my_rho data = my_data
  Thermal Conductivity = constant k = 20.0
  Specific Heat      = CONSTANT cp = 1.0 # J/kg-K
  Heat Conduction = generalized
End Aria Material testuser

```

From the subroutine implementation it becomes clear that DATA_BLOCK parameter retrieval from within a FORTRAN subroutine is somewhat obscure in that the input file named data and values must be explicitly defined within the subroutine to match the input file description. Moreover, the variables *rdat* and *idat* provided through the interface should not be used within the subroutine as storage allocation for those variables is not provided within the code. For this reason FORTRAN-like C material model subroutines are generally preferred over the FORTRAN counterpart.

```

      Subroutine my_rho(objid,nelem,nint,coords,temperature,
&                      rho,time,rdat,idat,ierror)
c
c  rdaand idat should not used within a material subroutine
c    s doing so may corrupt internal data
c
      implicit none
      integer nelem,nint
      integer objid(nelem)
      double precision coords(3,nelem,nint)
      double precision temperature(nelem,nint)
      double precision rho(nelem,nint)

```

```

double precision time
double precision rdat
double precision idat
integer ierror

integer i, j

double precision temp_limit
double precision rho_low
double precision rho_high

character*9 real_data_name
c                                     3 data values
double precision data_rdat(3)
c                                     9 characters long
real_data_name = 'real_data'
c                                     3 data values
c                                     9 characters long
call aria_get_instance_real_data(data_rdat,3,
&                                real_data_name,9)

temp_limit = data_rdat(1)
rho_low    = data_rdat(2)
rho_high   = data_rdat(3)

ierror = 0

do i=1,nelem
  do j=1,nint
    if ( temperature(i,j) .lt. temp_limit ) then
      rho(i,j) = rho_low
    else
      rho(i,j) = rho_high
    end if
  end do
end do

return
end

```

33.27. FORTRAN SUBROUTINE INTERFACE FUNCTIONS

A number of utility functions are supplied for use in the FORTRAN subroutines. These utilities provide access to internal variables that one might wish to use within the subroutine and enables manipulation of these Double Precision and Integer variables to a certain extent. Examples of interface functions used to modify values associated with boundary condition, material data or global variables.

User interface function calls are part of the application code that are accessible from the user subroutine. As an example, in order to retrieve a global variable named *T_AVERAGE* the subroutine body would contain an external definition of the retrieval function and the function call as indicated here.

```
subroutine your_subroutine_interface( objid,nelem,nint,coords,temperature,
&                                     source,time,rdat,idat,ierror)
  implicit none
  integer nelem, nint
  integer objid(nelem)
  double precision coords(3,nelem,nint)
  double precision temperature(nelem,nint)
  double precision source(nelem,nint)
  double precision time
  integer ierror

  double precision t_avg
  character*9 cvar

  external aria_get_global_real_var

  cvar = "T_AVERAGE"
  ierror = 0
  .
  call aria_get_global_real_var(t_avg,1,cvar)
  .
C  statements referencing t_avg
  .
  return
end
}
```

Call signatures to the various FORTRAN user interface functions are provided below.

```
aria_get_time(double precision time)
```

```
aria_get_timestep_index(integer k)
```

```

aria_get_material_name(integer length, character name)

aria_get_contact_material_name(integer face_id, integer length, character name)

aria_get_contact_element(integer face_id, integer elem_id, integer found)

aria_get_pred_nodal_t(integer id, double precision t, integer found)

aria_get_prev_nodal_t(integer id, double precision t, integer found)

aria_get_species(integer id, double precision s)

aria_get_aux_var(integer id, double precision a)

aria_get_element_tdot(integer id, double precision tdot)

aria_get_encore_global_real_var(
    double precision value, integer varNameLen, character varName)

aria_get_encore_global_int_var(
    integer value, integer varNameLen, character varName)

aria_get_global_real_var(
    double precision value, integer varNameLen, character varName)

aria_get_global_int_var(
    integer value, integer varNameLen, character varName)

aria_lupdate_global_real_var(
    double precision deltaValue, integer varNameLen, character varName)

aria_lupdate_global_int_var(
    integer deltaValue, integer varNameLen, character varName)

aria_get_element_volume(integer id, double precision value)

aria_get_element_mass(integer id, double precision value)

aria_get_real_nodal_var(
    double precision value, integer id, integer varNameLen, character varName)

aria_get_int_nodal_var(
    integer value, integer id, integer varNameLen, character varName)

```

```

aria_put_real_nodal_var(
    double precision value, integer id, integer varNameLen, character varName)

aria_put_int_nodal_var(
    integer value, integer id, integer varNameLen, character varName)

aria_get_real_elem_var(
    double precision value, integer id, integer varNameLen, character varName)

aria_get_int_elem_var(
    integer value, integer id, integer varNameLen, character varName)

aria_put_real_elem_var(
    double precision value, integer id, integer varNameLen, character varName)

aria_put_int_elem_var(
    integer value, integer id, integer varNameLen, character varName)

aria_get_real_face_var(
    double precision value, integer id, integer varNameLen, character varName)

aria_get_int_face_var(
    integer value, integer id, integer varNameLen, character varName)

aria_put_real_face_var(
    double precision value, integer id, integer varNameLen, character varName)

aria_put_int_face_var(integer value, integer id, integer varNameLen, character varName)

aria_get_material_real_data(
    double precision addr, integer length, character name, integer name_length)

aria_put_material_real_data(
    double precision addr, integer length, character name, integer name_length)

aria_get_material_int_data(
    integer addr, integer length, character name, integer name_length)

aria_put_material_int_data(
    integer addr, integer length, character name, integer name_length)

aria_get_region_real_data(
    double precision addr, integer length, character name, integer name_length)

aria_put_region_real_data(

```

```

    double precision addr, integer length, character name, integer name_length)

aria_get_region_int_data(
    integer addr, integer length, character name, integer name_length)

aria_put_region_int_data(
    integer addr, integer length, character name, integer name_length)

aria_get_instance_real_data(
    double precision addr, integer length, character name, integer name_length)

aria_put_instance_real_data(
    double precision addr, integer length, character name, integer name_length)

aria_get_instance_int_data(
    integer addr, integer length, character name, integer name_length)

aria_put_instance_int_data(
    integer addr, integer length, character name, integer name_length)

aria_get_spatial_dimension(integer spatDim)

aria_evaluate_function(
    integer numValues, double precision input, double precision output, character

```

33.28. SOLUTION MAPPING METHODOLOGY

Numerical simulations of full system models are oftentimes intensely consuming calculations. During the design process the need often arises to study the same problem with minor changes to a subcomponent of the original model. To fulfill this need a solution mapping methodology that simulates the thermal response of a subassembly, without having to repeat a simulation of the full assembly model has been developed. This capability is particularly useful in cases where the analyst must evaluate alternative subassembly designs and provide timely input to engineering design studies. This section describes how to apply this solution mapping methodology.

The basic idea of the Aria solution mapping methodology is to use existing simulation results (e.g temperature or heat flux) from a full assembly model to set boundary conditions (BCs) for a separate simulation of a smaller, but possibly more geometrically resolved, subassembly or component. In effect, the Aria thermal simulation of the full assembly serves as the “Donor” of the solution results, while the subassembly model becomes the “Recipient”. This methodology uses existing Aria code features to map solution results to the appropriate boundary surfaces of the subassembly model. It is important to mention that the methodology permits the analyst to use different meshes and mesh resolutions at the interface between the full and subassembly models.

33.28.1. Setting up Simulation for Donor Model

To set up a Donor model, the user modifies the Aria input file for the full assembly model so that it outputs the solution information that will be transferred or mapped to the outer surfaces of the Recipient subassembly model or mesh. The user can choose to set either Dirichlet boundary conditions (i.e. map temperature) or Neumann type boundary conditions (i.e. map heat fluxes) on the outer surface of the recipient model. Numerical studies conducted by the Aria development team indicate that temperature mapping generally provides much more reliable estimation of the subassembly temperatures than using heat flux mapping. In fact, the user is cautioned to avoid the flux mapping transfer capability, especially for long-duration transients when the error accumulates in time and can become quite substantial.

In either type of solution mapping, the user must compile and specify the material blocks surrounding and contacting the subassembly, which are to be used in the solution mapping. It is recommended that, where possible, the user should map the solution from the Donor model to an enclosing region that extends slightly beyond the subassembly, rather than mapping solutions directly on the subassembly exterior. This approach provides some measure of buffering of the effect of sudden changes in time varying BCs.

First, add a new “Begin Results Output” (described in [25.1](#)) block to the input file used specifically for mapping, such as the example shown below. This output block is in addition to the typical output block that writes the nodal field for the entire model domain.

```
.
.
.
    Begin Results Output Solution_Mapping
        Database Name = Donor_solution.e
        Include = BlockList
#        ... Use for Temperature Mapping Only ...
        Nodal Variables = solution->Temperature as T
#        ... Use for Heat Flux Mapping Only ...
        Nodal variables = pp->Heat_Conduction as Heat_Flux
        At Time 0.0, Increment = 1.0
        Timestep Adjustment Interval is 4
    End
.
.
```

In the above syntax example, the *BlockList* is the list of block IDs that will be used in the solution mapping. If heat flux mapping is used, then add the following command to the “Region” level of the input file:

```
.
    Postprocess Heat_Conduction on all_blocks
.
```

With above command lines added, execute the thermal simulation for the full assembly model and create the donor-solution exodus output file.

33.28.2. Setting up Simulation for Recipient Model

In most cases, the user can prepare the Aria input file for the Recipient model by copying and simplifying the input file from the original full assembly model. The input file for Recipient model will reference the subassembly mesh and the subassembly material definitions. With the input file stylized for the subassembly, the user should add:

1. A “Begin Finite Element Model” block
2. A “Begin Input_Output Region” block
3. Transfer Commands
4. Transfer definitions via the “Begin Transfer” block
5. BC XFER command (for temperature mapping only).

For the case where heat flux is used in the solution mapping, the last step is replaced with:

1. Addition of the user field command (see Chapter 9 and
2. Addition of a “Flux Vector Node Variable” (see Chapter 33.1)

33.28.2.1. 1. Finite Element Model

The purpose of the new Finite Element Block is to identify the exodus file generated by the Donor model. The syntax of this command block is described in Chapter 2. An example of this block is shown below:

```
Begin Finite Element Model Input_Transfer
  Database Name = Donor_solution.e
  Database Type = exodusII
End
```

This block is placed in the Domain level of the input file. Explanation of Domain, Procedure and Region levels of the input file can be found in Chapter 2 of the manual.

33.28.2.2. 2. Begin Input_Output Block

A description of the “Begin Input_Output Region” block can be found in Section [15.1](#). This command block is placed in the Procedure level of the input file. An example is given below:

```
Begin Input_Output Region Transfer_Region
    Use Finite Element Model Input_Transfer
End
```

33.28.2.3. 3. Transfer Commands

A detailed explanation of Transfer command syntax and usage is presented in Section [15.1](#) of this user manual. These commands are added to the “Begin System Main” block. An example of these transfer commands is shown below:

```
Begin Solution Control Description
    Use System Main
    Begin System Main
        Simulation Start Time = 0.0
        Simulation Termination Time = 3600.0
        Begin Transient solution_block_1
            Advance transfer_region
            Transfer trans_to_aria
            Advance myRegion
        End
    .
    .
End System Main
.
End Solution Control Description
```

The above command block is located in the Procedure level of the input file.

33.28.2.4. 4. Transfer Definitions

Syntax and usage of transfer definitions is presented in Section [15.1](#) of the manual. Here is an example of the transfer definitions for

```

Begin Transfer trans_to_aria
  Interpolate Volume Nodes from transfer_region to myRegion
  Nodes Outside Region = project    #or extrapolate, #or truncate
#    ... Use for Temperature transfer only ...
  Send Block block_1 block_2 ... to surface_1 surface_2 ...
  Send Field T State None to solution->Temperature State New
#    ... Use for heat flux transfer only ...
#    Send Block block_1 block_2 ... to block_1 block_2 ...
#    Send Field heat_flux State None to surf_flux State None
#    ... Tolerance settings ...
  Search Geometric Tolerance is 0.001
  Search Surface Gap Tolerance is 0.01
End

```

The above example has transfer definitions for both temperature and heat flux, however, only one set of commands can be used.

33.28.2.5. 5a. BC XFER Command

As explained previously, the BC XFER command is used to set the temperature BC on the Recipient model. The command is placed in the Region level of the input file. Here is an example of the command:

```

BC XFER Dirichlet on surface_1 ... Temperature    #BC sidesets for recipient mesh

```

General usage and syntax for the BC XFER command can be found in Chapter 9 of the manual.

33.28.2.6. 5b. Heat Flux BC Commands

For the case where heat flux mapping is used, the above BC XFER command is replaced by: (1) user field definition and (2) heat flux BC specification. Syntax for the user field definition is presented in Chapter 9 of the manual, while its use in a heat flux BC specification is given in Chapter 33.1. Here are examples of the applicable commands:

```

#    ... Create User Field to store mapped heat flux ...
  User Field Real Nodal Vector surf_flux on block_1

```

The above command must be added to the Region level of the input file. In turn, the *surf_flux* is used to set the heat flux BC via the command block:

```
#    ... Set the heat flux BC ...  
Begin Heat Flux Boundary Condition mapped_flux  
  add Surface surface_1  
  Flux Vector Node Variable = surf_flux  
End
```

34. CORRELATION HEAT TRANSFER COEFFICIENT REFERENCE

34.1. HEAT TRANSFER COEFFICIENT CORRELATION LIBRARY

For heat transfer problems involving convective flux boundary conditions, a convection heat transfer coefficient must be specified (Ch 33.1). An extensive built-in heat transfer coefficient correlation library has been incorporated into Aria (see [42]) for generalized heat transfer problems involving fluid flow. The current code implementation includes only subset of this library but future plans are to provide full support of those correlations. This library includes correlations for laminar and turbulent flows of forced and free convection, for internal and external flow geometries, and for gases and liquids (including liquid metals). These correlations are especially useful for reduced order flow modeling in which a full Conjugate Heat Transfer simulation is not desired.

Each correlation supplies a Nusselt Number (Nu) from which the heat transfer coefficient (h) may be computed via

$$h = \frac{K}{D_h} * Nu \quad (34.1)$$

where K is the scalar thermal conductivity and D_h is a characteristic length for the simulation. Hence in all cases, K and D_h MUST be specified. The parameter K is supplied in the fluid "Aria Material" command block and D_h in the "Heat Transfer Correlation Coefficient" command block. In applying the convective flux, provision is made for switching between laminar and turbulent correlations based on a user specification of the transition Reynolds Number (R_{ex}).

Correlations are implemented with various mathematical forms, required input variables and valid flow regimes. A sample input for the correlation heat transfer coefficient is shown below.

```
Begin Heat Transfer Correlation Coefficient ziggurat
```

```
  LAMINAR    CORRELATION = type 18
```

```
  TURBULENT  CORRELATION = type 18
```

```
  Transition Reynolds Number = 400
```

```
  Characteristic Length = 0.1
```

```
  Entrance      Length = 0.5
```

```
Compute Reynolds Number
Compute Prandtl Number
Compute Wall Temperature
Compute Fluid Temperature
Compute Friction Factor model = smooth tube
End
```

Contents of the input command block correspond to entries listed in correlation Classification [34.1.1](#) and the D_h parameter corresponds to the "characteristic length" entry. Parsed contents of the input command block are verified against the "Dependence" requirements of the selected correlation Type [34.1.2](#) and any missing requirements are reported in the log file.

34.1.1. Classification

Due to the large number of correlations, a taxonomy based on the required input parameters was developed in order to provide a quick mapping between a model and its index ID. There are currently 20 parameters which all the correlations are dependent on and these are

- f Friction factor
- Re Flow Reynolds number
- Pr Flow Prandtl number
- Pr_w Flow Prandtl number evaluated with wall conditions
- T Fluid temperature
- T_w Wall temperature
- L Wall length
- g Gravitational constant
- r Ratio of annulus inner diameter to outer diameter
- ρ Fluid density
- μ Dynamic viscosity
- ν Kinematic viscosity
- β Expansion coefficient
- θ Wall angle (in radians)
- V Scalar flow velocity magnitude
- Re_x Transitional Reynolds number
- S_t Transverse pitch
- S_l Longitudinal pitch
- ϕ Porosity
- D_e Entrance length

These may be computed analytically from the model variables or overridden by a user specified constant. It is to be noted that specification of a parameter constant means that other parameters which are dependent on it will use this value e.g constant kinematic viscosity will also be used in Reynolds number calculations instead of a material property evaluation.

Each correlation specification description below is of the form *Specification* : {Regime, Phase, Convection, Flow, Author, Shape, Special} where the component options are

Regime: {Laminar, Turbulent, Both}

Phase: {Gas, Liquid, Gas|Liquid, LiquidMetal, Organic}

Convection: {Forced, Free}

Flow: {Internal, External}

Author: {Hausen, Modified_Sieder-Tate, Churchill-Bernstein, Petukhov, Colburn, Dittus-Boelter, Sieder-Tate, Taylor, Nusselt, Notter-Sliecher, Seban-Shimazaki, Azer-Chao, Sliecher, Denton, Jeschar, Achenbach, Beek, Whitaker, Witte, Ranz-Marshall, Modified_Ranz-Marshall, Hilpert, Zhulkauskas, Churchill-Chu, McAdams, Morgan, Gnielinski, Modified_Gnielinski}

Shape: {NoShape, Cylinder, Sphere, Cube, Square_CornerOn, Square_FlatOn, Hexagon_CornerOn, Hexagon_FlatOn, Flat_Plate_Vertical, TubeBank_Aligned_Cylinder, TubeBank_Staggered_Cylinder, Flat_Plate, Vertical_Or_Angle_Surface, Vertical_Surface, Horizontal_Plate_OnHC, Horizontal_Plate_OffHC, Horizontal_Cylinder, Annulus}

Special: {N/A, Crossflow, Local, Average, PackedBed, FullDevLam_ConstFlux, FullDevLam_ConstTemp, ConstFlux, ConstTemp, Insulated_InnerWall, Insulated_OuterWall}

34.1.2. Correlation Listing



Beta Capability: Correlation Types 25 and 71-74 are the most tested correlations. All other correlations have not been extensively tested and should be used with caution.

Type 1 This correlation applies to cases of fully-developed internal laminar flow with a constant wall flux or constant wall temperature, for which a Nusselt number may be determined analytically.

Dependence: { K , D_h }

Specification: { Laminar, Gas|Liquid, Forced, Internal, NoAuthor, NoShape, FullDevLam_ConstFlux }

Correlation: $Nu = 4.36$

Range: { $Pr > 0.6$ }

Type 2 This correlation applies to cases of fully-developed internal laminar flow with a constant wall flux or constant wall temperature, for which a Nusselt number may be determined analytically.

Dependence: $\{K, D_h\}$

Specification: $\{\text{Laminar, Gas|Liquid, Forced, Internal, NoAuthor, NoShape, FullDevLam\_ConstFlux}\}$

Correlation: $Nu = 3.666$

Range: $\{Pr > 0.6\}$

Type 3 This correlation by Hausen applies to cases of thermally fully-developed laminar flow with entrance effects.

Dependence: $\{K, D_h, D_e, Re, Pr\}$

Specification: $\{\text{Laminar, Gas|Liquid, Forced, Internal, Hausen, NoShape, N/A}\}$

Correlation:

$$I = \frac{D_h}{D_e} Re Pr$$

$$Nu = 3.66 + \frac{0.0668 \cdot I}{1 + 0.4 \cdot I^{0.66667}}$$

.

Range: $\{Pr \gg 1\}$ or unheated entrance

Type 4 This correlation by Nusselt applies to cases of thermally fully-developed turbulent flow with entrance effects.

Dependence: $\{K, D_h, D_e, Re, Pr\}$

Specification: $\{\text{Turbulent, Gas|Liquid, Forced, Internal, Nusselt, NoShape, N/A}\}$

Correlation: $Nu = 0.036 Re^{0.8} Pr^{0.3333} \left(\frac{D_h}{D_e}\right)^{0.05556}$

Type 5 This modified Ranz-Marshall correlation applies to cases of thermally fully-developed flow with entrance effects.

Dependence: $\{K, D_h, D_e, Re, Pr\}$

Specification: $\{\text{Both, Liquid, Forced, External, Modified\_Ranz-Marshall, NoShape, N/A}\}$

Correlation: $Nu = 2 + 0.6 \sqrt{Re} (Pr)^{0.3333} \cdot 25 (D_e/D_h)^{-0.7}$

Type 14 This correlation by Azer-Chao applies to cases of constant surface temperature liquid metals in tubes.

Dependence: $\{K, D_h, Re, Pr\}$

Specification: $\{\text{Turbulent, LiquidMetal, Forced, Internal, Azer-Chao, NoShape, N/A}\}$

Correlation: $Pe = Re Pr, Nu = 5.0 + 0.05 Pe^{0.8} Pr^{0.25}$

Type 15 This correlation by Sliecher applies to cases of constant surface temperature liquid metals in tubes.

Dependence: $\{K, D_h, Re, Pr\}$

Specification: {Both, LiquidMetal, Forced, Internal, Sliecher, NoShape, N/A}

Correlation: $Pe = RePr, Nu = 4.8 + 0.0156Pe^{0.85}Pr^{0.08}$

Range: $\{0.004 < Pr < 0.1\}, \{Re < 500000\}$

Type 18 This correlation applies to cases of flow over a sphere.

Dependence: $\{K, D_h, Re, Pr\}$

Specification: {Both, Gas, Forced, External, NoAuthor, Sphere, N/A}

Correlation: $Nu = 0.37Re^{0.6} \cdot 1.126Pr^{0.3333}$

Range: $\{17 < Re < 700000\}$

Type 21 This correlation by Zhulkauskas applies to cases of aligned cylindrical tube bank in cross flow.

Dependence: $\{K, D_h, Re, Pr\}$

Specification: {Both, Gas, Forced, External, Zhulkauskas, TubeBank_Aligned_Cylinder, Crossflow}

Correlation: $Nu = C_1 Re^{C_2} Pr^{0.36}$

$$(C_1, C_2) = \begin{cases} (0.27, 0.63) & Re < 200000 \\ (0.021, 0.84) & \text{else} \end{cases}$$

Range: $\{1 < Re < 1000000\}, \{0.7 < Pr < 500\}$

Type 23 This correlation by Petukhov applies to cases of turbulent gas flow with friction factor correlation for smooth surfaces.

Dependence: $\{K, D_h, Re, Pr, f\}$

Specification: {Turbulent, Gas, Forced, Internal, Petukhov, NoShape, N/A}

Correlation: $Nu = \frac{0.125fRePr}{1.07 + 12.7\sqrt{0.125f}(\Pr^{0.6667} - 1)}$

Range: $\{3000 < Re < 5000000\}, \{0.5 < Pr < 2000\}$

Type 25 This correlation by Dittus-Boelter applies to cases of turbulent flow.

Dependence: $\{K, D_h, Re, Pr, T, T_w\}$

Specification: {Turbulent, Gas|Liquid, Forced, Internal, Dittus-Boelter, NoShape, N/A}

Correlation: $Nu = 0.023Re^{0.8}Pr^e$

$$e = \begin{cases} 0.3 & T_w < T \\ 0.4 & \text{else} \end{cases}$$

Range: $\{10000 < Re < 1000000\}, \{0.7 < Pr < 160\}$

Type 26 This correlation by Sieder-Tate applies to cases of turbulent gas flow.

Dependence: $\{K, D_h, Re, Pr, T, T_w\}$

Specification: {Turbulent, Gas, Forced, Internal, Sieder-Tate, NoShape, N/A}

Correlation: $Nu = 0.027Re^{0.8}Pr^{0.3333} \left(\frac{T}{T_w}\right)^{0.098}$

Range: $\{10000 < Re < 1000000\}, \{0.7 < Pr < 160\}$

Type 27 This correlation by Whitaker applies to cases of gas flow over a sphere.

Dependence: $\{K, D_h, Re, Pr, T, T_w\}$

Specification: $\{\text{Both, Gas, Forced, External, Whitaker, Sphere, N/A}\}$

$$\text{Correlation: } Nu = 2 + (0.4\sqrt{Re} + 0.06Re^{0.6667})Pr^{0.4}\left(\frac{T}{T_w}\right)^{0.175}$$

Range: $\{3.5 < Re < 76000\}, \{0.71 < Pr < 380\}$

Type 28 This correlation by Hilpert applies to cases of cylinder in cross flow.

Dependence: $\{K, D_h, Re, Pr, T, T_w\}$

Specification: $\{\text{Both, Gas, Forced, External, Hilpert, Cylinder, Crossflow}\}$

$$\text{Correlation: } Re = Re\left(\frac{T}{T_f}\right)^{0.7}, Nu = C_1 Re^{C_2} Pr^{0.3333}$$

$$(C_1, C_2) = \begin{cases} (0.989, 0.33) & Re < 4 \\ (0.911, 0.385) & Re < 40 \\ (0.683, 0.466) & Re < 4000 \\ (0.193, 0.618) & Re < 40000 \\ (0.027, 0.805) & \text{else} \end{cases}$$

Range: $\{0.4 < Re < 400000\}$

Type 34 This correlation by Zhulkauskas applies to cases of cylinder in cross flow.

Dependence: $\{K, D_h, Re, Pr, T, T_w\}$

Specification: $\{\text{Both, Gas, Forced, External, Zhulkauskas, Cylinder, Crossflow}\}$

$$\text{Correlation: } T_f = \frac{T+T_w}{2}, Re = Re\left(\frac{T}{T_f}\right)^{0.7}, Nu = C_1 Re^{C_2} Pr^{C_3}$$

$$(C_1, C_2) = \begin{cases} (0.989, 0.33) & Re < 4 \\ (0.911, 0.385) & Re < 40 \\ (0.683, 0.466) & Re < 4000 \\ (0.027, 0.805) & \text{else} \end{cases}$$

$$C_3 = \begin{cases} 0.36 & Pr > 10 \\ 0.37 & \text{else} \end{cases}$$

Range: $\{1 < Re < 1000000\}, \{0.7 < Pr < 500\}$

Type 35 This correlation by Churchill-Bernstein applies to cases of cylinder in cross flow.

Dependence: $\{K, D_h, Re, Pr, T, T_w\}$

Specification: $\{\text{Both, Gas, Forced, External, Churchill-Bernstein, Cylinder, Crossflow}\}$

$$\text{Correlation: } T_f = \frac{T+T_w}{2}, Re = Re\left(\frac{T}{T_f}\right)^{0.7},$$

$$Nu = 0.3 + \frac{0.62\sqrt{Re}Pr^{0.3333}}{(1+(0.4/Pr)^{0.6667})^{0.25}}(1 + (Re/282000)^{0.625})^{0.8}$$

Range: $\{0.2 < Re * Pr\}$

Type 36 This correlation applies to cases of flow over a flat plate.

Dependence: { K, D_h , Re, Pr, T, T_w }

Specification: {Laminar, Gas, Forced, External, NoAuthor, Flat_Plate, Local}

Correlation: $T_f = \frac{T+T_w}{2}$, $Re = Re \cdot (T/T_f)^{0.7}$, $Nu = 0.332\sqrt{Re}Pr^{0.3333}$

Range: { $0.6 < Pr$ }

Type 37 This correlation applies to cases of flow over a flat plate.

Dependence: { K, D_h , Re, Pr, T, T_w }

Specification: {Laminar, Gas, Forced, External, NoAuthor, Flat_Plate, Average}

Correlation: $T_f = \frac{T+T_w}{2}$, $Re = Re \cdot (T/T_f)^{0.7}$, $Nu = 0.664\sqrt{Re}Pr^{0.3333}$

Range: { $0.6 < Pr$ }

Type 38 This correlation applies to cases of flow over a flat plate.

Dependence: { K, D_h , Re, Pr, T, T_w }

Specification: {Turbulent, Gas, Forced, External, NoAuthor, Flat_Plate, N/A}

Correlation: $T_f = \frac{T+T_w}{2}$, $Re = Re \cdot (T/T_f)^{0.7}$, $Nu = 0.0296Re^{0.8}Pr^{0.3333}$

Range: { $0.6 < Pr < 60$ }

Type 39 This correlation by Sieder-Tate applies to cases of turbulent liquid flow.

Dependence: { K, D_h , Re, Pr, T, T_w , μ }

Specification: {Turbulent, Liquid, Forced, Internal, Sieder-Tate, NoShape, N/A}

Correlation: $\mu_w = \left(\mu^{-0.2661} + \frac{T_w - T}{37.073} \right)^{-3.758}$, $Nu = 0.027Re^{0.8}Pr^{0.3333} \left(\frac{\mu}{\mu_w} \right)^{0.14}$

Range: { $10000 < Re < 1000000$ }, { $0.7 < Pr < 160$ }

Type 58 This correlation by Churchill-Chu applies to free convection from a vertical surface, or non-vertical surface if angle is less than 60° (measured from vertical).

Dependence: { K, D_h , Pr, T, T_w , L, g, ρ , μ , θ }

Specification: {Laminar, Gas, Free, External, Churchill-Chu,

Vertical_Or_Angle_Surface, N/A}

Correlation:

$$x = L^3, \beta = \frac{1}{T_f}, T_f = \frac{T + T_w}{2}, \rho_f = \rho \frac{T}{T_f}, \mu_f = \mu(T_f/T)^{0.7}$$

$$Gr = g \cos(\theta) x (\rho_f)^2 \frac{|T_w - T|}{T_f \mu_f^2}, Ra = Gr Pr$$

$$Nu = 0.68 + 0.67 \frac{Ra^{0.25}}{(1 + (0.492/Pr)^{0.565})^{0.4444}}$$

Range: { $Ra < 1e^9$ }, { $\theta < 60^\circ$ }

Type 59 This correlation by Churchill-Chu applies to free convection from a vertical surface, or non-vertical surface if angle is less than 60° (measured from vertical).

Dependence: $\{K, D_h, Pr, T, T_w, L, g, \rho, \mu, \theta, \beta\}$

Specification: $\{\text{Laminar, Liquid, Free, External, Churchill-Chu, Vertical\_Or\_Angle\_Surface, N/A}\}$

Correlation:

$$x = \beta L^3, T_f = \frac{T + T_w}{2}, \mu_f = \left(\mu^{-0.2661} + \frac{T_f - T}{37.073} \right)^{-3.758}, Pr = Pr \cdot \mu_f / \mu$$

$$Gr = gx(\rho)^2 \frac{|T_w - T|}{T_f \mu_f^2}, Ra = Gr Pr$$

$$Nu = 0.68 + 0.67 \frac{Ra^{0.25}}{(1 + (0.492/Pr)^{0.565})^{0.4444}}$$

Range: $\{Ra < 1e^9\}, \{\theta < 60^\circ\}$

Type 60 This correlation by Churchill-Chu applies to free convection from a vertical surface.

Dependence: $\{K, D_h, Pr, T, T_w, L, g, \rho, \mu\}$

Specification: $\{\text{Both, Gas, Free, External, Churchill-Chu, Vertical\_surface, N/A}\}$

Correlation:

$$x = L^3, \beta = \frac{1}{T_f}, T_f = \frac{T + T_w}{2}, \rho_f = \rho \frac{T}{T_f}, \mu_f = \mu(T_f/T)^{0.7}$$

$$Gr = gx(\rho_f)^2 \frac{|T_w - T|}{T_f \mu_f^2}, Ra = Gr Pr$$

$$Nu = \left(0.825 + \frac{0.387 Ra^{0.16667}}{(1 + (0.492/Pr)^{0.5625})^{0.2963}} \right)^2$$

Type 61 This correlation by McAdams applies to free convection from a horizontal surface; either the upper surface of a heated plate or the lower surface of a cooled plate.

Dependence: $\{K, D_h, Pr, T, T_w, L, g, \rho, \mu\}$

Specification: $\{\text{Both, Gas, Free, External, McAdams, Horizontal\_Plate\_OnHC, N/A}\}$

Correlation:

$$x = L^3, \beta = \frac{1}{T_f}, T_f = \frac{T + T_w}{2}, \rho_f = \rho \frac{T}{T_f}, \mu_f = \mu(T_f/T)^{0.7}, Gr = gx(\rho_f)^2 \frac{|T_w - T|}{T_f \mu_f^2}, Ra = Gr Pr$$

$$Nu = \begin{cases} 0.54 Ra^{0.25} & Ra < 1e^7 \\ 0.15 Ra^{0.3333} & \text{else} \end{cases}$$

Range: $\{1e^4 < Ra < 1e^{11}\}$

Type 62 This correlation by McAdams applies to free convection from a horizontal surface; either the upper surface of a cooled plate or the lower surface of a heated plate.

Dependence: $\{K, D_h, Pr, T, T_w, L, g, \rho, \mu\}$

Specification: $\{\text{Both, Gas, Free, External, McAdams, Horizontal\_Plate\_OffHC, N/A}\}$

Correlation:

$$x = L^3, \beta = \frac{1}{T_f}, T_f = \frac{T + T_w}{2}, \rho_f = \rho \frac{T}{T_f}, \mu_f = \mu(T_f/T)^{0.7}, Gr = gx(\rho_f)^2 \frac{|T_w - T|}{T_f \mu_f^2}, Ra = GrPr$$

$$Nu = 0.27Ra^{0.25}$$

Range: $\{1e^5 < Ra < 1e^{10}\}$

Type 63 This correlation by Morgan applies to free convection from a horizontal cylinder.

Dependence: $\{K, D_h, Pr, T, T_w, L, g, \rho, \mu\}$

Specification: $\{\text{Both, Gas, Free, External, Morgan, Horizontal\_Cylinder, N/A}\}$

Correlation:

$$x = L^3, \beta = \frac{1}{T_f}, T_f = \frac{T + T_w}{2}, \rho_f = \rho \frac{T}{T_f}, \mu_f = \mu(T_f/T)^{0.7}, Gr = gx(\rho_f)^2 \frac{|T_w - T|}{T_f \mu_f^2}, Ra = GrPr$$

$$Nu = C_1 Ra^{C_2}$$

$$(C_1, C_2) = \begin{cases} (0.675, 0.058) & Ra < 1e^{-2} \\ (1.02, 0.148) & Ra < 100 \\ (0.85, 0.188) & Ra < 10000 \\ (0.48, 0.25) & Ra < 1e^7 \\ (0.125, 0.333) & \text{else} \end{cases}$$

Range: $\{1e^{-10} < Ra < 1e^{12}\}$

Type 64 This correlation by Churchill-Chu applies to free convection from a horizontal cylinder.

Dependence: $\{K, D_h, Pr, T, T_w, L, g, \rho, \mu\}$

Specification: $\{\text{Both, Gas, Free, External, Churchill-Chu, Horizontal\_Cylinder, N/A}\}$

Correlation:

$$x = L^3, \beta = \frac{1}{T}, T_f = \frac{T + T_w}{2}, \rho_f = \rho \frac{T}{T_f}, \mu_f = \mu(T_f/T)^{0.7}, Gr = gx(\rho_f)^2 \frac{|T_w - T|}{T_f \mu_f^2}, Ra = GrPr$$

$$Nu = \left(0.6 + \frac{0.387Ra^{0.16667}}{(1 + (0.559/Pr)^{0.5625})^{0.2963}}\right)^2$$

Range: $\{1e^{-5} < Ra < 1e^{12}\}$

Type 65 This correlation by Churchill-Chu applies to free convection from a sphere.

Dependence: $\{K, D_h, Pr, T, T_w, L, g, \rho, \mu\}$

Specification: {Both, Gas, Free, External, Churchill-Chu, Sphere, N/A}

Correlation:

$$x = L^3, \beta = \frac{1}{T}, T_f = \frac{T + T_w}{2}, \rho_f = \rho \frac{T}{T_f}, \mu_f = \mu (T_f/T)^{0.7}, Gr = gx(\rho_f)^2 \frac{|T_w - T|}{T_f \mu_f^2}, Ra = GrPr$$

$$Nu = 2 + \frac{0.589Ra^{0.25}}{(1 + (0.469/Pr)^{0.5625})^{0.4444}}$$

Range: $\{1e^{11} < Ra, 0.7 < Pr\}$

Type 72 This correlation by Gnielinski applies to cases of turbulent gas flow in a circular tube with friction factor correlation for smooth surfaces.

Dependence: {K, D_h , Re, Pr, f}

Specification: {Turbulent, Gas, Forced, Internal, Gnielinski, Horizontal_Cylinder, N/A}

Correlation: $Nu = \frac{\frac{f}{8}(Re-1000)Pr}{1 + 12.7\sqrt{\frac{f}{8}}(Pr^{0.6667}-1)}$

Range: $\{3000 < Re < 5000000\}, \{0.5 < Pr < 2000\}$

Type 73 This modified correlation by Gnielinski applies to cases of turbulent flow in an annulus with friction factor correlation for annular surfaces where the inner wall is heated and the outer wall is insulated.

Dependence: {K, D_h , Re, Pr, f, r, T, T_w , Pr_w }

Specification: {Turbulent, Gas|Liquid, Forced, Internal, Modified_Gnielinski, Annulus, Insulated_OuterWall}

Correlation:

$$F = 0.75r^{-0.17}, b = 1.07 + \frac{900}{Re} - \frac{0.63}{1 + 10Pr}$$

$$Nu = cF \frac{\frac{f}{8}RePr}{b + 12.7\sqrt{\frac{f}{8}}(Pr^{0.6667} - 1)}$$

$$c = \begin{cases} 1 & \text{GAS and } T > T_w \\ \left(\frac{T}{T_w}\right)^{0.45} & \text{GAS and } T < T_w \\ \left(\frac{Pr}{Pr_w}\right)^{0.11} & \text{LIQUID} \end{cases}$$

Range: $\{10000 < Re\}$

Type 74 This modified correlation by Gnielinski applies to cases of turbulent flow in an annulus with friction factor correlation for annular surfaces where the inner wall is insulated and the outer wall is heated.

Dependence: {K, D_h , Re, Pr, f, r, T, T_w , Pr_w }

Specification: {Turbulent, Gas|Liquid, Forced, Internal, Modified_Gnielinski, Annulus, Insulated_InnerWall}

Correlation:

$$F = 0.9 - 0.15r^{0.6}, b = 1.07 + \frac{900}{Re} - \frac{0.63}{1 + 10Pr}$$

$$Nu = cF \frac{\frac{f}{8} Re Pr}{b + 12.7 \sqrt{\frac{f}{8}} (Pr^{0.6667} - 1)}$$

$$c = \begin{cases} 1 & \text{GAS and } T > T_w \\ \left(\frac{T}{T_w}\right)^{0.45} & \text{GAS and } T < T_w \\ \left(\frac{Pr}{Pr_w}\right)^{0.11} & \text{LIQUID} \end{cases}$$

Range: $\{10000 < Re\}$

34.1.3. Usage

The convection correlations can be used in two distinct use cases, forced convection through a channel and free convection heat transfer. In the case of forced convection the calculation of flow velocity in the channel coupled with the computed bulk/reference temperature of the fluid enables characterization of the flow. This enables the evaluation of Reynolds number and Prandtl number using the average film temperature. These two parameters are then used in the chosen forced flow correlation. An example input for the convection boundary condition is shown below.

```
begin convective flux boundary condition insideWall
  add surface surface_2
  use advective bar airBar bulknodes
  USE CORRELATION CONVECTION MODEL FlowInAnnulus
end convective flux boundary condition insideWall
```

For free convection heat transfer the far-field temperature can be modeled using a bulk volume element [31.1](#). This temperature is used in evaluation of film temperature properties needed for calculation of the correlation Grashoff number.

Cases in which the far-field temperature should remain constant (the convective surface is surrounded by an infinite fluid reservoir), are modeled by assigning a large constant volume to the bulk volume element. This will produce solutions in which the bulk volume element temperature will fluctuate while remaining fairly stable near the specified constant temperature value. Cases for which the convective surface is bounded (enclosed) are modeled by assigning the appropriate surrounding volume to the bulk volume element (i.e. the fluid is assumed to be perfectly mixed). Note that in this case the bulk volume element need not exist on the initial discretization/mesh as it can be created internally upon startup.

Free convection problems where a variation of temperature is desired requires that the meshed discretization contain a bulk volume element. This bulk volume element will be referenced in one of two ways through the bulk volume element command block, matching the name of the command block or with a "use block" command line in the command block. Additionally the mesh must also

contain a nodeset for the bulk volume element node. This will enable a direct association of the bulk volume element with a boundary condition that defines the variation of the far-field temperature. An example of this usage is shown below.

```
Begin Temperature Boundary Condition fluid
  add surface nodelist_1    # defined on the bulk volume element node
  Temperature Time function is fluid_temp_time
End
```

```
Begin Bulk Fluid Element aBulkNode
  material = aBulk
  Initial Temperature = 288.0
  bulk element volume = constant v = 1.0e4
  bulk eq energy for temperature using p0 with mass
  use block block_2        # block_2 must exist in the mesh
End
```

```
begin convective flux boundary condition outsideWall
  add surface surface_2
  use bulk element aBulkNode
  USE CORRELATION CONVECTION MODEL FreeConv
end convective flux boundary condition outsideWall
```

34.1.4. Visualization

Aria provides a means of outputting the heat transfer coefficient via the solution options command block. It must be noted that for a given surface associated with the correlation heat transfer coefficient, such as in a convective boundary condition coupled to an advective bar, only the actual surface can be used for output. This means that an attempt to construct a sideset on an advective bar and output the coefficients on the bar will fail because it is not a part of the associated boundary condition. An example of the syntax is given below:

```
begin solution options
  post process nodal normalized heat_transfer_coefficient on surface_2 as HTCp
end
```

34.2. HEAT TRANSFER CORRELATION COEFFICIENT

Scope: Equation System

```
Begin Heat Transfer Correlation Coefficient COEFF name
```

```
  Apply Gnielinski Film Gradient Correction [ With Exponent {=|are|
  is} Exponent ]
```


Apply Hausen Entrance Effect Correction [Maximum Correction {=|are|is} *MaxCorrection*]

Characteristic Length {=|are|is} *Dh*

Compute *ComputeCorrParam* [Model {=|are|is} *Value...*]

Density {=|are|is} *rho*

Entrance Length {=|are|is} *De*

Expansion Coefficient {=|are|is} *beta*

Fluid Phase {=|are|is} *FluidPhase*

Friction Factor {=|are|is} *f*

Gravitational Constant {=|are|is} *g*

Kinematic Viscosity {=|are|is} *nu*

Laminar Correlation {=|are|is} Type *CorrelationType*

Porosity {=|are|is} *phi*

Prandtl Number {=|are|is} *Pr*

Reynolds Number {=|are|is} *Re*

Turbulent Correlation {=|are|is} Type *CorrelationType*

Temperature {=|are|is} *t*

Transition Reynolds Number {=|are|is} *Rex*

Velocity {=|are|is} *v*

Wall Angle {=|are|is} *theta*

Wall Length {=|are|is} *l*

Wall Temperature {=|are|is} *Tw*

End

Summary Specified heat transfer correlation coefficient model.

Description Enables the user to specify a correlation model for use with computing heat transfer coefficients in conjunction with advective bar networks.

34.2.1. Apply Gnielinski Film Gradient Correction

Scope: Heat Transfer Correlation Coefficient

Apply Gnielinski Film Gradient Correction [With Exponent {=|are|is}
Exponent]

Parameter	Value	Default
<i>Exponent</i>	real	NONE

Summary Enable a Gnielinski film temperature gradient correction factor to account for variation of fluid properties with temperature when computing the pipe and annular flow correlation heat transfer coefficients (Types 23, 25, 72-74).

Description For gas phase convection the heat transfer coefficient correlations include a correction factor of the form $\left(\frac{T}{T_w}\right)^n$.

For gas cooling $\left(\frac{T}{T_w}\right) > 1.0$ $n = 0$.

For gas heating $0.5 < \left(\frac{T}{T_w}\right) < 1.0$, n varies for different gases but $n = 0.45$ is generally recommended. For CO_2 and steam $n = 0.15$.

For liquids the correction factor is a function of bulk fluid and wall Prandtl number $\left(\frac{Pr_b}{Pr_w}\right)^{0.11}$.

34.2.2. Apply Hausen Entrance Effect Correction

Scope: Heat Transfer Correlation Coefficient

Apply Hausen Entrance Effect Correction [Maximum Correction {=|are|is}
MaxCorrection]

Parameter	Value	Default
<i>MaxCorrection</i>	real	10

Summary Enable the Hausen entrance effect correction factor for pipe and annular flow correlation heat transfer coefficients (Types 23, 25, 72-74).

Description Applies a correction factor of the form $\left(1 + \frac{d_H}{L}\right)^{\frac{2}{3}}$ to the heat transfer coefficient where d_H is the hydraulic diameter and L is the distance from the pipe or annulus entrance to the point the flux is applied. By default the maximum value of the correction is 10, it can optionally be set using the MaxCorrection parameter in this command line. For $L < L_{min}$ the correction factor is not applied. This correction factor may only be applied when the correlation is being used with an advective bar model to represent the fluid flow.

34.2.3. Characteristic Length

Scope: Heat Transfer Correlation Coefficient

Characteristic Length {=|are|is} *Dh*

Parameter	Value	Default
<i>Dh</i>	real	undefined

Summary Specifies the characteristic length for parameter computations such as Reynolds Number, etc.

34.2.4. Compute

Scope: Heat Transfer Correlation Coefficient

Compute *ComputeCorrParam* [Model {=|are|is} *Value...*]

Parameter	Value	Default
<i>ComputeCorrParam</i>	{annulus diameter ratio characteristic length density fluid temperature fluid velocity friction factor kinematic viscosity prandtl number reynolds number wall prandtl number wall temperature}	undefined

Summary Specifies that model parameter be computed through such means as extraction, generic form, specific model, etc. Current options for the parameters and associated models include

CHARACTERISTIC LENGTH: {Hydraulic Diameter | Wetted Perimeter}

FLUID VELOCITY: This should always be set to the name of the advection velocity used in the energy equation. This will most likely be *advection velocity* which is the internal variable used in Aria but may be set manually to anything else such as a user defined velocity field. FRICTION FACTOR: {Smooth Tube}

34.2.5. Density

Scope: Heat Transfer Correlation Coefficient

Density {=|are|is} *rho*

Parameter	Value	Default
<i>rho</i>	real	undefined

Summary Specify a density to either compute or specify by value for usage with a correlation convection coefficient.

34.2.6. Entrance Length

Scope: Heat Transfer Correlation Coefficient

Entrance Length {=|are|is} *De*

Parameter	Value	Default
<i>De</i>	real	undefined

Summary Specify an entrance length for usage with a correlation convection coefficient.

34.2.7. Expansion Coefficient

Scope: Heat Transfer Correlation Coefficient

Expansion Coefficient {=|are|is} *beta*

Parameter	Value	Default
<i>beta</i>	real	undefined

Summary Specify an expansion coefficient by value for usage with a correlation convection coefficient.

34.2.8. Fluid Phase

Scope: Heat Transfer Correlation Coefficient

Fluid Phase {=|are|is} *FluidPhase*

Parameter	Value	Default
<i>FluidPhase</i>	{gas liquid}	GAS

Summary Specify the fluid phase for usage with a correlation convection coefficient.

34.2.9. Friction Factor

Scope: Heat Transfer Correlation Coefficient

Friction Factor {=|are|is} *f*

Parameter	Value	Default
<i>f</i>	real	undefined

Summary Specify a friction factor to either compute or specify by value for usage with a correlation convection coefficient.

34.2.10. Gravitational Constant

Scope: Heat Transfer Correlation Coefficient

Gravitational Constant {=|are|is} *g*

Parameter	Value	Default
<i>g</i>	real	undefined

Summary Specify a gravitational constant by value for usage with a correlation convection coefficient.

34.2.11. Kinematic Viscosity

Scope: Heat Transfer Correlation Coefficient

Kinematic Viscosity {=|are|is} *nu*

Parameter	Value	Default
<i>nu</i>	real	undefined

Summary Specify a kinematic viscosity to either compute or specify by value for usage with a correlation convection coefficient.

34.2.12. Laminar Correlation

Scope: Heat Transfer Correlation Coefficient

Laminar Correlation {=|are|is} Type *CorrelationType*

Parameter	Value	Default
<i>CorrelationType</i>	{1 14 15 18 2 21 23 25 26 27 28 3 34 35 36 37 38 39 4 5 58 59 60 61 62 63 64 65 72 73 74}	undefined

Summary Specifies the laminar correlation model.

34.2.13. Porosity

Scope: Heat Transfer Correlation Coefficient

Porosity {=|are|is} *phi*

Parameter	Value	Default
<i>phi</i>	real	undefined

Summary Specify a Porosity to either compute or specify by value for usage with a correlation convection coefficient.

34.2.14. Prandtl Number

Scope: Heat Transfer Correlation Coefficient

Prandtl Number {=|are|is} *Pr*

Parameter	Value	Default
<i>Pr</i>	real	undefined

Summary Specify a Prandtl number to either compute or specify by value for usage with a correlation convection coefficient.

34.2.15. Reynolds Number

Scope: Heat Transfer Correlation Coefficient

Reynolds Number {=|are|is} *Re*

Parameter	Value	Default
<i>Re</i>	real	undefined

Summary Specify a Reynold's number to either compute or specify by value for usage with a correlation convection coefficient.

34.2.16. Turbulent Correlation

Scope: Heat Transfer Correlation Coefficient

Turbulent Correlation {=|are|is} Type *CorrelationType*

Parameter	Value	Default
<i>CorrelationType</i>	{1 14 15 18 2 21 23 25 26 27 28 3 34 35 36 37 38 39 4 5 58 59 60 61 62 63 64 65 72 73 74}	undefined

Summary Specifies the turbulent correlation model.

34.2.17. Temperature

Scope: Heat Transfer Correlation Coefficient

Temperature {=|are|is} *t*

Parameter	Value	Default
<i>t</i>	real	undefined

Summary Specify a Fluid Temperature to either compute or specify by value for usage with a correlation convection coefficient.

34.2.18. Transition Reynolds Number

Scope: Heat Transfer Correlation Coefficient

Transition Reynolds Number {=|are|is} *Rex*

Parameter	Value	Default
<i>Rex</i>	real	undefined

Summary Specify a transition Reynolds number to either compute or specify by value for usage with a correlation convection coefficient.

34.2.19. Velocity

Scope: Heat Transfer Correlation Coefficient

Velocity {=|are|is} *v*

Parameter	Value	Default
<i>v</i>	real	undefined

Summary Specify a velocity to either compute or specify by value for usage with a correlation convection coefficient.

34.2.20. Wall Angle

Scope: Heat Transfer Correlation Coefficient

Wall Angle {=|are|is} *theta*

Parameter	Value	Default
<i>theta</i>	real	undefined

Summary Specify a wall angle by value for usage with a correlation convection coefficient.

34.2.21. Wall Length

Scope: Heat Transfer Correlation Coefficient

Wall Length {=|are|is} *l*

Parameter	Value	Default
<i>l</i>	real	undefined

Summary Specify a wall length by value for usage with a correlation convection coefficient.

34.2.22. Wall Temperature

Scope: Heat Transfer Correlation Coefficient

Wall Temperature {=|are|is} T_w

Parameter	Value	Default
T_w	real	undefined

Summary Specify a Wall Temperature to either compute or specify by value for usage with a correlation convection coefficient.

34.2.23. Use Correlation Convection Model

Scope:

Use Correlation Convection Model *Name*

Parameter	Value	Default
<i>Name</i>	string	undefined

Summary Specifies correlation model for convection coefficient

35. CHEMISTRY OVERVIEW

Aria provides two ways of modeling chemical contributions to the transport equations it solves: CHEMEQ and General Chemistry. The details of these two approaches are described in the following chapters, and the purpose of this overview is to describe the differences between these approaches and provide guidelines for which one to select for a given application.

35.1. FEATURE COMPARISON

As a quick reference, a list of features supported by both solvers is shown in Table 35.1 below.

As the table illustrates, CHEMEQ is best suited for evaluating reactions without species transport in order to obtain a source term for the energy equation. It also links to pressurization zones (described in a later chapter) to enable reduced-cost pressurization calculations. CHEMEQ stores its species concentrations in an element field and updates that element field in time while providing a source term for the energy equation.

On the other hand, General Chemistry is best suited for situations where you want to resolve species transport and reaction. General Chemistry is designed only to provide source terms, so there must be a linear system set up for each DOF (energy, species concentrations, etc...) to actually update its values in time. For cases where the species are not transported, the added cost of setting up this linear system makes CHEMEQ the more efficient choice. One advantage of General Chemistry is the updated reaction input format which allows you to mix different types of reactions in the same mechanism, which is not possible in CHEMEQ unless you implement it yourself in a user subroutine.

Feature	CHEMEQ	General Chemistry
Arrhenius Reactions	X	X
Distributed Arrhenius Reactions	X	X
Pressure Dependent Reactions	X	X
User Subroutine Reactions	X	
Time Dependent Reactions		X
General Form Reactions		X
Prout-Tompkins Reactions	X	X
Can Mix Reaction Types		X
Can be Solved with Species Transport		X
Can be Solved Without Transport	X	
Porous System Reactions		X
Activation Temperature	X	
Deactivation Temperature	X	
Activation Time	X	X
Deactivation Time	X	X
General ODE solver interface	X	X
Arbitrary Concentration Units	X	X
Can link to pressurization zones	X	
Segregated solve	X	X
Coupled solve		X
Provides Energy Source	X	X
Provides Species Sources		X
Reversible Reactions		
Equilibrium Chemistry		

Table 35.1-1.. Feature table for CHEMEQ and General Chemistry.

36. CHEMEQ REFERENCE

36.1. COMMON INPUT STYLE

The chapter on general chemistry describes a method for entering reactions in individual blocks. ChemEq also supports this syntax for entering reactions, which looks like

```
Begin Reaction R1
  Reaction is A -> B
  Rate Function = Arrhenius  A = 0.1  Ea = 350  R = 1
  Concentration Function = Standard  mu = 1.0 0.0
  Heat of Reaction = -1e6
End
```

You can enter reactions in ChemEq using the legacy syntax described in this chapter, or the new block syntax. You cannot, however, mix the syntaxes.

36.2. CHEMICAL HEATING

Materials undergoing non-diffusive endothermic or exothermic chemical reactions can be modeled in Aria. The effect of such reactions is incorporated into the energy conservation equation as a volumetric heating term, which is calculated from the reaction rates. In this section, we give a brief overview of the equations implemented in Aria¹.

The volumetric heating due to the reactions may be written as

$$\dot{q}(\mathbf{x}, t, T) = \sum_{j=1}^{N_r} R_j r_j, \quad (36.1)$$

where R_j is the known endothermic or exothermic energy release for step j of the reaction, r_j is the calculated reaction rate for the same step, and the summation over the index j is performed for the N_r reaction steps.

Some of the burden of managing the units properly for this expression fall to the user. As described in a subsequent section, you can specify energy release units in the ChemEq block as either per volume or

¹Heat transfer in the presence of chemical reactions is detailed in Glassman's Combustion [43].

per unit mass. The units of $\dot{q}$ are always power per unit volume (e.g. W/m³). When you select the “per unit mass” option, the right hand side of the equation above is multiplied by the local density. For example, if the concentration units are mass fractions, you should use the “per unit mass” option. If the concentration units are mass densities, you should use the “per unit volume” option.

Step j of a multi-step chemical reaction can be expressed using the stoichiometric equation

$$\sum_{i=1}^{N_s} \nu'_{ij} M_i \rightarrow \sum_{i=1}^{N_s} \nu''_{ij} M_i, \quad (36.2)$$

where M_i is the chemical symbol for species i , ν'_{ij} is the stoichiometric coefficient of the reactant species i in reaction step j , ν''_{ij} is the stoichiometric coefficient of the product species i in reaction step j , and N_s represents the number of chemical species. When a species does not occur as a reactant or product in equation (36.2) for a particular reaction step, the corresponding stoichiometric coefficient is set to zero.

The net rate of change in the concentration of the species is determined from the following ordinary differential equation:

$$\frac{dN_i}{dt} = \sum_{j=1}^{N_r} (\nu''_{ij} - \nu'_{ij}) r_j, \quad (36.3)$$

where N_i is the concentration (or mole fraction) for species i . In equations (36.1) and (36.3), the reaction rates are calculated according to the law of mass action

$$r_j = k_j \prod_{i=1}^{N_s} N_i^{\mu_{ij}} \quad \text{for } j = 1, 2, \dots, N_r, \quad (36.4)$$

where k_j is the kinetic coefficient for reaction step j , and μ_{ij} is the given concentration exponent for reaction step j and species i . The kinetic coefficient, k_j , for each reaction step is usually determined from the Arrhenius equation, which may be written as

$$k_j = M_j A_j \exp\left(\frac{-E_j}{RT}\right) \left(\frac{p}{p_0}\right)^{\alpha_j} T^{\beta_j}, \quad (36.5)$$

where A_j is the pre-exponential factor, M_j is the rate multiplier, E_j is the activation energy, R is the appropriate universal gas constant, T is the temperature, β_j is the steric coefficient, p is the pressure, p_0 is a reference pressure and α_j is the pressure exponent factor. Upon substitution of (36.5) and (36.4) into (36.3), we obtain a nonlinear system of ordinary differential equations for the evolution of the chemical species concentrations, namely

$$\frac{dN_i}{dt} = \sum_{j=1}^{N_r} \left[(\nu''_{ij} - \nu'_{ij}) A_j M_j \exp\left(\frac{-E_j}{RT}\right) \left(\frac{p}{p_0}\right)^{\alpha_j} T^{\beta_j} \prod_{k=1}^{N_s} N_k^{\mu_{kj}} \right] \quad (36.6)$$

Equation (36.6), with appropriate initial conditions for the species concentrations, must be solved simultaneously with equation (5.9) to obtain the time evolution of the temperature field and species

concentrations. This is a difficult coupled system of nonlinear equations to solve, because the time scales associated with the chemical reactions can be very different from the time scale associated with conduction. Furthermore, the time scale associated with one chemical reaction step may be very different from the next. An operator splitting strategy is used to decouple the concentration equations from the energy equation at every time step.

Finally, the thermal properties of the chemical material are regarded as weighted averages of the N_s values associated with each species component. Another weighted average that is sometimes useful when interpreting results is the reacted gas fraction, f_{RG} , which is defined as the fraction of reacting material that exists in gas phase,

$$f_{RG} = \frac{(1 - X_c) \sum_{i=1}^{N_s} N_i g_i}{\sum_{i=1}^{N_s} N_i} \quad (36.7)$$

where X_c represents the condensed fraction for the reactive material, and the parameter g_i is defined as

$$g_i = \begin{cases} 1 & \text{if } N_i \text{ is a gas phase species} \\ 0 & \text{if } N_i \text{ is not a gas phase species} \end{cases} \quad (36.8)$$

36.3. ALTERNATE REACTION MODELS

The default reaction model, Arrhenius, was described in the previous section. Alternate reaction models can be selected for the ChemEq block, and are described in this section.

36.3.1. Prout-Tompkins Reaction Model

The Prout-Tompkins reaction model is used for a reaction with only one product and one reactant. The concentration of the reactant is noted as α , and must be a normalized quantity (typically mass fraction). The three additional required parameters for the model are m , n , and p . The rate of this reaction is then evaluated as:

$$r_0 = A_0 \exp\left(\frac{-E_0}{RT}\right) \alpha^n [1 - (1 - 10^{-p}) \alpha]^m \quad (36.9)$$

The values of m , n , and p are provided to the ChemEq description using a data block.

36.4. CONCENTRATION UNITS

The units of the concentration, N_i , used in the formulation in the previous section are up to the user. They could be molar concentrations, mole fractions, mass fractions, or mass concentrations (densities). For the purpose of evaluating the reactions described in the previous section, this choice does not matter. However, if you are using a pressurization model in conjunction with the ChemEq model, you

have to specify which unit system your concentrations are in so the moles of gas produced can be calculated correctly.

You can also extract the concentrations of individual species from ChemEq to expressions, to allow further manipulations like concentration-dependent thermal properties. To use this capability, the units for the ChemEq block must be specified. There is no implicit unit conversion done in this process, so if the ChemEq units are mass fractions, you can only extract them to the mass fraction expressions. Any further conversions required can be done after they are extracted from ChemEq.

36.5. NUMERICAL SOLUTION

Numerical simulations including chemical heating require a coupling of subcycled transient solutions for Equation (36.6) and the energy equation (5.10). Given appropriate initial conditions for the species concentrations and temperatures at each element quadrature point, the strategy employed here is to first solve Equation (36.6) for updated species concentrations and an associated volumetric heating rate. Here solving for values at quadrature points skirts any issues with chemistry averaging for adjacent material blocks. Quadrature point volume heating rates are spatially integrated and applied as a source contribution (5.11) to the energy equation which can then be solved for an updated temperature distribution.

In addition to solving for the chemical chemistry state and heating rates at quadrature points, the CHEMEQ interface returns a characteristic timestep used in its subcycled iteration. Since chemistry is subcycled within the FEM model step this characteristic time step will always be substantially smaller than the time step used for outer iteration. Nevertheless, the chemistry time time step must be considered in the outer iteration time step selection if one is to accurately model the system chemistry. The strategy used here is to enable a user specified scaling of the minimum chemistry time step (via CHEMISTRY STEP MULTIPLIER command) in the time step selection process for the FEM model time step. Selection of the chemistry time step is illustrated schematically in Figure 36.5-1 below. Note that reduction of the CHEMISTRY STEP MULTIPLIER parameter will often cause the overall minimum chemistry time step to dictate the outer iteration time step.

The numerical model for modeling chemical heating is divided into two sections. One contains a detailed description of the chemical system and the other specifies details of how the set of ordinary differential equations (36.6) are to be solved. Command line input for these two aspects of the numerical model are described in the sections which follow.

The detailed chemical system command line descriptions are provided as an input command block embedded within a higher-level Aria Material command block described in Material Properties (4). It is important to note that chemical heating constitutes a volumetric source term contribution to the energy equation, hence the source must be invoked using a command line as described in Source Terms (11). In most cases chemical heating is thermally activated above some threshold temperature and is controlled independently for each element block to which it is applied. Additional controls for activation and deactivation of the chemical system heat source are provided in the CHEMEQ solver section. The activity status for the source on any element block is available for output as a global variable, *block_number_is_on*.




Figure 36.5-1.. Chemistry Time Step Selection

36.6. PARAMETERS FOR CHEMEQ MODEL

Scope: Material Phase

Begin Parameters For Chemeq Model *ModelName*

Activation Energies {=*|are|is*} *activation energies...*

Activation Energy St Devs {=*|are|is*} *activation energy st devs...*

Aux Variable Names {=*|are|is*} *aux variable names...*

Aux Variable Subroutine {=*|are|is*} *aux variable subroutine*

Concentration Exponents For *SpeciesName* {=*|are|is*} *Exponents...*

Concentration Units {=*|are|is*} *concentration units...*

Condensed Fraction {=*|are|is*} *condensed fraction*

Energy Release Units {=*|are|is*} *energy release units*

Energy Releases {=*|are|is*} *energy releases...*

Enthalpies Of Formation {=*|are|is*} *enthalpies of formation...*

Extent Of Reaction Based On *extent of reaction based on...*

Log Preexponential Factors {=*|are|is*} *log preexponential factors...*
 Number Of Reactions {=*|are|is*} *number of reactions*
 Pressure {=*|are|is*} *pressure...*
 Pressure Exponents {=*|are|is*} *pressure exponents...*
 Rate Multiplier {=*|are|is*} *rate multiplier...*
 Reaction Rate Model {=*|are|is*} *reaction rate model*
 Reaction Rate Subroutine {=*|are|is*} *reaction rate subroutine*
 Reference Pressure {=*|are|is*} *reference pressure*
 Species Molecular Weights {=*|are|is*} *species molecular weights...*

 Species Names {=*|are|is*} *species names...*
 Species Phases {=*|are|is*} *species phases...*
 Steric Coefficients {=*|are|is*} *steric coefficients...*
 Stoichiometric Coefficients For *SpeciesName* {=*|are|is*} *Exponents...*
 Begin Reaction *ReactionName*
 End

End

Summary Parameters for the CHEMEQ chemistry model within Aria. The ModelName must appear in a SRC term for an ENERGY equation in order to be applied.

36.6.1. Activation Energies

Scope: Parameters For Chemeq Model

Activation Energies {=*|are|is*} *activation energies...*

Parameter	Value	Default
<i>activation energies</i>	<i>real...</i>	<i>undefined</i>

Summary This command specifies the activation energies for each reaction.

36.6.2. Activation Energy St Devs

Scope: Parameters For Chemeq Model

Activation Energy St Devs {=|are|is} *activation energy st devs...*

Parameter	Value	Default
<i>activation energy st devs</i>	real...	undefined

Summary This command supplies the standard deviations for the activation energies for each reaction. The order is significant, and corresponds to the order in which the Reactions are specified.

36.6.3. Aux Variable Names

Scope: Parameters For Chemeq Model

Aux Variable Names {=|are|is} *aux variable names...*

Parameter	Value	Default
<i>aux variable names</i>	string...	undefined

Summary Supplies the names for any auxiliary variables. The number of auxiliary variables is implied by the size of this list.

Description The entries must be separated by whitespace, without commas. These variables do not participate in the reaction kinetics, but are derived from the species variables and calculated in the user-defined subroutine named via the "AUX VARIABLE SUBROUTINE NAME" line command.

36.6.4. Aux Variable Subroutine

Scope: Parameters For Chemeq Model

Aux Variable Subroutine {=|are|is} *aux variable subroutine*

Parameter	Value	Default
<i>aux variable subroutine</i>	string	undefined

Summary Supplies the name of the user-defined subroutine that performs any auxiliary variable calculations. This command is required if auxiliary variables are named.

36.6.5. Concentration Exponents For

Scope: Parameters For Chemeq Model

Concentration Exponents For *SpeciesName* {=*|are|is*} *Exponents...*

Parameter	Value	Default
<i>SpeciesName</i>	string	undefined
<i>Exponents</i>	real...	undefined

Summary For the given species, this command specifies the concentration exponents for each reaction.

36.6.6. Concentration Units

Scope: Parameters For Chemeq Model

Concentration Units {=*|are|is*} *concentration units...*

Parameter	Value	Default
<i>concentration units</i>	string...	UNKNOWN_UNITS

Summary Specifies the concentration units. This input is only required when using a pressurization model. Valid inputs include: "Mass Fraction", "Mass Fractions", "Mole Fraction", "Mole Fractions", "Mass", "Density", "Moles", or "Molar"

36.6.7. Condensed Fraction

Scope: Parameters For Chemeq Model

Condensed Fraction {=*|are|is*} *condensed fraction*

Parameter	Value	Default
<i>condensed fraction</i>	real	undefined

Summary Specifies mass fraction of the condensed phase.

36.6.8. Energy Release Units

Scope: Parameters For Chemeq Model

Energy Release Units {=*|are|is*} *energy release units*

Parameter	Value	Default
<i>energy release units</i>	{per unit mass per unit volume}	PER VOLUME

Summary Specifies the energy release units for each reaction, PER VOLUME or PER UNIT MASS.

Default is PER VOLUME. If PER UNIT MASS is selected, the specified heat release value is multiplied by the local density.

36.6.9. Energy Releases

Scope: Parameters For Chemeq Model

Energy Releases {=|are|is} *energy releases...*

Parameter	Value	Default
<i>energy releases</i>	real...	undefined

Summary This command specifies the energy release for each reaction.

36.6.10. Enthalpies Of Formation

Scope: Parameters For Chemeq Model

Enthalpies Of Formation {=|are|is} *enthalpies of formation...*

Parameter	Value	Default
<i>enthalpies of formation</i>	real...	undefined

Summary This command specifies the enthalpies of formation for each species

36.6.11. Extent Of Reaction Based On

Scope: Parameters For Chemeq Model

Extent Of Reaction Based On *extent of reaction based on...*

Parameter	Value	Default
<i>extent of reaction based on</i>	string...	undefined

Summary This command supplies the species on which the progress variable for each distributed activation energy depends. The order is significant, and corresponds to the order in which the Reactions are specified.

36.6.12. Log Preexponential Factors

Scope: Parameters For Chemeq Model

Log Preexponential Factors {=*|are|is*} *log preexponential factors...*

Parameter	Value	Default
<i>log preexponential factors</i>	real...	undefined

Summary This command specifies the natural logarithms of the pre-exponential factors for each reaction.

36.6.13. Number Of Reactions

Scope: Parameters For Chemeq Model

Number Of Reactions {=*|are|is*} *number of reactions*

Parameter	Value	Default
<i>number of reactions</i>	integer	undefined

Summary Specifies the number of reactions for this material.

36.6.14. Pressure

Scope: Parameters For Chemeq Model

Pressure {=*|are|is*} *pressure...*

Parameter	Value	Default
<i>pressure</i>	string...	undefined

Summary Specifies the expression for pressure for this material. The preferred option is to use 'Pressure = From_Material_Definition' and put a pressure specification in the material block (e.g. 'Pressure = Pressurization_Model' or 'Pressure = Encore_Function'). If you are using pressurization zones, you must use this approach. Using 'Pressure = Pressurization_Model' here will generate an error.

36.6.15. Pressure Exponents

Scope: Parameters For Chemeq Model

Pressure Exponents {=*|are|is*} *pressure exponents...*

Parameter	Value	Default
<i>pressure exponents</i>	real...	undefined

Summary This command specifies the pressure exponents for each reaction.

36.6.16. Rate Multiplier

Scope: Parameters For Chemeq Model

Rate Multiplier {=*|are|is*} *rate multiplier...*

Parameter	Value	Default
<i>rate multiplier</i>	string...	1

Summary Specifies a generic expression for the rate multiplier for this ChemEq model. This input is optional, and the rate multiplier defaults to 1.0 if this is omitted.

36.6.17. Reaction Rate Model

Scope: Parameters For Chemeq Model

Reaction Rate Model {=*|are|is*} *reaction rate model*

Parameter	Value	Default
<i>reaction rate model</i>	string	undefined

Summary By default, reaction rates are Arrhenius. If this line command is included, then a named reaction rate model can be used. Current options are: "Prout_Tompkins"

36.6.18. Reaction Rate Subroutine

Scope: Parameters For Chemeq Model

Reaction Rate Subroutine {=*|are|is*} *reaction rate subroutine*

Parameter	Value	Default
<i>reaction rate subroutine</i>	string	undefined

Summary By default, reaction rates are Arrhenius. If this line command is included, then the named subroutine is called instead.

36.6.19. Reference Pressure

Scope: Parameters For Chemeq Model

Reference Pressure {=*|are|is*} *reference pressure*

Parameter	Value	Default
<i>reference pressure</i>	real	undefined

Summary Specifies the reference pressure for this material.

36.6.20. Species Molecular Weights

Scope: Parameters For Chemeq Model

Species Molecular Weights {=|are|is} *species molecular weights...*

Parameter	Value	Default
<i>species molecular weights</i>	real...	undefined

Summary Supplies the molecular weight for each chemical species. The order is significant, and corresponds to the order in which the Species Names are specified.

36.6.21. Species Names

Scope: Parameters For Chemeq Model

Species Names {=|are|is} *species names...*

Parameter	Value	Default
<i>species names</i>	string...	undefined

Summary Supplies names for the chemical species. The number of chemical species is implied by the size of this list. The entries must be separated by whitespace, without commas.

36.6.22. Species Phases

Scope: Parameters For Chemeq Model

Species Phases {=|are|is} *species phases...*

Parameter	Value	Default
<i>species phases</i>	{condensed gas}	undefined

Summary Supplies the phase for each chemical species. The order is significant, and corresponds to the order in which the Species Names are specified.

36.6.23. Steric Coefficients

Scope: Parameters For Chemeq Model

Steric Coefficients {=|are|is} *steric coefficients...*

Parameter	Value	Default
<i>steric coefficients</i>	real...	undefined

Summary This command specifies the steric coefficients for each reaction.

36.6.24. Stoichiometric Coefficients For

Scope: Parameters For Chemeq Model

Stoichiometric Coefficients For *SpeciesName* {=*|are|is*} *Exponents...*

Parameter	Value	Default
<i>SpeciesName</i>	string	undefined
<i>Exponents</i>	real...	undefined

Summary For the given species, this command specifies the stoichiometric coefficients for each reaction.

36.7. CHEMEQ SOLVER FOR

Scope: Equation System

Begin Chemeq Solver For *ModelName*

Absolute Tolerance {=*|are|is*} *absTol*

Activation Temperature {=*|are|is*} *T_act*

Activation Temperature Rate {=*|are|is*} *T_dot*

Activation Time {=*|are|is*} *T_init*

Allow Old Heat Generation Method {=*|are|is*} *Bool*

Asymptotic Tolerance {=*|are|is*} *Tol*

Aux Variable *Name* {=*|are|is*} *C_init*

Chemistry Step Multiplier {=*|are|is*} *Dt_cond_over_dt_chem*

Deactivation Temperature {=*|are|is*} *t ChemistryDeactivationAction*

Deactivation Temperature Overshoot {=*|are|is*} *dT_overshoot*

Deactivation Temperature Rate {=*|are|is*} *T_dot ChemistryDeactivationAction*

Deactivation Time {=*|are|is*} *T_stop ChemistryDeactivationAction*

Enable Enthalpy Integration

Epsilon Max {=*|are|is*} *E_max*

Epsilon Min {=*|are|is*} *E_min*

Maximum Substeps {=*|are|is*} *maxSubSteps*

Minimum Chemistry Timestep {=*|are|is*} *Dt_min*

Minimum Concentration For *Name* {=*|are|is*} *C_min*

Ode Solver {=*|are|is*} *odeSolver...*

Percentage Asymptotics {=*|are|is*} *PercentValue*

Post Deactivation Gas Release {=*|are|is*} *gasRelease*

Post Deactivation Heat Release {=*|are|is*} *heatRelease*

Post Deactivation Release Time {=*|are|is*} *releaseTime*

Rate Limiter Factor {=*|are|is*} *rateLimiterFactor*

Relative Tolerance {=*|are|is*} *relTol*

Species *Name* {=*|are|is*} *Conc*

End

Summary Parameters for the CHEMEQ solver applicable to the previously defined material with CHEMEQ model *ModelName*. The CHEMEQ SOLVER model produces no independent action since the *ModelName* must first appear in a SRC term for an ENERGY equation before it be applied.

36.7.1. Absolute Tolerance

Scope: Chemeq Solver For

Absolute Tolerance {=*|are|is*} *absTol*

Parameter	Value	Default
<i>absTol</i>	real	1e-12

Summary Specifies the absolute solution tolerance for the ODE solver

36.7.2. Activation Temperature

Scope: Chemeq Solver For

Activation Temperature {=*|are|is*} *T_act*

Parameter	Value	Default
<i>T_act</i>	real	0.0

Summary Specification of threshold activation temperature for chemistry.

36.7.3. Activation Temperature Rate

Scope: Chemeq Solver For

Activation Temperature Rate {=*|are|is*} *T_dot*

Parameter	Value	Default
<i>T_dot</i>	real	REAL_MAX

Summary Specification of temperature rate limit (*T_dot*) for which chemistry activation occurs.

36.7.4. Activation Time

Scope: Chemeq Solver For

Activation Time {=*|are|is*} *T_init*

Parameter	Value	Default
<i>T_init</i>	real	REAL_MAX

Summary Specification of activation time for chemistry.

36.7.5. Allow Old Heat Generation Method

Scope: Chemeq Solver For

Allow Old Heat Generation Method {=*|are|is*} *Bool*

Parameter	Value	Default
<i>Bool</i>	{false true}	FALSE

Summary Specifies whether to allow the use of the old heat generation method, which is known to not satisfy energy conservation.

36.7.6. Asymptotic Tolerance

Scope: Chemeq Solver For

Asymptotic Tolerance {=*|are|is*} *Tol*

Parameter	Value	Default
<i>Tol</i>	real	100.0

Summary Specifies the asymptotic selection criterion for the chemical rate equations.

36.7.7. Aux Variable

Scope: Chemeq Solver For

Aux Variable *Name* {=|are|is} *C_init*

Parameter	Value	Default
<i>Name</i>	string	undefined
<i>C_init</i>	real	0.0

Summary Specifies the initial concentration for the named auxiliary variable.

36.7.8. Chemistry Step Multiplier

Scope: Chemeq Solver For

Chemistry Step Multiplier {=|are|is} *Dt_cond_over_dt_chem*

Parameter	Value	Default
<i>Dt_cond_over_dt_chem</i>	real	100.0

Summary This command specifies the ratio of the maximum allowed conduction timestep to the smallest, current chemistry time step.

36.7.9. Deactivation Temperature

Scope: Chemeq Solver For

Deactivation Temperature {=|are|is} *t ChemistryDeactivationAction*

Parameter	Value	Default
<i>t</i>	real	REAL_MAX
<i>ChemistryDeactivationAction</i>	{continue terminate}	TERMINATE

Summary Specification of deactivation temperature and how the simulation should proceed after deactivation.

36.7.10. Deactivation Temperature Overshoot

Scope: Chemeq Solver For

Deactivation Temperature Overshoot {=|are|is} *dT_overshoot*

Parameter	Value	Default
<i>dT_overshoot</i>	real	1.0

Summary Specification of acceptable overshoot of the deactivation temperature for the limiting procedure

36.7.11. Deactivation Temperature Rate

Scope: Chemeq Solver For

Deactivation Temperature Rate {=|are|is} T_{dot}
ChemistryDeactivationAction

Parameter	Value	Default
T_{dot}	real	REAL_MAX
<i>ChemistryDeactivationAction</i>	{continue terminate}	TERMINATE

Summary Specification of temperature rate limit (T_{dot}) for deactivation and how the simulation should proceed after deactivation.

36.7.12. Deactivation Time

Scope: Chemeq Solver For

Deactivation Time {=|are|is} T_{stop} *ChemistryDeactivationAction*

Parameter	Value	Default
T_{stop}	real	REAL_MAX
<i>ChemistryDeactivationAction</i>	{continue terminate}	TERMINATE

Summary Specification of deactivation time for chemistry and how the simulation should proceed after deactivation.

36.7.13. Enable Enthalpy Integration

Scope: Chemeq Solver For

Summary Enables integration of enthalpy along with species.

36.7.14. Epsilon Max

Scope: Chemeq Solver For

Epsilon Max {=|are|is} E_{max}

Parameter	Value	Default
E_{max}	real	10.0

Summary Specifies the upper bound convergence criterion and chemistry time scale check.

36.7.15. Epsilon Min

Scope: Chemeq Solver For

Epsilon Min `{=|are|is}` *E_min*

Parameter	Value	Default
<i>E_min</i>	real	0.0001

Summary Specifies the lower bound convergence criterion and chemistry time scale check.

36.7.16. Maximum Substeps

Scope: Chemeq Solver For

Maximum Substeps `{=|are|is}` *maxSubSteps*

Parameter	Value	Default
<i>maxSubSteps</i>	integer	100000

Summary Specifies the maximum number of chemistry substeps per global time step.

36.7.17. Minimum Chemistry Timestep

Scope: Chemeq Solver For

Minimum Chemistry Timestep `{=|are|is}` *Dt_min*

Parameter	Value	Default
<i>Dt_min</i>	real	1.0e-15

Summary Specifies the minimum time step allowed during the solution of the chemical rate equations.

36.7.18. Minimum Concentration For

Scope: Chemeq Solver For

Minimum Concentration For *Name* `{=|are|is}` *C_min*

Parameter	Value	Default
<i>Name</i>	string	undefined
<i>C_min</i>	real	1.0e-12

Summary Specifies the minimum concentration for the named species. This comes with a caveat for transient calculations with long simulation times. The internal implementation within CHEMEQ will always limit the minimum species concentration which implies that a non-zero value for a reactant will always result in species production. This has implications for mass fraction conservation as these errors eventually grow with long simulation times. Reduction of this value helps to reduce the error but this results in a longer run times because the reaction rate equations become stiffer and this results in a smaller chemistry time step being selected. For a typical foam decomposition simulation, this default value is acceptable and for an explosives simulation, the value may be increased to 1.0e-8.

36.7.19. Ode Solver

Scope: Chemeq Solver For

Ode Solver {=|are|is} *odeSolver...*

Parameter	Value	Default
<i>odeSolver</i>	string...	NONE

Summary This command selects the ODE solver to use for a segregated solve. For available options, refer to the 'ODE Solvers' section in the 'Chemistry Solver Reference' chapter of the user manual. This command is required to activate an ODE solver, without it the legacy CHEMEQ solver will be used.

36.7.20. Percentage Asymptotics

Scope: Chemeq Solver For

Percentage Asymptotics {=|are|is} *PercentValue*

Parameter	Value	Default
<i>PercentValue</i>	real	0.0

Summary Specifies the percentage of the chemical rate equations that will always be solved using asymptotics.

36.7.21. Post Deactivation Gas Release

Scope: Chemeq Solver For

Post Deactivation Gas Release {=|are|is} *gasRelease*

Parameter	Value	Default
<i>gasRelease</i>	real	0.01

Summary Amount of gas to be released uniformly after deactivation (units are always in moles per volume).

36.7.22. Post Deactivation Heat Release

Scope: Chemeq Solver For

Post Deactivation Heat Release {=|are|is} *heatRelease*

Parameter	Value	Default
<i>heatRelease</i>	real	0.01

Summary Amount of energy to be released uniformly after deactivation. The units must be consistent with the base ChemEq heat release units (energy per volume or energy per mass).

36.7.23. Post Deactivation Release Time

Scope: Chemeq Solver For

Post Deactivation Release Time {=|are|is} *releaseTime*

Parameter	Value	Default
<i>releaseTime</i>	real	0.01

Summary Time after deactivation for constant heat and gas sources to be active

36.7.24. Rate Limiter Factor

Scope: Chemeq Solver For

Rate Limiter Factor {=|are|is} *rateLimiterFactor*

Parameter	Value	Default
<i>rateLimiterFactor</i>	real	0.01

Summary Enables a rate limiter and specifies what fraction of the fluid time step to consider for the limiter time step.

36.7.25. Relative Tolerance

Scope: Chemeq Solver For

Relative Tolerance {=|are|is} *relTol*

Parameter	Value	Default
<i>relTol</i>	real	1e-6

Summary Specifies the relative solution tolerance for the ODE solver

36.7.26. Species

Scope: Chemeq Solver For

Species *Name* {=|are|is} *Conc*

Parameter	Value	Default
<i>Name</i>	string	undefined
<i>Conc</i>	real	0.0

Summary Specifies the initial concentration for the named species.

37. GENERAL CHEMISTRY REFERENCE

37.1. INTRODUCTION

Aria provides a general capability to specify arbitrary chemical mechanisms of irreversible reactions as part of a simulation. Both homogeneous (single phase) and volumetric heterogeneous (multiple material phases) mechanisms are currently supported. The mechanism is defined by the user in the material block in the input deck, and this definition will then provide species, mass, and energy source terms that can be inserted into the various transport equations being solved.

It may be more convenient to specify the mechanism in either a mole-based unit system or a mass-based unit system, so both capabilities are provided. The formulation of both versions of this functionality are described in the following sections.

Reactions can be specified in two ways in a general chemistry block. The first way uses a format similar to CHEMEQ, where all reactions have the same form, and you enter blocks of coefficients. These inputs are described in the following section. The second method is to enter individual reaction blocks, which is described in the Reaction Inputs section later in this chapter. These reaction blocks are placed inside the general chemistry block.

An example input using the traditional input style is

```
BEGIN general chemistry gas_chem
  Species Names = As Bs
  Number of Reactions = 1
  Species Variable Name = density
  Universal Gas Constant = 1.0
  Preexponential Factors = 0.1
  Steric Coefficients      = 0.0
  Activation Energies      = 350.0
  Concentration Exponents for As      = 1.0
  Concentration Exponents for Bs      = 0.0
  Stoichiometric Coefficients for As   = -1.0
  Stoichiometric Coefficients for Bs   = 1.0
  Heats of Reaction          = -1e6
END
```


and the same mechanism input using reaction blocks would be

```
BEGIN general chemistry gas_chem
  Species Names = As Bs
  Species Variable Name = density

  Begin Reaction R1
    Reaction is As -> Bs
    Rate Function = Arrhenius  A = 0.1  Ea = 350  R = 1
    Concentration Function = Standard  mu = 1.0 0.0
    Heat of Reaction = -1e6
  End
END
```

These two input methods can also be combined, but the specified number of reactions on the "Number of Reactions" line should be only the number listed in the traditional format, not including reactions inside "Begin Reaction" blocks.

37.2. REQUIRED PREREQUISITES

Using general chemistry requires that several expressions be defined in the same material block or available on the block it is evaluated on. These expressions, and the conditions when they are required, are described in the following list.

- Specific heat of each species (only required if you request a chemistry source term for the energy equation)
- Enthalpy of each species (only required if you request a chemistry source term for the energy equation, if you use an evaluator for specific heat this is created automatically)
- Temperature
- Pressure (optional, if you do not provide it and use a pressure dependent reaction rate it will use 101325 Pa)
- Concentrations (required, you specify what form of concentration, e.g. mass fraction, density, species, or species fraction)
- Molecular weights of each species (required if you use molar concentrations)

The phases for inputs (temperature and pressure) come from NO_MATERIAL_PHASE by default. You can specify a list of temperature phases using the old input syntax to override this default. The pressure, when using the old input syntax always comes from the same phase as temperature. When using the new reaction block format, these can be specified separately for each reaction.

37.3. GENERAL CHEMISTRY

Scope: Material Phase

Begin General Chemistry *ModelName*

Species Names {=|are|is} *species names...*

Species Variable Name {=|are|is} *species variable name...*

Species Phases {=|are|is} *species phases...*

Number Of Reactions {=|are|is} *number of reactions*

Universal Gas Constant {=|are|is} *universal gas constant*

Preexponential Factors {=|are|is} *preexponential factors...*

Steric Coefficients {=|are|is} *steric coefficients...*

Activation Energies {=|are|is} *activation energies...*

Temperature Phases {=|are|is} *temperature phases...*

Concentration Exponents For *SpeciesName* {=|are|is} *exponents...*

Stoichiometric Coefficients For *SpeciesName* {=|are|is} *coefficients...*

Heats of Reaction {=|are|is} *heats of reaction...*

Enthalpy of Formation For *SpeciesName* {=|are|is} *enthalpy of formation...*

Nucleation Time {=|are|is} *nucleation time...*

Activation Temperature {=|are|is} *temperature*

Deactivation Temperature {=|are|is} *temperature action*

Deactivation Temperature Rate {=|are|is} *rate action*

Deactivation Temperature Overshoot {=|are|is} *overshoot*

Newton Temperature Solve {=|are|is} *Bool*

End

Summary Parameters for the General Chemistry model within Aria. The *ModelName* must appear in a SRC term for an ENERGY or MASS equation in order to be applied.

37.3.1. Activation Energies

Scope: General Chemistry

Activation Energies `{=|are|is} activation energies...`

Parameter	Value	Default
<i>activation energies</i>	real...	undefined

Summary This command specifies the activation energies for each reaction.

37.3.2. Concentration Exponents For

Scope: General Chemistry

Concentration Exponents For *SpeciesName* `{=|are|is} exponents...`

Parameter	Value	Default
<i>SpeciesName</i>	string	undefined
<i>Exponents</i>	real...	undefined

Summary For the given species, this command specifies the concentration exponents for each reaction.

37.3.3. Enthalpy of Formation For

Scope: General Chemistry

Enthalpy of Formation For *SpeciesName* `{=|are|is} enthalpy of formation`

Parameter	Value	Default
<i>SpeciesName</i>	string	undefined
<i>Enthalpy of Formation</i>	real	undefined

Summary For the given species, this command specifies the enthalpy of formation. This is the preferred method of determining heat release. If this is omitted and the heat of reaction is provided instead, the code attempts to determine a set of formation enthalpies that satisfy the heats of reaction. If this cannot be done, an error is thrown.

37.3.4. Species Variable Name

Scope: General Chemistry

Species Variable Name {=|are|is} *species variable name*

Parameter	Value	Default
<i>species variable name</i>	string	None

Summary Specifies the species variable name. Options currently include "Density" (for mass-based calculations) or "Species" (for molar based calculations).

37.3.5. Heats of Reaction

Scope: General Chemistry

Heats of Reaction {=|are|is} *heats of reaction...*

Parameter	Value	Default
<i>heats of reaction</i>	real...	0.0

Summary This command specifies the heat of reaction for each reaction. If the enthalpies of formation are provided, this section is ignored. Otherwise, these are converted to enthalpies of formation as described later in this chapter.

37.3.6. Preexponential Factors

Scope: General Chemistry

Preexponential Factors {=|are|is} *preexponential factors...*

Parameter	Value	Default
<i>preexponential factors</i>	real...	undefined

Summary This command specifies the pre-exponential factors for each reaction.

37.3.7. Universal Gas Constant

Scope: General Chemistry

Universal Gas Constant {=|are|is} *universal gas constant*

Parameter	Value	Default
<i>universal gas constant</i>	real	undefined

Summary Specifies the universal gas constant to use with any of the traditionally specified reactions. Reactions entered in their own blocks define their own constants.

37.3.8. Nucleation Time

Scope: General Chemistry

Nucleation Time {=|are|is} *nucleation time*

Parameter	Value	Default
<i>nucleation time</i>	real	undefined

Summary This is an optional input that specifies a nucleation time to apply to the reactions. If provided, it is applied to all the traditionally specified reactions, but not to reactions entered in their own Reaction block.

37.3.9. Number Of Reactions

Scope: General Chemistry

Number Of Reactions {=|are|is} *number of reactions*

Parameter	Value	Default
<i>number of reactions</i>	integer	undefined

Summary Specifies the number of reactions for this material, not including reactions entered in their own Reaction block.

37.3.10. Species Names

Scope: General Chemistry

Species Names {=|are|is} *species names...*

Parameter	Value	Default
<i>species names</i>	string...	undefined

Summary Supplies names for the chemical species. The number of chemical species is implied by the size of this list. The entries must be separated by whitespace, without commas.

37.3.11. Species Phases

Scope: General Chemistry

Species Phases {=|are|is} *species phases...*

Parameter	Value	Default
<i>Species Phases</i>	string...	undefined

Summary Supplies the phase for each chemical species. The order is significant, and corresponds to the order in which the Species Names are specified.

37.3.12. Temperature Phases

Scope: General Chemistry

Temperature Phases {=|are|is} *temperature phases...*

Parameter	Value	Default
<i>Temperature Phases</i>	string...	NO_MATERIAL_PHASE

Summary Supplies the phase for each reaction gets its temperature. This does not apply to reactions entered in Reaction blocks.

37.3.13. Steric Coefficients

Scope: General Chemistry

Steric Coefficients {=|are|is} *steric coefficients...*

Parameter	Value	Default
<i>steric coefficients</i>	real...	undefined

Summary This command specifies the steric coefficients for each reaction.

37.3.14. Stoichiometric Coefficients For

Scope: General Chemistry

Stoichiometric Coefficients For *SpeciesName* {=|are|is} *Exponents...*

Parameter	Value	Default
<i>SpeciesName</i>	string	undefined
<i>Exponents</i>	real...	undefined

Summary For the given species, this command specifies the stoichiometric coefficients for each reaction.

37.3.15. Activation Temperature

Scope: General Chemistry

Activation Temperature {=|are|is} *temperature*

Parameter	Value	Default
<i>temperature</i>	real	undefined

Summary This command specifies the activation temperature for the chemistry mechanism.

37.3.16. Deactivation Temperature

Scope: General Chemistry

Deactivation Temperature $\{=|are|is\}$ *temperature action*

Parameter	Value	Default
<i>temperature</i>	real	undefined
<i>action</i>	string	undefined

Summary This command specifies the deactivation temperature for the chemistry mechanism. The action string should be either 'continue' or 'terminate'.

37.3.17. Deactivation Temperature Rate

Scope: General Chemistry

Deactivation Temperature Rate $\{=|are|is\}$ *rate action*

Parameter	Value	Default
<i>rate</i>	real	undefined
<i>action</i>	string	undefined

Summary This command specifies the deactivation temperature rate for the chemistry mechanism. The action string should be either 'continue' or 'terminate'.

37.3.18. Deactivation Temperature Overshoot

Scope: General Chemistry

Deactivation Temperature Overshoot $\{=|are|is\}$ *overshoot*

Parameter	Value	Default
<i>overshoot</i>	real	undefined

Summary This command specifies the allowable overshoot (ΔT) for a temperature deactivation. Failing to stop within $T_{deactivate} + \Delta T$ will result in a failed time step (up to a maximum of three consecutive failures).

37.3.19. Newton Temperature Solve

Scope: General Chemistry

Newton Temperature Solve {=|are|is} Bool

Parameter	Value	Default
Bool	{false true}	false

Summary This command specifies whether or not Newton's method is desired when solving for the temperature. When set to true, Newton's method is used to calculate the temperature. Otherwise, the temperature is computed assuming a constant heat capacity.

37.4. MOLAR FORMULATION OF CHEMICAL MECHANISM

37.4.1. Species Transport

Consider a multi-step chemical reaction mechanism comprised of j irreversible reactions. This system can be expressed as



where $\bar{\nu}'_{ij}$ is the molar stoichiometric coefficient for reactant species M_i and $\bar{\nu}''_{ij}$ is the molar stoichiometric coefficient for product species M_i , and N_s is the number of chemical species. When a species does not appear in either the reactants or products for a reaction j , its stoichiometric coefficients are set to zero.

The net rate of change of molar concentration of species M_i , summed over all j reactions in the mechanism is then

$$\frac{d[M_i]}{dt} = \sum_{j=1}^{N_r} (\bar{\nu}''_{ij} - \bar{\nu}'_{ij}) \bar{r}_j, \quad (37.2)$$

where N_r is the number of reactions and $\bar{r}_j$ is the molar reaction rate for reaction j , calculated according to the law of mass action,

$$\bar{r}_j = k_j \prod_{i=1}^{N_s} [M_i]^{\mu_{ij}} \quad (37.3)$$

where μ_{ij} is the concentration exponent for species i in reaction j and $\bar{k}_j$ is the kinetic coefficient for reaction j , modeled using the Arrhenius form

$$\bar{k}_j = \bar{A}_j T^{\beta_j} \exp\left(-\frac{E_j}{R_u T}\right), \quad (37.4)$$

where $\bar{A}_j$ is the pre-exponential factor, β_j is the steric coefficient, E_j is the activation energy, R_u is the universal gas constant, and T is the temperature. Combining all terms, the final expression for the molar production rate of species i is then

$$\frac{d[M_i]}{dt} = \dot{\omega}_i = \sum_{j=1}^{N_r} \left[(\bar{\nu}_{ij}'' - \bar{\nu}_{ij}') \bar{A}_j T^{\beta_j} \exp\left(-\frac{E_j}{R_u T}\right) \prod_{k=1}^{N_s} [M_k]^{\mu_{kj}} \right]. \quad (37.5)$$

It is entirely possible that the simulation might be configured such that the native species solution variable might not be the molar concentration $[M_k]$, but instead might be something like mole fraction, species density, or mass fraction. In these cases, it is up to the user to provide a set of material models to convert whatever the solution variable is into something dimensionally equivalent to molar concentration, and then to provide the name of the final converted molar concentration variable to the chemistry configuration block in the Aria input deck. Some useful conversion into molar concentration include

$$[M_i] = \frac{\rho X_i}{W} = \frac{\rho Y_i}{W_i} = \frac{\rho_i}{W_i}, \quad (37.6)$$

where X_i is the mole fraction of species i , Y_i is the mass fraction of species i , ρ_i is the density of species i , W_i is the molecular weight of species i , and W is the mixture molecular weight computed as $W = \sum X_i W_i = (\sum Y_i / W_i)^{-1}$.

If the reaction mechanism is specified on a molar basis, then the result of the calculations will be a volumetric mole production rate. If this is to be used by a mass-based species transport equation, then an appropriate source term model should be specified by the user for the species transport equations, that include the requisite unit conversions.

37.4.2. Continuity Transport

Once the individual species source terms have been formulated, the overall continuity equation source term for material phase k can then be computed as a summation over all of the individual species source terms as

$$\frac{d[M]_k}{dt} = \dot{\omega}_{c,k} = \sum_{i=1}^{N_{s,k}} \frac{d[M_i]}{dt} \quad (37.7)$$

where $[M]_k$ is the overall molar concentration in material phase k and the summation is over the $N_{s,k}$ species in material phase k . The volumetric material phase is intended to represent the different states of the material in a single volume, such as can be found in porous flow where there may be a solid skeleton phase, a gas phase, and/or a liquid phase occupying the pores. If there is only a single material phase (homogeneous combustion), then this continuity source term will be zero; it can only be non-zero when mass is being exchanged between material phases.

37.4.3. Energy Transport

The volumetric heating source term presents an interesting complexity, since the form of the source term itself varies depending on the type of energy equation being solved. For example, a user might want to solve an enthalpy equation, a sensible enthalpy equation, or even a temperature equation. The molar enthalpy for a particular species i is defined as

$$\bar{h}_i = \Delta \bar{h}_{f,i}^o + \int_{T_{\text{ref}}}^T \bar{c}_{p,i}(T) dT \quad (37.8)$$

$$= \Delta \bar{h}_{f,i}^o + \bar{h}_{s,i}, \quad (37.9)$$

where $\Delta \bar{h}_{f,i}^o$ is the molar heat of formation for species i at the reference temperature T_{ref} , $\bar{c}_{p,i}$ is the molar specific heat of species i , and the molar sensible enthalpy $\bar{h}_{s,i}$ is defined as the integral of the specific heat from the reference state up to the temperature of interest. See Section 37.6 for a discussion of specifying standard states for species. The mixture molar enthalpy may be calculated by

$$\bar{h} = \bar{h}_s + \sum_{i=1}^{N_s} \Delta \bar{h}_{f,i}^o X_i, \quad (37.10)$$

where the mixture molar sensible enthalpy is defined as

$$\bar{h}_s = \sum_{i=1}^{N_s} \bar{h}_{s,i} X_i. \quad (37.11)$$

For homogeneous combustion, an enthalpy equation requires no combustion source term at all, but the enthalpy must be known for each individual species, including both the chemical and sensible portions. For poorly-characterized species, the heat of formation might be unknown or harder to measure (or approximate) than the specific heat. In these cases, a sensible enthalpy equation might be more convenient.

The energy source term due to combustion when not using total enthalpy becomes

$$\bar{S}_{h_s} = - \sum_{i=1}^{N_s} \Delta \bar{h}_{f,i}^o \dot{\omega}_i \quad (37.12)$$

$$= - \sum_{i=1}^{N_s} \Delta \bar{h}_{f,i}^o \left(\sum_{j=1}^{N_r} (\bar{\nu}_{ij}'' - \bar{\nu}_{ij}') \bar{r}_j \right) \quad (37.13)$$

$$= - \sum_{j=1}^{N_r} \left(\sum_{i=1}^{N_s} \Delta \bar{h}_{f,i}^o (\bar{\nu}_{ij}'' - \bar{\nu}_{ij}') \right) \bar{r}_j \quad (37.14)$$

$$= - \sum_{j=1}^{N_r} \Delta \bar{h}_{R,j} \bar{r}_j, \quad (37.15)$$

where $\Delta \bar{h}_{R,j}$ is the molar heat of reaction for reaction j , which is potentially easier to measure than the heat of formation for individual species. When specifying the reaction system, either the heat of

reaction or the enthalpy of formation can be provided. However, if a set of non-physical heats of reaction is provided, an error will be generated.

Extra care must be taken in the case of volumetric heterogeneous combustion, since mass is conserved globally but not within each individual material phase since mass is converted from one phase to another (e.g. from a porous solid into a gas). In this case, if separate enthalpy transport equations are solved for each material phase, a source term appears in each equation that accounts for the enthalpy addition or removal due to creation or destruction of mass within that phase. See Section 37.7 for further details on the form of this source term.

37.5. MASS FORMULATION OF CHEMICAL MECHANISM

37.5.1. Species Transport

The model form presented in the previous section is on a molar basis, but it may be more convenient to formulate the chemical mechanism on a mass basis. In this case, the multi-step chemical reaction mechanism may be written as

$$\sum_{i=1}^{N_s} \nu'_{ij} M_i \rightarrow \sum_{i=1}^{N_s} \nu''_{ij} M_i. \quad (37.16)$$

Here, the view is taken that the stoichiometric coefficient $\bar{\nu}_{ij}$ is a molar ratio between species i and a reference species, $\bar{\nu}_{ij} = \frac{N_i}{N_{\text{ref}}}$, where the reference species is often taken to be one of the reactants that can be identified as the “fuel”. Thus, the mass-based stoichiometric coefficients are $\nu'_{ij} = \bar{\nu}'_{ij} \frac{W_i}{W_{\text{ref}}}$ and $\nu''_{ij} = \bar{\nu}''_{ij} \frac{W_i}{W_{\text{ref}}}$, where W_i is the molecular weight of species i and W_{ref} is the molecular weight of the reference species.

The net rate of change of mass concentration (or species density), is then

$$\begin{aligned} \frac{d\rho_i}{dt} = \dot{\omega}_i''' &= W_i \sum_{j=1}^{N_r} (\bar{\nu}''_{ij} - \bar{\nu}'_{ij}) \bar{r}_j \\ &= W_i \sum_{j=1}^{N_r} \frac{W_{\text{ref}}}{W_i} (\nu''_{ij} - \nu'_{ij}) \bar{r}_j \\ &= \sum_{j=1}^{N_r} (\nu''_{ij} - \nu'_{ij}) r_j, \end{aligned} \quad (37.17)$$

where the mass reaction rate is $r_j = W_{\text{ref}} \bar{r}_j$ and the relations in Equation 37.6 are used to convert molar concentration to species density. The mass reaction rate for reaction j is then specified in terms of mass

quantities as

$$\begin{aligned}\bar{r}_j &= \bar{k}_j W_{\text{ref}} \prod_{i=1}^{N_s} \frac{\rho_i^{\mu_{ij}}}{W_i^{\mu_{ij}}} \\ &= k_j \prod_{i=1}^{N_s} \rho_i^{\mu_{ij}}\end{aligned}\quad (37.18)$$

where the mass kinetic coefficient is

$$k_j = \frac{W_{\text{ref}}}{\prod_{i=1}^{N_s} W_i^{\mu_{ij}}} \bar{A}_j T^{\beta_j} \exp\left(-\frac{E_j}{R_u T}\right). \quad (37.19)$$

or, more compactly,

$$k_j = A_j T^{\beta_j} \exp\left(-\frac{E_j}{R_u T}\right), \quad (37.20)$$

where the molecular weights can be “absorbed” into the pre-exponential factor to convert it into a mass-based quantity,

$$A_j = \frac{W_{\text{ref}}}{\prod_{i=1}^{N_s} W_i^{\mu_{ij}}} \bar{A}_j. \quad (37.21)$$

Combining all terms above yields the final expression for the volumetric mass production rate for species i ,

$$\frac{d\rho_i}{dt} = \dot{\omega}_i''' = \sum_{j=1}^{N_r} \left[(\nu_{ij}'' - \nu_{ij}') A_j T^{\beta_j} \exp\left(-\frac{E_j}{R_u T}\right) \prod_{k=1}^{N_s} \rho_k^{\mu_{kj}} \right], \quad (37.22)$$

which has the same basic functional form as Equation 37.5, meaning that the same model implementation can be used interchangeably for either a mass-based or a mole-based formulation, as long as all user-provided parameters are in an internally-consistent units basis.

The same caveats exist for the mass formulation as the mole formulation, with regard to proper units for the input species variables and the output species reaction rates. Proper material model and source term models must be specified to convert the desired species solution variable into species densities as an input and to convert the volumetric mass production rate into appropriate units for the transport equation source term. Some common conversions into species density include

$$\rho_i = \rho Y_i = \frac{W_i}{W} \rho X_i = W_i [M_i]. \quad (37.23)$$

37.5.2. Continuity Transport

Once the individual species source terms have been formulated, the overall mass-based continuity equation source term for material phase k can then be computed as a summation over all of the individual species source terms as

$$\frac{d\rho_k}{dt} = \dot{\omega}_{c,k}''' = \sum_{i=1}^{N_{s,k}} \frac{d\rho_i}{dt}, \quad (37.24)$$

where ρ_k is the overall density of material phase k and the summation is over the $N_{s,k}$ species in material phase k . If there is only a single material phase (homogeneous combustion), then this continuity source term will be zero; it can only be non-zero when mass is being exchanged between material phases.

37.5.3. Energy Transport

As with the mole-based formulation, the volumetric heating source term takes on a different form depending on the type of equation being solved. For example, a user might want to solve an enthalpy equation, a sensible enthalpy equation, or even a temperature equation. The enthalpy for a particular species i is defined as

$$h_i = \Delta h_{f,i}^o + \int_{T_{\text{ref}}}^T c_{p,i}(T) dT \quad (37.25)$$

$$= \Delta h_{f,i}^o + h_{s,i}, \quad (37.26)$$

where $\Delta h_{f,i}^o$ is the mass-based heat of formation for species i at the reference temperature T_{ref} , $c_{p,i}$ is the specific heat of species i , and the sensible enthalpy $h_{s,i}$ is defined as the integral of the specific heat from the reference state up to the temperature of interest. See Section 37.6 for a discussion of specifying standard states for species. The mixture enthalpy may be calculated by

$$h = h_s + \sum_{i=1}^{N_s} \Delta h_{f,i}^o Y_i, \quad (37.27)$$

where the mixture sensible enthalpy is defined as

$$h_s = \sum_{i=1}^{N_s} h_{s,i} Y_i. \quad (37.28)$$

For homogeneous combustion, an enthalpy equation requires no combustion source term at all, but the enthalpy must be known for each individual species, including both the chemical and sensible portions. For poorly-characterized species, the heat of formation might be unknown or harder to measure (or approximate) than the specific heat. In these cases, a sensible enthalpy equation might be more convenient.

For a sensible enthalpy equation, the source term due to combustion becomes

$$S_{h_s} = - \sum_{i=1}^{N_s} \Delta h_{f,i}^o \dot{\omega}_i''' \quad (37.29)$$

$$= - \sum_{i=1}^{N_s} \Delta h_{f,i}^o \left(\sum_{j=1}^{N_r} (\nu_{ij}'' - \nu_{ij}') r_j \right) \quad (37.30)$$

$$= - \sum_{j=1}^{N_r} \left(\sum_{i=1}^{N_s} \Delta h_{f,i}^o (\nu_{ij}'' - \nu_{ij}') \right) r_j \quad (37.31)$$

$$= - \sum_{j=1}^{N_r} \Delta h_{R,j} r_j, \quad (37.32)$$

where $\Delta h_{R,j}$ is the mass-based heat of reaction for reaction j , which is potentially easier to measure or approximate than the heat of formation for individual species. When specifying the reaction system, either the heat of reaction or the enthalpy of formation can be provided. However, if a set of non-physical heats of reaction is provided, an error will be generated.

As with the molar formulation, extra care must be taken in the case of volumetric heterogeneous combustion since mass is conserved globally but not within each individual material phase. In this case, if separate enthalpy transport equations are solved for each material phase, a source term appears in each equation that accounts for the enthalpy addition or removal due to creation or destruction of mass within that phase. See Section 37.7 for further details on the treatment of this source term.

37.6. SPECIFYING STANDARD STATES FOR SPECIES ENTHALPY

When modeling problems involving chemical reactions with species having different specific heats it is important to specify the standard state for the enthalpy of each species appropriately in order to model the heat release of the reactions correctly. As seen in 37.4.3 and 37.5.3 the enthalpy for a species is given by:

$$h_i = \Delta h_{f,i}^o + \int_{T_{\text{ref}}}^T c_{p,i}(T) dT \quad (37.33)$$

$$= \Delta h_{f,i}^o + h_{s,i}, \quad (37.34)$$

Each specific heat model in Aria that supports enthalpy evaluation (as required for use with the general chemistry capability) provides two optional parameters for specifying the standard state: "ho" is used to specify $\Delta h_{f,i}^o$, and "T_standard" is used to specify T_{ref} . Both parameters default to 0 if unspecified. In general we recommend following one of two approaches:

1. Use a sensible enthalpy formulation and specify either heats of reaction or species formation enthalpies in the general chemistry block. In this case the "ho" parameter for each species specific heat model should be unspecified so it defaults to 0 and the "T_standard" parameter should be set to the appropriate temperature for the heats of reaction or formation enthalpies you provide.
2. Use a total enthalpy formulation and do not specify any heats of reaction or species formation enthalpies in the general chemistry block. In this case the "ho" parameter for each species should be set to its formation enthalpy and the "T_standard" parameter should be set to the appropriate reference temperature.

37.7. HETEROGENEOUS REACTION ENERGY TERM

As mentioned in 37.4.3 and 37.5.3 volumetric heterogeneous reactions conserve mass overall, but mass is transferred between phases. As a result, when separate enthalpy equations are solved for each phase

additional source terms must be added to account for the change of mass within the phase. Two forms of this source are supported in Aria, the default is a total enthalpy conserving form that contributes:

$$S_{h_{dest}} = \dot{\rho}_{ij} h_i(T_{or}) \quad (37.35)$$

$$S_{h_{or}} = -\dot{\rho}_{ij} h_i(T_{or}) \quad (37.36)$$

where *dest* is the phase that species *i* is in, *or* is the origin phase of the reaction, $\dot{\rho}_{ij}$ is the production (or destruction) rate of species *i* due to reaction *j*, and $h_i(T_{or})$ is the enthalpy of species *i* at the current temperature of the the origin phase. Note that the species and reaction origin phases may be the same, in which case the contributions cancel. This form of the source terms using the enthalpy of the species at the origin phase temperature ensures that no thermodynamically inconsistent behavior (e.g. a hotter destination phase increasing in temperature while the origin phase cools for a reaction with o heat of reaction) can occur.

The second form of the source term does not conserve total enthalpy, it maintains constant temperature of both phases (if the specified heat of reaction is o). This may be activated using the "Phase Transfer Preseved Variable = Temperature" line command in the general chemistry mechanism. This is most useful for chemistry mechanisms where the is insufficient data to construct a complete set of enthalpies of formation and a simple constant heat of reaction is desired. This is achieved by neglecting the balancing contribution of energy to the origin phase of the reaction, Eq. 37.36 and using $h_i(T_{dest})$ in place of $h_i(T_{or})$ for the destination phase contribution.

37.8. REACTION BLOCK OVERVIEW

The chemistry module in TFTK provides a common input syntax for specifying chemical reaction mechanisms in both Fuego and Aria. The individual reactions will be entered in reaction blocks that are nested within an overall chemistry block defined by the application.

An example mechanism is shown below, with more details about the available options in the following sections.

```
Begin Reaction R1
  Reaction is A -> B
  Rate Function = Arrhenius  A = 0.1  Ea = 350  R = 1
  Concentration Function = Standard  mu = A 1.0
  Heat of Reaction = -1e6
End

Begin Reaction R2
  Reaction is B -> C
  Rate Function = Arrhenius  A = 0.1  Ea = 350  R = 1
  Concentration Function = Standard  mu = Automatic
  Heat of Reaction = 1e6
End
```

37.9. REACTION UNITS

The method for specifying units can vary between Fuego and Aria. In Aria, the user specifies the "Species Variable Name". This defines what values the rate functions use for the Y values. There is no implicit conversion, so if the species variable name is DENSITY, the Y values will be in units of mass per volume. Likewise, if the species variable name is SPECIES, the units of Y will be in moles per volume. While it is technically possible to specify a species variable of mass fraction or species fraction (mole fraction), this should be done with caution since unit management will be completely up to the user.

Given the user-specified units of Y , a reaction rate (ω_j) is calculated for each reaction. The time rate of change of a reactant or product in a reaction is simply the product of ω_j with the stoichiometric coefficient for that species. This means if the rate function is kept constant but all stoichiometric coefficients are scaled by a constant factor, the production and consumption rates will also be scaled.

Similarly, the heat source is the product of the calculated ω_j value and the reaction heat release. The resulting units should be in power per volume (e.g. W/m³). As before, the user should ensure that the units of ω_j and the reaction heat release are consistently defined to produce the appropriate output unit.

37.10. REACTION INPUTS

The reactions described above use a common reaction form with an Arrhenius rate and a standard concentration dependence. The chemistry module uses a generic reaction form, where the reaction rate is expressed as a product of four contributing functions

$$\omega_j = f_m(t, T, P, Y) f_r(t, T, P, Y) f_p(P, T) f_c(Y), \quad (37.37)$$

where f_m is the multiplier function, f_r is the rate function, f_p is the pressure function, and f_c is the concentration function. The available options for each of these functions are outlined in the following section. They can be selected in the input file by adding as many reaction blocks in the parent chemistry description block, as

```
Begin Reaction [REACTION NAME]
  Reaction is A + 1.2B -> 3C
  Multiplier Function = [Optional, See below]
  Rate Function = [Required, See below]
  Pressure Function = [Optional, See below]
  Concentration Function = [Optional, See below]
  Temperature Phase = [GAS_PHASE, SOLID_PHASE, NO_MATERIAL_PHASE (default)]
  Pressure Phase = [GAS_PHASE, SOLID_PHASE, NO_MATERIAL_PHASE (default)]
  Heat of Reaction = [Value]
  Origin Phase Heat Fraction = [Value]
End
```


where each reaction in a given general chemistry block must have a unique name. The reaction string is parsed to determine the appropriate stoichiometry for the reaction. The left hand side and right hand side must be separated by either ">" or "=>". There are multiple options for each of the functions, which are described in the following sections.

If the pressure phase argument is omitted but temperature phase is provided, the pressure phase defaults to the same phase as the temperature. By default, all of the reaction heating is applied in the temperature phase (e.g. solid phase). However, if you specify a value for the "Origin Phase Heat Fraction" between 0 and 1 you can divide that heat between phases. The fraction specified controls how much energy goes into the origin phase (a.k.a. temperature phase). The remaining energy is split evenly between the other phases that participate in the chemistry model.

If a reversible reaction is desired, the forward and reverse reaction must be specified in two separate reaction blocks. However, there is an option to say 'Reaction is Reverse of [REACTION NAME]' giving the name of the forward reaction block. This will copy over the reaction string with the opposite signs for the stoichiometric coefficients, the rate function, the temperature and pressure phases, and the equal and opposite heat of reaction. If the forward reaction block contains a concentration function that is not Unity, this statement will also create a Standard concentration function for the reverse reaction with automatic coefficients. These default rate and concentration functions can be overwritten by specifying a new function inside the reverse reaction block. An example of how this option might be used for an equilibrium model is shown below.

```
Begin Reaction [FORWARD REACTION NAME]
  Reaction is A -> B
  Rate Function = [Required, See below]
  Concentration Function = [Optional, See below]
  Heat of Reaction = [Value]
End
Begin Reaction [REVERSE REACTION NAME]
  Reaction is Reverse of [FORWARD REACTION NAME]
  Multiplier Function = [Thermodynamic_Equilibrium, Simplified_Equilibrium, See below]
End
```

A summary of all the reactions parsed from the input is also printed to the log file so you can verify they are evaluating as you have intended. An example of this output is shown below.

```
+-----+
| Reaction Summary |
+-----+

Name:          R1
Reaction String: A->B
Stoich Coeffs:  -1.00000 1.00000
Temperature Phase: No Material Phase
Pressure Phase:  No Material Phase
```

Heat of Reaction:	-1.00000e+06
Multiplier Function:	Unity
Rate Function:	Arrhenius
Arguments:	A = 0.100000 Ea = 350.000 beta = 0.00000 R = 1.00000
Pressure Function:	Unity
Concentration Function:	Standard
Arguments:	mu = 1.00000 0.00000

37.10.1. Multiplier Functions

37.10.1.1. Unity

The default multiplier function is unity,

$$f_m(t, T, P, Y) = 1 \quad (37.38)$$

and can be used by either omitting the Multiplier Function line or using

Multiplier Function = Unity

37.10.1.2. Tanh_Time

The tanh_time multiplier function uses a hyperbolic tangent function of time to increase the reaction rate at a specified time.

$$f_m(t, T, P, Y) = \frac{1}{2} (1 + \tanh(x_{span}(t - x_{ref}))) (f_{end} - f_{start}) + f_{start} \quad (37.39)$$

The two inputs for this are x_{ref} and x_{span} . If you do not specify an input for the span, it uses $x_{span} = 1/x_{ref}$, unless x_{ref} was set as 0, in which case an error is thrown. The default start and end points (f_{start} and f_{end}) of the tanh blending function are 0 and 1, respectively. These can be overridden by user-specified start and end values if desired. Example inputs are shown below.

Multiplier Function = Tanh_Time x_ref = 54

Multiplier Function = Tanh_Time x_ref = 2.5 span = 0.1

Multiplier Function = Tanh_Time x_ref = 2.5 span = 0.1 start = 1 end = 100

37.10.1.3. Tanh_Temperature

The tanh_temperature multiplier function uses a hyperbolic tangent function of temperature to increase the reaction rate at a specified temperature.

$$f_m(t, T, P, Y) = \frac{1}{2} (1 + \tanh(x_{span}(T - x_{ref}))) (f_{end} - f_{start}) + f_{start} \quad (37.40)$$

The arguments for this function as the same format as for the tanh_time function.

Multiplier Function = Tanh_Temperature x_ref = 450

Multiplier Function = Tanh_Temperature x_ref = 600 span = 10

Multiplier Function = Tanh_Temperature x_ref = 600 span = 10 start = 100 end = 5

37.10.1.4. Thermodynamic_Equilibrium

The thermodynamic_equilibrium multiplier function can be used to calculate the inverse equilibrium constant $\frac{1}{K_c}$ using thermodynamic properties. When multiplied by the forward rate function, this will provide a reverse rate function. The equation for K_c satisfies the Van't Hoff equation and uses Gibbs free energy.

$$f_m(t, T, P, Y) = \exp \left\{ - \sum_{i=1}^{n_s} \frac{\nu_i}{RT} (TS_i^o - H_i^o) \right\} \left(\frac{RT}{P_{atm}} \right)^{\sum_{i=1}^{n_s} \nu_i} \quad (37.41)$$

In this equation, P_{atm} is the atmospheric pressure, R is the universal gas constant, n_s is the number of species, ν_i is the stoichiometric coefficient of the i th species, and S_i^o and H_i^o are the standard state molar entropy and molar enthalpy of the i th species respectively.

The two optional inputs for this are atmospheric pressure, P_{atm} , and the universal gas constant, R . The default values for these are 101325 Pa and 8.314 J/mol-K respectively. Heat capacity evaluators must be provided with the species properties in order to use this function (the enthalpy and entropy evaluators will be derived from the provided heat capacity evaluators). Example inputs are shown below.

Multiplier Function = Thermodynamic_Equilibrium

Multiplier Function = Thermodynamic_Equilibrium Patm = 101325 R = 8.314

37.10.1.5. Simplified_Equilibrium

The simplified_equilibrium multiplier function can be used to calculate the inverse equilibrium constant $\frac{1}{K_c}$ using a known value of the equilibrium constant (in terms of partial pressures) at a specific temperature and the heat of reaction. When multiplied by the forward rate function, this will provide a reverse rate function. The equation for K_c is the integrated Van't Hoff equation.

$$f_m(t, T, P, Y) = \left(\frac{1}{K_{eq}} \right) \exp \left\{ \frac{\Delta H^o}{R} \left(\frac{1}{T} - \frac{1}{T_{eq}} \right) \right\} \left(\frac{RT}{P_{atm}} \right)^{\sum_{i=1}^{n_s} \nu_i} \quad (37.42)$$

In this equation, P_{atm} is the atmospheric pressure, R is the universal gas constant, n_s is the number of species, ν_i is the stoichiometric coefficient of the i th species, K_{eq} is the known equilibrium constant (in terms of partial pressures) at temperature T_{eq} , and ΔH° is the heat of reaction.

The required input for this is T_{eq} . The optional inputs include K_{eq} , P_{atm} , and R defaulted to 1.0, 101325 Pa, and 8.314 J/mol-K respectively. Either the heat of reaction or the enthalpies of formation must be provided with the reactions in the input file to use this equation accurately. Example inputs are shown below.

```
Multiplier Function = Simplified_Equilibrium Teq=800
Multiplier Function = Simplified_Equilibrium Teq=800 Keq=0.6
Multiplier Function = Simplified_Equilibrium Teq=800 Keq=0.6 Patm=101325 R=8.314
```

37.10.1.6. General

The general multiplier function uses a function string supplied in the input file to evaluate the rate generally. Allowable variables in this string include t (time), T (temperature), P (pressure), and any valid species name from the current model. The value used for a species is in whatever unit system the general chemistry model is using. Powers in this string are denoted using the '^' character. These functions can include multi-argument functions like min and max.

An example input for this option is

```
Multiplier Function = General Function = 0.5*(1+tanh((T-350)^2))*max(T,300)
```

37.10.2. Rate Functions

37.10.2.1. Unity

The rate function is the only required function, so it has no default like the others. However, you can still select Unity for it if desired, using

```
Rate Function = Unity
```

$$f_r(t, T, P, Y) = 1 \quad (37.43)$$

37.10.2.2. Arrhenius

The Arrhenius rate function is the most common, and uses

$$f_r(t, T, P, Y) = AT^\beta \exp\left(\frac{-E_a}{RT}\right) \quad (37.44)$$

The pre-exponential constant, A , is the only required input. Optional inputs include E_a , β , and R . If omitted, the defaults for these are 0 for E_a and β and 8.314 for R . Some example lines to select this rate function is

```
Rate Function = Arrhenius  A = 100 Ea = 20000
```

```
Rate Function = Arrhenius  A = 100 Ea = 350 R = 1
```

```
Rate Function = Arrhenius  A = 100 beta = 2 Ea = 350 R = 1
```

37.10.2.3. Distributed Arrhenius

The Distributed Arrhenius rate function uses a cumulative normal distribution to vary the activation energy with respect to a selected progress species.

$$f_r(t, T, P, Y) = AT^\beta \exp\left(\frac{-(E_a + \sigma\zeta)}{RT}\right) \quad (37.45)$$

$$\zeta = CDF^{-1}(1 - Y_j/Y_0) \quad (37.46)$$

where CDF^{-1} is the clipped inverse cumulative normal distribution function, Y_j is the concentration of the selected progress species, Y_0 is the specified reference concentration, and σ is the activation energy variation. In addition to these inputs, the same input rules as for the Arrhenius reaction apply (only A is required of those again). The name specified for the progress species must be a valid species name.

Some example inputs for this rate type are (note that these are shown on multiple lines to fit in the manual, but must be on the same line in your input file):

```
Rate Function = Distributed_Arrhenius  A = 100 Ea = 20000 sigma = 1000 Y0 = 1.2
ProgressSpecies = N2
```

```
Rate Function = Distributed_Arrhenius  A = 100 beta = 2 Ea = 350 R = 1 sigma = 100
Y0 = 1.2 ProgressSpecies = N2
```

37.10.2.4. General

The general rate function uses a function string supplied in the input file to evaluate the rate generally. Allowable variables in this string include t (time), T (temperature), P (pressure), and any valid species name from the current model. The value used for a species is in whatever unit system the general chemistry model is using. Powers in this string are denoted using the '^' character. These functions can include multi-argument functions like min and max.

An example input for this option is:

```
Rate Function = General Function = 2.1*exp(-350/T)*N2^3.2*(1-CO2)*max(CO2,0.1)
Rate Function = General Function = (T>300 ? 5.0 : 0.01)*CO2*exp(-350/T)
```

37.10.3. Pressure Functions

37.10.3.1. Unity

The default pressure function is unity,

$$f_p(P, T) = 1 \quad (37.47)$$

and can be used by either omitting the Pressure Function line or using

```
Pressure Function = Unity
```

37.10.3.2. Exponential

The exponential pressure function is evaluated as

$$f_p(P, T) = \left(\frac{P}{P_{ref}} \right)^n, \quad (37.48)$$

where P_{ref} must be positive. An example input for this option is

```
Pressure Function = Exponential P_ref = 1 n = 1.5
```

37.10.4. Concentration Functions

37.10.4.1. Unity

The default concentration function is unity,

$$f_c(Y) = 1 \quad (37.49)$$

and can be used by either omitting the Concentration Function line or using

```
Concentration Function = Unity
```

37.10.4.2. Standard

The standard concentration function is evaluated as

$$f_c(Y) = \prod_{i=1}^{N_s} Y_i^{\mu_i} \quad (37.50)$$

The values of μ can be specified manually using a list of entries for μ . This is done by entering a list of name-value pairs for each entry with a non-zero μ value. Alternately, you can provide a list of μ values for all species.

Alternately, if your reaction rate only depends on the concentration of the reactants, and the value of μ is the same as the stoichiometric coefficient, then you can have the values set automatically from the reaction stoichiometry by using the keyword "Automatic".

For example, if your reaction is " $2A + B \rightarrow C$ " the automatic option would do the same thing as specifying $\mu = A2B1$. If you have repeated species as both reactants and products, only the reaction portion of the coefficient is considered. For example, " $A + B \rightarrow 2A + C$ " would result in automatic exponents of $\mu = A1B1$.

```
Concentration Function = Standard mu = A 2 B 1
Concentration Function = Standard mu = 2 1 0
Concentration Function = Standard mu = Automatic
```

37.10.4.3. Prout Tompkins

The Prout Tompkins concentration function can only be used with a reaction that has a single reactant and a single product, and is evaluated as

$$f_c(Y) = \alpha^n (1 - (1 - 10^{-p}) \alpha)^m \quad (37.51)$$

where α is the concentration of the reactant. An example input for this model is

```
Concentration Function = Prout_Tompkins n = 1.2 m = 2.5 p = 9
```

37.10.4.4. Evaporation

The evaporation concentration function is evaluated as

$$f_c(Y) = A \sqrt{\frac{2}{\pi MRT}} \frac{1}{2 - C_c} (C_e p_v(T) x_{liq} - C_c p x_{vap}) \quad (37.52)$$

$$p_v(T) = p_0 \exp \left(\frac{L}{R} \left(\frac{1}{T_b} - \frac{1}{T} \right) \right) \quad (37.53)$$

where C_c and C_e are the condensation and evaporation coefficients, L is the molar enthalpy of vaporization, T_b is the boiling temperature at p_0 , p is the gas phase pressure, A is the surface area, x_{liq} is the mole fraction of the liquid that is evaporating, and x_{vap} is the gas phase mole fraction of the evaporating species. If L is provided in mass units, R must be converted appropriately so their units match. If you provide only C_c or only C_e , then the coefficients are assumed to be the same.

For reactions that do not include evaporation, species that are defined in the material but not involved in any reactions may be omitted from the chemistry definition block. When using evaporation reactions, this is not allowed since it will alter the value of the mole fractions in the equations above. You must also use a species variable name of 'species' when using evaporation since this requires molar concentrations to get mole fractions.

The only rate, pressure, and multiplier functions allowed with an Evaporation concentration function are the Unity functions.

Concentration Function = Evaporation R=8.314 M=18e-3 Cc=0.01 Tb=373 L=4e4

37.10.4.5. General Evaporation

This is a more general case of the evaporation function specified above. With general evaporation, different forms of the saturation pressure may be specified through a fugacity functor. The general evaporation function is evaluated as

$$f_c(Y) = A \sqrt{\frac{2}{\pi M R T}} \frac{1}{2 - C_c} (C_e f_l - C_c f_v) \quad (37.54)$$

where f_l and f_v are the fugacity of the liquid and vapor respectively. Choices for the liquid fugacity include:

1. HENRY_CONSTANT: returns $x_{liq}H$ for a specified Henry's law constant H .
2. ANTOINE: returns $x_{liq}10^{(A - \frac{B}{C+T})}$ for specified Antoine coefficients A , B , and C .
3. VANT_HOFF_BOILING: returns $x_{liq}P_{atm} \exp\left(\frac{L}{R} \left(\frac{1}{T_b} - \frac{1}{T}\right)\right)$ for required parameters of molar enthalpy of vaporization L and boiling temperature T_b at P_{atm} ; and optional parameters of atmospheric pressure P_{atm} and universal gas constant R with default values of 101325 Pa and 8.314 J/mol-K respectively.

Choices for the vapor fugacity include:

1. IDEAL_GAS: returns $x_{vap}P$ (no parameters to specify).

In the equation for $f_c(Y)$, inputs R , M , C_c , and C_e work the same as they would for the Evaporation case above. The rules defined above for using Evaporation also apply to General_Evaporation.

For an example reaction $\text{Liq} \rightarrow \text{Gas}$, general evaporation may be specified as


```

Concentration Function = General_Evaporation  R=8.314  M=18e-3  Cc=0.01
Begin Fugacity For Liq
    Type = VANT_HOFF_BOILING
    Parameter Patm = 101325
    Parameter R = 8.314
    Parameter Tb = 373
    Parameter L = 4e4
End
Begin Fugacity For Gas
    Type = IDEAL_GAS
End

```

which would give the same result as the Evaporation example given above. Other options for the liquid fugacity might look like

```

Begin Fugacity For Liq
    Type = ANTOINE
    Parameter A = 8
    Parameter B = 1000
    Parameter C = 200
End

```

```

Begin Fugacity For Liq
    Type = HENRY_CONSTANT
    Parameter H = 1
End

```

37.10.4.6. Condensation

The condensation concentration function is evaluated as

$$f_c(Y) = \frac{3DM(f_v - f_l)}{r^2 RT} \quad (37.55)$$

where f_l and f_v are the fugacity of the liquid and vapor respectively. Choices for the fugacity are given in the General Evaporation description above.

In the equation for $f_c(Y)$, D is the diffusion coefficient, M is the molar mass of the condensing species, r is the droplet radius, R is the universal gas constant, and T is temperature. The required parameter for condensation is D , while the optional parameter of R has the default value 8.314 J/mol-K.

Similar rules apply for using Condensation as using General_Evaporation defined above. However, you must use a mass basis for Y when using condensation and provide the molecular weights of all species present in order to calculate the mole fractions in the fugacity functions.

For an example reaction $\text{Gas} \rightarrow \text{Liq}$, condensation may be specified as

```
Concentration Function = Condensation  R=8.314  D=1e-4
Begin Fugacity For Gas
    Type = IDEAL_GAS
End
Begin Fugacity For Liq
    Type = VANT_HOFF_BOILING
    Parameter Patm = 101325
    Parameter R = 8.314
    Parameter Tb = 373
    Parameter L = 4e4
End
```

38. CHEMISTRY SOLVER REFERENCE

38.1. INTRODUCTION

The chemistry solver block specifies how a given chemistry description is solved. The description can currently only be a general chemistry description, however the ODE solvers can now be selected in a ChemEQ solver block using the same options.

If you do not provide a chemistry solver block for a general chemistry description, it will use the default algorithm (COUPLED).

38.2. SOLUTION APPROACHES

38.2.1. Coupled Solve

For a coupled solve, the chemistry description provides an instantaneous production rate for each DOF, calculated using values at state NP1. This rate is used directly as a source in the transport equation. This is the default solution algorithm.

This approach provides strong coupling between solution variables, but can limit the fluid time step prohibitively for stiff chemistry sets.

38.2.2. Segregated Solve

The segregated solution uses a frozen flow field to integrate the reaction ODEs from time N to time NP1 and uses the final values to calculate a source term consistent with the selected time integrator for the transport equations. Inputs to the problem, such as pressure, density, or specific heat, are held constant during this integration. The resulting source term is then provided explicitly in the transport equations.



Warning: The segregated chemistry solve is known to give poor results for cases where the reactions are rate-limited by transport. For example, consider a very fast reaction which can fully consume the available reactant in a single fluid time step. At present the segregated solution mechanism will eventually converge to the coupled result with time step refinement for these cases, but will typically require smaller time steps than the coupled solve so it is not recommended for these cases. Future improvements to these cases are possible, please contact sierra-help@sandia.gov if you would like to see them prioritized.

38.3. ODE SOLVER PARAMETERS

There are several ODE solvers available that can be selected. The basic set of input arguments for an ODE solver are given below, where the specific solver arguments are described in the following subsections.

```
ODE Solver = [SOLVER ARGS]
Absolute Tolerance = 1e-10
Relative Tolerance = 1e-5
Maximum Substeps = 100000
Minimum Step Size = 1e-15
```

38.3.1. CVODE

The CVODE solver is the most flexible of the options available, and often the fastest. It is the only option that allows you to select the method (BDF or ADAMS), the order (max of 5 for BDF and 12 for ADAMS), and the iteration scheme (FUNCTIONAL or NEWTON). For stiff problems, “BDF 5 NEWTON” will be most robust, but is also the most costly. For non-stiff problems, a lower order Adams method, such as “ADAMS 6 FUNCTIONAL” may be better.

The default is “BDF 5 NEWTON” if you only write “ODE Solver = CVODE”. A few valid options are shown below.

```
ODE Solver = CVODE [METHOD] [ORDER] [ITERATION\_SCHEME]
ODE Solver = CVODE ADAMS 6 FUNCTIONAL
ODE Solver = CVODE BDF 3 NEWTON
ODE Solver = CVODE
```

38.3.2. LSODE

The LSODE solver can sometimes provide better performance than CVODE for large, stiff problems. It always uses the BDF 5 NEWTON scheme, so there are no extra options. The minimum time in LSODE is set to machine precision and cannot be set by the user.

```
ODE Solver = LSODE
```

38.3.3. RKEH

The RKEH is the Euler-Heun Method. It is a second-order error-adaptive Runge-Kutta scheme. It is typically the slow for stiff systems, but may be advantageous for slowly changing non-stiff systems.

```
ODE Solver = RKEH
```

38.3.4. RK12

The RK12 is the Fehlberg 1-2 Method. It is a second-order error-adaptive Runge-Kutta scheme. It is typically the slow for stiff systems, but may be advantageous for slowly changing non-stiff systems.

```
ODE Solver = RK12
```

38.3.5. RKBS

The RKBS is the Bogacki-Shampine Method. It is a third-order error-adaptive Runge-Kutta scheme. It is typically the slow for stiff systems, but may be advantageous for slowly changing non-stiff systems,

```
ODE Solver = RKBS
```

38.3.6. RKF45

The RKF45 is the Runge-Kutta-Fehlberg 4-5 Method. It is a fourth-order error-adaptive Runge-Kutta scheme. It is typically the slow for stiff systems, but may be advantageous for slowly changing non-stiff systems,

```
ODE Solver = RKF5
```

38.3.7. CashKarp

The CashKarp is the Cash-Karp Method. It is a fourth-order error-adaptive Runge-Kutta scheme. It is typically the slow for stiff systems, but may be advantageous for slowly changing non-stiff systems.

```
ODE Solver = CashKarp
```

38.3.8. DOPRI5

The DOPRI5 is the Dormand-Prince Method. It is a fourth-order error-adaptive Runge-Kutta scheme. It is typically the slow for stiff systems, but may be advantageous for slowly changing non-stiff systems.

```
ODE Solver = DOPRI5
```

38.4. CHEMISTRY SOLVER PARAMETERS FOR

Scope: Equation System

```
Begin Chemistry Solver Parameters For ModelName
```

```
Absolute Tolerance {=|are|is} absTol
```

```
Chemistry Solver Algorithm {=|are|is} algorithmType
```

```
Maximum Substeps {=|are|is} maxSubSteps
```

```
Minimum Step Size {=|are|is} minStepSize
```

```
Ode Solver {=|are|is} odeSolver...
```

```
Relative Tolerance {=|are|is} relTol
```

```
End
```

Summary Parameters for the chemistry solver applicable to the previously defined material with chemistry model *ModelName*. The chemistry solver model produces no independent action since the *ModelName* must first appear in a SRC term for an ENERGY or SPECIES equation before it be applied.

38.4.1. Absolute Tolerance

Scope: Chemistry Solver Parameters For

Absolute Tolerance {=|are|is} *absTol*

Parameter	Value	Default
<i>absTol</i>	real	1e-12

Summary Specifies the absolute solution tolerance for the ODE solver

38.4.2. Chemistry Solver Algorithm

Scope: Chemistry Solver Parameters For

Chemistry Solver Algorithm {=|are|is} *algorithmType*

Parameter	Value	Default
<i>algorithmType</i>	string	COUPLED

Summary This command specifies the coupling algorithm between the chemistry model and transport equations

38.4.3. Maximum Substeps

Scope: Chemistry Solver Parameters For

Maximum Substeps {=|are|is} *maxSubSteps*

Parameter	Value	Default
<i>maxSubSteps</i>	integer	100000

Summary Specifies the maximum number of chemistry substeps per global time step.

38.4.4. Minimum Step Size

Scope: Chemistry Solver Parameters For

Minimum Step Size {=|are|is} *minStepSize*

Parameter	Value	Default
<i>minStepSize</i>	real	1e-30

Summary Specifies the minimum integration step size.

38.4.5. Ode Solver

Scope: Chemistry Solver Parameters For

Ode Solver {=|are|is} *odeSolver...*

Parameter	Value	Default
<i>odeSolver</i>	string...	CVODE

Summary This command selects the ODE solver to use for a segregated solve. For available options, refer to the 'ODE Solvers' section of this chapter.

38.4.6. Relative Tolerance

Scope: Chemistry Solver Parameters For

Relative Tolerance {=|are|is} *relTol*

Parameter	Value	Default
<i>relTol</i>	real	1e-6

Summary Specifies the relative solution tolerance for the ODE solver

39. PRESSURIZATION MODEL REFERENCE

39.1. PRESSURIZATION ZONES



Beta Capability: The pressurization zones capability is under active development hence this capability should be used with some caution.

Pressure-dependent chemical reactions may produce gas species in a confined space, so the pressure of that confined space must be tracked to resolve the pressure dependency properly. This pressure is often uniform enough that solving the continuity equation is unnecessarily expensive. To accomplish this without continuity, you can specify pressurization zones in the region block in the input file.

For each pressurization zone, you specify a list of source blocks (ChemEQ blocks providing gas to that zone) and pressurization blocks (block in which the gas is accumulating) or pressurized bulk nodes (or both). The available gas volume for the zone is the integration of the gas volume fraction over all the pressurization blocks and bulk nodes you have listed. The temperature of the zone is calculated using a weighted average over the pressurization blocks, which you can select as either a volume average, ideal gas average, mass average, or thermal mass average (ρC_p). The blocks do not have to be contiguous, and the source block does not have to be included in the pressurization blocks.

You can also enter an excess volume in the pressurization zone input block, which is added to the total volume of the blocks and bulk nodes for the pressure calculation. The temperature of this excess volume is assumed to be the same as the one calculated for the listed blocks and bulk nodes unless you specify a different temperature. Depending on what temperature averaging method you select, you may also need to provide a weight to use in conjunction with the specified temperature.

For each pressurization zone, a global variable for pressure, temperature, gas volume, and total moles will be created and shown in the log file. These can be output to heartbeat, included in the Exodus file, and used in Encore or user functions along with other global variables.

39.1.1. Temperature Averaging Methods

This section describes the different averaging methods that can be selected to get an effective temperature (T_{eff}). In all cases, ϕ is the volume fraction of gas. This effective temperature is what is

used in the equation of state to calculate the pressure in the pressurization zone.

39.1.1.1. Volume

When using the volume averaging method, the effective temperature is calculated from

$$T_{eff} = \frac{\int \phi T dV}{\int \phi dV} \quad (39.1)$$

39.1.1.2. Ideal Gas

When using the ideal gas averaging method, the effective temperature is calculated based on the ideal gas law. Starting with

$$n_{tot} = \frac{PV_{tot}}{RT_{eff}} = \sum n_i = \sum \frac{PV_i}{RT_i} \quad (39.2)$$

By re-arranging these relationships to solve for T_{eff} and converting to integral form we get

$$T_{eff} = \frac{\int \phi dV}{\int \phi/T dV} \quad (39.3)$$

39.1.1.3. Density

When using the density (ρ) averaging method, the effective temperature is calculated from

$$T_{eff} = \frac{\int \phi \rho T dV}{\int \phi \rho dV} \quad (39.4)$$

39.1.1.4. Thermal Mass

When using the thermal mass (ρC_p) averaging method, the effective temperature is calculated from

$$T_{eff} = \frac{\int \phi \rho C_p T dV}{\int \phi \rho C_p dV} \quad (39.5)$$

39.1.2. Equations of State

Given the volume, temperature, and number of moles of gas produced by all sources, an appropriate equation of state is still required to calculate pressure. This is specified in the pressurization model block, and can be one of the options listed below. Any arguments required for the equation of state are given on the same line, after its name. All equations of state have the optional gas constant argument, R, which defaults to 8314 J/kmol-K if omitted.

39.1.2.1. *Ideal Gas*

The ideal gas equation of state requires no coefficients and evaluates the pressure as

$$p = \frac{nRT}{V}. \quad (39.6)$$

and is specified by "Equation of State = Ideal_Gas" or "Equation of State = Ideal_Gas R = 8.314".

39.1.2.2. *BKWS*

The BKWS equation of state requires one parameter, the co-volume (V_{co}). The pressure is then evaluated using:

$$x = \frac{n\kappa V_{co}}{V\sqrt{T + 6620}} \quad (39.7)$$

$$Z = 1 + x \exp(0.298x) \quad (39.8)$$

$$p = \frac{ZnRT}{V}. \quad (39.9)$$

It is specified by "Equation of State = BKWS covol = VALUE" or "Equation of State = BKWS covol = VALUE R = 8.314".

39.1.2.3. *Van Der Waal*

The VanDerWaal equation of state requires two parameters, a and b . The pressure is then evaluated using:

$$p = \frac{nRT}{V - bn} - a \frac{n^2}{V^2} \quad (39.10)$$

It is specified by "Equation of State = VanDerWaal a = VALUE b = VALUE" or "Equation of State = VanDerWaal a = VALUE b = VALUE R = 8.314".

39.1.3. Venting and Coupling of Multiple Pressurization Zones

As of version 4.40 Aria has some basic capabilities to model venting of a pressurization zone to the environment, as well as to couple the pressure of multiple pressurization zones to one another. Venting may be modeled by setting "VENTING MODEL = VENTED" in the pressurization model block. This also requires specifying a model for the venting flow rate as a function of the pressure in the zone. At present there are 2 supported models, one that accounts for choked flow and one that does not. Both models take the form:

$$\dot{m} = K \rho \sqrt{(P - P_{ambient}) / \rho} \quad (39.11)$$

where K is an empirical factor, ρ is the density of the gas in the pressurization zone, P is the pressure in the pressurization zone, and $P_{ambient}$ is the pressure of the environment the gas is venting to. The choked flow model switches to the form:

$$\dot{m}_{choked} = K \rho \sqrt{P \left(1 - \frac{1}{P_{crit}}\right) / \rho} \quad (39.12)$$

once $\frac{P}{P_{ambient}} > P_{crit}$ where P_{crit} is the user-specified critical pressure ratio. The value of K can be set using any of the generic material model forms supported by Aria (i.e. constant, polynomial, user function, etc.). A sample vented pressurization zone input deck block is presented below:

```
Begin Pressurization Model pZone1
  Initial Pressure = 13
  Initial Mixture Molecular Weight = 32
  Pressure Unit = psi

  Pressurization Source Blocks = block_1
  Pressurized Blocks = block_1

  Venting Model = Vented
  Venting Model Property Venting_Volumetric_Flow_Rate = K_FACTOR_WITH_CHOKING
    critical_pressure_ratio=2.
  Venting Model Property ambient_pressure = constant value = 13
  Venting Model Property K_factor = constant value=1.e-2

  Equation of State = Ideal_Gas

  Temperature Averaging = rhoCp
End Pressurization Model pZone1
```

Multiple pressurization zones may be connected using the same model forms for the flow rate as are available for venting. This can be used to model multiple sealed volumes connected by a restricted flow

path or feature that is initially sealed until it reaches a certain temperature or pressure for example. The coupling is turned on using the syntax:

```
Begin Bulk Node Coupling coupling
  Bulk Nodes = pZone1 pZone2
  Couple density model = k_factor_flow
  Couple species model = k_factor_flow
  additional parameter K_factor = user_function name=k_coupling X=time
End
```

where "pZoner" and "pZone2" are the names of 2 pressurization zones present in the model.

39.1.3.1. Flow Rate Limiter

When the K_factor value is large and the time step is large, the resulting high flow rate between zones may cause numerical convergence issues. To alleviate this, you can specify a flow rate limiter in your coupling specification, as

```
Begin Bulk Node Coupling coupling12
  Bulk Nodes = PZone1 PZone2
  Couple density model = k_factor_flow flow_rate_limiter=100
  Couple species model = k_factor_flow flow_rate_limiter=100
  additional parameter K_factor = Constant value = 10
End
```

When using the limiter option, the code first calculates the amount of mass transfer between the two zones that would result in pressure equilibrium. This is divided by the current fluid time step to determine a baseline flow rate. The baseline flow rate is then multiplied by the limiter you specify to obtain the maximum allowable flow rate. In this example, the flow rate is limited to reaching equilibrium in 1 % of the current fluid time step. A larger limiter value results in less clipping of the flow rate (so less limiting). When this limiter is not provided, there is no flow rate limiting.

39.1.3.2. Coupling Algorithm

When the flow rates between coupled pressurization zones is large, it can cause numerical convergence issues in the overall nonlinear solution. When this is the case, you have the option of using a segregated solution approach for the coupling contributions to the pressurization zones. To use this option, you must first specify an ODE solver block in the Aria region, as shown in the example below. The syntax for this block is the same as for the chemistry ODE solver blocks, and is described in [Section 38.3](#).

```

Begin ODE Solver Parameters PZone
  ODE Solver = CVODE
  Absolute Tolerance = 1e-15
  Relative Tolerance = 1e-9
End ODE Solver Parameters

```

Next, you must select the segregated coupling algorithm in each pressurization zone involved in the coupling network and list which ODE solver to use.

```

Begin Pressurization Model pZone1
  Coupling Algorithm = Segregated
  Solver Name = PZONE
End Pressurization Model pZone1

```

There are a few notes to be aware of when using this option:

- The coupled network will use the ODE solver specified in the first block it stores, so if you specify different solvers in each pressurization model some of them will be ignored.
- The segregated approach only works for CLOSED pressurization zones. If you were using a VENTED pressurization zone in your network to vent to atmosphere, you will need to add a new pressurization zone to represent atmosphere (with a large excess volume and no listed blocks) and vent to that instead.
- For very high flow rates, the flow rate limiter described previously may still be required for good convergence.

39.2. PRESSURIZATION MODEL

Scope: Aria Region

```

Begin Pressurization Model ModelName
  Coupling Algorithm {=|are|is} couplingAlg
  Equation Of State {=|are|is} equationOfState...
  Excess Volume {=|are|is} excessVolume
  Excess Volume Temperature {=|are|is} excessVolumeTemperature
  Excess Volume Weight {=|are|is} excessVolumeWeight
  Initial Mixture Molecular Weight {=|are|is} initMMW
  Initial Pressure {=|are|is} initPressure
  Pressure Unit {=|are|is} pressureUnit

```

Pressurization Source Blocks {=|are|is} *sourceBlocks...*

Pressurized Blocks {=|are|is} *pressurizedBlocks...*

Pressurized Bulk Nodes {=|are|is} *pressurizedBulkNodes...*

Solver Name {=|are|is} *solverName*

Temperature Averaging {=|are|is} *ventingModel*

Venting Model {=|are|is} *ventingModel*

Venting Model Property *propertyName* {=|are|is} *propertyModelAndParams...*

End

Summary Parameters for the pressurization model

39.2.1. Coupling Algorithm

Scope: Pressurization Model

Coupling Algorithm {=|are|is} *couplingAlg*

Parameter	Value	Default
<i>couplingAlg</i>	{coupled segregated}	COUPLED

Summary This command specifies the coupling algorithm (COUPLED or SEGREGATED).

39.2.2. Equation Of State

Scope: Pressurization Model

Equation Of State {=|are|is} *equationOfState...*

Parameter	Value	Default
<i>equationOfState</i>	string...	undefined

Summary Specifies the equation of state to use (Ideal_Gas, VanDerWaal, or BKWS). The gas constant is an optional argument (R = value), and defaults to 8314 J/kmol-K if omitted.

39.2.3. Excess Volume

Scope: Pressurization Model

Excess Volume {=|are|is} *excessVolume*

Parameter	Value	Default
<i>excessVolume</i>	real	0.0

Summary Specifies the volume of the excess volume. This volume is assumed to be at the average zone temperature unless you also specify an excess volume temperature.

39.2.4. Excess Volume Temperature

Scope: Pressurization Model

Excess Volume Temperature {=|are|is} *excessVolumeTemperature*

Parameter	Value	Default
<i>excessVolumeTemperature</i>	real	Copied

Summary Specifies the temperature of the excess volume. If omitted, the excess volume is treated as the same temperature as the main averaged temperature. If provided, you must also provide a weighting factor to use for RHO and RHO_CP temperature averaging schemes.

39.2.5. Excess Volume Weight

Scope: Pressurization Model

Excess Volume Weight {=|are|is} *excessVolumeWeight*

Parameter	Value	Default
<i>excessVolumeWeight</i>	real	1

Summary Specifies the weighting factor to use for the excess volume. For RHO averaging, this will be the density. For rhoCp averaging, this will be rho times Cp. For volume and ideal gas averaging this should not be provided.

39.2.6. Initial Mixture Molecular Weight

Scope: Pressurization Model

Initial Mixture Molecular Weight `{=|are|is} initMMW`

Parameter	Value	Default
<i>initMMW</i>	real	28.97

Summary Specifies the mixture molecular weight of the initial gas present in the pressurization zone

Description Default is 28.97 g/mol for dry air. This should be specified in the appropriate units for the simulation. If no boundary conditions (e.g. venting or coupling to a gas transport region of the model) are applied to the pressurization zone then the value does not affect the results of the simulation.

39.2.7. Initial Pressure

Scope: Pressurization Model

Initial Pressure `{=|are|is} initPressure`

Parameter	Value	Default
<i>initPressure</i>	real	-1.0

Summary Specifies the initial pressure in the specified pressure units.

39.2.8. Pressure Unit

Scope: Pressurization Model

Pressure Unit `{=|are|is} pressureUnit`

Parameter	Value	Default
<i>pressureUnit</i>	string	Pa

Summary This command specifies the units of pressure that is returned. Options are PA, ATM, and PSI (Default is Pa)

39.2.9. Pressurization Source Blocks

Scope: Pressurization Model

Pressurization Source Blocks `{=|are|is} sourceBlocks...`

Parameter	Value	Default
<i>sourceBlocks</i>	string...	undefined

Summary A list of ChemEq blocks that provide the gas source(s) for this pressurization model.

39.2.10. Pressurized Blocks

Scope: Pressurization Model

Pressurized Blocks {=|are|is} *pressurizedBlocks...*

Parameter	Value	Default
<i>pressurizedBlocks</i>	string...	undefined

Summary A list of blocks that the pressurization occurs in.

39.2.11. Pressurized Bulk Nodes

Scope: Pressurization Model

Pressurized Bulk Nodes {=|are|is} *pressurizedBulkNodes...*

Parameter	Value	Default
<i>pressurizedBulkNodes</i>	string...	undefined

Summary A list of bulk nodes that the pressurization occurs in.

39.2.12. Solver Name

Scope: Pressurization Model

Solver Name {=|are|is} *solverName*

Parameter	Value	Default
<i>solverName</i>	string	NONE

Summary This command specifies the name of the ODE solver block to use for pressurization.

39.2.13. Temperature Averaging

Scope: Pressurization Model

Temperature Averaging {=|are|is} *ventingModel*

Parameter	Value	Default
<i>ventingModel</i>	string	IDEAL_GAS

Summary This command specifies the temperature averaging model to use (VOLUME, IDEAL_GAS, RHO, or RHOCp)

39.2.14. Venting Model

Scope: Pressurization Model

Venting Model {=|are|is} *ventingModel*

Parameter	Value	Default
<i>ventingModel</i>	string	undefined

Summary This command specifies the venting model to use (OPEN, CLOSED, or VENTED)

39.2.15. Venting Model Property

Scope: Pressurization Model

Venting Model Property *propertyName* {=|are|is} *propertyModelAndParams...*

Parameter	Value	Default
<i>propertyName</i>	string	undefined
<i>propertyModelAndParams</i>	string...	undefined

Summary Define a material property associated with the venting model. Required if the venting model is VENTED. At a minimum a model for the VENTING_VOLUMETRIC_FLOW_RATE must be provided, and depending on the choice of that model additional properties may be required.

40. BURN FRONT MODEL REFERENCE

40.1. BURN FRONT MODEL



Beta Capability: The burn front model capability is under active development hence this capability should be used with some caution.

Some energetics are modeled in Aria using finite rate chemical mechanisms, however this approach can be more expensive than is necessary to capture some thermal effects. An alternate approach is to define a burn front using a level set, which moves at a prescribed outward velocity and releases heat as it moves.

To enable this capability, the burn front model provides a mechanism for initializing the level set field based on an initiation or ignition temperature.

40.1.1. Model Setup

To set up a burn front model, you must make the following changes to the input file:

1. Define the burn model parameters (burn speed, heat release, initiation, and front width) in each energetic material. The burn speed and heat release can be any generic expression (constant, Encore, etc...).

Burn Speed	= Constant	Value = 0.01	# m/s
Burn Heat Release	= Constant	Value = 1e6	# J/kg
Burn Initiation	= Temperature	Tign = 750	# K
Burn Front Width	= Constant	Width = 0.005	# m

2. Add a level set equation before your temperature equation.

```
Begin Equation System LevelSet
[SOLVER SETTINGS]
```

```
EQ Level_Set for Level_Set on all_EM Using Q1 with mass ADV
EQ Extension_Speed for Extension_Speed on all_EM Using Q1 with xfer
End Equation System LevelSet
```

3. Add an energy source term from the level set burn.

Source for energy on block_1 = Burn_Front

4. Set the initial condition for the level set field to a large positive number everywhere (needs to be larger than the specified level set width).

40.1.2. Model Assumptions and Limitations

This section contains various notes about how the model will behave under certain conditions, and implicit assumptions and limitations of the model.

- By default each block can only have one ignition event. Once it is ignited it initializes the level set field and does not monitor for subsequent ignition. For multiple ignition events, you must specify a 'min_ignition_spacing = X' value on the Burn Initiation line. This will allow multiple ignition events as long as they are separated from an existing burn front by the specified distance. Pick a minimum ignition spacing (d) that is several times larger than your interface width ($d > 3w$), and that provides $Da \gg 1$, where $Da = \frac{v_b d}{\alpha}$ (α = thermal diffusivity and v_b = burn speed). This is so that the thermal front cannot move ahead of the burn front and trigger non-physical internal ignition points.

Burn Initiation = Temperature Tign = 750 min_ignition_spacing = 0.01

- The only mechanism for propagation of the burn front between blocks is thermal, where the heat from one material causes another to ignite.
- The level set is distanced using a global distance, so a tortuous material may result in a burn front that jumps from one location to a nearby location. Using the fast-marching level set may alleviate this issue, but is only compatible with tet meshes.
- The total energy release from the burn model is independent of time step size and burn front speed, but the local temperature profile may not be. For example, if a heat flux is applied to a block in a burn front model and a small time step is used, the nodes on the heated surface will ignite and the front will propagate into the block. If a very large time step is used, the entire block may ignite at once releasing its heat uniformly.

41. SOLUTION OPTIONS

41.1. SOLUTION OPTIONS

Scope: Aria Region

```
Begin Solution Options OptionsName
  Apply Flux Limiter Stabilization
  Assemble Tpetra {=|are|is} Value
  Check Matrix For Discrete Maximum Principle
  Face Stabilization Multiplier {=|are|is} Multiplier
  Force Non Tale {=|are|is} Value
  Free Stream Reynolds Number {=|are|is} input_Re
  Ignore Coordinate Displacements {=|are|is} Value
  Maximum Temperature Allowed From Temperature Extraction {=|are|is}
  MaxTemp
  Maximum Wall Time {=|are|is} WallTime Hours
  Minimum Temperature Allowed From Temperature Extraction {=|are|is}
  MinTemp
  Omit Enthalpy Adjustment After Temperature Clipping
  Omit Finite Difference Sensitivities For Cantera Properties
  Use Inverse Density Continuity Scaling {=|are|is} Value
  Begin Cvfem Algorithm Specification PStabName
End

Begin Edc Model Specification EdcSpecName
End

Begin Hdiff Model Specification HdiffOptionsName
End
```

Begin Porous Flow Options *blockName*

End

Begin Species Options *blockName*

End

Begin Turbulence Model Specification *TurbSpecName*

End

End

Summary Specify information regarding the governing equations to be solved.

41.1.1. Apply Flux Limiter Stabilization

Scope: Solution Options

Summary Enables flux limiter stabilization for diffusion.

Description This activates flux limiter stabilization for diffusion terms to prevent non-physical temperatures on meshes that don't satisfy the requirements for a discrete maximum principle, or for anisotropic material properties.

41.1.2. Assemble Tpetra

Scope: Solution Options

Assemble Tpetra {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	{false true}	FALSE

Summary EXPERIMENTAL: Enable (true) to assemble to TPETRA and compare matrix and RHS to FEI matrix.

41.1.3. Check Matrix For Discrete Maximum Principle

Scope: Solution Options

Summary Examine rows of the system matrix before boundary conditions are applied and check if the diagonal entries are non-negative, the off-diagonal entries are non-positive, the row-sum is non-negative. If these conditions fail, it is possible the solution will contain non-physical values, and the discrete maximum principle is not satisfied by the matrix. If any of these conditions fail, a warning is printed to the log file. More output can be obtained with turning on debug logging.

41.1.4. Face Stabilization Multiplier

Scope: Solution Options

Face Stabilization Multiplier {=|are|is} *Multiplier*

Parameter	Value	Default
<i>Multiplier</i>	real	1.0

Summary Multiplier for face stabilization term.

Description This value specifies the multiplier applied to the stabilization terms activated by the GRAD_JUMP_PENALTY or DMP stabilization terms on the specified equation.

41.1.5. Force Non Tale

Scope: Solution Options

Force Non Tale {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	{false true}	FALSE

Summary Enable (true) to force simulation not to use TALE.

41.1.6. Free Stream Reynolds Number

Scope: Solution Options

Free Stream Reynolds Number {=|are|is} *input_Re*

Parameter	Value	Default
<i>input_Re</i>	real	undefined

Summary Input Reynolds number is used for solving nondimensional viscous problems using the GasDyn equations.

41.1.7. Ignore Coordinate Displacements

Scope: Solution Options

Ignore Coordinate Displacements {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	{false true}	FALSE

Summary Enable (true) or disable (false) displacing the physical coordinates by either MESH_DISPLACEMENTS or SOLID_DISPLACEMENTS. By default, this is false, and physical_coordinates are displaced. However, this can be disabled by setting this to true, and physical_coordinates will be equal to model_coordinates.

41.1.8. Maximum Temperature Allowed From Temperature Extraction

Scope: Solution Options

Maximum Temperature Allowed From Temperature Extraction {=|are|is} *MaxTemp*

Parameter	Value	Default
<i>MaxTemp</i>	real	2400.0 K

Summary Specify a maximum cutoff temperature for extraction from enthalpy and composition

Description This option specifies the maximum temperature to be allowed to be extracted from enthalpy, given the mixture composition. If a temperature is computed that is greater than this value, the temperature is reset to equal the maximum allowed value.

41.1.9. Maximum Wall Time

Scope: Solution Options

Maximum Wall Time {=|are|is} *WallTime* Hours

Parameter	Value	Default
<i>WallTime</i>	real	Infinite

Summary Specify a maximum wall time to let the simulation end gracefully and output before slurm kills it.

41.1.10. Minimum Temperature Allowed From Temperature Extraction

Scope: Solution Options

Minimum Temperature Allowed From Temperature Extraction {=|are|is} *MinTemp*

Parameter	Value	Default
<i>MinTemp</i>	real	250.0 K

Summary Specify a minimum cutoff temperature for extraction from enthalpy and composition

Description This option specifies the minimum temperature to be allowed to be extracted from enthalpy, given the mixture composition. If a temperature is computed that is less than this value, the temperature is reset to equal the minimum allowed value.

41.1.11. Omit Enthalpy Adjustment After Temperature Clipping

Scope: Solution Options

Summary Do not adjust enthalpy to be consistent with clipped temperatures

Description When temperature extraction fails to produce a viable result, the temperature will usually be clipped at either the upper or lower limit temperature. By default, the enthalpy will then be adjusted up or down to match the clipped temperature so that the thermochemical state is internally consistent. This omits the enthalpy adjustment, leaving clipped nodes in an inconsistent state.

41.1.12. Omit Finite Difference Sensitivities For Cantera Properties

Scope: Solution Options

Summary Do not populate any Cantera property sensitivities via finite difference

41.1.13. Use Inverse Density Continuity Scaling

Scope: Solution Options

Use Inverse Density Continuity Scaling {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	{false true}	TRUE

Summary Enable (true) or disable (false) the inverse element scaling of the continuity equation.

41.2. CVFEM ALGORITHM SPECIFICATION

Scope: Solution Options

Begin Cvfem Algorithm Specification *PStabName*

Activate Acoustic Compressibility Algorithm

Activate Ausm Plus Scheme

Activate Edge Based Diffusion Operator [With *CorrectionType*]

Activate Edge Based Fourth Order Advection

Activate Kexact Muscl Scheme For Equation *EquationString* [{of|species} *SpeciesName* |{in|material_phase} *MaterialPhaseName*][
Using K {=|are|is} *kappa*]

Activate Mixture Fraction Clipping Utility At *UtilClipLocation*

Activate Muscl Scheme For Equation *EquationString* [{of|species} *SpeciesName* |{in|material_phase} *MaterialPhaseName*]

Activate Pressure Projection Algorithm

Activate Projected Stress Stabilization

Activate Scv Nodal Gradient

Activate Shakib Scaling

Activate Vrtm In Mass Flux Vector

Ausm Alpha {=|are|is} *alpha*

Ausm Beta {=|are|is} *beta*

Clip Cvfem Level Set Dof

First Order Upwind Factor {=|are|is} *RealValue* For Equation
EquationString [{of|species} *SpeciesName* |{in|material_phase} *MaterialPhaseName*]

Flux Scheme {=|are|is} *FluxScheme*

Freeze Muscl Limiter At Global Step {=|are|is} *freezeStep*

Hybrid Upwind Factor {=|are|is} *RealValue* For Equation
EquationString [{of|species} *SpeciesName* |{in|material_phase} *MaterialPhaseName*]

Interpolate Density And Velocity Separately In Mass Flux Vector

Lag Nodal Pressure Gradient In Mass Flux Vector Expression

Lag Nodal Tau In Mass Flux Vector Expression

```

Muscl Limiter {=|are|is} MusclLimiter For Equation EquationString
[ {of|species} SpeciesName |{in|material_phase} MaterialPhaseName
]

Omit Diffusion Term From Sucv Tau

Omit Disting Bc Ip Sensitivities

Omit Dt Term From Sucv Tau

Pressure Stabilization Characteristic Length {=|are|is} CharLength

Pressure Stabilization Order {=|are|is} Cvfempstaborder

Pressure Stabilization Parameter Scaling {=|are|is} TauScaling

Pressure Stabilization Scaling {=|are|is} CvfemPStabScaling [ With
Value {=|are|is} ConstantTau ]

Roe Entropy Fix C {=|are|is} epsc

Roe Entropy Fix U {=|are|is} epsu

Upwind Method {=|are|is} UpwMethod For Equation EquationString [
{of|species} SpeciesName |{in|material_phase} MaterialPhaseName ]

Use Approximate Roe Sensitivities

Use Opposing Subface In Open Mass Flux

Use Specified Pressure In Open Mass Flux

```

End

Summary Specify CVFEM algorithmic modeling options.

41.2.1. Activate Acoustic Compressibility Algorithm

Scope: Cvfem Algorithm Specification

Summary Variable thermodynamic pressure to allow for closed system pressurization

41.2.2. Activate Ausm Plus Scheme

Scope: Cvfem Algorithm Specification

Summary Activate AUSM plus with standard values for alpha and beta

Description Activate AUSM plus scheme.

41.2.3. Activate Edge Based Diffusion Operator

Scope: Cvfem Algorithm Specification

Summary Activate edge-based scheme for diffusion operator.

Description Only implemented now for tke and sdr - interior only

41.2.4. Activate Edge Based Fourth Order Advection

Scope: Cvfem Algorithm Specification

Summary Activate edge-based advection for fourth order LES scheme

Description Activate edge-based advection for fourth order LES scheme

41.2.5. Activate Kexact Muscl Scheme For Equation

Scope: Cvfem Algorithm Specification

Activate Kexact Muscl Scheme For Equation *EquationString* [{of|species}
SpeciesName | {in|material_phase} *MaterialPhaseName*] [Using K {=|are|is}
kappa]

Parameter	Value	Default
<i>EquationString</i>	string	undefined
<i>SpeciesName</i>	string	undefined
<i>MaterialPhaseName</i>	string	undefined

Summary Use kexact MUSCL variable extrapolation for the specified equation

Description Use kexact MUSCL variable extrapolation for the specified equation. The projected gradients for the necessary variables must be computed using a `cvfem_lumped_muscl_projection` equation.

41.2.6. Activate Mixture Fraction Clipping Utility At

Scope: Cvfem Algorithm Specification

Activate Mixture Fraction Clipping Utility At *UtilClipLocation*

Parameter	Value	Default
<i>UtilClipLocation</i>	{begin_nonlinear_solve end_nonlinear_solve manually_run post_iterate post_linear_solve post_nonlinear_solve pre_iterate pre_linear_solve pre_nonlinear_solve run_initially run_once run_post_linear_system_initialization}	undefined

Summary Activate clipping utility for mixture fraction

Description Sometimes it helps to clip the mixture fraction. This is a utility that provides this support.

41.2.7. **Activate Muscl Scheme For Equation**

Scope: Cvfem Algorithm Specification

Activate Muscl Scheme For Equation *EquationString* [{of | species}
SpeciesName | {in | material_phase} *MaterialPhaseName*]

Parameter	Value	Default
<i>EquationString</i>	string	undefined
<i>SpeciesName</i>	string	undefined
<i>MaterialPhaseName</i>	string	undefined

Summary Use MUSCL variable extrapolation for the specified equation

Description Use MUSCL variable extrapolation for the specified equation. The projected gradients for the necessary variables must be computed using a cvfem_lumped_muscl_projection equation.

41.2.8. **Activate Pressure Projection Algorithm**

Scope: Cvfem Algorithm Specification

Summary Activate PP alg.

Description Rather than fully coupling uvwp, activate a pressure projection algorithm. This will require creating two EQ systems: uvw and p. However, once this is created, the code will handle supplemental utilities. This option can only be used in the context of a momentum lumped mass matrix

41.2.9. Activate Projected Stress Stabilization

Scope: Cvfem Algorithm Specification

Summary Activate full momentum stress term for residual stabilization

Description Activate full momentum stress term for residual stabilization

41.2.10. Activate Scv Nodal Gradient

Scope: Cvfem Algorithm Specification

Summary Use scv nodal gradient for MUSCL and edge-based diffusion terms

Description Use scv nodal gradient for MUSCL and edge-based diffusion terms; default is to use nodal grad based on Green Gauss over the dual mesh with edge based integration points.

41.2.11. Activate Shakib Scaling

Scope: Cvfem Algorithm Specification

Summary Specify Shakib scaling; temp line command

41.2.12. Activate Vrtm In Mass Flux Vector

Scope: Cvfem Algorithm Specification

Summary Activate velocity relative to mesh in mass flux vector

Description In some cases, the volume may be constant, although there is mesh motion. This is the case in wind energy sliding mesh applications. This algorithm pays not attention to GCL and assumes that the time rate of volume is zero. Again, this is fine in solid rotation.

41.2.13. Ausm Alpha

Scope: Cvfem Algorithm Specification

Ausm Alpha {= | are | is} *alpha*

Parameter	Value	Default
<i>alpha</i>	real	0.0

Summary Set constant alpha in Mach splitting function.

Description Default is 0, unless ausm+ is chosen, then the default is 3/16.

41.2.14. Ausm Beta

Scope: Cvfem Algorithm Specification

Ausm Beta {=|are|is} *beta*

Parameter	Value	Default
<i>beta</i>	real	0.0

Summary Set constant beta in Mach splitting function.

Description Default is 0, unless ausm+ is chosen, then the default is 1/8..

41.2.15. Clip Cvfem Level Set Dof

Scope: Cvfem Algorithm Specification

Summary Clip level set; only germane for conserved level set formulation that has bounds between zero and unity

41.2.16. First Order Upwind Factor

Scope: Cvfem Algorithm Specification

First Order Upwind Factor {=|are|is} *RealValue* For Equation *EquationString*
[{of|species} *SpeciesName* |{in|material_phase} *MaterialPhaseName*]

Parameter	Value	Default
<i>RealValue</i>	real	1.0
<i>EquationString</i>	string	undefined
<i>SpeciesName</i>	string	undefined
<i>MaterialPhaseName</i>	string	undefined

Summary First-order upwind factor, $0 < x \leq 1$.

Description This value specifies the explicit upwind blending between pure upwind and the chosen convection operator, e.g., $UPW * (firstOrderUpwind) + (1 - firstOrderUpwind) * (blendedUpwindCentral)$.

where UPW is the pure first order upwind value and blendedUpwindCentral is a blend between the selected upwind method and central difference operator based on the local cell Peclet number (see Hybrid Upwind Factor line command).

For now, the blendedUpwindCentral is pure central.

41.2.17. Flux Scheme

Scope: Cvfem Algorithm Specification

Flux Scheme {=|are|is} *FluxScheme*

Parameter	Value	Default
<i>FluxScheme</i>	{ausm ausm_plus roe van_leer}	undefined

Summary Set flux scheme used by all equations in the high-Mach CVFEM formulation.

Description Set flux scheme used by all equations in the high-Mach CVFEM formulation.

41.2.18. Freeze Muscl Limiter At Global Step

Scope: Cvfem Algorithm Specification

Freeze Muscl Limiter At Global Step {=|are|is} *freezeStep*

Parameter	Value	Default
<i>freezeStep</i>	real	undefined

Summary Freeze MUSCL limiter at a given global step

Description Freeze the MUSCL limiter

41.2.19. Hybrid Upwind Factor

Scope: Cvfem Algorithm Specification

Hybrid Upwind Factor {=|are|is} *RealValue* For Equation *EquationString* [{of|species} *SpeciesName* | {in|material_phase} *MaterialPhaseName*]

Parameter	Value	Default
<i>RealValue</i>	real	1.0
<i>EquationString</i>	string	undefined
<i>SpeciesName</i>	string	undefined
<i>MaterialPhaseName</i>	string	undefined

Summary Hybrid upwind factor dials in blending between user specified operator and central.

Description Allows blending of the Peclet factor. A value of zero produces pure central. Higher values blend more user specified upwind (currently, pure first order upwind).

41.2.20. Interpolate Density And Velocity Separately In Mass Flux Vector

Scope: Cvfem Algorithm Specification

Summary use $(\rho)_{ip}*(u)_{ip}$ rather than default $(\rho*u)_{ip}$

41.2.21. Lag Nodal Pressure Gradient In Mass Flux Vector Expression

Scope: Cvfem Algorithm Specification

Summary Compute the nodal pressure gradient calculation.

Description Lag the nodal pressure gradient assembly for use in the stabilized mass flux vector expression. This command will place the calculation at the top of the non-linear iteration. In general, it will not be wise to use this option for steady simulations as there is one nonlinear loop.

41.2.22. Lag Nodal Tau In Mass Flux Vector Expression

Scope: Cvfem Algorithm Specification

Summary Compute the nodal tau calculation.

Description Lag the nodal tau assembly for use in the stabilized mass flux vector expression. This command will place the calculation at the top of the non-linear iteration. In general, it will not be wise to use this option for steady simulations as there is one nonlinear loop.

41.2.23. Muscl Limiter

Scope: Cvfem Algorithm Specification

Muscl Limiter {=*|are|is*} *MusclLimiter* For Equation *EquationString* [{*of|species*} *SpeciesName* |{*in|material_phase*} *MaterialPhaseName*]

Parameter	Value	Default
<i>MusclLimiter</i>	{ <i>muscl_minmod muscl_none muscl_superbee muscl_van_albada muscl_van_leer</i> }	undefined
<i>EquationString</i>	string	undefined
<i>SpeciesName</i>	string	undefined
<i>MaterialPhaseName</i>	string	undefined

Summary Specify the MUSCL limiter method.

Description TVD limiter.

41.2.24. Omit Diffusion Term From Sucv Tau

Scope: Cvfem Algorithm Specification

Summary Do not use timestep in the expression for the SUCV stabilization coefficient

41.2.25. Omit Disting Bc Ip Sensitivities

Scope: Cvfem Algorithm Specification

Summary Drop distinguishing bc sensitivities for ip values.

Description Drop distinguishing bc sensitivities for ip values.

41.2.26. Omit Dt Term From Sucv Tau

Scope: Cvfem Algorithm Specification

Summary Do not use timestep in the expression for the SUCV stabilization coefficient

41.2.27. Pressure Stabilization Characteristic Length

Scope: Cvfem Algorithm Specification

Pressure Stabilization Characteristic Length {=|are|is} *CharLength*

Parameter	Value	Default
<i>CharLength</i>	real	undefined

Summary Specify a constant length scale to compute tau; only applicable for characteristic scaling

41.2.28. Pressure Stabilization Order

Scope: Cvfem Algorithm Specification

Pressure Stabilization Order {=|are|is} *Cvfempstaborder*

Parameter	Value	Default
<i>Cvfempstaborder</i>	{fourth_order second_order zeroth_order}	undefined

Summary Order of pressure stabilization

41.2.29. Pressure Stabilization Parameter Scaling

Scope: Cvfem Algorithm Specification

Pressure Stabilization Parameter Scaling {=|are|is} *TauScaling*

Parameter	Value	Default
<i>TauScaling</i>	real	undefined

Summary Scaling of tau

41.2.30. Pressure Stabilization Scaling

Scope: Cvfem Algorithm Specification

Pressure Stabilization Scaling {=|are|is} *CvfemPStabScaling* [With Value {=|are|is} *ConstantTau*]

Parameter	Value	Default
<i>CvfemPStabScaling</i>	{characteristic constant shakib stabilized time_step}	undefined

Summary Scaling coefficient for pressure stabilization

41.2.31. Roe Entropy Fix C

Scope: Cvfem Algorithm Specification

Roe Entropy Fix C {=|are|is} *epsc*

Parameter	Value	Default
<i>epsc</i>	real	0.1

Summary Small constant for entropy fix (modification of $|U \pm c|$ eigenvalues in Roe scheme)

41.2.32. Roe Entropy Fix U

Scope: Cvfem Algorithm Specification

Roe Entropy Fix U {=|are|is} *epsu*

Parameter	Value	Default
<i>epsu</i>	real	0.1

Summary Small constant for entropy fix (modification of $|U|$ eigenvalues in Roe scheme)

41.2.33. Upwind Method

Scope: Cvfem Algorithm Specification

Upwind Method {=*|are|is*} *UpwMethod* For Equation *EquationString* [{of |
species} *SpeciesName* |{in|material_phase} *MaterialPhaseName*]

Parameter	Value	Default
<i>UpwMethod</i>	{fourth gupw muscl sucv upw}	UPW
<i>EquationString</i>	string	undefined
<i>SpeciesName</i>	string	undefined
<i>MaterialPhaseName</i>	string	undefined

Summary Specify method that is blended with pure second order.

Description This user defined method will be blended with pure second order based on cell Peclet blending. In most cases, this operator is upwinded, however, in the case of 4th order a higher order centered scheme is used.

41.2.34. Use Approximate Roe Sensitivities

Scope: Cvfem Algorithm Specification

Summary Use approximate Roe sensitivities for the LHS instead of Van Leer

Description By default, the Roe flux uses the sensitivities for the Van Leer flux scheme from the LHS matrix. This command turns on a different approximation, based more closely on the Roe flux itself; this approximation converges more quickly for some problems, but is less robust for others. Currently this option only has an effect when the "NC_ADV" equation term is used.

41.2.35. Use Opposing Surface In Open Mass Flux

Scope: Cvfem Algorithm Specification

Summary Open mass flux will be computed using the interpolated pressure at the opposing subface

41.2.36. Use Specified Pressure In Open Mass Flux

Scope: Cvfem Algorithm Specification

Summary User specified pressure in open BC will be used to compute gradp in open mass flux BC

41.3. POROUS FLOW OPTIONS

Scope: Solution Options

Begin Porous Flow Options *blockName*

Integrate Advection By Parts {=*|are|is*}
integrate_advection_by_parts

Use Cvfem {=*|are|is*} *use_cvfem*

End

Summary Specify solution options for porous flow.

41.3.1. Integrate Advection By Parts

Scope: Porous Flow Options

Integrate Advection By Parts {=*|are|is*} *integrate_advection_by_parts*

Parameter	Value	Default
<i>integrate_advection_by_parts</i>	{ <i>false true</i> }	undefined

Summary Do you wish to integrate the advection associated with porous flow species by parts?

41.3.2. Use Cvfem

Scope: Porous Flow Options

Use Cvfem {=*|are|is*} *use_cvfem*

Parameter	Value	Default
<i>use_cvfem</i>	{ <i>false true</i> }	undefined

Summary Specify whether to use CVFEM or Galerkin discretization. Default is Galerkin.

41.4. TURBULENCE MODEL SPECIFICATION

Scope: Solution Options

```
Begin Turbulence Model Specification TurbSpecName

    Activate Cvfem Lumped Turbulent Source Term Algorithm
    Activate Kepsilon Source Term Trickster Linearization
    Activate New Komega Src Linearization
    Activate Rhs Sdr Sensitivities To TurbSensParams
    Activate Rhs Tke Sensitivities To TurbSensParams
    Activate Turbulence Clipping Utility At UtilClipLocation
    Implicit Les Filter Scale {=|are|is} Value
    Limit Turbulent Ke Production To Value Times Dissipation
    Omit Finite Difference Sensitivity Due To Utau
    Omit Sensitivities In Turbulent Production Term
    Omit Sensitivities To Turbulent Production From Ke Source Only
    Omit Velocity Divergence In Turbulent Production Term
    Time Filter {=|are|is} Value
    Turbulence Model {=|are|is} TurbulenceModel
    Turbulence Model Parameter TurbParams {=|are|is} Value

End
```

Summary Specify turbulence modeling options.

41.4.1. Activate Cvfem Lumped Turbulent Source Term Algorithm

Scope: Turbulence Model Specification

Summary Lump cvfem turbulent ke, tdr and ksgs rhs source terms

Description This is appropriate for CVFEM only as it uses a special flavor of lumping source terms.

41.4.2. Activate Kepsilon Source Term Trickster Linearization

Scope: Turbulence Model Specification

Summary Follow classic Patankar approach to linearization of k rhs

Description The dissipation rate in the k equation includes sensitivities to k by using the Prandtl Kolmogorov relationship to for the model for of the dissipation rate. This procedure provides additional diagonal dominance for the k rhs source term.

41.4.3. Activate New Komega Src Linearization

Scope: Turbulence Model Specification

Summary Alternate komega src linearization

Description Alt komega src linearization

41.4.4. Activate Rhs Sdr Sensitivities To

Scope: Turbulence Model Specification

Activate Rhs Sdr Sensitivities To *TurbSensParams*

Parameter	Value	Default
<i>TurbSensParams</i>	{dens_sens sdr_sens tke_sens turb_prod_sens tvisc_sens}	undefined

Summary Dial in rhs sens for sdr equation

41.4.5. Activate Rhs Tke Sensitivities To

Scope: Turbulence Model Specification

Activate Rhs Tke Sensitivities To *TurbSensParams*

Parameter	Value	Default
<i>TurbSensParams</i>	{dens_sens sdr_sens tke_sens turb_prod_sens tvisc_sens}	undefined

Summary Dial in rhs sens for tke equation

41.4.6. Activate Turbulence Clipping Utility At

Scope: Turbulence Model Specification

Activate Turbulence Clipping Utility At *UtilClipLocation*

Parameter	Value	Default
<i>UtilClipLocation</i>	{begin_nonlinear_solve end_nonlinear_solve manually_run post_iterate post_linear_solve post_nonlinear_solve pre_iterate pre_linear_solve pre_nonlinear_solve run_initially run_once run_post_linear_system_initialization}	undefined

Summary Activate clipping utility for turbulence quantities

Description Sometimes it helps to clip the turbulence quantities. This is a utility that provides this support.

41.4.7. Implicit Les Filter Scale

Scope: Turbulence Model Specification

Implicit Les Filter Scale {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	undefined

Summary Provide implicit filter length

Description In constant coefficient LES models, allow the user to specify and implicit filter length. The default is to determine a length scale tied to the mesh.

41.4.8. Limit Turbulent Ke Production

Scope: Turbulence Model Specification

Limit Turbulent Ke Production To *Value* Times Dissipation

Parameter	Value	Default
<i>Value</i>	real	1.0e-8

Summary Choose to limit production source terms

Description This option limits the turbulent ke production to a scale factor of dissipation, $\text{prod} = \min(\text{prod}, \text{limit} \cdot \text{den} \cdot \text{en1})$. In practice, the ratio of production to dissipation is not very high. In some flows, it is useful to specify a value of approximately 1000. The ratio should be checked as part of the analysis to make sure that violation of the physical ratio has not been done. In general, this option is only activated in domain locations where dissipation rate is very small.

41.4.9. Omit Finite Difference Sensitivity Due To Utau

Scope: Turbulence Model Specification

Summary Omit FD sensitivity from utau

Description The wall friction velocity, utau, can be complex to evaluate in the context of the law of the wall. The default is to compute sensitivities via finite difference. Sometimes, this seems to add some overhead and spurious sensitivities.

41.4.10. Omit Sensitivities In Turbulent Production Term

Scope: Turbulence Model Specification

Summary Do not include sensitivities for turbulence production

Description This option removes the analytical sensitivities for the production of turbulent kinetic energy. It seems that most simulations are more stable if this option is activated.

41.4.11. Omit Sensitivities To Turbulent Production From Ke Source Only

Scope: Turbulence Model Specification

Summary Omit sensitivities to turbulence production from the KE source term

Description This option removes the analytical sensitivities for the production of turbulent kinetic energy in the KE source terms (where they may be destabilizing) but retains them elsewhere (where they may be helpful). Mutually exclusive w/ the previous option.

41.4.12. Omit Velocity Divergence In Turbulent Production Term

Scope: Turbulence Model Specification

Summary Do not include divergence term in turbulence production

Description This option removes the divergence term from the turbulent production of kinetic energy. The default is to include this term.

41.4.13. Time Filter

Scope: Turbulence Model Specification

Time Filter {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	real	1.0e32

Summary Time filter size for Time Filtered Navier-Stokes model

Description Turbulent viscosity is normally calculated based on a time scale given by k/ϵ (for k -epsilon models) or T (v2f model). The TFNS model substitutes the minimum of the normal computed value and the user-specified time filter size in the turbulent viscosity calculation. In general, this filter should be no less than twice the physical time step. A non-fatal warning is issued if this condition is violated.

41.4.14. Turbulence Model

Scope: Turbulence Model Specification

Turbulence Model {=|are|is} *TurbulenceModel*

Parameter	Value	Default
<i>TurbulenceModel</i>	{dsmag kepsilon komega ksgs laminar sarans smag sst}	undefined

Summary Specify type of turbulence model to be used

41.4.15. Turbulence Model Parameter

Scope: Turbulence Model Specification

Turbulence Model Parameter *TurbParams* {=|are|is} *Value*

Parameter	Value	Default
<i>TurbParams</i>	{a_1 beta beta_1 beta_star c_epsilon c_epsilon_1 c_epsilon_2 c_mu c_mu_cs c_mu_epsilon edc_c_gamma_lam edc_c_lam_trans edc_c_tau_lam gamma gamma_1 kappa lr_omega minimum_turbulent_viscosity pr_t ramp_time sa_cb1 sa_cb2 sa_cv1 sa_cw2 sa_cw3 sa_sigma sc_t sigma_epsilon_lam sigma_epsilon_trb sigma_k1_trb sigma_k_lam sigma_k_trb sigma_omega1_trb sigma_omega_lam sigma_omega_trb von_karman wall_length_factor y_plus_crit}	undefined
<i>Value</i>	real	undefined

Summary Turbulence model parameters

41.5. EDC MODEL SPECIFICATION

Scope: Solution Options

```

Begin Edc Model Specification EdcSpecName

    Activate Co2 Dissociation Model

    Activate Hydrogen Dissociation Model

    Activate Ignition Model {=@|at|for|in|on|over} IgnPart

    Activate Laminar Limit Model

    Activate Lumped Source Term Model

    Activate Separate Co Irreversible Oxidation Pathway

    Activation Time {=|are|is} Time

    Fuel Name {=|are|is} Fuel

    Ignition Threshold Temperature {=|are|is} IgnTemp

    Minimum Product Fraction {=|are|is} Prmin

    Reaction Time Scale {=|are|is} Tchem

    Reference Property {=|are|is} Value

    Reference Property Of Species {=|are|is} Value

Begin Oxidizer Mixture Specification OxMixName

```

End

End

Summary Specify EDC combustion model options.

41.5.1. Activate Co2 Dissociation Model

Scope: Edc Model Specification

Summary Include effects of CO₂ dissociation into CO and O₂ at high temperatures

Description At high temperatures, the equilibrium between CO₂, CO, and O₂ shifts away from CO₂, which can significantly decrease the flame temperature. Activating this model will add this effect to the standard EDC combustion model.

41.5.2. Activate Hydrogen Dissociation Model

Scope: Edc Model Specification

Summary Include effects of H₂ dissociation into H

Description At temperatures greater than about 2000K, the equilibrium between H₂ and H will yield non-negligible concentrations of H which can significantly decrease flame temperatures. Activating this model will add this effect to the standard EDC combustion model using the correlations of W.W. Erikson, which are derived from the NASA CEA code [44, 45].

Note that the H species must be included in the Cantera input XML file, and neither H nor H₂ should be the "last" species in the list since this species is not independent of the rest (to enforce unity sum) and may be susceptible to more noise than the others. Since temperature and other properties are very sensitive to oscillations in the H and H₂ equilibrium, this noise could be problematic.

41.5.3. Activate Ignition Model

Scope: Edc Model Specification

Activate Ignition Model {*@ | at | for | in | on | over*} *IgnPart*

Parameter	Value	Default
<i>IgnPart</i>	string	undefined

Summary MeshPart on which to use the EDC ignition model

Description Turn on the ignition model for this MeshPart. If fuel and oxidizer are present and the temperature is below the ignition threshold temperature everywhere in the part, reaction will begin. Volume block names and surface names are valid for this command, as well as the alias "all_blocks" and "all_surfaces". Multiple parts must be specified with multiple instances of this line command.

41.5.4. Activate Laminar Limit Model

Scope: Edc Model Specification

Summary Turn on the EDC laminar limit model for low-turbulence situations

Description Turn on the EDC laminar limit model. This model requires setting three model constants: CtauLam, CgammaLam, and ClamTrans. The model uses a time scale based on a velocity gradient rather than the turb_ke/turb_diss. This appropriate time scale permits the flame to anchor in laminar regions.

41.5.5. Activate Lumped Source Term Model

Scope: Edc Model Specification

Summary Nodally lump the EDC source term

Description If set, the EDC source terms are nodally lumped, rather than using the default implementation of a consistent approach at the Gauss points.

41.5.6. Activate Separate Co Irreversible Oxidation Pathway

Scope: Edc Model Specification

Summary Add CO oxidation pathway as a separate reaction pathway. This should really be used only in the context of a propellant fire in the presence of hydrogen combustion.

41.5.7. Activation Time

Scope: Edc Model Specification

Activation Time {=|are|is} *Time*

Parameter	Value	Default
<i>Time</i>	real	0.0

Summary The time at which the EDC combustion model is activated. No combustion will occur before this time.

41.5.8. Fuel Name

Scope: Edc Model Specification

Fuel Name {=|are|is} *Fuel*

Parameter	Value	Default
<i>Fuel</i>	string	undefined

Summary The name of the EDC fuel species, typically either H₂ or a major hydrocarbon

41.5.9. Ignition Threshold Temperature

Scope: Edc Model Specification

Ignition Threshold Temperature {=|are|is} *IgnTemp*

Parameter	Value	Default
<i>IgnTemp</i>	real	1000 K

Summary The temperature below which the ignition model is activated

Description If the ignition model is requested (through the "ACTIVATE IGNITION MODEL" line command, then it will be activated if all temperatures in the corresponding block are below this temperature.

41.5.10. Minimum Product Fraction

Scope: Edc Model Specification

Minimum Product Fraction {=|are|is} *Prmin*

Parameter	Value	Default
<i>Prmin</i>	real	1.0e-6

Summary The minimum product fraction, below which the EDC model will be deactivated.

41.5.11. Reaction Time Scale

Scope: Edc Model Specification

Reaction Time Scale {=|are|is} *Tchem*

Parameter	Value	Default
<i>Tchem</i>	real	7.0e-5

Summary Reaction time scale to set extinction

Description Characteristic time scale of the chemical kinetics. Residence time in the fine structure region will be compared to this to determine if extinction will result.

41.5.12. Reference

Scope: Edc Model Specification

Reference *Property* {=|are|is} *Value*

Parameter	Value	Default
<i>Property</i>	string	undefined
<i>Value</i>	real	undefined

Summary Reference property for initial diagnostic output

Description If all required properties are set, the EDC model will print the adiabatic flame temperature and heat of combustion for the mechanism defined by the specified fuel.

41.5.13. Reference

Scope: Edc Model Specification

Reference *Property Of Species* {=|are|is} *Value*

Parameter	Value	Default
<i>Property</i>	string	undefined
<i>Species</i>	string	undefined
<i>Value</i>	real	undefined

Summary Reference species-dimensioned property for initial diagnostic output

Description If all required properties are set, the EDC model will print the adiabatic flame temperature and heat of combustion for the mechanism defined by the specified fuel.

41.6. OXIDIZER MIXTURE SPECIFICATION

Scope: Edc Model Specification

```
Begin Oxidizer Mixture Specification OxMixName
    Mass_Fraction SpeciesName {=|are|is} Value
    Mole_Fraction SpeciesName {=|are|is} Value
End
```

Summary Specify either mass fractions or mole fractions for the oxidizer mixture. Only non-zero species need to be included, and the mass or mole fractions must sum to unity. The default is air, with a 0.2095:0.7905 molar ratio between O₂ and N₂.

41.6.1. Mass_Fraction

Scope: Oxidizer Mixture Specification

Mass_Fraction *SpeciesName* {=|are|is} *Value*

Parameter	Value	Default
<i>SpeciesName</i>	string	undefined
<i>Value</i>	real	undefined

Summary Oxidizer mixture mass fraction for the given species

41.6.2. Mole_Fraction

Scope: Oxidizer Mixture Specification

Mole_Fraction *SpeciesName* {=|are|is} *Value*

Parameter	Value	Default
<i>SpeciesName</i>	string	undefined
<i>Value</i>	real	undefined

Summary Oxidizer mixture mole fraction for the given species

41.6.3. Assemble Tpetra

Scope:

Assemble Tpetra {=|are|is} *Value*

Parameter	Value	Default
<i>Value</i>	{false true}	FALSE

Summary EXPERIMENTAL: Enable (true) to assemble to TPETRA and compare matrix and RHS to FEI matrix.

42. STRING FUNCTIONS

String functions can be used to define scalar, vector, and tensor expressions as a function of position (x, y, z) and time t as well as any expression that has been registered from the input deck. Currently the arguments for the string function must be scalars, although in the future vectors and tensors will be supported. If the function contains commas or spaces, it should be enclosed in quotes. Sensitivities for these string functions are calculated using finite-differences.

42.1. EXPRESSION EVALUATION

String function evaluation is handled using the STK expression evaluator. The specific set of valid variables that can be used in the function depends on where it is being used, but often includes things like time (t) and spatial coordinates (x, y, z) . In some cases, global variables are also registered as valid variables.

Variable names are case sensitive in the evaluator, however the calling app may remove this by converting the expression to all upper case or lower case in the code.

In addition to the registered variables, there are a large number of standard functions and operations available in the evaluator. The following section shows a number of different operators with examples and descriptions.

42.1.1. Powers

Powers can be specified either using the `pow` function or the standard a^b notation.

```
3^2  
pow(3,2)
```

42.1.2. Min and Max Functions

There are min and max functions that take 2 to 4 comma-separated inputs.

```
min(1,2)  
min(1,2,3,4)  
max(1,2)  
max(1,2,3,4)
```

42.1.3. Inline Variables

You can define variables inline in the function string, although doing this with `aprepro` in your input file is often more straightforward.

```
a=1;b=2;a+b+4
```

42.1.4. Ramps and Pulses

There are a number of pre-defined ramp and step functions.

```
cycloidal_ramp(t,ts,te)
haversine_pulse(t,ts,te)
cosine_ramp(t)
cosine_ramp(t,te)
cosine_ramp(t,ts,te)
sign(x)
unit_step(t,ts,te)
point2d(x,y,r,w)
point3d(x,y,z,r,w)
```

42.1.4.1. Cosine Ramp

The `cosine_ramp` function provides a smooth ramp from 0 to 1. It can be used with 1, 2, or 3 inputs. The form with one input uses a start and end time of 0 and 1. The form with two inputs specifies the end time, but uses a start time of 0. Note that `cos_ramp` is also a valid function, and is equivalent to `cosine_ramp`.

$$\text{cosine\_ramp}(t, t_s, t_e) = \begin{cases} 0, & t \leq t_s \\ \frac{1}{2} \left(1 - \cos \left(\frac{\pi(t-t_s)}{t_e-t_s} \right) \right), & t_s < t < t_e \\ 1, & t \geq t_e \end{cases} \quad (42.1)$$

42.1.4.2. Cycloidal Ramp

The `cycloidal_ramp` function is another smooth ramp function from 0 to 1. Unlike the `cosine_ramp` function, it requires all three arguments.

$$\text{cycloidal\_ramp}(t, t_s, t_e) = \begin{cases} 0, & t \leq t_s \\ \frac{t-t_s}{t_e-t_s} - \frac{1}{2\pi} \sin \left(\frac{2\pi(t-t_s)}{t_e-t_s} \right), & t_s < t < t_e \\ 1, & t \geq t_e \end{cases} \quad (42.2)$$

42.1.4.3. Haversine Pulse

The `haversine_pulse` function is a smooth sinusoidal finite width pulse, defined by

$$\text{haversine\_pulse}(t, t_s, t_e) = \begin{cases} 0, & t \leq t_s \\ \sin\left(\frac{\pi(t-t_s)}{t_e-t_s}\right)^2, & t_s < t < t_e \\ 0, & t \geq t_e \end{cases} \quad (42.3)$$

42.1.4.4. Sign

The `sign` function returns the sign of its single argument

$$\text{sign}(x) = \begin{cases} 1, & x \geq 0 \\ -1, & x < 0 \end{cases} \quad (42.4)$$

42.1.4.5. Unit Step

The `unit_step` function is a sharp square step function

$$\text{unit\_step}(t, t_s, t_e) = \begin{cases} 0, & t \leq t_s \\ 1, & t_s < t < t_e \\ 0, & t \geq t_e \end{cases} \quad (42.5)$$

42.1.4.6. 2D Point

The `point2d` function provides a 2D point mask for applying a function in a certain spatial window. It is equivalent to a longer call to `cosine_ramp` where

$$\text{point2d}(x, y, r, w) = 1 - \text{cosine\_ramp}(\sqrt{x^2 + y^2}, r - w/2, r + w/2) \quad (42.6)$$

42.1.4.7. 3D Point

The `point3d` function provides a 3D point mask for applying a function in a certain spatial window. It is equivalent to a longer call to `cosine_ramp` where

$$\text{point3d}(x, y, z, r, w) = 1 - \text{cosine\_ramp}(\sqrt{x^2 + y^2 + z^2}, r - w/2, r + w/2) \quad (42.7)$$

42.1.5. Basic Math

There are standard mathematical functions. Most of these require no explanation, although it is worth noting that `log` is the natural log (equivalent to `ln` not `log10`).

```
exp(x)
ln(x)
log(x)
log10(x)
pow(a,b)
sqrt(x)
erfc(x)
erf(x)
acos(x)
asin(x)
asinh(x)
atan(x)
atan2(y,x)
atanh(x)
cos(x)
cosh(x)
acosh(x)
sin(x)
sinh(x)
tan(x)
tanh(x)
```

42.1.6. Rounding Functions

There are a variety of rounding and numerical manipulation routines available.

```
ceil(x)
floor(x)
abs(x)
mod(x,y)
ipart(x)
fpart(x)
```

You can round up with `ceil` and round down with `floor`. You can separate a number into its integer part (`ipart`) and floating point part (`fpart`). You can compute the modulus with `mod` and get the absolute value with `abs`.

42.1.7. Polar Coordinate and Angle Helpers

When working with polar and rectangular coordinates there are helper functions for converting coordinate systems as well as for converting degrees to radians and back.

```
poltorectx(r,theta)
poltorecty(r,theta)
deg(r)
rad(d)
recttopola(x,y)
recttopolr(x,y)
```

The conversion functions are:

$$\text{poltorectx}(r, \theta) = r \cos(\theta) \quad (42.8)$$

$$\text{poltorecty}(r, \theta) = r \sin(\theta) \quad (42.9)$$

$$\text{recttopola}(x, y) = \text{atan2}(y, x) \quad (42.10)$$

$$\text{recttopolr}(x, y) = \sqrt{x^2 + y^2} \quad (42.11)$$

The angle returned by `recttopola` is adjusted to be between 0 and 2π .

42.1.8. Distributions and Random Sampling

There are several functions available for generating pseudo-random output with different distributions. When using random output in a string function, be careful using it in places where it can affect nonlinear convergence.

For example, setting an initial condition using a random distribution is acceptable since it is only evaluated once. However, using that to define a material property (for example, thermal conductivity) or boundary condition would result in that property varying not just in time and space, but also from one nonlinear iteration to the next, which would general keep a Newton solver from converging. The `ts_random` and `ts_normal` functions are designed to help with this problem.

```

weibull_pdf(x,shape,scale)
normal_pdf(x,mu,sigma)
gamma_pdf(x,shape,scale)
log_uniform_pdf(x,xmin,xmax)
exponential_pdf(x,beta)
random()
random(seed)
time()
ts_random(t,x,y,z)
ts_normal(t,x,y,z,mu,sigma,minR,maxR)

```

42.1.8.1. Weibull Distribution

The `weibull_pdf` function returns a Weibull distribution, where λ is the scale parameter and k is the shape parameter.

$$\text{weibull\_pdf}(x, k, \lambda) = \begin{cases} \frac{k}{\lambda} \left(\frac{x}{\lambda}\right)^{k-1} e^{-(x/\lambda)^k}, & x \geq 0 \\ 0, & x < 0 \end{cases} \quad (42.12)$$

42.1.8.2. Normal Distribution

The `normal_pdf` function returns a normal distribution, where μ is the mean and σ is the standard deviation.

$$\text{normal\_pdf}(x, \mu, \sigma) = \frac{1}{\sqrt{2\pi\sigma^2}} \exp\left(-\frac{(x-\mu)^2}{2\sigma^2}\right) \quad (42.13)$$

42.1.8.3. Gamma Distribution

The `gamma_pdf` function returns a gamma distribution, where θ is the scale parameter and k is the shape parameter.

$$\text{gamma\_pdf}(x, k, \theta) = \frac{1}{\Gamma(k)\theta^k} x^{k-1} e^{-x/\theta} \quad (42.14)$$

42.1.8.4. Log Uniform Distribution

The `log_uniform_pdf` function returns a log-uniform distribution

$$\text{log\_uniform\_pdf}(x, x_0, x_1) = \frac{1}{(\ln(x_1) - \ln(x_0))x} \quad (42.15)$$

42.1.8.5. Exponential Distribution

The `exponential_pdf` function returns a one-parameter exponential distribution

$$\text{exponential\_pdf}(x, \beta) = \frac{1}{\beta} e^{-x/\beta} \quad (42.16)$$

42.1.8.6. Random Values

There are several functions for generating pseudo-random numbers. These can be used as inputs to any of the distributions, or as standalone values to get a uniform distribution.

`random()` calls a platform-independent fast pseudo-random number algorithm. It is seeded with a static constant, so the first call to it will always produce the same value. The value returned will be between 0 and 1.

`random(seed)` calls the same algorithm as `random()` but sets the seed first then returns a number between 0 and 1. The seed in this case can be any floating point number.

`time()` returns the current time integer. This can be used to provide a random number seed to make the distributions non-deterministic from run to run.

`ts_random(t,x,y,z)` returns a uniformly distributed random number from 0 to 1 that is unique in time and space. This means that repeated evaluations of this function at the same point in time and space will produce the same output. This is useful for applying randomness on boundary conditions, for example, where the value should not change during nonlinear iterations at a given time.

`ts_normal(t,x,y,z,mu,sigma,minR,maxR)` returns a clipped normally distributed random number with a mean of `mu` and standard deviation of `sigma`. The output is clipped to be between `minR` and `maxR` and, like `ts_random`, the output is deterministic in time and space.

42.1.9. Boolean and Ternary Logic

In addition to all these functions, you can make more complicated functions using ternary statements and boolean logic.

You can use ternary operators for simple conditional assignment. The basic structure of a ternary operator is `boolean ? value_if_true : value_if_false`. For example, the following if-else code

```
if x > 2.2:
    return 1.2*y
else
    return 0.1*y
```

can be converted to a ternary operator that returns the same thing


```
(x > 2.2 ? 1.2 : 0.1) * y
```

You can also use boolean operations in the string functions. By default, booleans that evaluate to true are treated as 1 and booleans that are false are 0. The prior example can be expressed using boolean statements as

```
(x>2.2)*1.2*y + (x<=2.2)*0.1*y  
((x>2.2)*1.1 + 0.1)*y
```

These operations can be combined (multiplication of boolean statements is equivalent to a logical and). To replicate the `unit_step` function described earlier you can use either ternary or boolean operators. The following three functions all produce the same result—a step of height 5 between 1 and 2.

```
5*unit_step(x,1,2)  
((x>1 && x<2) ? 5 : 0)  
5*(x>1)*(x<2)
```

42.2. SCALAR STRING FUNCTIONS

Scalar string functions can be used to define scalar material properties as well as boundary conditions and initial conditions for scalar quantities. Some examples of correct syntactical usage of these scalar string functions are listed below.

Example

```
density = scalar_string_function f = "2*x"
```

Here, the material property "density" was assigned a value depending on the "x" coordinate.

Example

```
BC dirichlet for temperature on surface_1 =  
scalar_string_function f = "density*sin(t)"
```

Here, a dirichlet boundary condition was applied on a surface for temperature as a function of the material property density (defined in the first example) and time. You can insert any expression that exists in your input deck as an argument for the function. If the expression is not found, the program will exit.

Example

```
IC for temperature on block_1 = scalar_string_function f =  
"x*y*z"
```

Here, an initial condition for temperature is set also as a function of the spatial coordinates. This is for a three-dimensional case as the "z" component is included. If this line was used in a two-dimensional geometry, the program would exit because it could not find the "z" coordinate.

42.3. VECTOR STRING FUNCTIONS

Vector string functions work in the same manner as their scalar counterpart, but must have functions specified for each vector component

Example

```
BC dirichlet for velocity on surface_1 = vector_string_function
f_x = "1-x" f_y = "viscosity*sin(t)" f_z = "0.0"
```

Here we apply a dirichlet BC on velocity for a three-dimensional geometry.

42.4. TENSOR STRING FUNCTIONS

Tensor string functions work in the same manner as vectors, but must have functions specified for each tensor component

Example

```
Intrinsic Permeability = tensor_string_function f_xx = "1-x"
f_yy = "1e-12*exp(t)" f_xy = "solid_phase_porosity*1e-12" f_yx =
"0"
```

Here we define the intrinsic permeability as a tensor string function for a two-dimensional geometry. For the `tensor_string_function`, the user must supply all components of the tensor. However, one can use the `tensor_string_function_symmetric` command

Example

```
Intrinsic Permeability = tensor_string_function_symmetric
f_xx = "1-x" f_yy = "1e-12*exp(t)" f_xy =
"solid_phase_porosity*1e-12"
```

which enforces symmetry on the off-diagonal tensor component such that $f_{yx} = f_{xy}$.

42.5. USING CONDITIONAL OPERATORS

String functions also have the ability to apply conditional operators

Example

```
density = scalar_string_function f = "x > 0 ? 2*x : 2"
```

This applies the function $2*x$ when $x > 0$, otherwise setting density to 2.

Example

```
density = scalar_string_function f = "(x>0)*2*x + (x<=0)*2"
```

This does the exact same operation as the previous example. In this case the boolean $(x>0)$ or $(x<=0)$ gets evaluated as 0 or 1 depending on if the statement is false or true as a function of "x".

43. FREQUENTLY ASKED QUESTIONS

This chapter includes a compilation of frequently asked questions and problematic scenarios raised by users of the SIERRA Multimechanics Module: Aria. Here the questions are grouped into specific categories of interest but some of the items may appear in more than one category.

- General [43.1](#)
- Capability [43.2](#)
- Errors [43.3](#)
- Solver [43.4](#)
- Thermal [43.5](#)
- Radiation [43.6](#)
- Timestep [43.7](#)
- Contact [43.8](#)
- Species [43.9](#)
- Porous Media [43.10](#)
- Electrostatics [43.11](#)
- Grid Refinement [43.12](#)
- Postprocessing [43.13](#)

43.1. GENERAL

Aria example/tutorial files.

SNL internal users can find an Aria training presentation, which includes two PDFs and multiple example files on the following website:

<http://compsim.sandia.gov/compsim/>

To navigate to the presentations, go to “Support & Services -> Documentation”. Once there, go to “Version of the Day -> General Release”. This will open a new page with an expandable tree. Go to “Training/Tutorials -> Thermal/Fluid”.

Methods for accessing VOTD code.

SNL internal users can access VOTD code on the various platforms by executing module `load sierra/master`.

Use of the VOTD code for production simulations is generally discouraged as stability of the code is subject to daily change. Whenever possible the analyst is encouraged to use the current released distribution executable.

What is the Aria command to specify a log file name.

If the input file is named `base_input.i` then by default the log file is written to `base_input.log`. One can specify an alternative log file by providing optional arguments, either `-o other.log` or `-l other.log` to the job execution command line.

What optional arguments can be used with the Aria command.

The list of arguments which can be used with the Aria command can be listed by:

```
aria -h
```

Is the includefile command supported in Aria?

Yes, this feature is supported in all Sierra Mechanics applications. However, the `aprepro include` command is more robust and supports nested include files, while Sierra's `includefile` command does not.

What is the difference between History and Heartbeat output?

The big difference between history and heartbeat output is the type of output. History output is binary format, like Exodus, while Heartbeat output is in ASCII format, like a .txt file. Thus the History output must be visualized with a graphical tool while Heartbeat output is simply inspected or used to generate x-y plots.

Why does restart output a file per processor?

The reason for this is that one typically continues a restart on the same number of processors as the original run. This is also the reason why restart files aren't concatenated at the end of a successful run. Additionally, unless the intent is to overwrite a restart file, one must specify different names for the input and output restart files in the Restart Data block.

Recently the ability to restart with a different number of processors has been provided but requires that one first concatenate the original files and perform the decomposition on the new processor count.

Can one include a text file in an input deck?

Yes, Aprepro provides a way to do this. The syntax is as follows:

```
{include "materials.dat"}
```

Aprepro must be executed on the input deck before running.

43.2. CAPABILITY

Can one use steady-state simulation results to specify initial conditions on a different geometry.

There are two possible approaches to accomplish this:

1. using the `omit` block option with the initial conditions via the IC read file option
2. Interpolate the simulation results onto the new geometry using transfers from the Input_Output Region.

Can Aria solve a condensation problem?

There is ongoing work in studies of evaporation, but condensation is not currently supported.

Can one use a FORTRAN user subroutine for heat flux boundary condition?

Yes one can do this but FORTRAN subroutines are currently available only for heat transfer problems.

What can one model with shell elements in Aria.

Typical usage of thermal shell elements in Aria is for materials, which have no through-thickness temperature variation but have thermal diffusion in the plane of the shell. The shell can also account for thermal capacitance. Cases where the through thickness resistance of heat flow through the material is more important will generally be modeled with resistance contact (no shell). The in-between case is a combination of the above. Limited support is also available for shells with through-thickness temperature variation but these models are restricted to having only shell elements.

Does Aria support 1D elements, such as bars?

Aria does support 2D and 3D bar elements however no provision is made for application of flux boundary conditions at the end of the bar. Thus in many cases one may be better off using volume elements instead.

How does one implement a volumetric source on a 2D mesh.

The fundamental assumption in 2D FEM Cartesian formulations is that of a unit depth cross-section in defining the corresponding volume. Hence, the command `add volume block_name` will work in both 2D and 3D cases.

Can Aria be run explicitly?

Explicit methods do circumvent the complicated details of efficient preconditioners and general solver efficiencies based on both matrix condition number and potential high core counts with generally low work per core. However, depending on the time scales of interest of the problem, explicit methods can be painfully inefficient. In general, production Aria does not support explicit methods.

How to load a single displacement field.

To load a previously computed displacement field and use it throughout the Aria thermal simulation, one needs to extract the displacement solution from a single time plane in the displacements file and assign it to the `mesh_displacements` Field in Aria. Internally Aria will

update the current configuration, `model_coordinates + mesh_displacements`, and compute on that geometry.

Is it possible to write a plugin to create a boundary condition that prescribes an angular velocity to a block?

Yes, one can write plugins for boundary conditions. However, in order to apply an angular velocity boundary condition to a block one would presumably be solving for the block motion.

Is there a way to apply a force on surface?

In Aria forces cannot be applied directly at a node. Instead nodal forces are computed from integrated surface tractions:

```
BC Flux for solid on surface_10 = Constant_Traction Y = 1800.0
```

What is the expression syntax for beam sections in Aria?

Syntax is similar to that of shells:

```
bar area = constant a = 0.000768
```

How can one define a temporally-ramped velocity.

The syntax should be:

```
BC LINEAR_IN_TIME Dirichlet at surface_1 velocity_x coefs = 0.1
```

If one wants to ramp up from `velocity_x = C0` to `velocity_x = C1` in time `C2` and then hold `velocity_x` at `C1` then try `BC RAMP_LINEAR_IN_TIME` instead:

```
BC RAMP_LINEAR_IN_TIME Dirichlet at surface_1 velocity_x coefs = C0 C1 C2
```

so that `velocity_x = C0 + (C1-C0) *MIN(t/C2,1.0)`. If the user manual is not handy, it is sometimes useful to extract the command syntax from the executable using:

```
sierra aria -i your.i -print-syntax | grep -i LINEAR_IN_TIME
```

This produces a somewhat cryptic definition of the expected syntax but it sometimes helps.

43.3. ERRORS

Cannot find a volume element on the surface error.

This problem often occurs when attempting to use a nodeset in flux boundary condition definition. Aria applies surface sideset contributions as volume contributions and often uses volume information to lookup surface information. Thus Aria is unable to look up the volume element unless it has a sideset, even though the surface nodesets are specified.

2D analysis fails due to incorrect element type used.

Typically this occurs when the grid file uses some form of 3D elements. If the grid file was created in CUBIT, then one needs to change the element type before exporting the mesh. An example of how you do that in CUBIT is:

```
block 1 element type quad
```

Additionally one must make sure to use the `dimension 2` in the CUBIT export command in order to ensure that the z coordinate is not included in the output file.

Unable to achieve convergence in anisotropic thermo-diffusion model.

This class of problems is difficult to solve. First off, the matrix is non-symmetric, which is automatically harder to solve. Second, there are different sets of physics occurring in the problem (in this case, species and temperature), and each set of physics will have a different contribution. If their contributions aren't within a couple orders of magnitude, then the problem also has great difficulty in converging. This has been viewed in thermoelectric models. In a few instances, the analyst was able to work around this difficulty by specifying a different system of units (e.g., changing from volts to millivolts). The idea here is to rescale the solution variables to be of comparable magnitude.

Nonphysical temperature overshoot in 2-material conduction model.

Typically, the temperature overshoot issue can be resolved by using `lumped_mass` instead of `mass` in the EQ specification. Use of the `mass` keyword invokes construction of a consistent mass matrix. While consistent mass is supported by a theoretical foundation for convergence, it oftentimes exhibits the behavior of overshooting. Most models which involve a large step change are better dealt with using a "lumped mass" matrix.

Problem with enforcing species conservation.

Usually a problem stems from inconsistent units being used in the models. Make sure the units for the reactions are consistent with everything else.

TET10 interpolation for post-processing produces an error.

Since the TET10 element is second-order, one needs to use Q2 in the EQ specifications and for post-processing, since in both cases there is interpolation involved.

Contact resistance error: edges share more than two element faces.

This can occur when portions of the specified contact surfaces are physically connected. Typically these type of problems are related to the mesh when `unmerge` command is used. Double checking the mesh would be the first place to start.

43.4. SOLVER

What do real residual check and time step fails mean?

Real Residual Check Failed means that the solve was unable to arrive at a solution that satisfied the solve tolerance specified in the radiosity solver command block. The Time Step Failed message in the log file means exactly that, the Newton step has failed to converge in the number of maximum number of nonlinear iterations specified. This will cause the time step to be reduced and the Newton step will be retried.

Unable to achieve convergence in anisotropic thermo-diffusion model.

This class of problems is difficult to solve. First off, the matrix is non-symmetric, which is automatically harder to solve. Second, there are different sets of physics occurring in the problem (in this case, species and temperature), and each set of physics will have a different contribution. If their contributions aren't within a couple orders of magnitude, then the problem also has great difficulty in converging. This has been viewed in thermoelectric models. In a few instances, the analyst was able to work around this difficulty by specifying a different system of units (e.g., changing from volts to millivolts). The idea here is to rescale the solution variables to be of comparable magnitude.

Contact problem that is being solved is not converging.

Typically, this occurs when some blocks might not be constructing the appropriate contact constraints. By adjusting the interaction constraint tolerances might help to perform converged solves on a submodel. The issue can be remedied by adding the following tolerances to the contact definition command block:

```
begin search options
  normal tolerance = 0.0001
  tangential tolerance = 0.00005
end search options
```

Also, the amount of contact present in a model will dictate the choice of linear solver. The recommended choice would be:

```
solution method = gmres
preconditioning method = dd-ilut
```

Aztec numerical breakdown error.

This specific problem occurs when the matrix near diagonal elements either go to 0 or approach a singularity. This is a common occurrence when fluids are involved.

43.5. THERMAL

How to define function-based tensor thermal conductivity?

Assuming that functions are user defined functions (tabular functions). Letting the conductivity functions be `func_kx`, `func_ky`, `func_kz` respectively then the syntax for temperature dependent functions would be:

```
tensor thermal_conductivity = user_function Name_xx = func_kx Name_yy =  
func_kx Name_zz = func_ky X= temperature
```

If the functions are time dependent then only difference would be: `X = time`.

Does contact conductance contribute to the Joule heating term in the energy equation?

Joule heating is applied volumetrically. Contact conductance is modeled as an interface flux condition between opposing surfaces and has no intrinsic association with a volume. Hence contact conductance cannot contribute to Joule heating.

Can Aria solve a condensation problem?

There is ongoing work in studies of evaporation, but not yet condensation.

How to evaluate the time rate change in thermal energy.

The time rate change in thermal energy should be $\rho * C_p * (dT/dt) * \text{elem\_volume}$. The results block should contain:

```
nodal variables = time_derivative_at_time->TEMPERATURE as dtemp_dt  
nodal variables = pp->density as rho  
nodal variables = pp->specific_heat as cp  
element variables = current_element_volume as e_vol
```

Then within the EnSight calculator you can define a variable and evaluate the following expression:

```
rho*cp *dtemp_dt*e_vol
```

How does Aria output the temperature of shell elements? Does it output the average or the outer or inner surface temperature?

For the standard shell there is only one nodal value of temperature. For the specialized implementations, linear and quadratic shells there are two nodal values of surface temperature, one associated with top and bottom of the shell.

Can one model a thermal symmetry boundary condition?

Yes, you can either specify no boundary condition on your symmetry surface, which will default to adiabatic, or specify a zero flux boundary condition, which will satisfy a symmetric solution.

How does one terminate a run based on variable rate of change (dT/dt)?

One can use the same approach for terminating a maximum rate of temperature change, dT/dt , in the same way as for using maximum temperature via `Encore MIN MAX Postprocessor` command block.

How does specify variable density and specific heat?

One can specify both variable density and specific heat with the `user_function`.

What can one model with shell elements in Aria.

Typical usage of thermal shell elements in Aria is for materials, which have no through-thickness temperature variation but still model diffusion in the plane of the shell. The shell can also account for thermal capacitance. Cases where the through thickness resistance of heat flow through the material is more important will generally be modeled with resistance contact (no shell). The in-between case is a combination of the above.

How to link reference temperature to temperature of bulk fluid element used in convective flux boundary condition.

Numerical modeling of heat transfer by enclosure radiation represents the transport between facets of the surface representation of a closed volume. Modeling this problem with enclosure radiation would require a surface representation of the body within the cavity where the closed volume is defined by the void region bounded by body and cavity. From a solution perspective, enclosure radiation heat transfer is de-coupled from the standard finite element solution. This means that one can solve the enclosure radiation problem and also include convective heat transfer from the surrounding cavity surface by computing an average body temperature and using that value as the reference temperature. Alternatively one could define a bulk element for the air cavity and setup the convective heat transfer problem to include both the cavity surface and body surface. Aria allows for superposition of heat flux contributions. In an approach with a bulk element representation of the body, the bulk element temperature would serve as the reference temperature for both convective and radiative heat transfer between the cavity surfaces and the body. If one wishes to treat the absorptive medium as being optically thin one would mesh the cavity interior and the body and use the Rosseland Mean approximation of thermal conductivity.

How to save thermal conductivity as a nodal/element variable for output.

This can be accomplished using the `postprocess` command. Use this command in the Region scope:

```
Postprocess Thermal_Conductivity on block_1 block_2 block_n
```

and in the Results Output, use this command:

```
Nodal Variables = pp->Thermal_Conductivity as K
```

Is it possible to use radiation enclosure and heat loss by convection using the bulk fluid element approximation?

In Aria flux contributions are cumulative. Both convection to a bulk node cavity temperature can be superposed with the enclosure radiation flux.

How to represent thermal conductivity as a polynomial function of temperature.

Since the independent variable is Temperature, specification would be:

```
something = Polynomial Variable=Temperature Order=2 C0=6.0789 C1=-0.0225 C2=4.0e5
```

Element Death For Laser Melting Through Plate Array.

Laser flux algorithms assume visibility of the source by the surfaces assigned in the flux definition. Hence, element death in each of the plates occurs simultaneously instead of in succession.

How to calculate heat flux through a sideset.

1. If it's a global variable you want, then add the following block in the Region scope:

```
Begin Solution Options
  post process FLUX heat_conduction on surface_1 as Q_Surf
End Solution Options
```

Then you can use this as a global variable in your output blocks:

```
Begin Results OUTPUT AriaOutput
  global Variables = Q_surf
End Results OUTPUT AriaOutput
```

Or in heartbeat output:

```
Begin HEARTBEAT Heart1
  variable = global Q_Surf as Q_Surf
End HEARTBEAT Heart1
```

2. If you'd like the heat flux at each node point, then add this line to the Region scope of your input deck:

```
Postprocess Heat_Conduction on surface_1
```

Then you can use the nodal values in your output as such:

```
Begin Results OUTPUT AriaOutput
  Nodal Variables = pp->heat_conduction as Q
End Results OUTPUT AriaOutput
```

All of the post-processing commands can be found in the Postprocessor Operations chapter [21](#) of the Aria user manual.

How to properly define contact to transfer heat.

Contact requires that the mesh be discontinuously meshed at the contact interface with normals oriented into the contact interface. In the case that `surface_1` and `surface_2` have normals oriented in the same direction, the search will fail and no contact constraints will be applied, hence no heat transfer.

Assigning a Dirichlet temperature BC to an entire block in aria.

Try the following:

```
BC USER_FUNCTION_IN_TIME DIRICHLET ON BLOCK_3 TEMPERATURE =  
UserFunctionName
```

Is there a way to apply a force on surface?

Nodal forces are computed from integrated surface tractions:

```
BC Flux for solid on surface_10 = Constant_Traction Y = 1800.0
```

Syntax for having a tensor thermal conductivity described by polynomials in both directions in Aria?

The Aria code does not currently have an option to specify tensor thermal conductivity using polynomials. Alternative are to use either:

1. User Function tensor or
2. a Calore style user sub to compute and set the tensor.

Estimating the heat flux.

For the Aria application, there a couple of ways to estimate the heat flux at selected locations. The first method is to use the `heat_flux` postprocessor on `all_blocks` while the second is to use the calculator function in EnSight.

43.6. RADIATION

Viewfactor calculation doesn't converge due to bad rowsum.

Typically, this occurs when there is a problem with the mesh or the surfaces specified in the Enclosure Definition. The preferred method to debug enclosures is to add the following line to the Enclosure Definition Block:

```
Rowsum Database name = your_enclosure_file.e
```

Upon job execution Aria will output a file containing rowsums for each of the enclosure facets. One can then view the enclosure geometry colored by the rowsum value in order to spot the problem areas. For a good enclosure, each facet should have a viewfactor rowsum very near 1. Another option that one could try is to use the option `Use Dash Enclosures` at the Aria Region Scope. This option will “skin” all the blocks in the data set and will create all the enclosures that are contained therein.

Is it possible to use radiation enclosure and heat loss by convection using the bulk fluid element approximation?

In Aria flux contributions are cumulative. Both convection to a bulk node cavity temperature can be superposed with the enclosure radiation flux.

Is there a way to rebalance aria viewfactors from a 64 node run to be used on a 16 node run?

Currently, the view factors can be used only with the same number of processors for which they were originally computed.

Is there a way to extract the incident heat flux seen by a component within an enclosure definition?

Add these commands to the Begin Results Output block:

```
face variables = radiosity as J  
face variables = irradiance as G  
face variables = rad_flux as Q
```

Problem with enclosure radiation calculations.

Typically the root cause of this problem is having surface normals pointing in the wrong direction. Make sure that all sidesets have the correct surface normal.

43.7. TIME STEPPING

What do real residual check and time step fails mean?

Real Residual Check Failed means that the solve was unable to arrive at a solution that satisfied the solve tolerance specified in the radiosity solver command block. The Time Step Failed message in the log file means exactly that, the Newton step has failed to converge in the number of maximum number of nonlinear iterations specified. This will cause the time step to be reduced and the Newton step will be retried.

How does one terminate a run based on variable rate of change (dT/dt)?

One can use the same approach for terminating a maximum rate of temperature change, dT/dt , in the same way as for using maximum temperature via Encore MIN MAX Postprocessor command block.

Time step size not increasing.

Even after setting the maximum time step, the time step might be limited or constrained by the output increment in the Begin Results Output block.

Aria fails to exit when timestep refined to zero.

Simple workaround is after the Initial Time Step Size = 5 command, add the syntax Minimum Time Step Size = 5. This will prevent Aria from trying to half the time-step and will force it to exit.

Early-time results of steady-state run are nonphysical.

When one runs a linear to mildly non-linear model in a pseudo-transient manner, the intermediate results obtained will generally appear unreasonable and even nonphysical. Although it may appear that physical time steps are being taken, the only result that can be relied upon is the steady-state solution, as long as the solution has converged.

How can I transition a tabular material property from steady-state to transient?

The following input is sufficient for changing a material property between steady-state and transient analysis in the same simulation. Note that the steady-state material property goes from 0.0 to 1.0, and the transient portion comprises 1.0000001 and onward.

```
begin definition for function mat1_time
  type is piecewise linear
  abscissa = x_label
  ordinate = y_label
  begin values
    0.000000    0
    1.000000    0
    1.0000001 129
    1e9         129
  end values
end
```

43.8. CONTACT

What are the proper units for electrical contact conductance coefficient?

The units are equivalent to a heat transfer coefficient which would have the units of $1/(\text{resistance} \cdot \text{area})$, which is equivalent to $(\text{current}/(\text{volts} \cdot \text{area}))$.

Can I define contact conductance as an analytic function?

No, this capability is not currently available.

Can one simulate a sliding block in Aria?

Yes, one can do this but the contact physics will be based strictly upon contact between the two surfaces, without sliding friction effects.

How to model multiple thermal and electrical contact conductances.

Typically, attempts to use two contact definitions in the Aria Region fail due to conflicts between the conductance coefficient used in each of the contact definitions. This problem can be circumvented by using multiple Aria Regions or by defining multiple sidesets at the contact interface.

Contact problem that is being solved is not converging.

Typically, this occurs when some blocks might not be constructing the appropriate contact constraints. By adjusting the interaction constraint tolerances might help to perform converged solves on a submodel. The issue can be remedied by adding the following tolerances to the contact definition command block:

```
begin search options
  normal tolerance = 0.0001
  tangential tolerance = 0.00005
end search options
```

These tolerances reflect physical distance which should represent the the geometry of the modeled discretization. Also, the amount of contact present in a model will dictate the choice of linear solver. For generalized contact, `tied_temperature` or `gap_conductance` the recommended solver is:

```
solution method = gmres
preconditioning method = dd-ilut
```

What are the proper units for electrical contact conductance coefficient?

The units are equivalent to a heat transfer coefficient which would have the units of $1/(\text{resistance} \cdot \text{area})$, which is equivalent to $(\text{current}/(\text{volts} \cdot \text{area}))$.

43.9. SPECIES

Does Aria support modeling a reaction that is dependent on temperature, pressure, and species concentration?

Yes, it is possible to implement a user plugin for quantities that are dependent on each of those.

Problem with enforcing species conservation.

Usually a problem stems from inconsistent units being used in the models. Make sure the units for the reactions are consistent with everything else.

Species diffusion subroutines cause non-physical results and residuals are high.

Try using a direct solver. At times, GMRES with Jacobi or DD-ILUT for preconditioning methods may not converge.

43.10. POROUS MEDIA

How can one output the non-wetting phase pressure?

Since the non-wetting phase pressure is needed in the wetting phase solution, it is available for output not as a solution variable but as a post-processed variable. In general, the pressure can be output provided one is able to specify its material phase. In this case the syntax would be:

```
postprocess non_wetting_phase_pressure on all_blocks
```

and the variable could be output to a results file as:

```
nodal variables = pp->non_wetting_phase_pressure as P_NW
```

Can capillary pressure be added as postprocess variable?

Yes, post-processing of capillary pressure is supported, which can later be added to an output.

No expression for intrinsic permeability vs. time table.

Intrinsic permeability is handled a bit differently than other porous media properties since the tensor character (ratio of coefficients) is normally preserved. Instead intrinsic permeability is modified by introducing a scaling factor:

```
Intrinsic Permeability = Constant XX=1.0 YY=1.0 ZZ=1.0
```

```
Intrinsic Permeability scaling = user_function name = Time_Permeability_Function x
```

What is the difference between the options Porosity = Mesh_deforming and

Porosity = Solid_deforming?

Mesh_Deforming and Solid_Deforming are identical, except Mesh_Deforming works on the mesh equation and Solid_Deforming works on the solid equation.

What do all the different forms of density mean?

For porous media problems, a typical input file may contain specifications for many types of density. The common instances are DENSITY, SOLID_DENSITY, BULK_MASS_DENSITY, and BULK_DENSITY.

The units for DENSITY are different for solid and non-solid phases. For the solid phase, DENSITY is mass per element volume, while for non-solid phases it is mass per phase volume.

The SOLID_DENSITY is an intrinsic material property, defined as the mass of a substance divided by the volume occupied by that substance. In Aria it is only a valid property for the solid phase, and is typically used to define a variable porosity in combination with the solid mass fractions.

The BULK_MASS_DENSITY is in units of mass per element volume for all phases. This is used in the mass term for mass balance equations, and can be selected from a number of different models. Because of the unit difference in DENSITY between solid and non-solid phases not all models are applicable in all phases. The POROUS_DENSITY, MASS_FRACTION_POROUS_DENSITY, and MULTIPHASE_POROUS_DENSITY models are only valid in non-solid phases while the

MASS_FRACTION_DENSITY and DENSITY models are only valid in the solid phase. An error will be generated if you attempt to use the wrong model for a given phase.

The BULK_DENSITY has the same units as BULK_MASS_DENSITY. It is primarily used as a convenient way of specifying an initial condition that implicitly includes porosity. It can be used for the solid phase to initialize DENSITY using the MASS_AVERAGE model.

43.11. ELECTROSTATICS

What are the proper units for electrical contact conductance coefficient?

The units are equivalent to a heat transfer coefficient which would have the units of $1/(\text{resistance} \cdot \text{area})$, which is equivalent to $(\text{current}/(\text{volts} \cdot \text{area}))$.

Is Aria capable of calculating and outputting an electromotive force resulting from a body in an electric field?

Currently, there is no native postprocessor in the Aria code to compute resultant electromotive force.

43.12. GRID REFINEMENT

Can Aria do focused mesh refinement?

Yes, the manner in which the refinement occurs is controlled by the `marker_field`. Most of the adaptivity support is finite element based, single level of refinement and is driven by Encore. The necessary commands include:

```
Begin Sierra Aria
  Begin Uniform Marker uniform_mark
    Store in marker_field
  End   Uniform Marker uniform_mark

  Begin Procedure AriaProcedure
    Begin Solution Control Description
      Use System Main
    Begin System Main
      MarkAdapt AriaRegion using uniform_mark
      Begin Transient TransientBlock
        Advance AriaRegion
        Begin Parameters for Transient TransientBlock
          ...
```

When using uniform mesh refinement, does the new mesh get saved somewhere?

The new mesh is on the output from the uniform mesh refinement run. The disadvantage with that is the file size with multiple time planes in it. A more economical option is to use an additional Results Output block that saves zero time plane with the refined mesh. The syntax would be something like that in the example where the `At Step 0 Interval = 10e10` being ridiculously high should cause only one time plane to appear in the output file. One may also use the Sierra executable `stk_adapt_exe` for uniform mesh refinement - documentation for this application may be found on Compsim.

Problem encountered with using 8-node quad.

In order to support mesh refinement in the same way for all elements, Aria does not support the 8-node quad. It only supports 9-node element.

How does one coarsen a mesh?

The input modifications consist of two new lines:

```
MarkAdapt AriaRegion Using total\_mark When "recover_ind > 0.5"
MarkAdapt AriaRegion Using total\_mark2 When "recover_ind < 0.25"
```

This syntax turns on refinement when the error indicator exceeds the value 0.5 and switches to coarsening when the error is less than 0.25. When the error is between these values, the mesh is left unchanged.

43.13. POST PROCESSING

How can one output the non-wetting phase pressure?

Since the non-wetting phase pressure is needed in the wetting phase solution, it is available for output not as a solution variable but as a post-processed variable. In general, the pressure can be output provided one is able to specify its material phase. In this case the syntax would be:

```
postprocess non_wetting_phase_pressure on all_blocks
```

and the variable could be output to a results file as:

```
nodal variables = pp->non_wetting_phase_pressure as P_NW
```

How to output the min and max temp on specified blocks.

This can be accomplished using Encore:

```
$-----  
$   Specify Encore output to text file  
$-----  
Begin Postprocessor Output Control Encore_Out  
  Output Time  
  Write To File TempMinMax.txt  
  Floating Point Precision Is 3  
  Floating Point Format Is Fixed  
End   Postprocessor Output Control Encore_Out  
  
$-----  
$   Create Encore field function  
$-----  
Begin Field Function spos  
  Use Nodal Field Solution->Temperature  
End   Field Function spos  
  
$-----  
$   Determine maximum value of field function  
$-----  
Begin Min Max Postprocessor TMinMax_1  
  Use Function spos  
  Compute Min Max  
  Volumes block_1  
End   Min Max Postprocessor TMinMax_1  
  
Begin Procedure AriaProcedure  
  Begin Aria Region AriaRegion  
    Evaluate Postprocessor TMinMax_1
```

...

How to output mass inventory.

Include the following commands at the Aria Region scope:

```
Begin solution options
  post process mass
  post process volume
End
```

Model hangs when trying to output elem_temperature.

The proper syntax for postprocessing Temperature as an element variable is:

```
Postprocess TEMPERATURE on all_blocks using P0
```

This will interpolate the nodal temperature as a single element value, a zeroth-order polynomial (P0).

How to evaluate the time rate change in thermal energy.

The time rate change in thermal energy should be $\rho * C_p * (dT/dt) * \text{elem\_volume}$. The results block should contain:

```
nodal variables = time_derivative_at_time->TEMPERATURE as dtemp_dt
nodal variables = pp->density as rho
nodal variables = pp->specific_heat as cp
element variables = current_element_volume as e_vol
```

Then within the EnSight calculator you can define a variable and evaluate the following expression:

```
rho*cp *dtemp_dt*e_vol
```

How does Aria output the temperature of shell elements? Does it output the average or the outer or inner surface temperature?

For the standard shell there is only one nodal value of temperature. For the specialized implementations, linear and quadratic shells there are two nodal values of surface temperature, one associated with top and bottom of the shell.

How to save thermal conductivity as a nodal/element variable for output.

This can be accomplished using the postprocess command. Use this command in the Region scope:

```
Postprocess Thermal_Conductivity on block_1 block_2 block_n
```

and in the Results Output, use this command:

Nodal Variables = pp->Thermal_Conductivity as K

Can capillary pressure be added as postprocess variable?

Yes, post-processing of capillary pressure is supported, which can later be added to an output.

How to visualize the results continuously regardless of the time step selected by ARIA?

To visualize the results of an adaptively time-stepped simulation in an equal-time-step fashion, one can use a ParaView filter, “Temporal Interpolator”. This filter allows one to view a time-dependent data set where the data’s field data between adjacent time steps is linearly interpolated.

How to output an ASCII history file for data at a selected location over time.

One way of getting the history output that one specifies is to use Encore to do the interpolation. Graphics packages such as EnSight and ParaView can then be used to generate time history of an output parameter at selected locations.

TET10 interpolation for post-processing produces an error.

Since the TET10 element is second-order, one needs to use Q2 in the EQ specifications and for post-processing, since in both cases there is interpolation involved.

How to output element block volumes for steady-state simulation.

In order to output volume and mass in Aria one uses the following command block in the Aria Region:

```
Begin Solution Options
  post process volume
End   Solution Options
```

Log file has unwanted postprocessor history at every time step.

Remember to comment out the following:

```
begin postprocessor output control test
  output to log file
end   postprocessor output control test
```

Is there a way to apply a force on surface?

Nodal forces are computed from integrated surface tractions:

```
BC Flux for solid on surface_10 = Constant_Traction Y = 1800.0
```

Using Tecplot to plotting/visualize Aria results.

One can use exotec2 - the syntax is:

```
exotec2 exo_in tec_out
```


where `exo_in` is the exodus file and `tec_out` is the Tecplot translation.

Is there a way to extract the incident heat flux seen by a component within an enclosure definition?

Add these commands to the Begin Results Output block:

```
face variables = radiosity as J  
face variables = irradiance as G  
face variables = rad_flux as Q
```

Estimating the heat flux.

For the Aria application, there are a couple of ways to estimate the heat flux at selected locations. The first method is to use the `heat_flux` postprocessor on `all_blocks` while the second is to use the calculator function in EnSight.

44. DEVELOPER DOCUMENTATION

When working within the code base developers may wish to setup their environment to reference the development toolset.

44.1. SETTING THE ENVIRONMENT-DEVELOPERS AT SANDIA LABS

The environment for using Aria is the same as for individual Sierra applications and can be configured by module files. The modules ensure that the look and feel of running Sierra applications is the same across a multitude of compute platforms. To obtain the proper environment for code execution one simply runs:

```
$ module load sierra-devel
```

44.1.1. Setting up for the `csh` and `tcsh` Shells

Add SNTools to your path. In either your `/.cshrc` or `/.tcshrc` file add the line

```
set path=(/home/sntools/devel/linux/install/sntools/engine $path)
```

44.1.2. Setting up for the `bash` Shell

Add SNTools to your path. In either your `/.bashrc` or `/.profile` file add the line

```
export PATH=/home/sntools/devel/linux/sntools/engine:$PATH
```

44.2. AN INTRODUCTION TO ARIA'S EXPRESSION SYSTEM

The following is the conference paper from the Coupled Problems 2005 conference, See [46].

This section provides a brief overview of a core element of Aria's design called the Expression system. Understanding the Expression system is not essential for using Aria but it is useful in understanding how some of Aria's features behave. It is also the simplest point of entry for developing and extending Aria with new material properties and boundary conditions. In short, the Expression system is the abstraction of low- to mid-level numerical calculations so as to make the code highly general, reusable, extensible and scalable.

In order to provide a low entry barrier for user extensions we have chosen a design where the essential numerical entities of boundary conditions, material properties, etc., are all implemented the same way. Specifically, these are implemented as C++ classes called **Expressions**. In addition to supplying the functional evaluation of the numerical quantity, **Expression** implementers provide information regarding what the **Expression** provides, what other **Expressions** it may depend on, the tensorial order of the provided quantity, etc. A higher-level **Expression Manager** is then able to determine the minimal and sufficient set of **Expressions** required to perform the simulation and to ensure that they are evaluated in the proper order. In addition to providing a simple extension technique, this makes the core development of Aria very clean and abstracts nonessential details from many of the basic algorithms, while still employing the most efficient numerical kernels and data management techniques at the lowest levels.

To motivate our approach, we start with a simple example. In the FEM solution of the Navier-Stokes equations the following integral, among others, is computed.

$$\int_V \rho \mathbf{v} \cdot \nabla \mathbf{v} \phi^i dV = \sum_e \int_{V_e} \rho \mathbf{v} \cdot \nabla \mathbf{v} \phi^i |j| dV_e \quad (44.1)$$

Here ρ is the density, $\mathbf{v}$ is the fluid velocity and ϕ^i is weight function associated with local node i . V is the domain of integration in the physical space and V_e is that in the space of the element with $|j|$ being the Jacobian of transformation from V_e to V . Thus, the assembly kernel responsible for this calculation needs access to all of these quantities. We will show that the kernel, however, does not need to know the particulars of, say, the density model or of the weight function, especially regarding which other quantities they may depend on. Moreover, there are likely to be other assembly kernels that may also require these same quantities, such as the advection term of the energy transport equation,

$$\int_V \rho C_p \mathbf{v} \cdot \nabla T \phi^i dV = \sum_e \int_{V_e} \rho C_p \mathbf{v} \cdot \nabla T \phi^i |j| dV_e \quad (44.2)$$

where C_p is the specific heat and T is the temperature. Efficient evaluation of (44.2) should make use of ρ , $|j|$, $\mathbf{v}$ and any other quantities that might have previously been computed in the assembly of (44.1). Keeping track of which quantities are needed and which quantities have already been evaluated in a previous part of the assembly, regardless of the equation system that is being solved, is the purpose of Aria's **Expression Manager**.




Figure 44.2-1.. Schematic UML class diagram for the Expression subsystem.

In Aria, all of the quantities presented above, ρ , ∇v , $|j|$, ϕ^i , etc., are implemented as C++ classes derived from the base class **Expression**. Each **Expression** has these basic responsibilities:

- Identification. Each **Expression** identifies itself with a generic description, such as **density** and, when applicable, a specific model description, such as **cubic_in_temperature**.
- Prerequisites. Each **Expression** (and **Expression** user) provides a list of other **Expressions** (using the generic identifiers) that are required for its own calculations. To continue the example, the **Expression** which implements the **cubic_in_temperature** model would have **temperature** as a prerequisite. Arbitrarily complex terms may be built of successively simpler components which ultimately result in a dependency tree with the simplest ingredients being the leaves of the graph.
- Tensor Properties. Each **Expression** states its tensor order (scalar, vector, second order tensor, etc.) and dimension. With this information, **Expression** users can dynamically determine how to index the values provided by the expression. For example, some thermal conductivities may be scalars while others may be second order tensors as is the case with anisotropic materials.
- Evaluation. Each **Expression** implements a virtual function for computing its values. Depending upon the nonlinear solution strategy, additional methods may be required for computing, for example, Newton sensitivities.

When an **Expression** is created, it makes itself known to an **Expression Manager**. The **Expression Manager** is responsible for establishing the minimal but sufficient list of **Expressions** required for the calculation. This is done utilizing the lists of prerequisites provided by **Expression** users and other **Expressions**. The relationships among **Expressions**, **Expression** users, and the **Expression Manager** is illustrated schematically in figure 44.2-1 with the use of UML. This figure illustrates two salient features of our Expression subsystem: **Expressions** are themselves **Expression** users and **Expression** users, such as assembly kernels, are the original source for all prerequisites.

The richness of the information provided in these lists of prerequisites quickly becomes apparent. For example, the **Expression Manager** is able to further utilize the prerequisite information to order the list of **Expressions** for evaluation. This is done so that when an **Expression** is evaluated, all of its prerequisite **Expressions** have already been evaluated. Regardless of how complicated the multiphysics problem happens to be, there are no duplicate evaluations and no overhead costs that would be incurred with lazy-evaluation. Another powerful use for the prerequisite information is in dynamically determining and computing sensitivities for Newton's method. Since primitive variables, or degrees of freedom, are also represented as **Expressions**, the prerequisites for any given **Expression** are recursively checked to see if any of them represents a primitive variable. In combination with runtime-queried tensor properties (see above), an **Expression** developer can implement and evaluate the **Expression**'s sensitivities without ever having direct knowledge of the degrees of freedom in the system. Lastly, Aria utilizes this information for additional purposes such as sparse matrix allocation and automated memory management.

44.3. NONLINEAR COUPLING STRATEGIES IN ARIA

One of the difficulties with writing broadly applicable computational mechanics software is that developers can't take advantage of specific knowledge of the application domain in order to optimize the algorithm. Thus, in providing generality one sometimes sacrifices efficiency. One place this is evident in multiphysics modeling is in the choice of coupling strategies. While it is well understood that a fully coupled system solved with Newton's method utilizing analytic sensitivities is formally the most robust and correct approach to solving multiphysics applications it is also computationally expensive and complex to implement. Furthermore, while Newton's method has the fastest rate of asymptotic convergence it's domain of convergence is often empirically observed to be smaller than other methods. Lastly, in some applications, certain subsets of the physics may be only weakly coupled so that a loosely coupled approach may be more computationally efficient. To address these concerns while remaining general and flexible Aria offers a number of options for nonlinear solution strategies and physics coupling.

In defining a problem in Aria, users configure one or more **Regions**. Each **Region** consists of one or more PDEs to be solved on some or all of the input mesh. All of the PDEs in each **Region** are solved in a tightly coupled (i.e., single matrix) manner using one of several nonlinear solution strategies available. Users may then define loose couplings between two or more **Regions**. For example, some or all of a solution from one **Region** may be transferred to another **Region** where it is treated as a constant, external field. The aggregate nonlinear problem including the contributions from all of the **Regions** may be iterated to convergence. The particulars of which physics are solved in each **Region** and the nonlinear solution strategy used within and between **Regions** is completely specified through the input file. Furthermore, an Aria user may pick a simple, minimal algorithm without needing to fit it into an overly-generalized worst-case scenario that represents the union of all possible algorithms.

Dynamically-specified loose coupling has many potential advantages that users may leverage. First, the resulting linear system is considerably smaller and contains far fewer off-diagonal contributions which can significantly increase the performance of linear solvers. Also, a resulting linear system may have a more attractive form, such as symmetric positive-definite, that permits the use of tailored iterative

solutions techniques. Other extensions to loose coupling include subcycling of transient simulations where each **Region** may advance in time with its own time step size and in-core coupling to other Sierra applications.

44.4. DEVELOPER RECIPES

44.4.1. Adding a New Flux Boundary Condition

1. Add a new name for your model
 - a) Add a new `Identifier` entry to `Aria_Model_Names.h`
 - b) Add the string in `Aria_Model_Names.C`
2. Add your new `Expression` class.
 - a) Copy-paste-rename a similar `Expression` definition. See, e.g., `Aria_Material_Models.h`.
 - b) Copy-paste-rename a similar `Expression` implementation. See, e.g., `Aria_Material_Models.C`.
3. Add an entry to the `Expression_Factory::create_model_expression()`.
 - a) Copy-paste-rename a similar entry in `Aria_Expression_Factory.C`.

44.4.2. Adding a New Material Model

1. Add a new name for your model
 - a) Add a new `Identifier` entry to `Aria_Model_Names.h`
 - b) Add the string in `Aria_Model_Names.C`
2. Add your new `Expression` class.
 - a) Copy-paste-rename a similar `Expression` definition. See, e.g., `Aria_Material_Models.h`.
 - b) Copy-paste-rename a similar `Expression` implementation. See, e.g., `Aria_Material_Models.C`.
3. Add an entry to the `Expression_Factory::create_model_expression()`.
 - a) Copy-paste-rename a similar entry in `Aria_Expression_Factory.C`.

44.5. EXPRESSION REFERENCE AND API

This section provides a high-level view of how Expressions are run by Aria, from creation to computation. This section also provides a brief description of the Expression methods that a user either must or can optionally supply.

44.5.1. Execution Sequence

1. Initialization Phase (Input Parsing Time)

- a) `Expression::Expression()` (See [44.5.2](#)): Constructor. Called at creation time. Defines identity, dependents and parameters. Required.
- b) `Expression_Manager::preprocess_expressions()` : Called after all expressions have been created and all dependencies have been registered/requested. Unused expressions are destroyed. Dependency based ordering established.
- c) `Expression::set_nonlinear_method()` : Sets the nonlinear method that will be used.
- d) `Expression::create_dynamic_storage()` : Initializes storage for values and Newton sensitivities but does not actually allocate memory.
- e) `Expression::postregistration_setup()` (See [44.5.3](#)) : Called once, after the `Expression_Manager` has determined that the Expression will indeed be used but before simulation begins. Called in dependency order. Can get references to dependent's storage (values, Newton sensitivities, etc.).
- f) `Kernel::postregistration_setup()` : Assembly kernels can interrogate the Expressions available to them and get references to values and Newton sensitivities.

2. Simulation Phase

- a) `Expression::prepare_to_recompute()` (See [44.5.4](#)): Called once for each workset, immediately prior to `compute_values()`. Can be used to resize or reinitialize storage (usually done by base class), inquire about simulation time, etc.
- b) `Expression::compute_values()` (See [44.5.5](#)) : Computes the values of the Expression. Required to compile.
- c) `Expression::compute_sensitivities()` (See [44.5.6](#)) : Computes the Newton sensitivities of the Expression. Required to compile.

3. Shutdown Phase

- a) `Expression::~Expression()` (See [44.5.7](#)) : Destructor. Can be used to free memory allocations (note: `Real_MDArray` storage is automatically de-allocated). Required but normally empty.

44.5.2. Constructor

44.5.3. `postregistration_setup()`

44.5.4. `prepare_to_recompute()`

44.5.5. `compute_values()`

44.5.6. `compute_sensitivities()`

44.5.7. Destructor

44.6. NEWTON SENSITIVITY CHECKING FOR EXPRESSIONS

When you run Aria you can ask it to look for sensitivity errors in every Expression if you're using Newton's method. If activated, Aria will compare the analytic sensitivities provided by each expression with numerically computed values. This feature is enabled by adding the command line option `-arialog sens_check` to Aria. If you're using the `sierra` tool to run Aria, then add `-O` `"-arialog sens_check"` (including quotes) to the `sierra` command line. The same holds if you're running the Arpeggio application.

You can also run the entire test suite with Jacobian checking enabled by adding `-u aria_args =` `"-arialog sens_check"` to the `runtest` command line.

44.7. PROFILING

It's a good idea to profile the code before spending time trying to optimizing and performance tuning. Fortunately, profiling is pretty easy to do. On Linux, one approach is to use the `gprof` tool. To profile code with `gprof`, you'll need to compile with the `-pg` option. The easiest way to do this is to set environment variables `USER_CFLAGS` and `USER_LDFLAGS` to `-pg`. In the `bash/ksh/zsh` shell, use, e.g., `export USER_CFLAGS=-pg` and in `tcsh/csh` use `setenv USER_CFLAGS -pg`. You'll only get detailed profiling information for code compiled and linked with this flag so you may want to recompile some of the framework too. You can profile debug or optimized code.

With the instrumented executable, run Aria as you normally would. This will generate a file called `gmon.out`. Lastly, run `gprof` to analyze the data: `gprof executable > gprof.txt` where `executable` is the executable (probably including an absolute or relative path) used in the run. The output stored in `gprof.txt` will give you some real data telling where the real bottle necks are.

44.8. PURIFY: MEMORY ANALYSIS AND DEBUGGING

1. Build Aria on Linux. This works for both optimized and debug modes but use debug if you want to see line numbers in Purify.
2. Copy the complete link line into a file.
3. Add `-show` option to `mpiCC`.
4. Remove the `-static` option from the link line arguments.
5. Adjust any path to `Apps_aria.o` if necessary.
6. Put `which mpiCC` on the previous line to verify you're getting `mpiCC` from `/usr/local/mpi/sierra/mpich/1.2.5.2/gcc-3.2.2/bin/`.
7. You might also verify `gcc` is version 3.2.2 (`gcc -v`).
8. Source the script.
9. Copy the link line (start with `g++ ...`) and paste it into a file.
10. Preface `g++` with `purify`, e.g., `purify -always-use-cache-dir -cache-dir='pwd' /g++ ...`
11. Source this script and it will instrument your executable. It takes a while...
12. Optionally verify that the executable is purified by running `ldd aria.x`
13. Copy executable to `aria/bin` directory, removing the `.tmp` extension.
14. Run it standalone (via `sierra`, `runtest` or by hand) or with TotalView.

44.9. BUILDING AGAINST OTHER PROJECTS

Sometimes it can be very useful to build against changes that have been made in a different project. For example, if you are waiting for a project's changes to be checked in but would like to start developing against those changes in another project. To do this with the SNTTools build tool you can use the `-a` option to build. The argument to this option is the XML file for each *product* you want to include in your build. So, if you want to use the version of Krino found in a project located in `/path/to/project/` then you would add `-a /path/to/project/krino/krino_sn.xml` to your normal build command line.

44.10. INTERFACING WITH MATLAB

44.10.1. Reading Aria Matrices Into MATLAB

This is sort of an “old” way of getting matrices into MATLAB but it still works just fine.

From Matt Hopkins:

You can read a `.mtx` matrix into MATLAB via the following. Let `my_matrix.mtx` be the matrix sitting in the debug output path you’re interested in.

```
>> A_ascii = load('my_matrix.mtx');  
>> A = spconvert(A_ascii(2:end,:));
```

And now `A` is in MATLAB’s sparse matrix format. It even ignores the zeros in the `.mtx` file (does not allocate space for them).

From there you can do some pretty nifty things. `spy(A)` does sort of what `matvis` does (graphical view of matrix nonzeros). `condest(A)` estimates the 1-norm condition number of `A` (might take a while for large `A`). Etc.

44.10.2. Interfacing Aria from within MATLAB

Russell Hooper is developing a pretty sophisticated MATLAB interface that allows you to control Aria and probe nonlinear and linear solver data structures directly from within MATLAB. This is rapidly evolving so no details are given here... except for how to build and run Aria/MATLAB.

This recipe is taken from an email exchange between Matt Hopkins and Russell Hooper in early April 2006. It most likely only works on Linux.

```
% setenv LD_LIBRARY_PATH /usr/local/matlab/7.2/bin/glnx86:${LD_LIBRARY_PATH}  
  
% build aria -j8 -a /home/rhoope/Trilinos_6.0 \  
  CXXFLAGS="-I/usr/local/matlab/7.2/extern/include/" \  
  -a /home/rhoope/projects/noxMatlabStable/equationsolver \  
  LDFLAGS="-L/usr/local/matlab/7.2/bin/glnx86 -leng"
```

If you want to build a debug version, add “-g” to both the `CXXFLAGS` and `LDFLAGS`.

To execute aria, first invoke `sierra aria -i input.i -script-only`. Then copy the file `sierra.sh` into another, ie `opt.sh`. Finally, remove the “-o logfilename” argument from `opt.sh` so that your run is truly interactive.

44.11. ERROR HANDLING

Traditional techniques for error handling of numerous and varied. Sometimes functions will return special values indicating success or failure of the call. Sometimes global variables or flags are set to indicate an error has occurred. Sometimes `abort()` is simply called (bad!).

C++ and the SIERRA Framework offer facilities to support error handling. The two primary error handling techniques are *exception handling* and *assertions*. Both of these can be combined to implement *Design by Contract* though this is not formally done in Aria.

Whether one should use an exception or an assertion is sometimes a subtle question. In general, assertions should be used for cases where the error is not likely to occur due merely to user input. However, assertions can also be useful for computationally expensive tests which would adversely affect production calculations.

44.11.1. Exception Handling

C++ offers *exception handling* and the SIERRA Framework utility library provides a parallel-safe layer for exception handling. Because exceptions in C++ are ordinary classes, applications may choose to specialize exceptions for handling and detecting specific failure modes. When SIERRA exceptions are used in conjunction with the SIERRA diagnostic tracing facility, it is possible to get a stack trace (or sometimes a partial one) that illustrates the code path where the exception was thrown.

In most cases, Aria developers do not need to worry about catching exceptions (they're normally fatal errors). The top-level SIERRA Framework routine `run_sierra()` handles the responsibility of catching any uncaught exceptions, converting them into parallel exceptions if necessary, and propagating the exception to any other processors.

If the reader is not already familiar with exception handling in C++, a good place to start is with [47]. In its simplest form, SIERRA exceptions can be used as follows.

```
#include <util/Exception.h>
// ...
if(something_bad_happened)
{
    sierra::Exception x("Nice descriptive error message.");
    throw x;
}
```

The `sierra::Exception` class inherits from `std::string` and so it supports all of `std::string`'s operations, most notably the `+` (concatenation) operator.

```
#include <util/Exception.h>
// ...
if(something_bad_happened)
```

```

{
    sierra::Exception x("Nice descriptive error message.");
    x += "  More info here.";
    throw x;
}

```

Additionally, the `sierra::Exception` class supports the put-to operator, `<<`, for stream-like handling.

```

#include <util/Exception.h>
// ...
if(something_bad_happened)
{
    sierra::Exception x;
    x << "Nice descriptive error message."
      << "  More info here.";
    throw x;
}

```

However, in order to keep the `sierra::Exception` class light weight, it does not inherit from `std::ostringstream`. Instead, operator`<<` is only defined for the most common objects, such as strings, integers, floats/doubles, etc. The consequence of this is that if you define a class with operator`<<` for ostream, that operator will not work with `sierra::Exception` objects. In these cases, it is sometimes useful to use a `std::ostringstream` to construct the error message and then pass the resulting `std::string` to the exception.

```

#include <util/Exception.h>
#include <sstream>
// ...
if(something_bad_happened)
{
    std::ostringstream os;
    os << "Nice descriptive error message."
      << "  Object foo: ";
    << some_object
      << " is unusable";
    sierra::Exception x;
    x << os.str();
    throw x;
}

```

Finally, the construction and throwing of the exception can occur on the same line for brevity. In this case, all we need is a temporary object which is unnamed.

```

#include <util/Exception.h>
// ...
if(something_bad_happened)
{
    throw sierra::Exception() << "Nice descriptive error message."
                                << " Integer out of bounds: j = "
                                << j;
}

```

44.11.2. Assertions

Assertions are a common way to ensure that certain conditions that are assumed by the code to be true are indeed true. For example, a function or piece of code may require that a pointer be non-NULL, an integer be greater than zero, etc. Using the C++ `assert()` macro is a good way to test such conditions that *should* hold under normal circumstances. By using `assert()`, the enclosed test will only be performed if the code is compiled in debug mode; in optimized mode, the macros expand to nothing. Thus, developers can use asserts extensively to test conditions assumed by their code without affecting production-mode performance. Assertions also provide an excellent way to document *and enforce* the assumptions that the developer made in writing the code.

The SIERRA Framework provides an alternate implementation of the `assert()` macro that utilizes the parallel-safe exception handling described above. The macro, `ThrowAssert()`, is defined in the same header file as the exception class.

```

#include <util/Exception.h>
// ...
void
some_function(const MyClass * myclass_ptr)
{
    ThrowAssert(0 != myclass_ptr);
    // It should be OK to use the pointer.
    // ...
}

```

Because assertions expand to empty code in optimized mode, developers must be careful to never put variable assignments or other state-altering code inside an assert.

```

#include <util/Exception.h>
// ...
// This is a bug:
ThrowAssert(j = i + 2 > 4);

```

A common trick to getting more useful messages from a failed assertion is to add a help string like this:

```

#include <util/Exception.h>
// ...
void
some_function(const Int & num)
{
    ThrowAssert(num > 10 &&
                "This function only works properly when num is larger than 10");
    // It should be OK to use the pointer.
    // ...
}

```

Lastly, another macro, `ThrowRequire()` is available. This macro is identical to the `ThrowAssert()` macro except this it is always enabled, even in optimized builds. This macro is currently not used in *Aria* but use it if you want. The concise and readable form of these macros can help keep code short while still being readable and expressive.

44.12. OUTPUTTING USER INFORMATION (LOGGING)

The SIERRA Framework utility library supplies a flexible logging facility. The problem with normal `printf` and `cout` output functions is that they get really annoying in parallel. Further, these messages simply roll off the top of the user's screen unless they are careful to redirect the standard output and error streams to a file. Lastly, it's difficult, and may involve recompiling the application, to tailor these messages depending on the kind of information a user is interested in.

44.12.1. The DiagWriter Logging Facility

SIERRA's logging facility, `DiagWriter`, is designed to address these three issues. The `DiagWriter` class, in the simplest sense, is a `std::ostream` class that supports the put-to (`<<`) operator for writing messages.

```

#include <Aria_DiagWriter.h>
//...
namespace Aria
{
    arialog << "This is a message the user will always see." << std::endl;
}

```

Note the use of `std::endl` instead of `std::endl` (the standard and portable newline). This is an unfortunate but important point; using `std::endl` will result in ugly compiler errors.

The most interesting feature of the `DiagWriter` class is that the output can be tagged with a bit field called a *message mask*. These masks are defined in `Aria_DiagWriter_fwd.h` as enums with meaningful names, e.g., `LOG_EXPRESSION` and `LOG_NONLINEAR`. To mask your output message, you can use the `m()` method on the `DiagWriter` object.

```

#include <Aria_DiagWriter.h>
//...
namespace Aria
{
    arialog.m(LOG_EXPRESSION)
        << "This message is supposedly related to Expressions."
        << std::endl;
    arialog.m(LOG_EXPRESSION | LOG_NONLINEAR)
        << "This message is supposedly related to Expressions "
        << "and/or the nonlinear solver"
        << std::endl;
}

```

Messages that contain a mask are only written if that is enabled via the *print mask* and messages that don't have a specified mask are always written. The user can define a print mask using the “-arialog *string*” command line argument where the provided string maps to one (or more) of the bit masks. The file `Aria_DiagWriter.C` contains the mapping between the string names and the bit mask values. For example, “expression” is assigned to `LOG_EXPRESSION`. When the user supplies the command line argument “-arialog expression” then the messages written are those masked with `LOG_EXPRESSION` and those with no bit masks.

The `DiagWriter` class contains many more features that are beyond the scope of this section. Explore the header files and the code for more examples.

44.12.2. The Tracing Facility

Tracing is a common and extremely useful debugging utility. With tracing enabled, the code prints the name of each function as it enters and exits the function. C++ doesn't provide any standard way to accomplish this so the `Trace` class is provided by the SIERRA Framework utility library.

The `Trace` class works by creating an instance (object) as the first line of a. The object constructor takes as an argument a string (`char *`) containing the name of the function. When tracing is enabled the constructor prints this name. When the application leaves this function, the local `Trace` object is automatically destroyed as it goes out of scope. When tracing is enabled, the automatically-called destructor re-prints the function name. The output of nested functions is nested so the output provides a hierarchical view of the flow of control. The most basic usage looks like this:

```

#include <Aria_DiagWriter.h>
//...
namespace Aria
{
    void my_func(const Int & i)
    {
        Trace diag_trace("Aria::my_func(const Int & i)");
        //... normal code follows
    }
}

```

```

    }
}

```

The Trace class utilizes the DiagWriter class for writing and for determining if tracing is enabled. So, tracing may be enabled using “-arialog trace” on the command line and Aria::Trace objects mask all output with LOG_TRACE.

Though it’s not discussed here, tracing can be turned on and off during the normal execution so that tracing information can be gathered only when it’s desired. Read through the header files and the code for examples of doing that. One example of where this is used is in the exception handling. When an exception is thrown, the tracing bit mask is automatically turned on. As the function stack unwinds during the throw, any functions instrumented with Trace objects will get destructed and hence they will print their owning function name. The result is a stack trace, or traceback, which can be extremely useful for debugging.

Adding all of the Trace objects to a code can be a daunting task, especially if you’re really anal and want the function arguments and namespace to be a part of the function’s printed name (which can be important with polymorphic functions). Aria uses the traceString tool (<http://tracestring.sourceforge.net/>) to automatically instrument the code with the Trace objects. The traceString tool will enclose the Trace objects in a pair of special strings so that it can safely update or remove the inserted code later on. Typically, it looks like this:

```

#include <Aria_DiagWriter.h>
//...
namespace Aria
{
    void my_func(const Int & i)
    {
        /* %TRACE[ON]% */ Trace diag_trace("Aria::my_func(const Int & i)"); /* %TRACE% */
        //... normal code follows
    }
}

```

To learn more about traceString, talk to Pat...

44.13. CATALOGUE OF ASSEMBLY KERNEL EXPRESSIONS

Aria supplies several generic expressions that can be used for top-level assembly kernels for equation terms. When adding new equations or terms to existing equations, one of the follow generic expressions can often be used.

44.13.1. Scalar_Source_Kernel_Expression

This Expression assembles a source term for a scalar transport equation. Note that the MASS and SRC terms can both be cast in this form. The general form is:

$$-m \sum_{g=1}^{N_g} \left(\prod_{r=1}^{N_c} c_r(\mathbf{x}_g) \right) \left(\sum_{s=1}^{N_s} f_s(\mathbf{x}_g) \right) \phi^i(\mathbf{x}_g) |j| w_g \quad (44.3)$$

Here, m is a multiplier that defaults to 1, N_g is the number of Gauss points in the quadrature rule, N_c is the number of coefficients and N_s is the number of sources provided. As an example, consider the term,

$$\int_{\Omega_e} \rho C_p \frac{\partial T}{\partial t} |j| \phi^i d\Omega_e = \sum_{g=1}^{N_g} \rho C_p \frac{\partial T}{\partial t} |j| \phi^i w_g \quad (44.4)$$

In this example, $N_r = 2$ with $c_1 = \rho$ and $c_2 = C_p$; $N_s = 1$ with $f_1 = \frac{\partial T}{\partial t}$; and $m = -1$. As a side note, in the code the quantities $|j|$ and w_g are treated as additional coefficients for convenience.

44.13.2. Scalar_Advection_Kernel_Expression

This Expression assembles an advection term for a scalar transport equation. The general form is:

$$m \sum_{g=1}^{N_g} \left(\prod_{r=1}^{N_c} c_r(\mathbf{x}_g) \right) \mathbf{v}_a \cdot \nabla S(\mathbf{x}_g) \phi^i(\mathbf{x}_g) |j| w_g \quad (44.5)$$

Here, m is a multiplier that defaults to 1, N_g is the number of Gauss points in the quadrature rule, N_c is the number of coefficients, $\mathbf{v}_a$ is a configurable advection velocity and S is a scalar field. As an example, consider the term,

$$\int_{\Omega_e} \rho C_p \mathbf{v} \cdot \nabla T |j| \phi^i d\Omega_e = \sum_{g=1}^{N_g} \rho C_p \mathbf{v} \cdot \nabla T |j| \phi^i w_g \quad (44.6)$$

In this example, $N_r = 2$ with $c_1 = \rho$ and $c_2 = C_p$; $S = T$; $\mathbf{v}_a = \mathbf{v}$; and $m = 1$. As a side note, in the code the quantities $|j|$ and w_g are treated as additional coefficients for convenience.

44.13.3. Scalar_Diffusion_Kernel_Expression

This Expression assembles a diffusion term for a scalar transport equation. The general form is:

$$m \sum_{g=1}^{N_g} \left(\prod_{r=1}^{N_c} c_r(\mathbf{x}_g) \right) \left(\sum_{k=1}^{N_F} \mathbf{F}_k(\mathbf{x}_g) \right) \cdot \nabla \phi^i(\mathbf{x}_g) |j| w_g \quad (44.7)$$

Here, m is a multiplier that defaults to 1, N_g is the number of Gauss points in the quadrature rule, N_c is the number of coefficients and N_F is the number of flux models provided. As an example, consider the term,

$$\int_{\Omega_e} \mathbf{q} \nabla \phi^i |j| \, d\Omega_e = \sum_{g=1}^{N_g} \mathbf{q} \cdot \nabla \phi^i |j| w_g \quad (44.8)$$

In this example, $N_r = 0$; $N_F = 1$ with $F_1 = \mathbf{q}$ where $\mathbf{q}$ is the Fourier heat flux, $\mathbf{q} = -\kappa \nabla T$; and $m = 1$. As a side note, in the code the quantities $|j|$ and w_g are treated as additional coefficients for convenience.

44.13.4. Vector_Source_Kernel_Expression

This Expression assembles a source term for a vector transport equation. Note that the MASS and SRC terms can both be cast in this form. The general form is:

$$-m \sum_{g=1}^{N_g} \left(\prod_{r=1}^{N_c} c_r(\mathbf{x}_g) \right) \left(\sum_{s=1}^{N_s} \mathbf{f}_s(\mathbf{x}_g) \right) \phi^i(\mathbf{x}_g) |j| w_g \quad (44.9)$$

Here, m is a multiplier that defaults to 1, N_g is the number of Gauss points in the quadrature rule, N_c is the number of coefficients and N_k is the number of sources provided. In this case, the sources $\mathbf{f}_s$ are vector quantities. As an example, consider the term,

$$\int_{\Omega_e} \rho \frac{\partial \mathbf{v}}{\partial t} |j| \phi^i \, d\Omega_e = \sum_{g=1}^{N_g} \rho \frac{\partial \mathbf{v}}{\partial t} |j| \phi^i w_g \quad (44.10)$$

In this example, $N_1 = 2$ with $c_1 = \rho$, $N_s = 1$ with $\mathbf{f}_1 = \frac{\partial \mathbf{v}}{\partial t}$; and $m = -1$. As a side note, in the code the quantities $|j|$ and w_g are treated as additional coefficients for convenience.

44.13.5. Vector_Advection_Kernel_Expression

This Expression assembles an advection term for a vector transport equation. The general form is:

$$m \sum_{g=1}^{N_g} \left(\prod_{r=1}^{N_c} c_r(\mathbf{x}_g) \right) \mathbf{v}_a \cdot \nabla \mathbf{V}(\mathbf{x}_g) \phi^i(\mathbf{x}_g) |j| w_g \quad (44.11)$$

Here, m is a multiplier that defaults to 1, N_g is the number of Gauss points in the quadrature rule, N_c is the number of coefficients, $\mathbf{v}_a$ is a configurable advection velocity and $\mathbf{V}$ is a vector field. As an example, consider the term,

$$\int_{\Omega_e} \rho \mathbf{v} \cdot \nabla \mathbf{v} |j| \phi^i \, d\Omega_e = \sum_{g=1}^{N_g} \rho \mathbf{v} \cdot \nabla \mathbf{v} |j| \phi^i w_g \quad (44.12)$$

In this example, $N_r = 1$ with $c_1 = \rho$; $\mathbf{V} = \mathbf{v}$; $\mathbf{v}_a = \mathbf{v}$; and $m = 1$. As a side note, in the code the quantities $|j|$ and w_g are treated as additional coefficients for convenience.

44.13.6. Vector_Diffusion_Kernel_Expression

This Expression assembles a diffusion term for a vector transport equation. The general form is:

$$m \sum_{g=1}^{N_g} \left(\prod_{r=1}^{N_c} c_r(\mathbf{x}_g) \right) \left(\sum_{k=1}^{N_F} \mathbf{F}_k^t(\mathbf{x}_g) \right) : \nabla (e_j \phi^i(\mathbf{x}_g)) |j| w_g \quad (44.13)$$

Here, m is a multiplier that defaults to 1, N_g is the number of Gauss points in the quadrature rule, N_c is the number of coefficients and N_F is the number of flux models provided. As an example, consider the term,

$$\int_{\Omega_e} \mathbf{T}^t : \nabla (e_j \phi^i) |j| d\Omega_e = \sum_{g=1}^{N_g} \mathbf{T}^t : \nabla (e_j \phi^i) |j| w_g \quad (44.14)$$

In this example, $N_r = 0$; $N_F = 1$ with $F_1 = \mathbf{T}$ where $\mathbf{T}$ is the Newtonian stress, $\mathbf{T} = \mu (\nabla \mathbf{v} + \nabla \mathbf{v}^t) - p \mathbf{I}$; and $m = 1$. As a side note, in the code the quantities $|j|$ and w_g are treated as additional coefficients for convenience.

44.14. DEFINING AND SOLVING ODES IN ARIA PLUGINS

This section covers how to define and solve an ODE or system of ODEs in an Aria plugin. The equations to solve must be of the form,

$$\frac{d\vec{y}}{dt} = f(t, \vec{y}) \quad (44.15)$$

The ODE to solve must be declared as a subclass of the Aria ODE class, and must define at least the derivatives function, and it may also be useful to define the initialization and Jacobian functions:

```
derivatives(double t, const FArray<double,1>& y, FArray<double,1>& dydt)
initialize(double t, const FArray<double,1>& y)
jacobian(double t, const FArray<double,1>& y, FArray<double,2>& dfdy)
```

The initialize() function is called by the ODE solver at construction to set the initial values of $\vec{y}$, and the derivatives() function is called within the solver during solution. The default Jacobian function implements a numerical Jacobian, but it can be overwritten to allow an analytical one.

The currently available solvers are described in the Chemistry Solver Reference chapter. All solvers use adaptive sub-stepping to meet the requested tolerances. The solver stores the problem state (t , $\vec{y}$, and $\frac{d\vec{y}}{dt}$) throughout solution as well as any intermediate states required by the particular solution algorithm. Any of the ODE solvers can be used to solve an ODE that inherits from the Aria ODE class, although for stiff ODEs an appropriate solver should be selected.

44.15. DEFINING AND USING GLOBAL VARIABLES

Occasionally it is useful to define a global variable that is available to the user for output to the log or results files, or to be used in user subroutines. These variables may be created using the `Region::new_global_variable` or `Region::new_global_variable2` functions. A variety of value types (e.g. Real, Int, etc.) are supported, as are a number of reduction operations (`MPI::Sum`, `MPI::Max`, etc.). `Region::new_global_variable()` returns a `GlobalVariable<Op, T>` and is the preferred version. `GlobalVariable<Op, T>` stores a single value that is globally consistent once it is synchronized using the `Region::synchronize_global_variables()` call. `Region::new_global_variable2()` returns a `GlobalVariable2<Op, T>` which stores 2 values, one local and one global. There are currently some user plugins that access both the local and global values separately so the type is still available for compatibility, but we would prefer to not have both types in the future.

44.16. ERRORS AND WARNINGS HOW-TO

Editorial note: This How-To is mostly taken from Dave Bauer's collection of How-Tos. Minor changes include formatting, editorial corrections and possibly additional information related to Aria.

44.16.1. Reporting

There are several types of warnings and exceptions that occur in sierra. Warnings are informational messages to the user which may effect the results, but which will allow the execution to complete. Dooms are error conditions which will allow the program to continue to a point, but will not allow it to complete. Often these are within the parser when you want the parser to continue to plod on ahead but not actually execute the code. Exceptions occur when all bets are off.

The Warning and Doom classes send their assembled message to the sierra reporter at destruction. The Exception classes send their assembled message to the sierra reporter within the catch block.

The warning and exception classes will all accept the put-to operator (`<<`) with plain old data. Since it is easy to put useful information to the user/developer in the message, please do so. For warnings directed to developers, it is recommended that the message be terminated with a

```
<< std::endl << WarnTrace;
```

For exceptions, always use

```
<< std::endl << StackTrace;
```

`WarnTrace` and `StackTrace` generate a "pretty" source file and line number message. If the message is purely informational for the user the `std::endl` and `WarnTrace` for the message should be omitted.

These are the include files:

```
#include <util/Exception.h>// throw sierra
#exception declarations
#include <util/ExceptionReport.h>// sierra reporter and
#RuntimeWarning declarations
```

The `RuntimeUserError` class should be thrown in place of `RuntimeError` when it was the user's fault that the program died. This generally means that the input deck has an error that a `RuntimeDoomed`, the preferred method since it allows the parser, etc to continue, cannot handle since a seg fault or the like is imminent. It kills the output of the traceback since the user really does care and will only cause confusion.

Also, don't put the `WarnTrace` or `StackTrace` to the `RuntimeUserError`.

The following code snippets serve as examples for the warning, doomed and exception conditions.

```
class_tag *
Parser::prsr_handler_x(
const Prsr_CommandValues & value)
{

    if (runtime_warning_condition)
sierra::RuntimeWarning() << "My useful message about " <<
some_data << std::endl << WarnTrace;

    if (runtime_exception_condition)
        throw sierra::RuntimeError() << "My useful message about " <<
        some_data << std::endl << StackTrace;

    if (runtime_exception_condition)
        throw sierra::RuntimeUserError() << "My useful message about "
        << some_data;

    if (parse_handler_warning_condition)
        sierra::RunWarning() << "My useful message about " <<
        some_data << std::endl << WarnTrace;

    if (parse_handler_doomed_condition)
        sierra::RuntimeDoomed() << "My useful message about " <<
        some_data << std::endl << WarnTrace;

}
```

44.16.2. Throttling a Specific Warning or Doom

If a particular warnings is going to be repeated countless times, you can request a unique message id from sierra using

```
int message_id = sierra::get_next_message_id();
int message_id = sierra::get_next_message_id(int max_messages_displayed);
```

and pass `message_id` to the message constructor. This value is often stored within the function that generates the message using a static variable. This technique may not be suitable for all situations. Only a limited number of messages of each id are sent to the sierra reporter.

```
if (runtime_warning_condition) {
    static message_id = get_next_message_id();
    sierra::RuntimeWarning(message_id) << "My useful message about
    " << some_data << std::endl << WarnTrace;
}

if (parse_handler_warning_condition) {
    static message_id = get_next_message_id();
    sierra::Prsr::ParseWarning(value, message_id) << "My useful
    message about " << some_data << std::endl << WarnTrace;
}

if (parse_handler_doomed_condition) {
    static message_id = get_next_message_id();
    sierra::Prsr::ParseDoomed(value, message_id) << "My useful
    message about " << some_data << std::endl << WarnTrace;
}

if (parse_handler_exception_condition) {
    static message_id = get_next_message_id();
    sierra::Prsr::ParseError(value, message_id) << "My useful
    message about " << some_data << std::endl << WarnTrace;
}
```

44.16.3. Setting Output Throttles

There are several functions which can throttle the amount of data which is displayed.

To set the maximum number of warnings or dooms before an exception is thrown:

```

void sierra::set_max_warnings(int max_warnings);
void sierra::set_max_dooms(int max_dooms);

int sierra::get_max_warnings();
int sierra::get_max_dooms();

```

To set the maximum number of warnings displayed. Each occurrence is still counted, but not displayed. Dooms are always displayed.

```

void sierra::set_max_displayed_warnings(int max_display_warnings);
int sierra::get_max_displayed_warnings();

```

To set the default maximum id messages to display, set `get_next_message_id()` below:

```

int sierra::set_default_max_id_display(int
default_max_id_displayed)
int sierra::set_default_max_id_display(int
default_max_id_displayed)

```

44.16.4. Sierra Exception Reporter

What is this sierra reporter thing you ask? It goes like this: When a Warning or a Doom class is destroyed, `report_exception()` is called with the message. `report_exception()` then calls the registered `report_exception_handler`. The `report_exception_handler` has a signature of

```

(*) (const char *message, int type)

```

and is set with `set_report_exception_handler()`. Sierra sets this to use the `sierra_report_exception_handler()` which writes the message to `sierra::Env::output()`.

If you want special decorations around your messages during execution, you can change the reporter. The parse, instantiation and commit handlers are set by `run_sierra()`.

44.16.5. The Output **versus** OutputP0 Dilemma

Unfortunately, determining what to do with the output from multiple processors can be an issue. If a warning is going to happen on all processors, you may want to wrapper it with a test for processor zero and only output it there. The default `report_exception_handler` sends the output to `Env::output()`

44.16.6. Getting Counts

To get the number of warnings issued, even if not displayed:

```
get_warning_count()
```

To get the number of dooms issued, even if not displayed:

```
get_doomed_count()
```

44.16.7. Traceback and Tracing

The traceback messages are generated by the Trace and Traceback classes upon their destruction. So, if the source code has had trace objects constructed, the stack trace will show them. If efficiency becomes an issue, the `#define app_TRACE_ENABLED` can be undefined which will cause the Trace and Traceback classes to be empty.

The trace object can be used to extract function signature information. The `getFunctionSpec()`, `getFunctionName()`, `getFunctionShortName()`, `getFunctionClass()`, `getFunctionShortClass()` and `getFunctionNamespace()` functions will all extract appropriate information from the function signature.

The program `/usr/netpub/traceString/traceString` (on Linux) can be used to quickly place the trace objects in your source code. I suggest editing the results and placing `[ON]`, `[TRACEBACK]` or `[NONE]` after the first `%TRACE` as in `%TRACE [NONE] %`. These will instruct `traceString` which object type to create. Then, rerun `traceString`. I set it to `NONE` for functions which will execute many many times or cannot throw an error or not have much value in a stack trace (accessors, etc). I set it to `TRACEBACK` if it will not be useful to see traced during a trace run, but be useful in a traceback. And `ON` otherwise which incurs some overhead that enables the conditional runtime trace.

Here is the `.traceString` file I use and suggest be used throughout `sierra`.

```
[START_OF_ROUTINE_PATTERNS]
default    : Trace trace__("${FQNAME}");
off        :
Off        :
OFF        :
none       :
None       :
NONE       :
spec       : static Tracespec trace__("${FQNAME}");
Spec       : static Tracespec trace__("${FQNAME}");
SPEC       : static Tracespec trace__("${FQNAME}");
on         : Trace trace__("${FQNAME}");
On         : Trace trace__("${FQNAME}");
```



```

ON          : Trace trace__("$ (FQNAME)");
traceback  : Traceback trace__("$ (FQNAME)");
Traceback  : Traceback trace__("$ (FQNAME)");
TRACEBACK  : Traceback trace__("$ (FQNAME)");

```

44.16.8. Deriving from a Sierra Exception

When deriving a new exception from the framework exceptions and using the put-to ($\ll$) operator, you must include the following template functions in your class or

```
throw MyError() << "My error message cause of " << x;
```

will certainly fail. It only took me a day to relearn this, but:

If `MyError` does not implement a put-to operator, it uses the base classes put to operator, say `RuntimeError`. Well, the `RuntimeError` put-to operator returns a reference to a `RuntimeError`, so now you are going to be throwing a `RuntimeError` exception not a `MyError` exception. This is only an issue when using the temporaries. By putting the `MyError()` construction on the same line as the throw. I.e.,

```

MyError x;
x << "My error message cause of " << x;
throw x;

```

works fine since we are actually throwing `x`, a `MyError` object.

So, add these if you derive from a sierra exception and wish to throw the temporary object and use the put operator all in one pretty line:

```

class MyError : public RuntimeError {
.
.
.
    inline MyError& operator<<(ExceptionString& (*f)(ExceptionString
&)) {
        f(*this);
        return *this;
    }

    template <class T>
    inline MyError &operator<<(const T &t) {
        RuntimeError::operator<<(t);
        return *this;
    }
};

```

44.16.9. `path_name()`

When generating error messages with object names, use the `path_name()` form rather than just name. This generates a dot (.) separated list of names from the Procedure on down.

44.16.10 `abort()` – Don't use it

`abort()` does not provide any useful information when the application dies. By replacing `abort` calls with Warnings, Dooks and Exceptions, the code will be easier to maintain and the user will get better diagnostic output.

44.16.11 `Apub_Parser_Base` – Useful for parsing, not needed for error reporting

This class stashes useful information from within a parser that is likely to be needed after parsing. The runtime error reporting routines handle error reporting making the line number and command value information redundant for error reporting.

44.17. DIAGNOSTIC WRITER HOW-TO

Editorial note: This How-To is mostly taken from Dave Bauer's collection of How-Tos. Minor changes include formatting, editorial corrections and possibly additional information related to Aria.

This document briefly describes the implementation of the diagnostic writer and masked based output. The diagnostic writer is intended to replace debug level output with but masked based diagnostic output. By utilizing the diagnostic writer, your normal output can be separated or interleaved with the diagnostic output, the diagnostic output can be enabled/disabled at specific times during a run, and entire classes can be output by simply putting the object to the diagnostic writer.

44.17.1. Output

Application output falls into three classes. Normal execution output, warning and error output, and diagnostic output. Normal execution output is handled via the `Env::outputP0()` and `Env::output()` functions and by the application diagnostic writer. Warning and error output is handled by the `RuntimeWarning`, `RuntimeDoomed` and runtime exception classes (`RuntimeError`, `LogicError`, etc), which is eventually written to the env output stream and the diagnostic output stream. And diagnostic output is for selected operationally descriptive output.

In many cases, the diagnostic output is utilized as the primary output stream when selectable level of user output is desired. With that in mind, an `InfoWriter` class has been written. However, additional discussion is required to complete the design and implementation of this class for primary application output.

44.17.2. Diagnostic Writer

The diagnostic writer allows you to write diagnostic information to the diagnostics stream by specifying the content from the command line or the input deck. It a debug level built on a bit mask.

Since there are many applications and libraries, there are several diagnostic writers. Each diagnostic writer has its own bit mask, command line parser and writer. However, they all share a common diagnostic stream. So, output from each diagnostic writer is properly interleaved.

Each application defines its own diagnostic writer. This is generally defined within the `app_DiagWriter_fwd.h`, `app_DiagWriter.h`, `app_DiagWriter.C` files. The `app_DiagWriter_fwd.h` file defines the `LOG_xxx` bit assignments. These values are used to specify the type of message to be written. The `app_DiagWriter.h` rarely needs to be modified. It declares the diagnostic writer for the application or library. The `app_DiagWriter.C` files defines the parser which provides names for the `LOG_xxx` bit masks.

44.17.3. Using The Diagnostic Writer

To have your program send output whenever a specified log bit is set, add the following to your code:

```
dwout.m(LOG_xxx) << "description, " << value << std::endl;
```

or, if much computation or MPI is involved:

```
if (dwout.shouldPrint(LOG_xxx)) {  
    dout << "really_spendy_function(), " <<  
    really_spendy_function() << std::endl;  
}
```

Where `dwout` is the name of the diagnostic writer, `LOG_xxx` is the bit which describes the type of message, `description` is a description of the data. `value` is the value of interest. And, `std::endl` ends the message.

Note that nearly all (please let me know what's missing) containers have output operators. So to write an entire vector, just write the vector variable, the diagnostic writer will take care of the rest.

44.17.4. Turning on the LOG_xxx Bits

Each application has its own command line option and line commands for flipping on the bits. The command line option has limited functionality in that the parameters cannot be switched on and off during an application execution. However, it is useful for a quick look.

For sierra framework, the command line option is `-m`, and each application has its own option name. Use the `-h` option to display a table of command line options and parameters.

The `Diagnostic Control` command block in the sierra block controls each the diagnostic writers:

Option	Description
error	Display error messages
warning	Display warning messages
members	Display data structure members
timer	Display execution time during trace
trace	Display execution trace
contact	Display contact diagnostic information
geometry	Display geometry diagnostic information
scontrol	Display solver control diagnostic information
search	Display search diagnostic information
transfer	Display transfer diagnostic information
parser	Display parser diagnostic information
parameters	Display parameter diagnostic information
io	Display contact I/O information
plugins	Display user function and plugin diagnostic information

Table 44.17-1.. Diagnostic writer options for Framework (fmwkout).

```

Begin Diagnostic Control <diagwriter>
  From time t0 to t1 enable <parameters>
  From step s0 to s1 enable <parameters>
  On condition c enable <parameters>
  Enable <parameters>
End Diagnostic Control <diagwriter>

```

Please refer to Diagnostic Control for implementation details.

The diagnostic output can be selectively enabled based on time, step or an application specified condition. During the application's procedure execution loop, the diagnostic controller evaluates the enclosed line commands in the order specified in the input deck. The diagnostic options specified in the first line command that meets its criteria are applied.

Since control parameters are only applied when the criteria is met, it is important to include an ENABLE line command with the base settings to be applied as a baseline.

Table 44.17.4 lists some of the options available for the framework diagnostic writer fmwkout and options for the Aria diagnostic writer arialog are given in table 44.17.4. Other application will likely implement additional diagnostic writers.

44.17.5. Diagnostic Stream

The diagnostic stream specified the output destination for all the active diagnostic writers. The stream allows the output from the diagnostic writers to be interleaved.

The command line option

Option	Description
bc	Display boundary condition information
debug	Display extra debugging information
eq	Display equation information
expression	Display Expression information
hadapt	Display h-adaptivity information
linsolve	Display linear solver information
nonlinear	Display nonlinear solver information
pp	Display postprocessor information
sens_check	Enable the Expression Newton sensitivity checker
species	Display species information
transfer	Display transfer related information
plugin	Display plugin information

Table 44.17-2.. Diagnostic writer options for Aria (arialog).

```
-dout <destination>
```

and the sierra block line command

```
diagnostic stream <destination>
```

determines the output. <destination> may be cout, cerr, outputp0, output or a path. If a path is given, each processor creates its own file suffixing the path with .n.p where n is the number of processors and p is the rank of each processor. See Diagnostic Stream for specifying the output destination.

44.17.6. Coding Objects

To code your own objects to play with the diagnostic writer, you only need to add a `verbose_print()` member function to your class. And, a `operator«()` function to your namespace. Naturally the implementation for `verbose_print()` is generally in the .C file, not the header.

```
class MyClass : public ParentClass
{
public:
    DiagWriter &verbose_print(DiagWriter &dout) const {
        if (dout.shouldPrint()) {
dout << "MyClass " << m_name << push << std::endl;
ParentClass::verbose_print(dout).std::endl();
dout << "m_var1, " << m_var1 << std::endl;
dout << "m_var2, " << m_var2 << std::endl;
```

```

dout << "m_ptr1, " << c_ptr(m_ptr1) << std::endl;
dout << "m_ptr2, " << c_ptr_name(m_ptr2) << std::endl;
dout << pop;
    }
    return dout;
}
};

inline DiagWriter &operator<<(Diagwriter &dout, const MyClass
&my_class) {
    return my_class.verbose_print(dout);
}

```

If your class is polymorphic, be sure to define `verbose_print()` as `virtual`.

When writing a subclass from your class, the put-to operator (`<<`) will by do what you expect, even when you cast. So you need to use the direct call form.

44.17.7. Writing Containers

You can write an STL container by simple putting it to the diagnostic writer. This is implemented using templates in `utility/include/DiagWriter.h`.

44.17.8. Writing Pointers

Writing of pointers is usually quite ugly since you need to check if the pointer is null first. Instead, use the `c_ptr()` function. If the pointer is null it writes "(pointer), <not created>". Or, you can use `c_ptr_name()` function which will call the `name()` function of the pointed to object if the pointer is not null.

You can have you own pointed object function called by replacing `name` with your member function name below.

```

template <class T>
inline c_ptr_func_<T, const String &> c_ptr_name(const T *t) {
    return c_ptr_func_<T, const String &>(t, &T::name);
}

```

44.17.9. Diagnostic Control

The diagnostic control block in the sierra command block is handled by the `Fmwk::DiagControl::Control` class. Simply add

```
Fmwk::DiagControl::Control diag_control(step_cntr(),  
                                         time(Fmwk::STATE_OLD), 0);
```

at the beginning of your main procedure control loop. This line exists in the Solver Control procedure.

44.18. TIMERS AND TIMING HOW-TO

Editorial note: This How-To is mostly taken from Dave Bauer's collection of How-Tos. Minor changes include formatting, editorial corrections and possibly additional information related to Aria.

This document briefly describes the time metrics collection features available to sierra applications.

The `DiagTimer` and `Timer` classes provide runtime metric information for properly rigged objects.

The system has a root "System" timer. This timer is started when `run_sierra()` is called and stopped before the successful completion information is displayed.

44.18.1. DiagTimer and Timer

The `DiagTimer` class implements the basic developer interface to the timers. Generally, the framework form, `Timer`, will be used to implement timers within a framework derived class.

Timers are intended to be members of your classes or static objects created within a function or member function. Each timer has a name, a parent and a timer class. The name is used to find a child timer of a parent and to display the collected metrics. The parent is used to build the hierarchy of metrics gathered in an application. And the timer class or type categorizes the timers so they may be enabled, disabled and selected for display.

The timing information is actually maintained in a separate tree. So, during timer construction within a class, the timer is a reference to the real timing metric information in the tree. This design means that timers are not destroyed when an object is destroyed.

The timers are hierarchical by name. So, by giving a timer a unique name among its siblings, each object has its own timer and its children timers are also unique.

44.18.2. Add a Timer to a Class

To add a timer to a class, include the header file and add the timer as a member of the class. Then, during construction initialization, specify the timer's name and parent timer. You can also specify a timer class if it is different from the parents.

Then, to start/stop the timer, use the `TimeBlock` and `TimeBlockSynchronized` to ensure that a started timer is stopped.

```
#include <util/Timer.h>

class MyClass
{
public:
    // etc.

    Timer &getMyTimer() {
        return m_myTimer;
    }

    Timer &getMySubTimer() {
        return m_mySubTimer;
    }

private:
    Timer m_myTimer;
    Timer m_mySubTimer;
    // etc.
};

MyClass::MyClass(
    Region & region)
: m_myTimer("My Timer", region.getRegionTimer()),
  m_mySubTimer("My SubTimer", m_myTimer)
{
    // etc.
}

// When controlling timers using the TimeBlocks, be sure to give the
// object a name. Some compilers destroy unnamed objects immediately,
// other destroy them at the end of the block. I usually use timer__
```



```

MyClass::someFunction()
{
    Timer::TimeBlock timer__(m_myTimer); // Metrics in block are
    // collected to m_myTimer;
}

MyClass::someFunction()
{
    Timer::TimeBlockSynchronized timer__(m_myTimer);
    // MPI_Barrier then start timer
}

MyClass::someOtherFunction()
{
    m_myTimer.start(); // Works, but is dangerous if stop() is not called.
    m_myTimer.stop();
}

```

44.18.3. Adding a Timer to a Function

To add a timer to a function, create a static Timer in the function, then start/stop it using the Timer::TimeBlock. Note that if there is no parent specified, the root timer "System" will be the timer's parent.

```

int
myFunction()
{
    static Timer my_timer("My Timer");
    Timer::TimeBlock(my_timer);
    // etc.
}

```

44.18.4. Getting Information from a Timer

Each timer has an accumulation time/count, a checkpoint time/count and a recent lap time/count. The accumulation time is the overall time/count since the start of the application. The checkpoint time/count records the current values when set, then the difference from that time/count can be obtained. This is useful for displaying delta times for iterations. The lap time is the time accumulated during the last start()/stop() cycle for the timer.

The metrics available are `getCPUTime()`, `getWallTime()`, `getFlopCount()`, `getIOCount()`, `getMsgCount()`. Flop, IO, and Msg are not implemented on most platforms (any really).

```
m_myTimer.getCpuTime().getStart(); // Timer most recent start time
m_myTimer.getCpuTime().getStop(); // Timer most recent stop time
m_myTimer.getCpuTime().getLap(); // Most recent stop - start
m_myTimer.getCpuTime().getTotal(); // Accumulated time
m_myTimer.getCpuTime().getTotal(false); // Accumulated time less checkpoint time
```

I could add `getCheckpoint()` and `getCheckpointTotal()` as variations on a theme, but...

44.18.5. Displaying the Timers

To display a table of the collected timing information, use the `Timer::printTable()` function. The function lets you specify the classes and the metrics to output. Note that only enabled timers and metrics are displayed. Use `TIMER_CHECKPOINT` to display checkpointed time. It also resets the checkpoint time/count after display.

```
std::cout << Timer::printTable(TIMER_CPU | TIMER_ALL);
```

44.18.6. Enabling/Disabling the Timers

Timers are enabled by timer class. They can be enabled using the `Timer::setEnabledTimers()` function, by the `-timer` command line option or by the `ENABLE TIMER` input deck line command.

44.18.7. Timers in the Framework

The framework creates several timers and starts/stops them when it has control of the operations.

header timers are given the name associated with the name of the object automatic timers are handled within framework and required no additional coding otherwise, instructions are given on how to collect the data for the timer

Domain:

Domain	header
LinearSystem	automatic
Initialize	automatic
Execute	automatic
Load	automatic
Solve	automatic

Procedure:

Procedure	header
Initialize	automatic
Restart	automatic
Execute	automatic
MeshInput	automatic
MeshOutput	automatic
Transfer	automatic

Region:

Region	header
Initialize	call Timer::TimeBlock timer__(getRegionInitializeTimer()); at
Execute	call Timer::TimeBlock timer__(getRegionExecuteTimer()); at beg

Mechanics:

Mechanics	header

Algorithm:

Algorithm	header
Apply	automatic

WorksetAlgorithm: (sub class of Algorithm)

Gather	automatic
ScatterAssemble	automatic

NonLinearCoupler:

NonLinearSolver	automatic
Initialize	automatic
Scatter	automatic
Solve	automatic

NonLinearSolver:

NonLinearSolve	automatic
Initialize	automatic
Scatter	automatic
Solve	automatic

UserInputFunction:

UserInputFunction	automatic

GLOSSARY

coefficient: Each *field* that is represented by a basis function expansion has a set of coefficients that are used in that expansion. For example, the three dimensional velocity vector represented by an eight node, tri-linear hex element has eight coefficients. In this example, each coefficient is also a vector with three *components*.

This is consistent with the Sierra data model wherein vectors and tensors are single-entity data types.

Although for certain basis function representations the coefficients may be the exact value of the *field* at a point this is not the case in general.

component: The number of values required to describe a *field* at a point. Equal to the tensor dimension raised to the power of the tensor order. For example, temperature has one component, velocity has 3 components (in 3 dimensions) and stress has 9 components.

dof: An entry in the vector of unknowns, i.e. , in the linear solver solution vector.

field: The physical variable of interest, e.g. , temperature or velocity.

multidof: A *field* is a multidof if it contains more than one *component*

BIBLIOGRAPHY

- [1] Micheal W. Glass. Computational Simulation home page.
<http://compsim.sandia.gov/compsim/>. 1.1
- [2] Patrick K. Notz. Thermal/Fluid Developer's Trac Wiki.
<https://prod.sandia.gov/sierra-trac/wiki/Modules/Aria>. 1.1
- [3] The SNTools Project. [SNTools SourceForge Project](#). Online. 2.3
- [4] I. M. Krieger. Rheology of monodisperse latices. Adv. Colloid Interface Sci., 3:111–136, 1972.
4.1.1373, 4.56.10
- [5] Javier Bonet and Richard D. Wood. Nonlinear Continuum Mechanics for Finite Element Analysis. Cambridge University Press, 1997. 4.30.3, 4.45.3, 5.17, 1
- [6] Ted Belytschko, Wing Kam Liu, and Brian Moran. Nonlinear Finite Elements for Continua and Structures. John Wiley and Sons, 2004. 4.30.3, 4.45.3, 5.17, 1, 2
- [7] W. M. Deen. Analysis of Transport Phenomena. Topics in Chemical Engineering. Oxford University Press, New York, 1998. 5.1
- [8] M. J. Martinez. Mathematical and numerical formulation of nonisothermal multicomponent three-phase flow in porous media. Technical Report SAND95-1247, Sandia National Laboratories, Albuquerque, NM, USA, 1995.
<http://www.prod.sandia.gov/cgi-bin/techlib/access-control.pl/1995/951247.pdf>. 5.12.1
- [9] M. J. Martinez, P. L. Hopkins, and J. N. Shadid. LDRD final report: physical simulation of nonisothermal multiphase multicomponent flow in porous media. Technical Report SAND97-1766, Sandia National Laboratories, Albuquerque, NM, USA, 1997.
<http://www.prod.sandia.gov/cgi-bin/techlib/access-control.pl/1997/971766.pdf>. 5.12.1
- [10] M. J. Martinez, P. L. Hopkins, and P. N. Reeves. PorSalsa user's manual. Technical Report SAND2001-1555, Sandia National Laboratories, Albuquerque, NM, USA, 2001.
<http://www.prod.sandia.gov/cgi-bin/techlib/access-control.pl/2001/011555.pdf>. 5.12.1
- [11] Chris Lautenberger and Carlos Fernandez-Pello. Generalized pyrolysis model for combustible solids. Fire Safety Journal, 44(6):819–839, 2009. 5.12.2.7
- [12] D. K. Gartling, C. E. Hickox, and R. C. Givler. Simulations of coupled viscous and porous flow problems. Comp. Fluid Dyn., 1-2:23–48, 1997. 5.13
- [13] S. A. Roberts, D. R. Noble, E. M. Benner, and P. R. Schunk. Multiphase hydrodynamic lubrication flow using a three-dimensional shell finite element model. Comput. Fluids, 2013. , in press. 5.14

- [14] Lawrence E. Malvern. Introduction to the Mechanics of a Continuous Medium. Series in Engineering of the Physical Sciences. Prentice-Hall, Upper Saddle River, NJ, USA, 1969. [5.17](#), [1](#), [3](#)
- [15] George E. Mase. Theory and Problems of Continuum Mechanics. Schaum's Outline Series. McGraw-Hill, New York, NY, USA, 1970. [5.17](#), [1](#), [3](#), [4](#), [6](#), [7](#)
- [16] Clark R. Dohrmann and Pavel B. Bochev. A stabilized finite element method for the Stokes problem based on polynomial pressure projections. Int. J. Num. Meth. Fluids, 46:183–201, 2004. [6.23](#)
- [17] Pavel B. Bochev, Clark R. Rohrmann, and Max D. Gunzburger. Stabilization of low-order mixed finite elements for the Stokes equations. SIAM J. Numer. Anal., 44(1):82–101, 2006. [6.23](#)
- [18] T. Hughes, L. P. Franca, and M. Balestra. A new finite element formulation for computational fluid dynamics: V. circumventing the babuska-brezzi condition: a stable petrov-galerkin formulation of the stokes problem accomodating equal-order interpolations. Comput. Methods Appl. Mech. Engrg., 59:85–99, 1986. [6.23](#)
- [19] R. A. Cairncross, P. R. Schunk, T. A. Baer, R. R. Rao, and P. A. Sackinger. A finite element method for free surface flows of incompressible fluids in three dimensions. part i. boundary fitted mesh motion. Int. J. Numer. Methd. Fluids, 33:375–403, 2000. [9.2.22](#)
- [20] T. D. Blake and J. De Coninck. The influence of solid-liquid interactions on dynamic wetting. Adv. Colloid and Interface Sci., 96:21–36, 2002. [9.2.34](#)
- [21] G. S. Beavers and D. D. Joseph. Boundary conditions at a naturally permeable wall. J. Fluid Mech., 30:197–207, 1967. [9.5](#)
- [22] P. G. Saffman. On the boundary condition at the surface of a porous medium. Studies in Applied Mathematics, 50(2):93–101, 1971. [9.5](#), [9.5](#)
- [23] R. H. Davis and H. A. Stone. Flow through beds of porous particles. Chemical Engineering Science, 48(23):3993–4005, 1993. [9.5](#)
- [24] Ken S. Chen, Gregory H. Evens, Richard S. Larson, David R. Noble, and William G. Houf. Final report on LDRD project: A phenomenological model for multicomponent transport with simultaneous electrochemical reactions in concentrated solutions. SAND 2000-0207, Sandia National Laboratories, Albuquerque, NM 87185, USA, January 2000. [11.3.15](#)
- [25] I. M. Levi. Users' Guide to the Transient Heat Conduction Finite Element Code HTCON. Technical Report MM70-5425-17, Bell Telephone Laboratories, Whippany, NJ, USA, 1970. [16.2](#)
- [26] A. F. Emery, K. Sugihara, and A. T. Jones. A comparison of some of the thermal characteristics of finite-element and finite-difference calculations of transient problems. Num. Heat Trans., 2:97–113, 1979. [16.2](#)
- [27] F. Damjanic and D. R. J. Owen. Practical considerations for thermal transient finite element analysis using isoparametric elements. Nucl. Engrg. Des., 69:109–126, 1982. [16.2](#)
- [28] E. Rank, C. Katz, and H. Werner. On the importance of the discrete maximum principle in transient analysis using finite element methods. Int. J. Num. Meth. Engng., 19:1771–1782, 1983. [16.2](#)

- [29] H. S. Carslaw and J. C. Jaeger. Conduction of Heat in Solids. Clarendon Press, Oxford, 2nd edition, 1959. [16.2](#)
- [30] D. K. Gartling. NACHOS II - a finite element computer program for incompressible flow problems. part I - theoretical background. Technical Report SAND86-1816, Sandia National Labs, Albuquerque, NM, USA, April 1986. [16.5.26](#)
- [31] Erik Boman, Karen Devine, Robert Heaphy, Bruce Hendrickson, William Mitchell, Matthew St. John, and Courtenay Vaughan. Zoltan home page. <http://www.cs.sandia.gov/Zoltan>, 1999. [19](#)
- [32] Karen Devine, Bruce Hendrickson, Erik Boman, Matthew St. John, and Courtenay Vaughan. Zoltan: A Dynamic Load Balancing Library for Parallel Applications; User's Guide. Sandia National Laboratories, Albuquerque, NM, 1999. Tech. Report SAND99-1377 http://www.cs.sandia.gov/Zoltan/ug_html/ug.html. [19](#)
- [33] Karen Devine, Erik Boman, Robert Heaphy, Bruce Hendrickson, and Courtenay Vaughan. Zoltan data management services for parallel dynamic applications. Computing in Science and Engineering, 4(2):90–97, 2002. [19](#)
- [34] Kevin D. Copps and Brian C. Carnes. Sierra Verification Module: Encore User Guide - Version 4.28. SAND 2013-3344, Sandia National Laboratories, Albuquerque, NM 87185, USA, June 2013. [21.1](#)
- [35] R. Siegel and J. R. Howell. Thermal Radiation Heat Transfer. Taylor and Francis, Washington, D.C., 1992. [22.1](#)
- [36] M. W. Glass. Chaparral: A library for solving enclosure radiation heat transfer problems. Technical Report SAND95-2049, Sandia National Laboratories, Albuquerque, New Mexico, 1995. [22.2](#)
- [37] Robert Kosik, Peter Fleischmann, Bernhard Haindl, Paola Pietra, and Siegfried Selberherr. On the interplay between meshing and discretization in three-dimensional diffusion simulation. IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems, 19(11):1233–1240, 2000. [33.3](#)
- [38] Changna Lu, Weizhang Huang, and Jianxian Qiu. Maximum principle in linear finite element approximations of anisotropic diffusion–convection–reaction problems. Numerische Mathematik, 127(3):515–537, 2014. [33.3](#)
- [39] Dmitri Kuzmin. Linearity-preserving flux correction and convergence acceleration for constrained galerkin schemes. Journal of Computational and Applied Mathematics, 236(9):2317–2337, 2012. [33.3](#)
- [40] Dmitri Kuzmina and John N Shadidb. A new approach to enforcing discrete maximum principles in continuous galerkin methods for convection-dominated transport equations. Preprint: Ergebnisberichte des Instituts für Angewandte Mathematik, 529. [33.3](#)
- [41] E. R. G. Eckert. Survey of boundary layer heat transfer at high velocities and high temperatures. Technical report, WADC, 1960. [33.10](#)

- [42] D. Dobranich. Sfsim input manual -a compute program for the engineering simulation of flow systems. Technical Report SAND92-0694, Sandia National Laboratories, Albuquerque, NM, USA, September 1992. [34.1](#)
- [43] I. Glassman. Combustion. Academic Press, New York, 1977. [1](#)
- [44] S. Gordan and B. J. McBride. Computer program for calculation of complex chemical equilibrium compositions and applications I. analysis. Technical Report Ref. Publication 1311, NASA, October 1994. [41.5.2](#)
- [45] B. J. McBride and S. Gordan. Computer program for calculation of complex chemical equilibrium compositions and applications II. users manual and program description. Technical Report Ref. Publication 1311, NASA, June 1996. [41.5.2](#)
- [46] P. K. Notz, S. R. Subia, M. H. Hopkins, and P. A. Sackinger. A novel approach to solving highly coupled equations in a dynamic, extensible and efficient way. In M. Papadrakakis, E. Onate, and B. Schrefler, editors, Computation Methods for Coupled Problems in Science and Engineering, page 129, Barcelona, Spain, April 2005. Intl. Center for Num. Meth. in Engng. (CIMNE). [44.2](#)
- [47] Bjarne Stroustrup. The C++ Programming Language, Special Edition. Addison Wesley, Reading, MA, 2000. [44.II.1](#)

INDEX

A

Abort If Field Not Defined On Copy Transfer Send Or
Receive Object, [1123](#), [1124](#)

Abscissa, [58](#), [59](#)

Abscissa Offset, [58](#), [59](#)

Abscissa Scale, [58](#), [60](#)

Absolute Tolerance, [1607](#), [1608](#), [1646](#), [1647](#)

Absorption Coefficient, [70](#), [1437](#), [1438](#), [1507](#), [1508](#)

Absorption Coefficient Data File, [1437](#), [1438](#)

Absorption Coefficient Encore Function, [1507](#), [1508](#)

Absorption Coefficient: Copied, [70](#)

Absorption Coefficient: Porous Phase Average, [71](#)

Absorption Coefficient: Scalar String Function, [71](#)

Absorption Coefficient: User Plugin, [71](#)

Absorption Cross Section, [72](#)

Absorption Cross Section: Calore User Sub, [73](#)

Absorption Cross Section: Copied, [72](#)

Absorption Cross Section: Linearized, [73](#)

Absorption Cross Section: Scalar String Function, [73](#)

Absorption Cross Section: User Plugin, [72](#)

Accept Solution After Maximum Nonlinear Iterations,
[1164](#)

Activate Acoustic Compressibility Algorithm, [1667](#), [1668](#)

Activate Ausm Plus Scheme, [1667](#), [1668](#)

Activate Co2 Dissociation Model, [1684](#), [1685](#)

Activate Cvfem Lumped Turbulent Source Term
Algorithm, [1679](#)

Activate Edge Based Diffusion Operator, [1667](#), [1669](#)

Activate Edge Based Fourth Order Advection, [1667](#), [1669](#)

Activate Hydrogen Dissociation Model, [1684](#), [1685](#)

Activate Ignition Model, [1684](#), [1685](#)

Activate Kepsilon Source Term Trickster Linearization, [1679](#),
[1680](#)

Activate Kexact Muscl Scheme For Equation, [1667](#), [1669](#)

Activate Laminar Limit Model, [1684](#), [1686](#)

Activate Lumped Source Term Model, [1684](#), [1686](#)

Activate Mean Beam Model With Bulk Node, [1259](#), [1261](#)

Activate Mixture Fraction Clipping Utility At, [1667](#), [1669](#)

Activate Muscl Scheme For Equation, [1667](#), [1670](#)

Activate New Komega Src Linearization, [1679](#), [1680](#)

Activate Pressure Projection Algorithm, [1667](#), [1670](#)

Activate Projected Stress Stabilization, [1667](#), [1671](#)

Activate Rhs Sdr Sensitivities To, [1679](#), [1680](#)

Activate Rhs Tke Sensitivities To, [1679](#), [1680](#)

Activate Scv Nodal Gradient, [1667](#), [1671](#)

Activate Separate Co Irreversible Oxidation Pathway, [1684](#),
[1686](#)

Activate Shakib Scaling, [1667](#), [1671](#)

Activate Turbulence Clipping Utility At, [1679](#), [1681](#)

Activate Vrtm In Mass Flux Vector, [1667](#), [1671](#)

Activation, [1507](#), [1509](#)

Activation Energies, [1599](#), [1600](#), [1618](#), [1619](#)

Activation Energy St Devs, [1599](#), [1601](#)

Activation Temperature, [1507](#), [1509](#), [1607](#), [1608](#), [1618](#), [1622](#)

Activation Temperature Rate, [1607](#), [1609](#)

Activation Time, [1607](#), [1609](#), [1684](#), [1686](#)

Adapt, [1085](#), [1086](#), [1089](#), [1090](#), [1094](#), [1098](#), [1102](#), [1103](#)

Adaptivity, [1085](#), [1090](#), [1102](#)

Add Part, [1496](#)

Add Surface, [1259](#), [1262](#), [1408](#), [1409](#), [1420](#), [1421](#), [1423](#), [1424](#),
[1428](#), [1430](#), [1437](#), [1439](#), [1447](#), [1449](#), [1461](#), [1463](#), [1484](#),
[1486](#), [1517](#)

Add Volume, [1074](#), [1075](#), [1420](#), [1421](#), [1477](#), [1478](#), [1499](#), [1500](#),
[1507](#), [1509](#)

Additional Parameter, [1410](#)

Additional Steps, [1311](#), [1313](#), [1325](#), [1326](#), [1334](#), [1335](#), [1346](#), [1347](#)

Additional Times, [1311](#), [1313](#), [1325](#), [1326](#), [1334](#), [1335](#), [1346](#), [1347](#)

Adiabatic Wall Temperature, [1461](#), [1463](#)

Adiabatic Wall Temperature Altitude Function, [1461](#), [1463](#)

Adiabatic Wall Temperature From Recovery Factor, [1461](#),
[1464](#)

Adiabatic Wall Temperature Time Function, [1461](#), [1464](#)

Advance, [1089](#), [1091](#), [1094](#), [1095](#), [1098](#), [1099](#), [1102](#), [1103](#), [1106](#),
[1111](#)

Advected Bubble, [74](#)

Advected Bubble: Copied, [74](#)

Advected Bubble: Scalar String Function, [75](#)

Advected Bubble: User Plugin, [75](#)

Advection, [834](#), [861](#)

ADVECTION VELOCITY, [740](#)

Advection Velocity, [75](#)

Advection Velocity: User Plugin, [76](#)

Advection Velocity: Vector String Function, [76](#)

Advective Bar Network, [1477](#)

Aero Heat Flux Boundary Condition, [1461](#)

Aft Semi Axis, [1507](#), [1510](#)

Air Water Mass Flux: Fickian, [76](#)

Alias, [46](#), [47](#)

All Fields, [1123](#), [1124](#)

All Volumes, [1420](#), [1421](#)

Allow Old Heat Generation Method, [1607](#), [1609](#)
 Allow Order Switch For, [1142](#), [1144](#)
 Altitude, [77](#), [1461](#), [1465](#)
 Altitude Time Function, [1461](#), [1465](#)
 Altitude: Copied, [77](#)
 Altitude: Scalar String Function, [78](#)
 Altitude: User Plugin, [77](#)
 Ambient Pressure, [78](#)
 Ambient Pressure: Copied, [78](#)
 Ambient Pressure: Scalar String Function, [79](#)
 Ambient Pressure: User Plugin, [79](#)
 Analytic Initial Condition, [1387](#), [1391](#)
 Angular Intensity, [79](#)
 Angular Intensity: Copied, [80](#)
 Angular Intensity: Scalar String Function, [80](#)
 Angular Intensity: User Plugin, [80](#)
 Angular Velocity, [1437](#), [1439](#)
 ANISOTROPIC CONDUCTIVITY USER
 SUBROUTINE, [1538](#)
 anneal, [749](#)
 ANNEAL MESH ON STARTUP, [749](#)
 Annulus Diameter Ratio, [81](#)
 Annulus Diameter Ratio Function, [1477](#), [1478](#)
 Annulus Diameter Ratio Threshold, [1477](#), [1478](#)
 Annulus Diameter Ratio: Copied, [81](#)
 Annulus Diameter Ratio: Correlation, [82](#)
 Annulus Diameter Ratio: Correlation Spatial User
 Function, [83](#)
 Annulus Diameter Ratio: Scalar String Function, [82](#)
 Annulus Diameter Ratio: Spatial User Function, [82](#)
 Annulus Diameter Ratio: User Plugin, [81](#)
 Append, [1325](#), [1326](#)
 Apply Flux Limiter Stabilization, [1662](#), [1663](#)
 Apply Gnielinski Film Gradient Correction, [1584](#), [1586](#)
 Apply Hausen Entrance Effect Correction, [1585](#), [1586](#)
 Area Output, [1259](#), [1262](#)
 arialog, [1381](#)
 Assemble Tpetra, [1662](#), [1663](#), [1689](#)
 assert, [1733](#)
 Asymptotic Tolerance, [1607](#), [1609](#)
 At Discontinuity Evaluate To, [58](#), [60](#)
 At Step, [1311](#), [1313](#), [1325](#), [1327](#), [1334](#), [1336](#), [1342](#), [1345](#), [1346](#),
 [1348](#)
 At Time, [1311](#), [1314](#), [1325](#), [1327](#), [1334](#), [1336](#), [1346](#), [1348](#)
 At Wall Time, [1346](#), [1348](#)
 Ausm Alpha, [1667](#), [1671](#)
 Ausm Beta, [1667](#), [1672](#)
 Aux Variable, [1607](#), [1610](#)
 Aux Variable Names, [1599](#), [1601](#)
 Aux Variable Subroutine, [1599](#), [1601](#)
 AUX VARIABLE USER SUBROUTINE, [1544](#)
 Auxiliary Mesh Field: Scalar, [83](#)
 Axisymmetry Axis, [54](#)
 Aztec Equation Solver, [1211](#)

B

Balanced Force, [942](#)
 Band, [1261](#), [1278](#), [1279](#)
 Banded Wavelength Model, [1278](#)
 BAR AREA, [577](#)
 CONSTANT, [577](#)
 ELEMENT_ATTRIBUTE, [577](#)
 Bar Area, [84](#)
 Bar Area: Copied, [84](#)
 Bar Area: Element Attribute, [85](#)
 Bar Area: Scalar String Function, [85](#)
 Bar Area: User Plugin, [84](#)
 Bar Perimeter, [85](#)
 Bar Perimeter: Copied, [86](#)
 Bar Perimeter: Element Attribute, [87](#)
 Bar Perimeter: Scalar String Function, [86](#)
 Bar Perimeter: User Plugin, [86](#)
 Bc Bulk Node Coupling For Density = K Factor Flow,
 [1000](#)
 Bc Bulk Node Coupling For Density = K Factor Flow With
 Choking, [1001](#)
 Bc Bulk Node Coupling For Species = K Factor Flow, [1001](#)
 Bc Bulk Node Coupling For Species = K Factor Flow With
 Choking, [1002](#)
 BC Dirichlet, [750](#)
 BC CIRC_X, [755](#)
 BC CIRC_Y, [756](#)
 BC CONST, [756](#)
 BC DISTRIBUTION FACTOR, [756](#)
 BC LINEAR, [757](#)
 BC LINEAR_IN_TIME, [757](#)
 BC PARAB, [757](#)
 BC PERIODIC_LINEAR_IN_TIME, [758](#)
 BC PERIODIC_STEP_IN_TIME, [758](#)
 BC RAMP_LINEAR_IN_TIME, [759](#)
 BC ROTATING_X, [759](#)
 BC ROTATING_Y, [760](#)
 BC TRANSLATE, [760](#)
 BC UNIDIRECTIONAL_FLOW_X, [761](#)
 BC UNIDIRECTIONAL_FLOW_Y, [761](#)
 BC USER FIELD, [762](#)
 BC USER_FUNCTION_IN_TIME, [763](#)
 BC XFER, [762](#)
 BC DISTING, [1041](#)
 BC EDGE, [1040](#)
 WETTING, [1040](#)
 Bc Enforcement, [1186](#), [1187](#), [1200](#), [1201](#), [1211](#), [1212](#)
 BC FLUX, [764](#)
 CALORE_USER_SUB, [766](#)
 CAPILLARY, [783](#)
 CONSTANT, [765](#)
 CONSTANT_TRACTION, [783](#)
 DISTRIBUTION_FACTOR, [768](#)
 ELECTRIC_TRACTION, [784](#)

ENCLOSURE_RADIATION, 768
 ENCORE_FUNCTION, 768
 FLOW_HYDROSTATIC, 784
 FREE_OPEN_FLOW, 785
 GAUSSIAN_LINE_WELD, 773
 GAUSSIAN_SPOT_WELD, 775
 GENERALIZED_NAT_CONV, 777
 GENERALIZED_RAD, 777
 LASER, 771
 LASER_WELD, 772
 LATENT_HEAT, 781
 LUBRICATION_PRESSURE, 786
 NAT_CONV, 781, 782
 NAT_E, 784
 OPEN_FLOW, 785
 ORIENTED_SLIP, 786
 PID_CONTROLLED, 769
 PID_CONTROLLED_BIDIRECTIONAL, 771
 PID_CONTROLLED_COOLER, 770
 PRESSURE, 786
 RAD, 782
 SHARP_LINE_WELD, 778
 SHARP_SPOT_WELD, 780
 SLIP, 787
 TRANSIENT_TRACTION, 787
 USER_FUNCTION, 789
 VAPOR_COOLING, 782
 WETTING_SPEED_BLAKE_LS, 788
 Bc Heat Flux, 87
 Bc Heat Flux: User Field Times Inward Normal, 88
 Bc Heat Flux: User Plugin, 87
 Bc Heat Flux: Vector String Function, 88
 Bc Interface Colloc Disting For Lubrication Height =
 Deforming, 1034
 Bc Rad Reference Temperature, 88
 Bc Rad Reference Temperature: Bulk Node, 90
 Bc Rad Reference Temperature: Calore User Sub, 90
 Bc Rad Reference Temperature: Copied, 89
 Bc Rad Reference Temperature: Fortran, 91
 Bc Rad Reference Temperature: Scalar String Function,
 89
 Bc Rad Reference Temperature: User Plugin, 89
 Bc Reference Temperature, 91
 Bc Reference Temperature: Bulk Node, 92
 Bc Reference Temperature: Calore User Sub, 93
 Bc Reference Temperature: Computed Adiabatic Wall, 93
 Bc Reference Temperature: Copied, 91
 Bc Reference Temperature: Fortran, 94
 Bc Reference Temperature: Scalar String Function, 92
 Bc Reference Temperature: User Plugin, 92
 Beam Diameter, 1437, 1439, 1507, 1510
 Beam Diameter At Depth, 1507, 1510
 Beam Radius, 1437, 1439
 BETA, 577
 CONSTANT, 578
 CONVERTED, 578
 ENCORE_FUNCTION, 579
 LINEAR, 579
 Beta, 94
 Beta: Converted, 95
 Beta: Copied, 94
 Beta: Linear, 96
 Beta: Scalar String Function, 95
 Beta: User Plugin, 95
 Bicgstab Solver, 1186, 1188
 Blocking Surfaces, 1259, 1262
 Body Acceleration, 96
 Body Acceleration: User Plugin, 96
 Body Acceleration: Vector String Function, 97
 Boundary Entrained Enthalpy, 97
 Boundary Entrained Enthalpy: Copied, 97
 Boundary Entrained Enthalpy: Scalar String Function, 98
 Boundary Entrained Enthalpy: User Plugin, 98
 Boundary Entrained Mass Fraction, 98
 Boundary Entrained Mass Fraction: Copied, 99
 Boundary Entrained Mass Fraction: Scalar String Function,
 99
 Boundary Entrained Mass Fraction: User Plugin, 99
 Boundary Pressure, 100
 Boundary Pressure: Copied, 100
 Boundary Pressure: Scalar String Function, 101
 Boundary Pressure: User Plugin, 100
 Bsp Tree Max Depth, 1248, 1249
 Bulk Conductivity, 101
 Bulk Conductivity: Copied, 101
 Bulk Conductivity: Linear Temperature And Density, 103
 Bulk Conductivity: Porous Phase Average, 103
 Bulk Conductivity: Scalar String Function, 102
 Bulk Conductivity: T Exponent, 102
 Bulk Conductivity: User Plugin, 102
 Bulk Conductivity: Volume Average, 103
 Bulk Coordinates, 1403, 1404
 Bulk Density, 104
 Bulk Density: Copied, 104
 Bulk Density: Scalar String Function, 105
 Bulk Density: Single Component Ideal Gas, 105
 Bulk Density: T Exponent, 105
 Bulk Density: User Plugin, 104
 Bulk Element Pressure, 106, 1403, 1404
 Bulk Element Pressure: Calore User Sub, 106
 Bulk Element Pressure: Integrated, 106
 Bulk Element Volume, 107, 1403, 1405
 Bulk Element Volume: Calore User Sub, 107
 Bulk Element Volume: Integrated, 107
 Bulk Eq, 1403, 1405
 Bulk Fluid Element, 1403
 Bulk Mass Density, 109
 Bulk Mass Density: Copied, 110

- Bulk Mass Density: Density, [108](#)
- Bulk Mass Density: Mass Fraction Density, [108](#)
- Bulk Mass Density: Mass Fraction Porous Density, [109](#)
- Bulk Mass Density: Multiphase Porous Density, [109](#)
- Bulk Mass Density: Porous Density, [108](#)
- Bulk Mass Density: Scalar String Function, [110](#)
- Bulk Mass Density: User Plugin, [110](#)
- Bulk Node Coupling, [1410](#)
- Bulk Nodes, [1410](#), [1411](#)
- Bulk Nodes Ignore Restart, [1410](#)
- Bulk Source For, [1403](#), [1406](#)
- BULK VISCOSITY, [579](#)
 - CONSTANT, [580](#)
 - CURING_FOAM, [580](#)
 - ENCORE_FUNCTION, [581](#)
- Bulk Viscosity, [111](#)
- Bulk Viscosity: Copied, [111](#)
- Bulk Viscosity: Curing Foam, [112](#)
- Bulk Viscosity: Interpolated Phase Average, [113](#)
- Bulk Viscosity: Mass Average, [113](#)
- Bulk Viscosity: Phase Average, [112](#)
- Bulk Viscosity: Scalar String Function, [112](#)
- Bulk Viscosity: User Plugin, [111](#)
- Bulk Viscosity: Volume Average, [113](#)
- Burn Front Width, [114](#)
- Burn Heat Release, [114](#)
- Burn Heat Release: Copied, [114](#)
- Burn Heat Release: Scalar String Function, [115](#)
- Burn Heat Release: User Plugin, [115](#)
- Burn Initiation: Temperature, [115](#)
- Burn Speed, [116](#)

C

- Calculate Volume From Enclosing Surface, [1403](#), [1406](#)
- Calore
 - user subroutines
 - boundary conditions, [600](#), [607](#), [632](#), [766](#)
 - density, [585](#)
 - emissivity, [600](#)
 - heat transfer coefficient, [607](#)
 - radiation_form_factor, [632](#)
 - source, [1048](#)
 - thermal conductivity, [667](#), [674](#)
 - thermal diffusivity, [675](#)
- Calore User Sub, [862](#), [924](#), [958](#), [1028](#)
- Cantera, [1024](#), [1030](#)
- Cantera Xml File, [136](#)
- Capillary, [791](#), [891](#), [917](#), [941](#), [969](#)
- Capillary Force, [850](#), [934](#)
- Capillary Gap, [917](#)
- Capillary Pressure, [116](#)
- Capillary Pressure: Brooks Corey, [119](#)
- Capillary Pressure: Computed, [119](#)
- Capillary Pressure: Copied, [116](#)

- Capillary Pressure: Encore Saturation, [118](#)
- Capillary Pressure: Scalar String Function, [117](#)
- Capillary Pressure: Udell Cubic, [118](#)
- Capillary Pressure: User Plugin, [117](#)
- Capillary Pressure: Van Genuchten, [117](#)
- Capillary Stabilization, [892](#), [899](#), [940](#)
- Catalyst, [1313](#)
- Cauchy stress, [718](#)
- Cg Solver, [1186](#), [1194](#)
- Characteristic Length, [1585](#), [1587](#)
- Characteristic Length: Correlation, [120](#)
- Characteristic Length: Correlation Bar Perimeter, [120](#)
- Characteristic Length: Correlation Hydraulic Diameter, [120](#)
- Characteristic Length: Correlation Wetted Perimeter, [121](#)
- Charge Density, [121](#)
- Charge Density: Copied, [121](#)
- Charge Density: Scalar String Function, [122](#)
- Charge Density: User Plugin, [122](#)
- Check Matrix For Discrete Maximum Principle, [1228](#), [1229](#), [1662](#), [1664](#)
- Chemeq, [1499](#), [1501](#)
- chemeq foam
 - thermal conductivity, [636](#)
- Chemeq Solver For, [1607](#)
- Chemical Potential: From Equilibrium Potential, [123](#)
- Chemical Potential: Ideal Solution, [122](#)
- Chemical Potential: Isotropic Mesh Stress, [123](#)
- Chemistry
 - CHEMEQ
 - source, [1049](#)
- Chemistry Solver Algorithm, [1646](#), [1647](#)
- Chemistry Solver Parameters For, [1646](#)
- Chemistry Step Multiplier, [1607](#), [1610](#)
- Cht Dirichlet Robin, [981](#)
- Cht Flux, [980](#)
- Cht Robin, [982](#), [1013](#)
- Circle Weld, [986](#)
- Circular Path Center, [1437](#), [1440](#)
- Circular Path Start Vector, [1437](#), [1440](#)
- Clip Cvfem Level Set Dof, [1667](#), [1672](#)
- Clip Isoparametric Coords, [1069](#)
- Closed Surface Volume, [1408](#), [1517](#)
- Co2 Convective Outflow, [845](#)
- Column Titles, [58](#), [60](#)
- Component Separator Character, [46](#), [47](#), [1311](#), [1314](#), [1346](#), [1349](#)
- Composite Name, [1386](#), [1387](#)
- Composition Method, [1391](#), [1392](#)
- Compute, [1585](#), [1587](#)
- Compute Indicator On, [1085](#), [1086](#), [1089](#), [1091](#), [1094](#), [1095](#), [1098](#), [1099](#), [1102](#), [1103](#)
- Compute Rule, [1248](#), [1249](#)
- Compute Time Of Arrival On, [1391](#), [1392](#)

Compute Time Of Arrival With Element Speed, [1391](#), [1393](#)
 Compute Visibility Field, [1437](#), [1440](#)
 Compute_Surface_Distance, [1387](#)
 Concentration Exponents For, [1599](#), [1602](#), [1618](#), [1619](#)
 Concentration Units, [1599](#), [1602](#)
 Condensed Fraction, [1599](#), [1602](#)
 Conductance Coefficient, [1291](#), [1292](#)
 Conductance Coefficient Contact Pressure Function, [1291](#), [1292](#)
 Conductance Coefficient For, [1291](#), [1292](#)
 Conductance Coefficient Fortran Subroutine, [1291](#), [1293](#)
 Conductance Coefficient Subroutine, [1291](#), [1293](#)
 Conductance Coefficient Temperature Function, [1291](#), [1293](#)
 Conductance Coefficient Time Function, [1291](#), [1294](#)
 Conductance Coefficient Voltage Function, [1291](#), [1294](#)
 CONDUCTIVITYUSER SUBROUTINE, [1540](#)
 Cone Length, [1461](#), [1465](#)
 Constant Traction, [795](#), [804](#), [848](#), [946](#)
 Constant Velocity, [844](#)
 Constant With Cutoff Voltage, [960](#)
 CONSTRAIN, [1068](#)
 Contact Definition, [1287](#)
 Contact Electrical Conductance Coefficient, [123](#)
 Contact Electrical Conductance Coefficient: Calore User Sub, [125](#)
 Contact Electrical Conductance Coefficient: Copied, [124](#)
 Contact Electrical Conductance Coefficient: Scalar String Function, [124](#)
 Contact Electrical Conductance Coefficient: User Plugin, [124](#)
 Contact Heat Transfer Coefficient, [125](#)
 Contact Heat Transfer Coefficient: Calore User Sub, [127](#)
 Contact Heat Transfer Coefficient: Copied, [126](#)
 Contact Heat Transfer Coefficient: Scalar String Function, [126](#)
 Contact Heat Transfer Coefficient: User Plugin, [126](#)
 Contact Smooth Surface, [1287](#), [1288](#)
 Contact Surface, [1287](#), [1288](#)
 Continuity Diffusion Coefficient, [127](#)
 Continuity Diffusion Coefficient: Copied, [127](#)
 Continuity Diffusion Coefficient: Scalar String Function, [128](#)
 Continuity Diffusion Coefficient: Shakib, [128](#)
 Continuity Diffusion Coefficient: User Plugin, [128](#)
 Continuity Diffusive Flux: Basic, [129](#)
 Continuity Diffusive Flux: Pressure Poisson, [129](#)
 Continuity Face Stabilization Scaling: Default, [129](#)
 Convective Coefficient, [1447](#), [1449](#)
 Convective Coefficient Encore Function, [1447](#), [1450](#)
 Convective Coefficient Fortran Subroutine, [1447](#), [1450](#)
 Convective Coefficient Node Variable, [1447](#), [1450](#)
 Convective Coefficient Scale Factor, [1447](#), [1451](#)
 Convective Coefficient Subroutine, [1447](#), [1451](#)
 Convective Coefficient Temperature Function, [1447](#), [1451](#)
 Convective Coefficient Time Function, [1448](#), [1452](#)
 Convective Flux Boundary Condition, [1447](#)
 Convective Outflow, [844](#), [866](#), [968](#)
 Converged When, [1107](#), [1108](#), [1111](#)
 Convergence Tolerance, [1188](#), [1189](#), [1191–1195](#), [1254](#), [1255](#), [1257](#), [1258](#)
 Coordinate Offset, [1461](#), [1466](#)
 Coordinate Offset Axis, [1461](#), [1466](#)
 Coordinate Reference, [1477](#), [1479](#)
 Coordinate System, [51](#)
 Copied, [1003](#), [1005](#), [1006](#), [1009](#), [1010](#), [1012](#), [1015](#), [1018](#), [1019](#), [1023](#), [1026](#), [1027](#)
 Copy, [1123](#), [1124](#)
 Couple, [1410](#), [1411](#)
 Coupling, [1257](#), [1258](#)
 Coupling Algorithm, [1654](#), [1655](#)
 Courant Limit, [1142](#), [1144](#)
 Create, [46](#), [47](#)
 Create Element Field, [1358](#), [1359](#)
 Create Nodal Field, [1358](#), [1360](#)
 Criterion, [1074](#), [1075](#)
 CTE, [581](#)
 CONSTANT, [582](#)
 ENCORE_FUNCTION, [582](#)
 Cte, [130](#)
 Cte: Copied, [130](#)
 Cte: Scalar String Function, [131](#)
 Cte: User Plugin, [130](#)
 curing epoxy foam
 bulk viscosity, [580](#)
 density, [586](#)
 energy source, [1053](#), [1054](#)
 species source, [1062](#), [1063](#)
 specific heat, [659](#), [1054](#)
 thermal conductivity, [668](#)
 viscosity, [683](#)
 CURRENT DENSITY, [583](#)
 BASIC, [583](#)
 DIELECTRIC_DISPLACEMENT, [583](#)
 OHMS_LAW, [584](#)
 THERMOELECTRIC, [584](#)
 Current Density, [131](#)
 Current Density: Basic, [132](#)
 Current Density: Curl B, [134](#)
 Current Density: Dielectric Displacement, [133](#)
 Current Density: Electrolyte, [133](#)
 Current Density: Mhd, [134](#)
 Current Density: Ohms Law, [132](#)
 Current Density: Thermoelectric, [133](#)
 Current Density: User Plugin, [131](#)
 Current Density: Vector String Function, [132](#)
 Current Exchange Density, [134](#)
 Current Exchange Density: Copied, [135](#)

Current Exchange Density: Scalar String Function, [135](#)
 Current Exchange Density: User Plugin, [135](#)
 Curvature, [823](#), [851](#)
 Cvfem Algorithm Specification, [1229](#), [1662](#), [1667](#)
 Cycle Count, [1346](#), [1349](#)
 Cylinder, [1391](#), [1393](#)

D

Darcy, [1003](#)
 Darcy Leak, [789](#)
 Darcy Slip, [800](#)
 Darcy Solvent, [1008](#)
 Darcy's law, [602](#), [610](#), [616](#), [630](#), [638](#)
 Dash Closure Metric Samples, [1259](#), [1263](#), [1281](#)
 Dash Penalty Factor, [1291](#), [1294](#)
 Dash Solve Enclosures, [1259](#), [1263](#)
 Dash Subfaceting Algorithm, [1259](#), [1263](#)
 Data, [742](#)
 Data Block, [742](#)
 Data File, [58](#), [60](#)
 Data Probe, [1342](#)
 Database Name, [46](#), [48](#), [1259](#), [1264](#), [1311](#), [1314](#), [1334](#), [1336](#), [1346](#), [1349](#)
 Database Type, [46](#), [48](#), [1311](#), [1315](#), [1334](#), [1337](#), [1346](#), [1350](#)
 Dd-Ilu Preconditioner, [1188](#), [1189](#), [1191](#), [1194](#), [1196](#)
 Dd-Ilut Preconditioner, [1188](#), [1189](#), [1191](#), [1194](#), [1198](#)
 Deactivation Temperature, [1607](#), [1610](#), [1618](#), [1623](#)
 Deactivation Temperature Overshoot, [1607](#), [1610](#), [1618](#), [1623](#)
 Deactivation Temperature Rate, [1607](#), [1611](#), [1618](#), [1623](#)
 Deactivation Time, [1607](#), [1611](#)
 Debug, [58](#), [61](#)
 Debug Dump, [1346](#), [1350](#)
 Debug Output Level, [1200](#), [1202](#), [1211](#), [1212](#), [1220](#), [1221](#)
 Debug Output Path, [1200](#), [1202](#), [1211](#), [1212](#), [1220](#), [1221](#)
 debugging, [1363](#), [1381](#), [1729](#)
 Decay Constant: Hdiff, [136](#)
 Decomposition Method, [50](#), [1346](#), [1350](#)
 Define Direction, [1038](#)
 Define Point, [1038](#)
 Definition For Function, [58](#)
 Deformation gradient, [717](#)
 DENSITY, [584](#)
 CALORE_USER_SUB, [585](#)
 COMPRESSIBLE_BOUSSINESQ, [585](#)
 CONSTANT, [586](#)
 CURING_FOAM, [586](#)
 ENCORE_FUNCTION, [587](#)
 EXP_DECAY, [587](#)
 IDEAL_GAS, [588](#)
 INCOMPRESSIBLE_IDEAL_GAS, [588](#)
 POLYNOMIAL, [589](#)
 SINGLE_COMPONENT_IDEAL_GAS, [589](#)
 THERMAL, [590](#)

 USER_FUNCTION, [590](#)
 Density, [136](#), [1585](#), [1587](#)
 Density Ratio Convective Coefficient, [1461](#), [1466](#)
 Density Ratio Exponent, [1461](#), [1467](#)
 Density Scale Factor, [51](#), [52](#)
 Density: Adaptive Table Lookup, [147](#)
 Density: Calore User Sub, [138](#)
 Density: Cantera, [138](#)
 Density: Cantera Molten Salt, [138](#)
 Density: Clsm, [139](#)
 Density: Compressible Boussinesq, [139](#)
 Density: Concentration Average, [147](#)
 Density: Copied, [137](#)
 Density: Curing Foam, [140](#)
 Density: Exp Decay, [140](#)
 Density: Foam Time Temp, [140](#)
 Density: Fortran, [149](#)
 Density: From Bubble State, [141](#)
 Density: From Chemeq, [148](#)
 Density: From Chemeq Solids, [148](#)
 Density: From Mass Fraction, [147](#)
 Density: From Volume Fraction, [141](#)
 Density: General Ideal Gas, [142](#)
 Density: General Ideal Gas Extract Average Pressure, [142](#)
 Density: General Ideal Gas Thermodynamic Pressure, [142](#)
 Density: Ideal Gas, [143](#)
 Density: Incompressible Ideal Gas, [143](#)
 Density: Interpolated Phase Average, [144](#)
 Density: Mass Average, [146](#)
 Density: Mass Preserving, [146](#)
 Density: Mixture Fraction, [144](#)
 Density: Phase Average, [144](#)
 Density: Porous Phase Average, [148](#)
 Density: Scalar String Function, [137](#)
 Density: Single Component Adiabatic Ideal Gas, [145](#)
 Density: Single Component Ideal Gas, [145](#)
 Density: Stanford, [145](#)
 Density: Sum All Species, [149](#)
 Density: Thermal, [146](#)
 Density: User Plugin, [137](#)
 Depth Direction, [1507](#), [1510](#)
 Depth Semi Axis, [1507](#), [1511](#)
 Determine Sharing, [1200](#), [1202](#), [1211](#), [1213](#)
 Developer Command: Ngp Search, [1308](#)
 Diagnostic Control, [1382](#)
 Diagnostic Stream, [1384](#)
 diagnostics, [1381](#)
 DiagWriter, [1734](#)
 Differentiate Expression, [58](#), [61](#)
 Disable Parallel Redistribution, [1260](#), [1264](#)
 Dispersed Phase Density, [149](#)
 Dispersed Phase Density: Copied, [150](#)
 Dispersed Phase Density: Scalar String Function, [150](#)
 Dispersed Phase Density: User Plugin, [150](#)

- Dispersed Phase Momentum Stress: Newtonian, [151](#)
- Dispersed Phase Velocity, [151](#)
- Dispersed Phase Velocity: User Plugin, [151](#)
- Dispersed Phase Velocity: Vector String Function, [152](#)
- Dispersed Phase Volume Fraction, [152](#)
- Dispersed Phase Volume Fraction: Copied, [152](#)
- Dispersed Phase Volume Fraction: Scalar String Function, [153](#)
- Dispersed Phase Volume Fraction: User Plugin, [153](#)
- Display Truncation Error For, [1157](#)
- Distance Function Is Closest Receive Node To Send Centroid, [1123](#), [1125](#)
- Distance Variable, [1386](#), [1387](#)
- distinguishing conditions, [1041](#)
 - DARCY_LEAK, [1042](#)
 - ELECTROSMOTIC_VELOCITY, [1045](#)
 - KINEMATIC, [1042](#)
 - POLYNOMIAL, [1043](#)
 - WETTING_SPEED_BLAKE_LS, [1044](#)
- Distribution, [1507](#), [1511](#)
- Distribution Coefficient, [153](#)
- Distribution Coefficient: Competitive Langmuir, [155](#)
- Distribution Coefficient: Copied, [154](#)
- Distribution Coefficient: Langmuir, [155](#)
- Distribution Coefficient: Scalar String Function, [154](#)
- Distribution Coefficient: User Plugin, [154](#)
- Distribution Factor, [924](#)
- Drop Tolerance, [1198](#)

E

- Eckert Convective Coefficient, [1461](#), [1467](#)
- Edc Model Specification, [1229](#), [1662](#), [1684](#)
- Edge, [1311](#), [1315](#)
- Edge Variables, [1311](#), [1315](#)
- Effective Beam Radius, [1437](#), [1440](#), [1507](#), [1511](#)
- Effective Diffusivity: Hdiff, [155](#)
- Efficiency, [1507](#), [1511](#)
- ELASTICITY FORMULATION, [737](#)
- ELECTRIC DISPLACEMENT, [595](#)
 - BASIC, [595](#)
 - LINEAR, [595](#)
- Electric Displacement: Basic, [156](#)
- Electric Displacement: Generalized, [156](#)
- Electric Displacement: Linear, [156](#)
- Electric Traction, [800](#), [847](#), [946](#)
- ELECTRICAL CONDUCTIVITY, [591](#)
 - CONSTANT, [592](#)
 - ENCORE_FUNCTION, [592](#)
 - EXPONENTIAL, [593](#)
 - FROM_RESISTANCE, [593](#)
 - POLYNOMIAL, [593](#)
 - TBC, [594](#)
 - THERMAL, [594](#)
- Electrical Conductivity, [157](#)

- Electrical Conductivity: Arrhenius, [159](#)
- Electrical Conductivity: Bruggeman Volume Averaged, [159](#)
- Electrical Conductivity: Copied, [157](#)
- Electrical Conductivity: Electrode, [160](#)
- Electrical Conductivity: From Resistivity, [158](#)
- Electrical Conductivity: Scalar String Function, [158](#)
- Electrical Conductivity: Tbc, [158](#)
- Electrical Conductivity: Thermal, [159](#)
- Electrical Conductivity: User Plugin, [157](#)
- ELECTRICAL PERMITTIVITY, [595](#)
 - CONSTANT, [596](#)
 - ENCORE_FUNCTION, [596](#)
- Electrical Permittivity, [160](#)
- Electrical Permittivity: Copied, [161](#)
- Electrical Permittivity: Scalar String Function, [161](#)
- Electrical Permittivity: User Plugin, [161](#)
- ELECTRICAL RESISTANCE, [596](#)
 - CONSTANT, [597](#)
 - ENCORE_FUNCTION, [597](#)
 - EXPONENTIAL, [597](#)
 - FROM_CONDUCTIVITY, [598](#)
 - POLYNOMIAL, [598](#)
 - USER_FUNCTION, [599](#)
- Electrical Resistance, [162](#)
- Electrical Resistance: Copied, [162](#)
- Electrical Resistance: Scalar String Function, [163](#)
- Electrical Resistance: User Plugin, [162](#)
- Electrical Resistivity, [163](#)
- Electrical Resistivity: Copied, [163](#)
- Electrical Resistivity: From Conductivity, [164](#)
- Electrical Resistivity: Scalar String Function, [164](#)
- Electrical Resistivity: User Plugin, [164](#)
- Electromigration Coefficient, [165](#)
- Electromigration Coefficient: Copied, [165](#)
- Electromigration Coefficient: Scalar String Function, [166](#)
- Electromigration Coefficient: User Plugin, [165](#)
- Electroosmotic Velocity, [922](#)
- Element, [1312](#), [1315](#), [1325](#), [1327](#), [1334](#), [1337](#)
- ELEMENT COEFFICIENT USER SUBROUTINE, [1530](#)
- Element Death, [1074](#)
- Element Subroutine, [1428](#), [1430](#), [1437](#), [1441](#), [1499](#), [1501](#)
- Element Variable, [1499](#), [1501](#)
- Element Variables, [1312](#), [1316](#)
- Ellipsoid, [1391](#), [1393](#)
- Embedded Blocks, [1069](#)
- EMISSION, [599](#)
 - CALORE_USER_SUB, [600](#)
 - CONSTANT, [600](#)
 - ENCORE_FUNCTION, [601](#)
 - POLYNOMIAL, [601](#)
 - USER_FUNCTION, [602](#)
- Emissivity, [166](#), [1260](#), [1264](#), [1279](#), [1484](#), [1486](#)

Emissivity For Bands, [1484](#), [1487](#)
 Emissivity Fortran Subroutine, [1484](#), [1487](#)
 Emissivity Function, [1260](#), [1265](#), [1279](#), [1280](#), [1484](#), [1487](#)
 Emissivity Subroutine, [1260](#), [1265](#), [1279](#), [1280](#), [1484](#), [1488](#)
 Emissivity Time Function, [1260](#), [1266](#), [1279](#), [1280](#), [1484](#), [1488](#)
 Emissivity: Banded Wavelength, [168](#)
 Emissivity: Calore User Sub, [167](#)
 Emissivity: Copied, [166](#)
 Emissivity: Fortran, [168](#)
 Emissivity: Scalar String Function, [167](#)
 Emissivity: User Plugin, [167](#)
 Enable, [1382–1384](#)
 Enable Enthalpy Integration, [1607](#), [1611](#)
 Enable Large Ids, [1312](#), [1316](#)
 Enable Parallel Redistribution, [1260](#), [1266](#)
 ENABLE REBALANCE, [1180](#)
 Enclosing Blocks, [1069](#), [1070](#)
 Enclosure Definition, [1259](#)
 Enclosure Mbk, [169](#)
 Enclosure Mbk: Calore User Sub, [170](#)
 Enclosure Mbk: Copied, [169](#)
 Enclosure Mbk: Scalar String Function, [170](#)
 Enclosure Mbk: User Plugin, [170](#)
 Enclosure Mbl, [171](#)
 Enclosure Mbl: Calore User Sub, [172](#)
 Enclosure Mbl: Copied, [171](#)
 Enclosure Mbl: From Geometry, [173](#)
 Enclosure Mbl: Scalar String Function, [172](#)
 Enclosure Mbl: User Plugin, [172](#)
 Enclosure Radiation, [926](#), [962](#)
 Encore, [579](#), [581](#), [582](#), [587](#), [592](#), [596](#), [597](#), [601](#), [603](#), [608](#), [611](#), [618](#), [620](#), [625](#), [630](#), [634](#), [637](#), [639](#), [641](#), [644–646](#), [650](#), [651](#), [657](#), [660](#), [665](#), [668](#), [676](#), [678](#), [683](#), [690](#), [693](#), [768](#), [1054](#)
 Encore Function, [1499](#), [1501](#)
 Energy Diffusive Flux: Basic, [173](#)
 Energy Diffusive Flux: Energy Mass, [174](#)
 Energy Diffusive Flux: From Mixture Mass Diffusivity, [174](#)
 Energy Face Stabilization Scaling: Default, [174](#)
 Energy Release Units, [1599](#), [1602](#)
 Energy Releases, [1599](#), [1603](#)
 Enforcement, [1287](#), [1291](#)
 Enforcement For, [1291](#), [1295](#)
 Enforcement For Continuity = Tied Ip Continuity, [1297](#)
 Enforcement For Current = Bulter Volmer, [1297](#)
 Enforcement For Current = Conductance, [1297](#)
 Enforcement For Current = Gap Conductance, [1297](#)
 Enforcement For Current = Tied Voltage, [1298](#)
 Enforcement For Cvfem Continuity = Tied Continuity, [1298](#)
 Enforcement For Cvfem Energy = Conductance, [1298](#)

Enforcement For Cvfem Energy = Gap Conductance, [1298](#)
 Enforcement For Cvfem Energy = Tied Temperature, [1299](#)
 Enforcement For Cvfem Lumped Projection = Tied Gradp, [1299](#)
 Enforcement For Cvfem Momentum = Tied Momentum, [1299](#)
 Enforcement For Cvfem Projection = Tied Gradp, [1299](#)
 Enforcement For Cvfem Specific Dissipation Rate = Tied Sdr, [1299](#)
 Enforcement For Cvfem Turbulent Kinetic Energy = Tied Tke, [1299](#)
 Enforcement For Energy = Cht Robin, [1300](#)
 Enforcement For Energy = Conductance, [1300](#)
 Enforcement For Energy = Conductance Salgon, [1300](#)
 Enforcement For Energy = Contact Resistance, [1301](#)
 Enforcement For Energy = Gap Conductance, [1301](#)
 Enforcement For Energy = Niche Tied, [1301](#)
 Enforcement For Energy = Phase Change, [1302](#)
 Enforcement For Energy = Tied D Style Rad Temperature, [1302](#)
 Enforcement For Energy = Tied D Style Temperature, [1302](#)
 Enforcement For Energy = Tied Ip Temperature, [1303](#)
 Enforcement For Energy = Tied Temperature, [1303](#)
 Enforcement For Hfem Continuity = Tied Ip Continuity, [1303](#)
 Enforcement For Hfem Momentum = Tied Ip Momentum, [1303](#)
 Enforcement For Hfem Momentum = Tied Momentum, [1303](#)
 Enforcement For Lubrication Height = Deforming, [1304](#)
 Enforcement For Mass Balance = Bulk Node Mass Open, [1304](#)
 Enforcement For Mass Balance = Bulk Node Open, [1304](#)
 Enforcement For Mass Balance = Bulk Node Species Open, [1304](#)
 Enforcement For Mass Balance = Conserved Mass, [1305](#)
 Enforcement For Mesh = Lubrication Pressure, [1305](#)
 Enforcement For Momentum = Tied Ip Momentum, [1305](#)
 Enforcement For Momentum = Tied Momentum, [1305](#)
 Enforcement For Porous Enthalpy = Bulk Node Open, [1305](#)
 Enforcement For Porous Enthalpy = Bulk Node Open Uncoupled, [1306](#)
 Enforcement For Porous Enthalpy = Contact Resistance, [1306](#)
 Enforcement For Porous Species = Bulk Node Open All Inflow, [1306](#)
 Enforcement For Voltage = Tied Voltage, [1307](#)
 Enthalpies Of Formation, [1599](#), [1603](#)
 ENTHALPY, [602](#)

CONSTANT, 603
 ENCORE_FUNCTION, 603
 Enthalpy, 175
 Enthalpy Advection: Material Phase Sum, 178
 Enthalpy Advection: Porous, 177
 Enthalpy Advection: Porous Upwind, 177
 Enthalpy of Formation For, 1618, 1619
 Enthalpy: Cantera, 176
 Enthalpy: Copied, 175
 Enthalpy: From Temperature, 176
 Enthalpy: Mass Average, 177
 Enthalpy: Scalar String Function, 176
 Enthalpy: User Plugin, 175
 Entrance Distance: Correlation Bar, 178
 Entrance Effect Starting Node Id, 1477, 1479
 Entrance Length, 1585, 1588
 Entrance Length: Correlation, 178
 Entry Pressure, 179
 Entry Pressure: Copied, 179
 Entry Pressure: Scalar String Function, 180
 Entry Pressure: User Plugin, 179
 Epsilon Max, 1607, 1611
 Epsilon Min, 1607, 1612
 EQ BRINKMAN_MOMENTUM, 736
 EQ CHARGE_DENSITY, 726
 EQ CONTINUITY, 725
 EQ CURRENT, 726
 EQ ENERGY, 727
 EQ EXTENSION_SPEED, 728
 EQ LEVEL_SET, 727
 EQ LUBRICATION, 736
 EQ MASS_BALANCE, 728
 EQ MESH, 729
 EQ MOMENTUM, 729
 EQ POROUS_ENTHALPY, 731
 EQ POROUS_SPECIES, 730
 EQ POTENTIAL, 731
 EQ PROJECTION, 732
 EQ SOLID, 733
 EQ SP, 734
 EQ SPECIES, 733
 EQ STRESS_TENSOR_PROJECTION, 737
 EQ SUSPENSION, 735
 EQ VOLTAGE, 735
 Equation, 1429, 1430, 1448, 1452, 1484, 1488
 Ampere, 702
 Brinkman Momentum, 714
 ChargeDensity, 701
 Continuity, 695
 Current, 701
 Energy, 695
 Fluid Momentum, 698
 Lubrication, 715
 Mass Conservation, 695
 Potential Projection Equation, 716
 Solid Momentum, 699
 Species, 697
 Stress Tensor Projection, 715
 Suspension, 703
 Voltage, 700
 EQUATION OF STATE, 603
 IDEAL_GAS, 604
 Equation Of State, 1654, 1655
 Equilibrium Capillary Gap, 918
 Equilibrium Constant: Arrhenius, 180
 Equilibrium Potential, 180
 Equilibrium Potential: Copied, 181
 Equilibrium Potential: From Chemical Potential, 182
 Equilibrium Potential: Lcoo2, 183
 Equilibrium Potential: Nernst, 182
 Equilibrium Potential: Scalar String Function, 181
 Equilibrium Potential: Two Phase, 182
 Equilibrium Potential: User Plugin, 181
 Equilibrium Pressure, 183
 Equilibrium Pressure: Copied, 184
 Equilibrium Pressure: Scalar String Function, 184
 Equilibrium Pressure: User Plugin, 184
 Evaluate Expression, 58, 61
 Evaluate From, 58, 64
 Event, 1085, 1086, 1089, 1091, 1094, 1095, 1098, 1099, 1102, 1104, 1106, 1111
 exception handling, 1731
 Excess Volume, 1654, 1656
 Excess Volume Temperature, 1654, 1656
 Excess Volume Weight, 1654, 1656
 Exchange Current Density, 185
 Exchange Current Density: Copied, 185
 Exchange Current Density: Rate Constant Species, 186
 Exchange Current Density: Scalar String Function, 186
 Exchange Current Density: User Plugin, 185
 Exclude, 1312, 1316
 Exclude Ghosted, 1123, 1125
 Execute Postprocessor Group, 1085, 1087, 1090, 1092, 1094, 1096, 1098, 1100, 1102, 1104
 Exists, 1312, 1316, 1325, 1328, 1334, 1337, 1346, 1350
 Expand Box Percentage, 1069, 1070
 Expansion Coefficient, 1585, 1588
 Expert Belos Solver, 1187, 1189
 Expert Ifpack2 Preconditioner, 1188, 1190, 1191, 1194, 1197
 Exponential Vapor Cooling, 871
 Exponential Vapor Recoil Pressure, 914
 Expression
 compute_sensitivities(), 1728
 compute_values(), 1728
 postregistration_setup(), 1728
 prepare_to_recompute(), 1728
 Constructor, 1728
 Destructor, 1728

Expression Variable:, 58, 64

Expressions, 59

Extension Speed, 186

Extension Speed Diffusive Flux: Definition, 188

Extension Speed Multiplier, 188

Extension Speed Multiplier: Copied, 188

Extension Speed Multiplier: Scalar String Function, 189

Extension Speed Multiplier: User Plugin, 189

Extension Speed: Copied, 187

Extension Speed: Scalar String Function, 187

Extension Speed: User Plugin, 187

Extension Velocity, 1386, 1388

Extent Of Reaction Based On, 1599, 1603

Extrapolated Pressure, 965

F

Face, 1312, 1317, 1325, 1328, 1334, 1338

Face Field Scalar, 980

Face Stabilization Multiplier, 1662, 1664

Face Variables, 1312, 1317

facet, 1239

Facets, 1391, 1394

Fail Time Step On Bad Aztec Solver Status, 1142, 1144

Fail Time Step When Time Step Size Ratio Is Below, 1142, 1145

Failed Time Step Size Ratio, 1143, 1145

Fei Error Behavior, 1200, 1203, 1211, 1213, 1220, 1222

Fei Output Level, 1200, 1203, 1211, 1213, 1220, 1222

Field, 1423, 1424

Field Name, 1069, 1070

Field Scaling, 1429, 1431, 1499, 1502

File Cycle Count, 1346, 1351

Fill Fraction, 1198, 1199

Fill Level, 1196

Filter Nonlinear Solution, 1164

Finite Element Model, 46

First Order Upwind Factor, 1667, 1672

Fission Cross Section, 189

Fission Cross Section: Copied, 190

Fission Cross Section: Linearized, 191

Fission Cross Section: Scalar String Function, 190

Fission Cross Section: User Plugin, 190

Fixed Curvature, 993

Fixed Time, 1358, 1360

Flow Area, 191

Flow Area: Copied, 191

Flow Area: Correlation Spatial User Function, 193

Flow Area: Scalar String Function, 192

Flow Area: Spatial User Function, 192

Flow Area: User Plugin, 192

Flow Cross Sectional Area Function, 1477, 1479

Flow Hydrostatic, 801

FLOWING LIQUID VISCOSITY, 688

CONSTANT, 689

Flowing Liquid Viscosity, 193

Flowing Liquid Viscosity: Copied, 193

Flowing Liquid Viscosity: Scalar String Function, 194

Flowing Liquid Viscosity: User Plugin, 194

Fluid Beta: Correlation, 194

Fluid Density, 1477, 1480

Fluid Density Function, 1477, 1480

Fluid Density: Correlation, 195

Fluid Gamma, 1461, 1468

Fluid Gas Constant, 1461, 1468

Fluid Phase, 1585, 1588

Fluid Properties Temperature Function, 1461, 1468

Fluid Robin Coupled, 868

Fluid Robin Coupled One Region, 952, 962

Fluid Robin Coupled With Solid Convection, 865

Fluid Robin Coupled With Solid Convection One Region, 961

Fluid Solid Convection Coupled, 864

Fluid Solid Convection Coupled One Region, 963

Fluid Specific Heat Temperature Function, 1461, 1469

Fluid Temperature, 195

Fluid Temperature: Copied, 195

Fluid Temperature: Scalar String Function, 196

Fluid Temperature: User Plugin, 196

Fluid Thermal Conductivity Temperature Function, 1461, 1469

Fluid Velocity Magnitude: Correlation, 196

Fluid Viscosity, 1477, 1480

Fluid Viscosity Temperature Function, 1462, 1469

Flush Interval, 1325, 1328

Flux, 1429, 1431, 1437, 1441

Flux Encore Function, 1429, 1431

Flux Fortran Subroutine, 1429, 1431, 1437, 1441

Flux Node Variable, 1429, 1432

Flux Scale Factor, 1429, 1432

Flux Scheme, 1667, 1673

Flux Temperature Function, 1429, 1432

Flux Time Function, 1429, 1433

Flux Type, 1437, 1441

Flux Vector Node Variable, 1429, 1433

Flux Vector: Summed, 197

Force Non Tale, 1662, 1664

Forchheimer Drag Coeff, 197

Forchheimer Drag Coeff: Copied, 197

Forchheimer Drag Coeff: Scalar String Function, 198

Forchheimer Drag Coeff: User Plugin, 198

Form Factor Fortran Subroutine, 1484, 1489

Format, 1325, 1329

Fortran, 870

Fortran User Sub, 1013

Free Open Flow, 794, 809, 827, 900, 932, 947

Free Stream Reynolds Number, 1662, 1664

Freestream Density, 198

Freestream Density Altitude Function, 1462, 1469

- Freestream Density: Copied, [199](#)
- Freestream Density: Scalar String Function, [199](#)
- Freestream Density: User Plugin, [199](#)
- Freestream Gamma, [200](#)
- Freestream Pressure, [200](#), [1462](#), [1470](#)
- Freestream Pressure Altitude Function, [1462](#), [1470](#)
- Freestream Pressure Time Function, [1462](#), [1470](#)
- Freestream Pressure: Copied, [200](#)
- Freestream Pressure: Scalar String Function, [201](#)
- Freestream Pressure: User Plugin, [201](#)
- Freestream Temperature, [201](#), [1462](#), [1470](#)
- Freestream Temperature Altitude Function, [1462](#), [1471](#)
- Freestream Temperature Time Function, [1462](#), [1471](#)
- Freestream Temperature: Copied, [202](#)
- Freestream Temperature: Scalar String Function, [202](#)
- Freestream Temperature: User Plugin, [202](#)
- Freeze Element Block Solution State, [1415](#), [1416](#)
- Freeze Muscl Limiter At Global Step, [1667](#), [1673](#)
- Friction Factor, [203](#), [1585](#), [1588](#)
- Friction Factor: Copied, [203](#)
- Friction Factor: Correlation, [205](#)
- Friction Factor: Correlation Smooth Annulus, [205](#)
- Friction Factor: Correlation Smooth Tube, [205](#)
- Friction Factor: Scalar String Function, [204](#)
- Friction Factor: Smooth Annulus, [204](#)
- Friction Factor: Smooth Tube, [204](#)
- Friction Factor: User Plugin, [203](#)
- From, [1123](#), [1125](#)
- From Chemeq, [1004](#)
- From Cht Temperature, [887](#), [976](#), [985](#)
- From Cht Temperature Cpt, [797](#)
- From Mesh Displacement, [1020](#)
- From No Material Phase, [1029](#)
- From Other Phase, [1032](#)
- From Species, [1011](#)
- From Step, [1382](#), [1384](#), [1385](#)
- From Temperature, [886](#), [1025](#)
- Fuel Name, [1684](#), [1687](#)

G

- Gamma, [206](#)
- Gamma Dot, [206](#)
- Gamma Dot: Copied, [206](#)
- Gamma Dot: Scalar String Function, [207](#)
- Gamma Dot: User Plugin, [207](#)
- Gap Conductance Coefficient, [207](#)
- Gap Conductance Coefficient: Calore User Sub, [209](#)
- Gap Conductance Coefficient: Copied, [208](#)
- Gap Conductance Coefficient: Fortran, [209](#)
- Gap Conductance Coefficient: Scalar String Function, [208](#)
- Gap Conductance Coefficient: User Plugin, [208](#)
- Gap Height, [210](#)
- Gap Height: Copied, [210](#)

- Gap Height: Scalar String Function, [211](#)
- Gap Height: User Plugin, [210](#)
- Gas Phase Retardation, [211](#)
- Gas Phase Retardation: Copied, [211](#)
- Gas Phase Retardation: Scalar String Function, [212](#)
- Gas Phase Retardation: User Plugin, [212](#)
- Gauss Point Integration Order, [1123](#), [1125](#)
- Gaussian Line Power Weld, [927](#)
- Gaussian Line Weld, [925](#)
- Gaussian Ray Trace, [928](#)
- Gaussian Spot Power Weld, [882](#)
- Gaussian Spot Weld, [881](#)
- Gdsw Equation Solver, [1220](#)
- Gdsw Version, [1220](#), [1222](#)
- General Chemistry, [1618](#)
- Generalized Nat Conv, [867](#), [873](#), [877](#), [895](#), [967](#)
- Generalized Rad, [878](#), [894](#), [961](#), [967](#)
- Generic: Constant, [751](#)
- Generic: Encore Function, [752](#)
- Generic: Exponential, [755](#)
- Generic: Global, [752](#)
- Generic: Polynomial, [753](#)
- Generic: User Field, [754](#)
- Generic: User Function, [753](#)
- Geometric Tolerance, [1248](#), [1249](#)
- Get Global From Region, [1496](#), [1497](#)
- Glass Transition Temperature, [212](#)
- Glass Transition Temperature: Copied, [213](#)
- Glass Transition Temperature: Debenedeto, [214](#)
- Glass Transition Temperature: Scalar String Function, [213](#)
- Glass Transition Temperature: User Plugin, [213](#)
- Global, [1312](#), [1317](#), [1325](#), [1329](#), [1334](#), [1338](#)
- Global Constants, [55](#)
- Global Id Mapping Backward Compatibility, [46](#), [48](#)
- Global Operator, [1496](#), [1497](#)
- Global Variables, [1312](#), [1318](#)
- Gmres Solver, [1187](#), [1191](#)
- Gnielinski Film Gradient Correction: Correlation, [214](#)
- Goma, [23](#)
- Gravitational Constant, [1585](#), [1589](#)
- Gravitational Constant: Correlation, [214](#)
- Gravity Vector, [55](#), [56](#)
- Green strain, [717](#)
- Green-Lagrange strain, [717](#)

H

- Hausen Entrance Effect Correction: Correlation, [215](#)
- Hdiff Flux: Constant Cl, [215](#)
- Hdiff Model Specification, [1229](#), [1662](#)
- Heartbeat, [1325](#), [1359](#)
- HEAT CONDUCTION, [604](#)
 - BASIC, [604](#)
 - CONVECTED_ENTHALPY, [605](#)
 - FOURIERS_LAW, [605](#)

GENERALIZED, [605](#)
 THERMOELECTRIC, [606](#)
 Heat Conduction: Basic, [217](#)
 Heat Conduction: Convected Enthalpy, [216](#)
 Heat Conduction: Fouriers Law, [217](#)
 Heat Conduction: Generalized, [215](#)
 Heat Conduction: Mass Diffusion Energy Transport, [218](#)
 Heat Conduction: Phase Average, [216](#)
 Heat Conduction: Porous Diffusive Enthalpy Flux, [218](#)
 Heat Conduction: Porous Simplified Diffusive Enthalpy Flux, [218](#)
 Heat Conduction: Radiative Flux, [217](#)
 Heat Conduction: Thermoelectric, [216](#)
 Heat Flux Boundary Condition, [1428](#)
 HEAT OF VAPORIZATION, [606](#)
 CONSTANT, [606](#)
 Heat Of Vaporization, [219](#)
 Heat Of Vaporization: Copied, [219](#)
 Heat Of Vaporization: Scalar String Function, [220](#)
 Heat Of Vaporization: User Plugin, [219](#)
 HEAT TRANSFER COEFFICIENT, [607](#)
 CALORE_USER_SUB, [607](#)
 CONSTANT, [608](#)
 ENCORE_FUNCTION, [608](#)
 POLYNOMIAL, [608](#)
 USER_FUNCTION, [609](#)
 Heat Transfer Coefficient, [220](#)
 Heat Transfer Coefficient: Aero, [222](#)
 Heat Transfer Coefficient: Calore User Sub, [221](#)
 Heat Transfer Coefficient: Copied, [220](#)
 Heat Transfer Coefficient: Correlation, [223](#)
 Heat Transfer Coefficient: Fortran, [222](#)
 Heat Transfer Coefficient: Scalar String Function, [221](#)
 Heat Transfer Coefficient: User Plugin, [221](#)
 Heat Transfer Correlation Coefficient, [1584](#)
 Heats of Reaction, [1618](#), [1620](#)
 Hemicube Max Subdivides, [1248](#), [1250](#)
 Hemicube Min Separation, [1248](#), [1250](#)
 Hemicube Resolution, [1248](#), [1250](#)
 History Output, [1334](#), [1359](#)
 Hybrid Upwind Factor, [1667](#), [1673](#)
 Hydraulic Diameter, [223](#)
 Hydraulic Diameter Function, [1477](#), [1480](#)
 Hydraulic Diameter: Copied, [224](#)
 Hydraulic Diameter: Correlation, [225](#)
 Hydraulic Diameter: Correlation Spatial User Function, [225](#)
 Hydraulic Diameter: Scalar String Function, [224](#)
 Hydraulic Diameter: Spatial User Function, [225](#)
 Hydraulic Diameter: User Plugin, [224](#)
 Hydrogen Advection Velocity: Hdiff, [226](#)
 Hydrogen Diffusion Supg Tau: Shakib, [226](#)
 Hydrostatic Pressure, [227](#)
 Hydrostatic Pressure: Copied, [227](#)

Hydrostatic Pressure: Scalar String Function, [228](#)
 Hydrostatic Pressure: User Plugin, [227](#)

I

IC CIRC_X, [745](#)
 IC CIRC_Y, [745](#)
 IC CONSTANT, [745](#)
 IC COUETTE_SH, [747](#)
 IC COUETTE_X, [746](#)
 IC COUETTE_Y, [746](#)
 IC LINEAR, [748](#)
 IC PARAB, [749](#)
 IC READ_FILE, [747](#)
 Ideal Gas Constant, [55](#), [56](#)
 Ignition Threshold Temperature, [1684](#), [1687](#)
 Ignore Coordinate Displacements, [1662](#), [1665](#)
 Ignore Flux Coverage, [1429](#), [1433](#), [1448](#), [1452](#), [1484](#), [1489](#)
 Ilu Fill, [1200](#), [1203](#), [1211](#), [1214](#)
 Ilu Omega, [1211](#), [1214](#)
 Ilu Threshold, [1200](#), [1204](#), [1211](#), [1214](#)
 Implicit Les Filter Scale, [1679](#), [1681](#)
 Include, [1312](#), [1318](#)
 Include All Blocks, [51](#), [52](#)
 Incremental Number Of Steps, [1107](#), [1108](#)
 Indicatemarkadapt, [1085](#), [1087](#), [1090](#), [1092](#), [1094](#), [1096](#), [1098](#),
[1100](#), [1102](#), [1104](#)
 Induction Time Constant, [228](#)
 Induction Time Constant: Copied, [228](#)
 Induction Time Constant: Scalar String Function, [229](#)
 Induction Time Constant: User Plugin, [229](#)
 Inflow, [830](#), [838](#), [885](#), [912](#)
 Inflow Outflow, [950](#)
 Influx Vector Node Variable, [1429](#), [1434](#)
 Initial Condition, [1420](#)
 Initial Deltat, [1107](#), [1108](#), [1111](#)
 Initial Mixture Molecular Weight, [1654](#), [1657](#)
 Initial Nonlinear Residual Tolerance For Time Step Control,
[1143](#), [1145](#)
 Initial Offset Distance, [1386](#), [1388](#)
 Initial Porosity, [229](#)
 Initial Porosity: Copied, [230](#)
 Initial Porosity: Scalar String Function, [230](#)
 Initial Porosity: User Plugin, [230](#)
 Initial Pressure, [1403](#), [1406](#), [1654](#), [1657](#)
 Initial Scale Factor, [1386](#), [1388](#)
 Initial Temperature, [1403](#), [1407](#), [1477](#), [1481](#)
 Initial Time Step Size, [1143](#), [1146](#)
 Initial Value, [1496](#), [1498](#)
 Initialize, [1084](#), [1106](#)
 Input Database Name, [1260](#), [1266](#), [1346](#), [1351](#)
 Input_Output Region, [1358](#)
 Integer, [742](#), [743](#)
 Integer Data, [1291](#), [1295](#), [1423](#), [1424](#), [1429](#), [1434](#), [1437](#), [1442](#),
[1448](#), [1452](#), [1484](#), [1489](#), [1499](#), [1502](#)

Integrate Advection By Parts, 1678
 Integrated, 1507, 1512
 Integrated Flux Output, 1260, 1267, 1429, 1434, 1437, 1442, 1448, 1453, 1462, 1471, 1484, 1489
 Integrated Power Output, 1260, 1267, 1429, 1435, 1437, 1442, 1448, 1453, 1462, 1472, 1485, 1490, 1499, 1502, 1507, 1512
 INTEGRATION RULE, 739
 Intensity Diffusion: Spherical Harmonic, 231
 Interaction, 1287, 1307
 Interaction Defaults, 1288
 Interaction Output, 1069, 1070
 Interface, 805, 814, 864, 905, 912, 943
 Interface Courant Limit, 1143, 1146
 interfacial tension, *see* SURFACE TENSION
 INTERNAL ENERGY, 610
 ENCORE_FUNCTION, 611
 GAS_PHASE, 611
 Internal Energy, 231
 Internal Energy: Copied, 231
 Internal Energy: Gas Phase, 232
 Internal Energy: Scalar String Function, 232
 Internal Energy: User Plugin, 232
 Interphase Area, 233
 Interphase Area: Copied, 233
 Interphase Area: Scalar String Function, 234
 Interphase Area: User Plugin, 233
 Interphase Friction Coefficient: Wen Yu, 234
 Interpolate, 1123, 1126
 Interpolate Density And Velocity Separately In Mass Flux Vector, 1667, 1674
 Interpolation Function, 1123, 1126
 INTRINSIC PERMEABILITY, 610
 CONSTANT, 610
 Intrinsic Permeability, 234
 Intrinsic Permeability Scaling, 238
 Intrinsic Permeability Scaling: Copied, 238
 Intrinsic Permeability Scaling: Forchheimer, 240
 Intrinsic Permeability Scaling: Kozeny, 239
 Intrinsic Permeability Scaling: Scalar String Function, 239
 Intrinsic Permeability Scaling: T Exponent, 240
 Intrinsic Permeability Scaling: User Plugin, 239
 Intrinsic Permeability: Carmen Kozeny, 237
 Intrinsic Permeability: Diagonal, 235
 Intrinsic Permeability: Log Reordered Adagio, 236
 Intrinsic Permeability: Reordered Adagio, 235
 Intrinsic Permeability: Tensor String Function, 237
 Intrinsic Permeability: Tensor String Function Symmetric, 238
 Intrinsic Permeability: Volume Average, 236
 Intrinsic Permeability: Young And Todd, 236
 Inv Neutron Velocity, 241
 Inv Neutron Velocity: Copied, 241
 Inv Neutron Velocity: Scalar String Function, 242

Inv Neutron Velocity: User Plugin, 242
 Inversion Aversion Exponent, 51, 52
 Inversion Aversion Stiffness, 51, 52
 Inversion Aversion Transition Jacobian, 51, 53
 Involve, 1090, 1092, 1094, 1096, 1098, 1100, 1102, 1104, 1106, 1107, 1112
 Irradiation, 242
 Irradiation Node Variable, 1485, 1490
 Irradiation Subroutine, 1485, 1490
 Irradiation Time Function, 1485, 1491
 Irradiation: Calore User Sub, 244
 Irradiation: Copied, 243
 Irradiation: Scalar String Function, 243
 Irradiation: User Plugin, 243
 Isobaric Compressibility, 244
 Isobaric Compressibility: Copied, 244
 Isobaric Compressibility: Scalar String Function, 245
 Isobaric Compressibility: User Plugin, 245

J

Jacobi Preconditioner, 1188, 1190, 1191, 1194, 1199
 Joule Heating, 1499, 1503

K

K Factor, 245
 K Factor: Copied, 246
 K Factor: Scalar String Function, 246
 K Factor: User Plugin, 246
 K-E Turbulence Model Parameter, 55, 56
 K-W Turbulence Model Parameter, 55, 56
 Kinematic, 816, 820, 828, 836, 854, 903, 921, 933, 938, 959, 975, 987
 Kinematic Viscosity, 1585, 1589
 Kinematic Viscosity: Correlation, 247
 Kluz Solver, 1187, 1194
 Known Time Discontinuities, 1143, 1146
 Kuntz, 809

L

Labels, 1325, 1329
 Lag Nodal Pressure Gradient In Mass Flux Vector
 Expression, 1667, 1674
 Lag Nodal Tau In Mass Flux Vector Expression, 1667, 1674
 Lagrangian strain, 717
 Lamé coefficients, 718
 Lambda Brooks Corey, 247
 Lambda Brooks Corey: Copied, 247
 Lambda Brooks Corey: Scalar String Function, 248
 Lambda Brooks Corey: User Plugin, 248
 Laminar Correlation, 1585, 1589
 Laminar Correlation Heat Transfer Coefficient: Correlation, 248
 Laser Heat Flux Boundary Condition, 1437

Laser Heating, [1507](#)
 Laser Power, [249](#)
 Laser Power: Copied, [249](#)
 Laser Power: Scalar String Function, [250](#)
 Laser Power: User Plugin, [249](#)
 Laser Weld, [880](#)
 Latent Heat, [250](#), [853](#), [872](#)
 Latent Heat: Copied, [250](#)
 Latent Heat: Porous Phase Specific Average, [251](#)
 Latent Heat: Scalar String Function, [251](#)
 Latent Heat: User Plugin, [251](#)
 Legend, [1325](#), [1329](#)
 Lens, [875](#)
 Lens Deposition, [859](#)
 Lens Particles Pressure, [802](#)
 Les Turbulence Model Parameter, [55](#), [57](#)
 Level Set, [252](#)
 Level Set Curvature, [253](#)
 Level Set Curvature: Copied, [253](#)
 Level Set Curvature: Scalar String Function, [254](#)
 Level Set Curvature: User Plugin, [254](#)
 Level Set Diffusive Flux, [255](#)
 Level Set Diffusive Flux: Shock Capturing, [254](#)
 Level Set Diffusive Flux: Unit Gradient, [255](#)
 LEVEL SET HEAVISIDE, [612](#)
 SMOOTH, [612](#)
 Level Set Heaviside, [255](#)
 Level Set Heaviside: Bf Interpolated, [257](#)
 Level Set Heaviside: Copied, [256](#)
 Level Set Heaviside: Interpolated, [257](#)
 Level Set Heaviside: Scalar String Function, [256](#)
 Level Set Heaviside: Sharp Analytic, [258](#)
 Level Set Heaviside: Smooth, [257](#)
 Level Set Heaviside: User Plugin, [256](#)
 Level Set Interface, [1386](#)
 Level Set Normal Bulk Conductivity, [258](#)
 Level Set Normal Bulk Conductivity: Copied, [258](#)
 Level Set Normal Bulk Conductivity: Inverse Volume Average, [259](#)
 Level Set Normal Bulk Conductivity: Scalar String Function, [259](#)
 Level Set Normal Bulk Conductivity: User Plugin, [259](#)
 Level Set Normal Bulk Conductivity: Volume Average, [260](#)
 Level Set Normal Conductivity, [260](#)
 Level Set Normal Conductivity: Copied, [260](#)
 Level Set Normal Conductivity: Scalar String Function, [261](#)
 Level Set Normal Conductivity: User Plugin, [261](#)
 Level Set Tangential Bulk Conductivity, [262](#)
 Level Set Tangential Bulk Conductivity: Copied, [262](#)
 Level Set Tangential Bulk Conductivity: Inverse Volume Average, [261](#)
 Level Set Tangential Bulk Conductivity: Scalar String Function, [263](#)
 Level Set Tangential Bulk Conductivity: User Plugin, [263](#)
 Level Set Tangential Bulk Conductivity: Volume Average, [262](#)
 Level Set Tangential Conductivity, [263](#)
 Level Set Tangential Conductivity: Copied, [264](#)
 Level Set Tangential Conductivity: Scalar String Function, [264](#)
 Level Set Tangential Conductivity: User Plugin, [264](#)
 LEVEL SET WIDTH, [612](#)
 CONSTANT, [613](#)
 Level Set Width, [265](#)
 Level Set: Copied, [252](#)
 Level Set: Scalar String Function, [253](#)
 Level Set: User Plugin, [252](#)
 Light Speed, [55](#), [57](#)
 Limit Solution Increment, [1143](#), [1147](#)
 Limit Turbulent Ke Production, [1679](#), [1681](#)
 Liquid Phase Retardation, [265](#)
 Liquid Phase Retardation: Copied, [265](#)
 Liquid Phase Retardation: Scalar String Function, [266](#)
 Liquid Phase Retardation: User Plugin, [266](#)
 load balancing, [1180](#)
 Local Coordinate System, [51](#), [53](#), [1398](#), [1400](#)
 log file, [1363](#)
 Log Preexponential Factors, [1600](#), [1604](#)
 logging, [1363](#), [1381](#), [1734](#)
 Low Reynolds, [857](#), [989](#)
 Ls Capillary, [792](#), [891](#), [917](#), [940](#)
 Ls Capillary Stabilization, [794](#), [819](#), [900](#)
 Ls Oriented Slip, [915](#)
 Lubrication Height, [266](#)
 LUBRICATION HEIGHT LOWER, [613](#)
 CONSTANT, [613](#)
 Lubrication Height Lower, [268](#)
 Lubrication Height Lower: Copied, [268](#)
 Lubrication Height Lower: Scalar String Function, [269](#)
 Lubrication Height Lower: User Plugin, [269](#)
 LUBRICATION HEIGHT UPPER, [613](#)
 CONSTANT, [614](#)
 Lubrication Height Upper, [269](#)
 Lubrication Height Upper: Copied, [270](#)
 Lubrication Height Upper: Scalar String Function, [270](#)
 Lubrication Height Upper: User Plugin, [270](#)
 Lubrication Height: Combined, [268](#)
 Lubrication Height: Copied, [267](#)
 Lubrication Height: Scalar String Function, [267](#)
 Lubrication Height: User Plugin, [267](#)
 LUBRICATION K, [614](#)
 CONSTANT, [614](#)
 PRANDTL_MIXING, [615](#)
 Lubrication K, [271](#)
 Lubrication K: Copied, [271](#)

- Lubrication K: Scalar String Function, [272](#)
- Lubrication K: User Plugin, [271](#)
- Lubrication Pressure, [272](#)
- Lubrication Pressure: Copied, [272](#)
- Lubrication Pressure: Scalar String Function, [273](#)
- Lubrication Pressure: User Plugin, [273](#)
- LUBRICATION VELOCITY LOWER, [615](#)
 - CONSTANT, [615](#)
- Lubrication Velocity Lower, [273](#)
- Lubrication Velocity Lower: User Plugin, [274](#)
- Lubrication Velocity Lower: Vector String Function, [274](#)
- LUBRICATION VELOCITY UPPER, [616](#)
 - CONSTANT, [616](#)
- Lubrication Velocity Upper, [274](#)
- Lubrication Velocity Upper: User Plugin, [275](#)
- Lubrication Velocity Upper: Vector String Function, [275](#)

M

- Mach Number, [275](#), [1462](#), [1472](#)
- Mach Number Time Function, [1462](#), [1472](#)
- Mach Number: Copied, [276](#)
- Mach Number: Scalar String Function, [276](#)
- Mach Number: User Plugin, [276](#)
- Magnetic Field Flux: Remanent, [277](#)
- Magnetic Flux Intensity, [277](#)
- Magnetic Flux Intensity: Copied, [277](#)
- Magnetic Flux Intensity: Scalar String Function, [278](#)
- Magnetic Flux Intensity: User Plugin, [278](#)
- Magnetic Flux Stress: Grad B, [278](#)
- Magnetic Flux Stress: Grad Div B, [279](#)
- Magnetic Flux Stress: Magnetic Pressure, [279](#)
- Magnetic Permeability, [279](#)
- Magnetic Permeability: Copied, [279](#)
- Magnetic Permeability: Scalar String Function, [280](#)
- Magnetic Permeability: User Plugin, [280](#)
- Magnetic Potential Stress: Grad A, [280](#)
- Magnetic Potential Stress: Voltage, [281](#)
- Magnetic Pressure, [281](#)
- Magnetic Pressure: Copied, [281](#)
- Magnetic Pressure: Scalar String Function, [282](#)
- Magnetic Pressure: User Plugin, [282](#)
- Magnetic Relative Permeability, [282](#)
- Magnetic Relative Permeability: Copied, [283](#)
- Magnetic Relative Permeability: Scalar String Function, [283](#)
 - [283](#)
- Magnetic Relative Permeability: User Plugin, [283](#)
- Magnetization, [284](#)
- Magnetization: User Plugin, [284](#)
- Magnetization: Vector String Function, [284](#)
- Mark, [1085](#), [1087](#), [1090](#), [1093](#), [1094](#), [1097](#), [1098](#), [1101](#), [1102](#), [1105](#)
- Markadapt, [1085](#), [1088](#), [1090](#), [1093](#), [1094](#), [1097](#), [1098](#), [1101](#), [1102](#), [1105](#)
- Masked Nat Conv, [869](#)

- Masking, [285](#)
- Masking: Copied, [285](#)
- Masking: Scalar String Function, [286](#)
- Masking: User Plugin, [285](#)
- Mass Average, [1019](#)
- Mass Balance Advective Flux: Porous, [286](#)
- Mass Balance Advective Flux: Porous Upwind, [286](#)
- Mass Balance Advective Flux: Single Phase, [287](#)
- Mass Balance Diffusive Flux: Basic, [288](#)
- Mass Balance Diffusive Flux: Density, [288](#)
- Mass Balance Diffusive Flux: Nernst Planck, [287](#)
- Mass Balance Diffusive Flux: Porous, [287](#)
- Mass Diffusivity, [288](#)
- Mass Diffusivity: Air Water, [290](#)
- Mass Diffusivity: Arrhenius, [291](#)
- Mass Diffusivity: Cantera, [290](#)
- Mass Diffusivity: Chapman Enskog, [291](#)
- Mass Diffusivity: Copied, [289](#)
- Mass Diffusivity: From Schmidt, [290](#)
- Mass Diffusivity: Scalar String Function, [289](#)
- Mass Diffusivity: User Plugin, [289](#)
- Mass Flow Rate, [1477](#), [1481](#)
- Mass Flow Rate Function, [1477](#), [1481](#)
- Mass Fluid Robin Coupled, [953](#)
- MASS FLUX, [616](#)
 - DARCY, [617](#)
- Mass Flux, [796](#), [809](#), [896](#), [919](#), [930](#), [948](#), [963](#), [978](#)
- Mass Flux From Temperature, [897](#)
- Mass Flux: Darcy, [291](#)
- Mass Fraction, [292](#)
- Mass Fraction Diffusive Flux: Basic, [294](#)
- Mass Fraction Diffusive Flux: Energy Mass, [294](#)
- Mass Fraction Fluid Robin Coupled, [952](#)
- Mass Fraction Fluid Robin Coupled One Region, [951](#)
- Mass Fraction: Copied, [292](#)
- Mass Fraction: Fracbal, [293](#)
- Mass Fraction: From Chemeq, [293](#)
- Mass Fraction: From Density, [294](#)
- Mass Fraction: Scalar String Function, [293](#)
- Mass Fraction: User Plugin, [292](#)
- Mass Open, [846](#)
- Mass_Fraction, [1688](#), [1689](#)
- Master, [1035](#), [1036](#)
- Matched Flux On, [1260](#), [1267](#)
- Material, [51](#), [53](#), [1403](#), [1407](#)
- Material =, [51](#), [53](#)
- Material Data Block: Resource, [295](#)
- MATLAB, interfacing, [1730](#)
- Matrix Format, [1200](#), [1204](#), [1211](#), [1214](#)
- Matrix Output, [1186](#), [1187](#)
- Matrix Reduction, [1200](#), [1204](#), [1211](#), [1215](#)
- Matrix Scaling, [1186](#), [1188](#), [1200](#), [1205](#), [1211](#), [1215](#)
- Matrix Viewer, [1200](#), [1205](#), [1211](#), [1215](#)
- Max Degrees, [1437](#), [1443](#)

Max Feature Size On Surfaces, [1386](#), [1388](#)
 Maximum Acceptable Linear Residual Ratio, [1143](#), [1147](#)
 Maximum Accepted Nonlinear Correction, [1165](#)
 Maximum Accepted Nonlinear Residual, [1165](#)
 Maximum Consecutive Time Step Failures, [1143](#), [1147](#)
 Maximum Global Var Limit, [1143](#), [1148](#)
 Maximum Iterations, [1188](#), [1189](#), [1191–1195](#), [1200](#), [1205](#), [1211](#),
 [1216](#), [1221](#), [1223](#), [1254](#), [1255](#), [1257](#), [1258](#)
 Maximum Line Search Steps, [1165](#)
 Maximum Linear Residual Ratio, [1143](#), [1148](#)
 Maximum Nonlinear Iterations, [1165](#)
 MAXIMUM NUMBER OF REBALANCES, [1181](#)
 Maximum Number Of Rebalances, [1158](#)
 Maximum Pressure Solve Iterations, [1477](#), [1481](#)
 Maximum Search Tolerance, [1477](#), [1482](#)
 Maximum Solution Limit, [1143](#), [1148](#)
 Maximum Substeps, [1607](#), [1612](#), [1646](#), [1647](#)
 Maximum Temperature Allowed From Temperature
 Extraction, [1662](#), [1665](#)
 Maximum Time Step Size, [1143](#), [1149](#)
 Maximum Time Step Size Ratio, [1143](#), [1149](#)
 Maximum Wall Time, [1662](#), [1665](#)
 Mean Beam Length, [1260](#), [1268](#)
 Melt Temperature, [295](#)
 Melt Temperature: Copied, [295](#)
 Melt Temperature: Scalar String Function, [296](#)
 Melt Temperature: User Plugin, [296](#)
 Melting, [861](#)
 Melting Capillary Darcy, [1011](#)
 memory analysis, [1729](#)
 Mesh, [1391](#), [1394](#)
 mesh
 annealing, [749](#)
 Mesh Body Acceleration, [296](#)
 Mesh Body Acceleration: User Plugin, [297](#)
 Mesh Body Acceleration: Vector String Function, [297](#)
 MESH GROUP, [740](#)
 MESH LAMBDA, [617](#)
 CONSTANT, [618](#)
 CONVERTED, [618](#)
 ENCORE_FUNCTION, [618](#)
 Mesh Lambda, [297](#)
 Mesh Lambda: Converted, [299](#)
 Mesh Lambda: Converted Plane Stress, [299](#)
 Mesh Lambda: Copied, [298](#)
 Mesh Lambda: Elemental Volume, [299](#)
 Mesh Lambda: Inverse Element Volume, [300](#)
 Mesh Lambda: Scalar String Function, [298](#)
 Mesh Lambda: User Plugin, [298](#)
 Mesh Poissons Ratio, [300](#)
 Mesh Poissons Ratio: Copied, [300](#)
 Mesh Poissons Ratio: Scalar String Function, [301](#)
 Mesh Poissons Ratio: User Plugin, [301](#)
 MESH STRESS, [620](#)
 ISOTHERMAL, [621](#)
 LAME, [623](#)
 LINEAR_ELASTIC, [621](#)
 NEOHOOKEAN_ELASTIC, [622](#)
 NONLINEAR_ELASTIC, [622](#)
 RESIDUAL, [623](#)
 THERMAL, [623](#)
 Mesh Stress, [301](#)
 Mesh Stress: Electrode Old, [306](#)
 Mesh Stress: Isothermal, [303](#)
 Mesh Stress: Lamé, [308](#)
 Mesh Stress: Linear Elastic, [304](#)
 Mesh Stress: Mooney Rivlin, [305](#)
 Mesh Stress: Neohookean Elastic, [305](#)
 Mesh Stress: Nonlinear Elastic, [305](#)
 Mesh Stress: Porous Effective, [304](#)
 Mesh Stress: Residual, [306](#)
 Mesh Stress: Saturation Weighted Porous Effective, [304](#)
 Mesh Stress: Species, [307](#)
 Mesh Stress: Species Anisotropic, [308](#)
 Mesh Stress: Species Transversely Isotropic, [307](#)
 Mesh Stress: Tensor String Function, [302](#)
 Mesh Stress: Tensor String Function Symmetric, [303](#)
 Mesh Stress: Thermal, [306](#)
 Mesh Stress: User Plugin, [302](#)
 MESH TWO MU, [619](#)
 CONSTANT, [619](#)
 CONVERTED, [620](#)
 ENCORE_FUNCTION, [620](#)
 Mesh Two Mu, [309](#)
 Mesh Two Mu: Converted, [310](#)
 Mesh Two Mu: Copied, [309](#)
 Mesh Two Mu: Elemental Volume, [310](#)
 Mesh Two Mu: Faux Plasticity, [311](#)
 Mesh Two Mu: Inverse Element Volume, [311](#)
 Mesh Two Mu: Scalar String Function, [310](#)
 Mesh Two Mu: User Plugin, [309](#)
 Mesh Velocity, [311](#)
 Mesh Velocity: User Plugin, [312](#)
 Mesh Velocity: Vector String Function, [312](#)
 Mesh Youngs Modulus, [312](#)
 Mesh Youngs Modulus: Copied, [313](#)
 Mesh Youngs Modulus: Faux Plasticity, [314](#)
 Mesh Youngs Modulus: Melting Jamming Porous, [314](#)
 Mesh Youngs Modulus: Scalar String Function, [313](#)
 Mesh Youngs Modulus: User Plugin, [313](#)
 Meshed Enclosure, [1260](#), [1268](#)
 Method, [1254](#), [1255](#)
 Minimum Chemistry Timestep, [1607](#), [1612](#)
 Minimum Concentration For, [1608](#), [1612](#)
 Minimum Global Var Limit, [1143](#), [1150](#)
 Minimum Nonlinear Solves, [1166](#)
 Minimum Product Fraction, [1684](#), [1687](#)
 Minimum Resolved Time Step Size, [1143](#), [1150](#)

Minimum Solution Limit, [1143](#), [1150](#)
 Minimum Step Size, [1646](#), [1647](#)
 Minimum Temperature Allowed From Temperature
 Extraction, [1662](#), [1666](#)
 Minimum Time Step Size, [1143](#), [1151](#)
 Mixed, [862](#)
 Mixture Density, [314](#)
 Mixture Density: Copied, [315](#)
 Mixture Density: Scalar String Function, [315](#)
 Mixture Density: User Plugin, [315](#)
 Mixture Fraction, [316](#)
 Mixture Fraction Diffusive Flux: Basic, [317](#)
 Mixture Fraction Diffusivity, [317](#)
 Mixture Fraction Diffusivity: Copied, [318](#)
 Mixture Fraction Diffusivity: From Schmidt, [319](#)
 Mixture Fraction Diffusivity: Scalar String Function, [318](#)
 Mixture Fraction Diffusivity: User Plugin, [318](#)
 Mixture Fraction: Copied, [316](#)
 Mixture Fraction: Scalar String Function, [317](#)
 Mixture Fraction: User Plugin, [316](#)
 Mixture Mass Diffusivity, [319](#)
 Mixture Mass Diffusivity: Copied, [319](#)
 Mixture Mass Diffusivity: Mixture Average, [320](#)
 Mixture Mass Diffusivity: Scalar String Function, [320](#)
 Mixture Mass Diffusivity: User Plugin, [320](#)
 Mixture Molecular Weight, [321](#)
 Mixture Molecular Weight: Cantera, [322](#)
 Mixture Molecular Weight: Copied, [321](#)
 Mixture Molecular Weight: Mass Average, [322](#)
 Mixture Molecular Weight: Mole Average, [323](#)
 Mixture Molecular Weight: Scalar String Function, [322](#)
 Mixture Molecular Weight: User Plugin, [321](#)
 Mole_Fraction, [1688](#), [1689](#)
 MOLECULAR WEIGHT, [624](#)
 CONSTANT, [624](#)
 ENCORE_FUNCTION, [625](#)
 Molecular Weight, [323](#)
 Molecular Weight: Cantera, [324](#)
 Molecular Weight: Copied, [323](#)
 Molecular Weight: Dynamic Species, [325](#)
 Molecular Weight: Scalar String Function, [324](#)
 Molecular Weight: User Plugin, [324](#)
 Momentum Face Stabilization Scaling: Default, [325](#)
 MOMENTUM STRESS, [625](#)
 FORMAL_NEWTONIAN, [627](#)
 INCOMPRESSIBLE_NEWTONIAN, [626](#)
 LS_CAPILLARY, [626](#)
 MAXWELL, [628](#)
 NEWTONIAN_DILATIONAL, [627](#)
 NEWTONIAN_PRESSURE, [628](#)
 NEWTONIAN_VISCOUS, [627](#)
 Momentum Stress: Bad Sensitivity, [325](#)
 Momentum Stress: Balanced Force, [325](#)
 Momentum Stress: Formal Newtonian, [326](#)

Momentum Stress: Grad Div, [326](#)
 Momentum Stress: Incompressible Newtonian, [326](#)
 Momentum Stress: Lorentz, [329](#)
 Momentum Stress: Ls Capillary, [327](#)
 Momentum Stress: Ls Implicit Capillary, [327](#)
 Momentum Stress: Ls Implicit Normal Capillary, [327](#)
 Momentum Stress: Maxwell, [329](#)
 Momentum Stress: Mckenzie, [329](#)
 Momentum Stress: Newtonian Dilational, [328](#)
 Momentum Stress: Newtonian Pressure, [328](#)
 Momentum Stress: Newtonian Viscous, [328](#)
 Momentum Stress: Suspension, [327](#)
 Monitor, [1325](#), [1330](#)
 Motion Specification, [1387](#)
 Muelu Preconditioner, [1188](#), [1190](#), [1191](#), [1194](#), [1198](#)
 Muscl Limiter, [1668](#), [1674](#)

N

Narrow Band Element Size Multiplier, [1386](#), [1389](#)
 Narrow Band Width, [1386](#), [1389](#), [1390](#)
 Nat Conv, [810](#), [813](#), [854](#), [895](#)
 Nat E, [972](#)
 Neutron, [330](#)
 Neutron Diffusion: Basic, [331](#)
 Neutron Diffusion: Ficks Law, [331](#)
 Neutron Diffusivity, [332](#)
 Neutron Diffusivity: Copied, [332](#)
 Neutron Diffusivity: Five Ten, [333](#)
 Neutron Diffusivity: Scalar String Function, [333](#)
 Neutron Diffusivity: User Plugin, [332](#)
 Neutron: Copied, [330](#)
 Neutron: Scalar String Function, [331](#)
 Neutron: User Plugin, [330](#)
 Newton Temperature Solve, [1618](#), [1624](#)
 No Slip, [836](#), [889](#), [920](#), [970](#)
 Nodal, [1312](#), [1318](#), [1325](#), [1330](#), [1334](#), [1338](#)
 Nodal Variable, [1499](#), [1503](#)
 Nodal Variables, [1312](#), [1318](#)
 Nodal_Id, [1342](#), [1343](#)
 Nodal_Location, [1342](#), [1343](#)
 Node, [1312](#), [1319](#), [1325](#), [1330](#), [1334](#), [1338](#)
 Node Normal Capillary, [991](#)
 Node Subroutine, [1420](#), [1421](#), [1423](#), [1425](#)
 NODE USER SUBROUTINE, [1528](#)
 Node Variables, [1312](#), [1319](#)
 Nodes Outside Region, [1123](#), [1127](#)
 Nodeset, [1312](#), [1319](#), [1325](#), [1330](#), [1334](#), [1339](#)
 Nodeset Variables, [1312](#), [1319](#)
 Non Ibp Pressure, [802](#)
 Nonblocking Surfaces, [1260](#), [1268](#)
 Nonlinear, [1090](#), [1094](#), [1102](#)
 Nonlinear Correction Ratio Tolerance, [1166](#)
 Nonlinear Correction Scaling, [1166](#)
 Nonlinear Correction Tolerance, [1167](#)

Nonlinear Relaxation Factor, [1167](#)
 Nonlinear Residual Minimum Convergence Rate, [1167](#)
 Nonlinear Residual Ratio Tolerance, [1168](#)
 Nonlinear Residual Scaling, [1168](#)
 Nonlinear Residual Tolerance, [1168](#)
 Nonlinear Solution Strategy, [1169](#)
 Nonwetting Phase Retardation, [333](#)
 Nonwetting Phase Retardation: Copied, [334](#)
 Nonwetting Phase Retardation: Scalar String Function, [334](#)
 Nonwetting Phase Retardation: User Plugin, [334](#)
 Normal Capillary Stabilization, [793](#), [819](#), [898](#)
 Normal Tolerance, [1307](#)–[1309](#)
 Nucleation Time, [1618](#), [1621](#)
 Num Levels, [1200](#), [1205](#), [1211](#), [1216](#)
 Number Of Adaptivity Steps, [1107](#), [1109](#), [1112](#)
 Number Of Reactions, [1600](#), [1604](#), [1618](#), [1621](#)
 Number Of Rotations, [1248](#), [1251](#)
 Number Of Steps, [1107](#), [1109](#), [1112](#)
 Number Of Sweeps, [1197](#), [1199](#), [1200](#)

O

Ode Solver, [1608](#), [1613](#), [1646](#), [1648](#)
 Offset Time, [1358](#), [1360](#)
 Omit Block, [46](#), [49](#)
 Omit Diffusion Term From Sucv Tau, [1668](#), [1675](#)
 Omit Disting Bc Ip Sensitivities, [1668](#), [1675](#)
 Omit Dt Term From Sucv Tau, [1668](#), [1675](#)
 Omit Enthalpy Adjustment After Temperature Clipping, [1662](#), [1666](#)
 Omit Finite Difference Sensitivities For Cantera Properties, [1662](#), [1666](#)
 Omit Finite Difference Sensitivity Due To Utau, [1679](#), [1682](#)
 Omit Sensitivities In Turbulent Production Term, [1679](#), [1682](#)
 Omit Sensitivities To Turbulent Production From Ke Source Only, [1679](#), [1682](#)
 Omit Velocity Divergence In Turbulent Production Term, [1679](#), [1682](#)
 Omit Volume, [46](#), [49](#)
 One Temp Multiphase Open, [868](#)
 Open, [798](#), [811](#), [818](#), [843](#), [866](#), [923](#)
 Open Adv Flow, [814](#), [817](#), [826](#), [828](#), [833](#), [842](#), [892](#), [905](#), [908](#), [931](#), [949](#), [956](#), [957](#), [978](#), [996](#)
 Open Adv Flow From Temperature, [893](#)
 Open Adv Pen Flow, [908](#)
 Open Circuit Voltage, [335](#)
 Open Circuit Voltage: Electrode Object, [336](#)
 Open Circuit Voltage: User Plugin, [335](#)
 Open Circuit Voltage: Vector String Function, [335](#)
 Open Flow, [799](#), [813](#), [832](#), [845](#), [846](#), [885](#), [888](#), [901](#), [912](#), [996](#), [1000](#)
 Open Flow Convection, [812](#)

Open Flow Darcy, [992](#)
 Open Nc Adv Flow, [909](#)
 Opposed Normal Threshold Angle, [1287](#), [1289](#)
 optimization, [1728](#)
 Optional, [1346](#), [1351](#)
 Ordinate, [58](#), [65](#)
 Ordinate Offset, [58](#), [65](#)
 Ordinate Scale, [59](#), [65](#)
 Oriented Slip, [914](#)
 Origin, [1398](#), [1399](#)
 Orthog Method, [1211](#), [1216](#)
 Outflow, [951](#)
 Output, [1085](#), [1088](#), [1090](#), [1093](#), [1094](#), [1097](#), [1098](#), [1101](#), [1102](#), [1105](#), [1112](#)
 output, [1363](#), [1381](#)
 Output Database Name, [1260](#), [1269](#), [1346](#), [1352](#)
 Output Mesh, [1312](#), [1320](#)
 Output On Signal, [1312](#), [1320](#), [1325](#), [1331](#), [1334](#), [1339](#), [1346](#), [1352](#)
 Output Rule, [1248](#), [1251](#), [1254](#), [1256](#), [1257](#), [1259](#), [1287](#), [1289](#)
 Output To File, [1342](#), [1345](#)
 Overlapping Enclosure, [1260](#), [1269](#)
 Overlay Count, [1346](#), [1352](#)
 Overwrite, [1312](#), [1320](#), [1335](#), [1339](#), [1347](#), [1353](#)
 Oxidizer Mixture Specification, [1684](#), [1688](#)

P

Pairwise Monte Carlo Sample Rule, [1248](#), [1251](#)
 Pairwise Monte Carlo Toli, [1248](#), [1252](#)
 Pairwise Monte Carlo Tol2, [1248](#), [1252](#)
 Pairwise Number Of Monte Carlo Samples, [1248](#), [1252](#)
 Pairwise Number Of Visibility Samples, [1248](#), [1253](#)
 Pairwise Visibility Sample Rule, [1248](#), [1253](#)
 Param-Bool, [1200](#), [1206](#)
 Param-Int, [1200](#), [1206](#), [1211](#), [1216](#), [1221](#), [1223](#)
 Param-Real, [1200](#), [1206](#), [1211](#), [1217](#), [1221](#), [1223](#)
 Param-String, [1200](#), [1207](#), [1211](#), [1217](#), [1221](#), [1224](#)
 Parameters For, [1084](#), [1107](#)
 Parameters For Aria Region, [1107](#), [1142](#)
 Parameters For Block, [46](#), [51](#)
 Parameters For Chemeq Model, [1599](#)
 Parameters For Phase, [46](#)
 Parameters For Surface, [46](#)
 Parametric Tolerance, [1342](#), [1344](#)
 Partial Enclosure Area, [336](#), [1260](#), [1269](#)
 Partial Enclosure Area Subroutine, [1260](#), [1270](#)
 Partial Enclosure Area Time Function, [1260](#), [1270](#)
 Partial Enclosure Area: Calore User Sub, [338](#)
 Partial Enclosure Area: Copied, [337](#)
 Partial Enclosure Area: Scalar String Function, [337](#)
 Partial Enclosure Area: User Plugin, [337](#)
 Partial Enclosure Emissivity, [338](#), [1260](#), [1270](#)
 Partial Enclosure Emissivity Subroutine, [1260](#), [1270](#)
 Partial Enclosure Emissivity Time Function, [1260](#), [1271](#)

Partial Enclosure Emissivity: Calore User Sub, 339
 Partial Enclosure Emissivity: Copied, 338
 Partial Enclosure Emissivity: Scalar String Function, 339
 Partial Enclosure Emissivity: User Plugin, 339
 Partial Enclosure Flux Output, 1260, 1271
 Partial Enclosure Irradiance Output, 1260, 1271
 Partial Enclosure Radiosity Output, 1260, 1272
 Partial Enclosure Temperature, 340, 1260, 1272
 Partial Enclosure Temperature Subroutine, 1260, 1272
 Partial Enclosure Temperature Time Function, 1260, 1272
 Partial Enclosure Temperature: Calore User Sub, 341
 Partial Enclosure Temperature: Copied, 340
 Partial Enclosure Temperature: Scalar String Function, 341
 Partial Enclosure Temperature: User Plugin, 341
 Partial Molar Volume, 342
 Partial Molar Volume: Copied, 342
 Partial Molar Volume: Scalar String Function, 343
 Partial Molar Volume: User Plugin, 343
 Path Function, 1437, 1443, 1507, 1512
 Path Radius, 1437, 1443
 Peltier Coefficient, 343
 Peltier Coefficient: Copied, 344
 Peltier Coefficient: Scalar String Function, 344
 Peltier Coefficient: User Plugin, 344
 Penetration Depth, 1507, 1513
 Percentage Asymptotics, 1608, 1613
 Perform Initial Redistance, 1386, 1389
 performance tuning, 1728
 Period, 1415, 1416
 Periodic, 1035
 Periodicity Time, 1358, 1361
 permeability
 intrinsic, 610
 relative, 638
 Phase, 51, 54
 Phase Change Relaxation Factor, 1156
 PHASE CHANGE SPECIFIC HEAT, 663
 Phase Change Specific Heat, 345
 Phase Change Specific Heat: Calore User Sub, 345
 Phase Change Specific Heat: Curing Foam, 346
 Phase Change Specific Heat: Scalar String Function, 345
 Phi, 346
 Phi: Copied, 347
 Phi: Scalar String Function, 347
 Phi: User Plugin, 347
 PID
 source, 1049, 1051
 Pid Controlled, 984
 Pid Controlled Bidirectional, 979
 Pid Controlled Cooler, 983
 Piola-Kirchhoff stress, 718
 Planck Constant, 55, 57
 Plane, 1391, 1394
 Plastic Strain, 348
 Plastic Strain: Copied, 348
 Plastic Strain: Scalar String Function, 349
 Plastic Strain: User Plugin, 348
 Point, 1399
 Point On Axis, 1035, 1036
 POINT SOURCE FOR ..., 1046
 Poisson's ratio, 718
 POISSONS RATIO, 629
 CONSTANT, 629
 ENCORE_FUNCTION, 630
 Polymerization Shift Factor, 349
 Polymerization Shift Factor: Copied, 349
 Polymerization Shift Factor: Scalar String Function, 350
 Polymerization Shift Factor: User Plugin, 350
 Polymerization Shift Factor: Wlf, 350
 Polynomial Order, 1200, 1207, 1211, 1218
 POROSITY, 630
 CONSTANT, 630
 DEFORMING, 631
 POLYNOMIAL, 631
 ROCK_COMPRESSIBLE, 631
 Porosity, 351, 1585, 1589
 porosity, 703
 Porosity Def, 355
 Porosity Def: Copied, 355
 Porosity Def: Deforming, 356
 Porosity Def: Scalar String Function, 356
 Porosity Def: User Plugin, 356
 Porosity: Constant From Electrode Object Old, 354
 Porosity: Coussy, 353
 Porosity: Deformable Rock Compressible, 352
 Porosity: Deforming, 351
 Porosity: From Density Ratio, 353
 Porosity: From Volume Fraction Gas, 354
 Porosity: Mesh Deforming, 351
 Porosity: Modified Kozeny, 354
 Porosity: One Minus Volume Fractions, 353
 Porosity: Rock Compressible, 352
 Porosity: Scalar String Function, 355
 Porosity: Solid Deforming, 352
 porous flow, 602, 610, 616, 630, 638, 643, 644, 646, 676
 Porous Flow Options, 1229, 1663, 1678
 Porous Flow System: Air Water, 358
 Porous Flow System: Co2 Brine Salt, 358
 Porous Flow System: Mixed Single Phase, 357
 Porous Flow System: Single Phase, 357
 Porous Flow System: Two Phase Immiscible, 357
 Porous Robin Averaged Coeff, 954
 Porous Robin Coupled, 817, 898
 Porous Robin Coupled One Region, 807, 955
 Porous Robin Coupled With Solid Phase Convection, 806

Porous Robin Coupled With Solid Phase Convection One Region, 806
 Porous Robin Interface, 889
 Porous Robin One Region, 863, 890
 Post Deactivation Gas Release, 1608, 1613
 Post Deactivation Heat Release, 1608, 1614
 Post Deactivation Release Time, 1608, 1614
 Post Process, 1228, 1230
 Post Process Flux, 1228, 1230
 Post Process Mass, 1228, 1230
 Post Process Nodal, 1228, 1231
 Post Process Volume, 1228, 1231
 Postprocess, 1228, 1234
 Potential, 358
 Potential: Copied, 359
 Potential: Scalar String Function, 359
 Potential: User Plugin, 359
 Power, 1437, 1443, 1507, 1513
 Power Encore Function, 1437, 1444, 1507, 1513
 Power Time Function, 1437, 1444, 1507, 1513
 Pp: Cvfem Yplus, 362
 Pp: Fluid Traction, 360
 Pp: Mesh Traction, 361
 Pp: Mesh Von Mises, 360
 Pp: Solid Traction, 361
 Pp: Solid Von Mises, 360
 Pp: Surface Normal Shell, 362
 Pp: Turbulent Kinetic Energy Source, 362
 Pp: Vector Mean Curvature, 363
 Pp: Viscous Traction, 361
 Pp: Yplus, 362
 Prandtl Number, 363, 1585, 1590
 Prandtl Number: Copied, 363
 Prandtl Number: Correlation, 365
 Prandtl Number: General, 364
 Prandtl Number: Scalar String Function, 364
 Prandtl Number: User Plugin, 364
 Precision, 1325, 1331
 Preconditioner Subdomain Overlap, 1200, 1207, 1211, 1218
 Preconditioning Method, 1201, 1208, 1211, 1218
 Preconditioning Steps, 1201, 1208, 1211, 1218
 Precursor Concentration, 365
 Precursor Concentration: Copied, 365
 Precursor Concentration: Scalar String Function, 366
 Precursor Concentration: User Plugin, 366
 Precursor Conservation, 366
 Precursor Conservation: Copied, 367
 Precursor Conservation: Scalar String Function, 367
 Precursor Conservation: User Plugin, 367
 Predictor Fields, 1158
 Predictor Order, 1143, 1151
 Predictor-Corrector Begin After Step, 1143, 1152
 Predictor-Corrector Field Normalization, 1143, 1152
 Predictor-Corrector Normalization, 1143, 1153
 Predictor-Corrector Tolerance, 1143, 1153
 Preexponential Factors, 1618, 1620
 Preprocess Enclosures, 1260, 1273, 1282
 Preset Solver, 1187, 1192
 Pressure, 368, 902, 944, 971, 1600, 1604
 Pressure Bc, 1477, 1482
 Pressure Darcy, 803
 Pressure Exponents, 1600, 1604
 Pressure Solve Tolerance, 1477, 1482
 PRESSURE STABILIZATION, 738
 Pressure Stabilization Characteristic Length, 1668, 1675
 Pressure Stabilization Order, 1668, 1675
 Pressure Stabilization Parameter Scaling, 1668, 1676
 Pressure Stabilization Scaling, 1668, 1676
 Pressure Unit, 1654, 1657
 Pressure User Function, 849, 902, 944
 Pressure: Copied, 368
 Pressure: Copy Phase All, 369
 Pressure: Equation Of State, 371
 Pressure: From Capillary Pressure, 371
 Pressure: From Ideal Gas Density, 371
 Pressure: From No Material Phase, 369
 Pressure: From Other Material Phase, 370
 Pressure: Ideal Gas, 370
 Pressure: Pressurization Model, 370
 Pressure: Scalar String Function, 369
 Pressure: User Plugin, 368
 Pressurization Model, 1654
 Pressurization Source Blocks, 1655, 1657
 Pressurized Blocks, 1655, 1658
 Pressurized Bulk Nodes, 1655, 1658
 print mask, 1381
 Print Timer Information Every, 55
 profiling, 1728
 Projected Capillary, 801
 Projected Level Set Curvature, 372
 Projected Level Set Curvature: Copied, 372
 Projected Level Set Curvature: Scalar String Function, 373
 Projected Level Set Curvature: User Plugin, 372
 Projected Pressure Gradient, 373
 Projected Pressure Gradient: User Plugin, 373
 Projected Pressure Gradient: Vector String Function, 374
 Projected Pressure Stab Tau, 374
 Projected Pressure Stab Tau: Copied, 374
 Projected Pressure Stab Tau: Scalar String Function, 375
 Projected Pressure Stab Tau: User Plugin, 375
 Property, 1312, 1321, 1335, 1340, 1347, 1353
 PSPG, 738
 Pspg, 965, 994
 PSPP, 738
 Purify, 1729
 Pyrolysis, 815, 820, 829, 855, 858, 883, 937, 974

R

- Rad, [796](#), [853](#), [877](#)
- RADIATION FORM FACTOR, [632](#)
 - CALORE_USER_SUB, [632](#)
 - CONSTANT, [633](#)
 - ENCORE_FUNCTION, [634](#)
 - POLYNOMIAL, [633](#)
 - USER_FUNCTION, [634](#)
- Radiation Form Factor, [375](#), [1485](#), [1491](#)
- Radiation Form Factor Subroutine, [1485](#), [1491](#)
- Radiation Form Factor Temperature Function, [1485](#), [1492](#)
- Radiation Form Factor Time Function, [1485](#), [1492](#)
- Radiation Form Factor: Calore User Sub, [377](#)
- Radiation Form Factor: Copied, [376](#)
- Radiation Form Factor: Fortran, [377](#)
- Radiation Form Factor: Scalar String Function, [376](#)
- Radiation Form Factor: User Plugin, [376](#)
- RADIATIVE CONDUCTIVITY, [635](#)
 - CHEMEQ_FOAM, [636](#)
 - CONSTANT, [635](#)
 - ENCORE_FUNCTION, [637](#)
 - OPTICALLY_THICK, [636](#)
 - POLYNOMIAL, [637](#)
 - USER_FUNCTION, [638](#)
- Radiative Conductivity, [378](#)
- Radiative Conductivity: Chemeq Foam, [380](#)
- Radiative Conductivity: Copied, [378](#)
- Radiative Conductivity: Optically Thick, [379](#)
- Radiative Conductivity: Scalar String Function, [379](#)
- Radiative Conductivity: User Plugin, [378](#)
- Radiative Conductivity: Volume Average, [379](#)
- Radiative Flux Boundary Condition, [1484](#)
- Radiosity Database Name, [1260](#), [1273](#)
- Radiosity Solver, [1257](#)
- Random, [1391](#), [1394](#)
- Rate Limiter Factor, [1608](#), [1614](#)
- Rate Multiplier, [1600](#), [1605](#)
- Reaction, [1600](#)
- Reaction Rate Model, [1600](#), [1605](#)
- Reaction Rate Multiplier, [380](#)
- Reaction Rate Multiplier: Copied, [380](#)
- Reaction Rate Multiplier: Electrode Object, [382](#)
- Reaction Rate Multiplier: One Minus Gas Volume Fraction, [381](#)
- Reaction Rate Multiplier: Scalar String Function, [381](#)
- Reaction Rate Multiplier: User Plugin, [381](#)
- Reaction Rate Multiplier: Vitrification, [382](#)
- Reaction Rate Subroutine, [1600](#), [1605](#)
- REACTION RATE USER SUBROUTINE, [1544](#)
- Reaction Time Scale, [1684](#), [1687](#)
- Read Variable, [1496](#), [1498](#)
- Real, [742](#), [743](#)
- Real Data, [1291](#), [1296](#), [1423](#), [1425](#), [1429](#), [1435](#), [1437](#), [1444](#), [1448](#), [1453](#), [1485](#), [1492](#), [1500](#), [1503](#)
- rebalance, [1180](#)
- REBALANCE LOAD MEASURE, [1181](#)
- REBALANCE TIME STEP FREQUENCY, [1182](#)
- Receive Blocks, [1123](#)
- Recession, [815](#), [821](#), [829](#), [834](#), [856](#), [858](#), [932](#), [937](#), [975](#), [988](#)
- Reciprocity Rule, [1254](#), [1256](#)
- Reconstructed Curvature, [992](#)
- Redistance Method, [1386](#), [1389](#)
- Ref Temp Convective Coefficient Subroutine, [1448](#), [1454](#)
- REF TEMPERATURE HEAT TRANSFER COEFFICIENT USER SUBROUTINE, [1534](#)
- Reference, [1684](#), [1688](#)
- Reference Axis, [1035](#), [1036](#)
- Reference Density, [1462](#), [1473](#)
- Reference Htc, [1462](#), [1473](#)
- Reference Pressure, [1600](#), [1605](#)
- Reference Temperature, [1448](#), [1454](#), [1462](#), [1473](#), [1485](#), [1492](#)
- Reference Temperature Fortran Subroutine, [1448](#), [1454](#), [1485](#), [1493](#)
- Reference Temperature Global Variable, [1448](#), [1454](#), [1485](#), [1493](#)
- Reference Temperature Node Variable, [1448](#), [1455](#)
- Reference Temperature Subroutine, [1448](#), [1455](#), [1485](#), [1493](#)
- Reference Temperature Temperature Function, [1448](#), [1455](#), [1485](#), [1493](#)
- Reference Temperature Time Function, [1448](#), [1456](#), [1462](#), [1473](#), [1485](#), [1494](#)
- Reinitialize Dof, [1404](#), [1407](#)
- Reinitialize Every Step, [1386](#), [1390](#)
- Reinitialize Transient, [1107](#), [1109](#), [1112](#)
- RELATIVE PERMEABILITY, [638](#)
 - CONSTANT, [639](#)
 - ENCORE_FUNCTION, [639](#)
 - POLYNOMIAL, [640](#)
- Relative Permeability, [383](#)
- Relative Permeability: Brooks Corey, [387](#)
- Relative Permeability: Copied, [383](#)
- Relative Permeability: Mass Average, [385](#)
- Relative Permeability: Scalar String Function, [384](#)
- Relative Permeability: T Exponent, [384](#)
- Relative Permeability: Udell Cubic Gas, [385](#)
- Relative Permeability: Udell Cubic Liquid, [386](#)
- Relative Permeability: User Plugin, [383](#)
- Relative Permeability: Van Genuchten Gas, [385](#)
- Relative Permeability: Van Genuchten Liquid, [386](#)
- Relative Permeability: Volume Average, [384](#)
- Relative Tolerance, [1608](#), [1614](#), [1646](#), [1648](#)
- Remove Block, [51](#), [54](#)
- Reordering, [1196](#), [1198](#), [1199](#)
- Reservoir Depth, [387](#)
- Reservoir Depth: Copied, [388](#)
- Reservoir Depth: Scalar String Function, [388](#)
- Reservoir Depth: User Plugin, [388](#)
- Reset Initial Time Step Size, [1143](#), [1154](#)

- Reset On, [1496](#), [1498](#)
- Residual Norm Scaling, [1201](#), [1208](#), [1211](#), [1219](#)
- Residual Norm Tolerance, [1201](#), [1208](#), [1211](#), [1219](#), [1221](#), [1224](#)
- Residual Saturation, [389](#)
- Residual Saturation: Copied, [389](#)
- Residual Saturation: Scalar String Function, [390](#)
- Residual Saturation: User Plugin, [389](#)
- Residual Scaling, [1188](#), [1189](#), [1191–1195](#)
- residual stress, [718](#)
- Resistive Load, [960](#)
- Restart, [1347](#), [1353](#)
- Restart Data, [1346](#), [1359](#)
- Restart Iterations, [1191](#), [1192](#), [1201](#), [1209](#), [1211](#), [1219](#)
- Restart Time, [1347](#), [1354](#), [1356](#)
- Restriction Parts, [1342](#), [1345](#)
- Results Output, [1311](#), [1359](#)
- Retardation, [392](#)
- Retardation: Copied, [392](#)
- Retardation: Gas Phase Distributed, [390](#)
- Retardation: Liquid Phase Distributed, [391](#)
- Retardation: Nonwetting Phase Distributed, [391](#)
- Retardation: Saturated Distributed, [390](#)
- Retardation: Scalar String Function, [393](#)
- Retardation: User Plugin, [392](#)
- Retardation: Wetting Phase Distributed, [391](#)
- Reynolds Number, [393](#), [1585](#), [1590](#)
- Reynolds Number: Copied, [393](#)
- Reynolds Number: Correlation, [395](#)
- Reynolds Number: General, [394](#)
- Reynolds Number: Scalar String Function, [394](#)
- Reynolds Number: User Plugin, [394](#)
- Roe Entropy Fix C, [1668](#), [1676](#)
- Roe Entropy Fix U, [1668](#), [1676](#)
- Rotation Axis Vector, [1437](#), [1444](#)
- Row Ordering, [1201](#), [1209](#)
- Rowsum Database Name, [1261](#), [1274](#)
- Rt Pressure Darcy, [803](#)
- Rte Field, [983](#)
- Rte Sp, [982](#)

S

- Saturated Retardation, [395](#)
- Saturated Retardation: Copied, [395](#)
- Saturated Retardation: Scalar String Function, [396](#)
- Saturated Retardation: User Plugin, [396](#)
- Saturation, [396](#)
- Saturation: Copied, [397](#)
- Saturation: From Other Phase, [398](#)
- Saturation: Scalar String Function, [397](#)
- Saturation: User Plugin, [397](#)
- Saturation: Van Genuchten, [398](#)
- SAVE RESIDUALS, [739](#)
- Scalar String Function, [797](#), [808](#), [811](#), [812](#), [822](#), [826](#), [830](#), [831](#), [833](#), [835](#), [838](#), [839](#), [842](#), [843](#), [846](#), [847](#), [852](#), [855](#), [856](#),

- [860](#), [863](#), [867](#), [884](#), [886](#), [889](#), [907](#), [911](#), [913](#), [919](#), [923](#), [930](#), [931](#), [933](#), [935](#), [936](#), [939](#), [947](#), [950](#), [953](#), [955](#), [956](#), [959](#), [964](#), [966](#), [972](#), [976](#), [977](#), [987–989](#), [993](#), [994](#), [1000](#), [1002](#), [1004](#), [1007](#), [1010](#), [1014–1016](#), [1020](#), [1022](#), [1025](#), [1027](#), [1029](#), [1031](#), [1032](#)

- Scale By, [59](#), [66](#)
- Scaled Convective Coefficient Subroutine, [1448](#), [1456](#)
- SCALED ELEMENT COEFFICIENT USER SUBROUTINE, [1532](#)
- Scaled Nat Conv, [872](#)
- Scaled Ref Temp Convective Coefficient Subroutine, [1448](#), [1456](#)
- SCALED REF TEMPERATURE HEAT TRANSFER COEFFICIENT USER SUBROUTINE, [1536](#)
- Scaling, [398](#)
- Scaling Time Function, [1429](#), [1435](#), [1500](#), [1503](#)
- Scaling With Global Variable, [1429](#), [1436](#), [1500](#), [1504](#)
- Scaling: Copied, [399](#)
- Scaling: Scalar String Function, [399](#)
- Scaling: User Plugin, [399](#)
- Scattering Coefficient, [400](#)
- Scattering Coefficient: Copied, [400](#)
- Scattering Coefficient: Scalar String Function, [401](#)
- Scattering Coefficient: User Plugin, [400](#)
- Scattering Cross Section, [401](#)
- Scattering Cross Section: Calore User Sub, [402](#)
- Scattering Cross Section: Copied, [401](#)
- Scattering Cross Section: Scalar String Function, [402](#)
- Scattering Cross Section: User Plugin, [402](#)
- Schloegl, [1007](#)
- Schmidt Number, [403](#)
- Schmidt Number: Copied, [403](#)
- Schmidt Number: Scalar String Function, [404](#)
- Schmidt Number: User Plugin, [404](#)
- Search, [1287](#), [1289](#)
- Search Coordinate Field, [1123](#), [1127](#)
- Search Geometric Tolerance, [1123](#), [1128](#)
- Search Interval, [1477](#), [1483](#)
- Search Method, [1069](#), [1071](#), [1308](#), [1309](#), [1342](#), [1345](#)
- Search Options, [1288](#), [1308](#)
- Search Surface Gap Tolerance, [1123](#), [1128](#)
- Search Tolerance, [1035](#), [1037](#), [1069](#), [1071](#)
- Search Type, [1123](#), [1129](#)
- SEEBECK COEFFICIENT, [640](#)
 - CONSTANT, [640](#)
 - ENCORE_FUNCTION, [641](#)
 - POLYNOMIAL, [641](#)
 - USER_FUNCTION, [642](#)
- Seebeck Coefficient, [404](#)
- Seebeck Coefficient: Copied, [405](#)
- Seebeck Coefficient: Scalar String Function, [405](#)
- Seebeck Coefficient: User Plugin, [405](#)
- Segregated Global Minimum Convergence Rate, [1161](#)

Segregated Global Nonlinear Initial Residual Tolerance, [1161](#)
 Segregated Global Nonlinear Number Of Steps, [1161](#)
 Segregated Global Nonlinear Relative Residual Tolerance, [1162](#)
 Segregated Global Nonlinear Residual Tolerance, [1162](#)
 Segregated Global Nonlinear Target Number Of Steps Per Time Step, [1162](#)
 Select Fei, [1201](#), [1210](#), [1212](#), [1220](#)
 Select One Receiver For Each Send Object, [1123](#), [1129](#)
 Select One Unique Receiver For Each Send Object, [1123](#), [1129](#)
 Send, [1123](#), [1130](#)
 Send Block, [1123](#), [1130](#)
 Send Blocks, [1123](#)
 Send Field, [1123](#), [1130](#)
 Sequential, [1085](#), [1102](#)
 Set Information Stream Path, [1382](#), [1384](#), [1385](#)
 Sgs Preconditioner, [1188](#), [1190](#), [1191](#), [1194](#), [1197](#)
 Shared Ownership Rule, [1201](#), [1209](#), [1211](#), [1219](#)
 Sharp Line Weld, [878](#)
 Sharp Spot Weld, [879](#)
 Shear Free, [850](#), [946](#)
 shear modulus, [718](#)
 Shell Lofting Factor, [406](#)
 Shell Lofting Factor: Copied, [406](#)
 Shell Lofting Factor: Element Attribute, [407](#)
 Shell Lofting Factor: Scalar String Function, [407](#)
 Shell Lofting Factor: User Plugin, [406](#)
 SHELL THICKNESS, [643](#)
 CONSTANT, [643](#)
 ELEMENT_ATTRIBUTE, [643](#)
 Shell Thickness, [407](#)
 Shell Thickness: Copied, [408](#)
 Shell Thickness: Element Attribute, [409](#)
 Shell Thickness: Scalar String Function, [408](#)
 Shell Thickness: User Plugin, [408](#)
 Sideset, [1312](#), [1321](#)
 Sideset Variables, [1312](#), [1321](#)
 Simple Dp Interp, [824](#), [958](#)
 Simple Inflow, [831](#), [865](#), [884](#), [911](#)
 Simple Interp, [799](#), [805](#), [818](#), [825](#), [832](#), [840](#), [918](#), [939](#), [954](#), [973](#), [974](#), [976](#), [993](#)
 Simple Interp Tensor, [906](#), [997](#)
 Simple Interp Vector, [907](#), [997](#)
 Simple Max Feature Size On Surfaces, [1387](#), [1390](#)
 Simple Spring Force, [840](#)
 Simulation Max Global Iterations, [1085](#), [1088](#), [1113](#)
 Simulation Start Time, [1085](#), [1088](#), [1113](#)
 Simulation Termination Time, [1085](#), [1089](#), [1113](#)
 SKELETON DENSITY, [643](#)
 CONSTANT, [644](#)
 ENCORE_FUNCTION, [644](#)
 Skeleton Density, [409](#)
 Skeleton Density: Copied, [409](#)
 Skeleton Density: Scalar String Function, [410](#)
 Skeleton Density: User Plugin, [410](#)
 Skeleton Enthalpy: Cpt, [410](#)
 SKELETON INTERNAL ENERGY, [644](#)
 CONSTANT, [645](#)
 ENCORE_FUNCTION, [645](#)
 LINEAR, [645](#)
 Skeleton Internal Energy, [411](#)
 Skeleton Internal Energy: Copied, [411](#)
 Skeleton Internal Energy: Cpt, [412](#)
 Skeleton Internal Energy: Linear, [412](#)
 Skeleton Internal Energy: Scalar String Function, [412](#)
 Skeleton Internal Energy: User Plugin, [411](#)
 SKELETON SPECIFIC HEAT, [646](#)
 CONSTANT, [646](#)
 ENCORE_FUNCTION, [646](#)
 POLYNOMIAL, [647](#)
 USER_FUNCTION, [647](#)
 Skeleton Specific Heat, [413](#)
 Skeleton Specific Heat: Copied, [413](#)
 Skeleton Specific Heat: Scalar String Function, [414](#)
 Skeleton Specific Heat: User Plugin, [413](#)
 Skin All Blocks, [1287](#), [1290](#)
 Slave, [1035](#), [1037](#)
 Slave Variable, [1291](#), [1296](#)
 Slip, [916](#)
 Slip Length, [904](#), [916](#)
 Slope Of Time Step Size, [1143](#), [1154](#)
 Smoothed Capillary, [793](#)
 Solid Body Acceleration, [414](#)
 Solid Body Acceleration: User Plugin, [414](#)
 Solid Body Acceleration: Vector String Function, [415](#)
 Solid Density, [415](#)
 Solid Density: Copied, [415](#)
 Solid Density: Scalar String Function, [416](#)
 Solid Density: User Plugin, [416](#)
 SOLID LAMBDA, [648](#)
 CONSTANT, [649](#)
 CONVERTED, [649](#)
 ENCORE_FUNCTION, [650](#)
 Solid Lambda, [416](#)
 Solid Lambda: Converted, [418](#)
 Solid Lambda: Converted Plane Stress, [418](#)
 Solid Lambda: Copied, [417](#)
 Solid Lambda: Scalar String Function, [417](#)
 Solid Lambda: User Plugin, [417](#)
 Solid Poissons Ratio, [418](#)
 Solid Poissons Ratio: Copied, [419](#)
 Solid Poissons Ratio: Scalar String Function, [419](#)
 Solid Poissons Ratio: User Plugin, [419](#)
 Solid Pressure Gradient: Gidaspow, [420](#)
 SOLID STRESS, [652](#)
 ISOTHERMAL, [652](#)

- LAME, [655](#)
- LINEAR_ELASTIC, [653](#)
- NEOHOOKEAN_ELASTIC, [653](#)
- NONLINEAR_ELASTIC, [654](#)
- RESIDUAL, [654](#)
- THERMAL, [654](#)
- Solid Stress, [420](#)
- Solid Stress: Incompressible Newtonian, [424](#)
- Solid Stress: Isothermal, [422](#)
- Solid Stress: Lame, [426](#)
- Solid Stress: Linear Elastic, [422](#)
- Solid Stress: Mooney Rivlin, [423](#)
- Solid Stress: Neohookean Elastic, [424](#)
- Solid Stress: Nonlinear Elastic, [424](#)
- Solid Stress: Porous Effective, [423](#)
- Solid Stress: Residual, [424](#)
- Solid Stress: Saturation Weighted Porous Effective, [423](#)
- Solid Stress: Species, [425](#)
- Solid Stress: Species Anisotropic, [426](#)
- Solid Stress: Species Transversely Isotropic, [425](#)
- Solid Stress: Tensor String Function, [421](#)
- Solid Stress: Tensor String Function Symmetric, [422](#)
- Solid Stress: Thermal, [425](#)
- Solid Stress: User Plugin, [421](#)
- SOLID TWO MU, [650](#)
 - CONSTANT, [651](#)
 - CONVERTED, [651](#)
 - ENCORE_FUNCTION, [651](#)
- Solid Two Mu, [427](#)
- Solid Two Mu: Converted, [428](#)
- Solid Two Mu: Copied, [427](#)
- Solid Two Mu: Scalar String Function, [428](#)
- Solid Two Mu: User Plugin, [427](#)
- Solid Youngs Modulus, [428](#)
- Solid Youngs Modulus: Copied, [429](#)
- Solid Youngs Modulus: Scalar String Function, [429](#)
- Solid Youngs Modulus: User Plugin, [429](#)
- Solidification, [861](#)
- Solution Control, [1132](#)
- Solution Control Description, [1084](#)
- Solution Method, [1201](#), [1210](#), [1212](#), [1220](#)
- Solution Options, [1228](#), [1662](#)
- Solve Pressure, [1477](#), [1483](#)
- Solve Transpose, [1201](#), [1210](#)
- Solver, [1257](#), [1259](#)
- Solver Name, [1655](#), [1658](#)
- Solver Type, [1192](#), [1193](#)
- Soret Coefficient, [430](#)
- Soret Coefficient: Copied, [430](#)
- Soret Coefficient: Scalar String Function, [431](#)
- Soret Coefficient: User Plugin, [430](#)
- Sound Speed, [431](#)
- Source Direction Vector, [1437](#), [1445](#)
- SOURCE FOR CURRENT, [1060](#)
- BUTLER_VOLMER_SIMPLE, [1060](#)
- ELECTRODE_OBJECT, [1061](#)
- POLYNOMIAL, [1061](#)
- SOURCE FOR ENERGY, [1048](#)
- CALORE_USER_SUB, [1048](#)
- CHEMEQ_HEATING, [1049](#)
- COMPRESSIVE_WORK, [1052](#)
- CONSTANT, [1053](#)
- CURING_FOAM_HEAT_OF_RXN, [1053](#)
- CURING_FOAM_LATENT_HEAT, [1053](#)
- CURING_FOAM_SPECIFIC_HEAT, [1054](#)
- ELECTRODE_OBJECT, [1057](#)
- ENCORE_FUNCTION, [1054](#)
- JOULE_HEATING, [1055](#)
- MELTING, [1052](#)
- PID_CONTROLLED, [1049](#)
- PID_CONTROLLED_BIDIRECTIONAL, [1051](#)
- PID_CONTROLLED_COOLER, [1051](#)
- POLYNOMIAL, [1056](#)
- TBC_JOULE_HEATING, [1056](#)
- USER_FUNCTION, [1057](#)
- VISCOUS DISSIPATION, [1057](#)
- SOURCE FOR MESH, [1066](#)
- HYDROSTATIC, [1066](#)
- MESH BODY ACCELERATION, [1066](#)
- SOURCE FOR MOMENTUM, [1057](#)
- BOUSSINESQ, [1059](#)
- CONSTANT_VECTOR, [1058](#)
- HYDROSTATIC, [1058](#)
- POTENTIAL, [1058](#)
- ROTATING_BODY_FORCE, [1059](#)
- SOURCE FOR POROUS_SPECIES, [1064](#)
- ELECTRODE_OBJECT, [1064](#)
- SOURCE FOR POTENTIAL, [1065](#)
- HYDROSTATIC, [1065](#)
- SOURCE FOR SOLID, [1067](#)
- HYDROSTATIC, [1067](#)
- SOLID BODY ACCELERATION, [1067](#)
- SOURCE FOR SPECIES, [1062](#)
- CURING_FOAM_EXTENT, [1062](#)
- CURING_FOAM_VFRAC, [1063](#)
- POLYNOMIAL, [1063](#)
- SOURCE FOR VOLTAGE, [1064](#)
- POLYNOMIAL, [1064](#)
- Source Fortran Subroutine, [1500](#), [1504](#)
- Source Start Location, [1437](#), [1445](#)
- Source Type, [1507](#), [1514](#)
- Source Velocity Vector, [1438](#), [1445](#)
- Spatial Influence Factor, [1507](#), [1514](#)
- Species, [431](#), [1608](#), [1615](#)
- SPECIES DIFFUSION, [655](#)
- BASIC, [656](#)
- FICKS_LAW, [656](#)

Species Diffusion: All Subindices Use Stefan Maxwell,
436

Species Diffusion: Basic, 437

Species Diffusion: Chemical Potential, 439

Species Diffusion: Constant Tensorial, 437

Species Diffusion: Darcy, 439

Species Diffusion: Electromigration, 439

Species Diffusion: Ficks Law, 436

Species Diffusion: Mass Balance Fracbal, 440

Species Diffusion: Nernst Planck, 436

Species Diffusion: Tensor Chemical Potential, 440

Species Diffusion: Tensor Electromigration, 439

Species Diffusion: Tensor Thermophoresis, 438

Species Diffusion: Tensorial, 437

Species Diffusion: Tensorial Dispersive, 438

Species Diffusion: Thermophoresis, 438

SPECIES DIFFUSIVITY, 656

ARRHENIUS, 656

CONSTANT, 657

ENCORE_FUNCTION, 657

Species Diffusivity, 440

Species Diffusivity: Arrhenius, 442

Species Diffusivity: Copied, 441

Species Diffusivity: Dissolution, 442

Species Diffusivity: Scalar String Function, 441

Species Diffusivity: User Plugin, 441

Species Expansion Coeff, 442

Species Expansion Coeff: Copied, 443

Species Expansion Coeff: Scalar String Function, 443

Species Expansion Coeff: User Plugin, 443

Species Face Stabilization Scaling: Default, 444

Species Fraction, 444

Species Fraction: Copied, 444

Species Fraction: From Chemeq, 445

Species Fraction: From Species, 446

Species Fraction: Scalar String Function, 445

Species Fraction: User Plugin, 445

Species Mobility, 446

Species Mobility: Copied, 446

Species Mobility: Nernst Einstein, 447

Species Mobility: Scalar String Function, 447

Species Mobility: User Plugin, 447

Species Molecular Weights, 1600, 1606

Species Names, 475, 1600, 1606, 1618, 1621

Species Options, 1229, 1663

Species Phases, 1600, 1606, 1618, 1621

Species Production: From Time Rate Of Change, 448

Species Surface, 448

Species Surface: Copied, 448

Species Surface: Diffusion To Surf Correction, 450

Species Surface: Equivalent To Bulk, 449

Species Surface: Scalar String Function, 449

Species Surface: User Plugin, 449

Species Valence, 450

Species Valence: Copied, 450

Species Valence: Scalar String Function, 451

Species Valence: User Plugin, 451

Species Variable Name, 1618, 1620

Species: Chemeq Gas, 433

Species: Copied, 432

Species: From Chemeq, 434

Species: From Density, 435

Species: From Mass Fraction, 434

Species: From Material Phase, 435

Species: From Phase All, 435

Species: Partial Molar Volume, 433

Species: Phase Average, 434

Species: Scalar String Function, 432

Species: Solvent Concentration From Solute Concentrations
And Partial Molar Volumes, 433

Species: Sum All Species, 433

Species: User Plugin, 432

Specific Dissipation Rate, 451

Specific Dissipation Rate Density, 453

Specific Dissipation Rate Density: Copied, 453

Specific Dissipation Rate Density: Scalar String Function,
454

Specific Dissipation Rate Density: User Plugin, 453

Specific Dissipation Rate Diffusive Flux: Basic, 454

Specific Dissipation Rate: Copied, 452

Specific Dissipation Rate: Scalar String Function, 452

Specific Dissipation Rate: User Plugin, 452

SPECIFIC HEAT, 658

CONSTANT, 659

CONSTANT_EVALUATOR, 658

CURING_FOAM, 659

ENCORE_FUNCTION, 660

EXPONENTIAL, 661

POLYNOMIAL, 661

POLYNOMIAL_EVALUATOR, 658

T_EXPONENT, 659

TABULAR_EVALUATOR, 659

USE_PHASE_CHANGE, 662

USER_FUNCTION, 662

Specific Heat, 458

Specific Heat Cp, 460

Specific Heat Cp: Cantera, 461

Specific Heat Cp: Copied, 460

Specific Heat Cp: Scalar String Function, 461

Specific Heat Cp: User Plugin, 460

Specific Heat: Calore User Sub, 455

Specific Heat: Cantera, 457

Specific Heat: Curing Foam, 455

Specific Heat: Fortran, 459

Specific Heat: Interpolated Phase Average, 456

Specific Heat: Mass Average, 457

Specific Heat: Nasa14, 458

Specific Heat: Phase Average, 455

Specific Heat: Porous Phase Specific Average, 457
 Specific Heat: Scalar String Function, 454
 Specific Heat: T Exponent, 458
 Specific Heat: Use Phase Change, 456
 Specific Surface Area, 461
 Specific Surface Area: Copied, 462
 Specific Surface Area: Scalar String Function, 462
 Specific Surface Area: User Plugin, 462
 Speed, 1507, 1514
 Sphere, 1392, 1395
 Spring Force, 849, 990
 stabilization, 738
 Start Time, 1107, 1109, 1113, 1312, 1322, 1325, 1331, 1335, 1340, 1347, 1354, 1358, 1362, 1438, 1445, 1462, 1474, 1507, 1515
 State, 1415, 1416
 Stefan Boltzmann Constant, 55, 57
 Steric Coefficients, 1600, 1606, 1618, 1622
 Stoichiometric Coefficients For, 1600, 1607, 1618, 1622
 Stop Time, 1438, 1446, 1462, 1474, 1507, 1515
 Stop When Initial Nonlinear Residual Is Below, 1143, 1154
 Stream Name, 1325, 1331
 Subcycle, 1090, 1094, 1098
 Subdomain Overlap Level, 1196, 1198, 1199
 Submodel, 1069
 Superlu Solver, 1187, 1190
 SUPG, 696
 Supg Tau: Classic Energy, 465
 Supg Tau: Classic Mixture Fraction, 467
 Supg Tau: Classic Momentum, 465
 Supg Tau: Classic Species, 468
 Supg Tau: Shakib Charge Density, 469
 Supg Tau: Shakib Cvfem Dispersed Phase Momentum, 467
 Supg Tau: Shakib Cvfem Level Set, 466
 Supg Tau: Shakib Cvfem Mixture Fraction, 466
 Supg Tau: Shakib Cvfem Momentum, 466
 Supg Tau: Shakib Energy, 463
 Supg Tau: Shakib Enthalpy, 463
 Supg Tau: Shakib Level Set, 464
 Supg Tau: Shakib Mass Balance, 469
 Supg Tau: Shakib Mixture Fraction, 468
 Supg Tau: Shakib Momentum, 463
 Supg Tau: Shakib Species, 468
 Supg Tau: Shakib Suspension, 464
 Surface, 1312, 1322
 Surface Roughness, 1477, 1483
 Surface Stabilization, 814, 935
 SURFACE TENSION, 664
 CONSTANT, 664
 ENCORE_FUNCTION, 665
 LINEAR_T, 665
 Surface Tension, 470
 Surface Tension: Copied, 470
 Surface Tension: Linear T, 471
 Surface Tension: Scalar String Function, 471
 Surface Tension: User Plugin, 470
 Surface Variables, 1312, 1322
 Surfaces, 1307, 1308
 SUSPENSION FLUX, 666
 PHILLIPS, 666
 Suspension Flux: Balance, 472
 Suspension Flux: Fad Phillips, 472
 Suspension Flux: Hydrostatic, 473
 Suspension Flux: Phillips, 471
 Suspension Hindrance Function: Morris, 473
 Suspension Normal Viscosity: Morris, 474
 Suspension Q Tensor: Ct Aligned, 474
 Suspension Q Tensor: Flow Aligned, 475
 Suspension Q Tensor: Isotropic, 474
 Suspension Traction, 934
 Symmetry Flow, 906, 942, 991, 995, 999
 Synchronize Output, 1312, 1322, 1325, 1332, 1335, 1340, 1347, 1355
 System, 1084, 1085

T

Temperature, 475, 1420, 1422, 1423, 1425, 1585, 1590
 Temperature Averaging, 1655, 1658
 Temperature Boundary Condition, 1423
 Temperature Fortran Subroutine, 1423, 1426
 Temperature Function, 1500, 1504
 Temperature Is Celsius, 1404, 1407
 Temperature Node Variable, 1423, 1426
 Temperature Phases, 1618, 1622
 Temperature Scale Factor, 1423, 1426
 Temperature Time Function, 1423, 1427
 Temperature: Calore User Sub, 477
 Temperature: Cantera, 477
 Temperature: Cht Robin, 478
 Temperature: Copied, 476
 Temperature: Correlation Fluid, 479
 Temperature: Correlation Wall, 479
 Temperature: Fortran User Sub, 478
 Temperature: From No Material Phase, 477
 Temperature: Scalar String Function, 476
 Temperature: User Plugin, 476
 Tensor Bulk Conductivity, 479
 Tensor Bulk Conductivity Scaling, 482
 Tensor Bulk Conductivity Scaling: Copied, 483
 Tensor Bulk Conductivity Scaling: Scalar String Function, 483
 Tensor Bulk Conductivity Scaling: T Exponent, 484
 Tensor Bulk Conductivity Scaling: User Plugin, 483
 Tensor Bulk Conductivity: Diagonal, 480
 Tensor Bulk Conductivity: Level Set Aligned, 482
 Tensor Bulk Conductivity: Tensor String Function, 481

Tensor Bulk Conductivity: Tensor String Function
 Symmetric, [481](#)
 Tensor Bulk Conductivity: Volume Average, [480](#)
 Tensor Electrical Conductivity, [485](#)
 Tensor Electrical Conductivity: Calore User Sub, [484](#)
 Tensor Electrical Conductivity: Tensor String Function,
 [485](#)
 Tensor Electrical Conductivity: Tensor String Function
 Symmetric, [486](#)
 Tensor Electromigration Coefficient, [486](#)
 Tensor Mass Diffusivity, [487](#)
 Tensor Mass Diffusivity: Tensor String Function, [488](#)
 Tensor Mass Diffusivity: Tensor String Function Symmetric,
 [489](#)
 Tensor Mass Diffusivity: User Plugin, [488](#)
 Tensor Soret Coefficient, [489](#)
 Tensor Species Diffusivity, [490](#)
 Tensor Species Diffusivity: Tensor String Function, [491](#)
 Tensor Species Diffusivity: Tensor String Function
 Symmetric, [492](#)
 Tensor Species Diffusivity: User Plugin, [491](#)
 Tensor Species Expansion Coeff, [492](#)
 Tensor Species Mobility, [494](#)
 Tensor Species Mobility: Nernst Einstein, [493](#)
 Tensor String Function, [909](#), [998](#)
 Tensor String Function Symmetric, [910](#), [998](#)
 Tensor Thermal Conductivity, [495](#)
 Tensor Thermal Conductivity: Calore User Sub, [494](#)
 Tensor Thermal Conductivity: Level Set Aligned, [497](#)
 Tensor Thermal Conductivity: Mass Average, [496](#)
 Tensor Thermal Conductivity: Mesh Input, [496](#)
 Tensor Thermal Conductivity: Summed, [496](#)
 Tensor Thermal Conductivity: Tensor String Function,
 [497](#)
 Tensor Thermal Conductivity: Tensor String Function
 Symmetric, [498](#)
 Termination Time, [1107](#), [1109](#), [1114](#), [1312](#), [1323](#), [1325](#), [1332](#), [1335](#),
 [1341](#), [1347](#), [1355](#)
 Teuchos Parameter Block, [1201](#)
 THERMAL CONDUCTIVITY, [666](#)
 CALORE_USER_SUB, [667](#)
 CALORE_USER_SUB (TENSOR), [674](#)
 CONSTANT, [667](#)
 CONSTANT (TENSOR), [672](#)
 CURING_FOAM, [668](#)
 ENCORE_FUNCTION, [668](#)
 MESH_INPUT, [669](#)
 OPTICALLY_THICK, [670](#)
 POLYNOMIAL, [671](#)
 POWER_LAW, [670](#)
 THERMAL, [671](#)
 USER_FUNCTION, [671](#)
 USER_FUNCTION (TENSOR), [673](#)
 Thermal Conductivity, [498](#)
 Thermal Conductivity: Activation User Function, [504](#)
 Thermal Conductivity: Calore User Sub, [500](#)
 Thermal Conductivity: Cantera, [500](#)
 Thermal Conductivity: Copied, [499](#)
 Thermal Conductivity: Curing Foam, [500](#)
 Thermal Conductivity: Fortran, [507](#)
 Thermal Conductivity: From Prandtl, [501](#)
 Thermal Conductivity: Interpolated Phase Average, [502](#)
 Thermal Conductivity: Linear Temperature And Density,
 [504](#)
 Thermal Conductivity: Mass Average, [505](#)
 Thermal Conductivity: Optically Thick, [501](#)
 Thermal Conductivity: Phase Average, [501](#)
 Thermal Conductivity: Porous Arithmetic Mixture, [505](#)
 Thermal Conductivity: Porous Emt Mixture, [506](#)
 Thermal Conductivity: Porous Geometric Mixture, [506](#)
 Thermal Conductivity: Porous Harmonic Mixture, [505](#)
 Thermal Conductivity: Power Law, [502](#)
 Thermal Conductivity: Saturation Power Law, [502](#)
 Thermal Conductivity: Scalar String Function, [499](#)
 Thermal Conductivity: Summed, [504](#)
 Thermal Conductivity: T Exponent, [503](#)
 Thermal Conductivity: Thermal, [503](#)
 Thermal Conductivity: User Plugin, [499](#)
 Thermal Conductivity: Volume Average, [503](#)
 THERMAL DIFFUSIVITY, [674](#)
 CALORE_USER_SUB, [675](#)
 CONSTANT, [675](#)
 ENCORE_FUNCTION, [676](#)
 Thermal Diffusivity, [507](#)
 Thermal Diffusivity: Calore User Sub, [508](#)
 Thermal Diffusivity: Copied, [507](#)
 Thermal Diffusivity: Scalar String Function, [508](#)
 Thermal Diffusivity: User Plugin, [508](#)
 Thermal Latent Heat, [876](#)
 thermal stress, [718](#)
 Thermodynamic Pressure, [509](#)
 Thermodynamic Pressure: Copied, [509](#)
 Thermodynamic Pressure: Scalar String Function, [510](#)
 Thermodynamic Pressure: User Plugin, [510](#)
 Theta, [1035](#), [1037](#)
 ThrowAssert, [1733](#)
 Tic Drag Coeff, [511](#)
 Tic Drag Coeff: Copied, [511](#)
 Tic Drag Coeff: Scalar String Function, [512](#)
 Tic Drag Coeff: User Plugin, [511](#)
 Tic Drag: Basic, [510](#)
 Time Derivative: Calculated, [512](#)
 Time Filter, [1679](#), [1683](#)
 Time Function, [1500](#), [1505](#)
 Time Integration Method, [1143](#), [1154](#)
 Time Scale Factor, [46](#), [49](#)
 Time Step Quantum, [1107](#), [1110](#), [1114](#)
 Time Step Style, [1107](#), [1110](#), [1114](#)

Time Step Variation, [1143](#), [1155](#)
 Timeseries Name, [1312](#), [1323](#)
 Timestamp Format, [1325](#), [1333](#)
 Timestep Adjustment Interval, [1312](#), [1324](#), [1325](#), [1333](#), [1335](#), [1341](#),
 [1347](#), [1355](#)
 Title, [1312](#), [1324](#), [1335](#), [1341](#)
 Toggle Block, [1415](#)
 Topology Database Name, [1261](#), [1274](#)
 Tortuosity Factor, [512](#)
 Tortuosity Factor: Bruggeman, [514](#)
 Tortuosity Factor: Comiti, [514](#)
 Tortuosity Factor: Copied, [513](#)
 Tortuosity Factor: Lanfrey, [514](#)
 Tortuosity Factor: Scalar String Function, [513](#)
 Tortuosity Factor: User Plugin, [513](#)
 Total Change In Time, [1107](#), [1110](#), [1115](#)
 TOTAL INTERNAL ENERGY, [676](#)
 ENCORE_FUNCTION, [676](#)
 POROUS, [677](#)
 Total Internal Energy, [515](#)
 Total Internal Energy: Copied, [515](#)
 Total Internal Energy: Porous Flow, [516](#)
 Total Internal Energy: Scalar String Function, [516](#)
 Total Internal Energy: User Plugin, [515](#)
 Tpetra Equation Solver, [1186](#)
 Trace, [1735](#)
 traceString, [1736](#)
 tracing, [1735](#)
 Transfer, [1085](#), [1089](#), [1090](#), [1093](#), [1094](#), [1097](#), [1098](#), [1101](#), [1102](#),
 [1105](#)–[1107](#), [1115](#), [1122](#), [1123](#)
 Transfer Element Death, [1075](#)
 Transient, [1085](#), [1089](#)
 Transient Traction, [804](#), [848](#), [945](#)
 Transition Reynolds Number, [1585](#), [1591](#)
 Transition Reynolds Number: Correlation, [516](#)
 Transport Cross Section, [517](#)
 Transport Cross Section: Copied, [517](#)
 Transport Cross Section: Linearized, [518](#)
 Transport Cross Section: Scalar String Function, [518](#)
 Transport Cross Section: User Plugin, [517](#)
 Transported Enthalpy: Porous, [519](#)
 Transported Enthalpy: Standard, [518](#)
 Travel Semi Axis, [1507](#), [1515](#)
 Trilinos Equation Solver, [1200](#)
 Turbulence Dissipation Rate, [519](#)
 Turbulence Dissipation Rate Diffusive Flux: Basic, [520](#)
 Turbulence Dissipation Rate: Copied, [519](#)
 Turbulence Dissipation Rate: Scalar String Function, [520](#)
 Turbulence Dissipation Rate: User Plugin, [520](#)
 Turbulence Model, [55](#), [58](#), [1679](#), [1683](#)
 Turbulence Model Parameter, [1679](#), [1683](#)
 Turbulence Model Specification, [1229](#), [1663](#), [1679](#)
 Turbulent Bulk Viscosity, [521](#)
 Turbulent Bulk Viscosity: Copied, [521](#)
 Turbulent Bulk Viscosity: Scalar String Function, [522](#)
 Turbulent Bulk Viscosity: User Plugin, [521](#)
 Turbulent Correlation, [1585](#), [1590](#)
 Turbulent Correlation Heat Transfer Coefficient:
 Correlation, [522](#)
 Turbulent Energy Diffusive Flux: Gradient Transport,
 [522](#)
 Turbulent Kinetic Energy, [523](#)
 Turbulent Kinetic Energy Density, [524](#)
 Turbulent Kinetic Energy Density: Copied, [524](#)
 Turbulent Kinetic Energy Density: Scalar String Function,
 [525](#)
 Turbulent Kinetic Energy Density: User Plugin, [525](#)
 Turbulent Kinetic Energy Diffusive Flux: Basic, [525](#)
 Turbulent Kinetic Energy: Copied, [523](#)
 Turbulent Kinetic Energy: Scalar String Function, [524](#)
 Turbulent Kinetic Energy: User Plugin, [523](#)
 Turbulent Mass Diffusivity, [526](#)
 Turbulent Mass Diffusivity: Copied, [526](#)
 Turbulent Mass Diffusivity: From Schmidt, [527](#)
 Turbulent Mass Diffusivity: Scalar String Function, [527](#)
 Turbulent Mass Diffusivity: User Plugin, [526](#)
 Turbulent Mass Fraction Diffusive Flux: Gradient
 Transport, [527](#)
 Turbulent Mixture Fraction Diffusive Flux: Gradient
 Transport, [528](#)
 Turbulent Mixture Fraction Diffusivity, [528](#)
 Turbulent Mixture Fraction Diffusivity: Copied, [528](#)
 Turbulent Mixture Fraction Diffusivity: From Schmidt,
 [529](#)
 Turbulent Mixture Fraction Diffusivity: Scalar String
 Function, [529](#)
 Turbulent Mixture Fraction Diffusivity: User Plugin, [529](#)
 Turbulent Momentum Stress, [530](#)
 Turbulent Momentum Stress: Formal Newtonian Isotropic,
 [532](#)
 Turbulent Momentum Stress: Incompressible Newtonian
 Isotropic, [532](#)
 Turbulent Momentum Stress: Newtonian Dilational
 Isotropic, [532](#)
 Turbulent Momentum Stress: Newtonian Isotropic, [533](#)
 Turbulent Momentum Stress: Tensor String Function,
 [531](#)
 Turbulent Momentum Stress: Tensor String Function
 Symmetric, [531](#)
 Turbulent Momentum Stress: User Plugin, [530](#)
 Turbulent Prandtl Number, [533](#)
 Turbulent Prandtl Number: Copied, [533](#)
 Turbulent Prandtl Number: Scalar String Function, [534](#)
 Turbulent Prandtl Number: User Plugin, [534](#)
 Turbulent Schmidt Number, [534](#)
 Turbulent Schmidt Number: Copied, [535](#)
 Turbulent Schmidt Number: Scalar String Function, [535](#)
 Turbulent Schmidt Number: User Plugin, [535](#)

Turbulent Thermal Conductivity: From Prandtl, [536](#)
Turbulent Thermal Diffusivity: From Prandtl, [536](#)
Type, [59](#), [66](#), [1399](#), [1400](#), [1496](#), [1499](#)

U

Umfpack Solver, [1187](#), [1194](#)
unit conversions, [719](#)
units, [719](#)
Universal Gas Constant, [1618](#), [1620](#)
Update Bulk Volume Pressure, [1404](#), [1408](#)
Update Search Every, [1287](#), [1290](#)
Upwind Method, [1668](#), [1677](#)
Uq Flux Multiplier, [1448](#), [1457](#), [1462](#), [1474](#)
Use Advective Bar, [1448](#), [1457](#), [1485](#), [1494](#)
Use Approximate Roe Sensitivities, [1668](#), [1677](#)
Use Banded Wavelength Model, [1261](#), [1274](#), [1485](#), [1494](#)
Use Block, [1404](#), [1408](#)
Use Bulk Element, [1448](#), [1457](#), [1485](#), [1495](#)
Use Correlation Convection Model, [1448](#), [1458](#), [1592](#)
Use Cvfem, [1678](#)
Use Dash Enclosures, [1261](#), [1275](#), [1282](#)
Use Data Block, [536](#), [1420](#), [1422](#), [1423](#), [1427](#), [1429](#), [1436](#), [1438](#),
[1446](#), [1448](#), [1458](#), [1485](#), [1495](#), [1500](#), [1505](#)
Use Death, [1423](#), [1427](#)
Use Dof Averaged Nonlinear Residual, [1169](#)
Use Enclosure, [1448](#), [1458](#)
Use External Control, [1313](#), [1324](#), [1347](#), [1356](#)
Use File Variable, [1420](#), [1422](#)
Use Finite Element Model, [1359](#), [1362](#)
Use Generic Names, [46](#), [50](#)
Use Initial Nonlinear Residual For Time Step Control, [1144](#),
[1155](#)
Use Initialize, [1085](#), [1089](#), [1115](#)
Use Inverse Density Continuity Scaling, [1662](#), [1666](#)
Use Linear Solver, [1169](#)
Use Material, [46](#), [50](#)
Use Old Temperature, [1507](#), [1516](#)
Use Opposing Subface In Open Mass Flux, [1668](#), [1677](#)
Use Output Scheduler, [1313](#), [1324](#), [1325](#), [1333](#), [1335](#), [1341](#), [1347](#),
[1356](#)
Use Radiosity Solver, [1261](#), [1275](#)
Use Secondary Linear Solver, [1170](#)
Use Specified Pressure In Open Mass Flux, [1668](#), [1677](#)
Use System, [1084](#), [1115](#)
Use Toggle Block, [1261](#), [1275](#), [1291](#), [1296](#), [1417](#), [1423](#), [1428](#), [1429](#),
[1436](#), [1438](#), [1446](#), [1448](#), [1459](#), [1462](#), [1474](#), [1485](#), [1495](#),
[1500](#), [1505](#), [1508](#), [1516](#)
Use Verdi, [1500](#), [1506](#)
Use Viewfactor Calculation, [1261](#), [1276](#)
Use Viewfactor Smoothing, [1261](#), [1276](#)
Use With Restart, [1496](#), [1499](#)
user defined functions, [579](#), [581](#), [582](#), [587](#), [592](#), [596](#), [597](#), [601](#),
[603](#), [608](#), [611](#), [618](#), [620](#), [625](#), [630](#), [634](#), [637](#), [639](#), [641](#),

[644](#)–[646](#), [650](#), [651](#), [657](#), [660](#), [665](#), [668](#), [676](#), [678](#),
[683](#), [690](#), [693](#), [768](#), [1054](#)

User Expression, [537](#)
User Expression: Scalar String Function, [537](#)
User Field, [40](#)
User Field Mask, [1448](#), [1459](#)
User Field Scaling, [1448](#), [1459](#)
user function
 boundary conditions, [789](#)
User Plugin, [1005](#), [1006](#), [1008](#), [1009](#), [1016](#)–[1018](#), [1021](#), [1024](#),
[1028](#), [1030](#), [1031](#), [1033](#)
User Variable, [1496](#)
User Vector Field, [869](#), [874](#)
User Vector Field Influx, [875](#)
Utility Group, [1408](#), [1409](#), [1517](#)

V

VALENCE, [677](#)
 CONSTANT, [678](#)
 ENCORE_FUNCTION, [678](#)
Valence, [537](#)
Valence: Copied, [538](#)
Valence: Scalar String Function, [538](#)
Valence: User Plugin, [538](#)
Value, [1423](#), [1428](#), [1500](#), [1506](#)
Values, [59](#), [67](#)
Vapor Cooling, [871](#)
Vapor Recoil Pressure, [913](#)
Variable, [1325](#), [1333](#), [1335](#), [1342](#)
Vector, [1399](#), [1400](#)
VECTOR POINT SOURCE FOR ..., [1047](#)
Vector String Function, [792](#), [795](#), [816](#), [822](#)–[825](#), [827](#), [835](#), [837](#),
[851](#), [890](#), [901](#), [903](#), [920](#), [921](#), [941](#), [949](#), [957](#), [964](#),
[968](#)–[970](#), [973](#), [986](#), [990](#), [995](#), [1022](#)
Vector User Function Disting, [790](#)
Velocity, [541](#), [1585](#), [1591](#)
Velocity Bc, [1477](#), [1483](#)
Velocity Flux, [542](#)
Velocity Flux: Copied, [542](#)
Velocity Flux: Scalar String Function, [543](#)
Velocity Flux: User Plugin, [542](#)
Velocity: Darcy, [539](#)
Velocity: Darcy Solvent, [539](#)
Velocity: From Mesh Displacement, [540](#)
Velocity: Melting Capillary Darcy, [539](#)
Velocity: Schloegl, [540](#)
Velocity: User Plugin, [541](#)
Velocity: Vector String Function, [541](#)
Venting Model, [1655](#), [1659](#)
Venting Model Property, [1655](#), [1659](#)
Venting Volumetric Flow Rate, [543](#)
Venting Volumetric Flow Rate: Copied, [543](#)
Venting Volumetric Flow Rate: K Factor, [544](#)

Venting Volumetric Flow Rate: K Factor With Choking, [545](#)
 Venting Volumetric Flow Rate: Scalar String Function, [544](#)
 Venting Volumetric Flow Rate: User Plugin, [544](#)
 Verdi Qdot Scaling, [1500](#), [1506](#)
 Viewfactor Calculation, [1248](#)
 Viewfactor Smoothing, [1254](#)
 Viewfactor Update, [1261](#), [1276](#)
 Viewfactor Update Start Time, [1261](#), [1277](#)
 VISCOSITY, [679](#)
 ARRHENIUS, [679](#)
 ARRHENIUS_CARREAU, [679](#)
 BINGHAM_WLF, [680](#)
 BINGHAM_WLFT, [680](#)
 CARREAU, [681](#)
 CARREAU_T, [682](#)
 CONSTANT, [682](#)
 CURING_FOAM, [683](#)
 ENCORE_FUNCTION, [683](#)
 KRIEGER, [684](#)
 POLYNOMIAL, [684](#)
 POWER_LAW, [685](#)
 THERMAL, [685](#)
 USER_FUNCTION, [685](#)
 WELD, [688](#)
 Viscosity, [545](#)
 Viscosity: Arrhenius, [547](#)
 Viscosity: Arrhenius Carreau, [547](#)
 Viscosity: Bingham Wlf, [548](#)
 Viscosity: Bingham Wlft, [548](#)
 Viscosity: Cantera, [551](#)
 Viscosity: Carreau, [549](#)
 Viscosity: Carreau T, [550](#)
 Viscosity: Casson, [550](#)
 Viscosity: Clsm, [551](#)
 Viscosity: Copied, [546](#)
 Viscosity: Curing Epoxy, [552](#)
 Viscosity: Curing Foam, [552](#)
 Viscosity: Interpolated Phase Average, [556](#)
 Viscosity: Keyes, [553](#)
 Viscosity: Krieger, [554](#)
 Viscosity: Mass Average, [559](#)
 Viscosity: Mixture Fraction, [554](#)
 Viscosity: Mixture Fraction Turbulent, [555](#)
 Viscosity: Morris Boulay, [555](#)
 Viscosity: Phase Average, [556](#)
 Viscosity: Power Law, [556](#)
 Viscosity: Ramacciotti, [558](#)
 Viscosity: Scalar String Function, [546](#)
 Viscosity: Species Average, [560](#)
 Viscosity: Sutherland, [557](#)
 Viscosity: Thermal, [558](#)
 Viscosity: User Plugin, [546](#)

Viscosity: Volume Average, [559](#)
 Viscosity: Weld, [557](#)
 Visualization, [1477](#), [1484](#)
 Visualize Contact, [1287](#), [1290](#)
 void ratio, [703](#)
 Voltage, [560](#)
 Voltage: Copied, [560](#)
 Voltage: Scalar String Function, [561](#)
 Voltage: User Plugin, [561](#)
 Volume Fraction, [561](#)
 VOLUME FRACTION GAS, [689](#)
 CONSTANT, [689](#)
 ENCORE_FUNCTION, [690](#)
 FROM_MASS_FRACTIONS, [689](#)
 POLYNOMIAL, [691](#)
 USER_FUNCTION, [691](#)
 Volume Fraction Gas, [564](#)
 Volume Fraction Gas: Copied, [564](#)
 Volume Fraction Gas: From Density, [565](#)
 Volume Fraction Gas: From Mass Fractions, [568](#)
 Volume Fraction Gas: From Porosity, [569](#)
 Volume Fraction Gas: From Reaction Extent, [567](#)
 Volume Fraction Gas: From Species, [569](#)
 Volume Fraction Gas: From Thermal Expansion, [568](#)
 Volume Fraction Gas: Fromfoamtimetemp, [566](#)
 Volume Fraction Gas: Interpolated Phase Average, [567](#)
 Volume Fraction Gas: Phase Average, [566](#)
 Volume Fraction Gas: Scalar String Function, [565](#)
 Volume Fraction Gas: Species, [567](#)
 Volume Fraction Gas: User Plugin, [565](#)
 Volume Fraction: Copied, [562](#)
 Volume Fraction: From Electrode Object Old, [564](#)
 Volume Fraction: From Mass Fraction, [563](#)
 Volume Fraction: From Molar Volume, [563](#)
 Volume Fraction: From Porosity, [563](#)
 Volume Fraction: Scalar String Function, [562](#)
 Volume Fraction: User Plugin, [562](#)
 Volume Heating, [1499](#)
 Volumetric Heat Transfer Coefficient, [569](#)
 Volumetric Heat Transfer Coefficient: Copied, [570](#)
 Volumetric Heat Transfer Coefficient: Scalar String Function, [570](#)
 Volumetric Heat Transfer Coefficient: User Plugin, [570](#)

W

Wall Angle, [1585](#), [1591](#)
 Wall Angle: Correlation, [571](#)
 Wall Function, [839](#), [841](#), [857](#), [904](#), [936](#), [943](#), [948](#)
 Wall Function From Cht Temperature, [897](#)
 Wall Function From Temperature, [896](#)
 Wall Length, [1585](#), [1591](#)
 Wall Length: Correlation, [571](#)
 Wall Temperature, [571](#), [1585](#), [1592](#)
 Wall Temperature: Copied, [572](#)

Wall Temperature: Scalar String Function, [572](#)
Wall Temperature: User Plugin, [572](#)
Weight Power, [1254](#), [1257](#)
Well Outflow, [843](#)
Wetted Perimeter, [573](#)
Wetted Perimeter Function, [1478](#), [1484](#)
Wetted Perimeter: Copied, [573](#)
Wetted Perimeter: Correlation Spatial User Function, [574](#)
Wetted Perimeter: Scalar String Function, [574](#)
Wetted Perimeter: Spatial User Function, [574](#)
Wetted Perimeter: User Plugin, [573](#)
Wetting, [791](#)
Wetting Outflow, [790](#)
Wetting Phase Retardation, [575](#)
Wetting Phase Retardation: Copied, [575](#)
Wetting Phase Retardation: Scalar String Function, [576](#)
Wetting Phase Retardation: User Plugin, [576](#)
Wetting Speed Blake Ls, [922](#)
Width Semi Axis, [1508](#), [1516](#)
Wisdom: Magic Eight Ball, [576](#)

X

X Offset, [59](#), [66](#)
X Scale, [59](#), [66](#)
X-Y Plane Symmetry, [1248](#), [1253](#)
X-Z Plane Symmetry, [1248](#), [1253](#)
Xml File, [1189](#), [1190](#), [1197](#), [1198](#)

Y

Y Offset, [59](#), [67](#)
Y Scale, [59](#), [67](#)
Y-Z Plane Symmetry, [1248](#), [1254](#)
Young's modulus, [718](#)
YOUNGS MODULUS, [692](#)
 CONSTANT, [693](#)
 ENCORE_FUNCTION, [693](#)

Z

Zoltan, [1180](#)

DISTRIBUTION

Email—Internal (encrypt for OUO)

Name	Org.	Sandia Email Address
Technical Library	01177	libref@sandia.gov



Sandia
National
Laboratories

Sandia National Laboratories
is a multimission laboratory
managed and operated by
National Technology &
Engineering Solutions of
Sandia LLC, a wholly owned
subsidiary of Honeywell
International Inc., for the U.S.
Department of Energy's
National Nuclear Security
Administration under contract
DE-NA0003525.