

TM C3 Experiment – Advanced Environmental Capture

Experiment Contributors: Andrew Van Blarigan, Franklin Cocchi, Daniel Hudson, Joshua Crawford
Jimmy Harris, Diane Gomez, Zeyang Cai, Jonathan Wilkerson

HOT Shot program enables TM to advance the TRL levels of critical new environmental capture technologies targeted for insertion in ANDI, the W87-0 JETU and the W87-1 EFTU.

Quick Look

TRL before HOT Shot: 3



TRL after HOT Shot: 4

Program of Impact: ANDI

Objective: achieve high confidence shock and vibration measurements in flight




Program	HOT SHOT				
	C2	C3	C4	C5	ANDI
Gas damped sensors	✓	✓	✓		✓
Digital filter and decimation	✓	✓	✓		✓
Event capture	✓	✓		✓	
Firmware based encryption		✓		✓	
High Speed Bus	✓	✓	✓	✓	
Isolated TDA			✓	✓	
Burst transmission		✓		✓	




Aliasing

- Solution: Oversample ADC, Digital Filter
- Advantages: Rapid roll-off, easily configurable




Noise floor

- Challenge: need high signal to noise ratio
- Proven on benchtop, need flight data to advance TRL



Next Generation Sensor

	Endevco 65-10	Endevco 7280AM7
Range G's	100-500	2K
Sensitivity	10-50 mV/G	150 μ V/G
Resonance	>30kHz	>25kHz
Robust against resonance	✗	✓
Signal Measurement	Single Ended	Differential
Immune to Ground Loops	✗	✓
Noise floor less than 0.15Grms	✓	✓
Flight test	?	?



Sample Capture Rate

- Solution: Spacewire
- Advantages: Higher capture rate during ground testing enables identification of otherwise hidden content

