



# The Refurbished Z Facility: Capabilities and Recent Experiments

SAND2008-7945P



**23rd National Symposium on Plasma  
Science and Technology  
Plasma - 2008  
December 10 - 13, 2008  
Bhabha Atomic Research Center, Mumbai**

**Dr. Dillon H. McDaniel  
Senior Scientist  
Pulsed Power Sciences  
Sandia National Laboratories**



Sandia is a multiprogram laboratory operated by Sandia Corporation, a Lockheed Martin Company, for the United States Department of Energy's National Nuclear Security Administration under contract DE-AC04-94AL85000.





# Thanks to my colleagues at Sandia for their many important and invaluable contributions

**Special thanks to the following individuals for providing specific input for this presentation:**

**B. W. Atherton**

**M. E. Cuneo**

**G. L. Donovan**

**C. A. Hall,**

**M. C. Herrmann**

**M. L. Kiefer**

**R. J. Leeper**

**G. T. Leifeste**

**F. W. Long**

**M. K. Matzen**

**G. R. McKee**

**T. A. Mehlhorn**

**J. L. Porter**

**L. X. Schneider**

**K. W. Struve**

**W. A. Stygar**

**E. A. Weinbrecht**



Sandia National Laboratories



# Presentation Outline

- **Refurbishment of Z**
  - Objectives
  - Timeline
  - Construction Phase
  - Facility Startup/Commissioning
- **Primary Z Applications**
  - Magnetic Implosions for X-Rays and Fusion
  - Magnetic Pressures for Dynamic Material Properties
- **Z Beamlet and Z Petawatt**
- **Summary**





# Sandia Pulsed Power Collaborators and Partners

## Laboratories


- **Laboratory for Laser Energetics (Rochester, NY)**
- **Lawrence Berkeley National Laboratory (Berkeley, CA)**
- **Lawrence Livermore National Laboratory (Livermore, CA)**
- **Los Alamos National Laboratory (Los Alamos, NM)**
- **Naval Research Laboratory (Washington, DC)**
  
- **Atomic Weapons Establishment (Aldermaston, UK)**
- **Commissariat a l'energie Atomique (France)**
- **Centre d'Etudes Gramat (Gramat, France)**
- **High Current Electronics Institute (Tomsk, Russia)**
- **Kurchatov Institute (Moscow, Russia)**
- **Lebedev Institute (Moscow, Russia)**
- **TRINITI (Troitsk, Russia)**
- **VNIIEF (Sarov, Russia)**
- **VNIITF (Chelyabinsk, Russia)**
  
- **BARC (Mumbai, India)**



Sandia National Laboratories



# The Z accelerator was a very successful experimental platform for performing HED science



- First shot in September 1996; last shot in July 2006
- Z has operated at 20 MA and 50 TW<sub>e</sub> on over 1700 shots
- Results have been published in over 200 peer-reviewed journal articles



# The Z Refurbishment Project pursued a balanced set of objectives

## Capability

### More Energy & Current Delivered

- Develop and install new capacitors that double the amount of energy stored within the same volume
- Design the pulsed power circuit specifically for z-pinch and material property applications

## Capacity

### High Operational Reliability

- Design the pulsed power drive system as conservatively as possible while simultaneously increasing delivered energy and current
- Fabricate the hardware from stainless steel instead of aluminum for durability

## Precision

### Better Repeatability Pulsed Shaping


- Incorporate individual lasers on each of the lines in order to precisely trigger and time each module individually
- Increase the Intermediate Storage Capacitor length for longer pulse options in support of dynamic materials testing



Sandia National Laboratories




# All pulsed power components were replaced as part of the refurbishment project






# The Z Refurbishment project spanned 7 years from the initial planning efforts




Sandia National Laboratories



**In only 14 months, Z was dismantled, reconstructed, and all new subsystems installed and tested**

**July 2006**



**Last Experiment on Z**



In only 14 months, Z was dismantled, reconstructed, and all new subsystems installed and tested

August 2006



**Dismantlement of Old Z Underway**



In only 14 months, Z was dismantled, reconstructed, and all new subsystems installed and tested

September 2006



8.45 PH

Teardown Complete, Rebuild Underway



Sandia National Laboratories



In only 14 months, Z was dismantled, reconstructed, and all new subsystems installed and tested

November 2006



New Oil/Water Separation Wall Nearly Done



In only 14 months, Z was dismantled, reconstructed, and all new subsystems installed and tested

January 2007




Tank Painting Completed



In only 14 months, Z was dismantled, reconstructed, and all new subsystems installed and tested

February 2007




Pulse Forming Lines In – Water Leak Test



In only 14 months, Z was dismantled, reconstructed, and all new subsystems installed and tested

March-April 2007



Intermediate Storage Capacitor Installation Underway




Sandia National Laboratories



In only 14 months, Z was dismantled, reconstructed, and all new subsystems installed and tested

May 2007




Transmission Lines Installation Completed




In only 14 months, Z was dismantled, reconstructed, and all new subsystems installed and tested

June 2007



**Insulator Stack/Water Convolute Installed**




**In only 14 months, Z was dismantled, reconstructed, and all new subsystems installed and tested**


**September 2007**




**Subsystem Testing Completed, First Shot on Refurbished Z**



# On the tenth shot we achieved the goal of a peak load current of 26 MA



Peak stack,  
outer-MITL, and  
inner-MITL  
currents agree  
to within 2%.



**ICE load hardware for  
shots 1770-1775**


shot number	pulse length	Marx-charge voltage	peak load current
1770	short	70 kV	<b>20.6 MA</b>
1772	short	75 kV	<b>22.8 MA</b>
1773	short	80 kV	<b>23.8 MA</b>
1774	short	85 kV	<b>25.6 MA</b>
1775	long	90 kV	<b>26.4 MA</b>



# We also demonstrated that the peak MITL current can be reproduced to within 1%


We were required to demonstrate 3% reproducibility for an NNSA milestone

The stretch goal was 2%  
We've demonstrated 1%






By shorting water switches and adjusting switch timings we can achieve tailored long-pulse current profiles







# High Energy Density Physics experiments are mounted at the center of the Z accelerator

**Z accelerator**




**Convolute and load region**




**Wire-array z-pinch implosion**  
~ 2 cm




# Magnetically-driven z-pinch implosions efficiently convert electrical energy into radiation




**Initiation**



**Ablation**




**Implosion**



**Stagnation**

## On Z:



- **Energy: x-ray**  
≈15% of stored electrical
- **Power: x-ray**  
≈2- 4 times electrical



Sandia National Laboratories



# The double-ended hohlraum concept separates capsule, hohlraum, and z-pinch physics issues




## Target heating



## Compression



## Ignition




## Burn







# The integrated target design builds on several years of validation experiments on Z




Double pinch development



Z-Backlighter development



Symmetry





Pulse shaping  Sandia National Laboratories




# Z is being used to measure the opacity of materials at high temperatures and pressures


opacity sample  
same charge  
states in sun



photoionization sample  
radiation effects in  
plasma surrounding  
black hole



Fe + Mg transmission  
 $T_e \sim 156 \text{ eV}, n_e \sim 10^{22} \text{ cm}^{-3}$




Ne transmission at  
 $T_e \sim 25 \text{ eV}, n_e \sim 10^{19} \text{ cm}^{-3}$

Modeling of stellar interiors and accretion powered objects depend on material opacities at high temperatures and pressures that have never been measured




Sandia National Laboratories





# Replacing the wire array with an “ICE cube” enables material property experiments on Z

**Z accelerator**



**Convolute and load region**



**Material property experiment**





Sandia National Laboratories




Magnetic pressure associated with the high current can be used directly for material property experiments

Sample



Flyer Plate

Sample





Isentropic Compression Experiments:  
direct pressure wave through sample

Shock Hugoniot Experiments:  
flyer plate launched to shock sample



# Shaping the current pulse enables high ICE pressures and flyer plate velocities

## Magnetic pressure drive





- Flyer plates to velocities of 34 km/s
  - » Deuterium EOS to 1.8 Mbar
  - » High-Z Hugoniot expts to > 20 Mbar
- Isentropic Compression Experiments
  - » Off-Hugoniot EOS measurements to 4 Mbar
  - » Al strength measurements to 2.4 Mbar
  - » Solid-solid and liquid-solid phase transitions



# Precision measurements on Z quantified properties of Be & diamond for the National Ignition Campaign



## Stress versus density for diamond









Initial Z experiments were designed to obtain wave profiles to infer strength

## Coax strength load hardware







# Wave profile analysis is providing reasonable estimates of strength at high pressure





# Coaxial geometry has produced Isentropic compression to $\sim 400$ GPa





# Available Laser Systems




- $\lambda=527\text{nm}$
- $\tau=0.3\text{-}8\text{ns}$   
(2ns common)
- $\phi\sim75\mu\text{m}$  spotsize
- $E<2\text{kJ}$
- $I<10^{17}\text{ W/cm}^2$
- $\sim3\text{ hr/shot}$
- 2 pulse MFB

- $\lambda=1054\text{nm}$
- $\tau=500\text{fs min}$
- $\phi\sim30\mu\text{m}$  spotsize
- $E<60\text{J} (<500\text{J pending})$
- $I>10^{19}\text{ W/cm}^2$
- $\sim3\text{ hr/shot}$
- Sub-ps probe  
@ 527nm, <20mJ


- $\lambda=1064\text{nm} (532\text{nm option})$
- $\tau=150\text{ps}$
- $\phi\sim5\mu\text{m}$  spotsize
- $E<10\text{J}$
- $I<10^{17}\text{ W/cm}^2$
- $\sim20\text{ min/shot}$
- Pending: 8-10ns operations  
at >100J @1 $\omega$



Sandia National Laboratories



# Facility Overview




Sandia National Laboratories



# Both Z Beamlet and Z-Petawatt are part of the Z Backlighter Facility

# Z Backlighter



## Z Beamlet

- $\lambda = 527 \text{ nm}$
- November 2007
- $\tau = 0.3 - 8 \text{ ns}$
- $\phi \sim 75 \mu\text{m}$  spotsizes
- $E < 2 \text{ kJ}$
- $I < 10^{17} \text{ W/cm}^2$

## Z Petawatt


- $\lambda = 1054 \text{ nm}$
- November 2007
  - $\tau = 500 \text{ fs min}$
  - $\phi \sim 30 \mu\text{m}$  spotsizes
  - $E < 500 \text{ J}$
  - $I > 10^{19} \text{ W/cm}^2$
- Goal in 2010
  - 2 kJ/10 ps

## Compression chamber installation







# The Z-Beamlet Laser system





# Curved-crystal imaging offers an elegant solution for backlighting in hostile environments



- Concept proposed in mid-1990s.
  - S.A. Pikuz *et al.*, Rev. Sci. Instrum. **68**, 740 (1997).
- A 1.865 keV backlighter built at NRL
  - Y. Aglitskiy *et al.*, Rev. Sci. Instrum. **70**, 530 (1999).
- Crystal imaging techniques proposed for microscopy/backlighting on NIF
  - J.A. Koch *et al.*, Rev. Sci. Instrum. **70**, 525 (1999).
- 1.865 and 6.151 keV diagnostics successfully implemented on Z facility
  - D.B. Sinars *et al.*, Rev. Sci. Instrum. **75**, 3672 (2004).

## Bent-crystal Imaging


- Monochromatic (~0.5 eV bandpass)
- 10 micron resolution
- Large field of view (e.g. 20 mm x 4 mm)
- Debris mitigation




# X-ray backlighting has led to rapid progress in the understanding of wire-array magnetically-driven implosions

## Tungsten Wire Array implosions radiographed at 6.151 keV



Ablation



Implosion



Stagnation & X-ray production



**Magnetic Rayleigh-Taylor and other instabilities strongly affect wire array zpinches from the very beginning**

**Few carefully benchmarked magnetic Rayleigh-Taylor experiments have been done**



**Late in time current delivery to small radius is limited by mass “left behind”**




# The higher spatial resolution bent-crystal imaging system revealed new features in imploding capsules


3.4-mm diameter plastic ICF capsule

Capsules had 100s of known defects on surface that apparently produced a myriad of small jets



~20  $\mu\text{m}$  diameter jets visible







# X-ray backlighting enabled us to optimize the symmetry of capsule implosions on Z


**Secondary hohlraum dimensions**

Radius ( $R_{sec}$ ) = 9.6 mm  
Length ( $L_{sec}$ ) = 13 - 17 mm




**Time-integrated  $P_2$  radiation symmetry**





# In late 2007, Z-Petawatt delivered ~125 J compressed pulse to an inactive Z-Accelerator


- **Z-Petawatt will enable:**
  - New radiography options
    - » X-rays for radiography up to 100 keV range
    - » Proton radiography
    - » Sub-picosecond resolution radiography
  - Fast Ignitor fusion research on Z
- **ZPW enhances Z backlighting abilities**
  - 43.5 cm beamsize
  - Applies 1480 l/mm 94 cm gold gratings (Nova)
  - Demonstrated up to 414 J uncompressed
  - Demonstrated 125 J compressed in initial shots
  - Limit: ~1 PW (500 J / 500 fs)
- **Future backlighting on active Z to include:**
  - A complete diagnostics suite
  - A fully active Final Optics Assembly
  - Active and passive debris mitigation
  - Active back-reflection isolation



**Cu K<sub>α</sub> x-rays yielded a contact radiograph and x-ray spectra with better signal to noise than 100 TW scale tests**



Sandia National Laboratories



## Summary

- The Z accelerator has been a very successful experimental platform for performing HED science
  - Inertial confinement fusion
  - Dynamic material properties
  - Radiation hydrodynamics, radiation effects, and basic science
- The Z Refurbishment Project was completed in September 2007 and has delivered over 26 MA to ICE loads
- Commissioning of refurbished Z is going well – no barriers to full performance
- Refurbished Z combined with Z-Beamlet and Z-Petawatt provide an exciting experimental platform for future work