


Horizontal Lifting Fixtures

SE and PE Boxes



June 25, 2007

Tim DuBay and Kevin Austin





SE Box Lifting Fixture


- Design to hook, Host hardware from there.



SE Box Lifting Fixture

- **Assembly Drawing R91546**
- **Material: Aluminum Alloy 6061-T6 per QQ-A-250/11.**
 - **R91551 Lifting Clamp Spacer**
 - **R91547 Interface Beam**
 - **R91548 Spreader Beam**
 - **R91549 Lifting Clamp Lower**
 - **R91550 Lifting Clamp Upper**
- **Material: 303 Stainless Steel.**
 - **R91552 Panel Screw**





SE Box Lifting Fixture

- **Fasteners**

- **NAS1352N3-10 Socket Head #10-24**
 - **MS51029-51 Set Screw .25-20**
Material: Heat-Resistant steel per FF-S-86.
 - **Panel Screw**
Material: 303 Stainless Steel

- **Hardware**

- **Crosby Swivel Hook**
Safe Working Load 1000 pounds

Material: Forged steel in accordance with procurement specification




SE Box Lifting Fixture

- **Hardware**

- NAS1149C0363R, Flat washer**


- Material: Steel, Corrosion Resistant 301 per MIL-S-7952
or 1025.**

- **All hardware is captive.**



SE Box Lifting Fixture

- **Surface Finish**
 - R91547 and R91548 are Anodize per 9904102 Class 2, color Red.
 - R91549 and R91550 are Alodine per Mil-c-5541C Class 3
 - Screws, NAS1352 and MS51029 are passivated per QQ-P-35.
 - Washers, NAS1149 are passivated per QQ-P-35 or AMS2700.
 - Crosby Swivel Hook, uncoated.




SE Box Lifting Fixture

- Identification
 - Part Identification will be on R91547.
 - Part Number: R91546
 - Serial Number: 001
 - Rated Load: 43 pounds
 - Weight: 3.8 pounds
 - Proof Tag will be attached on R91547
 - Part Number: R91546
 - Proof Load: 116 pounds
 - Rated Working Load: 43 pounds
 - Proof Load Test xx/xx/xx
 - Next Proof Load Test xx/xx/xx
 - PL Inspection Accep.



SE Box Lifting Fixture

- Designed to lift in vertical direction
- Proof weight applied and measured at hook





SE Box Lifting Fixture

- **MAGE Proof Test Option 1**
 - **Test Requirements**

MAGE Specs

Live Load (LL)	42.6
Dead Load (DL)	3.8
BTH= LL + DL	46.4

Factors of Safety

	Static MAGE
Working Load	1
Design Limit Load (DLL)	1.25
Proof Load	1.5
Design Yield	2.5
Design Ultimate	4

Proof Test Options (lbf)

	Option 1
	One static test
Mage Weight	4
Lift Rated Load	43
Sling Rated Load	46
DLL	58
Proof Weight	116
Design Yield Load	174
Design Ultimate Load	290


SE Box Lifting Fixture

- Preliminary Design Analysis


- Using the DLL of 58lbs the Design Yield Load = $3 \times \text{DLL} = 174\text{lbf}$ and Design Ultimate Load = $5 \times \text{DLL} = 290\text{lbs}$

On part R91550

- Yield Stress FOS of 22



Ultimate Stress FOS of 14.8






SE Box Lifting Fixture

- Preliminary Design Analysis


- Using the DLL of 58lbs the Design Yield Load = $3 \times \text{DLL} = 174\text{lbf}$ and Design Ultimate Load = $5 \times \text{DLL} = 290\text{lbs}$

On part R91549

- Yield Stress FOS of 33



Ultimate Stress FOS of 22




SE Box Lifting Fixture

- Preliminary Design Analysis


- Using the DLL of 58lbs the Design Yield Load = $3 \times \text{DLL} = 174\text{lbf}$ and Design Ultimate Load = $5 \times \text{DLL} = 290\text{lbs}$

On part R91547

- Yield Stress FOS of 11.5



Ultimate Stress FOS of 8






SE Box Lifting Fixture

- Preliminary Design Analysis


- Using the DLL of 58lbs the Design Yield Load = $3 \times \text{DLL} = 174\text{lbf}$ and Design Ultimate Load = $5 \times \text{DLL} = 290\text{lbs}$


On part R91548

- Yield Stress FOS of 19



Ultimate Stress FOS of 13





SE Box Lifting Fixture

- Preliminary Design Analysis

- Fasteners

- NAS1352N3-10 Socket Head #10

- Yield Strength and Ultimate Tensile Strength per FF-S-86 are 120 ksi and 160 ksi respectively
 - After .57 Derating they are 68 ksi and 91 ksi

- Yield FOS

- Tensile = 27

- Ultimate FOS

- Tensile = 22

- Thumbscrews

- Yield Strength and Ultimate Tensile Strength are 35 ksi and 87.3 ksi respectively

- Yield FOS

- Tensile = 22

- Ultimate FOS

- Tensile = 33



SE Box Lifting Fixture

- Preliminary Design Analysis
- Hardware
 - Crosby Swivel Hook
 - Safe Working Load 1000 lbs
 - After .57 Derating safe working load = 570 lbs
 - Yield FOS using Design Yield Strength = $3 \times \text{DLL}$
 - Tensile = 3.3



SE Box Lifting Fixture

- **Test Procedure**
 - **Proof Load (116 lbf) is applied for a total of three cycles (0-100%-0) and held at 100% for (10) minutes during each cycle.**
 - **Visual Inspection performed before each critical lift**





SE Box Lifting Fixture

- Operational Test
 - Uses equivalent weight
 - MAGE is traversed vertically using appropriate crane hoist

PE Box Lifting Fixture



- Assembly Drawing R91449
- Material: Aluminum Alloy 6061-T6 per QQ-A-250/11.
 - R91551 Lifting Clamp Spacer
 - R91450 Interface Beam
 - R91451 Spreader Beam
 - R91549 Lifting Clamp Lower
 - R91550 Lifting Clamp Upper
- Material: 303 Stainless Steel.
 - R91552 Panel Screw






PE Box Lifting Fixture


- Design to hook, Host hardware after that.





PE Box Lifting Fixture

- **Fasteners**
 - **NAS1352N3-10 Socket Head #10**
 - **MS51029-51 Set Screw .25-20**
Material: Heat-Resistant steel per FF-S-86.
 - **Panel Screw**
Material: 303 Stainless Steel
- **Hardware**
 - **Crosby Swivel Hook**
Safe Working Load 1000 pounds
Material: Forged steel in accordance with procurement specification
- **All hardware is captive.**



PE Box Lifting Fixture

- **Surface Finish**
 - R91450 and R91451 are Anodize per 9904102 Class 2, color Red.
 - R91549 and R91550 are Alodine per Mil-c-5541C Class 3
 - Screws, NAS1352 and MS51029 are passivated per QQ-P-35.
 - Washers, NAS1149 are passivated per QQ-P-35 or AMS2700.
 - Crosby Swivel Hook, is uncoated.



PE Box Lifting Fixture


- Identification

- Part Identification will be on R91450

- Part Number: R91449
 - Serial Number: 001
 - Rated Load: 83 Pounds
 - Weight: 7.9 pounds

- Proof Tag will be attached on R91450

- Part Number: R91449
 - Proof Load: 228 pounds
 - Rated Working Load: 83 pounds
 - Proof Load Test xx/xx/xx
 - PL Inspection Accep. xxx



PE Box Lifting Fixture

- **MAGE Proof Test Option 1**
 - Test Requirements

MAGE Specs (lbf)


Live Load (LL)	83
Dead Load (DL)	7.9
BTH= LL + DL	90.9

Factors of Safety

	Static MAGE
Working Load	1
Design Limit Load (DLL)	1.25
Proof Load	1.5
Design Yield	2.5
Design Ultimate	4


Proof Test Options (lbf)

	Option 1
	One static test
Mage Weight	8
Lift Rated Load	83
Sling Rated Load	91
DLL	114
Proof Weight	228
Design Yield Load	342
Design Ultimate Load	570



PE Box Lifting Fixture

- Designed to lift in vertical direction
- Proof weight applied and measured at hook




PE Box Lifting Fixture

- Preliminary Design Analysis


- Using the DLL of 114lbs the Design Yield Load = $3 \times \text{DLL} = 342 \text{ lbf}$ and Design Ultimate Load = $5 \times \text{DLL} = 570 \text{ lbs}$

On part R91550_PE

- Yield Stress FOS of 11



Ultimate Stress FOS of 8



PE Box Lifting Fixture



- Preliminary Design Analysis


- Using the DLL of 114lbs the Design Yield Load = $3 \times \text{DLL} = 342\text{lbf}$ and Design Ultimate Load = $5 \times \text{DLL} = 570\text{lbs}$

On part R91450

- Yield Stress FOS of 45

Ultimate Stress FOS of 30






PE Box Lifting Fixture

- Preliminary Design Analysis


- Using the DLL of 114lbs the Design Yield Load = $3 \times \text{DLL} = 342\text{lbf}$ and Design Ultimate Load = $5 \times \text{DLL} = 570\text{lbs}$

On part R91459_PE

- Yield Stress FOS of 17



Ultimate Stress FOS of 11






PE Box Lifting Fixture

- Preliminary Design Analysis


- Using the DLL of 114lbs the Design Yield Load = $3 \times \text{DLL} = 342\text{lbf}$ and Design Ultimate Load = $5 \times \text{DLL} = 570\text{lbs}$


On part R91451

- Yield Stress FOS of 4



Ultimate Stress FOS of 2.7





PE Box Lifting Fixture

- Preliminary Design Analysis

- Fasteners

- NAS1352N3-10 Socket Head #10

- Yield Strength and Ultimate Tensile Strength per FF-S-86 are 120 ksi and 160 ksi respectively
 - After .57 Derating they are 68 ksi and 91 ksi

- Yield FOS

- Tensile = 14

- Ultimate FOS

- Tensile = 11

- Thumbscrews


- Yield Strength and Ultimate Tensile Strength are 35 ksi and 87.3 ksi respectively

- Yield FOS

- Tensile = 14.5


- Ultimate FOS

- Tensile = 22



PE Box Lifting Fixture

- Preliminary Design Analysis
- Hardware
 - Crosby Swivel Hook
 - Safe Working Load 1000 lbs
 - After .57 Derating safe working load = 570 lbs
 - Yield FOS using Design Yield Strength = 3^*DLL
 - Tensile = 1.7



PE Box Lifting Fixture

- **Test Procedure**
 - Proof load (228 lbf) is applied for a total of three cycles (0-100%-0) and held at 100% for 10 minutes during each cycle.
 - Visual inspection performed before each critical lift
- **Operation Test**
 - Uses equivalent weight
- **MAGE is traversed vertically using appropriate crane hoist**