



BIFACIAL TESTING AT PV USA LATEST DATA AND FINDINGS

PV Evolution Labs (PVEL)

Tristan Erion-Lorico, Head of PV Module Business

tristan.erion-lorico@pvel.com

February 2021

DOE-PVEL-08546-4

PVEL is the Independent Lab of the Downstream Solar Market

Our mission is to support the worldwide PV buyer community by generating data that accelerates adoption of solar technology.



10+

Years of
experience

400+

Bills of materials
tested

400+

Global downstream
partners

30+GW

Annual project
pipelines
supported

PVEL's Outdoor Bifacial Study

- › 10 Nextracker Horizon rows
- › 2 albedos
- › 9 PV module brands
- › 1,500V inverters

Study Participants:


- › Astronergy
- › ET Solar
- › First Solar
- › GCL S.I.
- › Jinko Solar
- › LONGi
- › Morgan Solar
- › Q CELLS
- › Trina



This material is based upon work partially supported by the U.S. Department of Energy's Office of Energy Efficiency and Renewable Energy (EERE) under the Solar Energy Technologies Office (SETO), Award Number DE-EE0008546. **DISCLAIMER:** This presentation was prepared as an account of work partially sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.


PVEL's Flash Value vs. Nameplate

- › Normalizing energy harvest data to nameplate can result in different values versus normalizing to PVEL's pre-lightsoak flash measurement.
- › Mfr.A had the largest spread between the two module types, with a monofacial flash result 0.6% lower than nameplate and a bifacial flash result 1.8% higher than nameplate.




Monthly Specific Yield – Monofacial

- › Focusing on monofacial, the monthly and total Wh/Wp values, normalized to PVEL's flash (not nameplate), reveal a surprisingly wide range of performance.
- › From Aug. to Jan. the highest performer (Mfr.B, Mono PERC, Full Cell) is **11.8%** higher than the lowest performer (Mfr.E, Mono PERC, Half Cell), and 6.1% higher than the average.




Monthly Specific Yield – Bifacial on Natural Groundcover

- › The monthly Wh/Wp values for bifacial modules over natural groundcover (normalized to PVEL's flash) also show a significant range of performance.
- › From Aug. to Jan. the highest performer (Mfr.H, HJT, glass//glass) is **8.5%** higher than the lowest performer (Mfr.E, PERC, glass//glass), and 4.0% higher than the average.



Bifacial Gain vs. Irradiance (Monthly)

- Plotting Mfr.C's bifacial gain versus irradiance each month provides interesting insights into how the bifacial gains are higher at low irradiance.
- Locations with more diffused light will provide higher bifacial gains, however above 600 W/m² the bifacial gain does not vary.





THANK YOU

Tristan Erion-Lorico

Head of PV Module Business

tristan.erion-lorico@pvel.com



THIS MATERIAL IS BASED UPON WORK SUPPORTED BY THE U.S. DEPARTMENT OF ENERGY'S OFFICE OF ENERGY EFFICIENCY AND RENEWABLE ENERGY (EERE) UNDER THE SOLAR ENERGY TECHNOLOGIES OFFICE (SETO), AWARD NUMBER DE-EE0008546.

DISCLAIMER:

THIS PRESENTATION WAS PREPARED AS AN ACCOUNT OF WORK SPONSORED BY AN AGENCY OF THE UNITED STATES GOVERNMENT. NEITHER THE UNITED STATES GOVERNMENT NOR ANY AGENCY THEREOF, NOR ANY OF THEIR EMPLOYEES, MAKES ANY WARRANTY, EXPRESS OR IMPLIED, OR ASSUMES ANY LEGAL LIABILITY OR RESPONSIBILITY FOR THE ACCURACY, COMPLETENESS, OR USEFULNESS OF ANY INFORMATION, APPARATUS, PRODUCT, OR PROCESS DISCLOSED, OR REPRESENTS THAT ITS USE WOULD NOT INFRINGE PRIVATELY OWNED RIGHTS. REFERENCE HEREIN TO ANY SPECIFIC COMMERCIAL PRODUCT, PROCESS, OR SERVICE BY TRADE NAME, TRADEMARK, MANUFACTURER, OR OTHERWISE DOES NOT NECESSARILY CONSTITUTE OR IMPLY ITS ENDORSEMENT, RECOMMENDATION, OR FAVORING BY THE UNITED STATES GOVERNMENT OR ANY AGENCY THEREOF. THE VIEWS AND OPINIONS OF AUTHORS EXPRESSED HEREIN DO NOT NECESSARILY STATE OR REFLECT THOSE OF THE UNITED STATES GOVERNMENT OR ANY AGENCY THEREOF.