

Thermomechanical Modeling of Counter-Flow Packed-Bed Particle-to-sCO₂ Heat Exchangers




Nicolas A. DeLovato, Kevin Albrecht,
Clifford Ho

Concentrating Solar Technologies Department,
Sandia National Laboratories, Albuquerque, NM






Sandia National Laboratories is a multimission laboratory managed and operated by National Technology & Engineering Solutions of Sandia, LLC, a wholly owned subsidiary of Honeywell International Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.

Particle-sCO₂ Solar Power Plant




- High temperature-stable particles enable the use of a high efficiency sCO₂ Brayton cycle.
- The performance of the particle-sCO₂ heat exchanger is crucial to the levelized cost of electricity.

Particle-sCO₂ Heat Exchanger Design



- Design of a 1 MW_{th} particle-sCO₂ heat exchanger for the G3P3 Particle Pilot Plant.
- The performance, sizing, and start-up procedure for the heat exchanger was determined.


Particle-sCO₂ Heat Exchanger Model



Modeling Objectives:

- Determine thermal performance via the overall heat transfer coefficient (U).
- Calculate the number of microchannel plates required for a 1 MW_{th} thermal duty.
- Establish a start-up procedure which does not create stresses outside the allowable range.

Steady State Results



Particle Bed Velocity




Plate Temperature




Plate Stress

- Adding the particle flow around the headers reduced U by less than 1%.
- The overall heat transfer coefficient was determined to be $434.47 \text{ W/m}^2\text{-K}$, an improvement from $167 \text{ W/m}^2\text{-K}$ [1] for a cross-flow heat exchanger design.
- The number of 0.58 m wide, 1.28 m tall plates required for a 1 MW_{th} thermal duty was 35.

[1] Albrecht, K. J. and Ho, C. "Heat Transfer Models of Moving Packed Bed Particle to sCO₂ Heat Exchangers," Power Energy (2017).

Particle Mass Flow Rate Ramping





Plate Stress During Start-Up



- The particle flow rate was increased at various rates until the target flow rate was reached.
- The heat exchanger was initially set to the target inlet temperature of the sCO₂.
- All flow rate ramps caused a peak stress around 130 MPa, well above the allowable stress.

Particle Temperature Ramping





Plate Stress During Start-Up



- The particle inlet temp. was increased at various rates until the target temp. was reached.
- The heat exchanger was initially set to the target inlet temperature of the sCO₂.
- All temperature ramps caused less peak stress than the flow rate ramps.

Plate Vertical Edge Effects






Plate Stress During Start-Up

- Initially the plate's design had a 15.4 mm space from the edge of the plate to the 1st channel.
- This space at the sides of the plate caused areas of high stress during start-up.
- Reducing this space to 3 mm decreased the stress on the sides of the plate significantly.

Start-Up Procedure Analysis



- The particle inlet temperature ramps were then applied to the heat exchanger with 3 mm spacers.
- The spacers' peak stress reduced significantly when the spacers were reduced to 3mm.

Start-Up Procedure Analysis




Plate Stress During Start-Up

- The particle inlet temperature ramps were then applied to the design with 3 mm spacers.
- A 20 °C per minute ramp was determined as the quickest start-up procedure to stay under the allowable stress on the vertical sides.

Conclusions

- Key factors found in the modeling of this heat exchanger:
 - Around 160% increase in U for counter-flow from cross-flow HX.
 - Areas within the plate without bad thermal communication cause high stress.
 - Temperature ramps induced less stress than flow rate ramps.
- Further model development:
 - Implement a CFD analysis of the sCO₂ flow through microchannel plate.
 - Investigate stress around microchannels with refined mesh.

ACKNOWLEDGEMENTS

The paper is based upon work supported in part by the Gen 3 Particle Pilot Plant (CPS 3412), program managers: Matt Bauer, Vijay Rajgopal, and Shane Powers.

Sandia National Laboratories is a multimission laboratory managed and operated by National Technology and Engineering Solutions of Sandia LLC, a wholly owned subsidiary of Honeywell International Inc. for the U.S. Department of Energy's National Nuclear Security Administration under contract DENA0003525.