



Receiver Design and On-Sun Testing for G3P3-USA



PRESENTED BY

Clifford K. Ho

Sandia National Laboratories, Albuquerque, NM, ckho@sandia.gov

Contributors:

Nathan Schroeder, Henk Laubscher, Lindsey Yue,
Brantley Mills, Reid Shaeffer, Joshua Christian,
and Kevin J. Albrecht

Sandia National Laboratories, Albuquerque, NM



SAND2020-XXXX





Sandia National Laboratories is a multimission laboratory managed and operated by National Technology & Engineering Solutions of Sandia, LLC, a wholly owned subsidiary of Honeywell International Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.

Overview

- Introduction and Objectives
- Receiver Design
- On-Sun Testing
- Next Steps

Introduction

High-Temperature Falling Particle Receiver



Gen 3 Particle Pilot Plant

- $\sim 1 - 2 \text{ MW}_t$ receiver
- 6 MWh_t storage
- 1 MW_t particle-to-sCO₂ heat exchanger

K. Albrecht, SNL

Objective

- Develop new design features to improve receiver thermal efficiency
- Perform on-sun testing to evaluate performance of new design features and obtain operational experience

Overview

- Introduction and Objectives

- Receiver Design

- On-Sun Testing

- Next Steps




G3P3-USA Receiver Design Evolution



2015 - 2018

NSTTF
1 MW_{th} FPR




Design Challenges

- Low thermal efficiency
- Sensitivity to wind

FPR = Falling particle receiver

Feature evaluation




Design refinement

Design evaluation

2020


Optimized
G3P3 FPR



Pathway

- Wind Evaluation
- Ground Testing
- On-sun Testing
- Model Validation


Stair Testing




Drawing of “stairs” in receiver cavity



Particle flow over two-stair configuration (5 - 10 kg/s)






2015 - 2018

Feature evaluationDesign Challenges

- Low thermal efficiency
- Sensitivity to wind

FPR = Falling
particle receiver

Design refinementDesign evaluation

Pathway

- Wind Evaluation
- Ground Testing
- On-sun Testing
- Model Validation

SNOUT and Reduced Volume Receiver


Baseline




SNOUT



Baseline



Reduced volume receiver



Experiment



Simulation

SNOUT and reduced-volume reduced advective heat loss by ~20 - 25%

Overview

- Introduction and Objectives


- Receiver Design

- On-Sun Testing

- Next Steps



Control Room and On-Sun Testing




On-sun testing of
particle receiver with
StAIRs and reduced
volume


Summary of Tests (until Sep. 4)

Date	Start	End	Description	Weather
17-Aug-20	11h00	14h30	Receiver testing 500°C and 700°C, peak flux of 60 and 115 W/cm^2, two stairs	Very windy afternoon, Some cumulonimbus clouds
18-Aug-20	11h00	14h30	Receiver testing 500°C and 700°C, peak flux of 60 and 115 W/cm^2, two stairs	Hazy from smoke
20-Aug-20	10h30	15h00	Test load cells, 50 W/cm^2, 500-600 °C, test single stair, top stair only	
21-Aug-20	10h30	14h00	Receiver testing, load cell troubleshooting, single top stair	Hazy from smoke, low DNI
4-Sep-20	10h30	15h00	Receiver test day, 500C @ 5kg/s and 10 kg/s, with 50 W/Cm^2 700C @ ±5kg/s and 50 W/cm^2 700C at 108W/cm^2	Good DNI clear skies

On-Sun Particle Temperatures



Preliminary Receiver Efficiencies





Overview

- Introduction and Objectives
- Receiver Design
- On-Sun Testing
- Next Steps

Next Steps

- Perform additional on-sun tests with clear days and more reliable mass flow rates
- Evaluate impact of wind speed & direction
- Evaluate impact of reduced-volume receiver and stairs
- Process on-sun data for world's first particle-to-sCO₂ heat exchanger



Acknowledgments



- This work is funded in part or whole by the U.S. Department of Energy Solar Energy Technologies Office under Award Number 34211
 - DOE Project Managers: Matthew Bauer, Vijay Rajgopal, and Shane Powers