



Sandia
National
Laboratories

G3P3 Panel:

Technoeconomic and Scaling Considerations for Gen3 Particle Technology

Luis Gonzalez-Portillo, Kevin J. Albrecht, Jeremy Sment, Clifford Ho

U.S. Department of Energy Gen3 Summit, G3P3 Panel

CPS# 34211

August 26, 2021




Sandia National Laboratories is a multimission laboratory managed and operated by National Technology & Engineering Solutions of Sandia, LLC, a wholly owned subsidiary of Honeywell International Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.

Comparison of 1 MW and 200 MW concepts



1 MW_t Particle Pilot
Plant Design





100 MWe Particle CSP
Plant Concept




Design decisions as system increases size from pilot to commercial scale:

- What is the preferred tower construction method and height to meet optical power requirements?
- Should storage be vertically integrated in to the tower or ground-based?
- What is the preferred method of particle conveyance and flow control?
- Should thermal equipment (receiver, storage bin, heat exchanger, lift) scale in number or size?
- Should particle cost or properties be prioritized (naturally occurring or engineered)?

Component Scaling Considerations



Dometechnology.com




Solex-VPE-Sandia



Technoeconomic System Analysis



- Techno-economic model for a commercial particle plant developed for LCOE analysis
- Cost and performance models developed from vendor quotes and prototype designs
- Model
 - Solar field modeled with SolarPILOT
 - Power cycle modeled with Software from Dyreby's and Gavic's Thesis
 - Particle-based components developed in EES
 - Receiver
 - Storage
 - Lifts
 - Primary heat exchanger




Particle Receiver – Optical Properties



- Analytical model developed to calculate the apparent optical properties in a curtain from intrinsic particle surface
- Free particles must have an absorptivity above 60% to improve LCOE compared to CARBO
- Particle durability and flow properties must also be considered when evaluating tradeoffs

Particle Attrition/Loss




- Non-hermetically sealed particle system with directly irradiated receiver can be susceptible to particle loss
- Particle loss can significantly impact LCOE if rate exceeds 0.001% of system throughput
- LCOE is less sensitive to lower cost particles, but loss rate should never exceed 0.01% of system throughput

Probabilistic Analysis



- A probabilistic analysis was performed to quantify LCOE uncertainty and identify key parameters that impact the LCOE
- Four independent particle-based CSP configurations were studied:
 - One receiver and ground storage
 - One receiver and tower-integrated storage
 - Three receivers and ground storage
 - Three receivers and tower-integrated storage
- Uncertainty distributions were assigned to component costs and performance parameters that are unknown




	Variable	Units	Design Value	Min Value	Max value
ALL MODELS	Cycle			0.8	0.89
	Compressor efficiency	-		0.8	0.89
	Turbine efficiency	-		0.87	0.93
	Tower cost	\$/kg	1	0.75	1.25
BOP	Rec	\$/kg	1	0.75	1.25
	BOP cost	\$/kWe	167	125.25	208.75
	PHX	\$/m ²	6594.5	4158	9031
	Flow distribution/piping cost	\$/s/kg	4753	3564.75	5941.25
1-REC MODEL	Rec	\$/m ²	37400	28050	46750
	lift	\$/s/m ²	58.37	43.7775	72.9625
3-REC MODEL	Rec	\$/m ²	48620	36465	60775
	lift	\$/s/m ²	116.74	58.37	175.11
GROUND-BASED TES	Tower	Tower cost fixed	\$	1194300	725696
	TES	Bins cost	\$/m ²	0.675	133.11
	PHX	Horizontal conveyor + Flow control + hoppers	\$/s/kg		
TOWER INTEG TES	tower	Tower cost variable	-	0.5	0
	PHX	Flow control + hoppers	\$/s/kg	1946	1459.5

Probabilistic Analysis – Results



- **1-receiver designs**
 - Achieves lowest LCOE if receiver advective loss does not scale with size
- **3-receivers designs**
 - Results in smallest receiver aperture dimensions and tower height
 - Opportunity to incorporate redundancy in receiver and particle conveyance system
- **Tower-storage designs**
 - Achieve lower LCOE than designs with ground-based storage in non-seismic areas
- **All Configurations**
 - Similar LCOE probability for $< 0.06 \text{ \$/kWh}$



Conclusions/Future Work



- Most likely configuration for commercial scale particle-based CSP system will incorporate three falling particle receivers, ground-based storage, skip hoist conveyance, and moving packed-bed heat exchangers
- Future technoeconomic studies should look to incorporate:
 - Transients for starting and stopping components
 - Active heliostat control and aiming strategy
 - Identify break point for ground-based vs. vertically-integrated storage
- Component analysis at commercial scale should focus on:
 - Allowable heat exchanger ramp rate and lifetime for shell and plate moving-packed bed design
 - Storage bin design and thermal performance for ground or tower based systems
 - Improved receiver predictions for advective heat loss in open cavity receivers
 - Demonstrations of commercial skip hoist charging and discharging with measured heat loss

Acknowledgements



Sandia would like to acknowledge the contributions of industry partners VPE and Solex

This work was funded in part or whole by the U.S. Department of Energy Solar Energy Technologies Office under Award Numbers 34211.

Technology Managers: Matthew Bauer, Vijay Rajgopal, and Shane Powers



Sandia National Laboratories is a multimission laboratory managed and operated by National Technology & Engineering Solutions of Sandia, LLC, a wholly owned subsidiary of Honeywell International Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.

