



DECOVALEX-2023 Task E (BATS) Introduction



DECOVALEX-2023 Meeting 4
Monday November 8, 2021
Virtual Workshop

Kristopher L. Kuhlman
Sandia National Laboratories

Sandia National Laboratories is a multi-mission laboratory managed and operated by National Technology and Engineering Solutions of Sandia LLC, a wholly owned subsidiary of Honeywell International Inc. for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.
Approved for unclassified, unlimited release.

Outline

- Introduction
- 1992 Waste Isolation Pilot Plant (WIPP) data
- 2020 Brine Availability Test in Salt (BATS) data
- Next Steps



BATS test ready (Dec. 2019) in WIPP N-940 drift



Drilling BATS boreholes (Feb. 2019)


Motivation

No
Image

Alpine miner at WIPP



Cross-section view of Excavation Damaged Zone (EDZ) around drifts




Task E Goals

- Understand and predict THMC processes impacting *brine availability* in salt
 - Water response to pressure (Δp), stress ($\Delta \sigma$), and temperature (ΔT)?
 - How does EDZ control migration of water (ϕ , k , relative perm. k_r)?
 - How does EDZ evolve with Δp , $\Delta \sigma$, and ΔT ?



Q1: Is two-phase flow in EDZ important?

Q2: How to simulate brine pulse after heating?


- WIPP Test Cases:
 - Small-Scale Brine Inflow test (1987-1992)
 - Ongoing heated Brine Availability Test in Salt (BATS)



Waste Isolation Pilot Plant (WIPP) Context







Layout of WIPP North End





WIPP Small-Scale Brine Inflow Test (1987-1992)

- Monitored 17 unheated boreholes
- Weekly brine inflow data
- INTRAVEL study (Beauheim et al., 1997)
- Effects of stratigraphy / orientation / drift
- Considered single-phase brine flow





Brine Availability Test in Salt (BATS)

- Two Arrays: Heated / Unheated
- Behind packer
 - Circulate dry N₂
 - Quartz lamp heater (750 W)
- Samples / Analyses
 - Gas stream (natural / applied tracers and isotopic makeup)
- Cement Seals
 - Sorel cement + Salt concrete: 3-axis strain & temperature
- Geophysics
 - 3× Electrical resistivity tomography (ERT)
 - 3× Acoustic emissions (AE)
- Phases:
 - BATS 1a: first heating cycle (Jan-Mar 2020)
 - BATS 1b-1c: Tracers (Jan-May 2021)
 - BATS 2: drill new heated array (Oct 2021)



January-March 2020 BATS 1a Test Data


Temperature data during BATS 1a





BATS 1a test and data summarized in Kuhlman et al. (2020)

May-Aug 2021 BATS 1b Gas Tracer Test Data

Pressure in Source Borehole



Breakthrough to Heated Borehole



Gas Tracer Test Responses

- Unheated pressure response is repeatable
- Pressure maintained at source (D) until heat off
- No tracer breakthrough to heater (HP) until heat off
- Drop in humidity in adjacent borehole (SM) when heat off
- No response in seal (SL) borehole

Humidity behind packers

Task E Steps

Step 0: Single-process H¹ and T benchmarks

Step 1: TH¹ benchmark & H²M/H² initial condition setup

Step 2: TH²M heated brine inflow test case

Step 3: Alternatives (ERT/AE joint inversion, seals, TH²MC, creep)

Table 3. Proposed detailed Task E schedule of steps.

	Apr.	Nov.	Apr.	Nov.	Apr.	Nov.	Apr.	Nov.
	2020		2021		2022		2023	
Step 0								
Step 1								
Midterm Report → (Nov 2021)								
Step 2								
Step 3								
				Papers and Final Report → (Nov 2023)				

H¹= single-phase; H² = two-phase




Infrared heater in BATS HP borehole

Task E Step 0 (Apr. 2020 - Apr. 2021)

0. Single-process H^1 and T benchmarks


a) H^1 brine inflow to boreholes (1991 small-scale brine inflow test)

- Simulate brine inflow to 3 (of 17) boreholes in Finley et al. (1992) dataset
- Brine flow down p gradient (borehole @ 0.1 MPa, far-field @ hydrostatic \sim 6 MPa)



b) Heat conduction (BATS; Kuhlman et al., 2020)

- Simulate T profile (heating and cooling) during heater test
- Heat conduction: 60-cm interval of borehole wall is constant temperature (\sim 100 °C), heater midpoint is 2.75-m deep into 10-cm borehole,



c) Estimate model parameter uncertainty and parameter sensitivity for both through time


- *Quantify uncertainty* in prediction and measure Δ prediction with Δ input parameters (*sensitivity*)

Task E Step 1a (Nov. 2020 - Apr. 2021)

1. TH¹ benchmark & H² initial conditions setup

a) Benchmark TH¹ brine production to analytical solution (McTigue, 1990)

- Compare numerical models against coupled linear solution (space & time)
- Halite properties from Table 1, McTigue (1986)
- Compare with/without model non-linearities (e.g., fluid viscosity $f(T)$)
- Thermal pressurization response from flat initial pressure
- ***Two Types of Responses***
 1. Classical TH response (fluid expansion only)
 2. Mechanically coupled THM response (fluid + solid expansion)
- McTigue (1986): paper discusses (2) but gives parameters for (1)!
- Different thermal pressurizations predicted, based on conceptual model







Task E Step 1b (Nov. 2020 - Nov. 2021)


1. TH¹ benchmark & H² initial conditions setup

b) Parameterize two-phase flow in salt EDZ (few data exist)

- *Literature capillary pressure data*
 - Recompacting granular salt
 - anhydrite EDZ at WIPP
 - Salt “analogues” (tight sandstone or shale)



Fractured
WIPP
anhydrite
from EDZ





Task E Step 1c (Nov. 2020 - Nov. 2021)

1. TH¹ benchmark & H² initial conditions setup

c) H² brine inflow to in BATS drift (1D radial profile) w/ H² characterization

- DRZ to 1 drift radius ($k_{\text{DRZ}} \gg k_{\text{far}}$)
- Initialize two-phase flow models
 - Pressure distribution ($p_{\text{DRZ}} \approx p_{\text{ATM}} \ll p_{\text{far}}$)
 - Brine saturation distribution ($S_{e,\text{DRZ}} \ll S_{e,\text{far}}$)
- Increased porosity (damage) also desaturates medium
 - Quickly dry out from fully saturated IC?
 - Slowly evolve from variably saturated IC?
- Relative permeability to brine may be lower in DRZ



IC = initial conditions





EDZ = Excavation Damaged Zone

EdZ = Excavation disturbed Zone

Task E Step 2

2. TH²M heated brine inflow test case

a) Predict brine production during **increases** and **decreases** in T




- $k[\epsilon(\sigma(T))]$ Permeability as a function of strain, due to stress, due to thermal expansion
- Slower permeability decrease and thermal expansion during heating (i.e., creation of dam)
- Quick permeability increase and thermal contraction during cooling (i.e., release dam)

Task E Step 3 (Alternatives)


1. BATS brine / gas tracer tests
2. ERT/AE data to constrain brine inflow estimates
 - ERT sensitive to brine saturation, daily ERT tomograms
 - AE source locations to confirm changes in ϕ, k
3. Predict behavior of BATS seals / GRS lab tests
 - GRS laboratory experimental data (WIPP brine & salt)
 - BATS strain, T data in cement plugs (Sorel & salt concrete)
4. Additional C processes
 - Include water types explicitly in models (fluid inclusions, clay dehydration)
5. Effects of viscoplastic creep on brine production

Based on interest of teams: Chose one/two?



Summary

- Task E brine inflow test cases
 - Unheated: Small-scale brine inflow (1987-1991)
 - Heated & Unheated: BATS test (ongoing)
- Task E evolution
 - $H^1/T \rightarrow TH^1 \rightarrow H^2/H^2M \rightarrow TH^2/TH^2M$
 - **Q: Is H^2 needed to explain brine inflow observations?**
 - **Q: Is $\Delta T \rightarrow \Delta\sigma \rightarrow k, \phi$ feedback needed to explain brine inflow observations?**
 - Uncertainty quantification & parameter sensitivity at each step (w/ added complexity)



Continuous miner at WIPP

Task E Interactions M3 – M4

- Summary of Task E Interactions
 - 26-30 Apr 2021: DECOVALEX M3
 - 16 Jun 2021: Task E optional #1
 - 11 Aug 2021: Task E optional #2
 - 29 Sep 2021: Task E optional #3
 - 8-12 Nov 2020: DECOVALEX M4
- “Optional” Discussions Meetings are Successful
 - <90 minutes each
 - Discussion between participants
 - Clear up data issues
 - Point out errors/inconsistencies in task specification



Task E (Thursday, Stream 3) Preview

- Teams: DOE, COVRA, GRS, BGR, RWM
- Results and Discussion on Step 1b
 - BATS two-phase flow
 - Two-phase flow model initialization
- Next steps
 - BATS heater and brine production
 - BATS gas tracer test

BATS 1.0 over coring Oct 2021



Thank you!

