


DECOVALEX23: Task C, Step 1

SNL Preliminary Thermal Hydrologic Modeling of Full-Scale Heater Experiment




PRESENTED BY

Teklu Hadgu, Thomas Dewers and Edward Matteo

Sandia National Laboratories is a multimission laboratory managed and operated by National Technology and Engineering Solutions of Sandia LLC, a wholly owned subsidiary of Honeywell International Inc. for the U.S. Department of Energy's National Nuclear Security

Sandia National Laboratories is a multimission laboratory managed and operated by National Technology & Engineering Solutions of Sandia, LLC, a wholly owned subsidiary of Honeywell International Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.



DECOVALEX23
Interim Meeting

Feb 21, 2022





Outline



- Preliminary thermal and TH simulations of Step 1
- Meshing and representation of tunnel
- PFLOTRAN simulations
- Summary of modeling results and future work

I. Step 1: TH Modeling using PFLOTRAN

- Preliminary thermal and thermal-hydrology modeling of Step 1 for the full-scale in-situ heater test
- Used properties developed in Step 0
- Used Task C specified material properties:
 - Thermal conductivity vs saturation equation
 - Density of water equation with constant thermal expansion
 - Porosity and pore compressibility equation
- Heating schedule of the three heaters





Initial condition:

- $T = 15 \text{ }^{\circ}\text{C}$ everywhere
- Hydrostatic pressure at opalinus clay
- Bentonite blocks initial condition:
 - Calculated liquid saturation = 0.919
- Granular bentonite initial condition:
 - calculated liquid saturation = 0.227

Diffusion Coefficient:


- Liquid phase: $2.0 \times 10^{-9} \text{ m}^2/\text{s}$
- Gas phase: $2.42 \times 10^{-5} \text{ m}^2/\text{s}$

Boundary Condition:

- Column outer boundary at 2.0 MPa and 15 °C
- Specified heat applied at heater boundary



Opalinus Clay:

- Anisotropy in permeability and thermal conductivity




Domain size: 50 m x 50 m x 50 m


Step 1: Meshing of Heaters and Bentonite Blocks




Step1: Representation of the Experimental Tunnel



Step 1-Thermal: Prediction of Temperature Distribution along Tunnel Axis at 5 Years




Step 1-Thermal: Prediction of Temperature Distribution at 5 Years: Cross-section at Heater 2



Step 1-Thermal: Prediction of Temperature Evolution at Selected Observation Points



Task C, Step 1: Thermal-Only Temperature Results



Summary



- Conducted preliminary Task C, Step 1 PFLOTRAN simulations using material properties developed in Step 0
- Next Steps:
 - Updated Step 1 thermal and thermal-hydrology modeling
 - Comparison of modeling results with experimental data