



Gate Set Tomography of a Logical Qubit



Kenneth Rudinger¹, Julie Campos^{1,2}, Mario Morford-Oberst¹, Erik Nielsen¹, Stefan Seritan¹, T. Setso Metodi¹, Robin Blume-Kohout¹



¹Quantum Performance Laboratory, Sandia National Laboratories

²Duke University

American Physical Society March Meeting 2022

Sandia National Laboratories is a multimission laboratory managed and operated by National Technology and Engineering Solutions of Sandia, LLC., a wholly owned subsidiary of Honeywell International, Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.



Gate Set Tomography of a Logical Qubit



- Key takeaway: Gate set tomography shows promise as a tool for characterizing logical qubits; questions remain!

Open questions about logical qubits




Open questions about logical qubits

- How should we *describe* logical operations on logical qubits?

II	II	IX	IY	IZ	IX	IX	IX	IX	IY	IY	IY	IY	IZ	IZ	IZ	IZ
IX																
IY																
IZ																
XI																
XX																
XY																
XZ																
YI																
YX																
YY																
YZ																
ZI																
ZX																
ZY																
ZZ																

Open questions about logical qubits

- How should we *describe* logical operations on logical qubits?
- How should we *characterize* logical operations on logical qubits?



Open questions about logical qubits

- How should we *describe* logical operations on logical qubits?
- How should we *characterize* logical operations on logical qubits?
- What can we *learn* from logical qubit characterization?



Open questions about logical qubits




- How should we *describe* logical operations on logical qubits?
- How should we *characterize* logical operations on logical qubits?
- What can we *learn* from logical qubit characterization?
- → Can we build predictive and debugging tools for logical qubits?




Open questions about logical qubits



- How should we *describe* logical operations on logical qubits?
- How should we *characterize* logical operations on logical qubits?
- What can we *learn* from logical qubit characterization?
- → Can we build predictive and debugging tools for logical qubits?
- → Can we use (or adapt) existing physical qubits frameworks for understanding logical qubit behavior?





Understanding physical qubits





This picture is *roughly* correct!
What about logical qubits?

Why does QCVV work?




Why does QCVV work?



Logical GST



GST is a powerful tool for debugging and predicting behavior of small numbers of physical qubits. Can we use GST on logical qubits?



Why GST?




- GST works well for characterizing (physical) one- and two-qubit systems.
 - *Demonstration of qubit operations below a rigorous fault tolerance threshold with gate set tomography*, Nat. Commun. 8, 14485 (2017)
 - *Demonstration of a parametrically activated entangling gate protected from flux noise*, Phys. Rev. A 101, 012302 (2020)
 - *Machine Learning of Noise-Resilient Quantum Circuits*, Phys. Rev. X Quantum 2, 010324 (2021)
 - *Precision tomography of a three-qubit donor quantum processor in silicon*, Nature, 601, 348–353 (2022)
 - *Quantum logic with spin qubits crossing the surface code threshold*, Nature, 601, 343–347 (2022)
 - Etc.
- GST does an excellent job of characterizing qubits that aren't perfectly well-behaved (exhibit leakage, drift, other non-Markovian errors) *without* necessarily understanding or fully capturing those dynamics.
- Logical qubits *should* behave like nice two-level systems. If so, characterize with GST! If not, capture violation of that model with GST.

Gate Set Tomography - Review




- Circuits: A collection of structured, “process-tomography-like” circuits.
- Analysis: Maximum likelihood estimation on observed outputs
- Output: Process matrix estimates for quantum logic operations (gates, state preparations/measurements).
- Number of circuits $< 100 - 1000$ s
- Estimates are self-consistent and Heisenberg-limited in accuracy; provide built-in Markovianity check (how well does the estimate fit the data?)




Logical GST

- What does it even mean to “do logical GST”?
- Simple “naïve” approach (don’t criticize me yet!)
 - Take GST circuits and run them on a logical qubit (simulation or experiment), promoting physical gates to logical gates. (Button-pushes are *logical operations not physical*. E.g., $H \rightarrow H^{\otimes 7}$)




Logical GST

- What does it even mean to “do logical GST”?
- Simple “naïve” approach (don’t criticize me yet!)
 - Take GST circuits and run them on a logical qubit (simulation or experiment), promoting physical gates to logical gates. (Button-pushes are *logical operations not physical*. E.g., $H \rightarrow H^{\otimes 7}$)
 - Optional: Have a **new button** for QEC.



Logical GST- Let's do it!



- Let's do this on a simple logical gate set:
 - Steane $[[7,1,3]]$ code
 - All-to-all CNOT connectivity
 - $\{H, S, QEC\}$ logical operations
 - Simple error model:
 - *Only* error is 10% depolarization on physical S, S^\dagger ($S_{\text{logical}} = S \otimes S^\dagger \otimes S \otimes S^\dagger \dots$)
 - Maximum germ depth is 16; 774 circuits.
 - 1000 shots per circuit.
 - Simulation run using Logical Qubit Simulator (LoQS)- a hybrid density matrix/Monte Carlo simulation tool built on pyGSTi and QuantumSim (not yet publicly available, but soon we hope!)
 - 5.5 wall-clock-hours; 790 compute-hours. (Most of the time spent on circuits with rounds of QEC).

Logical GST



- What's it look like?!
- Look at *physical* GST first:

Figure 1. Model violation summary.




Figure 2. Model violation per iteration.




Figure 3. Histogram of per-circuit model violation.




Table 1. Comparison of estimated gates to targets.

Gate	Entanglement Infidelity	1/2 Trace Distance	1/2 Diamond-Dist	Eigenvalue Ent. Infidelity	Eigenvalue 1/2 Diamond-Dist
Gh:0	5×10^{-7}	0.000698	0.000698	0	0.000043
Gp:0	0.073964	0.073991	0.074478	0.07459	0.075084
\square	2×10^{-7}	0.000435	0.000435	2×10^{-7}	0.000653

Physical GST

Physical GST



Figure 1. Model violation summary.




Figure 2. Model violation per iteration.




Figure 3. Histogram of per-circuit model violation.




Table 1. Comparison of estimated gates to targets.

Gate	Entanglement Infidelity	1/2 Trace Distance	1/2 Diamond-Dist	Eigenvalue Ent. Infidelity	Eigenvalue 1/2 Diamond-Dist
Gh:0	5×10^{-7}	0.000698	0.000698	0	0.000043
Gp:0	0.073964	0.073991	0.074478	0.07459	0.075084
\square	2×10^{-7}	0.000435	0.000435	2×10^{-7}	0.000653

Physical GST



Figure 1. Model violation summary.




Figure 2. Model violation per iteration.




Figure 3. Histogram of per-circuit model violation.




Table 1. Comparison of estimated gates to targets.

Gate	Entanglement Infidelity	1/2 Trace Distance	1/2 Diamond-Dist	Eigenvalue Ent. Infidelity	Eigenvalue 1/2 Diamond-Dist
Gh:0	5×10^{-7}	0.000698	0.000698	0	0.000043
Gp:0	0.073964	0.073991	0.074478	0.07459	0.075084
\square	2×10^{-7}	0.000435	0.000435	2×10^{-7}	0.000653

Logical GST- same physical error model

Figure 1. Model violation summary.




Figure 2. Model violation per iteration.




Figure 3. Histogram of per-circuit model violation.




Table 1. Comparison of estimated gates to targets.

Gate	Entanglement Infidelity	1/2 Trace Distance	1/2 Diamond-Dist	Eigenvalue Ent. Infidelity	Eigenvalue 1/2 Diamond-Dist
Gh:0	4×10^{-7}	0.000616	0.000616	4×10^{-7}	0.000923
Gp:0	0.125196	0.125295	0.126246	0.126236	0.136838
QEC	3×10^{-7}	0.000525	0.000525	3×10^{-7}	0.000788

Logical GST

- What happened?! Markovian physical qubits but non-Markovian logical qubit?!

Logical GST- same physical error model

Figure 1. Model violation summary.




Figure 2. Model violation per iteration.




Figure 3. Histogram of per-circuit model violation.




Table 1. Comparison of estimated gates to targets.

Gate	Entanglement Infidelity	1/2 Trace Distance	1/2 Diamond-Dist	Eigenvalue Ent. Infidelity	Eigenvalue 1/2 Diamond-Dist
Gh:0	4×10^{-7}	0.000616	0.000616	4×10^{-7}	0.000923
Gp:0	0.125196	0.125295	0.126246	0.126236	0.136838
QEC	3×10^{-7}	0.000525	0.000525	3×10^{-7}	0.000788

Logical GST

- What happened?! Markovian physical qubits but non-Markovian logical qubit?!
- QEC makes previous gates *better*. *This is explicitly not Markovian.*

Logical GST- same physical error model

Figure 1. Model violation summary.




Figure 2. Model violation per iteration.




Figure 3. Histogram of per-circuit model violation.





Table 1. Comparison of estimated gates to targets.

Gate	Entanglement Infidelity	1/2 Trace Distance	1/2 Diamond-Dist	Eigenvalue Ent. Infidelity	Eigenvalue 1/2 Diamond-Dist
Gh:0	4×10^{-7}	0.000616	0.000616	4×10^{-7}	0.000923
Gp:0	0.125196	0.125295	0.126246	0.126236	0.136838
QEC	3×10^{-7}	0.000525	0.000525	3×10^{-7}	0.000788

Logical GST


- *What should the “API” for logical GST be?*
- As you may have expected, we do *not* want a “QEC button”. (Or work out valid way to model QEC operations within GST framework.)
- Follow every logical gate with a round (or more) of QEC.
E.g., $G_x \rightarrow G_x G_{\text{QEC}}$



Logical GST – Take 2



- Each button implements transversal gate followed by one round of QEC.
- H: 10^{-2} depolarization
- S, S^\dagger : $1.7*10^{-1}$ over-rotation (same infidelity as H)
- CNOT: $2*10^{-2}$ depolarization



Logical GST – Take 2



Figure 1. Model violation summary.



Figure 2. Model violation per iteration.




Figure 3. Histogram of per-circuit model violation.




Table 1. Comparison of estimated gates to targets.

Gate	Entanglement Infidelity	1/2 Trace Distance	1/2 Diamond-Dist	Eigenvalue Ent. Infidelity	Eigenvalue 1/2 Diamond-Dist
Gh:0	0.222543 \pm 0.088974	0.225698 \pm 0.092284	0.226201 \pm 0.091305	0.22176 \pm 0.086558	0.299398 \pm 0.089373
Gp:0	0.222178 \pm 0.047285	0.278262 \pm 0.063456	0.306064 \pm 0.079259	0.232854 \pm 0.050315	0.302705 \pm 0.072842
[]	0.224359 \pm 0.108209	0.297149 \pm 0.202904	0.313971 \pm 0.212221	0.224359 \pm 0.108209	0.430875 \pm 0.29547

- It works!
- Even a stochastic-only model fits the data!

Logical GST – Take 2



Figure 1. Model violation summary.




Figure 2. Model violation per iteration.




Figure 3. Histogram of per-circuit model violation.






Table 1. Comparison of estimated gates to targets.

Gate	Entanglement Infidelity	1/2 Trace Distance	1/2 Diamond-Dist	Eigenvalue Ent. Infidelity	Eigenvalue 1/2 Diamond-Dist
Gh:0	0.222543 ± 0.088974	0.225698 ± 0.092284	0.226201 ± 0.091305	0.22176 ± 0.086558	0.299398 ± 0.089373
Gp:0	0.222178 ± 0.047285	0.278262 ± 0.063456	0.306064 ± 0.079259	0.232854 ± 0.050315	0.302705 ± 0.072842
[]	0.224359 ± 0.108209	0.297149 ± 0.202904	0.313971 ± 0.212221	0.224359 ± 0.108209	0.430875 ± 0.29547

- It works!
- Even a stochastic-only model fits the data!
- What about a range of CNOT depolarizations?

Logical GST – Take 2



- Behavior is *mostly* as expected, though somewhat high N_σ values. ...some subtle non-Markovian effect?

Conclusions



- There exist regimes in which logical qubit operators are well-modeled by (Markovian) single-qubit process matrices.
- GST can be extended to logical qubits to learn those process matrices.
- The full scope of logical GST's applicability and utility remains an open question.
 - What about other codes? What about non-fault-tolerant operations? Can we extract useful information from syndrome data? Does pseudothreshold matter? Etc.
- www.pygsti.info
- Quantum Performance Laboratory looking to hire: qpl.sandia.gov
- kmrudin@sandia.gov
- Thanks to co-authors, Tom O'Brien, Marcello Caio, and you!