



Structural evolution of f-electron system under dynamic compression

Presented by: Sakun Duwal

Team members: Chad McCoy, Dan Dolan, Cody Melton, Marcus Knudson, Chris Seagle, Seth Root, Richard Hacking, Bernardo Farfan, Chris Johnson, C. S. Alexander


APS March meeting
March 16th, 2020
Chicago, IL







- ❖ Lanthanide -motivation
- ❖ Experimental methods
 - ❖ Laser shock, x-ray diffraction, Pyrometry (gas-gun)
- ❖ Results –XRD, Temperature measurements, Hugoniot data, DFT
- ❖ Summary

- ❖ Rare earth metals; technology metals
- ❖ Cell phones, color TVs
- ❖ A single iPhone contains eight different rare-earth metals; Vibration: Nd, Dy
- ❖ Batteries, lasers




3





Lanthanum	Cerium	Praseodymium	Neodymium	Promethium	Samarium	Europium	Gadolinium	Terbium	Dysprosium	Holmium	Erbium	Thulium	Ytterbium	Lutetium
La ³⁺	Ce ³⁺	Pr ³⁺	Nd ³⁺	Pm ³⁺	Sm ³⁺	Eu ³⁺	Gd ³⁺	Tb ³⁺	Dy ³⁺	Ho ³⁺	Er ³⁺	Tm ³⁺	Yb ³⁺	Lu ³⁺
115	111	109	108	106	104	103	102	100	99	97	96	95	94	93
Ionic radius in pico-meter														
[Xe] 4f ⁰ 5d ¹ 6s ²	[Xe] 4f ¹ 5d ¹ 6s ²	[Xe] 4f ³ 6s ²	[Xe] 4f ⁴ 6s ²	[Xe] 4f ⁵ 6s ²	[Xe] 4f ⁶ 6s ²	[Xe] 4f ⁷ 6s ²	[Xe] 4f ⁷ 5d ¹ 6s ²	[Xe] 4f ⁹ 6s ²	[Xe] 4f ¹⁰ 6s ²	[Xe] 4f ¹¹ 6s ²	[Xe] 4f ¹² 6s ²	[Xe] 4f ¹³ 6s ²	[Xe] 4f ¹⁴ 6s ²	[Xe] 4f ¹⁴ 5d ¹ 6s ²

- ❖ 4f shielding in lanthanides → decrease in radius → inertness from 4f characters
- ❖ **Shielding or screening effect of f-orbital < s, p, d-orbital** → lanthanide contraction
- ❖ High P phase transition sequence: hcp → Sm-Type → dhcp → fcc → dfcc. However, in Ce from fcc → fcc' → bcm → bct (4f electron hybridization)
- ❖ Systematic study of lanthanides to understand the effects of f-electrons
- ❖ Samarium – phase transitions at high pressure

Sm at high pressure: many phases and large uncertainties




- ❖ DAC studies: Sm-type $\rightarrow$ dhcp $\rightarrow$ fcc $\rightarrow$ dfcc $\rightarrow$ hP3
- ❖ Gas-gun studies below 100 GPa (1975)
- ❖ Very few DFT studies
- ❖ Huge uncertainty in P-T Hugoniot space






- Single- and two-stage gas guns, laser shock capability, multi-event hutch
- Time-resolved, in-situ measurements utilizing the tunable, high energy X-ray capabilities at the Advanced Photon Source (APS)
- Focus on diffraction, imaging, and scattering measurements; simultaneous continuum measurements



Multi-probe experiments yield simultaneous phase, P, density state





Laser interferometry to measure the surface velocity of solids moving at high speeds.





Laser, 351 nm
5 or 10 ns pulse
~100J
500 μm spot size

Velocimetry to determine pressure





- ❖ Velocimetry measurements at Sm/LiF interface
- ❖ Impedance matching method to determine the in-material states





❖ Sm-type phase stable at ambient conditions

Structural evolution at high pressure






- ❖ Sm-type phase stable at ambient conditions
- ❖ A new solid-solid phase observed at 23 GPa

Structural evolution at high pressure






- ❖ Sm-type phase stable at ambient conditions
- ❖ A new solid-solid phase observed at 23 GPa
- ❖ Onset of melting at 33 GPa

Structural evolution at high pressure







❖ Rietveld refinement suggest dfcc phase

Structural evolution at high pressure




- ❖ Sm-type phase stable at ambient conditions
- ❖ A new solid-solid phase observed at 23 GPa
- ❖ Onset of melting at 33 GPa

Structural evolution at high pressure




- ❖ Sm-type phase stable at ambient conditions
- ❖ A new solid-solid phase observed at 23 GPa
- ❖ Onset of melting at 33 GPa

c/a ratio deviates from ideal fcc lattice





- ❖ Decreasing lattice parameters with increase in pressure
- ❖ c-axis is more compressible than a-axis




- ❖ c/a ratio deviates from ideal fcc value, 2.45

Current work disagrees with the previously proposed melting




- ❖ Early shock work indicated melting based on U_s - U_p discontinuity
- ❖ XRD results suggests melting occurs at a higher pressure along the Hugoniot

DFT sparks insights into f-electron physics at play




DFT-MD, localized f-electrons



❖ Clear discrepancy in U_s - u_p


- ❖ Quality of results are highly sensitive to U/J /SOC treatment.
- ❖ Current DFT efforts struggle to reproduce cold curves near ambient when f -electrons are treated as valence, which will bias Hugoniot pressures and temperatures. **More investigation is needed for ab-initio Hugoniot for lanthanides**

DFT+U, localized f-electrons






❖ DFT+U using ELK; f-electrons are localized, but no SOC

DFT+U+SOC, “valence” f-electrons




- ❖ DFT+U+SOC using ELK; valence f-electrons
- ❖ Low pressure agreement still poor
- ❖ **Cold curve needs to be reproduced well before moving to Hugoniot**
- ❖ f-electrons participate in bonding at high pressure, but not at low pressure




- ❖ Temperature measurements made using multi-channel optical pyrometers (Avalanche photo diodes, APDs) using 4 channel system
- ❖ Sample needs to be a great emitter
- ❖ Well impedance matched with LiF (Z_{LiF} : 17.42; Z_{Sm} :15.75)

Temperature calibration for high quality data




Blackbody Source





$$T = \frac{c_2}{\lambda_m} \frac{1}{\ln\left(\frac{\epsilon_m c_1}{L_m \lambda_m^5} - 1\right)}$$

- ❖ Radiance detectors are calibrated by placing the radiance optical fiber into a blackbody source, varying the blackbody temperature over the expected range of experiment temperatures, and recording the signals, $V_{\text{Cal}}(T)$, at each temperature.
- ❖ For each detector, these calibration temperatures and signal voltages were fit to a numerical equation, to obtain smooth calibration interpolations at all relevant temperatures.








Velocimetry and emission measurements follows the same trend




Detector signals vs time, $V(t)$, are recorded on high-speed digital oscilloscopes.



Four simultaneous velocimetry and temperature measurements




Sm-Temperature calculations



$$T = \frac{c_2}{\lambda_m} \frac{1}{\ln\left(\frac{\epsilon_m c_1}{L_m \lambda_m^5} - 1\right)}$$



ϵ : emissivity ($0 < \epsilon < 1$); L_m : measured band radiance
 c_1, c_2 : radiation constants
 λ : wavelength




Gray band model

- 5 adjustable parameters to describe emissivity within each spectral band
- One emissivity changed per iteration, randomly alternating between spectral bands


Proposed phase diagram suggests melt occurs at much lower T



Melting curves of some other metals




Cerium






Jensen, JAP, 2021

Lithium



Guillaume et al, Nature Physics, 2011


- ❖ Structural study of Sm-type to dfcc to liquid
- ❖ DFT suggests f-electrons participate in bonding at higher pressure
- ❖ Temperature measurements constraining Hugoniot in P-T-Rho space
- ❖ Melting reported at lower temperature than DAC experiments




Acknowledgements



- ❖ 1640: Luke Shulenberger, C. Scott Alexander, Thomas Mattsson, Andrew Porwitzky
- ❖ DICE: Lena Pacheco, Keith Hodge
- ❖ STAR: Bernardo Farfan, Chris Johnson, John Martinez, Roberto Palomino, Rafael Sanchez
- ❖ DCS: Adam Schuman, Nick Sinclair, Yuelin Li, Korey Mercer, Ray Gunawadija, Xiaoming Wang, Pinaki Das, Austin Spencer, Paulo Rigg





Thank you!