



Thermal expansion, fluid flow, and thermal shock of cement and a cement/steel interface at elevated pressure and temperature

Stephen J. Bauer¹, Perry Barrow¹, William Kibikas^{1*},
Tatiana Pyatina², Toshifumi Sugama²

1 – Sandia National Laboratories, Albuquerque, NM
87175

2 – Brookhaven National Laboratory, Upton, NY 11973

2022 Geothermal Rising Conference





Authors and Organizations



Presenter: William Kibikas


R&D Geoscience Engineer

Sandia National Laboratories

**Sandia National
Laboratories** NM 87175, USA



**Brookhaven National
Laboratory** NY 11973, USA





Outline


- 1. Motivations**
- 2. Materials and methodology**
- 3. Experimental results**
- 4. Post-test analysis**
- 5. Conclusions**





Motivations

Importance of Borehole Cement Interface

- Cement is a critical component of well stability
- Cement seals surrounding rock from wellbore, protects from casing corrosion, and supports steel casing



Borehole schematic from Cuevas,
2021
2022 Geothermal Rising Conference




Vertical view showing ITZ between cement, steel, and rock from Yang *et al.*, 2022

- Weakest point in cement between the cement-steel interface or interfacial transition zone (ITZ)
- ITZ strength depends upon material properties and borehole conditions (pressure, temperature, etc.)

Cement-Steel Interface in Geothermal Systems

- Enhanced geothermal systems (EGS) typically inject cold water into hot formations ($T > 150 \text{ }^{\circ}\text{C}$)
- The 'thermal shock' from reducing temperature is expected to affect the cement-steel interface
 - Potentially weaken the bond and degrade the cement strength
- Thermomechanical behavior around borehole due to cold water injections remains largely uncharacterized





Geothermal system schematic modified from *Jordan et al, 2020*




Materials and Methodology

Borehole Cement Sample



- Thermally Insulating Lightweight Shock-Resistant Cement (TILRSC) developed by Brookhaven National Laboratory (for composition see *Sugama and Pyatina, 2021*)
- Cement sample tested is sheathed around steel tube simulating borehole ITZ

Test Plan



A – Assembled sample in test system

B – Loading frame

C – Pore pressure pumps

D – Pressure vessel with insulating furnace

E – Confining pressure pump


1. Sample confined at pressure of 20.7 MPa
2. Pore pressure applied at upstream and downstream ends to 17-17.3 MPa, upstream slightly higher to maintain fluid flow
3. Temperature increased to 100 °C and allowed to equilibrate
4. Cold water ($T < 40$ °C) injected with rapid flow rate at the upstream end to thermally shock sample for ~3 minutes
5. Temperature allowed to equilibrate with confining fluid
6. Repeat steps 3-5 at 200 °C
7. Unload pressures



Experimental Results




Cement Creep Test



- Full test approximately 170 hours
- Effect of temperature was characterized by lateral displacement (red)
- Thermal shocking occurred between **20-70 hours** (100 °C) and **110-160 hours** (200 °C)
- Negative displacement indicates contraction, positive displacement indicates expansion


100 °C – Thermal Shock

- Temperature increase to 100 °C causes significant compaction
- Two thermal shock tests conducted on same day (**arrows**)
- Cold water injection caused rapid, minor contraction
- Thermal shocks increased compaction but did not change displacement rate after





200 °C – Thermal Shock

- Temperature increase initially triggers significant expansion then contraction
- Four thermal shock tests, two each conducted on the same day (**arrows**)
- Cold water injection caused large rapid contraction then slow expansion as the cement-steel re-equilibrated to the surrounding temperature



Thermal Shock - Normalized Displacements



- Contraction is very rapid but stops after thermal shock test ends (~ 3 min)
- Expansion following contraction is smaller and occurs at a slower rate
- Larger thermal gradient produces greater contraction of the sample after each test




Post-Test Analysis

Post-Test Sample






Cross-section of cement sample shows possible **fractures (1)** and **altered zone (2)** around the cement-steel interface



Microscope image of interface shows apparent cracking but **no separation at interface**



Cement-Steel Interface



- 3D images of cement-steel interface after testing
- Nikon Eclipse LV 150 3D microscope
- Cement-steel bond remains coherent post-test



Conclusions



Conclusions

- Cement compacts irreversibly during heating at pressure
- Cold water injection enhances cement contraction, depending on the temperature difference between the fluid and the cement-steel
- Observed fracturing and cement contraction/expansion during thermal shock tests suggest thermal shocks are major cause of material modification around interface
- Experimental results and post-test analysis indicate integrity of cement-steel interface is maintained throughout testing



References and Acknowledgements

References

Cuevas, N. H. (2021). An approximate inversion scheme for surface-borehole electromagnetic in the presence of steel casing: 1D implementation. *Geophysics*, 86(2), E111-E121.

Jordan, T., Fulton, P., Tester, J., Bruhn, D., Asanuma, H., Harms, U., & Smith, J. (2020). Borehole research in New York State can advance utilization of low-enthalpy geothermal energy, management of potential risks, and understanding of deep sedimentary and crystalline geologic systems. *Scientific Drilling*, 28, 75-91.

Sugama, T., & Pyatina, T. (2021). Hydrophobic Lightweight Cement with Thermal Shock Resistance and Thermal Insulating Properties for Energy-Storage Geothermal Well Systems. *Materials*, 14(21), 6679.

Yang, Y., Li, L., Yu, W., Zhou, Y., Zhu, K., & Yuan, B. (2022). The Application of Breakthrough Pressure in the Evaluation of the Sealing Ability of Cement–Casing Interface and Cement Matrix in Underground Gas-Storage Wells. *Processes*, 10(4), 620.

Acknowledgements

We graciously acknowledge the Geothermal Technologies Office for supporting this research and specifically Arlene Anderson. Sandia National Laboratories is a multimission laboratory managed and operated by National Technology and Engineering Solutions of Sandia, LLC., a wholly owned subsidiary of Honeywell International, Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DENA0003525. **SAND2022-5257 C**



Thank You!