



Sandia  
National  
Laboratories

# Design and Testing of a Prototype Particle/sCO<sub>2</sub> Heat Exchanger at Gen3 Operating Conditions

Kevin Albrecht, Dereje Amogne, Ashley Byman,  
David Moon, Neville Jordison, Clifford Ho

SolarPACES 2022

Power Cycles

Friday, September 30, 2022





Sandia National Laboratories is a multimission laboratory managed and operated by National Technology & Engineering Solutions of Sandia, LLC, a wholly owned subsidiary of Honeywell International Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.

# Introduction

- Particle CSP is being developed to enable high efficiency sCO<sub>2</sub> power cycles
- The particle/sCO<sub>2</sub> heat exchanger is a critical enabling technology for these systems
- Moving packed-bed heat exchangers are a promising option
- Solex, VPE, and Sandia have been collaboratively developing advanced moving packed-bed heat exchangers



# Prior 20 kW<sub>t</sub> Stainless Steel Prototype Testing




Prototype heat exchanger designed and built as part of G3P3 program

Prototype performance measured using integrated particle and sCO<sub>2</sub> flow loops

Data was used to verify heat exchanger thermal model in Sierra/Aria



# 20 kW<sub>t</sub> Nickel Heat Exchanger Design Requirements



## Design Requirements:


- Design temperature: 800 °C
- Design pressure: 25 MPa
- Nickel alloy construction (IN617)
- Overall HTC: >450 W/m<sup>2</sup>-K
  - <3 mm particle channel width
  - sCO<sub>2</sub> microchannel enhancement
- Pressure Drop: <30 kPa
- Reduction in material per surface area

# 20 kW<sub>t</sub> Nickel Heat Exchanger Modeled Performance





- Model performance is based on stochastic analysis considering uncertainty in input parameters (conductivity, near-wall resistance, flow uniformity, sCO<sub>2</sub> HTC)
- Expected overall heat transfer coefficient is **603 W/m<sup>2</sup>-K** based on input parameters verified against 20 kW data or **526 W/m<sup>2</sup>-K** based on 90% confidence level

# Heat Exchanger Test Facility Upgrades



# Revised Particle and sCO<sub>2</sub> Flow Loop Geometric Design



# sCO<sub>2</sub> Flow Loop Assembly and Commissioning



- System has been operated up to temperatures of 500 °C using electric heat addition at 200 g/s and 17 MPa
- Recuperator and cooling heat exchangers appear to be over designed and within pressure drop allocations
- Pump performance map matches vendor data corrected for sCO<sub>2</sub> properties
- Electric heater is controllable and doesn't show any evidence of local hot spots

# Particle Flow Loop Assembly and Commissioning



- Particle system has been assembled with third-party prototype heat exchanger installed
- Skip hoist has been installed and integrated with LabVIEW control system and demonstrated up to 300 °C at 200 g/s
- Revised weigh hopper design has been installed and used as feed hopper for skip hoist
- Final item to be modified is the particle heater upgrade to achieve temperatures up to 800 °C



# Skip Hoist System Integration




## Design Requirements:

- Maximum flow rate: 300 g/s
- Operating temperature:  $>600$  °C
- Particle inventory: 22 kg
- Cycle time:  $< 75$  s
- Lift height: 14 ft (vertical)
- Agnostic to particle type
- Incorporate horizontal conveyance
- Low particle abrasion



# 60 kWt Particle Electric Heater



- Electric heater design uses cartridge heater elements to create a shell-and-tube geometry
- Heater element count based on heat flux limitation for particle heat transfer coefficient

# Summary



Revised particle and sCO<sub>2</sub> flow loop assembly and commissioning has been completed up to temperature of 500 °C and operating pressures of 17 MPa

Particle-to-sCO<sub>2</sub> heat exchanger with Gen3 operating conditions is nearing manufacturing completion

Testing of the particle-to-sCO<sub>2</sub> heat exchanger at Gen3 operating conditions should be completed in the last quarter of 2022



# Acknowledgements

Sandia would like to acknowledge the contributions of industry partners VPE and Solex. This work was funded in part or whole by the U.S. Department of Energy Solar Energy Technologies Office under Award Numbers 34211, 34152, and 37371.

Technology Managers: Matthew Bauer and Vijay Rajgopal



Sandia National Laboratories is a multimission laboratory managed and operated by National Technology & Engineering Solutions of Sandia, LLC, a wholly owned subsidiary of Honeywell International Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.