

Southwest Regional Partnership on Carbon Sequestration (Phase III)



Topical Report: Quantitative Risk Assessment

December 5, 2023

Authors:

Ting Xiao, Si-Yong Lee, Shaoping Chu, Ken Hnottavange-Telleen

U.S. Department of Energy Award Number:
DE- FC26-05NT42591.

Submitting Organization:
Energy and Geoscience Institute
The University of Utah
423 Wakara Way
Salt Lake City, Utah 84108

Abstract

Carbon capture, utilization, and storage (CCUS) in geological formations plays a key role in mitigating anthropogenic CO₂ emissions and achieving the aggressive goal of net-zero greenhouse gas emissions. Quantitative risk assessment is crucial for ensuring the safety and reliability of geologic carbon storage (GCS) by evaluating CO₂ migration in subsurface, forecasting potential leakage and induced seismicity risks, and optimizing operational and monitoring plans. We present the use, progress, and research trends of risk assessment from the Southwest Regional Partnership on Carbon Sequestration (SWP) as an example of large-scale CCUS projects in North America. The information provided in this report can help readers understand the significance of risk and uncertainty assessment and apply them effectively in large-scale CCUS projects.

Table of Contents

Abstract.....	2
1. Introduction.....	5
2. Geomechanical Risk and Uncertainty.....	5
3. Risks of Storage Capacity and Reservoir Performance	7
4. Quantitative Brine and CO ₂ Leakage Risk Assessment.....	9
4.1. Legacy Well Leakage Risk Assessment by the NRAP Tool	9
4.2. Wellbore and Caprock Leakage Risk Assessment	11
4.3. Potential Chemical Impacts of Leakage on the USDW Aquifer.....	12
5. Uncertainty Reduction	13
6. Summary.....	14
Acknowledgement	15
Disclaimer.....	15
References.....	15

List of Figures

Figure 1. Simulated CO ₂ gas saturation during injection for case #12 (a), cross-plot of observed vs. predicted F value at t=1 year (b), PDFs and contour map of CDF for F value (c), F-value after 1 year injection [i] caprock Poisson's ratio vs. caprock Young's modulus, [ii] caprock friction angle vs. caprock Young's modulus, [iii] caprock friction angle vs. caprock Poisson's ratio, [iv] R' index vs. caprock Young's modulus, [v] R' index vs. caprock Poisson's ratio, and [vi] R' index vs. caprock friction angle.	7
--	---

Figure 2. Cumulative distribution functions (CDFs) of emulated cumulative oil production and net CO ₂ storage using response surface models [11].	8
--	---

Figure 3. Long-term CO₂ trapping mechanisms at the FWU: (a) the FWU reservoir model [17], (b) simulated major trapping mechanisms over time [17], and (c) simulated porosity loss after 600 years [16].

..... 9

Figure 4. Injection wells, legacy wells, and shallow groundwater monitoring wells in the FWU.10

Figure 5. Quantitative risk assessment of potential leakage through wells and caprock. 11

Figure 6. Approaches of potential chemical impacts of CO₂ leakage on the USDW aquifer. 13

Figure 7. Reservoir simulation models created over time and the forecasted accumulative CO₂ leakage with different generations of reservoir models: (a) first generation of dynamic history match (DHM) model (2015 and 2016, DHM1 and DHM2) [31], (b) updated DHM model (DHM3), (3) updated DHM model with hydrostratigraphic units (HU) [32], and (4) the forecasted accumulative CO₂ leakage at the end of simulation after 72 years (22 years injection and 50 years post-injection monitoring). Uncertainty reduces with the updates of the reservoir models. 14

List f Tables

Table 1. Wellbore integrity permeability distribution of different cases..... 10

1. Introduction

The demand for low-carbon energy sources is increasing worldwide to mitigate the effects of greenhouse gas emissions and limit the rise of global average temperature. The United States (U.S.) has set an ambitious goal of achieving a carbon-pollution-free power sector by 2035 and net-zero greenhouse gas emissions by 2050 [1]. Carbon capture, utilization, and storage (CCUS) in geological reservoirs is among the key strategies being employed to achieve this goal and reach mid-century climate targets [2,3].

The Southwest Regional Partnership on Carbon Sequestration (SWP) has conducted its Phase III since 2013, and has successfully injected and stored approximately 800,000 metric tons of CO₂ in an active CO₂-enhanced oil recovery (CO₂-EOR) site, the Farnsworth Unit (FWU) in northern Texas [4–6]. The SWP project has demonstrated commercial CCUS field operations, including reservoir engineering, monitoring, simulations, and risk evaluations, to ensure safe and secure sequestration of CO₂. The SWP project has also contributed significantly to the development of best practices manuals for geologic carbon storage. Overall, the SWP project has made substantial progress in advancing the commercial deployment of CCUS technologies, providing valuable insights and lessons for future CCUS projects.

Quantitative risk and uncertainty assessment for the SWP FWU project includes CO₂ storage capacity and trapping mechanisms, leakage pathways through wells and caprocks, CO₂ leakage into overlying USDWs, and geomechanical risks and induced seismicity [7]. Geo-cellular models created with characterization data, along with advanced approaches have been employed to improve the effectiveness of risk quantification. This report reviews the latest findings of risk and uncertainty assessment and provides insights from the SWP project, to guide future risk assessment applications in large scale CCUS projects.

2. Geomechanical Risk and Uncertainty

The investigation of geomechanical risk assessment – specifically, caprock failure – attributable to CO₂ injection, as presented in a simplified hypothetical geological model, was the focus of research

undertaken by Lee et al. [8]. Their comprehensive approach amalgamates the implementation of a multilaminate model [9], the creation of a Response Surface Model [10] in conjunction with the Box-Behnken design, the execution of associated numerical modeling experiments, and the utilization of Monte Carlo simulations. Probability distributions to encapsulate the inherent variability (elastic and mechanical properties of the caprock and aquifer formations) and uncertainty in prediction estimates (vertical displacement, total strain, and F value) were employed. This approach allows for a thorough probabilistic evaluation of caprock failure in association with CO₂ storage.

Lee et al. [8] concluded that while the Young's modulus of the caprock is the primary determinant of equivalent total strain, it does not provide a reliable measure for caprock integrity. The caprock can accommodate significant deformation without failure, if it possesses a low Young's modulus and high mechanical strength properties, such as the friction angle and uniaxial compressive strength. Similarly, vertical displacement was found to be an unreliable indicator for caprock integrity, as caprock failure can occur across a broad spectrum of vertical displacements, particularly when both the Young's modulus and mechanical strength properties have wide ranges. The study identified the F-value as the most dependable indicator for caprock failure, although it is a theoretical attribute (the shortest distance between the Mohr circle and the nearest failure envelop used to measure the sensitivity to failure) and not physically measurable in the field. Deviatoric stress levels were found to vary based on stress regimes, with the maximum levels observed under extensive and compressive stress regimes. Lastly, the study demonstrated the efficacy of the multilaminate framework and the Mohr-Coulomb constitutive model in providing a simplified, yet effective, probabilistic model of the mechanical behavior of fractured rocks, reducing mathematical and computational complexities.




Figure 1. Simulated CO₂ gas saturation during injection for case #12 (a), cross-plot of observed vs. predicted F value at $t=1$ year (b), PDFs and contour map of CDF for F value (c), F-value after 1 year injection [i] caprock Poisson's ratio vs. caprock Young's modulus, [ii] caprock friction angle vs. caprock Young's modulus, [iii] caprock friction angle vs. caprock Poisson's ratio, [iv] R' index vs. caprock Young's modulus, [v] R' index vs. caprock Poisson's ratio, and [vi] R' index vs. caprock friction angle.

3. Risks of Storage Capacity and Reservoir Performance

In the FWU CO₂-EOR project, the primary objectives are to enhance oil production and to permanently sequester as much CO₂ as possible. The uncertainties of co-optimization of CO₂ sequestration and oil recovery were quantified with Monte Carlo sampling, response surface methodology (RSM), and machine learning (ML) approaches (Fig. 2) [11–14]. Critical uncertainty parameters of reservoir permeability, reservoir permeability anisotropy, water alternating gas (WAG) cycle, bottom hole injection pressure, initial oil saturation, and oil price were identified. These studies provided useful insights for understanding the potential of CO₂ sequestration at a CO₂-EOR site and increasing the confidence level for decision-making and management to optimize field operations.




Figure 2. Cumulative distribution functions (CDFs) of emulated cumulative oil production and net CO_2 storage using response surface models [12].

Long-term CO_2 storage capacity and trapping mechanisms at the FWU were evaluated through numerical simulations and polynomial chaos expansion (PCE) [15–17]. The trapping mechanisms of hydrodynamic trapping, oil dissolution trapping, aqueous dissolution trapping and mineral trapping were specifically evaluated (Fig. 3). Results suggest that hydrodynamic trapping and oil dissolution trapping are the two major trapping mechanisms (Fig. 2 (b)) [15,18]. Mineral dissolution near the injection well may cause up to a 2.7% increase in porosity with WAG cycles by the end of injection phase, and precipitation near the production well may cause porosity reduction after 1,000 years, indicating slight mineral trapping [16]. In a risk assessment study of the FWU, mineral trapping after 600 years could be from negligible to 10% with low and high reactive surface area (RSA) settings (Fig. 2 (c)) [17].




Figure 3. Long-term CO₂ trapping mechanisms at the FWU: (a) the FWU reservoir model [18], (b) simulated major trapping mechanisms over time [18], and (c) simulated porosity loss after 600 years [17].

4. Quantitative Brine and CO₂ Leakage Risk Assessment

4.1. Legacy Well Leakage Risk Assessment by the NRAP Tool

Potential CO₂ and brine leakage from legacy wells at the FWU was analyzed using National Risk Assessment Partnership (NRAP) tools of Integrated Assessment Model for Carbon Storage (NRAP-IAM-CS) [19] and Reservoir Reduced-Order Model Generator (RROM-Gen) [20].

Storage reservoir simulation results of 11 permutation scenarios provided different pressure and CO₂ saturation results as the input for the leakage risk assessment. Simulation duration was assigned with 25 years of injection and 50 years of post-injection site care (PISC) period. These fields were converted by RROM-Gen and inputted to the NRAP-IAM-CS for risk quantification of CO₂ and brine leakage calculations. About 31 legacy wells were identified as potential leakage pathways (Fig. 4). Several different wellbore permeability probability distribution models were examined (Table 1). In each case, 1,000

realization probability simulations were conducted by sampling among the 11 reservoir simulation results (MS8 topical report).




Figure 4. Injection wells, legacy wells, and shallow groundwater monitoring wells in the FWU.

Table 1. Wellbore integrity permeability distribution of different cases.

Model	Distribution Type	Wellbore Permeability (m ²)		
		Minimum	Medium	Maximum
Alberta	Uniform	10 ⁻²⁰ , 95.4%	10 ⁻¹⁷ -10 ⁻¹⁴ , 4.4%	10 ⁻¹³ -10 ⁻¹² , 0.2%
Gulf of Mexico	Uniform	10 ⁻²⁰ , 88%	10 ⁻¹⁷ -10 ⁻¹⁴ , 11.4%	10 ⁻¹³ -10 ⁻¹² , 0.6%
FutureGen_Low	Log-normal	10 ⁻²⁰ , 90%		10 ⁻¹⁷ -10 ⁻¹⁵ , 10%
FutureGen_High	Log-normal	10 ⁻²⁰ -10 ⁻¹⁸ , 90%		10 ⁻¹⁵ -10 ⁻¹³ , 10%
Open Well (hypothetical)				Open wellbore, 100%
Cemented Well (hypothetical)				5×10 ⁻¹¹ , 100%

The results suggest that multiple factors can affect the potential CO₂ and brine leakage risk, such as wellbore pressure, CO₂ saturation in the reservoir, the distance between a legacy well and the nearby injection wells, and wellbore integrity condition. In the worst scenario of open well condition for all the legacy wells, the results suggest that about 10,000 tons (0.1% of the total injected CO₂ of about 10 million tons) may leak into the overlying underground source of drinking water (USDW) aquifer at the end of 50 years PISC period. With the cement well setting for all the legacy wells and hypothetically assuming all wellbores fail, the accumulative leakage at the end of PISC period is 0.04% of the total injected CO₂. Per Table 1, the likelihood of these two well integrity scenarios is near zero. Details of this assessment can be referred to the Milestone Report MS8 and Chu et al., [20].

4.2. Wellbore and Caprock Leakage Risk Assessment

Leakage risks through wellbores, caprocks, and faults at the FWU were evaluated using multiple approaches, including response surface methodology (RSM)[21], two-way coupling of hydrodynamic flow and mechanics simulations [22,23], reactive transport simulations calibrated with field observations [24], coupling of reactive transport and mechanics simulations [25], and interpretations of seismic reflection datasets [26] (Fig. 5). Results suggest that wellbore cement would maintain its integrity and structure after 100 years of interacting with CO₂. However, when CO₂ flows through any fractures between the cement and caprock, there may be a higher risk for the limestone caprock integrity [24]. CO₂ migration into the caprock and mineralogy alteration may be minimal without pre-existing fractures connecting the reservoir and the caprock because of a high capillary entry pressure [25]. According to evaluations on geomechanics changes at the field, it is unlikely for induced fractures to occur in the caprock, or for CO₂ to escape from either the caprock or the existing faults [22,23,25,26].

By considering up to 10% potential fracturing zones (micro fractures/cracks) of the FWU wellbores with permeability of 10⁻¹⁴ m², CO₂ leakage through wellbores could be negligible (< 10⁻¹⁰ kg/(m²·year)) because (1) lack of continuous leakage channels and (2) being trapped by cement [21]. These results indicate low risks on sealing formation integrity and potential risks.




Figure 5. Quantitative risk assessment of potential leakage through wells and caprock.

Natural seismicity around the FWU was characterized within a region approximately 180 km × 220 km [27]. This study suggests that the seismic risk for commercial-scale CO₂-EOR and storage at the FWU is low. A borehole geophone array consisting of 16 three-component geophones and a surface seismic array with 20 stations were deployed to monitor induced microseismicity at the FWU. Few microseismic events were detected using the surface seismic array. Continuously recorded borehole microseismic data were analyzed, and a few high-frequency (150-350 Hz) microseismic events and more than 13,000 low-frequency events (5-50 Hz) were detected from August 2019 to June 2021. The magnitudes of most detected microseismic events range from -1 to 0.5.

4.3. Potential Chemical Impacts of Leakage on the USDW Aquifer

The Ogallala (High Plains) aquifer, the largest USDW in North America, lies above the FWU. It is a major source of water for irrigation and municipal needs in northern Texas and the only USDW aquifer in the FWU area [28]. Quarterly shallow groundwater monitoring measurements date back to 2013, with no evidence of reservoir fluid infiltration into the Ogallala aquifer at the FWU. Samples of the Ogallala were collected, and CO₂-sediment interaction and trace metal release mechanisms were evaluated using laboratory-scale batch and column experiments, as well as numerical simulations (Fig. 6) [29–31]. Results suggest that CO₂ intrusion into the Ogallala sediment leads to calcite and dolomite dissolution, which releases trace metals of Mn, Zn, and U into the aqueous phase because of their impurities. Both carbonate mineral impurity and cation exchange dominate the mechanisms of trace metal release.

Risk assessment with RSM considered potential CO₂ leakage rates ranging from 0 to 30,000 kg/year (1g/s) from a single legacy well [21,32]. Results suggest that it is highly possible of detecting changes in pH, total dissolved solids (TDS), and Mn concentration within a 10 m radius from the leaky well after 10 years of leakage. However, the distance between monitoring wells and legacy wells could reach up to 1,000 m, indicating it may be difficult to detect a leakage plume solely through shallow groundwater monitoring. Effective early detection may require the use of multiple tools, such as borehole CO₂ monitoring, 4D seismicity, and water samples from deeper saline aquifers.




Figure 6. Approaches of potential chemical impacts of CO_2 leakage on the USDW aquifer.

5. Uncertainty Reduction

Risk assessment of potential leakage relies on effective reservoir modeling and simulations. Over time, as computational capacities advance and site characterization data expand and improve, reservoir simulation models evolved through several generations since the SWP FWU project (refer to Fig. 7). To quantify potential leakage (and risk of that leakage), NRAP tools and simulation results from each generation of reservoir models were used. Findings suggest that updating simulation models with site-specific characterization data is critical, as the uncertainty of the forecasted leakage rate was reduced (Fig. 7 (d)).




Figure 7. Reservoir simulation models created over time and the forecasted accumulative CO_2 leakage with different generations of reservoir models: (a) first generation of dynamic history match (DHM) model (2015 and 2016, DHM1 and DHM2) [33], (b) updated DHM model (DHM3), (3) updated DHM model with hydrostratigraphic units (HU) [34], and (4) the forecasted accumulative CO_2 leakage at the end of simulation after 72 years (22 years injection and 50 years post-injection monitoring). Uncertainty reduces with the updates of the reservoir models.

6. Summary

Risk assessment is crucial for CCUS projects, and it has been largely developed in the past ten years with numerous advanced approaches. With the goal of net-zero greenhouse gas emissions by 2050 in the U.S. and the recent amendment of the 45Q tax credit for GCS, CCUS has greatly increased the attractiveness for investment. Intensive risk and uncertainty assessment should be applied to ongoing and new CCUS projects. The SWP reached many major accomplishments and identified best “lessons learned” from risk assessment of the FWU project, serving as an example of a risk assessment framework for commercial-scale CCUS projects. A detailed overview of risk assessment in the SWP project can be also found in Xiao et al. [7].

Acknowledgement

Funding for this project is provided by the U.S. Department of Energy's (DOE) National Energy Technology Laboratory (NETL) through the Southwest Regional Partnership on Carbon Sequestration (SWP) under Award No. DE-FC26-05NT42591.

Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

References

- [1] The United States Department of State and the United States Executive Office of the President. The Long-Term Strategy of the United States: Pathways to Net-Zero Greenhouse Gas Emissions by 2050. Washington DC: 2021.
- [2] Haszeldine RS. Carbon Capture and Storage: How Green Can Black Be? *Science* (80-) 2009;325:1647–52. <https://doi.org/10.1126/science.1172246>.
- [3] Chen S, Liu J, Zhang Q, Teng F, McLellan BC. A critical review on deployment planning and risk analysis of carbon capture, utilization, and storage (CCUS) toward carbon neutrality. *Renew Sustain Energy Rev* 2022;167:112537. <https://doi.org/10.1016/j.rser.2022.112537>.
- [4] Balch R, McPherson B, Grigg R. Overview of a Large Scale Carbon Capture, Utilization, and Storage Demonstration Project in an Active Oil Field in Texas, USA. *Energy Procedia* 2017;114:5874–87. <https://doi.org/10.1016/j.egypro.2017.03.1725>.
- [5] Balch R, McPherson B, Will RA, Ampomah W. Recent Developments in Modeling: Farnsworth Texas, CO₂ EOR Carbon Sequestration Project. *SSRN Electron J* 2021:1–11. <https://doi.org/10.2139/ssrn.3821155>.
- [6] Balch R, McPherson B. Associated Storage With Enhanced Oil Recovery: A Large-Scale Carbon

Capture, Utilization, and Storage Demonstration in Farnsworth, Texas, USA. In: Huang L, editor. *Geophys. Monit. Geol. Carbon Storage*, John Wiley & Sons; 2022, p. 343–60. <https://doi.org/10.1002/9781119156871.ch20>.

[7] Xiao T, Chen T, Ma Z, Tian H, Meguerdijian S, Chen B, et al. A review of risk and uncertainty assessment for geologic carbon storage. *Renew Sustain Energy Rev* 2024;189:113945. <https://doi.org/10.1016/j.rser.2023.113945>.

[8] Lee S-Y, Mohamed FR, Lee K-H, McPherson B, Balch R, Yoon S. Probabilistic Evaluation of Geomechanical Risks in CO₂ Storage: An Exploration of Caprock Integrity Metrics Using a Multilaminate Model. *Energies* 2023;16:6954. <https://doi.org/10.3390/en16196954>.

[9] Zienkiewicz OC, Pande GN. Time-dependent multilaminate model of rocks—a numerical study of deformation and failure of rock masses. *Int J Numer Anal Methods Geomech* 1977;1:219–47. <https://doi.org/10.1002/nag.1610010302>.

[10] Box GEP, Draper NR. *Empirical model-building and response surfaces*. John Wiley & Sons; 1987.

[11] Dai Z, Middleton R, Viswanathan H, Fessenden-Rahn J, Bauman J, Pawar R, et al. An Integrated Framework for Optimizing CO₂ Sequestration and Enhanced Oil Recovery. *Environ Sci Technol Lett* 2014;1:49–54. <https://doi.org/10.1021/ez400103z>.

[12] Pan F, McPherson BJ, Dai Z, Jia W, Lee S-Y, Ampomah W, et al. Uncertainty analysis of carbon sequestration in an active CO₂-EOR field. *Int J Greenh Gas Control* 2016;51:18–28. <https://doi.org/10.1016/j.ijggc.2016.04.010>.

[13] Ampomah W, Balch RS, Cather M, Will R, Gunda D, Dai Z, et al. Optimum design of CO₂ storage and oil recovery under geological uncertainty. *Appl Energy* 2017;195:80–92. <https://doi.org/10.1016/j.apenergy.2017.03.017>.

[14] You J, Ampomah W, Sun Q, Kutsienyo EJ, Balch RS, Dai Z, et al. Machine learning based co-optimization of carbon dioxide sequestration and oil recovery in CO₂-EOR project. *J Clean Prod* 2020;260:120866. <https://doi.org/10.1016/j.jclepro.2020.120866>.

[15] Jia W, Pan F, Dai Z, Xiao T, McPherson B. Probabilistic Risk Assessment of CO₂ Trapping Mechanisms in a Sandstone CO₂-EOR Field in Northern Texas, USA. *Energy Procedia* 2017;114:4321–9. <https://doi.org/10.1016/j.egypro.2017.03.1581>.

[16] Pan F, McPherson BJ, Esser R, Xiao T, Appold MS, Jia W, et al. Forecasting Evolution of Formation Water Chemistry and Long-term Mineral Alteration for GCS in a Typical Clastic Reservoir of the Southwestern United States. *Int J Greenh Gas Control* 2016;54:1–14. <https://doi.org/10.1016/j.ijggc.2016.07.035>.

[17] Jia W, Xiao T, Wu Z, Dai Z, McPherson B. Impact of Mineral Reactive Surface Area on Forecasting Geological Carbon Sequestration in a CO₂-EOR Field. *Energies* 2021;14:1608. <https://doi.org/10.3390/en14061608>.

[18] Ampomah W, Balch R, Cather M, Rose-Coss D, Dai Z, Heath J, et al. Evaluation of CO₂ Storage Mechanisms in CO₂ Enhanced Oil Recovery Sites: Application to Morrow Sandstone Reservoir. *Energy & Fuels* 2016;30:8545–55. <https://doi.org/10.1021/acs.energyfuels.6b01888>.

[19] Pawar RJ, Bromhal GS, Chu S, Dilmore RM, Oldenburg CM, Stauffer PH, et al. The National Risk Assessment Partnership's integrated assessment model for carbon storage: A tool to support decision making amidst uncertainty. *Int J Greenh Gas Control* 2016;52:175–89. <https://doi.org/10.1016/j.ijggc.2016.06.015>.

[20] Chu S, Viswanathan H, Moodie N. Legacy Well Leakage Risk Analysis at the Farnsworth Unit Site. *Energies* 2023;16:6437. <https://doi.org/10.3390/en16186437>.

[21] Xiao T, McPherson B, Pan F, Esser R, Jia W, Bordelon A, et al. Potential chemical impacts of CO₂ leakage on underground source of drinking water assessed by quantitative risk analysis. *Int J Greenh Gas Control* 2016;50:305–16. <https://doi.org/10.1016/j.ijggc.2016.04.009>.

[22] Zhao X, Jha B. Role of Well Operations and Multiphase Geomechanics in Controlling Fault Stability During CO₂ Storage and Enhanced Oil Recovery. *J Geophys Res Solid Earth* 2019;2019JB017298. <https://doi.org/10.1029/2019JB017298>.

[23] McMillan M, Will R, Ampomah W, Balch R, Czoski P. Coupled Geomechanical Modeling to

Assess Cap Rock Integrity and Mechanical Fault Stability: Application to Farnsworth Field Unit Project. Day 4 Fri, April 26, 2019, SPE; 2019. <https://doi.org/10.2118/195377-MS>.

[24] Xiao T, McPherson B, Bordelon A, Viswanathan H, Dai Z, Tian H, et al. Quantification of CO₂-cement-rock interactions at the well-caprock-reservoir interface and implications for geological CO₂ storage. *Int J Greenh Gas Control* 2017;63:126–40. <https://doi.org/10.1016/j.ijggc.2017.05.009>.

[25] Xiao T, Xu H, Moodie N, Esser R, Jia W, Zheng L, et al. Chemical-Mechanical Impacts of CO₂ Intrusion into Heterogeneous Caprock. *Water Resour Res* 2020. <https://doi.org/10.1029/2020WR027193>.

[26] van Wijk J, Hobbs N, Rose P, Mella M, Axen G, Gragg E. Analysis of Geologic CO₂ Migration Pathways in Farnsworth Field, NW Anadarko Basin. *Energies* 2021;14:7818. <https://doi.org/10.3390/en14227818>.

[27] Chen T, Huang L. Seismicity characterization around the Farnsworth field site for combined large-scale CO₂ storage and EOR. *Int J Greenh Gas Control* 2015;33:63–8. <https://doi.org/10.1016/j.ijggc.2014.11.024>.

[28] George PG, Mace RE, Petrossian R. Aquifers of Texas, Report 380. Texas Water Development Board; 2011.

[29] Xiao T, Jia W, Esser R, Dai Z, McPherson B. Potential Chemical Impacts of Subsurface CO₂: An Integrated Experimental and Numerical Assessment for a Case Study of the Ogallala Aquifer. *Water Resour Res* 2021;57:1–15. <https://doi.org/10.1029/2020WR029274>.

[30] Xiao T, Wang B, Xu L, Esser R, Dai Z, Cather M, et al. Underground sources of drinking water chemistry changes in response to potential CO₂ leakage. *Sci Total Environ* 2022;157254. <https://doi.org/10.1016/j.scitotenv.2022.157254>.

[31] Xiao T, Tu J, Wang B, Esser R, Bailey T, Cather M, et al. Chemical impacts of subsurface CO₂ and brine on shallow groundwater quality. *Chemosphere* 2023;138048. <https://doi.org/10.1016/j.chemosphere.2023.138048>.

[32] Xiao T, McPherson B, Esser R, Jia W, Dai Z, Chu S, et al. Chemical Impacts of Potential CO₂ and Brine Leakage on Groundwater Quality with Quantitative Risk Assessment: A Case Study of the Farnsworth Unit. *Energies* 2020;13:6574. <https://doi.org/10.3390/en13246574>.

[33] Ampomah W., Balch RS, Grigg RB. Analysis of Upscaling Algorithms in Heterogeneous Reservoirs with Different Recovery Processes. *SPE Prod. Oper. Symp.*, SPE; 2015. <https://doi.org/10.2118/173588-MS>.

[34] Moodie N, Ampomah W, Jia W, Heath J, McPherson B. Assignment and calibration of relative permeability by hydrostratigraphic units for multiphase flow analysis, case study: CO₂-EOR operations at the Farnsworth Unit, Texas. *Int J Greenh Gas Control* 2019;81:103–14. <https://doi.org/10.1016/j.ijggc.2018.09.014>.