

Recent Progress in Solid Oxide Cell Technology Analysis

at National Energy Technology Laboratory



Gregory A. Hackett, Ph.D.

Strategic Systems Analysis and Engineering



This presentation was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference therein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed therein do not necessarily state or reflect those of the United States Government or any agency thereof.

Agenda / Acknowledgements



- **Recent Progress in SOFC/SOEC/R-SOC Systems Analysis Efforts at NETL**
 - Techno-Economic and Market Assessment of Hydrogen-Fueled SOFC
 - Techno-Economic Analysis of Modularized SOFC Technology
 - Large-Scale Hydrogen Production with Solid Oxide Electrolysis Cell Technology
- **Future Work**
- **Wrap-Up**

Acknowledgements

DOE-FECM r-SOC Program
NETL SOFC FWP (FWP-1022411)

Primary Contributors

Kyle Buchheit
Alexander Noring
Arun Iyengar
Tony Burgard
Douglas Allan
Mark Woods
Dale Kearns

Techno-Economic and Market Assessment of Hydrogen-Fueled SOFC

TEA of Hydrogen-Fueled SOFC Systems





Objective/Approach

- **The objective of this study is to quantify of the cost and performance impacts associated with operating SOFC technology on pure hydrogen fuel**
- **Approach**
 - Execute an analysis of hydrogen-fueled solid oxide fuel cell configurations
 - Investigate the impact of increased heat generation resulting from the use of pure hydrogen fuel
 - Assess at a smaller scale - Preferred for comparison, given the expense and role that hydrogen may play in power generation
 - The analysis should consider system configurations that aim to mitigate the increased parasitic losses associated with the exothermic hydrogen oxidation reaction
 - Assess the impact of operating these devices in combined heat and power (CHP) configurations to cost and performance
 - Develop market assessment for CHP applications

TEA of Hydrogen-Fueled SOFC Systems



Cost Results – Levelized Cost of Electricity



Source: NETL

Market Assessment of H₂ Fueled SOFC



Introduction


- **Using energy market models (MARKAL and TIMES), NETL assessed several scenarios to examine the potential deployment of H₂ fueled SOFC**
- **Scenarios examined:**
 - State-of-the-art reference case
 - Reference with SOFC technology available
 - Net-zero by 2050 (CO₂ emissions economy wide reach net-zero)
 - Net-zero by 2050 with SOFC technology available
- **Found significant deployment potential for SOFC in the net-zero scenario since it provides an opportunity to mitigate hard-to-decarbonize industrial areas**
- **This technology pathway has the potential to reduce the marginal price of CO₂ in the net-zero scenario by almost 50%**

H₂ Production and Consumption in 2015–2075




Reference Scenario

Hydrogen Production: Reference



Hydrogen Consumption: Reference



Source: NETL

SMR and CCG are the most economically attractive options for H₂ production in Reference scenario and in the long-term future, CCG replaces SMR. H₂ demand constantly increases in the ammonia and refining industries, and there is no deployment of H₂ technologies in other sectors.



U.S. DEPARTMENT OF
ENERGY


PRELIMINARY RESULTS – SUBJECT TO CHANGE – DO NOT CITE OR QUOTE

H₂ Production and Consumption in 2015–2075


Reference Scenario with SOFC



Hydrogen Production by Technology



Hydrogen Consumption by Technology



Source: NETL


SMR and CCG are the most economically attractive options for H₂ production in Reference SOFC scenario and in the long-term future, CCG replaces SMR. H₂ demand increases exponentially after 2035; SOFC deployment is maximum in this scenario.

H₂ Production and Consumption in 2015–2075


Net-Zero Scenario with SOFC



Hydrogen Production by Technology



Hydrogen Consumption by Technology



Source: NETL

H₂ production relies on technologies with capture and storage. New H₂ demand goes to electricity production and process heat via SOFC.




U.S. DEPARTMENT OF
ENERGY

PRELIMINARY RESULTS – SUBJECT TO CHANGE – DO NOT CITE OR QUOTE

SOFC in Industrial Processes by Industry




All Industries



SOFC in Industrial Processes by Industry



Select Industries



U.S. DEPARTMENT OF
ENERGY


PRELIMINARY RESULTS – SUBJECT TO CHANGE – DO NOT CITE OR QUOTE

Electricity Production/CO₂ Emissions in 2015–2075:


Reference Scenario with SOFC



Electricity Production by Technology



CO₂ Emissions



Electricity generation from H2 - SOFC increases after 2035 and it is more competitive than Solar PV. CO₂ emissions is increasing after 2040 and higher than in Reference scenario due to industrial CO₂ increase (as result of H2 production from fossil fuels w/o CCS).



U. S. DEPARTMENT OF
ENERGY

PRELIMINARY RESULTS – SUBJECT TO CHANGE – DO NOT CITE OR QUOTE


Source: NETL

Electricity Production/CO₂ Emissions in 2015–2075:


Net-Zero Scenario with SOFC



Electricity Production by Technology



CO₂ Emissions



Electricity generation from H2 - SOFC increases after 2035 and it is more competitive than Solar PV. CO₂ emissions is increasing after 2040 and higher than in Reference scenario due to industrial CO₂ increase (as result of H2 production from fossil fuels w/o CCS).




U. S. DEPARTMENT OF
ENERGY

PRELIMINARY RESULTS – SUBJECT TO CHANGE – DO NOT CITE OR QUOTE

Source: NETL

Marginal CO₂ Price



Net Zero Ref Scenario

Net Zero with SOFC Scenario

Source: NETL



U.S. DEPARTMENT OF
ENERGY

PRELIMINARY RESULTS – SUBJECT TO CHANGE – DO NOT CITE OR QUOTE

Techno-Economic Analysis of Modularized SOFC Technology

Objective/Approach


- **Modern grid dynamics have elucidated the need for a more modular, flexible approach for development of electric generation units.**
 - Prior NETL analyses have focused on large-scale (>500 MWe) SOFC systems. When considering a dynamic grid with increased VRE penetration, the pathway toward SOFC commercialization will likely leverage smaller scale SOFC systems
- **NETL is developing a techno-economic assessment of SOFC systems at the 10–250 kWe scale to evaluate the applicability of current programmatic cost targets of \$225–250/kWe per stack and \$900–1000/kWe per system at these scales**
- **Approach**
 - Use the NGFC-DG (distributed generation) model from prior work
 - Performance models run at 250 kWe, gross
 - Performance characteristics will be nearly identical between cases
 - Run Aspen simulations for material and energy balances for scaling
 - SOFC vendor information will be used to change performance points, equipment costs, stack/module sizes, etc.

TEA of Modularized SOFC



Proposed System

- 250 kWe, gross
- Advanced case: 100% internal reformation
- Atmospheric system without carbon capture
- Air combustor
- CHP option to produce heated water at 140 °F



Source: NETL

TEA of Modularized SOFC



Preliminary Results - Performance

Performance Summary	MOD-250	MOD-250-CHP
Total Gross Power Output, kW _e	250	250
Recovered Thermal Power, kW _{th}	-	96
Total Auxiliaries, kW _e	3.5	3.5
Net Power, kW_e	246.5	246.5
Net Plant Electrical Efficiency (HHV)	60.2%	60.2%
Net Plant Thermal Efficiency (HHV)	-	23.4%
Net Plant Combined Efficiency (HHV)	60.2%	83.6%
Natural Gas Feed Flow, kg/h (lb/h)	28.1 (62.0)	28.1 (62.0)
Net Plant Heat Rate (HHV), kJ/kWh (Btu/kWh)	5,980 (5,670)	5,980 (5,670)
HHV Thermal Input, kW _{th}	410	410
Carbon Dioxide Capture Rate, %	NA	NA

HHV = Higher heating value

Source: NETL

Large-Scale Hydrogen Production with Solid Oxide Electrolysis Cell Technology

Large-Scale H₂ Production via SOEC




Objective/Approach

- **The objective of this study is to establish a detailed TEA to assess the effectiveness of incremental technology improvements needed for solid oxide electrolysis cell (SOEC) technology to achieve the U.S. DOE's Hydrogen Shot goal of hydrogen production at less than \$1 per kilogram.**
- **Approach:**
 - A literature review on long-duration SOEC stack tests informed the state-of-the-art basis for the techno-economic pathway.
 - The pathway considers incremental technology improvements to key system parameters, with system performance and cost assessed for each pathway step.
 - Each step is assessed at both atmospheric and pressurized operating conditions
 - Sensitivity studies are conducted to understand the relative impact of each parameter and identify avenues for additional cost reductions.
 - System efficiency and leveled costs of hydrogen (LCOH) for each case are presented.

Large-Scale H₂ Production via SOEC

System Design Basis

- SOEC H₂ production facility sized to an electrolysis load of 1 GW_{DC}
 - Produces ~250,000 metric tons annually, about 2.5% of annual U.S. H₂ production
- Stacks operated near the thermoneutral voltage ($\approx 1.28V$)
- All steam and heat generated by electric boilers and heaters
- H₂ recycle to ensure >10% H₂ in the feed to the stack
- Sweep air flow controlled to ensure <35 mol% oxygen in air-electrode exhaust




Source: NETL

Large-Scale H₂ Production via SOEC



SOEC Pathway



Source: NETL




U.S. DEPARTMENT OF
ENERGY

Large-Scale H₂ Production via SOEC



Preliminary Cost Results - Atmospheric & Pressurized LCOH without Electricity




Source: NETL

Large-Scale H₂ Production via SOEC



Preliminary Cost Results - Electricity Price Needed for \$1/kg



Source: NETL



U.S. DEPARTMENT OF
ENERGY

PRELIMINARY RESULTS – SUBJECT TO CHANGE – DO NOT CITE OR QUOTE


On-going / Future Work

Performance and Cost of Hydrogen Fuel Cells



- **Current Status:**
 - Market Assessment of H₂ Fueled SOFC
 - Finalize/Publish Results – May/June 2024
 - Techno-Economic Analysis of Modularized SOFC Technology
 - Finalize Results – Summer 2024
 - Large-Scale Hydrogen Production from SOEC Technology
 - Finalize/Publish Results – May/June 2024
 - Abstract submitted for full presentation at ECS PRiME – October 2024
- **Future Work:**
 - Re-engage NETL IDAES/PSE Team (dynamic operation/business case)
 - Enhance R-SOC analysis with additional configurations
 - Alternate fuels for SOFC operation modes

Integrated Energy Systems for Power and H₂



The IDAES platform is being applied to explore whether tightly coupled integrated energy systems that have the flexibility to produce both power and hydrogen should play a role in DOE's goals of decarbonizing the power sector by 2035 and broader economy by 2050.



Questions/ Comments

VISIT US AT: www.NETL.DOE.gov

 @NETL_DOE

 @NETL_DOE

 @NationalEnergyTechnologyLaboratory

CONTACT:

- Gregory Hackett
- Gregory.Hackett@netl.doe.gov

