

LA-UR- 96-2333

CONF-9603208--1

*Title:*

PLANS FOR AN ULTRA COLD NEUTRON SOURCE AT LOS ALAMOS

RECEIVED

AUG 26 1996

OSTI

*Author(s):*

Susan J. Seestrom, Tom J. Bowles, Roger Hill, Geoffrey L. Greene (Los Alamos National Laboratory, P-23)

*Submitted to:*

Japan Hadron Project Workshop- "Nuclear Physics & Fundamental Physics with Neutrons", March 15-16, 1996.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED



**Los Alamos**  
NATIONAL LABORATORY

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the University of California for the U.S. Department of Energy under contract W-7405-ENG-36. By acceptance of this article, the publisher recognizes that the U.S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. The Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy.

Form No. 836 R5  
ST 2629 10/91

#### **DISCLAIMER**

**Portions of this document may be illegible  
in electronic image products. Images are  
produced from the best available original  
document.**

# Plans for an Ultra Cold Neutron Source at Los Alamos

Susan J. SEESTROM, Thomas J. BOWLES, Roger HILL, and Geoffrey L. GREENE,  
*Los Alamos National Laboratory, Los Alamos, NM 87545, USA*

Ultra Cold Neutrons (UCN) can be produced at spallation sources using a variety of techniques. To date the technique used has been to Bragg scatter and Doppler shift cold neutrons into UCN from a moving crystal. This is particularly applicable to short-pulse spallation sources. We are presently constructing a UCN source at LANSCE using method.. In addition, large gains in UCN density should be possible using cryogenic UCN sources. Research is under way at Gatchina to demonstrate technical feasibility of be a frozen deuterium source. If successful, a source of this type could be implemented at future spallation source, such as the long pulse source being planned at Los Alamos, with a UCN density that may be two orders of magnitude higher than that presently available at reactors.

## 1. Introduction

The coherent scattering of low energy neutrons can be described by an index of refraction. The index of refraction  $n$  is a function of the coherent scattering length  $b$  of the medium and the neutron energy  $E$ :

$$n^2 = 1 - \frac{2 \pi \hbar^2 \rho b}{m E}$$

At a given energy neutrons will be totally externally reflected for glancing angles of incidence satisfying Snells law for an angle of zero in the medium. Because the index of refraction is energy dependent, there exists for most materials an energy below which neutrons are totally externally reflected for all angles of incidence. This typically occurs for neutron velocities below 5-7 m/sec ( 500 Å ), and these neutrons are called ultra cold. This leads to the possibility that UCN can be totally confined within a bottle for periods in excess of 100 seconds, making a compact source of stored neutrons for use in measurements of fundamental physics.

An area in which UCN have had and will continue to have a great impact is the study of neutron beta decay. Neutron beta decay is the simplest example of a nuclear beta decay, and one whose interpretation is not plagued by uncertainties in nuclear structure. The comparison of neutron lifetime, neutron beta-decay asymmetry, and decay rates for nuclear super-allowed beta decays can be used to test the Minimal Standard Model (MSM) prediction of V-A structure of the weak interaction. Neutron data of sufficient accuracy can be used to determine the weak vector and axial vector coupling constants  $G_V$  and  $G_A$  independent of the information from nuclear decays. The ability to make neutron lifetime measurements using both cold neutron beams and stored UCN was an important advantage in understanding the systematic effects in these measurements. We believe UCN will be similarly important in measurements of the various decay correlations in neutron beta decay.

## 2. UCN Rotor Sources

The highest UCN density to date has been achieved at the ILL reactor by converting cold neutrons into UCN by multiple reflection from the rapidly moving blades of a turbine. This technique involves Doppler shifting 40-50-m/s neutrons down into the UCN regime (< 8 m/s) and can make effective use of the high cold neutron flux from cold moderators at reactors to provide continuous beams of UCN. This device has produced measured UCN densities of 87 UCN/cm<sup>3</sup>, a world record.<sup>1)</sup> The ILL source first gravitationally decelerates the cold neutrons in an 18-m vertical guide tube between the liquid deuterium moderator and the turbine converter. This novel approach substantially reduces the losses in the transport of the cold neutrons as thick windows in the guide tube can be avoided and transport losses are less due to the smaller number of average reflections necessary for a neutron to reach the turbine. Thus, the ILL source provides the benchmark that other sources must be compared to.

The considerations for UCN production at a spallation source are quite different from a reactor. In a spallation source, a proton beam strikes a high-Z target in which approximately 1 neutron per 30 MeV of beam power (compared to about 180 MeV for a reactor) is produced.<sup>2)</sup> These fast neutrons are then thermalized and cooled in a variety of moderators. For UCN production, the spallation neutrons must be first moderated in a liquid hydrogen moderator. We will discuss UCN production at two different types of spallation sources: short pulse (SPSS) and long pulse (LPSS) spallation sources. The SPSS is characterized by facilities like LANSCE, ISIS, and IPNS where the proton pulse is typically a few microseconds or less. In this case, the pulse width of cold neutrons is determined by the moderator. At a LPSS, the pulse width may range from a millisecond to continuous wave (cw). In this case, the pulse width of the cold neutrons is dominated by the pulse width of the proton beam. A LPSS is characterized by either SINQ (cw) or the proposal at LANSCE to construct a 1-MW spallation source using the beam directly from the LANSCE accelerator.

At a SPSS, the high-energy spallation neutrons are not fully moderated and at present, the time-averaged flux is at least an order of magnitude less than that at the ILL reactor. However, one can take advantage of the pulsed nature of the

source to produce and store UCN at the peak intensities available, which are comparable to or can exceed that at a reactor. A technique for doing this was demonstrated many years ago at the ZING-P<sup>1</sup> source at Argonne National Laboratory<sup>3)</sup> and at a test setup at LANSCE. This technique involves Doppler-shifted Bragg scattering of neutrons to convert 400-m/s neutrons down into the UCN regime. A rotor carrying a scattering crystal (for example, Mica) moves away from the neutron pulse from the liquid hydrogen moderator at one half of the velocity of the neutrons that will be converted into the UCN regime. The rotor velocity required is determined by the Bragg scattering condition associated with the lattice spacing of the crystal. For mica one reflects 199 m/s neutrons in the center of mass frame; the incident neutrons are reflected back from the crystal with the same velocity at which they impinge on the crystal. In the laboratory frame, the 398 m/s neutrons are stopped. Thus, a puff of UCN is produced which then begins to expand. Some fraction of the UCN cloud will drift into a guide tube placed close to the position at which the rotor intersects the neutron beam. A shutter at the entrance to the guide tube opens while the puff is expanding and closes after a few ms. Thus, it is possible to bottle the UCN at the peak flux rather than the average flux. The penalty paid is that the filling time will be longer at a SPSS than at a reactor. However, for a rather wide range of experiments, this is not a serious concern.

At Los Alamos, we are installing such a rotor converter on the existing LANSCE cold moderator. The moderator is a gadolinium-decoupled liquid para-hydrogen LH<sub>2</sub> moderator 12 cm × 12 cm × 5 cm deep, irradiated by fast neutrons from two tungsten targets arranged in a flux-trap geometry. The moderator is viewed by a <sup>58</sup>Ni-lined guide tube with a cross-section of 6 cm × 6 cm. A Mica crystal, moving away from the neutron pulse at a velocity of 199 m/s, will be installed on the end of a rotor that rotates in synchronism with the beam pulse rate (20 Hz) at a position about 8 m from the moderator.

A schematic view of the apparatus planned at LANSCE is shown in Fig. 1. We expect to produce UCN at a density of at least 10 UCN/cm<sup>3</sup> using the existing liquid hydrogen moderator at LANSCE. It is expected that in the near future LANSCE will begin operations on a nine-month production schedule every year. This will allow a fundamental physics program to begin. A new fully coupled moderator (i.e., without any poisons) will be installed in 1997. This will increase the width of the neutron pulses and will result in an increase in the density of UCN by a factor of about three. As the power of SPSS is expected to increase from the current 100-kW level to initially 1 MW and later to 5–10 MW, one can expect substantial advances in the UCN densities to be achieved.

### 3. Cryogenic UCN Sources

A rotor converter is a fairly simple instrument to implement and is well suited to a SPSS and would be compatible with a LPSS as long as the neutron pulse lengths did not exceed several hundred microseconds. Even with longer neutron pulse lengths, a rotor would still operate, but with lower efficiency. Ultimately it seems that in order to

obtain substantial gains in densities one will need to go to some form of cryogenic UCN moderators. Investigations have been carried out to study production of UCN in superthermal (e.g. producing a UCN density *higher* than the *thermal* UCN density of the source) sources in which neutrons are down scattered by phonon emission in liquid <sup>4</sup>He.<sup>4)</sup> The upscattering rate should be very low as the phonon density in such a moderator is very low. Proof-of-principle tests of this idea have been carried out at reactors and it appears that high densities of UCN can be obtained in the liquid He moderator.<sup>5)</sup> However, it has proven difficult to implement this as a realistic source because there have been technical problems in trying to efficiently extract the UCN from the source. Efficient extraction from the liquid source requires a windowless extraction system that is compatible with the reactor requirements.

While the LHe superthermal source certainly merits further efforts, especially for experiments that can be performed in the LHe production volume, a potentially attractive scheme for producing UCN is a technique now under development by the research group of A. Serebrov at the Gatchina reactor.<sup>6)</sup> This employs a frozen D<sub>2</sub> moderator at 4–6 K placed close to the active zone of the reactor. The density of UCN in this source is significantly increased over that in a liquid D<sub>2</sub> cold source by the Boltzmann factor at the lower temperature. Very preliminary results from the Gatchina group have shown a gain in UCN densities achieved of a factor of 10 compared to a liquid deuterium source. Such a source implemented at a LPSS has the advantage that the heat loads on the moderator are much less than at a reactor, thus providing one more freedom to optimize the moderator design and minimize its distance from the spallation target, thus increasing the flux.

A 1-MW Linac-only spallation source based on the LANSCE accelerator has been proposed as a means to provide complementary capabilities to those available at the short-pulse MLNSC spallation source. The new spallation target would be constructed in Experimental Area A at LANSCE, an area that will no longer be used for nuclear physics research after 1996. The LANSCE linac is envisaged to operate at 60 Hz providing 1.25 mA (with some potential to go to 2.5 mA) current of 800-MeV protons with a duration of 1.0 ms per pulse. The accelerator would operate at 60 Hz to the LPSS with a 1-ms beam pulse width, thus yielding a 6% duty factor. The beam would impinge on a tungsten flux trap split target viewed by up to six moderators that could be either water or liquid hydrogen. These moderators would produce beams of thermal and cold neutrons for use in materials science and defense programs. We are planning for a UCN source that could be installed at the LPSS.

The time-averaged beam power of this source is as much as sixty times less than the thermal power of research reactors. However, the energy required to produce a neutron at a spallation source is roughly 30 MeV as compared to 180 MeV at a reactor. In addition, it is possible to make a brighter neutron source using a spallation target than at a reactor. These factors yield a gain of ten for thermal neutrons and a gain of fifteen for cold neutrons relative to a reactor. In addition, it is possible (for some


- classes of experiments) to make use of the time structure of the beam to advantage.

For UCN, estimates indicate that densities of  $10^3$ - $10^4$  UCN/cm<sup>3</sup> could be achieved. Such a source would provide the densities required to carry out a fundamental physics research program that could probe for physics beyond the standard model with substantially improved sensitivity. The existence of such an intense UCN source may also prove of interest to materials science. Assuming funding is provided in the near term, a cryogenic UCN source could be implemented at a LANSCE LPSS within the next five years.

The authors would like to thank R. Golub, S. Lamoreaux, Y. Masuda, F. Mezei, A. Michaudon, and M. Pendlebury, for useful discussions.

#### References

- 1) A. Steyerl and S. S. Malik, Nucl. Instrum. Methods. **A284** (1989) 200.
- 2) J. S. Fraser et al., Physics in Canada **21** (1965) 17.
- 3) T. O. Brun et al., Phys. Lett. **A75** (1980) 223.
- 4) A. I. Kilvington et al., Phys. Lett. **A125** (1987) 416.
- 5) H. Yoshiki et al., Phys. Rev. Lett. **68** (1992) 1323.
- 6) A. Serebrov et al., submitted to Nucl. Instrum. Methods.



#### DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.