

BNL-63603

Coherent Synchrotron Radiation in the Isochronous Muon Collider Ring*

Juan C. Gallardo

Center for Accelerator Physics, Brookhaven National Laboratory, Upton, NY 11973 USA

ABSTRACT

We show that the coherent (shielded) synchrotron radiation is negligible in a 4 TeV c-of-m muon collider.

I INTRODUCTION

To achieve the luminosity of $\mathcal{L} = 10^{35} \text{ cm}^{-2} \text{ s}^{-1}$ in a $\mu^+ \mu^-$ collider [1], two bunches per sign of $N = 2 \times 10^{12}$ particles each and a betatron function of $\beta^* = 3 \text{ mm}$ at the interaction point (IP) are required. This small β^* at the IP constrains the size of the bunch to be $\sigma_z \sim \beta^*$. To maintain this rather short bunch without excessive rf power consumption, an isochronous lattice has been chosen for the final collider ring. [2] One of the important advantages of muons as opposed to electrons is that at up to at least 2 TeV energy it is possible to accelerate muons in circular machines as their synchrotron radiation is reduced by a factor of $(\frac{m_e}{m_\mu})^2 \sim 23 \times 10^{-6}$ with respect to electrons. Nevertheless, the large number of muons in a short bunch suggests the possibility of strong shielded coherent synchrotron radiation. First, we use the well known formulae [3][4] to evaluate the power of shielded coherent synchrotron radiation in the isochronous muon collider ring. Finally, following the results obtained by Kheifets and Zotter [5] for a bunch with a Gaussian longitudinal charge distribution we show that the coherent synchrotron radiation in the isochronous $\mu^+ \mu^-$ collider ring is negligible if the rms bunch length is larger than $\approx 0.3 \text{ mm}$.

II INCOHERENT SYNCHROTRON RADIATION

The main parameters of the present design of a muon collider ring are shown in Tb. I. To calculate the incoherent radiation power we start by recalling the Larmor formula for a circular machine [5];

$$P_\gamma \left[\frac{\text{GeV}}{\text{s}} \right] = 8.8575 \times 10^{-5} \frac{c}{2\pi} \frac{E^4 [\text{GeV}]}{\rho [\text{m}]} \left(\frac{m_e}{m_\mu} \right)^4 \quad (1)$$

is the instantaneous radiation power per particle. For a beam of N_e particles the total synchrotron (incoherent) radiation power per turn is

$$P_\gamma [\text{MW}] = 8.8575 \times 10^{-2} \frac{E^4 [\text{GeV}]}{\rho [\text{m}]} \left(\frac{m_e}{m_\mu} \right)^4 I [\text{A}] \quad (2)$$

where the current $I [\text{A}] = e N_\mu \frac{c\beta}{2\pi\rho} \approx 13.75 \text{ mA}$.

For the 4 T in center-of-mass muon collider ring, $P_\gamma \approx 10 \text{ kW}$ which it corresponds to $\sim 8.5 \text{ W/m}$. This has to be compared with 1 KW/m produced by muon decay [6] (electrons

Table I: High energy-high luminosity $\mu^+ \mu^-$ collider

Maximum c-m Energy [TeV]	4
Luminosity $\mathcal{L} [10^{35} \text{ cm}^{-2} \text{ s}^{-1}]$	1.0
Circumference [km]	8.08
Time Between Collisions [μs]	12
Energy Spread $\sigma_E [\text{units } 10^{-3}]$	2
Pulse length $\sigma_z [\text{mm}]$	3
Free space at the IP [m]	± 6.25
Luminosity lifetime [No.turns]	900
Horizontal betatron tune, ν_x	55.79
Vertical betatron tune, ν_y	38.82
rms emittance, $\epsilon_{x,y} [10^{-6} \pi \text{ m-rad}]$	0.0026
rms normalized emittance, $\gamma \epsilon_{x,y} [10^{-6} \pi \text{ m-rad}]$	50.0
Beta-function values at IP, $\beta_{x,y}^* [\text{mm}]$	3
rms Beam size at IP [μm]	2.8
Quadrupole pole fields near IP [T]	6.0
Peak beta-function, $\beta_{x\text{max}} [\text{km}]$	284
Peak beta-function, $\beta_{y\text{max}} [\text{km}]$	373
Magnet Aperture closest to IP [cm]	12
Beam-Beam tune shift per crossing	0.05
Repetition Rate [Hz]	15
rf frequency [GHz]	1.3
rf voltage [MeV]	130
Particles per Bunch [units 10^{12}]	2
No. of Bunches of each sign	2
Peak current $\mathcal{I} = eNc/\sqrt{2\pi\sigma_z} [\text{kA}]$	12.8
Average current $\bar{\mathcal{I}} = eNc/\text{Circum} [\text{A}]$	0.032
Bending Field [T]	8.5

and electron synchrotron radiation); therefore the shielding of the super-conducting magnets is determined by the products of muon decay ($\mu^\pm \rightarrow e^\pm + \nu_e + \nu_\mu$). Although the energy is deposited mainly at 90 and 270 azimuthal angle, the simplest solution to bring the energy deposition on the super-conducting coils to safe levels is to include a 6 cm radius of Tungsten liner in the beam pipe [7]. Any increase in the synchrotron radiation would thus be rather expensive and/or unmanageable from a cooling power point of view or realistic pole-tip fields. Therefore, it is natural to study the possibility of coherent synchrotron radiation.

Before discussing coherent radiation we recall some useful expressions from Jackson [8]. First, the critical frequency is

*Work supported by the US Department of Energy under contract DE-ACO2-76-CH00016 and DE-AC03-76SF00515.

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

given by:

$$\omega_c = \frac{3}{2} \gamma^3 \frac{c}{\rho}, \quad \epsilon_c [keV] = 0.665 E^2 [GeV] B [T] \left(\frac{m_e}{m_\mu} \right)^2 \quad (3)$$

and harmonic number[9] $n_c = 3\gamma^3$.

Second, assuming a Gaussian angular distribution of the radiation (θ is the angle between the observation direction and the tangent to the trajectory of the particle at the moment of emission) then the rms divergence is:

$$\sigma_\theta \approx \begin{cases} \frac{1.07}{\gamma} \left(\frac{\omega_c}{\omega} \right)^{1/3} & \omega \ll \omega_c \\ \frac{0.64}{\gamma} & \omega = \omega_c \\ \frac{0.58}{\gamma} \left(\frac{\omega_c}{\omega} \right)^{1/2} & \omega \gg \omega_c \end{cases} \quad (4)$$

Notice that at low frequencies ($\omega \ll \omega_c$) the radiation is much wider than the average $\sigma_\theta \sim \frac{1}{\gamma}$ and that at high frequency ($\omega \gg \omega_c$), the angular range is much narrower than the average. This concludes this brief summary of very well known results of incoherent synchrotron radiation.

III COHERENT SYNCHROTRON RADIATION

A Free space

Coherent radiation at wavelength λ is obtained if the relative distance between particles is approximately of order λ . In this case the radiation fields emitted by these particles interfere constructively and the resulting field is the radiation of a representative particle (charge e) multiplied by the total charge of the ensemble ($\sum_{j=1}^{N_\mu} e = eN_\mu$). This leads to the characteristic N_μ^2 behavior of coherence.

If the longitudinal length of the bunch of muons is σ_μ , then the condition for coherence in free space is

$$\sigma_\mu \lesssim \frac{\lambda}{2\pi} \equiv \frac{c}{\omega} \quad (5)$$

To understand this fact we refer the reader to Jackson[10]. Assume a set of N_μ muons moving in a circle with fixed relative positions around the circle, they produce a power

$$P = P_n \left| \sum_{i=1}^{N_\mu} e^{-in\phi_i} \right|^2 = P_n N_\mu + N_\mu(N_\mu - 1) P_n f_n \quad (6)$$

where P_n is the incoherent power emitted by one particle in the frequency $\omega = n\omega_0$ and f_n is a form factor

$$f_n = \left(\int d\phi \cos(n\phi) S(\phi) \right)^2 \quad (7)$$

where $S(\phi)$ is the longitudinal distribution of the bunch and $\omega_0 = c/\rho$ is the revolution frequency. For a Gaussian distribution with rms bunch length σ_s

$$S(\phi) d\phi = \frac{1}{\sqrt{2\pi}} \left(\frac{\rho}{\sigma_s} \right) e^{-\frac{\phi^2 \rho^2}{2\sigma_s^2}} \quad (8)$$

and after an elementary integration

$$f_n = e^{-\frac{n^2 \sigma_s^2}{\rho^2}} \quad (9)$$

From this expression we can derive the coherent condition in Eq.3. The second term in Eq.5 gives the power of coherent radiation $N_\mu(N_\mu - 1) \simeq N_\mu^2$, i.e. proportional to the square of the number of particles or equivalently to the square of the bunch current I_n at the n -th harmonic. This dependence suggests to assign an effective impedance to the coherent radiation following Ohm's law $P_n = Z_n I_n^2$.

In our case, $\lambda \gtrsim 1.8$ cm, hence is comparable to the transverse size of the beam pipe. Under this condition the coherent radiation and its characteristics are substantially changed by the presence of metallic walls. The induced currents tend to decrease the radiation fields created by the bunch (destructive interference). This fact is denoted as *shielding*[11],[12]

B Metallic boundaries

In the presence of metallic boundaries the image charges and currents created by the beam itself (self induced fields) have the potential to destructively interfere with the radiation field emitted by the beam; this effect is clearly more effective the closer the beam to the wall, i.e. the smaller is the dimension of the beam pipe.

The condition for coherent synchrotron radiation can be made plausible following the arguments from Kheifets and Zotter[11].

Assume a beam moving between 2 parallel conductive plates; the tangential radiation field must vanish at the conductor, hence $k_\perp = |k| \sigma_\theta$ with $|k|^2 = |k_\perp|^2 + |k_\parallel|^2$. At the surface $k_\parallel = 0$ then $|k|^2 = |k_\perp|^2$. The cutoff wave vector due to the waveguide is $\frac{\pi}{h}$, therefore $k_\perp > \frac{\pi}{h}$ or

$$\sigma_\theta > \frac{\pi \rho}{nh} \quad (10)$$

At the end of the previous section, Eq.5 we recalled that $\sigma_\theta \approx 1.07 \left(\frac{3}{2n} \right)^{1/3}$, therefore

$$n > \frac{1}{1.07} \sqrt{\frac{2}{3}} \left(\frac{\pi \rho}{h} \right)^{3/2} \equiv n_{th} \quad (11)$$

hence the possible coherent radiation harmonic number is limited from below. Now from Eq.8 the condition for coherence limits the harmonic number from above, i.e.

$$n < n_{coh} = \frac{\rho}{\sigma_s} \quad (12)$$

Combining Eqs.11 and 12 we get approximately (up to small numeric factors)

$$n_{th} \equiv \sqrt{\frac{2}{3}} \left(\frac{\pi \rho}{h} \right)^{3/2} < n < \frac{\rho}{\sigma_s} \equiv n_{coh} \quad (13)$$

or in terms of wavelength

$$\sigma_s < \lambda < \frac{h}{\pi} \sqrt{\frac{6h}{\pi \rho}} \equiv \lambda_{th} \quad (14)$$

Notice that the upper limit λ_{th} is smaller than the waveguide cutoff $\lambda_{c.o.} \approx h(\frac{h}{\rho} \ll 1)$. Consequently, there will be coherent synchrotron radiation only if

$$\sigma_s < 2\pi\rho\sqrt{\frac{3}{2}}\left(\frac{h}{\pi\rho}\right)^{3/2} \quad (15)$$

Before applying Eq.15 to the collider ring to show that there is no coherent radiation possible, we write for completeness the expression for the total power of shielded coherent synchrotron radiation

$$P_{coh} \approx N_{\mu}^2 \frac{\omega_0}{2\rho} \frac{e^2}{4\pi\epsilon_0} \left(\frac{\rho}{\sigma_s}\right)^{4/3} F(x_{th}, x_{up}) \quad (16)$$

where the form factor $F(x_{th}, x_{up}) = \int_{x_{th}}^{x_{up}} dx e^{-x} x^{-1/3}$, with $x_{th} = \frac{2}{3} \left(\frac{\pi\rho}{h}\right)^3 \left(\frac{\sigma_s}{\rho}\right)^2$ and $x_{up} = \frac{9}{4} \gamma^6 \left(\frac{\sigma_s}{\gamma}\right)^2$. Expanding the function $F(x_{th}, x_{up})$, assuming that $\frac{x_{up}}{x_{th}} \gg 1$ we get

$$F(x_{th}, \infty) = \begin{cases} \Gamma(2/3) & x_{th} \ll 1 \\ x_{th}^{-1/3} e^{-x_{th}} & x_{th} \gg 1 \end{cases} \quad (17)$$

Next we evaluate n_{th} and n_{coh} obtaining, $n_{coh} = 3.7 \times 10^5$ and $n_{th} = 3.2 \times 10^7$ or $\lambda_{th} \sim 0.2$ mm which is a factor of 10 smaller than σ_s . We conclude that for the isochronous muon collider ring no radiation can be emitted coherently and we have an order of magnitude of safety margin.

IV CONCLUSION

With the present design parameters of a muon collider ring, there is no possible coherent synchrotron radiation

V REFERENCES

- [1] R. B. Palmer, et al., *Muon Colliders*, Proceedings of the 9th Advanced ICFA Beam Dynamics Workshop, Ed. J. C. Gallardo, AIP Conference Proceedings 372, 1996. R. B. Palmer et al., *Muon Collider Design*, submitted to the Proceedings of the Symposium on Physics Potential and Development of Muon-Muon Colliders, San Francisco, CA, Dec. 1995.
- [2] D. Trobojevic, et al., *Design of the Muon Collider Isochronous Storage Ring Lattice*, Proceedings of the Micro Bunches Workshop, Eds. E. B. Blum, M. Dienes J. B. Murphy, AIP Conference Proceedings 367, 1996; Juan C. Gallardo and Robert B. Palmer, *Final Focus System for a Muon Collider. A Test Model*, submitted to the Proceedings of the Symposium on Physics Potential and Development of Muon-Muon Colliders, San Francisco, CA, Dec. 1995.
- [3] L. I. Schiff, *Production of particle energies beyond 200 MeV*, Rev. Sci. Instr. V.17, 6 (1946).
- [4] J. S. Nodvick and D. S. Saxon, *Suppression of coherent radiation by electrons in a synchrotron*, Phy. Rev. 96, 180 (1954).
- [5] H. Wiedemann, *Particle Accelerator Physics*, Springer-Verlag, Berlin, Heidelberg 1993, pp. 300.
- [6] *Muon Collider: A Feasibility Study*, Report BNL-52503, Fermi Lab-Conf.-96/092, LBNL-38946.
- [7] I. Stumer, private communication.
- [8] J. D. Jackson, *Classical Electrodynamics*, John Wiley & Sons, New York, 1967.
- [9] Kwang-Je Kim, *Characteristic of Synchrotron Radiation*, AIP Conference Proceedings 184, pp. 582, Eds. M. Month and M. Dienes, AIP 1989. Notice that ω_c is one half the critical frequency defined by Jackson in Ref. 9.
- [10] See Ref.8, problem 14.11, pp. 502.
- [11] S. A. Kheifets and B. Zotter, *Coherent Synchrotron Radiation, Wake Field and Impedance*, CERN-SL Report 95-43 (AP), June 6, 1995; S. A. Kheifets, *Coherent Radiation in the CLIC Isochronous Ring*, CERN-CLIC Note 287, July 7, 1995; S. Heifets and A. Michailichenko, *On the Impedance due to Synchrotron Radiation*, SLAC/AP-83, December 1990.
- [12] R. L. Warnock, *Shielded Coherent Synchrotron Radiation and its possible effect in the next linear collider*, SLAC-PUB-5375, 1990; SLAC-PUB-5417, 1991; SLAC-PUB-5523, 1991.
- [13] S. A. Kheifets and B. Zotter, *Shielding Effects on Coherent Synchrotron Radiation*, Eds. E. B. Blum, M. Dienes J. B. Murphy, AIP Conference Proceedings 367, 1996.