

RECEIVED BY 10 MAY 11 1982

DOE/JPL - 956045 - 82/4

DISTRIBUTION CATEGORY UC-63

DOE/JPL/956045--82/4

DE82 014193

SILICON PRODUCTION-PROCESS EVALUATIONS

QUARTERLY TECHNICAL PROGRESS REPORT (IV)

Issue Date: May 1, 1982

Reporting Period: Feb. 1, 1982 - April 30, 1982

TREI
Texas Research and Engineering Institute, Inc.
P. O. BOX 9
PORT NECHES, TEXAS 77651

MASTER

JPL Contract No. 956045

Contractual Acknowledgement

The JPL Flat-Plate Solar Array (FSA) Project is sponsored by the U.S. Department of Energy and forms part of the Solar Photovoltaic Conversion Program to initiate a major effort toward the development of low-cost solar arrays. This work was performed for the Jet Propulsion Laboratory, California Institute of Technology by agreement between NASA and DOE.

DISCLAIMER

This book was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

HBW

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

DISCLAIMER

"This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights."

ABSTRACT

For the HSC process (Hemlock Semiconductor Corporation), chemical engineering analysis of the process for producing silicon from dichlorosilane in a 1,000 MT/yr plant is nearing completion. Progress and status for the major process engineering activities involved in the analysis are reported: base case conditions (100%), reaction chemistry (100%), process flow diagram (100%), material balance (100%) energy balance (100%), property data (100%), equipment design (90%), major equipment list (90%) and labor (90%).

Engineering design of the third distillation column (D-03, DCS column) in the process was accomplished. The initial design is based on a 94.35% recovery of the light key (DCS, dichlorosilane) in the distillate and a 99.9% recovery of the heavy key (TCS, trichlorosilane) in the bottoms. The specified separation of DCS and TCS is achieved at a reflux ratio of 15 with 20 trays (equilibrium stages). Additional specifications and results are reported including equipment size, temperatures and pressure.

Specific raw material requirements necessary to produce the silicon in the process are presented. The primary raw materials include metallurgical grade silicon, silicon tetrachloride, hydrogen, copper (catalyst) and lime (waste treatment). Hydrogen chloride is produced as a by-product in the silicon deposition.

Cost analysis of the HSC process (Hemlock Semiconductor Corporation) was initiated during this reporting period. The initial cost engineering activities are about 30% complete. The costs for raw materials and utilities necessary to produce silicon in HSC process are reported. Raw material costs are \$2.66 (1980 dollars) and \$3.07 (1982 dollars) per kg of silicon. Utility costs are \$4.75 (1980 dollars) and \$5.69 (1982 dollars) per kg of silicon.

TABLE OF CONTENTS

	<u>PAGE</u>
I. CHEMICAL ENGINEERING ANALYSIS.....	1
II. COST ANALYSIS.....	7
III. SUMMARY - CONCLUSIONS.....	11
IV. PLANS.....	12

APPENDIX

A1 PROCESS ENGINEERING: DESIGN SPECIFICATIONS FOR DISTILLATION, D-03.....	13
A2 PROCESS ENGINEERING: DESIGN RESULTS FOR DISTILLATION, D-03.....	15

MILESTONE CHART

I. CHEMICAL ENGINEERING ANALYSIS

During this reporting period, primary efforts were continued on the chemical engineering analysis of the HSC process (Hemlock Semiconductor Corporation).

Progress and status for the chemical engineering analysis are summarized below for the major engineering activities:

	<u>Prior</u>	<u>Current</u>
1. Base Case Conditions	96%	100%
2. Reaction Chemistry	96%	100%
3. Process Flow Diagram	85%	100%
4. Material Balance	85%	100%
5. Energy Balance	60%	100%
6. Property Data	60%	100%
7. Equipment Design	40%	90%
8. Major Equipment List	30%	90%
9. Labor	10%	90%

Initial engineering design of the third distillation column (D-03, DCS column) in the process was accomplished. The function of the distillation column is to separate DCS (dichlorosilane) and TCS (trichlorosilane). The distillation column has a single feed which is the distillate from D-02 column.

For the initial process engineering design of D-03 distillation column, the specifications for the separation include a 94.35% recovery of the light key (DCS, dichlorosilane) in the distillate and a 99.9% recovery of the heavy key (TCS, trichlorosilane) in the bottoms. A partial condenser is used for safety reasons in the distillation which is conducted at 90 psia. Additional specifications used in performing the design are given in Appendix A1.

The results for the process engineering design of D-03 indicate the specified separation of DCS and TCS is achieved at a reflux ratio of 15 with 20 trays (equilibrium stages). Additional detailed results including feed tray location and equipment size are given in Appendix A2.

The design curve for D-03 distillation column is shown in Figure I-1. The design curve discloses the results for number of trays (equilibrium stages) required for the separation versus reflux ratio for the distillation.

Status details for the chemical engineering analysis are given in Table I-1. The preliminary process engineering design is based on a 1,000 MT/yr plant for producing silicon from dichlorosilane.

Raw material requirements necessary to produce the product are presented in Table I-2. In the process, the primary raw materials required to produce the silicon include metallurgical grade silicon, silicon tetrachloride, hydrogen, copper (catalyst) and lime (waste treatment). Hydrogen chloride is produced as a by-product in the silicon deposition. The detailed raw material requirements are summarized in the tabulation including hourly flow rate and mass required per kg of silicon produced.

The utility requirements for the process are given in Table I-3. The major utilities include electricity, steam, cooling water, refrigeration, process water and fuel. Among these utilities, the primary utility involving the greatest energy usage is the electricity for the deposition reaction in which silicon is produced by deposition on an electrically heated polycrystalline rod. The surface of the polycrystalline silicon rod is usually in the temperature range of 1000-1100C for the silicon deposition.

Preparation of the list of major process equipment and production labor required to operate the equipment is in progress and nearing completion. The major process equipment and labor requirements are about 90% complete.




Figure 1-1 Design Curve for Distillation, D-03

Table I-1

CHEMICAL ENGINEERING ANALYSIS:
PRELIMINARY PROCESS DESIGN ACTIVITIES FOR HSC PROCESS

<u>Prel. Process Design Activity</u>	<u>Status</u>	<u>Prel. Process Design Activity</u>	<u>Status</u>
1. Specify Base Case Conditions	●	6. Property Data	●
1. Plant Size	●	1. Physical	●
2. Product Specifics	●	2. Thermodynamic	●
3. Additional Conditions	●	3. Additional	●
2. Define Reaction Chemistry	●	7. Equipment Design Calculations	●
1. Reactants, Products	●	1. Storage Vessels	●
2. Equilibrium	●	2. Unit Operations Equipment	●
3. Process Flow Diagram	●	3. Process Data (P, T, rate, etc.)	●
1. Flow Sequence, Unit Operations	●	4. Additional	●
2. Process Conditions (T, P, etc.)	●	8. List of Major Process Equipment	●
3. Environmental	●	1. Size	●
4. Company Interaction (Technology Exchange)	●	2. Type	●
	●	3. Materials of Construction	●
4. Material Balance Calculations	●	9. Production Labor Requirements	●
1. Raw Materials	●	1. Process Technology	●
2. Products	●	2. Production Volume	●
3. By-Products	●	10. Forward for Economic Analysis	0
5. Energy Balance Calculations	●		
1. Heating	●		
2. Cooling	●		
3. Additional	●		
		0 Plan	
		● In Progress	
		● Complete	

TABLE I-2

RAW MATERIAL REQUIREMENTS FOR HSC PROCESS

<u>RAW MATERIALS</u>	<u>REQUIREMENTS</u>	
	<u>lb/hr for 1000 MT/yr Silicon</u>	<u>lb/kg of Silicon</u>
1. M. G. Silicon	270.11	2.014
2. Silicon Tetrachloride (SiCl_4 , make-up)	535.73	3.67
3. Liquid Hydrogen (H_2 , make-up)	45.82	0.342
4. Copper Catalyst	3.44	0.026
5. Hydrate Lime (Ca(OH)_2)	259.9	1.937
6. Hydrogen Chloride (HCl , by-product)	129.96	0.969

TABLE I-3
UTILITY REQUIREMENTS FOR HSC PROCESS

<u>UTILITIES</u>	<u>TOTAL REQUIREMENTS FOR PLANT</u>	<u>REQUIREMENTS PER KG OF SILICON</u>
1. Electricity		
1) For Deposition Reaction	12,000 kw	90.0 kw-hr
2) For Gas Compression	260 kw	1.94 kw-hr
3) For Pumping Liquid	55 kw	0.41 kw
	<hr/>	<hr/>
	12,315 kw	92.35 kw
2. Steam		
1) Superheated, 100 psia	5 k lb/hr	37.3 lb
2) Saturated, 100 psia	17 k lb/hr	126.7 lb
	<hr/>	<hr/>
	22 k lb/hr	164.0 lb
3. Cooling water		
1) Cooling and Condensing	96 k gal/hr	715.6 gal
4. Refrigerant	0.90 M BTU/hr	.007 M Btu
1) Refrigeration		
5. Process Water		
1) Waste Treatment	215 gal	3.39 gal
6. Fuel		
1) Direct-Fired Heater	4 M BTU/hr	.03 M BTU
2) Incineration	1.5 M BTU/hr	.011 M BTU
	<hr/>	<hr/>
	5.5 M BTU/hr	.041 M BTU

NOTE:

$$k = \text{kilo} = 10^3$$

$$M = \text{mega} = 10^6$$

II. COST ANALYSIS

The cost analysis activity involves an economic analysis of the process under consideration for the production of silicon. The cost analysis for the particular technology is based on process design results, such as requirements for raw materials and major process equipment necessary to produce the product, from the chemical engineering analysis activity. Primary results issuing from the cost analysis include plant capital investment and product cost which are useful in identification of those processes showing promise for meeting project cost goals.

During this reporting period, cost analysis of the HSC process (Hemlock Semiconductor Corporation) was initiated for a 1,000 MT/yr silicon plant. Progress and status for the major cost engineering activities involved in the analysis are summarized below:

	<u>Prior</u>	<u>Current</u>
1. Process Design Inputs	10%	50%
2. Base Case Conditions	10%	50%
3. Raw Material Costs	0%	50%
4. Utility Costs	0%	50%
5. Major Process Equipment Costs	0%	20%
6. Production Labor Costs	0%	10%
7. Plant Investment Cost	0%	Plan
8. Total Product Cost	0%	Plan

Status details for the cost analysis are shown in Table II-1.

The cost of raw materials necessary to produce the product are presented in Table II-2. The tabulation indicates that raw material costs are \$2.66 (1980 dollars) and \$3.07 (1982 dollars) per kg of silicon.

The cost of utilities required for the production of the product are given in Table II-3. The utility costs are \$4.75 (1980 dollars) and \$5.69 (1982 dollars) per kg of silicon.

Cost estimation for the major process equipment necessary to produce the silicon product is in progress. Determination of the major process equipment costs is about 30% complete.

TABLE II-1
COST ANALYSIS:
PRELIMINARY ECONOMIC ANALYSIS ACTIVITIES FOR HSC PROCESS

<u>Prel. Process Economic Activity</u>	<u>Status</u>	<u>Prel. Process Economic Activity</u>	<u>Status</u>
1. Process Design Inputs	0	6. Production Labor Costs	0
1. Raw Material Requirements	0	1. Base Cost Per Man Hour	0
2. Utility Requirements	0	2. Cost/Kg Silicon Per Area	0
3. Equipment List	0	3. Total Cost/Kg Silicon	0
4. Labor Requirements	0		
2. Specify Base Case Conditions	0	7. Estimation of Plant Investment	0
1. Base Year for Costs	0	1. Battery Limits Direct Costs	0
2. Appropriate Indices for Costs	0	2. Other Direct Costs	0
3. Additional	0	3. Indirect Costs	0
3. Raw Material Costs	0	4. Contingency	0
1. Base Cost/Lb of Material	0	5. Total Plant Investment	0
2. Material Cost/Kg of Silicon	0	(Fixed Capital)	
3. Total Cost/Kg of Silicon	0		
4. Utility Costs	0	8. Estimation of Total Product Cost	0
1. Base Cost for Each Utility	0	1. Direct Manufacturing Cost	0
2. Utility Cost/Kg of Silicon	0	2. Indirect Manufacturing Cost	0
3. Total Cost/Kg of Silicon	0	3. Plant Overhead	0
5. Major Process Equipment Costs	0	4. By-Product Credit	0
1. Individual Equipment Cost	0	5. General Expenses	0
2. Cost Index Adjustment	0	6. Total Cost of Product	0
		0 Plan	
		0 In Progress	
		0 Complete	

TABLE II-2
RAW MATERIAL COST FOR HSC PROCESS

<u>Raw Material</u>	<u>Raw Material Requirement, 1b/kg of Si</u>	<u>Raw Material Cost, \$/1b of Material</u>		<u>Cost, \$/kg of Si</u>	
		<u>1980 dollars</u>	<u>1982 dollars</u>	<u>1980 dollars</u>	<u>1982 dollars</u>
1. M. G. Silicon	2.014	0.63	0.62	1.27	1.25
2. Silicon Tetrachloride (SiCl ₄ , make-up)	3.67	0.26	0.36	0.95	1.32
3. Liquid Hydrogen (H ₂ , make-up)	0.342	1.485	1.679	0.51	0.57
4. Copper Catalyst	0.026	0.75	0.75	0.02	0.02
5. Hydrate Lime (CA(OH) ₂)	1.937	0.017 (33.5 \$/ton)	0.017	0.03	0.03
6. Hydrogen Chloride (HCl, by-product)	0.969	0.12	0.12	(0.12)	(0.12)
				2.66	3.07

TABLE II-3
UTILITY COST FOR HSC PROCESS

<u>Utility</u>	<u>Utility Requirement Unit/kg of Si</u>	<u>Utility Cost, \$/unit</u>		<u>Cost, \$/kg of Si</u>	
		<u>1980 dollars</u>	<u>1982 dollars</u>	<u>1980 dollars</u>	<u>1982 dollars</u>
1. Electricity	92.35 kw-hr	.045 \$/kw-hr	.054 \$/kw-hr	4.16	4.99
2. Steam	164 lb	1.89 \$/k lb	2.268 \$/k lb	0.310	0.372
3. Cooling Water	715.6 gal	.126 \$/k gal	0.151 \$/k gal	0.090	0.108
4. Refrigeration	.007 M BTU	14.7 \$/M BTU	17.64 \$/M BTU	0.103	0.124
5. Process Water	3.39 gal	.567 \$/k gal	0.680 \$/k gal	0.002	0.002
6. Fuel	.041 M BTU	1.96 \$/M BTU	2.352 \$/M BTU	0.080	0.096
				4.745	5.694

Note:

k = kilo = 10^3
M = mega = 10^6

III. SUMMARY - CONCLUSIONS

As a result of accomplishments during this reporting period, the following summary-conclusions are made:

1. For the HSC process (Hemlock Semiconductor Corporation), chemical engineering analysis of the process for producing silicon from dichlorosilane in a 1,000 MT/yr plant is nearing completion. Progress and status for the major process engineering activities involved in the analysis are reported: base case conditions (100%), reaction chemistry (100%), process flow diagram (100%), material balance (100%), energy balance (100%), property data (100%), equipment design (90%), major equipment list (90%) and labor (90%).
2. Initial engineering design of the third distillation column (D-03, DCS column) in the process was accomplished. The initial design is based on a 94.35% recovery of the light key (DCS, dichlorosilane) in the distillate and a 99.9% recovery of the heavy key (TCS, trichlorosilane) in the bottoms. The specified separation of DCS and TCS is achieved at a reflux ratio of 15 with 20 trays (equilibrium stages). Additional specifications and results are reported including equipment size, temperatures and pressure.
3. Cost analysis of the HSC process (Hemlock Semiconductor Corporation) was initiated during this reporting period. The initial cost engineering activities are about 30% complete. The costs for raw materials and utilities necessary to produce silicon in HSC process are reported. Raw material costs are \$2.66 (1980 dollars) and \$3.07 (1982 dollars) per kg of silicon. Utility costs are \$4.75 (1980 dollars) and \$5.69 (1982 dollars) per kg of silicon.

IV. PLANS

Plans for the next reporting period are summarized below:

1. Continue chemical engineering analysis of the HSC process (Hemlock Semiconductor Corporation) for silicon.
2. For the preliminary process design, major efforts will be devoted to equipment design, major equipment list and labor requirements.
3. Cost analysis will continue as results issue from the chemical engineering analysis.

APPENDIX A1

PROCESS ENGINEERING: DESIGN SPECIFICATIONS FOR DISTILLATION, D-03

Issue No. 1

1. Process Equipment Name Distillation, D-03 (DCS Column)
2. Process Equipment Function Separation of DCS (Dichlorosilane) and TCS (Trichlorosilane).
3. Feed Specifications
 1. No. of Feeds 1
 2. No. of Feed Components 4
 3. Feed Components MCS, DCS, TCS, TET
 4. Feed Concentration See Item 7
 5. Feed Temperature 91 C
 6. Feed Pressure 90 Psia
 7. Light Key - LK Dichlorosilane (DCS)
 8. Heavy Key - HK Trichlorosilane (TCS)
4. Distillate Specifications
 1. Recovery of Light Key (LK) in Distillate 94.35 %
 2. Concentration Spec. Low TCS, TET
5. Bottoms Specifications
 1. Recovery of Heavy Key (HK) in Bottoms 99.9 %
 2. Concentration Spec. Low in MCS, DCS
6. General Specifications
 1. Pressure for Distillation 90 psia
 2. Condenser Type Partial

Required amount for feed of CVD reactors is drawn from the top of this column in vapor phase, it is then mixtured with H₂ and feeded to CVD reactor. Only refulx flow is condensed and collected in accumulator, and feeded back to column.

7. Feed Concentration

<u>Component</u>	<u>Feed Concentration</u>
1. SiH ₃ Cl , MCS	0.0044870
2. SiH ₂ Cl ₂ , DCS	0.1034000
3. SiHCl ₃ , TCS	0.8856370
4. SiCl ₄ , TET	0.0064760
<hr/>	
Total	1.000000
Temperature (C)	91
Pressure (Psia)	90
Mass Flow (1b-mole/hr)	256.53
Liquid Fraction	1.
Feed Source	Distillate of D-02

Note :

1. Feed concentration and temperature are from design of D-02

APPENDIX A2

PROCESS ENGINEERING: DESIGN RESULTS FOR DISTILLATION, D-03

Issue No. 1

1. Process Equipment Name Distillation, D-03 (DCS Column)

2. Equipment Specifications

1. No. of Equilibrium Trays $N =$ 20

2. No. of Equilibrium Feed Tray $N_F =$ 11

3. Tray Efficiency 65 %

4. No. of Actual Trays $N_{actual} =$ 32

5. No. of Actual Feed Tray $N_{F,actual} =$ 16

6. Tray Spacing 18 in.

7. Type of Tray Single Pass Crossflow Seive Tray

8. Column Diameter 4 ft.

9. Column Height 60 ft.

10. Reflux Ratio $R =$ 15

11. Design Temp. Top = 52 C

Bottom = 97 C

12. Design Pressure 90 psia

13. Materials of Construction Steel

3. Product Specifications

1. Feed Specifications

1. Feed Concentration See Item 7 of Design Spec.

2. Light Key - LK Dichlorosilane (DCS)

3. Heavy Key - HK Trichlorosilane (TCS)

2. Distillate Specifications

1. Recovery of Light Key (LK) in Distillate 94.35 %

2. Concentration Spec. See Item 4

3. Bottoms Specifications

1. Recovery of Heavy Key (HK) in Bottoms 99.9 %

2. Concentration Spec. See Item 4

4. Results for Streams Concentration

<u>Component</u>	<u>Concentration</u>	
	<u>Distillate</u>	<u>Bottom</u>
1. SiH_3Cl , MCS	0.0435621	Neglibile
2. SiH_2Cl_2 , DCS	0.9390411	0.0076186
3. SiHCl_3 , TCS	0.0173968	0.9837867
4. SiCl_4 , TET	neglibile	0.0085947
 Total	 1.000000	 1.0000000

Distillate : 26.3 lb-mole/hr at 52 °C

Bottom : 230.23 lb-mole/hr at 97 °C

5. Results for Number of Trays

<u>Reflux Ratio, R</u>	<u>No. of Equil. Trays, N</u>	<u>No. of Actual Trays N_{actual}</u>
12	29 (13)	45
14	23 (12)	36
15	20 (11)	31
20	18 (11)	28
25	17 (10)	27
30	16 (10)	25

MILESTONE CHART

1981									1982					
M	J	J	A	S	O	N	D	J	F-A	M	J	J		
1. Chem. Eng. Analysis														
1. Base Case Cond.														
2. Reaction Chem.														
3. Process Flowsheet														
4. Material Balance														
5. Energy Balance														
6. Property Data														
7. Equip. Design														
8. Major Equip.														
9. Labor Req.														
10. Forward Econ.														
2. Economic Analysis														
1. Process Design														
2. Base Case Cond.														
3. Raw Mat. Costs														
4. Utility Costs														
5. Major Equip. Costs														
6. Labor Costs														
7. Plant Invest.														
8. Product Cost														
FINAL REPORT														