


TITLE: AN OVERVIEW OF THE NATIONAL URANIUM RESOURCE EVALUATION
HYDROGEOCHEMICAL AND STREAM SEDIMENT RECONNAISSANCE PROGRAM

AUTHOR(S): Stephen L. Bolivar

MASTER

SUBMITTED TO: Geochemical Exploration Symposium,
Hanover, Germany, April 10-13, 1980.



University of California

By acceptance of this article, the publisher recognizes that the U.S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes.

The Los Alamos Scientific Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED



LOS ALAMOS SCIENTIFIC LABORATORY

Post Office Box 1663 Los Alamos, New Mexico 87545

An Affirmative Action/Equal Opportunity Employer

**AN OVERVIEW OF THE
NATIONAL URANIUM RESOURCE EVALUATION
HYDROGEOCHEMICAL AND STREAM SEDIMENT RECONNAISSANCE PROGRAM**

**Bolivar, Stephen L., Resource Characterization Group, MS 586,
Los Alamos Scientific Laboratory, Los Alamos, New Mexico 87545**

ABSTRACT

A Hydrogeochemical and Stream Sediment Reconnaissance (HSSR) for uranium is currently being conducted throughout the conterminous United States and Alaska. The HSSR is part of the National Uranium Resource Evaluation sponsored by the US Department of Energy.

This ambitious geochemical reconnaissance program is conducted by four Department of Energy laboratories: Los Alamos Scientific Laboratory, Lawrence Livermore Laboratory, Oak Ridge Gaseous Diffusion Plant, and Savannah River Laboratory. The program is based on an extensive review of world literature, reconnaissance work done in other countries, and pilot studies conducted by each laboratory. Sample-collection methods and sample density are determined to optimize the probability of detecting potential uranium mineralization. To achieve this aim, each laboratory has developed independent standardized field collection procedures that are designed for its section of the country. Field parameters such as pH, conductivity, climate, geography, and geology are recorded at each site. Most areas are sampled at densities of one sample site per 10 to 23 km².

The HSSR program has helped to improve existing hydrogeochemical reconnaissance exploration techniques. In addition to providing industry with data that may help to identify potential uranium districts and to extend known uranium provinces, the HSSR also provides multi-element analytical data that can be used in water quality, soil, sediment, environmental, and base-metal exploration studies.


INTRODUCTION

In 1972, the Atomic Energy Commission initiated a National Uranium Resource Evaluation (NURE). The major objective of this program is the assessment of the nuclear fuel resources in the conterminous US and Alaska (US Department of Energy, 1979). The NURE program is now administered by the Department of Energy (DOE) and consists of hydrogeochemical and stream-sediment reconnaissance, aerial gamma-ray radiometric surveys, topical geologic studies, "world-class" studies, subsurface geologic investigations, technology applications, and resource estimation methodology.

This report is concerned with the Hydrogeochemical and Stream Sediment Reconnaissance (HSSR). Four DOE laboratories, Lawrence Livermore Laboratory (LLL), Los Alamos Scientific Laboratory (LASL), Oak Ridge Gaseous Diffusion Plant (ORGP), and Savannah River Laboratory (SRL), have conducted the hydrogeochemical program. Areas of responsibility are shown for each laboratory in Fig. 1. Each laboratory developed its own geochemical reconnaissance program for uranium based on time and funding constraints and emphasized the determination of uranium concentrations in both natural waters and waterborne sediments. This report summarizes the programs developed by the LASL, ORGP, and SRL. The LLL program is not discussed because of the very small areal coverage by this laboratory.

RECONNAISSANCE GEOCHEMICAL EXPLORATION

In the HSSR program, reconnaissance geochemical exploration can be readily defined as any method which employs a systematic search for favorable uranium terranes by detecting one or more elements in sampling media. The analytical precision (reproducibility) required generally needs only to be quantitatively accurate enough to distinguish above and below background



-  PILOT STUDY AREAS
- LLL LAWRENCE LIVERMORE LABORATORY
- SRL SAVANNAH RIVER LABORATORY
- ORGDP OAK RIDGE GASEOUS DIFFUSION PLANT
- LASL LOS ALAMOS SCIENTIFIC LABORATORY

TABLE I

TYPICAL SAMPLE MEDIA USED IN RECONNAISSANCE GEOCHEMICAL SAMPLING

<u>Media</u>	<u>Use</u>
Rocks	Helps to determine potential host rocks; used mainly in detailed surveys.
Soils	Extremely useful in areas of low relief, thick overburden, and arid climate; used predominant; in detailed surveys.
Organic Matter	Some biogeochemical processes concentrate certain elements in plant tissues; extremely useful in semi-desert areas and in detailed surveys.
Gases	Due to radioactive decay, some daughter products may be detected depending on atmosphere and soil conditions.
Ground Waters	Extremely useful in arid areas and give information on subsurface environment; commonly used in reconnaissance.
Stream Waters	Waters circulate over large areas and are extremely useful in searching for soluble elements; most used in reconnaissance.
Stream Sediments	Useful in areas of high relief and give rough index of geology of catchment basin; commonly sampled in reconnaissance programs.

THE SEARCH FOR URANIUM

During the complex decay of uranium to its various daughter products, several radioactive elements are formed that can be detected easily by direct radiometric methods. However, simple, rapid methods using a gamma-radiation detector such as a Geiger-Muller or scintillation counter are ineffective where a relatively thin inactive overburden covers an ore body (Bowie et al, 1971). Because uranium is soluble and because of the recent use of highly sensitive analytical technology such as neutron activation analysis, which permits fast and relatively cheap automation-type programs, the use of geochemical methods for exploration has yielded favorable results.

Uranium in most rocks occurs as an oxide in the +4 valence. In weathering zones of surficial environments, uranium is oxidized to the +6 valence, which is easily leached from surface rocks and carried as the uranyl ion into solution in most natural waters. Hexavalent uranium generally stays in solution until it is absorbed or encounters a reducing environment where it is precipitated as an oxide or hydroxide. Organic matter in streams and lakes provides favorable surfaces for the precipitation of uranium. However, uranium also will precipitate with ferric and manganese hydroxides, particularly where pH and carbonate ion concentrations are low (Lyck et al, 1971).

Uranium is extremely well suited for hydrogeochemical surveys because of its high solubility compared to most other metals (Bowie et al, 1971). General reviews describing the use of hydrogeochemical prospecting are found in Hawken and Webb (1962), Bradshaw et al (1973), and Lovison (1974) among others. However, the mobility of uranium depends on several factors, including the time of year, weathering and erosion, pH, Eh, absorption, the permeability of the geologic material in which water is in contact, and the content of clay minerals in sediment. In the USSR program, time and funding constraints

requires that any field measurements taken are a maximum aid in evaluation of the data, yet require minimum time in the field to conduct. The field measurements taken by each laboratory are listed in Table II.

Sample Media used in the HSSR Program

In the HSSR program, stream water, ground water, and stream sediments are the major media used. However, plant tissues were used by ORDDP and SRL in pilot studies, and helium samples are collected by SRL in pilot and reconnaissance studies and by ORDDP in detailed surveys. Because much of Alaska is extensively covered by lakes, LAZL collects lake waters and lake sediments. The type sample collected in any area depends on the results of extensive literature research of studies in similar terrane having comparable geology and geography (Table II).

Stream waters may be most useful in the broad-scale detection of anomalous areas in both reconnaissance and detailed exploration programs (Snukoff, 1956; Grimbert and Loriod, 1968; Boborg and Runnells, 1971). This media is an invaluable tool in heavily forested and mountainous terrane. Furthermore, according to Flx (1956), uranium in most natural waters can be considered to be a rough index of the uranium content of nearby geologic formations. However, natural waters must come into contact with mineral deposits and remain in contact with them long enough for some of the ore and/or indicator elements to be dissolved and for dispersion patterns to form. In addition, hydrologic systems are generally very complex, and a knowledge of how they work is essential in the detailed interpretation of geochemical data.

Ground waters, because of their long residence time in hydrologic systems and intimate contact with subsurface rocks have the potential to contain more dissolved minerals than surface streams, and can provide invaluable subsurface

TABLE II

FIELD MEASUREMENTS, NOMINAL SAMPLING DENSITIES,
AND CHEMICAL ANALYSES FOR THE HSSR PROGRAM

	<u>LASL</u>		<u>ORGP</u>	<u>SRL</u>
	<u>Rocky Mountains</u>	<u>Alaska</u>		
<u>Field Measurements</u>				
	pH temperature conductivity ground radio- activity	pH temperature conductivity ground radio- activity dissolved oxygen	pH temperature conductivity ground radio- activity total alkalinity phenolphthalein mixed-indicator dissolved oxygen	pH temperature conductivity ground radio- activity total alkalinity
<u>Media and Nominal Sampling Densities</u>				
Stream waters	10 km ²	11.5 km ²	26 km ²	13 km ²
Stream sediments	10 km ²	11.5 km ²	13-26 km ²	13 km ²
Ground waters	10 km ² (springs and wells)	--	26 km ² (springs and wells)	13 km ² (springs and wells)
Lake waters	--	23 km ²	--	--
Lake sediments	--	23 km ²	--	--
Organic matter (plant tissue)	--	--	pilot only	in a few areas
Helium	--	--	with ground water only	with ground water only
<u>Chemical Analyses</u>				
Sediment	Ag, Al, Au, Ba, Be, Ca, Cd, Co, Cl, Co, Cr, Cs, Cu, Dy, Eu, Fe, Hf, K, Li, La, Lu, Mg, Mn, Na, Ni, Nb, Pb, Rb, Sb, Se, Sm, Sn, Sr, Ta, Th, Th, Ti, U, V, W, Yb, Zn		Ag, Al, As, B, Ba, Be, Ca, Co, Co, Cr, Cu, Fe, Hf, K, Li, Lu, Mg, Mn, Mo, Na, Nb, Ni, P, Se, Se, Sr, Th, Ti, U, V, Y, Zn, Zr	Ag, Al, Ba, Be, Ce, Co, Cr, Cu, Dy, Eu, Hf, K, La, Li, Lu, Mg, Mn, Mo, Nb, Ni, P, Pb, Se, Sm, Sn, Sr, Th, Ti, U, V, W, Y, Yb, Zn
Water	Ca, Co, Cr, Cu, Fe, Mg, Mn, Mo, Ni, Pb, Ti, U, Zn		Ag, Al, As, B, Be, Be, Ca, Co, Cl, Co, Cr, Cu, Fe, K, Li, Mg, Mn, Mo, Na, Ni, P, Se, Se, Sr, Ti, U, V, Y, Zn, Zr, Zr	Al, Be, Cl, Dy, F, Mg, Mn, Na, U, V

data. Samples of well water and spring water may be particularly valuable for exploration in arid regions where ground waters may be the only aqueous medium available to sample (Boyle et al. 1971). This medium is also useful in humid areas, where surface streams contain low uranium concentrations because of dilution and continual exposure of outcrops to rain and consequent leaching and removal of soluble uranium (Little and Durham, 1971). For optimum use, ground water samples should be taken from aquifers at known depths (Denson et al, 1956).

Stream sediments (wet or dry) also are valuable indicators in outlining geochemical provinces. In the last 12 years, stream sediment surveys have been the chief method for geochemical reconnaissance exploration (Rose, 1977). Information from sediment samples can be related directly to the catchment basin of each stream. This type of medium is not affected directly by climatic changes as readily as surface waters are. Consequently, uranium values in sediment samples are generally more consistent and yield more easily recognizable anomalies than do uranium values in surface waters that fluctuate between wet and dry periods. In areas of high relief or in desert areas, stream sediment samples may be the only available sample medium. In Sweden, stream sediments have been used extensively (Brundin and Nairic, 1972) and as a geochemical prospecting medium are clearly desired over water samples by some authors (Morris, 1971). Investigators differ as to what type of sediment sample to collect; Morris (1971) favors samples composed of clastics, and Dyck et al (1971) favor organic-rich samples.

In some regions of Alaska, the terrain is extremely flat and large areas are underlain by permafrost. The low relief results in complex and disrupted drainage systems with poor circulation and with sediments that are irregularly deposited. Therefore, lake waters and lake sediments may give the best results

in these areas. However, since water samples from Alaskan lakes generally have very low uranium concentrations, precise measurements of uranium at the 0.5 parts per billion (ppb) level are needed. Dyck et al (1971) have shown that lake sampling in parts of the Canadian Shield is effective in delineating areas favorable for future exploration and is faster than stream sampling; however, they emphasized that lakes should be sampled near inlets and outlets to obtain best results. Other surveys utilizing lake samples include MacDonald (1969), Meyer (1969), Boyle et al (1971), and Dyck (1974).

Various combinations of media may provide the optimum exploration method. For example, in a rain-forest terrane, a stream water (and possibly stream sediment) sample coupled with a vegetation sample might be best. Each particular physiographic province should be studied separately, and all sampling media should be thoroughly tested in the orientation studies (Bradshaw et al, 1973; Levinson, 1974), particularly if vegetal or biogeochemical type media are used. Biogeochemical studies have been used with some success especially in arid areas (Boyle et al, 1971). For example, in the Colorado Plateau, a deep-rooted vetch, *Astragalus pattersoni*, requires considerable selenium to grow. Because selenium is associated with uranium deposits in this area, this species can be used as an ore guide (Massingill, 1979). However, biogeochemical studies involve complex interrelationships between geology, soil science, botany, and ecology and should be used with extreme caution (Levinson, 1974).

Auxiliary Elements

In searching for uranium deposits, the major element of interest is obviously uranium. But certain other elements may form a much wider dispersion halo resulting from their chemical behavior and weathering characteristics and may act as supplemental indicators of uranium. The indicators or pathfinder

elements most commonly used in uranium exploration are molybdenum, sulphur, lead, arsenic, vanadium, zinc, copper, nickel, cobalt, and thorium (Hawkes and Webb, 1962). Other elements, such as gold, tin, and tungsten can be analyzed for their own worth. Rare earth elements provide a basis for in-depth geochemical studies, particularly with respect to uranium mobilization and ore genesis. In general, the more elements sought, the more potential value the analytical data have. The particular elements selected for analysis by the respective laboratory depend on pilot surveys, analytical facilities, and funding constraints (Table II).

SETTING UP AN HSSR PROGRAM

From the principles first applied by Russian scientists in the early 1930s, geochemical exploration has evolved tremendously. Reviews of geochemical exploration for uranium have been compiled by Boyle et al (1971), Bowle et al (1971), Grimbert (1972), Dall'Aglia (1972), and Rose (1977) among others. In addition, large-scale geochemical surveys have been conducted in Canada, Finland, France, Norway, United Kingdom, and the USSR, as well as the NURE in the US. Most procedures and ideas reviewed in this paper are a direct consequence of similar programs developed in other countries and of standard geochemical sampling practices summarized by Hawkes and Webb (1962) and Lovinson (1974).

In a program with the magnitude of the HSSR, certain problems are inherent. More than one million samples will be collected from more than 650 000 locations. Sample analyses must be edited so that they are analytically correct and site locations are checked for accuracy before the data are reported to the public. Lastly, the samples need to be archived for future reference. Because two different regions of responsibility contain extensive

mountainous areas, basins, plateaus, and desert terraces, each laboratory developed its own program. To accomplish this goal, the five basic steps cited in Table III were followed.

In the USSR, the goal is to sample the entire US and Alaska so that areas favorable for uranium exploration are delineated on a regional scale. In all likelihood, data from the USSR program will not identify ore bodies, but rather, they will help outline geochemical provinces and delineate areas favorable for detailed follow-up studies.

Initially, a thorough literature research was conducted. The geochemistry of uranium as well as regional information on the type of geology, climate, structure, known types of ore deposits in the area, proven methods of exploration, and various types of equipment available for field sampling and field measurements were all examined. Based on this research, an initial program was set up by each laboratory.

Because uranium deposits seldom occur under simple geochemical conditions, one important aspect in developing a successful USSR program is the ability to test all methodologies and sampling philosophies. Most geochemical anomalies result from the movements of natural waters and soils; therefore, it is also necessary to understand the geometry, size, and type of dispersion patterns that may exist and how they are influenced by geology, climate, and topography (Lovering et al, 1956). This is done by means of pilot or orientation studies. The ideal place to conduct pilot studies is in the vicinity of known uranium deposits characteristic of the region being studied, where the extent of dispersion halos for anomalies related directly to ore bodies can be determined. Ideally, the areas should not be contaminated by human activity so that natural geochemical patterns can be observed and compared to background levels in unmineralized terrain (Graham and Webb, 1961). However,

TABLE II

STEPS IN SETTING UP AN HSSR PROGRAM

1. **Goals Outlined.**
2. **Leadership and Experience.**
Experienced management helps to minimize program costs.
3. **Literature Research of Selected Area.**
This research includes examination of all available information pertaining to the area of study. Topics should include physiography, geology, structure, hydrology, climate, known types of mineralization, geochemistry of element(s) sought, and case histories.
4. **Pilot (Orientation) Studies.**
All variables--how to collect the sample, which samples to collect, and how to treat the sample--should be fully examined. At the conclusion of the pilot study, a manual of systematic procedures is prepared and followed during later collection of samples from comparable terranes.
5. **Logistics.**
This includes studying the feasibility of subcontracting and methods of quality assurance for both field and analytical data. Report preparation, dissemination of data, and follow-up or detailed studies and how they are to be implemented are also considered.

such areas may not be available or may be limited to small deposits. Studies should cover the full range of environmental and climatic conditions typical of the study area. In addition, technical parameters and limits of the program are tested, modified, and improved until a methodology is developed that satisfies the goals of the overall program. Some parameters that need to be considered in designing and undertaking an HSSR program are listed in Table IV; the pilot study areas completed by the laboratories are shown in Fig. 1.

Each laboratory has developed for its own area of responsibility a field procedures manual that explains the purpose of the program; the care, calibration, and use of field equipment; and general procedures to be followed for all aspects of the program. Because varying methods of sample collection and preparation affect the effectiveness of geochemical surveys, field procedures and equipment are continuously being updated, and pilot studies are conducted for each new region so that the manuals are revised as necessary.

The DOE laboratories subcontract the majority of their sample collection responsibilities. The samples are collected according to systematic and standardized sampling procedures that are outlined in sample collection manuals. All field equipment necessary to collect samples and to take and record the required major data, including sample containers and data forms, are provided by the laboratories. At least two sets of maps which contain either a grid outline or preselected sample locations are also provided. Field personnel are required to attend a short training course where the objectives of the program, sampling methodology, and care and calibration of field equipment are taught. Samples are required to be able to read a map and recognize geologic regions. The DOE provides identification cards which are loaned by laboratory personnel after a prospective sampler attends the training course. In addition, each laboratory provides a public relations brochure, written for the

TABLE IV

TECHNICAL PARAMETERS TO CONSIDER IN DESIGNING AND UNDERTAKING AN ELSR PROGRAM

- | | |
|---|--|
| <p>A. Geology</p> <ul style="list-style-type: none"> a) lithologic regimes b) structural controls c) geomorphology d) weathering profiles e) ore occurrences (mineralized areas) f) uranium concentrations, background vs anomalous g) uranium and indicator element geochemistry h) dispersion patterns i) area to which pilot applies | <p>D. Sample Spacing (Reconnaissance Scale)</p> <ul style="list-style-type: none"> a) minimum b) maximum c) optimum for each sample type |
| <p>B. Hydrology</p> <ul style="list-style-type: none"> a) climatic regimes b) seasonal variations c) precipitation d) surface waters (drainage area, flow rates) e) ground waters (aquifers, recharge rates) | <p>E. Sample Location</p> <ul style="list-style-type: none"> a) where to take samples b) potential contaminants |
| <p>C. Sample Types</p> <ul style="list-style-type: none"> a) surface waters (streams, lakes) b) ground waters (springs, wells) c) sediment (wet--dry) d) others (grass, plant tissue) e) amount of sample to collect f) relation among different media g) influence of topography | <p>F. Sample Preparation</p> <ul style="list-style-type: none"> a) water--no treatment, acidification, filtration, ion-exchange concentrations b) sediment--sieving, type of sieve material, drying considerations, crushing, acid leach c) storage problems d) adequacy of analytical facilities |
| | <p>G. Sample Containers</p> <ul style="list-style-type: none"> a) water--glass bottles, polyethylene, teflon b) sediment--polyethylene, paper, or cloth bags c) storage problems |

layman, explaining the USSR. Laboratory personnel are present in a supervisory capacity during all aspects of the sampling and provide help with equipment malfunctions and gaining access to properties, as well as with monitoring the program. Subcontractors are required to contact the respective laboratory personnel at least weekly. In addition, LASL, ORGDP, and SRL require field crews to keep a composite 1° x 2° NTIS quadrangle map showing the progress of the contract.

Contract areas generally cover one or more NTIS quadrangles. Access is provided by the subcontractor and usually involves use of four-wheel drive vehicles. However, sample collection in some mountainous terranes requires horses or backpacking. Most areas in Alaska are sampled by use of helicopters.

FIELD MEASUREMENTS

There are many chemical factors that control the solubility of uranium in water, several of which are listed in Table V. A review of the literature shows disagreement as to which measurements are most important; uranium itself is the best indicator of uranium deposits. Of the measurements listed in Table V, the following are relatively easy to routinely measure in the field.

pH - In general, as pH decreases, uranium content increases. However, because uranium is soluble over such a wide range of pH (Ulrich and Loriod, 1963), pH is important to interpretation only when extreme values are encountered (Ottle and Hall, 1973).

conductivity - Uranium concentrations in waters from a given region generally correlate with concentrations of major components (approximated by conductivity), i.e., an increase in conductivity will usually correspond to an increase in uranium content in natural waters (Richardson, 1969; Hall and Hall, 1971; Dyar, 1970).

TABLE 7

SOME PARAMETERS TO BE CONSIDERED IN FIELD MEASUREMENTS

pH	dissolved oxygen
conductivity	Eh
temperature	bicarbonate
ground radioactivity	chloride
alkalinity	sulfate

1
2




temperature - The temperature of water affects the rate of chemical and biological reactions which may influence the concentration of uranium (Fix, 1956; Gatis and Ball, 1975).


equivalent uranium - Scintillometer measurements of "shield in" and "shield out" readings allow an equivalent uranium value to be calculated, which then can be used as a ground truth tie for airborne radiometric data. A high equivalent value may be an indication of mineralization of uranium and thorium daughter products (Whitehead and Brooks, 1969).

In general, field measurements are taken by use of small, lightweight, battery-operated portable field instruments (Figs. 2A and 2B). Typical pH meters weigh about 0.5 kg, can be easily calibrated in the field, are temperature compensated, and have a ± 0.1 pH precision. Spare probes can readily be exchanged. Conductivity meters, similar in size and weight to the pH meters, can measure up to 50 000 $\mu\text{mho/cm}$ ($\pm 1\%$) and are easily calibrated by use of a standardized KCl solution.


All temperatures are measured with precalibrated thermometers. The air temperature in the shade is recorded to the nearest Celsius degree. The water temperature is usually recorded to the nearest 0.5°C .

Several types of instruments that combine pH, conductivity, temperature, and dissolved oxygen measurements are also available. These water quality checkers are generally lightweight instruments having the versatility of making several different measurements with only one piece of equipment (Fig. 2C). They are ideal for use in areas of difficult access. Temperature (0 to 30°C , $\pm 0.5^\circ\text{C}$), conductivity (0 to 5000 $\mu\text{mho/cm}$, ± 1 $\mu\text{mho/cm}$), pH (0 to 14 , ± 0.1 pH), and dissolved oxygen (0 to 20 parts per million (ppm), ± 1.0 ppm) can usually be measured. Most types are battery operated and can be recharged. Availability





A



B

measurements are usually performed with field titration kits. Ground radioactivity is measured with portable scintillometers.

Some water samples contain abundant suspended material. This material may require filtration because as the suspended matter may contain additional uranium that is not in solution. All laboratories filter their water samples. Depending on the weight and size limitations of sample gear, several different filter models are used. One lightweight type used by LASL is shown in Fig. 3A. A slightly different and heavier model is used by SRL and runs off a fluorocarbon gas canister that can apply pressure up to 40 psi (Fig. 3B).

In any program of this magnitude, thousands of sediment samples are handled during peak periods. Because samples are analyzed for both uranium and a variety of other elements, any material that comes in contact with the sample could drastically affect the trace element data. Consequently, a method to collect (usually some sort of plastic scoop) and transport the sample (either a plastic or paper bag) had to be determined. All laboratories analyze the fine-sized fraction that passes through a 100 mesh screen.

SAMPLE COLLECTION

LASL

The LASL collection procedures are written for samples collected either in the Rocky Mountain states or in Alaska (Sharp and Amodeo, 1978).

Water sampling. In the Rocky Mountain states, about 50 ml of water are collected in two 25-ml vials that have been prewashed with dilute nitric acid. Ground-water samples from both wells and springs are collected as near the emergence source as possible. Holding tanks are not sampled. Stream waters are collected from the flowing current away from the bank. All waters are

filtered through a 0.45- μ membrane and acidified to pH ≤ 1.0 with 8 M reagent-grade nitric acid. All water measurements are made with instruments previously discussed (Fig. 2).


In Alaska, 50 ml of water are collected, but because of the water purity and due to the high costs per sample location, the time-consuming operation of filtration is omitted. Measurements are usually taken with a water quality checker (Fig. 2C). In addition to standard field measurements (Table II), dissolved oxygen is taken for all Alaska water samples.

Sediment Samples. Up to 1 kg of sediment is collected from at least three adjacent spots at each location. The sample is usually collected with a polyethylene scoop. The sediment must be water transported and taken below the water level (if water is present) and must contain enough organic-rich, fine-grained particles to fill a 25-ml polyethylene vial. In lake areas in Alaska, the sediment is collected with a specially designed 11-kg, suction-operated bottom sampler that can be dropped from the side of a helicopter (Fig. 4). After collection, sediments are put into a rip-top polyethylene bag and double labeled with the sample location number. The samples are dried at $\leq 100^{\circ}\text{C}$ and sieved to -100 mesh by the subcontractor. Ground radioactivity measurements are taken at all sites.

ORRDP

The ORRDP collects samples according to a ground-water (Oak Ridge Gaseous Diffusion Plant, 1978a) or a stream-water, stream-sediment format (Oak Ridge Gaseous Diffusion Plant, 1978b).

Ground Water. Well or spring waters are collected. After flushing the well and rinsing the water containers, two 250-ml polyethylene bottles are filled. The samples are taken as close to the wellhead as possible, but all



treated water and holding tanks are avoided. The samples are then sent to ORQDP for filtering through a 0.45- μ m cellulose acetate paper and analysis. All field measurements (Table II) are made with a water quality checker (Fig. 2C) which has been in operation for at least two minutes. This instrument is calibrated daily. In addition, total alkalinity, phenolphthalein alkalinity, and mixed-indicator alkalinity are determined with a. alkalinity test kit.

Stream Samples. Stream sediment or stream samples are collected from all basin locations. Stream waters are collected at the point of maximum flow. After a water sample is collected, the same field measurements are made as for a ground water sample. Sediment samples are gathered with a scoop and collected parallel to the longitudinal axis of the stream. The sample consists of a composite of several samples taken 2 to 3 m apart. The sediment is collected from the active portion of the stream and all organic, windblown, and floodplain materials are avoided. At least 25 g of the -100 mesh fraction are required. After collection, the sample is placed in a paper envelope, sealed with vinyl tape and sent to ORQDP. It is then dried at 85°C and sieved to -100 mesh.

SRI.

The SRI samples are collected according to procedures outlined by Priede and Jones (1972). Sample procedures vary according to sample type and climate and are grouped according to ground water, surface stream taken in humid areas, or surface stream taken in arid areas.

Ground Water. Spring and well-water samples are collected as near the source as possible. Well systems are thoroughly flushed before sampling. All treated waters (e. g., chlorinated) and samples from holding tanks are avoided.

After sample containers are prerinsed, about two liters of water are collected. Samples are filtered through a 0.3- μ m Nuclepore membrane in the field by use of a pressure filter apparatus (Fig. 1). Temperature, pH, and conductivity measurements are taken on the unfiltered water samples by instruments similar to those shown in Figs. 2A and 2B. About 50 ml of filtered water are used for alkalinity measurements that are made with a field titration kit.

Because of the low uranium concentrations in water samples in the eastern US and because of sample preservation problems, SRL developed a field ion-exchange procedure. About 1 l of water with a conductivity of 500 μ mho/cm or less is mixed with 10 g (4 g dry weight) of 100- to 200-mesh high purity cation-anion exchange resin. For samples exhibiting conductivity values greater than 500 μ mho/cm, a smaller volume of water is used. The ion exchange resin is mixed for about 10 minutes using a battery-operated stirrer. The resin is then allowed to settle into the original 2-oz bottle, which is sent to SRL for analysis of its contents.

Dissolved helium is measured for all ground water samples. The collection technique is modified from Dyck et al (1976). Generally, a clean, 10-oz soft drink bottle is filled and 2 ml of water withdrawn; the bottle is then capped, inverted, and then sent to SRL for analysis.

Surface Streams Taken in Humid Areas. Sample procedures and measurements for stream water samples are identical to those for ground water samples. In addition, 60 ml of filtered water are collected in a 2-oz bottle containing 1 ml of ultrapure nitric acid.

A sediment sample is collected either by use of a spring-loaded jaw scoop (for silty to rocky bottoms) or by a bail sampler which consists of a stainless steel tube with an attached bail and bag (for rocky bottoms). At least five sediment samples are collected along 10 m of the stream bed. A

stainless steel sieve is used to field screen the sediments and the -40 mesh fraction is retained. About 0.5 kg of the -40 mesh fraction is then placed into a Kraft paper bag and labeled. Samples are dried at 90 to 100°C before sending them to SRL.

Surface Streams in Arid Areas. Pilot surveys have determined that soil samples from arid areas generally are as effective as stream samples from arid areas, although dry wash areas are avoided when stream beds coexist in the same grid square. The sample procedure for dry sediments is the same as for wet sediments; however, the sample is usually collected with a shovel or trowel. If significant amounts of windblown sand are present, a composite of at least 15 separate areas is used. The sample is then sieved to a -18 to +40 and -40 mesh fractions. Both size fractions are then sent to SRL.

FIELD OBSERVATIONS

In a reconnaissance program, chances are high that any particular sample location will not be revisited. Therefore, it is essential to record all field measurements and observations at the site so that the information later can be used in evaluation of the data.

To do this, each laboratory has developed data forms on which the sampler can record the sample type, location, weather, possible contaminants, field measurements, and geologic observations. Field observations are number coded and can be recorded in minimal time. Each form has additional space for comments or clarification of information. Figure 5 is an example of the form used by LASL; it can be adapted for any type of sample normally collected. The SRL used separate data forms for ground water samples and surface samples in the eastern US prior to October 1973 but has adopted a standardized form for all sites in more recent sampling. The ORGP uses the same data form for

ground water, stream water, or sediment samples. The content of all data forms for all laboratories is similar.

In addition, each laboratory has systematic coded numbering systems. The LASL and ORUDP use prenumbered adhesive stickers whereas the SRL employs a system that requires writing the sample number on the sample containers. Each system is coded so that the state and quadrangle from which the sample was taken can be identified easily.

The following observations are generally recorded at each sample location for each laboratory.

location - All laboratories supply subcontractors with at least two copies of field maps. These maps are generally 7.5 minute (1:24 000), 15 minute (1:62 500), or county road maps. Each map contains a sample grid and/or premarked sample location. After sample collection, locations are transferred from the field map to an unrolled copy that can then be digitized at the respective laboratory for the latitudes and longitudes of the sample location. The SRL also requires a photograph of the site and directions for reaching the site.

weather - Seasonal climatic conditions may drastically affect uranium concentrations in surface waters and, to a much lesser extent, in sediments (Fix, 1956; Gornunov et al, 1953; Dol et al, 1975; Rose et al, 1976). Consequently, hydrogeological surveys should be completed as rapidly as possible. During periods of high runoff, normal uranium concentrations may be diluted whereas after a prolonged drought, uranium concentrations in runoff may be increased for a short period (Pendock, 1961; Lapatikina, 1964).

mining - Several elements, including uranium, in both surface waters and sediments tend to have relatively short halflives in areas of

HYDROGEOCHEMICAL AND STREAM/LAKE SEDIMENT FIELD DATA

ATTACH IDENTICAL SAMPLE NUMBER HERE						REPLICATE		SAMPLE TYPE(S)				LOCATION												DATE				AIR TEMP °F		WATER TEMP °C		COMMENTS		SPEC. MEAS.																																									
												LATITUDE						LONGITUDE																																																									
												DEG MIN SEC						DEG MIN SEC						DAY MO YR HR				°F		°C																																													
304927						222445		150711						43827						5677				9+12		75C																																																	
6.8						1208		85						98164622						11323112																																																							
pH						SPECIFIC CONDUCTANCE		LETTER I.D.				CPS						CPS						TYPE COLOR				TYPE COLOR				FLOW LEVEL				COLOR				STREAM CHANNEL				TYPE DENSITY				RELIEF WEATHER				OWNERSHIP				CONTAMINANTS				TYPE				IN				FT				FT			
								SHIELD IN				SHIELD OUT						ROCK				SED				WATER				VEG																																													

IN THE CASE OF EACH CIRCLED ENTRY SPACE, ENTER MOST APPROPRIATE DESIGNATORS LISTED BELOW:

(7) USE WITH REPLICATE
SAMPLER ONLY
(CHRONOLOGICALLY A,B,C, etc.)

(8) 1 NONE
2 STREAM < 5m WIDE
3 STREAM 5-15m WIDE
4 DEEP
5 SPRING
6 WELL
7 NATURAL POND
8 ARTIFICIAL POND
9 OTHER

(9) 1 NONE
2 FATTENED AND ACIDIFIED
3 FILTERED ONLY
4 ACIDIFIED ONLY
5 OTHER

(10) 1 NONE
2 WET STREAM
3 WET SEEP
4 WET SPRING
5 WET POND
6 DRY STREAM
7 DRY NATURAL POND
8 DRY ARTIFICIAL POND
9 OTHER

(11) 1 SIEVED -40 MESH
2 SIEVED -60 MESH
3 SIEVED -80 MESH
4 SIEVED -100 MESH
5 SIEVED -170 MESH
6 SIEVED -250 MESH
7 OTHER

(39) ENTER "C" WHEN
COMMENTS ARE MADE

(40) ENTER "S" WHEN
SPECIAL MEASUREMENTS
ARE MADE

(24) 1 SEDIMENTARY
2 METAMORPHIC
3 MAGMA
4 UNKNOWN

(30) 1 WHITE/BUFF
2 YELLOW
3 ORANGE
4 PINK/RED
5 GREEN
6 BROWN
7 GRAY
8 BLACK
9 OTHER

(31) 1 BOULDERS
2 COBBLES
3 GRAVEL
4 SAND
5 MUD
6 MUCK
7 OTHER

(62) 1 STAGNANT
2 SLOW
3 MODERATE
4 FAST
5 TORRENT

(63) 1 DRY
2 LOW
3 NORMAL
4 HIGH
5 FLOOD

(64) 1 CLEAR
2 MURKY
3 CLOUDY
4 MUDDY
5 ALGAL
6 OTHER

(65) 1 DEPOSITING
2 ERODING
3 UNKNOWN

(66) 1 CONIFER
2 DECEIDUOUS
3 BRUSH
4 GRASS
5 MOSS
6 MARSH
7 OTHER

(67) 1 BARREN
2 SPARSE
3 MODERATE
4 DENSE
5 VERY DENSE

(68) 1 FLAT
2 LOW < 10m
3 GENTLE 15-60m
4 MODERATE 60-300m
5 HIGH > 300m
6 OTHER

(69) 1 CLEAR
2 PARTLY CLOUDY
3 OVERCAST
4 RAINY
5 SNOWY
6 OTHER

(70) 1 FEDERAL
2 STATE
3 PRIVATE
4 INDIAN
5 OTHER

(71) 1 NONE
2 MINING
3 AGRICULTURE
4 INDUSTRY
5 SE WARE
6 POWER GENERATION
7 URBAN
8 RECREATION
9 OTHER

(72) 1 WINDMILL - STOCK
2 WINDMILL - DOMESTIC
3 SUBMERSIBLE PUMP
4 SUCTION PUMP
5 JET PUMP
6 LARGE TURBINE
7 HARD BAIL
8 UNKNOWN
9 OTHER

MAP NAME (a) Mt. Sample MONTANA MAP NUMBER (a) N4515.0-W11437.5 MAP SCALE 1:24000

COMMENTS: EXPLAIN ALL "OTHER" DESIGNATORS USED ABOVE, PLUS DESCRIBE ALL UNUSUAL OR SIGNIFICANT CONDITIONS SUCH AS SPECIAL RESTRICTIONS, TYPE (a) AND PROXIMITY OF CONTAMINANTS, QUANTITY OF ORGANIC DEBRIS, WELL CASING DESCRIPTION (AGE, RUST, AMOUNT OF USE, etc.), AQUIFER DESCRIPTION (NAME, DEPTH, etc.), STREAM CHANNEL DESCRIPTION, AND GENERAL ROCK NAME WHEN KNOWN. NOT EVIDENCE OF RECENT PRECIPITATION

Abandoned lead/zinc mine approx. 1 mile upstream

SPECIAL FIELD MEASUREMENTS
AS PER CONTRACT SPECS

I CERTIFY THAT THE ABOVE SAMPLE HAS BEEN TAKEN AND TREATED AS SPECIFIED BY LAB AND INDICATED ABOVE

John Smith
SIGNATURE

high relief (Chamberlain, 1964). Furthermore, access to water may be difficult and sediment may be absent locally. Therefore, sample densities may have to be increased so that adequate coverage can be obtained.

geology - Uranium content in both water and sediment generally reflects the local geology. For example, because of complexing of uranium with carbonate ions, a stream flowing over carbonate terrane would be expected to have higher uranium content than a similar stream flowing over siliceous terrane (Levinson, 1974). Sediments from acidic igneous rocks generally have greater uranium concentration than sediments from other rock types (Rogers and Adams, 1970). Also, ground waters that circulate along fractures and faults may contribute significant amount of uranium as well as other trace metals (Doi et al, 1975; Dyck, 1975). Consequently, the local geology may be the most important observation that will help in interpretation of the data.

contamination - All sources of contamination, such as mine waters, tailings, trash, and man-made structures (bridges, culverts, and well casings) are avoided where possible. However, any potential contaminant, such as uranium-rich phosphate fertilizers (Boberg and Runnells, 1971), is noted on the data form.

vegetation - In terrane containing abundant vegetation, relatively short dispersion trains in surface water can exist. This generally results from organic matter absorbing uranium from the water and, consequently, increasing the uranium concentration in sediment (Dill'Aglis, 1971; Dyck et al, 1971).

SAMPLING DENSITIES

In reconnaissance exploration sampling, densities may range from one sample per 1.6 km² to one sample per 160 km² or even greater (Levinson, 1974). Dispersion haloes even for small deposits can ordinarily be detected as far as several hundred meters in ground water and up to several km in some streams. Large deposits in the western US can be detected many kilometers downstream (Fix, 1956). According to Hawkes and Webb (1962), for a catchment area of 8 to 32 km², the surface drainage and/or sediment dispersion pattern for a significant ore body may vary from 300 to 3200 m. Ostle (1954) was able to detect anomalies in surface waters over 10 km downstream from waste dumps. Results of Canadian surveys for areas extensively covered by lakes suggest similar information can be obtained on a grid of one sample location per 8 km² compared to one sample location per 16 km² except for areas where deposits are very localized (Garrett, 1977). Clearly, the selected density depends on geology, hydrology, and climate. Complete coverage is not always possible for regions having poor access. One should choose a spacing so that at least two or more samples fall within the anticipated zone of an anomaly (Loving et al, 1956). Based on an extensive research of similar studies in similar terrains, the laboratories have selected the nominal sample densities shown in Table II.

The following sections briefly describe the type of media sampled for respective physiographic provinces. An extensive review of the geology and known and potential uranium hosts can be found in US Department of Energy Interim Report (1979).

LASL

LASL's total land area of responsibility in the program amounts to about 35% of the US. Some 250 000 sample locations will be taken from 2.7 million km^2 of land. The area includes most of the Rocky Mountain states and all of Alaska (Fig. 6). Much of the Rocky Mountain region consists of rugged mountain ranges separated by intermontane basins. In these mountains and on their flanks, fast-flowing stream waters and their sediments are the major sample media. Well-water samples are the major sample media in the intermontane basins.

Part of the Colorado Plateau is also in the LASL region, and this area contains several uranium districts, including the Grants mineral belt in New Mexico, which is the largest uranium-producing area in the US. The climate in the Plateau region and in the southern part of the LASL area of responsibility is semi-arid. In these areas, well water samples are collected when possible, although in sparsely populated areas dry stream beds they may be the only available sampling media.

Alaska contains a diversity of physiographic provinces. The northern and much of the interior of the state is underlain by regions of permafrost. These areas are also extensively covered by lakes and, consequently, primarily lake water and sediments are sampled. Two mountain ranges cross the state, the Brooks Range in the north and the Alaska Range in the south. In these areas fast-flowing stream waters and stream sediments are predominantly collected. The southeastern part of the state is not only rugged but also heavily vegetated. Therefore, primarily stream waters and stream sediments are collected.

Based on several pilot studies, LASL selected a sample density of one location per 10 km^2 for the Rocky Mountain states. All sample locations are


preselected by LASL personnel. Surface streams are chosen to represent drainage areas of about 10 km^2 . Sites which cannot be reached in the field are reselected to approximate the original drainage area as closely as possible. For sampling lakes in Alaska, a pattern containing 23-km^2 grids (1 per 9 mi^2) is put onto field maps, and helicopter pilots then select all sample locations as near as possible to the center of each grid square. Streams are sampled at twice this density, or two sample locations per 23 km^2 .

ORGDP

The total area of responsibility for ORGDP is about 2.6 million km^2 (Fig. 6). Samples in the northern regions are collected mostly from streams in marshlands. Much of the ORGDP area is within the Great Plains and Central Lowlands, which is comprised of generally low-lying topography. This area is extensively farmed and, although abundant, surface streams do not offer optimum samples. However, these lowlands are underlain by large ground-water aquifers and, consequently, ground-water samples predominate.

The southern area with its semi-arid climate contrasts sharply to the mid-continental US. There are also some known sandstone-type deposits in the Coastal Plain of Texas. Ground-water media provide the best sample media here, because streams generally are dry and may contain wind-blown material.

The sample density for ORGDP of one location per 26 km^2 predominantly reflects collection of ground-water media. All ground-water locations are chosen according to a grid system. A well location is selected in a grid for which well log information exists. If a site cannot be reached, an alternate is picked by the sampler, but it is the sampler's responsibility to select a site near to and representative of the original and to collect the necessary well log information (e.g., producing horizons, depth, and pump type).



Stream sample sites are selected according to considerations of drainage basins and drainage patterns. Sites are chosen by ORGDP personnel for basins that drain from 3 to 30-km² areas and average about 26 km². Any site locations that samplers are unable to reach are reselected to simulate the original site as nearly as possible.

SRL

The SRL area of responsibility includes all or parts of 37 states in the eastern US and western US. The procedures described in this report generally refer to SRL's operation in the eastern US because they have only recently begun sampling in the western US (Fig. 6). Regions in the eastern US consist predominantly of rolling hills and piedmont-type topography. The climate in these areas is generally humid with significant rainfall and abundant vegetation. Both streams and ground-water sample media are available, but access onto private property may be locally difficult.

The SRL region of responsibility in the western US includes part of the Basin and Range physiographic province. Much of this area is semi-arid and sparsely populated. Consequently, availability of the ground-water medium may be at a minimum and stream beds may be dry and filled with windblown debris. In addition, much of the area has interior drainage, and evaporites and playas are common.

The Pacific Coast and Sierra Nevada consist predominantly of north-trending mountain ranges separated by valley systems. Fast-flowing streams are abundant, but access is a major problem.

The SRL locations are selected based on a random grid. A sample location, regardless of the sample type, is selected by the subcontractor for 10 to 30-km² areas; the average spacing is one site for every 14 km². Rural

of them are that no two adjacent grid squares can be left vacant and no two sample points can be closer than 1.5 km. Streams can drain no more than three times the area of the grid; the largest stream which heads in a grid is usually sampled.

SUMMARY

The NURE HSSR program is one of the largest reconnaissance geochemical exploration programs ever attempted. By the completion of the program, more than one million samples will be collected from more than 650 000 sample locations. All data are reported by 1° x 2° National Topographic Map Series quadrangle boundaries (Fig. 1). Each quadrangle contains from 1000 and 3000 (normally 1500) sample locations; each sample location consists of one water and/or one sediment sample. Uranium and as many as 43 additional elements are reported for each location, depending on sample type (Table II). All information is considered confidential and not for private use until it is open filed. These data are then made available to the public. The magnetic tapes can be obtained from:

QJO17 Project
UCC-MD Computer Applications Dept.
4570 North Building
Oak Ridge National Laboratory
P. O. Box X
Oak Ridge, Tennessee 37839
Phone: (615) 574-4364

no report. are available from:

Bendix Field Engineering Corporation
Technical Library
Grand Junction Office
P. O. Box 1563
Grand Junction, Colorado 81501
Phone (303) 241-3601, Ext. 173

ACKNOWLEDGMENTS

The author wishes to thank David E. Groussan, Spencer S. Shannon, Jr., and Wayne A. Morris who reviewed early drafts of this manuscript and made many helpful contributions. In addition, special thanks are due Van Price of the Savannah River Laboratory, Todd Butz of the Oak Ridge Gaseous Diffusion Plant, and David Dahlan of the Department of Energy, Grand Junction Office, for their helpful suggestions.

REFERENCES

- Bauer, W.W. and Kumbell, D.D., 1971. Geochemical study of uranium in the South Platte River, Colorado. Geochim. Acta, 35: 433-450.
- Bowie, S.H.G., Ball, T.E. and Oatis, D., 1971. Geochemical methods in the detection of hidden uranium deposits. Can. Inst. Min. Metall., Spec. vol., 11: 103-111.
- Boyle, E.W., Hornbrook, E.H.W., Allen, R.C., Dyck, W. and Smith, A.Y., 1971. Hydrogeochemical methods—application in the Canadian Shield. Can. Min. Metall. Bull., 64: 60-71.
- Brinkman, P.H.D., Clows, D.R. and Walker, J.L., 1973. Exploration Geochemistry. Barringer Research Ltd., Rexdale, Ont., 49 pp.
- Brown, E.W., 1971. Geochemistry and ore exploration. Can. Inst. Min. Metall., Spec. vol., 11: 113-115.
- Brundin, H.H. and Hauris, E., 1972. Alternative sample types in regional geochemical prospecting. J. Geophys. Expl., 1: 7-16.
- Chamberlain, J.A., 1964. Hydrogeochemistry of uranium in the Bancroft-Haliburton Region, Ontario. Geol. Surv. Canada Bull., 18: 12 p.
- Dall'Asta, M., 1971. A study of the circulation of uranium in the supergene environment in the Italian Alpine Region. Geoch. Cosmochim. Acta, 35: 47-60.
- Dall'Asta, M., 1972. Planning and interpretation criteria in hydrogeochemical prospecting for uranium (with discussion). In: S.H.G. Bowie, H. Davis and D. Oatis (Editors), Uranium Prospecting Handbook, Institution of Mining and Metallurgy, London, pp. 121-134.
- Denson, E.H., Zeller, H.D. and Stephens, J.D., 1956. Water sampling as a guide in the search for uranium deposits and its use in evaluating widespread volcanic units or potential source beds for uranium. US Geol. Survey Prof. Paper, 300: 673-680.
- Doi, E., Hirano, R. and Mikami, Y., 1973. Uranium mineralization by ground water in sedimentary rocks, Japan. Environ. Geol., 70: 635-646.
- Dyck, W., 1974. Geochemical studies in the surficial environment of the Bancroft area, Ontario. Geol. Surv. Canada Paper, 74-52, 30 p.
- Dyck, W., 1976. Geochemistry applied to uranium exploration. Geol. Surv. Canada Paper, 76-61 31-47.
- Dyck, W., Dunn, A.C., Denson, E.C., Hobbs, J.L., Pollock, J.C. and Oatis, D., 1971. Comparison of regional geochemical uranium exploration methods in the Bancroft area, Ontario. Can. Inst. Min. Metall., Spec. vol., 11: 1-10.

Dyck, W., Pelchat, J.C. and Mailleur, G.A., 1976. Equipment and procedures for the collection and determination of dissolved gases in natural waters. Geol. Surv. Canada Paper, 75-32: 10 p.

Fix, P.F., 1956. Hydrogeochemical exploration for uranium. US Geol. Surv. Prof. Paper, 300: 667-671.

Garrett, R.G., 1977. Sample density investigations in lake sediment geochemical surveys of Canada's uranium reconnaissance program. US DOE, Open file Rept., OE-77(77), pp. 173-183.

Germanov, A.E., Batlink, S.G., Volkov, G.A., Lisitin, A.K. and Serebrennikov, J.S., 1958. Some regularities of uranium distribution in underground waters. Proceedings 2nd XI International Conference on Peaceful Uses of Atomic Energy, Geneva, 2: 126-130.

Grimbert, A., 1972. Use of geochemical techniques in uranium prospecting (with discussion). In: S.H.U. Bowie, M. Davis and D. Ostle (Editors), Uranium Prospecting Handbook, Institution of Mining and Metallurgy, London pp. 110-120.

Grimbert, A. and Loriot, R., 1968. Geochemical prospecting for uranium (trans. from French). IS AEC Off. of Info. Services, Springfield, VA, AEC-tr-7572, 38 pp.

Hawkes, H.E. and Webb, J.S., 1962. Geochemistry in Mineral Exploration, Harper and Row, New York, NY, 415 pp.

Lovinson, A.A., 1974. Introduction to Exploration Geochemistry, Applied Publishing Ltd., Calgary, Alta., 612 pp.

Little, H.W. and Durham, C.C., 1971. Uranium in stream sediments in carboniferous rocks of Nova Scotia. Geol. Surv. Canada Paper, 70-54: 17 pp.

Lopitkin, A.P., 1964. Characteristics of migration of uranium in the natural waters of humid regions and their use in the determination of the geochemical background for uranium. Geochem. Int., 4: 788-795.

Lovring, T.S., Lakin, H.W., Ward, F.M. and Cannon, F.C., 1956. The use of geochemical data in the methods in prospecting for uranium. US Geol. Surv. Prof. Paper, 300: 667-671.

Mudroch, J.A., 1969. An orientation study of the uranium distribution in lake water, Saskatchewan District, Saskatchewan. Colorado School of Mines Quarterly, 64: 357-376.

Murphy, G.L., 1970. Uranium indicator plants of the Colorado Plateau. New Mexico Geology, 1: 49-52.

Murray, W.T., 1969. Uranium in lake water from the Kaiparok Region, Labrador. Canadian Journal of Mineralogy, 7: 377-384.

Morse, R.H., 1971. Comparison of geochemical prospecting methods using ratios with those using ratios and uranium. Int. J. Geol. Sci., 11: 213-230.

Oak Ridge Gaseous Diffusion Plant, 1973a. Procedures manual for groundwater reconnaissance sampling. US DOE, Open file Rept., OJIX-62(73), 19 pp. plus 3 appendixes.

Oak Ridge Gaseous Diffusion Plant, 1973b. Procedures manual for stream sediment reconnaissance sampling. US DOE, Open file Rept., OJIX-84(73), 19 pp. plus 5 appendixes.

Ostle, J., 1954. Geochemical prospecting for uranium. Mining Magazine, 91: 201-205.

Ostle, D. and Ball, T.K., 1973. Some aspects of geochemical surveys for uranium (with discussion). In: Uranium Exploration Methods, International Atomic Energy Agency, Vienna, pp. 171-187.

Parozek, J.D., 1911. Uranium in British surface and underground waters. Nature, 191: 1139-1190.

Price, V. and Jones, P.L., 1977. Training manual for water and sediment geochemical reconnaissance. Savannah River Laboratory, Open file Rept., DPST-79-219, 104 pp.

Regeus, J.J.W., and Adams, J.A.S., 1970. Uranium. In: E.H. Wedepohl (Editor), Handbook of Geochemistry, v. II-2, chapter 92, Berlin, Springer Verlag.

Ross, A.W., Keith, M. and Suhr, M.H., 1976. Geochemical drainage surveys for uranium: sampling and analytical methods based on trial surveys in Pennsylvania. US ERDA, Open file Rept., OJIX-28(76), 34 pp.

Ross, A.W., Jr., 1977. Geochemical exploration for uranium. In: Systematic and hydrogeological and stream sediment reconnaissance for uranium in the United States, US DOE, Open file Rept., OJIX-77(77), pp. 313-342.

Saukoff, A.A., 1956. Radiohydrogeological method in prospecting for uranium deposits. Proceedings of International Conference on Peaceful Uses of Atomic Energy, Geneva, 6: 750-759.

Sharp, R.R., Jr. and Ansell, P.L., 1973. Field procedures for the uranium hydrogeological and stream sediment reconnaissance as used by the Los Alamos Scientific Laboratory. US DOE, Open file Rept., OJIX-29(73), 64 pp.

US Department of Energy, 1979. National Uranium Resource Reassessment. Technical Report, June 1979. US DOE, Open file Rept., DOE-111(79), 141 pp.

Whitford, R.W. and Brooks, R.R., 1968. A comparative evaluation of the geochemical, hydrogeological, and biological methods of prospecting for uranium. Int. J. Geol. Sci., 8: 179-188.

LIST OF FIGURES

- Fig. 1. Index map showing regions of responsibility, pilot study areas, and NTMS quadrangle boundaries for the HSSR program.
- Fig. 2. Typical field instruments used in the HSSR program (A = pH meter, B = conductivity meter, C = water quality checker).
- Fig. 3. Typical filter assemblies used in the HSSR program (A = LASL standard 50-ml syringe filter assembly, B = SRL pressure filter assembly).
- Fig. 4. Bottom sampler used to obtain lake sediments in Alaska.
- Fig. 5. Representative data form used in the HSSR program.
- Fig. 6. Major physiographic provinces for the HSSR.