
**The Installation of the Westbay
Multiport Ground-Water Sampling
System in Well 699-43-42K Near
the 216-B-3 Pond**

T. J. Gilmore

September 1989

**Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute**



DISCLAIMER

This program was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor Battelle Memorial Institute, nor any or their employees, makes **any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights.** Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or Battelle Memorial Institute. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

PACIFIC NORTHWEST LABORATORY
operated by
BATTELLE MEMORIAL INSTITUTE
for the
UNITED STATES DEPARTMENT OF ENERGY
under Contract DE-AC06-76RLO 1830

Printed in the United States of America

Available to DOE and DOE contractors from the
Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831;
prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service,
U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

NTIS Price Codes, Microfiche A01

Printed Copy

<u>Pages</u>	<u>Price Codes</u>
001-025	A02
026-050	A03
051-075	A04
076-100	A05
101-125	A06
126-150	A07
151-175	A08
176-200	A09
201-225	A10
226-250	A11
251-275	A12
276-300	A13

3 3679 00056 5285

PNL-6973
UC-11,41

THE INSTALLATION OF THE WESTBAY MULTIPORT
GROUND-WATER SAMPLING SYSTEM IN WELL
699-43-42K NEAR THE 216-B-3 POND

T. J. Gilmore

September 1989

Prepared for
the U.S. Department of Energy
under Contract DE-AC06-76RL0 1830

Pacific Northwest Laboratory
Richland, Washington 99352

SUMMARY

In 1988 and 1989, Pacific Northwest Laboratory installed a multiport ground-water sampling system in well 699-43-42K drilled near the 216-B-3 Pond on the Hanford Site in southeastern Washington State. The multiport system will be used to evaluate methods for determining the vertical distribution of contaminants and hydraulic heads in ground water. This installation was in conjunction with a similar multiport installation near the 300 Area of the Hanford Site. Well 699-43-42K is adjacent to two Resource Conservation and Recovery Act (RCRA) ground-water monitoring wells, which will allow for a comparison of sampling intervals and head measurements between the multiport system and the RCRA monitoring wells.

Eight sampling ports were installed in the upper unconfined aquifer by backfilling at depths of 161.1 ft, 174.1 ft, 187.1 ft, 201.17 ft, 217.2 ft, 230.2 ft, 243.2 ft, and 255.2 ft below land surface. However, because of damage to the casing during installation, only the top four ports should be used for pressure measurements and sampling until repairs occur. The locations of the sampling ports were determined by the hydrogeology of the area and the screened intervals of adjacent ground-water monitoring wells.

Installation by backfilling around the multiport system was the first method of its kind on the Hanford Site and proved adequate. For future installations, an alternative method is recommended where the multiport system would be placed inside a cased and screened well using packers to isolate the sampling zones.

CONTENTS

SUMMARY	iii
INTRODUCTION	1
GEOLOGY	5
GEOPHYSICAL LOGGING	6
DRILLING AND INSTALLATION	7
DRILLING OPERATIONS	7
INSTALLATION	7
Backfill Material	9
Usable Sampling Ports	12
WELL DEVELOPMENT	14
CONCLUSION AND RECOMMENDATIONS	15
REFERENCES	19
APPENDIX A	A.1

FIGURES

1	Hanford Site Location Map	2
2	Location of 699-43-42K Near the 216-B-3 Pond on the Hanford Site	3
3	Diagram of Multiport System and Adjacent Resource Conservation and Recovery Act Monitoring Wells	4
4	Well 699-43-42K Construction Progress Curve	8
5	Completion Arrangement at the Well Head	10
6	Multiport Monitoring Zone Configuration	11
7	Pressure Transducer Readings	13
8	Installation of Multiport System in a Cased and Screened Well a) placing 4-in. stainless-steel casing in well; b) backfilling around 4-in. stainless-steel casing; c) placing multiport system in well and inflating packers	17

INTRODUCTION

A Westbay multiport ground-water sampling system was installed in a well on the Hanford Site as part of Pacific Northwest Laboratory's (PNL's) (a) Site-Wide Ground-Water Monitoring Project. The installation of the multiport system is part of a program to evaluate methods that determine the vertical distribution of contaminants and hydraulic head in the ground water. Two multiport systems were installed during the last quarter of 1988 and the first quarter of 1989. This report discusses the installation and completion of the multiport system in well 699-43-42K near the 216-B-3 Pond on the Hanford Site. A similar report discusses the installation of a multiport system in well 399-1-20 near the 300 Area on the Hanford Site (Gilmore 1989).

The drilling of well 699-43-42K for the multiport system was completed in January 1989 by Onwego Drilling Company, Richland, Washington, under sub-contract to PNL. Pacific Northwest Laboratory furnished contract management and supervised the drilling and installation of the multiport system. Geological data were gathered by PNL personnel. Under contract to PNL, Westbay Instruments Ltd. provided initial consultation on the assembly and installation of the system.

Well 699-43-42K is located in southeastern Washington State on the Hanford Site (Figures 1 and 2). Coordinates for well 699-43-42K are N136,445.2 E576,997.5 meters NAD83 (North American Datum of 1983). The well was drilled to a total depth of 263.0 ft and was completed to 261.87 ft. The multiport system was installed immediately adjacent to two Resource Conservation and Recovery Act (RCRA) ground-water monitoring wells, 699-42-42B and 699-43-42J (Figure 2). Well 699-42-42B was completed to 250 ft, and well 699-43-42J was completed to 180 ft (Figure 3). This location will provide a comparison of sampling intervals between the multiport system and the RCRA monitoring wells.

(a) Pacific Northwest Laboratory is operated for the U.S. Department of Energy by Battelle Memorial Institute under Contract DE-AC06-76RL0, 1830.




FIGURE 1. Hanford Site Location Map

Appendix A contains the as-built diagrams with a geologic column, geo-physical logs, the completion/inspection reports; the casing record sheets for well 699-43-42K; and the gamma log with the lithology and port intervals.




FIGURE 2. Location of 699-43-42K Near the 216-B-3 Pond on the Hanford Site




FIGURE 3. Diagram of Multiport System and Adjacent Resource Conservation and Recovery Act Monitoring Wells

GEOLOGY

The stratigraphy in well 699-43-42K closely correlates with that in the adjacent RCRA monitoring wells. Three major stratigraphic formations were encountered during drilling, which include in ascending order the Columbia Basalt Group, the Ringold Formation, and the glacial-fluvial sediments.

The top of the basalt occurs at 243 ft and is present at the final depth of 263 ft below ground surface in well 699-43-42K. The top of the basalt is likely the erosional remnants of the Elephant Mountain Member (Graham, Last, and Fecht 1984). The basalt is very dark grayish brown, amygdaloid, with some oxidized coatings. The amygdalites are commonly filled with siliceous, white opaline-type material. Between 260 and 258 ft, a zone of relatively easier drilling occurs. The sample descriptions describe this zone as gravelly silty-sand composed predominantly of basalt grains. The natural gamma log supports this description and indicates the zone to be coarser grained than the surrounding basalt signature. This zone is possibly an epiblastic interbed or a weathered zone in or between basalt flows.

The Ringold Formation has been identified in the region by Graham, Last, and Fecht (1984) and Tallman et al. (1979), and extends from approximately 243 to 111 ft below the ground surface. The basal, lower, and middle Ringold units are suggested to be present in the region of well 699-43-42K (Graham, Last, and Fecht 1984); however, the correlation of these units to this well requires more characterization work. The Ringold Formation in this discussion is treated as undifferentiated, with the notable lithologic changes discussed. The Ringold Formation is generally characterized by gravels and sands in a silty matrix. There was an increase in the silt and gravel contents over the Hanford formation, but no noticeable increase or decrease in the percentage of basalt grains. Two notable units of clayey silt exist in the well. These occur at 233 to 204 ft and 181 to 150 ft below the ground surface. The layers of clayey silt are bracketed by sandy gravels.

The upper glacial-fluvial sediments informally termed the Hanford formation extend from 111 ft to near the surface. The sediments between 111 ft

and 17 ft are composed of unconsolidated well-sorted, medium to fine sands. Thin layers of silt approximately 1 ft thick occur at 97 ft and 93 ft. The sediments are composed of gravelly sand from 17 ft to the surface. Geology logs are presented in Appendix A.

GEOPHYSICAL LOGGING

Pacific Northwest Laboratory logged well 699-43-42K using density, natural gamma, and neutron probes on November 18, 1989. The well was logged between 0 ft and 263 ft. The natural gamma logs were used to verify silt/clay layers and interbeds in the decisions to locate sampling ports (Appendix A).

DRILLING AND INSTALLATION

DRILLING OPERATIONS

Well 699-43-42K was drilled using a Bucyrus Erie 22-W cable tool drilling rig by the drive barrel and hard-tool method. Drilling operations began on September 29, 1988, and continued to November 16, 1988, totaling 36 days of drilling (Figure 4). The total depth of the well was 263 ft. A drive barrel was used to drill between 0 ft and 111 ft, and a hard tool was used between 111 and 236 ft. Temporary telescoping carbon steel 12-in. casing was placed from the surface to 116.5 ft, and 10-in. temporary casing was placed from the surface to the total depth of 258.5 ft. During construction, the 10-in. casing was removed twice, once at 116 ft to replace bent casing and once at 207 ft to replace a lost drive shoe. The drive shoe was not recovered and was pushed into the well sidewall at approximately 206 ft.

INSTALLATION

Prior to the installation of the multiport system, sampling intervals were determined based on the hydrogeology of the borehole and the screened intervals of adjacent monitoring wells. The natural gamma geophysical logs and geology logs were used to locate these sampling intervals. The required multiport casing lengths for the chosen sampling intervals were calculated and the pieces laid out in order. Each casing length was given a number sequentially from the bottom of the monitoring well, and an appropriate coupling was attached to the top of each casing. All casing lengths were measured and recorded (see Appendix A). The multiport components were protected by plastic shipping covers until installation. Casing lengths were 10 ft and under in length in divisions of 5 ft, 2 ft, and 1 ft. The multiport system was constructed of 1.5-in.-inside-diameter polyvinylchloride (PVC) pipe with well screens that measured 2.88 in. outside diameter. The multiport system was then placed in the well inside a 4-in. schedule 80 PVC protective casing. This casing was used to protect the multiport system and keep the screens free of seal material. A centralizer was placed 10 ft from the bottom of the protective casing to center the multiport system in the well. As the multiport system was placed in the well, each assembled joint




FIGURE 4. Well 699-43-43K Construction Progress Curve

was hydraulically tested by applying a minimum internal pressure of 100 psi. After the multiport system was properly positioned and secured, the system was backfilled.

The temporary carbon steel casing was removed during the backfilling using hydraulic jacks (Figure 5), which proved much easier than using the cable-tool rig to remove the casing (Gilmore 1989). A minimum 1-ft overlap was maintained between the carbon steel casing and the backfill material. A longer overlap was employed when placing the sand filter pack, and a shorter overlap was required when placing the bentonite to reduce "hitching" of the clay on the end of the casing. When the temporary carbon steel casing is cut with an acetylene cutting torch, the protective casing around the multiport system must be shielded from the heat. A 4-in. steel pipe with an adaptive collar to screw into a 4-in. PVC pipe was used over the multiport system to protect the system from the heat.

Backfill Material

A minimum of 10-in. casing was required to accommodate working room for the tremie pipe and protective casing around the multiport system for the placement of the annular filter packs and seals. Eight sampling ports were placed at 161.1 ft, 174.1 ft, 187.1 ft, 201.17 ft, 217.2 ft, 230.2 ft, 243.2 ft, and 255.2 ft below land surface. Backfill around the sampling ports was 20-40 Colorado Silica Sand emplaced by gravity feed. Each sampling port has approximately 2.5 ft of sand filter pack above it and 4.5 ft of filter sand pack below it for a total sampling interval of approximately 7 ft (Figure 6). Medium-size Enviroplug bentonite chunks were placed by gravity feed between the filter sand packs isolating each sampling interval. The medium-size Enviroplug is composed of irregularly shaped bentonite pieces that range in size from 1/4 to 1 in. Prior to placing the bentonite in the well, it was sieved over a coarse mesh screen to remove the fines in order to reduce bridging in the well. The bentonite was then poured through a funnel into a 4-in. PVC tremie pipe for placement in the well. The funnel was used to control the speed of the placement of the bentonite to approximately 2.5 lb/min, because bridging would occur at higher rates. The minimum thickness of the bentonite seals was 5.9 ft between ports 3 and 4.




FIGURE 5. Completion Arrangement at the Well Head




FIGURE 6. Multiport Monitoring Zone Configuration

The integrity of the seals was confirmed by pressure transducer readings at each port (Figure 7). A surface seal of cement grout was placed from 20 ft to the surface. The installation of the Westbay multiport system was initiated on December 8, 1988, and was completed on January 12, 1989, for a total of 23 working days. This installation time included 6 days spent retrieving and rewelding the 10-ft casing that broke below the ground surface. Excluding this repair time it took approximately 2 days of completion per sampling port.

Usable Sampling Ports

During installation of the multiport system, the casing was damaged when the tremie pipe used to place the annular seal was dropped and fell approximately 15 ft. This occurred at approximately 220 ft below land surface. It was determined that a hole in the casing was open to formation water during the development of the ports. The static water level inside the casing during development returned to 162.5 ft after each evacuation of the casing. The casing, if intact, is designed to be water tight. The location of the hole was indicated by a static water level in the casing of 162.5 ft, which is the same as the piezometric level that has been calculated for approximately 219 ft below land surface. In addition, a tight spot in the casing will not allow a tool of greater length than 0.8 ft to pass below the 219 ft level. Confirmation of the break in the casing was attempted using a downhole camera; however, the water in the multiport system at 219 ft was murky and the exact nature of the damage could not be seen. The casing does not provide a pathway for contaminant migration as a result of the damage.

At present, it is suggested that only the upper four ports at depths of 161.1 ft, 174.1 ft, 187.1 ft, and 201.17 ft below land surface be used for pressure measurements and sampling. The ports at 217.2 ft, 230.2 ft, 243.2 ft, and 255.2 ft below land surface are near or below the damage in the casing. The damage should first be repaired, and/or a smaller sized sampler (less than 0.8 ft long) be used for the lower ports. The hole in the casing will not affect the pressure measurements or sampling.




FIGURE 7. Pressure Transducer Readings

WELL DEVELOPMENT

The pumping ports were not opened after it was determined that the casing was damaged and there was a possible hole. Because of the hole in the casing, if a port were opened it would be exposed to the formation water coming in from the damaged zone. If a port were unable to be reclosed, open communication would exist in the aquifer, and the system would be compromised. Currently, the upper four ports can be used without risk to communication between discrete zones in the unconfined aquifer.

CONCLUSIONS AND RECOMMENDATIONS

The Westbay system is a versatile multiport system that provides data on vertical contamination and hydraulic head distribution representative of formation conditions from a single well. The system's major advantage is its modular design, allowing versatile monitoring configurations that can be easily customized to any location and installed in a single well. Another advantage is that the samples and pressure measurements are taken outside the access tube through the sampling port. This eliminates the need to purge the access tube during sampling; therefore, the sample's fluid chemistry is not altered as a result of degassing, oxidation, biogenic activity, and precipitation. The lag time on fluid pressure measurements is also reduced relative to a conventional standpipe well. Additionally, the multiport system allows the integrity of coupling valves, joints, and the annulus seals to be verified during installation and operation.

A major disadvantage is that the operation of the system is labor intensive and requires substantial training. The installation of the system in a backfilling operation is also more difficult than conventional standpipe well construction because the multiple screened intervals and the PVC construction require additional protection during backfilling. Very little maintenance can be performed after the system is installed by backfilling; therefore, should the system components fail, the life span of the system would be curtailed.

Studies on obtaining representative samples without purging the system are recommended prior to installing more multiport systems. Results from these studies could have an impact on installation methods. One method that is recommended for technical review is the installation of the system in a specially cased and screened well. This method would allow the removal and repair of the system after installation and would reduce the possibility of damage to the multiport system during well completion. Stainless steel 4-in. casing, screened at desired monitoring locations, would be placed in

the well and backfilled. The multiport system would be placed inside this 4-in. stainless steel casing, using packers to isolate sampling intervals (Figure 8). According to Frank Patton, President and owner of Westbay Instruments Inc., a similar installation technique has been used successfully by the Orange County Water District, California.




FIGURE 8. Installation of Multiport System in a Cased and Screened Well
 a) placing 4-in. stainless-steel casing in well; b) back filling around 4-in. stainless-steel casing; c) placing multiport system in well and inflating packers (after drawings provided by Westbay Instruments Inc.)

REFERENCES

Black, W. H., H. R. Smith, and F. D. Patton. 1986. "Multiple-Level Ground-Water Monitoring with the MP system." Paper presented at the Surface and Bore Hole Geophysical Methods and Ground Water Instrumentation Conference and Exposition, October 1986, Denver, Colorado.

Gilmore, T. J. 1989. The Installation of a Multiport Ground-Water Sampling System in the 300 Area. PNL-6910, Pacific Northwest Laboratory, Richland, Washington.

Graham, M. J., G. V. Last, and K. R. Fecht. 1984. An Assessment of Aquifer Intercommunication with B Pond-Gable Mountain Pond at the Hanford Site. RHO-RE-ST-12P, Rockwell Hanford Operations, Richland, Washington.

Tallman, A. M., K. R. Fecht, M. C. Marratt, and G. V. Last. 1979. Geology of the Separations Area, Hanford Site, South-Central Washington. RHO-ST-23, Rockwell Hanford Operations, Richland, Washington.



APPENDIX A

KAISER ENGINEERS HANFORD		SURVEY DATA REPORT		Request No. - 8 9 1 - 0 3 3
Project/W.O. No. B 80919	Time B-Pond Monitoring Well			File No. W F 1 1 - 1 1 9
KEH Job No. B 80919-11	Prepared By Gary B. Wagner	Date 03/15/89	Reviewer Grant F. Brazil	1 1 1
DESCRIPTION OF WORK		ACCEPTABILITY (Within Plan Tolerance)	DISTRIBUTION	
Surveyed new well located at B-Pond for horizontal and vertical positions. Calculated coordinates based on Plant, NAD27, and NAD83 datums. Vertical position based on Plant datum.			Survey File <input type="checkbox"/>	OR
			Field Project File <input type="checkbox"/>	
			T. Gilmore <input type="checkbox"/>	1
			J. Rieger <input checked="" type="checkbox"/>	1
		TBD by <input type="checkbox"/>		
		Requestor <input type="checkbox"/>		
SURVEY RESULTS AND COMMENTS				
<u>B-POND WELL</u>				
<u>PLANT COORDINATES</u>		N 42,509.0	E-42,304.3	
<u>NAD83 COORDINATES</u>		N136,445.2	E576,997.5 (meters)	
<u>NAD27 COORDINATES</u>		N447,706.3	E2,252,908.4	
<u>ELEVATIONS</u>				
Top of casing elevation		581.38		
Top of brass cap elevation		579.03		

WELL COMPLETION/INSPECTION REPORT

Page 1 of 2

Specification No. B-47717-A-E Rev. No. 0
 Project Westbay Multipoint Ground Water Sampling
 Location B-Pond
 Drilling Co. Onward
 Driller Russ Unruh, Lenny Bultena
 Other (companies) Westbay
 Geologist(s) K.R. Oster, S.M. Garber, S.S. Terl
 T.G. Inc.

Well No. 679-43-42K Temp. Well No. WB-1
 Coordinates N 42 529.0 E 42 724.3 (Plant Coordinates)
 Casing Elev. 581.38 Ground Elev. 579.03

DRILLING METHOD

Rotary Air N/A Mud N/A
 Cable Tool D.O.-111'6.15' H 111'-303'6.15'
 Drilling Fluid 200 East Area Supply Water
 Other N/A

GEOPHYSICAL LOGGING			COMPLETION DATA			AQUIFER TESTING		
Sondes	Interval	Date	Drilled Depth	263'6.15'		Type	N/A	
Natural Gamma	263'-1'	11/18/88	Completed Depth	261.82'		Length of Test		
Neutron	263'-1'	11/18/88	Date Started	9/29/88		Volume Pumped		
Density	262'-0'	11/18/88	Date Completed	11/3/89		Drawdown		
			Static Water Level/Date	260.5'12/6/90		Date of Test		

INSPECTION RESULTS

CLEANING

Inspection Method visual
 Acceptance Criteria Spec. Specs. 6.1, 11.2
 Accept Reject Date
 Drilling Tools/Rig KRO 1/13/89
 Temporary Materials KRO 1/13/89
 Permanent Materials KRO 1/13/89

MATERIAL STORAGE/PACKING

Inspection Method visual
 Acceptance Criteria Spec. Specs. 6.2, 6.3
 Accept Reject Date
 Mtl. Handling/Storage KRO 1/12/89
 Material Packing KRO 1/13/89

LUBRICANTS/ADDITIVES

Inspection Method visual
 Acceptance Criteria Spec. Specs. 6.2, 11.3
 Accept Reject Date
 Depth(s) 1255.73' - 254.73'
 242.73' - 242.73'

Identify Accept Reject Date
 Additives Drilling Water KRO 1/13/89
 Lubricants Barium Pal. FM KRO 1/13/89

STRAIGHTNESS TEST

Inspection Method visual
 Acceptance Criteria Spec. Specs. 11.0, 3.5
 Accept KRO Reject Date 1/13/89

Inspection Method visual
 Acceptance Criteria Spec. Specs. 7.5 D
 Accept KRO Reject Date 1/11/89

WELL PROTECTION

Inspection Method visual
 Acceptance Criteria Spec. Specs. 11.0, 3.5
 Accept Reject Date
 Type Size Placement
 Westbay PVC 1.5" 81-92'-Surface
 (includes screened intervals)

Accept Reject Date
 Protective Posts KRO 1/13/89
 Locks

ANNULAR SEAL

Inspection Method verify using steel tape
 Type Interval
 Bentonite Plug Seal (medium) 262.35' - 259'

Acceptance Criteria Spec. Specs. 7.5 G, H, I, O
 Volume Accept Reject Date
 344 cu/ft (50 lb/cu) KRO 1/12/89
 460 cu/ft (70 lb/cu) KRO 1/12/89
 31/64 cu/ft (50 lb/cu) KRO 1/14/89
 4 cu/ft (100 lb/cu) KRO 1/14/89

Colorado Silica Sand (20-40 mesh) 259' - 252'
 Bentonite Plug Seal (medium) 252' - 246.41'
 Colorado Silica Sand (20-40 mesh) 246.46' - 240.2'

OTHER (initial if performed)

Continued on Page 2
 N/A Well Abandonment N/A Downhole TV Inspection Complete As-Built Diagram,
 Well Development Driller's/Geologist's Logs

For all blanks mark N/A if not applicable.

WELL COMPLETION/INSPECTION REPORT

Page 2 of 2

Specification No. R-U7717-A-F Rev. No. 0
 Project Westby Multipoint Ground Water Sampling
 Location P-Pond
 Drilling Co. Onsite 20
 Driller Russ Vanns, Lenny Bultena
 Other (companies) Westby
 Geologist(s) K.B. Oster, S.M. Goodwin, S.S. Tefel, T. Gilmore

Well No. 699-43-43K Temp. Well No. WB-1
 Coordinates N 42° 59.0' E 42° 304.3' (Plat. Coordinates)
 Casing Elev. 581.38 Ground Elev. 529.02

Type	SCREEN	Length	Slot Size	Depth(s)
PVC - Slotted		1'	10	230.7' - 229.7'
PVC - Slotted		1'	10	217.69' - 216.64'
DVC - Slotted		1'	10	201.67' - 200.67'
PVC - Slotted		1'	10	187.65' - 186.65'
PVC - Slotted		1'	10	174.64' - 173.64'
PVC - Slotted		1'	10	161.63' - 160.63'

Inspection Method Verify using steel tape
 Acceptance Criteria Spec. Sec 5. 60, 7.5
 Accept KRO Reject Date 1/13/89

ANNULAR SEAL

Type	Interval	Volume	Accept	Reject	Date
Bentonite Plug Seal (medium)	240.2' - 233.65'	5 bags (50 lbs ea)	KRO		12/15/88
Colorado Silica Sand (20-40 mesh)	233.65' - 227.3'	5 bags (100 lbs ea)	KRO		12/10/88
Bentonite Plug Seal (medium)	227.3' - 221.2'	4 1/2 bags (50 lbs ea)	KRO		12/19/88
Colorado Silica Sand (20-40 mesh)	221.2' - 214'	4 1/2 bags (100 lbs ea)	KRO		12/19/88
Bentonite Plug Seal (medium)	214' - 204.2'	6 1/2 bags (50 lbs ea)	KRO		12/21/88
Colorado Silica Sand (20-40 mesh)	204.2' - 198.05'	5 1/2 bags (100 lbs ea)	KRO		12/21/88
Bentonite Plug Seal (medium)	198.05' - 191'	5 1/2 bags (50 lbs ea)	KRO		12/22/88
Colorado Silica Sand (20-40 mesh)	191' - 184'	16 bags (100 lbs ea)	KRO		12/22/88
Bentonite Plug Seal (medium)	184' - 178'	4 3/4 bags (50 lbs ea)	KRO		12/22/88
Colorado Silica Sand (20-40 mesh)	178' - 171'	9 bags (100 lbs ea)	KRO		12/27/88
Bentonite Plug Seal (medium)	171' - 165'	7 bags (50 lbs ea)	KRO		12/27/88
Colorado Silica Sand (20-40 mesh)	165' - 158'	16 bags (100 lbs ea)	KRO		12/27/88
Bentonite Plug Seal (medium)	158' - 114'	9 9 1/4 bags (50 lbs ea)	KRO		12/28/88
Granular Bentonite Seal	114' - 20'	55 bags (100 lbs ea)	KRO		12/28/88
Cement Grout Seal	20' - .5'	17 bags (44 lbs ea)	KRO		1/12/89
Concrete Pad	.5' - + .33'		KRO		1/13/89

AS-BUILT DIAGRAM

Well Number (WB-1) Geologist Oster, Goodwin, Teel Page 1 of 3

Reviewed by J.L. McShan Date 2-2-89

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
116' 6 1/2" of 12" Carbon Steel		45		Gravelly Sand
Casing (Removed)		44		" "
258' 6 1/2" of 10" Carbon Steel		43		" "
Casing (Removed)		42		Sand (medium)
Cement Grout		41		" (Fine)
Granular Bentonite Top 20'		40		" (medium-fine)
		39		" "
		38		" (medium)
		37		" "
		36		" "
		35		" "
		34		" "
12" Drive Shot		33		" "
Enviroplug Medium Top 114'		32		" "
		31		" "
		30		" "
		29		" "
		28		" "
		27		" "
		26		" "
		25		" "
		24		" "
		23		" "
		22		" "
		21		" "
		20		" "
		19		" "
		18		" "
		17		" "
		16		" "
		15		" "
		14		" "
		13		" "
		12		" "
		11		" "
		10		" "
		9		" "
		8		" "
		7		" "
		6		" "
		5		" "
		4		" "
		3		" "
		2		" "
		1		" "
		0		" "

A-1800-186 (3/87)

AS-BUILT DIAGRAM

 Well Number (WB-1) Geologist Oster, Goodwin, Tefl Page 2 of 3

 Reviewed by J.L. Marshall

 Date 2-2-89

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
258 6/8" of 10" Carbon Steel Casing		33		Silty Sandy Gravel
Screenings 10 slot PVC		32		" " "
Sampling Pipe diameter is 1.5"		31		" " "
20-40 Colo. Silica Sand Top 158'		30		" " "
Measurement Port 161.13'		29		Water table 2158'
Enviroplug Medium Top 165'		28		Gravelly Silty Clay
20-40 Colo. Silica Sand Top 171'		27		TOP OF SILT/CLAY @ 159'
Measurement Port 174.14'		26		Slightly Gravelly Sandy Silty Clay
Enviroplug Medium Top 178'		25		Sandy Clayey Silt
20-40 Colo. Silica Sand Top 184'		24		Slightly Gravelly Clayey Sandy Silt
Measurement Port 187.15'		23		" " " "
Enviroplug Medium Top 191'		22		" " " "
20-40 Colo. Silica Sand Top 198.05'		21		TOP OF GRAVELS @ 181.5'
Measurement Port 201.17'		20		Silty Sandy Gravel
Enviroplug Medium Top 204.2'		19		" " "
20-40 Colo. Silica Sand Top 214'		18		" " "
Measurement Port 217.19'		17		Gravelly Silty Sand
Enviroplug Medium Top 221.2'		16		TOP OF SILT/CLAY @ 204.5'
20-40 Colo. Silica Sand Top 227.3'		15		Slightly Gravelly Sandy Silt / Clay
Measurement Port 230.2'		14		BOULDERS @ 202"
Enviroplug Medium Top 233.65'		13		Sandy Silt / Clay
20-40 Colo. Silica Sand Top 240.2'		12		" "
Sampling Port 243.23'		11		" "
Enviroplug Medium Top 246.46'		10		Slightly Gravelly Sandy Silt / Clay
20-40 Colo. Silica Sand Top 252'		9		GRAVELLY SAND (G) S G @ 233'
10" Drive Shot		8		G S A SG @ 235'
		7		SG A ZSG @ 239.5'
		6		SILTY SANDY GRAVEL
		5		VESICULAR BASALT @ 243'
		4		" " "
		3		" " "
		2		" " "
		1		" " "
		0		" " "
		-1		" " "
		-2		" " "
		-3		" " "
		-4		" " "
		-5		" " "
		-6		" " "
		-7		" " "
		-8		" " "
		-9		" " "
		-10		" " "
		-11		" " "
		-12		" " "
		-13		" " "
		-14		" " "
		-15		" " "
		-16		" " "
		-17		" " "
		-18		" " "
		-19		" " "
		-20		" " "
		-21		" " "
		-22		" " "
		-23		" " "
		-24		" " "
		-25		" " "

A-1800-188 (3/87)



Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number (WB-1) Geologist Oster, Goodwin, Trol Page 3 of 3

Reviewed by V.L. McShan Date 2-2-89

CASING LENGTH MEASUREMENT RECORD

Project: Battelle PNL Date: December 1, 1988 Project No.: 606-88

Location: BPond Drillhole No.: WB-1 Nominal B.O.H.: 163'

Casing Size/Type: 1.5" MP Measured By: Kurt Seedhouse

Section No.	Serial No.	Description	Nominal Length, ft.	Measured Length, ft. Top of Coupling	Cumulative Length, ft. Top of Coupling	Magnetic Collars
0	--	End Cap	1'	1' 4/16	.16	--
1	2117	5' Pumping Port	5'	5' 0"	5.16	4.16
2	4062	2' Measurement Port	2'	2' 1/16	7.16	--
3	--	5' Coupling	5'	5' 0"	12.16	--
4	2105	5' Pumping Port	5'	5' 0"	17.16	16.16
5	4063	2' Measurement Port	2'	2' 2/16	19.17	--
6	--	5' Coupling	5'	5' 1/16	24.18	--
7	--	1' Coupling	1'	1' 2/16	26.19	--
8	2112	5' Pumping Port	5'	5' 1/16	30.19	29.18
9	4066	2' Measurement Port	2'	2' 1/16	32.20	--
10	--	5' Coupling	5'	5' 1/16	37.20	--
11	--	1' Coupling	1'	1' 0"	38.20	--
12	2113	5' Coupling Port	5'	5' 0"	43.20	42.20
13	4061	2' Measurement Port	2'	2' 1/16	45.21	--
14	--	5' Coupling	5'	5' 1/16	50.21	--
15	--	2' Coupling	2'	2' 1/16	52.22	--
16	--	5' Coupling	5'	5' 1/16	57.22	--
17	2114	2' Pumping Port	2'	2' 0"	58.22	58.22
18	4058	2' Measurement Port	2'	2' 1/16	61.23	--
19	--	5' Coupling	5'	5' 1/16	66.23	--
20	--	5' Coupling	5'	5' 1/16	71.24	--
21	2103	2' Pumping Port	2'	2' 1/16	73.24	72.24
22	4059	2' Measurement Port	2'	2' 1/16	75.25	--
23	--	5' Coupling	5'	5' 1/16	80.25	--
24	--	1' Coupling	1'	1' 2/16	81.26	
25	2106	5' Pumping Port	5'	5' 0"	86.26	85.26

CASING LENGTH MEASUREMENT RECORD

Project: Battelle PNL Date: December 1, 1988 Project No.: 606-88
 Location: BPond Drillhole No.: WB-1 Nominal B.O.H.: 163'
 Casing Size/Type: 1.5" MP Measured By: Kurt Seedhouse

Section No.	Serial No.	Description	Nominal Length, ft.	Measured Length, ft. Top of Coupling	Cumulative Length, ft. Top of Coupling	Magnetic Collars
26	4857	2' Pumping Port	2'	2' 0"	86.26	--
27	--	5' Coupling, 1' Coup.	5'	5' 1/16	94.27	--
27a	--	1' Correction	--	--	--	--
28	2104	5' Pumping Port	5'	5' 0"	99.27	97.27
29	4054	2' Measurement Port	2'	2' 1/16	101.27	--
30	--	10' Coupling	10'	10' 1/16	111.28	--
31	--	10' Coupling	10'	10' 0"	121.28	--
32	--	10' Coupling	10'	10' 1/16	131.29	--
33	--	10' Coupling	10'	10' 2/16	141.30	--
34	--	10' Coupling	10'	10' 2/16	151.31	--
35	--	10' Coupling	10'	10' 1/16	161.31	--
36	--	10' Coupling	10'	10' 0"	171.31	--
37	--	10' Coupling	10'	10' 0"	181.31	--
38	--	10' Coupling	10'	10' 0"	191.31	--
39	--	10' Coupling	10'	10' 0"	201.31	--
40	--	10' Coupling	10'	10' 1/16	211.32	--
41	--	10' Coupling -	10'	10' 1/16	221.32	--
42	--	10' Coupling	10'	10' 0"	231.32	--
43	--	10' Coupling	10'	10' 1/16	241.33	--
44	--	10' Coupling	10'	10' 0"	251.33	--
45	--	10' Coupling	10'	10' 1/16	261.33	--

DISTRIBUTION

<u>No. of Copies</u>	<u>No. of Copies</u>
<u>OFFSITE</u>	26 <u>Pacific Northwest Laboratory</u>
2 DOE/Office of Scientific and Technical Information	R. W. Bryce J. W. Falco M. D. Freshley R. H. Gray T. J. Gilmore (5)
<u>ONSITE</u>	
2 <u>DOE Richland Operations Office</u>	J. M. Hales P. C. Hays M. G. Hefty G. V. Last R. E. Lundgren
E. A. Bracken M. W. Tiernan	S. P. Luttrell P. J. Mitchell
2 <u>Westinghouse Hanford Company</u>	R. W. Nelson R. L. Skaggs R. M. Smith R. E. Wildung
K. R. Fecht R. L. Jackson	Publishing Coordination Technical Report Files (5)

