

High Quality Tube to Tubesheet Joints - When, Where and Why,  
A. F. Lillie, Energy Systems Group

MASTER

High quality tube-to-tubesheet joints are required wherever and whenever a failure of the joint can lead to an extended plant shutdown (and consequent economic loss) due either to damage to the heat exchanger or lengthy time to locate and repair the leak and requalify the unit for service. A prime example of such a joint occurs in the steam generator tube-to-tubesheet joints of a sodium-cooled fast breeder reactor where the welds separate highly reactive fluids (sodium-and-steam/water).

The Atomics International (AI) division of Rockwell International's Energy System Group is currently designing and building the steam generators (evaporators and superheaters) for the nation's first large breeder reactor, the Clinch River Breeder Reactor (CRBR) plant near Oak Ridge, Tennessee. The integrity of the tube-tubesheet joints (1514 welds per unit in a total of 9 units) over the 30 year lifetime of these units is crucial to the demonstration of the fast breeder reactor as a reliable, economic energy option for production of electricity in the years ahead.

The joint is an autogenous butt weld performed using the internal bore weld (IBW) process. The weld is fully inspectable using high precision radiography and ultrasonic techniques in addition to standard visual, liquid penetrant and helium leak check inspections. The tubes and tubesheets are fabricated from high purity 2½ cr-1Mo low alloy ferritic steel, and, as a precaution against in-service weld cracking, each tube-to-tubesheet weld is heat treated prior to inspection.

The weld was originally developed under a Rockwell funded program which designed and built a 30 MWT test model of the AI "hockeystick" steam generator, known as the AI Modular Steam Generator (AI-MSG). As a result of the flawless performance of that unit in the early 70's, the hockey stick was selected by DOE as the reference steam generator for the CRBR. AI was awarded the current contract for design and fabrication of the CRBR steam generators in late 1975 and is currently in the process of building the 11 units (1 prototype, 9 plant units plus 1 spare plant unit).

An integral part of the contract was the requirement for further development and refinement of the tube-to-tubesheet weld, leading to definition of acceptance criteria for the weld based upon the highest quality weld reasonably achievable in the development phase of the program. The acceptance criteria are based on the use of a high precision microfocus rod anode radiography technique capable of imagining 1 mil porosity levels. In addition, a special ultrasonic inspection technique was developed by AI to measure the weld geometry (concavity, convexity, wall thinning) to assure that the welds meet the necessary configuration requirements. Special post weld heat treat equipment and techniques have been developed to allow individual PWHT of each and every weld prior to inspection.

In summary, the tube-to-tubesheet welds in the CRBR steam generators are among if not the highest quality welds being produced in industry today. These stringent quality requirements must be met if this most critical of fast breeder reactor components--the steam generators--are to function reliably and assure a place for the breeder reactor option in the future energy supply for the United States.

## **DISCLAIMER**


**This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.**

---

## **DISCLAIMER**

**Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.**

# AI-MSG EVAPORATOR/SUPERHEATER MODULE




6999-2501C

## DISCLAIMER

This book was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

# AI HOCKEYSTICK STEAM GENERATOR —1970—


AI MODULAR STEAM GENERATOR (AI-MSG) FABRICATION



Rockwell International  
Energy Systems Group

40000-4060CNA


AI HOCKEYSTICK  
STEAM GENERATOR  
—1970—  
HIGH RELIABILITY  
TUBE-TO-TUBESHEET  
WELD DEVELOPED



Rockwell International  
Energy Systems Group

41001-4019B

## CRBRP STEAM GENERATOR CONFIGURATION



77521791


# FULLY INSPECTABLE TUBE-TO-TUBESHEET JOINT HAS HIGH RELIABILITY

- FUNCTION

TUBESIDE CIRCUIT SEAL FORMING A PORTION OF THE SODIUM – STEAM/WATER BOUNDARY

- CONFIGURATION

AUTogenous BUTT WELD OF 2-1/4 CR - 1 MO ESR TUBE – TO – 2-1/4 CR - 1 MO VAR MACHINED TUBESHEET SPIGOT (1514 WELDS PER STEAM GENERATOR)



- FUNCTIONAL REQUIREMENTS

HIGH RELIABILITY, FOR 30 YEAR DESIGN LIFETIME, AGAINST STEAM/WATER-TO-SODIUM LEAKS

- INSPECTIONS PERFORMED


VISUAL  
HELIUM LEAK CHECK  
DYE PENETRANT  
RADIOGRAPHY (ROD ANODE)  
ULTRASONIC (FOR GEOMETRY)



Rockwell International  
Atomics International Division

# POROSITY ACCEPTANCE CRITERIA IS VERY STRINGENT

## WELD RADIOGRAPH DEPICTED



\*K FACTOR = SUM OF DIAMETERS (in mils) OF ALL PORES EXCEEDING 5 mils IN DIAMETER




Rockwell International  
Energy Systems Group

79-AU1-35-43

# WELD MUST MEET TIGHT CONFIGURATION REQUIREMENTS


## UNCONSTRAINED 5G WELDING IS USED



Rockwell International  
Energy Systems Group

79-AU1-35-42






EACH WELD IS INDIVIDUALLY  
POST WELD HEAT TREATED



Rockwell International  
Energy Systems Group

1949-1153CNA


# EACH WELD RECEIVES 5 SEPARATE INSPECTIONS AFTER POST WELD HEAT TREAT



Rockwell International  
Atomics International Division

79-AU1-35-15A

TOBE-100388146 ULTRASONIC INSPECTION



MR. GREGORY ROD VANGEL

