

SOLVENT REFINED LIGNITE PROCESS DEVELOPMENT  
QUARTERLY TECHNICAL PROGRESS REPORT NO. 1  
JULY, AUGUST, SEPTEMBER 1977

NOTICE  
This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Donald E. Severson, Principal Investigator  
Engineering Experiment Station  
University of North Dakota 950 1305

April 7, 1978

**MASTER**

PREPARED FOR THE UNITED STATES  
ENERGY RESEARCH AND DEVELOPMENT ADMINISTRATION

Under Contract No. EF-77-6-02-4189  
UND Account No. 4604

zb

## **DISCLAIMER**

**This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.**

---

## **DISCLAIMER**

**Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.**

Blank Page

## CONTENTS

I.	OBJECTIVE AND SCOPE	5
II.	SUMMARY	7
III.	TECHNICAL PROGRESS	8
	A. PDU Operation	8
	1. General	8
	2. M-33	8
	3. L-1	13
	4. L-2	15
	5. Discussion of Results	17
	B. PDU Maintenance and Construction	25
	1. General	25
	2. Area 00: Buildings and Utilities	25
	3. Area 01A: Coal Preparation and Storage	25
	4. Area 01B: Slurry Preparation and Pumping	25
	5. Area 02: Slurry Preheating, Dissolving and Gas Separation	25
	6. Area 03: Solid-Liquid Separation	25
	7. Area 04: Liquid Separation and Solvent Recycle	26
	8. Area 05: Gas Separation and Recycle	26
	C. Project Lignite Laboratory	26
IV.	CONCLUSIONS	28
V.	APPENDICES	29
	A. Statement of Work	29
	B. PDU Run M-33	32
	C. PDU Run L-1	98
	D. PDU Run L-2	241

Blank Page

## I. OBJECTIVES AND SCOPE

Project Lignite was established in 1972 in the Department of Chemical Engineering at the University of North Dakota for the purpose of determining the appropriate technological approach to the conversion of Northern Great Plains lignite to premium solid, liquid and gaseous fuels. The ultimate goal of the work was to make recommendations for a refinery based on lignite as feedstock. The experimental portion of the program was intended to develop data and know-how to carry out technological steps in the refinery processes for which information for scaleup was insufficient.

In keeping with this objective, laboratory and benchscale work were carried out and a continuous process development unit (PDU) was constructed and operated to demonstrate the feasibility of continuous liquefaction of lignite. Economic studies were made, and under a project subcontract, the Department of Chemistry of UND developed information on catalytic hydrogenation of solvent refined lignite.

The continuous process originally envisioned was the two stage conversion of lignite to fuel liquids, with solvent refined lignite as an intermediate and useful fuel product. The first stage is a unit converting 50 pounds per hour of raw lignite into solvent refined lignite by reaction with synthesis gas (carbon monoxide and hydrogen) in the presence of a hydrogen donor solvent that is continually regenerated from the lignite during processing. The mineral separations system is a countercurrent decantation process carried out at elevated temperature and pressure. The second stage was to be the catalytic hydrogenation to premium liquid fuels of the solvent refined lignite produced in the first stage. However, this latter step was not implemented, and the program has been directed at developing the liquefaction and solid-liquid separation stages.

Project Lignite was originally undertaken in accordance with Office of Coal Research Contract No. 14-32-0001-1224, later changed to ERDA Contract No. E(49-18)-1224, for the period March 28, 1972, through March 27, 1977. The period was later extended to June 15, 1977. In early 1977, a supplemental agreement was made under ERDA Contract No. EF-77-C-02-4189 to provide for the continuation of Project Lignite for the period June 1, 1977, through June 15, 1978.

The continuation basically provides for extended runs in the liquefaction section of the Process Development Unit, together

with some operation of the gas clean-up and recycle sections, the evaluation of the solid/liquid separation section, corrosion coupon testing, the determination of solids accumulation on the dissolvers, the production of clean solvent refined lignite, and data collection and analysis.

This report is the first of the required quarterly progress reports. The work statement for the supplemental agreement for the continuation of Project Lignite is attached as Appendix A.

## II. SUMMARY

Approximately 900 hours of liquefaction operation were accumulated with the PDU most of which was in two extended runs scheduled for 28 days each. Relatively high conversions were maintained with potential solvent recoveries of over 100 percent of solvent charged. Actual solvent recoveries, however, were about 90 percent. Product distribution changed with time of operation with relatively more SRL and less liquids produced while total conversion remained high. Buildup of solids in the reactor resulted in deposits on reactor walls and reduction in residence time giving a higher melting point product. Process upsets and higher melting point SRL caused plugs in piping and process vessels as well as pumping difficulties. Product gas cleanup and recycle were accomplished without difficulty and with no significant difference noted in liquefaction characteristics.

In a short run (83 hours), Gascoyne lignite was found to have the greatest response to liquefaction of the lignites tested so far. Conversions were high and yields of SRL were high at the expense of light oil production.

Operation of the solids-liquid separation unit gave significant separation of SRL from the mineral matter and unreacted lignite although the separation was variable and less effective than desired.

Distillation of solvent by the routine laboratory method and equipment was compared with results using standard ASTM procedure. The routine distillation gave slightly lower distillate volumes at a given vapor temperature.

### III. TECHNICAL PROGRESS

#### A. PDU OPERATIONS

##### 1. General

Run M-33, the last of the short tests (nominally a week), was completed, and the long test series (nominally a month) was started. During Run M-33, four yield periods were established totaling 83 hours of operation on lignite. This run continued the investigation of the effects of different sources (mines) of the feed lignite on liquefaction and plant operability.

The extended runs were given a different code designation, that of the "L" series. Two runs, L-1 and L-2, of the three planned for the program were completed. Each run was scheduled for 28 days and lignite was processed for approximately 75 percent of actual operating time for a total of 860 hours. Operation of the PDU for extended periods was established with relatively high conversion and indicated potential recovery of solvent over 100 percent. Mechanical problems were still troublesome and upsets in operation often resulted in formation of plugs in the lines which usually could be corrected without shutdown. Build-up of solids in the reactor was also noted.

Summary data for Run M-33 are included in Table 1 and that for Runs L-1 and L-2 in Tables 2 and 3. Detailed write-ups for the runs are included in the Appendix with Run M-33 in Appendix B, Run L-1 in Appendix C, and Run L-2 in Appendix D. Each run is reviewed and average results discussed in the following sections.

Emphasis in laboratory work was directed towards analytical support of the PDU operations. Some special work was done on distillation procedures for recycle solvent in comparing results using ASTM procedures with those from the routine laboratory distillations.

##### 2. Run M-33

Lignite from the Gascoyne mine of the Knife River Coal Mining Company near Gascoyne, ND was used as feedstock in the continuing investigation of the effects of coal source on liquefaction yields and plant operability. Ash and moisture content of the Gascoyne lignite was significantly higher than those of the lignites previously used with the PDU, being approximately 9 and 35 percent, respectively.

TABLE 1: SUMMARY DATA FOR RUN M-33

Lignite Source Yield Period Symbols	← Gascoyne →			
	M-33A	M-33B	M-33C	M-33D
Hours on Coal at end of Y.P.	○ →			
During Run	23.0	35.0	71.0	83.0
Cumulative	1925.8	1937.8	1973.8	1985.8
Reactors Used			R-1B	
Coal Charged, lbs/hr	41	45	47	42
Gas Charged, SCF/hr	413	430	430	437
Solvent/Coal Ratio	2.18	2.04	1.94	2.16
LHSV, Hr <sup>-1</sup>	1.34	1.37	1.49	1.43
GHSV, Hr <sup>-1</sup>	289	301	301	306
Coal Rate, lbs/hr/CF	28.8	31.3	32.7	29.3
Gas Rate, SCF/lb Coal	10.0	9.7	9.2	10.4
Gas Consumed, SCF/lb Coal	2.4	2.7	2.4	1.9
Mol% H <sub>2</sub> in Gas Consumed	19.2	19.1	6.7	-19.4*
Yields, Wt% MAF Coal				
Net Gas	39.9	34.2	34.1	39.1
Net Oil	58.1	66.6	63.4	62.0
(Lt Oil)	(-4.6)	(2.8)	(6.0)	(17.6)
(SRL)	(62.7)	(63.8)	(57.4)	(44.4)
Net H <sub>2</sub> O and Ash	-5.6	-6.4	-9.3	-11.8
Unconverted MAF Coal	7.6	5.5	11.8	10.7
Solvent Recycle, %				
Actual	89.8	94.2	86.2	98.6
Potential (Calc.)	98.9	100.7	101.7	104.4
Potential (Excluding Lt Oil)	96.5	96.4	95.1	100.2
Material Balance, %	99.5	96.8	97.0	98.6
Conditions				
Temperatures, °F				
Slurry Preheater Outlet	762	752	741	749
Dissolver Inlet	735	725	717	721
R-1A 3 ft	NIU	NIU	NIU	NIU
R-1A 15 ft	NIU	NIU	NIU	NIU
R-1B 3 ft	768	762	765	768
R-1B 15 ft	822	815	822	828
Dissolver Outlet	751	743	751	748
Flash Preheat	629	642	650	657
Flash Vapor	513	513	515	523
Pressures				
Dissolver, psig	2500	2500	2500	2500
Inter, Sep., psig	300	300	300	300
Vacuum Flash Vapor, Torr	15	15	15	15
SLS System in Use?	No	No	Yes	No
Percent H <sub>2</sub> in Feed Gas	52.4	49.6	51.1	50.5
CO <sub>2</sub> Yield, Wt% MAF Coal	56.2	55.6	57.1	60.6
C <sub>1</sub> -C <sub>3</sub> Yield, Wt% MAF Coal	9.1	7.9	6.7	6.6
Gas Consumed (H <sub>2</sub> Equiv) Wt% MAF Coal	2.36	2.64	2.34	1.80

\* Negative value indicates a net hydrogen production.

6/14/78

TABLE 2: SUMMARY DATA FOR EXTENDED RUN L-1

Yield Period Symbols	L-1B	L-1C	L-1D	L-1E	L-1F	L-1H	L-1I	L-1J	L-1K
Hours on Coal @ End of Y.P.									
Since Reactor Cleaning	70.0	82.0	31.5	43.5	60.0	101.0	113	152.5	164.5
During Run	70.0	82.0	162.4	174.4	313.9	354.9	366.9	406.3	418.3
Cumulative	2055.8	2067.8	2148.2	2160.2	2299.7	2340.9	2352.7	2392.1	2404.1
Reactor Used	← R-1B →				← R-1A →				
Coal Charged, lbs/hr	47	50	50	48	50	52	51	51	50
Gas Charged, SCF/hr (Recycle Gas, SCF/hr)	472	489	454	434	462	469	469	487	481
Solvent/Coal Ratio	1.96	1.88	1.85	1.92	1.87	1.76	1.75	1.77	1.81
LHSV, Hr <sup>-1</sup>	1.38	1.44	1.41	1.46	1.44	1.43	1.41	1.40	1.42
GHSV, Hr <sup>-1</sup>	330	342	318	304	323	328	328	341	336
Coal Rate, lbs/hr/CF	32.7	35.2	34.8	33.8	35.1	36.2	35.9	35.3	35.2
Gas Rate, SCF/lb Coal	10.1	9.7	9.1	8.9	9.2	9.1	9.1	9.6	9.6
Gas Consumed, SCF/lb Coal	2.7	2.3	2.8	2.9	3.1	1.7	2.1	1.4	1.7
Mol% H <sub>2</sub> in Gas Consumed	25.6	19.6	26.8	21.6	27.6	32.2	24.3	13.3	19.6
Yields, Wt % MAF Coal									
Net Gas	36.8	28.2	33.3	31.0	40.3	27.1	30.0	28.5	26.9
Net Oil	74.0	73.0	62.6	71.6	56.1	65.0	65.0	61.8	65.8
(Dist Oil)	(23.0)	(24.2)	(9.0)	(15.7)	(4.1)	(3.9)	(5.9)	(10.5)	(22.2)
(SRL)	(51.0)	(48.8)	(53.6)	(55.9)	(52.0)	(61.1)	(59.1)	(51.3)	(43.6)
Net H <sub>2</sub> O & Ash	-11.6	-8.5	-3.2	-5.8	-5.3	-4.1	-4.4	-0.9	-3.5
Unconverted MAF Coal	0.8	7.3	7.3	3.2	8.9	12.0	9.4	10.6	10.8
Solvent Recycle, %									
Actual	89.7	95.0	93.4	91.4	86.8	93.3	93.2	83.5	86.4
Potential (Calc)	107.3	108.0	103.0	105.2	101.4	101.4	102.1	103.7	107.6
Potential (Excluding Lt Oil)	100.5	103.9	-	99.3	-	-	-	97.2	101.4
Material Balance, %	100.2	100.2	98.1	99.6	99.5	101.3	101.0	98.6	99.3
Conditions									
Temperatures, °F									
Slurry Preheater Outlet	717	715	718	721	715	736	741	754	757
Dissolver Inlet	698	695	693	697	702	710	715	729	733
R-1A 3 ft	NIU	NIU	NIU	NIU	770	745	746	755	758
R-1A 15 ft	NIU	NIU	NIU	NIU	828	823	824	815	804
R-1B 3 ft	757	757	745	742	NIU	NIU	NIU	NIU	NIU
R-1B 15 ft	827	829	824	822	NIU	NIU	NIU	NIU	NIU
Dissolver Outlet	779	767	-	-	-	-	-	-	-
Flash Preheat	646	647	650	655	650	626	626	636	641
Flash Vapor	526	526	530	528	507	505	504	508	504
Pressures									
Dissolver, psig	2500	2500	2500	2500	2500	2500	2500	2500	2500
Inter. Sep., psig	300	300	300	308	273	296	290	290	297
Vacuum Flash, Torr	15	14	14	15	14	14	14	14	14
SLS System in Use?	No	No	No	No	Yes	No	No	Yes	Yes
Mole Percent H <sub>2</sub> in Feed Gas	53.2	52.8	52.4	52.4	53.4	54.1	52.2	52.2	52.5
Mole Percent CO in Feed Gas	46.3	46.8	47.1	47.0	46.0	45.5	47.1	47.2	47.0
CO <sub>2</sub> Yield, Wt % MAF Coal	52.6	43.4	51.0	50.7	59.5	41.0	42.6	38.1	38.6
C <sub>1</sub> -C <sub>3</sub> Yield, Wt % MAF Coal	7.9	6.6	7.0	6.8	8.1	5.9	6.7	4.6	4.8
Gas Consumed (H <sub>2</sub> Equiv), Wt % MAF Coal	2.30	1.97	2.41	2.42	2.68	2.09	1.82	1.21	1.48

TABLE 3: SUMMARY DATA FOR EXTENDED RUN L-2

Yield Period Symbols	L-2B	L-2C	L-2D	L-2E	L-2F	L-2G	L-2H	L-2I	L-2 Overall
Hours on Coal @ End of Y.P.									
Since Reactor Cleaning	33.5	45.5	109.5	121.5	68.5	80.5	99.0	110.8	-
During Run	80.3	92.3	156.0	168.0	306.1	318.1	429.5	441.4	441.4
Cumulative	2521.7	2533.7	2597.4	2609.4	2747.5	2759.5	2871.0	2882.8	2882.8
Reactor Used	← R-1A →				← R-1B →		← R-1A →		
Coal Charged, lbs/hr	49	46	47	48	46	47	47	50	49
Gas Charged, SCF/hr (Recycle Gas, SCF/hr)	459(210)	458(234)	457(240)	442(252)	506(292)	511(263)	475(168)	486(221)	465(184)
Solvent/Coal Ratio	1.82	1.97	1.92	1.87	1.99	1.93	1.91	1.83	1.90
LHSV, Hr <sup>-1</sup>	1.38	1.37	1.38	1.48	1.41	1.40	1.40	1.42	1.42
GHSV, Hr <sup>-1</sup>	321	320	320	309	354	358	332	340	325
Coal Rate, lbs/hr/CF	34.1	32.4	33.0	33.9	32.5	33.0	33.0	35.0	34.0
Gas Rate, SCF/lb Coal	9.4	9.9	9.7	9.1	10.9	10.8	10.1	9.7	9.6
Gas Consumed, SCF/lb Coal	2.0	1.0	3.7	1.5	2.9	3.6	4.3	3.2	2.4
Mol% H <sub>2</sub> in Gas Consumed	33.8	-48.7*	59.1	12.8	40.4	55.0	35.6	38.1	29.0
Yields, Wt % MAF Coal									
Net Gas	36.6	38.3	23.6	21.8	38.2	36.7	28.4	22.3	30.6
Net Oil	49.6	49.6	58.6	62.0	58.8	61.6	70.4	75.7	63.5
(Dist Oil)	(9.0)	(13.7)	(-0.1)	(3.7)	(17.7)	(22.6)	(21.3)	(14.3)	(15.6)
(SRL)	(40.6)	(35.9)	(58.7)	(58.3)	(41.1)	(39.0)	(49.1)	(61.4)	(47.9)
Net H <sub>2</sub> O & Ash	-2.0	-1.9	0.7	-0.8	-5.8	-6.7	-8.1	-6.5	-5.4
Unconverted MAF Coal	15.8	14.0	17.1	17.0	8.8	8.4	9.3	8.5	11.3
Solvent Recycle, %									
Actual	89.1	92.3	93.1	91.6	101.0	92.7	100.2	98.5	92.6
Potential (Calc)	103.0	104.2	100.0	101.2	105.4	107.2	107.0	104.8	105.0
Potential (Excluding Lt Oil)	94.3	92.8	91.9	89.5	95.6	94.7	95.7	96.7	90.7
Material Balance, %	98.5	98.7	99.9	99.2	96.7	96.7	97.9	96.0	94.7
Conditions									
Temperatures, °F									
Slurry Preheater Outlet	746	751	747	741	726	721	729	738	737
Dissolver Inlet	735	736	746	739	711	714	710	718	726
R-1A 3 ft	778	776	752	739	NIU	NIU	777	699	752(3 ft)
R-1A 15 ft	820	822	808	798	NIU	NIU	785	787	799(7 ft)
R-1B 3 ft	NIU	NIU	NIU	NIU	747	745	NIU	NIU	802(11 ft)
R-1B 15 ft	NIU	NIU	NIU	NIU	832	829	NIU	NIU	810(15 ft)
Dissolver Outlet	817	812	813	803	824	828	792	781	809
Flash Preheat	630	639	644	641	643	646	656	654	644
Flash Vapor	512	505	503	496	509	505	496	492	502
Pressures									
Dissolver, psig	2460	2460	2450	2450	2460	2460	2450	2450	2460
Inter, Sep., psig	250	250	250	250	238	240	240	240	245
Vacuum Flash, Torr	14	14	15	15	14	14	14	14	14
SLS System in Use?	No								
Mole Percent H <sub>2</sub> in Feed Gas	54.0	55.2	57.4	50.1	45.2	45.2	48.3	53.4	51.1
Mole Percent CO in Feed Gas	31.6	29.6	33.4	41.6	36.7	38.7	43.9	40.0	36.9
CO <sub>2</sub> Yield, Wt % MAF Coal	37.8	42.7	37.9	33.3	46.9	44.6	54.1	41.8	41.0
C <sub>1</sub> -C <sub>3</sub> Yield, Wt % MAF Coal	14.7	12.7	5.1	4.6	12.4	11.9	7.4	4.3	10.5
Gas Consumed (H <sub>2</sub> Equiv), Wt % MAF Coal	1.71	0.87	3.18	1.32	2.55	3.10	3.66	2.74	2.12

\*Negative value indicates a net hydrogen production.

One reactor was used with nominal process conditions of 820-830°F maximum temperature of liquefaction at 2500 psig dissolver operating pressure. Hourly space velocities of liquid and gas were 1.41 and 301, respectively. All recoverable organic distillates with atmospheric boiling points above about 400°F were recycled for use as solvent. The molar ratio of hydrogen to carbon monoxide was maintained at 1 and product gases were not recycled. The solids-liquid separation unit was operated during the later part of the run.

Four yield periods were completed, M-33A through M-33D, during which 83 hours of balanced operation was achieved. Material balances of from 96.8 to 99.5 percent were adjusted to 100 percent closure by compensating for known errors followed by normalizing to 100 percent recovery. Conversion of MAF lignite to gas, oil and SRL averaged 91.1 percent for the four yield periods. Consumption of reducing gases was 2.4 SCF per pound of as-charged lignite. Actual recovery of solvent for recycle averaged 92.2 percent while the calculated potential recovery was 101.3 percent. Average of SRL yields was 57.4 weight percent while yield of net organic liquids averaged 62.5 weight percent of the MAF lignite charged. These results indicate the Gascoyne lignite to be one of the more reactive of the lignite samples tested.

The liquids-solids separation unit was operated during yield period M-33C. Results were favorable with unconverted coal and ash concentrations in the vacuum bottoms product (SRL) being reduced to 0 to 0.2 weight percent, respectively.

Operating problems during the run included oil-water separation, plugging of the F-1 bottoms leg, failure of gaskets and check valves in pumps P-5 and P-11A of the deashing unit, and difficulty in removing accumulated solids from the solids precipitation tower.

Oil-water separation was not always effective and continuous monitoring of the effluent streams was required. Some of the difficulty in separation was caused by the partial miscibility of the oil-water phases and by apparent changes in oil density during the run. Variation in density of the oil phase affected the position of the oil-water interface in the separation vessel. A low interface position results in oil withdrawal in the waste water underflow, and a high position causes water to be contained in the oil overflow.

Plugging of the F-1 vacuum bottoms discharge line occurred several times. Most of the difficulty was caused by the temperature control of the heating elements in the line tracing. Too

high a temperature promotes coking while too low a temperature allows product solidification. Fluctuations in the melting point (250-450°F) of the vacuum bottoms additionally complicate temperature control. The problems of changes in oil density and in melting point of the vacuum bottoms were not unique to liquefaction of Gascoyne lignite. Similar problems had been encountered in use of Zap lignite.

Failure of the gasket in the toluene-slurry circulating pump P-5 and plugging of the F-0 vacuum bottoms discharge pump P-11A initially prevented integration of the liquid-solids separation system with the liquefaction section of the PDU. After repairs, the deashing unit was brought on stream. Following 28 hours of operation, the collar connecting the valve stem on the V-8 bottoms withdrawal valve and the actuator was loosened and became misaligned so that the actuator could not operate the valve. Before the actuator was reconnected to the valve, the line had plugged so that the deashing operations were stopped. However, the operation of the liquefaction section continued until the scheduled shut-down.

### 3. Run L-1

A series of three runs, each scheduled for 28 days of continuous operation, was planned for the PDU with the general objectives of testing plant performance for longer periods of operation on lignite, determining the effects of solvent recycle on liquefaction yield, and testing the effects of off-gas cleaning on the process. Additionally, the solids-liquids separation unit was to operate intermittently to produce a quantity of low-ash content SRL.

Run L-1, the first in the series, used normal process conditions which were thought to be optimum for minimizing production of gases and maximizing yields of SRL. Lignite from North American Coal Company's mine near Zap, ND was liquefied with a nominal maximum reactor temperature of 820-840°F at a pressure of 2500 psig. Charge rates of lignite and solvent were at the design capacity. One reactor was used and all recoverable organic distillates with boiling points above about 400°F were recycled. An equimolar mixture of hydrogen and carbon monoxide was used at a total feed rate of about 9.4 SCF per lb of as-charged lignite. The deashing section was operated at 300 psig and 450°F using toluene as the solvent. Toluene to slurry ratio was approximately four to one by volume.

Nine yield periods, each of a nominal 12 hours duration, were completed. Quantitative material balances were made for each period.

Elemental balances were made for two of the periods. Actual material balance closures were from 98.1 to 101.3 percent and were normalized to 100 percent recovery. A forced carbon balance was necessary in yield period L-1E and was made by adjusting the oil-water ratio of the waste water stream. V-8 bottoms compositions were calculated for yield periods L-1J and L-1K, which involved deashing, by making material balances around the deashing unit assuming average ash loss obtained when the deashing unit was not in use.

Conversion of MAF lignite to gas, oil and SRL was high, averaging 92.2 percent with a range from 88 to 99.2 weight percent. In the first yield period, pyridine soluble content of the F-1 vacuum bottoms was unusually high. Such high conversion was not expected, and it is believed that the conversions over 93 percent are not representative of typical results for solvent refining of lignite. Net gas yields averaged 31 weight percent of the MAF lignite charged and were close to the expected yields. The average net hydrocarbon liquid yield of 66 weight percent is considered typical. The hydrocarbon liquids were 20 percent distillable oil and 80 percent SRL. On a hydrogen equivalent basis, consumption of reducing gases was 2.0 weight percent of the MAF lignite or 2.35 SCF per lb of as-charged lignite.

Three of the nine yield periods were completed with the deashing system in operation. The ash content of the F-1 vacuum bottoms varied from 0.9 to 6.4 percent while the unconverted lignite content ranged from 0.3 to 2.9 weight percent.

Actual solvent recovery for recycle averaged about 90 percent for the nine yield periods. The longest period of operation without fresh solvent make-up was 120 hours which is approximately 24 turnovers of solvent inventory.

Run L-1 was scheduled for 672 hours of continuous operation of which 652 hours were to be devoted to liquefaction of lignite. Lignite was actually charged for 460.5 hours which was about 75 percent of the actual operating time. Approximately 11.4 tons of lignite was processed at an average feed rate of 49.5 lb/hr.

Operating problems exclusive of equipment malfunctions were in the three categories of F-1 vacuum bottoms withdrawal, solids build-up in the reactor and process lines, and solvent recovery. Product solidification in the vacuum-flash leg on two occasions was caused by a malfunction in the heat tracing tapes resulting in nonuniform heating. This can be avoided by careful control of temperatures provided the melting point of the product remains below 450°F. Solids also collected on the walls of the bottom

drawoff leg and in the vessel because of localized coking and adhesion to the walls of a thick sand-like material discharged from the reactor.

About halfway through the run, and after Reactor R-1B had been about 76 hours on lignite, the pressure within the reactor began to rise slowly, and the pressure drop between the reactor outlet and the high pressure flash separator increased to between 300-400 psi indicating solids buildup in the 5/16-inch ID tubing. Attempts to clear the line by flushing with solvent were not successful and operations were continued in spite of the pressure drop. After 85 additional hours on lignite, the line plugged and operations were switched to Reactor R-1A which was utilized for the remainder of the run. Upon disassembly of Reactor R-1A after the run, it was found that this reactor was also partially plugged with material in a sort of long pitch spiral; the thickness of the plug was up to 2 inch in the 3-5/8 inch ID reactor. The decrease in reactor volume because of buildup and the corresponding decrease in residence time caused a reduced conversion resulting in a lower reactor temperature. The lower conversion may also have caused the higher melting point of the vacuum bottoms observed near the end of the run. The air cooler tubing from the top of the reactor also had significant reduction in effective volume due to deposits. Lignite was processed for a total of 201 hours in Reactor R-1A and for a total of 259 hours in Reactor R-1B. The longest continuous periods of operation without interruptions in the lignite feed were 136 hours for Reactor R-1A and 134 hours for Reactor R-1B.

Solvent recovery data indicated that for the entire run about 4 percent more organic liquid was generated than charged, but in the course of the run an average of 90 percent was recycled. Loss of organic liquid (oil) occurred in the oil-water separation system, in the light ends column and in the F-1 bottoms product.

#### 4. Run L-2

The second of the three scheduled extended runs used nominal run conditions similar to those employed for L-1 of 820-830°F maximum reaction temperature, 2500 psig operating pressure, and liquid and gas hourly space velocities of 1.43 and 336, respectively. The recovered organic distillates boiling above about 350°F were recycled. In addition to the objective of Run L-1 of evaluating plant operability during extended operation using continuous liquefaction recycle, the effects of off-gas clean-up and recycle on liquefaction yields were to be determined. One reactor volume was used throughout the run.

Eight yield periods were established. Quantitative material balances were made for all yield periods and elemental balances done for six of the nine periods including an overall yield period of 441.4 hours. Material balance closures varied from 94.7 percent for the overall balance to an average of 98 percent for the eight standard yield periods. For comparison purposes the 12-hour yield periods were adjusted and normalized to 100 percent recovery. Adjustments in the calculations for three yield periods and the overall balance are discussed in detail in Appendix D.

The net gas yield was 30.6 weight percent of the MAF lignite charged and that of net hydrocarbon liquids, 63.5 percent. Distillable oil was 24.6 percent of the total organic liquid yield while SRL comprised the remaining 75.4 percent. Conversion of MAF lignite to oil, gas and SRL varied from 83 to 91.5 percent while overall conversion for the entire run was 88.7 percent. Actual recovery of solvent for recycle during processing was 92.6 percent. The potential solvent recovery on a total oil basis was calculated to be 104 to 105 percent. On a light-oil free basis (about 520°F plus boiling point material) solvent recovery was 90 to 94 percent. Consumption of reducing gases on a hydrogen equivalent basis was 2.1 weight percent of the MAF lignite or 4 SCF per pound of MAF lignite charged. Operating with gas recycle presented no problems and approximately the same net yields were obtained as when operating with once-through gas. Lignite was processed approximately 75 percent of the actual operating time or 54 percent of the total scheduled time. Nearly 11 tons of lignite were processed at an average rate of 48.6 lbs/hr.

The run was initially delayed because of plugging in some process lines believed clear after Run L-1. After processing started, a solid state contactor in the heating tape circuit for the F-1 vacuum-bottoms draw-off leg failed closed allowing over-heating of the bottoms to coking temperature. Leakage also developed in the S-1 high-pressure slurry-let-down valves. Correction of these and other minor problems accounted for the first 155 hours of the scheduled 672. To compensate for the lost time, planned run time was increased to 816 hours. After being at temperature for approximately 30 hours, problems developed with the slurry charge pumps which had worked well pumping solvent, but would not pump the lignite-solvent slurry. The difficulty is believed to be caused by the presence of larger size material in the pulverized lignite. Comparison of sieve analysis for the material charged during Run L-2 when pumping problems existed to those of the M-Series when no difficulty was encountered indicated that nearly 22 percent of the pulverized lignite was larger than 65 US mesh for L-2 and only 0.4 percent for the M-Series. The particle size

distribution for L-2 indicated significantly larger material which interfered with proper sealing of the slurry pump check valves. When a new pulverizer screen was installed and a finer feed material prepared, the pumps performed satisfactorily.

The problem with solids build-up in the reactor, noted in Run L-1, was also encountered in L-2. After 220 hours of processing using Reactor R-1A, the melting point of F-1 vacuum bottoms had increased to approximately 450°F, and operations were switched to dissolver R-1B. The effects of a clean reactor were quickly apparent in reduced melting temperature of the vacuum bottoms of less than 350°F, improved operation of the vacuum bottoms discharge system, and increased conversion. Reactor R-1A was cooled by flushing with solvent, disassembled and cleaned of solids. Collected solids amounted to about one third of the reactor volume.

The system continued to operate smoothly for about 70 hours until the back pressure control valve plugged causing a major upset in the liquefaction section which resulted in a forced shutdown. After 40 hours spent to clear or replace plugged lines, the unit was restarted and processing resumed when operating pressure and temperature were reached. For an additional 110 hours, smooth operation was achieved, but then plugging in the vacuum-flash-drum F-1 and its bottoms discharge line resulted in slurry overflow of the vacuum flash tower, plugging of the overhead condenser, the condensate accumulator S-7, the line from S-7 to the condensate bottoms pump, the pump and the line to the solvent accumulator A-5A. The run was terminated and 94 hours were spent in complete disassembly of the vacuum-flash-solvent recovery system, cleaning and reassembly.

## 5. Discussion of Results

### a. General

A total of 980.5 hours were completed in processing lignite in the Process Development Unit with 897.5 hours being achieved in two extended runs. High average conversion of lignite to gas, oil and SRL was achieved in the last scheduled short run investigating effects of lignite source; Gascoyne lignite was liquefied for 83 hours at the highest conversion of any lignite processed up to that time. While the PDU could be operated smoothly at high yields with solvent and gas recycle, mechanical and operating problems persisted. The major operating problems were related to solids buildup in the reactors and to oil-water phase separations. Correlations and observations of the liquefaction operations are discussed in the following.

b. Source of Lignite

Lignite from three different North Dakota mines have been liquefied in the PDU under similar process conditions. One, from the Zap Mine of the North American Coal Co. near Zap, ND in Mercer County, has been used as a "standard" lignite in most runs. The second lignite was from the Larson Mine of Baukol-Noonan, Inc. near Larson, ND in Burke County, and third, from the Gascoyne Mine of the Knife River Coal Mining Co. near Gascoyne, ND in Bowman County. Nominal process conditions were 825°F maximum reactor temperature, 2500 psig reactor pressure and hourly space velocities of liquid and gas, 1.4 and 280, respectively. Reducing gases were equimolar in hydrogen and carbon monoxide. Comparisons are made graphically and summary tables presented in Appendix B. Major results from the average of the first two yield periods of comparable runs are summarized in the following:

Lignite	Zap Average (M-29)	Larson Average (M-32)	Gascoyne Average (M-33)
Yields, Wt%			
MAF Lignite			
Net Gas	36	33	37
Light Oil	13	-3	-1
SRL	46	58	63
Conversion, Wt%			
MAF Lignite	90	80	93
Reducing Gas Consumption, SCF/lb lignite			
	3.1	1.8	2.6
Solvent Recovery possible %			
	104	99	100

The gross yield data indicate significant differences in response to liquefaction depending on the source of lignite. Larson lignite appears to be the least reactive for the process conditions selected with an average overall conversion of 81 percent while the Gascoyne lignite is most reactive with an indicated conversion of 93 percent. Total yield of liquids and gas were also the highest using Gascoyne lignite and the lowest with the Larson. However, separation of the net organic liquids into distillable and SRL components indicates that Zap lignite had the highest yield of the distillable fraction (light oil). Both Larson and Gascoyne lignites actually exhibited a net loss in

distillable oil because of loss of more solvent boiling range material by cracking, polymerization, or condensation than is produced from the lignite. The highest overall solvent production was with the Zap lignite. The Larson and Gascoyne lignites showed a slight net loss or an essential balance of solvent, respectively.

A comparison of yields per unit conversion of MAF lignite for the same averaged yield periods is given in the following tabulation:

Lignite	Zap	Larson	Gascoyne
Average ratio of yield to total conversion			
Net Gas	0.402	0.409	0.396
Net Liquid	0.658	0.688	0.668
Net Distillable Oil	0.145	-0.038	-0.010
Net SRL	0.513	0.726	0.678

Per unit of lignitic matter converted, the three lignites exhibit similar distribution to liquid and gaseous components. However, more of the Zap lignite was converted to lower molecular weight liquids as shown by the highest distillable oil yield, and lowest yield of SRL. The Gascoyne and Larson lignites produced more SRL but results in lower yields of distillable oils and losses of solvent.

The liquefaction tests indicate that lignites do respond differently although the lignites are from generally the same geological age and formation. Gascoyne lignite appears to be the most responsive to liquefaction, Zap lignite responds slightly less, and the Larson lignite the least active. Test conditions were those believed to be nearly optimum for Zap lignite. No attempt has been made to determine optimum conditions for the Larson or Gascoyne lignites.

Except for variations in moisture and ash content, and some differences in ash composition, the lignites were similar as shown in the following selected typical analytical values:

Lignite	Zap	Larson	Gascoyne
Proximate analysis, Wt%, as charged			
Moisture	30.9	26.8	34.0
Fixed Carbon	25.4	24.1	26.3
Ash	6.0	5.5	8.9

Lignite	Zap	Larson	Gascoyne
Ultimate analysis, Wt%, dry			
Carbon	68.8	67.8	62.2
Hydrogen	4.1	4.5	4.1
Sulfur	0.7	0.4	1.4
Nitrogen	0.9	0.7	1.0
Ash	8.7	7.5	13.4
Oxygen (diff)	16.7	19.1	17.9
Ash Component, Wt% of ash			
SiO <sub>2</sub>	20.2	19.0	37.6
Al <sub>2</sub> O <sub>3</sub>	10.5	17.7	12.9
CaO	26.7	22.4	20.5
Na <sub>2</sub> O	6.7	14.3	4.1

The moisture and ash as well as fixed carbon contents followed the apparent order of indicated activity being highest for the Gascoyne lignite followed by the Zap lignite and lower for the Larson lignite. Except for the high SiO<sub>2</sub> content in the ash of the Gascoyne lignite, no gross differences between the lignites is apparent from the ash and dry ultimate analyses.

### c. Effect of Solvent Recycle on Liquefaction

A major objective of the extended runs in regards to process effects was to determine if there would be any progressive changes in product yields or distribution because of solvent recycle. The effects of extended periods of solvent recycle were more apparent during Run L-2 than during Run L-1 because of improved and longer periods of operation without addition of make-up solvent. The approximate number of solvent cycles through the reactor was estimated at the middle of each yield period for Run L-2 and net yields for each data period were plotted depending on the number of solvent passes. The graphs are presented in Appendix D, Figure 1. Generally, total conversion is little influenced by the number of solvent cycles being fairly constant at about 88 percent of the MAF lignite despite a somewhat reduced reaction temperature.

In Run M-29, data had indicated an increase in total conversion until about eight recycles of solvent, after which conversion remained nearly constant. Previous data have indicated that in the range of operational temperature, a temperature reduction decreases total conversion. Thus if it had been possible to control the reaction temperature nearer the desired level, an improved conversion could have been realized. Although total conversion remained essentially constant, increased total net liquid yields occur at the expense of decreased gas yields as the liquefaction solvent becomes more lignite derived. Again this relationship is also temperature dependent. Water consumption by reaction also seems independent of the number of cycles.

With increasing number of cycles for the solvent, and with the decrease in reaction temperature, the net SRL yield increased while the net distillable oil yield decreased (See Figure 2, Appendix D) being less than 15 percent of the MAF lignite after 18 cycles. If this trend is the result of solvent recycle rather than lowered temperature and continued, production of coal derived solvent might be reduced below that required for solvent balance.

During Run L-2, the feed solvent was monitored by infrared spectroscopy to determine variations in the aromatic-to-aliphatic carbon ratio, called the IR ratio, depending on hours of operation (number of solvent recycles). Sulfur concentration of solvent was also measured. (See Figures 3 and 4, Appendix D.) Aromaticity of the solvent, as indicated by the infrared ratio, increased with time of operation for the first 150 hours of operation after start-up which was equivalent to about 11 solvent cycles. After this time, the infrared ratio was essentially constant indicating an approach to equilibrium between solvent charged and solvent produced. Sulfur content decreased with time of operation from nearly 1.5 percent to about 0.5 percent. Batch autoclave tests had indicated approximately 0.3 percent for the sulfur content of lignite derived solvent. With a longer test period the sulfur concentration should become constant at some equilibrium value, perhaps slightly higher than that found in the batch autoclave tests.

#### d. Effect of Solids Accumulation in Reactors

A major unresolved problem in maintaining continuous long term operation of the PDU is the accumulation of solids in the reactor. With the present dissolver design featuring upflow of slurry at low space velocities, unreacted lignitic material and ash tend to agglomerate and are not removed with the slurry. Not only do the accumulated solids reduce the available reaction volume and consequently the slurry residence time, but at intervals some of the solids are discharged and plug the downstream lines. The problem is compounded because of the reduced residence time which results in lowered production of liquids in the solvent boiling range and an increase in the melting point of the vacuum bottoms. The higher melting point causes solidification of the SRL and plugging in subsequent processing resulting in process upsets and often in shutdown of operations. Major modifications in reactor design seem necessary to prevent the accumulation of solids.

The longest period of operation using one reactor, 220 hours, was accomplished during Run L-2 using Reactor R-1A. Shutdown in operations was required because the increase in the melting point of the F-1 bottoms presented many operating problems. After cooling, the reactor was disassembled and 43 pounds of solids were removed

by drilling. Samples were taken at various elevations in the reactor and analyzed for ash and pyridine insoluble contents with the following results:

Height from Reactor Base, ft	Ash, Wt%	Pyridine Insoluble, Wt%
Bottom	28.2	43.9
3	21.5	62.7
6	19.1	69.7
9	18.1	73.5
12	15.9	73.7

Typically, ash content of the deposits decreased with height, while the pyridine insolubles increased. Higher ash content near the bottom indicate that the more reacted residue from liquefaction being heavier and perhaps more agglomerated, tends to settle against the upward flow of slurry. The increase in pyridine insolubles is indicative of coking of SRL material at the higher temperatures.

Comparison of the residue in the reactor remaining after 48 hours and after 220 hours of operation indicated the same general trend with reactor height in ash content and pyridine insolubles (See Appendix D), although the ash and pyridine insolubles contents were higher after 220 hours than after 48.

It appears that the total solids in the reactor after initial buildup remains fairly constant with time at about 29 lb/cu ft of reactor volume. Also it is not clear what would happen in the present reactors with longer periods of lignite processing. Under the present conditions, the accumulation is sufficient to decrease conversion and change distribution of products significantly after 220 hours of processing.

#### e. Effect of Gas Recycle

In Run L-2, the product gas stream was washed with caustic to remove carbon dioxide and hydrogen sulfide. Approximately 75 percent of the cleaned gas was recycled to the process and the remainder was vented to the thermal oxidizer to reduce accumulation of other gases such as methane in the recycle gas stream. Makeup gas was added to the recycle stream as required. This portion of the pilot plant system operated without difficulty.

The effect, if any, of gas recycle on liquefaction was limited as indicated by the comparisons on the following page of yield data for the average of Run L-1, without gas recycle, with the averages from Run L-2, with gas recycle.

	<u>Without Gas Recycle</u>	<u>With Gas Recycle</u>
Average Temp., °F	822	810
Yields, Wt%		
MAF Lignite		
Net Gas	31.3	30.7
Net Liquid	66.1	60.8
Net Water & Ash	-5.2	-3.9
Unconverted Lignite	7.8	12.4
Possible solvent for Recycle, %	104.0	104.1

For these average data obtained under somewhat similar process conditions, the effects of solvent reuse should be approximately the same and differences could be attributable to gas recycle or to changes in other variables. There are some differences in conversions and liquid yields but these are of the range to be expected because of the differences in average temperatures. Consequently, the results appear to be equivalent.

f. Deashing of Vacuum Bottoms (SRL)

Three yield periods during Run L-1 were completed with the toluene extraction-settling separation system integrated with the liquefaction operations. In addition to mechanical and plugging problems within the deashing system itself, operational problems in the liquefaction system were also reflected in adverse operation of the deashing unit, and resulted in erratic separation. Separation was achieved with ash contents of the product being as low as 0.9 percent while the unconverted lignite content was as low as 0.3 percent. The ash content of the initial vacuum bottoms is from 10 to 12 percent and the bottoms also contain up to 10 percent unconverted lignite as determined by the pyridine solubility test.

While the extraction deashing method is attractive, more work has to be done in modification of the present system and to insure that the vacuum bottoms feed to deashing can be handled by the pumping system.

g. Solvent Recovery

With the Zap lignite, sufficient possible solvent is generated from the lignite to sustain the process. However, because of recovery problems, sampling, and decrease in distillable material with solids buildup, solvent is lost, and makeup solvent must be added. During Run L-1, an average of 4 percent more organic liquid

was generated than charged, although throughout the run an average of only 90 percent was recovered and recycled.

The 14 percent average loss occurred mainly in three areas: with the F-1 vacuum bottoms, with the waste water and light oil streams, and in operation of the small light ends column. Most of the losses could be remedied in larger scale operations.

#### h. PDU Operability

The liquefaction unit was operated on lignite for approximately 900 hours, most of which was accumulated during the two extended tests. Although lignite was processed for about 75 percent of the actual operating time, the objective of long term smooth operability of the PDU was not completely achieved. Failure of equipment such as that of heat tracing lines contributed to down time. Any malfunction causing process upsets compounded operating problems as the reacted slurry or vacuum bottoms would solidify on loss of temperature, would coke if temperatures were too high resulting in plugged lines and process vessels, or otherwise would cause trouble in transfer of material. The vacuum bottoms withdrawal system was particularly troubled by product solidification and buildup as was the high pressure piping. The separation system for light oil and water operated with variable efficiency, and often carryover of oil was as high as 25 to 30 percent of the water. The small light ends column, because of unfavorable area-volume relationship, had high heat loss which made it very sensitive to changes in cooling water rates to the partial condenser, and at times excessive reflux condensation caused column flooding.

The major non-correctable problem hindering operability was solid accumulation in the reactor. Such accumulation is not unique to liquefaction of lignite as similar problems have been encountered in processes using higher rank coal and upflow dissolvers. Accumulation of solids in the reactor caused difficulties in two ways. With time, the solids tended to deposit on the walls of the dissolver and coke into a hard mass which plugged the unit preventing flow of the lignite solvent slurry. Retention of solids reduced the effective volume for liquefaction and decreased residence time. This resulted in decreased overall conversion of the lignite and a higher melting point vacuum bottoms. The higher melting point material was more difficult to pump and to separate from the solvent. The higher melting point also contributed to solidification in piping and process equipment downstream from the reactors.

## B. PDU MAINTENANCE AND CONSTRUCTION

### 1. General

With two 28-day runs scheduled, nearly all effort was directed towards maintaining the operability of the unit. Maintaining clean work areas and sound safety practices were stressed during the reporting period. Some activities are discussed in the following subsections, and additional details are available in the monthly reports.

### 2. Area 00: Buildings and Utilities

The partition to isolate the control-instrumentation area of PDU from the operational areas was completed. A supplementary heating and ventilating system to service the control room is being installed.

### 3. Area 01A: Coal Preparation and Storage

A small concrete apron was installed adjacent to the Invertabin storage pad to facilitate footing for the lift truck to the storage area during inclement weather.

### 4. Area 01B: Slurry Preparation and Pumping

Before the first scheduled long run the check valve assemblies on the two Hills-McCanna slurry-charge pumps were rebuilt with new stainless steel seats and ceramic balls. The removed seats and balls showed some evidence of wear or erosion. All equipment and lines in this section were cleaned and washed with a heavy aromatic solvent.

### 5. Area 02: Slurry Preheating, Dissolving, and Gas Separation

The bottom closure on dissolver R-1B was removed, the dissolver was cleaned and the corrosion test coupons installed prior to M-33 were removed. Another set of test coupons was installed for the start of Run L-1. Some 316 stainless steel tubing at the outlet of reactor R-1B was replaced with Incoloy 800 tubing before Run M-33. The four slurry letdown valves constituting the primary and auxiliary captive volume letdown systems were cleaned and checked.

### 6. Area 03: Solids-Liquid Separation

The Teflon seats in both the solids-removal valve and the block valve above it were replaced with Rulon seats which should be more resistant to the severe operating conditions experienced. The valves were set so that the block valve remains open while

the dump valve cycles. The top valve will close automatically when electric power to the air solenoid valve is interrupted. The solids precipitation tower (V-8) was partially disassembled to allow removal of solids which accumulated during Run M-33 after failure of the solids removal valve.

#### 7. Area 04: Liquid Separation and Solvent Recycle

Two 100-gallon solvent storage tanks were installed on weigh cells and piped in series for use as solvent accumulator (A-5A) for Run L-1.

#### 8. Area 05: Gas Purification and Recycle

Equipment, sight glasses and control valves were cleaned.

### C. PROJECT LIGNITE LABORATORY

The major effort of the laboratory staff was to provide analytical support for PDU operations. Some special analytical work was done on distillations using ASTM methods D-86 and D-1160 for comparison with results obtained using the routine Project Lignite Laboratory (PLL) distillation procedure. Additionally, a Pensky-Martens closed-cup flash-pump test was performed on a light oil stream (S-8 bottoms from the PDU).

Data from the flash point test showed that the light oil had a low flash temperature of 100°F which indicated that extreme care must be taken with these highly volatile liquids.

The recycle solvent distillation data are presented graphically in Figure 1. Measured temperatures were adjusted to equivalent temperatures at atmospheric pressure (760 mm Hg) using API Procedure 5A1.13 which had been developed for use with petroleum hydrocarbon mixtures. Applicability of the correction to hydrocarbon liquids derived from lignite has not been established although the use of the procedure gave apparently reasonable corrections.

The adjusted vapor temperature scale is nominally cartesian while the recovered volume scale (abscissa) has probability divisions. The general shapes of all curves are similar. However, the data from the PLL distillation indicates that a significantly higher temperature is required to distill a given fraction of the recycle solvent. The discrepancy is more pronounced as the volume of overhead exceeds 50 percent. The tests at the higher vacuums (1.6 mm Hg and 5 mm Hg abs.) gave essentially the same results during the initial stages of distillation, but as the distillation continued, the recovery in the PLL distillation deviates more

FIGURE I  
 COMPARISON OF ASTM AND PLL DISTILLATIONS ADJUSTED TO  
 EQUIVALENT ATMOSPHERIC BOILING POINTS





FIGURE 2  
COMPARISON OF ASTM AND PLL DISTILLATIONS AT 1.6 TORR



and more from the three ASTM distillations.

Measured vapor temperatures for the two distillation procedures at the same pressure (1.6 mm Hg) as a function of volume distilled are illustrated in Figure 2 using the same plotting procedure as for Figure 1. The PLL distillation gives a lower total volume of distillate at any vapor temperature. Initially, both distillations are nearly the same, but the slope of the PLL distillation curve is greater. This indicates that the longer column used in the PLL method results in more effective fractionation. When 50 percent of the sample has been vaporized, the vapor temperature using the ASTM D-1160 test is 329°F compared to 363°F for the PLL distillation procedure.

## IV. CONCLUSIONS

### A. PDU OPERATIONS

1. During almost 800 hours of operation in liquefaction of Zap lignite in two runs, relatively high conversions could be maintained during the extended tests with potential solvent recovery of over 100 percent, although actual solvent recovery was about 90 percent.

2. Gascoyne lignite was found to give the highest conversions of any lignite yet tested in the PDU up to that time with high yields of SRL but relatively lower yields of distillable oils, including solvent-type material.

3. Product gas cleanup and recycle were accomplished without undue difficulty and no significant differences were apparent in liquefaction characteristics when compared to similar tests without recycle.

4. The solids-liquid separation unit using toluene extraction-settling was operated for three yield periods with significant separation achieved, although ash content of the SRL was variable and higher than desired.

5. Buildup of solids in the dissolver was found to affect operability of the PDU. In addition to coking and deposition in the reactor, reduction in residence time resulted in a higher melting point product and subsequent solidification in downstream process vessels and piping.

### B. PDU MAINTENANCE AND CONSTRUCTION

Because of the scheduled long duration runs, maintenance activities were concentrated on repairs concerned with insuring operation of the unit, during which problems with pumps, valves and control equipment were the major mechanical difficulties encountered.

### C. PROJECT LIGNITE LABORATORY

Solvent distillations conducted by ASTM methods for comparison with the routine Project Lignite Laboratory (PLL) distillations indicated the PLL distillations to be somewhat more efficient.

## APPENDIX A

### STATEMENT OF WORK

#### Objective

The objective of this one year project is to obtain adequate data on which to base a decision regarding scale up at an existing facility, should it prove desirable. The data also will be available for new economic evaluations.

#### Tasks

The basic task involves operating the continuous unit processing 0.6 tons per day of lignite and providing support functions to acquire and analyze process data. These process data are required by ERDA in order to make future decisions concerning the desirability of scaling up the process in a larger existing facility for the production of solvent refined lignite. The same data will serve to guide any other development activities which may be required.

#### Task 1 - Operating of One-Half Ton Per Day Unit for Extended Runs

Under the existing project optimum conditions are being established for possible extended operations. An extended run is defined as covering periods of more than 1 week, preferably about 4 weeks (672 hours) of continuous operation. Such runs will establish the effects of continuing to recycle the lignite generated process solvent and demonstrate the extent of solvent balance achieved under the operating conditions which have been explored to date.

Three such runs conducted over a period of 6 months should be sufficient for this task. Because current operations are limited to a 5 day week, additional manpower will be required. Maximum use of overtime is suggested, due to the short term nature of this work, i.e., possibly 3 months total continuous operation during a period of 6 months. If adequate data is obtained in a short time from the extended runs, and if the ERDA technical project officer agrees, shorter runs may be conducted during this phase of the project, further evaluating construction materials and the effect of varying operating pressures and gas composition.

#### Task 2 - Operation of Gas Cleanup and Recycle Sections

If possible, this section will be operated as an integral part of the PDU on an extended run to determine makeup gas requirements and the effect of any impurities in the recycle gas. No major design or engineering changes will be introduced in this section.

#### Task 3 - Solid/Liquid Separation

The separation section will be operated as an integral

part of the PDU, producing a clean solvent refined lignite for characterization. A secondary task is to evaluate operation of the separation unit as designed. No major design or equipment changes will be introduced.

#### Task 4 - Corrosion Coupon Testing

After appropriate analysis and consultation, as required, the contractor will have a number of coupons of austenitic stainless steels pre-stressed and inserted in the PDU for corrosion testing. The steels to be tested will include selected types from those used in the SRC plants at Tacoma and Wilsonville: stainless steel types 304, 310, 316, and 347. The contractor will prepare a plan for this task explaining his selections of material, the method of pre-stressing and test-site locations. This corrosion coupon test plan will be submitted to ERDA for approval by the Technical Project Office prior to its implementation.

#### Task 5 - Determine Extent of Solids Accumulation in Dissolvers

The reactors (dissolvers) may accumulate mineral matter and unconverted coal during operation. The contractor will determine the composition of the solids and the rate at which solids are accumulated. The possible existence of a maximum concentration of solids at steady conditions, will also be explored.

#### Task 6 - Production of Clean Solvent Refined Lignite

The contractor will produce up to one ton of clean solvent refined lignite for shipment in drums to other ERDA contractors, as specified by the Technical Project Officer. This material will be evaluated by the appropriate contractors for various purposes including upgrading to chemical feedstocks, light liquid fuels, and use as a solid fuel. It is anticipated that half of the quantity produced will have a melting point higher than 340°F. Actual quantities and specifications for the product will be established during the contract by agreement between the ERDA Technical Project Officer and the contractor.

#### Task 7 - Data Collection and Analysis

This task continues to be significant. The contractor will provide material balances (over-all and for major streams and vessels), solvent balance, hydrogen consumption, product yields and product characteristics within 30 days of completion of a PDU run. Properties to be measured and reported for the solvent refined lignite and liquid products include:

1. Distillation Curve
2. Viscosity
3. Specific Gravity

4. Penetration or Melting Point of the Product  
(at temperatures not suitable for viscosity measurements)
5. Elemental Analysis (including chlorine)
6. Trace Elements
7. Asphaltene Content

Correlation studies will be made of the data obtained from runs to examine the effect of changing different process variables.

The corrosion coupon data will be analyzed as part of this task.

Yield structures and appropriate data summaries will be published in quarterly reports, and a final report will be prepared.

## APPENDIX B

### Process Development Unit Run M-33

June 20-24, 1977

Run M-33 was made to continue the investigation of the effects of coal variation on plant operability and liquefaction yields. Lignite mined by the Knife River Coal Mining Company near Gascoyne, North Dakota, was used. Gascoyne lignite differed from previous lignites tried in the PDU in that the ash and moisture contents were significantly higher at about 9 percent and 35 percent, respectively. Other significant differences are apparent from the ultimate analysis and X-ray fluorescence analysis of the ash shown in the table on the following page.

Nominal operating conditions in Run M-33 were 820-830°F maximum liquefaction temperature and 2500 psig dissolver operating pressure with liquid and gas hourly space velocities of 1.41 and 301, respectively. One reactor volume was used and all recoverable organic liquids boiling above about 350°F at one atmosphere were recycled. The feed gas contained equal volumes of hydrogen and carbon monoxide. Product gases were not recycled but were sampled, measured and then oxidized. The deashing unit was on stream during part of the run.

Numerous operating problems were encountered during the run, mainly with (1) oil-water separation, (2) plugging of the F-1 vacuum bottoms leg, (3) gaskets and check valves in pumps P-5 and P-11A of the deashing unit and (4) solids removal from the solids precipitation tower.

Oil-water separation proved difficult throughout the run with constant monitoring of effluent streams required. Substantial quantities of oil were lost with the waste water, partly because of partial miscibility of the two phases and partly because of fluctuating oil densities. Changes in oil density affected the position of the oil water interface within the separation vessel. Interface location is critical in the separation process as a low interface results in oil withdrawal with the waste water underflow while a high interface results in water leaving with the oil overflow. It should be noted that this problem is not unique to the processing of Gascoyne lignite as similar problems have been experienced when handling Zap lignite also.

Plugging of the F-1 vacuum bottoms outlet line occurred several times during the run and at least once required drilling to clear. Temperature control of the line tracing elements presents one of the main problems. Over heating promotes coking and under-heating results in product solidification. The sometimes widely fluctuating melting point (250-450°F) of the vacuum bottoms product further complicates temperature control problems. Again this is a problem not unique to Gascoyne lignite.

Analyses of  
North Dakota Lignites

Proximate Analysis, Wt %

Mine Location	Zap	Velva	Larson	Gascoyne
Moisture	30.91	29.58	26.85	34.03
Ash	6.04	5.91	5.48	8.87
Volatile Matter	37.65	42.45	43.56	30.76
Fixed Carbon	25.40	22.06	24.11	26.34
Total	100.00	100.00	100.00	100.00

Ultimate Analysis, Wt % (Dry Basis)

Mine Location	Zap	Velva	Larson	Gascoyne
Carbon	68.82	65.99	67.82	62.20
Hydrogen	4.10	4.23	4.49	4.15
Nitrogen	0.88	0.83	0.69	0.96
Oxygen (by diff)	16.72	20.22	19.06	17.86
Sulfur	0.74	0.34	0.45	1.38
Ash	8.74	8.39	7.49	13.45
Total	100.00	100.00	100.00	100.00

X-Ray Fluorescence Analysis of Ash, Wt %

Mine Location	Zap	Velva	Larson	Gascoyne
Loss on ignition @ 800°C	0.4	-	-	-
SiO <sub>2</sub>	20.2	28.4	19.0	37.6
Al <sub>2</sub> O <sub>3</sub>	10.5	14.1	17.7	12.9
Fe <sub>2</sub> O <sub>3</sub>	10.0	4.5	6.0	5.6
TiO <sub>2</sub>	0.5	0.5	0.4	0.8
P <sub>2</sub> O <sub>5</sub>	0.6	0.9	1.0	0.5
CaO	26.7	31.2	22.4	20.5
MgO	6.8	9.1	5.7	6.9
Na <sub>2</sub> O	6.7	1.8	14.3	4.1
K <sub>2</sub> O	0.4	0.6	0.4	0.3
SO <sub>2</sub>	17.2	8.9	13.1	10.8
Total	100.00	100.00	100.00	100.00

Gasket failure in the toluene-slurry circulating pump P-5 and check valve plugging in the F-0 vacuum bottoms removal pump, P-11A, delayed integration of the solids-liquid separation unit. After the gaskets were replaced and the check valves cleaned, the deashing unit was brought on stream and operated for approximately 26 hours. Yield period M-33C was started and completed during this period. At the end of M-33C, it was found that the collar connecting the V-8 bottoms withdrawal valve stem and the actuator had become loose and misaligned, with the result that movement of the actuator did not operate the valve. The bottoms line had already plugged before the actuator could be reconnected to the valve, and deashing operations were terminated. Liquefaction operations continued through another yield period to a scheduled and orderly shutdown 12 hours later.

Four yield periods were completed and two, M-33C and D, were selected for complete workup including elemental balances and oil phase ASTM D86 and D1160 distillations. The results of these workups along with the quantitative material balance data for yield periods M-33A and B are attached.

Material balance closure for the four yield periods varied from 96.8 to 99.5 percent. The various yield periods were adjusted to 100 percent recovery as follows. In data period M-33A, the one half of one percent error in material balance closure was corrected by increasing the F-1 vacuum bottoms rate. A partial plug had developed at the bottom of the draw off leg and while it was being cleared some F-1 vacuum bottoms sprayed onto the floor and was lost. A similar situation occurred during yield period M-33B with some of the vacuum bottoms material clinging to the walls of the drawoff leg. Consequently, the F-1 bottoms rate was increased so that the ratio of the F-1 vacuum bottoms to feed coal was comparable to that of yield period M-33A. This initially increased the material balance closure from 96.8 percent to 97.5 percent. The remaining loss was then normalized among all outgoing product streams.

In yield period M-33C, during which the deashing unit was on stream, material balance closure was low at 97 percent because the V-8 bottoms draw off line plugged and an indeterminate amount of solids accumulated in the bottom of the precipitation tower. Consequently, the material balance was adjusted to 100 percent recovery first by decreasing the V-9 overhead rate to maintain a constant inventory in the toluene accumulator and then by increasing the V-8 bottoms rate to provide mass balance closure. The V-8 bottoms composition was calculated by making a material balance around the deashing unit assuming that the level in the toluene accumulator remained constant but that the composition changed.

Material balance closure in yield period M-33D was 98.6 percent and was adjusted to 100 percent recovery by normalizing all outgoing

product streams because no particular sources of error were known.

A comparison of the four material balance periods after adjustment is shown on the following page.

Net gas yields averaged 36.8 and net organic liquid yields 62.5 weight percent of the MAF lignite charged. Net distillable oil yields averaged 5.4 weight percent of the MAF lignite fed while SRL yields averaged 57.1 weight percent.

Conversion of MAF lignite to gas, oil and SRL averaged 91.1 percent. Reducing gas consumption averaged 2.4 SCF per pound raw lignite charged.

Actual solvent recovery for recycle averaged 92.2 percent with a calculated possible recovery of 101.4 percent.

Results of the deashing operation during yield period M-33C were quite favorable with the unconverted coal and ash contents of the vacuum bottoms product reduced to 0 and 0.2 weight percent, respectively.

As mentioned earlier, Run M-33 was made to evaluate Gascoyne lignite as feed to the liquefaction process and to determine plant operability. A comparison of results with three different lignites in Runs M-29, M-32 and M-33 are tabulated on a following page. Conversion of MAF coal to gas, oil, and SRL averaged 80.4 weight percent when using Larson lignite (Run M-32) which is significantly lower than that obtained when using either Zap or Gascoyne lignite, and is apparently the result of lower reactivity of the lignite. The Gascoyne lignite seems to be the most reactive of the three coal varieties, yielding MAF lignite conversions of about 93 percent.

A graphical comparison of the results with the three lignites is attached. The highest conversion and gas and liquid yields are obtained with Gascoyne lignite and the lowest with Larson lignite. However, dividing the net organic liquid yield into its distillable oil and SRL components indicates that the Zap lignite provides higher yields of distillable oil, while both Larson and Gascoyne lignite show a net loss of distillable oil, because of the loss of more solvent range material by cracking and/or polymerization and condensation than is produced from the coal.

The graphs of solvent recovery indicate the highest overall solvent production (and also actual recycle) occurs with Zap lignite, and that both Larson and Gascoyne show slight net losses of solvent.

When the yields are calculated as fractions of the MAF coal converted, the following results are obtained:

Process Development Unit Run M-33

Yield Period	M-33A	M-33B	M-33C	M-33D	Average
No. of Reactors	1	1	1	1	1
LHSV	1.34	1.37	1.49	1.43	1.41
GHSV	289	301	301	306	299
Solvent/MAF Coal Ratio	4.08	3.84	3.54	3.95	3.85
H <sub>2</sub> /CO Mol Ratio	1.1	1.0	1.0	1.0	1.0
Temperatures, °F					
Preheater Outlet, E-1	762	752	741	749	751
Reactor 3 ft	768	762	765	768	766
Reactor 7 ft	799	794	799	804	799
Reactor 11 ft	797	790	802	806	799
Reactor 15 ft	822	815	822	828	822
Max. Reaction	822	815	822	828	822
Vacuum Flash Ovhd	513	513	515	523	516
Dissolver Pressure, Psig	2500	2500	2500	2500	2500
Solvent Recycle, %					
Actual	89.8	94.2	86.2	98.6	92.2
Possible	98.9	100.7	101.7	104.4	101.4
Yields, Wt % MAF Lignite					
Net Gas	39.9	35.2	34.1	39.1	36.8
Net Liquid	58.1	66.6	63.4	62.0	62.5
(Lt Oil)	(-4.6)	(2.8)	(6.0)	(17.6)	(5.4)
(SRC)	(62.7)	(63.8)	(57.4)	(44.4)	(57.1)
Net H <sub>2</sub> O and Ash	-5.6	-6.4	-9.3	-11.8	-8.2
Unconverted Coal	7.6	5.5	11.8	10.7	8.9
Overall Material Balance, %	99.5	96.8	97.0	98.6	98.0

Process Development Unit Runs M-29, 32 and 33





Run	M-29A & B Average B	M-29F & G Average A	M-32A & B Average B	M-33A & B Average B
Reactor				
Type of Lignite	Zap	Zap	Larson	Gascoyne
LHSV	1.38	1.41	1.43	1.36
GHSV	270	268	325	295
Solvent/MAF Coal Ratio	3.00	3.13	2.90	3.96
Percent H <sub>2</sub> in Feed Gas	48.0	49.8	52.9	51.0
Temperatures, °F				
Preheater Outlet, E-1	710	716	738	757
Maximum Reaction	836	826	824	818
Dissolver Pressure, Psig	2400	2450	2500	2500
Solvent Recycle, %				
Actual	92.4	95.2	87.6	92.0
Possible	105.1	100.8	98.8	99.8
Yields, Wt % MAF Lignite				
Net Gas	36.3	36.8	32.9	37.0
Net Liquid	62.0	58.3	55.3	62.4
(Lt Oil)	(15.6)	(2.9)	(-3.1)	(-0.9)
(SRL)	(46.4)	(55.4)	(58.4)	(63.3)
Net H <sub>2</sub> O and Ash	-8.8	-6.8	-7.8	-6.0
Unconverted Coal	10.5	11.7	19.6	6.6
Overall Material Balance, %	98.0	98.6	98.7	98.2
Conversion, Wt % MAF Coal	89.5	88.3	80.4	93.4
Reducing Gas Consumption, SCF/lb Coal	3.2	2.4	1.8	2.6

Lignite Variety	Larson	Gascoyne	Zap AB	Zap FG
<u>Net Gas Yield</u> Conversion	0.409	0.396	0.405	0.417
<u>Net Organic Liquid Yield</u> Conversion	0.688	0.668	0.693	0.660
<u>Net Distillable Oil Yield</u> Conversion	-0.038	-0.010	0.174	0.033
<u>Net SRL Yield</u> Conversion	0.726	0.678	0.519	0.627

For a given degree of MAF lignite conversion, the various lignites do not vary much in gas and organic liquid yields, but the Zap lignite produces the highest net distillable oil yield and consequently the lowest SRL yield. The Gascoyne and Larson lignites produce more SRL, but at the expense of solvent as indicated by the overall net loss of distillable liquids.


In summary then it appears that the Gascoyne lignite is the more reactive of the three lignites tested followed closely by Zap and then by Larson lignites. It should be noted; however, that Runs M-32 (Larson) and M-33 (Gascoyne) were made at conditions thought to be near optimum for Zap lignite. No attempts have been made yet to find the actual optimum conditions for Larson or Gascoyne lignites.

FIGURE 1 - YIELDS AND CONVERSION WITH THREE NORTH DAKOTA LIGNITES



NET YIELDS AND CONVERSION ARE WEIGHT PERCENT OF MAF COAL CHARGED

FIGURE 2-SOLVENT RECYCLE AND PRODUCT DISTRIBUTION WITH THREE NORTH DAKOTA LIGNITES



RUN CONDITIONS


RUN NO. M-33A

DATE MADE 6/21-22/77

TEMPERATURE °F		PRESSURE, psig
PREHEATER E-1		SEPARATORS S-1 and S-2
SAND BATH	773	2500
INLET	288	SEPARATOR S-3
OUTLET	762	300
DISSOLVERS		SEPARATORS S-4A and S-4B
R-1A (1)		60
(2)		VACUUM FLASH, F-1
(3)		15 Torr
(4)		LIGHT ENDS COLUMN, F-2
R-1B (1)	768	0
(2)	799	SOLVENT COLUMN, F-3
(3)	797	NIU
(4)	822	HEAVY ENDS COLUMN, F-4
REACTOR PRODUCT SEPARATORS		NIU
S-1	590	VACUUM FLASH, F-0
S-2	74	NIU
S-3	487	SETTLING TOWER, V-8
S-4A	80	NIU
S-4B	77	RECOVERY TOWER, V-7
PREHEATER E-11		NIU
DOWTHERM	670	
INLET	448	
OUTLET	629	
VACUUM FLASH F-1		
OVERHEAD VAPOR	513	
UPPER WALL	576	
LOWER WALL	679	
DOWNCOMER	458	
CONDENSATE		
ACCUMULATOR, S-7	82	
PREHEATER E-13		
DOWTHERM	511	
INLET	76	
OUTLET	340	
LIGHT ENDS COLUMN, F-2		
REBOILER	424	
LOWER SECTION	490	
FEED SECTION	322	
OVERHEAD	178	
S-8	83	
S-9	-	
SOLVENT COLUMN, F-3		
REBOILER	NIU	
LOWER SECTION		
FEED SECTION		
OVERHEAD		
HEAVY ENDS COLUMN, F-4		
REBOILER	NIU	
LOWER SECTION		
FEED SECTION		
OVERHEAD		
VACUUM FLASH, F-0		
OVERHEAD	NIU	
BOTTOMS		
PRECIPITATION TOWER, V-8		
ZONE (1)	NIU	
(2)		
(3)		
RECOVERY TOWER V-9		
REBOILER	NIU	
OVERHEAD		

Date of Run	Start	End	Run.No: M-33A
Time of Run	6/21/77	6/22/77	Units: lbs/hr. °F, psig
Length of Run	1430	0230	Prep. By: BCL & GGB
Hours on Coal at End of Y.P.	12	hours	Updated: 12/20/77
	23.0		

### MASS RATES AND RUN CONDITIONS



147.12 TOTAL

$\square$  OPEN  $\blacksquare$  CLOSED

TOTAL 147.12

Numbers in parentheses are not included in the totals.

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 F-1 Btms Increased  
 Revised: 12/20/77

Run No: M-33A  
 Date: 6/21-22/77  
 Time: 1430-0230

SUMMARY

Temperature: 762°F  
 Pressure: 2500 psig  
 LHSV: 1.34  
 GHSV: 288

lbs/hour

STREAM DESCRIPTION	Total In	Total Out	Net Yield	WT % MAF Lignite	
SAMPLE POINT					
Hydrogen - H <sub>2</sub>	1.14	1.04	-0.10		
Carbon Monoxide - CO	14.51	8.63	-5.88		
Carbon Dioxide - CO <sub>2</sub>		12.39	12.39		
Hydrogen Sulfide - H <sub>2</sub> S		0.32	0.32		
Methane - CH <sub>4</sub>		1.25	1.25	8.80	39.91
Ethane - C <sub>2</sub> H <sub>6</sub>		0.50	0.50		
Propane - C <sub>3</sub> H <sub>8</sub>		0.26	0.26		
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>		0.02	0.02		
Ammonia - NH <sub>3</sub>		0.04	0.04		
Light Oil - (0-100°C @ 1.6 Torr)	5.08	7.03	1.95	12.80	58.05
Solvent - (100-230°C @ 1.6 Torr)	67.86	75.13	7.27		
Heavy Oil - (230-255°C @ 1.6 Torr)	17.06	6.81	-10.25		
SRL		13.83	13.83		
Coal (MAF)	22.05	1.68	-20.37		-92.38
Ash	3.86	3.48	-0.38		-1.72
Water	15.56	14.71	-0.85		-3.86
Phenol					
TOTAL	147.12	147.12	-0-		

ELEMENTAL	Quantitative				
	Total In	Total Out	Net Yield	WT % MAF Lignite	
Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
TOTAL					

PROJECT LIGNITE  
 ADJUSTED & MEASURED MATERIAL BALANCE  
 Updated: 12/20/77

Run No: M-33A  
 Date: 6/21-22/77  
 Time: 1430-0230

MATERIAL IN

Temperature: 762°F  
 Pressure: 2500 psig  
 LHSV: 1.34  
 GHSV: 289

lbs/hour

STREAM DESCRIPTION	Feed Gas	Lignite	Feed Solvent		Total In
	Sx-21	Sx-1	Sx-14		
Hydrogen - H <sub>2</sub>	1.14				1.14
Carbon Monoxide - CO	14.51				14.51
Carbon Dioxide - CO <sub>2</sub>					
Hydrogen Sulfide - H <sub>2</sub> S					
Methane - CH <sub>4</sub>					
Ethane - C <sub>2</sub> H <sub>6</sub>					
Propane - C <sub>3</sub> H <sub>8</sub>					
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					
Ammonia - NH <sub>3</sub>					
Light Oil - (0-100°C @ 1.6 Torr)			5.08		5.08
Solvent - (100-230°C @ 1.6 Torr)			67.86		67.86
Heavy Oil - (230-255°C @ 1.6 Torr)			17.06		17.06
SRL					
Coal (MAF)		22.05			22.05
Ash		3.86			3.86
Water		15.32	0.24		15.56
Phenol					
TOTAL	15.65	41.23	90.24		147.12

ELEMENTAL	Quantitative					Total
	Feed Gas	Lignite	Feed Solvent			
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE  
F-1 Btms Increased

Updated: 12/20/77

Run No: M-33A  
Date: 6/21-22/77  
Time: 1430-0230

Temperature: 762°F  
Pressure: 2500 psig  
LHSV: 1.34  
GHSV: 289

MATERIAL OUT  
lbs/hour

STREAM DESCRIPTION	Product Gas	MATERIAL OUT (lbs/hour)				
		S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exh.
SAMPLE POINT	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	0.97	0.06				0.01
Carbon Monoxide - CO	8.02	0.55				0.06
Carbon Dioxide - CO <sub>2</sub>	10.23	1.86				0.30
Hydrogen Sulfide - H <sub>2</sub> S	0.23	0.09				
Methane - CH <sub>4</sub>	1.16	0.08				0.01
Ethane - C <sub>2</sub> H <sub>6</sub>	0.42	0.07				0.01
Propane - C <sub>3</sub> H <sub>8</sub>	0.19	0.05				0.02
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>		0.02				
Ammonia - NH <sub>3</sub>	0.02		0.02			
Light Oil - (0-100°C @ 1.6 Torr)			1.68		0.83	
Solvent - (100-230°C @ 1.6 Torr)			3.03		1.90	
Heavy Oil - (230-255°C @ 1.6 Torr)			0.42			
SRL						
Coal (MAF)						
Ash						
Water			13.69		0.45	
Phenol						
TOTAL	21.24	2.78	18.84	Neg1.	3.18	0.41

ELEMENTAL	MATERIAL OUT (lbs/hour)					
	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exh.	TOTAL
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 F-1 Btms Increased  
 Revised: 12/20/77

Run No: M-33A  
 Date: 6/21/22/77  
 Time: 1430-0230

MATERIAL OUT

Temperature: 762°F  
 Pressure: 2500 psig  
 LHSV: 1.34  
 GHSV: 289

STREAM DESCRIPTION	lbs/hour				Total Out
	Cold Trap	F-1 Btms	←Recycle Solvent→ S-7 Btms	F-3 Btms	
SAMPLE POINT	Sx-33	Sx-2	Sx-39	Sx-12	
Hydrogen - H <sub>2</sub>					1.04
Carbon Monoxide - CO					8.63
Carbon Dioxide - CO <sub>2</sub>					12.39
Hydrogen Sulfide - H <sub>2</sub> S					0.32
Methane - CH <sub>4</sub>					1.25
Ethane - C <sub>2</sub> H <sub>6</sub>					0.50
Propane - C <sub>3</sub> H <sub>8</sub>					0.26
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					0.02
Ammonia - NH <sub>3</sub>					0.04
Light Oil - (0-100°C @ 1.6 Torr)	0.17		2.55	1.80	7.03
Solvent - (100-230°C @ 1.6 Torr)	0.18		60.58	9.44	75.13
Heavy Oil - (230-255°C @1.6 Torr)	0.04		5.89	0.46	6.81
SRL		13.83			13.83
Coal (MAF)		1.68			1.68
Ash		3.48			3.48
Water	0.28		0.29		14.71
Phenol					
TOTAL	0.67	18.99	69.31	11.70	147.12

ELEMENTAL	lbs/hour				Total
	Cold Trap	F-1 Btms	←Recycle Solvent→ S-7 Btms	F-3 Btms	
Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
TOTAL					

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/19/77

Run No: M-33A  
Date: 6/21-22/77  
Time: 1430-0230

WEIGHT PERCENT

SAMPLE DESCRIPTION	Feed	F-1	Makeup	F-3	Feed	S-8
	Coal	Btms	Solvent	Btms	Solvent	Oil
SAMPLE POINT	Sx-1	Sx-2	Sx-8	Sx-12	Sx-14	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100°C @ 1.6 Torr)			4.93	15.40	5.63	30.26
Solvent - (100-230°C @ 1.6 Torr)			90.40	80.70	75.20	69.06
Heavy Oil - (230-255°C @1.6 Torr)			4.60	3.90	18.90	
SRL		72.84				
Coal (MAF)	53.47	8.86				
Ash	9.36	18.30				
Water	37.17		0.07		0.27	0.68
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		89.15				
Melting Point °F		292				
Specific Gravity 60/60			1.028	0.997	1.039	
Viscosity, cp			49.5	14.1		

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	1	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/19/77

Run No: M-33A

Date: 6/21-22/77

Time: 1430-0230

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-8	S-8	Product	Feed	S-4B	S-4B
	Water	Total	Gas	Gas	Water	Oil
SAMPLE POINT	Sx-16	Sx-16	Sx-19	Sx-21	Sx-23	Sx-23
Hydrogen - H <sub>2</sub>			4.56	7.28		
Carbon Monoxide - CO			37.78	92.72		
Carbon Dioxide - CO <sub>2</sub>			48.17			
Hydrogen Sulfide - H <sub>2</sub> S			1.06			
Methane - CH <sub>4</sub>			5.45			
Ethane - C <sub>2</sub> H <sub>6</sub>			1.96			
Propane - C <sub>3</sub> H <sub>8</sub>			0.91			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)			0.11		0.12	
Light Oils - (0-100°C @ 1.6 Torr)		26.17				32.52
Solvent - (100-230°C @ 1.6 Torr)		59.73				58.42
Heavy Oil - (230-255°C @1.6 Torr)						8.08
SRL						
Coal (MAF)						
Ash						
Water	100	14.10			99.88	0.98
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						0.941
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/19/77

Run No: M-33A

Date: 6/21-22/77

Time: 1430-0230

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4B Btms	S-4A Ovhd	J-1 Disch	Cold Trap	S-7 Btms	
SAMPLE POINT	Sx-23	Sx-30	Sx-32	Sx-33	Sx-39	
Hydrogen -H <sub>2</sub>		2.21	1.46			
Carbon Monoxide-CO		19.85	13.58			
Carbon Dioxide-CO <sub>2</sub>		67.01	73.16			
Hydrogen Sulfide-H <sub>2</sub> S		3.06				
Methane-CH <sub>4</sub>		2.83	3.16			
Ethane-C <sub>2</sub> H <sub>6</sub>		2.55	3.46			
Propane-C <sub>3</sub> H <sub>8</sub>		1.92	5.18			
Butane-C <sub>4</sub> H <sub>10</sub>						
Nitrogen-N <sub>2</sub>		0.47				
Ammonia-NH <sub>3</sub> (PPM)	0.09	0.10				
Light Oils-(0-100°C @ 1.6 Torr)	8.94			25.56	3.68	
Solvent-(100-230°C @ 1.6 Torr)	16.07			26.10	87.40	
Heavy Oil-(230-255°C @1.6 Torr)	2.22			5.83	8.50	
SRL						
Coal (MAF)						
Ash						
Water	72.68			42.51	0.42	
Phenol						
TOTAL	100	100	100	100	100	
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60					1.049	
Viscosity, cp					42.4	

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	3	2	

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/19/77

Run No: M-33A

Date: 6/21-22/77

Time: 1430-0230

MOLE PERCENT

SAMPLE DESCRIPTION	Product Gas	Feed Gas	S-4A Ovhd	J-1 Disch.		
	Sx-19	Sx-21	Sx-30	Sx-32		
Hydrogen - H <sub>2</sub>	43.96	52.35	29.41	22.10		
Carbon Monoxide - CO	26.00	47.65	18.88	14.66		
Carbon Dioxide - CO <sub>2</sub>	21.10		40.56	50.24		
Hydrogen Sulfide - H <sub>2</sub> S	0.60		2.40			
Methane - CH <sub>4</sub>	6.56		4.72	5.96		
Ethane - C <sub>2</sub> H <sub>6</sub>	1.26		2.26	3.48		
Propane - C <sub>3</sub> H <sub>8</sub>	0.40		1.16	3.56		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>			0.45			
Ammonia - NH <sub>3</sub> (PPM)	0.12		0.16			
Light Oils - (0-100° C @ 1.6 Torr)						
Solvent - (100-230° C @ 1.6 Torr)						
Heavy Oil - (230-255° C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100		
Calc Mole Wt.	19.27	14.39	26.63	30.22		
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	3	2	2		

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Updated: 12/20/77

Run No: M-33A  
Date: 6/21-22/77  
Time: 1430-0230

MATERIAL OUT

Temperature: 762°F  
Pressure: 2500 psig  
LHSV: 1.34  
GHSV: 289

STREAM DESCRIPTION	Product Gas	lbs/hour				
		S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exh.
SAMPLE POINT	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	0.97	0.06				0.01
Carbon Monoxide - CO	8.02	0.55				0.06
Carbon Dioxide - CO <sub>2</sub>	10.23	1.86				0.30
Hydrogen Sulfide - H <sub>2</sub> S	0.23	0.09				
Methane - CH <sub>4</sub>	1.16	0.08				0.01
Ethane - C <sub>2</sub> H <sub>6</sub>	0.42	0.07				0.01
Propane - C <sub>3</sub> H <sub>8</sub>	0.19	0.05				0.02
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>		0.02				
Ammonia - NH <sub>3</sub>	0.02		0.02			
Light Oil - (0-100°C @ 1.6 Torr)			1.68		0.83	
Solvent - (100-230°C @ 1.6 Torr)			3.03		1.90	
Heavy Oil - (230-255°C @1.6 Torr)			0.42			
SRL						
Cool (MAF)						
Ash						
Water			13.69		0.45	
Phenol						
<b>TOTAL</b>	<b>21.24</b>	<b>2.78</b>	<b>18.84</b>	<b>Negl.</b>	<b>3.18</b>	<b>0.41</b>

Elemental	Quantitative					
	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exh.
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
<b>TOTAL</b>						

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Updated: 12/20/77

Run No: M-33A  
Date: 6/21-22/77  
Time: 1430-0230

MATERIAL OUT

Temperature: 762°F  
Pressure: 2500 psig  
LHSV: 1.34  
GHSV: 289

lbs/hour

STREAM DESCRIPTION	Cold Trap	F-1 Btms	←Recycle S-7 Btms	Solvent→ F-3 Btms		Total Out
	Sx-33	Sx-2	Sx-39	Sx-12		
Hydrogen - H <sub>2</sub>						1.04
Carbon Monoxide - CO						8.63
Carbon Dioxide - CO <sub>2</sub>						12.39
Hydrogen Sulfide - H <sub>2</sub> S						0.32
Methane - CH <sub>4</sub>						1.25
Ethane - C <sub>2</sub> H <sub>6</sub>						0.50
Propane - C <sub>3</sub> H <sub>8</sub>						0.26
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						0.02
Ammonia - NH <sub>3</sub>						0.04
Light Oil - (0-100°C @ 1.6 Torr)	0.17		2.55	1.80		7.03
Solvent - (100-230°C @ 1.6 Torr)	0.18		60.58	9.44		75.13
Heavy Oil - (230-255°C @ 1.6 Torr)	0.04		5.89	0.46		6.81
SRL		13.32				13.32
Coal (MAF)		1.62				1.62
Ash		3.34				3.34
Water	0.28		0.29			14.71
Phenol						
TOTAL	0.67	18.28	69.31	11.70		146.41

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

RUN CONDITIONS  
 RUN NO. M-33B  
 DATE MADE 6/22/77

TEMPERATURE °F

PRESSURE, psig

PREHEATER E-I  
 SAND BATH 755  
 INLET 279  
 OUTLET 752

DISSOLVERS  
 R-1A (1) \_\_\_\_\_  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_  
 (4) \_\_\_\_\_  
 R-1B (1) 762  
 (2) 794  
 (3) 790  
 (4) 815

REACTOR PRODUCT SEPARATORS  
 S-1 588  
 S-2 73  
 S-3 486  
 S-4A 73  
 S-4B 68

PREHEATER E-II  
 DOWTHERM 680  
 INLET 445  
 OUTLET 642

VACUUM FLASH F-1  
 OVERHEAD VAPOR 513  
 UPPER WALL 595  
 LOWER WALL 586  
 DOWNCOMER 460  
 CONDENSATE  
 ACCUMULATOR, S-7 78

PREHEATER E-13  
 DOWTHERM 575  
 INLET 69  
 OUTLET 503

LIGHT ENDS COLUMN, F-2  
 REBOILER 439  
 LOWER SECTION 506  
 FEED SECTION 448  
 OVERHEAD 191  
 S-8 74  
 S-9 -

SOLVENT COLUMN, F-3  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

HEAVY ENDS COLUMN, F-4  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

VACUUM FLASH, F-0  
 OVERHEAD NIU  
 BOTTOMS \_\_\_\_\_

PRECIPITATION TOWER, V-8  
 ZONE (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_

RECOVERY TOWER V-9  
 REBOILER NIU  
 OVERHEAD \_\_\_\_\_

SEPARATORS, S-1 and S-2  
2500

SEPARATOR S-3  
300

SEPARATORS S-4A and S-4B  
60

VACUUM FLASH, F-1  
15 Torr

LIGHT ENDS COLUMN, F-2  
0

SOLVENT COLUMN, F-3  
NIU

HEAVY ENDS COLUMN, F-4  
NIU


VACUUM FLASH, F-0  
NIU

SETTLING TOWER, V-8  
NIU

RECOVERY TOWER, V-7  
NIU

	Start	End	Run No: M-33B
Date of Run	6/22/77	6/22/77	Units: lbs/hr, °F, Psig
Time of Run	0230	1430	Prep. By: BCL & GGB
Length of Run	12	hours	Updated: 12/20/77
Hours on Coal at End of Y.P.	35.0		

### MASS RATES AND RUN CONDITIONS



153.48 TOTAL

☒ OPEN      ☒ CLOSED

Numbers in parentheses are not included in the totals.

TOTAL 153.48

PRODUCT GAS TO THERMAL	22.96
OXIDIZER	
PRODUCT GAS TO RECYCLE	-0-
Sx-20	
X-4 KNOCKOUT POT BTMS	-0-
ABSORBED GASES	NIU
WASTE GAS	1.85
Sx-30	
S-4A BOTTOMS	-0-
S-4B BOTTOMS	18.83
Sx-37	
S-4A BOTTOMS	-0-
S-4B BOTTOMS	18.83
Sx-23	
TOLUENE ACCUMULATOR	NIU
D.C. OHD	Negl.
Sx-19	
SCRUBBER	
S-2	
S-1	
S-3	
S-4A	
S-4B	
S-7	
S-9	
S-11	
S-13	
S-15	
S-17	
S-19	
S-21	
S-23	
S-27	
S-31	
S-33	
S-35	
S-37	
S-39	
S-41	
S-43	
S-45	
S-47	
S-49	
S-51	
S-53	
S-55	
S-57	
S-59	
S-61	
S-63	
S-65	
S-67	
S-69	
S-71	
S-73	
S-75	
S-77	
S-79	
S-81	
S-83	
S-85	
S-87	
S-89	
S-91	
S-93	
S-95	
S-97	
S-99	
S-101	
S-103	
S-105	
S-107	
S-109	
S-111	
S-113	
S-115	
S-117	
S-119	
S-121	
S-123	
S-125	
S-127	
S-129	
S-131	
S-133	
S-135	
S-137	
S-139	
S-141	
S-143	
S-145	
S-147	
S-149	
S-151	
S-153	
S-155	
S-157	
S-159	
S-161	
S-163	
S-165	
S-167	
S-169	
S-171	
S-173	
S-175	
S-177	
S-179	
S-181	
S-183	
S-185	
S-187	
S-189	
S-191	
S-193	
S-195	
S-197	
S-199	
S-201	
S-203	
S-205	
S-207	
S-209	
S-211	
S-213	
S-215	
S-217	
S-219	
S-221	
S-223	
S-225	
S-227	
S-229	
S-231	
S-233	
S-235	
S-237	
S-239	
S-241	
S-243	
S-245	
S-247	
S-249	
S-251	
S-253	
S-255	
S-257	
S-259	
S-261	
S-263	
S-265	
S-267	
S-269	
S-271	
S-273	
S-275	
S-277	
S-279	
S-281	
S-283	
S-285	
S-287	
S-289	
S-291	
S-293	
S-295	
S-297	
S-299	
S-301	
S-303	
S-305	
S-307	
S-309	
S-311	
S-313	
S-315	
S-317	
S-319	
S-321	
S-323	
S-325	
S-327	
S-329	
S-331	
S-333	
S-335	
S-337	
S-339	
S-341	
S-343	
S-345	
S-347	
S-349	
S-351	
S-353	
S-355	
S-357	
S-359	
S-361	
S-363	
S-365	
S-367	
S-369	
S-371	
S-373	
S-375	
S-377	
S-379	
S-381	
S-383	
S-385	
S-387	
S-389	
S-391	
S-393	
S-395	
S-397	
S-399	
S-401	
S-403	
S-405	
S-407	
S-409	
S-411	
S-413	
S-415	
S-417	
S-419	
S-421	
S-423	
S-425	
S-427	
S-429	
S-431	
S-433	
S-435	
S-437	
S-439	
S-441	
S-443	
S-445	
S-447	
S-449	
S-451	
S-453	
S-455	
S-457	
S-459	
S-461	
S-463	
S-465	
S-467	
S-469	
S-471	
S-473	
S-475	
S-477	
S-479	
S-481	
S-483	
S-485	
S-487	
S-489	
S-491	
S-493	
S-495	
S-497	
S-499	
S-501	
S-503	
S-505	
S-507	
S-509	
S-511	
S-513	
S-515	
S-517	
S-519	
S-521	
S-523	
S-525	
S-527	
S-529	
S-531	
S-533	
S-535	
S-537	
S-539	
S-541	
S-543	
S-545	
S-547	
S-549	
S-551	
S-553	
S-555	
S-557	
S-559	
S-561	
S-563	
S-565	
S-567	
S-569	
S-571	
S-573	
S-575	
S-577	
S-579	
S-581	
S-583	
S-585	
S-587	
S-589	
S-591	
S-593	
S-595	
S-597	
S-599	
S-601	
S-603	
S-605	
S-607	
S-609	
S-611	
S-613	
S-615	
S-617	
S-619	
S-621	
S-623	
S-625	
S-627	
S-629	
S-631	
S-633	
S-635	
S-637	
S-639	
S-641	
S-643	
S-645	
S-647	
S-649	
S-651	
S-653	
S-655	
S-657	
S-659	
S-661	
S-663	
S-665	
S-667	
S-669	
S-671	
S-673	
S-675	
S-677	
S-679	
S-681	
S-683	
S-685	
S-687	
S-689	
S-691	
S-693	
S-695	
S-697	
S-699	
S-701	
S-703	
S-705	
S-707	
S-709	
S-711	
S-713	
S-715	
S-717	
S-719	
S-721	
S-723	
S-725	
S-727	
S-729	
S-731	
S-733	
S-735	
S-737	
S-739	
S-741	
S-743	
S-745	
S-747	
S-749	
S-751	
S-753	
S-755	
S-757	
S-759	
S-761	
S-763	
S-765	
S-767	
S-769	
S-771	
S-773	
S-775	
S-777	
S-779	
S-781	
S-783	
S-785	
S-787	
S-789	
S-791	
S-793	
S-795	
S-797	
S-799	
S-801	
S-803	
S-805	
S-807	
S-809	
S-811	
S-813	
S-815	
S-817	
S-819	
S-821	
S-823	
S-825	
S-827	
S-829	
S-831	
S-833	
S-835	
S-837	
S-839	
S-841	
S-843	
S-845	
S-847	
S-849	
S-851	
S-853	
S-855	
S-857	
S-859	
S-861	
S-863	
S-865	
S-867	
S-869	
S-871	
S-873	
S-875	
S-877	
S-879	
S-881	
S-883	
S-885	
S-887	
S-889	
S-891	
S-893	
S-895	
S-897	
S-899	
S-901	
S-903	
S-905	
S-907	
S-909	
S-911	
S-913	
S-915	
S-917	
S-919	
S-921	
S-923	
S-925	
S-927	
S-929	
S-931	
S-933	
S-935	
S-937	
S-939	
S-941	
S-943	
S-945	
S-947	
S-949	
S-951	
S-953	
S-955	
S-957	
S-959	
S-961	
S-963	
S-965	
S-967	
S-969	
S-971	
S-973	
S-975	
S-977	
S-979	
S-981	
S-983	
S-985	
S-987	
S-989	
S-991	
S-993	
S-995	
S-997	
S-999	
S-1001	
S-1003	
S-1005	
S-1007	
S-1009	
S-1011	
S-1013	
S-1015	
S-1017	
S-1019	
S-1021</	

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 F-1 Btms Increased, then Normalized  
 Revised: 12/20/77

Run No: M-33B  
 Date: 6/22/77  
 Time: 0230-1430

SUMMARY  
 lbs/hour

Temperature: 752°F  
 Pressure: 2500 psig  
 LHSV: 1.37  
 GHSV: 301

STREAM DESCRIPTION	lbs/hour				
	Total In	Total Out	Net Yield		WT % MAF Lignite
SAMPLE POINT					
Hydrogen - H <sub>2</sub>	1.13	1.01	-0.12		
Carbon Monoxide - CO	16.00	8.90	-7.10		
Carbon Dioxide - CO <sub>2</sub>		13.23	13.23		
Hydrogen Sulfide - H <sub>2</sub> S		0.23	0.23		
Methane - CH <sub>4</sub>		1.11	1.11	8.15	34.24
Ethane - C <sub>2</sub> H <sub>6</sub>		0.47	0.47		
Propane - C <sub>3</sub> H <sub>8</sub>		0.29	0.29		
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					
Ammonia - NH <sub>3</sub>		0.04	0.04		
Light Oil - (0-100°C @ 1.6 Torr)	5.62	9.32	3.70	15.86	66.64
Solvent - (100-230°C @ 1.6 Torr)	67.29	75.92	8.63		
Heavy Oil - (230-255°C @ 1.6 Torr)	18.44	6.77	-11.67		
SRL		15.20	15.20		
Coal (MAF)	23.80	1.31	-22.49		-94.49
Ash	4.09	3.41	-0.68		-2.86
Water	17.11	16.27	-0.84		-3.53
Phenol					
TOTAL	153.48	153.48	-0-		

ELEMENTAL					
	Total In	Total Out	Net Yield		WT % MAF Lignite
Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
TOTAL					

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Updated: 12/20/77

Run No: M-33B  
Date: 6/22/77  
Time: 0230-1430

MATERIAL IN  
  
lbs/hour

Temperature: 752°F  
Pressure: 2500 psig  
LHSV: 1.37  
GHSV: 301

STREAM DESCRIPTION	Feed Gas	Lignite	Feed Solvent		Total In
	Sx-21	Sx-1	Sx-14		
Hydrogen - H <sub>2</sub>	1.13				1.13
Carbon Monoxide - CO	16.00				16.00
Carbon Dioxide - CO <sub>2</sub>					
Hydrogen Sulfide - H <sub>2</sub> S					
Methane - CH <sub>4</sub>					
Ethane - C <sub>2</sub> H <sub>6</sub>					
Propane - C <sub>3</sub> H <sub>8</sub>					
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					
Ammonia - NH <sub>3</sub>					
Light Oil - (0-100°C @ 1.6 Torr)			5.62		5.62
Solvent - (100-230°C @ 1.6 Torr)			67.29		67.29
Heavy Oil - (230-255°C @ 1.6 Torr)			18.44		18.44
SRL					
Coal (MAF)		23.80			23.80
Ash		4.09			4.09
Water		16.85	0.26		17.11
Phenol					
<b>TOTAL</b>	<b>17.13</b>	<b>44.74</b>	<b>91.61</b>		<b>153.48</b>

ELEMENTAL	Quantitative				
	Feed Gas	Lignite	Feed Solvent		Total In
Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
<b>TOTAL</b>					

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 F-1 Btms Increased, then Normalized  
 Revised: 12/20/77

Run No: M-33B  
 Date: 6/22/77  
 Time: 0230-1430

MATERIAL OUT

lbs/hour

Temperature: 752°F  
 Pressure: 2500 psig  
 LHSV: 1.37  
 GHSV: 301

STREAM DESCRIPTION	Product Gas	MATERIAL OUT				
		S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
SAMPLE POINT	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	0.97	0.04				
Carbon Monoxide - CO	8.46	0.38				0.06
Carbon Dioxide - CO <sub>2</sub>	11.64	1.25				0.34
Hydrogen Sulfide - H <sub>2</sub> S	0.19	0.04				
Methane - CH <sub>4</sub>	1.05	0.05				0.01
Ethane - C <sub>2</sub> H <sub>6</sub>	0.41	0.04				0.02
Propane - C <sub>3</sub> H <sub>8</sub>	0.23	0.04				0.02
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>	0.01	0.01	0.02			
Light Oil - (0-100°C @ 1.6 Torr)			1.08		0.48	
Solvent - (100-230°C @ 1.6 Torr)			1.96		1.89	
Heavy Oil - (230-255°C @ 1.6 Torr)			0.27		0.04	
SRL						
Cool (MAF)						
Ash						
Water			15.50		0.59	
Phenol						
TOTAL	22.96	1.85	18.83	Negl.	3.00	• 0.45

ELEMENTAL	MATERIAL OUT					
	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust	TOTAL
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 F-1 Btms Increased, the Normalized  
 Revised: 12/20/77

Run No: M-33B  
 Date: 6/22/77  
 Time: 0230-1430

MATERIAL OUT

Temperature: 752°F  
 Pressure: 2500 psig  
 LHSV: 1.37  
 GHSV: 301

lbs/hour

STREAM DESCRIPTION	Cold Trap	F-1 Btms	←Recycle Solvent→		Total Out
			S-7 Btms	F-3 Btms	
SAMPLE POINT	Sx-33	Sx-2	Sx-39	Sx-12	
Hydrogen - H <sub>2</sub>					1.01
Carbon Monoxide - CO					8.90
Carbon Dioxide - CO <sub>2</sub>					13.23
Hydrogen Sulfide - H <sub>2</sub> S					0.23
Methane - CH <sub>4</sub>					1.11
Ethane - C <sub>2</sub> H <sub>6</sub>					0.47
Propane - C <sub>3</sub> H <sub>8</sub>					0.29
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					
Ammonia - NH <sub>3</sub>					0.04
Light Oil - (0-100°C @ 1.6 Torr)	0.05		6.63	1.08	9.32
Solvent - (100-230°C @ 1.6 Torr)	0.15		61.88	10.04	75.92
Heavy Oil - (230-255°C @ 1.6 Torr)	0.03		6.13	0.30	6.77
SRL		15.20			15.20
Coal (MAF)		1.31			1.31
Ash		3.41			3.41
Water			0.18		16.27
Phenol					
TOTAL	0.23	19.92	74.82	11.42	153.48

ELEMENTAL	Quantitative					TOTAL
	Cold Trap	F-1 Btms	S-7 Btms	F-3 Btms	Total Out	
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/20/77

Run No: M-33B  
Date: 6/22/77  
Time: 0230-1430

WEIGHT PERCENT

SAMPLE DESCRIPTION	Lignite	F-1 Btms	Makeup Solvent	F-3 Btms	Feed Solvent	S-8 Oil
SAMPLE POINT	Sx-1	Sx-2	Sx-8	Sx-12	Sx-14	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100°C @ 1.6 Torr)			4.53	9.50	6.13	19.86
Solvent - (100-230°C @ 1.6 Torr)			63.60	87.90	73.45	78.20
Heavy Oil - (230-255°C @1.6 Torr)			31.80	2.60	20.13	1.50
SRL		76.32				
Coal (MAF)	53.20	6.59				
Ash	9.15	17.09				
Water	37.65		0.07		0.29	0.44
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		92.05				
Melting Point °F		242				
Specific Gravity 60/60			1.028	1.004	1.054	
Viscosity, cp			49.5	18.6	49.3	

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/20/77

Run No: M-33B

Date: 6/22/77

Time: 0230-1430

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-8	S-8	Product	Feed	*S-4B	S-4B
	Water	Total	Gas	Gas	Oil	Water
SAMPLE POINT	Sx-16	Sx-16	Sx-19	Sx-21	Sx-23	Sx-23
Hydrogen - H <sub>2</sub>			4.20	6.57		
Carbon Monoxide - CO			36.83	93.43		
Carbon Dioxide - CO <sub>2</sub>			50.71			
Hydrogen Sulfide - H <sub>2</sub> S			0.84			
Methane - CH <sub>4</sub>			4.58			
Ethane - C <sub>2</sub> H <sub>6</sub>			1.80			
Propane - C <sub>3</sub> H <sub>8</sub>			0.98			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)			0.06			0.11
Light Oils - (0-100° C @ 1.6 Torr)		16.00			32.03	
Solvent - (100-230° C @ 1.6 Torr)		62.99			58.42	
Heavy Oil - (230-255° C @1.6 Torr)		1.21			8.08	
SRL						
Coal (MAF)						
Ash						
Water	100	19.80			1.47	99.89
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60					0.958	
Viscosity, cp						
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	2

\*Insufficient oil sample for distillation. Analysis assumed the same as M-33A

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/20/77

Run No: M-33B

Date: 6/22/77

Time: 0230-1430

WEIGHT PERCENT

	WEIGHT PERCENT					
	S-4B Total	S-4A Ovhd	J-1 Disch.	Cold Trap	S-4A Oil	S-4A Water
SAMPLE DESCRIPTION						
SAMPLE POINT	Sx-23	Sx-30	Sx-32	Sx-33	Sx-37	Sx-37
Hydrogen - H <sub>2</sub>		1.97	1.12			
Carbon Monoxide - CO		20.27	12.81			
Carbon Dioxide - CO <sub>2</sub>		67.70	76.44			
Hydrogen Sulfide - H <sub>2</sub> S		2.23				
Methane - CH <sub>4</sub>		2.92	2.64			
Ethane - C <sub>2</sub> H <sub>6</sub>		2.37	3.24			
Propane - C <sub>3</sub> H <sub>8</sub>		2.27	3.75			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)	0.09	0.27				0.15
Light Oils - (0-100°C @ 1.6 Torr)	5.72			20.21	28.60	
Solvent - (100-230°C @ 1.6 Torr)	10.43			63.80	71.40	
Heavy Oil - (230-255°C @1.6 Torr)	1.44			13.30		
SRL						
Coal (MAF)						
Ash						
Water	82.32			2.69		99.85
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60					0.942	
Viscosity, cp					5.6	

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	1	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/20/77

Run No: M-33B  
Date: 6/22/77

Time: 0230-1430

WEIGHT PERCENT

	Quantitative		Elemental			
	S-4A Total	Recycle Solvent				
SAMPLE DESCRIPTION						
SAMPLE POINT	Sx-37	Sx-39				
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)	0.01	8.86				
Light Oils - (0-100° C @ 1.6 Torr)	27.52	82.70				
Solvent - (100-230° C @ 1.6 Torr)	68.69	8.20				
Heavy Oil - (230-255° C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water	3.78	0.24				
Phenol						
TOTAL	100	100				
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60		1.059				
Viscosity, cp		42.5				
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2				

PROJECT: LIGNITE  
SAMPLE ANALYSIS

Updated: 12/20/77

Run No: M-33B

Date: 6/22/77

Time: 0230-1430

MOLE PERCENT

	MOLE PERCENT				
	Product Gas	Feed Gas	S-4A Ovhd	J-1 Exhaust	
<b>SAMPLE DESCRIPTION</b>					
<b>SAMPLE POINT</b>	Sx-19	Sx-21	Sx-30	Sx-32	
Hydrogen -H <sub>2</sub>	42.28	49.62	27.02	17.98	
Carbon Monoxide-CO	26.50	50.38	19.88	14.70	
Carbon Dioxide-CO <sub>2</sub>	23.22		42.26	55.82	
Hydrogen Sulfide-H <sub>2</sub> S	0.50		1.80		
Methane-CH <sub>4</sub>	5.77		5.01	5.29	
Ethane-C <sub>2</sub> H <sub>6</sub>	1.21		2.17	3.47	
Propane-C <sub>3</sub> H <sub>8</sub>	0.45		1.42	2.74	
Butane-C <sub>4</sub> H <sub>10</sub>					
Nitrogen-N <sub>2</sub>					
Ammonia-NH <sub>3</sub> (PPM)	0.07		0.44		
Light Oils-(0-100°C @ 1.6 Torr)					
Solvent-(100-230°C @ 1.6 Torr)					
Heavy Oil-(230-255°C @ 1.6 Torr)					
SRL					
Coal (MAF)					
Ash					
Water					
Phenol					
<b>TOTAL</b>	100	100	100	100	
Calc Mole Wt	20.15	15.10	27.47	32.13	
Melting Point °F					
Specific Gravity 60/60					
Viscosity, cp					

Elemental	Carbon				
	Hydrogen				
	Nitrogen				
	Sulfur				
	Oxygen (by diff)				
	Ash				
	TOTAL				
	Number of Sample Avg.	2	2	2	2

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Updated: 12/20/77

Run No: M-33B  
Date: 6/22/77  
Time: 0230-1430

MATERIAL OUT

Temperature: 752°F  
Pressure: 2500 psig  
LHSV: 1.37  
GHSV: 301

lbs/hour

STREAM DESCRIPTION	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	0.91	0.03				0.01
Carbon Monoxide - CO	7.98	0.35				0.05
Carbon Dioxide - CO <sub>2</sub>	10.99	1.18				0.32
Hydrogen Sulfide - H <sub>2</sub> S	0.18	0.04				
Methane - CH <sub>4</sub>	0.99	0.05				0.01
Ethane - C <sub>2</sub> H <sub>6</sub>	0.39	0.04				0.01
Propane - C <sub>3</sub> H <sub>8</sub>	0.21	0.04				0.02
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>	0.01	0.01	0.02			
Light Oil - (0-100°C @ 1.6 Torr)			1.02		0.45	
Solvent - (100-230°C @ 1.6 Torr)			1.85		1.78	
Heavy Oil - (230-255°C @ 1.6 Torr)			0.25		0.04	
SRL						
Coal (MAF)						
Ash						
Water			14.62		0.56	
Phenol						
<b>TOTAL</b>	<b>21.66</b>	<b>1.74</b>	<b>17.76</b>	<b>Neg1.</b>	<b>2.83</b>	<b>0.42</b>

ELEMENTAL	Quantitative					
	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
<b>TOTAL</b>						

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Updated: 12/20/77

Run No: M-33B  
Date: 6/22/77  
Time: 0230-1430

MATERIAL OUT

Temperature: 752°F  
Pressure: 2500 psig  
LHSV: 1.37  
GHSV: 301

		lbs/hour				
Quantitative	STREAM DESCRIPTION	Cold Trap	F-1 Btms	←Recycle Solvent→ S-7 Btms	F-3 Btms	Total Out
	SAMPLE POINT	Sx-33	Sx-2	Sx-39	Sx-12	
	Hydrogen - H <sub>2</sub>					0.95
	Carbon Monoxide - CO					8.38
	Carbon Dioxide - CO <sub>2</sub>					12.49
	Hydrogen Sulfide - H <sub>2</sub> S					0.22
	Methane - CH <sub>4</sub>					1.05
	Ethane - C <sub>2</sub> H <sub>6</sub>					0.44
	Propane - C <sub>3</sub> H <sub>8</sub>					0.27
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					
	Ammonia - NH <sub>3</sub>					0.04
	Light Oil - (0-100°C @ 1.6 Torr)	0.04		6.63	1.08	9.22
	Solvent - (100-230°C @ 1.6 Torr)	0.14		61.88	10.04	75.69
	Heavy Oil - (230-255°C @ 1.6 Torr)	0.03		6.13	0.30	6.75
	SRL		13.49			13.49
	Coal (MAF)		1.16			1.16
	Ash		3.02			3.02
	Water	0.01		0.18		15.37
	Phenol					
	<b>TOTAL</b>	<b>0.22</b>	<b>17.67</b>	<b>74.82</b>	<b>11.42</b>	<b>148.54</b>
Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	<b>TOTAL</b>					


RUN CONDITIONS  
 RUN NO. M-33C  
 DATE MADE 6/23-24/77

TEMPERATURE °F		PRESSURE, psig
PREHEATER E-I SAND BATH <u>753</u> INLET <u>266</u> OUTLET <u>741</u>	PREHEATER E-13 DOWTHERM <u>571</u> INLET <u>99</u> OUTLET <u>505</u>	SEPARATORS S-1 and S-2 <u>2500</u> SEPARATOR S-3 <u>300</u> SEPARATORS S-4A and S-4B <u>60</u>
DISSOLVERS R-1A (1) _____ (2) _____ (3) _____ (4) _____ R-1B (1) <u>765</u> (2) <u>799</u> (3) <u>802</u> (4) <u>822</u>	LIGHT ENDS COLUMN, F-2 REBOILER <u>426</u> LOWER SECTION <u>504</u> FEED SECTION <u>422</u> OVERHEAD <u>192</u> S-8 <u>90</u> S-9 _____ SOLVENT COLUMN, F-3 REBOILER <u>NIU</u> LOWER SECTION _____ FEED SECTION _____ OVERHEAD _____	VACUUM FLASH, F-1 <u>15 Torr</u> LIGHT ENDS COLUMN, F-2 <u>0</u> SOLVENT COLUMN, F-3 <u>NIU</u> HEAVY ENDS COLUMN, F-4 <u>NIU</u> VACUUM FLASH, F-0 <u>15 Torr</u> SETTLING TOWER, V-8 <u>300</u> RECOVERY TOWER, V-7 <u>2</u>
REACTOR PRODUCT SEPARATORS S-1 <u>607</u> S-2 <u>75</u> S-3 <u>440</u> S-4A <u>89</u> S-4B <u>87</u>	HEAVY ENDS COLUMN, F-4 REBOILER <u>NIU</u> LOWER SECTION _____ FEED SECTION _____ OVERHEAD _____ VACUUM FLASH, F-0 OVERHEAD <u>440</u> BOTTOMS <u>470</u>	
PREHEATER E-II DOWTHERM <u>685</u> INLET <u>376</u> OUTLET <u>650</u>	PRECIPITATION TOWER, V-8 ZONE (1) <u>433</u> (2) <u>437</u> (3) <u>442</u> RECOVERY TOWER V-9 REBOILER <u>500</u> OVERHEAD <u>324</u>	
VACUUM FLASH F-1 OVERHEAD VAPOR <u>515</u> UPPER WALL <u>621</u> LOWER WALL <u>615</u> DOWNCOMER <u>453</u> CONDENSATE ACCUMULATOR, S-7 <u>91</u>		

Date of Run	Start	End	Run No.: M-33C
Time of Run	6/23/77	6/24/77	Units: °F, psig, lbs/hr
Length of Run	1430	0230	Prep. By: BCL & GGB
Hours on Coal at End of Y.P.	12	hours	Updated: 12/22/77
	71.0		

### MASS RATES AND RUN CONDITIONS

PRODUCT GAS TO THERMAL	22.43
OXIDIZER	-0-
PRODUCT GAS TO RECYCLE	-0-



241.28 TOTAL

☒ OPEN

☒ CLOSED

TOTAL 241.28

Numbers in parentheses are not included in the totals.

-67-

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 V-9 Ovhd and V-8 Btms Adjusted with Forced Ash Balance  
 Revised 12/22/77

Run No: M-33C  
 Date: 6/23/77  
 Time: 1430-0230

SUMMARY  
 lbs/hour

Temperature: 741°F  
 Pressure: 2500 psig  
 LHSV: 1.49  
 GHSV: 301

STREAM DESCRIPTION	Total In	Total Out	Net Yield	Wt % MAF Lignite	
SAMPLE POINT					
Hydrogen - H <sub>2</sub>	1.16	1.12	-0.04	8.74	34.06
Carbon Monoxide - CO	15.52	7.69	-7.83		
Carbon Dioxide - CO <sub>2</sub>		14.65	14.65		
Hydrogen Sulfide - H <sub>2</sub> S		0.23	0.23		
Methane - CH <sub>4</sub>		0.96	0.96		
Ethane - C <sub>2</sub> H <sub>6</sub>		0.42	0.42		
Propane - C <sub>3</sub> H <sub>8</sub>		0.33	0.33		
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					
Ammonia - NH <sub>3</sub>		0.02	0.02		
Light Oil - (0-100°C @ 1.6 Torr)	98.89	104.27	5.38	16.27	63.40
Solvent - (100-230°C @ 1.6 Torr)	74.81	70.69	-4.12		
Heavy Oil - (230-255°C @ 1.6 Torr)	3.92	4.20	0.28		
SRL		14.73	14.73		
Coal (MAF)	25.66	3.03	-22.63		-88.19
Ash	3.97	3.97	-0-		-0-
Water	17.35	14.97	-2.38		-9.27
Phenol					
TOTAL	241.28	241.28	-0-		

Carbon	182.52	182.84	0.32		
Hydrogen	19.15	19.26	0.11		
Nitrogen	0.26	0.37	0.11		
Sulfur	1.80	1.68	-0.12		
Oxygen (by diff)	33.58	33.16	-0.42		
Ash	3.97	3.97	-0-		
TOTAL	241.28	241.28	-0-		

PROJECT LIGNITE  
 ADJUSTED & MEASURED MATERIAL BALANCE  
 Updated: 12/22/77

Run No: M-33C  
 Date: 6/23/77  
 Time: 1430-0230

MATERIAL IN

Temperature: 741°F  
 Pressure: 2500 psig  
 LHSV: 1.49  
 GHSV: 301

lbs/hr

STREAM DESCRIPTION	Feed Gas	Lignite	Feed Solvent	Feed Toluene	Total In
	Sx-21	Sx-1	Sx-14	Sx-40	
Hydrogen - H <sub>2</sub>	1.16				1.16
Carbon Monoxide - CO	15.52				15.52
Carbon Dioxide - CO <sub>2</sub>					
Hydrogen Sulfide - H <sub>2</sub> S					
Methane - CH <sub>4</sub>					
Ethane - C <sub>2</sub> H <sub>6</sub>					
Propane - C <sub>3</sub> H <sub>8</sub>					
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					
Ammonia - NH <sub>3</sub>					
Light Oil - (0-100°C @ 1.6 Torr)			13.29	85.60	98.89
Solvent - (100-230°C @ 1.6 Torr)			73.68	1.13	74.81
Heavy Oil - (230-255°C @ 1.6 Torr)			3.92		3.92
SRL					
Coal (MAF)		25.66			25.66
Ash		3.97			3.97
Water		17.16	0.19		17.35
Phenol					
TOTAL	16.68	46.79	91.08	86.73	241.28

Elemental	Feed Gas	Lignite	Feed Solvent	Feed Toluene	Total In
Carbon	6.65	17.91	78.83	79.13	182.52
Hydrogen	1.16	3.20	7.25	7.54	19.15
Nitrogen		0.24	0.02		0.26
Sulfur		0.33	1.45	0.02	1.80
Oxygen (by diff)	8.87	21.14	3.53	0.04	33.58
Ash		3.97			3.97
TOTAL	16.68	46.79	91.08	86.73	241.28

PROJECT LIGNITE

ADJUSTED MATERIAL BALANCE

V-9 Ovhd and V-8 Btms Adjusted with Forced Ash Balance

Revised: 12/22/77

Run No: M-33C  
Date: 6/23/77  
Time: 1430-0230

MATERIAL OUT  
lbs/hour

Temperature: 741°F  
Pressure: 2500 psig  
LHSV: 1.49  
GHSV: 301

STREAM DESCRIPTION	Product Gas	MATERIAL OUT (lbs/hour)				
		S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
SAMPLE POINT	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	1.08	0.04				
Carbon Monoxide - CO	7.30	0.35				0.04
Carbon Dioxide - CO <sub>2</sub>	12.42	1.89				0.34
Hydrogen Sulfide - H <sub>2</sub> S	0.16	0.07				
Methane - CH <sub>4</sub>	0.89	0.06				0.01
Ethane - C <sub>2</sub> H <sub>6</sub>	0.35	0.06				0.01
Propane - C <sub>3</sub> H <sub>8</sub>	0.23	0.08				0.02
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>			0.02			
Light Oil - (0-100°C @ 1.6 Torr)			2.49		3.11	
Solvent - (100-230°C @ 1.6 Torr)			2.81		0.13	
Heavy Oil - (230-255°C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water			14.78		0.02	
Phenol						
TOTAL	22.43	2.55	20.10	Negl.	3.26	0.42

ELEMENTAL	MATERIAL OUT (lbs/hour)					
	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
Carbon	7.66	0.82	4.70		2.60	0.14
Hydrogen	1.42	0.09	2.11		0.34	0.01
Nitrogen			0.02		0.01	
Sulfur	0.15	0.07	0.04		0.01	
Oxygen (by diff)	13.20	1.57	13.23		0.30	0.27
Ash						
TOTAL	22.43	2.55	20.10	Negl	3.26	0.42

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

V-9 Ovhd and V-8 Btms Adjusted With Forced Ash Balance

Revised: 12/22/77

Temperature: 741°F  
Pressure: 2500 psig  
LHSV: 1.49  
GHSV: 301

Run No: M-33C  
Date: 6/23/77  
Time: 1430-0230

MATERIAL OUT  
lbs/hour

STREAM DESCRIPTION	Cold Trap	V-8 Btms	F-1 Btms	V-9 Ovhd	← Recycle S-7 Btms	Solvent → F-3 Btms
	Sx-33	Calc	Sx-2	Sx-28	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	0.31	2.95		82.65	11.75	1.01
Solvent - (100-230°C @ 1.6 Torr)	0.01	1.94	0.37	4.08	48.88	12.47
Heavy Oil - (230-255°C @ 1.6 Torr)					3.68	0.52
SRL		0.46	14.27			
Coal (MAF)		3.03				
Ash		3.94	0.03			
Water					0.17	
Phenol						
<b>TOTAL</b>	<b>0.32</b>	<b>12.32</b>	<b>14.67</b>	<b>86.73</b>	<b>64.48</b>	<b>14.00</b>

Carbon	0.25	6.88	12.57	78.99	55.74	12.49
Hydrogen	0.03	0.59	0.88	7.51	5.09	1.19
Nitrogen		0.04	0.12		0.14	0.04
Sulfur	0.01	0.07	0.14	0.07	0.93	0.19
Oxygen (by diff)	0.03	0.80	0.93	0.16	2.58	0.09
Ash		3.94	0.03			
<b>TOTAL</b>	<b>0.32</b>	<b>12.32</b>	<b>14.67</b>	<b>86.73</b>	<b>64.48</b>	<b>14.00</b>

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 V-9 Ovhd and V-8 Btms Adjusted with Forced Ash Balance  
 Revised: 12/22/77

Run No: M-33C  
 Date: 6/23/77  
 Time: 1430-0230

MATERIAL OUT  
 lbs/hour

Temperature: 741°F  
 Pressure: 2500 psig  
 LHSV: 1.49  
 GHSV: 301

Quantitative	STREAM DESCRIPTION					Total Out
	SAMPLE POINT					
	Hydrogen - H <sub>2</sub>					1.12
	Carbon Monoxide - CO					7.69
	Carbon Dioxide - CO <sub>2</sub>					14.65
	Hydrogen Sulfide - H <sub>2</sub> S					0.23
	Methane - CH <sub>4</sub>					0.96
	Ethane - C <sub>2</sub> H <sub>6</sub>					0.42
	Propane - C <sub>3</sub> H <sub>8</sub>					0.33
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					
	Ammonia - NH <sub>3</sub>					0.02
	Light Oil - (0-100°C @ 1.6 Torr)					104.27
	Solvent - (100-230°C @ 1.6 Torr)					70.69
	Heavy Oil - (230-255°C @1.6 Torr)					4.20
	SRL					14.73
	Cool (MAF)					3.03
	Ash					3.97
	Water					14.97
	Phenol					
	TOTAL					241.28

Elemental	Carbon					182.84
	Hydrogen					19.26
	Nitrogen					0.37
	Sulfur					1.68
	Oxygen (by diff)					33.16
	Ash					3.97
	TOTAL					241.28

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/22/77

Run No: M-33C

Date: 1430-0230

Time: 6/23-24/77

WEIGHT PERCENT

SAMPLE DESCRIPTION	Lignite	F-1 Btms	Makeup Solvent	F-2 Btms	Feed Solvent	S-8 Oil
	Sx-1	Sx-2	Sx-8	Sx-12	Sx-14	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100°C @ 1.6 Torr)			5.01	7.20	14.59	95.33
Solvent - (100-230°C @ 1.6 Torr)		2.50	84.50	89.10	80.90	4.00
Heavy Oil - (230-255°C @1.6 Torr)			10.20	3.70	4.30	
SRL		97.32				
Coal (MAF)	54.84					
Ash	8.48	0.18				
Water	36.68		0.29		0.21	0.67
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		100				
Melting Point °F		193				
Specific Gravity 60/60			1.038	1.008	1.034	
Viscosity, cp			57.4	16.8	28.2	

Carbon	38.28	85.73	87.58	89.21	86.55	79.84
Hydrogen	6.83	5.98	8.18	8.54	7.96	10.41
Nitrogen	0.51	0.80	0.12	0.28	0.02	0.24
Sulfur	0.71	0.94	2.00	1.34	1.59	0.19
Oxygen (by diff)	45.19	6.37	2.12	0.63	3.88	9.32
Ash	8.48	0.18				
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/22/77

Run No: M-33C

Date: 6/23-24/77

Time: 1430-0230

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-8 Water	S-8 Total	Product Gas	Feed Gas	S-4B Oil	S-4B Water
SAMPLE POINT	Sx-16	Sx-16	Sx-19	Sx-21	Sx-23	Sx-23
Hydrogen -H <sub>2</sub>			4.81	6.95		
Carbon Monoxide-CO			32.53	93.05		
Carbon Dioxide-CO <sub>2</sub>			55.37			
Hydrogen Sulfide-H <sub>2</sub> S			0.70			
Methane-CH <sub>4</sub>			3.97			
Ethane-C <sub>2</sub> H <sub>6</sub>			1.57			
Propane-C <sub>3</sub> H <sub>8</sub>			1.03			
Butane-C <sub>4</sub> H <sub>10</sub>						
Nitrogen-N <sub>2</sub>						
Ammonia-NH <sub>3</sub> (PPM)			0.02			0.11
Light Oils-(0-100°C @ 1.6 Torr)		95.33			44.94	
Solvent-(100-230°C @ 1.6 Torr)		4.00			50.79	
Heavy Oil-(230-255°C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water	100	0.67			4.27	99.89
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60					0.954	
Viscosity, cp						

Carbon		79.84	34.12	39.88	84.88	
Hydrogen	11.11	10.41	6.34	6.95	8.76	11.12
Nitrogen		0.24	0.02		0.22	0.09
Sulfur		0.19	0.66		0.74	
Oxygen (by diff)	88.89	9.32	58.86	53.17	5.40	88.79
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/22/77

Run No: M-33C

Date: 6/23-24/77

Time: 1430-0230

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4B	V-8	V-9	S-4A	J-1	Cold
	Total	Btms	Ovhd	Ovhd	Exhaust	Trap
SAMPLE POINT	Sx-23	Sx-27	Sx-28	Sx-30	Sx-32	Sx-33
Hydrogen - H <sub>2</sub>				1.80	1.17	
Carbon Monoxide - CO				13.74	8.43	
Carbon Dioxide - CO <sub>2</sub>				74.01	80.85	
Hydrogen Sulfide - H <sub>2</sub> S				2.76		
Methane - CH <sub>4</sub>				2.42	2.42	
Ethane - C <sub>2</sub> H <sub>6</sub>				2.17	3.02	
Propane - C <sub>3</sub> H <sub>8</sub>				2.96	4.11	
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)	0.08			0.14		
Light Oils - (0-100°C @ 1.6 Torr)	12.38		95.30			96.40
Solvent - (100-230°C @ 1.6 Torr)	13.99		4.70			2.35
Heavy Oil - (230-255°C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						0.35
Water	73.55					0.90
Phenol						
TOTAL	100	NA	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60			0.868			
Viscosity, cp						

Carbon	23.38		91.08	32.05	33.26	78.60
Hydrogen	10.47		8.66	3.55	3.12	10.53
Nitrogen	0.12			0.12		0.36
Sulfur	0.20		0.08	2.60		1.84
Oxygen (by diff)	65.83		0.18	61.68	63.62	8.32
Ash						0.35
TOTAL	100	NA	100	100	100	100
Number of Sample Avg.	2		2	2	2	1

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/22/77

Run No: M-33C  
Date: 6/23-24/77  
Time: 1430-0230

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-7	Feed		V-8		
	Btms	Toluene		Btms		
SAMPLE POINT	Sx-39	Sx-40		*Calc.		
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100°C @ 1.6 Torr)	18.23	98.70		23.94		
Solvent - (100-230°C @ 1.6 Torr)	75.80	1.30		15.75		
Heavy Oil - (230-255°C @1.6 Torr)	5.70					
SRL				3.73		
Coal (MAF)				24.60		
Ash				31.98		
Water	0.27	0.27				
Phenol						
TOTAL	100	100		100		
Pyridine Solubles (Wt % Ash free)				57.51		
Melting Point °F						
Specific Gravity 60/60	1.033					
Viscosity, cp	22.7					

Carbon	86.44	91.24		55.84		
Hydrogen	7.89	8.69		4.77		
Nitrogen	0.22			0.30		
Sulfur	1.45	0.02		0.59		
Oxygen (by diff)	4.00	0.05		6.52		
Ash				31.98		
TOTAL	100	100		100		
Number of Sample Avg.	2	2		-		

\*Analysis calculated by material balance around the deashing unit.

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/22/77

Run No: M-33C  
Date: 6/23-24/77  
Time: 1430-0230

MOLE PERCENT

SAMPLE DESCRIPTION	Product	Feed	S-4A	J-1		
	Gas	Gas	Ovhd	Disch.		
SAMPLE POINT	Sx-19	Sx-21	Sx-30	Sx-32		
Hydrogen - H <sub>2</sub>	46.53	51.11	26.11	19.10		
Carbon Monoxide - CO	22.46	48.89	14.20	9.81		
Carbon Dioxide - CO <sub>2</sub>	24.33		48.68	59.85		
Hydrogen Sulfide - H <sub>2</sub> S	0.40		2.35			
Methane - CH <sub>4</sub>	4.80		4.38	4.92		
Ethane - C <sub>2</sub> H <sub>6</sub>	1.01		2.09	3.28		
Propane - C <sub>3</sub> H <sub>8</sub>	0.45		1.95	3.04		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)	0.02		0.24			
Light Oils - (0-100°C @ 1.6 Torr)						
Solvent - (100-230°C @ 1.6 Torr)						
Heavy Oil - (230-255°C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100		
Mole Wt (Calc)	19.33	14.71	28.94	32.57		
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2		

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: M-33C  
DATE: 6/23-24/77  
TIME: 1430-0230

SAMPLE DESCRIPTION	F-1 Btms	Makeup Solv	F-3 Btms	Feed Solv	S-8 Oil
SAMPLE POINT	Sx-2	Sx-8	Sx-12	Sx-14	Sx-16
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR		5	5	5	
IBP		70.2	89.5	70.2	
5%		121.0	114.2	98.8	
10%		142.6	116.0	114.8	
20%		185.2	123.6	137.8	
30%		188.8	131.6	162.0	
40%		191.0	145.4	168.6	
50%		196.2	160.4	183.3	
60%		203.0	173.4	189.2	
70%		212.0	182.4	195.6	
80%		230.0	190.6	203.6	
90%		248.6	206.8	223.8	
95%		260.0	222.2	231.0	
DRY PT.			222.2	231.0	
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR					744
IBP					79
5%					99
10%					130
20%					152
30%					168
40%					184
50%					191
60%					199
70%					208
80%					216
90%					223
95%					-
DRY PT.					216
ASPHALTENE TEST					
WT % ASH	0.18				
WT % UNCONVERTED COAL	-				
WT % PRE-ASPHALTENES	21.20				
WT % ASPHALTENES	36.46				
WT % MALTENES & DIST. OIL	42.16				
TOTAL	100.00				
SAYBOLT VISCOSITY, SSU					
100° F		16.1	11.1	12.7	
210° F		8.8	8.6	8.7	
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)		0.29	0.00	0.21	1.16
INFRARED RATIO					
SP. GRAV. 60/60 F		1.038	1.008	1.034	

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION, USUALLY LESS THAN 5% FOR THE F-1 VACUUM BOTTOMS MATERIAL

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: M-33C  
DATE: 6/23-24/77  
TIME: 1430-0230

SAMPLE DESCRIPTION	V-9 Btms	Cold TRap	S-7 Btms	S-4A Oil	Recycle Solv
SAMPLE POINT	Sx-28	Sx-33	Sx-34	Sx-37	Sx-39
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR	5		5		5
IBP	123.0		81.0		63.6
5%	170.0		106.5		95.4
10%	180.0		121.0		114.8
20%	188.5		144.7		136.5
30%	195.0		169.3		158.6
40%	204.0		178.3		170.8
50%	213.0		185.0		179.5
60%	225.0		191.0		184.3
70%	245.0		199.0		192.8
80%	260.0		209.0		200.6
90%			229.0		223.0
95%					239.3
DRY PT.			229.0		239.3
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR		742		742	
IBP		69		80	
5%		78		164	
10%		96		190	
20%		125		200	
30%		146		208	
40%		162		212	
50%		176		217	
60%		187		231	
70%		193		268	
80%		201		308	
90%		211		336	
95%					
DRY PT.		215		340	
ASPHALTENE TEST					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
SAYBOLT VISCOSITY, SSU					
100° F					11.8
210° F					8.6
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)		0.90			0.27
INFRARED RATIO					
SP. GRAV. 60/60 F				0.960	1.033

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION. USUALLY LESS THAN 5% FOR THE F-1 VACUUM BOTTOMS MATERIAL

PROJECT LIGNITE  
 SAMPLE ANALYSES  
 RUN NO: M-33C  
 DATE: 6/23-24/77  
 TIME: 1430-0230

SAMPLE DESCRIPTION	Deashing Solv.			
SAMPLE POINT	Sx-40			
ASTM D-1160 DISTILLATION DATA				
PRESSURE, TORR				
IBP				
5%				
10%				
20%				
30%				
40%				
50%				
60%				
70%				
80%				
90%				
95%				
DRY PT.				
ASTM D-86 DISTILLATION DATA				
BAROMETRIC PRESSURE, TORR	744			
IBP	111			
5%	112			
10%	112			
20%	112			
30%	112			
40%	112			
50%	112			
60%	112			
70%	112			
80%	113			
90%	114			
95%				
DRY PT.	130			
ASPHALTENE TEST				
WT % ASH				
WT % UNCONVERTED COAL				
WT % PRE-ASPHALTENES				
WT % ASPHALTENES				
WT % MALTENES & DIST. OIL				
TOTAL				
SAYBOLT VISCOSITY, SSU				
100° F				
210° F				
MISCELLANEOUS				
KF H <sub>2</sub> O WT% (Raw Sx)				
INFRARED RATIO				
SP. GRAV. 60/60 F	0.867			

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
 ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
 MALTENES-N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
 DISTILLABLE OIL - RECOVERABLE BY DISTILLATION. USUALLY LESS THAN 5% FOR THE F-1 VACUUM BOTTOMS MATERIAL





PROJECT: LIGNITE  
 MEASURED MATERIAL BALANCE  
 Updated: 12/22/77

Run No: M-33C  
 Date: 6/23/77  
 Time: 1430-0230

MATERIAL OUT

Temperature: 741°F  
 Pressure: 2500 psig  
 LHSV 1.49  
 GHSV: 301

lbs/hour

STREAM DESCRIPTION					Total Out
SAMPLE POINT					
Hydrogen - H <sub>2</sub>					1.12
Carbon Monoxide - CO					7.69
Carbon Dioxide - CO <sub>2</sub>					14.65
Hydrogen Sulfide - H <sub>2</sub> S					0.23
Methane - CH <sub>4</sub>					0.96
Ethane - C <sub>2</sub> H <sub>6</sub>					0.42
Propane - C <sub>3</sub> H <sub>8</sub>					0.33
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					
Ammonia - NH <sub>3</sub>					0.02
Light Oil - (0-100°C @ 1.6 Torr)					106.16
Solvent - (100-230°C @ 1.6 Torr)					68.98
Heavy Oil - (230-255°C @1.6 Torr)					4.20
SRL					14.27
Coal (MAF)					
Ash					0.03
Water					14.97
Phenol					
TOTAL					234.03

Carbon					180.58
Hydrogen					19.11
Nitrogen					0.33
Sulfur					1.61
Oxygen (by diff)					32.37
Ash					0.03
TOTAL					234.03


RUN CONDITIONS

RUN NO. M-33D  
 DATE MADE 6/24/77

TEMPERATURE °F		PRESSURE, psig
PREHEATER E-I	PREHEATER E-I3	SEPARATORS S-1 and S-2
SAND BATH <u>756</u>	DOWTHERM <u>571</u>	<u>2500</u>
INLET <u>266</u>	INLET <u>82</u>	SEPARATOR S-3
OUTLET <u>749</u>	OUTLET <u>479</u>	<u>300</u>
DISSOLVERS	LIGHT ENDS COLUMN, F-2	SEPARATORS S-4A and S-4B
R-1A (1) _____	REBOILER <u>416</u>	<u>60</u>
(2) _____	LOWER SECTION <u>502</u>	VACUUM FLASH, F-1
(3) _____	FEED SECTION <u>424</u>	<u>15 Torr</u>
(4) _____	OVERHEAD <u>193</u>	LIGHT ENDS COLUMN, F-2
R-1B (1) <u>768</u>	S-8 <u>83</u>	<u>0</u>
(2) <u>804</u>	S-9 _____	SOLVENT COLUMN, F-3
(3) <u>806</u>		<u>NIU</u>
(4) <u>828</u>		HEAVY ENDS COLUMN, F-4
REACTOR PRODUCT SEPARATORS	SOLVENT COLUMN, F-3	<u>NIU</u>
S-1 <u>607</u>	REBOILER <u>NIU</u>	VACUUM FLASH, F-0
S-2 <u>73</u>	LOWER SECTION _____	<u>NIU</u>
S-3 <u>492</u>	FEED SECTION _____	SETTLING TOWER, V-8
S-4A <u>81</u>	OVERHEAD _____	<u>NIU</u>
S-4B <u>79</u>		RECOVERY TOWER, V-7
PREHEATER E-II	HEAVY ENDS COLUMN, F-4	<u>NIU</u>
DOWTHERM <u>685</u>	REBOILER <u>NIU</u>	
INLET <u>434</u>	LOWER SECTION _____	
OUTLET <u>657</u>	FEED SECTION _____	
VACUUM FLASH F-1	OVERHEAD _____	
OVERHEAD VAPOR <u>523</u>	VACUUM FLASH, F-0	
UPPER WALL <u>616</u>	OVERHEAD <u>NIU</u>	
LOWER WALL <u>619</u>	BOTTOMS _____	
DOWNCOMER <u>456</u>	PRECIPITATION TOWER, V-8	
CONDENSATE	ZONE (1) <u>NIU</u>	
ACCUMULATOR, S-7 <u>86</u>	(2) _____	
	(3) _____	
	RECOVERY TOWER V-9	
	REBOILER <u>NIU</u>	
	OVERHEAD _____	

	Start	End	Run No: M-33D
Date of Run	6/24/77	6/24/77	Units: lbs/hr; °F, Psig
Time of Run	0230	1430	Prep. By BCL & GGB
Length of Run	12	hours	Up. H. Fed: 12/19/77
Hours on Coal at End of Y. P.	83.0		

### MASS RATES AND RUN CONDITIONS



149.56 TOTAL

☒ OPEN

☒ CLOSED

TOTAL 149.56

Numbers in parentheses are not included in the totals.

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE  
Normalized

Run No: M-33D  
Date: 6/24/77  
Time: 0230-1430

SUMMARY

Temperature: 749°F  
Pressure: 2500 psig  
LHSV: 1.43  
GHSV: 306

lbs/hour

STREAM DESCRIPTION	Total In	Total Out	Net Yield		Wt % MAF Lignite	
SAMPLE POINT						
Hydrogen - H <sub>2</sub>	1.16	1.24	0.08	}		
Carbon Monoxide - CO	15.97	9.08	-6.89			
Carbon Dioxide - CO <sub>2</sub>		13.86	13.86			
Hydrogen Sulfide - H <sub>2</sub> S		0.36	0.36			
Methane - CH <sub>4</sub>		0.93	0.93			
Ethane - C <sub>2</sub> H <sub>6</sub>		0.37	0.37		8.95	39.15
Propane - C <sub>3</sub> H <sub>8</sub>		0.21	0.21			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>		0.03	0.03			
Light Oil - (0-100°C @ 1.6 Torr)	5.89	9.79	3.90	}		
Solvent - (100-230°C @ 1.6 Torr)	77.49	78.08	0.59		14.18	62.03
Heavy Oil - (230-255°C @ 1.6 Torr)	7.00	6.54	-0.46			
SRL		10.15	10.15			
Coal (MAF)	22.86	2.44	-20.42		-89.32	
Ash	3.92	3.18	-0.74		-3.24	
Water	15.27	13.30	-1.97		-8.62	
Phenol						
TOTAL	149.56	149.56	-0-			
Carbon	102.16	101.70	-0.46			
Hydrogen	11.17	11.71	0.54			
Nitrogen	0.37	0.44	0.07			
Sulfur	1.96	1.91	-0.05			
Oxygen (by diff)	29.98	30.62	0.64			
Ash	3.92	3.18	-0.74			
TOTAL	149.56	149.56	-0-			

PROJECT LIGNITE  
ADJUSTED & MEASURED MATERIAL BALANCE  
Updated: 12/19/77

Run No: M-33D  
Date: 6/24/77  
Time: 0230-1430

MATERIAL IN

Temperature: 749°F  
Pressure: 2500 psig  
LHSV: 1.43  
GHSV: 306

		lbs/hour				
STREAM DESCRIPTION	Feed Gas	Lignite	Feed Solvent			Total In
SAMPLE POINT	Sx-21	Sx-1	Sx-14			
Hydrogen - H <sub>2</sub>	1.16					1.16
Carbon Monoxide - CO	15.97					15.97
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)			5.89			5.89
Solvent - (100-230°C @ 1.6 Torr)			77.49			77.49
Heavy Oil - (230-255°C @ 1.6 Torr)			7.00			7.00
SRL						
Cool (MAF)		22.86				22.86
Ash		3.92				3.92
Water		15.11	0.16			15.27
Phenol						
<b>TOTAL</b>	<b>17.13</b>	<b>41.89</b>	<b>90.54</b>			<b>149.56</b>

Carbon	6.85	15.95	79.36			102.16
Hydrogen	1.16	2.83	7.18			11.17
Nitrogen		0.21	0.16			0.37
Sulfur		0.30	1.66			1.96
Oxygen (by diff)	9.12	18.68	2.18			29.98
Ash		3.92				3.92
<b>TOTAL</b>	<b>17.13</b>	<b>41.89</b>	<b>90.54</b>			<b>149.56</b>

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE  
Normalized  
Updated: 12/19/77

Run No: M-33D  
Date: 6/24/77  
Time: 0230-1430

MATERIAL OUT

Temperature: 749°F  
Pressure: 2500 psig  
LHSV: 1.43  
GHSV: 306

		lbs/hour					
Quantitative	STREAM DESCRIPTION	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
	SAMPLE POINT	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
	Hydrogen - H <sub>2</sub>	1.15	0.08				0.01
	Carbon Monoxide - CO	8.33	0.67				0.08
	Carbon Dioxide - CO <sub>2</sub>	11.43	1.97				0.46
	Hydrogen Sulfide - H <sub>2</sub> S	0.29	0.07				
	Methane - CH <sub>4</sub>	0.84	0.08				0.01
	Ethane - C <sub>2</sub> H <sub>6</sub>	0.29	0.06				0.02
	Propane - C <sub>3</sub> H <sub>8</sub>	0.14	0.05				0.02
	Butane - C <sub>4</sub> H <sub>10</sub>						
	Nitrogen - N <sub>2</sub>						
	Ammonia - NH <sub>3</sub>	0.02		0.01			
	Light Oil - (0-100°C @ 1.6 Torr)			0.26		3.53	
	Solvent - (100-230°C @ 1.6 Torr)			0.25		1.06	
	Heavy Oil - (230-255°C @ 1.6 Torr)			0.03			
	SRL						
	Coal (MAF)						
	Ash						
	Water			11.01		1.73	
	Phenol						
	TOTAL	22.49	2.98	11.56	Negl	6.32	0.60
Elemental	Carbon	7.67	0.97	0.45		4.02	0.20
	Hydrogen	1.46	0.12	1.27		0.65	0.02
	Nitrogen	0.01	0.01	0.01		0.03	
	Sulfur	0.27	0.07	0.01		0.05	
	Oxygen (by diff)	13.08	1.81	9.82		1.57	0.38
	Ash						
	TOTAL	22.49	2.98	11.56	Negl.	6.32	0.60

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized  
 Updated: 12/19/77

Run No: M-33D  
 Date: 6/24/77  
 Time: 0230-1430

MATERIAL OUT

Temperature: 749°F  
 Pressure: 2500 psig  
 LHSV: 1.43  
 GHSV: 306

		lbs/hour				
Quantitative	STREAM DESCRIPTION	Cold Trap	F-1 Btms	← Recycle S-7 Btms	Solvent → F-2 Btms	Total Out
	SAMPLE POINT	Sx-33	Sx-2	Sx-39	Sx-12	
	Hydrogen - H <sub>2</sub>					1.24
	Carbon Monoxide - CO					9.08
	Carbon Dioxide - CO <sub>2</sub>					13.86
	Hydrogen Sulfide - H <sub>2</sub> S					0.36
	Methane - CH <sub>4</sub>					0.93
	Ethane - C <sub>2</sub> H <sub>6</sub>					0.37
	Propane - C <sub>3</sub> H <sub>8</sub>					0.21
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					
	Ammonia - NH <sub>3</sub>					0.03
	Light Oil - (0-100°C @ 1.6 Torr)	0.06		4.44	1.50	9.79
	Solvent - (100-230°C @ 1.6 Torr)	0.14		53.69	22.94	78.08
	Heavy Oil - (230-255°C @1.6 Torr)	0.01		5.62	0.88	6.54
	SRL		10.15			10.15
	Coal (MAF)		2.44			2.44
	Ash		3.18			3.18
	Water	0.47		0.09		13.30
	Phenol					
	<b>TOTAL</b>	<b>0.68</b>	<b>15.77</b>	<b>63.84</b>	<b>25.32</b>	<b>149.56</b>
Elemental	Carbon	0.18	10.72	55.21	22.28	101.70
	Hydrogen	0.07	0.71	5.20	2.21	11.71
	Nitrogen		0.14	0.17	0.07	0.44
	Sulfur		0.14	1.05	0.32	1.91
	Oxygen (by diff)	0.43	0.88	2.21	0.44	30.62
	Ash		3.18			3.18
	<b>TOTAL</b>	<b>0.68</b>	<b>15.77</b>	<b>63.84</b>	<b>25.32</b>	<b>149.56</b>

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/19/77

Run No: M-33D

Date: 6/24/77

Time: 0230-1430

WEIGHT PERCENT

SAMPLE DESCRIPTION	Lignite	F-1 Btms	Makeup Solvent	F-3 Btms	Feed Solvent	S-8 Oil
	Sx-1	Sx-2	Sx-8	Sx-12	Sx-14	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100°C @ 1.6 Torr)			5.01	5.93	6.51	73.40
Solvent - (100-230°C @ 1.6 Torr)			84.50	90.60	85.58	22.05
Heavy Oil - (230-255°C @1.6 Torr)			10.20	3.47	7.73	
SRL		64.36				
Coal (MAF)	54.56	15.47				
Ash	9.36	20.17				
Water	36.08		0.29		0.18	4.55
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		80.62				
Melting Point °F		319				
Specific Gravity 60/60			1.038	1.007	1.043	
Viscosity, cp			57.4	17.5	40.42	

Carbon	38.09	68.00	87.58	88.00	87.65	83.73
Hydrogen	6.75	4.51	8.18	8.73	7.93	9.98
Nitrogen	0.50	0.86	0.12	0.27	0.18	0.53
Sulfur	0.71	0.90	2.00	1.27	1.83	1.14
Oxygen (by diff)	44.59	5.56	2.12	1.73	2.41	4.62
Ash	9.36	20.17				
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated:12/19/77

Run No: M-33D

Date: 6/24/77

Time: 0230-1430

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-8	S-8	Product	Feed	S-4B	S-4B
	Water	Total	Gas	Gas	Oil	Water
SAMPLE POINT	Sx-16	Sx-16	Sx-19	Sx-21	Sx-23	Sx-23
Hydrogen -H <sub>2</sub>			5.12	6.79		
Carbon Monoxide-CO			37.05	93.21		
Carbon Dioxide-CO <sub>2</sub>			50.83			
Hydrogen Sulfide-H <sub>2</sub> S			1.28			
Methane-CH <sub>4</sub>			3.73			
Ethane-C <sub>2</sub> H <sub>6</sub>			1.31			
Propane-C <sub>3</sub> H <sub>8</sub>			0.61			
Butane-C <sub>4</sub> H <sub>10</sub>						
Nitrogen-N <sub>2</sub>						
Ammonia-NH <sub>3</sub> (PPM)			0.07			0.10
Light Oils-(0-100°C @ 1.6 Torr)		55.81			47.83	
Solvent-(100-230°C @ 1.6 Torr)		16.76			47.37	
Heavy Oil-(230-255°C @1.6 Torr)					4.81	
SRL						
Coal (MAF)						
Ash						
Water	100	27.43				99.90
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon		63.66	34.09	39.95	84.89	
Hydrogen	11.11	10.25	6.51	6.79	8.76	11.12
Nitrogen		0.40	0.06		0.22	0.08
Sulfur		0.87	1.20		1.36	
Oxygen (by diff)	88.89	24.82	58.14	53.26	4.77	88.80
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/19/77

Run No: M-33D

Date: 6/24/77

Time: 0230-1430

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4B	S-4A	J-1	Cold	Recycle	
	Total	Ovhd	Dish.	Trap	Solvent	
SAMPLE POINT	Sx-23	Sx-30	Sx-32	Sx-33	Sx-39	
Hydrogen - H <sub>2</sub>		2.60	1.49			
Carbon Monoxide - CO		22.33	13.87			
Carbon Dioxide - CO <sub>2</sub>		65.98	76.77			
Hydrogen Sulfide - H <sub>2</sub> S		2.29				
Methane - CH <sub>4</sub>		2.74	2.48			
Ethane - C <sub>2</sub> H <sub>6</sub>		2.05	2.65			
Propane - C <sub>3</sub> H <sub>8</sub>		1.74	2.74			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>		0.17				
Ammonia - NH <sub>3</sub> (PPM)	0.10	0.10				
Light Oils - (0-100°C @ 1.6 Torr)	2.21			8.48	6.96	
Solvent - (100-230°C @ 1.6 Torr)	2.19			21.08	84.10	
Heavy Oil - (230-255°C @1.6 Torr)	0.22			1.69	8.80	
SRL						
Coal (MAF)						
Ash						
Water	95.28			68.75	0.14	
Phenol						
TOTAL	100	100	100	100	100	
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60					1.048	
Viscosity, cp					43.30	

Carbon	3.92	32.68	33.10	26.51	86.48	
Hydrogen	11.01	4.16	3.14	10.26	8.15	
Nitrogen	0.09	0.25		0.10	0.27	
Sulfur	0.06	2.16		0.52	1.64	
Oxygen (by diff)	84.92	60.75	63.76	62.61	3.46	
Ash						
TOTAL	100	100	100	100	100	
Number of Sample Avg.	2	2	2	2	2	

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/19/77

Run No: M-33D

Date: 6/24/77

Time: 0230-1430

MOLE PERCENT

SAMPLE DESCRIPTION	Product Gas	Feed Gas	S-4A Ovh'd	J-1 Disch.		
	Sx-19	Sx-21	Sx-30	Sx-32		
Hydrogen - H <sub>2</sub>	47.66	50.50	32.89	22.62		
Carbon Monoxide - CO	24.64	49.50	20.16	15.06		
Carbon Dioxide - CO <sub>2</sub>	21.51		37.90	53.03		
Hydrogen Sulfide - H <sub>2</sub> S	0.70		1.70			
Methane - CH <sub>4</sub>	4.34		4.32	4.72		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.81		1.73	2.68		
Propane - C <sub>3</sub> H <sub>8</sub>	0.26		1.00	1.89		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>			0.15			
Ammonia - NH <sub>3</sub> (PPM)	0.08		0.15			
Light Oils - (0-100° C @ 1.6 Torr)						
Solvent - (100-230° C @ 1.6 Torr)						
Heavy Oil - (230-255° C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100		
Mole Wt (Calc)	18.62	14.87	25.27	30.39		
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Elemental	Quantitative					
	Product Gas	Feed Gas	S-4A Ovh'd	J-1 Disch.		
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2		

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: M-44D  
DATE: 6/24/77  
TIME: 0230-1430

SAMPLE DESCRIPTION	F-1 Btms	Makeup Solv	LEC Btms	Feed Solv.	Cold trap	011
SAMPLE POINT	Sx-2	Sx-8	Sx-12	Sx-14	Sx-33	
ASTM D-1160 DISTILLATION DATA						
PRESSURE, TORR		5	5	5		
IBP		70.2	105.0	80.0		
5%		121.0	117.5	108.5		
10%		142.6	120.0	121.0		
20%		185.2	127.0	150.8		
30%		188.8	140.0	169.8		
40%		191.0	143.0	178.0		
50%		196.2	157.0	185.2		
60%		203.0	172.3	191.6		
70%		212.0	181.0	199.0		
80%		230.0	188.6	207.3		
90%		248.6	201.0	239.6		
95%		260.0	218.0	260.0		
DRY PT.						
ASTM D-86 DISTILLATION DATA						
BAROMETRIC PRESSURE, TORR						747
IBP						86
5%						98
10%						100
20%						101
30%						102
40%						103
50%						105
60%						256
70%						310
80%						336
90%						348
95%						-
DRY PT.						350
ASPHALTENE TEST						
WT % ASH		20.17				
WT % UNCONVERTED COAL		15.47				
WT % PRE-ASPHALTENES		20.63				
WT % ASPHALTENES		24.44				
WT % MALTENES & DIST. OIL		19.29				
TOTAL		100.00				
SAYBOLT VISCOSITY, SSU						
100° F			16.1	11.3	13.4	
210° F			8.8	9.1	8.9	
MISCELLANEOUS						
KF H <sub>2</sub> O WT% (Raw Sx)			0.29		0.18	68.75
INFRARED RATIO						
SP. GRAV. 60/60 F			1.038	1.008	1.043	

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES - BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES - N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION, USUALLY LESS THAN 5% FOR THE F-1 VACUUM BOTTOMS MATERIAL

PROJECT LIGNITE  
 SAMPLE ANALYSES  
 RUN NO: M-33D  
 DATE: 6/24/77  
 TIME: 0230-1430

SAMPLE DESCRIPTION	S-7 Btms	S-4A Btms			
SAMPLE POINT	Sx-34/39	Sx-37			
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR	5				
IBP	72.6				
5%	111.6				
10%	128.2				
20%	155.3				
30%	172.6				
40%	181.6				
50%	186.6				
60%	193.2				
70%	200.4				
80%	211.2				
90%	236.4				
95%	260.0				
DRY PT.					
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR		749			
IBP		80			
5%		127			
10%		172			
20%		204			
30%		221			
40%		231			
50%		239			
60%		251			
70%		281			
80%		315			
90%		338			
95%		-			
DRY PT.		342			
ASPHALTENE TEST					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
SAYBOLT VISCOSITY, SSU					
100° F	14.3				
210° F	8.8				
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)	0.14				
INFRARED RATIO					
SP. GRAV. 60/60 F	1.048	0.953			

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
 ASPHALTENES - BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
 MALTENES - N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
 DISTILLABLE OIL - RECOVERABLE BY DISTILLATION, USUALLY LESS THAN 5% FOR THE F-1 VACUUM BOTTOMS MATERIAL



PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Updated: 12/19/77

Run No: M-33D  
Date: 6/24/77  
Time: 0230-1430

MATERIAL OUT

Temperature: 749°F  
Pressure: 2500 psig  
LHSV: 1.43  
GHSV: 306

lbs/hour

STREAM DESCRIPTION	Cold Trap	F-1 Btms	←Recycle Solvent→		Total Out
			S-7 Btms	F-2 Btms	
SAMPLE POINT	Sx-33	Sx-2	Sx-39	Sx-12	
Hydrogen - H <sub>2</sub>					1.19
Carbon Monoxide - CO					8.76
Carbon Dioxide - CO <sub>2</sub>					13.37
Hydrogen Sulfide - H <sub>2</sub> S					0.35
Methane - CH <sub>4</sub>					0.90
Ethane - C <sub>2</sub> H <sub>6</sub>					0.36
Propane - C <sub>3</sub> H <sub>8</sub>					0.20
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					
Ammonia - NH <sub>3</sub>					0.04
Light Oil - (0-100°C @ 1.6 Torr)	0.06		4.44	1.50	9.66
Solvent - (100-230°C @ 1.6 Torr)	0.14		53.69	22.94	78.03
Heavy Oil - (230-255°C @ 1.6 Torr)	0.01		5.62	0.88	6.54
SRL		9.80			9.80
Cool (MAF)		2.35			2.35
Ash		3.07			3.07
Water	0.45		0.09		12.84
Phenol					
TOTAL	0.66	15.22	63.84	25.32	147.46

Carbon	0.18	10.35	55.21	22.28	100.87
Hydrogen	0.07	0.69	5.20	2.21	11.59
Nitrogen	-	0.13	0.17	0.07	0.42
Sulfur	-	0.14	1.05	0.32	1.88
Oxygen (by diff)	0.41	0.84	2.21	0.44	29.63
Ash		3.07			3.07
TOTAL	0.66	15.22	63.84	25.32	147.46

## Appendix C

### Process Development Unit Run L-1 July 10 - August 6, 1977

Run L-1 was the first in a series of three runs, each to involve 28 days of continuous operation. The purpose of the run was to test plant operability for extended periods of coal processing and to determine the effects of solvent recycle on liquefaction yields. In addition, the solid-liquids separation unit was intermittently on-stream in an effort to produce a substantial quantity of low-ash solvent refined lignite.

Nominal run conditions were those thought to be optimum for minimizing gas and maximizing SRL yields when processing lignite mined near Zap, North Dakota. The maximum reaction temperature in the liquefaction reactor was nominally controlled at 820-840°F with the reactor operating at 2500 psig pressure. Coal and solvent charge rates to the Process Development Unit were equivalent to those used for the unit's design i.e. 50 lbs/hr coal feed - 93 lbs/hr solvent feed. One reactor volume, about 1.4 cubic feet, was used throughout the run and all recoverable organic liquids boiling above 300°F were recycled. The gas charge rate averaged about 9.4 standard cubic feet per pound of raw coal fed and the gas consisted of equal parts hydrogen and carbon monoxide. All product gases were measured, sampled, and oxidized. The product deashing section of the PDU was operated at 300 psig and 450°F using toluene as the deashing solvent. The solvent to charge slurry ratio was nominally four to one by volume.

Operating difficulties during Run L-1, exclusive of those attributable to wear and tear of process machinery, fall into three broad categories: (1) F-1 vacuum bottoms withdrawal; (2) Solids buildup in the liquefaction reactor and process lines and (3) Solvent recovery.

Problems with the vacuum bottoms withdrawal system were basically two - product solidification and buildup. Solidification of product within the vacuum flash drum leg occurred on two separate occasions and was caused by non-uniform heat tracing in the vicinity of the vacuum lockout valves in one case and by heat tracing element burn out in the second. Product solidification within the vacuum flash vessel leg was relatively easy to avoid by careful temperature monitoring and control, provided the conversion of coal to pyridine soluble material was sufficiently high so that the vacuum bottoms melting point remained below 450°F.

The second problem with the vacuum flash tower and with the bottoms withdrawal system in particular was solids buildup

on the walls of the bottoms drawoff leg and the vessel proper. This buildup seems to result via two mechanisms. First, localized coking with the coked material acting as an initiator for further buildup, and, second, adhesion to the walls of a very thick, sandy like material which is relatively high in ash and unconverted coal. This material may result when solids are burped from the liquefaction reactor and then carried through the system, flowing relatively easily when diluted with hot process solvent but becoming very viscous when the solvent is removed. This material characteristically exhibits a melting point in excess of 500°F. These high melting point solids may also result when solids accumulations in the liquefaction reactor is sufficient to decrease residence time and suppress conversion.

This leads to the second major problem in extended unit operations; that is, solids buildup in the liquefaction reactor and associated high pressure piping.

During Run L-1, coal processing operations were temporarily interrupted when the high pressure tubing between dissolver R-1B and the high pressure flash separator S-1 plugged. Prior to this incident, and after approximately 76 hours of coal feed to the dissolver, the pressure within the reactor began increasing slowly. The pressure drop measured between the dissolver outlet and the high pressure flash separator increased to between 300 and 400 psig indicating material buildup in the 5/16 inch ID tubing connecting these two vessels. While coal feed was cut out, efforts to clear the line by flushing with solvent proved ineffective, so coal processing was resumed and continued for approximately another 85 hours, after which time the line plugged and operations were switched to the standby reactor R-1A. Reactor R-1A was used for the remainder of the run and afterwards was disassembled and cleaned. Disassembly revealed that reactor R-1A was also partially plugged with the plug thickness varying up to perhaps 2-inches at places in the 3-5/8-inch ID vessel. This decrease in volume, with the corresponding decrease in residence time, may be responsible for the lower temperature gradients resulting from lower conversions, which correspondingly produced the higher melting point vacuum bottoms seen near the end of the run. The air cooler tubing from the top of reactor R-1A to separator S-1 was found to have uniform deposits about 1/16-inch in thickness, reducing the internal diameter from 5/16-inch to 3/16-inch. The deposits were initially black, but became light tan or white upon heating, without a noticeable decrease in volume. A rough analysis of the deposits after heating, conducted by the Grand Forks Energy Research Center with an electron micro-probe, indicated the approximate distribution of the major components. This analysis with the major constituents calculated as oxides and normalized to 100 percent, is compared with a typical X-ray fluorescence analysis of the

Zap lignite ash in the table below:

	Tubing Deposits	Zap Lignite Ash
Na <sub>2</sub> O	11.9	6.7
MgO	21.8	6.8
CaO	16.7	26.7
Fe <sub>2</sub> O <sub>3</sub>	8.2	10.0
Al <sub>2</sub> O <sub>3</sub>	31.8	10.5
SiO <sub>2</sub>	2.9	20.2
SO <sub>3</sub>	6.7	17.2
Other	-	1.9

An analysis by X-ray diffraction of the tubing deposits indicated the presence of magnesium oxide, but no calcium carbonate. There are obvious differences between the compositions of lignite ash and the tubing deposits, but no firm conclusions as to the cause of fouling have been reached. Reactor R-1A was used intermittently throughout Run L-1 without cleaning the product cooling line. During its use, coal was processed for approximately 204 hours as compared to 161 hours of coal processing before dissolver R-1B plugged.

The third major problem associated with extended PDU operations is solvent recovery. Data from Run L-1 indicate that on the average about 4 percent more organic liquid is generated than charged; but throughout the run an average of only 90 percent was actually recovered and recycled. The 14 percent oil loss occurred mainly in three areas. First, some of the solvent remains with the F-1 vacuum bottoms. A good vacuum bottoms product with a melting point around 350°F contains roughly 9.8 weight percent solvent. This translated into percent of charge solvent amounts to 2.7 percent when the charge solvent to feed coal ratio is 1.86.

The second area of solvent loss is the separation system for waste water and S-4A light oil streams. On the average, the waste water stream contained about 11.4 weight percent oil during Run L-1. Efficiency of the gravimetric separation system varied substantially throughout the run. In some cases only trace amounts of oil were present in the waste water while at other times this stream contained as much as 25 or 30 percent oil. The oil lost in this way amounted to 1.9 percent of the charge solvent. Solvent losses of this nature can be easily remedied in a larger scale plant by incorporating a relatively larger settling or separation volume to provide a longer settling time.

The third area of solvent loss was with the light ends column. Because of the column's small size, heat losses in the area of the top flange and light oil draw off port would at times cause excessive condensation of oil vapor resulting in the column flooding. In this state, the distillation column overhead

contained substantial quantities of recycleable oil. The problem was worsened by water in the feed to the distillation column which results in solvent range oil going overhead because of steam distillation.

During Run L-1 nine data periods, each of a nominal 12 hours duration, were completed and quantitative material balances made. In addition elemental balances were made for two of the nine yield periods and are included in their respective workups. All nine material balance workups, including sample analyses, ASTM D-86 and D-1160 distillation data and average run conditions, are attached.

Material balance closures varied from 98.1 percent in data period L-1D to 101.3 percent in yield period L-1H. In all nine cases, the outgoing product streams were normalized to provide 100 percent recovery. In addition, in yield period L-1E where elemental balances were available, a forced carbon balance was made by adjusting the oil-water ratio of the waste water stream; and in yield periods L-1J and L-1K, for which only poor samples of the V-8 bottoms were available, the V-8 bottoms compositions were calculated by making material balances around the deashing unit assuming an ash loss equal to that of the average ash loss of the L-1 yield periods made without the deashing unit on stream.

A comparison of the nine material balance periods after adjustment is shown on the following page. Also included in the comparison is a tenth column showing the average of all the L-1 data periods.

Conversion of MAF lignite to gas, oil and SRL varied from 88 to 99.2 weight percent with the overall average being 92.2 percent. During the early yield periods of Run L-1, the pyridine soluble material content of the F-1 vacuum bottoms appeared unusually high and the pyridine extraction and ash tests were repeated in triplicate on each sample. Essentially the same results were obtained, confirming the initial tests. It is not known why such high (above 93%) MAF lignite conversions were obtained in some of the data periods, but it is felt that those yield periods where conversions were above 93% should not be viewed as representative of expected results in the solvent refining of lignite.

Net gas yields were within the range anticipated for the reaction conditions employed. They varied from 27 to 40 percent with the average close to 31 weight percent of the MAF lignite charged. The average net hydrocarbon liquid yield averaged about 66 weight percent of the MAF lignite fed and was typical of previous results obtained at similar conditions. The breakdown of the hydrocarbon liquid yield into its distillable oil and SRL components was 20 and 80 percent, respectively.

Table 1

## Process Development Unit Run L-1

Yield Period	L-1B	L-1C	L-1D	L-1E	L-1F	L-1H	L-1I	L-1J	L-1K	L-1 Average
Reactor in Use	R-1B	R-1B	R-1B	R-1B	R-1A	R-1A	R-1A	R-1A	R-1A	-
SLS System in Use	No	No	No	No	Yes	No	No	Yes	Yes	-
LHSV	1.38	1.44	1.41	1.46	1.44	1.43	1.41	1.40	1.42	1.42
GHSV	330	342	318	304	323	328	328	341	336	328
Solvent/MAF Coal Ratio	3.16	3.02	2.96	3.03	3.00	2.89	2.82	2.87	2.91	2.96
H <sub>2</sub> /CO Mol Ratio	1.16	1.13	1.11	1.11	1.16	1.19	1.11	1.11	1.12	1.13
Temperature, °F										
Preheater Outlet, E-1	717	715	718	721	715	736	741	754	757	730
Reactor 3 ft	757	757	745	742	770	745	746	755	758	753
Reactor 7 ft	797	798	798	794	811	761	762	772	774	785
Reactor 11 ft	806	806	782	782	804	770	764	771	773	784
Reactor 15 ft	827	829	824	822	828	823	824	815	804	822
Max. Reaction	827	829	824	822	828	823	824	815	804	822
Vacuum Flash Ovhd	526	526	530	528	507	505	504	508	504	515
Dissolver Pressure, psig	2500	2500	2500	2500	2500	2500	2500	2500	2500	2500
Solvent Recycle, %										
Actual	89.7	95.0	93.4	91.4	86.8	93.3	93.2	83.5	86.4	90.3
Possible	107.3	108.0	103.0	105.2	101.4	101.4	102.1	103.7	107.6	104.0
Possible (Ex Light Oil)	100.5	103.9	-	99.3	-	-	-	97.2	101.4	-
Yield, Wt % MAF Lignite										
Net Gas	36.8	28.2	33.3	31.0	40.3	27.1	30.0	28.5	26.9	31.3
Net Liquid	74.0	73.0	62.6	71.6	56.1	65.0	65.0	61.8	65.8	66.1
(Dist. Oil)	(23.0)	(24.2)	(9.0)	(15.7)	(4.1)	(3.9)	(5.9)	(10.5)	(22.2)	(13.2)
(SRL)	(51.0)	(48.8)	(53.6)	(55.9)	(52.0)	(61.1)	(59.1)	(51.3)	(43.6)	(52.9)
Net Water & Ash	-11.6	-8.5	-3.2	-5.8	-5.3	-4.1	-4.4	-0.9	-3.4	-5.2
Unconverted Coal	0.8	7.3	7.3	3.2	8.9	12.0	9.4	10.6	10.8	7.8
Overall Material Balance, %	100.2	100.2	98.1	99.6	99.5	101.3	101.0	98.6	99.3	99.8
Number of solvent passes thru Liquefaction Reactor by middle of yield period. (Estimated)	1.1	2.1	8.8	9.8	9.5	1.9	2.9	6.7	8.4	-

Actual solvent recovery for recycle averaged about 90 percent for the nine data periods, but because of various operating and equipment problems during the run the longest period of operations without fresh solvent addition was 120 hours or about 24 turnovers for the solvent inventory. Overall, the calculated maximum possible solvent available for recovery, which includes all organic liquids, averaged 104 percent which compares well with that obtained from previous runs.

Of the nine data periods, three were completed with the deashing system on stream. During these yield periods, the ash content of the F-1 vacuum bottoms varied from 0.9 to 6.4 weight percent while the unconverted coal content varied from 0.3 to 2.9 weight percent. For comparison, the ash content of undeashed F-1 vacuum bottoms would range between 10 and 12 weight percent and the unconverted coal content would be about 9-1/2 percent, for an MAF lignite conversion of about 92 percent with a feed lignite containing about 6 percent ash and 33 percent moisture.

Consumption of reducing gases on a hydrogen equivalent basis averaged 2.0 weight percent of the MAF coal charged or 2.3 standard cubic feet of gas per pound raw coal fed.

The two prime objectives of Run L-1 were (1) to demonstrate and to define the problems of long term plant operations and (2) to determine the effects of extended solvent recycle on liquefaction yields. In these respects Run L-1 was only partly successful. Results from the run indicate that the general problems of long term plant operations are (A) solids buildup in the reactors which eventually lead to low conversions and plugging; (B) erosion and some corrosion; and (C) equipment malfunctions.

The effects of extended solvent reuse are only sketchily known from the data at hand. To illustrate, the number of solvent passes thru the liquefaction reactor has been estimated for each of the nine data periods and listed at the bottom of Table 1. There does not appear to be a discernable relationship between the net yields and the number of solvent cycles. This is perhaps because only oil boiling above 350°F was recycled. From the distillation data obtained during this run, it appears that approximately 0.5 percent more liquefaction solvent, i.e. 450-850°F boiling range material, was made than was charged. This is consistent with the general trend of previous similar runs where the yield of 450-850°F material was sometimes slightly more and sometimes slightly less than that charged.

In summary, Run L-1 was scheduled for 672 hours of continuous operation with 652 hours devoted to coal processing. In practice, from the time coal was first introduced to the time coal was last shut off 615-1/2 hours of operating time were logged during which coal was actually charged for 460-1/2 hours or about

75 percent of the actual operating time. The total amount of lignite processed was 22,800 pounds at an average feed rate of 49-1/2 pounds per hour.

Make-up solvent was added at various times throughout the run, either because operating difficulties resulted in the loss of solvent, or because of the failure to recover enough of the solvent range material. The longest period of operation without make-up solvent addition was 120 hours. Thus one of the primary purposes of the run, to demonstrate long continued operation without make-up solvent addition, was not entirely successful. However, the 120 hours of operation without solvent addition represented approximately 24 turnovers of the solvent inventory. During this period the solvent inventory decreased by 1093 pounds for an average loss of 9.1 lbs/hr, including that in samples. A large part of the loss represented the failure to recover all of the recoverable solvent in the streams from the oil-water separator and in the F-1 vacuum bottoms. There was no significant effect on liquefaction during solvent recycle as the original starting solvent was being replaced by coal derived material.

A chronological log of Run L-1 follows to provide additional details of the operations and difficulties of the Process Development Unit.

1. Run Hours 0 to 89.

After the usual start-up difficulties coal was charged at 0500 hours of the second day of operation. The unit was allowed to line out for 45 hours, at which time yield period L-1A was initiated. However, the yield period was terminated after only three hours because of plugging in the bottoms draw-off leg of vacuum flash column F-1. The leg was cleared without interrupting the coal feed, but a considerable amount of recycle solvent was lost, and the solvent system was replenished with fresh solvent. After 9 hours of lined out operation another yield period operation was initiated.

2. Run Hours 89 to 113.

Two yield periods of 12 hours duration each were run back to back. The run conditions were as follows:

	Specified
Pressure, psig	2500
Max. Dissolver Temperature, °F	820 to 830
Solvent to Raw Coal Ratio	1.8:1
Slurry Flow Rate, lbs/hr.	140
LHSV	1.4
GHSV	330

### 3. Run Hours 113 to 289.5

After the yield period L-1C the plant was run for several days to test longer term operability. During the fifth day of operation the F-1 bottom draw-off leg plugged again, this time as the result of a burned out heat tape which allowed part of the leg to cool down to 280°F. The heat tape was replaced and the solidified SRL was cleared from the leg.

During this period, the compressors experienced some minor malfunctions as a result of worn check valves. Other minor problems involved the trim of the high pressure letdown valves and packing in valves and pumps.

On the afternoon of the seventh day of operation, with an outside temperature of 96°F, the safety relief disc blew out on a carbon dioxide extinguisher on the upper catwalk near the dissolvers heads. The sound of the explosion and the dense fumes were interpreted as a vessel or line failure at the top of the dissolvers and the emergency shutdown procedure was implemented. The carbon dioxide extinguisher at this high temperature location has been replaced by a dry powder extinguisher.

The emergency shut down caused the plugging of numerous lines including preheater coil E-1 and dissolver R-1B. Hence PDU operations were suspended and startup solvent was prepared by distilling Raw FS-120 carbon black feedstock until the coil in E-1 could be removed and replaced.

The liquefaction section was started up again, this time with dissolver R-1A in service. After this start-up, there were numerous problems with wire-drawn valves around the dissolvers and with partial plugging of the line between S-1 and S-3. Therefore the operations were again interrupted to repair these valves and clean the lines.

At 2000 hours on the tenth day of operations the plant was again started up, this time with dissolver R-1B in operations, and coal was charged at 0600 hours on the eleventh day. After 19-1/2 hours lining out, yield period operations were started.

### 4. Run Hours 289.5 to 313.5

Yield periods L-1D and L-1E were 12 hours each and were run back to back. These yield periods were successfully completed with only a few minor problems under the same nominal operating conditions as had been used for L-1B and L-1C. Again only the liquefaction section was in operation.

### 5. Run Hours 313.5 to 453

After completion of yield period L-1E, preparations were made for the startup of the solid-liquid separation section or deashing section. However, after 32 hours, the pressure in

dissolver R-1B began to increase slowly. The pressure behavior indicated that there was probably some material build up in the 5/16" Incoloy line between dissolver R-1B and separator S-1. The pressure drop between these two vessels increased to 300-400 psig. This line could not be cleared with solvent flushing. Finally, after about 85 hours of pressure drop build-up, the line became plugged and operations were switched to dissolver R-1A. Thus far the deashing unit had been used only sparingly. After the warm up of dissolver R-1A, both the liquefaction and separation units were started up in series. After lining out for 39 hours on coal, yield period operations were initiated.

#### 6. Run Hours 453 to 473

Yield period L-1F was the first attempted with both the liquefaction and the separation sections in operation simultaneously. During this yield period both distilled solvent and toluene were added to the respective charge tanks A-5A and A-1A in order to enable the solvent pumps to keep suction. The only other problem encountered during L-1F yield period was with deashing settler V-8. The solids dumping valves developed a leak which was easily remedied.

Yield period L-1G was started back to back with L-1F. About seven hours into the yield period problems were experienced with the slurry charge pump. A bleed valve in the slurry system which was opened to flush the pump released some of the dissolver contents and resulted in sudden depressurization of the dissolver R-1A. This upset resulted in plugging of various parts of the system and the yield period was terminated.

#### 7. Run Hours 473 to 529.5

After lines and reactors were cleared and the slurry pump repaired, operations were resumed still using dissolver R-1A. Coal was charged at 0400 hours of the 21st day, and the liquefaction section only was lined out for 21-1/2 hours before starting yield period operations.

#### 8. Run Hours 529.5 to 553.5

Yield periods L-1H and L-1I were run back to back and successfully completed. Both were made at the same nominal conditions as the previous yield periods.

#### 9. Run Hours 553.5 to 58.

After completing two yield periods with liquefaction section operation only, the deashing section was started up. Because of depletion of the recycle liquefaction solvent, additional recycle solvent was added. The added solvent was that which had remained after Run M-33 and had been stored for such

contingency. After 27-1/2 hours of switching in and lining out the deashing unit, yield period operations were again initiated.

10. Run Hours 581 to 605

Yield periods L-1J and L-1K were made with both liquefaction and separation sections in operation simultaneously. They were successfully completed with little difficulty.

11. Run Hours 605 to 644.5

Following yield periods L-1J and K, some changes were made in the operation of the deashing system which seemed to give improved results. However, operation of this section was terminated when the gasket in the solids withdrawal valve failed, allowing toluene and SRL to spray out.

After 30 hours more on coal for the liquefaction section, another yield period operation was started. However, yield period L-1L was terminated because of plugging problems in the flash drum F-1. During this period the temperature rise through the dissolver had decreased, indicating less reaction, perhaps because of lower residence time because of build up of solids in the reactor or on the reactor wall.

Operations were continued for a time after the termination of L-1L, but the problems with the vacuum bottoms became so acute that shut down procedures were initiated after 644.5 hours of the scheduled 660 hours of the run before shut down. The last sample taken of the vacuum bottoms had a melting point higher than the 500°F maximum range of the gradient bar melting point apparatus.

12. Recapitulation

Run L-1 was the first of the three scheduled long runs of four weeks duration. Overall, it was fairly successful, as indicated by the summary table following:

Total Time Scheduled	672 hours
Operating Time on Coal Scheduled	652 hours
Actual Operating Time*	615.5 hours
Actual Time on Coal during Operating Time	460.5 hours
Time on Coal as percent of Actual Operating Time	74.8%
Scheduled Operating Time	70.8%
Total Scheduled Time	68.5%

\*From time coal first introduced to time coal last shut off. During actual time on coal 22,800 pounds of lignite was processed at an average feed rate of 49.5 pounds per hour.

RUN CONDITIONS

RUN NO. L-1B

DATE MADE 7/13-14/77

TEMPERATURE °F

PRESSURE, psig

PREHEATER E-1  
 SAND BATH 725  
 INLET 265  
 OUTLET 717

DISSOLVERS  
 R-1A (1) \_\_\_\_\_  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_  
 (4) \_\_\_\_\_  
 R-1B (1) 757  
 (2) 797  
 (3) 806  
 (4) 827

REACTOR PRODUCT SEPARATORS  
 S-1 618  
 S-2 77  
 S-3 477  
 S-4A 89  
 S-4B 88

PREHEATER E-11  
 DOWTHERM 672  
 INLET 440  
 OUTLET 646

VACUUM FLASH F-1  
 OVERHEAD VAPOR 526  
 UPPER WALL 598  
 LOWER WALL 588  
 DOWNCOMER 493  
 CONDENSATE  
 ACCUMULATOR, S-7 92

PREHEATER E-13  
 DOWTHERM 596  
 INLET 89  
 OUTLET 504

LIGHT ENDS COLUMN, F-2  
 REBOILER 464  
 LOWER SECTION 560  
 FEED SECTION 464  
 OVERHEAD 185  
 S-8 88  
 S-9 -

SOLVENT COLUMN, F-3  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

HEAVY ENDS COLUMN, F-4  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

VACUUM FLASH, F-0  
 OVERHEAD NIU  
 BOTTOMS \_\_\_\_\_

PRECIPITATION TOWER, V-8  
 ZONE (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_

RECOVERY TOWER V-9  
 REBOILER NIU  
 OVERHEAD \_\_\_\_\_

SEPARATORS S-1 and S-2  
2500

SEPARATOR S-3  
300

SEPARATORS S-4A and S-4B  
60

VACUUM FLASH, F-1  
15 Torr

LIGHT ENDS COLUMN, F-2  
0

SOLVENT COLUMN, F-3  
NIU

HEAVY ENDS COLUMN, F-4  
NIU

VACUUM FLASH, F-0  
NIU


SETTLING TOWER, V-8  
NIU

RECOVERY TOWER, V-7  
NIU

	Start	End	Run No: L-1B
Date of Run	7/13/77	7/14/77	Units: lbs/hr., °F, psig
Time of Run	1500	0300	Prep. By: BCL & GGB
Length of Run	12	hrs.	Updated: 1/3/78
Hours on Coal at End of Y. P.	70.0		

### MASS RATES AND RUN CONDITIONS

PRODUCT GAS TO THERMAL OXIDIZER	24.24
PRODUCT GAS TO RECYCLE	-0-
K-4 KNOCKOUT POT BTMS	-0-
ABSORBED GASES	NIU
WASTE GAS	3.39
S-4A BOTTOMS	-
S-4B BOTTOMS	18.87
TOLUENE ACCUMULATOR	NIU
D.C. OHD	Negl.
LIGHT OILS	3.55
V-9 BOTTOMS	NIU
J-1 EXHAUST GASES	0.57
COLD TRAP GASES	0.07
COLD TRAP LIQUIDS	NIU
V-8 BOTTOMS	NIU
VACUUM BOTTOMS	23.00
A-5A OVERFLOW	-



155.75 TOTAL

☒ OPEN      ☒ CLOSED

TOTAL 155.75

Numbers in parentheses are not included in the totals.

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE  
Normalized  
Revised: 1/3/78

Run No: L-1B  
Date: 7/13-14/77  
Time: 1500-0300

Temperature: 717°F  
Pressure: 2500 psig  
LHSV: 1.38  
GHSV: 330

SUMMARY  
lbs/hour

STREAM DESCRIPTION	Total	Total	Net		WT % MAF
	In	Out	Yield		Lignite
SAMPLE POINT					
Hydrogen - H <sub>2</sub>	1.32	1.15	-0.17		
Carbon Monoxide - CO	16.11	9.18	-6.93		
Carbon Dioxide - CO <sub>2</sub>		15.17	15.17		
Hydrogen Sulfide - H <sub>2</sub> S		0.21	0.21		
Methane - CH <sub>4</sub>		1.38	1.38		
Ethane - C <sub>2</sub> H <sub>6</sub>		0.61	0.61	10.61	36.76
Propane - C <sub>3</sub> H <sub>8</sub>		0.29	0.29		
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.18	0.19	0.01		
Ammonia - NH <sub>3</sub>		0.04	0.04		
Light Oil - (0-100°C @ 1.6 Torr)	4.80	11.02	6.22		
Solvent - (100-230°C @ 1.6 Torr)	82.62	84.26	1.64	21.37	74.05
Heavy Oil - (230-255°C @1.6 Torr)	3.75	2.53	-1.22		
SRL		14.73	14.73		
Coal (MAF)	28.86	0.23	-28.63		-99.20
Ash	2.90	2.63	-0.27		-0.94
Water	15.21	12.13	-3.08		-10.67
Phenol					
TOTAL	155.75	155.75	-0-		

ELEMENTAL					
	Total	Total	Net		WT % MAF
Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
TOTAL					

PROJECT LIGNITE  
MEASURED & ADJUSTED MATERIAL BALANCE  
Revised: 1/3/78

Run No: L-1B  
Date: 7/13-14/78  
Time: 1500-0300

MATERIAL IN

Temperature: 717°F  
Pressure: 2500 psig  
LHSV: 1.38  
GHSV: 330

lbs/hour

STREAM DESCRIPTION	Feed Gas	Lignite	Feed Solvent		Total In
	Sx-21	Sx-1	Sx-14		
Hydrogen - H <sub>2</sub>	1.32				1.32
Carbon Monoxide - CO	16.11				16.11
Carbon Dioxide - CO <sub>2</sub>					
Hydrogen Sulfide - H <sub>2</sub> S					
Methane - CH <sub>4</sub>					
Ethane - C <sub>2</sub> H <sub>6</sub>					
Propane - C <sub>3</sub> H <sub>8</sub>					
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.18				0.18
Ammonia - NH <sub>3</sub>					
Light Oil - (0-100°C @ 1.6 Torr)			4.80		4.80
Solvent - (100-230°C @ 1.6 Torr)			82.62		82.62
Heavy Oil - (230-255°C @ 1.6 Torr)			3.75		3.75
SRL					
Cool (MAF)		28.86			28.86
Ash		2.90			2.90
Water		14.98	0.23		15.21
Phenol					
TOTAL	17.61	46.74	91.40		155.75

ELEMENTAL	Quantitative				
	Feed Gas	Lignite	Feed Solvent		Total In
Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
TOTAL					

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE  
Normalized  
Revised: 1/3/78

Run No: L-1B  
Date: 7/13-14/77  
Time: 1500-0300

MATERIAL OUT

Temperature: 717°F  
Pressure: 2500 psig  
LHSV: 1.38  
GHSV: 330

Quantitative	STREAM DESCRIPTION	Product Gas	S-4A Overhead	S-4B Btms	S-8 Overhead	S-8 Btms	J-1 Exhaust
	SAMPLE POINT	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
	Hydrogen - H <sub>2</sub>	1.09	0.06				
	Carbon Monoxide - CO	8.70	0.44				0.04
	Carbon Dioxide - CO <sub>2</sub>	12.27	2.46				0.44
	Hydrogen Sulfide - H <sub>2</sub> S	0.15	0.06				
	Methane - CH <sub>4</sub>	1.22	0.14				0.02
	Ethane - C <sub>2</sub> H <sub>6</sub>	0.47	0.11				0.03
	Propane - C <sub>3</sub> H <sub>8</sub>	0.16	0.09				0.04
	Butane - C <sub>4</sub> H <sub>10</sub>						
	Nitrogen - N <sub>2</sub>	0.17	0.02				
	Ammonia - NH <sub>3</sub>	0.01	0.01	0.02			
	Light Oil - (0-100°C @ 1.6 Torr)			4.44		3.49	
	Solvent - (100-230°C @ 1.6 Torr)			1.99		0.06	
	Heavy Oil - (230-255°C @ 1.6 Torr)			0.55			
	SRL						
	Cool (MAF)						
	Ash						
	Water			11.87			
	Phenol						
	<b>TOTAL</b>	<b>24.24</b>	<b>3.39</b>	<b>18.87</b>	<b>Negl.</b>	<b>3.55</b>	<b>0.57</b>

Elemental	Carbon						
	Hydrogen						
	Nitrogen						
	Sulfur						
	Oxygen (by diff)						
	Ash						
	<b>TOTAL</b>						

PROJECT: LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized  
 Revised: 1/3/78

Run No: L-1B  
 Date: 7/13-14/77  
 Time: 1500-0300

MATERIAL OUT

Temperature: 717°F  
 Pressure: 2500 psig  
 LHSV: 1.38  
 GHSV: 330

STREAM DESCRIPTION	lbs/hour					Total Out
	Cold Trap	F-1 Btms	← Recycle S-7 Btms	Solvent → F-2 Btms		
SAMPLE POINT	Sx-33	Sx-2	Sx-39	Sx-12		
Hydrogen - H <sub>2</sub>						1.15
Carbon Monoxide - CO						9.18
Carbon Dioxide - CO <sub>2</sub>						15.17
Hydrogen Sulfide - H <sub>2</sub> S						0.21
Methane - CH <sub>4</sub>						1.38
Ethane - C <sub>2</sub> H <sub>6</sub>						0.61
Propane - C <sub>3</sub> H <sub>8</sub>						0.29
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						0.19
Ammonia - NH <sub>3</sub>						0.04
Light Oil - (0-100°C @ 1.6 Torr)	0.07		3.02			11.02
Solvent - (100-230°C @ 1.6 Torr)		5.41	49.01	27.79		84.26
Heavy Oil - (230-255°C @ 1.6 Torr)			1.35	0.63		2.53
SRL		14.73				14.73
Coal (MAF)		0.23				0.23
Ash		2.63				2.63
Water			0.26			12.13
Phenol						
TOTAL	0.07	23.00	53.64	28.42		155.75

ELEMENTAL						TOTAL
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/3/78

Run No: L-1B  
Date: 7/13-14/77  
Time: 1500-0300

WEIGHT PERCENT

SAMPLE DESCRIPTION	Lignite	F-1 Btms	Makeup Solvent	F-2 Btms	Feed Solvent	Strip Oil
	Sx-1	Sx-2	Sx-8	Sx-12	Sx-14	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100°C @ 1.6 Torr)			3.73		5.25	98.40
Solvent - (100-230°C @ 1.6 Torr)		23.50	89.50	97.80	90.40	1.60
Heavy Oil - (230-255°C @1.6 Torr)			6.70	2.20	4.10	
SRL		64.05				
Coal (MAF)	61.74	1.01				
Ash	6.20	11.44				
Water	32.06		0.07		0.25	
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		98.86				
Melting Point °F		244				
Specific Gravity 60/60			1.040	1.052	1.047	
Viscosity, cp						

Elemental	Quantitative					
	Lignite	F-1 Btms	Makeup Solvent	F-2 Btms	Feed Solvent	Strip Oil
	Sx-1	Sx-2	Sx-8	Sx-12	Sx-14	Sx-16
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/3/78

Run No: L-1B

Date: 7/13-14/77

Time: 1500-0300

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-8 Water	S-8 Total	Product Gas	Feed Gas	S-4B Oil	S-4B Water
SAMPLE POINT	Sx-16	Sx-16	Sx-19	Sx-21	Sx-23	Sx-23
Hydrogen - H <sub>2</sub>			4.51	7.51		
Carbon Monoxide - CO			35.87	91.50		
Carbon Dioxide - CO <sub>2</sub>			50.62			
Hydrogen Sulfide - H <sub>2</sub> S			0.61			
Methane - CH <sub>4</sub>			5.04			
Ethane - C <sub>2</sub> H <sub>6</sub>			1.92			
Propane - C <sub>3</sub> H <sub>8</sub>			0.68			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>			0.72	0.99		
Ammonia - NH <sub>3</sub> (PPM)			0.03			0.21
Light Oils - (0-100° C @ 1.6 Torr)		98.40			62.82	
Solvent - (100-230° C @ 1.6 Torr)		1.60			28.10	
Heavy Oil - (230-255° C @1.6 Torr)					7.80	
SRL						
Coal (MAF)						
Ash						
Water	100				1.28	99.79
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60					0.958	
Viscosity, cp						

Quantitative

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	-	2	2	2	2	2

Elemental

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/3/78

Run No: L-1B

Date: 7/13-14/77

Time: 1500-0300

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4B	S-4A	J-1	Cold	Recycle	
	Total	Ovhd	Disch.	Trap	Solvent	
SAMPLE POINT	Sx-23	Sx-30	Sx-32	*Sx-33	Sx-39	
Hydrogen - H <sub>2</sub>		1.73	0.92			
Carbon Monoxide - CO		13.11	7.50			
Carbon Dioxide - CO <sub>2</sub>		72.71	76.76			
Hydrogen Sulfide - H <sub>2</sub> S		1.66				
Methane - CH <sub>4</sub>		4.14	3.54			
Ethane - C <sub>2</sub> H <sub>6</sub>		3.30	4.57			
Propane - C <sub>3</sub> H <sub>8</sub>		2.54	6.71			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>		0.63				
Ammonia - NH <sub>3</sub> (PPM)	0.13	0.18				
Light Oils - (0-100°C @ 1.6 Torr)	23.52			99.92	5.62	
Solvent - (100-230°C @ 1.6 Torr)	10.52				91.37	
Heavy Oil - (230-255°C @1.6 Torr)	2.92				2.52	
SRL						
Coal (MAF)						
Ash						
Water	62.91			0.08	0.49	
Phenol						
TOTAL	100	100	100	100	100	
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60					1.052	
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	-	2	

\*Insufficient sample for distillation. Assumed to be light oil and water.

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/3/78

Run No: L-1B

Date: 7/13-14/77

Time: 1500-0300

MOLE PERCENT

	MOLE PERCENT				
	Product Gas	Feed Gas	S-4A Ovhd	J-1 Disch.	
SAMPLE DESCRIPTION					
SAMPLE POINT	Sx-19	Sx-21	Sx-30	Sx-32	
Hydrogen - H <sub>2</sub>	43.99	53.20	24.75	15.39	
Carbon Monoxide - CO	24.99	46.30	13.40	8.92	
Carbon Dioxide - CO <sub>2</sub>	22.44		47.30	58.15	
Hydrogen Sulfide - H <sub>2</sub> S	0.35		1.40		
Methane - CH <sub>4</sub>	6.15		7.40	7.38	
Ethane - C <sub>2</sub> H <sub>6</sub>	1.25		3.15	5.08	
Propane - C <sub>3</sub> H <sub>8</sub>	0.30		1.65	5.08	
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.50	0.50	0.65		
Ammonia - NH <sub>3</sub> (PPM)	0.03		0.30		
Light Oils - (0-100° C @ 1.6 Torr)					
Solvent - (100-230° C @ 1.6 Torr)					
Heavy Oil - (230-255° C @ 1.6 Torr)					
SRL					
Coal (MAF)					
Ash					
Water					
Phenol					
TOTAL	100	100	100	100	
Calc Mole Wt.	19.51	14.17	28.62	33.33	
Melting Point °F					
Specific Gravity 60/60					
Viscosity, cp					
Elemental	Carbon				
	Hydrogen				
	Nitrogen				
	Sulfur				
	Oxygen (by diff)				
	Ash				
	TOTAL				
	Number of Sample Avg.	2	2	2	2

PROJECT LIGNITE  
 SAMPLE ANALYSES  
 RUN NO: L-1B  
 DATE: 7/13-14/77  
 TIME: 1500-0300

SAMPLE DESCRIPTION	Makeup Solv	F-2 Btms	Feed Solv.	S-8 Oil	S-4B Oil
SAMPLE POINT	Sx-8	Sx-12	Sx-14	Sx-16	Sx-23
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR IBP 5% 10% 20% 30% 40% 50% 60% 70% 80% 90% 95% DRY PT.	5 73.5 134 164 187 193 198 203 208 218 226 240 252.5 260	5 143 152 157 162.5 169 174 180 184 191 196 204 221 231	5 43.4 117 145 175.6 187.2 193.5 198.6 205 212.2 223 244.3 260 260		
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR IBP 5% 10% 20% 30% 40% 50% 60% 70% 80% 90% 95% DRY PT.				745 59 65 68 72 76 80 84 89 94 101 212 212	742 91 92 169 169 220 249 277 302 328 328 328 328 356
ASPHALTENE TEST					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
SAYBOLT VISCOSITY, SSU					
100° F	15.7	14.5	14.8		
210° F	9.2	9.0	8.9		
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)	0.07		0.25		1.28
INFRARED RATIO					
SP. GRAV. 60/60 F	1.040	1.052	1.047		0.959

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
 ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
 MALTENES-N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
 DISTILLABLE OIL-RECOVERABLE BY DISTILLATION. USUALLY LESS THAN 5% FOR THE F-1 VACUUM BOTTOMS MATERIAL

PROJECT LIGNITE  
 SAMPLE ANALYSES  
 RUN NO: L-1B  
 DATE: 7/13-14/77  
 TIME: 1500-0300

SAMPLE DESCRIPTION	S-7 Btms				
SAMPLE POINT	Sx-39				
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR	5				
IBP	60.4				
5%	113.5				
10%	137.2				
20%	170.2				
30%	183.8				
40%	189.6				
50%	197.0				
60%	199.3				
70%	208.2				
80%	216.5				
90%	239.6				
95%	260.				
DRY PT.					
VOLUME PERCENT	TEMPERATURE, °C				
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR					
IBP					
5%					
10%					
20%					
30%					
40%					
50%					
60%					
70%					
80%					
90%					
95%					
DRY PT.					
VOLUME PERCENT	TEMPERATURE, °C				
ASPHALTENE TEST					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
SAYBOLT VISCOSITY, SSU					
100° F	14.9				
210° F	9.2				
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)	0.49				
INFRARED RATIO					
SP. GRAV. 60/60 F	1.052				

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
 ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
 MALTENES-N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
 DISTILLABLE OIL - RECOVERABLE BY DISTILLATION. USUALLY LESS THAN 5% FOR THE F-1 VACUUM BOTTOMS MATERIAL

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 1/3/78

Run No: L-1B  
Date: 7/13-14/77  
Time: 1500-0300

MATERIAL OUT

Temperature: 717°F  
Pressure: 2500 psig  
LHSV: 1.38  
GHSV: 330

STREAM DESCRIPTION	Product Gas	lbs/hour				
		S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
SAMPLE POINT	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	1.10	0.06				
Carbon Monoxide - CO	8.73	0.44				0.04
Carbon Dioxide - CO <sub>2</sub>	12.31	2.47				0.44
Hydrogen Sulfide - H <sub>2</sub> S	0.15	0.06				
Methane - CH <sub>4</sub>	1.23	0.14				0.02
Ethane - C <sub>2</sub> H <sub>6</sub>	0.47	0.11				0.03
Propane - C <sub>3</sub> H <sub>8</sub>	0.16	0.09				0.04
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.17	0.02				
Ammonia - NH <sub>3</sub>	0.01	0.01	0.02			
Light Oil - (0-100°C @ 1.6 Torr)			4.46		3.50	
Solvent - (100-230°C @ 1.6 Torr)			1.99		0.06	
Heavy Oil - (230-255°C @ 1.6 Torr)			0.55			
SRL						
Coal (MAF)						
Ash						
Water			11.92			
Phenol						
TOTAL	24.33	3.40	18.94	Negl.	3.56	0.57

Elemental	Quantitative					
	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 1/3/78

Run No: L-1B  
Date: 7/13-14/77  
Time: 1500-0300

MATERIAL OUT

Temperature: 717°F  
Pressure: 2500 psig  
LHSV: 1.38  
GHSV: 330

lbs/hour

STREAM DESCRIPTION	Cold Trap	F-1 Btms	←Recycle S-7 Btms	Solvent→ F-2 Btms	Total Out
	Sx-33	Sx-2	Sx-39	Sx-12	
Hydrogen - H <sub>2</sub>					1.16
Carbon Monoxide - CO					9.21
Carbon Dioxide - CO <sub>2</sub>					15.22
Hydrogen Sulfide - H <sub>2</sub> S					0.21
Methane - CH <sub>4</sub>					1.39
Ethane - C <sub>2</sub> H <sub>6</sub>					0.61
Propane - C <sub>3</sub> H <sub>8</sub>					0.29
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					0.19
Ammonia - NH <sub>3</sub>					0.04
Light Oil - (0-100°C @ 1.6 Torr)	0.07		3.02		11.05
Solvent - (100-230°C @ 1.6 Torr)		5.43	49.01	27.79	84.28
Heavy Oil - (230-255°C @ 1.6 Torr)			1.35	0.63	2.53
SRL		14.78			14.78
Cool (MAF)		0.23			0.23
Ash		2.64			2.64
Water			0.26		12.18
Phenol					
TOTAL	0.07	23.08	53.64	28.42	156.01

Elemental	Quantitative					Total
	Cold Trap	F-1 Btms	←Recycle S-7 Btms	Solvent→ F-2 Btms		
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						


RUN CONDITIONS

RUN NO. I-1C  
 DATE MADE 7/14/77

TEMPERATURE °F		PRESSURE, psig
PREHEATER E-I		SEPARATORS S-1 and S-2
SAND BATH	<u>726</u>	<u>2500</u>
INLET	<u>260</u>	SEPARATOR S-3
OUTLET	<u>715</u>	<u>300</u>
DISSOLVERS		SEPARATORS S-4A and S-4B
R-1A (1)	<u>        </u>	<u>61</u>
(2)	<u>        </u>	VACUUM FLASH, F-1
(3)	<u>        </u>	<u>14 Torr</u>
(4)	<u>        </u>	LIGHT ENDS COLUMN, F-2
R-1B (1)	<u>757</u>	<u>0</u>
(2)	<u>798</u>	SOLVENT COLUMN, F-3
(3)	<u>806</u>	<u>NIU</u>
(4)	<u>829</u>	HEAVY ENDS COLUMN, F-4
REACTOR PRODUCT SEPARATORS		<u>NIU</u>
S-1	<u>622</u>	VACUUM FLASH, F-0
S-2	<u>79</u>	<u>NIU</u>
S-3	<u>474</u>	SETTLING TOWER, V-8
S-4A	<u>83</u>	<u>NIU</u>
S-4B	<u>79</u>	RECOVERY TOWER, V-7
PREHEATER E-II		<u>NIU</u>
DOWTHERM	<u>672</u>	
INLET	<u>435</u>	
OUTLET	<u>647</u>	
VACUUM FLASH F-1		
OVERHEAD VAPOR	<u>526</u>	
UPPER WALL	<u>600</u>	
LOWER WALL	<u>583</u>	
DOWNCOMER	<u>491</u>	
CONDENSATE		
ACCUMULATOR, S-7	<u>87</u>	
PREHEATER E-13		
DOWTHERM	<u>596</u>	
INLET	<u>79</u>	
OUTLET	<u>558</u>	
LIGHT ENDS COLUMN, F-2		
REBOILER	<u>471</u>	
LOWER SECTION	<u>575</u>	
FEED SECTION	<u>500</u>	
OVERHEAD	<u>185</u>	
S-8	<u>86</u>	
S-9	<u>-</u>	
SOLVENT COLUMN, F-3		
REBOILER	<u>NIU</u>	
LOWER SECTION	<u>        </u>	
FEED SECTION	<u>        </u>	
OVERHEAD	<u>        </u>	
HEAVY ENDS COLUMN, F-4		
REBOILER	<u>NIU</u>	
LOWER SECTION	<u>        </u>	
FEED SECTION	<u>        </u>	
OVERHEAD	<u>        </u>	
VACUUM FLASH, F-0		
OVERHEAD	<u>NIU</u>	
BOTTOMS	<u>        </u>	
PRECIPITATION TOWER, V-8		
ZONE (1)	<u>NIU</u>	
(2)	<u>        </u>	
(3)	<u>        </u>	
RECOVERY TOWER V-9		
REBOILER	<u>NIU</u>	
OVERHEAD	<u>        </u>	

	Start	End	Run No: L-1C
Date of Run	7/14/77	7/14/77	Units: lbs/hr, °F, psig
Time of Run	0300	1500	Prep. By: BCL & GGB
Length of Run	12 hrs.		Updated: 1/3/78
Hours on Coal at End of Y.P.	82.0		

### MASS RATES AND RUN CONDITIONS



-123-

☒ OPEN      ☒ CLOSED

Numbers in parentheses are not included in the totals.

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized  
 Revised: 1/3/78

Run No: L-1C  
 Date: 7/14/77  
 Time: 0300-1500

SUMMARY  
 lbs/hour

Temperature: 715°F  
 Pressure: 2500 psig  
 LHSV: 1.44  
 GHSV: 342

STREAM DESCRIPTION	Total In	Total Out	Net Yield	Wt % MAF Lignite	
SAMPLE POINT					
Hydrogen - H <sub>2</sub>	1.36	1.24	-0.12		
Carbon Monoxide - CO	16.88	9.97	-6.91		
Carbon Dioxide - CO <sub>2</sub>		13.53	13.53		
Hydrogen Sulfide - H <sub>2</sub> S		0.21	0.21		
Methane - CH <sub>4</sub>		1.06	1.06	8.79	28.17
Ethane - C <sub>2</sub> H <sub>6</sub>		0.49	0.49		
Propane - C <sub>3</sub> H <sub>8</sub>		0.50	0.50		
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.18	0.17	-0.01		
Ammonia - NH <sub>3</sub>		0.04	0.04		
Light Oil - (0-100°C @ 1.6 Torr)	7.64	11.79	4.15		
Solvent - (100-230°C @ 1.6 Torr)	83.66	87.53	3.87	22.77	72.98
Heavy Oil - (230-255°C @ 1.6 Torr)	2.81	2.35	-0.46		
SRL		15.21	15.21		
Coal (MAF)	31.20	2.28	-28.92		-92.69
Ash	3.00	2.70	-0.30		-0.96
Water	16.82	14.48	-2.34		-7.50
Phenol					
TOTAL	163.55	163.55	-0-		

Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
TOTAL					

PROJECT LIGNITE  
MEASURED & ADJUSTED MATERIAL BALANCE  
Revised: 1/3/78

Run No: L-1C  
Date: 7/14/77  
Time: 0300-1500

MATERIAL IN

Temperature: 715°F  
Pressure: 2500 psig  
LHSV: 1.44  
GHSV: 342

lbs/hour

STREAM DESCRIPTION	Feed Gas	Lignite	Feed Solvent		Total In
	Sx-21	Sx-1	Sx-14		
Hydrogen - H <sub>2</sub>	1.36				1.36
Carbon Monoxide - CO	16.88				16.88
Carbon Dioxide - CO <sub>2</sub>					
Hydrogen Sulfide - H <sub>2</sub> S					
Methane - CH <sub>4</sub>					
Ethane - C <sub>2</sub> H <sub>6</sub>					
Propane - C <sub>3</sub> H <sub>8</sub>					
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.18				0.18
Ammonia - NH <sub>3</sub>					
Light Oil - (0-100°C @ 1.6 Torr)			7.64		7.64
Solvent - (100-230°C @ 1.6 Torr)			83.66		83.66
Heavy Oil - (230-255°C @ 1.6 Torr)			2.81		2.81
SRL					
Coal (MAF)		31.20			31.20
Ash		3.00			3.00
Water		16.20	0.62		16.82
Phenol					
TOTAL	18.42	50.40	94.73		163.55

ELEMENTAL	TOTAL				
	Carbon	Hydrogen	Nitrogen	Sulfur	Oxygen (by diff)
Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
TOTAL					

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Normalized  
Revised: 1/3/78

Temperature: 715°F  
Pressure: 2500 psig  
LHSV: 1.44  
GHSV: 342

Run No: L-1C  
Date: 7/14/77  
Time: 0300-1500

MATERIAL OUT  
lbs/hour

STREAM DESCRIPTION	Product Gas	lbs/hour				
		S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
SAMPLE POINT	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	1.14	0.09				0.01
Carbon Monoxide - CO	9.17	0.73				0.07
Carbon Dioxide - CO <sub>2</sub>	10.37	2.73				0.43
Hydrogen Sulfide - H <sub>2</sub> S	0.14	0.07				
Methane - CH <sub>4</sub>	0.93	0.12				0.01
Ethane - C <sub>2</sub> H <sub>6</sub>	0.37	0.10				0.02
Propane - C <sub>3</sub> H <sub>8</sub>	0.38	0.09				0.03
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.14	0.03				
Ammonia - NH <sub>3</sub>	0.01	0.01	0.02			
Light Oil - (0-100°C @ 1.6 Torr)			0.32		7.01	
Solvent - (100-230°C @ 1.6 Torr)			0.36			
Heavy Oil - (230-255°C @ 1.6 Torr)					0.21	
SRL						
Coal (MAF)						
Ash						
Water			14.20		0.10	
Phenol						
<b>TOTAL</b>	<b>22.65</b>	<b>3.97</b>	<b>14.90</b>	<b>Negl.</b>	<b>7.32</b>	<b>0.57</b>

Elemental	lbs/hour					
	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust	Total
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
<b>TOTAL</b>						

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE  
Normalized  
Revised: 1/3/78

Run No: L-1C  
Date: 7/14/77  
Time: 0300-1500

MATERIAL OUT

Temperature: 715°F  
Pressure: 2500 psig  
LHSV: 1.44  
GHSV: 342

	lbs/hour					Total Out
	Cold Trap	F-1 Btms	←Recycle Solvent→ S-7 Btms	F-2 Btms		
<b>STREAM DESCRIPTION</b>	<b>*Sx-33</b>	<b>Sx-2</b>	<b>Sx-39</b>	<b>Sx-12</b>		
SAMPLE POINT						
Hydrogen - H <sub>2</sub>						1.24
Carbon Monoxide - CO						9.97
Carbon Dioxide - CO <sub>2</sub>						13.53
Hydrogen Sulfide - H <sub>2</sub> S						0.21
Methane - CH <sub>4</sub>						1.06
Ethane - C <sub>2</sub> H <sub>6</sub>						0.49
Propane - C <sub>3</sub> H <sub>8</sub>						0.50
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						0.17
Ammonia - NH <sub>3</sub>						0.04
Light Oil - (0-100°C @ 1.6 Torr)	0.13		4.33			11.79
Solvent - (100-230°C @ 1.6 Torr)		4.28	51.14	31.75		87.53
Heavy Oil - (230-255°C @1.6 Torr)			1.57	0.57		2.35
SRL		15.21				15.21
Coal (MAF)		2.28				2.28
Ash		2.70				2.70
Water			0.18			14.48
Phenol						
<b>TOTAL</b>	<b>0.13</b>	<b>24.47</b>	<b>57.22</b>	<b>32.32</b>		<b>163.55</b>

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	<b>TOTAL</b>					

\*No sample available. Assumed to be 100% light oil

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/3/78

Run No: L-1C

Date: 7/14/77

Time: 0300-1500

WEIGHT PERCENT

SAMPLE DESCRIPTION	WEIGHT PERCENT					
	Lignite	F-1 Btms	F-2 Btms	Feed Solvent	S-8 Btms	Product Gas
SAMPLE POINT	Sx-1	Sx-2	Sx-12	Sx-14	Sx-16	Sx-19
Hydrogen - H <sub>2</sub>						5.05
Carbon Monoxide - CO						40.48
Carbon Dioxide - CO <sub>2</sub>						45.78
Hydrogen Sulfide - H <sub>2</sub> S						0.64
Methane - CH <sub>4</sub>						4.11
Ethane - C <sub>2</sub> H <sub>6</sub>						1.62
Propane - C <sub>3</sub> H <sub>8</sub>						1.66
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						0.61
Ammonia - NH <sub>3</sub> (PPM)						0.05
Light Oils - (0-100°C @ 1.6 Torr)				8.06	95.78	
Solvent - (100-230°C @ 1.6 Torr)		17.50	98.24	88.32	-	
Heavy Oil - (230-255°C @ 1.6 Torr)			1.76	2.97	2.90	
SRL		62.15				
Coal (MAF)	61.90	9.30				
Ash	5.96	11.05				
Water	32.14			0.65	1.32	
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		89.55				
Melting Point °F		262				
Specific Gravity 60/60			1.031	1.053		
Viscosity, cp						
Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	TOTAL					
	Number of Sample Avg.	3	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/3/78

Run No: L-1C  
Date: 7/14/77  
Time: 0300-1500

WEIGHT PERCENT

SAMPLE DESCRIPTION	Feed Gas	S-4B Oil	S-4B Water	S-4B Total	S-4A Ovhd	J-1 Disch.
SAMPLE POINT	Sx-21	Sx-23	Sx-23	Sx-23	Sx-30	Sx-32
Hydrogen - H <sub>2</sub>	7.39				2.27	1.07
Carbon Monoxide - CO	91.63				18.37	11.82
Carbon Dioxide - CO <sub>2</sub>					68.75	75.97
Hydrogen Sulfide - H <sub>2</sub> S					1.67	
Methane - CH <sub>4</sub>					3.11	2.66
Ethane - C <sub>2</sub> H <sub>6</sub>					2.54	3.28
Propane - C <sub>3</sub> H <sub>8</sub>					2.32	5.20
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.98				0.84	
Ammonia - NH <sub>3</sub> (PPM)			0.13	0.12	0.13	
Light Oils - (0-100°C @ 1.6 Torr)		46.90		2.16		
Solvent - (100-230°C @ 1.6 Torr)		52.50		2.42		
Heavy Oil - (230-255°C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water		0.60	99.87	95.30		
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/3/78

Run No: L-1C

Date: 7/14/77

Time: 0300-1500

WEIGHT PERCENT

Quantitative	SAMPLE DESCRIPTION	Recycle Solvent				
	SAMPLE POINT	Sx-39				
	Hydrogen - H <sub>2</sub>					
	Carbon Monoxide - CO					
	Carbon Dioxide - CO <sub>2</sub>					
	Hydrogen Sulfide - H <sub>2</sub> S					
	Methane - CH <sub>4</sub>					
	Ethane - C <sub>2</sub> H <sub>6</sub>					
	Propane - C <sub>3</sub> H <sub>8</sub>					
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					
	Ammonia - NH <sub>3</sub> (PPM)					
	Light Oils - (0-100°C @ 1.6 Torr)	7.57				
	Solvent - (100-230°C @ 1.6 Torr)	89.37				
	Heavy Oil - (230-255°C @ 1.6 Torr)	2.75				
	SRL					
	Coal (MAF)					
	Ash					
	Water	0.31				
	Phenol					
TOTAL	100					
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60	1.054					
Viscosity, cp						

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	TOTAL					
	Number of Sample Avg.	2				

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/3/78

Run No: L-1C

Date: 7/14/77

Time: 0300-1500

MOLE PERCENT

SAMPLE DESCRIPTION	Product	Feed	S-4A	J-1		
	Gas	Gas	Ovhd	Disch.		
SAMPLE POINT	Sx-19	Sx-21	Sx-30	Sx-32		
Hydrogen - H <sub>2</sub>	46.75	52.75	30.05	17.29		
Carbon Monoxide - CO	26.75	46.75	17.40	13.73		
Carbon Dioxide - CO <sub>2</sub>	19.25		41.45	56.17		
Hydrogen Sulfide - H <sub>2</sub> S	0.35		1.30			
Methane - CH <sub>4</sub>	4.75		5.15	5.40		
Ethane - C <sub>2</sub> H <sub>6</sub>	1.00		2.25	3.55		
Propane - C <sub>3</sub> H <sub>8</sub>	0.70		1.40	3.86		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.40	0.50	0.80			
Ammonia - NH <sub>3</sub> (PPM)	0.05		0.20			
Light Oils - (0-100°C @ 1.6 Torr)						
Solvent - (100-230°C @ 1.6 Torr)						
Heavy Oil - (230-255°C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100		
Calc Mole Wt.	18.50	14.29	26.53	32.53		
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	TOTAL					
	Number of Sample Avg.	2	2	2	2	

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: L-1C  
DATE: 7/14/77  
TIME: 0300-1500

SAMPLE DESCRIPTION	LEC Btms	Feed Solv.	S-8 Oil	S-4B Oil	S-7 Btms
SAMPLE POINT	Sx-12	Sx-14	Sx-16	Sx-23	Sx-39
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR	5	5			5
IBP	133.6	71.3			65
5%	153.8	103			105
10%	157.2	132.2			128.5
20%	161.7	164.7			157.5
30%	168.2	178.2			173
40%	174.8	187.4			181
50%	181	193.8			185
60%	186	198.6			193
70%	191	204.3			200
80%	198.2	218			208
90%	211.2	238.3			224
95%	229.5				240.5
DRY PT.	234.5	265			260
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR			742	746	
IBP			68	70	
5%			80	108	
10%			80	151	
20%			157	202	
30%			182	220	
40%			197	250	
50%			209	280	
60%			222	305	
70%			235	335	
80%			247	355	
90%			259	363	
95%			260		
DRY PT.			263	363	
ASPHALTENE TEST					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
SAYBOLT VISCOSITY, SSU					
100° F	13.1	15.1			15.0
210° F	8.8	8.9			8.9
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)		0.65	1.32	0.60	0.31
INFRARED RATIO		0.30			
SP. GRAV. 60/60 F	1.031	1.053			1.054

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL- RECOVERABLE BY DISTILLATION, USUALLY LESS THAN 5% FOR THE F-1 VACUUM BOTTOMS MATERIAL

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 1/3/78

Run No: L-1C  
Date: 7/14/77  
Time: 0300-1500

MATERIAL OUT

Temperature: 715°F  
Pressure: 2500 psig  
LHSV: 1.44  
GHSV: 342

lbs/hour

STREAM DESCRIPTION	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	1.15	0.09				0.01
Carbon Monoxide - CO	9.21	0.73				0.07
Carbon Dioxide - CO <sub>2</sub>	10.42	2.74				0.43
Hydrogen Sulfide - H <sub>2</sub> S	0.15	0.07				
Methane - CH <sub>4</sub>	0.93	0.13				0.01
Ethane - C <sub>2</sub> H <sub>6</sub>	0.37	0.10				0.02
Propane - C <sub>3</sub> H <sub>8</sub>	0.38	0.09				0.03
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.14	0.03				
Ammonia - NH <sub>3</sub>	0.01	0.01	0.02			
Light Oil - (0-100°C @ 1.6 Torr)			0.32		7.04	
Solvent - (100-230°C @ 1.6 Torr)			0.36			
Heavy Oil - (230-255°C @ 1.6 Torr)					0.21	
SRL						
Coal (MAF)						
Ash						
Water			14.27		0.10	
Phenol						
TOTAL	22.76	3.99	14.97	Negl.	7.35	0.57

ELEMENTAL	Quantitative					
	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 1/3/78

Run No: L-1C  
Date: 7/14/77  
Time: 0300-1500

MATERIAL OUT

Temperature: 715°F  
Pressure: 2500 psig  
LHSV: 1.44  
GHSV: 342

lbs/hour

STREAM DESCRIPTION	Cold Trap	← Recycle Solvent →			Total Out
		F-1 Btms	S-7 Btms	F-2 Btms	
SAMPLE POINT	*Sx-33	Sx-2	Sx-39	Sx-12	
Hydrogen - H <sub>2</sub>					1.25
Carbon Monoxide - CO					10.01
Carbon Dioxide - CO <sub>2</sub>					13.59
Hydrogen Sulfide - H <sub>2</sub> S					0.22
Methane - CH <sub>4</sub>					1.07
Ethane - C <sub>2</sub> H <sub>6</sub>					0.49
Propane - C <sub>3</sub> H <sub>8</sub>					0.50
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					0.17
Ammonia - NH <sub>3</sub>					0.04
Light Oil - (0-100°C @ 1.6 Torr)	0.13		4.33		11.82
Solvent - (100-230°C @ 1.6 Torr)		4.30	51.14	31.75	87.55
Heavy Oil - (230-255°C @ 1.6 Torr)			1.57	0.57	2.35
SRL		15.28			15.28
Cool (MAF)		2.29			2.29
Ash		2.71			2.71
Water			0.18		14.55
Phenol					
<b>TOTAL</b>	<b>0.13</b>	<b>24.58</b>	<b>57.22</b>	<b>32.32</b>	<b>163.89</b>

Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
<b>TOTAL</b>					

\*No sample available. Assumed to be 100% light oil.

RUN CONDITIONS

RUN NO. L-1D  
 DATE MADE 7/22/77

TEMPERATURE °F

PRESSURE, psig

PREHEATER E-1  
 SAND BATH 733  
 INLET 312  
 OUTLET 718

DISSOLVERS

R-1A (1) \_\_\_\_\_  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_  
 (4) \_\_\_\_\_  
 R-1B (1) 745  
 (2) 798  
 (3) 782  
 (4) 824

REACTOR PRODUCT SEPARATORS

S-1 600  
 S-2 77  
 S-3 486  
 S-4A 82  
 S-4B 78

PREHEATER E-11

DOWTHERM 677  
 INLET 438  
 OUTLET 650

VACUUM FLASH F-1

OVERHEAD VAPOR 530  
 UPPER WALL 600  
 LOWER WALL 581  
 DOWNCOMER 378  
 CONDENSATE  
 ACCUMULATOR, S-7 88

PREHEATER E-13  
 DOWTHERM 597  
 INLET 82  
 OUTLET 558

LIGHT ENDS COLUMN, F-2

REBOILER 459  
 LOWER SECTION 549  
 FEED SECTION 474  
 OVERHEAD 200  
 S-8 86  
 S-9 -

SOLVENT COLUMN, F-3

REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

HEAVY ENDS COLUMN, F-4

REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

VACUUM FLASH, F-0

OVERHEAD NIU  
 BOTTOMS \_\_\_\_\_

PRECIPITATION TOWER, V-8

ZONE (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_

RECOVERY TOWER V-9

REBOILER NIU  
 OVERHEAD \_\_\_\_\_

SEPARATORS S-1 and S-2  
2500

SEPARATOR S-3  
300

SEPARATORS S-4A and S-4B  
60

VACUUM FLASH, F-1  
14 Torr

LIGHT ENDS COLUMN, F-2  
0

SOLVENT COLUMN, F-3  
NIU

HEAVY ENDS COLUMN, F-4  
NIU


VACUUM FLASH, F-0  
NIU

SETTLING TOWER, V-8  
NIU

RECOVERY TOWER, V-7  
NIU

	Start	End	Run No: L-1D
Date of Run	7/22/77	7/22/77	Units: lbs/hr, °F, psig
Time of Run	0130	1330	Prep. By: BCL & GGB
Length of Run	12	hrs.	Updated: 1/24/78
Hours on Coal at End of Y.P.	162.4		

### MASS RATES AND RUN CONDITIONS



159.06 TOTAL

☒ OPEN

☒ CLOSED

TOTAL 159.06

Numbers in parentheses are not included in the totals.

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE  
Normalized  
Revised: 1/24/78

SUMMARY

Run No: L-1D  
Date: 7/22/77  
Time: 0130-1330

Temperature: 718°F  
Pressure: 2500 psig  
LHSV: 1.41  
GHSV: 318

lbs/hour

Stream Description	Total In	Total Out	Net Yield		Wt % MAF Coal	
Sample Point						
Hydrogen - H <sub>2</sub>	1.26	1.06	-0.20	}		
Carbon Monoxide - CO	15.81	8.18	-7.63			
Carbon Dioxide - CO <sub>2</sub>		15.80	15.80			
Hydrogen Sulfide - H <sub>2</sub> S		0.16	0.16			
Methane - CH <sub>4</sub>		1.30	1.30		10.31	33.29
Ethane - C <sub>2</sub> H <sub>6</sub>		0.57	0.57			
Propane - C <sub>3</sub> H <sub>8</sub>		0.29	0.29			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.18	0.16	-0.02			
Ammonia - NH <sub>3</sub>		0.04	0.04			
(IBP-255°C @1.6 Torr) Distillable Oil	91.79	94.58	2.79	}	19.39	
SRL		16.60	16.60			
Coal (MAF)	30.97	2.25	-28.72		-92.74	
Ash	3.18	3.16	-0.02		-0.06	
Water	15.87	14.91	-0.96		-3.10	
Phenol						
Total	159.06	159.06				

Quantitative

Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
Total					

Elemental

PROJECT LIGNITE  
MEASURED & ADJUSTED MATERIAL BALANCE  
Revised: 1/24/78

MATERIAL IN

Run No: L-1D  
Date: 7/22/77  
Time: 0130-1330

Temperature: 718°F  
Pressure: 2500 psig  
LHSV: 1.41  
GHSV: 318

lbs/hour

Stream Description	Feed Gas	Lignite	Feed Solvent	Total In
Sample Point	Sx-21	Sx-1	Sx-14	
Hydrogen - H <sub>2</sub>	1.26			1.26
Carbon Monoxide - CO	15.81			15.81
Carbon Dioxide - CO <sub>2</sub>				
Hydrogen Sulfide - H <sub>2</sub> S				
Methane - CH <sub>4</sub>				
Ethane - C <sub>2</sub> H <sub>6</sub>				
Propane - C <sub>3</sub> H <sub>8</sub>				
Butane - C <sub>4</sub> H <sub>10</sub>				
Nitrogen - N <sub>2</sub>	0.18			0.18
Ammonia - NH <sub>3</sub>				
Distillable Oil (IBP-255°C @1.6 Torr)			91.79	91.79
SRL				
Coal (MAF)		30.97		30.97
Ash		3.18		3.18
Water		15.58	0.29	15.87
Phenol				
<b>Total</b>	<b>17.25</b>	<b>49.73</b>	<b>92.08</b>	<b>159.06</b>

Carbon				
Hydrogen				
Nitrogen				
Sulfur				
Oxygen (by diff)				
Ash				
<b>Total</b>				

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized  
 Revised: 1/24/78

MATERIAL OUT

Run No: L-1D  
 Date: 7/22/77  
 Time: 0130-1330

Temperature: 718°F  
 Pressure: 2500 psig  
 LHSV: 1.41  
 GHSV: 318

lbs/hour

Stream Description	Product Gas	S-4A	S-4B	S-8	S-8	J-1
		Ovhd	Btms	Ovhd	Btms	Exhaust
Sample Point	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	0.99	0.07				
Carbon Monoxide - CO	7.62	0.50				0.06
Carbon Dioxide - CO <sub>2</sub>	12.89	2.44				0.47
Hydrogen Sulfide - H <sub>2</sub> S	0.10	0.06				
Methane - CH <sub>4</sub>	1.15	0.13				0.02
Ethane - C <sub>2</sub> H <sub>6</sub>	0.45	0.10				0.02
Propane - C <sub>3</sub> H <sub>8</sub>	0.18	0.09				0.02
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.13	0.03				
Ammonia - NH <sub>3</sub>		0.02	0.02			
Distillable Oil (IBP-255°C @1.6 Torr)			0.04		6.02	
SRL						
Coal (MAF)						
Ash						
Water			14.55		0.07	
Phenol						
Total	23.51	3.44	14.61	Negl.	6.09	0.59

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	Total					

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized  
 Revised: 1/24/78

Run No: L-1D  
 Date: 7/22/77  
 Time: 0130-1330

MATERIAL OUT

Temperature: 718°F  
 Pressure: 2500 psig  
 LHSV: 1.41  
 GHSV: 318

lbs/hour

Stream Description	Cold Trap	F-1 Btms	←Recycle S-7 Btms	Solvent→ F-2 Btms	Total Out
	Sample Point	Sx-33	Sx-2	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>					1.06
Carbon Monoxide - CO					8.18
Carbon Dioxide - CO <sub>2</sub>					15.80
Hydrogen Sulfide - H <sub>2</sub> S					0.16
Methane - CH <sub>4</sub>					1.30
Ethane - C <sub>2</sub> H <sub>6</sub>					0.57
Propane - C <sub>3</sub> H <sub>8</sub>					0.29
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					0.16
Ammonia - NH <sub>3</sub>					0.04
Distillable Oil (IBP-255°C @1.6 Torr)	0.02	2.81	81.11	4.58	94.58
SRL		16.60			16.60
Coal (MAF)		2.25			2.25
Ash		3.16			3.16
Water	0.01		0.28		14.91
Phenol					
Total	0.03	24.82	81.39	4.58	159.06

Elemental	Quantitative					
	Stream Description	Cold Trap	F-1 Btms	←Recycle S-7 Btms	Solvent→ F-2 Btms	Total Out
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
Total						

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1D  
Date: 7/22/77  
Time: 0130-1330

WEIGHT PERCENT

Sample Description	Lignite	F-1 Btms	Makeup Solvent	LEC Btms	Feed Solvent	S-8 Oil
Sample Point	Sx-1	*Sx-2	Sx-8	Sx-12	Sx-14	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Distillable Oil (IBP-255°C @1.6 Torr)		11.35	99.93	100	99.69	98.91
SRL		66.87				
Coal (MAF)	62.27	9.06				
Ash	6.40	12.72				
Water	31.33		0.07		0.31	1.09
Total	100	100	100	100	100	100
P.S. (Ash-free)		89.62				
Melting Point		338				
Specific Gravity 60/60			1.040	1.028	1.042	
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff.)						
Ash						
Total						
Number of Sample Avg.	2	2	2	2	2	2

\*Distillable oil calculated by following equation =  
Wt % Distillable Oil = -0.1273 (F-1 Btms Melting Point) + 54.38  
See attached graph.

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1D  
Date: 7/22/77  
Time: 0130-1330

WEIGHT PERCENT

Sample Description	S-8 Water	S-8 Total	Product Gas	Feed Gas	S-4B Oil	S-4B Water
Sample Point	Sx-16	Sx-16	Sx-19	Sx-21	Sx-23	Sx-23
Hydrogen - H <sub>2</sub>			4.24	7.28		
Carbon Monoxide - CO			32.40	91.65		
Carbon Dioxide - CO <sub>2</sub>			54.82			
Hydrogen Sulfide - H <sub>2</sub> S			0.42			
Methane - CH <sub>4</sub>			4.88			
Ethane - C <sub>2</sub> H <sub>6</sub>			1.93			
Propane - C <sub>3</sub> H <sub>8</sub>			0.76			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>			0.55	1.07		
Ammonia - NH <sub>3</sub> (PPM) (IBP-255°C @1.6 Torr)						0.14
Distillable Oil		98.91			100	
SRL						
Coal (MAF)						
Ash						
Water	100	1.09				99.86
Total	100	100	100	100	100	100
P.S. (Ash-free)						
Melting Point :						
Specific Gravity 60/60						
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff.)						
Ash						
Total						
Number of Sample Avg.	2		2	2	-	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1D  
Date: 7/22/77  
Time: 0130-1330

WEIGHT PERCENT

Sample Description	S-4B Total	S-4A Ovhd	J-1 Discharge	Cold Trap	Recycle Solvent	
Sample Point	Sx-23	Sx-30	Sx-32	Sx-33	Sx-39	
Hydrogen - H <sub>2</sub>		1.99	0.90			
Carbon Monoxide - CO		14.56	9.86			
Carbon Dioxide - CO <sub>2</sub>		71.05	80.21			
Hydrogen Sulfide - H <sub>2</sub> S		1.67				
Methane - CH <sub>4</sub>		3.88	2.80			
Ethane - C <sub>2</sub> H <sub>6</sub>		2.80	2.99			
Propane - C <sub>3</sub> H <sub>8</sub>		2.64	3.24			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>		0.82				
Ammonia - NH <sub>3</sub> (PPM)	0.14	0.59				
Distillable Oil (IBP-255°C @1.6 Torr)	0.30			56.22	99.65	
SRL						
Coal (MAF)						
Ash						
Water	99.56			43.78	0.35	
Total	100	100	100	100	100	
P.S. (Ash-free)						
Melting Point						
Specific Gravity 60/60					1.054	
Viscosity, cp						

Quantitative

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff.)						
Ash						
Total						
Number of Sample Avg.	2	2	2	2		

Elemental

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1D

Date: 7/22/77

Time: 0130-1330


MOLE PERCENT

SAMPLE DESCRIPTION	Product Gas	Feed Gas	S-4A Ovhd	J-1 Disch.		
	Sx-19	Sx-21	Sx-30	Sx-32		
Hydrogen - H <sub>2</sub>	42.91	52.35	27.37	15.06		
Carbon Monoxide - CO	23.41	47.10	14.29	11.85		
Carbon Dioxide - CO <sub>2</sub>	25.20		44.36	61.36		
Hydrogen Sulfide - H <sub>2</sub> S	0.25		1.35			
Methane - CH <sub>4</sub>	6.17		6.67	5.90		
Ethane - C <sub>2</sub> H <sub>6</sub>	1.30		2.56	3.35		
Propane - C <sub>3</sub> H <sub>8</sub>	0.35		1.65	2.48		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.40	0.55	0.80			
Ammonia - NH <sub>3</sub> (PPM)	0.01		0.95			
Light Oils - (0-100°C @ 1.6 Torr)						
Solvent - (100-230°C @ 1.6 Torr)						
Heavy Oil - (230-255°C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100		
Calc. Mole Wt.	20.23	14.39	27.47	33.66		
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2		

DISTILLABLE OIL CONTENT OF F-I BOTTOMS  
VERSUS  
F-I BOTTOMS MELTING POINT



PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 1/24/78

MATERIAL OUT

Run No: L-1D  
Date: 7/22/77  
Time: 0130-1330

Temperature: 718°F  
Pressure: 2500 psig  
LHSV: 1.41  
GHSV: 318

lbs/hour

Stream Description	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
Sample Point	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	0.96	0.07				
Carbon Monoxide - CO	7.30	0.48				0.06
Carbon Dioxide - CO <sub>2</sub>	12.36	2.34				0.44
Hydrogen Sulfide - H <sub>2</sub> S	0.09	0.05				
Methane - CH <sub>4</sub>	1.10	0.13				0.02
Ethane - C <sub>2</sub> H <sub>6</sub>	0.44	0.09				0.02
Propane - C <sub>3</sub> H <sub>8</sub>	0.17	0.09				0.02
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.12	0.03				
Ammonia - NH <sub>3</sub>		0.02	0.02			
Distillable Oil (IBP-255°C @1.6 Torr)			0.04		5.78	
SRI						
Coal (NAF)						
Ash						
Water			13.95		0.06	
Phenol						
Total	22.54	3.30	14.01	Negl.	5.84	0.56

Quantitative

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
Total						

Elemental

PROJECT MIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 1/24/78

MATERIAL OUT

Run No: L-1D  
Date: 7/22/77  
Time: 0130-1330

Temperature: 718°F  
Pressure: 2500 psig  
LHSV: 1.41  
GHSV: 318

lbs/hour

Stream Description	Cold Trap	F-1 Btms	← Recycle Solvent →		Total Out
			S-7 Btms	F-2 Btms	
Sample Point	Sx-33	Sx-2	Sx-39	Sx-12	
Hydrogen - H <sub>2</sub>					1.03
Carbon Monoxide - CO					7.84
Carbon Dioxide - CO <sub>2</sub>					15.14
Hydrogen Sulfide - H <sub>2</sub> S					0.14
Methane - CH <sub>4</sub>					1.25
Ethane - C <sub>2</sub> H <sub>6</sub>					0.55
Propane - C <sub>3</sub> H <sub>8</sub>					0.28
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					0.15
Ammonia - NH <sub>3</sub>					0.04
Distillable Oil (IBP-255°C @1.6 Torr)	0.02	2.70	81.11	4.58	94.23
SRL		15.91			15.91
Coal (MAF)		2.16			2.16
Ash		3.03			3.03
Water	0.01		0.28		14.30
Phenol					
Total	0.03	23.80	81.39	4.58	156.05

Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
Total					


RUN CONDITIONS  
 RUN NO. L-1E  
 DATE MADE 7/22-23/77

TEMPERATURE °F		PRESSURE, psig
PREHEATER E-I	PREHEATER E-13	SEPARATORS S-1 and S-2
SAND BATH <u>738</u>	DOWTHERM <u>595</u>	<u>2500</u>
INLET <u>309</u>	INLET <u>90</u>	SEPARATOR S-3
OUTLET <u>721</u>	OUTLET <u>539</u>	<u>308</u>
DISSOLVERS	LIGHT ENDS COLUMN, F-2	SEPARATORS S-4A and S-4B
R-1A (1) _____	REBOILER <u>461</u>	<u>60</u>
(2) _____	LOWER SECTION <u>561</u>	VACUUM FLASH, F-1
(3) _____	FEED SECTION <u>474</u>	<u>15 Torr</u>
(4) _____	OVERHEAD <u>220</u>	LIGHT ENDS COLUMN, F-2
R-1B (1) <u>742</u>	S-8 <u>93</u>	<u>0</u>
(2) <u>794</u>	S-9 <u>-</u>	SOLVENT COLUMN, F-3
(3) <u>782</u>		<u>NIU</u>
(4) <u>822</u>	SOLVENT COLUMN, F-3	HEAVY ENDS COLUMN, F-4
REACTOR PRODUCT SEPARATORS	REBOILER <u>NIU</u>	<u>NIU</u>
S-1 <u>586</u>	LOWER SECTION _____	VACUUM FLASH, F-0
S-2 <u>79</u>	FEED SECTION _____	<u>NIU</u>
S-3 <u>485</u>	OVERHEAD _____	SETTLING TOWER, V-8
S-4A <u>90</u>		<u>NIU</u>
S-4B <u>88</u>	HEAVY ENDS COLUMN, F-4	RECOVERY TOWER, V-7
PREHEATER E-II	REBOILER <u>NIU</u>	<u>NIU</u>
DOWTHERM <u>676</u>	LOWER SECTION _____	
INLET <u>438</u>	FEED SECTION _____	
OUTLET <u>655</u>	OVERHEAD _____	
VACUUM FLASH F-1	VACUUM FLASH, F-0	
OVERHEAD VAPOR <u>528</u>	OVERHEAD <u>NIU</u>	
UPPER WALL <u>604</u>	BOTTOMS _____	
LOWER WALL <u>585</u>	PRECIPITATION TOWER, V-8	
DOWNCOMER <u>461</u>	ZONE (1) <u>NIU</u>	
CONDENSATE	(2) _____	
ACCUMULATOR, S-7 <u>94</u>	(3) _____	
	RECOVERY TOWER V-9	
	REBOILER <u>NIU</u>	
	OVERHEAD _____	

	Start	End	Run No: L-1E
Date of Run	7/22/77	7/23/77	Units: lbs/hr, °F, psig
Time of Run	1330	0130	Prep. By: GGB & BCL
Length of Run	12	hrs.	Updated: 7/25/77
Hours on Coal at End of Y. P.	174.4		

### MASS RATES AND RUN CONDITIONS

PRODUCT GAS TO THERMAL OXIDIZER	21.82
PRODUCT GAS TO RECYCLE	-0-
K-4 KNOCKOUT POT BTMS	-0-
ABSORBED GASES	NIU
WASTE GAS	3.53
S-4A BOTTOMS	-0-
S-4B BOTTOMS	16.92
TOLUENE ACCUMULATOR	NIU
D.C. OHD	Negl.
LIGHT OILS	4.93
V-9 BOTTOMS	NIU
J-1 EXHAUST GASES	0.57
COLD TRAP	0.59
V-8 BOTTOMS	NIU
VACUUM BOTTOMS	24.18
A-5A OVERFLOW	-



157.79 TOTAL

☒ OPEN

☒ CLOSED

TOTAL 157.79

Numbers in parentheses are not included in the totals.

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Normalized with Forced Carbon Balance by Adjusting S-4B oil/H<sub>2</sub>O ratio

Revised: 12/22/77

Run No: L-1E  
Date: 7/22-23/77  
Time: 1330-0130

SUMMARY

Temperature: 721°F  
Pressure: 2500 psig  
LHSV: 1.46  
GHSV: 304

	lbs/hour				Wt % MAF Lignite	
	Total In	Total Out	Net Yield			
STREAM DESCRIPTION						
SAMPLE POINT						
Hydrogen - H <sub>2</sub>	1.20	1.04	-0.16	} 9.47	30.98	
Carbon Monoxide - CO	15.06	6.95	-8.11			
Carbon Dioxide - CO <sub>2</sub>		15.49	15.49			
Hydrogen Sulfide - H <sub>2</sub> S		0.17	0.17			
Methane - CH <sub>4</sub>		1.21	1.21			
Ethane - C <sub>2</sub> H <sub>6</sub>		0.54	0.54			
Propane - C <sub>3</sub> H <sub>8</sub>		0.33	0.33			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.21	0.17	-0.04			
Ammonia - NH <sub>3</sub>		0.04	0.04			
Light Oil - (0-100°C @ 1.6 Torr)	6.72	12.14	5.42	} 21.89	71.60	
Solvent - (100-230°C @ 1.6 Torr)	80.97	81.76	0.79			
Heavy Oil - (230-255°C @1.6 Torr)	4.93	3.52	-1.41			
SRL		17.09	17.09			
Cool (MAF)	30.57	0.99	-29.58		-96.76	
Ash	2.72	2.56	-0.16		-0.52	
Water	15.41	13.79	-1.62		-5.30	
Phenol						
TOTAL	157.79	157.79	-0-			

Elemental	Carbon	108.66	108.66	-0-		
	Hydrogen	11.66	11.72	0.06		
	Nitrogen	0.71	0.66	-0.05		
	Sulfur	1.74	1.97	0.23		
	Oxygen (by diff)	32.30	32.22	-0.08		
	Ash	2.72	2.56	-0.16		
	TOTAL	157.79	157.79	-0-		

PROJECT LIGNITE  
MEASURED & ADJUSTED MATERIAL BALANCE  
Revised: 12/22/77

Run No: L-1E  
Date: 7/22-23/77  
Time: 1330-0130

MATERIAL IN

Temperature: 721°F  
Pressure: 2500 psig  
LHSV: 1.46  
GHSV: 304

lbs/hour

Quantitative	STREAM DESCRIPTION	Feed Gas	Lignite	Feed Solvent		Total In
		SAMPLE POINT	Sx-21	Sx-1	Sx-14	
	Hydrogen - H <sub>2</sub>	1.20				1.20
	Carbon Monoxide - CO	15.06				15.06
	Carbon Dioxide - CO <sub>2</sub>					
	Hydrogen Sulfide - H <sub>2</sub> S					
	Methane - CH <sub>4</sub>					
	Ethane - C <sub>2</sub> H <sub>6</sub>					
	Propane - C <sub>3</sub> H <sub>8</sub>					
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>	0.21				0.21
	Ammonia - NH <sub>3</sub>					
	Light Oil - (0-100°C @ 1.6 Torr)			6.72		6.72
	Solvent - (100-230°C @ 1.6 Torr)			80.97		80.97
	Heavy Oil - (230-255°C @ 1.6 Torr)			4.93		4.93
	SRL					
	Coal (MAF)		30.57			30.57
	Ash		2.72			2.72
	Water		15.07	0.34		15.41
	Phenol					
	TOTAL	16.47	48.36	92.96		157.79

Elemental	Carbon		Hydrogen		Nitrogen		Sulfur		Oxygen (by diff)		Ash	
		6.45	21.40	80.81								
	1.20	3.17	7.29									
	0.21	0.30	0.20									
		0.25	1.49									
	8.61	20.52	3.17									
		2.72										
	TOTAL	16.47	48.36	92.96								157.79

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized with Forced Carbon Balance by Adjusting S-4B Oil/H<sub>2</sub>O Ratio  
 Revised: 12/22/77

Run No: L-1E  
 Date: 7/22-23/77  
 Time: 1330-0130

MATERIAL OUT

Temperature: 721°F  
 Pressure: 2500 psig  
 LHSV: 1.46  
 GHSV: 304

		lbs/hour					
Quantitative	STREAM DESCRIPTION	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
	SAMPLE POINT	Sx-19	Sx-30	calc.	Sx-44	Sx-16	Sx-32
	Hydrogen - H <sub>2</sub>	0.97	0.06				0.01
	Carbon Monoxide - CO	6.49	0.40				0.06
	Carbon Dioxide - CO <sub>2</sub>	12.36	2.68				0.45
	Hydrogen Sulfide - H <sub>2</sub> S	0.11	0.06				
	Methane - CH <sub>4</sub>	1.09	0.11				0.01
	Ethane - C <sub>2</sub> H <sub>6</sub>	0.42	0.10				0.02
	Propane - C <sub>3</sub> H <sub>8</sub>	0.22	0.09				0.02
	Butane - C <sub>4</sub> H <sub>10</sub>						
	Nitrogen - N <sub>2</sub>	0.15	0.02				
	Ammonia - NH <sub>3</sub>	0.01	0.01	0.02			
	Light Oil - (0-100°C @ 1.6 Torr)			1.75		4.53	
	Solvent - (100-230°C @ 1.6 Torr)			1.84		0.13	
	Heavy Oil - (230-255°C @ 1.6 Torr)			0.21		0.21	
	SRL						
	Coal (MAF)						
	Ash						
	Water			13.10		0.06	
	Phenol						
	TOTAL	21.82	3.53	16.92	Negl.	4.93	0.57
Elemental	Carbon	7.49	1.13	3.20		3.87	0.19
	Hydrogen	1.38	0.14	1.81		0.50	0.01
	Nitrogen	0.16	0.03	0.02		0.01	
	Sulfur	0.10	0.05	0.04		0.02	
	Oxygen (by diff)	12.69	2.18	11.85		0.53	0.37
	Ash						
	TOTAL	21.82	3.53	16.92	Negl.	4.93	0.57

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Normalized with Forced Carbon Balance by Adjusting S-4B Oil/H<sub>2</sub>O Ratio.  
Revised: 12/22/77

Run No: L-1E  
Date: 7/22-23/77  
Time: 1330-0130

MATERIAL OUT

Temperature: 721°F  
Pressure: 2500 psig  
LHSV: 1.46  
GHSV: 304

lbs/hour

STREAM DESCRIPTION	Cold Trap	F-1 Btms	←Recycle Solvent→		Total Out
			S-7 Btms	F-2 Btms	
SAMPLE POINT	Sx-33	Sx-2	Sx-39	Sx-12	
Hydrogen - H <sub>2</sub>					1.04
Carbon Monoxide - CO					6.95
Carbon Dioxide - CO <sub>2</sub>					15.49
Hydrogen Sulfide - H <sub>2</sub> S					0.17
Methane - CH <sub>4</sub>					1.21
Ethane - C <sub>2</sub> H <sub>6</sub>					0.54
Propane - C <sub>3</sub> H <sub>8</sub>					0.33
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					0.17
Ammonia - NH <sub>3</sub>					0.04
Light Oil - (0-100°C @ 1.6 Torr)	0.12		5.74		12.14
Solvent - (100-230°C @ 1.6 Torr)	0.40	3.54	72.48	3.37	81.76
Heavy Oil - (230-255°C @ 1.6 Torr)			3.03	0.07	3.52
SRL		17.09			17.09
Coal (MAF)		0.99			0.99
Ash		2.56			2.56
Water	0.07		0.56		13.79
Phenol					
TOTAL	0.59	24.18	81.81	3.44	157.79

Carbon	0.45	18.91	70.38	3.04	108.66
Hydrogen	0.05	1.22	6.32	0.29	11.72
Nitrogen		0.24	0.19	0.01	0.66
Sulfur	0.01	0.23	1.46	0.06	1.97
Oxygen (by diff)	0.08	1.02	3.46	0.04	32.22
Ash		2.56			2.56
TOTAL	0.59	24.18	81.81	3.44	157.79

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/22/77

Run No: L-1E

Date: 7/22-23/77

Time: 1330-0130

WEIGHT PERCENT

SAMPLE DESCRIPTION	Feed Coal	F-1 Btms	Makeup Solvent	F-2 Btms	Feed Solvent	S-8 Oil
SAMPLE POINT	Sx-1	Sx-2	Sx-8	Sx-12	Sx-14	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100°C @ 1.6 Torr)			3.73		7.23	91.86
Solvent - (100-230°C @ 1.6 Torr)		14.62	89.50	98.00	87.10	2.60
Heavy Oil - (230-255°C @ 1.6 Torr)			6.70	2.00	5.30	4.30
SRL		70.70				
Coal (MAF)	63.22	4.10				
Ash	5.62	10.58				
Water	31.16		0.07		0.37	1.24
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		95.42				
Melting Point °F		290				
Specific Gravity 60/60			1.040	1.032	1.054	
Viscosity, cp						

Carbon	44.25	78.20	87.39	88.49	86.93	78.57
Hydrogen	6.55	5.04	8.16	8.29	7.84	10.17
Nitrogen	0.63	1.00	0.10	0.23	0.22	0.27
Sulfur	0.51	0.96	2.28	1.79	1.60	0.32
Oxygen (by diff)	42.44	4.22	2.07	1.20	3.41	10.67
Ash	5.62	10.58				
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/22/77

Run No: L-1E  
Date: 7/22-23/77  
Time: 1330-0130

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-8 Water	S-8 Total	Product Gas	Feed Gas	S-4B Oil	S-4B Water
SAMPLE POINT	Sx-16	Sx-16	Sx-19	Sx-21	Sx-23	Sx-23
Hydrogen -H <sub>2</sub>			4.44	7.28		
Carbon Monoxide-CO			29.73	91.46		
Carbon Dioxide-CO <sub>2</sub>			56.63			
Hydrogen Sulfide-H <sub>2</sub> S			0.51			
Methane-CH <sub>4</sub>			5.01			
Ethane-C <sub>2</sub> H <sub>6</sub>			1.95			
Propane-C <sub>3</sub> H <sub>8</sub>			0.99			
Butane-C <sub>4</sub> H <sub>10</sub>						
Nitrogen-N <sub>2</sub>			0.70	1.26		
Ammonia-NH <sub>3</sub> (PPM)			0.04			0.12
Light Oils-(0-100°C @ 1.6 Torr)		91.86			45.37	
Solvent-(100-230°C @ 1.6 Torr)		2.60			47.50	
Heavy Oil-(230-255°C @1.6 Torr)		4.30			5.50	
SRL						
Coal (MAF)						
Ash						
Water	100	1.24			1.63	99.88
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon		78.57	34.31	39.20	82.77	
Hydrogen	11.11	10.17	6.30	7.28	9.13	11.12
Nitrogen		0.27	0.73	1.26	0.25	0.10
Sulfur		0.32	0.48		1.00	
Oxygen (by diff)	88.89	10.67	58.18	52.26	6.85	88.78
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/22/77

Run No: L-1E  
Date: 7/22-23/77  
Time: 1330-0130

SAMPLE DESCRIPTION	WEIGHT PERCENT						
	S-4B Total	S-4A Ovhd	J-1 Disch.	Cold Trap	S-4A Oil	S-4A Water	
SAMPLE POINT	Sx-23	Sx-30	Sx-32	Sx-33	Sx-37	Sx-37	
Hydrogen - H <sub>2</sub>		1.85	0.83				
Carbon Monoxide - CO		11.32	10.77				
Carbon Dioxide - CO <sub>2</sub>	SEE CALCULATED S-4B COMPOSITION	75.86	79.76				
Hydrogen Sulfide - H <sub>2</sub> S		1.60					
Methane - CH <sub>4</sub>		3.10	2.27				
Ethane - C <sub>2</sub> H <sub>6</sub>		2.72	3.03				
Propane - C <sub>3</sub> H <sub>8</sub>		2.53	3.34				
Butane - C <sub>4</sub> H <sub>10</sub>							
Nitrogen - N <sub>2</sub>			0.63				
Ammonia - NH <sub>3</sub> (PPM)		0.10	0.39			0.20	
Light Oils - (0-100°C @ 1.6 Torr)		5.90			19.88	52.85	
Solvent - (100-230°C @ 1.6 Torr)		6.18			68.31	42.98	
Heavy Oil - (230-255°C @1.6 Torr)	0.71				3.30		
SRL							
Coal (MAF)							
Ash							
Water	87.11			11.81	0.87	99.80	
Phenol							
TOTAL	100	100	100	100	100	100	
Pyridine Solubles (Wt % Ash free)							
Melting Point °F							
Specific Gravity 60/60					0.975		
Viscosity, cp							

Carbon	10.76	32.11	33.22	76.93	83.29	
Hydrogen	10.86	3.79	2.62	8.51	9.55	11.13
Nitrogen	0.12	0.95		0.40	0.23	0.16
Sulfur	0.13	1.51		0.98	0.90	
Oxygen (by diff)	78.13	61.64	64.16	13.18	6.03	88.71
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	5	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/22/77

Run No: L-1E  
Date: 7/22-23/77  
Time: 1330-0130

WEIGHT PERCENT

	S-4A	Recycle		S-4B		
	Total	Solvent		Btms		
SAMPLE DESCRIPTION	Sx-37	Sx-39		Calc.		
SAMPLE POINT						
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)				0.09		
Light Oils - (0-100° C @ 1.6 Torr)	52.59	7.02		10.38		
Solvent - (100-230° C @ 1.6 Torr)	42.77	88.60		10.86		
Heavy Oil - (230-255° C @ 1.6 Torr)	3.28	3.70		1.26		
SRL						
Coal (MAF)						
Ash						
Water	1.36	0.68		77.41		
Phenol						
TOTAL	100	100		100		
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60		1.052				
Viscosity, cp						

Carbon	82.87	86.03		18.93		
Hydrogen	9.56	7.73		10.67		
Nitrogen	0.23	0.23		0.14		
Sulfur	0.90	1.78		0.23		
Oxygen (by diff)	6.44	4.23		70.03		
Ash						
TOTAL	100	100		100		
Number of Sample Avg.	2	2		-		

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/22/77

Run No: L-1E

Date: 7/22-23/77

Time: 1330-0130

MOLE PERCENT

SAMPLE DESCRIPTION	Product Gas	Feed Gas	S-4A Ovhd	J-1 Disch.		
	Sx-19	Sx-21	Sx-30	Sx-32		
Hydrogen - H <sub>2</sub>	44.27	52.35	26.50	14.16		
Carbon Monoxide - CO	21.19	47.00	11.60	13.12		
Carbon Dioxide - CO <sub>2</sub>	25.69		49.45	61.84		
Hydrogen Sulfide - H <sub>2</sub> S	0.30		1.35			
Methane - CH <sub>4</sub>	6.25		5.55	4.84		
Ethane - C <sub>2</sub> H <sub>6</sub>	1.30		2.60	3.45		
Propane - C <sub>3</sub> H <sub>8</sub>	0.45		1.65	2.59		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.50	0.65	0.65			
Ammonia - NH <sub>3</sub> (PPM)	0.05		0.65			
Light Oils - (0-100°C @ 1.6 Torr)						
Solvent - (100-230°C @ 1.6 Torr)						
Heavy Oil - (230-255°C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100		
Calc. Mole Wt.	19.96	14.39	28.68	34.12		
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Elemental	Quantitative						
	Sx-19	Sx-21	Sx-30	Sx-32			
Carbon							
Hydrogen							
Nitrogen							
Sulfur							
Oxygen (by diff)							
Ash							
TOTAL							
Number of Sample Avg.	2	2	2	2			

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: L-1E  
DATE: 7/22-23/77  
TIME: 1330-0130

SAMPLE DESCRIPTION	F-1 Btms	Makeup Solv	LEC Btms	Feed Solv.	S-8 Oil
SAMPLE POINT	Sx-2	Sx-8	Sx-12	Sx-14	Sx-16
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR IBP 5% 10% 20% 30% 40% 50% 60% 70% 80% 90% 95% DRY PT.	TEMPERATURE, °C		5	5	5
		73.5	150	67	
		134	155.5	106	
		164	161.5	133	
		187	165.5	165	
		193	172.0	180	
		198	179.0	187	
		203	182.6	193	
		208	187.4	198	
		218	193.2	205	
		226	197.5	212	
		240	210.0	228	
		252.5	229.5	249	
		260	233.2	260	
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR IBP 5% 10% 20% 30% 40% 50% 60% 70% 80% 90% 95% DRY PT.	TEMPERATURE, °C				742
					67
					79
					84
					158
					186
					200
					210
					223
					235
					246
					260
					290
					290
ASPHALTENE TEST					
WT % ASH	10.58				
WT % UNCONVERTED COAL	4.10				
WT % PRE-ASPHALTENES	37.68				
WT % ASPHALTENES	20.44				
WT % MALTENES & DIST. OIL	27.20				
TOTAL	100.00				
SAYBOLT VISCOSITY, SSU					
100° F		15.7	13.0	14.0	
210° F		9.2	8.5	8.7	
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)		0.07	0.09	0.37	1.24
INFRARED RATIO			0.35	0.28	
SP. GRAV. 60/60 F		1.040	1.032	1.054	

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES - BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES - N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION. USUALLY LESS THAN 5% FOR THE F-1 VACUUM BOTTOMS MATERIAL

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: L-1E  
DATE: 7/22-23/77  
TIME: 1330-0130

SAMPLE DESCRIPTION	S-4B Oil	S-4A Oil	Recycle Solv.	
SAMPLE POINT	Sx-23	Sx-37	Sx-39	
ASTM D-1160 DISTILLATION DATA				
PRESSURE, TORR			5	
IBP			68	
5%			105	
10%			131	
20%			164	
30%			178	
40%			186	
50%			194	
60%			198	
70%			204	
80%			210	
90%			226	
95%			247	
DRY PT.			263	
ASTM D-86 DISTILLATION DATA				
BAROMETRIC PRESSURE, TORR	747	752		
IBP	84	79		
5%	147.5	182		
10%	182	192		
20%	205	216		
30%	228.5	254		
40%	258	280		
50%	284	290		
60%	312	316		
70%	336	340		
80%	362	355		
90%		360		
95%				
DRY PT.	362	360		
ASPHALTENE TEST				
WT % ASH				
WT % UNCONVERTED COAL				
WT % PRE-ASPHALTENES				
WT % ASPHALTENES				
WT % MALTENES & DIST. OIL				
TOTAL				
SAYBOLT VISCOSITY, SSU				
100° F			14.4	
210° F			8.5	
MISCELLANEOUS				
KF H <sub>2</sub> O WT% (Raw Sx)	1.63	0.87	0.68	
INFRARED RATIO			0.36	
SP. GRAV. 60/60 F		0.975	1.052	

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES - BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES - N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION, USUALLY LESS THAN 5% FOR THE F-1 VACUUM BOTTOMS MATERIAL

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 12/22/77

Run No: L-1E  
Date: 7/22-23/77  
Time: 1330-0130

MATERIAL OUT

Temperature: 721°F  
Pressure: 2500 psig  
LHSV: 1.46  
GHSV: 304

lbs/hour

STREAM DESCRIPTION	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	0.96	0.06				0.01
Carbon Monoxide - CO	6.44	0.40				0.06
Carbon Dioxide - CO <sub>2</sub>	12.26	2.65				0.45
Hydrogen Sulfide - H <sub>2</sub> S	0.11	0.06				
Methane - CH <sub>4</sub>	1.09	0.11				0.01
Ethane - C <sub>2</sub> H <sub>6</sub>	0.42	0.10				0.02
Propane - C <sub>3</sub> H <sub>8</sub>	0.21	0.09				0.02
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.15	0.02				
Ammonia - NH <sub>3</sub>	0.01	0.01	0.02			
Light Oil - (0-100°C @ 1.6 Torr)			0.99		4.49	
Solvent - (100-230°C @ 1.6 Torr)			1.04		0.13	
Heavy Oil - (230-255°C @ 1.6 Torr)			0.12		0.21	
SRL						
Coal (MAF)						
Ash						
Water			14.62		0.06	
Phenol						
<b>TOTAL</b>	<b>21.65</b>	<b>3.50</b>	<b>16.79</b>	<b>Negl.</b>	<b>4.89</b>	<b>0.57</b>

Carbon	7.43	1.13	1.81		3.84	0.19
Hydrogen	1.36	0.13	1.83		0.50	0.01
Nitrogen	0.16	0.03	0.02		0.01	
Sulfur	0.10	0.05	0.01		0.02	
Oxygen (by diff)	12.60	2.16	13.12		0.52	0.37
Ash						
<b>TOTAL</b>	<b>21.65</b>	<b>3.50</b>	<b>16.79</b>	<b>Negl.</b>	<b>4.89</b>	<b>0.57</b>

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 12/22/77

Run No: L-1E  
Date: 7/22-23/77  
Time: 1330-0130

MATERIAL OUT

Temperature: 721°F  
Pressure: 2500 psig  
LHSV: 1.46  
GHSV: 304

lbs/hour

STREAM DESCRIPTION	Cold Trap	F-1 Btms	←Recycle S-7 Btms	Solvent → F-2 Btms	Total Out
	Sx-33	Sx-2	Sx-39	Sx-12	
Hydrogen - H <sub>2</sub>					1.03
Carbon Monoxide - CO					6.90
Carbon Dioxide - CO <sub>2</sub>					15.36
Hydrogen Sulfide - H <sub>2</sub> S					0.17
Methane - CH <sub>4</sub>					1.21
Ethane - C <sub>2</sub> H <sub>6</sub>					0.54
Propane - C <sub>3</sub> H <sub>8</sub>					0.32
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					0.17
Ammonia - NH <sub>3</sub>					0.04
Light Oil - (0-100°C @ 1.6 Torr)	0.11		5.74		11.33
Solvent - (100-230°C @ 1.6 Torr)	0.40	3.51	72.48	3.37	80.93
Heavy Oil - (230-255°C @ 1.6 Torr)			3.03	0.07	3.43
SRL		16.96			16.96
Coal (MAF)		0.98			0.98
Ash		2.54			2.54
Water	0.07		0.56		15.31
Phenol					
TOTAL	0.58	23.99	81.81	3.44	157.22

ELEMENTAL	Quantitative					TOTAL
	Cold Trap	F-1 Btms	←Recycle S-7 Btms	Solvent → F-2 Btms	Total Out	
Carbon	0.45	18.76	70.38	3.04		107.03
Hydrogen	0.05	1.21	6.32	0.29		11.70
Nitrogen	-	0.24	0.19	0.01		0.66
Sulfur	-	0.23	1.46	0.06		1.93
Oxygen (by diff)	0.08	1.01	3.46	0.04		33.36
Ash		2.54				2.54
TOTAL	0.58	23.99	81.81	3.44		157.22

RUN CONDITIONS

RUN NO. L-1F  
 DATE MADE 7/28-29/77

TEMPERATURE °F

PRESSURE, psig

PREHEATER E-1  
 SAND BATH 723  
 INLET 305  
 OUTLET 715

DISSOLVERS  
 R-1A (1) 770  
 (2) 811  
 (3) 804  
 (4) 828  
 R-1B (1) \_\_\_\_\_  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_  
 (4) \_\_\_\_\_

REACTOR PRODUCT SEPARATORS  
 S-1 614  
 S-2 80  
 S-3 463  
 S-4A 82  
 S-4B 79

PREHEATER E-11  
 DOWTHERM 677  
 INLET 365  
 OUTLET 650

VACUUM FLASH F-1  
 OVERHEAD VAPOR 507  
 UPPER WALL 627  
 LOWER WALL 593  
 DOWNCOMER 439  
 CONDENSATE  
 ACCUMULATOR, S-7 86

PREHEATER E-13  
 DOWTHERM 596  
 INLET 80  
 OUTLET 565

LIGHT ENDS COLUMN, F-2  
 REBOILER 406  
 LOWER SECTION 526  
 FEED SECTION 450  
 OVERHEAD 213  
 S-8 85  
 S-9 -

SOLVENT COLUMN, F-3  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

HEAVY ENDS COLUMN, F-4  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

VACUUM FLASH, F-0  
 OVERHEAD 440  
 BOTTOMS 495

PRECIPITATION TOWER, V-8  
 ZONE (1) 417  
 (2) 418  
 (3) 428

RECOVERY TOWER V-9  
 REBOILER 493  
 OVERHEAD 330

SEPARATORS S-1 and S-2  
2500

SEPARATOR S-3  
273

SEPARATORS S-4A and S-4B  
60

VACUUM FLASH, F-1  
14 Torr

LIGHT ENDS COLUMN, F-2  
0

SOLVENT COLUMN, F-3  
NIU

HEAVY ENDS COLUMN, F-4  
NIU

VACUUM FLASH, F-0  
14 Torr


SETTLING TOWER, V-8  
300

RECOVERY TOWER, V-7  
2

	Start	End	Run No: L-1F
Date of Run	7/28/77	7/29/77	Units: lbs/hr, °F, psig
Time of Run	2100	0900	Prep. By: BCL & GGB
Length of Run	12	hrs.	Updated: 1/4/78
Hours on Coal at End of Y.P.	313.9		

### MASS RATES AND RUN CONDITIONS

PRODUCT GAS TO THERMAL	24.66
OXIDIZER	-0-
PRODUCT GAS TO RECYCLE	-0-



252.39 TOTAL      OPEN      CLOSED      TOTAL 252.39

Numbers in parentheses are not included in the totals.

PROJECT : IGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized  
 Revised: 1/4/78

Run No: L-1F  
 Date: 7/28/77  
 Time: 2100-0900

SUMMARY

Temperature: 715°F  
 Pressure: 2500 psig  
 LHSV: 1.44  
 GHSV: 323

lbs/hour

Stream Description	Total In	Total Out	Net Yield		Wt % MAF Coal	
Sample Point						
Hydrogen - H <sub>2</sub>	1.30	1.07	-0.23	}		
Carbon Monoxide - CO	15.68	7.23	-8.45			
Carbon Dioxide - CO <sub>2</sub>		18.53	18.53			
Hydrogen Sulfide - H <sub>2</sub> S		0.18	0.18			
Methane - CH <sub>4</sub>		1.40	1.40			
Ethane - C <sub>2</sub> H <sub>6</sub>		0.64	0.64		12.53	40.24
Propane - C <sub>3</sub> H <sub>8</sub>		0.48	0.48			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.22	0.16	-0.06			
Ammonia - NH <sub>3</sub>		0.04	0.04			
Distillable Oil (IBP-255°C @ 1.6 Torr)	184.63	185.91	1.28	}	17.48	
SRL		16.20	16.20			
Coal (MAF)	31.14	2.78	-28.36		-91.07	
Ash	3.38	3.24	-0.14		-0.45	
Water	16.04	14.53	-1.51		-4.85	
Phenol						
<b>Total</b>	<b>252.39</b>	<b>252.39</b>	<b>-0-</b>			

Elemental					
Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
<b>Total</b>					

PROJECT LIGNITE  
 MEASURED & ADJUSTED MATERIAL BALANCE  
 Revised: 1/4/78

MATERIAL IN

Run No: L-1F  
 Date: 7/28/77  
 Time: 2100-0900

Temperature: 715°F  
 Pressure: 2500 psig  
 LHSV: 1.44  
 GHSV: 323

lbs/hour

Stream Description	Feed Gas	Lignite	Feed Solvent	Feed Toluene	Total In
Sample Point	Sx-21	Sx-1	Sx-14	Sx-40	
Hydrogen - H <sub>2</sub>	1.30				1.30
Carbon Monoxide - CO	15.68				15.68
Carbon Dioxide - CO <sub>2</sub>					
Hydrogen Sulfide - H <sub>2</sub> S					
Methane - CH <sub>4</sub>					
Ethane - C <sub>2</sub> H <sub>6</sub>					
Propane - C <sub>3</sub> H <sub>8</sub>					
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.22				0.22
Ammonia - NH <sub>3</sub>					
(IBP-255°C @1.6 Torr) Distillable Oil			93.57	91.06	184.63
SRL					
Coal (MAF)		31.14			31.14
Ash		3.38			3.38
Water		15.74	0.30		16.04
Phenol					
<b>Total</b>	<b>17:20</b>	<b>50.26</b>	<b>93.87</b>	<b>91.06</b>	<b>252.39</b>

Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
<b>Total</b>					

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized  
 Revised: 1/4/78

Run No: L-1F  
 Date: 7/28/77  
 Time: 2100-0900

MATERIAL OUT

Temperature: 715°F  
 Pressure: 2500 psig  
 LHSV: 1.44  
 GHSV: 323

lbs/hour

Stream Description	Product Gas	lbs/hour				
		S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
Sample Point	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	1.00	0.06				0.01
Carbon Monoxide - CO	6.74	0.44				0.05
Carbon Dioxide - CO <sub>2</sub>	14.63	3.29				0.61
Hydrogen Sulfide - H <sub>2</sub> S	0.12	0.06				
Methane - CH <sub>4</sub>	1.24	0.14				0.02
Ethane - C <sub>2</sub> H <sub>6</sub>	0.50	0.12				0.02
Propane - C <sub>3</sub> H <sub>8</sub>	0.29	0.15				0.04
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.13	0.03				
Ammonia - NH <sub>3</sub>	0.01	0.01	0.01		0.01	
(IBP-255°C @1.6 Torr) Distillable Oil			0.34		10.04	
SRL						
Coal (MAF)						
Ash						
Water			9.40		4.84	
Phenol						
Total	24.66	4.30	9.75	Negl.	14.89	0.75

Elemental	lbs/hour					
	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
Total						

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized  
 Revised: 1/4/78

Run No: L-1F  
 Date: 7/28/77  
 Time: 2100-0900

MATERIAL OUT

Temperature: 715°F  
 Pressure: 2500 psig  
 LHSV: 1.44  
 GHSV: 323

lbs/hour

Stream Description	Cold Trap	V-8 Btms	F-1 Btms	V-9 Ovhd	Recycle S-7 Btms	Solvent F-2 Btms
Sample Point	Sx-33	Sx-27	Sx-2	Sx-28	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
(IBP-255°C @1.6 Torr)						
Distillable Oil	0.60	11.42	3.75	78.51	72.16	9.09
SRL		5.49	10.71			
Coal (MAF)		2.36	0.42			
Ash		2.22	1.02			
Water	0.08				0.21	
Phenol						
Total	0.68	21.49	15.90	78.51	72.37	9.09

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
Total						

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized  
 Revised: 1/4/78

Run No: L-1F  
 Date: 7/28/77  
 Time: 2100-0900

MATERIAL OUT

Temperature: 715°F  
 Pressure: 2500 psig  
 LHSV: 1.44  
 GHSV: 323

lbs/hour

Stream Description						Total Out
Sample Point						
Hydrogen - H <sub>2</sub>						1.07
Carbon Monoxide - CO						7.23
Carbon Dioxide - CO <sub>2</sub>						18.53
Hydrogen Sulfide - H <sub>2</sub> S						0.18
Methane - CH <sub>4</sub>						1.40
Ethane - C <sub>2</sub> H <sub>6</sub>						0.64
Propane - C <sub>3</sub> H <sub>8</sub>						0.48
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						0.16
Ammonia - NH <sub>3</sub>						0.04
Distillable Oil (IBP-255°C @1.6 Torr)						185.91
SRL						16.20
Coal (MAF)						2.78
Ash						3.24
Water						14.53
Phenol						
Total						252.39

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	Total					

PROJECT LIGNITE  
 SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1F  
 Date: 7/28/77  
 Time: 2100-0900

WEIGHT PERCENT

Sample Description	Lignite	F-1 Btms	Makeup Solvent	LEC Btms	Feed Solvent	S-8 Oil
Sample Point	Sx-1	*Sx-2	Sx-8	Sx-12	Sx-14	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
(IBP-255°C @1.6 Torr)						
Distillable Oil		23.57	99.80	100	99.68	100
SRL		67.33				
Coal (MAF)	61.96	2.66				
Ash	6.72	6.44				
Water	31.32		0.20		0.32	
Total	100	100	100	100	100	100
P.S. (Ash-free)		97.16				
Melting Point		242				
Specific Gravity 60/60			1.040	1.032	1.033	
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff.)						
Ash						
Total						
Number of Sample Avg.	2	2	2	2	2	2

\*Distillable oil calculated by following equation:

$$\text{Wt \% Distillable Oil} = -0.1273 (\text{F-1 Btms Melting Point}) + 54.38$$

See graph.

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1F  
Date: 7/28/77  
Time: 2100-0900

WEIGHT PERCENT

Sample Description	S-8 Water	S-8 Total	Product Gas	Feed Gas	S-4B Oil	S-4B Water
Sample Point	Sx-16	Sx-16	Sx-19	Sx-21	Sx-23	Sx-23
Hydrogen - H <sub>2</sub>			4.07	7.55		
Carbon Monoxide - CO			27.32	91.16		
Carbon Dioxide - CO <sub>2</sub>			59.31			
Hydrogen Sulfide - H <sub>2</sub> S			0.49			
Methane - CH <sub>4</sub>			5.04			
Ethane - C <sub>2</sub> H <sub>6</sub>			2.02			
Propane - C <sub>3</sub> H <sub>8</sub>			1.16			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>			0.54	1.29		
Ammonia - NH <sub>3</sub> (PPM)	0.13	0.04	0.05			0.13
Distillable Oil (IBP-255°C @ 1.6 Torr)		67.43			100	
SRL						
Coal (MAF)						
Ash						
Water	99.87	32.53				99.87
Total	100	100	100	100	100	100
P.S. (Ash-free)						
Melting Point						
Specific Gravity 60/60						
Viscosity, cp						

Quantitative

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (bv diff.)						
Ash						
Total						
Number of Sample Avg.	2	2	2	2	-	2

Elemental

PROJECT LIGNITE  
 SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1F  
 Date: 7/28/77  
 Time: 2100-0900

WEIGHT PERCENT

Sample Description	S-4B Total	V-8 Btms	V-9 Ovhd	S-4A Ovhd	J-1 Disch.	Cold Trap
Sample Point	Sx-23	*Sx-27	Sx-28	Sx-30	Sx-32	Sx-33
Hydrogen - H <sub>2</sub>				1.42	0.68	
Carbon Monoxide - CO				10.24	6.22	
Carbon Dioxide - CO <sub>2</sub>				76.50	82.00	
Hydrogen Sulfide - H <sub>2</sub> S				1.44		
Methane - CH <sub>4</sub>				3.19	2.18	
Ethane - C <sub>2</sub> H <sub>6</sub>				2.79	3.23	
Propane - C <sub>3</sub> H <sub>8</sub>				3.59	5.69	
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>				0.69		
Ammonia - NH <sub>3</sub> (PPM)	0.13			0.14		
(1BP-255°C @1.6 Torr)						
Distillable Oil	3.43	53.14	100			88.19
SRL		25.55				
Coal (MAF)		10.98				
Ash		10.33				
Water	96.44					11.81
Total	100	100	100	100	100	100
P.S. (Ash-free)						
Melting Point						
Specific Gravity 60/60						
Viscosity, cp						

Elemental						
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff.)						
Ash						
Total						
Number of Sample Avg.	-	-	-	2	2	2

\*Composition calculated by mass balance around area 03.

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1F  
Date: 7/28/77  
Time: 2100-0900

WEIGHT PERCENT

Sample Description	Recycle Solvent	Deashing Solvent				
Sample Point	Sx-39	Sx-40				
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
(IBP-255°C @1.6 Torr)						
Distillable Oil	99.71	100				
SRL						
Coal (MAF)						
Ash						
Water	0.29					
Total	100	100				
P.S. (Ash-free)						
Melting Point						
Specific Gravity 60/60	1.034					
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff.)						
Ash						
Total						
Number of Sample Avg.	-	-				

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1F

Date: 7/28/77

Time: 2100-0900

MOLE PERCENT


SAMPLE DESCRIPTION	Product Gas	Feed GAS	S-4A Ovhd	J-1 Disch.		
	Sx-19	Sx-21	Sx-30	Sx-32		
Hydrogen - H <sub>2</sub>	42.39	53.35	21.80	12.19		
Carbon Monoxide - CO	20.30	46.00	11.20	7.94		
Carbon Dioxide - CO <sub>2</sub>	28.05		53.25	66.55		
Hydrogen Sulfide - H <sub>2</sub> S	0.30		1.30			
Methane - CH <sub>4</sub>	6.55		6.10	4.86		
Ethane - C <sub>2</sub> H <sub>6</sub>	1.40		2.85	3.84		
Propane - C <sub>3</sub> H <sub>8</sub>	0.55		2.50	4.62		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.40	0.65	0.75			
Ammonia - NH <sub>3</sub> (PPM)	0.06		0.25			
Light Oils - (0-100° C @ 1.6 Torr)						
Solvent - (100-230° C @ 1.6 Torr)						
Heavy Oil - (230-255° C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100		
Calc Mole Wt	20.81	14.13	30.63	35.71		
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Quantitative

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2		

Elemental

DISTILLABLE OIL CONTENT OF F-I BOTTOMS  
VERSUS  
F-I BOTTOMS MELTING POINT



PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 1/4/78

MATERIAL OUT

Run No: L-1F  
Date: 7/28/77  
Time: 2100-0900

Temperature: 715°F  
Pressure: 2500 psig  
LHSV: 1.44  
GHSV: 323

lbs/hour

Stream Description	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
Sample Point	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	0.99	0.06				
Carbon Monoxide - CO	6.65	0.43				0.05
Carbon Dioxide - CO <sub>2</sub>	14.44	3.24				0.61
Hydrogen Sulfide - H <sub>2</sub> S	0.12	0.06				
Methane - CH <sub>4</sub>	1.23	0.14				0.02
Ethane - C <sub>2</sub> H <sub>6</sub>	0.49	0.12				0.02
Propane - C <sub>3</sub> H <sub>8</sub>	0.28	0.15				0.04
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.13	0.03				
Ammonia - NH <sub>3</sub>	0.01	0.01	0.01		0.01	
(IBP-255°C @1.6 Torr)						
Distillable Oil			0.33		9.91	
SRL						
Coal (MAF)						
Ash						
Water			9.28		4.78	
Phenol						
Total	24.34	4.24	9.62	Negl.	14.70	0.74

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
Total						

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 1/4/78

MATERIAL OUT

Run No: L-1F  
Date: 7/28/77  
Time: 2100-0900

Temperature: 715°F  
Pressure: 2500 psig  
LHSV: 1.44  
GHSV: 323

lbs/hour

Stream Description	Cold Trap	V-8 Btms	F-1 Btms	V-9 Ovhd	← Recycle S-7 Btms	Solvent → F-2 Btms
	Sx-33	Sx-27	Sx-2	Sx-28	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Distillable Oil (IBP-255°C @1.6 Torr)	0.59	11.27	3.70	78.51	72.16	9.09
SRL		5.42	10.56			
Coal (MAF)		2.33	0.42			
Ash		2.19	1.01			
Water	0.08				0.21	
Phenol						
Total	0.67	21.21	15.69	78.51	72.37	9.09

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
Total						

PROJECT : IGNITE  
 MEASURED MATERIAL BALANCE  
 Revised: 1/4/78

MATERIAL OUT

Run No: L-1F  
 Date: 7/28/77  
 Time: 2100-0900

Temperature: 715°F  
 Pressure: 2500 psig  
 LHSV: 1.44  
 GHSV: 323

lbs/hour

Stream Description					Total Out
Sample Point					
Hydrogen - H <sub>2</sub>					1.05
Carbon Monoxide - CO					7.13
Carbon Dioxide - CO <sub>2</sub>					18.29
Hydrogen Sulfide - H <sub>2</sub> S					0.18
Methane - CH <sub>4</sub>					1.39
Ethane - C <sub>2</sub> H <sub>6</sub>					0.63
Propane - C <sub>3</sub> H <sub>8</sub>					0.47
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					0.16
Ammonia - NH <sub>3</sub>					0.04
Distillable Oil (IBP-255°C @1.6 Torr)					185.56
SRL					15.98
Coal (MAF)					2.75
Ash					3.20
Water					14.35
Phenol					
Total					251.18

Quantitative

Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
Total					

Elemental

RUN CONDITIONS

RUN NO. L-1H  
 DATE MADE 8/1/77

TEMPERATURE °F

PRESSURE, psig

PREHEATER E-I  
 SAND BATH 758  
 INLET 319  
 OUTLET 736

DISSOLVERS  
 R-1A (1) 745  
 (2) 761  
 (3) 770  
 (4) 823  
 R-1B (1) \_\_\_\_\_  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_  
 (4) \_\_\_\_\_

REACTOR PRODUCT SEPARATORS  
 S-1 622  
 S-2 80  
 S-3 467  
 S-4A 80  
 S-4B 74

PREHEATER E-II  
 DOWTHERM 646  
 INLET 432  
 OUTLET 626

VACUUM FLASH F-1  
 OVERHEAD VAPOR 505  
 UPPER WALL 617  
 LOWER WALL 610  
 DOWNCOMER 434  
 CONDENSATE  
 ACCUMULATOR, S-7 83

PREHEATER E-13  
 DOWTHERM 596  
 INLET 75  
 OUTLET 565

LIGHT ENDS COLUMN, F-2  
 REBOILER 399  
 LOWER SECTION 468  
 FEED SECTION 416  
 OVERHEAD 190  
 S-8 79  
 S-9 -

SOLVENT COLUMN, F-3  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

HEAVY ENDS COLUMN, F-4  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

VACUUM FLASH, F-0  
 OVERHEAD NIU  
 BOTTOMS \_\_\_\_\_

PRECIPITATION TOWER, V-8  
 ZONE (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_

RECOVERY TOWER V-9  
 REBOILER NIU  
 OVERHEAD \_\_\_\_\_

SEPARATORS S-1 and S-2  
2500

SEPARATOR S-3  
296

SEPARATORS S-4A and S-4B  
60

VACUUM FLASH, F-1  
14 Torr

LIGHT ENDS COLUMN, F-2  
0

SOLVENT COLUMN, F-3  
NIU

HEAVY ENDS COLUMN, F-4  
NIU


VACUUM FLASH, F-0  
NIU

SETTLING TOWER, V-8  
NIU

RECOVERY TOWER, V-7  
NIU

	Start	End	Run No: L-1H
Date of Run	8/1/77	8/1/77	Units: lbs/hr. °F. psig
Time of Run	0130	1330	Prep. By: BCL & GGB
Length of Run	12	hrs.	Updated: 1/24/78
Hours on Coal at End of Y. P.	354.9		

### MASS RATES AND RUN CONDITIONS



159.76 TOTAL

⊗ OPEN

⊗ CLOSED

TOTAL 159.76

Numbers in parentheses are not included in the totals.

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized  
 Revised: 1/24/78

SUMMARY

Run No: L-1H  
 Date: 8/1/77  
 Time: 0130-1330

Temperature: 736°F  
 Pressure: 2500 psig  
 LHSV: 1.43  
 GHSV: 328

lbs/hour

Stream Description	Total In	Total Out	Net Yield		WT % MAF Coal	
Sample Point						
Hydrogen - H <sub>2</sub>	1.34	1.13	-0.21			
Carbon Monoxide - CO	15.75	9.56	-6.19			
Carbon Dioxide - CO <sub>2</sub>		12.81	12.81			
Hydrogen Sulfide - H <sub>2</sub> S		0.17	0.17			
Methane - CH <sub>4</sub>		0.89	0.89			
Ethane - C <sub>2</sub> H <sub>6</sub>		0.60	0.60	8.45	27.04	
Propane - C <sub>3</sub> H <sub>8</sub>		0.35	0.35			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.15	0.15	-0-			
Ammonia - NH <sub>3</sub>		0.03	0.03			
Distillable Oil (IBP-255°C @1.6 Torr)	90.36	91.58	1.22	20.31	64.99	
SRL		19.09	19.09			
Coal (MAF)	31.25	3.76	-27.49		-87.97	
Ash	3.22	3.20	-0.02		-0.06	
Water	17.69	16.44	-1.25		-4.00	
Phenol						
Total	159.76	159.76	-0-			

Elemental	Total In	Total Out	Net Yield		WT % MAF Coal	
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
Total						

PROJECT LIGNITE  
 MEASURED & ADJUSTED MATERIAL BALANCE  
 Revised: 1/24/78

MATERIAL IN

Run No: L-1H  
 Date: 8/1/77  
 Time: 0130-1330

Temperature: 736°F  
 Pressure: 2500 psig  
 LHSV: 1.43  
 GHSV: 328

lbs/hour

Quantitative	Stream Description	Feed Gas	Lignite	Feed Solvent		Total In
	Sample Point	Sx-21	Sx-1	Sx-14		
	Hydrogen - H <sub>2</sub>	1.34				1.34
	Carbon Monoxide - CO	15.75				15.75
	Carbon Dioxide - CO <sub>2</sub>					
	Hydrogen Sulfide - H <sub>2</sub> S					
	Methane - CH <sub>4</sub>					
	Ethane - C <sub>2</sub> H <sub>6</sub>					
	Propane - C <sub>3</sub> H <sub>8</sub>					
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>	0.15				0.15
	Ammonia - NH <sub>3</sub>					
	(IBP-255°C @1.6 Torr) Distillable Oil			90.36		90.36
	SRL					
	Coal (MAF)		31.25			31.25
	Ash		3.22			3.22
	Water		17.26	0.43		17.69
	Phenol					
	Total	17.24	51.73	90.79		159.76

Elemental						
	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	Total					

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized  
 Revised: 1/24/78

Run No: L-1H  
 Date: 8/1/77  
 Time: 0130-1330

MATERIAL OUT

Temperature: 736°F  
 Pressure: 2500 psig  
 LHSV: 1.43  
 GHSV: 328

lbs/hour

Stream Description	Product Gas	S-4A	S-4B	S-8	S-8	J-1
		Ovhd	Btms	Ovhd	Btms	Exhaust
Sample Point	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	1.06	0.06				0.01
Carbon Monoxide - CO	8.97	0.50				0.09
Carbon Dioxide - CO <sub>2</sub>	10.19	2.07				0.55
Hydrogen Sulfide - H <sub>2</sub> S	0.12	0.05				
Methane - CH <sub>4</sub>	0.81	0.07				0.01
Ethane - C <sub>2</sub> H <sub>6</sub>	0.49	0.09				0.02
Propane - C <sub>3</sub> H <sub>8</sub>	0.23	0.10				0.02
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.13	0.02				
Ammonia - NH <sub>3</sub>	0.01		0.02			
(IBP-255°C @1.6 Torr) Distillable Oil			1.53		3.46	
SRL						
Coal (MAF)						
Ash						
Water			15.52			
Phenol						
Total	22.01	2.96	17.07	Negl.	3.46	0.70

Elemental	Quantitative					
	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
Total						

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized  
 Revised: 1/24/78

MATERIAL OUT

Run No: L-1H  
 Date: 8/1/77  
 Time: 0130-1330

Temperature: 736°F  
 Pressure: 2500 psig  
 LHSV: 1.43  
 GHSV: 328

lbs/hour

Stream Description	Cold Trap	F-1 Btms	← Recycle S-7 Btms	Solvent → F-2 Btms	Total Out
	Sx-33	Sx-2	Sx-39	Sx-12	
Hydrogen - H <sub>2</sub>					1.13
Carbon Monoxide - CO					9.56
Carbon Dioxide - CO <sub>2</sub>					12.81
Hydrogen Sulfide - H <sub>2</sub> S					0.17
Methane - CH <sub>4</sub>					0.89
Ethane - C <sub>2</sub> H <sub>6</sub>					0.60
Propane - C <sub>3</sub> H <sub>8</sub>					0.35
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					0.15
Ammonia - NH <sub>3</sub>					0.03
Distillable Oil (IBP-255°C @1.6 Torr)	0.15	2.12	71.55	12.77	91.58
SRL		19.09			19.09
Coal (NAF)		3.76			3.76
Ash		3.20			3.20
Water	0.23		0.69		16.44
Phenol					
Total	0.38	28.17	72.24	12.77	159.76

Elemental	Quantitative					Total
	Cold Trap	F-1 Btms	← Recycle S-7 Btms	Solvent → F-2 Btms		
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
Total						

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1H  
Date: 8/1/77  
Time: 0130-1330

WEIGHT PERCENT

Sample Description	Lignite	F-1 Btms	Makeup Solvent	F-3 Btms	Feed Solvent	S-8 Oil
Sample Point	Sx-1	*Sx-2	Sx-8	Sx-12	Sx-14	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
(IBP-255°C @1.6 Distillable Oil Torr)		7.53	99.80	100	99.53	100
SRL		67.77				
Coal (MAF)	60.41	13.34				
Ash	6.23	11.36				
Water	33.36		0.20		0.47	
Total	100	100	100	100	100	100
P.S. (Ash-free)		84.95				
Melting Point		368				
Specific Gravity 60/60			1.040	1.006	1.039	
Viscosity, cp						

Elemental	Lignite	F-1 Btms	Makeup Solvent	F-3 Btms	Feed Solvent	S-8 Oil
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff.)						
Ash						
Total						
Number of Sample Avg.	2	2	2	2	2	2

\*Distillable oil calculated using the following equation:  
 $Wt \% \text{ Distillable oil} = -0.1273 (\text{F-1 Btms melting point}) + 54.38.$   
 See graph

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1H  
Date: 8/1/77  
Time: 0130-1330

WEIGHT PERCENT

Sample Description	S-8 Water	S-8 Total	Product Gas	Feed Gas	S-4B Oil	S-4B Water
Sample Point	Sx-16	Sx-16	Sx-19	Sx-21	Sx-23	Sx-23
Hydrogen - H <sub>2</sub>			4.82	7.75		
Carbon Monoxide - CO			40.77	91.35		
Carbon Dioxide - CO <sub>2</sub>			46.28			
Hydrogen Sulfide - H <sub>2</sub> S			0.54			
Methane - CH <sub>4</sub>			3.68			
Ethane - C <sub>2</sub> H <sub>6</sub>			2.22			
Propane - C <sub>3</sub> H <sub>8</sub>			1.05			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>			0.59	0.90		
Ammonia - NH <sub>3</sub> (PPM)			0.05			0.14
(IBP-255°C @1.6 Torr)						
Distillable Oil		100			98.57	
SRL						
Coal (MAF)						
Ash						
Water	100				1.43	99.86
Total	100	100	100	100	100	100
P.S. (Ash-free)						
Melting Point						
Specific Gravity 60/60						
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff.)						
Ash						
Total						
Number of Sample Avg.	-	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1H  
Date: 8/1/77  
Time: 0130-1330

WEIGHT PERCENT

Sample Description	S-4B Total	S-4A Ovhd	J-1 Disch.	Cold Trap	Recycle Solvent	
Sample Point	Sx-23	Sx-30	Sx-32	Sx-33	Sx-39	
Hydrogen - H <sub>2</sub>		1.98	0.93			
Carbon Monoxide - CO		17.08	12.32			
Carbon Dioxide - CO <sub>2</sub>		69.85	78.35			
Hydrogen Sulfide - H <sub>2</sub> S		1.59				
Methane - CH <sub>4</sub>		2.35	1.35			
Ethane - C <sub>2</sub> H <sub>6</sub>		3.12	3.67			
Propane - C <sub>3</sub> H <sub>8</sub>		3.31	3.38			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>		0.60				
Ammonia - NH <sub>3</sub> (PPM)	0.13	0.12				
Distillable Oil (IBP-255°C @1.6 Torr)	8.96			40.70	99.04	
SRL						
Coal (MAF)						
Ash						
Water	90.91			59.30	0.96	
Total	100	100	100	100	100	
P.S. (Ash-free)						
Melting Point						
Specific Gravity 60/60					1.042	
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff.)						
Ash						
Total						
Number of Sample Avg.	2	2	2	2	2	

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1H

Date: 8/1/77


Time: 0130-1330

MOLE PERCENT

SAMPLE DESCRIPTION	Product Gas	Feed Gas	S-4A Ovhd	J-1 Disch.		
	Sx-19	Sx-21	Sx-30	Sx-32		
Hydrogen - H <sub>2</sub>	45.62	54.05	27.55	15.66		
Carbon Monoxide - CO	27.54	45.50	17.00	14.82		
Carbon Dioxide - CO <sub>2</sub>	19.89		44.25	59.97		
Hydrogen Sulfide - H <sub>2</sub> S	0.30		1.30			
Methane - CH <sub>4</sub>	4.35		4.10	2.84		
Ethane - C <sub>2</sub> H <sub>6</sub>	1.40		2.90	4.12		
Propane - C <sub>3</sub> H <sub>8</sub>	0.45		2.10	2.59		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.40	0.45	0.60			
Ammonia - NH <sub>3</sub> (PPM)	0.05		0.20			
Light Oils - (0-100° C @ 1.6 Torr)						
Solvent - (100-230° C @ 1.6 Torr)						
Heavy Oil - (230-255° C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100		
Calc Mole Wt.	18.91	13.95	27.88	33.68		
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2		

DISTILLABLE OIL CONTENT OF F-I BOTTOMS  
VERSUS  
F-I BOTTOMS MELTING POINT



PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 1/24/78

MATERIAL OUT

Run No: L-1H  
Date: 8/1/77  
Time: 0130-1330

Temperature: 736°F  
Pressure: 2500 psig  
LHSV: 1.43  
GHSV: 328

lbs/hour

Stream Description	Product Gas	S-4A	S-4B	S-8	S-8	J-1
		Ovhd	Btms	Ovhd	Btms	Exhaust
Sample Point	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	1.09	0.06				0.01
Carbon Monoxide - CO	9.22	0.52				0.09
Carbon Dioxide - CO <sub>2</sub>	10.46	2.12				0.56
Hydrogen Sulfide - H <sub>2</sub> S	0.12	0.05				
Methane - CH <sub>4</sub>	0.83	0.07				0.01
Ethane - C <sub>2</sub> H <sub>6</sub>	0.50	0.10				0.03
Propane - C <sub>3</sub> H <sub>8</sub>	0.24	0.10				0.02
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.13	0.02				
Ammonia - NH <sub>3</sub>	0.01		0.02			
(IBP-255°C @1.6 Torr) Distillable Oil			1.57		3.55	
SRL						
Coal (MAF)						
Ash						
Water			15.94			
Phenol						
Total	22.60	3.04	17.53	Negl.	3.55	0.72

Elemental	Quantitative					
	Stream Description	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
Total						

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 1/24/78

MATERIAL OUT

Run No: L-1H  
Date: 8/1/77  
Time: 0130-1330

Temperature: 736°F  
Pressure: 2500 psig  
LHSV: 1.43  
GHSV: 328

lbs/hour

Stream Description	Cold Trap	F-1 Btms	Recycle Solvent		Total Out
			S-7 Btms	F-2 Btms	
Sample Point	Sx-33	Sx-2	Sx-39	Sx-12	
Hydrogen - H <sub>2</sub>					1.16
Carbon Monoxide - CO					9.83
Carbon Dioxide - CO <sub>2</sub>					13.14
Hydrogen Sulfide - H <sub>2</sub> S					0.17
Methane - CH <sub>4</sub>					0.91
Ethane - C <sub>2</sub> H <sub>6</sub>					0.63
Propane - C <sub>3</sub> H <sub>8</sub>					0.36
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					0.15
Ammonia - NH <sub>3</sub>					0.03
(IBP-255°C @1.6 Torr) Distillable Oil	0.16	2.18	71.55	12.77	91.78
SRL		19.60			19.60
Coal (MAF)		3.86			3.86
Ash		3.29			3.29
Water	0.23		0.69		16.86
Phenol					
Total	0.39	28.93	72.24	12.77	161.77

Elemental	Carbon				
	Hydrogen				
	Nitrogen				
	Sulfur				
	Oxygen (by diff)				
	Ash				
	Total				

RUN CONDITIONS

RUN NO. L-11  
 DATE MADE 8/1-2/77

TEMPERATURE °F

PRESSURE, psig

PREHEATER E-I  
 SAND BATH 760  
 INLET 322  
 OUTLET 741

DISSOLVERS  
 R-1A (1) 746  
 (2) 762  
 (3) 764  
 (4) 824  
 R-1B (1) \_\_\_\_\_  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_  
 (4) \_\_\_\_\_

REACTOR PRODUCT SEPARATORS  
 S-1 617  
 S-2 80  
 S-3 465  
 S-4A 83  
 S-4B 60

PREHEATER E-II  
 DOWTHERM 646  
 INLET 433  
 OUTLET 626

VACUUM FLASH F-1  
 OVERHEAD VAPOR 504  
 UPPER WALL 623  
 LOWER WALL 611  
 DOWNCOMER 436  
 CONDENSATE  
 ACCUMULATOR, S-7 85

PREHEATER E-13  
 DOWTHERM 596  
 INLET 78  
 OUTLET 566

LIGHT ENDS COLUMN, F-2  
 REBOILER 400  
 LOWER SECTION 474  
 FEED SECTION 425  
 OVERHEAD 194  
 S-8 81  
 S-9 -

SOLVENT COLUMN, F-3  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

HEAVY ENDS COLUMN, F-4  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

VACUUM FLASH, F-0  
 OVERHEAD NIU  
 BOTTOMS \_\_\_\_\_

PRECIPITATION TOWER, V-8  
 ZONE (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_

RECOVERY TOWER V-9  
 REBOILER NIU  
 OVERHEAD \_\_\_\_\_

SEPARATORS S-1 and S-2  
2500

SEPARATOR S-3  
290

SEPARATORS S-4A and S-4B  
60

VACUUM FLASH, F-1  
14 Torr

LIGHT ENDS COLUMN, F-2  
0

SOLVENT COLUMN, F-3  
NIU

HEAVY ENDS COLUMN, F-4  
NIU

VACUUM FLASH, F-0  
NIU


SETTLING TOWER, V-8  
NIU

RECOVERY TOWER, V-7  
NIU

	Start	End	Run No: I-II
Date of Run	8/1/77	8/2/77	Units: lbs/hr, °F, psig
Time of Run	1330	0130	Prep. By: BCL & GGB
Length of Run	12	hrs.	Updated: 1/4/78
Hours on Coal at End of Y.P.	366.9		

### MASS RATES AND RUN CONDITIONS

PRODUCT GAS TO THERMAL	22.57
OXIDIZER	-
PRODUCT GAS TO RECYCLE	-
K-4 KNOCKOUT POT BTMS	-
ABSORBED GASES	NIU
WASTE GAS	4.07
S-4A BOTTOMS	-
S-4B BOTTOMS	16.78
TOLUENE ACCUMULATOR	NIU
D.C. OHD	Negl.
LIGHT OILS	4.30
V-9 BOTTOMS	-
J-1 EXHAUST GASES	0.71
COLD TRAP	0.34
COLD TRAP LIQUIDS	-
V-8 BOTTOMS	NIU
VACUUM BOTTOMS	26.63
A-5A OVERFLOW	-



-193-

158.93 TOTAL

⊗ OPEN

⊗ CLOSED

TOTAL 158.93

Numbers in parentheses are not included in the totals.

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized  
 Revised: 1/4/78

Run No: L-11  
 Date: 8/1-2/77  
 Time: 1330-0130

SUMMARY

Temperature: 741°F  
 Pressure: 2500 psig  
 LHSV: 1.41  
 GHSV: 328

lbs/hour

Stream Description	Total In	Total Out	Net Yield		Wt. % MAF Coal
Sample Point					
Hydrogen - H <sub>2</sub>	1.29	1.15	-0.14	} 9.52	30.03
Carbon Monoxide - CO	16.30	10.20	-6.10		
Carbon Dioxide - CO <sub>2</sub>		13.49	13.49		
Hydrogen Sulfide - H <sub>2</sub> S		0.20	0.20		
Methane - CH <sub>4</sub>		0.90	0.90		
Ethane - C <sub>2</sub> H <sub>6</sub>		0.67	0.67		
Propane - C <sub>3</sub> H <sub>8</sub>		0.55	0.55		
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.26	0.17	-0.09		
Ammonia - NH <sub>3</sub>		0.04	0.04		
(IBP-255°C @1.6 Torr) Distillable Oil	89.30	91.18	1.88	} 20.60	64.99
SRL		18.72	18.72		
Coal (MAF)	31.70	2.98	-28.72		-90.60
Ash	3.11	2.86	-0.25		-0.79
Water	16.97	15.82	-1.15		-3.63
Phenol					
<b>Total</b>	<b>158.93</b>	<b>158.93</b>	<b>-0-</b>		

Elemental	Carbon				
	Hydrogen				
	Nitrogen				
	Sulfur				
	Oxygen (bv diff)				
	Ash				
	<b>Total</b>				

PROJECT LIGNITE  
MEASURED & ADJUSTED MATERIAL BALANCE  
Revised: 1/4/78

MATERIAL IN

Run No: L-11  
Date: 8/1-2/77  
Time: 1330-0130

Temperature: 741°F  
Pressure: 2500 psig  
LHSV: 1.41  
GHSV: 328

lbs/hour

Stream Description	Feed Gas	Lignite	Feed Solvent	Total In
Sample Point	Sx-21	Sx-1	Sx-14	
Hydrogen - H <sub>2</sub>	1.29			1.29
Carbon Monoxide - CO	16.30			16.30
Carbon Dioxide - CO <sub>2</sub>				
Hydrogen Sulfide - H <sub>2</sub> S				
Methane - CH <sub>4</sub>				
Ethane - C <sub>2</sub> H <sub>6</sub>				
Propane - C <sub>3</sub> H <sub>8</sub>				
Butane - C <sub>4</sub> H <sub>10</sub>				
Nitrogen - N <sub>2</sub>	0.26			0.26
Ammonia - NH <sub>3</sub>				
(IBP-255°C @1.6 Torr) Distillable Oil			89.30	89.30
SRL				
Coal (MAF)		31.70		31.70
Ash		3.11		3.11
Water		16.53	0.44	16.97
Phenol				
<b>Total</b>	<b>17.85</b>	<b>51.34</b>	<b>89.74</b>	<b>158.93</b>

Quantitative	Carbon				
	Hydrogen				
	Nitrogen				
	Sulfur				
	Oxygen (by diff)				
	Ash				
Elemental	<b>Total</b>				

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Normalized  
Revised: 1/4/78

MATERIAL OUT

Run No: L-11  
Date: 8/1-2/77  
Time: 1330-0130

Temperature: 741°F  
Pressure: 2500 psig  
LHSV: 1.41  
GHSV: 328

lbs/hour

Stream Description	Product Gas	lbs/hour				
		S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
Sample Point	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	1.07	0.07				0.01
Carbon Monoxide - CO	9.41	0.70				0.09
Carbon Dioxide - CO <sub>2</sub>	10.20	2.75				0.54
Hydrogen Sulfide - H <sub>2</sub> S	0.12	0.08				
Methane - CH <sub>4</sub>	0.78	0.11				0.01
Ethane - C <sub>2</sub> H <sub>6</sub>	0.51	0.14				0.02
Propane - C <sub>3</sub> H <sub>8</sub>	0.34	0.17				0.04
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.13	0.04				
Ammonia - NH <sub>3</sub>	0.01	0.01	0.02			
(IBP-255°C @1.6 Distillable Oil Torr)			1.47		4.30	
SRL						
Coal (MAF)						
Ash						
Water			15.29			
Phenol						
Total	22.57	4.07	16.78	Negl.	4.30	0.71

Elemental	lbs/hour					
	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust	Total
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
Total						

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized  
 Revised: 1/4/78

Run No: L-1I  
 Date: 8/1-2/77  
 Time: 1330-0130

MATERIAL OUT

Temperature: 741°F  
 Pressure: 2500 psig  
 LHSV: 1.41  
 GHSV: 328

lbs/hour

	lbs/hour					Total Out
	Cold Trap	F-1 Btms	← Recycle S-7 Btms	Solvent → F-2 Btms		
Stream Description						
Sample Point	Sx-33	Sx-2	Sx-39	Sx-12		
Hydrogen - H <sub>2</sub>						1.15
Carbon Monoxide - CO						10.20
Carbon Dioxide - CO <sub>2</sub>						13.49
Hydrogen Sulfide - H <sub>2</sub> S						0.20
Methane - CH <sub>4</sub>						0.90
Ethane - C <sub>2</sub> H <sub>6</sub>						0.67
Propane - C <sub>3</sub> H <sub>8</sub>						0.55
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						0.17
Ammonia - NH <sub>3</sub>						0.04
Distillable Oil (IBP-255°C @1.6 Torr)	0.09	2.07	67.44	15.81		91.18
SRL		18.72				18.72
Coal (MAF)		2.98				2.98
Ash		2.86				2.86
Water	0.25		0.28			15.82
Phenol						
Total	0.34	26.63	67.72	15.81		158.93

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
Total						

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-11  
Date: 8/1-2/77  
Time: 1330-0130

WEIGHT PERCENT

Sample Description	Lignite	F-1 Btms	Makeup Solvent	LEC Btms	Feed Solvent	S-8 Btms
Sample Point	Sx-1	*Sx-2	Sx-8	Sx-12	Sx-14	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
(IBP-255°C @1.6 Torr)						
Distillable Oil		7.79	99.80	100	99.51	100
SRL		70.28				
Coal (MAF)	61.75	11.19				
Ash	6.06	10.74				
Water	32.19		0.20		0.49	
Total	100	100	100	100	100	100
P.S. (Ash-free)		87.46				
Melting Point		366				
Specific Gravity 60/60			1.040	1.017	1.039	
Viscosity, cp						

Elemental						
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff.)						
Ash						
Total						
Number of Sample Avg.						

\*Distillable oil calculated using following equation:  
Wt % Distillable Oil = -0.1273 (F-1 Btms Melting Point) + 54.38  
See Attached graph.

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated 1/4/78

Run No: L-11  
Date: 8/1-2/77  
Time: 1330- 0130

WEIGHT PERCENT

Sample Description	Product Gas	Feed Gas	S-4B Oil	S-4B Water	S-4B Total	S-4A Ovhd
Sample Point	Sx-19	Sx-21	Sx-23	Sx-23	Sx-23	Sx-30
Hydrogen - H <sub>2</sub>	4.75	7.22				1.77
Carbon Monoxide - CO	41.69	91.32				17.23
Carbon Dioxide - CO <sub>2</sub>	45.17					67.69
Hydrogen Sulfide - H <sub>2</sub> S	0.54					1.85
Methane - CH <sub>4</sub>	3.45					2.73
Ethane - C <sub>2</sub> H <sub>6</sub>	2.28					3.59
Propane - C <sub>3</sub> H <sub>8</sub>	1.50					4.10
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.59	1.46				0.89
Ammonia - NH <sub>3</sub> (PPM)	0.03			0.15	0.14	0.15
Distillable Oil (IBP-255°C @1.6 Torr)			99.46		8.73	
SRL						
Coal (MAF)						
Ash						
Water			0.54	99.85	91.13	
Total	100	100	100	100	100	100
P.S. (Ash-free)						
Melting Point						
Specific Gravity 60/60						
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff.)						
Ash						
Total						
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-11  
Date: 8/1-2/77  
Time: 1330-0130

WEIGHT PERCENT

Sample Description	J-1 Disch.	Cold Trap	Recycle Solvent			
Sample Point	Sx-32	Sx-33	Sx-39			
Hydrogen - H <sub>2</sub>	0.74					
Carbon Monoxide - CO	13.16					
Carbon Dioxide - CO <sub>2</sub>	75.17					
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>	1.56					
Ethane - C <sub>2</sub> H <sub>6</sub>	3.36					
Propane - C <sub>3</sub> H <sub>8</sub>	6.01					
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Distillable Oil (IBP-255°C @1.6 Torr)		26.08	99.58			
SRL						
Coal (MAF)						
Ash						
Water		73.92	0.42			
Total	100	100	100			
P.S. (Ash-free)						
Melting Point						
Specific Gravity 60/60			1.044			
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff.)						
Ash						
Total						
Number of Sample Avg.	2	3	2			

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-11  
Date: 8/1-2/77  
Time: 1330-0130

MOLE PERCENT


SAMPLE DESCRIPTION	Product Gas	Feed Gas	S-4A Ovhd	J-1 Exhaust		
	Sx-19	Sx-21	Sx-30	Sx-32		
Hydrogen - H <sub>2</sub>	45.19	52.15	25.15	12.75		
Carbon Monoxide - CO	28.34	47.10	17.50	16.24		
Carbon Dioxide - CO <sub>2</sub>	19.54		43.75	59.04		
Hydrogen Sulfide - H <sub>2</sub> S	0.30		1.55			
Methane - CH <sub>4</sub>	4.10		4.85	3.38		
Ethane - C <sub>2</sub> H <sub>6</sub>	1.45		3.40	3.87		
Propane - C <sub>3</sub> H <sub>8</sub>	0.65		2.65	4.72		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.40	0.75	0.90			
Ammonia - NH <sub>3</sub> (PPM)	0.03		0.25			
Light Oils - (0-100° C @ 1.6 Torr)						
Solvent - (100-230° C @ 1.6 Torr)						
Heavy Oil - (230-255° C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100		
Calc Mole Wt	19.03	14.44	28.44	34.56		
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Quantitative

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2		

Elemental

DISTILLABLE OIL CONTENT OF F-I BOTTOMS  
VERSUS  
F-I BOTTOMS MELTING POINT



PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 1/4/78

MATERIAL OUT

Run No: L-1I  
Date: 8/1-2/77  
Time: 1330-0130

Temperature: 741°F  
Pressure: 2500 psig  
LHSV: 1.41  
GHSV: 328

lbs/hour

Stream Description	Product Gas	lbs/hour				
		S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
Sample Point	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	1.09	0.07				0.01
Carbon Monoxide - CO	9.60	0.71				0.10
Carbon Dioxide - CO <sub>2</sub>	10.40	2.81				0.54
Hydrogen Sulfide - H <sub>2</sub> S	0.12	0.08				
Methane - CH <sub>4</sub>	0.79	0.11				0.01
Ethane - C <sub>2</sub> H <sub>6</sub>	0.53	0.15				0.02
Propane - C <sub>3</sub> H <sub>8</sub>	0.35	0.17				0.04
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.14	0.04				
Ammonia - NH <sub>3</sub>	0.01	0.01	0.02			
(IBP-255°C @1.6 Torr) Distillable Oil			1.50		4.39	
SRL						
Coal (MAF)						
Ash						
Water			15.61			
Phenol						
Total	23.03	4.15	17.13	Negl.	4.39	0.72

Elemental	lbs/hour					
	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
Total						

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 1/4/78

MATERIAL OUT

Run No: L-II  
Date: 8/1-2/77  
Time: 1330-0130

Temperature: 741°F  
Pressure: 2500 psig  
LHSV: 1.41  
GHSV: 328

lbs/hour

Stream Description	Cold Trap	F-1 Btms	←Recycle S-7 Btms	Solvent → F-2 Btms	Total Out
	Sample Point	Sx-33	Sx-2	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>					1.17
Carbon Monoxide - CO					10.41
Carbon Dioxide - CO <sub>2</sub>					13.75
Hydrogen Sulfide - H <sub>2</sub> S					0.20
Methane - CH <sub>4</sub>					0.91
Ethane - C <sub>2</sub> H <sub>6</sub>					0.70
Propane - C <sub>3</sub> H <sub>8</sub>					0.56
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					0.18
Ammonia - NH <sub>3</sub>					0.04
Distillable Oil (IBP-255°C @1.6 Torr)	0.09	2.12	67.44	15.81	91.35
SRL		19.10			19.10
Coal (MAF)		3.04			3.04
Ash		2.92			2.92
Water	0.26		0.28		16.15
Phenol					
<b>Total</b>	<b>0.35</b>	<b>27.18</b>	<b>67.72</b>	<b>15.81</b>	<b>160.48</b>

Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
<b>Total</b>					

RUN CONDITIONS

RUN NO. L-1J

DATE MADE 8/3/77

TEMPERATURE °F

PRESSURE, psig

PREHEATER E-1  
 SAND BATH 773  
 INLET 315  
 OUTLET 754

DISSOLVERS  
 R-1A (1) 755  
 (2) 772  
 (3) 771  
 (4) 815  
 R-1B (1) \_\_\_\_\_  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_  
 (4) \_\_\_\_\_

REACTOR PRODUCT SEPARATORS  
 S-1 610  
 S-2 80  
 S-3 463  
 S-4A 83  
 S-4B 76

PREHEATER E-11  
 DOWTHERM 661  
 INLET 367  
 OUTLET 636

VACUUM FLASH F-1  
 OVERHEAD VAPOR 508  
 UPPER WALL 628  
 LOWER WALL 638  
 DOWNCOMER 466  
 CONDENSATE  
 ACCUMULATOR, S-7 85

PREHEATER E-13  
 DOWTHERM 598  
 INLET 80  
 OUTLET 551

LIGHT ENDS COLUMN, F-2  
 REBOILER 365  
 LOWER SECTION 457  
 FEED SECTION 438  
 OVERHEAD 208  
 S-8 86  
 S-9 -

SOLVENT COLUMN, F-3  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

HEAVY ENDS COLUMN, F-4  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

VACUUM FLASH, F-0  
 OVERHEAD 495  
 BOTTOMS -

PRECIPITATION TOWER, V-8  
 ZONE (1) 355  
 (2) 380  
 (3) 407

RECOVERY TOWER V-9  
 REBOILER 470  
 OVERHEAD 311

SEPARATORS S-1 and S-2  
2500

SEPARATOR S-3  
290

SEPARATORS S-4A and S-4B  
61

VACUUM FLASH, F-1  
14 Torr

LIGHT ENDS COLUMN, F-2  
0

SOLVENT COLUMN, F-3  
NIU

HEAVY ENDS COLUMN, F-4  
NIU

VACUUM FLASH, F-0  
14 Torr


SETTLING TOWER, V-8  
300

RECOVERY TOWER, V-7  
2

	Start	End	Run No: L-IJ
Date of Run	8/3/77	8/3/77	Units: lbs/hr, °F, psig
Time of Run	0500	1700	Prep. By: GGB & BCL
Length of Run	12	hrs.	Updated: 8/4/77
Hours on Coal at End of Y.P.	406.3		

### MASS RATES AND RUN CONDITIONS

PRODUCT GAS TO THERMAL	23.50
OXIDIZER	-
PRODUCT GAS TO RECYCLE	-



249.69 TOTAL

⊗ OPEN

⊗ CLOSED

Numbers in parentheses are not included in the totals.

TOTAL 249.69

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE  
Normalized with V-8 Btms Composition Calculated  
Revised: 12/30/77

Run No: L-1J  
Date: 8/3/77  
Time: 0500-1700

SUMMARY

Temperature: 754°F  
Pressure: 2500 psig  
LHSV: 1.40  
GHSV: 341

lbs/hour

STREAM DESCRIPTION	Total In	Total Out	Net Yield	WE % MAF Coal	
SAMPLE POINT					
Hydrogen - H <sub>2</sub>	1.34	1.29	-0.05		
Carbon Monoxide - CO	16.98	12.42	-4.56		
Carbon Dioxide - CO <sub>2</sub>		11.83	11.83		
Hydrogen Sulfide - H <sub>2</sub> S		0.22	0.22		
Methane - CH <sub>4</sub>		0.66	0.66	8.84	28.46
Ethane - C <sub>2</sub> H <sub>6</sub>		0.49	0.49		
Propane - C <sub>3</sub> H <sub>8</sub>		0.29	0.29		
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.23	0.16	-0.07		
Ammonia - NH <sub>3</sub>		0.03	0.03		
Light Oil - (0-100°C @ 1.6 Torr)	99.92	105.44	5.52		
Solvent - (100-230°C @ 1.6 Torr)	78.44	75.42	-3.02	19.19	61.78
Heavy Oil - (230-255°C @ 1.6 Torr)	1.88	2.64	0.76		
SRL		15.93	15.93		
Coal (MAF)	31.06	3.29	-27.77		-89.40
Ash	2.79	2.62	-0.17		-0.55
Water	17.05	16.96	-0.09		-0.29
Phenol					
TOTAL	249.69	249.69	-0-		

Carbon	184.62	183.86	-0.76		
Hydrogen	19.55	20.18	0.63		
Nitrogen	0.78	0.64	-0.14		
Sulfur	1.64	1.59	-0.05		
Oxygen (by diff)	40.31	40.80	0.49		
Ash	2.79	2.62	-0.17		
TOTAL	249.69	249.69	-0-		

PROJECT LIGNITE  
MEASURED & ADJUSTED MATERIAL BALANCE

Revised: 12/30/77

Run No: L-1J  
Date: 8/3/77  
Time: 0500-1700

MATERIAL IN  
lbs/hour

Temperature: 754°F  
Pressure: 2500 psig  
LHSV: 1.40  
GHSV: 341

Quantitative	STREAM DESCRIPTION	Feed Gas	Lignite	Liquef. Solvent	Deashing Solvent	Total In
	SAMPLE POINT	Sx-21	Sx-1	Sx-14	Sx-40	
	Hydrogen - H <sub>2</sub>	1.34				1.34
	Carbon Monoxide - CO	16.98				16.98
	Carbon Dioxide - CO <sub>2</sub>					
	Hydrogen Sulfide - H <sub>2</sub> S					
	Methane - CH <sub>4</sub>					
	Ethane - C <sub>2</sub> H <sub>6</sub>					
	Propane - C <sub>3</sub> H <sub>8</sub>					
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>	0.23				0.23
	Ammonia - NH <sub>3</sub>					
	Light Oil - (0-100°C @ 1.6 Torr)			9.50	90.42	99.92
	Solvent - (100-230°C @ 1.6 Torr)			77.80	0.64	78.44
	Heavy Oil - (230-255°C @ 1.6 Torr)			1.88		1.88
	SRL					
	Coal (MAF)		31.06			31.06
	Ash		2.79			2.79
	Water		16.70	0.35		17.05
	Phenol					
	<b>TOTAL</b>	<b>18.55</b>	<b>50.55</b>	<b>89.53</b>	<b>91.06</b>	<b>249.69</b>

Elemental	Carbon	Hydrogen	Nitrogen	Sulfur	Oxygen (by diff)	Ash	Total
		7.28	1.34	0.23		9.70	2.79
	22.03	3.41	0.32	0.30	21.70		50.55
	75.64	6.72	0.22	1.34	5.61		89.53
	79.67	8.08	0.01		3.30		91.06
	184.62	19.55	0.78	1.64	40.31	2.79	249.69
	<b>TOTAL</b>	<b>18.55</b>	<b>50.55</b>	<b>89.53</b>	<b>91.06</b>		<b>249.69</b>

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized with the V-8 Btms Composition Calculated  
 Revised: 12/30/77

Run No: L-1J  
 Date: 8/3/77  
 Time: 0500-1700

MATERIAL OUT

Temperature: 754°F  
 Pressure: 2500 psig  
 LHSV: 1.40  
 GHSV: 341

STREAM DESCRIPTION	Product Gas	lbs/hour				
		S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
SAMPLE POINT	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	1.22	0.06				0.01
Carbon Monoxide - CO	11.68	0.60				0.14
Carbon Dioxide - CO <sub>2</sub>	9.26	2.16				0.41
Hydrogen Sulfide - H <sub>2</sub> S	0.16	0.06				
Methane - CH <sub>4</sub>	0.57	0.07				0.02
Ethane - C <sub>2</sub> H <sub>6</sub>	0.35	0.10				0.04
Propane - C <sub>3</sub> H <sub>8</sub>	0.12	0.13				0.04
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.13	0.03				
Ammonia - NH <sub>3</sub>	0.01	0.01	0.01			
Light Oil - (0-100°C @ 1.6 Torr)			0.32		9.02	
Solvent - (100-230°C @ 1.6 Torr)			0.26		0.22	
Heavy Oil - (230-255°C @1.6 Torr)			0.03		0.27	
SRL						
Coal (MAF)						
Ash						
Water			7.92		8.49	
Phenol						
TOTAL	23.50	3.22	8.54	Negl.	18.00	0.66

Carbon	8.33	1.08	0.52		7.78	0.25
Hydrogen	1.47	0.13	0.94		1.92	0.03
Nitrogen	0.14	0.04	0.01		0.01	
Sulfur	0.15	0.06	0.01		0.03	
Oxygen (by diff)	13.41	1.91	7.06		8.26	0.38
Ash						
TOTAL	23.50	3.22	8.54	Negl.	18.00	0.66

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized with V-8 Btms Composition Calculated  
 Revised: 12/30/77

Run No: L-1J  
 Date: 8/3/77  
 Time: 0500-1700

MATERIAL OUT

Temperature: 754°F  
 Pressure: 2500 psig  
 LHSV: 1.40  
 GHSV: 341

		lbs/hour				
STREAM DESCRIPTION	Cold Trap	V-8 Btms	F-1 Btms	V-9 Ovhd	←Recycle S-7 Btms	Solvent→ F-2 Btms
SAMPLE POINT	Sx-33	Calc	Sx-2	Sx-28	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	0.11	7.12		80.46	4.81	3.60
Solvent - (100-230°C @ 1.6 Torr)	0.02	4.28	6.16	0.77	45.42	18.29
Heavy Oil - (230-255°C @ 1.6 Torr)					0.72	1.62
SRL		3.37	12.56			
Coal (MAF)		3.23	0.06			
Ash		2.44	0.18			
Water	0.29				0.26	
Phenol						
<b>TOTAL</b>	<b>0.42</b>	<b>20.44</b>	<b>18.96</b>	<b>81.23</b>	<b>51.21</b>	<b>23.51</b>

Carbon	0.11	15.28	15.86	70.40	43.58	20.67
Hydrogen	0.04	1.32	1.09	7.16	4.13	1.95
Nitrogen		0.07	0.16	0.01	0.13	0.07
Sulfur		0.12	0.14	0.01	0.73	0.34
Oxygen (by diff)	0.27	1.21	1.53	3.65	2.64	0.48
Ash		2.44	0.18			
<b>TOTAL</b>	<b>0.42</b>	<b>20.44</b>	<b>18.96</b>	<b>81.23</b>	<b>51.21</b>	<b>23.51</b>

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE  
Normalized with V-8 Btms Composition Calculated  
Revised: 12/30/77

Run No: L-1J  
Date: 8/3/77  
Time: 0500-1700

MATERIAL OUT  
lbs/hour

Temperature: 754°F  
Pressure: 2500 psig  
LHSV: 1.40  
GHSV: 341

STREAM DESCRIPTION						Total
						Out
<b>SAMPLE POINT</b>						
Quantitative	Hydrogen - H <sub>2</sub>					1.29
	Carbon Monoxide - CO					12.42
	Carbon Dioxide - CO <sub>2</sub>					11.83
	Hydrogen Sulfide - H <sub>2</sub> S					0.22
	Methane - CH <sub>4</sub>					0.66
	Ethane - C <sub>2</sub> H <sub>6</sub>					0.49
	Propane - C <sub>3</sub> H <sub>8</sub>					0.29
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					0.16
	Ammonia - NH <sub>3</sub>					0.03
	Light Oil - (0-100°C @ 1.6 Torr)					105.44
	Solvent - (100-230°C @ 1.6 Torr)					75.42
	Heavy Oil - (230-255°C @1.6 Torr)					2.64
	SRL					15.93
	Coal (MAF)					3.29
	Ash					2.62
	Water					16.96
	Phenol					
<b>TOTAL</b>					<b>249.86</b>	
Elemental	Carbon					183.86
	Hydrogen					20.18
	Nitrogen					0.64
	Sulfur					1.59
	Oxygen (by diff)					40.80
	Ash					2.62
<b>TOTAL</b>					<b>249.69</b>	

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/30/77

Run No: L-1J

Date: 8/3/77

Time: 0500-1700

WEIGHT PERCENT

SAMPLE DESCRIPTION	Feed	F-1	F-2	Feed	S-8	S-8
	Coal	Btms	Btms	Solvent	Oil	Water
SAMPLE POINT	Sx-1	Sx-2	Sx-12	Sx-14	Sx-16	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100° C @ 1.6 Torr)			15.30	10.61	94.38	
Solvent - (100-230° C @ 1.6 Torr)		32.50	77.80	86.90	2.30	
Heavy Oil - (230-255° C @1.6 Torr)			6.90	2.10	2.80	
SRL		66.23				
Coal (MAF)	61.44	0.33				
Ash	5.52	0.94				
Water	33.04			0.39	0.52	100
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		99.67				
Melting Point °F		198				
Specific Gravity 60/60			1.015	1.031		
Viscosity, cp						

Elemental	Quantitative					
	Feed Coal	F-1 Btms	F-2 Btms	Feed Solvent	S-8 Oil	S-8 Water
Carbon	43.58	83.63	87.91	84.49	81.35	
Hydrogen	6.74	5.77	8.28	7.50	10.33	11.11
Nitrogen	0.63	0.84	0.29	0.24	0.08	
Sulfur	0.60	0.74	1.47	1.50	0.31	
Oxygen (by diff)	42.93	8.08	2.05	6.27	7.93	88.89
Ash	5.52	0.94				
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/30/77

Run No: L-1J

Date: 8/3/77

Time: 0500-1700

WEIGHT PERCENT

SAMPLE DESCRIPTION	WEIGHT PERCENT					
	S-8 Total	Product Gas	Feed Gas	S-4B Oil	S-4B Water	S-4B Total
SAMPLE POINT	Sx-16	Sx-19	Sx-21	Sx-23	Sx-23	Sx-23
Hydrogen - H <sub>2</sub>		5.21	7.22			
Carbon Monoxide - CO		49.70	91.52			
Carbon Dioxide - CO <sub>2</sub>		39.41				
Hydrogen Sulfide - H <sub>2</sub> S		0.66				
Methane - CH <sub>4</sub>		2.44				
Ethane - C <sub>2</sub> H <sub>6</sub>		1.49				
Propane - C <sub>3</sub> H <sub>8</sub>		0.49				
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>		0.54	1.26			
Ammonia - NH <sub>3</sub> (PPM)		0.06			0.13	0.12
Light Oils - (0-100°C @ 1.6 Torr)	50.12			51.63		3.73
Solvent - (100-230°C @ 1.6 Torr)	1.22			42.10		3.04
Heavy Oil - (230-255°C @1.6 Torr)	1.49			5.60		0.40
SRL						
Coal (MAF)						
Ash						
Water	47.17			0.67	99.87	92.71
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon	43.21	35.47	39.22	84.26		6.08
Hydrogen	10.70	6.26	7.22	9.42	11.12	11.00
Nitrogen	0.04	0.59	1.26	0.20	0.11	0.12
Sulfur	0.16	0.62		0.98		0.07
Oxygen (by diff)	45.89	57.06	52.30	5.14	88.77	82.73
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/30/77

Run No: L-1J

Date: 8/3/77

Time: 0500-1700

WEIGHT PERCENT

SAMPLE DESCRIPTION	V-8	V-9	S-4A	J-1	Cold	S-4A
	Rtms	Ovhd	Ovhd	Disch	Trap	Oil
SAMPLE POINT	Sx-27	Sx-28	Sx-30	Sx-32	Sx-33	Sx-37
Hydrogen - H <sub>2</sub>			1.92	1.92		
Carbon Monoxide - CO			18.67	20.57		
Carbon Dioxide - CO <sub>2</sub>			67.13	62.12		
Hydrogen Sulfide - H <sub>2</sub> S			1.89			
Methane - CH <sub>4</sub>			2.21	3.34		
Ethane - C <sub>2</sub> H <sub>6</sub>			3.17	5.40		
Propane - C <sub>3</sub> H <sub>8</sub>			3.87	6.65		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>			0.90			
Ammonia - NH <sub>3</sub> (PPM)			0.24			
Light Oils - (0-100°C @ 1.6 Torr)	46.23	99.05			26.50	52.34
Solvent - (100-230°C @ 1.6 Torr)	26.29	0.95			5.50	30.70
Heavy Oil - (230-255°C @1.6 Torr)						15.90
SRL	14.03					
Coal (MAF)	8.96					
Ash	4.49					
Water					68.00	1.06
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)	90.62					
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Elemental	V-8	V-9	S-4A	J-1	Cold	S-4A
	Rtms	Ovhd	Ovhd	Disch	Trap	Oil
Carbon	85.33	86.67	33.68	38.02	25.59	79.37
Hydrogen	7.29	8.81	3.95	5.05	10.59	9.02
Nitrogen	0.28	0.01	1.10		0.30	0.20
Sulfur	0.99	0.01	1.78		0.25	0.79
Oxygen (by diff)	1.62	4.50	59.49	56.93	63.27	10.62
Ash	4.49					
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	1	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/30/77

Run No: L-1J

Date: 8/3/77

Time: 0500-1700

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4A	S-4A	Recycle	Deashing		V-8
	Water	Total	Solvent	Solvent		Btms
SAMPLE POINT	Sx-37	Sx-37	Sx-39	Sx-40		Calc.
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)	0.19	0.07				
Light Oils - (0-100° C @ 1.6 Torr)		32.92	9.40	99.30		34.83
Solvent - (100-230° C @ 1.6 Torr)		19.31	88.70	0.70		20.94
Heavy Oil - (230-255° C @ 1.6 Torr)		10.00	1.40			
SRL						16.49
Coal (MAF)						15.80
Ash						11.94
Water	99.81	37.70	0.50			
Phenol						
TOTAL	100	100	100	100		100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon		49.92	85.11	87.49		74.75
Hydrogen	11.12	9.80	8.06	8.88		6.47
Nitrogen	0.16	0.19	0.26	0.01		0.35
Sulfur		0.50	1.42	-		0.57
Oxygen (by diff)	88.72	39.59	5.15	3.62		5.92
Ash						11.94
TOTAL	100	100	100	100		100
Number of Sample Avg.	2	2	2	2		-

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 12/30/77

Run No: L-1J

Date: 8/3/77

Time: 0500-1700

MOLE PERCENT

SAMPLE DESCRIPTION	Product Gas	Feed Gas	S-4A Ovhd	J-1 Disch.		
	Sx-19	Sx-21	Sx-30	Sx-32		
Hydrogen - H <sub>2</sub>	47.12	52.15	26.75	26.28		
Carbon Monoxide - CO	32.08	47.20	18.60	20.16		
Carbon Dioxide - CO <sub>2</sub>	16.19		42.55	38.74		
Hydrogen Sulfide - H <sub>2</sub> S	0.35		1.55			
Methane - CH <sub>4</sub>	2.75		3.85	5.73		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.90		2.95	4.94		
Propane - C <sub>3</sub> H <sub>8</sub>	0.20		2.45	4.15		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.35	0.65	0.90			
Ammonia - NH <sub>3</sub> (PPM)	0.06		0.40			
Light Oils - (0-100°C @ 1.6 Torr)						
Solvent - (100-230°C @ 1.6 Torr)						
Heavy Oil - (230-255°C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100		
Calc. Mole Wt.	18.07	14.44	27.89	27.44		
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Quantitative

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	1		

Elemental

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: L-1J  
DATE: 8/3/77  
TIME: 0500-1700

SAMPLE DESCRIPTION	F-1 Btms	LEC Btms	Feed Solv.	S-8 Oil	S-4B Oil
SAMPLE POINT	Sx-2	Sx-12	Sx-14	Sx-16	Sx-23
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR		5	5		
IBP		34	83		
5%		134	104		
10%		148	119		
20%		162	140		
30%		192	162		
40%		212	178		
50%		227	185		
60%		237.5	192		
70%		247	197.5		
80%		262	206		
90%			222		
95%			247		
DRY PT.			247		
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR				742	746
IBP				50	61
5%				72	114
10%				91	141
20%				105	196
30%				114	229
40%				119	250
50%				127	270
60%				140	290
70%				162	316
80%				197	333
90%				231	352
95%				275	
DRY PT.				280	354
ASPHALTENE TEST					
WT % ASH	0.94				
WT % UNCONVERTED COAL	0.33				
WT % PRE-ASPHALTENES	26.29				
WT % ASPHALTENES	41.86				
WT % MALTENES & DIST. OIL	30.58				
TOTAL	100.00				
SAYBOLT VISCOSITY, SSU					
100° F		13.2	12.1		
210° F		8.6	8.9		
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)			0.39	0.52	0.67
INFRARED RATIO			0.27		
SP. GRAV. 60/60 F		1.015	1.031		

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION. USUALLY LESS THAN 5% FOR THE F-1 VACUUM BOTTOMS MATERIAL

PROJECT LIGNITE  
 SAMPLE ANALYSES  
 RUN NO: L-1J  
 DATE: 8/3/77  
 TIME: 0500-1700

SAMPLE DESCRIPTION	V-9 Ovhd	V-9 Btms	Cold Trap	S-4A Oil	S-7 Btms
SAMPLE POINT	Sx-28	Sx-29	Sx-33	Sx-37	Sx-39
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR IBP 5% 10% 20% 30% 40% 50% 60% 70% 80% 90% 95% DRY PT.		5 114.5 165 179 192 197 200 207 220 245 260			5 78 106 120 141 163 176 184 190 196 203 218 238 238
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR IBP 5% 10% 20% 30% 40% 50% 60% 70% 80% 90% 95% DRY PT.	742 109 112 112 112 112 112 113 113 113 113 113 113 114 168		741 87 87 96 105 110 114 118 126 128 146	747 76 91 141 193 227 247 270 284 311 327	
ASPHALTENE TEST					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
SAYBOLT VISCOSITY, SSU					
100° F					12.1
210° F					8.5
MISCELLANEOUS					
KF H <sub>2</sub> O WT%(Raw Sx)			68.00	1.06	0.50
INFRARED RATIO					0.37
SP. GRAV. 60/60 F				0.968	1.029

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
 ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
 MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
 DISTILLABLE OIL - RECOVERABLE BY DISTILLATION. USUALLY LESS THAN 5% FOR THE F-1 VACUUM BOTTOMS MATERIAL

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: L-1J  
DATE: 8/3/77  
TIME: 0500-1700

SAMPLE DESCRIPTION	Deashing Solv.			
SAMPLE POINT	Sx-40			
ASTM D-1160 DISTILLATION DATA				
PRESSURE, TORR				
IBP				
5%				
10%				
20%				
30%				
40%				
50%				
60%				
70%				
80%				
90%				
95%				
DRY PT.				
VOLUME PERCENT	TEMPERATURE, °C			
ASTM D-86 DISTILLATION DATA				
BAROMETRIC PRESSURE, TORR	746			
IBP	112			
5%	112			
10%	112			
20%	112			
30%	112			
40%	112			
50%	112			
60%	112			
70%	112			
80%	112			
90%	113			
95%	113			
DRY PT.	183			
VOLUME PERCENT	TEMPERATURE, °C			
ASPHALTENE TEST				
WT % ASH				
WT % UNCONVERTED COAL				
WT % PRE-ASPHALTENES				
WT % ASPHALTENES				
WT % MALTENES & DIST. OIL				
TOTAL				
SAYBOLT VISCOSITY, SSU				
100° F				
210° F				
MISCELLANEOUS				
KF H <sub>2</sub> O. WT% (Raw Sx)				
INFRARED RATIO				
SP. GRAV. 60/60 F				

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION. USUALLY LESS THAN 5% FOR THE F-1 VACUUM BOTTOMS MATERIAL

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE

Revised: 12/30/77

MATERIAL OUT

Temperature: 754°F

Pressure: 2500 psig

LHSV: 1.40

GHSV: 341

Run No: L-1J

Date: 8/3/77

Time: 0500-1700

lbs/hour

	lbs/hour					
	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
STREAM DESCRIPTION	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
SAMPLE POINT						
Hydrogen - H <sub>2</sub>	1.18	0.06				0.01
Carbon Monoxide - CO	11.24	0.58				0.13
Carbon Dioxide - CO <sub>2</sub>	8.92	2.08				0.40
Hydrogen Sulfide - H <sub>2</sub> S	0.15	0.06				
Methane - CH <sub>4</sub>	0.55	0.07				0.02
Ethane - C <sub>2</sub> H <sub>6</sub>	0.34	0.10				0.04
Propane - C <sub>3</sub> H <sub>8</sub>	0.11	0.12				0.04
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.12	0.03				
Ammonia - NH <sub>3</sub>	0.01		0.01			
Light Oil - (0-100°C @ 1.6 Torr)			0.31		8.68	
Solvent - (100-230°C @ 1.6 Torr)			0.25		0.21	
Heavy Oil - (230-255°C @ 1.6 Torr)			0.03		0.26	
SRL						
Coal (MAF)						
Ash						
Water			7.62		8.17	
Phenol						
TOTAL	22.62	3.10	8.22	Negl.	17.32	0.64

Carbon	8.02	1.04	0.50		7.48	0.24
Hydrogen	1.42	0.12	0.90		1.85	0.03
Nitrogen	0.13	0.04	0.01		0.01	
Sulfur	0.14	0.06	0.01		0.03	
Oxygen (by diff)	12.91	1.84	6.80		7.95	0.37
Ash						
TOTAL	22.62	3.10	8.22	Negl.	17.32	0.64

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 12/30/77

Run No: L-1J  
Date: 8/3/77  
Time: 0500-1700

MATERIAL OUT

Temperature: 754°F  
Pressure: 2500 psig  
LHSV: 1.40  
GHSV: 341

lbs/hour

	lbs/hour					
	Cold Trap	V-8 Btms	F-1 Btms	V-9 Ovhd	←Recycle S-7 Btms	Solvent→ F-2 Btms
STREAM DESCRIPTION	Sx-33	Sx-27	Sx-2	Sx-28	Sx-39	Sx-12
SAMPLE POINT						
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	0.11	9.10		80.46	4.81	3.60
Solvent - (100-230°C @ 1.6 Torr)	0.02	5.17	5.93	0.77	45.42	18.29
Heavy Oil - (230-255°C @ 1.6 Torr)					0.72	1.62
SRL		2.76	12.09			
Coal (MAF)		1.76	0.06			
Ash		0.88	0.17			
Water	0.27				0.26	
Phenol						
TOTAL	0.40	19.67	18.25	81.23	51.21	23.51

Carbon	0.10	16.78	15.26	70.40	43.58	20.67
Hydrogen	0.04	1.43	1.05	7.16	4.13	1.95
Nitrogen		0.06	0.15	0.01	0.13	0.07
Sulfur		0.20	0.14	0.01	0.73	0.34
Oxygen (by diff)	0.26	0.32	1.48	3.65	2.64	0.48
Ash		0.88	0.17			
TOTAL	0.40	19.67	18.25	81.23	51.21	23.51

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 12/30/77

Run No: L-1J  
Date: 8/3/77  
Time: 0500-1700

MATERIAL OUT

Temperature: 754°F  
Pressure: 2500 psig  
LHSV: 1.40  
GHSV: 341

lbs/hour

Quantitative	STREAM DESCRIPTION					Total Out
	SAMPLE POINT					
	Hydrogen - H <sub>2</sub>					1.25
	Carbon Monoxide - CO					11.95
	Carbon Dioxide - CO <sub>2</sub>					11.40
	Hydrogen Sulfide - H <sub>2</sub> S					0.21
	Methane - CH <sub>4</sub>					0.64
	Ethane - C <sub>2</sub> H <sub>6</sub>					0.48
	Propane - C <sub>3</sub> H <sub>8</sub>					0.27
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					0.15
	Ammonia - NH <sub>3</sub>					0.02
	Light Oil - (0-100°C @ 1.6 Torr)					107.07
	Solvent - (100-230°C @ 1.6 Torr)					76.06
	Heavy Oil - (230-255°C @ 1.6 Torr)					2.63
	SRL					14.85
	Cool (MAF)					1.82
	Ash					1.05
	Water					16.32
	Phenol					
	TOTAL					246.17

Elemental	Carbon					184.07
	Hydrogen					20.08
	Nitrogen					0.61
	Sulfur					1.66
	Oxygen (by diff)					38.70
	Ash					1.05
	TOTAL					246.17

RUN CONDITIONS

RUN NO. L-1K

DATE MADE 8/3-4/77

TEMPERATURE °F

PRESSURE, psig

PREHEATER E-I  
 SAND BATH 777  
 INLET 307  
 OUTLET 757

DISSOLVERS  
 R-1A (1) 758  
 (2) 774  
 (3) 773  
 (4) 804  
 R-1B (1) \_\_\_\_\_  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_  
 (4) \_\_\_\_\_

REACTOR PRODUCT SEPARATORS  
 S-1 593  
 S-2 79  
 S-3 460  
 S-4A 83  
 S-4B 77

PREHEATER E-II  
 DOWTHERM 667  
 INLET 360  
 OUTLET 641

VACUUM FLASH F-I  
 OVERHEAD VAPOR 504  
 UPPER WALL 626  
 LOWER WALL 626  
 DOWNCOMER 451  
 CONDENSATE  
 ACCUMULATOR, S-7 86

PREHEATER E-13  
 DOWTHERM 597  
 INLET 77  
 OUTLET 567

LIGHT ENDS COLUMN, F-2  
 REBOILER 395  
 LOWER SECTION 470  
 FEED SECTION 422  
 OVERHEAD 183  
 S-8 80  
 S-9 -

SOLVENT COLUMN, F-3  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

HEAVY ENDS COLUMN, F-4  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

VACUUM FLASH, F-O  
 OVERHEAD 492  
 BOTTOMS -

PRECIPITATION TOWER, V-8  
 ZONE (1) 342  
 (2) 372  
 (3) 398

RECOVERY TOWER V-9  
 REBOILER 449  
 OVERHEAD 312

SEPARATORS S-1 and S-2  
2500

SEPARATOR S-3  
297

SEPARATORS S-4A and S-4B  
60

VACUUM FLASH, F-I  
14 Torr

LIGHT ENDS COLUMN, F-2  
0

SOLVENT COLUMN, F-3  
NIU

HEAVY ENDS COLUMN, F-4  
NIU

VACUUM FLASH, F-O  
14 Torr


SETTLING TOWER, V-8  
300

RECOVERY TOWER, V-7  
2

	Start	End	Run No: L-1K
Date of Run	8/3/77	8/4/77	Units: lbs/hr, °F, psig
Time of Run	1700	0500	Prep. By: BCL & GGB
Length of Run	12	hrs.	Updated: 1/4/78
Hours on Coal at End of Y. P.	418.3		

### MASS RATES AND RUN CONDITIONS

PRODUCT GAS TO THERMAL	22.29
OXIDIZER	-0-
PRODUCT GAS TO RECYCLE	-0-
K-4 KNOCKOUT POT BTMS	-0-
ABSORBED GASES	NIU



-224-

254.86 TOTAL      OPEN      CLOSED      TOTAL 254.86

Numbers in parentheses are not included in the totals.

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized with V-8 Btms Composition Calculated  
 Revised: 1/4/78

Run No: L-1K  
 Date: 8/3-4/77  
 Time: 1700-0500

SUMMARY

Temperature: 757°F  
 Pressure: 2500 psig  
 LHSV: 1.42  
 GHSV: 336

lbs/hour

STREAM DESCRIPTION	Total In	Total Out	Net Yield	WE % MAF Coal	
SAMPLE POINT					
Hydrogen - H <sub>2</sub>	1.33	1.24	-0.09		
Carbon Monoxide - CO	16.67	11.49	-5.18		
Carbon Dioxide - CO <sub>2</sub>		12.03	12.03		
Hydrogen Sulfide - H <sub>2</sub> S		0.14	0.14		
Methane - CH <sub>4</sub>		0.63	0.63	8.39	26.94
Ethane - C <sub>2</sub> H <sub>6</sub>		0.49	0.49		
Propane - C <sub>3</sub> H <sub>8</sub>		0.36	0.36		
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.20	0.15	-0.05		
Ammonia - NH <sub>3</sub>		0.06	0.06		
Light Oil - (0-100°C @ 1.6 Torr)	111.44	117.31	5.87		
Solvent - (100-230°C @ 1.6 Torr)	74.40	73.17	-1.23	20.50	65.81
Heavy Oil - (230-255°C @ 1.6 Torr)	0.18	2.47	2.29		
SRL		13.57	13.57		
Cool (MAF)	31.15	3.35	-27.80		-89.25
Ash	2.88	2.71	-0.17		-0.55
Water	16.61	15.69	-0.92		-2.95
Phenol					
TOTAL	254.86	254.86	-0-		

ELEMENTAL	Quantitative				
	Total In	Total Out	Net Yield	WE % MAF Coal	
Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
TOTAL					

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 1/4/78

Run No: L-1K  
Date: 8/3-4/77  
Time: 1700-0500

MATERIAL IN

lbs/hour

Temperature: 757°F  
Pressure: 2500 psig  
LHSV: 1.42  
GHSV: 336

STREAM DESCRIPTION	Feed	Lignite	Feed	Deashing	Total
	Gas		Solvent	Solvent	
SAMPLE POINT	Sx-21	Sx-1	Sx-14	Sx-40	In
Hydrogen - H <sub>2</sub>	1.33				1.33
Carbon Monoxide - CO	16.67				16.67
Carbon Dioxide - CO <sub>2</sub>					
Hydrogen Sulfide - H <sub>2</sub> S					
Methane - CH <sub>4</sub>					
Ethane - C <sub>2</sub> H <sub>6</sub>					
Propane - C <sub>3</sub> H <sub>8</sub>					
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.20				0.20
Ammonia - NH <sub>3</sub>					
Light Oil - (0-100°C @ 1.6 Torr)			16.23	95.21	111.44
Solvent - (100-230°C @ 1.6 Torr)			74.21	0.19	74.40
Heavy Oil - (230-255°C @ 1.6 Torr)			0.18		0.18
SRL					
Coal (MAF)		31.15			31.15
Ash		2.88			2.88
Water		16.28	0.33		16.61
Phenol					
TOTAL	18.20	50.31	90.95	95.40	254.86

ELEMENTAL	Quantitative					
	Feed Gas	Lignite	Feed Solvent	Deashing Solvent	Total In	
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized with V-8 Btms Composition Calculated  
 Revised: 1/4/78

Run No: L-1K  
 Date: 8/3-4/77  
 Time: 1700-0500

MATERIAL OUT

Temperature: 757°F  
 Pressure: 2500 psig  
 LHSV: 1.42  
 GHSV: 336

lbs/hour

STREAM DESCRIPTION	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	1.14	0.09				0.01
Carbon Monoxide - CO	10.52	0.86				0.11
Carbon Dioxide - CO <sub>2</sub>	9.29	2.25				0.49
Hydrogen Sulfide - H <sub>2</sub> S	0.10	0.04				
Methane - CH <sub>4</sub>	0.53	0.08				0.02
Ethane - C <sub>2</sub> H <sub>6</sub>	0.37	0.10				0.02
Propane - C <sub>3</sub> H <sub>8</sub>	0.19	0.12				0.05
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.12	0.03				
Ammonia - NH <sub>3</sub>	0.03	0.01	0.02			
Light Oil - (0-100°C @ 1.6 Torr)			2.13		7.41	
Solvent - (100-230°C @ 1.6 Torr)			1.10		0.06	
Heavy Oil - (230-255°C @1.6 Torr)			0.20			
SRL						
Coal (MAF)						
Ash						
Water			15.14			
Phenol						
TOTAL	22.29	3.58	18.59	Negl.	7.47	0.70

ELEMENTAL	Quantitative					
	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized with V-8 Btms Composition Calculated  
 Revised: 1/4/78

Run No: L-1K  
 Date: 8/3-4/77  
 Time: 1700-0500

MATERIAL OUT  
 lbs/hour

Temperature: 757°F  
 Pressure: 2500 psig  
 LHSV: 1.42  
 GHSV: 336

STREAM DESCRIPTION	Cold	V-8	F-1	V-9	←Recycle	Solvent→
	Trap	Btms	Btms	Ovhd	S-7 Btms	F-2 Btms
SAMPLE POINT	Sx-33	Calc.	Sx-2	Sx-28	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	0.31	8.51		83.87	10.25	4.83
Solvent - (100-230°C @ 1.6 Torr)	0.03	5.41	4.21	0.72	47.25	14.39
Heavy Oil - (230-255°C @1.6 Torr)		0.70			1.24	0.33
SRL		2.18	11.39			
Cool (MAF)		2.86	0.49			
Ash		2.01	0.70			
Water	0.23				0.32	
Phenol						
TOTAL	0.57	21.67	16.79	84.59	59.06	19.55

ELEMENTAL	Quantitative					
	Cold Trap	V-8 Btms	F-1 Btms	V-9 Ovhd	←Recycle S-7 Btms	Solvent→ F-2 Btms
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Normalized with V-8 Btms Composition Calculated  
 Revised: 1/4/78

Run No: L-1K  
 Date: 8/3-4/77  
 Time: 1700-0500

MATERIAL OUT  
 lbs/hour

Temperature: 757°F  
 Pressure: 2500 psig  
 LHSV: 1.42  
 GHSV: 336

Quantitative	STREAM DESCRIPTION					Total Out
	SAMPLE POINT					
	Hydrogen - H <sub>2</sub>					1.24
	Carbon Monoxide - CO					11.49
	Carbon Dioxide - CO <sub>2</sub>					12.03
	Hydrogen Sulfide - H <sub>2</sub> S					0.14
	Methane - CH <sub>4</sub>					0.63
	Ethane - C <sub>2</sub> H <sub>6</sub>					0.49
	Propane - C <sub>3</sub> H <sub>8</sub>					0.36
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					0.15
	Ammonia - NH <sub>3</sub>					0.06
	Light Oil - (0-100°C @ 1.6 Torr)					117.31
	Solvent - (100-230°C @ 1.6 Torr)					73.17
	Heavy Oil - (230-255°C @1.6 Torr)					2.47
	SRL					13.57
	Coal (MAF)					3.35
	Ash					2.71
	Water					15.69
	Phenol					
	TOTAL					254.86

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	TOTAL					

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1K

Date: 8/3-4/77

Time: 1700-0500

WEIGHT PERCENT

SAMPLE DESCRIPTION	WEIGHT PERCENT					
	Lignite	F-1 Btms	Makeup Solvent	F-3 Btms	Feed Solvent	S-8 Oil
SAMPLE POINT	Sx-1	*Sx-2	Sx-8	Sx-12	Sx-14	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100° C @ 1.6 Torr)			3.74	24.70	17.84	99.20
Solvent - (100-230° C @ 1.6 Torr)		25.10	92.42	73.60	81.60	0.80
Heavy Oil - (230-255° C @1.6 Torr)			3.64	1.70	0.20	
SRL		67.85				
Coal (MAF)	61.92	2.91				
Ash	5.72	4.14				
Water	32.36		0.20		0.36	
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		96.96				
Melting Point °F		230				
Specific Gravity 60/60			1.040	1.007	1.030	
Viscosity, cp						

Elemental	WEIGHT PERCENT					
	Lignite	F-1 Btms	Makeup Solvent	F-3 Btms	Feed Solvent	S-8 Oil
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	2

\*Distillable oil calculated by following equation .

$$\text{Wt\% Distillable Oil} = -0.1273 (\text{F-1 Btms Melting Point}) + 54.38. \text{ See graph.}$$

PROJECT: LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1K

Date: 8/3-4/77

Time: 1700-0500

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-8	S-8	Product	Feed	S-4B	S-4B
	Water	Total	Gas	Gas	Oil	Water
SAMPLE POINT	Sx-16	Sx-16	Sx-19	Sx-21	Sx-23	Sx-23
Hydrogen - H <sub>2</sub>			5.12	7.32		
Carbon Monoxide - CO			47.21	91.61		
Carbon Dioxide - CO <sub>2</sub>			41.66			
Hydrogen Sulfide - H <sub>2</sub> S			0.46			
Methane - CH <sub>4</sub>			2.40			
Ethane - C <sub>2</sub> H <sub>6</sub>			1.64			
Propane - C <sub>3</sub> H <sub>8</sub>			0.84			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>			0.53	1.07		
Ammonia - NH <sub>3</sub> (PPM)			0.14			0.14
Light Oils - (0-100°C @ 1.6 Torr)		99.20			61.04	
Solvent - (100-230°C @ 1.6 Torr)		0.80			31.70	
Heavy Oil - (230-255°C @1.6 Torr)					5.60	
SRL						
Coal (MAF)						
Ash						
Water	100				1.66	99.86
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Elemental	Carbon						
	Hydrogen						
	Nitrogen						
	Sulfur						
	Oxygen (by diff)						
	Ash						
	TOTAL						
	Number of Sample Avg.	-	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1K  
Date: 8/3-4/77  
Time: 1700-0500

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4B	V-8	V-9	S-4A	J-1	Cold
	Total	Btms	Ovhd	Ovhd	Disch.	Trap
SAMPLE POINT	Sx-23	Sx-27	Sx-28	Sx-30	Sx-32	Sx-33
Hydrogen -H <sub>2</sub>				2.37	1.24	
Carbon Monoxide-CO				24.00	16.20	
Carbon Dioxide-CO <sub>2</sub>				62.93	70.41	
Hydrogen Sulfide-H <sub>2</sub> S				1.25		
Methane-CH <sub>4</sub>				2.23	2.35	
Ethane-C <sub>2</sub> H <sub>6</sub>				2.78	3.60	
Propane-C <sub>3</sub> H <sub>8</sub>				3.48	6.20	
Butane-C <sub>4</sub> H <sub>10</sub>						
Nitrogen-N <sub>2</sub>				0.70		
Ammonia-NH <sub>3</sub> (PPM)	0.11			0.26		
Light Oils-(0-100°C @ 1.6 Torr)	11.44	39.25	99.15			54.85
Solvent-(100-230°C @ 1.6 Torr)	5.94	24.98	0.85			5.20
Heavy Oil-(230-255°C @1.6 Torr)	1.05	3.24				
SRL		11.56				
Coal (MAF)		15.14				
Ash		5.83				
Water	81.46					39.95
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Quantitative

Elemental

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	1

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1K

Date: 8/3-4/77

Time: 1700-0500

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4A Oil	S-4A Water	S-4A Total	Recycle Solvent	Deashing Solvent	V-8 Btms
SAMPLE POINT	Sx-37	Sx-37	Sx-37	Sx-39	Sx-40	Calc.
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)		0.16				
Light Oils - (0-100°C @ 1.6 Torr)	69.00		68.46	17.35	99.80	39.25
Solvent - (100-230°C @ 1.6 Torr)	29.20		28.97	80.00	0.20	24.98
Heavy Oil - (230-255°C @1.6 Torr)	1.80		1.79	2.10		3.24
SRL						10.07
Coal (MAF)						13.18
Ash						9.28
Water		99.84	0.78	0.55		
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Molting Point °F						
Specific Gravity 60/60				1.031		
Viscosity, cp						

Elemental	S-4A Oil	S-4A Water	S-4A Total	Recycle Solvent	Deashing Solvent	V-8 Btms
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	-

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 1/4/78

Run No: L-1K

Date: 8/3-4/77

Time: 1700-0500

MOLE PERCENT

SAMPLE DESCRIPTION	Product Gas	Feed Gas	S-4A Ovhd	J-1 Disch.		
	Sx-19	Sx-21	Sx-30	Sx-32		
SAMPLE POINT	Sx-19	Sx-21	Sx-30	Sx-32		
Hydrogen - H <sub>2</sub>	46.90	52.50	30.73	19.29		
Carbon Monoxide - CO	30.90	46.95	22.19	18.05		
Carbon Dioxide - CO <sub>2</sub>	17.35		37.03	49.93		
Hydrogen Sulfide - H <sub>2</sub> S	0.25		0.95			
Methane - CH <sub>4</sub>	2.75		3.60	4.59		
Ethane - C <sub>2</sub> H <sub>6</sub>	1.00		2.40	3.74		
Propane - C <sub>3</sub> H <sub>8</sub>	0.35		2.05	4.40		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.35	0.55	0.65			
Ammonia - NH <sub>3</sub> (PPM)	0.15		0.40			
Light Oils - (0-100° C @ 1.6 Torr)						
Solvent - (100-230° C @ 1.6 Torr)						
Heavy Oil - (230-255° C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100		
Calc. Mole Wt.	18.33	14.35	25.89	31.20		
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Quantitative

Elemental

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2		

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: L-1K  
DATE: 8/3-4/77  
TIME: 1700-0500

SAMPLE DESCRIPTION	LEC Btms	Feed Solv	S-8 Oil	S-4B Oil	V-9 Ovhd
SAMPLE POINT	Sx-12	Sx-14	Sx-16	Sx-23	Sx-28
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR	5	5			
IBP	104	78			
5%	108	93			
10%	111	106			
20%	118	130			
30%	126	152			
40%	136	167			
50%	149	177			
60%	165	183			
70%	176	189			
80%	185	196			
90%	196	206			
95%	207	212.5			
DRY PT.	211	230			
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR			742	737	742
IBP			40	83	107
5%			89	101	112
10%			101	126	112
20%			116	201	112
30%			123	224	112
40%			138	245	112
50%			159	261	112
60%			188	272	113
70%			198	278	113
80%			207	312	113
90%			220		113
95%			226		115
DRY PT.			230	336	125
ASPHALTENE TEST					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
SAYBOLT VISCOSITY, SSU					
100° F	10.8	11.4			
210° F	8.5	8.8			
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)		0.36	0.52	1.66	
INFRARED RATIO		0.29			
SP. GRAV. 60/60 F	1.007	1.030			


PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION. USUALLY LESS THAN 5% FOR THE F-1 VACUUM BOTTOMS MATERIAL

PROJECT LIGNITE  
 SAMPLE ANALYSES  
 RUN NO: L-1K  
 DATE: 8/3-4/77  
 TIME: 1700-0500

SAMPLE DESCRIPTION	Cold Trap	S-4A Oil	S-7 Btms	Deash. Solv
SAMPLE POINT	Sx-33	Sx-37	Sx-39	Sx-40
ASTM D-1160 DISTILLATION DATA				
PRESSURE, TORR			5	
IBP			78	
5%			88	
10%			100	
20%			127	
30%			146	
40%			163.5	
50%			176	
60%			183.5	
70%			188	
80%			195.5	
90%			213	
95%			226	
DRY PT.			227	
ASTM D-86 DISTILLATION DATA				
BAROMETRIC PRESSURE, TORR	746	742		744
IBP	91	84		106
5%	101	107		109
10%	106	139		110
20%	113	198		111.5
30%	113	218		111.5
40%	115	229		112
50%	116	239		112
60%	119	256		112
70%	124	278		112
80%	142	315		112
90%	162	346		112
95%		357		112
DRY PT.	167	360		176
ASPHALTENE TEST				
WT % ASH				
WT % UNCONVERTED COAL				
WT % PRE-ASPHALTENES				
WT % ASPHALTENES				
WT % MALTENES & DIST. OIL				
TOTAL				
SAYBOLT VISCOSITY, SSU				
100° F			11.5	
210° F			8.6	
MISCELLANEOUS				
KF H <sub>2</sub> O WT% (Raw Sx)			0.55	
INFRARED RATIO				
SP. GRAV. 60/60 F		0.969	1.031	

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
 ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
 MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
 DISTILLABLE OIL - RECOVERABLE BY DISTILLATION. USUALLY LESS THAN 5% FOR THE F-1 VACUUM BOTTOMS MATERIAL

DISTILLABLE OIL CONTENT OF F-I BOTTOMS  
VERSUS  
F-I BOTTOMS MELTING POINT



PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 1/4/78

MATERIAL OUT

Temperature: 757°F  
Pressure: 2500 psig  
LHSV: 1.42  
GHSV: 336

Run No: L-1K  
Date: 8/3-4/77  
Time: 1700-0500

lbs/hour

STREAM DESCRIPTION	Product Gas	S-4A	S-4B	S-8	S-8	J-1
		Ovhd	Btms	Ovhd	Btms	Exhaust
SAMPLE POINT	Sx-19	Sx-30	Sx-23	Sx-44	Sx-16	Sx-32
Hydrogen - H <sub>2</sub>	1.12	0.08				0.01
Carbon Monoxide - CO	10.33	0.85				0.11
Carbon Dioxide - CO <sub>2</sub>	9.12	2.22				0.49
Hydrogen Sulfide - H <sub>2</sub> S	0.10	0.04				
Methane - CH <sub>4</sub>	0.52	0.08				0.02
Ethane - C <sub>2</sub> H <sub>6</sub>	0.36	0.10				0.02
Propane - C <sub>3</sub> H <sub>8</sub>	0.18	0.12				0.04
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.12	0.02				
Ammonia - NH <sub>3</sub>	0.03	0.01	0.02			
Light Oil - (0-100°C @ 1.6 Torr)			2.09		7.27	
Solvent - (100-230°C @ 1.6 Torr)			1.08		0.06	
Heavy Oil - (230-255°C @ 1.6 Torr)			0.19			
SRL						
Cool (MAF)						
Ash						
Water			14.87			
Phenol						
<b>TOTAL</b>	<b>21.88</b>	<b>3.52</b>	<b>18.25</b>	<b>Negl.</b>	<b>7.33</b>	<b>0.69</b>

Elemental	Quantitative					
	Product Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd	S-8 Btms	J-1 Exhaust
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
<b>TOTAL</b>						

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 1/4/78

Run No: L-1K  
Date: 8/3-4/77  
Time: 1700-0500

MATERIAL OUT

Temperature: 757°F  
Pressure: 2500 psig  
LHSV: 1.42  
GHSV: 336

		lbs/hour				
Quantitative	STREAM DESCRIPTION	Cold Trap	V-8 Btms	F-1 Btms	V-9 Ovhd	←Recycle S-7 Btms Solvent→ F-2 Btms
		SAMPLE POINT	Sx-33	Sx-27	Sx-2	Sx-28
	Hydrogen - H <sub>2</sub>					
	Carbon Monoxide - CO					
	Carbon Dioxide - CO <sub>2</sub>					
	Hydrogen Sulfide - H <sub>2</sub> S					
	Methane - CH <sub>4</sub>					
	Ethane - C <sub>2</sub> H <sub>6</sub>					
	Propane - C <sub>3</sub> H <sub>8</sub>					
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					
	Ammonia - NH <sub>3</sub>					
	Light Oil - (0-100°C @ 1.6 Torr)	0.31	8.35		83.87	10.25 4.83
	Solvent - (100-230°C @ 1.6 Torr)	0.03	5.32	4.14	0.72	47.25 14.39
	Heavy Oil - (230-255°C @ 1.6 Torr)		0.69			1.24 0.33
	SRL		2.46	11.18		
	Cool (MAF)		3.22	0.48		
	Ash		1.24	0.68		
	Water	0.22				0.32
	Phenol					
	TOTAL	0.56	21.28	16.48	84.59	59.06 19.55
Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	TOTAL					

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 1/4/78

Run No: L-1K  
Date: 8/3-4/77  
Time: 1700-0500

MATERIAL OUT  
  
lbs/hour

Temperature: 757°F  
Pressure: 2500 psig  
LHSV: 1.42  
GHSV: 336

Quantitative	STREAM DESCRIPTION					Total Out
	SAMPLE POINT					
	Hydrogen - H <sub>2</sub>					1.21
	Carbon Monoxide - CO					11.29
	Carbon Dioxide - CO <sub>2</sub>					11.83
	Hydrogen Sulfide - H <sub>2</sub> S					0.14
	Methane - CH <sub>4</sub>					0.62
	Ethane - C <sub>2</sub> H <sub>6</sub>					0.48
	Propane - C <sub>3</sub> H <sub>8</sub>					0.34
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					0.14
	Ammonia - NH <sub>3</sub>					0.06
	Light Oil - (0-100°C @ 1.6 Torr)					116.97
	Solvent - (100-230°C @ 1.6 Torr)					72.99
	Heavy Oil - (230-255°C @1.6 Torr)					2.45
	SRL					13.64
	Coal (MAF)					3.70
	Ash					1.92
	Water					15.41
	Phenol					
	TOTAL					253.19

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	TOTAL					

## APPENDIX D

### Process Development Unit Run L-2 August 21 - September 23, 1977

Run L-2 was the second of three runs scheduled for 672 hours of continuous operation. The objectives were (1) to evaluate long term plant operability with continuous liquefaction solvent recycle and (2) to determine the effects of off-gas clean-up and recycle on liquefaction yields.

Nominal run conditions were similar to those of previous Run L-1 and were 820-830°F maximum reaction temperature and 2500 psig dissolver operating pressure with liquid and gas hourly space velocities of 1.43 and 336, respectively. All recoverable organic distillates boiling above 350°F were recycled. The main product gas stream was caustic washed to remove carbon dioxide and hydrogen sulfide and then approximately three quarters was recycled and one quarter vented to the thermal oxidizer. One reactor volume, about 1.4 cubic feet, was used throughout the run.

Initially Run L-2 got off to a bad start because plugging in some lines that had not been replaced at the end of Run L-1 delayed PDU startup. Later, after coal processing had started, a solid state contactor in the electrical circuit servicing the heat tapes on the F-1 vacuum bottoms draw off leg failed closed, allowing the leg to overheat and coke the vacuum bottoms.

Operating difficulties initiated by the plugging of the vacuum flash tower bottoms outlet were compounded when the S-1 high pressure slurry letdown valves started leaking. These problems, coupled with other minor operating problems with the slurry charge pumps, consumed approximately the first 155 hours of the scheduled 672. To compensate, the run was extended an additional 144 hours for a total of 816 hours.

With the initial problems resolved, satisfactory startup was achieved on about the sixth day of operations. The unit operated at temperature for about thirty hours, then problems developed with the slurry charge pumps. The pumps worked well with solvent but not with coal slurry. This apparently resulted from an increase in the particle size distribution of the ground coal caused by a worn screen in the coal pulverizer. Sieve analyses for a feed coal sample taken while the pumping problem existed and one taken during the earlier M-series of runs are compared on the following page.

US Screen Sieve Mesh	Total Percentages			
	On		Passing	
	L-2	M-Series	L-2	M-Series
65	21.9	0.4	78.1	99.6
100	39.5	3.3	60.6	96.7
150	63.1	16.2	36.9	83.8
170	78.5	43.5	21.5	56.5
230	89.3	71.6	10.8	28.4
325	95.3	90.7	4.8	9.3
Pan	100.0	100.0	0.0	0.0

There is a significant change in the particle size distribution between the M-series and L-2 feed coal samples. These larger particles are believed to have interfered with the proper sealing of the slurry pump check valves and consequently with the pump's overall performance.

When a new pulverizer screen had been installed and a finer feed coal prepared, the run progressed smoothly, although some minor problems did arise. Solvent recovery during the run was less than desired but better than during Run L-1. The loss amounted to about 10 percent of the hourly feed solvent rate and aside from the usual loss due to sampling occurred mainly in the waste water and the light ends column overhead streams.

The problem of solids accumulation in the reactor was also encountered. After processing coal for approximately 220 hours in Reactor R-1A, the melting point of the F-1 vacuum bottoms had risen to about 450°F. This high melting point material offered considerable resistance to removal from the vacuum flash tower. The high melting point of the F-1 vacuum bottoms also indicated a low level of conversion and preparations were made for switching to Reactor R-1B. The coal feed was stopped and Reactor R-1A was flushed with solvent for about 12 hours while cooling. The vessel was then depressured, disassembled and cleared of solids buildup which amounted to approximately 32 percent of the free volume of the reactor.

With Reactor R-1B in service, the unit was brought to reaction conditions and coal processing resumed. The effects of switching to a clean reactor were immediately apparent in the improved operation of the vacuum bottoms removal system and in the reduced melting point of the vacuum bottoms (320-350°F).

After switching reactors, the unit operated smoothly for another 70 hours of coal processing, then the back pressure control valve plugged causing a major upset in the liquefaction section and a forced shutdown resulted. Approximately 40 hours were required to clear or replace plugged lines, after which the unit was restarted and heated. Coal processing resumed and proceeded smoothly for about 110 hours then was interrupted because of plugging in vacuum flash drum F-1 and its bottoms drawoff line. Slurry overflowed the vacuum flash tower, plugging

the overhead vapor condenser, the condensate accumulator S-7, the line from S-7 to the condensate bottoms pump, the pump itself and the line from the pump to the solvent accumulator A-5A. The liquefaction section was flushed with raw solvent and cooled for shutdown. Complete disassembly of the vacuum flash - solvent recovery equipment was required for cleaning and this, along with reassembly, consumed the remaining 94 hours of the run period.

Eight yield periods, each nominally 12 hours long, and one overall material balance (441.4 hours long) were completed during Run L-2. Quantitative material balances were made for all, and elemental balances made for six of the nine yield periods. All nine data period workups, including quantitative and elemental balances, sample analyses, ASTM D-86 and D-1160 distillation data and the average run conditions are attached.

Material balance closure varied from 94.7 percent for the overall balance to an average of 98 percent for the eight standard length data periods. The 12 hour long yield periods were all adjusted to 100 percent recovery in similar fashion. The main adjustment was made by increasing the product gas rate and calculating the recycle gas rate so that its contribution to the feed gas was consistent with the total feed gas rate and composition. The makeup gas rate was assumed to be the difference between the feed gas and recycle gas rates. In addition, some minor adjustments to the F-1 vacuum bottoms and J-1 discharge rates were made for certain yield periods. These adjustments involved assuming a value of 1/2 pound per hour for the J-1 discharge rate in those cases where the metering orifice was not working properly and changing the F-1 vacuum bottoms rate so that the ash out was less than or equal to the ash measured in for that particular data period. In the case of the F-1 bottoms rate change, the adjustment involved approximately the amount of material contained in one cycle of the vacuum bottoms drawoff system. Thus, depending on how quickly the vacuum bottoms collection drum was changed at the end of the yield period, the drum may have contained slightly less or slightly more vacuum bottoms material than that actually produced during the time period in question. Finally, in those yield periods for which elemental analyses were available and carbon balances were poor, forced carbon balances were made by adjusting the oil-water ratio in the waste water streams.

In the overall material balance, adjustment to 100 percent recovery was slightly different from that of the shorter yield periods because of the greater uncertainty in product rate measurements. The first step in adjustment was to increase the product gas rate so that the total gaseous nitrogen out equaled that in the feed. Next the F-1 vacuum bottoms rate was adjusted to satisfy a forced ash balance and then any remaining error was

normalized among the other outgoing liquid streams. With this completed a forced carbon balance was made and the oil-water ratio of the waste water stream adjusted as required. The end result of these adjustments to the overall material balance agreed with the results obtained from the shorter yield periods.

A comparison of the results for the nine data periods along with the average for the eight 12 hour long yield periods is shown on the following page.

Conversion of MAF lignite to gas, oil and SRL varied from 83 to 91.5 weight percent with the overall conversion for the run being 88.7 percent.

In general, the net gas yield was equal to 30.6 weight percent of the MAF lignite charged and the net hydrocarbon liquid yield 63.5 weight percent. Distillable oil made up 24.6 percent of the total organic liquid yield while SRL comprised the remaining 75.4 percent.

Actual solvent recovery for recycle during the coal processing period was about 92.6 percent. For the entire 600 odd hours of operation it was necessary to add about 3400 pounds of fresh solvent to maintain the working inventory. This constituted as hourly loss of about six percent of the feed solvent.

The calculated maximum possible solvent recovery on a total oil basis was 104-105 percent and on a light oil free basis 90-94 percent.

Consumption of reducing gases on a hydrogen equivalent basis was 2.1 weight percent of the MAF lignite or 4.0 standard cubic feet per pound MAF lignite charged.

As mentioned earlier, the two general objectives of Run L-2 were (1) to determine the effects of partial product gas recycle and (2) to determine the effects of extended solvent reuse.

Analysis of the first objective is perhaps best accomplished by comparing the average results of all 12-hour yield periods for Run L-1 with a similar average from Run L-2. This is done in Table 2 on the following page. In the overall averages for these two runs, the effects of extended solvent reuse should be approximately the same in both cases and the differences in product yields then attributable to gas recycle or to variations in other variables. The average results of the two runs in Table 2 do indicate some differences in net yields, but the magnitudes of the differences are small and perhaps due to experimental or material balance adjustment errors. Thus, the results of the two runs appear equivalent.

In regard to plant operability, the same type of problems

Table 1

## Process Development Unit Run L-2

Yield Period	L-2B	L-2C	L-2D	L-2E	L-2F	L-2G	L-2H	L-2I	Overall L-2	L-2B thru I Average
Reactor in Use	R-1A	R-1A	R-1A	R-1A	R-1B	R-1B	R-1A	R-1A	-	-
SLS System in Use	No	No								
LHSV	1.38	1.37	1.38	1.48	1.41	1.40	1.40	1.42	1.42	1.40
GHSV	321	320	320	309	354	358	332	340	325	332
Solvent/MAF Coal Ratio	3.00	3.21	3.14	3.04	3.28	3.14	3.07	2.96	3.10	3.10
H <sub>2</sub> /CO Mol Ratio	1.71	1.86	1.72	1.20	1.23	1.17	1.10	1.34	1.38	1.42
Temperatures, °F										
Preheater Outlet, E-1	746	751	747	741	726	721	729	738	737	737
Reactor 3 ft	778	776	752	739	747	745	777	699	752	752
Reactor 7 ft	823	825	809	808	791	788	786	765	799	799
Reactor 11 ft	820	816	793	780	818	824	786	777	802	802
Reactor 15 ft	820	822	808	798	832	829	785	787	810	810
Vacuum Flash Ovhd	512	505	503	496	509	505	496	492	502	502
Dissolver Pressure, psig	2460	2460	2450	2450	2460	2460	2450	2450	2460	2460
Solvent Recycle, %										
Actual	89.1	92.3	93.1	91.6	101.0	92.7	100.2	98.5	92.6	94.8
Possible	103.0	104.2	100.0	101.2	105.4	107.2	107.0	104.8	105.0	104.1
Possible (Ex Lt Oil)	94.3	92.8	91.9	89.5	95.6	94.7	95.7	96.7	90.7	93.9
Yields, Wt % MAF Coal										
Net Gas	36.6	38.3	23.6	21.8	38.2	36.7	28.4	22.3	30.6	30.7
Net Liquid	49.6	49.6	58.6	62.0	58.8	61.6	70.4	75.7	63.5	60.8
(Dist Oil)	(9.0)	(13.7)	(-0.1)	(3.7)	(17.7)	(22.6)	(21.3)	(14.3)	(15.6)	(12.8)
(SRL)	(40.6)	(35.9)	(58.7)	(58.3)	(41.1)	(39.0)	(49.1)	(61.4)	(47.9)	(48.0)
Net Water and Ash	-2.0	-1.9	0.7	-0.8	-5.8	-6.7	-8.1	-6.5	-5.4	-3.9
Unconverted Coal	15.8	14.0	17.1	17.0	8.8	8.4	9.3	8.5	11.3	12.4
Overall Material Balance, %	98.5	98.7	99.9	99.2	96.7	96.7	97.9	96.0	94.7	98.0
Solvent Passes @ Mid-Y.P.	1.3	2.4	12.0	14.9	4.5	5.5	15.6	16.8	-	-

Table 2  
Process Development Unit Runs L-1 & L-2

Run	L-1B - L-1K Average	L-2B - L-2I Average
LHSV	1.42	1.40
GHSV	328	332
Solvent/MAF Coal Ratio	2.96	3.10
H <sub>2</sub> /CO Mole Ratio	1.13	1.42
Temperatures, °F		
Preheater Outlet, E-1	730	737
Reactor, 3 ft	753	752
Reactor 7 ft	785	799
Reactor 11 ft	784	802
Reactor 15 ft	822	810
Maximum Reaction	822	810
Vacuum Flash Ovhd	515	502
Dissolver Pressure, psig	2500	2500
Solvent Recycle, %		
Actual	90.3	94.8
Possible	104.0	104.1
Yields, Wt % MAF Coal		
Net Gas	31.3	30.7
Net Liquid	66.1	60.8
(Dist. Oil)	(13.2)	(12.8)
(SRL)	(52.9)	(48.0)
Net Water and Ash	-5.2	-3.9
Unconverted Coal	7.8	12.4
Overall Material Balance, %	99.8	98.0

were encountered in both runs.

In summary then, operating with gas recycle posed no new operating problems and resulted in approximately the same net yields as operating with once-thru gas.

The effects of extended solvent recycle are more apparent in Run L-2 than in previous Run L-1, perhaps because of the better and longer operating periods without makeup solvent addition. The approximate number of solvent cycles without makeup solvent through the liquefaction reactor at the middle of each L-2 yield period was calculated and the net yields obtained in each data period plotted against the number of solvent passes. These are presented in Figure 1 on the following page.

Solvent recycle appears to have little effect on MAF lignite conversion. Conversion remains fairly constant at about 88 percent even though the temperature is lower in the runs with longer solvent recycle, which in this temperature range usually lowers conversion. Previous data obtained in Run M-29 indicated that the overall MAF lignite conversion increased with solvent recycle until about 8 passes, then leveled off and became constant. This trend might have been better demonstrated in Run L-2 had the temperatures been better controlled at the desired level.

Continued solvent recycle seems to favor increased total net liquid yields while the net gas yields decrease as the liquefaction solvent becomes more coal derived, though again this may be partially the effect of temperature. Water consumption remains relatively constant at about 4 weight percent of the MAF lignite.

Figure 2 presents a plot of the distillable oil and SRL components of the net liquid yield versus the number of solvent passes. With increasing solvent recycle and with decreasing temperature, the net SRL yield increases while net distillable oil yield decreases. If this trend persisted through greater solvent recycle, and perhaps decreasing temperature, only SRL might be generated, though in that case solvent production could be decreased below solvent sufficiency.

During Run L-2, the feed solvent was monitored by infrared spectroscopy for the aromatic-to-aliphatic carbon ratio, and analyzed for sulfur content periodically. Graphs of the IR ratio and sulfur content versus hours of use without make-up are shown on the following pages. In Figure 3, the infrared ratio (and consequently the solvent aromaticity) increases with time until approximately eleven solvent passes thru the liquefaction reactor have been completed. In this particular case, approximately 150 hours were required after initial startup to complete eleven passes. The starting solvent was the overhead condensate from

FIGURE 1  
EFFECTS OF SOLVENT RECYCLE ON LIQUEFACTION YIELDS  
RUN L-2  
AUGUST 21-SEPTEMBER 23, 1977




FIGURE 2  
EFFECTS OF SOLVENT RECYCLE ON LIQUEFACTION YIELDS  
RUN L-2  
AUGUST 21 - SEPTEMBER 23, 1977




FIGURE 3  
RUN L-2  
INFRARED RATIO vs TIME  
FEED SOLVENT (Sx-14)





FIGURE 4  
RUN L-2  
WEIGHT PERCENT SULFUR vs TIME  
FEED SOLVENT (Sx-14)



FS-120 carbon black feed stock that had been vacuum flashed at 20 Torr and about 525°F vapor temperature. In Figure 4, the sulfur content of the recycle solvent is shown to decrease steadily with time and apparently would level off at some equilibrium concentration below that shown on the graph. Batch autoclave experiments with low-sulfur solvents indicate the lignite derived sulfur content of SRL to be about 0.3 weight percent and a similar or slightly higher level might be expected for lignite derived solvent.

In review, some general statistics concerning Run L-2 are shown in the following table:

Total Time Scheduled	816 hours
Operating Time on Coal Scheduled	796 hours
Actual Operating Time*	591 hours
Actual Time on Coal during operating time	441.4 hours
Time on Coal as percent of Actual Operating Time	74.7%
Scheduled Operating Time	55.5%
Total Scheduled Time	54.1%

\*From time coal first introduced at 131 hours to time coal last shut off at 722 hours.

During the actual operating time on coal 21,468 pounds of lignite was processed at an average feed rate of 48.6 lbs/hr.

In Run L-2 two sets of reactor solids were obtained for analysis. The first set was removed from dissolver R-1B, which had been shut-down after approximately 48 hours of coal processing because of a leaky bottom closure. During shutdown the reactor was cooled to about 600°F by flushing with solvent for six hours. Flows were then stopped and the reactor was isolated and allowed to cool to room temperature, after which it was depressured, disassembled and 40 pounds of solids removed by drilling. Samples were taken at different distances from the bottom of the reactor and each was analyzed for ash and pyridine insoluble material. The results of these tests are presented in Table 3, and shown graphically in Figure 5. The mineral residue appears to be somewhat more concentrated near the base of the reactor, probably because of settling, although a plating-out type of mechanism may also be involved. The pyridine insoluble material is somewhat more concentrated in the upper regions of the reactor, probably because the SRL product is more subject to coking in the upper sections of the reactor where the temperatures are higher.

The second set of reactor solids samples was obtained from dissolver R-1A which had been shutdown after approximately 220 hours of coal processing because the melting point of the F-1 vacuum bottoms had risen excessively and presented numerous operating difficulties. During shutdown, reactor R-1A was cooled to below

450°F by flushing with solvent for about 12 hours. It was then isolated and allowed to cool to ambient temperature after which it was depressured, disassembled and 43 pounds of solids removed by drilling. As with the solids removed from reactor R-1B, samples were taken at various points throughout the reactor and analyzed for ash and pyridine insoluble material. The results are shown in Table 4 and Figure 6. The same general trends in composition are apparent for the R-1A reactor solids as were indicated for the R-1B solids, although one important difference may be noted. The concentration of both the ash and pyridine insoluble material has been shifted to the right, indicating an increase in these materials with time. The average data for the R-1B and R-1A reactor solids are plotted versus hours of coal processing in Figure 7. It appears that the amount of total solids in the reactor remained fairly constant with time at about 29 pounds per cubic foot of reactor volume. However, the concentrations of both ash and pyridine insoluble material increased with time. The pyridine insoluble material and the ash were both higher after 220 hours of operation in reactor R-1A than after 48 hours of operation in reactor R-1B. The apparent rate of increase over the period from 48 hours to 220 hours was 0.027 and 0.018 pounds per hour per cubic foot of reactor volume for pyridine insolubles and for ash, respectively.

It is not clear as to what might happen to the reactor solids during longer periods of coal processing; however, in the present reactors the conversion of MAF lignite to gas, oil and SRL is greatly decreased after approximately 220 hours of operation on coal.

Table 3

R-1B Reactor Solids  
Run L-2  
August 29, 1977  
48 hours of Coal Processing  
40 pounds of solids removed

Sample Location (feet from bottom of Reactor)	Wt % Ash	Wt % Pyridine Insoluble Material
7	10.4	39.1
10	12.4	57.1
13	11.6	57.6
15	11.5	59.9
Top	9.0	50.8

Table 4

Reactor R-1A Solids  
Run L-2  
September 9, 1977  
220 hours of Coal Processing  
43 pounds of solids removed

Sample Location (feet from base of Reactor)	Wt % Ash	Wt % Pyridine Insoluble Materil
Btm	28.2	43.9
3	21.5	62.7
6	19.4	69.7
9	18.1	73.5
12	15.9	73.7

FIGURE 5  
REACTOR R-1B SOLIDS  
Run L-2  
August 29, 1977  
48 hours of coal processing  
40 pounds of solids removed

○ ASH  
◇ PYRIDINE INSOLUBLE MATERIAL




FIGURE 6  
REACTOR R-1A SOLIDS  
Run L-2  
September 9, 1977  
220 hours of coal processing  
43 pounds of solids removed





FIGURE 7  
REACTOR SOLIDS ACCUMULATION  
RUN L-2



RUN CONDITIONS

RUN NO. L-2

DATE MADE 8/21-9/23/77

TEMPERATURE °F

PRESSURE, psig

Only one reactor in use at any one time

PREHEATER E-I  
 SAND BATH 757  
 INLET 276  
 OUTLET 737

DISSOLVERS  
~~XXXX~~ (1) 752  
 (2) 799  
 (3) 802  
 (4) 810  
~~XXXX~~ (1) \_\_\_\_\_  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_  
 (4) \_\_\_\_\_

REACTOR PRODUCT SEPARATORS  
 S-1 580  
 S-2 80  
 S-3 497  
 S-4A 82  
 S-4B 74

PREHEATER E-II  
 DOWTHERM 682  
 INLET 432  
 OUTLET 644

VACUUM FLASH F-I  
 OVERHEAD VAPOR 502  
 UPPER WALL 606  
 LOWER WALL 600  
 DOWNCOMER 550  
 CONDENSATE  
 ACCUMULATOR, S-7 83

PREHEATER E-13  
 DOWTHERM 403  
 INLET 80  
 OUTLET 176

LIGHT ENDS COLUMN, F-2  
 REBOILER 314  
 LOWER SECTION 229  
 FEED SECTION 227  
 OVERHEAD 180  
 S-8 73  
 S-9 -

SOLVENT COLUMN, F-3  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

HEAVY ENDS COLUMN, F-4  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

VACUUM FLASH, F-0  
 OVERHEAD NIU  
 BOTTOMS \_\_\_\_\_

PRECIPITATION TOWER, V-8  
 ZONE (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_

RECOVERY TOWER V-9  
 REBOILER NIU  
 OVERHEAD \_\_\_\_\_

SEPARATORS S-1 and S-2  
2460

SEPARATOR S-3  
245

SEPARATORS S-4A and S-4B  
62

VACUUM FLASH, F-1  
14 Torr

LIGHT ENDS COLUMN, F-2  
Atm

SOLVENT COLUMN, F-3  
NIU

HEAVY ENDS COLUMN, F-4  
NIU

VACUUM FLASH, F-0  
NIU


SETTLING TOWER, V-8  
NIU

RECOVERY TOWER, V-7  
NIU

	Start	End	Run No: L-2
Date of Run	8/21/77	9/23/77	Units: lbs, °F, psig
Time of Run	0000	2400	Prep. By: GGB
Length of Run	816	hrs.	Updated: 3/7/78
Hours on Coal at End of Y.P.	441.4		

### MASS RATES AND RUN CONDITIONS

PRODUCT GAS TO THERMAL	2622.0
OXIDIZER	
PRODUCT GAS TO RECYCLE	2673.7



-259-

69,830.1	TOTAL	OPEN	CLOSED	TOTAL	69830.1
----------	-------	------	--------	-------	---------

Numbers in parentheses are not included in the totals.

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Product Gas and F-1 Btms Rates Adjusted, then Normalized with Forced Carbon Balance  
Revised: 3/7/78

Run No: L-2 Overall  
Date: 8/21-9/23/77  
Time: 441.4 hrs of Coal Processing lbs.

SUMMARY

Temperature: 737°F  
Pressure: 2460 psig  
LHSV: 1.42  
GHSV: 325

STREAM DESCRIPTION	Total In	Total Out	Net Yield	WT % MAF Coal	
SAMPLE POINT					
Hydrogen - H <sub>2</sub>	554.4	473.9	-80.5		
Carbon Monoxide - CO	5856.9	3095.7	-2761.2		
Carbon Dioxide - CO <sub>2</sub>	27.3	5398.1	5370.8		
Hydrogen Sulfide - H <sub>2</sub> S		90.6	90.6		
Methane - CH <sub>4</sub>	633.4	1429.6	796.2	4011.9	30.63
Ethane - C <sub>2</sub> H <sub>6</sub>	204.8	551.5	346.7		
Propane - C <sub>3</sub> H <sub>8</sub>	95.2	328.5	233.3		
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	93.6	93.6	-0-		
Ammonia - NH <sub>3</sub>		16.0	16.0		
Light Oil - (0-100°C @ 1.6 Torr)	10011.5	14914.8	4903.3		
Solvent - (100-230°C @ 1.6 Torr)	29543.6	26758.5	-2785.1	8319.1	63.52
Heavy Oil - (230-255°C @ 1.6 Torr)	1100.1	1029.3	-70.8		
SRL		6271.7	6271.7		
Coat (MAF)	13097.6	1474.4	-11623.2		-88.74
Ash	1283.8	1283.8	-0-		-0-
Water	7327.9	6620.1	-707.8		-5.41
Phenol					
TOTAL	69830.1	69830.1	-0-		

Carbon	48186.9	48186.9	-0-		
Hydrogen	5433.5	5668.8	235.3		
Nitrogen	334.6	335.1	0.5		
Sulfur	582.8	578.6	-4.2		
Oxygen (by diff)	14008.5	13776.9	-231.6		
Ash	1283.8	1283.8	-0-		
TOTAL	69830.1	69830.1	-0-		

PROJECT LIGNITE  
MEASURED AND ADJUSTED MATERIAL BALANCE  
Revised: 3/6/78

Run No: L-2 Overall  
Date: 8/21-9/23/77  
Time: 441.4 hrs Coal Processing

MATERIAL IN

Temperature: 737°F  
Pressure: 2460 psig  
LHSV: 1.42  
GHSV: 325

Quantitative	STREAM DESCRIPTION	← Feed Gas →		Lignite	Feed Solvent	Total In
		Recycle Gas	Makeup Gas			
	SAMPLE POINT	Sx-20	Sx-18	Sx-1	*Sx-14	
	Hydrogen - H <sub>2</sub>	223.3	331.1			554.4
	Carbon Monoxide - CO	1445.9	4411.0			5856.9
	Carbon Dioxide - CO <sub>2</sub>	27.3				27.3
	Hydrogen Sulfide - H <sub>2</sub> S					
	Methane - CH <sub>4</sub>	633.4				633.4
	Ethane - C <sub>2</sub> H <sub>6</sub>	204.8				204.8
	Propane - C <sub>3</sub> H <sub>8</sub>	95.2				95.2
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>	43.8	49.8			93.6
	Ammonia - NH <sub>3</sub>					
	Light Oil - (0-100°C @ 1.6 Torr)				10011.5	10011.5
	Solvent - (100-230°C @ 1.6 Torr)				29543.6	29543.6
	Heavy Oil - (230-255°C @ 1.6 Torr)				1100.1	1100.1
	SRL					
	Coal (MAF)			13097.6		13097.6
	Ash			1283.8		1283.8
	Water			7086.6	241.3	7327.9
	Phenol					
	<b>TOTAL</b>	<b>2673.7</b>	<b>4791.9</b>	<b>21468.0</b>	<b>40896.5</b>	<b>69830.1</b>

Elemental	← Feed Gas →		Lignite	Feed Solvent	Total In
	Recycle Gas	Makeup Gas			
Carbon	1344.1	1890.4	9450.2	35502.2	48186.9
Hydrogen	439.8	331.1	1386.8	3275.8	5433.5
Nitrogen	43.8	49.8	122.4	118.6	334.6
Sulfur			128.8	454.0	582.8
Oxygen (by diff)	846.0	2520.6	9096.0	1545.9	14008.5
Ash			1283.8		1283.8
<b>TOTAL</b>	<b>2673.7</b>	<b>4791.9</b>	<b>21468.0</b>	<b>40896.5</b>	<b>69830.1</b>

\*Based on average solvent/coal ratio (1.905)

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Product Gas and F-1 Btms Rates Adjusted, then Normalized with Forced Carbon Balance

Revised: 3/7/78

Run No: L-2 Overall

Date: 8/21-9/23/77

Time: 441.4 hrs of Coal processing lbs

MATERIAL OUT

Temperature: 737°F

Pressure: 2460 psig

LHSV: 1.42

GHSV: 325

STREAM DESCRIPTION	Product Gas			S-4A	S-4B	S-8
	Vent Gas	Recycle Gas	Absorbed Gas	Ovhd	Btms	Ovhd
SAMPLE POINT	Sx-20	Sx-20	Calc	Sx-30	Calc	Sx-44
Hydrogen - H <sub>2</sub>	218.9	223.3		30.1		
Carbon Monoxide - CO	1418.0	1445.9		208.1		
Carbon Dioxide - CO <sub>2</sub>	26.7	27.3	3935.0	1263.2		
Hydrogen Sulfide - H <sub>2</sub> S			56.7	33.9		
Methane - CH <sub>4</sub>	621.2	633.4		162.1		
Ethane - C <sub>2</sub> H <sub>6</sub>	200.9	204.8		129.0		
Propane - C <sub>3</sub> H <sub>8</sub>	93.3	95.2		120.2		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	43.0	43.8		6.8		
Ammonia - NH <sub>3</sub>			4.8	3.9	7.3	
Light Oil - (0-100°C @ 1.6 Torr)					1599.7	
Solvent - (100-230°C @ 1.6 Torr)					631.8	
Heavy Oil - (230-255°C @1.6 Torr)					34.0	
SRL						
Coal (MAF)						
Ash						
Water					5827.0	
Phenol						
TOTAL	2622.0	2673.7	3996.5	1957.3	8099.8	Negl.

Carbon	1318.1	1344.1	1073.1	756.7	1884.2	
Hydrogen	431.3	439.8	4.0	121.1	855.3	
Nitrogen	43.0	43.8	4.0	10.0	13.8	
Sulfur			53.5	31.9	11.4	
Oxygen (by diff)	829.6	846.0	2861.9	1037.6	5335.1	
Ash						
TOTAL	2622.0	2673.7	3996.5	1957.3	8099.8	Negl.

PROJECT LIGNITE

ADJUSTED MATERIAL BALANCE

Product Gas & F-1 Btms Rates Adjusted, then Normalized with Forced Carbon Balance

Revised: 3/7/78

Temperature: 737°F

Run No: L-2 Overall

MATERIAL OUT

Pressure: 2460 psig

Date: 8/21-9/23/77

LHSV: 1.42

Time: 441.4 hrs of Coal Processing

lbs.

GHSV: 325

STREAM DESCRIPTION	S-8	J-1	Cold	F-1	← Recycle	→ Solvent
	Btms	Exhaust	Trap	Btms	S-7 Btms	LEC Btms
SAMPLE POINT	Sx-16	Sx-32	Sx-33	Sx-2	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>		1.6				
Carbon Monoxide - CO		23.7				
Carbon Dioxide - CO <sub>2</sub>		145.9				
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>		12.9				
Ethane - C <sub>2</sub> H <sub>6</sub>		16.8				
Propane - C <sub>3</sub> H <sub>8</sub>		19.8				
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	1499.7		50.9		5807.4	5957.1
Solvent - (100-230°C @ 1.6 Torr)	131.4		7.6	1054.9	21087.1	3845.7
Heavy Oil - (230-255°C @ 1.6 Torr)	13.0				863.2	119.1
SRL				6271.7		
Coal (MAF)				1474.4		
Ash				1283.8		
Water	553.3		63.8		176.0	
Phenol						
TOTAL	2197.4	220.7	122.3	10084.8	27933.7	9921.9
Carbon	1353.8	89.3	51.9	7755.2	24285.6	8274.9
Hydrogen	253.8	11.8	11.8	476.0	2192.8	871.1
Nitrogen	2.0		0.2	101.9	86.6	29.8
Sulfur	4.4		0.4	99.8	329.6	47.6
Oxygen (by diff)	583.4	119.6	58.0	368.1	1039.1	698.5
Ash				1283.8		
TOTAL	2197.4	220.7	122.3	10084.8	27933.7	9921.9

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Product Gas and F-1 Btms Rates Adjusted, then normalized with Forced Carbon Balance  
Revised: 3/7/78

Run No: L-2 Overall  
Date: 8/21-9/23/77  
Time: 441.4 hrs of Coal Processing

MATERIAL OUT

Temperature: 737°F  
Pressure: 2460 psig  
LHSV: 1.42  
GHSV: 325

lbs.

STREAM DESCRIPTION						Total Out
SAMPLE POINT						
Hydrogen - H <sub>2</sub>						473.9
Carbon Monoxide - CO						3095.7
Carbon Dioxide - CO <sub>2</sub>						5398.1
Hydrogen Sulfide - H <sub>2</sub> S						90.6
Methane - CH <sub>4</sub>						1429.6
Ethane - C <sub>2</sub> H <sub>6</sub>						551.5
Propane - C <sub>3</sub> H <sub>8</sub>						328.5
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						93.6
Ammonia - NH <sub>3</sub>						16.0
Light Oil - (0-100°C @ 1.6 Torr)						14914.8
Solvent - (100-230°C @ 1.6 Torr)						26758.5
Heavy Oil - (230-255°C @1.6 Torr)						1029.3
SRL						6271.7
Coal (MAF)						1474.4
Ash						1283.8
Water						6620.1
Phenol						
<b>TOTAL</b>						<b>69830.1</b>

Quantitative

Carbon						48186.9
Hydrogen						5668.8
Nitrogen						335.1
Sulfur						578.6
Oxygen (by diff)						13776.9
Ash						1283.8
<b>TOTAL</b>						<b>69830.1</b>

Elemental

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/7/78

Run No: L-2 Overall

Date: 8/21-9/23/77

Time: 441.4 hrs.

WEIGHT PERCENT

SAMPLE DESCRIPTION	Lignite	F-1 Btms	LEC Btms	Feed Solvent	S-8 Oil	S-8 Water
	Sx-1	*Sx-2	Sx-12	Sx-14	Sx-16	Sx-16
Hydrogen -H <sub>2</sub>						
Carbon Monoxide-CO						
Carbon Dioxide-CO <sub>2</sub>						
Hydrogen Sulfide-H <sub>2</sub> S						
Methane-CH <sub>4</sub>						
Ethane-C <sub>2</sub> H <sub>6</sub>						
Propane-C <sub>3</sub> H <sub>8</sub>						
Butane-C <sub>4</sub> H <sub>10</sub>						
Nitrogen-N <sub>2</sub>						
Ammonia-NH <sub>3</sub> (PPM)						
Light Oils-(0-100°C @ 1.6 Torr)			60.04	24.48	91.22	
Solvent-(100-230°C @ 1.6 Torr)		10.46	38.76	72.24	7.99	
Heavy Oil-(230-255°C @1.6 Torr)			1.20	2.69	0.79	
SRL		62.19				
Coal (MAF)	61.01	14.62				
Ash	5.98	12.73				
Water	33.01			0.59		100
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		83.25				
Melting Point °F		345				
Specific Gravity 60/60			0.990	1.042		
Viscosity, cp						

Quantitative

Carbon	44.02	76.90	83.40	86.81	82.35	
Hydrogen	6.46	4.72	8.78	8.01	11.69	11.11
Nitrogen	0.57	1.01	0.30	0.29	0.12	
Sulfur	0.60	.99	0.48	1.11	0.27	
Oxygen (by diff)	42.37	3.65	7.04	3.78	5.57	88.89
Ash	5.98	12.73				
TOTAL	100	100	100	100	100	100
Number of Sample Avg.						

Elemental

\*Wt % distillable oil calculated by following equation:

$$\text{Wt \% distillable oil} = -0.1273 (\text{F-1 Btms melting point}) + 54.38$$

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/7/78

Run No: L-2 Overall

Date: 8/21-9/23/77

Time: 441.4 hrs.

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-8 Total	Makeup Gas	Product Gas	Recycle Gas	Feed Gas	S-4B Oil
SAMPLE POINT	Sx-16	Sx-18	Sx-19	Sx-20	Sx-21	Sx-23
Hydrogen - H <sub>2</sub>		6.91	4.57	8.35	7.40	
Carbon Monoxide - CO		92.05	29.21	54.08	74.94	
Carbon Dioxide - CO <sub>2</sub>			44.78	1.02	0.41	
Hydrogen Sulfide - H <sub>2</sub> S			0.65			
Methane - CH <sub>4</sub>			13.46	23.69	10.35	
Ethane - C <sub>2</sub> H <sub>6</sub>			4.42	7.66	3.59	
Propane - C <sub>3</sub> H <sub>8</sub>			2.06	3.56	2.17	
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>		1.04	0.79	1.64	1.14	
Ammonia - NH <sub>3</sub> (PPM)			0.06			
Light Oils - (0-100° C @ 1.6 Torr)	68.25					69.75
Solvent - (100-230° C @ 1.6 Torr)	5.98					27.56
Heavy Oil - (230-255° C @1.6 Torr)	0.59					1.49
SRL						
Coal (MAF)						
Ash						
Water	25.18					1.20
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						0.979
Viscosity, cp						

Carbon	61.61	39.45	40.06	50.27	44.64	82.17
Hydrogen	11.55	6.91	9.23	16.45	11.10	9.15
Nitrogen	0.09	1.04	0.84	1.64	1.14	0.28
Sulfur	0.20		0.61			0.50
Oxygen (by diff)	26.55	52.60	49.26	31.64	43.12	7.90
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.						

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/7/78

Run No: L-2 Overall

Date: 8/21-9/23/77

Time: 441.4 hrs.

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4B Water	S-4B Total	S-4A Ovhd	J-1 Discharge	Cold Trap	S-7 Btms
SAMPLE POINT	Sx-23	Sx-23	Sx-30	Sx-32	Sx-33	Sx-34/39
Hydrogen - H <sub>2</sub>			1.54	0.71		
Carbon Monoxide - CO			10.63	10.73		
Carbon Dioxide - CO <sub>2</sub>			64.54	66.13		
Hydrogen Sulfide - H <sub>2</sub> S			1.73			
Methane - CH <sub>4</sub>			8.28	5.84		
Ethane - C <sub>2</sub> H <sub>6</sub>			6.59	7.63		
Propane - C <sub>3</sub> H <sub>8</sub>			6.14	8.96		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>			0.35			
Ammonia - NH <sub>3</sub> (PPM)	0.13	0.11	0.20			
Light Oils - (0-100° C @ 1.6 Torr)		8.86			41.65	20.79
Solvent - (100-230° C @ 1.6 Torr)		3.50			6.19	75.49
Heavy Oil - (230-255° C @1.6 Torr)		0.19				3.09
SRL						
Coal (MAF)						
Ash						
Water	99.87	87.34			52.16	0.63
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						1.048
Viscosity, cp						

Carbon		10.44	38.66	40.45	42.47	86.94
Hydrogen	11.12	10.87	6.19	5.33	9.62	7.85
Nitrogen	0.12	0.14	0.51		0.13	0.31
Sulfur		0.06	1.63		0.33	1.18
Oxygen (by diff)	88.76	78.49	53.01	54.22	47.45	3.72
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.						

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/7/78

Run No: L-2 Overall

Date: 8/21-9/23/77

Time: 441.4 hrs.

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4A Oil	S-4A Water	S-4A Total	S-7 Btms	Absorbed Gas	S-4B Btms
SAMPLE POINT	Sx-37	Sx-37	Sx-37	Sx-34/39	Calc	Calc
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>					98.46	
Hydrogen Sulfide - H <sub>2</sub> S					1.42	
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)		0.12	0.01		0.12	0.09
Light Oils - (0-100°C @ 1.6 Torr)	70.55		61.94	20.79		19.75
Solvent - (100-230°C @ 1.6 Torr)	27.53		24.17	75.49		7.80
Heavy Oil - (230-255°C @1.6 Torr)	0.98		0.86	3.09		0.42
SRL						
Coal (MAF)						
Ash						
Water	0.94	99.88	13.02	0.63		71.94
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60	0.964					
Viscosity, cp						

Carbon	82.25		72.21	86.94	26.85	23.26
Hydrogen	9.25	11.12	9.48	7.85	0.10	10.56
Nitrogen	0.25	0.10	0.23	0.31	0.10	0.17
Sulfur	0.43		0.38	1.18	1.34	0.14
Oxygen (by diff)	7.82	88.78	17.70	3.72	71.61	65.87
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.						

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/7/78

Run No: L-2 Overall

Date: 8/21-9/23/77

Time: 441.4 hrs.

MOLE PERCENT

SAMPLE DESCRIPTION	MOLE PERCENT					
	Makeup Gas	Product Gas	Recycle Gas	Feed Gas	S-4A Ovhd	J-1 Discharge
SAMPLE POINT	Sx-18	Sx-19	Sx-20	Sx-21	Sx-30	Sx-32
Hydrogen -H <sub>2</sub>	50.96	42.09	52.17	51.11	21.55	11.54
Carbon Monoxide-CO	48.49	19.20	24.12	36.94	10.64	12.51
Carbon Dioxide-CO <sub>2</sub>		18.73	0.29	0.13	41.12	49.07
Hydrogen Sulfide-H <sub>2</sub> S		0.35			1.43	
Methane-CH <sub>4</sub>		15.48	18.49	8.93	14.50	11.92
Ethane-C <sub>2</sub> H <sub>6</sub>		2.71	3.19	1.65	6.16	8.31
Propane-C <sub>3</sub> H <sub>8</sub>		0.86	1.01	0.68	3.91	6.65
Butane-C <sub>4</sub> H <sub>10</sub>						
Nitrogen-N <sub>2</sub>	0.55	0.52	0.73	0.56	0.35	
Ammonia-NH <sub>3</sub> (PPM)		0.06			0.34	
Light Oils-(0-100°C @ 1.6 Torr)						
Solvent-(100-230°C @ 1.6 Torr)						
Heavy Oil-(230-255°C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100	100	100
Calc Mole Wt.	14.75	18.40	12.49	13.80	28.03	32.65
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.						

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/7/78

Run No: L-2 Overall

Date: 8/21-9/23/77

Time: 441.4 hrs.

MOLE PERCENT

SAMPLE DESCRIPTION	Absorbed Gas					
	Calc					
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>	97.86					
Hydrogen Sulfide - H <sub>2</sub> S	1.83					
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)	0.31					
Light Oils - (0-100° C @ 1.6 Torr)						
Solvent - (100-230° C @ 1.6 Torr)						
Heavy Oil - (230-255° C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100					
Calc Mole Wt.	43.73					
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.						

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: L-2 Overall  
DATE: 8/21-9/23/77  
TIME: 0000-2400

SAMPLE DESCRIPTION	F-1 Btms	LEC Btms	Feed Solv.	S-8 Oil	S-4B Oil
SAMPLE POINT	Sx-2	Sx-12	Sx-14	Sx-16	Sx-23
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR		5	5		
IBP		45	48		
5%		67	83		
10%		72	94		
20%		80	116		
30%		88	137		
40%		97	155		
50%		108	170		
60%		122	180		
70%		141	188		
80%		162	198		
90%		182	222		
95%		198	254		
DRY PT.		202	256		
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR				740	740
IBP				55	83
5%				71	131
10%				80	176
20%				96	200
30%				110	212
40%				126	224
50%				139	243
60%				156	266
70%				173	294
80%				173	336
90%				204	350
95%				280	
DRY PT.				281	352
ASPHALTENE TEST					
WT % ASH	12.73				
WT % UNCONVERTED COAL	14.62				
WT % PRE-ASPHALTENES	31.92				
WT % ASPHALTENES	20.58				
WT % MALTENES & DIST. OIL	20.15				
TOTAL	100.00				
SAYBOLT VISCOSITY, SSU					
100° F		9.3	11.5		
210° F		8.0	8.5		
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)		-	0.59		1.20
INFRARED RATIO		0.23	0.34		
SP. GRAV. 60/60 F		0.990	1.042		0.979


PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES - BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES - N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.

**PROJECT LIGNITE**  
**SAMPLE ANALYSES**  
 RUN NO: L-2 Overall  
 DATE: 8/21-9/23/77  
 TIME: 0000-2400

SAMPLE DESCRIPTION	Cold Trap Oil	S-7 Btms	S-4A Oil		
SAMPLE POINT	Sx-33	Sx-34/39	Sx-37		
<b>ASTM D-1160 DISTILLATION DATA</b>					
PRESSURE, TORR  IBP 5% 10% 20% 30% 40% 50% 60% 70% 80% 90% 95% DRY PT.	TEMPERATURE, °C	5			
		47			
		83			
		97			
		124			
		146			
		164			
		174			
		182			
		189			
		200			
		226			
		256			
		258			
<b>ASTM D-86 DISTILLATION DATA</b>					
BAROMETRIC PRESSURE, TORR  IBP 5% 10% 20% 30% 40% 50% 60% 70% 80% 90% 95% DRY PT.	TEMPERATURE, °C	740	739		
		86	88		
		93	121		
		97	171		
		98	192		
		131	203		
		140	216		
		146	230		
		162	252		
		170	279		
		173	312		
			344		
			347		
<b>ASPHALTENE TEST</b>					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
<b>SAYBOLT VISCOSITY, SSU</b>					
100° F		12.1			
210° F		8.6			
<b>MISCELLANEOUS</b>					
KF H <sub>2</sub> O WT% (Raw Sx)	52.16	0.63	0.94		
INFRARED RATIO		0.35			
SP. GRAV. 60/60 F		1.048	0.964		

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
 ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
 MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
 DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.

DISTILLABLE OIL CONTENT OF F-I BOTTOMS  
VERSUS  
F-I BOTTOMS MELTING POINT



PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 3/7/78

Run No: L-2 Overall  
Date: 8/21-9/23/77  
Time: 441.4 hrs of Coal Processing

MATERIAL OUT

Temperature: 737°F  
Pressure: 2460 psig  
LHSV: 1.42  
GHSV: 325

STREAM DESCRIPTION	Product Gas			S-4A	S-4B	S-8
	Vent Gas	Recycle Gas	Absorbed Gas	Ovhd	Btms	Ovhd
SAMPLE POINT	Sx-20	Sx-20	Calc	Sx-30	Sx-23	Sx-44
Hydrogen - H <sub>2</sub>	118.9	223.3		30.1		
Carbon Monoxide - CO	770.1	1445.9		208.1		
Carbon Dioxide - CO <sub>2</sub>	14.5	27.3	3294.8	1263.2		
Hydrogen Sulfide - H <sub>2</sub> S			47.5	33.9		
Methane - CH <sub>4</sub>	337.3	633.4		162.1		
Ethane - C <sub>2</sub> H <sub>6</sub>	109.1	204.8		129.0		
Propane - C <sub>3</sub> H <sub>8</sub>	50.7	95.2		120.2		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	23.4	43.8		6.8		
Ammonia - NH <sub>3</sub>			4.0	3.9	7.7	
Light Oil - (0-100° C @ 1.6 Torr)					621.2	
Solvent - (100-230° C @ 1.6 Torr)					245.4	
Heavy Oil - (230-255° C @1.6 Torr)					13.3	
SRL						
Coal (MAF)						
Ash						
Water					6123.4	
Phenol						
TOTAL	1424.0	2673.7	3346.3	1957.3	7011.0	Neg.

Carbon	715.8	1344.1	898.5	756.7	732.0	
Hydrogen	234.2	439.8	3.3	121.1	762.1	
Nitrogen	23.4	43.8	3.3	10.0	9.8	
Sulfur			44.9	31.9	4.2	
Oxygen (by diff)	450.6	846.0	2396.3	1037.6	5502.9	
Ash						
TOTAL	1424.0	2673.7	3346.3	1957.3	7011.0	Negl.

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 3/7/78

Run No: L-2 Overall  
Date: 8/21-9/23/77  
Time: 441.4 hrs of Coal Processing

MATERIAL OUT

Temperature: 737°F  
Pressure: 2460 psig  
LHSV: 1.42  
GHSV: 325

STREAM DESCRIPTION	S-8	J-1	Cold	F-1	← Recycle	Solvent →
	Btms	Exhaust	Trap	Btms	S-7 Btms	LEC Btms
SAMPLE POINT	Sx-16	Sx-32	Sx-33	Sx-2	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>		1.6				
Carbon Monoxide - CO		23.7				
Carbon Dioxide - CO <sub>2</sub>		145.9				
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>		12.9				
Ethane - C <sub>2</sub> H <sub>6</sub>		16.8				
Propane - C <sub>3</sub> H <sub>8</sub>		19.8				
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	1298.1		44.1		5807.4	5957.1
Solvent - (100-230°C @ 1.6 Torr)	113.8		6.6	1008.5	21087.1	3845.7
Heavy Oil - (230-255°C @1.6 Torr)	11.2				863.2	119.1
SRL				5995.7		
Coal (MAF)				1409.5		
Ash				1227.3		
Water	478.9		55.2		176.0	
Phenol						
TOTAL	1902.0	220.7	105.9	9641.0	27933.7	9921.9

Carbon	1171.8	89.3	45.0	7413.9	24285.6	8274.9
Hydrogen	219.7	11.8	10.2	455.0	2192.8	871.1
Nitrogen	1.7		0.1	97.4	86.6	29.8
Sulfur	3.8		0.3	95.5	329.6	47.6
Oxygen (by diff)	505.0	119.6	50.3	351.9	1039.1	698.5
Ash				1227.3		
TOTAL	1902.0	220.7	105.9	9641.0	27933.7	9921.9



RUN CONDITIONS

RUN NO. L-2B  
 DATE MADE 8/31/77

TEMPERATURE °F

PRESSURE, psig

PREHEATER E-I

SAND BATH 766  
 INLET 298  
 OUTLET 746

DISSOLVERS

R-1A (1) 778  
 (2) 823  
 (3) 820  
 (4) 820  
 R-1B (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_  
 (4) \_\_\_\_\_

REACTOR PRODUCT SEPARATORS

S-1 595  
 S-2 79  
 S-3 514  
 S-4A 82  
 S-4B 74

PREHEATER E-II

DOWTHERM 677  
 INLET 440  
 OUTLET 630

VACUUM FLASH F-1

OVERHEAD VAPOR 512  
 UPPER WALL 596  
 LOWER WALL 571  
 DOWNCOMER 544  
 CONDENSATE  
 ACCUMULATOR, S-7 84

PREHEATER E-13

DOWTHERM 399  
 INLET 80  
 OUTLET 192

LIGHT ENDS COLUMN, F-2

REBOILER 356  
 LOWER SECTION 191  
 FEED SECTION -  
 OVERHEAD 180  
 S-8 74  
 S-9 -

SOLVENT COLUMN, F-3

REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

HEAVY ENDS COLUMN, F-4

REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

VACUUM FLASH, F-0

OVERHEAD NIU  
 BOTTOMS \_\_\_\_\_

PRECIPITATION TOWER, V-8

ZONE (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_

RECOVERY TOWER V-9

REBOILER NIU  
 OVERHEAD \_\_\_\_\_

SEPARATORS S-1 and S-2  
2460

SEPARATOR S-3  
250

SEPARATORS S-4A and S-4B  
62

VACUUM FLASH, F-1  
14 Torr

LIGHT ENDS COLUMN, F-2  
Atm

SOLVENT COLUMN, F-3  
NIU

HEAVY ENDS COLUMN, F-4  
NIU

VACUUM FLASH, F-0  
NIU


SETTLING TOWER, V-8  
NIU

RECOVERY TOWER, V-7  
NIU

	Start	End	Run No: L-2B
Date of Run	8/31/77	8/31/77	Units: lbs/hr, °F, Psig
Time of Run	0200	1400	Prep. By: GGB & BCL
Length of Run	12	hrs.	Updated: 3/3/78
Hours on Coal at End of Y.P.	80.3		

### MASS RATES AND RUN CONDITIONS

PRODUCT GAS TO THERMAL	6.66
OXIDIZER	
PRODUCT GAS TO RECYCLE	7.15



-278-

153.26 TOTAL

☒ OPEN      ☒ CLOSED

TOTAL 153.26

Numbers in parentheses are not included in the totals.

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product Gas and F-1 Btms Rates Adjusted  
 Revised: 3/3/78

Run No: L-2B  
 Date: 8/31/77  
 Time: 0200-1400

SUMMARY

Temperature: 746°F  
 Pressure: 2460 psig  
 LHSV: 1.38  
 GHSV: 321

	lbs/hour				WT% MAF Coal
	Total In	Total Out	Net Yield		
SAMPLE POINT					
Hydrogen - H <sub>2</sub>	1.31	1.14	-0.17		
Carbon Monoxide - CO	10.70	6.04	-4.66		
Carbon Dioxide - CO <sub>2</sub>	0.56	11.69	11.13		
Hydrogen Sulfide - H <sub>2</sub> S		0.13	0.13		
Methane - CH <sub>4</sub>	2.00	4.49	2.49	10.78	36.57
Ethane - C <sub>2</sub> H <sub>6</sub>	0.64	1.68	1.04		
Propane - C <sub>3</sub> H <sub>8</sub>	0.40	1.19	0.79		
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.16	0.14	-0.02		
Ammonia - NH <sub>3</sub>		0.05	0.05		
Light Oil - (0-100°C @ 1.6 Torr)	9.50	16.68	7.18		
Solvent - (100-230°C @ 1.6 Torr)	77.31	71.99	-5.32	14.62	49.59
Heavy Oil - (230-255°C @1.6 Torr)	1.61	2.41	0.80		
SRL		11.96	11.96		
Coal (MAF)	29.48	4.66	-24.82		-84.19
Ash	3.14	3.14	-0-		-0-
Water	16.45	15.87	-0.58		-1.97
Phenol					
TOTAL	153.26	153.26	-0-		

Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
TOTAL					

PROJECT LIGNITE  
MEASURED & ADJUSTED MATERIAL BALANCE  
Revised: 3/3/78

Run No: L-2B  
Date: 8/31/77  
Time: 0200-1400

MATERIAL IN

Temperature: 746°F  
Pressure: 2460 psig  
LHSV: 1.38  
GHSV: 321

lbs/hr.

Quantitative	STREAM DESCRIPTION	← Feed Gas →		Lignite	Feed Solvent	Total In.
		Recycle Gas	Makeup Gas			
	SAMPLE POINT	Sx-20	Sx-18	Sx-1	Sx-14	
	Hydrogen - H <sub>2</sub>	0.56	0.75			1.31
	Carbon Monoxide - CO	2.93	7.77			10.70
	Carbon Dioxide - CO <sub>2</sub>	0.56				0.56
	Hydrogen Sulfide - H <sub>2</sub> S					
	Methane - CH <sub>4</sub>	2.00				2.00
	Ethane - C <sub>2</sub> H <sub>6</sub>	0.64				0.64
	Propane - C <sub>3</sub> H <sub>8</sub>	0.40				0.40
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>	0.06	0.10			0.16
	Ammonia - NH <sub>3</sub>					
	Light Oil - (0-100°C @ 1.6 Torr)				9.50	9.50
	Solvent - (100-230°C @ 1.6 Torr)				77.31	77.31
	Heavy Oil - (230-255°C @ 1.6 Torr)				1.61	1.61
	SRL					
	Coal (MAF)			29.48		29.48
	Ash			3.14		3.14
	Water			16.09	0.36	16.45
	Phenol					
	<b>TOTAL</b>	<b>7.15</b>	<b>8.62</b>	<b>48.71</b>	<b>88.78</b>	<b>153.26</b>

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	<b>TOTAL</b>					

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product Gas and F-1 Btms Rates Adjusted  
 Revised: 3/3/78

Run No: L-2B  
 Date: 8/31/77  
 Time: 0200-1400

MATERIAL OUT

lbs/hr.

Temperature: 746°F  
 Pressure: 2460 psig  
 LHSV : 1.38  
 GHSV: 321

STREAM DESCRIPTION	Product Gas		Absorbed Gas	S-4A	S-4B	S-8
	Vent Gas	Recycle Gas		Gas Ovhd	Btms	Ovhd.
SAMPLE POINT	Sx-20	Sx-20	Calc	Sx-30	Sx-23	Sx-44
Hydrogen - H <sub>2</sub>	0.52	0.56		0.06		
Carbon Monoxide - CO	2.73	2.93		0.36		
Carbon Dioxide - CO <sub>2</sub>	0.52	0.56	6.92	3.36		
Hydrogen Sulfide - H <sub>2</sub> S			0.09	0.04		
Methane - CH <sub>4</sub>	1.86	2.00		0.58		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.60	0.64		0.39		
Propane - C <sub>3</sub> H <sub>8</sub>	0.37	0.40		0.37		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.06	0.06		0.02		
Ammonia - NH <sub>3</sub>				0.02	0.03	
Light Oil - (0-100°C @ 1.6 Torr)					2.40	
Solvent - (100-230°C @ 1.6 Torr)					1.65	
Heavy Oil - (230-255°C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water					14.00	
Phenol						
TOTAL	6.66	7.15	7.01	5.20	18.08	Negl.

Elemental	Product Gas		Absorbed Gas	S-4A	S-4B	S-8
	Vent Gas	Recycle Gas		Gas Ovhd	Btms	Ovhd.
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE  
Product Gas and F-1 Btms Rates Adjusted  
Revised: 3/3/78

Run No: L-2B  
Date: 8/31/77  
Time: 0200-1400

MATERIAL OUT

Temperature: 746°F  
Pressure: 2460 psig  
LHSV: 1.38  
GHSV: 321

lbs/hr.

STREAM DESCRIPTION	S-8	J-1	Cold	F-1	← Recycle	Solvent →
	Btms	*Exhaust	Trap	Btms	S-7 Btms	LEC Btms
SAMPLE POINT	Sx-16	Sx-32	Sx-33	Sx-1	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO		0.02				
Carbon Dioxide - CO <sub>2</sub>		0.33				
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>		0.05				
Ethane - C <sub>2</sub> H <sub>6</sub>		0.05				
Propane - C <sub>3</sub> H <sub>8</sub>		0.05				
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	3.50		0.26		6.69	3.83
Solvent - (100-230°C @ 1.6 Torr)	1.67		0.02	3.19	59.67	5.79
Heavy Oil - (230-255°C @1.6 Torr)					2.22	0.19
SRL				11.96		
Coal (MAF)				4.66		
Ash				3.14		
Water	1.05		0.09		0.73	
Phenol						
TOTAL	6.22	0.50	0.37	22.95	69.31	9.81

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

\*Rate assumed to be similar to those of the other L-2 yield periods in which the orifice meter was working properly.

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product Gas and F-1 Btms Rates Adjusted  
 Revised: 3/3/78

Run No: L-2B  
 Date: 8/31/77  
 Time: 0200-1400

MATERIAL OUT  
 lbs/hr.

Temperature: 746°F  
 Pressure: 2460 psig  
 LHSV: 1.38  
 GHSV: 321

STREAM DESCRIPTION						Total Out
SAMPLE POINT						
Hydrogen - H <sub>2</sub>						1.14
Carbon Monoxide - CO						6.04
Carbon Dioxide - CO <sub>2</sub>						11.69
Hydrogen Sulfide - H <sub>2</sub> S						0.13
Methane - CH <sub>4</sub>						4.49
Ethane - C <sub>2</sub> H <sub>6</sub>						1.68
Propane - C <sub>3</sub> H <sub>8</sub>						1.19
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						0.14
Ammonia - NH <sub>3</sub>						0.05
Light Oil - (0-100°C @ 1.6 Torr)						16.68
Solvent - (100-230°C @ 1.6 Torr)						71.99
Heavy Oil - (230-255°C @1.6 Torr)						2.41
SRL						11.96
Coal (MAF)						4.66
Ash						3.14
Water						15.87
Phenol						
TOTAL						153.26

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/3/78

Run No: L-2B

Date: 8/31/77

Time: 0200-1400

WEIGHT PERCENT

SAMPLE DESCRIPTION	Lignite	F-1 Btms	LEC Btms	Feed Solvent	S-8 Oil	S-8 Water
	Sx-1	*Sx-2	Sx-12	Sx-14	Sx-16	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100° C @ 1.6 Torr)			39.05	10.70	67.60	
Solvent - (100-230° C @ 1.6 Torr)		13.90	58.98	87.08	32.40	
Heavy Oil - (230-255° C @1.6 Torr)			1.97	1.81		
SRL		52.13				
Coal (MAF)	60.53	20.29				
Ash	6.45	13.68				
Water	33.02			0.41		100
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		76.49				
Melting Point °F		318				
Specific Gravity 60/60			0.997	1.040		
Viscosity, cp						

SAMPLE DESCRIPTION	Lignite	F-1 Btms	LEC Btms	Feed Solvent	S-8 Oil	S-8 Water
	Sx-1	*Sx-2	Sx-12	Sx-14	Sx-16	Sx-16
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	2

\*Distillable oil calculated by following equation:

Wt % Distillable Oil = -0.1273 (F-1 Btms Melting Point) + 54.38. See graph.

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/3/78

Run No: L-2B

Date: 8/31/77

Time: 0200-1400

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-8	Makeup	Product	Recycle	Feed	S-4B
	Total	Gas	Gas	Gas	Gas	Oil
SAMPLE POINT	Sx-16	Sx-18	Sx-19	Sx-20	Sx-21	*Sx-23
Hydrogen - H <sub>2</sub>		8.70	3.77	7.77	8.28	
Carbon Monoxide - CO		90.13	20.21	41.03	67.89	
Carbon Dioxide - CO <sub>2</sub>			47.81	7.83	3.54	
Hydrogen Sulfide - H <sub>2</sub> S			0.79			
Methane - CH <sub>4</sub>			19.54	27.96	12.68	
Ethane - C <sub>2</sub> H <sub>6</sub>			4.89	8.93	4.05	
Propane - C <sub>3</sub> H <sub>8</sub>			2.51	5.61	2.53	
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>		1.17	0.44	0.87	1.03	
Ammonia - NH <sub>3</sub> (PPM)			0.04			
Light Oils - (0-100° C @ 1.6 Torr)	56.19					58.93
Solvent - (100-230° C @ 1.6 Torr)	26.93					40.60
Heavy Oil - (230-255° C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water	16.88					0.47
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						0.956
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	2

\*Insufficient sample for distillation. Assumed to be the same as the S-4A Oil.

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/3/78

Run No: L-2B

Date: 8/31/77

Time: 0200-1400

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4B	S-4B	S-4A	J-1	Cold	S-4A
	Water	Total	Ovhd	Discharge	Trap	Oil
SAMPLE POINT	Sx-23	Sx-23	Sx-30	Sx-32	Sx-33	Sx-37
Hydrogen - H <sub>2</sub>			1.11	0.75		
Carbon Monoxide - CO			6.94	4.31		
Carbon Dioxide - CO <sub>2</sub>			64.56	66.70		
Hydrogen Sulfide - H <sub>2</sub> S			0.82			
Methane - CH <sub>4</sub>			11.16	9.52		
Ethane - C <sub>2</sub> H <sub>6</sub>			7.59	8.93		
Propane - C <sub>3</sub> H <sub>8</sub>			7.05	9.79		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)	0.18	0.14	0.39			
Light Oils - (0-100° C @ 1.6 Torr)		13.28	0.38		69.24	58.93
Solvent - (100-230° C @ 1.6 Torr)		9.15			6.30	40.60
Heavy Oil - (230-255° C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water	99.82	77.43			24.46	0.47
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						0.956
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2		2	2	1	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/3/78

Run No: L-2B

Date: 8/31/77

Time: 0200-1400

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4A	S-4A	S-7	Absorbed		
	Water	Total	Btms	Gas		
SAMPLE POINT	Sx-37	Sx-37	Sx-39	Calc.		
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>				98.67		
Hydrogen Sulfide - H <sub>2</sub> S				1.30		
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)	0.18	0.01		0.03		
Light Oils - (0-100° C @ 1.6 Torr)		55.07	9.65			
Solvent - (100-230° C @ 1.6 Torr)		37.94	86.10			
Heavy Oil - (230-255° C @1.6 Torr)			3.20			
SRL						
Coal (MAF)						
Ash						
Water	99.82	6.98	1.05			
Phenol						
TOTAL	100	100	100	100		
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60			1.056			
Viscosity, cp						
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	-		

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/3/78

Run No: L-2B

Date: 8/31/77

Time: 0200-1400

MOLE PERCENT

SAMPLE DESCRIPTION	Makeup Gas	Product Gas	Recycle Gas	Feed Gas	MOLE PERCENT	
					S-4A Ovhd	J-1 Discharge
SAMPLE POINT	Sx-18	Sx-19	Sx-20	Sx-21	Sx-30	Sx-32
Hydrogen -H <sub>2</sub>	57.15	36.43	50.25	53.99	16.20	11.91
Carbon Monoxide-CO	42.30	13.94	18.95	31.63	7.20	4.87
Carbon Dioxide-CO <sub>2</sub>		20.99	2.30	1.05	42.60	47.95
Hydrogen Sulfide-H <sub>2</sub> S		0.45			0.70	
Methane-CH <sub>4</sub>		23.59	22.60	10.34	20.25	18.81
Ethane-C <sub>2</sub> H <sub>6</sub>		3.15	3.85	1.76	7.35	9.42
Propane-C <sub>3</sub> H <sub>8</sub>		1.10	1.65	0.75	4.65	7.04
Butane-C <sub>4</sub> H <sub>10</sub>						
Nitrogen-N <sub>2</sub>	0.55	0.30	0.40	0.48	0.40	
Ammonia-NH <sub>3</sub> (PPM)		0.05			0.65	
Light Oils-(0-100°C @ 1.6 Torr)						
Solvent-(100-230°C @ 1.6 Torr)						
Heavy Oil-(230-255°C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100	100	100
Calc Mole Wt.	13.14	19.32	12.93	13.04	29.04	31.63
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Quantitative

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	2

Elemental

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/3/78

Run No: L-2B

Date: 8/31/77

Time: 0200-1400

MOLE PERCENT

Quantitative	SAMPLE DESCRIPTION	Absorbed Gas				
	SAMPLE POINT	Calc.				
	Hydrogen - H <sub>2</sub>					
	Carbon Monoxide - CO					
	Carbon Dioxide - CO <sub>2</sub>	98.25				
	Hydrogen Sulfide - H <sub>2</sub> S	1.67				
	Methane - CH <sub>4</sub>					
	Ethane - C <sub>2</sub> H <sub>6</sub>					
	Propane - C <sub>3</sub> H <sub>8</sub>					
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					
	Ammonia - NH <sub>3</sub> (PPM)	0.08				
	Light Oils - (0-100°C @ 1.6 Torr)					
	Solvent - (100-230°C @ 1.6 Torr)					
	Heavy Oil - (230-255°C @ 1.6 Torr)					
	SRL					
	Coal (MAF)					
	Ash					
	Water					
	Phenol					
TOTAL	100					
Calc. Mole Wt	43.81					
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	TOTAL					
	Number of Sample Avg.					

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: L-2B  
DATE: 8/31/77  
TIME: 0200-1400

SAMPLE DESCRIPTION	LEC Btms	Feed Solv.	S-8 Oil	Cold Trap	S-4A Oil
SAMPLE POINT	Sx-12	Sx-14	Sx-16	Sx-33	Sx-37
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR	5	5			
IBP	72.8	65.8			
5%	80.4	101			
10%	85.0	118.6			
20%	94.2	153.2			
30%	106.6	172			
40%	122.8	181.3			
50%	140	187			
60%	158.4	191.6			
70%	175.2	198.4			
80%	186.5	207.2			
90%	198.2	227.5			
95%	212.4	255.4			
DRY PT.	215	259			
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR			739	742	741
IBP			67	84	112
5%			144	99	158
10%			157	100	173
20%			170	101	200
30%			180	114	212
40%			196	127	234
50%			219	127	248
60%			255	132	294
70%			301	137	328
80%				137	338
90%					
95%					
DRY PT.			310	137	343
ASPHALTENE TEST					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
SAYBOLT VISCOSITY, SSU					
100° F					
210° F					
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Row Sx)		0.41		24.46	0.34
INFRARED RATIO					
SP. GRAV. 60/60 F	0.997	1.040			0.956


PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.

PROJECT LIGNITE  
 SAMPLE ANALYSES  
 RUN NO: L-2B  
 DATE: 8/31/77  
 TIME: 0200-1400

SAMPLE DESCRIPTION		S-7 Btms			
SAMPLE POINT		Sx-39			
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR		5			
IBP		21.4			
5%		101.3			
10%		119.6			
20%		156.8			
30%		173.2			
40%		180.6			
50%		185.6			
60%		190.8			
70%		199			
80%		209.3			
90%		234.8			
95%					
DRY PT.		260			
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR					
IBP					
5%					
10%					
20%					
30%					
40%					
50%					
60%					
70%					
80%					
90%					
95%					
DRY PT.					
ASPHALTENE TEST					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
SAYBOLT VISCOSITY, SSU					
100° F					
210° F					
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)		1.05			
INFRARED RATIO					
SP. GRAV. 60/60 F		1.056			

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
 ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
 MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
 DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.

DISTILLABLE OIL CONTENT OF F-I BOTTOMS  
VERSUS  
F-I BOTTOMS MELTING POINT



PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 3/3/78

Run No: L-2B  
Date: 8/31/77  
Time: 0200-1400

MATERIAL OUT

Temperature: 746°F  
Pressure: 2460 psig  
LHSV: 1.38  
GHSV: 321

	lbs/hr.					
	Product Gas Vent Gas	Recycle Gas	Absorbed Gas	S-4A Gas Ovhd	S-4B Btms	S-8 Ovhd
STREAM DESCRIPTION	Sx-20	Sx-20	Calc	Sx-30	Sx-23	Sx-44
Hydrogen - H <sub>2</sub>	0.26	0.56		0.06		
Carbon Monoxide - CO	1.36	2.93		0.36		
Carbon Dioxide - CO <sub>2</sub>	0.26	0.56	8.88	3.36		
Hydrogen Sulfide - H <sub>2</sub> S			0.12	0.04		
Methane - CH <sub>4</sub>	0.93	2.00		0.58		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.30	0.64		0.39		
Propane - C <sub>3</sub> H <sub>8</sub>	0.18	0.40		0.37		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.03	0.06		0.02		
Ammonia - NH <sub>3</sub>				0.02	0.03	
Light Oil - (0-100°C @ 1.6 Torr)					2.40	
Solvent - (100-230°C @ 1.6 Torr)					1.65	
Heavy Oil - (230-255°C @1.6 Torr)						
SRL						
Cool (MAF)						
Ash						
Water					14.00	
Phenol						
<b>TOTAL</b>	<b>3.32</b>	<b>7.15</b>	<b>9.00</b>	<b>5.20</b>	<b>18.08</b>	<b>Negl.</b>

Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
<b>TOTAL</b>					

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 3/3/78

Run No: L-2B  
Date: 8/31/77  
Time: 0200-1400

MATERIAL OUT

Temperature: 746°F  
Pressure: 2460 psig  
LHSV: 1.38  
GHSV: 321

Quantitative	lbs/hr.					
	S-8 Btms	J-1 Exhaust	Cold Trap	F-1 Btms	← Recycle S-7 Btms	Solvent → LEC Btms
STREAM DESCRIPTION	Sx-16	Sx-32	Sx-33	Sx-1	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	3.50		0.26		6.69	3.83
Solvent - (100-230°C @ 1.6 Torr)	1.67		0.02	3.12	59.67	5.79
Heavy Oil - (230-255°C @1.6 Torr)					2.22	0.19
SRL				11.69		
Coal (MAF)				4.55		
Ash				3.07		
Water	1.05		0.09		0.73	
Phenol						
<b>TOTAL</b>	<b>6.22</b>	<b>NA</b>	<b>0.37</b>	<b>22.43</b>	<b>69.31</b>	<b>9.81</b>

Elemental							
	Carbon						
	Hydrogen						
	Nitrogen						
	Sulfur						
	Oxygen (by diff)						
	Ash						
<b>TOTAL</b>							

NA - Not available

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 3/3/78

Run No: L-2B  
Date: 8/31/77  
Time: 0200-1400

MATERIAL OUT

Temperature: 746°F  
Pressure: 2460 psig  
LHSV: 1.38  
GHSV:321

lbs/hr.

Quantitative	STREAM DESCRIPTION					Total Out
	SAMPLE POINT					
	Hydrogen - H <sub>2</sub>					0.88
	Carbon Monoxide - CO					4.65
	Carbon Dioxide - CO <sub>2</sub>					13.06
	Hydrogen Sulfide - H <sub>2</sub> S					0.16
	Methane - CH <sub>4</sub>					3.51
	Ethane - C <sub>2</sub> H <sub>6</sub>					1.33
	Propane - C <sub>3</sub> H <sub>8</sub>					0.95
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					0.11
	Ammonia - NH <sub>3</sub>					0.05
	Light Oil - (0-100°C @ 1.6 Torr)					16.68
	Solvent - (100-230°C @ 1.6 Torr)					71.92
	Heavy Oil - (230-255°C @1.6 Torr)					2.41
	SRL					11.69
	Cool (MAF)					4.55
	Ash					3.07
	Water					15.87
	Phenol					
	TOTAL					150.89

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	TOTAL					

RUN CONDITIONS

RUN NO. L-2C  
 DATE MADE 9/7/77

TEMPERATURE °F

PRESSURE, psig

PREHEATER E-1  
 SAND BATH 770  
 INLET 292  
 OUTLET 751

DISSOLVERS  
 R-1A (1) 776  
 (2) 825  
 (3) 816  
 (4) 822  
 R-1B (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_  
 (4) \_\_\_\_\_

REACTOR PRODUCT SEPARATORS  
 S-1 596  
 S-2 77  
 S-3 508  
 S-4A 78  
 S-4B 72

PREHEATER E-11  
 DOWTHERM 677  
 INLET 440  
 OUTLET 639

VACUUM FLASH F-1  
 OVERHEAD VAPOR 505  
 UPPER WALL 597  
 LOWER WALL 570  
 DOWNCOMER 541  
 CONDENSATE  
 ACCUMULATOR, S-7 83

PREHEATER E-13  
 DOWTHERM 398  
 INLET 78  
 OUTLET 221

LIGHT ENDS COLUMN, F-2  
 REBOILER 354  
 LOWER SECTION 372  
 FEED SECTION 315  
 OVERHEAD 192  
 S-8 71  
 S-9 \_\_\_\_\_

SOLVENT COLUMN, F-3  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

HEAVY ENDS COLUMN, F-4  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

VACUUM FLASH, F-0  
 OVERHEAD NIU  
 BOTTOMS \_\_\_\_\_

PRECIPITATION TOWER, V-8  
 ZONE (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_

RECOVERY TOWER V-9  
 REBOILER NIU  
 OVERHEAD \_\_\_\_\_

SEPARATORS S-1 and S-2  
2460

SEPARATOR S-3  
250

SEPARATORS S-4A and S-4B  
61

VACUUM FLASH, F-1  
14 Torr

LIGHT ENDS COLUMN, F-2  
Atm

SOLVENT COLUMN, F-3  
NIU

HEAVY ENDS COLUMN, F-4  
NIU

VACUUM FLASH, F-0  
NIU


SETTLING TOWER, V-8  
NIU

RECOVERY TOWER, V-7  
NIU

Date of Run Time of Run Length of Run Hours on Coal at End of Y.P.	Start	End	Run No: L-2C
	8/31/77	9/1/77	Units: lbs/hr, °F, Psig
	1400	0200	Prep. By: BCL & GGB
	12	hrs.	Updated: 3/2/78
		92.3	

### MASS RATES AND RUN CONDITIONS

PRODUCT GAS TO THERMAL OXIDIZER	4.74
PRODUCT GAS TO RECYCLE	7.23



152.94 TOTAL

⊗ OPEN

⊗ CLOSED

TOTAL 152.94

Numbers in parentheses are not included in the totals.

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product Gas, Recycle Gas and F-1 Bottoms Rates Adjusted  
 Revised: 3/2/78

Run No: L-2C  
 Date: 8/31-9/1/77  
 Time: 1400-0200

SUMMARY  
 lbs/hr.

Temperature: 751°F  
 Pressure: 2460 psig  
 LHSV: 1.37  
 GHSV: 320

STREAM DESCRIPTION	Total In	Total Out	Net Yield	Wt % MAF Coal	
SAMPLE POINT					
Hydrogen - H <sub>2</sub>	1.03	1.15	0.12		
Carbon Monoxide - CO	10.57	5.44	-5.13		
Carbon Dioxide - CO <sub>2</sub>		12.03	12.03		
Hydrogen Sulfide - H <sub>2</sub> S		0.16	0.16		
Methane - CH <sub>4</sub>	2.35	4.43	2.08	10.79	38.29
Ethane - C <sub>2</sub> H <sub>6</sub>	0.71	1.56	0.85		
Propane - C <sub>3</sub> H <sub>8</sub>	0.35	1.01	0.66		
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.15	0.14	-0.01		
Ammonia - NH <sub>3</sub>		0.03	0.03		
Light Oil - (0-100°C @ 1.6 Torr)	9.26	18.99	9.73		
Solvent - (100-230°C @ 1.6 Torr)	78.18	73.07	-5.11	13.97	49.57
Heavy Oil - (230-255°C @ 1.6 Torr)	3.11	2.34	-0.77		
SRL		10.12	10.12		
Coal (MAF)	28.18	3.96	-24.22		-85.95
Ash	2.57	2.57	-0-		-0-
Water	16.48	15.94	-0.54		-1.91
Phenol					
TOTAL	152.94	152.94	-0-		

Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
TOTAL					

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product Gas, Recycle Gas and F-1 Btms Rates Adjusted  
 Revised: 3/2/78

Run No: L-2C  
 Date: 8/31-9/1/77  
 Time: 1400-0200

MATERIAL IN  
 lbs/hr.

Temperature: 751°F  
 Pressure: 2460 psig  
 LHSV: 1.37  
 GHSV: 320

STREAM DESCRIPTION	← Feed Gas →		Lignite	Feed Solvent	Total In
	Recycle Gas	Makeup Gas			
SAMPLE POINT	Sx-20	Sx-18	Sx-1	Sx-14	
Hydrogen - H <sub>2</sub>	0.65	0.38			1.03
Carbon Monoxide - CO	3.09	7.48			10.57
Carbon Dioxide - CO <sub>2</sub>					
Hydrogen Sulfide - H <sub>2</sub> S					
Methane - CH <sub>4</sub>	2.35				2.35
Ethane - C <sub>2</sub> H <sub>6</sub>	0.71				0.71
Propane - C <sub>3</sub> H <sub>8</sub>	0.35				0.35
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.08	0.07			0.15
Ammonia - NH <sub>3</sub>					
Light Oil - (0-100°C @ 1.6 Torr)				9.26	9.26
Solvent - (100-230°C @ 1.6 Torr)				78.18	78.18
Heavy Oil - (230-255°C @ 1.6 Torr)				3.11	3.11
SRL					
Cool (MAF)			28.18		28.18
Ash			2.57		2.57
Water			15.59	0.89	16.48
Phenol					
TOTAL	7.23	7.93	46.34	91.44	152.94

ELEMENTAL	Feed Gas		Lignite	Feed Solvent	Total In
	Recycle Gas	Makeup Gas			
Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
TOTAL					

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product Gas, Recycle Gas and F-1 Btms Rates Adjusted  
 Revised: 3/2/78

Run No: L-2C  
 Date: 8/31-9/1/77  
 Time: 1400-0200

MATERIAL OUT  
 lbs/hr.

Temperature: 751°F  
 Pressure: 2460 psig  
 LHSV: 1.37  
 GHSV: 320

STREAM DESCRIPTION	Product Gas			S-4A	S-4B	S-8
	Vent Gas	Recycle Gas	Absorbed Gas	Ovhd	Btms	Ovhd
SAMPLE POINT	Sx-20	Sx-20	Calc.	Sx-30	Sx-23	Sx-44
Hydrogen - H <sub>2</sub>	0.43	0.65		0.06		
Carbon Monoxide - CO	2.03	3.09		0.29		
Carbon Dioxide - CO <sub>2</sub>			9.08	2.64		
Hydrogen Sulfide - H <sub>2</sub> S			0.06	0.09		
Methane - CH <sub>4</sub>	1.54	2.35		0.48		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.46	0.71		0.35		
Propane - C <sub>3</sub> H <sub>8</sub>	0.23	0.35		0.39		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.05	0.08		0.01		
Ammonia - NH <sub>3</sub>				0.01	0.02	
Light Oil - (0-100°C @ 1.6 Torr)					3.17	
Solvent - (100-230°C @ 1.6 Torr)					1.76	
Heavy Oil - (230-255°C @1.6 Torr)					0.24	
SRL						
Cool (MAF)						
Ash						
Water					15.61	
Phenol						
TOTAL	4.74	7.23	9.14	4.32	20.80	Negl.

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product Gas, Recycle Gas and F-1 Btms Rates Adjusted  
 Revised: 3/2/78

Run No: L-2C  
 Date: 8/31-9/1/77  
 Time: 1400-0200

MATERIAL OUT  
 lbs/hr.

Temperature: 751°F  
 Pressure: 2460 psig  
 LHSV: 1.37  
 GHSV: 320

STREAM DESCRIPTION	S-8	J-1	Cold Trap	F-1	Recycle Solvent	
	Btms	Exhaust		Btms	S-7 Btms	F-2 Btms
SAMPLE POINT	Sx-16	*Sx-32	Sx-33	Sx-2	Sx-34	Sx-12
Hydrogen - H <sub>2</sub>		0.01				
Carbon Monoxide - CO		0.03				
Carbon Dioxide - CO <sub>2</sub>		0.31				
Hydrogen Sulfide - H <sub>2</sub> S		0.01				
Methane - CH <sub>4</sub>		0.06				
Ethane - C <sub>2</sub> H <sub>6</sub>		0.04				
Propane - C <sub>3</sub> H <sub>8</sub>		0.04				
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	1.99		0.07		9.26	4.50
Solvent - (100-230°C @ 1.6 Torr)	0.03		0.01	2.94	62.58	5.75
Heavy Oil - (230-255°C @ 1.6 Torr)					1.92	0.18
SRL				10.12		
Coal (MAF)				3.96		
Ash				2.57		
Water			0.12		0.21	
Phenol						
<b>TOTAL</b>	<b>2.02</b>	<b>0.50</b>	<b>0.20</b>	<b>19.59</b>	<b>73.97</b>	<b>10.43</b>

ELEMENTAL	Quantitative					
	S-8 Btms	J-1 Exhaust	Cold Trap	F-1 Btms	S-7 Btms	F-2 Btms
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
<b>TOTAL</b>						

\*Rate assumed similar to those of the other L-2 yield periods where the orifice meter was operating properly.

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product Gas, Recycle Gas and F-1 Btms Rates Adjusted  
 Revised: 3/2/78

Run No: L-2C  
 Date: 8/31-9/1/77  
 Time: 1400-0200

MATERIAL OUT  
 lbs/hr.

Temperature: 751°F  
 Pressure: 2460 psig  
 LHSV: 1.37  
 GHSV: 320

STREAM DESCRIPTION						Total Out
SAMPLE POINT						
Hydrogen - H <sub>2</sub>						1.15
Carbon Monoxide - CO						5.44
Carbon Dioxide - CO <sub>2</sub>						12.03
Hydrogen Sulfide - H <sub>2</sub> S						0.16
Methane - CH <sub>4</sub>						4.43
Ethane - C <sub>2</sub> H <sub>6</sub>						1.56
Propane - C <sub>3</sub> H <sub>8</sub>						1.01
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						0.14
Ammonia - NH <sub>3</sub>						0.03
Light Oil - (0-100°C @ 1.6 Torr)						18.99
Solvent - (100-230°C @ 1.6 Torr)						73.07
Heavy Oil - (230-255°C @1.6 Torr)						2.34
SRL						10.12
Cool (MAF)						3.96
Ash						2.57
Water						15.94
Phenol						
TOTAL						152.94

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/2/78

Run No: L-2C

Date: 8/31-9/1/77

Time: 1400-0200

WEIGHT PERCENT

SAMPLE DESCRIPTION	Lignite	F-1 Btms	LEC Btms	Feed Solvent	S-8 Oil	S-8 Water
	Sx-1	Sx-2	Sx-12	Sx-14	Sx-16	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100°C @ 1.6 Torr)			43.20	10.13	98.70	
Solvent - (100-230°C @ 1.6 Torr)		15.00	55.10	85.50	1.30	
Heavy Oil - (230-255°C @1.6 Torr)			1.70	3.40		
SRL		51.68				
Coal (MAF)	60.81	20.20				
Ash	5.55	13.12				
Water	33.64			0.97		100
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		76.75				
Melting Point °F		316				
Specific Gravity 60/60			1.006	1.062		
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/2/78

Run No: L-2C

Date: 8/31-9/1/77

Time: 1400-0200

WEIGHT PERCENT

SAMPLE DESCRIPTION	WEIGHT PERCENT					
	S-8 Total	Makeup Gas	Product Gas	Recycle Gas	Feed Gas	S-4B Oil
SAMPLE POINT	Sx-16	Sx-18	Sx-19	Sx-20	Sx-21	Sx-23
Hydrogen - H <sub>2</sub>		4.77	4.39	9.05	8.79	
Carbon Monoxide - CO		94.29	21.18	42.77	65.89	
Carbon Dioxide - CO <sub>2</sub>			45.73			
Hydrogen Sulfide - H <sub>2</sub> S			0.28			
Methane - CH <sub>4</sub>			18.12	32.45	14.53	
Ethane - C <sub>2</sub> H <sub>6</sub>			5.88	9.76	4.42	
Propane - C <sub>3</sub> H <sub>8</sub>			3.00	4.89	5.26	
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>		0.94	1.37	1.08	1.11	
Ammonia - NH <sub>3</sub> (PPM)			0.05			
Light Oils - (0-100° C @ 1.6 Torr)	98.70					61.05
Solvent - (100-230° C @ 1.6 Torr)	1.30					33.90
Heavy Oil - (230-255° C @ 1.6 Torr)						4.60
SRL						
Coal (MAF)						
Ash						
Water						0.45
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						0.966
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/2/78

Run No: L-2C  
Date: 8/31-9/1/77

Time: 1400-0200

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4B	S-4B	S-4A	J-1	Cold	S-4A
	Water	Total	Ovhd	Discharge	Trap	Oil
SAMPLE POINT	Sx-23	Sx-23	Sx-30	Sx-32	Sx-33	Sx-37
Hydrogen - H <sub>2</sub>			1.48	0.80		
Carbon Monoxide - CO			6.74	3.20		
Carbon Dioxide - CO <sub>2</sub>			61.12	67.83		
Hydrogen Sulfide - H <sub>2</sub> S			2.09			
Methane - CH <sub>4</sub>			11.21	9.13		
Ethane - C <sub>2</sub> H <sub>6</sub>			7.99	8.99		
Propane - C <sub>3</sub> H <sub>8</sub>			8.93	10.05		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>			0.25			
Ammonia - NH <sub>3</sub> (PPM)	0.11	0.08	0.19			
Light Oils - (0-100°C @ 1.6 Torr)		15.26			36.01	58.23
Solvent - (100-230°C @ 1.6 Torr)		8.48			6.10	41.30
Heavy Oil - (230-255°C @ 1.6 Torr)		1.15				
SRL						
Coal (MAF)						
Ash						
Water	99.89	75.03			57.89	0.47
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						0.956
Viscosity, cp						

Elemental	Carbon						
	Hydrogen						
	Nitrogen						
	Sulfur						
	Oxygen (by diff)						
	Ash						
	TOTAL						
	Number of Sample Avg.	2	2	2	2	1	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/2/78

Run No: L-2C

Date: 8/31-9/1/77

Time: 1400-0200

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4A	S-4A	S-7	Absorbed	WEIGHT PERCENT	
	Water	Total	Btms	Gas		
SAMPLE POINT	Sx-37	Sx-37	Sx-39	Calc.		
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>				99.29		
Hydrogen Sulfide - H <sub>2</sub> S				0.61		
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)	0.11	0.01		0.10		
Light Oils - (0-100°C @ 1.6 Torr)		54.45	12.51			
Solvent - (100-230°C @ 1.6 Torr)		38.62	84.60			
Heavy Oil - (230-255°C @1.6 Torr)			2.60			
SRL						
Coal (MAF)						
Ash						
Water	99.89	6.92	0.29			
Phenol						
TOTAL	100	100	100	100		
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2			-		

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/2/78

Run No: L-2C  
Date: 8/31-9/1/77  
Time: 1400-0200

MOLE PERCENT

SAMPLE DESCRIPTION	Makeup Gas	Product Gas	Recycle Gas	Feed Gas	MOLE PERCENT	
					S-4A Ovhd	J-1 Discharge
SAMPLE POINT	Sx-18	Sx-19	Sx-20	Sx-21	Sx-30	Sx-32
Hydrogen - H <sub>2</sub>	41.22	40.32	52.90	55.20	20.45	12.67
Carbon Monoxide - CO	58.20	13.88	17.85	29.55	6.65	3.62
Carbon Dioxide - CO <sub>2</sub>		19.07			38.35	48.87
Hydrogen Sulfide - H <sub>2</sub> S		0.15			1.70	
Methane - CH <sub>4</sub>		20.78	23.70	11.40	19.35	18.10
Ethane - C <sub>2</sub> H <sub>6</sub>		3.60	3.80	1.85	7.35	9.50
Propane - C <sub>3</sub> H <sub>8</sub>		1.25	1.30	1.50	5.60	7.24
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.58	0.90	0.45	0.50	0.25	
Ammonia - NH <sub>3</sub> (PPM)		0.05			0.30	
Light Oils - (0-100°C @ 1.6 Torr)						
Solvent - (100-230°C @ 1.6 Torr)						
Heavy Oil - (230-255°C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100	100	100
Calc Mole-Wt.	17.28	18.35	11.69	12.56	27.61	31.70
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	TOTAL					
	Number of Sample Avg.	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/2/78

Run No: L-2C

Date: 8/31-9/1/77

Time: 1400-0200

MOLE PERCENT

SAMPLE DESCRIPTION	Absorbed Gas					
	Calc.					
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>	98.96					
Hydrogen Sulfide - H <sub>2</sub> S	0.78					
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)	0.26					
Light Oils - (0-100° C @ 1.6 Torr)						
Solvent - (100-230° C @ 1.6 Torr)						
Heavy Oil - (230-255° C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100					
Calc. Mole Wt.	43.85					
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Quantitative

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	-					

Elemental

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: L-2C  
DATE: 8/31-9/1/77  
TIME: 1400-0200

SAMPLE DESCRIPTION	LEC Btms	Feed Solv.	S-8 Oil	S-4B Oil	Cold Trap
SAMPLE POINT	Sx-12	Sx-14	Sx-16	Sx-23	Sx-33
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR	5	5			
IBP	72.4	36.4			
5%	82.6	102			
10%	85.6	117.2			
20%	93.2	153.2			
30%	103.6	173.4			
40%	116	181			
50%	130	186.3			
60%	151.6	191.8			
70%	169.4	199			
80%	179.8	209.6			
90%	190.6	231.6			
95%	204.8	260			
DRY PT.	214.8				
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR			732	741	742
IBP			57	76	79
5%			65	115	82
10%			69	162	87
20%			78	194	94
30%			88	208	99
40%			97	223	102
50%			107	246	110
60%			117	270	111
70%			126	297	114
80%			140	334	117
90%			161	349	
95%					
DRY PT.			169	350	117
ASPHALTENE TEST					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
SAYBOLT VISCOSITY, SSU					
100° F					
210° F					
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)		0.97		0.45	57.89
INFRARED RATIO					
SP. GRAV. 60/60 F	1.006	1.062		0.966	

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES - BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES - N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: L-2C  
DATE: 8/31-9/1/77  
TIME: 1400-0200

SAMPLE DESCRIPTION	S-4A Oil	S-7 Btms			
SAMPLE POINT	Sx-37	Sx-39			
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR		5			
IBP		64.6			
5%		91			
10%		110.6			
20%		144.5			
30%		166			
40%		176.3			
50%		181			
60%		185			
70%		192			
80%		202			
90%		223			
95%		256			
DRY PT.		256			
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR		736			
IBP		77			
5%		97			
10%		158			
20%		197			
30%		213			
40%		232			
50%		254			
60%		276			
70%		314			
80%		340			
90%		363			
95%					
DRY PT.		368			
ASPHALTENE TEST					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
SAYBOLT VISCOSITY, SSU					
100° F					
210° F					
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)		0.47	0.29		
INFRARED RATIO					
SP. GRAV. 60/60 F		0.961			

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 3/2/78

Run No: L-2C  
Date: 8/31-9/1/77  
Time: 1400-0200

MATERIAL IN

Temperature: 751°F  
Pressure: 2460 psig  
LHSV: 1.37  
GHSV: 320

lbs/hr.

STREAM DESCRIPTION	← Feed Gas →		Lignite	Feed Solvent	Total In
	Recycle Gas	Makeup Gas			
SAMPLE POINT	Sx-20	Sx-18	Sx-1	Sx-14	
Hydrogen - H <sub>2</sub>	0.57	0.43			1.00
Carbon Monoxide - CO	2.68	8.37			11.05
Carbon Dioxide - CO <sub>2</sub>					
Hydrogen Sulfide - H <sub>2</sub> S					
Methane - CH <sub>4</sub>	2.04				2.04
Ethane - C <sub>2</sub> H <sub>6</sub>	0.61				0.61
Propane - C <sub>3</sub> H <sub>8</sub>	0.31				0.31
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.07	0.08			0.15
Ammonia - NH <sub>3</sub>					
Light Oil - (0-100°C @ 1.6 Torr)				9.26	9.26
Solvent - (100-230°C @ 1.6 Torr)				78.18	78.18
Heavy Oil - (230-255°C @ 1.6 Torr)				3.11	3.11
SRL					
Coal (MAF)			28.18		28.18
Ash			2.57		2.57
Water			15.59	0.89	16.48
Phenol					
<b>TOTAL</b>	<b>6.28</b>	<b>8.88</b>	<b>46.34</b>	<b>91.44</b>	<b>152.94</b>

Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
<b>TOTAL</b>					

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 3/2/78

MATERIAL OUT

Run No: L-2C  
Date: 8/31-9/1/77  
Time: 1400-0200

Temperature: 751°F  
Pressure: 2460 psig  
LHSV: 1.37  
GHSV: 320

lbs/hr.

Quantitative	STREAM DESCRIPTION	Product Gas			S-4A Ovhd	S-4B Btms	S-8 Ovhd
		Vent Gas	Recycle Gas	Absorbed Gas			
	SAMPLE POINT	Sx-20	Sx-20	Calc	Sx-30	Sx-23	Sx-44
	Hydrogen - H <sub>2</sub>	0.31	0.57		0.06		
	Carbon Monoxide - CO	1.48	2.68		0.29		
	Carbon Dioxide - CO <sub>2</sub>			9.15	2.64		
	Hydrogen Sulfide - H <sub>2</sub> S			0.06	0.09		
	Methane - CH <sub>4</sub>	1.13	2.04		0.48		
	Ethane - C <sub>2</sub> H <sub>6</sub>	0.34	0.61		0.35		
	Propane - C <sub>3</sub> H <sub>8</sub>	0.17	0.31		0.39		
	Butane - C <sub>4</sub> H <sub>10</sub>						
	Nitrogen - N <sub>2</sub>	0.04	0.07		0.01		
	Ammonia - NH <sub>3</sub>			0.01	0.01	0.02	
	Light Oil - (0-100°C @ 1.6 Torr)					3.17	
	Solvent - (100-230°C @ 1.6 Torr)					1.76	
	Heavy Oil - (230-255°C @1.6 Torr)					0.24	
	SRL						
	Cool (MAF)						
	Ash						
	Water					15.61	
	Phenol						
	<b>TOTAL</b>	<b>3.47</b>	<b>6.28</b>	<b>9.22</b>	<b>4.32</b>	<b>20.80</b>	<b>Negl.</b>

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	<b>TOTAL</b>					

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 3/2/78

Run No: L-2C  
Date: 8/31-9/1/77  
Time: 1400-0200

MATERIAL OUT

Temperature: 751°F  
Pressure: 2460 psig  
LHSV: 1.37  
GHSV: 320

lbs/hr.

STREAM DESCRIPTION	S-8	J-1	Cold	F-1	Recycle Solvent	
	Btms	Exhaust	Trap	Btms	S-7 Btms	F-2 Rtms
SAMPLE POINT	Sx-16	Sx-32	Sx-33	Sx-2	Sx-34	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	1.99		0.07		9.26	4.50
Solvent - (100-230°C @ 1.6 Torr)	0.03		0.01	3.04	62.58	5.75
Heavy Oil - (230-255°C @1.6 Torr)					1.92	0.18
SRL				10.49		
Cool (MAF)				4.10		
Ash				2.66		
Water			0.12		0.21	
Phenol						
<b>TOTAL</b>	<b>2.02</b>	<b>NA</b>	<b>0.20</b>	<b>20.29</b>	<b>73.97</b>	<b>10.43</b>

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
<b>TOTAL</b>						

NA - Not Available

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 3/2/78

Run No: L-2C  
Date: 8/31-9/1/77  
Time: 1400-0200

MATERIAL OUT  
  
lbs/hour

Temperature: 751°F  
Pressure: 2460 psig  
LHSV: 1.37  
GHSV: 320

STREAM DESCRIPTION						Total Out
SAMPLE POINT						
Hydrogen - H <sub>2</sub>						0.94
Carbon Monoxide - CO						4.45
Carbon Dioxide - CO <sub>2</sub>						11.79
Hydrogen Sulfide - H <sub>2</sub> S						0.15
Methane - CH <sub>4</sub>						3.65
Ethane - C <sub>2</sub> H <sub>6</sub>						1.30
Propane - C <sub>3</sub> H <sub>8</sub>						0.87
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						0.12
Ammonia - NH <sub>3</sub>						0.04
Light Oil - (0-100°C @ 1.6 Torr)						18.99
Solvent - (100-230°C @ 1.6 Torr)						73.17
Heavy Oil - (230-255°C @1.6 Torr)						2.34
SRL						10.49
Coal (MAF)						4.10
Ash						2.66
Water						15.94
Phenol						
TOTAL						151.00

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

RUN CONDITIONS

RUN NO. L-2D  
 DATE MADE 9/3/77

TEMPERATURE °F

PRESSURE, psig

PREHEATER E-I  
 SAND BATH 770  
 INLET 295  
 OUTLET 747

DISSOLVERS  
 R-1A (1) 752  
 (2) 809  
 (3) 793  
 (4) 808  
 R-1B (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_  
 (4) \_\_\_\_\_

REACTOR PRODUCT SEPARATORS  
 S-1 615  
 S-2 79  
 S-3 501  
 S-4A 80  
 S-4B 74

PREHEATER E-II  
 DOWTHERM 682  
 INLET 418  
 OUTLET 644

VACUUM FLASH F-1  
 OVERHEAD VAPOR 503  
 UPPER WALL 607  
 LOWER WALL 571  
 DOWNCOMER 569  
 CONDENSATE  
 ACCUMULATOR, S-7 80

PREHEATER E-13  
 DOWTHERM 398  
 INLET 77  
 OUTLET 160

LIGHT ENDS COLUMN, F-2  
 REBOILER 323  
 LOWER SECTION 214  
 FEED SECTION 212  
 OVERHEAD 179  
 S-8 75  
 S-9 -

SOLVENT COLUMN, F-3  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

HEAVY ENDS COLUMN, F-4  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

VACUUM FLASH, F-0  
 OVERHEAD NIU  
 BOTTOMS \_\_\_\_\_

PRECIPITATION TOWER, V-8  
 ZONE (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_

RECOVERY TOWER V-9  
 REBOILER NIU  
 OVERHEAD \_\_\_\_\_

SEPARATORS S-1 and S-2  
2450

SEPARATOR S-3  
250

SEPARATORS S-4A and S-4B  
60

VACUUM FLASH, F-1  
15 Torr

LIGHT ENDS COLUMN, F-2  
Atm

SOLVENT COLUMN, F-3  
NIU

HEAVY ENDS COLUMN, F-4  
NIU

VACUUM FLASH, F-0  
NIU

SETTLING TOWER, V-8  
NIU

RECOVERY TOWER, V-7  
NIU



PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Product Gas, Recycle Gas and F-1 Btms Rate Adjusted followed by a Forced Carbon Balance  
Revised: 2/28/78

Run No: L-2D  
Date: 9/3/77  
Time: 1000-2200

SUMMARY

Temperature: 747°F  
Pressure: 2450 psig  
LHSV: 1.38  
GHSV: 320

STREAM DESCRIPTION	Total In	Total Out	Net Yield		Wt % MAF Coal
SAMPLE POINT					
Hydrogen - H <sub>2</sub>	1.62	1.08	-0.54		
Carbon Monoxide - CO	11.00	5.77	-5.23		
Carbon Dioxide - CO <sub>2</sub>		10.91	10.91		
Hydrogen Sulfide - H <sub>2</sub> S		0.21	0.21		
Methane - CH <sub>4</sub>	1.35	2.10	0.75	6.79	23.60
Ethane - C <sub>2</sub> H <sub>6</sub>	0.52	0.95	0.43		
Propane - C <sub>3</sub> H <sub>8</sub>	0.14	0.43	0.29		
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.23	0.17	-0.06		
Ammonia - NH <sub>3</sub>		0.03	0.03		
Light Oil - (0-100°C @ 1.6 Torr)	23.51	28.90	5.39		
Solvent - (100-230°C @ 1.6 Torr)	64.49	59.72	-4.77	16.87	58.64
Heavy Oil - (230-255°C @ 1.6 Torr)	2.45	1.81	-0.64		
SRL		16.89	16.89		
Coal (MAF)	28.77	4.92	-23.85		-82.90
Ash	2.69	2.65	-0.04		-0.14
Water	16.05	16.28	0.23		0.80
Phenol					
<b>TOTAL</b>	<b>152.82</b>	<b>152.82</b>	<b>-0-</b>		

ELEMENTAL	Total In	Total Out	Net Yield		
Carbon	106.56	106.56	-0-		
Hydrogen	12.03	11.98	-0.05		
Nitrogen	0.73	0.70	-0.03		
Sulfur	1.26	1.41	0.15		
Oxygen (by diff)	29.55	29.52	-0.03		
Ash	2.69	2.65	-0.04		
<b>TOTAL</b>	<b>152.82</b>	<b>152.82</b>	<b>-0-</b>		

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Product Gas, Recycle Gas and F-1 Btms Rate Adjusted followed by a Forced Carbon Balance

Revised: 2/28/78

Run No: L-2D  
Date: 9/3/77  
Time: 1000-2200

MATERIAL IN

Temperature: 747°F  
Pressure: 2450 psig  
LHSV: 1.38  
GHSV: 320

STREAM DESCRIPTION	← Feed Gas →		Lignite	Feed Solvent	Total In
	Recycle Gas	Makeup Gas			
SAMPLE POINT	Sx-20	Sx-18	Sx-1	Sx-14	
Hydrogen - H <sub>2</sub>	0.76	0.86			1.62
Carbon Monoxide - CO	4.02	6.98			11.00
Carbon Dioxide - CO <sub>2</sub>					
Hydrogen Sulfide - H <sub>2</sub> S					
Methane - CH <sub>4</sub>	1.35				1.35
Ethane - C <sub>2</sub> H <sub>6</sub>	0.52				0.52
Propane - C <sub>3</sub> H <sub>8</sub>	0.14				0.14
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.12	0.11			0.23
Ammonia - NH <sub>3</sub>					
Light Oil - (0-100°C @ 1.6 Torr)				23.51	23.51
Solvent - (100-230°C @ 1.6 Torr)				64.49	64.49
Heavy Oil - (230-255°C @ 1.6 Torr)				2.45	2.45
SRL					
Cool (MAF)			28.77		28.77
Ash			2.69		2.69
Water			15.80	0.25	16.05
Phenol					
<b>TOTAL</b>	<b>6.91</b>	<b>7.95</b>	<b>47.26</b>	<b>90.70</b>	<b>152.82</b>

Carbon	3.26	2.99	20.76	79.55	106.56
Hydrogen	1.23	0.86	3.06	6.88	12.03
Nitrogen	0.12	0.11	0.26	0.24	0.73
Sulfur			0.25	1.01	1.26
Oxygen (by diff)	2.30	3.99	20.24	3.02	29.55
Ash			2.69		2.69
<b>TOTAL</b>	<b>6.91</b>	<b>7.95</b>	<b>47.26</b>	<b>90.70</b>	<b>152.82</b>

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Product Gas, Recycle Gas and F-1 Btms Rate Adjusted followed by a Forced Carbon Balance  
Revised: 2/28/78

Run No: L-2D  
Date: 9/3/77  
Time: 1000-2200

MATERIAL OUT  
lbs/hr.

Temperature: 747°F  
Pressure: 2450 psig  
LHSV: 1.38  
GHSV: 320

STREAM DESCRIPTION	Product Gas			S-4A	S-4B	S-8
	Vent Gas	Recycle Gas	Absorbed Gas	Ovhd	Btms	Ovhd
SAMPLE POINT	Sx-20	Sx-20	Calc.	Sx-30	Calc.	Sx-44
Hydrogen - H <sub>2</sub>	0.25	0.76		0.07		
Carbon Monoxide - CO	1.30	4.02		0.40		
Carbon Dioxide - CO <sub>2</sub>			8.24	2.30		
Hydrogen Sulfide - H <sub>2</sub> S			0.12	0.09		
Methane - CH <sub>4</sub>	0.44	1.35		0.28		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.17	0.52		0.24		
Propane - C <sub>3</sub> H <sub>8</sub>	0.04	0.14		0.22		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.04	0.12		0.01		
Ammonia - NH <sub>3</sub>				0.01	0.02	
Light Oil - (0-100°C @ 1.6 Torr)					0.44	
Solvent - (100-230°C @ 1.6 Torr)					0.21	
Heavy Oil - (230-255°C @1.6 Torr)					0.02	
SRL						
Coal (MAF)						
Ash						
Water					14.27	
Phenol						
TOTAL	2.24	6.91	8.36	3.62	14.96	Negl.

Carbon	1.06	3.26	2.25	1.38	0.56	
Hydrogen	0.40	1.23	0.01	0.24	1.65	
Nitrogen	0.04	0.12		0.01	0.02	
Sulfur			0.11	0.08		
Oxygen (by diff)	0.74	2.30	5.99	1.91	12.73	
Ash						
TOTAL	2.24	6.91	8.36	3.62	14.96	Negl.

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Product Gas, Recycle Gas and F-1 Btms Rates Adjusted followed by a Forced Carbon Balance  
Revised: 2/28/77

Run No: L-2D  
Date: 9/3/77  
Time: 1000-2200

MATERIAL OUT  
lbs/hr.

Temperature: 747°F  
Pressure: 2450 psig  
LHSV: 1.38  
GHSV: 320

STREAM DESCRIPTION	S-8	J-1	Cold	F-1	← Recycle	→ Solvent
	Btms	Exhaust	Trap	Btms	S-7 Btms	LEC Btms
SAMPLE POINT	Sx-16	*Sx-32	Sx-33	Sx-2	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO		0.05				
Carbon Dioxide - CO <sub>2</sub>		0.37				
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>		0.03				
Ethane - C <sub>2</sub> H <sub>6</sub>		0.02				
Propane - C <sub>3</sub> H <sub>8</sub>		0.03				
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	4.78		0.07		12.83	10.78
Solvent - (100-230°C @ 1.6 Torr)	0.81		0.03		52.01	6.66
Heavy Oil - (230-255°C @ 1.6 Torr)	0.20				1.27	0.32
SRL				16.89		
Cool (MAF)				4.92		
Ash				2.65		
Water	1.42		0.10		0.49	
Phenol						
TOTAL	7.21	0.50	0.20	24.46	66.60	17.76
Carbon	4.81	0.18	0.09	19.25	58.61	15.11
Hydrogen	0.74	0.02	0.02	1.15	5.02	1.50
Nitrogen	0.01			0.25	0.20	0.05
Sulfur	0.02			0.21	0.87	0.12
Oxygen (by diff)	1.63	0.30	0.09	0.95	1.90	0.98
Ash				2.65		
TOTAL	7.21	0.50	0.20	24.46	66.60	17.76

\* Rate assumed similar to those of the other L-2 yield periods where the orifice meter was operating properly.

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Product Gas, Recycle Gas and F-1 Btms Rate Adjusted followed by a Forced Carbon Balance  
Revised: 2/28/77

Run No: L-2D  
Date: 9/3/77  
Time: 1000-2200

MATERIAL OUT  
lbs/hr.

Temperature: 747°F  
Pressure: 2450 psig  
LHSV: 1.38  
GHSV: 320

STREAM DESCRIPTION						Total Out
SAMPLE POINT						
Hydrogen - H <sub>2</sub>						1.08
Carbon Monoxide - CO						5.77
Carbon Dioxide - CO <sub>2</sub>						10.91
Hydrogen Sulfide - H <sub>2</sub> S						0.21
Methane - CH <sub>4</sub>						2.10
Ethane - C <sub>2</sub> H <sub>6</sub>						0.95
Propane - C <sub>3</sub> H <sub>8</sub>						0.43
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						0.17
Ammonia - NH <sub>3</sub>						0.03
Light Oil - (0-100°C @ 1.6 Torr)						28.90
Solvent - (100-230°C @ 1.6 Torr)						59.72
Heavy Oil - (230-255°C @1.6 Torr)						1.81
SRL						16.89
Cool (MAF)						4.92
Ash						2.65
Water						16.28
Phenol						
TOTAL						152.82

Carbon						106.56
Hydrogen						11.98
Nitrogen						0.70
Sulfur						1.41
Oxygen (by diff)						29.52
Ash						2.65
TOTAL						152.82

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/28/78

Run No: L-2D

Date: 9/3/77

Time: 1000-2200

WEIGHT PERCENT

SAMPLE DESCRIPTION	Lignite	F-1 Btms	LEC Btms	Feed Solvent	S-8 Oil	S-8 Water
	Sx-1	Sx-2	Sx-12	Sx-14	Sx-16	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100° C @ 1.6 Torr)			60.70	25.92	82.50	
Solvent - (100-230° C @ 1.6 Torr)			37.50	71.10	14.00	
Heavy Oil - (230-255° C @1.6 Torr)			1.80	2.70	3.50	
SRL		69.06				
Coal (MAF)	60.88	20.11				
Ash	5.70	10.83				
Water	33.42			0.28		100
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		77.45				
Melting Point °F		440				
Specific Gravity 60/60			1.010	1.054		
Viscosity, cp						

Elemental	Quantitative					
	Lignite	F-1 Btms	LEC Btms	Feed Solvent	S-8 Oil	S-8 Water
Carbon	43.92	78.69	85.08	87.71	83.02	
Hydrogen	6.47	4.72	8.45	7.58	10.01	11.11
Nitrogen	0.56	1.00	0.27	0.27	0.21	
Sulfur	0.52	0.86	0.70	1.11	0.40	
Oxygen (by diff)	42.83	3.90	5.50	3.33	6.36	88.89
Ash	5.70	10.83				
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	4	2	2	2	-

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/28/78

Run No: L-2D

Date: 9/3/77

Time: 1000-2200

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-8	Makeup	Product	Recycle	Feed	S-4B
	Total	Gas	Gas	Gas	Gas	Oil
SAMPLE POINT	Sx-16	Sx-18	Sx-19	Sx-20	Sx-21	*Sx-23
Hydrogen - H <sub>2</sub>		10.80	6.08	11.01	9.31	
Carbon Monoxide - CO		87.76	34.53	58.24	75.94	
Carbon Dioxide - CO <sub>2</sub>			42.52			
Hydrogen Sulfide - H <sub>2</sub> S			0.62			
Methane - CH <sub>4</sub>			10.02	19.50	8.95	
Ethane - C <sub>2</sub> H <sub>6</sub>			3.92	7.56	3.53	
Propane - C <sub>3</sub> H <sub>8</sub>			1.61	2.02	1.25	
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>		1.44	0.68	1.67	1.02	
Ammonia - NH <sub>3</sub> (PPM)			0.02			
Light Oils - (0-100°C @ 1.6 Torr)	66.21					64.64
Solvent - (100-230°C @ 1.6 Torr)	11.24					31.20
Heavy Oil - (230-255°C @1.6 Torr)	2.81					3.10
SRL						
Coal (MAF)						
Ash						
Water	19.74					1.06
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						0.988
Viscosity, cp						

Carbon	66.63	37.61	38.38	47.28	43.10	82.11
Hydrogen	10.22	10.80	9.69	17.77	12.49	8.69
Nitrogen	0.17	1.44	0.70	1.67	1.02	0.33
Sulfur	0.32		0.58			0.77
Oxygen (by diff)	22.66	50.15	50.65	33.28	43.39	8.10
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	2

\*Insufficient oil sample-distillation data assumed to be the same as the S-4A Oil.

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/28/78

Run No: L-2D

Date: 9/3/77

Time: 1000-2200

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4B	S-4B	S-4A	J-1	Cold	S-7
	Water	Total	Ovhd	Discharge	Trap	Btms
SAMPLE POINT	Sx-23	Sx-23	Sx-30	Sx-32	Sx-33	Sx-34/39
Hydrogen - H <sub>2</sub>			2.07	0.81		
Carbon Monoxide - CO			11.14	10.07		
Carbon Dioxide - CO <sub>2</sub>			63.64	74.13		
Hydrogen Sulfide - H <sub>2</sub> S			2.46			
Methane - CH <sub>4</sub>			7.64	5.01		
Ethane - C <sub>2</sub> H <sub>6</sub>			6.74	4.71		
Propane - C <sub>3</sub> H <sub>8</sub>			5.94	5.27		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>			0.21			
Ammonia - NH <sub>3</sub> (PPM)	0.13	0.12	0.16			
Light Oils - (0-100°C @ 1.6 Torr)		6.20			34.03	19.26
Solvent - (100-230°C @ 1.6 Torr)		3.00			16.40	78.10
Heavy Oil - (230-255°C @ 1.5 Torr)		0.30				1.90
SRL						
Coal (MAF)						
Ash						
Water	99.87	90.38			49.57	0.74
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						1.059
Viscosity, cp						

Carbon		7.88	38.11	36.38	44.31	88.00
Hydrogen	11.12	10.89	6.58	3.96	9.81	7.54
Nitrogen	0.11	0.13	0.34		0.10	0.30
Sulfur		0.07	2.32		0.32	1.30
Oxygen (by diff)	88.77	81.03	52.65	59.66	45.46	2.86
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	1	4

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/28/78

Run No: L-2D

Date: 9/3/77

Time: 1000-2200

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4A	S-4A	S-4A	S-7	Absorbed	S-4B
	Oil	Water	Total	Btms	Gas	Btms
SAMPLE POINT	Sx-37	Sx-37	Sx-37	Sx-34/39	Calc	Calc.
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>					98.52	
Hydrogen Sulfide - H <sub>2</sub> S					1.44	
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)		0.08	0.02		0.04	0.12
Light Oils - (0-100°C @ 1.6 Torr)	64.64		49.42	19.26		2.94
Solvent - (100-230°C @ 1.6 Torr)	31.20		23.86	78.10		1.42
Heavy Oil - (230-255°C @1.6 Torr)	3.10		2.37	1.90		0.14
SRL						
Coal (MAF)						
Ash						
Water	1.06	99.92	24.33	0.74		95.38
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60	0.984			1.059		
Viscosity, cp						

Carbon	82.40		63.00	88.00	26.87	3.74
Hydrogen	8.39	11.11	9.03	7.54	0.09	11.01
Nitrogen	0.28	0.07	0.23	0.30	0.03	0.12
Sulfur	0.55		0.42	1.30	1.36	0.03
Oxygen (by diff)	8.38	88.82	27.32	2.86	71.65	85.10
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	4	-	-

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/28/78

Run No: L-2D

Date: 9/3/77

Time: 1000-2200

MOLE PERCENT

SAMPLE DESCRIPTION	MOLE PERCENT					
	Makeup Gas	Product Gas	Recycle Gas	Feed Gas	S-4A Ovhd	J-1 Exhaust
SAMPLE POINT	Sx-18	Sx-19	Sx-20	Sx-21	Sx-30	Sx-32
Hydrogen - H <sub>2</sub>	62.90	50.04	60.10	57.40	27.20	13.30
Carbon Monoxide - CO	36.50	20.29	22.70	33.45	10.45	11.83
Carbon Dioxide - CO <sub>2</sub>		15.90			38.00	55.45
Hydrogen Sulfide - H <sub>2</sub> S		0.30			1.90	
Methane - CH <sub>4</sub>		10.30	13.30	6.90	12.55	10.31
Ethane - C <sub>2</sub> H <sub>6</sub>		2.15	2.75	1.45	5.90	5.17
Propane - C <sub>3</sub> H <sub>8</sub>		0.60	0.50	0.35	3.55	3.94
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.60	0.40	0.65	0.45	0.20	
Ammonia - NH <sub>3</sub> (PPM)		0.02			0.25	
Light Oils - (0-100° C @ 1.6 Torr)						
Solvent - (100-230° C @ 1.6 Torr)						
Heavy Oil - (230-255° C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100	100	100
Calc Mole Wt	11.65	16.45	10.91	12.33	26.27	32.91
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/28/78

Run No: L-2D

Date: 9/3/77

Time: 1000-2200

MOLE PERCENT

Quantitative	SAMPLE DESCRIPTION	Absorbed Gas				
	SAMPLE POINT	Calc				
	Hydrogen - H <sub>2</sub>					
	Carbon Monoxide - CO					
	Carbon Dioxide - CO <sub>2</sub>	98.03				
	Hydrogen Sulfide - H <sub>2</sub> S	1.85				
	Methane - CH <sub>4</sub>					
	Ethane - C <sub>2</sub> H <sub>6</sub>					
	Propane - C <sub>3</sub> H <sub>8</sub>					
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					
	Ammonia - NH <sub>3</sub> (PPM)	0.12				
	Light Oils - (0-100°C @ 1.6 Torr)					
	Solvent - (100-230°C @ 1.6 Torr)					
	Heavy Oil - (230-255°C @ 1.6 Torr)					
	SRL					
	Coal (MAF)					
	Ash					
	Water					
	Phenol					
TOTAL	100					
Calc. Mole Wt.	43.78					
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	TOTAL					
	Number of Sample Avg.	-				

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: L-2D  
DATE: 9/3/77  
TIME: 1000-2200

SAMPLE DESCRIPTION	F-1 Btms	LEC Btms	Feed Solv.	S-8 Oil	S-7 Btms
SAMPLE POINT	Sx-2	Sx-12	Sx-14	Sx-16	Sx-34/39
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR		5	5		5
IBP		28.6	54.4		68.6
5%		67.2	79		83
10%		72.3	87.8		92.6
20%		79.3	106.5		118.1
30%		85.8	131		147.2
40%		93.8	157		166.2
50%		104	170.5		174.6
60%		118.4	177.3		180.4
70%		143.2	184.2		185.5
80%		165.8	193.2		192.6
90%		180.2	211.8		212
95%		192.2	237.5		248.4
DRY PT.		197.2	245.7		255.4
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR				752	
IBP				62	
5%				68	
10%				85	
20%				112	
30%				140	
40%				171	
50%				191	
60%				210	
70%				235	
80%				266	
90%				344	
95%				347	
DRY PT.					
ASPHALTENE TEST					
WT % ASH	10.83				
WT % UNCONVERTED COAL	20.11				
WT % PRE-ASPHALTENES	37.25				
WT % ASPHALTENES	15.05				
WT % MALTENES & DIST. OIL	16.76				
TOTAL	100.00				
SAYBOLT VISCOSITY, SSU					
100° F		9.7	11.7		12.8
210° F		8.2	8.5		8.5
MISCELLANEOUS					
KF H <sub>2</sub> O WT % (Raw Sx)			0.28		0.74
INFRARED RATIO		0.32	0.38		0.37
SP. GRAV. 60/60 F		1.010	1.054		1.059

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES - BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES - N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.

PROJECT LIGNITE  
 SAMPLE ANALYSES  
 RUN NO: L-2D  
 DATE: 9/3/77  
 TIME: 1000-2200

SAMPLE DESCRIPTION	S-4A 011				
SAMPLE POINT	Sx-37				
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR					
IBP					
5%					
10%					
20%					
30%					
40%					
50%					
60%					
70%					
80%					
90%					
95%					
DRY PT.					
	TEMPERATURE, °C				
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR	738				
IBP	89				
5%	161				
10%	188				
20%	201				
30%	209				
40%	221				
50%	238				
60%	261				
70%	295				
80%	336				
90%	355				
95%					
DRY PT.	357				
	TEMPERATURE, °C				
ASPHALTENE TEST					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
SAYBOLT VISCOSITY, SSU					
100° F					
210° F					
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)	1.06				
INFRARED RATIO					
SP. GRAV. 60/60 F	0.984				

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
 ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
 MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
 DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 2/28/78

Run No: L-2D  
Date: 9/3/77  
Time: 1000-2200

MATERIAL OUT

Temperature: 747°F  
Pressure: 2450 psig  
LHSV: 1.38  
GHSV: 320

lbs/hr.

STREAM DESCRIPTION	← Feed Gas →		Lignite	Feed Solvent	Total In
	Recycle Gas	Makeup Gas			
SAMPLE POINT	Sx-20	Sx-18	Sx-1	Sx-14	
Hydrogen - H <sub>2</sub>	0.65	0.97			1.62
Carbon Monoxide - CO	3.44	7.86			11.30
Carbon Dioxide - CO <sub>2</sub>					
Hydrogen Sulfide - H <sub>2</sub> S					
Methane - CH <sub>4</sub>	1.15				1.15
Ethane - C <sub>2</sub> H <sub>6</sub>	0.44				0.44
Propane - C <sub>3</sub> H <sub>8</sub>	0.12				0.12
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.10	0.13			0.23
Ammonia - NH <sub>3</sub>					
Light Oil - (0-100°C @ 1.6 Torr)				23.51	23.51
Solvent - (100-230°C @ 1.6 Torr)				64.49	64.49
Heavy Oil - (230-255°C @ 1.6 Torr)				2.45	2.45
SRL					
Coal (MAF)			28.77		28.77
Ash			2.69		2.69
Water			15.80	0.25	16.05
Phenol					
<b>TOTAL</b>	<b>5.90</b>	<b>8.96</b>	<b>47.26</b>	<b>90.70</b>	<b>152.82</b>

Carbon	2.79	3.37	20.76	79.55	106.47
Hydrogen	1.05	0.97	3.06	6.88	11.96
Nitrogen	0.10	0.13	0.26	0.24	0.73
Sulfur			0.25	1.01	1.26
Oxygen (by diff)	1.96	4.49	20.24	3.02	29.71
Ash			2.69		2.69
<b>TOTAL</b>	<b>5.90</b>	<b>8.96</b>	<b>47.26</b>	<b>90.70</b>	<b>152.82</b>

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 2/28/78

Run No: L-2D  
Date: 9/3/77  
Time: 1000-2200

MATERIAL OUT

Temperature: 747°F  
Pressure: 2450 psig  
LHSV: 1.38  
GHSV: 320

STREAM DESCRIPTION	← Product Gas →			S-4A	S-4B	S-8
	Vent Gas	Recycle Gas	Absorbed Gas	Ovhd	Btms	Ovhd
SAMPLE POINT	Sx-20	Sx-20	Calc	Sx-30	Sx-23	Sx-44
Hydrogen - H <sub>2</sub>	0.40	0.65		0.07		
Carbon Monoxide - CO	2.14	3.44		0.40		
Carbon Dioxide - CO <sub>2</sub>			7.54	2.30		
Hydrogen Sulfide - H <sub>2</sub> S			0.11	0.09		
Methane - CH <sub>4</sub>	0.72	1.15		0.28		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.28	0.44		0.24		
Propane - C <sub>3</sub> H <sub>8</sub>	0.07	0.12		0.22		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.06	0.10		0.01		
Ammonia - NH <sub>3</sub>				0.01	0.02	
Light Oil - (0-100°C @ 1.6 Torr)					0.93	
Solvent - (100-230°C @ 1.6 Torr)					0.45	
Heavy Oil - (230-255°C @1.6 Torr)					0.04	
SRL						
Coal (MAF)						
Ash						
Water					13.52	
Phenol						
<b>TOTAL</b>	<b>3.67</b>	<b>5.90</b>	<b>7.65</b>	<b>3.62</b>	<b>14.96</b>	<b>Negl.</b>

Carbon	1.74	2.79	2.06	1.38	1.18	
Hydrogen	0.65	1.05	0.01	0.24	1.63	
Nitrogen	0.06	0.10		0.01	0.02	
Sulfur			0.10	0.08	0.01	
Oxygen (by diff)	1.22	1.96	5.48	1.91	12.12	
Ash						
<b>TOTAL</b>	<b>3.67</b>	<b>5.90</b>	<b>7.65</b>	<b>3.62</b>	<b>14.96</b>	<b>Negl.</b>

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 2/28/78

Run No: L-2D  
Date: 9/3/77  
Time: 1000-2200

MATERIAL OUT

Temperature: 747°F  
Pressure: 2450 psig  
LHSV: 1.38  
GHSV: 320

lbs/hr.

STREAM DESCRIPTION	S-8	J-1	Cold	F-1	← Recycle	→ Solvent
	Btms	Exhaust	Trap	Btms	S-7 Btms	LEC Btms
SAMPLE POINT	Sx-16	Sx-32	Sx-33	Sx-2	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	4.78		0.07		12.83	10.78
Solvent - (100-230°C @ 1.6 Torr)	0.81		0.03		52.01	6.66
Heavy Oil - (230-255°C @1.6 Torr)	0.20				1.27	0.32
SRL				17.31		
Coal (MAF)				5.04		
Ash				2.72		
Water	1.42		0.10		0.49	
Phenol						
TOTAL	7.21	NA	0.20	25.07	66.60	17.76

Carbon	4.81		0.09	19.73	58.61	15.11
Hydrogen	0.74		0.02	1.18	5.02	1.50
Nitrogen	0.01			0.25	0.20	0.05
Sulfur	0.02			0.21	0.87	0.12
Oxygen (by diff)	1.63		0.09	0.98	1.90	0.98
Ash				2.72		
TOTAL	7.21	NA	0.20	25.07	66.60	17.76

NA - Not Available

PROJEC' LIGNITE  
MEASURED MATERIAL BALANCE  
 Revised: 2/28/78

Run No: L-2D  
 Date: 9/3/77  
 Time: 1000-2200

MATERIAL OUT  
  
 LBS/HR.

Temperature: 747°F  
 Pressure: 2450 psig  
 LHSV: 1.38  
 GHSV: 320

	STREAM DESCRIPTION				Total Out
	SAMPLE POINT				
Quantitative	Hydrogen - H <sub>2</sub>				1.12
	Carbon Monoxide - CO				5.98
	Carbon Dioxide - CO <sub>2</sub>				9.84
	Hydrogen Sulfide - H <sub>2</sub> S				0.20
	Methane - CH <sub>4</sub>				2.15
	Ethane - C <sub>2</sub> H <sub>6</sub>				0.96
	Propane - C <sub>3</sub> H <sub>8</sub>				0.41
	Butane - C <sub>4</sub> H <sub>10</sub>				
	Nitrogen - N <sub>2</sub>				0.17
	Ammonia - NH <sub>3</sub>				0.03
	Light Oil - (0-100°C @ 1.6 Torr)				29.39
	Solvent - (100-230°C @ 1.6 Torr)				59.96
	Heavy Oil - (230-255°C @1.6 Torr)				1.83
	SRL				17.31
	Cool (MAF)				5.04
	Ash				2.72
	Water				15.53
	Phenol				
	TOTAL				152.64
Elemental	Carbon				107.50
	Hydrogen				12.04
	Nitrogen				0.70
	Sulfur				1.41
	Oxygen (by diff)				28.27
	Ash				2.72
	TOTAL				152.64

RUN CONDITIONS

RUN NO. L-2E

DATE MADE 9/3-4/77

TEMPERATURE °F

PREHEATER E-I  
 SAND BATH 760  
 INLET 291  
 OUTLET 741

DISSOLVERS  
 R-1A (1) 739  
 (2) 808  
 (3) 780  
 (4) 798  
 R-1B (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_  
 (4) \_\_\_\_\_

REACTOR PRODUCT SEPARATORS  
 S-1 589  
 S-2 78  
 S-3 493  
 S-4A 78  
 S-4B 73

PREHEATER E-II  
 DOWTHERM 680  
 INLET 432  
 OUTLET 641

VACUUM FLASH F-1  
 OVERHEAD VAPOR 496  
 UPPER WALL 602  
 LOWER WALL 570  
 DOWNCOMER 562  
 CONDENSATE  
 ACCUMULATOR, S-7 79

PREHEATER E-13  
 DOWTHERM 397  
 INLET 79  
 OUTLET 170

LIGHT ENDS COLUMN, F-2  
 REBOILER 321  
 LOWER SECTION 212  
 FEED SECTION 213  
 OVERHEAD 180  
 S-8 74  
 S-9 -

SOLVENT COLUMN, F-3  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

HEAVY ENDS COLUMN, F-4  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

VACUUM FLASH, F-0  
 OVERHEAD NIU  
 BOTTOMS \_\_\_\_\_

PRECIPITATION TOWER, V-8  
 ZONE (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_

RECOVERY TOWER V-9  
 REBOILER NIU  
 OVERHEAD \_\_\_\_\_

PRESSURE, psig

SEPARATORS S-1 and S-2  
2450

SEPARATOR S-3  
250

SEPARATORS S-4A and S-4B  
62

VACUUM FLASH, F-1  
15 Torr

LIGHT ENDS COLUMN, F-2  
Atm

SOLVENT COLUMN, F-3  
NIU

HEAVY ENDS COLUMN, F-4  
NIU

VACUUM FLASH, F-0  
NIU


SETTLING TOWER, V-8  
NIU

RECOVERY TOWER, V-7  
NIU

	Start	End	Run No: L-2E
Date of Run	9/3/77	9/4/77	Units: lbs/hr., °F, psig
Time of Run	2200	1000	Prep. By: BCL & GGB
Length of Run	12	hrs.	Updated: 2/27/78
Hours on Coal at End of Y.P.	168.0		

### MASS RATES AND RUN CONDITIONS

PRODUCT GAS TO THERMAL	3.28
OXIDIZER	
PRODUCT GAS TO RECYCLE	8.53



155.92 TOTAL

☒ OPEN      ☒ CLOSED

TOTAL 155.92

Numbers in parentheses are not included in the totals.

-335-

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Product Gas, Recycle Gas and F-1 Btms Rates Adjusted followed by a Forced Carbon Balance  
Revised: 2/27/78

Run No: L-2E  
Date: 9/3-4/77  
Time: 2200-1000

SUMMARY

Temperature: 741°F  
Pressure: 2450 psig  
LHSV: 1.48  
GHSV: 309

		lbs/hr				
STREAM DESCRIPTION		Total In	Total Out	Net Yield		Wt % MAF Coal
SAMPLE POINT						
Hydrogen - H <sub>2</sub>		1.10	1.05	-0.05		
Carbon Monoxide - CO		13.65	8.87	-4.78		
Carbon Dioxide - CO <sub>2</sub>			9.88	9.88		
Hydrogen Sulfide - H <sub>2</sub> S			0.09	0.09		
Methane - CH <sub>4</sub>		1.21	1.93	0.72		
Ethane - C <sub>2</sub> H <sub>6</sub>		0.39	0.77	0.38	6.49	21.85
Propane - C <sub>3</sub> H <sub>8</sub>		0.13	0.40	0.27		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>		0.20	0.17	-0.03		
Ammonia - NH <sub>3</sub>			0.01	0.01		
Light Oil - (0-100°C @ 1.6 Torr)		22.04	30.34	8.30		
Solvent - (100-230°C @ 1.6 Torr)		66.01	58.56	-7.45	18.41	61.99
Heavy Oil - (230-255°C @ 1.6 Torr)		2.36	2.61	0.25		
SRL			17.31	17.31		
Coal (MAF)		29.70	5.04	-24.66		-83.03
Ash		2.72	2.72	-0-		-0-
Water		16.41	16.17	-0.24		-0.81
Phenol						
TOTAL		155.92	155.92	-0-		

Carbon		108.38	108.38	-0-		
Hydrogen		11.31	11.94	0.63		
Nitrogen		0.74	0.69	-0.05		
Sulfur		1.52	1.34	-0.18		
Oxygen (by diff)		31.25	30.85	-0.40		
Ash		2.72	2.72	-0-		
TOTAL		155.92	155.92	-0-		

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Product Gas, Recycle Gas and F-1 Btms Rates Adjusted followed by a Forced Carbon Balance

Revised: 2/27/78

Run No: L-2E  
Date: 9/3-4/77  
Time: 2200-1000

MATERIAL IN  
lbs/hr.

Temperature: 741°F  
Pressure: 2450 psig  
LHSV: 1.48  
GHSV: 309

STREAM DESCRIPTION	← Feed Gas →		Lignite	Feed Solvent	Total In
	Recycle Gas	Makeup Gas			
SAMPLE POINT	Sx-20	Sx-18	Sx-1	Sx-14	
Hydrogen - H <sub>2</sub>	0.71	0.39			1.10
Carbon Monoxide - CO	5.98	7.67			13.65
Carbon Dioxide - CO <sub>2</sub>					
Hydrogen Sulfide - H <sub>2</sub> S					
Methane - CH <sub>4</sub>	1.21				1.21
Ethane - C <sub>2</sub> H <sub>6</sub>	0.39				0.39
Propane - C <sub>3</sub> H <sub>8</sub>	0.13				0.13
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.11	0.09			0.20
Ammonia - NH <sub>3</sub>					
Light Oil - (0-100°C @ 1.6 Torr)				22.04	22.04
Solvent - (100-230°C @ 1.6 Torr)				66.01	66.01
Heavy Oil - (230-255°C @ 1.6 Torr)				2.36	2.36
SRL					
Cool (MAF)			29.70		29.70
Ash			2.72		2.72
Water			16.02	0.39	16.41
Phenol					
<b>TOTAL</b>	<b>8.53</b>	<b>8.15</b>	<b>48.44</b>	<b>90.80</b>	<b>155.92</b>

Carbon	3.89	3.29	21.56	79.64	108.38
Hydrogen	1.11	0.39	3.11	6.70	11.31
Nitrogen	0.11	0.09	0.28	0.26	0.74
Sulfur			0.27	1.25	1.52
Oxygen (by diff)	3.42	4.38	20.50	2.95	31.25
Ash			2.72		2.72
<b>TOTAL</b>	<b>8.53</b>	<b>8.15</b>	<b>48.44</b>	<b>90.80</b>	<b>155.92</b>

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Product Gas, Recycle Gas and F-1 Btms Rates Adjusted followed by a Forced Carbon Balance  
Revised: 2/27/78

Run No: L-2E  
Date: 9/3-4/77  
Time: 2200-1000

MATERIAL OUT

Temperature: 741°F  
Pressure: 2450 psig  
LHSV: 1.48  
GHSV: 309

STREAM DESCRIPTION	Product Gas → ← Vent Gas		Absorbed Gas	S-4A Ovhd	S-4B Btms	S-8 Ovhd
	Sx-20	Sx-20				
SAMPLE POINT	Sx-20	Sx-20	Calc.	Sx-30	Calc.	Sx-44
Hydrogen - H <sub>2</sub>	0.27	0.71		0.07		
Carbon Monoxide - CO	2.30	5.98		0.52		
Carbon Dioxide - CO <sub>2</sub>			6.98	2.57		
Hydrogen Sulfide - H <sub>2</sub> S			0.03	0.06		
Methane - CH <sub>4</sub>	0.47	1.21		0.22		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.15	0.39		0.20		
Propane - C <sub>3</sub> H <sub>8</sub>	0.05	0.13		0.18		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.04	0.11		0.02		
Ammonia - NH <sub>3</sub>					0.01	
Light Oil - (0-100°C @ 1.6 Torr)					3.22	
Solvent - (100-230°C @ 1.6 Torr)					1.58	
Heavy Oil - (230-255°C @1.6 Torr)					0.22	
SRL						
Cool (MAF)						
Ash						
Water					15.30	
Phenol						
TOTAL	3.28	8.53	7.01	3.84	20.33	Negl.

Carbon	1.50	3.89	1.90	1.39	4.27	
Hydrogen	0.43	1.11		0.20	2.11	
Nitrogen	0.04	0.11		0.02	0.02	
Sulfur			0.03	0.06	0.03	
Oxygen (by diff)	1.31	3.42	5.08	2.17	13.90	
Ash						
TOTAL	3.28	8.53	7.01	3.84	20.33	Negl.

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Product Gas, Recycle Gas and F-1 Btms Rate Adjusted followed by a Forced Carbon Balance  
Revised: 2/27/78

Run No: L-2E  
Date: 9/3-4/77  
Time: 2200-1000

MATERIAL OUT

Temperature: 741°F  
Pressure: 2450 psig  
LHSV: 1.48  
GHSV: 309

		lbs/hr				
Quantitative	STREAM DESCRIPTION	S-8 Btms	J-1 Exhaust	Cold Trap	F-1 Btms	←Recycle Solvent→ S-7 Btms F-2 Btms
	SAMPLE POINT	Sx-16	*Sx-32	Sx-33	Sx-2	Sx-39 Sx-12
	Hydrogen - H <sub>2</sub>					
	Carbon Monoxide - CO		0.07			
	Carbon Dioxide - CO <sub>2</sub>		0.33			
	Hydrogen Sulfide - H <sub>2</sub> S					
	Methane - CH <sub>4</sub>		0.03			
	Ethane - C <sub>2</sub> H <sub>6</sub>		0.03			
	Propane - C <sub>3</sub> H <sub>8</sub>		0.04			
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					
	Ammonia - NH <sub>3</sub>					
	Light Oil - (0-100°C @ 1.6 Torr)	3.31		0.17		14.96 8.68
	Solvent - (100-230°C @ 1.6 Torr)	0.25				51.12 5.61
	Heavy Oil - (230-255°C @1.6 Torr)	0.10				2.02 0.27
	SRL				17.31	
	Coal (MAF)				5.04	
	Ash				2.72	
	Water			0.36		0.51
	Phenol					
	TOTAL	3.66	0.50	0.53	25.07	68.61 14.56
Elemental	Carbon	3.18	0.20	0.16	19.73	60.23 11.93
	Hydrogen	0.40	0.02	0.05	1.18	5.24 1.20
	Nitrogen	0.01			0.25	0.20 0.04
	Sulfur	0.02			0.21	0.90 0.09
	Oxygen (by diff)	0.05	0.28	0.32	0.98	2.04 1.30
	Ash				2.72	
	TOTAL	3.66	0.50	0.53	25.07	68.61 14.56

\*Rate assumed similar to those of the other L-2 yield periods where the orifice meter was operating properly.

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Product Gas, Recycle Gas and F-1 Btms Rate Adjusted followed by a Forced Carbon Balance  
Revised: 2/27/78

Run No: L-2E  
Date: 9/3-4/77  
Time: 2200-1000

MATERIAL OUT  
lbs/hr.

Temperature: 741°F  
Pressure: 2450 psig  
LHSV: 1.48  
GHSV: 309

STREAM DESCRIPTION						Total
						Out
SAMPLE POINT						
Hydrogen - H <sub>2</sub>						1.05
Carbon Monoxide - CO						8.87
Carbon Dioxide - CO <sub>2</sub>						9.88
Hydrogen Sulfide - H <sub>2</sub> S						0.09
Methane - CH <sub>4</sub>						1.93
Ethane - C <sub>2</sub> H <sub>6</sub>						0.77
Propane - C <sub>3</sub> H <sub>8</sub>						0.40
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						0.17
Ammonia - NH <sub>3</sub>						0.01
Light Oil - (0-100°C @ 1.6 Torr)						30.34
Solvent - (100-230°C @ 1.6 Torr)						58.56
Heavy Oil - (230-255°C @1.6 Torr)						2.61
SRL						17.31
Coal (MAF)						5.04
Ash						2.72
Water						16.17
Phenol						
TOTAL						155.92

ELEMENTAL						Total
Carbon						108.38
Hydrogen						11.94
Nitrogen						0.69
Sulfur						1.34
Oxygen (by diff)						30.85
Ash						2.72
TOTAL						155.92

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/27/78

Run No: L-2E

Date: 9/3-4/77

Time: 2200-1000

WEIGHT PERCENT

SAMPLE DESCRIPTION	Lignite	F-1 Btms	Makeup Solvent	LEC Btms	Feed Solvent	S-8 Oil
	Sx-1	Sx-2	Sx-8	Sx-12	Sx-14	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100° C @ 1.6 Torr)			1.79	59.60	24.27	90.40
Solvent - (100-230° C @ 1.6 Torr)			94.00	38.50	72.70	6.80
Heavy Oil - (230-255° C @ 1.6 Torr)			4.00	1.90	2.60	2.80
SRL		69.06				
Coal (MAF)	61.32	20.11				
Ash	5.61	10.83				
Water	33.07		0.21		0.43	
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		77.45				
Melting Point °F		488				
Specific Gravity 60/60			1.043	1.005	1.053	
Viscosity, cp						

Carbon	44.51	78.69	88.84	81.92	87.71	86.87
Hydrogen	6.42	4.72	8.52	8.23	7.38	11.16
Nitrogen	0.58	1.00	0.13	0.30	0.29	0.19
Sulfur	0.56	0.86	1.82	0.62	1.37	0.48
Oxygen (by diff)	42.32	3.90	0.69	8.93	3.25	1.30
Ash	5.61	10.83				
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	4	1	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/27/78

Run No: L-2E

Date: 9/3-4/77

Time: 2200-1000

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-8	S-8	Makeup	Product	Recycle	Feed
	Water	Total	Gas	Gas	Gas	Gas
SAMPLE POINT	Sx-16	Sx-16	Sx-18	Sx-19	Sx-20	Sx-21
Hydrogen - H <sub>2</sub>			4.79	4.95	8.30	7.00
Carbon Monoxide - CO			94.15	41.00	70.11	81.28
Carbon Dioxide - CO <sub>2</sub>				40.42		
Hydrogen Sulfide - H <sub>2</sub> S				0.28		
Methane - CH <sub>4</sub>				9.09	14.19	6.82
Ethane - C <sub>2</sub> H <sub>6</sub>				2.34	4.55	2.79
Propane - C <sub>3</sub> H <sub>8</sub>				1.22	1.54	1.29
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>			1.06	0.70	1.31	0.82
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100°C @ 1.6 Torr)		90.40				
Solvent - (100-230°C @ 1.6 Torr)		6.80				
Heavy Oil - (230-255°C @1.6 Torr)		2.80				
SRL						
Coal (MAF)						
Ash						
Water	100					
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon		86.87	40.35	38.28	45.59	43.24
Hydrogen	11.11	11.16	4.79	7.93	13.04	9.49
Nitrogen		0.19	1.06	0.70	1.31	0.82
Sulfur		0.48		0.26		
Oxygen (by diff)	88.89	1.30	53.80	52.83	40.06	46.45
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/27/78

Run No: L-2E

Date: 9/3-4/77

Time: 2200-1000

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4B Oil	S-4B Water	S-4B Total	S-4A Ovhd	J-1 Disch.	Cold Trap
SAMPLE POINT	Sx-23	Sx-23	Sx-23	Sx-30	Sx-32	Sx-33
Hydrogen - H <sub>2</sub>				1.78	0.74	
Carbon Monoxide - CO				13.45	13.60	
Carbon Dioxide - CO <sub>2</sub>				67.07	65.69	
Hydrogen Sulfide - H <sub>2</sub> S				1.65		
Methane - CH <sub>4</sub>				5.76	4.97	
Ethane - C <sub>2</sub> H <sub>6</sub>				5.13	6.38	
Propane - C <sub>3</sub> H <sub>8</sub>				4.59	8.62	
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>				0.45		
Ammonia - NH <sub>3</sub> (PPM)		0.09	0.09	0.12		
Light Oils - (0-100°C @ 1.6 Torr)	62.18					32.28
Solvent - (100-230°C @ 1.6 Torr)	30.50					
Heavy Oil - (230-255°C @1.6 Torr)	4.20					
SRL						
Coal (MAF)						
Ash						
Water	3.12	99.91	99.91			67.72
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60	0.992					
Viscosity, cp						

Carbon	82.42			36.23	39.63	30.10
Hydrogen	8.11	11.12	11.12	5.10	4.83	9.27
Nitrogen	0.28	0.07	0.07	0.65		0.07
Sulfur	0.62			1.55		0.36
Oxygen (by diff)	8.57	88.81	88.81	56.47	55.54	60.20
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	1

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/27/78

Run No: L-2E

Date: 9/3-4/77

Time: 2200-1000

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-7	S-4A	S-4A	S-4A	S-7	Absorbed
	Btms	Oil	Water	Total	Btms	Gas
SAMPLE POINT	Sx-34/39	Sx-37	Sx-37	Sx-37	Sx-34/39	Calc.
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						99.56
Hydrogen Sulfide - H <sub>2</sub> S						0.44
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)			0.08	0.03		
Light Oils - (0-100°C @ 1.6 Torr)	21.81	71.28		47.70	21.81	
Solvent - (100-230°C @ 1.6 Torr)	74.50	23.00		15.39	74.50	
Heavy Oil - (230-255°C @1.6 Torr)	2.95	4.70		3.15	2.95	
SRL						
Coal (MAF)						
Ash						
Water	0.74	1.02	99.92	33.73	0.74	
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60	1.056	0.974			1.056	
Viscosity, cp						

Carbon	87.79	82.70		55.34	87.79	27.15
Hydrogen	7.64	8.97	11.11	9.68	7.64	0.03
Nitrogen	0.29	0.24	0.07	0.18	0.29	
Sulfur	1.31	0.47		0.32	1.31	0.41
Oxygen (by diff)	2.97	7.62	88.82	34.48	2.97	72.41
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	4	2	2	2	4	-

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/27/78

Run No: L-2E

Date: 9/3-4/77

Time: 2200-1000

WEIGHT PERCENT

Quantitative	SAMPLE DESCRIPTION	S-4B Btms				
	SAMPLE POINT	Calc				
	Hydrogen - H <sub>2</sub>					
	Carbon Monoxide - CO					
	Carbon Dioxide - CO <sub>2</sub>					
	Hydrogen Sulfide - H <sub>2</sub> S					
	Methane - CH <sub>4</sub>					
	Ethane - C <sub>2</sub> H <sub>6</sub>					
	Propane - C <sub>3</sub> H <sub>8</sub>					
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					
	Ammonia - NH <sub>3</sub> (PPM)	0.07				
	Light Oils - (0-100°C @ 1.6 Torr)	15.84				
	Solvent - (100-230°C @ 1.6 Torr)	7.77				
	Heavy Oil - (230-255°C @1.6 Torr)	1.07				
	SRL					
	Coal (MAF)					
	Ash					
	Water	75.25				
	Phenol					
TOTAL	100					
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Elemental	Carbon	21.00				
	Hydrogen	10.36				
	Nitrogen	0.12				
	Sulfur	0.16				
	Oxygen (by diff)	68.36				
	Ash					
	TOTAL	100				
	Number of Sample Avg.	-				

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/27/78

Run No: L-2E

Date: 9/3-4/77

Time: 2200-1000

MOLE PERCENT

	MOLE PERCENT					
	Makeup Gas	Product Gas	Recycle Gas	Feed Gas	S-4A Ovhd	J-1 Disch
<b>SAMPLE DESCRIPTION</b>						
<b>SAMPLE POINT</b>	Sx-18	Sx-19	Sx-20	Sx-21	Sx-30	Sx-32
Hydrogen - H <sub>2</sub>	41.35	44.50	53.40	50.13	24.65	12.04
Carbon Monoxide - CO	58.00	26.30	32.20	41.59	13.35	15.84
Carbon Dioxide - CO <sub>2</sub>		16.50			42.35	48.67
Hydrogen Sulfide - H <sub>2</sub> S		0.15			1.35	
Methane - CH <sub>4</sub>		10.20	11.40	6.11	10.00	10.13
Ethane - C <sub>2</sub> H <sub>6</sub>		1.40	1.95	1.33	4.75	6.93
Propane - C <sub>3</sub> H <sub>8</sub>		0.50	0.45	0.42	2.90	6.39
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.65	0.45	0.60	0.42	0.45	
Ammonia - NH <sub>3</sub> (PPM)					0.20	
Light Oils - (0-100° C @ 1.6 Torr)						
Solvent - (100-230° C @ 1.6 Torr)						
Heavy Oil - (230-255° C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
<b>TOTAL</b>	100	100	100	100	100	100
Calc Mole Wt.	17.25	17.96	12.86	14.33	27.78	32.60
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						
Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	TOTAL					
	Number of Sample Avg.	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/27/78

Run No: L-2E

Date: 9/3-4/77

Time: 2200-1000

MOLE PERCENT

Quantitative	SAMPLE DESCRIPTION	Absorbed Gas				
	SAMPLE POINT	Calc.				
	Hydrogen - H <sub>2</sub>					
	Carbon Monoxide - CO					
	Carbon Dioxide - CO <sub>2</sub>	99.43				
	Hydrogen Sulfide - H <sub>2</sub> S	0.57				
	Methane - CH <sub>4</sub>					
	Ethane - C <sub>2</sub> H <sub>6</sub>					
	Propane - C <sub>3</sub> H <sub>8</sub>					
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					
	Ammonia - NH <sub>3</sub> (PPM)					
	Light Oils - (0-100° C @ 1.6 Torr)					
	Solvent - (100-230° C @ 1.6 Torr)					
	Heavy Oil - (230-255° C @ 1.6 Torr)					
	SRL					
	Coal (MAF)					
	Ash					
	Water					
	Phenol					
TOTAL	100					
Calc Mole Wt.	43.94					
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	TOTAL					
	Number of Sample Avg.	2				

PROJECT LIGNITE  
 SAMPLE ANALYSES  
 RUN NO: L-2E  
 DATE: 9/3-4/77  
 TIME: 2200-1000

SAMPLE DESCRIPTION	F-1 Btms	LEC Btms	Feed Solv.	S-8 Oil	S-4B Oil
SAMPLE POINT	Sx-2	Sx-12	Sx-14	Sx-16	Sx-23
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR		5	5		
IBP		58	61.6		
5%		70	81.0		
10%		74	90.2		
20%		80	108.5		
30%		86	135.0		
40%		94	157.8		
50%		105	169.2		
60%		120	174.8		
70%		145	182.3		
80%		165.5	190.2		
90%		181	207.2		
95%		195.5	248.2		
DRY PT.		198.5	248.2		
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR				740	739
IBP				57	90
5%				66	147
10%				78	190
20%				106	207
30%				129	215
40%				145	226
50%				154	240
60%				167	261
70%				182	291
80%				203	338
90%				243	351
95%				316	
DRY PT.				318	354
ASPHALTENE TEST					
WT % ASH	10.83				
WT % UNCONVERTED COAL	20.11				
WT % PRE-ASPHALTENES	37.25				
WT % ASPHALTENES	15.05				
WT % MALTENES & DIST. OIL	16.76				
TOTAL	100.00				
SAYBOLT VISCOSITY, SSU					
100° F		9.9	11.5		
210° F		8.1	8.5		
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)		-	0.43		3.12
INFRARED RATIO		0.21	0.41		
SP. GRAV. 60/60 F		1.005	1.053		0.992

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
 ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
 MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
 DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: L-2E  
DATE: 9/3-4/77  
TIME: 2200-1000

SAMPLE DESCRIPTION	Cold Trap	S-7 Btms	S-4A Oil		
SAMPLE POINT	Sx-33	Sx-34/39	Sx-37		
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR		5			
IBP		32.7			
5%		81.5			
10%		92.4			
20%		115.2			
30%		143.8			
40%		163			
50%		171.8			
60%		177.5			
70%		182			
80%		189.9			
90%		211.6			
95%		252.9			
DRY PT.					
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR		739		739	
IBP		86		83	
5%		95		159	
10%		102		179	
20%		103		189	
30%		103		197	
40%		104		206	
50%		104		212	
60%		105		241	
70%		106		269	
80%		113		318	
90%				350	
95%					
DRY PT.		113		353	
ASPHALTENE TEST					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
SAYBOLT VISCOSITY, SSU					
100° F		11.9			
210° F		8.5			
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)	67.72	0.74	1.02		
INFRARED RATIO		0.43			
SP. GRAV. 60/60 F		1.056	0.974		

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 2/27/78

Run No: L-2E  
Date: 9/3-4/77  
Time: 2200-1000

MATERIAL IN

Temperature: 741°F  
Pressure: 2450 psig  
LHSV: 1.48  
GHSV: 309

	← Feed Gas →		lbs/hr.			Total In
	Recycle Gas	Makeup Gas	Lignite	Feed Solvent		
SAMPLE POINT	Sx-20	Sx-18	Sx-1	Sx-14		
Hydrogen - H <sub>2</sub>	0.59	0.46				1.05
Carbon Monoxide - CO	4.97	9.03				14.00
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>	1.01					1.01
Ethane - C <sub>2</sub> H <sub>6</sub>	0.32					0.32
Propane - C <sub>3</sub> H <sub>8</sub>	0.11					0.11
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.09	0.10				0.19
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)				22.04		22.04
Solvent - (100-230°C @ 1.6 Torr)				66.01		66.01
Heavy Oil - (230-255°C @ 1.6 Torr)				2.36		2.36
SRL						
Coal (MAF)			29.70			29.70
Ash			2.72			2.72
Water			16.02	0.39		16.41
Phenol						
<b>TOTAL</b>	<b>7.09</b>	<b>9.59</b>	<b>48.44</b>	<b>90.80</b>		<b>155.92</b>
Elemental						
Carbon	3.23	3.87	21.56	79.64		108.30
Hydrogen	0.93	0.46	3.11	6.70		11.20
Nitrogen	0.09	0.10	0.28	0.26		0.73
Sulfur			0.27	1.25		1.52
Oxygen (by diff)	2.84	5.16	20.50	2.95		31.45
Ash			2.72			2.72
<b>TOTAL</b>	<b>7.09</b>	<b>9.59</b>	<b>48.44</b>	<b>90.80</b>		<b>155.92</b>

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 2/27/78

Run No: L-2E  
Date: 9/3-4/77  
Time: 2200-1000

MATERIAL OUT  
  
lbs/hr.

Temperature: 741°F  
Pressure: 2450 psig  
LHSV: 1.48  
GHSV: 309

	← Product Gas →			S-4A Ovhd	S-4B Btms	S-8 Ovhd
	Vent Gas	Recycle Gas	Absorbed Gas			
STREAM DESCRIPTION	Sx-20	Sx-20	Calc	Sx-30	Sx-23	Sx-44
SAMPLE POINT	Sx-20	Sx-20	Calc	Sx-30	Sx-23	Sx-44
Hydrogen - H <sub>2</sub>	0.34	0.59		0.07		
Carbon Monoxide - CO	2.84	4.97		0.52		
Carbon Dioxide - CO <sub>2</sub>			7.49	2.57		
Hydrogen Sulfide - H <sub>2</sub> S			0.03	0.06		
Methane - CH <sub>4</sub>	0.58	1.01		0.22		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.18	0.32		0.20		
Propane - C <sub>3</sub> H <sub>8</sub>	0.06	0.11		0.18		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.05	0.09		0.02		
Ammonia - NH <sub>3</sub>					0.02	
Light Oil - (0-100°C @ 1.6 Torr)						
Solvent - (100-230°C @ 1.6 Torr)						
Heavy Oil - (230-255°C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water					20.31	
Phenol						
TOTAL	4.05	7.09	7.52	3.84	20.33	Negl.

Carbon	1.85	3.23	2.04	1.39		
Hydrogen	0.53	0.93		0.20	2.26	
Nitrogen	0.05	0.09		0.02	0.01	
Sulfur			0.03	0.06		
Oxygen (by diff)	1.62	2.84	5.45	2.17	18.06	
Ash						
TOTAL	4.05	7.09	7.52	3.84	20.33	Negl.

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 2/27/78

Run No: L-2E  
Date: 9/3-4/77  
Time: 2200-1000

MATERIAL OUT

lbs/hr.

Temperature: 741°F  
Pressure: 2450 psig  
LHSV: 1.48  
GHSV: 309

STREAM DESCRIPTION	S-8	J-1	Cold	F-1	← Recycle	Solvent →
	Btms	Exhaust	Trap	Btms	S-7 Btms	F-2 Btms
SAMPLE POINT	Sx-16	Sx-32	Sx-33	Sx-2	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	3.31		0.17		14.96	8.68
Solvent - (100-230°C @ 1.6 Torr)	0.25				51.12	5.61
Heavy Oil - (230-255°C @1.6 Torr)	0.10				2.02	0.27
SRL				16.89		
Cool (MAF)				4.92		
Ash				2.65		
Water			0.36		0.51	
Phenol						
TOTAL	3.66	NA	0.53	24.46	68.61	14.56
Carbon	3.18		0.16	19.26	60.23	11.93
Hydrogen	0.40		0.05	1.15	5.24	1.20
Nitrogen	0.01			0.24	0.20	0.04
Sulfur	0.02			0.21	0.90	0.09
Oxygen (by diff)	0.05		0.32	0.95	2.04	1.30
Ash				2.65		
TOTAL	3.66	NA	0.53	24.46	68.61	14.56

NA - Not Available

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 2/27/78

Run No: L-2E  
Date: 9/3-4/77  
Time: 2200-1000

MATERIAL OUT

Temperature: 741°F  
Pressure: 2450 psig  
LHSV: 1.48  
GHSV: 309

lbs/hr.

	STREAM DESCRIPTION					Total
	SAMPLE POINT					Out
Quantitative	Hydrogen - H <sub>2</sub>					1.00
	Carbon Monoxide - CO					8.33
	Carbon Dioxide - CO <sub>2</sub>					10.06
	Hydrogen Sulfide - H <sub>2</sub> S					0.09
	Methane - CH <sub>4</sub>					1.81
	Ethane - C <sub>2</sub> H <sub>6</sub>					0.70
	Propane - C <sub>3</sub> H <sub>8</sub>					0.35
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					0.16
	Ammonia - NH <sub>3</sub>					0.02
	Light Oil - (0-100°C @ 1.6 Torr)					27.12
	Solvent - (100-230°C @ 1.6 Torr)					56.98
	Heavy Oil - (230-255°C @1.6 Torr)					2.39
	SRL					16.89
	Cool (MAF)					4.92
	Ash					2.65
	Water					21.18
	Phenol					
	TOTAL					154.65

Elemental						Total
	Carbon					103.27
	Hydrogen					11.96
	Nitrogen					0.66
	Sulfur					1.31
	Oxygen (by diff)					34.80
	Ash					2.65
	TOTAL					154.65

RUN CONDITIONS  
 RUN NO. L-2F  
 DATE MADE 9/11-12/77

TEMPERATURE °F		PRESSURE, psig
PREHEATER E-I	PREHEATER E-13	SEPARATORS S-1 and S-2
SAND BATH <u>743</u>	DOWTHERM <u>408</u>	<u>2460</u>
INLET <u>309</u>	INLET <u>87</u>	SEPARATOR S-3
OUTLET <u>726</u>	OUTLET <u>185</u>	<u>240</u>
DISSOLVERS	LIGHT ENDS COLUMN, F-2	SEPARATORS S-4A and S-4B
R-1A (1) <u>NIU</u>	REBOILER <u>275</u>	<u>60</u>
(2) _____	LOWER SECTION <u>215</u>	VACUUM FLASH, F-1
(3) _____	FEED SECTION <u>214</u>	<u>14 Torr</u>
(4) _____	OVERHEAD <u>171</u>	LIGHT ENDS COLUMN, F-2
R-1B (1) <u>747</u>	S-8 <u>73</u>	<u>Atm</u>
(2) <u>791</u>	S-9 <u>-</u>	SOLVENT COLUMN, F-3
(3) <u>818</u>		<u>NIU</u>
(4) <u>832</u>	SOLVENT COLUMN, F-3	HEAVY ENDS COLUMN, F-4
REACTOR PRODUCT SEPARATORS	REBOILER <u>NIU</u>	<u>NIU</u>
S-1 <u>545</u>	LOWER SECTION _____	VACUUM FLASH, F-0
S-2 <u>84</u>	FEED SECTION _____	<u>NIU</u>
S-3 <u>479</u>	OVERHEAD _____	SETTLING TOWER, V-8
S-4A <u>90</u>	HEAVY ENDS COLUMN, F-4	<u>NIU</u>
S-4B <u>77</u>	REBOILER <u>NIU</u>	RECOVERY TOWER, V-7
PREHEATER E-II	LOWER SECTION _____	<u>NIU</u>
DOWTHERM <u>686</u>	FEED SECTION _____	
INLET <u>446</u>	OVERHEAD _____	
OUTLET <u>643</u>	VACUUM FLASH, F-0	
VACUUM FLASH F-1	OVERHEAD <u>NIU</u>	
OVERHEAD VAPOR <u>509</u>	BOTTOMS _____	
UPPER WALL <u>618</u>	PRECIPITATION TOWER, V-8	
LOWER WALL <u>581</u>	ZONE (1) <u>NIU</u>	
DOWNCOMER <u>523</u>	(2) _____	
CONDENSATE	(3) _____	
ACCUMULATOR, S-7 <u>91</u>	RECOVERY TOWER V-9	
	REBOILER <u>NIU</u>	
	OVERHEAD _____	


	Start	End	Run No: L-2F
Date of Run	9/11/77	9/12/77	Units: lbs/hr, °F, psig
Time of Run	1900	0700	Prep. By: BCL & GGB
Length of Run	12	hrs	Updated: 2/24/78
Hours on Coal at End of Y.P.	306.1		

### MASS RATES AND RUN CONDITIONS

PRODUCT GAS TO THERMAL OXIDIZER	4.46
PRODUCT GAS TO RECYCLE	10.23

#### 10.23 RECYCLE GAS

9:49 MAKEUP GAS  
46.50 LIGNITE



159.05 TOTAL

☒ OPEN      ☒ CLOSED

TOTAL 159.05

Numbers in parentheses are not included in the totals.

-355-

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product & Recycle Gas Rates Adjusted  
 Revised: 2/24/78

Run No: L-2F  
 Date: 9/11- 12/77  
 Time: 1900-0700

SUMMARY  
 lbs/hr.

Temperature: 726°F  
 Pressure: 2460 psig  
 LHSV: 1.41  
 GHSV: 354

STREAM DESCRIPTION	Total In	Total Out	Net Yield	Wt % MAF Coal	
SAMPLE POINT					
Hydrogen - H <sub>2</sub>	1.38	1.09	-0.29		
Carbon Monoxide - CO	13.61	7.62	-5.99		
Carbon Dioxide - CO <sub>2</sub>		13.20	13.20		
Hydrogen Sulfide - H <sub>2</sub> S		0.32	0.32		
Methane - CH <sub>4</sub>	3.05	4.99	1.94	10.76	38.26
Ethane - C <sub>2</sub> H <sub>6</sub>	0.98	1.90	0.92		
Propane - C <sub>3</sub> H <sub>8</sub>	0.43	1.06	0.63		
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.27	0.25	-0.02		
Ammonia - NH <sub>3</sub>		0.05	0.05		
Light Oil - (0-100°C @ 1.6 Torr)	19.78	27.93	8.15		
Solvent - (100-230°C @ 1.6 Torr)	70.46	67.39	-3.07	16.53	58.78
Heavy Oil - (230-255°C @ 1.6 Torr)	2.14	2.02	-0.12		
SRL		11.57	11.57		
Coal (MAF)	28.12	2.47	-25.65		-91.21
Ash	2.89	2.49	-0.40		-1.42
Water	15.94	14.70	-1.24		-4.41
Phenol					
TOTAL	159.05	159.05	-0-		

Carbon	110.67	110.42	-0.25		
Hydrogen	13.02	13.33	0.31		
Nitrogen	0.77	0.72	-0.05		
Sulfur	1.51	1.60	0.09		
Oxygen (by diff)	30.19	30.49	0.30		
Ash	2.89	2.49	-0.40		
TOTAL	159.05	159.05	-0-		

PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE  
Product & Recycle Gas Rates Adjusted  
Revised: 2/24/78

Run No: L-2F  
Date: 9/11-12/77  
Time: 1900-0700

MATERIAL IN  
lbs/hr.

Temperature: 726°F  
Pressure: 2460 psig  
LHSV: 1.41  
GHSV: 354

STREAM DESCRIPTION	← Feed Gas →		Lignite	Feed Solvent	Total In
	Recycle Gas	Makeup Gas			
SAMPLE POINT	Sx-20	Sx-18	Sx-1	Sx-14	
Hydrogen - H <sub>2</sub>	0.71	0.67			1.38
Carbon Monoxide - CO	4.90	8.71			13.61
Carbon Dioxide - CO <sub>2</sub>					
Hydrogen Sulfide - H <sub>2</sub> S					
Methane - CH <sub>4</sub>	3.05				3.05
Ethane - C <sub>2</sub> H <sub>6</sub>	0.98				0.98
Propane - C <sub>3</sub> H <sub>8</sub>	0.43				0.43
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.16	0.11			0.27
Ammonia - NH <sub>3</sub>					
Light Oil - (0-100°C @ 1.6 Torr)				19.78	19.78
Solvent - (100-230°C @ 1.6 Torr)				70.46	70.46
Heavy Oil - (230-255°C @ 1.6 Torr)				2.14	2.14
SRL					
Coal (MAF)			28.12		28.12
Ash			2.89		2.89
Water			15.49	0.45	15.94
Phenol					
<b>TOTAL</b>	<b>10.23</b>	<b>9.49</b>	<b>46.50</b>	<b>92.83</b>	<b>159.05</b>

Carbon	5.52	3.73	20.17	81.25	110.67
Hydrogen	1.75	0.67	3.01	7.59	13.02
Nitrogen	0.16	0.11	0.26	0.24	0.77
Sulfur			0.29	1.22	1.51
Oxygen (by diff)	2.80	4.98	19.88	2.53	30.19
Ash			2.89		2.89
<b>TOTAL</b>	<b>10.23</b>	<b>9.49</b>	<b>46.50</b>	<b>92.83</b>	<b>159.05</b>

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product & Recycle Gas Rates Adjusted  
 Revised: 2/24/78

Run No: L-2F  
 Date: 9/11-12/77  
 Time: 1900-0700

MATERIAL OUT

Temperature: 726°F  
 Pressure: 2460 psig  
 LHSV: 1.41  
 GHSV: 354

lbs/hr.

STREAM DESCRIPTION	Product Gas			S-4A	S-4B	S-8
	Vent Gas	Recycle Gas	Absorbed Gas	Ovhd	Btms	Ovhd
SAMPLE POINT	Sx-20	Sx-20	Calc.	Sx-30	Sx-23	Sx-44
Hydrogen - H <sub>2</sub>	0.31	0.71		0.07		
Carbon Monoxide - CO	2.14	4.90		0.51		
Carbon Dioxide - CO <sub>2</sub>			10.16	2.77		
Hydrogen Sulfide - H <sub>2</sub> S			0.23	0.09		
Methane - CH <sub>4</sub>	1.33	3.05		0.57		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.43	0.98		0.41		
Propane - C <sub>3</sub> H <sub>8</sub>	0.18	0.43		0.34		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.07	0.16		0.02		
Ammonia - NH <sub>3</sub>			0.02	0.01	0.02	
Light Oil - (0-100°C @ 1.6 Torr)					0.26	
Solvent - (100-230°C @ 1.6 Torr)					0.08	
Heavy Oil - (230-255°C @ 1.6 Torr)						
SRL						
Cool (MAF)						
Ash						
Water					13.81	
Phenol						
TOTAL	4.46	10.23	10.41	4.79	14.17	Negl.

Carbon	2.41	5.52	2.77	2.01	0.28	
Hydrogen	0.76	1.75	0.02	0.37	1.57	
Nitrogen	0.07	0.16	0.02	0.03	0.02	
Sulfur			0.21	0.08		
Oxygen (by diff)	1.22	2.80	7.39	2.30	12.30	
Ash						
TOTAL	4.46	10.23	10.41	4.79	14.17	Negl.

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product & Recycle Gas Rates Adjusted  
 Revised: 2/24/78

Run No: L-2F  
 Date: 9/11-12/77  
 Time: 1900-0700

MATERIAL OUT  
 lbs/hr.

Temperature: 726°F  
 Pressure: 2460 psig  
 LHSV: 1.41  
 GHSV: 354

STREAM DESCRIPTION	S-8	J-1	Cold	F-1	← Recycle Solvent →	
	Btms	Exhaust	Trap	Btms	S-7 Btms	LEC Btms
SAMPLE POINT	Sx-16	Sx-32	Sx-33	Sx-2	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO		0.07				
Carbon Dioxide - CO <sub>2</sub>		0.27				
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>		0.04				
Ethane - C <sub>2</sub> H <sub>6</sub>		0.08				
Propane - C <sub>3</sub> H <sub>8</sub>		0.11				
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	1.21		0.13		13.18	13.15
Solvent - (100-230°C @ 1.6 Torr)	0.02			2.38	58.41	6.50
Heavy Oil - (230-255°C @1.6 Torr)					1.92	0.10
SRL				11.57		
Coal (MAF)				2.47		
Ash				2.49		
Water	0.27		0.15		0.47	
Phenol						
<b>TOTAL</b>	<b>1.50</b>	<b>0.57</b>	<b>0.28</b>	<b>18.91</b>	<b>73.98</b>	<b>19.75</b>

Carbon	1.02	0.28	0.08	14.56	64.88	16.61
Hydrogen	0.18	0.05	0.03	0.90	5.87	1.83
Nitrogen				0.18	0.19	0.05
Sulfur				0.21	1.01	0.09
Oxygen (by diff)	0.30	0.24	0.17	0.57	2.03	1.17
Ash				2.49		
<b>TOTAL</b>	<b>1.50</b>	<b>0.57</b>	<b>0.28</b>	<b>18.91</b>	<b>73.98</b>	<b>19.75</b>

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product & Recycle Gas Rates Adjusted  
 Revised: 2/24/78

Run No: L-2F  
 Date: 9/11-12/77  
 Time: 1900-0700

MATERIAL OUT  
 lbs/hr.

Temperature: 726°F  
 Pressure: 2460 psig  
 LHSV: 1.41  
 GHSV: 354

						Total Out
Quantitative	STREAM DESCRIPTION					
	SAMPLE POINT					
	Hydrogen - H <sub>2</sub>					1.09
	Carbon Monoxide - CO					7.62
	Carbon Dioxide - CO <sub>2</sub>					13.20
	Hydrogen Sulfide - H <sub>2</sub> S					0.32
	Methane - CH <sub>4</sub>					4.99
	Ethane - C <sub>2</sub> H <sub>6</sub>					1.90
	Propane - C <sub>3</sub> H <sub>8</sub>					1.06
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					0.25
	Ammonia - NH <sub>3</sub>					0.05
	Light Oil - (0-100°C @ 1.6 Torr)					27.93
	Solvent - (100-230°C @ 1.6 Torr)					67.39
	Heavy Oil - (230-255°C @1.6 Torr)					2.02
	SRL					11.57
	Cool (MAF)					2.47
	Ash					2.49
	Water					14.70
	Phenol					
TOTAL					159.05	
Elemental	Carbon					110.42
	Hydrogen					13.33
	Nitrogen					0.72
	Sulfur					1.60
	Oxygen (by diff)					30.49
	Ash					2.49
TOTAL					159.05	

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/24/78

Run No: L-2F

Date: 9/11-12/77

Time: 1900-0700

WEIGHT PERCENT

SAMPLE DESCRIPTION	WEIGHT PERCENT					
	Lignite	F-1 Btms	LEC Btms	Feed Solvent	S-8 Water	S-8 Oil
SAMPLE POINT	Sx-1	*Sx-2	Sx-12	Sx-14	Sx-16	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100°C @ 1.6 Torr)			66.60	21.31		98.40
Solvent - (100-230°C @ 1.6 Torr)		12.57	32.90	75.90		1.60
Heavy Oil - (230-255°C @1.6 Torr)			0.50	2.30		
SRL		61.19				
Coal (MAF)	60.47	13.08				
Ash	6.22	13.16				
Water	33.31			0.49	100	
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		84.94				
Melting Point °F		330				
Specific Gravity 60/60			0.959	1.030		
Viscosity, cp						

Quantitative

Carbon	43.37	77.00	84.09	87.52		82.84
Hydrogen	6.47	4.75	9.28	8.18	11.11	12.18
Nitrogen	0.56	0.97	0.24	0.26		0.10
Sulfur	0.63	1.10	0.46	1.31		0.18
Oxygen (by diff)	42.75	3.02	5.93	2.73	88.89	4.70
Ash	6.22	13.16				
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	4	2	2	2	2

Elemental

\*Distillable oil calculated by following equation: Wt % Distillable oil = -0.1273 (F-1 Btms melting point) + 54.38. See attached graph.

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/24/78

Run No: L-2F

Date: 9/11-12/77

Time: 1900-0700

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-8	Makeup	Product	Recycle	Feed	S-4B
	Total	Gas	Gas	Gas	Gas	Water
SAMPLE POINT	Sx-16	Sx-18	Sx-19	Sx-20	Sx-21	Sx-23
Hydrogen - H <sub>2</sub>		7.10	4.10	6.95	6.11	
Carbon Monoxide - CO		91.74	27.25	47.93	69.54	
Carbon Dioxide - CO <sub>2</sub>			41.18			
Hydrogen Sulfide - H <sub>2</sub> S			0.91			
Methane - CH <sub>4</sub>			17.28	29.79	15.27	
Ethane - C <sub>2</sub> H <sub>6</sub>			5.62	9.61	4.77	
Propane - C <sub>3</sub> H <sub>8</sub>			2.82	4.14	2.98	
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>		1.16	0.75	1.58	1.33	
Ammonia - NH <sub>3</sub> (PPM)			0.09			0.13
Light Oils - (0-100°C @ 1.6 Torr)	80.69					
Solvent - (100-230°C @ 1.6 Torr)	1.31					
Heavy Oil - (230-255°C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water	18.00					99.87
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon	67.93	39.32	42.68	53.96	47.51	
Hydrogen	11.99	7.10	10.12	17.07	11.42	11.12
Nitrogen	0.08	1.16	0.82	1.58	1.33	0.11
Sulfur	0.15		0.86			
Oxygen (by diff)	19.85	52.42	45.52	27.39	39.74	88.77
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/24/78

Run No: L-2F

Date: 9/11-12/77

Time: 1900-0700

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4B	S-4B	S-4A	J-1	Cold	S-7
	Oil	Total	Ovhd	Discharge	Trap	Btms
SAMPLE POINT	*Sx-23	Sx-23	Sx-30	Sx-32	Sx-33	Sx-34/39
Hydrogen - H <sub>2</sub>			1.53	0.44		
Carbon Monoxide - CO			10.55	12.22		
Carbon Dioxide - CO <sub>2</sub>			57.79	48.03		
Hydrogen Sulfide - H <sub>2</sub> S			1.90			
Methane - CH <sub>4</sub>			11.97	6.99		
Ethane - C <sub>2</sub> H <sub>6</sub>			8.51	13.10		
Propane - C <sub>3</sub> H <sub>8</sub>			7.14	19.22		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>			0.42			
Ammonia - NH <sub>3</sub> (PPM)		0.13	0.19			
Light Oils - (0-100°C @ 1.6 Torr)	76.12	1.83			47.66	17.81
Solvent - (100-230°C @ 1.6 Torr)	23.00	0.55				78.95
Heavy Oil - (230-255°C @1.6 Torr)						2.60
SRL						
Coal (MAF)						
Ash						
Water	0.88	97.49			52.34	0.64
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60	0.935					1.036
Viscosity, cp						

Carbon	81.65	1.96	41.91	49.79	28.11	87.70
Hydrogen	9.42	11.08	7.66	8.30	10.09	7.94
Nitrogen	0.20	0.11	0.58		0.05	0.26
Sulfur	0.40	0.01	1.79		0.45	1.36
Oxygen (by diff)	8.33	86.84	48.06	41.91	61.30	2.74
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	1	4

\*Insufficient oil sample. Analysis assumed to be the same as the S-4A oil

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/24/78

Run No: L-2F

Date: 9/11-12/77

Time: 1900-0700

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4A	S-4A	S-4A	S-7	Absorbed	
	Water	Oil	Total	Btms	Gas	
SAMPLE POINT	Sx-37	Sx-37	Sx-37	Sx-34/39	Calc.	
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>					97.63	
Hydrogen Sulfide - H <sub>2</sub> S					2.15	
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)	0.10				0.22	
Light Oils - (0-100° C @ 1.6 Torr)		76.12	75.83	17.81		
Solvent - (100-230° C @ 1.6 Torr)		23.00	22.91	78.95		
Heavy Oil - (230-255° C @1.6 Torr)				2.60		
SRL						
Coal (MAF)						
Ash						
Water	99.90	0.88	1.26	0.64		
Phenol						
TOTAL	100	100	100	100	100	
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60		0.935		1.036		
Viscosity, cp						

Carbon		81.65	81.34	87.70	26.63	
Hydrogen	11.12	9.42	9.42	7.94	0.17	
Nitrogen	0.08	0.20	0.20	0.26	0.18	
Sulfur		0.40	0.40	1.36	2.02	
Oxygen (by diff)	88.80	8.33	8.64	2.74	71.00	
Ash						
TOTAL	100	100	100	100	100	
Number of Sample Avg.	2	2	2	2	-	

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/24/78

Run No: L-2F

Date: 9/11-12/77

Time: 1900-0700

MOLE PERCENT

SAMPLE DESCRIPTION	MOLE PERCENT					
	Makeup Gas	Product Gas	Recycle Gas	Feed Gas	S-4A Ovhd	J-1 Discharge
SAMPLE POINT	Sx-18	Sx-19	Sx-20	Sx-21	Sx-30	Sx-32
Hydrogen - H <sub>2</sub>	51.70	38.30	46.22	45.15	20.50	7.14
Carbon Monoxide - CO	47.70	18.20	22.76	36.70	10.10	14.28
Carbon Dioxide - CO <sub>2</sub>		17.50			35.20	35.71
Hydrogen Sulfide - H <sub>2</sub> S		0.50			1.50	
Methane - CH <sub>4</sub>		20.20	24.76	14.10	20.05	14.29
Ethane - C <sub>2</sub> H <sub>6</sub>		3.50	4.26	2.35	7.60	14.29
Propane - C <sub>3</sub> H <sub>8</sub>		1.20	1.25	1.00	4.35	14.29
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.60	0.50	0.75	0.70	0.40	
Ammonia - NH <sub>3</sub> (PPM)		0.10			0.30	
Light Oils - (0-100°C @ 1.6 Torr)						
Solvent - (100-230°C @ 1.6 Torr)						
Heavy Oil - (230-255°C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100	100	100
Calc. Mole Wt.	14.56	18.70	13.30	14.78	26.80	32.71
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Quantitative

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	2

Elemental

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/24/78

Run No: L-2F  
Date: 9/11-12/77  
Time: 1900-0700

MOLE PERCENT

SAMPLE DESCRIPTION	Absorbed Gas					
	Calc					
SAMPLE POINT						
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>	96.69					
Hydrogen Sulfide - H <sub>2</sub> S	2.76					
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)	0.55					
Light Oils - (0-100° C @ 1.6 Torr)						
Solvent - (100-230° C @ 1.6 Torr)						
Heavy Oil - (230-255° C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100					
Calc Mole Wt	43.58					
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.						

PROJECT LIGNITE  
 SAMPLE ANALYSES  
 RUN NO: L-2F  
 DATE: 9/11-12/77  
 TIME: 1900-0700

SAMPLE DESCRIPTION	F-1 Btms	LEC Btms	Feed Soly	S-8 Oil	S-7 Btms
SAMPLE POINT	Sx-2	Sx-12	Sx-14	Sx-16	Sx-34/39
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR		5	5		5
IBP		24.2	41.5		54
5%		51.6	76.5		85.6
10%		62.0	90.0		98.2
20%		71.5	116.		139.2
30%		78.8	146.3		159.4
40%		88.8	166		173.6
50%		98.2	176		181.6
60%		112.0	183		187.8
70%		128.8	189		191.2
80%		157.8	197		202.4
90%		180.6	217		226.2
95%		194.6	249		260
DRY PT.		195.3	254		260
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR				741	
IBP				45	
5%				52	
10%				57	
20%				64	
30%				72	
40%				80	
50%				88	
60%				97	
70%				107	
80%				121	
90%				129	
95%					
DRY PT.				132	
ASPHALTENE TEST					
WT % ASH	13.16				
WT % UNCONVERTED COAL	13.08				
WT % PRE-ASPHALTENES	26.96				
WT % ASPHALTENES	22.10				
WT % MALTENES & DIST. OIL	24.70				
TOTAL	100.00				
SAYBOLT VISCOSITY, SSU					
100° F		8.9	11.8		11.8
210° F		8.2	8.5		8.7
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)			0.49		0.64
INFRARED RATIO		0.16	0.29		0.30
SP. GRAV. 60/60 F		0.959	1.030		1.036


PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
 ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
 MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
 DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.

PROJECT LIGNITE  
 SAMPLE ANALYSES  
 RUN NO: L-2F  
 DATE: 9/11-12/77  
 TIME: 1900-0700

SAMPLE DESCRIPTION		S-4A 011			
SAMPLE POINT		Sx-37			
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR					
VOLUME PERCENT IBP 5% 10% 20% 30% 40% 50% 60% 70% 80% 90% 95% DRY PT.	TEMPERATURE, °C				
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR		741			
VOLUME PERCENT IBP 5% 10% 20% 30% 40% 50% 60% 70% 80% 90% 95% DRY PT.	TEMPERATURE, °C	80			
		89			
		149			
		179			
		192			
		206			
		219			
		239			
		261			
		302			
		320			
ASPHALTENE TEST					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
SAYBOLT VISCOSITY, SSU					
100° F					
210° F					
MISCELLANEOUS					
KF H <sub>2</sub> O WT % (Row Sx)		0.88			
INFRARED RATIO					
SP. GRAV. 60/60 F		0.935			

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
 ASPHALTENES - BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
 MALTENES - N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
 DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.

DISTILLABLE OIL CONTENT OF F-I BOTTOMS  
VERSUS  
F-I BOTTOMS MELTING POINT



**PROJECT LIGNITE**  
**MEASURED MATERIAL BALANCE**  
 Revised: 2/24/78

Run No: L-2F  
 Date: 9/11-12/77  
 Time: 1900-0700

MATERIAL IN  
 lbs/hr.

Temperature: 726°F  
 Pressure: 2460 psig  
 LHSV: 1.41  
 GHSV: 354

STREAM DESCRIPTION	← Feed Gas →		Gas →		Feed Solvent	Total In
	Recycle Gas	Makeup Gas	Lignite			
SAMPLE POINT	Sx-20	Sx-18	Sx-1	Sx-14		
Hydrogen - H <sub>2</sub>	0.59	0.79				1.38
Carbon Monoxide - CO	4.09	10.27				14.36
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>	2.54					2.54
Ethane - C <sub>2</sub> H <sub>6</sub>	0.82					0.82
Propane - C <sub>3</sub> H <sub>8</sub>	0.36					0.36
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.13	0.13				0.26
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)					19.78	19.78
Solvent - (100-230°C @ 1.6 Torr)					70.46	70.46
Heavy Oil - (230-255°C @ 1.6 Torr)					2.14	2.14
SRL						
Coal (MAF)			28.12			28.12
Ash			2.89			2.89
Water			15.49	0.45		15.94
Phenol						
<b>TOTAL</b>	<b>8.53</b>	<b>11.19</b>	<b>46.50</b>	<b>92.83</b>		<b>159.05</b>

Carbon	4.60	4.40	20.17	81.25		110.42
Hydrogen	1.46	0.79	3.01	7.59		12.85
Nitrogen	0.13	0.13	0.26	0.24		0.76
Sulfur			0.29	1.22		1.51
Oxygen (by diff)	2.34	5.87	19.88	2.53		30.62
Ash			2.89			2.89
<b>TOTAL</b>	<b>8.53</b>	<b>11.19</b>	<b>46.50</b>	<b>92.83</b>		<b>159.05</b>

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 2/24/78

Run No: L-2F  
Date: 9/11-12/77  
Time: 1900-0700

MATERIAL OUT

Temperature: 726°F  
Pressure: 2460 psig  
LHSV: 1.41  
GHSV: 354

lbs/hr.

STREAM DESCRIPTION	Product Gas			S-4A	S-4B	S-8
	Vent Gas	Recycle Gas	Absorbed Gas	Gas Ovhd	Btms	Ovhd
SAMPLE POINT	Sx-20	Sx-20	Calc	Sx-30	Sx-23	Sx-44
Hydrogen - H <sub>2</sub>	0.21	0.59		0.07		
Carbon Monoxide - CO	1.44	4.09		0.51		
Carbon Dioxide - CO <sub>2</sub>			8.08	2.77		
Hydrogen Sulfide - H <sub>2</sub> S			0.18	0.09		
Methane - CH <sub>4</sub>	0.90	2.54		0.57		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.29	0.82		0.41		
Propane - C <sub>3</sub> H <sub>8</sub>	0.12	0.36		0.34		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.05	0.13		0.02		
Ammonia - NH <sub>3</sub>			0.02	0.01	0.02	
Light Oil - (0-100°C @ 1.6 Torr)					0.26	
Solvent - (100-230°C @ 1.6 Torr)					0.08	
Heavy Oil - (230-255°C @1.6 Torr)						
SRL						
Cool (MAF)						
Ash						
Water					13.81	
Phenol						
TOTAL	3.01	8.53	8.28	4.79	14.17	Negl.

Carbon	1.62	4.60	2.20	2.01	0.28	
Hydrogen	0.51	1.46	0.01	0.37	1.57	
Nitrogen	0.05	0.13	0.02	0.03	0.02	
Sulfur			0.17	0.08		
Oxygen (by diff)	0.83	2.34	5.88	2.30	12.30	
Ash						
TOTAL	3.01	8.53	8.28	4.79	14.17	Negl.

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 2/24/78

Run No: L-2F  
Date: 9/11-12/77  
Time: 1900-0700

MATERIAL OUT

Temperature: 726°F  
Pressure: 2460 psig  
LHSV: 1.41  
GHSV: 354

	S-8 Btms	J-1 Exhaust	Cold Trap	F-1 Btms	←Recycle Solvent→ S-7 Btms	LEC Btms
STREAM DESCRIPTION	Sx-16	Sx-32	Sx-33	Sx-2	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO		0.07				
Carbon Dioxide - CO <sub>2</sub>		0.27				
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>		0.04				
Ethane - C <sub>2</sub> H <sub>6</sub>		0.08				
Propane - C <sub>3</sub> H <sub>8</sub>		0.11				
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	1.21		0.13		13.18	13.15
Solvent - (100-230°C @ 1.6 Torr)	0.02			2.38	58.41	6.50
Heavy Oil - (230-255°C @1.6 Torr)					1.92	0.10
SRL				11.57		
Cool (MAF)				2.47		
Ash				2.49		
Water	0.27		0.15		0.47	
Phenol						
<b>TOTAL</b>	<b>1.50</b>	<b>0.57</b>	<b>0.28</b>	<b>18.91</b>	<b>73.98</b>	<b>19.75</b>

Carbon	1.02	0.28	0.08	14.56	64.88	16.61
Hydrogen	0.18	0.05	0.03	0.90	5.87	1.83
Nitrogen				0.18	0.19	0.05
Sulfur				0.21	1.01	0.09
Oxygen (by diff)	0.30	0.24	0.17	0.57	2.03	1.17
Ash				2.49		
<b>TOTAL</b>	<b>1.50</b>	<b>0.57</b>	<b>0.28</b>	<b>18.91</b>	<b>73.98</b>	<b>19.75</b>



RUN CONDITIONS

RUN NO. L-2G  
 DATE MADE 9/12/77

TEMPERATURE °F

PRESSURE, psig

PREHEATER E-1  
 SAND BATH 740  
 INLET 305  
 OUTLET 721

DISSOLVERS  
 R-1A (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_  
 (4) \_\_\_\_\_  
 R-1B (1) 745  
 (2) 788  
 (3) 824  
 (4) 829

REACTOR PRODUCT SEPARATORS  
 S-1 548  
 S-2 88  
 S-3 507  
 S-4A 94  
 S-4B 81

PREHEATER E-11  
 DOWTHERM 685  
 INLET 446  
 OUTLET 646

VACUUM FLASH F-1  
 OVERHEAD VAPOR 505  
 UPPER WALL 620  
 LOWER WALL 584  
 DOWNCOMER 528  
 CONDENSATE  
 ACCUMULATOR, S-7 97

PREHEATER E-13  
 DOWTHERM 408  
 INLET 91  
 OUTLET 178

LIGHT ENDS COLUMN, F-2  
 REBOILER 282  
 LOWER SECTION 215  
 FEED SECTION 216  
 OVERHEAD 176  
 S-8 77  
 S-9 -

SOLVENT COLUMN, F-3  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

HEAVY ENDS COLUMN, F-4  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

VACUUM FLASH, F-0  
 OVERHEAD NIU  
 BOTTOMS \_\_\_\_\_

PRECIPITATION TOWER, V-8  
 ZONE (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_

RECOVERY TOWER V-9  
 REBOILER NIU  
 OVERHEAD \_\_\_\_\_

SEPARATORS S-1 and S-2  
2460

SEPARATOR S-3  
240

SEPARATORS S-4A and S-4B  
60

VACUUM FLASH, F-1  
14 Torr

LIGHT ENDS COLUMN, F-2  
Atm

SOLVENT COLUMN, F-3  
NIU

HEAVY ENDS COLUMN, F-4  
NIU


VACUUM FLASH, F-0  
NIU

SETTLING TOWER, V-8  
NIU

RECOVERY TOWER, V-7  
NIU

	Start	End	Run No: L-2G
Date of Run	9/12/77	9/12/77	Units: lbs/hr, °F, psig
Time of Run	0700	1900	Prep. By: BCL & GGB
Length of Run	12	hrs.	Updated: 2/24/78
Hours on Coal at End of Y. P.	318.1		

### MASS RATES AND RUN CONDITIONS



158.20 TOTAL

OPEN

CLOSED

TOTAL 158.20

Numbers in parentheses are not included in the totals.



PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product & Recycle Gas Rates Adjusted  
 Revised: 2/24/78

Run No: L-2G  
 Date: 9/12/77  
 Time: 0700-1900

MATERIAL IN

lbs/hr.

Temperature: 721°F  
 Pressure: 2460 psig  
 LHSV: 1.40  
 GHSV: 358

STREAM DESCRIPTION	← Feed	Gas →	Lignite	Feed Solvent	Total In.
	Recycle Gas	Makeup Gas			
SAMPLE POINT	Sx-20	Sx-18	Sx-1	Sx-14	
Hydrogen - H <sub>2</sub>	0.60	0.90			1.50
Carbon Monoxide - CO	5.09	9.31			14.40
Carbon Dioxide - CO <sub>2</sub>					
Hydrogen Sulfide - H <sub>2</sub> S					
Methane - CH <sub>4</sub>	2.66				2.66
Ethane - C <sub>2</sub> H <sub>6</sub>	0.86				0.86
Propane - C <sub>3</sub> H <sub>8</sub>	0.40				0.40
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.18	0.14			0.32
Ammonia - NH <sub>3</sub>					
Light Oil - (0-100°C @ 1.6 Torr)				24.14	24.14
Solvent - (100-230°C @ 1.6 Torr)				64.54	64.54
Heavy Oil - (230-255°C @ 1.6 Torr)				1.79	1.79
SRL					
Coal (MAF)			28.77		28.77
Ash			2.85		2.85
Water			15.55	0.42	15.97
Phenol					
TOTAL	9.79	10.35	47.17	90.89	158.20

Carbon	5.19	3.99	20.25	79.04	108.47
Hydrogen	1.51	0.90	3.09	7.86	13.36
Nitrogen	0.18	0.14	0.26	0.27	0.85
Sulfur			0.29	1.01	1.30
Oxygen (by diff)	2.91	5.32	20.43	2.71	31.37
Ash			2.85		2.85
TOTAL	9.79	10.35	47.17	90.89	158.20

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product & Recycle Gas Rates Adjusted  
 Revised: 2/24/78

Run No: L-2G  
 Date: 9/12/77  
 Time: 0700-1900

MATERIAL OUT

Temperature: 721°F  
 Pressure: 2460 psig  
 LHSV: 1.40  
 GHSV: 358

STREAM DESCRIPTION	Product Gas			S-4A Ovhd	S-4B Btms	S-8 Ovhd
	Vent Gas	Recycle Gas	Absorbed Gas			
SAMPLE POINT	Sx-20	Sx-20	Calc	Sx-30	Sx-23	Sx-44
Hydrogen - H <sub>2</sub>	0.33	0.60		0.08		
Carbon Monoxide - CO	2.79	5.09		0.77		
Carbon Dioxide - CO <sub>2</sub>			9.72	2.82		
Hydrogen Sulfide - H <sub>2</sub> S			0.25	0.12		
Methane - CH <sub>4</sub>	1.45	2.66		0.52		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.47	0.86		0.37		
Propane - C <sub>3</sub> H <sub>8</sub>	0.22	0.40		0.28		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.10	0.18		0.03		
Ammonia - NH <sub>3</sub>			0.04		0.02	
Light Oil - (0-100°C @ 1.6 Torr)						
Solvent - (100-230°C @ 1.6 Torr)						
Heavy Oil - (230-255°C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water					14.19	
Phenol						
TOTAL	5.36	9.79	10.01	4.99	14.21	Negl.

Carbon	2.84	5.19	2.65	2.02		
Hydrogen	0.83	1.51	0.02	0.34	1.58	
Nitrogen	0.10	0.18	0.04	0.03	0.02	
Sulfur			0.23	0.11		
Oxygen (by diff)	1.59	2.91	7.07	2.49	12.61	
Ash						
TOTAL	5.36	9.79	10.01	4.99	14.21	Negl.

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product & Recycle Gas Rates Adjusted  
 Revised: 2/24/78

Run No: L-2G  
 Date: 9/12/77  
 Time: 0700-1900

MATERIAL OUT  
 lbs/hr.

Temperature: 721°F  
 Pressure: 2460 psig  
 LHSV: 1.40  
 GHSV: 358

STREAM DESCRIPTION	S-8	J-1	Cold	F-1	← Recycle Solvent →	
	Btms	Exhaust	Trap	Btms	S-7 Btms	F-2 Btms
SAMPLE POINT	Sx-16	Sx-32	Sx-33	Sx-2	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO		0.13				
Carbon Dioxide - CO <sub>2</sub>		0.29				
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>		0.03				
Ethane - C <sub>2</sub> H <sub>6</sub>		0.06				
Propane - C <sub>3</sub> H <sub>8</sub>		0.03				
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	1.50		0.44		16.15	16.05
Solvent - (100-230°C @ 1.6 Torr)	0.02			2.30	51.32	7.21
Heavy Oil - (230-255°C @ 1.6 Torr)					1.99	
SRL				11.21		
Cool (MAF)				2.40		
Ash				2.41		
Water			0.03		0.27	
Phenol						
<b>TOTAL</b>	<b>1.52</b>	<b>0.54</b>	<b>0.47</b>	<b>18.32</b>	<b>69.73</b>	<b>23.26</b>

Carbon	1.21	0.23	0.37	14.11	60.25	19.68
Hydrogen	0.20	0.03	0.04	0.87	5.63	2.18
Nitrogen				0.18	0.21	0.06
Sulfur				0.20	0.86	0.09
Oxygen (by diff)	0.11	0.28	0.06	0.55	2.78	1.25
Ash				2.41		
<b>TOTAL</b>	<b>1.52</b>	<b>0.54</b>	<b>0.47</b>	<b>18.32</b>	<b>69.73</b>	<b>23.26</b>

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product & Recycle Gas Rates Adjusted  
 Revised: 2/24/78

Run No: L-2G  
 Date: 9/12/77  
 Time: 0700-1900

MATERIAL OUT  
 lbs/hr.

Temperature: 721°F  
 Pressure: 2460 psig  
 LHSV: 1.40  
 GHSV: 358

STREAM DESCRIPTION					Total Out
SAMPLE POINT					
Hydrogen - H <sub>2</sub>					1.01
Carbon Monoxide - CO					8.78
Carbon Dioxide - CO <sub>2</sub>					12.83
Hydrogen Sulfide - H <sub>2</sub> S					0.37
Methane - CH <sub>4</sub>					4.66
Ethane - C <sub>2</sub> H <sub>6</sub>					1.76
Propane - C <sub>3</sub> H <sub>8</sub>					0.93
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					0.31
Ammonia - NH <sub>3</sub>					0.06
Light Oil - (0-100°C @ 1.6 Torr)					34.14
Solvent - (100-230°C @ 1.6 Torr)					60.85
Heavy Oil - (230-255°C @1.6 Torr)					1.99
SRL					11.21
Coal (MAF)					2.40
Ash					2.41
Water					14.49
Phenol					
TOTAL					158.20
Carbon					108.55
Hydrogen					13.23
Nitrogen					0.82
Sulfur					1.49
Oxygen (by diff)					31.70
Ash					2.41
TOTAL					158.20

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/24/78

Run No: L-2G

Date: 9/12/77

Time: 0700-1900

WEIGHT PERCENT

SAMPLE DESCRIPTION	Lignite	F-1 Btms	LEC Btms	Feed Solvent	S-8 Water	S-8 Oil
	Sx-1	Sx-2	Sx-12	Sx-14	Sx-16	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100°C @ 1.6 Torr)			69.00	26.56		98.40
Solvent - (100-230°C @ 1.6 Torr)		12.57	31.00	71.01		1.60
Heavy Oil - (230-255°C @1.6 Torr)				1.97		
SRL		61.19				
Coal (MAF)	60.99	13.08				
Ash	6.05	13.16				
Water	32.96			0.46	100	
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		84.94				
Melting Point °F		330				
Specific Gravity 60/60			0.960	1.027		
Viscosity, cp						

Elemental	Quantitative					
	Lignite	F-1 Btms	LEC Btms	Feed Solvent	S-8 Water	S-8 Oil
	Sx-1	Sx-2	Sx-12	Sx-14	Sx-16	Sx-16
Carbon	42.93	77.00	84.60	86.96		79.45
Hydrogen	6.55	4.75	9.38	8.65	11.11	12.94
Nitrogen	0.55	0.97	0.28	0.30		0.01
Sulfur	0.62	1.10	0.38	1.11		0.20
Oxygen (by diff)	43.30	3.02	5.36	2.98	88.89	7.40
Ash	6.05	13.16				
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	4	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/24/78

Run No: L-2G

Date: 9/12/77

Time: 0700-1900

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-8	Makeup	Product	Recycle	Feed	S-4B
	Total	Gas	Gas	Gas	Gas	Water
SAMPLE POINT	Sx-16	Sx-18	Sx-19	Sx-20	Sx-21	Sx-23
Hydrogen - H <sub>2</sub>		8.65	4.09	6.16	6.05	
Carbon Monoxide - CO		89.97	27.05	52.03	72.51	
Carbon Dioxide - CO <sub>2</sub>			42.39			
Hydrogen Sulfide - H <sub>2</sub> S			1.08			
Methane - CH <sub>4</sub>			16.31	27.13	13.08	
Ethane - C <sub>2</sub> H <sub>6</sub>			5.34	8.80	4.34	
Propane - C <sub>3</sub> H <sub>8</sub>			2.45	4.08	2.18	
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>		1.38	1.11	1.80	1.84	
Ammonia - NH <sub>3</sub> (PPM)			0.18			0.15
Light Oils - (0-100°C @ 1.6 Torr)	98.40					
Solvent - (100-230°C @ 1.6 Torr)	1.60					
Heavy Oil - (230-255°C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						99.85
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon	79.45	38.56	41.65	53.03	46.14	
Hydrogen	12.94	8.65	9.78	15.44	10.59	11.12
Nitrogen	0.01	1.38	1.11	1.80	1.84	0.12
Sulfur	0.20		1.17			
Oxygen (by diff)	7.40	51.41	46.29	29.73	41.43	88.76
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/24/78

Run No: L-2G

Date: 9/12/77

Time: 0700-1900

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4B	S-4B	S-4A	J-1	Cold	S-7
	Oil	Total	Ovhd	Discharge	Trap	Btms
SAMPLE POINT	*Sx-23	Sx-23	Sx-30	Sx-32	Sx-33	Sx-34/39
Hydrogen - H <sub>2</sub>			1.52	0.90		
Carbon Monoxide - CO			15.37	23.92		
Carbon Dioxide - CO <sub>2</sub>			56.50	53.51		
Hydrogen Sulfide - H <sub>2</sub> S			2.41			
Methane - CH <sub>4</sub>			10.48	5.10		
Ethane - C <sub>2</sub> H <sub>6</sub>			7.48	10.20		
Propane - C <sub>3</sub> H <sub>8</sub>			5.57	6.37		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>			0.57			
Ammonia - NH <sub>3</sub> (PPM)		0.15	0.10			
Light Oils - (0-100° C @ 1.6 Torr)	77.93				93.98	23.16
Solvent - (100-230° C @ 1.6 Torr)	21.30					73.60
Heavy Oil - (230-255° C @1.6 Torr)						2.85
SRL						
Coal (MAF)						
Ash						
Water	0.77	99.85			6.02	0.39
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60	0.938					1.039
Viscosity, cp						

Elemental	Quantitative					
	S-4B Oil	S-4B Total	S-4A Ovhd	J-1 Discharge	Cold Trap	S-7 Btms
Carbon	83.82		40.40	42.03	78.14	86.40
Hydrogen	10.03	11.12	6.81	5.38	8.52	8.08
Nitrogen	0.22	0.12	0.65		0.30	0.30
Sulfur	0.42		2.27		0.18	1.24
Oxygen (by diff)	5.51	88.76	49.87	52.59	12.86	3.98
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	2

\*Insufficient sample available. Assumed to be the same as the S-4A oil.

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/24/78

Run No: L-2G

Date: 9/12/77

Time: 0700-1900

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4A Water	S-4A Oil	S-4A Total	S-7 Btms	Absorbed Gas	
SAMPLE POINT	Sx-37	Sx-37	Sx-37	Sx-34/39	Calc.	
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>					97.11	
Hydrogen Sulfide - H <sub>2</sub> S					2.48	
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)	0.14		0.01		0.41	
Light Oils - (0-100°C @ 1.6 Torr)		77.93	73.29	23.16		
Solvent - (100-230°C @ 1.6 Torr)		21.30	20.03	73.60		
Heavy Oil - (230-255°C @1.6 Torr)				2.85		
SRL						
Coal (MAF)						
Ash						
Water	99.86	0.77	6.67	0.39		
Phenol						
TOTAL	100	100	100	100	100	
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60		0.938		1.039		
Viscosity, cp						
Carbon		83.82	78.82	86.40	26.48	
Hydrogen	11.11	10.03	10.09	8.08	0.22	
Nitrogen	0.12	0.22	0.22	0.30	0.34	
Sulfur		0.42	0.40	1.24	2.33	
Oxygen (by diff)	88.77	5.51	10.47	3.98	70.63	
Ash						
TOTAL	100	100	100	100	100	
Number of Sample Avg.	2	2	2	2	-	

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/24/78

Run No: L-2G  
Date: 9/12/77  
Time: 0700-1900

MOLE PERCENT

SAMPLE DESCRIPTION	Makeup	Product	Recycle	Feed	S-4A	J-1
	Gas	Gas	Gas	Gas	Ovhd	Discharge
SAMPLE POINT	Sx-18	Sx-19	Sx-20	Sx-21	Sx-30	Sx-32
Hydrogen - H <sub>2</sub>	57.00	38.50	43.46	45.22	20.45	13.61
Carbon Monoxide - CO	42.35	18.20	26.24	38.69	14.75	25.68
Carbon Dioxide - CO <sub>2</sub>		18.15			34.50	36.56
Hydrogen Sulfide - H <sub>2</sub> S		0.60			1.90	
Methane - CH <sub>4</sub>		19.20	23.94	12.21	17.60	9.58
Ethane - C <sub>2</sub> H <sub>6</sub>		3.35	4.14	2.16	6.70	10.22
Propane - C <sub>3</sub> H <sub>8</sub>		1.05	1.31	0.74	3.40	4.35
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.65	0.75	0.91	0.98	0.55	
Ammonia - NH <sub>3</sub> (PPM)		0.20			0.15	
Light Oils - (0-100°C @ 1.6 Torr)						
Solvent - (100-230°C @ 1.6 Torr)						
Heavy Oil - (230-255°C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100	100	100
Calc. Mole Wt.	13.18	18.84	14.12	14.94	26.87	30.06
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Elemental	Carbon						
	Hydrogen						
	Nitrogen						
	Sulfur						
	Oxygen (by diff)						
	Ash						
	TOTAL						
	Number of Sample Avg.	2	2	2	3	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/24/78

Run No: L-2G

Date: 9/12/77

Time: 0700-1900

MOLE PERCENT

Quantitative	SAMPLE DESCRIPTION	Absorbed Gas				
	SAMPLE POINT	Calc.				
	Hydrogen - H <sub>2</sub>					
	Carbon Monoxide - CO					
	Carbon Dioxide - CO <sub>2</sub>	95.78				
	Hydrogen Sulfide - H <sub>2</sub> S	3.17				
	Methane - CH <sub>4</sub>					
	Ethane - C <sub>2</sub> H <sub>6</sub>					
	Propane - C <sub>3</sub> H <sub>8</sub>					
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					
	Ammonia - NH <sub>3</sub> (PPM)	1.05				
	Light Oils - (0-100° C @ 1.6 Torr)					
	Solvent - (100-230° C @ 1.6 Torr)					
	Heavy Oil - (230-255° C @ 1.6 Torr)					
	SRL					
	Coal (MAF)					
	Ash					
	Water					
	Phenol					
TOTAL	100					
Calc Mole Wt.	43.40					
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	TOTAL					
	Number of Sample Avg.					

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: L-2G  
DATE: 9/12/77  
TIME: 0700-1900

SAMPLE DESCRIPTION	F-1 Btms	LEC Btms	Feed Solv.	S-8 Btms	S-7 Btms
SAMPLE POINT	Sx-2	Sx-12	Sx-14	Sx-16	Sx-34/39
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR		5	5		5
IBP		32.4	40.8		52.5
5%		47.2	75.4		67.3
10%		59.4	85.8		89.6
20%		71.3	105.4		114.2
30%		78.8	129.2		140
40%		86.2	155.2		166.6
50%		95.4	172.2		174.4
60%		107.8	179.5		181.8
70%		125.5	187.8		189.9
80%		152.8	198.2		200.6
90%		180.4	224		226.3
95%		199.2	259.6		260
DRY PT.		199.2			260
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR				732	
IBP				48	
5%				58	
10%				63	
20%				71	
30%				81	
40%				91	
50%				98	
60%				108	
70%				116	
80%				128	
90%				138	
95%					
DRY PT.				147	
ASPHALTENE TEST					
WT % ASH	13.16				
WT % UNCONVERTED COAL	13.08				
WT % PRE-ASPHALTENES	26.96				
WT % ASPHALTENES	22.10				
WT % MALTENES & DIST. OIL	24.70				
TOTAL	100.00				
SAYBOLT VISCOSITY, SSU					
100° F		8.7	11.4		11.9
210° F		7.9	8.8		8.6
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Row Sx)			0.46		0.39
INFRARED RATIO		0.22	0.28		0.31
SP. GRAV. 60/60 F		0.960	1.027		1.040


PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.

PROJECT LIGNITE  
 SAMPLE ANALYSES  
 RUN NO: L-2G  
 DATE: 9/12/77  
 TIME: 0700-1900

SAMPLE DESCRIPTION	S-4A 011				
SAMPLE POINT	Sx-37				
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR					
IBP					
5%					
10%					
20%					
30%					
40%					
50%					
60%					
70%					
80%					
90%					
95%					
DRY PT.					
VOLUME PERCENT	TEMPERATURE, °C				
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR	741				
IBP	81				
5%	87				
10%	152				
20%	179				
30%	193				
40%	204				
50%	216				
60%	232				
70%	253				
80%	295				
90%	323				
95%					
DRY PT.	324				
VOLUME PERCENT	TEMPERATURE, °C				
ASPHALTENE TEST					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
SAYBOLT VISCOSITY, SSU					
100° F					
210° F					
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Raw Sx)	0.77				
INFRARED RATIO					
SP. GRAV. 60/60 F					

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
 ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
 MALTENES- N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
 DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.

DISTILLABLE OIL CONTENT OF F-I BOTTOMS  
VERSUS  
F-I BOTTOMS MELTING POINT



PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 2/24/78

Run No: L-2G  
Date: 9/12/77  
Time: 0700-1900

MATERIAL IN

Temperature: 721°F  
Pressure: 2460 psig  
LHSV: 1.40  
GHSV: 358

	← Feed Gas →		Lignite	Feed Solvent		Total In
	Recycle Gas	Makeup Gas				
STREAM DESCRIPTION	Sx-20	Sx-18	Sx-1	Sx-14		
SAMPLE POINT						
Hydrogen - H <sub>2</sub>	0.54	0.98				1.52
Carbon Monoxide - CO	4.56	10.24				14.80
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>	2.37					2.37
Ethane - C <sub>2</sub> H <sub>6</sub>	0.77					0.77
Propane - C <sub>3</sub> H <sub>8</sub>	0.36					0.36
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.16	0.16				0.32
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)				24.14		24.14
Solvent - (100-230°C @ 1.6 Torr)				64.54		64.54
Heavy Oil - (230-255°C @ 1.6 Torr)				1.79		1.79
SRL						
Coal (MAF)			28.77			28.77
Ash			2.85			2.85
Water			15.55	0.42		15.97
Phenol						
<b>TOTAL</b>	<b>8.76</b>	<b>11.38</b>	<b>47.17</b>	<b>90.89</b>		<b>158.20</b>

Carbon	4.65	4.39	20.25	79.04		108.33
Hydrogen	1.35	0.98	3.09	7.86		13.28
Nitrogen	0.16	0.16	0.26	0.27		0.85
Sulfur			0.29	1.01		1.30
Oxygen (by diff)	2.60	5.85	20.43	2.71		31.59
Ash			2.85			2.85
<b>TOTAL</b>	<b>8.76</b>	<b>11.38</b>	<b>47.17</b>	<b>90.89</b>		<b>158.20</b>

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 2/24/78

Run No: L-2G  
Date: 9/12/77  
Time: 0700-1900

MATERIAL OUT

lbs/hr.

Temperature: 721°F  
Pressure: 2460 psig  
LHSV: 1.40  
GHSV: 358

STREAM DESCRIPTION	Product Gas			S-4A Ovhd	S-4B Btms	S-8 Ovhd
	Vent Gas	Recycle Gas	Absorbed Gas			
SAMPLE POINT	Sx-20	Sx-20	Calc	Sx-30	Sx-23	Sx-44
Hydrogen - H <sub>2</sub>	0.21	0.54		0.08		
Carbon Monoxide - CO	1.75	4.56		0.77		
Carbon Dioxide - CO <sub>2</sub>			7.60	2.82		
Hydrogen Sulfide - H <sub>2</sub> S			0.20	0.12		
Methane - CH <sub>4</sub>	0.91	2.37		0.52		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.30	0.77		0.37		
Propane - C <sub>3</sub> H <sub>8</sub>	0.14	0.36		0.28		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.06	0.16		0.03		
Ammonia - NH <sub>3</sub>			0.03		0.02	
Light Oil - (0-100°C @ 1.6 Torr)						
Solvent - (100-230°C @ 1.6 Torr)						
Heavy Oil - (230-255°C @1.6 Torr)						
SRL						
Cool (MAF)						
Ash						
Water					14.19	
Phenol						
<b>TOTAL</b>	<b>3.37</b>	<b>8.76</b>	<b>7.83</b>	<b>4.99</b>	<b>14.21</b>	<b>Negl.</b>

Carbon	1.79	4.65	2.07	2.02		
Hydrogen	0.52	1.35	0.02	0.34	1.58	
Nitrogen	0.06	0.16	0.03	0.03	0.02	
Sulfur			0.18	0.11		
Oxygen (by diff)	1.00	2.60	5.53	2.49	12.61	
Ash						
<b>TOTAL</b>	<b>3.37</b>	<b>8.76</b>	<b>7.83</b>	<b>4.99</b>	<b>14.21</b>	<b>Negl.</b>

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 2/24/78

Run No: L-2G  
Date: 9/12/77  
Time: 0700-1900

MATERIAL OUT

Temperature: 721°F  
Pressure: 2460 psig  
LHSV: 1.40  
GHSV: 358

lbs/hr.

STREAM DESCRIPTION	S-8	J-1	Cold	F-1	← Recycle Solvent →	
	Btms	Exhaust	Trap	Btms	S-7 Btms	F-2 Btms
SAMPLE POINT	Sx-16	Sx-32	Sx-33	Sx-2	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO		0.13				
Carbon Dioxide - CO <sub>2</sub>		0.29				
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>		0.03				
Ethane - C <sub>2</sub> H <sub>6</sub>		0.06				
Propane - C <sub>3</sub> H <sub>8</sub>		0.03				
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	1.50		0.44		16.15	16.05
Solvent - (100-230°C @ 1.6 Torr)	0.02			2.30	51.32	7.21
Heavy Oil - (230-255°C @1.6 Torr)					1.99	
SRL				11.21		
Coal (MAF)				2.40		
Ash				2.41		
Water			0.03		0.27	
Phenol						
<b>TOTAL</b>	<b>1.52</b>	<b>0.54</b>	<b>0.47</b>	<b>18.32</b>	<b>69.73</b>	<b>23.26</b>

Carbon	1.21	0.23	0.37	14.11	60.25	19.68
Hydrogen	0.20	0.03	0.04	0.87	5.63	2.18
Nitrogen				0.18	0.21	0.06
Sulfur				0.20	0.86	0.09
Oxygen (by diff)	0.11	0.28	0.06	0.55	2.78	1.25
Ash				2.41		
<b>TOTAL</b>	<b>1.52</b>	<b>0.54</b>	<b>0.47</b>	<b>18.32</b>	<b>69.73</b>	<b>23.26</b>



RUN CONDITIONS

RUN NO. L-2H  
 DATE MADE 9/19/77

TEMPERATURE °F

PRESSURE, psig

PREHEATER E-I  
 SAND BATH 748  
 INLET 212  
 OUTLET 729

DISSOLVERS  
 R-1A (1) 777  
 (2) 786  
 (3) 786  
 (4) 785  
 R-1B (1) \_\_\_\_\_  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_  
 (4) \_\_\_\_\_

REACTOR PRODUCT SEPARATORS  
 S-1 578  
 S-2 76  
 S-3 488  
 S-4A 78  
 S-4B 76

PREHEATER E-II  
 DOWTHERM 684  
 INLET 426  
 OUTLET 656

VACUUM FLASH F-1  
 OVERHEAD VAPOR 496  
 UPPER WALL 604  
 LOWER WALL 591  
 DOWNCOMER 559  
 CONDENSATE  
 ACCUMULATOR, S-7 78

PREHEATER E-13  
 DOWTHERM 408  
 INLET 75  
 OUTLET 152

LIGHT ENDS COLUMN, F-2  
 REBOILER 298  
 LOWER SECTION 207  
 FEED SECTION 210  
 OVERHEAD 183  
 S-8 72  
 S-9 -

SOLVENT COLUMN, F-3  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

HEAVY ENDS COLUMN, F-4  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

VACUUM FLASH, F-0  
 OVERHEAD NIU  
 BOTTOMS \_\_\_\_\_

PRECIPITATION TOWER, V-8  
 ZONE (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_

RECOVERY TOWER V-9  
 REBOILER NIU  
 OVERHEAD \_\_\_\_\_

SEPARATORS S-1 and S-2  
2450  
 SEPARATOR S-3  
240  
 SEPARATORS S-4A and S-4B  
60  
 VACUUM FLASH, F-1  
14 Torr  
 LIGHT ENDS COLUMN, F-2  
0  
 SOLVENT COLUMN, F-3  
NIU  
 HEAVY ENDS COLUMN, F-4  
NIU  
 VACUUM FLASH, F-0  
NIU  
 SETTLING TOWER, V-8  
NIU  
 RECOVERY TOWER, V-7  
NIU



PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE

Product Gas Rate Adjusted Followed by a Forced Carbon Balance  
Revised: 2/23/78

Run No: L-2H  
Date: 9/19/77  
Time: 0200-1400

SUMMARY

Temperature: 729°F  
Pressure: 2450 psig  
LHSV: 1.40  
GHSV: 332

lbs/hr.

STREAM DESCRIPTION	Total In	Total Out	Net Yield		Wt % MAF Lignite	
SAMPLE POINT						
Hydrogen - H <sub>2</sub>	1.24	0.86	-0.38			
Carbon Monoxide - CO	15.23	5.60	-9.63			
Carbon Dioxide - CO <sub>2</sub>		15.77	15.77			
Hydrogen Sulfide - H <sub>2</sub> S		0.28	0.28			
Methane - CH <sub>4</sub>	1.20	2.25	1.05	8.27	28.36	
Ethane - C <sub>2</sub> H <sub>6</sub>	0.42	1.04	-0.62			
Propane - C <sub>3</sub> H <sub>8</sub>	0.19	0.69	0.50			
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.23	0.23	-0-			
Ammonia - NH <sub>3</sub>		0.06	0.06			
Light Oil - (0-100°C @ 1.6 Torr)	35.40	43.96	8.56			
Solvent - (100-230°C @ 1.6 Torr)	51.50	49.26	-2.24	20.54	70.44	
Heavy Oil - (230-255°C @ 1.6 Torr)	2.71	2.62	-0.09			
SRL		14.31	14.31			
Coal (MAF)	29.16	2.70	-26.46		-90.74	
Ash	2.94	2.82	-0.12		-0.41	
Water	15.83	13.60	-2.23		-7.65	
Phenol						
<b>TOTAL</b>	<b>156.05</b>	<b>156.05</b>	<b>-0-</b>			

Carbon	105.39	105.39	-0-			
Hydrogen	12.12	12.20	0.08			
Nitrogen	0.82	0.89	0.07			
Sulfur	0.89	1.02	0.13			
Oxygen (by diff)	33.89	33.73	-0.16			
Ash	2.94	2.82	-0.12			
<b>TOTAL</b>	<b>156.05</b>	<b>156.05</b>	<b>-0-</b>			

PROJECT LIGNITE  
MEASURED & ADJUSTED MATERIAL BALANCE  
Revised: 2/23/78

Run No: L-2H  
Date: 9/19/77  
Time: 0200-1400

MATERIAL IN

Temperature: 729°F  
Pressure: 2450 psig  
LHSV: 1.40  
GHSV: 332

	← Feed Gas →		Lignite	Feed Solvent	Total In
	Recycle Gas	Makeup Gas			
STREAM DESCRIPTION					
SAMPLE POINT	Sx-20	Sx-18	Sx-1	Sx-14	
Hydrogen - H <sub>2</sub>	0.47	0.77			1.24
Carbon Monoxide - CO	3.05	12.18			15.23
Carbon Dioxide - CO <sub>2</sub>					
Hydrogen Sulfide - H <sub>2</sub> S					
Methane - CH <sub>4</sub>	1.20				1.20
Ethane - C <sub>2</sub> H <sub>6</sub>	0.42				0.42
Propane - C <sub>3</sub> H <sub>8</sub>	0.19				0.19
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.13	0.10			0.23
Ammonia - NH <sub>3</sub>					
Light Oil - (0-100°C @ 1.6 Torr)				35.40	35.40
Solvent - (100-230°C @ 1.6 Torr)				51.50	51.50
Heavy Oil - (230-255°C @ 1.6 Torr)				2.71	2.71
SRL					
Cool (MAF)			29.16		29.16
Ash			2.94	0.74	2.94
Water			15.09		15.83
Phenol					
<b>TOTAL</b>	<b>5.46</b>	<b>13.05</b>	<b>47.19</b>	<b>90.35</b>	<b>156.05</b>

Carbon	2.70	5.22	21.43	76.04	105.39
Hydrogen	0.89	0.77	3.02	7.44	12.12
Nitrogen	0.13	0.10	0.27	0.32	0.82
Sulfur			0.32	0.57	0.89
Oxygen (by diff)	1.74	6.96	19.21	5.98	33.89
Ash			2.94		2.94
<b>TOTAL</b>	<b>5.46</b>	<b>13.05</b>	<b>47.19</b>	<b>90.35</b>	<b>156.05</b>

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product Gas Rate Adjusted followed by Forced Carbon Balance  
 Revised: 2/23/78

Run No: L-2H  
 Date: 9/19/77  
 Time: 0200-1400

MATERIAL OUT

Temperature: 729°F  
 Pressure: 2450 psig  
 LHSV: 1.40  
 GHSV: 332

lbs/hr.

STREAM DESCRIPTION	Product Gas			S-4A	S-4B	S-8
	Vent Gas	Recycle Gas	Absorbed Gas	Ovhd	Btms	Ovhd
SAMPLE POINT	Sx-20	Sx-20	Calc	Sx-30	Calc	Sx-44
Hydrogen - H <sub>2</sub>	0.31	0.47		0.08		
Carbon Monoxide - CO	1.99	3.05		0.53		
Carbon Dioxide - CO <sub>2</sub>			11.08	4.35		
Hydrogen Sulfide - H <sub>2</sub> S			0.20	0.08		
Methane - CH <sub>4</sub>	0.78	1.20		0.25		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.28	0.42		0.32		
Propane - C <sub>3</sub> H <sub>8</sub>	0.12	0.19		0.35		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.08	0.13		0.02		
Ammonia - NH <sub>3</sub>			0.04	0.01	0.01	
Light Oil - (0-100°C @ 1.6 Torr)					2.02	
Solvent - (100-230°C @ 1.6 Torr)					0.56	
Heavy Oil - (230-255°C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water					11.17	
Phenol						
TOTAL	3.56	5.46	11.32	5.99	13.76	Negl.

Carbon	1.76	2.70	3.02	2.14	2.11	
Hydrogen	0.58	0.89	0.02	0.27	1.49	
Nitrogen	0.08	0.13	0.03	0.03	0.02	
Sulfur			0.19	0.08	0.01	
Oxygen (by diff)	1.14	1.74	8.06	3.47	10.13	
Ash						
TOTAL	3.56	2.70	11.32	5.99	13.76	Negl.

PROJECT LIGNITE

ADJUSTED MATERIAL BALANCE

Product Gas Rate Adjusted followed by Forced Carbon Balance

Revised: 2/23/78

Temperature: 729°F

Pressure: 2450 psig

LHSV: 1.40

GHSV: 332

Run No: L-2H

Date: 9/19/77

Time: 0200-1400

MATERIAL OUT

lbs/hr.

STREAM DESCRIPTION	S-8	J-1	Cold	F-1	← Recycle	Solvent →
	Btms	Exhaust	Trap	Btms	S-7 Btms	LEC Btms
SAMPLE POINT	Sx-16	Sx-32	Sx-33	Sx-2	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO		0.03				
Carbon Dioxide - CO <sub>2</sub>		0.34				
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>		0.02				
Ethane - C <sub>2</sub> H <sub>6</sub>		0.02				
Propane - C <sub>3</sub> H <sub>8</sub>		0.03				
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	2.65		0.02		21.38	17.89
Solvent - (100-230°C @ 1.6 Torr)	0.06		0.02	0.74	40.72	7.16
Heavy Oil - (230-255°C @1.6 Torr)					2.62	
SRL				14.31		
Coal (MAF)				2.70		
Ash				2.82		
Water	1.55		0.08		0.80	
Phenol						
TOTAL	4.26	0.44	0.12	20.57	65.52	25.05

Carbon	2.16	0.16	0.04	15.40	55.54	20.36
Hydrogen	0.50	0.02	0.01	0.98	5.29	2.15
Nitrogen				0.23	0.27	0.10
Sulfur	0.01			0.21	0.46	0.06
Oxygen (by diff)	1.59	0.26	0.07	0.93	3.96	2.38
Ash				2.82		
TOTAL	4.26	0.44	0.12	20.57	65.52	25.05

**PROJECT LIGNITE  
ADJUSTED MATERIAL BALANCE**

Product Gas Rate Adjusted followed by a Forced Carbon Balance

Revised: 2/23/78

Run No: L-2H  
Date: 9/19/77  
Time: 0200-1400

MATERIAL OUT

Temperature: 729°F  
Pressure: 2450 psig  
LHSV: 1.40  
GHSV: 332

lbs/hr.

STREAM DESCRIPTION						Total
						Out
SAMPLE POINT						
Hydrogen - H <sub>2</sub>						0.86
Carbon Monoxide - CO						5.60
Carbon Dioxide - CO <sub>2</sub>						15.77
Hydrogen Sulfide - H <sub>2</sub> S						0.28
Methane - CH <sub>4</sub>						2.25
Ethane - C <sub>2</sub> H <sub>6</sub>						1.04
Propane - C <sub>3</sub> H <sub>8</sub>						0.69
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						0.23
Ammonia - NH <sub>3</sub>						0.06
Light Oil - (0-100°C @ 1.6 Torr)						43.96
Solvent - (100-230°C @ 1.6 Torr)						49.26
Heavy Oil - (230-255°C @1.6 Torr)						2.62
SRL						14.31
Cool (MAF)						2.70
Ash						2.82
Water						13.60
Phenol						
TOTAL						156.05

Quantitative

Carbon						105.39
Hydrogen						12.20
Nitrogen						0.89
Sulfur						1.02
Oxygen (by diff)						33.73
Ash						2.82
TOTAL						156.05

Elemental

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/23/78

Run No: L-2H  
Date: 9/19/77  
Time: 0200-1400

WEIGHT PERCENT

SAMPLE DESCRIPTION	Lignite	F-1 Btms	LEC Btms	Feed Solvent	S-8 Oil	S-8 Water
	SAMPLE POINT	Sx-1	*Sx-2	Sx-12	Sx-14	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100°C @ 1.6 Torr)			71.40	39.18	97.73	
Solvent - (100-230°C @ 1.6 Torr)		3.59	28.60	57.00	2.20	
Heavy Oil - (230-255°C @1.6 Torr)				3.00		
SRL		69.56				
Coal (MAF)	61.79	13.12				
Ash	6.24	13.73				
Water	31.97			0.82	0.07	100
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		84.79				
Melting Point °F		399				
Specific Gravity 60/60			0.989	1.026		
Viscosity, cp						

Carbon	45.40	74.86	81.30	84.16	79.57	
Hydrogen	6.39	4.76	8.57	8.24	12.14	11.11
Nitrogen	0.58	1.11	0.39	0.35	0.11	
Sulfur	0.68	1.04	0.24	0.63	0.11	
Oxygen (by diff)	40.71	4.50	9.50	6.62	8.07	88.89
Ash	6.24	13.73				
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	2

\*Distillable oil content calculated by following equation: Wt % Distillable oil =  
-0.1273 (F-1 Btms melting point) + 54.38. See attached graph.

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/23/78

Run No: L-2H  
Date: 9/19/77  
Time: 0200-1400

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-8 Total	Makeup Gas	Product Gas	Recycle Gas	Feed Gas	S-4B Oil
SAMPLE POINT	Sx-16	Sx-18	Sx-19	Sx-20	Sx-21	*Sx-23
Hydrogen - H <sub>2</sub>		5.87	4.30	8.64	6.52	
Carbon Monoxide - CO		93.34	27.64	55.87	82.88	
Carbon Dioxide - CO <sub>2</sub>			51.96			
Hydrogen Sulfide - H <sub>2</sub> S			0.35			
Methane - CH <sub>4</sub>			9.45	21.94	6.28	
Ethane - C <sub>2</sub> H <sub>6</sub>			3.76	7.78	2.17	
Propane - C <sub>3</sub> H <sub>8</sub>			1.80	3.39	1.07	
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>		0.79	0.72	2.38	1.08	
Ammonia - NH <sub>3</sub> (PPM)			0.02			
Light Oils - (0-100°C @ 1.6 Torr)	62.30					77.14
Solvent - (100-230°C @ 1.6 Torr)	1.40					21.50
Heavy Oil - (230-255°C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water	36.30					1.36
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						0.971
Viscosity, cp						

Elemental	S-8 Total	Makeup Gas	Product Gas	Recycle Gas	Feed Gas	S-4B Oil
Carbon	50.73	40.00	37.59	49.39	42.85	80.87
Hydrogen	11.77	5.87	7.76	16.30	8.71	9.50
Nitrogen	0.07	0.79	0.74	2.38	1.08	0.36
Sulfur	0.07		0.33			0.30
Oxygen (by diff)	37.36	53.34	53.58	31.93	47.36	8.97
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	2

\*Insufficient sample for distillation. Assumed to be the same as the S-4A oil.

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/23/78

Run No: L-2H

Date: 9/19/77

Time: 0200-1400

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4B Water	S-4B Total	S-4A Ovhd	J-1 Discharge	Cold Trap	S-4A Oil
SAMPLE POINT	Sx-23	Sx-23	Sx-30	Sx-32	Sx-33	Sx-37
Hydrogen - H <sub>2</sub>			1.28	0.56		
Carbon Monoxide - CO			8.87	6.22		
Carbon Dioxide - CO <sub>2</sub>			72.63	76.87		
Hydrogen Sulfide - H <sub>2</sub> S			1.32			
Methane - CH <sub>4</sub>			4.13	3.56		
Ethane - C <sub>2</sub> H <sub>6</sub>			5.27	5.00		
Propane - C <sub>3</sub> H <sub>8</sub>			5.93	7.79		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>			0.32			
Ammonia - NH <sub>3</sub> (PPM)	0.12	0.12	0.25			
Light Oils - (0-100° C @ 1.6 Torr)					20.01	77.14
Solvent - (100-230° C @ 1.6 Torr)					15.80	21.50
Heavy Oil - (230-255° C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water	99.88	99.88			64.19	1.36
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						0.971
Viscosity, cp						

Carbon			35.78	36.67	31.67	80.87
Hydrogen	11.12	11.12	4.56	3.87	10.41	9.50
Nitrogen	0.10	0.10	0.53		0.11	0.36
Sulfur			1.24		0.36	0.30
Oxygen (by diff)	88.78	88.78	57.89	59.46	57.45	8.97
Ash						
TOTAL	100	100	100	100	100	100
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/23/78

Run No: L-2H

Date: 9/19/77

Time: 0200-1400

WEIGHT PERCENT

	WEIGHT PERCENT					
	S-4A Water	S-4A Total	S-7 Btms	Absorbed Gas		S-4B Btms
SAMPLE DESCRIPTION						
SAMPLE POINT	Sx-37	Sx-37	Sx-34/39	Calc		Calc
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>				97.88		
Hydrogen Sulfide - H <sub>2</sub> S				1.78		
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)	0.17			0.34		0.10
Light Oils - (0-100°C @ 1.6 Torr)		74.66	32.63			14.63
Solvent - (100-230°C @ 1.6 Torr)		20.81	62.15			4.08
Heavy Oil - (230-255°C @1.6 Torr)			4.00			
SRL						
Coal (MAF)						
Ash						
Water	99.83	4.53	1.22			81.19
Phenol						
TOTAL	100	100	100	100		100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60			1.039			
Viscosity, cp						
<b>Quantitative</b>						
Carbon		78.27	84.77	26.69		15.34
Hydrogen	11.12	9.55	8.07	0.16		10.81
Nitrogen	0.14	0.35	0.42	0.28		0.15
Sulfur		0.29	0.70	1.68		0.06
Oxygen (by diff)	88.74	11.54	6.04	71.19		73.64
Ash						
TOTAL	100	100	100	100		100
Number of Sample Avg.	2	2	2	-		-
<b>Elemental</b>						

WASJAL LIGNITE  
SAMPLE ANALYSIS

Updated: 2/23/78

Run No: L-2H

Date: 9/19/77

Time: 0200-1400

MOLE PERCENT

SAMPLE DESCRIPTION	Makeup Gas	Product Gas	Recycle Gas	Feed Gas	S-4A Ovhd	J-1 Discharge
SAMPLE POINT	Sx-18	Sx-19	Sx-20	Sx-21	Sx-30	Sx-32
Hydrogen - H <sub>2</sub>	46.60	42.09	53.28	48.33	19.74	9.87
Carbon Monoxide - CO	52.95	19.30	24.61	43.85	9.78	7.90
Carbon Dioxide - CO <sub>2</sub>		23.09			50.94	62.10
Hydrogen Sulfide - H <sub>2</sub> S		0.20			1.20	
Methane - CH <sub>4</sub>		11.55	16.91	5.82	7.96	7.91
Ethane - C <sub>2</sub> H <sub>6</sub>		2.45	3.20	1.07	5.42	5.93
Propane - C <sub>3</sub> H <sub>8</sub>		0.80	0.95	0.36	4.16	6.29
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.45	0.50	1.05	0.57	0.35	
Ammonia - NH <sub>3</sub> (PPM)		0.02			0.45	
Light Oils - (0-100° C @ 1.6 Torr)						
Solvent - (100-230° C @ 1.6 Torr)						
Heavy Oil - (230-255° C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
TOTAL	100	100	100	100	100	100
Calc. Mole Wt.	15.88	19.55	12.33	14.81	30.86	35.55
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 2/23/78

Run No: L-2H

Date: 9/19/77

Time: 0200-1400

MOLE PERCENT

Quantitative	SAMPLE DESCRIPTION	Absorbed Gas.				
	SAMPLE POINT	Calc.				
	Hydrogen - H <sub>2</sub>					
	Carbon Monoxide - CO					
	Carbon Dioxide - CO <sub>2</sub>	96.86				
	Hydrogen Sulfide - H <sub>2</sub> S	2.28				
	Methane - CH <sub>4</sub>					
	Ethane - C <sub>2</sub> H <sub>6</sub>					
	Propane - C <sub>3</sub> H <sub>8</sub>					
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					
	Ammonia - NH <sub>3</sub> (PPM)	0.86				
	Light Oils - (0-100°C @ 1.6 Torr)					
	Solvent - (100-230°C @ 1.6 Torr)					
	Heavy Oil - (230-255°C @ 1.6 Torr)					
	SRL					
	Coal (MAF)					
	Ash					
	Water					
	Phenol					
TOTAL	100					
Calc Mole Wt.	43.54					
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	TOTAL					
	Number of Sample Avg.	-				

PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: L-2H  
DATE: 9/19/77  
TIME: 0200-1400

SAMPLE DESCRIPTION	F-1 Btms	LEC Btms	Feed Solv.	S-8 Oil	Cold Trap Oil
SAMPLE POINT	Sx-2	Sx-12	Sx-14	Sx-16	Sx-33
ASTM D-1160 DISTILLATION DATA					
PRESSURE, TORR		5	5		
IBP		49.6	54.4		
5%		64.8	73.0		
10%		69.2	80.0		
20%		76.9	94.2		
30%		82.2	103.8		
40%		88.4	121.0		
50%		95.8	145.4		
60%		104.5	166.6		
70%		119.0	179.0		
80%		142.8	191.3		
90%		173.2	226.2		
95%		194.0	260		
DRY PT.		199.8			
ASTM D-86 DISTILLATION DATA					
BAROMETRIC PRESSURE, TORR				740	736
IBP				52	93
5%				58	97
10%				67	99
20%				78	101
30%				90	207
40%				103	228
50%				114	242
60%				130	300
70%				143	321
80%				158	324
90%				175	
95%				178	
DRY PT.				178	332
ASPHALTENE TEST					
WT % ASH	13.73				
WT % UNCONVERTED COAL	13.12				
WT % PRE-ASPHALTENES	30.55				
WT % ASPHALTENES	25.18				
WT % MALTENES & DIST. OIL	17.42				
TOTAL	100.00				
SAYBOLT VISCOSITY, SSU					
100° F		9.5	11.1		
210° F		7.8	8.4		
MISCELLANEOUS					
KF H <sub>2</sub> O WT% (Row Sx)			0.82	0.07	21.57
INFRARED RATIO			0.33		
SP. GRAV. 60/60 F		0.989	1.026		

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES - BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES - N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.


PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: L-2H  
DATE: 9/19/77  
TIME: 0200-1400

SAMPLE DESCRIPTION	S-7 Btms	S-4A 011		
SAMPLE POINT	Sx-34/39	Sx-37		
ASTM D-1160 DISTILLATION DATA				
PRESSURE, TORR	5			
IBP	57.6			
5%	73.6			
10%	81.7			
20%	98.3			
30%	116.9			
40%	139.2			
50%	159			
60%	173.2			
70%	182.6			
80%	197.9			
90%	239			
95%	260			
DRY PT.				
ASTM D-86 DISTILLATION DATA				
BAROMETRIC PRESSURE, TORR		739		
IBP		91		
5%		91		
10%		182		
20%		197		
30%		204		
40%		214		
50%		223		
60%		238		
70%		258		
80%		289		
90%		336		
95%				
DRY PT.		341		
ASPHALTENE TEST				
WT % ASH				
WT % UNCONVERTED COAL				
WT % PRE-ASPHALTENES				
WT % ASPHALTENES				
WT % MALTENES & DIST. OIL				
TOTAL				
SAYBOLT VISCOSITY, SSU				
100° F	12.1			
210° F	8.6			
MISCELLANEOUS				
KF H <sub>2</sub> O WT% (Row Sx)	1.22	1.36		
INFRARED RATIO	0.32			
SP. GRAV. 60/60 F	1.039	0.971		

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
ASPHALTENES- BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
MALTENES-N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.

DISTILLABLE OIL CONTENT OF F-I BOTTOMS  
VERSUS  
F-I BOTTOMS MELTING POINT

-409-



PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 2/23/78

Run No: L-2H  
Date: 9/19/77  
Time: 0200-1400

MATERIAL OUT

Temperature: 729°F  
Pressure: 2450 psig  
LHSV: 1.40  
GHSV: 332

lbs/hr.

STREAM DESCRIPTION	Product Gas			S-4A	S-4B	S-8
	Vent Gas	Recycle Gas	Absorbed Gas	Ovhd	Btms	Ovhd
SAMPLE POINT	Sx-20	Sx-20	Calc	Sx-30	Sx-23	Sx-44
Hydrogen - H <sub>2</sub>	0.24	0.47		0.08		
Carbon Monoxide - CO	1.56	3.05		0.53		
Carbon Dioxide - CO <sub>2</sub>			8.61	4.35		
Hydrogen Sulfide - H <sub>2</sub> S			0.16	0.08		
Methane - CH <sub>4</sub>	0.61	1.20		0.25		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.22	0.42		0.32		
Propane - C <sub>3</sub> H <sub>8</sub>	0.10	0.19		0.35		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.07	0.13		0.02		
Ammonia - NH <sub>3</sub>			0.03	0.01	0.02	
Light Oil - (0-100°C @ 1.6 Torr)						
Solvent - (100-230°C @ 1.6 Torr)						
Heavy Oil - (230-255°C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water					13.74	
Phenol						
TOTAL	2.80	5.46	8.80	5.99	13.76	Negl.

Carbon	1.38	2.70	2.35	2.14		
Hydrogen	0.46	0.89	0.01	0.27	1.53	
Nitrogen	0.07	0.13	0.02	0.03	0.01	
Sulfur			0.15	0.08		
Oxygen (by diff)	0.89	1.74	6.27	3.47	12.22	
Ash						
TOTAL	2.80	2.70	8.80	5.99	13.76	Negl.

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 2/23/78

Run No: L-2H  
Date: 9/19/77  
Time: 0200-1400

MATERIAL OUT

Temperature: 729°F  
Pressure: 2450 psig  
LHSV: 1.40  
GHSV: 332

lbs/hr.

STREAM DESCRIPTION	S-8	J-1	Cold	F-1	← Recycle Solvent →	
	Btms	Exhaust	Trap	Btms	S-7 Btms	LEC Btms
SAMPLE POINT	Sx-16	Sx-32	Sx-33	Sx-2	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO		0.03				
Carbon Dioxide - CO <sub>2</sub>		0.34				
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>		0.02				
Ethane - C <sub>2</sub> H <sub>6</sub>		0.02				
Propane - C <sub>3</sub> H <sub>8</sub>		0.03				
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	2.65		0.02		21.38	17.89
Solvent - (100-230°C @ 1.6 Torr)	0.06		0.02	0.74	40.72	7.16
Heavy Oil - (230-255°C @1.6 Torr)					2.62	
SRL				14.31		
Coal (MAF)				2.70		
Ash				2.82		
Water	1.55		0.08		0.80	
Phenol						
<b>TOTAL</b>	<b>4.26</b>	<b>0.44</b>	<b>0.12</b>	<b>20.57</b>	<b>65.52</b>	<b>25.05</b>

Carbon	2.16	0.16	0.04	15.40	55.54	20.36
Hydrogen	0.50	0.02	0.01	0.98	5.29	2.15
Nitrogen				0.23	0.27	0.10
Sulfur	0.01			0.21	0.46	0.06
Oxygen (by diff)	1.59	0.26	0.07	0.93	3.96	2.38
Ash				2.82		
<b>TOTAL</b>	<b>4.26</b>	<b>0.44</b>	<b>0.12</b>	<b>20.57</b>	<b>65.52</b>	<b>25.05</b>

**PROJECT LIGNITE**  
**MEASURED MATERIAL BALANCE**  
 Revised: 2/23/78

Run No: L-2H  
 Date: 9/19/77  
 Time: 0200-1400

MATERIAL OUT

lbs/hr.

Temperature: 729°F  
 Pressure: 2450 psig  
 LHSV: 1.40  
 GHSV: 332

STREAM DESCRIPTION					Total Out
SAMPLE POINT					
Hydrogen - H <sub>2</sub>					0.79
Carbon Monoxide - CO					5.17
Carbon Dioxide - CO <sub>2</sub>					13.30
Hydrogen Sulfide - H <sub>2</sub> S					0.24
Methane - CH <sub>4</sub>					2.08
Ethane - C <sub>2</sub> H <sub>6</sub>					0.98
Propane - C <sub>3</sub> H <sub>8</sub>					0.67
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>					0.22
Ammonia - NH <sub>3</sub>					0.06
Light Oil - (0-100°C @ 1.6 Torr)					41.94
Solvent - (100-230°C @ 1.6 Torr)					48.70
Heavy Oil - (230-255°C @1.6 Torr)					2.62
SRL					14.31
Coal (MAF)					2.70
Ash					2.82
Water					16.17
Phenol					
TOTAL					152.77

Carbon					102.23
Hydrogen					12.11
Nitrogen					0.86
Sulfur					0.97
Oxygen (by diff)					33.78
Ash					2.82
TOTAL					152.77

RUN CONDITIONS

RUN NO. L-2I  
 DATE MADE 9/19-20/77

TEMPERATURE °F

PREHEATER E-1  
 SAND BATH 758  
 INLET 206  
 OUTLET 738

DISSOLVERS  
 R-1A (1) 699  
 (2) 765  
 (3) 777  
 (4) 787  
 R-1B (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_  
 (4) \_\_\_\_\_

REACTOR PRODUCT SEPARATORS  
 S-1 578  
 S-2 76  
 S-3 485  
 S-4A 76  
 S-4B 69

PREHEATER E-11  
 DOWTHERM 683  
 INLET 406  
 OUTLET 654

VACUUM FLASH F-1  
 OVERHEAD VAPOR 492  
 UPPER WALL 607  
 LOWER WALL 590  
 DOWNCOMER 574  
 CONDENSATE  
 ACCUMULATOR, S-7 74

PREHEATER E-13  
 DOWTHERM 406  
 INLET 71  
 OUTLET 149

LIGHT ENDS COLUMN, F-2  
 REBOILER 302  
 LOWER SECTION 208  
 FEED SECTION 209  
 OVERHEAD 182  
 S-8 68  
 S-9 -

SOLVENT COLUMN, F-3  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

HEAVY ENDS COLUMN, F-4  
 REBOILER NIU  
 LOWER SECTION \_\_\_\_\_  
 FEED SECTION \_\_\_\_\_  
 OVERHEAD \_\_\_\_\_

VACUUM FLASH, F-0  
 OVERHEAD NIU  
 BOTTOMS \_\_\_\_\_

PRECIPITATION TOWER, V-8  
 ZONE (1) NIU  
 (2) \_\_\_\_\_  
 (3) \_\_\_\_\_

RECOVERY TOWER V-9  
 REBOILER NIU  
 OVERHEAD \_\_\_\_\_

PRESSURE, psig

SEPARATORS S-1 and S-2  
2450

SEPARATOR S-3  
240

SEPARATORS S-4A and S-4B  
62

VACUUM FLASH, F-1  
14 Torr

LIGHT ENDS COLUMN, F-2  
Atm

SOLVENT COLUMN, F-3  
NIU

HEAVY ENDS COLUMN, F-4  
NIU


VACUUM FLASH, F-0  
NIU

SETTLING TOWER, V-8  
NIU

RECOVERY TOWER, V-7  
NIU

	Start	End	Run No: L-2I
Date of Run	9/19/77	9/20/77	Units: lbs/hr, °F, psig
Time of Run	1400	0145	Prep. By: BCL & GGB
Length of Run	11-3/4	hrs.	Updated: 3/6/78
Hours on Coal at End of Y.P.	441.4		

### MASS RATES AND RUN CONDITIONS



-414-

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product Gas, Recycle Gas and F-1 Btms Rates Adjusted  
 Revised: 3/6/78

Run No: L-2I  
 Date: 9/19-20/77  
 Time: 1400-0145

SUMMARY

Temperature: 738°F  
 Pressure: 2450 psig  
 LHSV: 1.42  
 GHSV: 340

STREAM DESCRIPTION	lbs/hr.		Net Yield		WE % MAF Coal
	Total In	Total Out			
SAMPLE POINT					
Hydrogen - H <sub>2</sub>	1.37	1.05	-0.32		
Carbon Monoxide - CO	14.39	7.11	-7.28		
Carbon Dioxide - CO <sub>2</sub>		12.84	12.84		
Hydrogen Sulfide - H <sub>2</sub> S		0.24	0.24		
Methane - CH <sub>4</sub>	1.05	1.73	0.68	6.85	22.33
Ethane - C <sub>2</sub> H <sub>6</sub>	0.27	0.60	0.33		
Propane - C <sub>3</sub> H <sub>8</sub>	0.18	0.48	0.30		
Butane - C <sub>4</sub> H <sub>10</sub>					
Nitrogen - N <sub>2</sub>	0.22	0.24	0.02		
Ammonia - NH <sub>3</sub>		0.04	0.04		
Light Oil - (0-100°C @ 1.6 Torr)	34.60	40.82	6.22		
Solvent - (100-230°C @ 1.6 Torr)	52.70	50.78	-1.92	23.22	75.68
Heavy Oil - (230-255°C @ 1.6 Torr)	3.39	3.47	0.08		
SRL		18.84	18.84		
Coal (MAF)	30.68	2.61	-28.07		-91.49
Ash	3.03	2.91	-0.12		-0.39
Water	17.16	15.28	-1.88		-6.13
Phenol					
TOTAL	159.04	159.04	-0-		

ELEMENTAL	lbs/hr.		Net Yield		WE % MAF Coal
	Total In	Total Out			
Carbon					
Hydrogen					
Nitrogen					
Sulfur					
Oxygen (by diff)					
Ash					
TOTAL					

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product Gas, Recycle Gas and F-1 Btms Rates Adjusted  
 Revised: 3/6/78

Run No: L-21  
 Date: 9/19-20/77  
 Time: 1400-0145

MATERIAL IN

Temperature: 738°F  
 Pressure: 2450 psig  
 LHSV: 1.42  
 GHSV: 340

Quantitative	← Feed Gas →	Gas				Total In
	Recycle Gas	Makeup Gas	Lignite	Feed Solvent		
STREAM DESCRIPTION	Sx-20	Sx-18	Sx-1	Sx-14		
SAMPLE POINT						
Hydrogen - H <sub>2</sub>	0.67	0.70				1.37
Carbon Monoxide - CO	4.51	9.88				14.39
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>	1.05					1.05
Ethane - C <sub>2</sub> H <sub>6</sub>	0.27					0.27
Propane - C <sub>3</sub> H <sub>8</sub>	0.18					0.18
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.16	0.06				0.22
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)				34.60		34.60
Solvent - (100-230°C @ 1.6 Torr)				52.70		52.70
Heavy Oil - (230-255°C @ 1.6 Torr)				3.39		3.39
SRL						
Cool (MAF)			30.68			30.68
Ash			3.03			3.03
Water			16.35	0.81		17.16
Phenol						
<b>TOTAL</b>	<b>6.84</b>	<b>10.64</b>	<b>50.06</b>	<b>91.50</b>		<b>159.04</b>

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	<b>TOTAL</b>					

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product Gas, Recycle Gas and F-1 Btms Rates Adjusted  
 Revised: 3/6/78

Run No: L-2I  
 Date: 9/19-20/77  
 Time: 1400-0145

MATERIAL OUT  
 lbs/hr.

Temperature: 738°F  
 Pressure: 2450 psig  
 LHSV: 1.42  
 GHSV: 340

STREAM DESCRIPTION	Product Gas			S-4A Ovhd	S-4B Btms	S-8 Ovhd
	Vent Gas	Recycle Gas	Absorbed Gas			
SAMPLE POINT	Sx-20	Sx-20	Calc	Sx-30	Sx-23	Sx-44
Hydrogen - H <sub>2</sub>	0.29	0.67		0.08		
Carbon Monoxide - CO	1.93	4.51		0.61		
Carbon Dioxide - CO <sub>2</sub>			9.00	3.51		
Hydrogen Sulfide - H <sub>2</sub> S			0.17	0.07		
Methane - CH <sub>4</sub>	0.45	1.05		0.22		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.11	0.27		0.21		
Propane - C <sub>3</sub> H <sub>8</sub>	0.08	0.18		0.20		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.07	0.16		0.01		
Ammonia - NH <sub>3</sub>			0.01	0.01	0.02	
Light Oil - (0-100°C @ 1.6 Torr)						
Solvent - (100-230°C @ 1.6 Torr)						
Heavy Oil - (230-255°C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water					15.03	
Phenol						
TOTAL	2.93	6.84	9.18	4.92	15.05	Negl.

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product Gas, Recycle Gas and F-1 Btms Rates Adjusted  
 Revised: 3/6/78

Run No: L-2I  
 Date: 9/19-20/77  
 Time: 1400-0145

MATERIAL OUT

Temperature: 738°F  
 Pressure: 2450 psig  
 LHSV: 1.42  
 GHSV: 340

	lbs/hr.					
STREAM DESCRIPTION	S-8 Btms	J-1 Exhaust	Cold Trap	F-1 Btms	← Recycle S-7 Btms	Solvent → F-2 Btms
SAMPLE POINT	Sx-16	Sx-32	Sx-33	Sx-2	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>		0.01				
Carbon Monoxide - CO		0.06				
Carbon Dioxide - CO <sub>2</sub>		0.33				
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>		0.01				
Ethane - C <sub>2</sub> H <sub>6</sub>		0.01				
Propane - C <sub>3</sub> H <sub>8</sub>		0.02				
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100° C @ 1.6 Torr)	4.54				19.65	16.63
Solvent - (100-230° C @ 1.6 Torr)	0.19		0.01	0.22	43.90	6.46
Heavy Oil - (230-255° C @1.6 Torr)					3.07	0.40
SRL				18.84		
Coal (MAF)				2.61		
Ash				2.91		
Water			0.25			
Phenol						
<b>TOTAL</b>	<b>4.73</b>	<b>0.44</b>	<b>0.26</b>	<b>24.58</b>	<b>66.62</b>	<b>23.49</b>

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
<b>TOTAL</b>						

PROJECT LIGNITE  
 ADJUSTED MATERIAL BALANCE  
 Product Gas, Recycle Gas, and F-1 Btms Rates Adjusted  
 Revised: 3/6/78

Run No: L-2I  
 Date: 9/19-20/77  
 Time: 1400-0145

MATERIAL OUT  
 lbs/hr.

Temperature: 738°F  
 Pressure: 2450 psig  
 LHSV: 1.42  
 GHSV: 340

Quantitative	STREAM DESCRIPTION						Total Out
	SAMPLE POINT						
	Hydrogen - H <sub>2</sub>						1.05
	Carbon Monoxide - CO						7.11
	Carbon Dioxide - CO <sub>2</sub>						12.84
	Hydrogen Sulfide - H <sub>2</sub> S						0.24
	Methane - CH <sub>4</sub>						1.73
	Ethane - C <sub>2</sub> H <sub>6</sub>						0.60
	Propane - C <sub>3</sub> H <sub>8</sub>						0.48
	Butane - C <sub>4</sub> H <sub>10</sub>						
	Nitrogen - N <sub>2</sub>						0.24
	Ammonia - NH <sub>3</sub>						0.04
	Light Oil - (0-100°C @ 1.6 Torr)						40.82
	Solvent - (100-230°C @ 1.6 Torr)						50.78
	Heavy Oil - (230-255°C @ 1.6 Torr)						3.47
	SRL						18.84
	Coal (MAF)						2.61
	Ash						2.91
	Water						15.28
	Phenol						
TOTAL							159.04

Elemental	Carbon						
	Hydrogen						
	Nitrogen						
	Sulfur						
	Oxygen (by diff)						
	Ash						
	TOTAL						

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/6/78

Run No: L-2I  
Date: 9/19-20/77  
Time: 1400-0145

WEIGHT PERCENT

SAMPLE DESCRIPTION	Lignite	WEIGHT PERCENT				
		F-1 Btms	LEC Btms	Feed Solvent	S-8 Oil	S-8 Water
SAMPLE POINT	Sx-1	*Sx-2	Sx-12	Sx-14	Sx-16	Sx-16
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>						
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)						
Light Oils - (0-100°C @ 1.6 Torr)			70.80	37.81	96.00	
Solvent - (100-230°C @ 1.6 Torr)		0.90	27.50	57.60	4.00	
Heavy Oil - (230-255°C @1.6 Torr)			1.70	3.70		
SRL		76.66				
Coal (MAF)	61.28	10.60				
Ash	6.06	11.84				
Water	32.66			0.89		100
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)		87.98				
Melting Point °F		420				
Specific Gravity 60/60			0.991			
Viscosity, cp						

Elemental	WEIGHT PERCENT					
	Lignite	F-1 Btms	LEC Btms	Feed Solvent	S-8 Oil	S-8 Water
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	-

\*Distillable oil calculated using the following equation:

$$\text{Wt \% distillable oil} = -0.1273 (\text{F-1 Btms melting point}) + 54.38. \text{ See graph}$$

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/6/78

Run No: L-2I

Date: 9/19-20/77

Time: 1400-0145

WEIGHT PERCENT

SAMPLE DESCRIPTION	WEIGHT PERCENT					
	S-8 Total	Makeup Gas	Product Gas	Recycle Gas	Feed Gas	S-4B Oil
SAMPLE POINT	Sx-16	Sx-18	Sx-19	Sx-20	Sx-21	*Sx-23
Hydrogen -H <sub>2</sub>		6.61	5.27	9.83	7.83	
Carbon Monoxide-CO		92.83	37.16	65.84	82.22	
Carbon Dioxide-CO <sub>2</sub>			44.44			
Hydrogen Sulfide-H <sub>2</sub> S			0.86			
Methane-CH <sub>4</sub>			7.34	15.38	5.39	
Ethane-C <sub>2</sub> H <sub>6</sub>			3.47	3.95	2.77	
Propane-C <sub>3</sub> H <sub>8</sub>			0.87	2.62	0.97	
Butane-C <sub>4</sub> H <sub>10</sub>						
Nitrogen-N <sub>2</sub>		0.56	0.55	2.38	0.82	
Ammonia-NH <sub>3</sub> (PPM)			0.04			
Light Oils-(0-100°C @ 1.6 Torr)	96.00					80.01
Solvent-(100-230°C @ 1.6 Torr)	4.00					18.50
Heavy Oil-(230-255°C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						1.49
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	2	2

\*Insufficient sample for distillation. Assumed to be the same as the S-4A oil.

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/6/78

Run No: L-2I

Date: 9/19-20/77

Time: 1400-0145

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4B	S-4B	S-4A	J-1	Cold	S-4A
	Water	Total	Ovhd	Discharge	Trap	Oil
SAMPLE POINT	Sx-23	Sx-23	Sx-30	Sx-32	Sx-33	Sx-37
Hydrogen - H <sub>2</sub>			1.60	0.69		
Carbon Monoxide - CO			12.41	13.23		
Carbon Dioxide - CO <sub>2</sub>			71.30	73.99		
Hydrogen Sulfide - H <sub>2</sub> S			1.36			
Methane - CH <sub>4</sub>			4.54	2.91		
Ethane - C <sub>2</sub> H <sub>6</sub>			4.31	4.41		
Propane - C <sub>3</sub> H <sub>8</sub>			4.03	4.77		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>			0.19			
Ammonia - NH <sub>3</sub> (PPM)	0.12	0.12	0.26			
Light Oils - (0-100°C @ 1.6 Torr)						80.01
Solvent - (100-230°C @ 1.6 Torr)					4.90	18.50
Heavy Oil - (230-255°C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water	99.88	99.88			95.10	1.49
Phenol						
TOTAL	100	100	100	100	100	100
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	2	1	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/6/78

Run No: L-2I

Date: 9/19-20/77

Time: 1400-0145

WEIGHT PERCENT

SAMPLE DESCRIPTION	S-4A	S-4A	S-7	Absorbed		
	Water	Total	Btms	Gas		
SAMPLE POINT	Sx-37	Sx-37	Sx-39	Calc.		
Hydrogen - H <sub>2</sub>						
Carbon Monoxide - CO						
Carbon Dioxide - CO <sub>2</sub>				98.02		
Hydrogen Sulfide - H <sub>2</sub> S				1.89		
Methane - CH <sub>4</sub>						
Ethane - C <sub>2</sub> H <sub>6</sub>						
Propane - C <sub>3</sub> H <sub>8</sub>						
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub> (PPM)	0.14	0.01		0.09		
Light Oils - (0-100° C @ 1.6 Torr)		75.92	29.50			
Solvent - (100-230° C @ 1.6 Torr)		17.56	65.90			
Heavy Oil - (230-255° C @1.6 Torr)			4.60			
SRL						
Coal (MAF)						
Ash						
Water	99.86	6.51				
Phenol						
TOTAL	100	100	100			
Pyridine Solubles (Wt % Ash free)						
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Elemental	Quantitative					
	Carbon					
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						
Number of Sample Avg.	2	2	2	-		

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/6/78

Run No: L-2I

Date: 9/19-20/77

Time: 1400-0145

MOLE PERCENT

	MOLE PERCENT					
	Makeup Gas	Product Gas	Recycle Gas	Feed Gas	S-4A Ovhd	J-1 Discharge
<b>SAMPLE DESCRIPTION</b>						
<b>SAMPLE POINT</b>	Sx-18	Sx-19	Sx-20	Sx-21	Sx-30	Sx-32
Hydrogen -H <sub>2</sub>	49.78	46.95	57.80	53.41	23.22	11.81
Carbon Monoxide-CO	49.92	23.64	27.65	40.04	12.86	16.08
Carbon Dioxide-CO <sub>2</sub>		17.99			47.04	57.23
Hydrogen Sulfide-H <sub>2</sub> S		0.45			1.16	
Methane-CH <sub>4</sub>		8.17	11.30	4.59	8.24	6.19
Ethane-C <sub>2</sub> H <sub>6</sub>		2.06	1.55	1.26	4.17	5.00
Propane-C <sub>3</sub> H <sub>8</sub>		0.35	0.70	0.30	2.66	3.69
Butane-C <sub>4</sub> H <sub>10</sub>						
Nitrogen-N <sub>2</sub>	0.30	0.35	1.00	0.40	0.20	
Ammonia-NH <sub>3</sub> (PPM)		0.04			0.45	
Light Oils-(0-100° C @ 1.6 Torr)						
Solvent-(100-230° C @ 1.6 Torr)						
Heavy Oil-(230-255° C @ 1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water						
Phenol						
<b>TOTAL</b>	100	100	100	100	100	100
Calc Mole Wt.	15.06	17.81	11.76	13.64	29.03	34.03
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						

Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	<b>TOTAL</b>					
	Number of Sample Avg.	2	2	2	2	2

PROJECT LIGNITE  
SAMPLE ANALYSIS

Updated: 3/6/78

Run No: L-2I

Date: 9/19-20/77

Time: 1400-0145

MOLE PERCENT

Quantitative	SAMPLE DESCRIPTION	Absorbed Gas				
	SAMPLE POINT	Calc				
	Hydrogen - H <sub>2</sub>					
	Carbon Monoxide - CO					
	Carbon Dioxide - CO <sub>2</sub>	97.35				
	Hydrogen Sulfide - H <sub>2</sub> S	2.43				
	Methane - CH <sub>4</sub>					
	Ethane - C <sub>2</sub> H <sub>6</sub>					
	Propane - C <sub>3</sub> H <sub>8</sub>					
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					
	Ammonia - NH <sub>3</sub> (PPM)	0.22				
	Light Oils - (0-100°C @ 1.6 Torr)					
	Solvent - (100-230°C @ 1.6 Torr)					
	Heavy Oil - (230-255°C @ 1.6 Torr)					
	SRL					
	Coal (MAF)					
	Ash					
	Water					
	Phenol					
TOTAL	100					
Calc. Mole Wt.	43.70					
Melting Point °F						
Specific Gravity 60/60						
Viscosity, cp						


Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	TOTAL					
	Number of Sample Avg.					

**PROJECT LIGNITE  
SAMPLE ANALYSES  
RUN NO: L-2I  
DATE: 9/19-20/77  
TIME: 1400-0145**

SAMPLE DESCRIPTION	LEC Btms	Feed Solv.	S-8 Oil	S-4A Oil	S-7 Btms
SAMPLE POINT	Sx-12	Sx-14	Sx-16	Sx-37	Sx-39
<b>ASTM D-1160 DISTILLATION DATA</b>					
PRESSURE, TORR	5	5			5
IBP	25	26.6			22
5%	68.6	77			81.8
10%	71.3	83			89.8
20%	77.6	93.8			104.5
30%	82.8	106.3			123.0
40%	87.8	125.4			144.8
50%	95.6	150.3			165.0
60%	105.4	169.8			177.2
70%	119.6	182			187.4
80%	142.6	195.2			202.2
90%	172.5	234.5			238.8
95%	188.5	260			
DRY PT.	199.6				238.8
<b>ASTM D-86 DISTILLATION DATA</b>					
BAROMETRIC PRESSURE, TORR			740	739	
IBP			53	92	
5%			58	129	
10%			67	187	
20%			89	197	
30%			104	204	
40%			123	214	
50%			141	226	
60%			160	237	
70%			175	257	
80%			196	274	
90%			236	334	
95%					
DRY PT.			268	338	
<b>ASPHALTENE TEST</b>					
WT % ASH					
WT % UNCONVERTED COAL					
WT % PRE-ASPHALTENES					
WT % ASPHALTENES					
WT % MALTENES & DIST. OIL					
TOTAL					
<b>SAYBOLT VISCOSITY, SSU</b>					
100° F					
210° F					
<b>MISCELLANEOUS</b>					
KF H <sub>2</sub> O WT % (Raw Sx)		0.89		1.49	1.15
INFRARED RATIO					
SP. GRAV. 60/60 F	0.991				

PREASPHALTENES - PYRIDINE SOLUBLE, BENZENE INSOLUBLE MATERIAL  
 ASPHALTENES - BENZENE SOLUBLE, N-PENTANE INSOLUBLE MATERIAL  
 MALTENES - N-PENTANE SOLUBLE MATERIAL NOT RECOVERABLE BY STANDARD DISTILLATION PROCEDURES  
 DISTILLABLE OIL - RECOVERABLE BY DISTILLATION.

DISTILLABLE OIL CONTENT OF F-I BOTTOMS  
VERSUS  
F-I BOTTOMS MELTING POINT



PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 3/6/78

Run No: L-2I  
Date: 9/19-20/77  
Time: 1400-0145

MATERIAL IN

Temperature: 738°F  
Pressure: 2450 psig  
LHSV: 1.42  
GHSV: 340

lbs/hr.

Quantitative	STREAM DESCRIPTION	← Feed	Gas →	Lignite	Feed Solvent	Total In
	Recycle Gas	Makeup Gas	Sx-20			
	Hydrogen - H <sub>2</sub>					1.38
	Carbon Monoxide - CO					14.35
	Carbon Dioxide - CO <sub>2</sub>					
	Hydrogen Sulfide - H <sub>2</sub> S					
	Methane - CH <sub>4</sub>					1.07
	Ethane - C <sub>2</sub> H <sub>6</sub>					0.27
	Propane - C <sub>3</sub> H <sub>8</sub>					0.18
	Butane - C <sub>4</sub> H <sub>10</sub>					
	Nitrogen - N <sub>2</sub>					0.23
	Ammonia - NH <sub>3</sub>					
	Light Oil - (0-100°C @ 1.6 Torr)				34.60	34.60
	Solvent - (100-230°C @ 1.6 Torr)				52.70	52.70
	Heavy Oil - (230-255°C @ 1.6 Torr)				3.39	3.39
	SRL					
	Coal (MAF)			30.68		30.68
	Ash			3.03		3.03
	Water			16.35	0.81	17.16
	Phenol					
	<b>TOTAL</b>			<b>50.06</b>	<b>91.50</b>	<b>159.04</b>
		6.94	10.54			
Elemental	Carbon					
	Hydrogen					
	Nitrogen					
	Sulfur					
	Oxygen (by diff)					
	Ash					
	<b>TOTAL</b>					

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 3/6/78

Run No: L-2I  
Date: 9/19-20/77  
Time: 1400-0145

MATERIAL OUT

Temperature: 738°F  
Pressure: 2450 psig  
LHSV: 1.42  
GHSV: 340

lbs/hr.

STREAM DESCRIPTION	Product Gas			S-4A Ovhd	S-4B Btms	S-8 Ovhd
	← Vent Gas	Recycle Gas	→ Absorbed Gas			
SAMPLE POINT	Sx-20	Sx-20	Calc	Sx-30	Sx-23	Sx-44
Hydrogen - H <sub>2</sub>	0.28	0.68		0.08		
Carbon Monoxide - CO	1.84	4.57		0.61		
Carbon Dioxide - CO <sub>2</sub>			8.18	3.51		
Hydrogen Sulfide - H <sub>2</sub> S			0.16	0.07		
Methane - CH <sub>4</sub>	0.43	1.07		0.22		
Ethane - C <sub>2</sub> H <sub>6</sub>	0.11	0.27		0.21		
Propane - C <sub>3</sub> H <sub>8</sub>	0.07	0.18		0.20		
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>	0.07	0.17		0.01		
Ammonia - NH <sub>3</sub>			0.01	0.01	0.02	
Light Oil - (0-100°C @ 1.6 Torr)						
Solvent - (100-230°C @ 1.6 Torr)						
Heavy Oil - (230-255°C @1.6 Torr)						
SRL						
Coal (MAF)						
Ash						
Water					15.03	
Phenol						
<b>TOTAL</b>	<b>2.80</b>	<b>6.94</b>	<b>8.35</b>	<b>4.92</b>	<b>15.05</b>	<b>Negl.</b>

Elemental	Product Gas			S-4A Ovhd	S-4B Btms	S-8 Ovhd
	← Vent Gas	Recycle Gas	→ Absorbed Gas			
Carbon						
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
<b>TOTAL</b>						

PROJECT LIGNITE  
MEASURED MATERIAL BALANCE  
Revised: 3/6/78

Run No: L-2I  
Date: 9/19-20/77  
Time: 1400-0145

MATERIAL OUT

Temperature: 738°F  
Pressure: 2450 psig  
LHSV: 1.42  
GHSV: 340

lbs/hr.

STREAM DESCRIPTION	S-8	J-1	Cold	F-1	← Recycle	Solvent →
	Btms	Exhaust	Trap	Btms	S-7 Btms	F-2 Btms
SAMPLE POINT	Sx-16	Sx-32	Sx-33	Sx-2	Sx-39	Sx-12
Hydrogen - H <sub>2</sub>		0.01				
Carbon Monoxide - CO		0.06				
Carbon Dioxide - CO <sub>2</sub>		0.33				
Hydrogen Sulfide - H <sub>2</sub> S						
Methane - CH <sub>4</sub>		0.01				
Ethane - C <sub>2</sub> H <sub>6</sub>		0.01				
Propane - C <sub>3</sub> H <sub>8</sub>		0.02				
Butane - C <sub>4</sub> H <sub>10</sub>						
Nitrogen - N <sub>2</sub>						
Ammonia - NH <sub>3</sub>						
Light Oil - (0-100°C @ 1.6 Torr)	4.54				19.65	16.63
Solvent - (100-230°C @ 1.6 Torr)	0.19		0.01	0.17	43.90	6.46
Heavy Oil - (230-255°C @1.6 Torr)					3.07	0.40
SRL				14.63		
Cool (MAF)				2.02		
Ash				2.26		
Water			0.25			
Phenol						
TOTAL	4.73	0.44	0.26	19.08	66.62	23.49

ELEMENTAL	Quantitative					
	Carbon					
Hydrogen						
Nitrogen						
Sulfur						
Oxygen (by diff)						
Ash						
TOTAL						

PROJECT LIGNITE  
 MEASURED MATERIAL BALANCE  
 Revised: 3/6/78

Run No: L-2I  
 Date: 9/19-20/77  
 Time: 1400-0145

MATERIAL OUT  
 lbs/hr.

Temperature: 738°F  
 Pressure: 2450 psig  
 LHSV: 1.42  
 GHSV: 340

	STREAM DESCRIPTION						Total Out
	SAMPLE POINT						
	Hydrogen - H <sub>2</sub>						1.05
	Carbon Monoxide - CO						7.08
	Carbon Dioxide - CO <sub>2</sub>						12.02
	Hydrogen Sulfide - H <sub>2</sub> S						0.23
	Methane - CH <sub>4</sub>						1.73
	Ethane - C <sub>2</sub> H <sub>6</sub>						0.60
	Propane - C <sub>3</sub> H <sub>8</sub>						0.47
	Butane - C <sub>4</sub> H <sub>10</sub>						
	Nitrogen - N <sub>2</sub>						0.25
	Ammonia - NH <sub>3</sub>						0.04
Quantitative	Light Oil - (0-100°C @ 1.6 Torr)						40.82
	Solvent - (100-230°C @ 1.6 Torr)						50.73
	Heavy Oil - (230-255°C @1.6 Torr)						3.47
	SRL						14.63
	Cool (MAF)						2.02
	Ash						2.26
	Water						15.28
	Phenol						
	TOTAL						152.68

Elemental	Carbon						
	Hydrogen						
	Nitrogen						
	Sulfur						
	Oxygen (by diff)						
	Ash						
		TOTAL					