

# The Shenandoah Solar Total Energy Project

James A. Leonard, Robert W. Hunke

Prepared by  
Sandia National Laboratories  
Albuquerque, New Mexico 87185 and Livermore, California 94550  
for the United States Department of Energy  
under Contract DE-AC04-76DP00789



***When printing a copy of any digitized SAND  
Report, you are required to update the  
markings to current standards.***

Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

**NOTICE:** This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof or any of their contractors or subcontractors.

Printed in the United States of America  
Available from  
National Technical Information Service  
U.S. Department of Commerce  
5285 Port Royal Road  
Springfield, VA 22161

NTIS price codes  
Printed copy: A02  
Microfiche copy: A01

# The Shenandoah Solar Total Energy Project

James A. Leonard, Robert W. Hunke  
Solar Energy Department 9720  
Sandia National Laboratories  
Albuquerque, NM 87185

## Abstract

The design and construction of the world's first solar total energy plant in the private sector has been completed and checkout is underway. The project, a major element of the Department of Energy's Solar Thermal Program, is the Solar Total Energy Project at Shenandoah, Georgia. During its operational phase, the solar plant will furnish electrical power, process steam, and other thermal energy to a nearby knitwear factory.

The solar system consists of a collector field containing 114 parabolic dish collectors which supply thermal energy at 400° C to drive a 400 kW multi-stage Rankine cycle turbine generator. Some steam is extracted from the turbine and supplied to the knitwear manufacturing processes. The system will be grid-connected, and the Georgia Power Company, through a cooperative agreement with DOE, is a participant in the project.

The report contains: (1) a description of the system and components being installed; (2) a summary of performance testing of the extraction turbine and of four prototype parabolic dish collectors; and (3) a discussion of design considerations and insights which have general applicability to solar thermal system designs.

FOREWORD

The material in this report was presented at the 1981 International Solar Energy Conference, "Solar Rising," and has been published in their proceedings. This publication is intended to widen the distribution to include other interested persons within the solar community; particularly with regard to thermal dish technology and solar total energy (cogeneration) applications.

A comprehensive set of Shenandoah project reports dealing with system performance modeling, summaries of fabrication and construction phase experiences, actual costs, checkout and startup experiences, as-built system descriptions, and operational phase test and evaluation plans will be published and distributed during 1983.

Contents

	<u>Page</u>
System Description	9
Qualification Test Summary	12
System Design Considerations and Insights	13
Summary	14
Acknowledgement	15

Illustrations

Figure 1 - Photo of the Shenandoah Solar Total Energy Project	10
Figure 2 - Block Diagram of the Shenandoah Solar Total Energy Project	11

Tables

Table 1 - STES Energy Output Capacity	9
---------------------------------------	---

### System Description

The Solar Total Energy Project at Shenandoah, Georgia, (Figure 1), is a prototype of a cascaded energy system using solar energy. Through system operation, definitive performance, cost, and operational and maintenance data will be obtained and an industrial solar total energy capability evaluated.

Shenandoah, about 35 miles south of Atlanta, is an industrial-residential planned community. Sun right easements have been obtained on the land bounding the STES site to prevent future shading of the collector field.

The system has the flexibility to operate in either a stand-alone or peak-shaving mode while providing the electrical, steam, and heating and cooling needs of the nearby Bleyle Knitwear Plant.

The STES consists of three major loops: solar collection and storage, power conversion, and thermal utilization, Figure 2.

One hundred and fourteen parabolic dish solar collectors, each seven meters in diameter, connected in parallel branches, form the collector field with a peak energy delivery rate of 2.7 MWT (MMBtu/hr). Energy is either transported to storage or supplied to a steam generator by a high-temperature silicone heat-transfer fluid. The temperature range of the solar collector field is 260°C (500°F) inlet, 400°C (750°F) outlet. To permit operation during transient weather conditions, a thermal storage capacity of 3 MWh (10 MMBtu) has been incorporated in the system. The solar collector is a 7-meter diameter paraboloid with a cavity receiver with 45 cm (18 in.) aperture. Reflected solar energy is focused onto a coil of blackened stainless steel tubing within the receiver. The total field temperature rise of 140°C (250°F) occurs in each receiver.

The power conversion loop employs a high efficiency, high speed (42,500 rpm) 4-stage steam, Rankine-cycle turbine, capable of providing 400 kWe. Process steam for the knitwear plant is extracted at an intermediate turbine stage. In a later phase, thermal energy from the turbine exhaust will be transferred to a thermal utilization loop for cooling of the Bleyle plant. An absorption air conditioner, operating on 110°C (230°F) steam will provide chilled cooling water. The solar plant will be connected to the Georgia Power Company grid so that electrical power production in excess of or less than the Bleyle plant demand can be accommodated for optimum solar economics. As a control system experiment, the plant can also be operated at any set-point output, in a load-following mode, or in a peak-shaving mode. Table 1 lists the energy capabilities of the STES.


TABLE 1

STES Energy Output Capacity

Electrical:	400 kWe
Cooling:	900 kWt (257 tons)
Process Steam:	630 kg/hr (1380 lbs/hr, 114 psia, 347°F)

High-temperature storage is provided in an ASME code carbon steel tank. The tank is 3.0 meters (10 feet) in diameter and 5.5 meters (18 feet) high with a capacity of 42 cubic meters (11,000 gallons). Thermal energy storage is provided in 400°C (750°F) heat transfer fluid in a thermocline mode. Approximately 1 hour equivalent of collector energy output is provided in storage for solar transient conditions. Storage for extended operation is not intended.

Figure 1






Figure 2

The Control and Instrumentation Subsystem initiates, regulates, and terminates collector tracking, energy storage, power generation, and thermal utilization for heating and cooling of the Bleyle plant. When operating in the peak-shaving mode, the CAIS will monitor and regulate the generation of power to satisfy steam requirements.

The CAIS consists of a central control console, a central minicomputer, and two remote microprocessor control units. The control system has the flexibility to be operated in a manual or automatic mode, and permits the operator to monitor or control the system functions from the control panel. Color graphic cathode ray tubes are employed for data display. Data archiving is performed with magnetic storage tapes and in hard copy form on a computer line printer. The remote microprocessors are programmable from the central minicomputer to allow a high degree of system control and versatility.

#### Qualification Test Summary

##### Parabolic Dish Collectors

A prototype collector array, simulating a portion of the STEP, was installed and tested at Sandia National Laboratories in Albuquerque. The facility has four 7-meter diameter collectors and a heat transfer loop. Pumps, valves, tubing/piping, insulation, controls and other components specified for the STEP were included.

The facility provided installation experience, design, and operation data and verification of design. Some of the major results are:

- o Mechanical and structural designs were evaluated, modified, where necessary, and retested in several instances, and the collectors qualified.
- o Receiver aperture plate and optical sensors overheated during normal operation and were redesigned using quartz cloth thermal protection.
- o The original reflector surface (RTV) proved unsatisfactory and a change to FEK 244 was developed and tested.
- o The receiver design was switched from a circuit of two parallel tubes to a single tube design to improve flow characteristics.
- o The heat transfer fluid, Syltherm 800, proved satisfactory at 750°F operating temperature.
- o The hybrid computer and optical tracking system was validated.
- o Stagnation testing, simulating loss of tracking power while in track, was performed and damage assessed.

Peak overall efficiency approached 62 percent for the collector with the FEK 244 reflector. Total aperture area of the collector is  $38.5 \text{ m}^2$  ( $414 \text{ ft}^2$ ). Weight per aperture area (less concrete counterweight--2650 lbs) is  $52 \text{ kg/m}^2$  ( $10.6 \text{ lbs/ft}^2$ ).

##### Turbine/Generator

The turbine/generator was specifically designed and developed for the Shenandoah project by Mechanical Technologies, Inc. of Albany, New York, under contract to Sandia National Laboratories (SNL) after it was determined that commercially available small-size turbine generators could attain thermal to electric efficiencies of only 7 to 11 percent at the system operating condition of  $382^\circ\text{C}$  and  $4.8 \text{ MPa}$  ( $720^\circ\text{F}$ , 700

psia). The MTI turbine provides thermal to electric efficiencies up to 15 percent. The turbine/generator acceptance testing has been completed. Daily startup and operating tests were run prior to shipment to the site.

### System Design Considerations and Insights

#### Foundations

Initial designs of the foundations for the solar collector specified piers of up to 28 inches diameter with 21 feet embedded length using initially provided soils data.

Tests were performed at the Site to evaluate the soils characteristics by actual test of piers. The governing criteria of failure was .64 cm (.25 inch) deflection at the ground level with 2727 kg (600 lbs) applied horizontal load at (4 feet, 9 inches) above ground and 8182 kg (18,000 lbs) uplift capacity. Test piers were 46 cm (18 inches) in diameter with embedded lengths of 1.83 m (6 feet), 2.74 m (9 feet), and 3.65 m (12 feet). The test data show a 45.7 m (18 inches) diameter pier, adequately reinforced with an embedded depth of (6 feet) is capable of withstanding the load. To account for varying soil conditions for the 20 km<sup>2</sup> (5 acre) field, and construction factors, the caissons were built to 20 inches diameter and 10 feet embedded length. The design provides a factor of safety of 2 based on test data.

- Foundation tests on Site are highly recommended where large numbers of foundations are required.
- Sufficient engineering effort should be provided to minimize the labor effort by well designed tools and fixtures.

#### Reflective Structure and Surfaces

As part of the development effort, the reflector materials, selected from a large matrix of candidate materials, were tested in a collector configuration. Materials tested were:

- Aluminum chemically brightened with RTV coating.
- Aluminum chemically brightened with clear anodize.
- Aluminum laminated with FEK 244 aluminized film.

The RTV surface exhibited a strong affinity for dust and cleaning was difficult requiring detergent wash, scrubbing, and a Freon cleaning agent to remove water spots.

The anodized aluminum initially had reflectance values comparable with the RTV coated reflector. The FEK 244 reflector showed a dramatic increase in collector efficiency. This experience showed that:

- Laboratory-size test samples are not necessarily indicative of full-scale performances in an actual environment. Results may be misleading.
- Reflector surface cleaning should be translated from small samples to large areas with care.

#### Piping System

It is essential and cost-effective to devote more design effort and capital investment to the piping system of a solar thermal plant than has traditionally been

invested in conventional thermal transport piping systems. This is true primarily because of the high value of thermal quality in a solar system. Whereas little penalty is associated with operation of a flame-fired heater at higher temperatures than necessary, a solar collector field's efficiency is reduced as operating temperature is increased. Other facts affecting this philosophy are the diurnal operating condition of solar collector systems and the relatively high value of solar collected energy. The latter point will increasingly influence the designs of conventional systems as well.

The following comments typify the application of such insights and the means by which they have been implemented in the Shenandoah design:

- o Daily thermal cycling and low viscosity oils can cause leaks to appear sooner than in systems with steady-state temperatures.
- o Welding and compression fittings provide much more reliable leak-tight joints than do screwed joints.
- o Leaking joints can cause soaked insulation, greatly increased thermal conductivity, fire hazards, and an unsightly appearance.
- o Penetrations in pipeline insulation for valves, supports, instrumentation, fittings, and maintenance should be minimized to reduce thermal losses.
- o Piping, valves, pumps, and fittings must be of an energy conservative design and must be well insulated.
- o Ease and speed of maintenance access is less important for a solar system than for a "round-the-clock" plant because maintenance can be performed when the sun is not shining.
- o The Shenandoah design has eliminated literally hundreds of insulation valves and other "convenience" fittings in favor of reduced capital cost and thermal losses.
- o The Shenandoah design has incorporated welded rather than flanged fittings at most valves.
- o Low thermal density insulation is cost effective by providing more usable energy off the field.
- o Nesting piping in a common insulation is thermally more efficient than individually insulated pipes.

#### Summary

A solar total energy system that uses parabolic dish collectors is being constructed that will have the capability to provide various energy forms, electrical and thermal, to a contemporary industrial facility with 25,000 square feet of floor space. Collector tests have demonstrated that existing fabrication techniques could produce an efficient parabolic dish solar collector. Performance measurements on the 7-meter dish have shown that the specified fabrication tolerances and performance of the full-scale unit can be realized in hardware.

#### Acknowledgement

The information presented is the results of efforts by the U.S. Department of Energy, Georgia Power Company, through Cooperative Agreement with DOE, participates in the project by providing the Site and cost-shared services. General Electric, under DOE contract, provided the collector and initial system design. Sandia National Laboratories provides technical and management support to the DOE.

AAI Corporation  
P. O. Box 6787  
Baltimore, MD 21204

Acurex Aerotherm (2)  
485 Clyde Avenue  
Mountain View, CA 94042  
Attn: J. Vindum  
H. Morse

Advanco Corporation  
999 N. Sepulveda Blvd.  
Suite 314  
El Segundo, CA 90245

Alpha Solarco  
1014 Vine Street  
Suite 2230  
Cincinnati, OH 45202

Anaconda Metal Hose Co.  
698 South Main Street  
Waterbury, CT 06720  
Attn: W. Genshino

Applied Concepts Corp.  
2501 S. Larimer County Rd. 21  
Berthoud, CO 80513  
Attn: Stan Pond

Applied Concepts Corp.  
P. O. Box 2760  
Reston, VA 22090  
Attn: J. S. Hauger

Applied Solar Resources  
490 East Pima  
Phoenix, AZ 85004  
Attn: W. H. Coady

Arizona Public Service Co.  
Box 21666 MS 1795  
Phoenix, AZ 85036  
Attn: B. L. Broussard

Battelle Memorial Institute  
Pacific Northwest Laboratory  
P. O. Box 999  
Richland, WA 99352  
Attn: K. Drumheller

Bechtel National, Inc.  
P. O. Box 3965  
50 Beale Street  
San Francisco, CA 94119  
Attn: E. Y. Lam

Black & Veatch (2)  
P. O. Box 8405  
Kansas City, MO 64114  
Attn: J. C. Grosskreutz  
D. C. Gray

Bloomer-Fiske, Inc.  
4000 S. Princeton  
Chicago, IL 60609  
Attn: C. Cain

Budd Company (The)  
Fort Washington, PA 19034  
Attn: W. W. Dickhart

Budd Company (The)  
Plastic R&D Center  
356 Executive Drive  
Troy, MI 48084  
Attn: J. N. Epel

Burns & Roe, Inc.  
800 Kinderkamack Road  
Oradell, NJ 07649  
Attn: G. Fontana

Burns & Roe (2)  
185 Crossways Park Dr.  
Woodbury, NY 11797  
Attn: R. J. Vondrasket  
J. Wysocki

BDM Corporation  
1801 Randolph Street  
Albuquerque, NM 87106  
Attn: T. Reynolds

Carrier Corp.  
Energy Systems Div.  
Summit Landing  
P. O. Box 4895  
Syracuse, NY 13221  
Attn: R. A. English

Columbia Gas System Service Corp.  
1600 Dublin Road  
Columbus, OH 43215  
Attn: J. Phillip Dechow

Corning Glass Company (2)  
Corning, NY 14830  
Attn: A. F. Shoemaker  
W. Baldwin

Custom Engineering, Inc.  
2805 South Tejon Street  
Englewood, CO 80110

DSET  
Black Canyon Stage  
P. O. Box 185  
Phoenix, AZ 85029  
Attn: G. A. Zerlaut

Desert Research Inst. Energy  
Systems Laboratory  
1500 Buchanan Blvd.  
Boulder City, NV 89005  
Attn: J. O. Bradley

Donnelly Mirrors, Inc.  
49 West Third Street  
Holland, MI 49423  
Attn: J. A. Knister

Eaton Corporation  
Industrial Drives Operations  
Cleveland Division  
3249 East 80th Street  
Cleveland, OH 44104  
Attn: R. Glatt

Electric Power Research  
Institute  
3412 Hillview Avenue  
Palo Alto, CA 94303  
Attn: J. E. Bigger

Energetics Corporation  
1201 Richardson Dr., Suite 216  
Richardson, TX 75080  
Attn: Lee Wilson

Energy Technology Engineering Center  
P. O. Box 1449  
Canoga Park, CA 91304  
Attn: J. Roberts

E-Systems, Inc.  
Energy Tech. Center  
P. O. Box 226118  
Dallas, TX 75266  
Attn: R. R. Walters

Eurodrive, Inc.  
2001 W. Main Street  
Troy, OH 45373  
Attn: S. D. Warner

Florida Solar Energy Center  
300 State Road, Suite 401  
Cape Canaveral, FL 32920  
Attn: Library

Ford Motor Company  
Glass Div., Technical Center  
25500 West Outer Drive  
Lincoln Park, MI 48246  
Attn: V. L. Lindberg

Foster Wheeler Solar Devel. Corp.  
12 Peach Tree Hill Road  
Livingston, NJ 07039  
Attn: Dr. A. C. Gangadharan

General Motors  
Harrison Radiator Division  
Lockport, NY 14094  
Attn: L. Brock

Georgia Power Co. (2)  
270 Peachtree  
P. O. Box 4545  
Atlanta, GA 30302  
Attn: J. Roberts  
W. Davis

Glitsch, Inc.  
P. O. Box 226227  
Dallas, TX 75266  
Attn: R. W. McClain

Haveg Industries, Inc.  
1287 E. Imperial Highway  
Santa Fe Springs, CA 90670  
Attn: J. Flynt

Highland Plating  
1128 N. Highland  
Los Angeles, CA 90038  
Attn: M. Faeth

Honeywell, Inc.  
Energy Resources Center  
2600 Ridgeway Parkway  
Minneapolis, MN 55413  
Attn: J. R. Williams

Insights West  
14022 Condessa Drive  
Del Mar, CA 92014  
Attn: Dr. David W. Kearney

Jacobs Engineering Co.  
251 South Lake Avenue  
Pasadena, CA 91101  
Attn: Meyer Schwartz

Jet Propulsion Laboratory (3)  
4800 Oak Grove Drive  
Pasadena, CA 91103  
Attn: J. Becker  
J. Lucas  
V. C. Truscello

Lawrence Livermore Laboratory  
University of California  
P. O. Box 808  
Livermore, CA 94500  
Attn: W. C. Dickinson

Los Alamos Scientific Lab (3)  
Los Alamos, NM 87545  
Attn: J. D. Balcomb  
D. P. Grimmer  
S. Moore

McDonnell-Douglas Astronautics  
Company (3)  
5301 Bolsa Avenue  
Huntington Beach, CA 92647  
Attn: J. B. Blackmon  
J. Rogan  
D. Steinmeyer

Meridian Corporation (2)  
5201 Leesburg Pike, Suite 400  
Falls Church, VA 22041  
Attn: J. White  
J. Meglen

Morse Chain  
Division of Borg-Warner Corp.  
4650 Steele Street  
Denver, CO 80211  
Attn: G. Fukayama

New Mexico State University  
Solar Energy Department  
Las Cruces, NM 88001

Omnium G  
1815 Orangethorpe Park  
Anaheim, CA 92801  
Attn: S. P. Lazzara

Owens-Illinois  
1020 N. Westwood  
Toledo, OH 43614  
Attn: Y. K. Pei

Texas Tech University  
Dept. of Electrical Engineering  
P. O. Box 4709  
Lubbock, TX 79409  
Attn: J. D. Reichert

U. S. Department of Energy  
San Francisco Operations Office  
1333 Broadway, Wells Fargo Bldg.  
Oakland, CA 94612  
Attn: R. W. Hughey

3M-Decorative Products Div.  
209-2N 3M Center  
St. Paul, MN 55144  
Attn: B. Benson

University of New Mexico (2)  
Department of Mechanical Eng.  
Albuquerque, NM 87113  
Attn: M. W. Wilden  
W. A. Gross

3M-Product Development  
Energy Control Products  
207-1W 3M Center  
St. Paul, MN 55144  
Attn: J. R. Roche

Viking  
3467 Ocean View Blvd.  
Glendale, CA 91208  
Attn: G. Gorandon

Toltec Industries, Inc.  
40th and East Main  
Clear Lake, IA 50428  
Attn: D. Chenault

Winsmith  
Div. of UMC Industries, Inc.  
Springville, NY 14141  
Attn: R. Bhise

U. S. Department of Energy (3)  
Albuquerque Operations Office  
P. O. Box 5400  
Albuquerque, NM 87185  
Attn: G. N. Pappas  
J. A. Morley  
J. Weisiger

Wyle Lab  
7800 Governor's Drive West  
Huntsville, AL 35807  
Attn: R. Losey

U. S. Department of Energy  
Division of Energy Storage Systems  
Washington, D.C. 20585  
Attn: J. Gahimer

U. S. Department of Energy (7)  
Division of Solar Thermal Tech.  
Washington, D.C. 20585  
Attn: G. W. Braun  
J. E. Greyerbiehl  
B. Hochheiser  
C. McFarland  
J. E. Rannels  
F. Wilkins

PPG Industries, Inc.  
One Gateway Center  
Pittsburg, PA 15222  
Attn: C. R. Frownfelter

Stanford Research Institute  
Menlo Park, CA 94025  
Attn: A. J. Slemmons

Parsons of California  
3437 S. Airport Way  
Stockton, CA 95206  
Attn: D. R. Biddle

Stearns-Roger  
4500 Cherry Creek  
Denver, CO 80217  
Attn: W. R. Lang

Power Kinetics, Inc.  
1223 Peoples Avenue  
Troy, NY 12180  
Attn: Mark Rice

W. B. Stine  
1230 Grace Drive  
Pasadena, CA 91105

Schott America  
11 East 26th Street  
New York, NY 10010  
Attn: J. Schrauth

Sun Gas Company  
Suite 930, 3 N. Park E  
Dallas, TX 75221  
Attn: R. I. Benner

Shelltech Associates  
809 Tolman Drive  
Stanford, CA 94305  
Attn: C. R. Steele

Sundstrand Electric Power  
4747 Harrison Avenue  
Rockford, IL 61101  
Attn: A. W. Adam

Solar Energy Information Center  
1536 Cole Blvd.  
Golden, CO 80401  
Attn: R. Ortiz

Sunpower Systems  
510 S. 52 Street  
Tempe, AZ 85281  
Attn: W. Matlock

Solar Energy Research Institute (8)  
1617 Cole Blvd.  
Golden, CO 80401  
Attn: B. L. Butler  
G. Gross  
B. P. Gupta  
J. Thornton

Suntec Systems, Inc.  
2101 Wooddale Drive  
St. Paul, MN 55110  
Attn: Jon H. Davison

Solar Kinetics, Inc.  
P. O. Box 47045  
Dallas, TX 75247  
Attn: G. Hutchison

Swedlow, Inc. (2)  
12122 Western Avenue  
Garden Grove, CA 92645  
Attn: E. Nixon  
M. M. Friefeld

Southwest Research Institute  
P. O. Box 28510  
San Antonio, TX 78284  
Attn: D. M. Deffenbaugh

TRW, Inc.  
Energy Systems Group of TRW, Inc.  
One Space Park, Bldg. R4, Rm 2074  
Redondo Beach, CA 90278  
Attn: J. M. Cherne

400 R. P. Stromberg  
1530 W. E. Caldes  
1550 F. W. Neilson  
2540 K. L. Gillespie  
2541 J. P. Abbin  
3161 J. E. Mitchell  
3600 R. W. Hunnicutt  
Attn: 3640 K. D. Harper  
3700 J. C. Strassel  
5510 D. B. Hayes  
5520 T. B. Lane  
5810 R. G. Kepler  
5820 R. E. Whan  
5830 M. J. Davis  
5840 N. Magnani  
8214 M. A. Pound  
8450 R. C. Wayne  
8451 C. F. Melius  
8451 W. R. Delameter  
8452 A. C. Skinrood  
8453 W. G. Wilson  
9000 G. A. Fowler  
9700 E. Beckner  
9720 D. G. Schueler  
9721 J. F. Banas  
9722 J. V. Otts  
9725 R. H. Braasch  
9727 J. A. Leonard (35)  
3141 J. L. Erickson (5)  
3151 W. L. Garner (3)  
3154-2 C. H. Dalin (25)  
(Unlimited Release  
for DOE/TIC)