


N. Mao
R. Gerig
J. McGill
K. Brown

Injection System of the SSC Medium Energy Booster



Superconducting Super Collider
Laboratory

APPROVED FOR RELEASE OR
PUBLICATION - O.R. PATENT GROUP
BY... DATE 4/3/95

Disclaimer Notice

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government or any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Superconducting Super Collider Laboratory is an equal opportunity employer.

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**

Injection System of the SSC Medium Energy Booster

N. Mao, R. Gerig, and J. McGill

Superconducting Super Collider Laboratory*
2550 Beckleymeade Ave.
Dallas, TX 75237, USA

K. Brown


Stanford Linear Accelerator Center
Stanford University
Stanford, CA 94309

April 1994

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

*Operated by the Universities Research Association, Inc., for the U.S. Department of Energy under Contract No. DE-AC35-89ER40486.



Injection System of the SSC Medium Energy Booster

N. Mao, R. Gerig, J. McGill, and K. Brown

Abstract


The Medium Energy Booster (MEB) is the third of the SSCL accelerators and the largest of the resistive magnet synchrotrons. It accelerates protons from an injection momentum of 12 GeV/c to a top momentum of 200 GeV/c. A beam injection system has been designed to inject the beam transferred from the Low Energy Booster (LEB) onto the MEB closed orbit in the MEB injection insertion region. The beam is injected via a vertical bending Lambertson septum magnet and a horizontal kicker with appropriate matching and very little beam loss and emittance dilution.

The beam optics of the injection system is described in this paper. The required parameters of the Lambertson septum magnet and the injection kicker are given.

1.0 INTRODUCTION

The MEB ring layout and the detail of the MEB injection insertion are shown in Figure 1.¹ The injection insertion adopts the standard FODO quadrupole spacing and uses missing dipoles to provide spaces for the beam transfer line,² septum magnet and kicker. The injection philosophy is as follows. The septum magnet (SEP3, Figures 2 and 3), located right upstream of the focusing quadrupole Q152, bends the beam up by 2.173° onto the MEB closed orbit plane. The horizontal kicker (HKICK), located right upstream of the focusing quadrupole Q154, completes the injection process, placing the beam onto the proper MEB horizontal closed orbit. This scheme takes advantage of the defocusing quadrupole Q153 present between the septum magnet and the horizontal kicker. The defocusing quadrupole bends the injection beam outward in the horizontal plane, thereby lessening the necessary strength of the injection kicker.

The lattice functions of the injection insertion are shown in Figure 4.¹ The functions at the exits of the septum magnet and the injection kicker are also listed in Table 1, lines 38 and 52, respectively. The injection system has been designed to inject the beam in both the collider fill mode and the test beam mode with the normalized transverse emittances (rms) of $0.6 \pi^* \text{mm}^* \text{mrad}$ and $4.0 \pi^* \text{mm}^* \text{mrad}$, respectively.



TIP-05570

Figure 1. MEB Ring Layout and Injection Insertion.




Figure 2. LEB-MEB Transfer Line and Absorber Line (Elevation View, LEB630 and LEB917).





Figure 3. LEB-MEB Transfer Line and Absorber Line (Plan View, LEB630 and LEB917).



TIP-06573

Figure 4. Lattice and Orbit Functions for Injection Insertion.

Table 1. Lattice Functions for the MEB Injection Insertion.

SYNCH RUN MEB
12-DEC-91 15:21:35

90 deg MEB lattices

SYNCH VERSION VAX. 8905

POS	TRKB	//	INJ1 CELL	S	QX	BX	AX	X	DX	QY	BY	AY	Y	DY
0	0.0000	0.0000000	59.8268	0.000000	1.846800	0.000000	0.0000000	11.9111	0.000000	0.000000	0.000000	0.000000	0.000000	
5 B	15.8580	0.089819	14.0485	0.694846	0.986929	-0.036702	0.112219	52.5069	-2.137776	0.000000	0.000000	0.000000	0.000000	
10 B	26.6708	0.197473	27.4022	-1.375607	1.279710	0.054087	0.150734	29.3312	1.454812	0.000000	0.000000	0.000000	0.000000	
15 QF	37.2788	0.237227	57.0951	2.242003	1.690605	-0.081201	0.252372	12.6105	-0.584100	0.000000	0.000000	0.000000	0.000000	
20 OOD	52.9183	0.335468	12.7860	0.591278	0.685626	-0.046431	0.351626	56.8462	-2.242883	0.000000	0.000000	0.000000	0.000000	
25 DXD	70.9577	0.464730	57.0935	-2.241911	0.856447	0.021973	0.457415	12.6084	0.583586	0.000000	0.000000	0.000000	0.000000	
30 O	81.5657	0.504483	27.4020	1.375603	0.523524	-0.027412	0.559048	29.3349	-1.454346	0.000000	0.000000	0.000000	0.000000	
35 OOD	92.3785	0.612137	14.0484	-0.694847	0.426085	0.020797	0.597564	52.4969	2.137999	0.000000	0.000000	0.000000	0.000000	
36 SB	98.8285	0.665449	27.4031	-1.375647	0.560228	0.020797	0.623844	29.3316	1.453517	0.000000	0.000000	0.000000	0.000000	
37 O	99.2055	0.6667586	28.4497	-1.415229	0.568027	0.020797	0.625917	28.2564	1.413721	0.000000	0.000000	0.000000	0.000000	
38 SB	105.6535	0.694641	51.0973	-2.096029	0.702171	0.020797	0.677654	14.4343	0.729238	0.000000	0.000000	0.000000	0.000000	
39 OOF	107.0365	0.698716	57.0968	-2.242005	0.730933	0.020797	0.693991	12.6202	0.582472	0.000000	0.000000	0.000000	0.000000	
40 QF	108.2365	0.701959	59.8299	0.000041	0.738657	-0.007975	0.709701	11.9334	-0.001248	0.000000	0.000000	0.000000	0.000000	
41 QF	109.4365	0.705201	57.0966	0.242080	0.711942	-0.036376	0.725407	12.6264	-0.585206	0.000000	0.000000	0.000000	0.000000	
42 OOF	110.8195	0.709277	51.0969	2.096095	0.661635	-0.036376	0.741732	14.4484	-0.732250	0.000000	0.000000	0.000000	0.000000	
43 B	117.2695	0.736330	28.4496	1.415289	0.483088	-0.018991	0.793390	28.3119	-1.416805	0.000000	0.000000	0.000000	0.000000	
44 O	117.6445	0.738467	27.4030	1.375705	0.475967	-0.018991	0.795459	29.3895	-1.456638	0.000000	0.000000	0.000000	0.000000	
45 B	124.0945	0.791776	14.0482	0.694899	0.409548	-0.001605	0.821690	52.5875	-2.139406	0.000000	0.000000	0.000000	0.000000	
46 OOD	125.0760	0.803441	12.7859	0.591304	0.407972	-0.001605	0.824546	56.8889	-2.243489	0.000000	0.000000	0.000000	0.000000	
47 QD	126.2760	0.818949	12.0872	0.000055	0.415664	0.014475	0.827800	59.6220	0.001762	0.000000	0.000000	0.000000	0.000000	
48 QD	127.4760	0.834458	12.7857	-0.591183	0.442985	0.031239	0.831054	56.8807	2.246686	0.000000	0.000000	0.000000	0.000000	
49 OOD	128.4574	0.846123	14.0477	-0.694769	0.473644	0.031239	0.833910	52.5732	2.142341	0.000000	0.000000	0.000000	0.000000	
50 B	134.9074	0.899435	27.4004	-1.375517	0.731189	0.048624	0.860163	29.3485	1.457844	0.000000	0.000000	0.000000	0.000000	
51 O	135.2824	0.901573	28.4469	-1.415098	0.749423	0.048624	0.862235	28.2701	1.417911	0.000000	0.000000	0.000000	0.000000	
52 SB	141.7324	0.928630	51.0927	-2.095880	1.063048	0.048624	0.914005	14.4093	0.731054	0.000000	0.000000	0.000000	0.000000	
53 OOF	143.1154	0.932706	57.0918	-2.241853	1.130295	0.048624	0.930376	12.5909	0.583779	0.000000	0.000000	0.000000	0.000000	
54 QF	144.3154	0.935949	59.8248	-0.000006	1.161841	0.003747	0.946126	11.9000	0.000906	0.000000	0.000000	0.000000	0.000000	
55 QF	145.5154	0.939191	57.0918	2.241842	1.139219	-0.041304	0.961879	12.5864	-0.581794	0.000000	0.000000	0.000000	0.000000	
60 OOD	161.1548	1.037435	12.7862	0.591220	0.758176	-0.006534	1.061342	56.7476	-2.240424	0.000000	0.000000	0.000000	0.000000	
65 DXB	179.1942	1.166690	57.0972	-2.242040	1.804189	0.071550	1.167175	12.6214	0.582155	0.000000	0.000000	0.000000	0.000000	
66 QF	180.3942	1.169933	59.8304	0.000024	1.847322	0.000059	1.182682	11.9354	-0.001596	0.000000	0.000000	0.000000	0.000000	

2.0 BEAM OPTICS OF INJECTION SYSTEM

The layout of the injection system is shown in Figure 5. The injection kicker (HKICK) is one cell downstream of the septum magnet (SEP3). The central trajectory separation between the injection beam and the circulating beam at the exit of the septum magnet in the horizontal plane is given by

$$\Delta x = K \sqrt{\beta_1 \beta_2} \sin(\phi_2 - \phi_1) \quad (1)$$

where K is the kicker strength, β_1 and β_2 are the β functions and ϕ_2 and ϕ_1 are the betatron phases at septum magnet exit and the kicker, respectively. Here the kicker is assumed to be a thin one. If the kicker has a length of L , the separation Δx is given by

$$\Delta x = \frac{K}{L} \sqrt{\beta_1} \int_0^L \sqrt{\beta_2(l)} \sin(\phi_2(l) - \phi_1) dl. \quad (2)$$




Figure 5. Layout of MEB Injection System.

The requirement for the separation between the two beam centroids at the septum magnet is related to the sizes of two beams, the beam centroid displacements caused by the magnet errors, and the thickness of the septum magnet. The parameters used in the injection system design are as follows:

The normalized beam transverse emittance (3σ test beam) = $9*4 \pi*mm*mrad$.

The β and η functions at the exit of the kicker, $\beta_x = 51.0927$ m

$\beta_y = 14.4093$ m

$\alpha_x = -2.09588$

$\alpha_y = 0.731054$

$\eta_x = -1.063048$ m

$\eta_y = 0$ m

$\eta_x' = -0.048624$

$\eta_y' = 0$.

The beam centroid displacement caused by the magnet errors = 3 mm.

The thickness of the septum = 2 mm.

Using these parameters, both analytical and numerical calculations show that a kicker strength of 0.85 mrad is adequate. It corresponds to a separation of 34.394 mm between the two beam centroids at the entrance of the septum magnet. This amount of separation is large enough to provide a 2.0 mm space for the septum. The numerical calculation is carried out with code TRANSPORT.³ The layout of the injection system is shown in Figure 5; the beam parameters are shown in Figure 6 and explained as follows.

(1) Beam sizes (3σ , $4\pi*mm*mrad$ test beam, $\delta p/p = 0.1\%$)

Circulating beam (Run LEB018A):

11.039 mm*7.074 mm, half size, at the entrance of the septum magnet,

12.013 mm*6.374 mm, half size, at the exit.

Injection beam (Run LEB018C and LEB630E):

11.028 mm*7.074 mm, half size, at the entrance of the septum magnet,

12.011 mm*6.374 mm, half size, at the exit.

(2) Separations between the two centroids of circulating beam and injection beam
(Run LEB018C and LEB630E)

Horizontal separations:

34.394 mm, at the entrance of the septum magnet,

37.219 mm, at the exit.

Vertical separations:

37.928 mm, at the entrance of the septum magnet,

0.000 mm, at the exit.

The geometry of the Lambertson septum magnet is so arranged that the mid-plane of the magnet gap is parallel with the central trajectory plane of the injection beam. The minimum edge-to-edge separation of the two beams in the horizontal direction (from the right edge of the circulating beam to the left edge of the injection beam) is 11.344 mm, as shown in Figure 6. If the beam centroid displacement caused by magnet errors is 3.0 mm, the distance from the right edge of the circulating beam to the vertex of the field-free region has to be at least 6.315 mm, as shown in Figure 7. In this case, the space available for septum is 2.029 mm (Figure 6), it meets the requirement.




Figure 6. Beam Parameters in the Septum Magnet.




Figure 7. Circulating Beam with or without Centroid Displacement Caused by Magnet Errors.

3.0 PARAMETERS OF SEPTUM MAGNET AND INJECTION KICKER

Based on the beam optics design of the MEB injection system, the main parameters of the injection Lambertson septum magnet are determined as follows:⁴

Number	1
Field aperture (w*h)	$>60 \text{ mm} * \pm 15 \text{ mm}$
Field-free aperture (w*h)	$50.8 \text{ mm} * 70 \text{ mm}$
Leakage field in field-free region (max, at the center of circulating beam)	$<0.0008 \text{ T}$ $<0.02 \text{ T/m}$ $<0.2 \text{ T/m}^2$
Magnet length	2.0 m
Good field region (w*h)	$60 \text{ mm} * \pm 15 \text{ mm}$
Field (max)	0.78 T
Field quality ($\Delta BL/BL$)	$1*10^{-4}$
TOD of power supply	$1*10^{-4}$

Here, w and h are with respect to the magnet gap, h is measured in the gap height direction. The conceptual design of the Lambertson septum magnet is shown in Figure 8.⁵





Figure 8. Conceptual Design of the Lambertson Septum Magnet.

The requirements for the injection kickers are as follows:

Number of magnets	≥ 4
Slot length	6.45 m
Aperture (H*V)	100 mm*50 mm
Strength (bending angle)	0.90 mrad
BL	0.036 T*m
TOD of power supply	$1*10^{-2}$

A twelve magnets kicker system design has been reported,⁶ where each magnet consists of ten cells.



REFERENCES

1. "Element Specification (Level 3A) for the Medium Energy Booster Accelerator of the Superconducting Super Collider," No. E10-000022, WBS 231, Rev. B, Superconducting Super Collider Laboratory, 1993.
2. N. Mao *et al.*, "Beam Optics of LEB-MEB Transfer Line for Superconducting Super Collider," *Proceedings of the 1993 Particle Accelerator Conference*, Washington, D.C., p. 333.
3. K. Brown *et al.*, "TRANSPORT, a Computer Program for Designing Charged Particle Beam Transport Systems," SLAC-91, Rev. 3, 1993.
4. "Element Specification (Level 3B) for the Low Energy Booster to Medium Energy Booster (LEB-MEB) Beam Transfer Line of the Superconducting Super Collider," No. E10-000030, WBS 222, Rev. D, Superconducting Super Collider Laboratory, 1994.
5. S. Sheynin, "Conceptual Design—Type B Symmetry Lambertson," Superconducting Super Collider Laboratory, 1993.
6. D. Anderson, "MEB Kicker Magnet System Design Status," Superconducting Super Collider Laboratory, July 1993.