

LANDFILL GAS CONVERSION TO LNG and LCO₂PHASE II
Contract No 725089 (CH10982)
PHASE II FINAL REPORTFor the Period
January 25, 1999 – April 30, 2000

prepared for

Dr Wai Lin Litzke
Dr James Wegrzyn
BROOKHAVEN TECHNICAL REPRESENTATIVES
BROOKHAVEN NATIONAL LABORATORY
Building 815
Upton, New York 11973
Tel (516) 344 7917

DOE Patent Clearance Granted

MPDvorscakJan 26, 2004

Date

Mark P. Dvorscak

(630) 252-2393

E-mail: mark.dvorscak@ch.doe.gov

Office of Intellectual Property Law

DOE Chicago Operations Office

by

William R Brown
W Jeffrey Cook
Lawrence A Siwajek
Marina NeymanACRION TECHNOLOGIES, INC
9099 Bank Street / Cleveland, Ohio 44125 / Tel (216) 573-1185

October 20, 2000

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**

EXECUTIVE SUMMARY

This report summarizes work on the development of a process to produce LNG (liquefied methane) for heavy vehicle use from landfill gas (LFG) using Acron's CO₂ wash process for contaminant removal and CO₂ recovery. Work was done in the following areas: 1) production of natural gas pipeline methane for liquefaction at an existing LNG facility, 2) production of LNG from sewage digester gas, 3) the use of mixed refrigerants for process cooling in the production of LNG, liquid CO₂ and pipeline methane, 4) cost estimates for an LNG production facility at the Arden Landfill in Washington PA.

Process designs and economics were developed to produce pipeline gas and liquid carbon dioxide (CO₂) from landfill gas (LFG) using the Acron CO₂ wash process. The patented Acron CO₂ wash process uses liquid CO₂ to absorb contaminants from the LFG. The process steps are compression, drying, CO₂ wash contaminant removal and CO₂ recovery, physical solvent residual CO₂ removal to pipeline specifications. Installed capital cost is \$5.3 million, annual operating costs \$1.0 million, and project payback is 3.1 years with methane at \$2.00 per MMBtu and liquid CO₂ at \$40/ton. This design is the basis for determining the economic feasibility of liquefying natural gas at large LNG peak shaving facilities, swapping lower cost landfill methane injected into the distribution system near the landfill for natural gas removed from the supply pipe at the peak shaving plant.

Pipeline natural gas specifications have been compiled and are reported. Two pipeline gas characteristics crucial to conversion of landfill gas to pipeline methane are heating value (Btu/SCF) and total inerts. These characteristics are not independent and are the most difficult to achieve in the upgrade of landfill methane to pipeline specifications. Heating value can be increased by propane injection, and may prove economic if the amount required is less than about 1 to 2 vol%. Injection of processed landfill methane into distribution and transmission pipelines must be examined carefully on a case-by-case basis and lengthy negotiations with the pipeline owner can be anticipated.

Vandor + Vandor, an independent subcontractor, studied "Wheeling" landfill methane for LNG. Vandor's work examined the feasibility of utilizing excess liquefaction capacity at large peak shaving plants to produce LNG, and distribution of LNG from the peak shaving plant(s) with Maryland. The concept appears feasible.

Sewage digester gas as a methane source for production of liquid methane has been investigated. AplusB, Inc., an independent subcontractor, studied sewage digester gas and reviewed commercial or near-commercial bio-digester technologies. Process designs were developed to convert digester gas to LNG at two levels of H₂S in the raw gas, 100 ppm and 600 ppm. Economics appear favorable for a 21,500 gal/day production facility with simple paybacks of 3 and 3.3 years. However Acron does not intend to actively pursue sewage digester gas as a methane source for LNG heavy duty truck fuel for several reasons: 1) digester gas is tightly integrated into the energy balance of most waste water treatment plants and conversion of digester methane to LNG for offsite use would require procurement of an alternative less expensive energy source to replace it; and 2) high H₂S levels at some wastewater treatment plants increase costs and 3) there is much greater opportunity to develop LNG projects at municipal landfills.

Mixed refrigerant systems have been compared with a conventional cascade refrigeration system for the LNG and liquid CO₂ designs developed in Phase I and the pipeline gas and liquid CO₂ design developed in Phase II. For the low temperature LNG and liquid CO₂ design the power requirement for the mixed refrigerant and cascade refrigeration systems were the same but the capital cost of the mixed refrigerant system was about 5% lower due to the presence of a single compression unit. For the warmer refrigeration requirements of the pipeline gas and CO₂ refrigeration system (-70°F), the mixed refrigerant system had a 19% lower power requirement than the cascade system and a 9% lower capital cost.

A cost estimate for gas compression and cleanup to supply a small LNG production facility to fuel refuse vehicles at the Arden Landfill in Washington PA was developed. Vendor quotes for a 1200 gal/day facility were acquired. The estimated plant cost is \$860,000.

The next step in the development process is to define the size and scope of a project at the Arden landfill. Acrion would pursue the task of firming the cost estimate and identifying lower cost technologies and sources for trace CO₂ removal. We would also identify the market for co-produced CO₂ in the area. Acrion's pilot LFG to liquid CO₂ pilot unit, currently under construction for placement at the NJ Ecocomplex, can supply high pressure contaminant free methane enriched gas which can be further processed to approximately 800 gal/day of LNG.